

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12404586
B2
September 02, 2025
Uehara; Noboru

Substrate rotating apparatus, processing system, and processing method

Abstract

A substrate rotating apparatus includes a main rotation mechanism, an auxiliary rotation mechanism, and a guide structure. The main rotation mechanism rotates around a first rotation shaft. The main rotation mechanism includes the auxiliary rotation mechanism. The auxiliary rotation mechanism revolves about the first rotation shaft, and rotates around a second rotation shaft. The second rotation shaft is displaced in a circumferential direction with respect to a third rotation shaft provided between the first rotation shaft and the second rotation shaft. The guide structure has a contact surface extending in a circumferential direction with respect to the first rotation shaft. The guide structure controls displacement of the second rotation shaft in the circumferential direction with respect to the third rotation shaft, and causes the auxiliary rotation mechanism to perform the revolving motion in an orbit along the contact surface.

Inventors:	Uehara; Noboru (Aichi, JP)
Applicant:	SANTEC HOLDINGS CORPORATION (Aichi, JP)
Family ID:	93935239
Assignee:	SANTEC HOLDINGS CORPORATION (Aichi, JP)
Appl. No.:	18/723129
Filed (or PCT Filed):	June 23, 2023
PCT No.:	PCT/JP2023/023385
PCT Pub. No.:	WO2024/262029
PCT Pub. Date:	December 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250116000 A1	Apr. 10, 2025

Publication Classification

Int. Cl.:	C23C16/458 (20060101)
U.S. Cl.:	
CPC	C23C16/4584 (20130101);

Field of Classification Search

CPC:	C23C (16/4584)
USPC:	118/730

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3128205	12/1963	Illsley	N/A	N/A
4034704	12/1976	Wossner	118/730	C23C 14/505
4501766	12/1984	Suzuki et al.	N/A	N/A
5002011	12/1990	Ohmine et al.	N/A	N/A
5106346	12/1991	Locher	475/11	F16H 1/22
6457864	12/2001	Chang et al.	N/A	N/A
12152297	12/2023	Uehara	N/A	H01L 21/68764
2002/0129475	12/2001	Tsai	29/25.01	C23C 16/4586
2003/0221466	12/2002	Hyatt, Jr.	70/379R	G07C 9/00658
2012/0145080	12/2011	Park	269/57	C23C 16/46
2019/0338421	12/2018	Zong	N/A	B05D 3/147
2024/0093358	12/2023	Uehara	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108396302	12/2017	CN	C23C 14/505
117995642	12/2023	CN	N/A
4025659	12/1991	DE	N/A
S58132755	12/1982	JP	N/A
06-88227	12/1993	JP	N/A
H06088227	12/1993	JP	N/A
H06192835	12/1993	JP	N/A
2006-63391	12/2005	JP	N/A

2006330656	12/2005	JP	N/A
2008-121103	12/2007	JP	N/A
2015-98618	12/2014	JP	N/A
2016-122788	12/2015	JP	N/A
2011072905	12/2010	KR	N/A
10-1292399	12/2012	KR	N/A
20220069084	12/2021	KR	N/A
2021/075074	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/JP2023/023385 dated Sep. 12, 2023. cited by applicant

Written Opinion for International Application No. PCT/JP2023/023385 dated Sep. 12, 2023. cited by applicant

Office Action issued in Korean Application No. 10-2024-7015485 dated Nov. 18, 2024. cited by applicant

International Search Report in Application No. PCT/JP2020/014868, mailed on Jun. 23, 2020. cited by applicant

Written Opinion of the International Searching Authority in Application No. PCT/JP2020/014868, mailed Apr. 28, 2022. cited by applicant

English Translation of Office Action issued in Chinese Patent Application No. 202080071635.4, dated Apr. 27, 2023. cited by applicant

Office Action issued in U.S. Appl. No. 17/768,060, dated Mar. 26, 2024. cited by applicant

Machine English Translation of Office Action issued in German Patent Application No. 112020005064.5, dated Apr. 24, 2024. cited by applicant

Machine English Translation of Office Action issued in Korean Patent Application No. 10-2022-7013902, dated May 7, 2024. cited by applicant

Office Action issued on Feb. 14, 2025, in the corresponding German Patent Application No. 112023000735.7. cited by applicant

Office Action issued on Mar. 27, 2025, in the corresponding Taiwanese Patent Application No. 113123254. cited by applicant

Primary Examiner: Bennett; Charlee J. C.

Attorney, Agent or Firm: Meunier Carlin & Curfman LLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a substrate rotating apparatus, a processing system, and a processing method.

BACKGROUND ART

(2) A thin film vapor deposition device is already known which comprise a lens holder that rotatably holds two or more lenses in order to form thin films with uniform thickness on the lenses (see, for example, Patent Document 1). In this thin film vapor deposition device, when the lens holder rotates, the lenses are rotated on the lens holder by a planetary gear mechanism.

Accordingly, the lenses revolve in accordance with rotation of the lens holder, while rotating on their own axes.

Patent Documents

(3) Patent Document 1: Japanese Unexamined Patent Application Publication No. H06-192835

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(4) In film forming devices used in optical and semiconductor fields, it is generally preferable that a uniform thin film can be formed on a substrate. If a thin film with a uniform film thickness can be formed on a large substrate, costs related to film formation can be reduced, and the productivity of product can be improved.

(5) However, a film material to be emitted as scattered particles from a film material source such as a vapor deposition source has a non-uniform spatial distribution with respect to a substrate. The non-uniformity worsens as an attempt is made to form a thin film on a large area of the substrate.

(6) For this reason, the film thickness of the thin film with non-uniform thickness formed on the substrate has been conventionally made uniform by using a film thickness correction plate.

However, the method for making a film thickness uniform using a film thickness correction plate requires mounting the film thickness correction plate on the substrate with high precision, and further requires remaking the film thickness correction plate in accordance with the spatial distribution of scattered particles.

(7) As in the cited document 1, also by a technique of revolving and rotating a substrate such as a lens, which is an object of film formation, during the film formation, it is possible to form a substantially uniform thin film on the substrate while reducing influence of the non-uniform spatial distribution of the scattered particles. However, even this technique leaves room for improvement of the uniformity of the thin film. In addition, if a complex mechanical structure is employed for improved uniformity of the thin film, the weight of the device may increase and the durability may deteriorate.

(8) Thus, according to some embodiments of the present disclosure, it is preferable that a new technique for a substrate rotating apparatus is provided which is suitable for uniform processing on a substrate, such as forming a film with uniform thickness on a substrate.

Means for Solving the Problems

(9) According to some embodiments, a substrate rotating apparatus is provided. The substrate rotating apparatus comprises a main rotation mechanism, an auxiliary rotation mechanism, and a guide structure. The main rotation mechanism rotates around a first rotation shaft.

(10) The main rotation mechanism comprises the auxiliary rotation mechanism. The auxiliary rotation mechanism revolves about the first rotation shaft as the main rotation mechanism rotates. The auxiliary rotation mechanism rotates around a second rotation shaft. The auxiliary rotation mechanism comprises a support structure for supporting a substrate as an object to be processed. The support structure rotates around the second rotation shaft. The second rotation shaft is displaced in a circumferential direction with respect to a third rotation shaft around the third rotation shaft. The third rotation shaft is provided between the first rotation shaft and the second rotation shaft in the main rotation mechanism.

(11) The guide structure is provided around the first rotation shaft and controls a revolving motion of the auxiliary rotation mechanism. The guide structure has a contact surface extending in a circumferential direction with respect to the first rotation shaft. The guide structure controls displacement of the second rotation shaft in the circumferential direction with respect to the third rotation shaft, and causes the auxiliary rotation mechanism to perform the revolving motion in an orbit along the contact surface when the contact surface and the auxiliary rotation mechanism are in contact with each other.

(12) In a conventional method of revolving and rotating on its own axis a support structure for a substrate as an object to be processed by using a planetary gear mechanism, a revolving orbit is a perfectly circular orbit. A disclosing party of the present disclosure has noticed that such circular

orbit hinders uniform processing on a substrate with high precision.

(13) In the substrate rotating apparatus according to some embodiments described above, since the guide structure enables control of the revolving orbit of the support structure, the revolving orbit is not limited to a perfectly circular orbit, unlike the planetary gear mechanism with the revolving orbit of the support structure being limited to a shape corresponding to a gear. That is, the substrate rotating apparatus according to some embodiments can achieve the revolving orbit other than the perfectly circular orbit by the guide structure having a shape other than a perfect circle.

(14) Accordingly, some embodiments allow greater design freedom for the support structure and a rotational motion of the substrate. This design freedom enables all points on the substrate as an object to be processed to be displaced with respect to a spatial distribution related to the processing such that non-uniformity of the aforementioned spatial distribution is cancelled out. Therefore, some embodiments can provide the substrate rotating apparatus for film formation that enables uniform processing on the substrate.

(15) According to some embodiments, the aforementioned design freedom enables all points on the substrate as an object of the film formation to be displaced with respect to a spatial distribution of the film material such that non-uniformity of the aforementioned spatial distribution is cancelled out. Therefore, some embodiments can provide the substrate rotating apparatus that enables a uniform thin film to be formed with high precision on the substrate.

(16) According to the substrate rotating apparatus of some embodiments, in order for the third rotation shaft to be located between the first rotation shaft and the second rotation shaft, a rotation diameter between the second rotation shaft and the third rotation shaft is smaller than a rotation diameter between the second rotation shaft and the first rotation shaft.

(17) In this case, when the second rotation shaft is displaced in the circumferential direction with respect to the third rotation shaft, a radial length between the auxiliary rotation mechanism and the first rotation shaft changes. That is, the auxiliary rotation mechanism can revolve in an orbit of other than a perfect circle along the contact surface.

(18) Displacement of the auxiliary rotation mechanism in a radial direction with respect to the first rotation shaft by the displacement in the circumferential direction with respect to the third rotation shaft can be achieved by a relatively simple rotational structure. Therefore, according to some embodiments, a substrate rotating apparatus excellent for uniform processing on a substrate can be implemented with a simple configuration, and further with a lightweight configuration. The simple configuration may contribute to the durability of the substrate rotating apparatus. The lightweight configuration may allow high-speed rotation of the main rotation mechanism with low energy.

(19) According to some embodiments, the contact surface may be an inner circumferential surface facing the first rotation shaft included in the guide structure. The inner circumferential surface may control radially outward displacement of the auxiliary rotation mechanism with respect to the first rotation axis.

(20) In a rotational system of the main rotation mechanism, a radially outward centrifugal force acts on the auxiliary rotation mechanism. That is, the auxiliary rotation mechanism attempts radially outward displacement. If the displacement due to the centrifugal force is controlled by a contact with the auxiliary rotation mechanism on the inner circumferential surface of the guide structure, it is then possible to stably revolve the auxiliary rotation mechanism in an orbit along the inner circumferential surface of the guide structure, and control the revolving motion of the support structure with high precision.

(21) According to some embodiments, the main rotation mechanism may comprise a rotation plate that rotates around the first rotation shaft. The rotation plate may have a slit along the circumferential direction with respect to the third rotation shaft. The auxiliary rotation mechanism may comprise the second rotation shaft penetrating the slit.

(22) The auxiliary rotation mechanism may comprise a rotating table including the support structure at a first end portion of the second rotation shaft. The auxiliary rotation mechanism may

comprise, at a second end portion opposite to the first end portion of the second rotation shaft, a wheel that travels on the contact surface of the guide structure. While the wheel travels on the contact surface along with the revolving motion, the wheel and the rotating table coupled via the second rotation shaft may rotate on their own axes.

(23) According to the substrate rotating apparatus as described above, revolution and rotation along the guide structure of the auxiliary rotation mechanism can be implemented by a relatively simple mechanical structure.

(24) According to some embodiments, the auxiliary rotation mechanism may be coupled to the main rotation mechanism via a spring that biases the auxiliary rotation mechanism in a direction to maintain contact with the contact surface. Biasing as such enables the auxiliary rotation mechanism to stably and accurately revolve along the contact surface of the guide structure.

(25) According to some embodiments, the substrate rotating apparatus may be configured so that the auxiliary rotation mechanism performs a revolving motion about the first rotation shaft in an elliptical orbit. According to some embodiments, the contact surface of the guide structure may be arranged in an elliptical shape in the circumferential direction with respect to the first rotation shaft.

(26) According to some embodiments, the contact surface of the guide structure may be arranged in a non-point symmetric ring shape in the circumferential direction with respect to the first rotation shaft. The auxiliary rotation mechanism may perform a revolving motion about the first rotation shaft in a non-point symmetric orbit. The revolving orbit as such is advantageous in uniform substrate processing. In particular, the revolving orbit as such is advantageous in formation of films with uniform thickness. This is because the spatial distribution of the film material shows a point symmetric distribution in many cases.

(27) According to some embodiments, the guide structure may comprise a sliding mechanism configured to move at least part of the contact surface in the radial direction with respect to the first rotation shaft. According to the substrate rotating apparatus comprising the sliding mechanism, a user can adjust the revolving orbit via the sliding mechanism, and achieve uniform processing on the substrate with higher precision.

(28) According to some embodiments, a processing system may be provided which comprises a processing apparatus configured to process a front surface of a substrate that rotates and revolves together with the auxiliary rotation mechanism by operation of the substrate rotating apparatus.

(29) According to some embodiments, the processing apparatus may be configured to process the front surface of the substrate by forming a film on the front surface of the substrate.

(30) According to some embodiments, the processing apparatus may be configured to process the front surface of the substrate by scraping the front surface of the substrate.

(31) According to some embodiments, the processing apparatus may be configured to process the front surface of the substrate by film formation, milling, or etching.

(32) According to some embodiments, the processing apparatus may be configured to process the front surface of the substrate by scattering a substance toward the front surface of the substrate.

According to some embodiments, the substance may be a substance for film formation.

(33) According to some embodiments, a processing method may be provided which comprises operating the aforementioned substrate rotating apparatus, and processing the front surface of the substrate that rotates and revolves together with the auxiliary rotation mechanism by operation of the substrate rotating apparatus.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a conceptual diagram of a dielectric film vapor deposition device comprising a substrate rotating apparatus in some embodiments.

- (2) FIG. 2 is a schematic plan view of the substrate rotating apparatus in some embodiments.
- (3) FIG. 3 is a schematic plan view of a guiding device in some embodiments.
- (4) FIG. 4 is a schematic cross-sectional view of the substrate rotating apparatus along rotation shafts in some embodiments.
- (5) FIG. 5 is a schematic rear view of a main rotation device on which an auxiliary rotation device is mounted in some embodiments.
- (6) FIGS. 6A and 6B are explanatory views for circumferential displacement of a rotating table along a slit provided in a main rotation plate in some embodiments.
- (7) FIGS. 7A and 7B are explanatory views for revolving and rotational motions in some embodiments.
- (8) FIG. 8 is a graph showing experimental results regarding a film thickness.
- (9) FIG. 9 is a diagram showing a circumferential profile of a guide rail in some embodiments.
- (10) FIG. 10 is a diagram showing a configuration of the guide rail comprising sliding mechanisms in some embodiments.
- (11) FIGS. 11A and 11B are conceptual diagrams showing a configuration of a processing system in some embodiments.

EXPLANATION OF REFERENCE NUMERALS

(12) **1** . . . dielectric film vapor deposition device, **10** . . . vapor deposition source, **15** . . . container, **100** . . . substrate rotating apparatus, **110** . . . motor, **130** . . . guiding device, **131** . . . base plate, **133** . . . ball bearing, **135** . . . shaft, **137** . . . guide member, **137A** . . . guide rail, **137B** . . . inner circumferential surface, **137C** . . . bottom plate, **137D** . . . hole, **139A** . . . guide rail, **141** . . . first sliding mechanism, **142** . . . second sliding mechanism, **150** . . . main rotation device, **151** . . . main rotation plate, **155** . . . shaft, **159** . . . slit, **170** . . . auxiliary rotation device, **171** . . . rotating table, **171A** . . . recess, **171B** . . . cavity, **175** . . . shaft, **179** . . . wheel, **179A** . . . wheel-body, **179B** . . . O-ring, **180** . . . rotating mechanism, **181** . . . link, **183** . . . joint, **185** . . . spring, **190** . . . substrate rotating apparatus, **200** . . . substrate, **300, 400** . . . processing system, **301, 401** . . . processing apparatus, **R1** . . . first rotation shaft, **R2** . . . second rotation shaft, **R3** . . . third rotation shaft, **RS** . . . light receiving sensor.

MODE FOR CARRYING OUT THE INVENTION

- (13) Hereinafter, some embodiments will be described with reference to the accompanying drawings.
- (14) A substrate rotating apparatus **100** of some embodiments is the substrate rotating apparatus **100** for film formation used in dielectric film vapor deposition or crystal growth. In order to assist in forming a uniform thin film on a substrate **200**, the substrate rotating apparatus **100** receives power from a motor **110** to revolve and rotate on its own axis the substrate **200** as an object of the film formation to be processed.
- (15) Examples of the substrate **200** include not only optical substrates, but also substrates for manufacturing semiconductor devices. The thin film formation on the optical substrates is carried out, for example, in order to provide specified optical properties to the optical substrates. Examples of the optical substrates include not only flat substrates, but also substrates having a convex surface or a concave surface.
- (16) For example, as shown in FIG. 1, the substrate rotating apparatus **100** is arranged within a container **15** of a dielectric film vapor deposition device **1** including two or more vapor deposition sources **10**. In the substrate rotating apparatus **100**, a surface of the substrate **200** as an object of the film formation faces the vapor deposition sources **10**.
- (17) The substrate rotating apparatus **100** receives power from the motor **110**, thereby to revolve and rotate on its own axis the substrate **200** within the container **15**. The container **15** is maintained in a vacuum state. In this state, a film material is vaporized from the vapor deposition source **10**, and the vaporized film material scatters as scattered particles within the container **15**. In FIG. 1, broken lines conceptually illustrate a spread of the scattered particles, and arrows conceptually

illustrate directions where the scattered particles flow.

(18) When the scattered particles are attached on the substrate **200**, a thin film is formed on the substrate **200**. When different kinds of thin films are stacked on the substrate **200**, the two or more vapor deposition sources **10** operate in order. Each of the vapor deposition sources **10**, when operating, vaporizes and scatters a corresponding film material so that the corresponding kind of thin film is formed on the substrate **200**.

(19) A spatial distribution of the film material scattered from each of the vapor deposition sources **10** to the substrate **200** has a substantially point symmetric geometric shape. The closer to the center the film materials, the greater the amount of the film materials scattered. The farther from the center the film materials, the smaller the amount of the film materials scattered.

(20) Accordingly, a film thickness λ of the thin film formed on the substrate **200** generally shows a distribution in accordance with a function

$\lambda = T(r) = T_0 + k_1 \cdot r + k_2 \cdot r^2 + k_3 \cdot r^3 + \dots$, that is, the distribution in accordance a univariate polynomial having a distance r from the center as a single variable. In a case where the thin film formation is performed in a state where the substrate **200** does not rotate and is stationary, the coefficients k_1 , k_2 , k_3 , $\dots$ are determined in accordance with a scattering distribution of the film material.

(21) In the substrate rotating apparatus **100** in some embodiments, the substrate **200** is revolved and rotated on its own axis, whereby all points on the substrate **200** are displaced with respect to the scattering distribution of the film material. This brings the coefficients k_1 , k_2 , $k_3 \dots$ closer to zero, and forms a homogeneous thin film, which shows the distribution $T(r)$ having only a constant term T_0 and the uniform film thickness λ irrespective of distance, in a large area of the substrate **200**.

(22) The substrate rotating apparatus **100** forms a more uniform thin film than before by achieving a non-point symmetric revolving orbit that is not a perfect circle, such as an ellipse. For this revolving orbit, the substrate rotating apparatus **100** is configured as shown in FIG. 2.

(23) The substrate rotating apparatus **100** shown in FIG. 2 comprises a guiding device **130**, a main rotation device **150** mounted on the guiding device **130**, and two or more auxiliary rotation devices **170** mounted on the main rotation device **150**.

(24) Broken lines in FIG. 2 indicate a portion located behind a front surface of the substrate rotating apparatus **100** in a transparent manner. Arrows in FIG. 2 indicate that the main rotation device **150** performs a rotational motion around a first rotation shaft **R1**, that the rotating table **171** of the auxiliary rotation device **170** performs a rotational motion around a second rotation shaft **R2**, and that the rotating table **171** is circumferentially displaceable around a third rotation shaft **R3**.

(25) As shown in FIGS. 3 and 4, the guiding device **130** comprises a base plate **131**, a shaft **135** rotatably held by the base plate **131** via a ball bearing **133**, and a guide member **137**.

(26) The guide member **137** comprises a guide rail **137A** and a bottom plate **137C** having a peripheral edge of the same shape as that of the profile of the guide rail **137A**. As shown in FIG. 4, the guide rail **137A** protrudes from the peripheral edge of the bottom plate **137C**.

(27) The bottom plate **137C** has a hole **137D** for the shaft **135** to pass through. The guide member **137** is fixed to the base plate **131** via, for example, a screw, with the shaft **135** penetrating the hole **137D**.

(28) The guide rail **137A** is arranged around the shaft **135** in a non-point symmetric ring shape in a state where the guide member **137** is fixed to the base plate **131**. In an example shown in FIG. 3, the guide rail **137A** has a circumferentially elliptical profile.

(29) The main rotation device **150** is rotatably held with respect to the guiding device **130**. As shown in FIGS. 2 and 4, the main rotation device **150** comprises a main rotation plate **151** and a shaft **155**. The shaft **155** extends from the center of the main rotation plate **151** toward the guiding device **130** in a normal direction of the main rotation plate **151**. The shaft **155** is coupled to the main rotation plate **151**, and further to a first end of the shaft **135** of the guiding device **130**.

(30) The shaft **135** has a second end protruding through a back surface of the guiding device **130**.

The motor **110** is coupled to the second end of the shaft **135**. As a result, the main rotation device **150** is arranged over the guiding device **130** such that the main rotation plate **151** receives power from the motor **110** to rotate around the shaft **155**. The shaft **155** corresponds to the first rotation shaft **R1**.

(31) As shown in FIG. 2, the main rotation plate **151** comprises slits **159** extending in a circumferential direction with respect to the third rotation shaft **R3** and spaced at intervals of 90 degrees. The number of the auxiliary rotation devices **170** is the same as that of the slits **159**. Each of the auxiliary rotation devices **170** penetrates the corresponding one of the slits **159**.

(32) As shown in FIGS. 2, 4, and 5, each of the auxiliary rotation devices **170** comprises the rotating table **171**, a shaft **175**, a wheel **179**, and a rotating mechanism **180**. The rotating mechanism **180** is arranged at a position corresponding to a broken line in FIG. 4. That is, the rotating mechanism **180** is provided on a back surface of the main rotation plate **151**. In FIG. 4, details of the rotating mechanism **180** are not shown.

(33) The shaft **175** is provided to penetrate the slit **159** and the rotating mechanism **180**. The rotating mechanism **180** supports the shaft **175** so that the shaft **175** is rotatable about its axis. The shaft **175** corresponds to the second rotation shaft **R2**.

(34) In addition, the rotating mechanism **180** supports the shaft **175** so that the shaft **175** is rotatable along the slit **159**, especially displaceable in the circumferential direction with respect to the third rotation shaft **R3**.

(35) As shown in FIG. 5, the rotating mechanism **180** comprises a link **181** configured to rotatably support the shaft **175**, a joint **183** configured to support the link **181** in a manner displaceable in the circumferential direction with respect to the third rotation shaft **R3**, and a spring **185**.

(36) The joint **183** is provided in the main rotation plate **151** so as to penetrate the main rotation plate **151** in a normal direction, and is thereby erected in the normal direction on the back surface of the main rotation plate **151**. The link **181** has a hole (not shown) that the joint **183** penetrates at a first end portion. The link **181** is supported to the joint **183** in a manner displaceable in a circumferential direction with respect to the joint **183** via the hole. This causes the link **181** to be attached to the main rotation plate **151** in a manner displaceable in the circumferential direction with respect to the third rotation shaft **R3** around the third rotation shaft **R3**.

(37) In one example, a shaft ball bearing may be provided between the joint **183** and the link **181**. As a result, the link **181** may be held by the joint **183** so as to be smoothly displaceable in a circumferential direction around the joint **183**.

(38) The link **181** further has a hole (not shown) that the shaft **175** penetrates at a second end portion that is farther from first rotation shaft **R1** than the first end portion. The link **181** supports the shaft **175** so that the shaft **175** is rotatable about its axis. As a result, the shaft **175** is attached to the rotating mechanism **180** in a manner rotatable around the second rotation shaft **R2** that is displaced in the circumferential direction with respect to the third rotation shaft **R3**. In one example, a shaft ball bearing may be provided between the shaft **175** and the link **181**. This allows the shaft **175** to be supported by the link **181** so as to be smoothly rotatable.

(39) The slit **159** provided in the main rotation plate **151** is an arc-shaped slit curved along the circumferential direction with respect to the third rotation shaft **R3**. The shaft **175** is held in the link **181** so that a length from the third rotation shaft **R3**, that is, a rotation diameter with respect to the third rotation shaft **R3**, corresponds to a distance from the third rotation shaft **R3** to the center of a slit **159**. As a result, as shown in FIGS. 6A and 6B, the shaft **175** is arranged along the slit **159** in a manner displaceable in the circumferential direction with respect to the third rotation shaft **R3**.

(40) The spring **185** is provided between the link **181** and the main rotation plate **151** so that a first end portion of the spring **185** is fixed to the link **181** and a second end portion of the spring **185** is fixed to the main rotation plate **151**.

(41) As shown in FIGS. 2 and 4, the third rotation shaft **R3** is located between the first rotation shaft **R1** and the second rotation shaft **R2** in a radial direction with respect to the first rotation shaft

R1. A rotation diameter between the second rotation shaft **R2** and the third rotation shaft **R3** is smaller than a rotation diameter between the second rotation shaft **R2** and the first rotation shaft **R1**.

(42) Accordingly, when the shaft **175** is displaced in the circumferential direction along the slit **159**, a radial length between the shaft **175** and the first rotation shaft **R1** changes.

(43) The spring **185** is provided between the link **181** and the main rotation plate **151** so as not to apply a biasing force to the link **181** when the shaft **175** is in a circumferential center position of the slit **159**, that is, a position where a radial distance from the first rotation shaft **R1** is the longest. In other words, the spring **185** is coupled to the link **181** so that a biasing force in a direction to return the shaft **175** to the center position is applied to the link **181** when the shaft **175** moves away from the center position.

(44) As shown in FIG. **4**, a first end portion of the shaft **175** protrudes from a front surface of the main rotation plate **151**. The first end portion of the shaft **175** is coupled to a center of the rotating table **171** on a back side of the rotating table **171**. As a result, the rotating table **171** is arranged on the front side of the main rotation plate **151** in a state rotatable around the shaft **175**, and, as shown in FIGS. **6A** and **6B**, in a state displaceable in the circumferential direction with respect to the third rotation shaft **R3** as the shaft **175** moves.

(45) As described above, the rotation diameter between the shaft **175** and the third rotation shaft **R3** is smaller than the rotation diameter between the shaft **175** and the first rotation shaft **R1**. Thus, the rotating table **171** is arranged over the main rotation plate **151** in a manner displaceable in a radial direction of the first rotation shaft **R1** as the shaft **175** moves in the circumferential direction with respect to the third rotation shaft **R3**.

(46) As shown in FIG. **2**, the rotating table **171** has a circular profile, and comprises on its front side a support structure that supports a rectangular substrate **200**. Specifically, the rotating table **171** has a rectangular recess **171A**, of which shape corresponds to that of the substrate **200**, on the front side (see FIG. **4**), and supports the substrate **200** fitted in the recess **171A**.

(47) As shown in FIG. **4**, the rotating table **171** has a hollow internal structure, and supports an edge of the substrate **200** from a back side of the substrate **200**. The shaft **175** coupled to the rotating table **171** is a hollow cylindrical member. A cavity **171B** of the rotating table **171** communicates with a second end portion opposite to the first end portion of the shaft **175**.

(48) The second end portion of the shaft **175** is located on a back side of the main rotation plate **151**. A light receiving sensor **RS** is provided at the second end portion of the shaft **175** so as to cover an opening of the shaft **175**. The light receiving sensor **RS** receives a measurement light that is emitted from above the substrate **200** and propagates through the substrate **200** and the cavity **171B**, and outputs a signal corresponding to a light intensity of the received measurement light. The signal output from the light receiving sensor **RS** is used to measure a thickness of a thin film formed on the substrate **200**.

(49) The second end portion of the shaft **175** is coupled to a center of the wheel **179**. Since the rotating table **171** is coupled to the first end portion of the shaft **175**, and the wheel **179** is coupled to the second end portion of the shaft **175** as such, the rotating table **171** rotates around the shaft **175** (that is, rotates on its own axis) in accordance with rotation of the wheel **179**.

(50) With respect to the wheel **179**, an O-ring **179B** is attached to a side wall of a wheel-body **179A** having a circular profile. The wheel **179** is arranged at a height where the O-ring **179B** is in contact with an inner circumferential surface **137B** of the guide rail **137A** so that the wheel **179** travels on the inner circumferential surface **137B** of the guide rail **137A**.

(51) That is, when the main rotation plate **151** rotates, the wheel **179** travels on the inner circumferential surface **137B** of the guide rail **137A** in accordance with a revolving motion of the rotating table **171** caused by rotation of the main rotation plate **151**.

(52) The spring **185** is provided so that the wheel **179**, when traveling, can safely travel on the inner circumferential surface **137B** of the guide rail **137A**, without being separated from, and even

slipping on, the inner circumferential surface **137B** of the guide rail **137A**.

(53) Due to the arrangement of the spring **185**, the wheel **179** receives a tension having a component directing radially outward of the main rotation plate **151** from the spring **185** via the shaft **175**, and is pressed against the inner circumferential surface **137B** of the guide rail **137A** so as to maintain the contact with the inner circumferential surface **137B** of the guide rail **137A**.

(54) That is, the wheel **179** receives a radially outward biasing force from the spring **185**, and is pressed against the inner circumferential surface **137B** of the guide rail **137A**. As a result, the wheel **179** revolves on an orbit along the guide rail **137A** while rotating on its own axis in a state where there is substantially no slipping on the inner circumferential surface **137B** of the guide rail **137A** or separation from the guide rail **137A**.

(55) When the guide rail **137A** is elliptical as shown in FIG. **3**, the wheel **179** of the auxiliary rotation device **170** and the rotating table **171** that works together rotate on their own axes while revolving in an elliptical orbit as shown in FIGS. **7A** and **7B**. When the main rotation plate **151** is rotated by an angle α in a direction of arrow with the wheel **179** being arranged as shown in FIG. **7A**, the wheel **179** moves to a position shown in FIG. **7B** while tracing an elliptical orbit. In FIGS. **7A** and **7B**, the main rotation plate **151** is shown by broken lines.

(56) During the rotation of the main rotation plate **151**, positions of the rotating table **171** and the wheel **179** in a radial direction of the main rotation plate **151** are controlled to positions along the guide rail **137A** by a centrifugal force, the biasing force by the spring **185**, and a dynamic action from the guide rail **137A** to the wheel **179** accompanied by reaction force. That is, the guide rail **137A** controls positions of the wheel **179** and the shaft **175** in the radial direction by the contact with the wheel **179** of the auxiliary rotation device **170**, and thereby controls the revolving motion of the rotating table **171**.

(57) The substrate rotating apparatus **100** in some embodiments rotates on its own axis the rotating table **171** that supports the substrate **200** while revolving the rotating table **171** along a non-point symmetric elliptical orbit, by the control of the revolving orbit using the guide rail **137A**. Such revolution and rotation cause complex displacement of all points on the substrate **200** such that the points traverse the non-uniform spatial distribution of the film material from the vapor deposition source **10**, and enables a thin film with uniform thickness to be formed on the front surface of the substrate **200**.

(58) A graph in FIG. **8** shows measurement results for comparison experiment. In the comparative experiment, a substrate holding base fixed so as not to move with respect to the main rotation plate **151** is provided between two adjacent auxiliary rotation devices **170** on the main rotation plate **151**. In that state, while the substrate rotating apparatus **100** was rotated, thin film formation was performed. A film thickness λ of the substrate **200** held by the rotating table **171** and a film thickness λ of the substrate **200** held by the substrate holding base were measured.

(59) A horizontal axis in the graph indicates a position of the front surface of the substrate **200**. A vertical axis in the graph indicates the film thickness λ of the thin film formed on the front surface of the substrate **200**. A line chart plotted with circular symbols indicates the spatial distribution of the film thickness λ on the substrate **200** mounted on the substrate holding base. A line chart plotted with rectangular symbols indicates the spatial distribution in the film thickness λ on the substrate **200** mounted on the rotating table **171** in some embodiments. As described above, it can be understood that a thin film with a uniform thickness (λ) can be formed on the substrate **200** with extremely high precision in the substrate rotating apparatus **100** of some embodiments.

(60) As explained above, in the substrate rotating apparatus **100** in some embodiments, the main rotation device **150** corresponding to a main rotation mechanism rotates around a first rotation shaft **R1** (shafts **135**, **155**).

(61) The rotating table **171**, the shaft **175**, and the wheel **179** of the auxiliary rotation device **170** corresponding to an auxiliary rotation mechanism revolve about the first rotation shaft **R1** (shafts **135**, **155**) as the main rotation plate **151** rotates, and rotate around a second rotation shaft **R2** (shaft

175) on its own axis. The rotating table 171, the shaft 175, and the wheel 179 are provided to the main rotation plate 151.

(62) In the auxiliary rotation device 170, the rotating table 171 comprising a support structure (recess 171A) of the substrate 200 rotates around the second rotation shaft R2 (shaft 175), and further, the second rotation shaft R2 (shaft 175) is displaced in the circumferential direction with respect to the third rotation shaft R3. The third rotation shaft R3 (joint 183) is provided between the first rotation shaft R1 (shafts 135, 155) and the second rotation shaft R2 (shaft 175) in the main rotation plate 151. Accordingly, with the circumferential displacement, the second rotation shaft R2 (shaft 175) is displaced in the radial direction with respect to the first rotation shaft R1.

(63) The guide rail 137A constituting a guide structure includes an inner circumferential surface 137B used for controlling the revolving motion of the rotating table 171. The inner circumferential surface 137B extends in the circumferential direction with respect to the first rotation shaft R1 (shafts 135, 155), has a non-point symmetric ring-shaped profile, and faces the first rotation shaft R1.

(64) The guide rail 137A brings the inner circumferential surface 137B into contact with the wheel 179 of the auxiliary rotation device 170, and regulates displacement of the wheel 179 radially outward of the main rotation plate 151. This regulation causes the guide rail 137A to control a circumferential displacement of the second rotation shaft R2 (shaft 175) and the rotating table 171 along the slit 159, and a resulting displacement in the radial direction with respect to the first rotation shaft R1, such that the rotating table 171 performs the revolving motion in an orbit corresponding to the inner circumferential surface 137B (an orbit along the inner circumferential surface 137B).

(65) As described above, the substrate rotating apparatus 100 in some embodiments enables the rotating table 171 to perform the non-point symmetric revolving motion while rotating on its own axis without employing a film thickness correction plate or a planetary gear mechanism, and displaces all points of the substrate 200 with respect to the spatial distribution of the film material scattered from the vapor deposition sources 10. Accordingly, as it can be understood from the experimental results as well, the uniform thin film with high precision can be formed on the front surface of the substrate 200.

(66) In the film formation using the planetary gear mechanism, it is difficult to remove an influence of even function terms of the function $T(r)$, that is, an influence of $r \cdot \sin n$ term with an even order n by making the coefficient closer to zero, since the revolving orbit is perfectly circular. On the other hand, in some embodiments, the rotating table 171 can be rotated in the non-point symmetric elliptical revolving orbit. Therefore, the influence of even function terms can be removed, and thus, the uniform film thickness λ can be achieved.

(67) Also, in the film formation using the planetary gear mechanism, when two or more vapor deposition sources 10 having different spatial distributions of scattered particles are used, it was difficult to make thin films to be uniformly formed in each of the vapor deposition sources 10, since the revolving orbit is perfectly circular. According to the substrate rotating apparatus 100 in some embodiments, such non-uniformity can be reduced. That is, the substrate rotating apparatus 100 can make the thin films formed using each of the two or more vapor deposition sources 10 more uniform than before.

(68) In addition, vibration is likely to be generated during rotation in the planetary gear mechanism. According to the substrate rotating apparatus 100 in some embodiments, vibration during rotation can be also reduced. Vibration reduction as such contributes to high precision film thickness formation.

(69) In some embodiments, the revolving orbit is controlled not by a gear but using the guide rail 137A. Thus, a relatively large-scale substrate rotating apparatus 100 can be easily manufactured, and a system can be built which can form films with uniform thickness on a large substrate 200. Therefore, according to some embodiments, costs related to film formation can be reduced, and

productivity of product can be improved.

(70) In some embodiments, the wheel **179** of the auxiliary rotation device **170** is pressed against the inner circumferential surface **137B** of the guide rail **137A**, using the biasing force and the centrifugal force by the spring **185**, so as not to be separated from, or further to slip on, the inner circumferential surface **137B**. Then, the rotation of the wheel **179** is used to rotate the rotating table **171** around the second rotation shaft R2 (shaft **175**). This allows high precision control of the rotational motion of the substrate **200**, and high precision formation of thin films.

(71) In some embodiments, the rotating mechanism **180** holds the second rotation shaft R2 in a manner movable in the circumferential direction with respect to the third rotation shaft R3 by the link mechanism, and thereby in a manner displaceable in the radial direction with respect to the first rotation shaft R1. Thus, with the simple configuration, the rotating table **171** can be held in a manner displaceable in the radial direction with respect to the first rotation shaft R1. Accordingly, a lightweight and durable substrate rotating apparatus **100** can be manufactured. Being lightweight is also advantageous in that the main rotation plate **151** can be rotated in high speed with less energy.

(72) According to some embodiments, various revolving orbits other than the elliptical orbit shown in FIG. 3 can be easily achieved by changing a circumferential shape of the guide rail **137A**. Ellipticity is not limited to the example shown in FIG. 3. For example, the revolving orbit may have any ellipse with an ellipticity a/b of 0.99 or less, where a is the shortest distance in the ellipse, and b is the longest distance in the ellipse.

(73) As shown in FIG. 9, the guide rail **137A** may be replaced with a guide rail **139A** having a non-point symmetric ring-shaped profile other than the elliptical profile. The guide rail **139A** may be arranged so as to circumferentially meander on the base plate **131**.

(74) Two or more guide members **137** including guide rails having different shapes may be prepared, and these guide members **137** may be alternately fixed to the base plate **131**. As a result, the substrate rotating apparatus **100** can achieve a very wide variety of revolving motions.

(75) The substrate rotating apparatus **100** may be provided with a mechanism configured to move the guide rails **137A**, **139A**. As shown in FIG. 10, a substrate rotating apparatus **190** comprises a first sliding mechanism **141** and a second sliding mechanism **142**. The first sliding mechanism **141** slides a first portion **1391** of a guide rail **139A** in a radial direction with respect to a first rotation shaft. The second sliding mechanism **142** slides a second portion **1392** of the guide rail **139A** in the radial direction with respect to the first rotation shaft. The first sliding mechanism **141** and the second sliding mechanism **142** are arranged on the base plate **131** of the guiding device **130**. The first portion **1391** and the second portion **1392** of the guide rail **139A** are separated from the bottom plate and other portions of the guide rail **139A**.

(76) The substrate rotating apparatus **190** can be configured similarly to the substrate rotating apparatus **100** of the aforementioned embodiment, except that the portions of the guide rail **139A** are configured to be movable and that the substrate rotating apparatus **190** comprises the first and second sliding mechanisms **141**, **142**. According to the substrate rotating apparatus **190**, since the revolving orbit of the rotating table **171** can be adjusted for uniform film thickness, thin films can be formed with higher precision.

(77) According to some embodiments, the substrate rotating apparatus **100** is arranged within the container **15** of the dielectric film vapor deposition device **1** comprising two or more vapor deposition sources **10**. The dielectric film vapor deposition device **1** corresponds to a processing system for film formation, and the two or more vapor deposition source **10** correspond to a processing apparatus.

(78) According to some embodiments, the substrate rotating apparatus **100** may be mounted to the processing system **300** for milling, as shown in FIG. 11A. Then, the substrate rotating apparatus **100** may be used to rotate the substrate **200** subject to milling. The processing system **300** shown in FIG. 11A comprises the substrate rotating apparatus **100** together with a processing apparatus **301** for milling. The processing system **300** is configured to scrape, by an ion beam from the processing

apparatus **301**, the front surface of the substrate **200** that rotates and revolves together with the rotating table **171** by the movement of the substrate rotating apparatus **100**.

(79) According to some embodiments, the substrate rotating apparatus **100** may be mounted to a processing system **400** for etching as shown in FIG. **11B**. Then, the substrate rotating apparatus **100** may be used to rotate the substrate **200** subject to etching. The processing system **400** shown in FIG. **11B** comprises the substrate rotating apparatus **100** together with a processing apparatus **401** for etching. The processing system **400** may be configured to scrape, by scattering an etching agent from the processing apparatus **301**, the front surface of the substrate **200** that rotates and revolves together with the rotating table **171** by the movement of the substrate rotating apparatus **100**.

(80) Example embodiments of the substrate rotating apparatus in some embodiments have been described in the above. However, it goes without saying that the substrate rotating apparatus should not be limited to the aforementioned embodiments, and various modes can be taken.

(81) For example, the substrate rotating apparatus **100** may not be provided with the spring **185**. Without the spring **185**, the wheel **179** may be sufficiently pressed onto the guide rail **137A** by the centrifugal force. In addition, the substrate rotating apparatus **100** shown in the drawings is conceptual, and the size and shape of each portions of the substrate rotating apparatus **100** are not limited to those in the drawings.

(82) Functions of one element in the aforementioned embodiments may be achieved by two or more elements. Functions of two or more elements in the aforementioned embodiments may be achieved by one element. A part of the configuration of the aforementioned embodiments may be omitted. It should be noted that any and all forms that are encompassed in the technical ideas identified by the languages in the claims are embodiments of the present disclosure.

Claims

1. A substrate rotating apparatus for film formation comprising: a main rotation device including a rotation plate configured to rotate around a first rotation shaft, the rotation plate having a slit; an auxiliary rotation device provided on the rotation plate and configured to revolve about the first rotation shaft as the rotation plate rotates; and a guide rail provided around the first rotation shaft and configured to control a revolving motion of the auxiliary rotation device, the guide rail having a contact surface extending in a circumferential direction with respect to the first rotation shaft, the auxiliary rotation device comprising: a second rotation shaft penetrating the slit of the rotation plate; a rotating table for supporting a substrate as an object to be processed, the rotating table being arranged at a first end portion of the second rotation shaft; and a wheel traveling on the contact surface, the wheel being arranged at a second end portion opposite to the first end portion of the second rotation shaft and coupled to the rotating table via the second rotation shaft, the wheel and the rotating table rotating around the second rotation shaft while the wheel travels on the contact surface along with the revolving motion, the slit of the rotation plate provided in a circumferential direction with respect to a third rotation shaft, the third rotation shaft being provided between the first rotation shaft and the second rotation shaft, the second rotation shaft being displaced, along the slit, in a circumferential direction with respect to the third rotation shaft, the guide rail controlling displacement of the second rotation shaft in the circumferential direction with respect to the third rotation shaft, and causing the auxiliary rotation device to perform the revolving motion in an orbit along the contact surface when the contact surface and the auxiliary rotation device are in contact with each other.
2. The substrate rotating apparatus according to claim 1, wherein the contact surface is an inner circumferential surface facing the first rotation shaft included in the guide rail, and the inner circumferential surface controls radially outward displacement of the auxiliary rotation device with respect to the first rotation shaft.
3. The substrate rotating apparatus according to claim 1, wherein the auxiliary rotation device is

coupled to the main rotation device via a spring that biases the auxiliary rotation device in a direction to maintain contact with the contact surface.

4. The substrate rotating apparatus according to claim 1, wherein the auxiliary rotation device performs a revolving motion about the first rotation shaft in an elliptical orbit.

5. The substrate rotating apparatus according to claim 4, wherein the contact surface is arranged in an elliptical shape in the circumferential direction with respect to the first rotation shaft.

6. The substrate rotating apparatus according to claim 1, wherein the contact surface is arranged in a non-point symmetric ring shape in the circumferential direction with respect to the first rotation shaft, and the auxiliary rotation device performs a revolving motion about the first rotation shaft in a non-point symmetric orbit.

7. A processing system comprising: a substrate rotating apparatus according to claim 1; and a processing apparatus configured to process a front surface of the substrate that rotates and revolves together with the auxiliary rotation device by operation of the substrate rotating apparatus.

8. The processing system according to claim 7, wherein the processing apparatus is configured to process the front surface of the substrate by forming a film on the front surface of the substrate or by scraping the front surface of the substrate.

9. The processing system according to claim 7, wherein the processing apparatus is configured to process the front surface of the substrate by film formation, milling, or etching.

10. The processing system according to claim 7, wherein the processing apparatus is configured to process the front surface of the substrate by scattering a substance toward the front surface of the substrate.

11. A processing method comprising: operating a substrate rotating apparatus, comprising: a main rotation device including a rotation plate configured to rotate around a first rotation shaft, the rotation plate having a slit; an auxiliary rotation device provided on the rotation plate and configured to revolve about the first rotation shaft as the rotation plate rotates; and a guide rail provided around the first rotation shaft and configured to control a revolving motion of the auxiliary rotation device, the guide rail having a contact surface extending in a circumferential direction with respect to the first rotation shaft, the auxiliary rotation device comprising: a second rotation shaft penetrating the slit of the rotation plate; a rotating table for supporting a substrate as an object to be processed, the rotating table being arranged at a first end portion of the second rotation shaft; and a wheel traveling on the contact surface, the wheel being arranged at a second end portion opposite to the first end portion of the second rotation shaft and coupled to the rotating table via the second rotation shaft, the wheel and the rotating table rotating around the second rotation shaft while the wheel travels on the contact surface along with the revolving motion, the slit of the rotation plate provided in a circumferential direction with respect to a third rotation shaft, the third rotation shaft being provided between the first rotation shaft and the second rotation shaft, the second rotation shaft being displaced, along the slit, in a circumferential direction with respect to the third rotation shaft, the guide rail controlling displacement of the second rotation shaft in the circumferential direction with respect to the third rotation shaft, and causing the auxiliary rotation device to perform the revolving motion in an orbit along the contact surface when the contact surface and the auxiliary rotation device are in contact with each other; and processing a front surface of the substrate that rotates and revolves together with the auxiliary rotation device by operation of the substrate rotating apparatus.
