

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407141
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Fremrot; Per Henrik et al.

Pluggable terminal block short circuit prevention system

Abstract

A pluggable terminal block short circuit prevention system includes a pluggable terminal block having a computing device connector with positive and negative power sub-connectors that connect to a pluggable terminal block connector on a computing device. A power system connector is included on the pluggable terminal block and includes terminal block positive and negative power contacts that are coupled to the positive and negative power sub-connectors on the computing device connector, respectively. The power system connector couples to a power system via power cabling having a power cabling connector that includes power cabling connector positive and negative power contacts that are configured to engage the terminal block positive and negative power contacts when the power cabling connector is connected to the power system connector, with the power cabling connector preventing relative movement between the power cabling connector positive and negative power contacts.

Inventors: Fremrot; Per Henrik (Novato, CA), Montgomery; Colin (Mountain View, CA), Shah; Maunish (Austin, TX)

Applicant: Dell Products L.P. (Round Rock, TX)

Family ID: 93651642

Assignee: Dell Products L.P. (Round Rock, TX)

Appl. No.: 18/326578

Filed: May 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240405489 A1	Dec. 05, 2024

Publication Classification

Int. Cl.: H01R24/38 (20110101); H01R13/59 (20060101); H01R105/00 (20060101)

U.S. Cl.:

CPC H01R24/38 (20130101); H01R13/59 (20130101); H01R2105/00 (20130101);
H01R2201/06 (20130101)

Field of Classification Search

CPC: H01R (13/59); H01R (24/38)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7306484	12/2006	Mahoney	439/578	H01R 24/542
2009/0305577	12/2008	Bradford-Stagg	439/680	H01R 24/38
2011/0078346	12/2010	O'Connor	710/63	H04L 49/351
2020/0067238	12/2019	Byrne	N/A	H01R 13/6683

OTHER PUBLICATIONS

Degson (Aug. 2022). "15EDGKAM-3.81-XXP-1Y-100A&Z(H) Customer Drawing" [Drawing No. 200102343] (Year: 2022). cited by examiner

Delock. (Jan. 2017). "Datasheet: Delock Adapter DC 2.1×5.5 mm female > Terminal Block 2 pin " [Item No. 65421] (Year: 2017). cited by examiner

Degson (Year: 2022). cited by examiner

Delock (Year: 2017). cited by examiner

Primary Examiner: Bauer; Scott

Background/Summary

BACKGROUND

(1) The present disclosure relates generally to information handling systems, and more particularly to preventing short circuits when using pluggable terminal blocks with information handling systems.

(2) As the value and use of information continues to increase, individuals and businesses seek additional ways to process and store information. One option available to users is information handling systems. An information handling system generally processes, compiles, stores, and/or communicates information or data for business, personal, or other purposes thereby allowing users to take advantage of the value of the information. Because technology and information handling needs and requirements vary between different users or applications, information handling systems may also vary regarding what information is handled, how the information is handled, how much information is processed, stored, or communicated, and how quickly and efficiently the information may be processed, stored, or communicated. The variations in information handling systems allow for information handling systems to be general or configured for a specific user or specific use such as financial transaction processing, airline reservations, enterprise data storage, or global

communications. In addition, information handling systems may include a variety of hardware and software components that may be configured to process, store, and communicate information and may include one or more computer systems, data storage systems, and networking systems.

(3) Information handling systems such as, for example, industrial computing devices such as edge gateway devices (e.g., the DELL® Edge Gateway 3200 available from DELL® Inc. of Round Rock, Texas, United States), may utilize pluggable terminal blocks to couple power systems to the industrial computing device to provide relatively low voltage Direct Current (DC) power to the industrial computing device. For example, conventional pluggable terminal blocks may include a terminal block chassis, a computing device connector that extends from the terminal block chassis and that is configured to connect to the industrial computing devices discussed above, and power wire couplings that are included on the terminal block chassis and that are configured to accept power wires (a positive wire, a negative wire, and a ground wire) that are coupled to a power system. The power wire couplings on the conventional pluggable terminal block include respective power wire contacts that are configured to engage partially exposed portions of the power wires (i.e., portions of the power wires that are not completely covered by insulating material) to couple the power wires to the computing device connector on the pluggable terminal block. The power wire couplings may be configured to secure the power wires to the conventional pluggable terminal block in a variety of manners including, for example, via the use of screw-in terminals, spring clamps, push-in terminals, and/or other securing mechanisms known in the art. Following the securing of power wires to the conventional pluggable terminal block, the computing device connector on the pluggable terminal block may then be connected to terminal block connectors on industrial computing devices like those discussed above. The utilization of such conventional pluggable terminal blocks can raise some issues.

(4) For example, incomplete insertion of the power wires into the power wire couplings on conventional pluggable terminal blocks and/or stress on the power wires connected to conventional pluggable terminal blocks may expose the exposed portion of the power wires, and in some cases can result in the power wires be disconnected from the conventional pluggable terminal blocks. As will be appreciated by one of skill in the art in possession of the present disclosure, the exposure and/or disconnection of power wires connected to conventional pluggable terminal blocks may cause a short circuit that can result in smoke, arcing, and/or other issues that can damage the computing device and/or power system to which they are connected, and/or present issues with the environments in which they are located (e.g., “magic” smoke created by a short circuit can contaminate a clean room environment and may be very costly to remedy).

(5) Accordingly, it would be desirable to provide a pluggable terminal block system that addresses the issues discussed above.

SUMMARY

(6) According to one embodiment, a pluggable terminal block short circuit prevention system includes a chassis; a processing system that is housed in the chassis; a pluggable terminal block connector that is coupled to the processing system and accessible on the surface of the chassis; and a pluggable terminal block including: a computing device connector that includes a computing device positive power sub-connector and a computing device negative power sub-connector, and that is connected to the pluggable terminal block connector; and a power system connector that is included on the pluggable terminal block and that includes a terminal block positive power contact that is coupled to the computing device positive power sub-connector, and a terminal block negative power contact that is coupled to the computing device negative power sub-connector, wherein the power system connector is coupled to a power system via power cabling having a power cabling connector that includes: a power cabling connector positive power contact that engages the terminal block positive power contact, and a power cabling connector negative power contact that engages the terminal block negative power contact, wherein the power cabling

connector prevents relative movement between the power cabling connector positive power contact and the power cabling connector negative power contact.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic view illustrating an embodiment of an Information Handling System (IHS).
- (2) FIG. 2A is a perspective view illustrating an embodiment of a computing device that may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure.
- (3) FIG. 2B is a perspective view illustrating an embodiment of a pluggable terminal block connector on the computing device of FIG. 2A.
- (4) FIG. 3A is a perspective front view illustrating an embodiment of a pluggable terminal block utilized in the pluggable terminal block short circuit prevention system of the present disclosure.
- (5) FIG. 3B is a perspective rear view illustrating an embodiment of the pluggable terminal block of FIG. 3A.
- (6) FIG. 4A is a perspective front view illustrating an embodiment of a pluggable terminal block utilized in the pluggable terminal block short circuit prevention system of the present disclosure.
- (7) FIG. 4B is a perspective rear view illustrating an embodiment of the pluggable terminal block of FIG. 4A.
- (8) FIG. 5 is a perspective front view illustrating an embodiment of a pluggable terminal block utilized in the pluggable terminal block short circuit prevention system of the present disclosure.
- (9) FIG. 6A is a perspective view illustrating an embodiment of a threaded barrel-style connector utilized in the pluggable terminal block short circuit prevention system of the present disclosure.
- (10) FIG. 6B is a perspective view illustrating an embodiment of a non-threaded barrel-style connector utilized in the pluggable terminal block short circuit prevention system of the present disclosure.
- (11) FIG. 7 is a flow chart illustrating an embodiment of a method for preventing short circuits with a pluggable terminal block.
- (12) FIG. 8A is a perspective view illustrating an embodiment of a conventional pluggable terminal block.
- (13) FIG. 8B is a perspective view illustrating an embodiment of the use of the conventional pluggable terminal block of FIG. 8A.
- (14) FIG. 8C is a perspective view illustrating an embodiment of issues associated with the use of the conventional pluggable terminal block of FIG. 8A.
- (15) FIG. 9A is a perspective view illustrating an embodiment of the pluggable terminal block of FIGS. 3A and 3B being connected to the computing device of FIGS. 2A and 2B during the method of FIG. 7.
- (16) FIG. 9B is a perspective view illustrating an embodiment of the pluggable terminal block of FIGS. 3A and 3B connected to the computing device of FIGS. 2A and 2B during the method of FIG. 7.
- (17) FIG. 9C is a perspective view illustrating an embodiment of the barrel-style connector of FIG. 6A or 6B being connected to the pluggable terminal block and computing device of FIG. 9B during the method of FIG. 7.
- (18) FIG. 9D is a perspective view illustrating an embodiment of the barrel-style connectors of FIG. 6A or 6B being connected to the pluggable terminal block and computing device of FIG. 9B during the method of FIG. 7.
- (19) FIG. 9E is a perspective view illustrating an embodiment of the barrel-style connector of FIG. 6A or 6B connected to the pluggable terminal block and computing device of FIG. 9B during the

method of FIG. 7.

DETAILED DESCRIPTION

(20) For purposes of this disclosure, an information handling system may include any instrumentality or aggregate of instrumentalities operable to compute, calculate, determine, classify, process, transmit, receive, retrieve, originate, switch, store, display, communicate, manifest, detect, record, reproduce, handle, or utilize any form of information, intelligence, or data for business, scientific, control, or other purposes. For example, an information handling system may be a personal computer (e.g., desktop or laptop), tablet computer, mobile device (e.g., personal digital assistant (PDA) or smart phone), server (e.g., blade server or rack server), a network storage device, or any other suitable device and may vary in size, shape, performance, functionality, and price. The information handling system may include random access memory (RAM), one or more processing resources such as a central processing unit (CPU) or hardware or software control logic, ROM, and/or other types of nonvolatile memory. Additional components of the information handling system may include one or more disk drives, one or more network ports for communicating with external devices as well as various input and output (I/O) devices, such as a keyboard, a mouse, touchscreen and/or a video display. The information handling system may also include one or more buses operable to transmit communications between the various hardware components.

(21) In one embodiment, IHS **100**, FIG. **1**, includes a processor **102**, which is connected to a bus **104**. Bus **104** serves as a connection between processor **102** and other components of IHS **100**. An input device **106** is coupled to processor **102** to provide input to processor **102**. Examples of input devices may include keyboards, touchscreens, pointing devices such as mice, trackballs, and trackpads, and/or a variety of other input devices known in the art. Programs and data are stored on a mass storage device **108**, which is coupled to processor **102**. Examples of mass storage devices may include hard discs, optical disks, magneto-optical discs, solid-state storage devices, and/or a variety of other mass storage devices known in the art. IHS **100** further includes a display **110**, which is coupled to processor **102** by a video controller **112**. A system memory **114** is coupled to processor **102** to provide the processor with fast storage to facilitate execution of computer programs by processor **102**. Examples of system memory may include random access memory (RAM) devices such as dynamic RAM (DRAM), synchronous DRAM (SDRAM), solid state memory devices, and/or a variety of other memory devices known in the art. In an embodiment, a chassis **116** houses some or all of the components of IHS **100**. It should be understood that other buses and intermediate circuits can be deployed between the components described above and processor **102** to facilitate interconnection between the components and the processor **102**.

(22) Referring now to FIG. **2A**, an embodiment of a computing device **200** is illustrated that may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure. In an embodiment, the computing device **200** may be provided by the IHS **100** discussed above with reference to FIG. **1**, and/or may include some or all of the components of the IHS **100**, and in specific examples, may be provided by industrial computing devices such as edge gateway device (e.g., the DELL® Edge Gateway 3200 available from DELL® Inc. of Round Rock, Texas, United States), which one of skill in the art in possession of the present disclosure will appreciate provides an industrial computing device that is typically utilized in manufacturing scenarios to collect data, pre-process that data, and provide that data for storage (e.g., in a network or cloud connected storage system). However, while illustrated and discussed as being provided by a particular type of computing device **200**, one of skill in the art in possession of the present disclosure will appreciate that the functionality of the computing device **200** discussed below may be provided by other devices that are configured to operate similarly as the computing device **200** and utilize pluggable terminal blocks to connect with power systems.

(23) In the illustrated embodiment, the computing device **200** includes a chassis **202** that houses the components of the computing device **200**, only some of which are illustrated and discussed below.

For example, the chassis **202** may house a processing system (not illustrated, but which may include the processor **102** discussed above with reference to FIG. **1**) and a memory system (not illustrated, but which may include the memory **114** discussed above with reference to FIG. **1**) that is coupled to the processing system and that includes instructions that, when executed by the processing system, cause the processing system to provide a computing device engine (not illustrated) that is configured to perform the functionality of the computing devices discussed below.

(24) In the illustrated embodiment, the chassis **202** includes a top surface **202a**, a bottom surface **202b** that is located opposite the chassis **202** from the top surface **202a**, a front surface **202c** that extends between the top surface **202a** and the bottom surface **202b**, a rear surface **202d** that is located opposite the chassis **202** from the front surface **202c** and that extends between the top surface **202a** and the bottom surface **202b**, and a pair of side surfaces **202e** and **202f** that are located opposite one another on the chassis **202** and that each extend between the top surface **202a**, the bottom surface **202b**, the front surface **202c** and the rear surface **202d**. The chassis **202** may include a pluggable terminal block connector **204** that, in the illustrated embodiment, is located on the rear surface **202d** and that is configured to connect a pluggable terminal block provided according to the teachings of the present disclosure.

(25) With reference to FIG. **2B**, in the illustrated embodiment, the pluggable terminal block connector **204** includes a positive power sub-connector **204a**, a ground sub-connector **204b**, and a negative power sub-connector **204c**, although embodiments in which the pluggable terminal block connector **204** includes only a positive power sub-connector **204a** and a negative power sub-connector **204c** will fall within the scope of the present disclosure as well. Furthermore, while a specific configuration/order of the positive power sub-connector **204a**, the ground sub-connector **204b**, and the negative power sub-connector **204c** is illustrated and described, one of skill in the art in possession of the present disclosure will appreciate how other configurations/ordering of the positive power sub-connector **204a**, the ground sub-connector **204b**, and/or the negative power sub-connector **204c** will fall within the scope of the present disclosure as well. However, while a specific computing device that utilizes a pluggable terminal block provided according to the teachings of the present disclosure has been illustrated and described, one of skill in the art in possession of the present disclosure will appreciate how other devices may utilize a pluggable terminal block provided according to the teachings of the present disclosure while remaining within the scope of the present disclosure as well.

(26) Referring now to FIGS. **3A** and **3B**, an embodiment of a pluggable terminal block **300** is illustrated that may be utilized in the pluggable terminal block short circuit prevention system of the present disclosure. As will be appreciated by one of skill in the art in possession of the present disclosure, the pluggable terminal block **300** provides a European-style terminal block (also referred to as a “Euroblock”, “Eurostyle” connector, and a “PHOENIX®” connector) with a modified power connector, and may be used to couple power systems to industrial computing devices in order to provide relatively low voltage Direct Current (DC) power to those industrial computing devices. However, while a specific use for the pluggable terminal block **300** has been described, one of skill in the art in possession of the present disclosure will appreciate how other uses of the pluggable terminal block **300** will fall within the scope of the present disclosure as well.

(27) In the illustrated embodiment, the pluggable terminal block **300** includes a pluggable terminal block chassis **302** having a top surface **302a**, a bottom surface **302b** that is located opposite the pluggable terminal block chassis **302** from the top surface **302a**, a front surface **302c** that extends between the top surface **302a** and the bottom surface **302b**, a rear surface **302d** that is located opposite the pluggable terminal block chassis **302** from the front surface **302c** and that extends between the top surface **302a** and the bottom surface **302b**, and a pair of opposing side surfaces **302e** and **302f** that are located opposite the pluggable terminal block chassis **302** from each other and that each extend between the top surface **302a**, the bottom surface **302b**, the front surface **302c**,

and the rear surface **302d**. As will be appreciated by one of skill in the art in possession of the present disclosure, the pluggable terminal block chassis **302** illustrated and described below may provide a European-style terminal block chassis for the European-style terminal block with the modified power connector described above.

(28) The pluggable terminal block chassis **302** includes a computing device connector **304** that extends from the front surface **302c** of the pluggable terminal block chassis **302** and, in the illustrated embodiment, includes a computing device positive power sub-connector **304a**, a ground sub-connector **304b**, and a computing device negative power sub-connector **304c** that are each configured to connect to the respective positive power sub-connector, negative power sub-connector, and ground sub-connector on the pluggable terminal block connector **204** included on the computing device **200** discussed above with reference to FIG. 2. However, while a specific configuration/order of the positive power sub-connector **304a**, the ground sub-connector **304b**, and the negative power sub-connector **304c** is illustrated and described, one of skill in the art in possession of the present disclosure will appreciate how other configurations/ordering of the positive power sub-connector **304a**, the ground sub-connector **304b**, and/or the negative power sub-connector **304c** will fall within the scope of the present disclosure as well. The pluggable terminal block chassis **302** also includes a pair of securing members **306a** and **306b** that extend opposite each other from the side surfaces **302e** and **302f**, respectively. In the specific examples provided below, the securing members **306a** and **306b** include screws that are configured to secure the pluggable terminal block chassis **302** to the pluggable terminal block connector **204** included on the computing device **200**, but one of skill in the art in possession of the present disclosure will appreciate how a variety of securing elements may be used to secure the pluggable terminal block chassis **302** to the pluggable terminal block connector **204** included on the computing device **200** while remaining within the scope of the present disclosure as well.

(29) The pluggable terminal block chassis **302** also includes a power system connector **308** that extends from the rear surface **302d** of the pluggable terminal block chassis **302**. In a specific example, the power system connector **308** may include a cantilever spring (not visible in FIGS. 3A and 3B) that provides a negative power contact and that is configured to engage a power cabling connector on power cabling, and a pin (not visible in FIGS. 3A and 3B) that provides a positive power contact and that is configured to engage the power cabling connector on the power cabling, as discussed in further detail below. However, while a specific structure of the power system connector **308** has been provided, one of skill in the art in possession of the present disclosure will appreciate how other power system connector structures (e.g., with the cantilever spring providing the positive power contact and the pin providing the negative power contact) will fall within the scope of the present disclosure as well.

(30) In the illustrated embodiment, the power system connector **308** also includes a threaded securing subsystem **308a** that is configured to secure power cabling to the pluggable terminal block **300**. In the specific example illustrated in FIGS. 3A and 3B, the power system connector **308** is provided by a female barrel-style power connector that extends from the chassis **302** of the pluggable terminal block **300** and that includes a threaded outer surface. However, as discussed below, the power system connector **308** may be replaced with a female barrel-style power connectors that extend into the chassis **302** of the pluggable terminal block **300** and that are not configured to secure power cabling to the pluggable terminal block **300** while remaining within the scope of the present disclosure as well. Furthermore, while illustrated and described as being provided by barrel-style power connectors, the power system connector **308** may be replaced by a variety of other types of power connectors (e.g., Universal Serial Bus (USB) connectors) that one of skill in the art in possession of the present disclosure would recognize as providing the structural benefits of the barrel-style power connections described below.

(31) As would be appreciated by one of skill in the art in possession of the present disclosure, the power system connector **308** includes a positive power sub-connector and a negative power sub-

connector, with the positive power sub-connector on the power system connector **308** coupled to the computing device positive power sub-connector **304a** on the computing device connector **304**, and the negative power sub-connector on the power system connector **308** coupled to the computing device negative power sub-connector **304c** on the computing device connector **304**. In an embodiment, the computing device ground sub-connector **304b** on the computing device connector **304** may be coupled to the negative power sub-connector on the power system connector **308** (e.g., to allow the computing device ground sub-connector **304b** to be coupled to ground via a power system connected to the power system connector **308**), although one of skill in the art in possession of the present disclosure will appreciate how other techniques for coupling the computing device ground sub-connector **304b** to ground will fall within the scope of the present disclosure.

(32) For example, referring now to FIGS. **4A** and **4B**, an embodiment of a pluggable terminal block **400** is illustrated that is substantially similar to the pluggable terminal block **300** discussed above with reference to FIGS. **3A** and **3B**, and thus similar components are provided with similar element numbers. Similarly as discussed above, the pluggable terminal block **400** may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure and may be used with the computing device **200** and/or other devices that utilize pluggable terminal blocks according to the teachings of the present disclosure. In the illustrated embodiment, the pluggable terminal block **400** includes a ground coupling device **402** that is located on the top surface **302a** of the pluggable terminal block chassis **302** and that, in the illustrated example, includes a fastener channel **402a** that is defined by the pluggable terminal block chassis **302**, along with a fastener device **402b** (e.g., a screw in the illustrated example) that is moveably connected to the fastener channel **402a**. As will be appreciated by one of skill in the art in possession of the present disclosure, a ground contact may be located in the fastener channel **402a** and coupled to the ground sub-connector **304b**.

(33) While not illustrated or described in detailed below, and as will be appreciated by one of skill in the art in possession of the present disclosure, following the connection of the pluggable terminal block **400** the computing device **200** (discussed in detail below), a grounding wire (not illustrated in FIG. **4A**) may be positioned in the fastener channel **402a** between the fastener device **402b** and the ground contact, and then the fastener device **402b** may be tightened to cause the grounding wire to engage the ground contact. As such, the pluggable terminal block of the present disclosure may be grounded in a variety of manners while remaining within the scope of the present disclosure.

(34) Referring now to FIG. **5**, an embodiment of a pluggable terminal block **500** is illustrated that is substantially similar to the pluggable terminal block **300** discussed above with reference to FIGS. **3A** and **3B**, and thus similar components are provided with similar element numbers. Similarly as discussed above, the pluggable terminal block **500** may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure and may be used with the computing device **200** and/or other devices that utilize pluggable terminal blocks according to the teachings of the present disclosure. As will be appreciated by one of skill in the art in possession of the present disclosure, the pluggable terminal block **500** omits the ground sub-connector **304b** that is included on the computing device connector **304** on the pluggable terminal block **300**. For example, the pluggable terminal block **500** may be utilized with a computing device and or power system that include separate grounding subsystems that do not utilize the pluggable terminal block **500**.

(35) Referring now to FIG. **6A**, an embodiment of power cabling **600** is illustrated that may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure, and provides an example of power cabling that may be secured to the pluggable terminal block. In the embodiment illustrated in FIG. **6A**, the power cabling **600** includes a power cable **602** having a power cabling connector included on at least one end (with only a single power cabling connector on one end of the power cable **602** illustrated in FIGS. **6A** and **6B**). The power cabling connector

includes a connector base **604**, and a barrel-style power connector **606** extends from the connector base **604** and is configured to transmit power received through the power cable **602** from a power system (not illustrated). The barrel-style power connector **606** includes a negative power contact **606a** and a positive power contact **606b**, with the barrel-style power connector **606** configured to prevent relative movement between the negative power contact **606a** and the positive power contact **606b**.

(36) In the illustrated embodiment, the negative power contact **606a** is located on the outer surface of the barrel-style power connector **606** and is configured to engage the cantilever spring (not illustrated in FIGS. **6A** and **6B**) that provides the negative power contact on the power system connector **308**, as discussed above. Furthermore, the positive power contact **606b** is located on the inner surface of the barrel-style connector **606** and is configured to engage the pin (not illustrated in FIG. **6A**) that provides the positive power contact on the power system connector **308**, as discussed above. A connector securing element **608** is included on the connector base **604** that is configured to secure the barrel-style power connector **606** in the power system connector **308** on the pluggable terminal blocks **300/400/500** discussed above. As can be seen in FIG. **6A**, the connector securing element **608** may include a threaded securing subsystem **608a** that one of skill in the art in possession of the present disclosure will appreciate is configured to engage the threaded securing subsystem **308a** on the power connector **308** of the pluggable terminal blocks **300/400/500** discussed above to secure the power cabling **600** to the pluggable terminal blocks **300/400/500**.

(37) With reference to FIG. **6B**, another embodiment of power cabling **610** is illustrated that may be utilized with the pluggable terminal block short circuit prevention system of the present disclosure, and provides an example of power cabling that is not configured to be secured to the pluggable terminal block. In the embodiment illustrated in FIG. **6B**, the power cabling **610** includes a power cable **612** having a power cabling connector included on at least one end (with only a single power cabling connector on one end of the power cable **612** illustrated in FIG. **6B**). The power cabling connector includes a connector base **614**, and a barrel-style power connector **616** extends from the connector base **614** and is configured to transmit power received through the power cable **612** from a power system (not illustrated). The barrel-style power connector **616** includes a negative power contact **616a** and a positive power contact **616b**, with the barrel-style power connector **616** configured to prevent relative movement between the negative power contact **616a** and the positive power contact **616b**.

(38) In the illustrated embodiment, the negative power contact **616a** is located on the outer surface of the barrel-style power connector **616**, and the positive power contact **616b** is located on the inner surface of the barrel-style connector **616**. As will be appreciated by one of skill in the art in possession of the present disclosure, the power cabling **610** may be configured to connect to the pluggable terminal block in manner similar to that described above for the power cabling **600**, but via a female barrel-style power connector that extends into the chassis **302** of the pluggable terminal block **300** and that is not configured to secure power cabling **610** to the pluggable terminal block. However, while specific examples of power cabling used with the pluggable terminal blocks of the present disclosure have been illustrated and described, one of skill in the art in possession of the present disclosure will appreciate how other power cabling may be utilized with the pluggable terminal blocks of the present disclosure while remaining within the scope of the present disclosure as well.

(39) Referring now to FIG. **7**, an embodiment of a method **700** for preventing short-circuits with a pluggable terminal block is illustrated. As discussed below, the systems and methods of the present disclosure provide a pluggable terminal block that includes a power system connector that is configured to couple to a power cabling connector that prevents relative movement between its power cabling connector positive and negative power contacts. For example, the pluggable terminal block short circuit prevention system of the present disclosure may include a pluggable terminal block having a computing device connector with a positive and negative power sub-connectors that

connect to a pluggable terminal block connector on a computing device. A power system connector is included on the pluggable terminal block and includes a terminal block positive and negative power contacts that are coupled to the positive and negative power sub-connectors on the computing device connector, respectively. The power system connector couples to a power system via power cabling having a power cabling connector that includes power cabling positive and negative power contacts that are configured to engage the terminal block positive and negative power contacts when the power cabling connector is connected to the power system connector, with the power cabling connector preventing relative movement between the power cabling connector positive and negative power contacts. As discussed below, the configuration of the power system connector on the pluggable terminal block to couple to a power cabling connector that prevents relative movement between its power cabling connector positive and negative power contacts prevents the power cabling connector positive and negative power contacts from engaging, thus preventing short circuits and/or arcing when using the pluggable terminal block.

(40) With reference to FIG. 8A, an embodiment of a conventional pluggable terminal block **800** is illustrated that one of skill in the art in possession of the present disclosure will recognize provides a conventional European-style terminal block that utilizes power wire couplings having respective power wire contacts that each are configured to accept respective exposed portions of power wires (a positive wire, a negative wire, and a ground wire in the illustrated embodiment) on power cabling that is coupled to a power system. As can be seen in FIG. 8A, the conventional pluggable terminal block **800** includes a pluggable terminal block chassis **802** having a top surface **802a**, a bottom surface **802b** that is located opposite the pluggable terminal block chassis **802** from the top surface **802a**, a front surface **802c** that extends between the top surface **802a** and the bottom surface **802b**, a rear surface **802d** that is located opposite the pluggable terminal block chassis **802** from the front surface **802c** and that extends between the top surface **802a** and the bottom surface **802b**, and a pair of opposing side surfaces **802e** and **802f** that are located opposite the pluggable terminal block chassis **802** from each other and that each extend between the top surface **802a**, the bottom surface **802b**, the front surface **802c**, and the rear surface **802d**.

(41) The pluggable terminal block chassis **802** includes a computing device connector **804** that extends from the front surface **802c** of the pluggable terminal block chassis **802** and includes a computing device positive power sub-connector **804a**, a computing device negative power sub-connector **804b**, and a ground sub-connector **804c** that are each configured to connect to a respective positive power sub-connector, negative power sub-connector, and ground sub-connector on a pluggable terminal block connector included on a computing device (e.g., similar to the pluggable terminal block connector **204** on the computing device **200** discussed above with reference to FIG. 2). The pluggable terminal block chassis **802** also includes a pair of securing members **806a** and **806b** that extend opposite each another from the side surfaces **802e** and **802f**, respectively, and that include screws that are configured to secure the pluggable terminal block chassis **802** to the pluggable terminal block connector on the computing device.

(42) The pluggable terminal block chassis **802** also includes a positive power wire coupling **808a**, a negative power wire coupling **808b**, and a ground wire coupling **808c** that are located on the rear surface **802d** of the pluggable terminal block chassis **802**. As would be appreciated by one of skill in the art in possession of the present disclosure, the positive power wire coupling **808a** includes a positive power contact that coupled to the computing device positive power sub-connector **804a** on the computing device connector **804**, the negative power wire coupling **808b** includes a negative power contact that is coupled to the computing device negative power sub-connector **804b** on the computing device connector **804**, and the ground wire coupling **808c** includes a ground contact that coupled to the computing device ground sub-connector **804c** on the computing device connector **804**.

(43) The pluggable terminal block chassis **802** also includes a positive power wire securing member **810a**, a negative power wire securing member **810b**, and a ground wire securing member

810c (e.g., each provided by a respective screw in the illustrated example) that are located on the top surface **802a** of the pluggable terminal block chassis **802**. As will be appreciated by one of skill in the art in possession of the present disclosure, each of the positive power wire securing member **810a**, the negative power wire securing member **810b**, and the ground wire securing member **810c** are configured to move relative to the pluggable terminal block chassis **802** to secure respective power wires to the pluggable terminal block **800**.

(44) For example, with reference to FIG. **8B**, power cabling with a positive power wire **812a**, a negative power wire **812b**, and a ground wire **812c** may be coupled to a power system (not illustrated), and the ends of each of the positive power wire **812a**, the negative power wire **812b**, and the ground wire **812c** may be “stripped” or otherwise exposed as illustrated. The exposed ends of the positive power wire **812a**, the negative power wire **812b**, and the ground wire **812c** may then be inserted into the respective positive power wire coupling **808a**, negative power wire coupling **808b**, and ground wire coupling **808c**. The positive power wire **812a**, negative power wire **812b** and ground wire **812c** may then be secured to the respective contacts in the positive power wire coupling **808a**, the negative power wire coupling **808b**, and the ground coupling **808c** by tightening the respective screws included in the respective positive power wire securing member **810a**, negative power wire securing member **810b**, and ground wire securing member **810c**, thus allowing power from the power system to be transmitted via the power cabling, through the pluggable terminal block **800**, and to the computing device.

(45) With reference to FIG. **8C**, in some situations the use of the exposed wires on the power cabling with the conventional pluggable terminal block **800** can result in short circuits, arcing, and/or other issues that would be apparent to one of skill in the art in possession of the present disclosure. For example, when stress is put on the power cabling, when the positive power wire **812a**, and negative power wire **812b** are not sufficiently separated, and/or in other short circuit or arcing scenarios known in the art, the positive power wire **812a** and negative power wire **812b** may engage and/or be positioned close enough to each other such that a short circuit and/or arcing **814** may occur, which as discussed above can result in smoke and/or other issues that can damage the computing device and/or power system to which they are connected, and/or present issues with the environments in which they are located (e.g., “magic” smoke created by a short circuit can contaminate a clean room environment and may be very costly to remedy). As discussed below, the pluggable terminal block of the present disclosure prevents such issues via the utilization of a power system connector that is configured to connect to power cabling connectors that prevent relative movement of their positive and negative power contacts.

(46) The method **700** begins at block **702** where a positive power sub-connector and negative power sub-connector on a computing device connector included on a pluggable terminal block are connected to a pluggable terminal block connector on a computing device. With references to FIGS. **9A** and **9B**, in an embodiment of block **702**, the computing device positive power sub-connector **304a**, the negative power sub-connector **304c**, and the ground sub-connector **304b** included on the computing device connector **304** on the pluggable terminal block **300** are connected to the pluggable terminal block connector **204** included on the computing device **200**. For example, the pluggable terminal block **300** may be positioned adjacent the pluggable terminal block connector **204** such that the positive power sub-connector **304a**, negative power sub-connector **304c**, and the ground sub-connector **304b** on the computing device connector **304** are aligned with the positive power sub-connector **204a**, the negative power sub-connector **204c**, and the ground sub-connector **204b** on the pluggable terminal block connector **204**.

(47) The pluggable terminal block **300** may then be moved in a direction A towards the pluggable terminal block connector **204** until the positive power sub-connector **304a**, the negative power sub-connector **304c**, and the ground sub-connector **304b** on the computing device connector **304** engage the positive power sub-connector **204a**, the negative power sub-connector **204c**, and the ground sub-connector **204b** on the pluggable terminal block connector **204**. However, as discussed

above, while the pluggable terminal block **300** and pluggable terminal block connector **204** are illustrated as including ground sub-connector **304b** and **204b**, respectively, embodiments in which the ground sub-connectors are omitted will fall within the scope of the present disclosure as well. As will be appreciated by one of skill in the art in possession of the present disclosure, following the connection of the pluggable terminal block **300** to the pluggable terminal block connector **204**, screws or other securing elements included in the securing members **306a** and **306b** (not visible in FIGS. **9A** and **9B**) may be tightened (or otherwise actuated) to secure the pluggable terminal block **300** to the computing device **200** and the pluggable terminal block connector **204**. However, while a specific example of connecting a pluggable terminal block **300** to a computing device/pluggable terminal block connector has been illustrated and described, one of skill in the art in possession of the present disclosure will appreciate how the pluggable terminal block **300** may be connected to computing devices/pluggable terminal block connectors in other manners while remaining within the scope of the present disclosure as well.

(48) The method **700** then proceeds to block **704** where power cabling is provided that includes a power cabling connector that prevents relative movement between a power cabling positive power contact on the power cabling connector and a power cabling negative power contact on the power cabling connector. With reference to FIGS. **6A** and **9C**, in an embodiment of block **704**, the power cabling **600** discussed above may be provided that includes the barrel-style power connector **606** that prevents relative movement between its power cabling negative power contact **606a** and its power cabling positive power contact **606b**. To provide specific example using the structure discussed above, the power cabling negative power contact **606a** on the barrel-style power connector **606** may be located on the outer surface of the barrel-style power connector **606**, and as discussed above that power cabling negative power contact **606a** is configured to contact the cantilevered spring that provides the negative power contact in the power system connector **308**. Similarly, the power cabling positive power contact **606b** on the barrel-style power connector **606** may be located on the inner surface of the barrel-style power connector **606**, and as discussed above that power cabling positive power contact **606b** is configured to contact the pin that provides the positive power contact in the power system connector **308**.

(49) As will be appreciated by one of skill in the art in possession of the present disclosure, the barrel-style power connector **606** prevents the power cabling negative power contact **606a** located on the outer surface of the barrel-style power connector **606** from moving relative to the power cabling positive power contact **606b** located on the inner surface of the barrel-style power connector **606**. However, while a specific example of a barrel-style power connector that prevents relative movement between its positive and negative power contacts has been described, one of skill in the art in possession of the present disclosure will appreciate how other power cabling connectors that prevent relative movement between their positive and negative power contacts (e.g., other fixed structure power connectors that would be apparent to one of skill in the art in possession of the present disclosure) may be utilized while remaining within the scope of the present disclosure as well.

(50) The method **700** then proceeds to block **706** where the power cabling is coupled to a power system. In an embodiment, at block **706**, the power cabling **600** discussed above with reference to FIG. **6A** is coupled to a power system directly, via a power adapter, and/or in a variety of other manners that would be apparent to one of skill in the art in possession of the present disclosure. For example, as discussed above, the power cabling **600** may include any of a variety of power system connectors (not illustrated in FIG. **6A**) on the opposite end of the power cable **602** from the connector base **604**, and any of those power system connectors may be configured to couple the power cabling **600** to a variety of different power systems.

(51) The method **700** then proceeds to block **708** where the power cabling connector is connected to the power system connector on the pluggable terminal block such that the power cabling connector positive power contact engages the pluggable terminal block positive power contact and

the power cabling connector negative power contact engages the pluggable terminal block negative power contact. With reference to FIGS. 9C and 9D, in an embodiment of block 708, the barrel-style power connector 606 included on the power cabling 600 is connected to the pluggable terminal block 300 that was connected to the computing device 200 at block 702. For example, the power cabling 600 may be placed adjacent the power system connector 308 included on the pluggable terminal block 300 such that the barrel-style power connector 606 and the connector securing element 608 on the power cabling 600 are aligned with the power system connector 308, as illustrated in FIG. 9C. Continuing with the specific example provided above, the connector base 604 is then moved in a direction B towards the power system connector 308 until the positive power contact on the barrel-style power connector 606 engages with the pin that provides the positive power contact on the power system connector 308, the negative power contact on the barrel-style power connector 606 engages the cantilever spring that provides the negative power contact on the power system connector 308, and the threaded securing subsystem 608a included on the connector base 604 engages with the threaded securing subsystem 308a included on the power system connector 308.

(52) With reference to FIGS. 9D and 9E, following the engagement of the barrel-style power connector 606 and the threaded securing subsystem 608a with the power system connector 308 as discussed above, the threaded securing subsystem 608a may be rotated in a direction C relative to the power system connector 308 to secure the power cabling 600 to the power system connector 308 on the pluggable terminal block 300. While not described in detail, one of skill in the art in possession of the present disclosure will appreciate how the barrel-style power connector 616 on the power cabling 610 described above with reference to FIG. 6B may couple to a female barrel-style power connector that replaces the power system connector 308 and extends into the chassis 302 of the pluggable terminal block 300 without securing the power cabling 610 to the pluggable terminal block 300 similarly as described above while remaining within the scope of the present disclosure as well. However, while a specific example of the use of a barrel-style power connector with the pluggable terminal block of the present disclosure has been described, as discussed above other types of fixed structure power cabling connectors may be utilized with the pluggable terminal block of the present disclosure while remaining within the scope of the present disclosure as well.

(53) As will be appreciated by one of skill in the art in possession of the present disclosure, fixed structure power system connectors (e.g., the barrel-style connectors discussed above, and/or other fixed structure power system connectors that may be utilized with the pluggable terminal block of the present disclosure) that include positive and negative power contacts that cannot move relative to each other prevent those positive and negative power contacts from coming into contact with each other as occurs with the exposed wire power cabling used with conventional pluggable terminal blocks, thus preventing short circuits and/or arcing during or subsequent to the coupling of the power system to the pluggable terminal block at blocks 706 and 708.

(54) Thus, systems and methods have been described that provide for a pluggable terminal block that includes a power system connector that is configured to couple to a power cabling connector that prevents relative movement between its power cabling connector positive and negative power contacts. For example, the pluggable terminal block short circuit prevention system of the present disclosure may include a pluggable terminal block having a computing device connector with a positive and negative power sub-connectors that connect to a pluggable terminal block connector on a computing device. A power system connector is included on the pluggable terminal block and includes a terminal block positive and negative power contacts that are coupled to the positive and negative power sub-connectors on the computing device connector, respectively. The power system connector couples to a power system via power cabling having a power cabling connector that includes power cabling positive and negative power contacts that are configured to engage the terminal block positive and negative power contacts when the power cabling connector is connected to the power system connector, with the power cabling connector preventing relative

movement between the power cabling connector positive and negative power contacts. As such, the power system connector on the pluggable terminal block of the present disclosure must be used with a power cabling connector that prevents relative movement between its power cabling connector positive and negative power contacts, which prevents short circuits and/or arcing when using the pluggable terminal block.

(55) Although illustrative embodiments have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiments may be employed without a corresponding use of other features. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the embodiments disclosed herein.

Claims

1. A pluggable terminal block short circuit prevention system, comprising: a pluggable terminal block chassis; a computing device connector that extends from the pluggable terminal block chassis, that includes a computing device positive power sub-connector, a computing device negative power sub-connector, and a computing device ground sub-connector, and that is configured to connect to a pluggable terminal block connector on a computing device; a ground coupling device that is included on the pluggable terminal block chassis, that is coupled to the computing device ground sub-connector, and that is configured to connect to a grounding wire to couple the computing device ground sub-connector to the grounding wire; and a power system connector that is included on the pluggable terminal block chassis and that includes a terminal block positive power contact that is coupled to the computing device positive power sub-connector, and a terminal block negative power contact that is coupled to the computing device negative power sub-connector, wherein the power system connector is configured to couple to a power system via power cabling having a power cabling connector that includes: a power cabling connector positive power contact that is configured to engage the terminal block positive power contact when the power cabling connector is connected to the power system connector; and a power cabling connector negative power contact that is configured to engage the terminal block negative power contact when the power cabling connector is connected to the power system connector, wherein the power cabling connector prevents relative movement between the power cabling connector positive power contact and the power cabling connector negative power contact.
2. The system of claim 1, wherein the power system connector and the power cabling connector are barrel-style power connectors.
3. The system of claim 2, wherein the barrel-style power connectors are configured to be secured together using corresponding threaded securing subsystems.
4. The system of claim 1, wherein the ground coupling device includes: a fastener channel defined by the pluggable terminal block chassis; a ground contact that is located in the fastener channel and that is coupled to the computing device ground sub-connector; and a fastener device that is configured to secure the grounding wire in the fastener channel in engagement with the ground contact.
5. The system of claim 1, wherein the fastener device is a screw.
6. The system of claim 1, wherein the pluggable terminal block chassis is a European-style terminal block chassis.
7. An Information Handling System (IHS), comprising: a chassis; a processing system that is housed in the chassis; a pluggable terminal block connector that is coupled to the processing system and accessible on the surface of the chassis; and a pluggable terminal block including: a computing device connector that includes a computing device positive power sub-connector, a computing device negative power sub-connector, and a computing device ground sub-connector, and that is connected to the pluggable terminal block connector; a ground coupling device that is

included on the pluggable terminal block chassis, that is coupled to the computing device ground sub-connector, and that is connected to a grounding wire to couple the computing device ground sub-connector to the grounding wire; and a power system connector that is included on the pluggable terminal block and that includes a terminal block positive power contact that is coupled to the computing device positive power sub-connector, and a terminal block negative power contact that is coupled to the computing device negative power sub-connector, wherein the power system connector is coupled to a power system via power cabling having a power cabling connector that includes: a power cabling connector positive power contact that engages the terminal block positive power contact; and a power cabling connector negative power contact that engages the terminal block negative power contact, wherein the power cabling connector prevents relative movement between the power cabling connector positive power contact and the power cabling connector negative power contact.

8. The IHS of claim 7, wherein the power system connector and the power cabling connector are barrel-style power connectors.

9. The IHS of claim 8, wherein the barrel-style power connectors are secured together using corresponding threaded securing subsystems.

10. The IHS of claim 7, wherein the ground coupling device includes: a fastener channel defined by the pluggable terminal block chassis; a ground contact that is located in the fastener channel and that is coupled to the computing device ground sub-connector; and a fastener device that is configured to secure the grounding wire in the fastener channel in engagement with the ground contact.

11. The IHS of claim 7, wherein the fastener device is a screw.

12. The IHS of claim 7, wherein the pluggable terminal block is a European-style terminal block.

13. The IHS of claim 7, wherein the power system connector is provided by a female barrel-style power connector that extends into the pluggable terminal block and that is not configured to secure the power cabling connector to the pluggable terminal block.

14. A method for preventing short circuits with a pluggable terminal block, comprising: connecting, by a computing device positive power sub-connector and a computing device negative power sub-connector included in a computing device connector on a pluggable terminal block, to a pluggable terminal block connector on a computing device; connecting, by a ground coupling device that is included on the pluggable terminal block and that is coupled to a computing device ground sub-connector, to a grounding wire to couple the computing device ground sub-connector to the grounding wire; and coupling, by a power system connector that is included on the pluggable terminal block and that includes a terminal block positive power contact that is coupled to the computing device positive power sub-connector and a terminal block negative power contact that is coupled to the computing device negative power sub-connector, to a power system via power cabling having a power cabling connector by: engaging, by the terminal block positive power contact when the power cabling connector is connected to the power system connector, with a power cabling connector positive power contact on the power cabling connector; and engaging, by the terminal block negative power contact when the power cabling connector is connected to the power system connector, with a power cabling connector negative power contact on the power cabling connector, wherein the power cabling connector prevents relative movement between the power cabling connector positive power contact and the power cabling connector negative power contact when the power cabling connector is connected to the power system connector.

15. The method of claim 14, wherein the power system connector and the power cabling connector are barrel-style power connectors.

16. The method of claim 15, wherein the barrel-style power connectors are secured together using corresponding threaded securing subsystems.

17. The method of claim 14, wherein the ground coupling device includes: a fastener channel defined by the pluggable terminal block; a ground contact that is located in the fastener channel and

that is coupled to the computing device ground sub-connector; and a fastener device that secures the grounding wire in the fastener channel in engagement with the ground contact.

18. The method of claim 14, wherein the fastener device is a screw.

19. The method of claim 14, wherein the pluggable terminal block is a European-style terminal block.

20. The method of claim 14, wherein the power system connector is provided by a female barrel-style power connector that extends into the pluggable terminal block and that is not configured to secure the power cabling connector to the pluggable terminal block.
