

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408283
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tan; Min et al.

Cover plate and display screen

Abstract

The present application discloses a cover plate and a display screen, the cover plate includes a cover plate body, an ink portion, and a barrier portion. The cover plate body includes a display region and a frame region. The frame region surrounds the display region, and an infrared sensing hole sub-region is disposed on the frame region. The ink portion is disposed on a surface of the cover plate body and is located in the frame region. The ink portion includes a white ink layer covering infrared sensing hole sub-region. The barrier portion is disposed in the frame region and is located on a side of the infrared sensing hole sub-region away from display region.

Inventors:	Tan; Min (Wuhan, CN), Zhang; Dongdong (Wuhan, CN), Pan; Kun (Wuhan, CN), Jing; Chuanhe (Wuhan, CN)
Applicant:	WUHAN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD. (Wuhan, CN)
Family ID:	93564575
Assignee:	WUHAN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD. (Wuhan, CN)
Appl. No.:	18/267658
Filed (or PCT Filed):	May 31, 2023
PCT No.:	PCT/CN2023/097588
PCT Pub. No.:	WO2024/239365
PCT Pub. Date:	November 28, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240397651 A1	Nov. 28, 2024

Foreign Application Priority Data

CN202310587204.9May. 23, 2023

Publication Classification

Int. Cl.: H05K5/03 (20060101); G06F1/16 (20060101); H10F30/10 (20250101)

U.S. Cl.:

CPC H05K5/03 (20130101); G06F1/1601 (20130101); H10F30/10 (20250101); G06F1/1603 (20130101); G06F1/1632 (20130101); G06F1/1637 (20130101)

Field of Classification Search

CPC: G06F (1/1601); G06F (1/1603); G06F (1/1632); G06F (1/1637); H05K (5/03); H10F (30/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9832868	12/2016	Wright	N/A	G06F 3/041
11493382	12/2021	Almanza-Workman et al.	N/A	N/A
2016/0054175	12/2015	Jia et al.	N/A	N/A
2017/0184764	12/2016	Matsuyuki	N/A	G02B 5/208
2017/0364172	12/2016	Kim	N/A	G06F 1/1686
2023/0071744	12/2022	Wang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102967362	12/2012	CN	N/A
103927051	12/2013	CN	N/A
111833721	12/2019	CN	N/A
111965871	12/2019	CN	N/A
112349866	12/2020	CN	N/A
113140688	12/2020	CN	N/A
116133459	12/2022	CN	N/A
2002268040	12/2001	JP	N/A
20130105110	12/2012	KR	N/A
20190072134	12/2018	KR	N/A
20200063188	12/2019	KR	N/A

OTHER PUBLICATIONS

Korean Office Action issued in corresponding Korean Patent Application No. 10-2023-7041031 dated Oct. 31, 2024, pp. 1-11, 25pp. cited by applicant

PCT International Search Report for International application No. PCT/CN2023/097588, mailed on Jan. 29, 2024, 11pp. cited by applicant

Primary Examiner: Gaworecki; Mark R

Attorney, Agent or Firm: The Roy Gross Law Firm, LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Phase of PCT Patent Application No. PCT/CN2023/097588 having International filing date of May 31, 2023, which claims the benefit of priority of Chinese Patent Application No. 202310587204.9, filed May 23, 2023, the contents of which are all incorporated herein by reference in their entirety.

FIELD OF INVENTION

(2) The present application relates to a field of display technologies, especially to a cover plate and a display screen.

BACKGROUND OF INVENTION

(3) In recent years, with the increasing demand for eye protection and energy-saving by consumers, in order to meet this demand, traditional technical solutions adjust the brightness of the apparatus screen by measuring the distance between the user's apparatus and their facial features, as well as the ambient light brightness, using an infrared sensor. This is done to achieve the goal of eye protection and energy-saving.

(4) The display screen of a traditional user apparatus has an infrared sensing hole, which is gradually located near an edge of a cover plate. The infrared sensing hole is coated with white ink, which shields visible light but allows infrared light to pass through. Due to the fluidity of ink, there may be certain tolerances in the printing process that cause white ink to overflow onto the edge of the display panel cover plate, changing the path of light reflection and refraction, resulting in a glowing phenomenon near the position of the infrared sensing hole corresponding to the edge of the cover plate.

SUMMARY OF INVENTION

Technical Issue

(5) An embodiment of the present application provides a cover plate and a display screen that can solve an issue of a glowing edge of a cover plate.

Technical Solution

(6) In one aspect, the embodiment of the present application provides a cover plate, comprising: a cover plate body comprising a display region and a frame region surrounding the display region, wherein an infrared sensing hole sub-region is disposed in the frame region; an ink portion disposed on a surface of the cover plate body, located in the frame region, and comprising a white ink layer covering the infrared sensing hole sub-region; and a barrier portion disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region; wherein a boundary of the white ink layer away from the display region does not extend beyond a boundary of the barrier portion away from display region.

(7) Optionally, in some embodiments of the present application, the ink portion further comprises a first black ink layer and a translucent black ink layer, and the first black ink layer is disposed in the frame region and surrounds the infrared sensing hole sub-region; and the translucent black ink layer is disposed in the frame region and covers the infrared sensing hole sub-region, and the white ink layer covers the translucent black ink layer.

- (8) Optionally, in some embodiments of the present application, the barrier portion comprises a barrier recess disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region.
- (9) Optionally, in some embodiments of the present application, the infrared sensing hole sub-region and the barrier recess are arranged along a first direction, a cross-sectional width of the barrier recess along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
- (10) Optionally, in some embodiments of the present application, a depth of the barrier recess is greater than or equal to a thickness of the ink portion.
- (11) Optionally, in some embodiments of the present application, the barrier portion comprises a barrier column disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region.
- (12) Optionally, in some embodiments of the present application, the infrared sensing hole sub-region and the barrier column are arranged along a first direction, a cross-sectional width of the barrier column along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
- (13) Optionally, in some embodiments of the present application, a height of the barrier column is greater than or equal to a thickness of the ink portion.
- (14) Optionally, in some embodiments of the present application, the barrier portion comprises a barrier recess and a barrier column, and the barrier column is disposed adjacent to the barrier recess.
- (15) Optionally, in some embodiments of the present application, the infrared sensing hole sub-region, the barrier recess, and the barrier column are arranged along a first direction, a cross-sectional width of at least one of the barrier recess and the barrier column along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
- (16) Optionally, in some embodiments of the present application, a depth of the barrier recess is greater than or equal to a thickness of the ink portion; or a height of the barrier column is greater than or equal to a thickness of the ink portion.
- (17) Optionally, in some embodiments of the present application, the barrier portion comprises at least two barrier recesses, and/or, the barrier portion comprises at least two barrier columns.
- (18) Optionally, in some embodiments of the present application, cross-sectional widths of the at least two barrier recesses along the second direction are unequal; and/or cross-sectional widths of at least two of the barrier columns along the second direction are unequal.
- (19) Optionally, in some embodiments of the present application, heights of the at least two barrier recesses along a thickness direction of the cover plate body are unequal; and/or heights of at least two of the barrier columns along the cover plate body thickness direction are unequal.
- (20) Optionally, in some embodiments of the present application, the ink portion further comprises a second black ink layer disposed on a side of the first black ink layer away from the cover plate body; a first through hole is defined in the first black ink layer corresponding to the infrared sensing hole sub-region; a second through hole is defined in the second black ink layer corresponding to the infrared sensing hole sub-region, the translucent black ink layer covers surfaces of the first through hole and the second through hole and partially covers the second black ink layer; and a cross-sectional width of the first through hole along a first direction is greater than or equal to a cross-sectional width of the second through hole along the first direction.
- (21) In another aspect, the embodiment of the present application also provides a display screen comprising a cover plate and a display panel, wherein the cover plate is bonded to a light exiting surface of the display panel and comprises: a cover plate body comprising a display region and a frame region, the frame region surrounds the display region, and an infrared sensing hole sub-region is defined in the frame region; an ink portion disposed on a surface of the cover plate body,

located in the frame region, and comprising a white ink layer covering the infrared sensing hole sub-region; and a barrier portion disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region; wherein a boundary of the white ink layer away from the display region does not extend beyond a boundary of the barrier portion away from display region.

(22) Optionally, in some embodiments of the present application, the ink portion further comprises a first black ink layer and a translucent black ink layer, and the first black ink layer is disposed in the frame region and surrounds the infrared sensing hole sub-region; and the translucent black ink layer is disposed in the frame region and covers the infrared sensing hole sub-region, and the white ink layer covers the translucent black ink layer.

(23) Optionally, in some embodiments of the present application, the barrier portion comprises a barrier recess or a barrier column, and the barrier portion is disposed in the frame region and is located on a side of the infrared sensing hole sub-region away from the display region.

(24) Optionally, in some embodiments of the present application, the infrared sensing hole sub-region and the barrier portion are arranged along a first direction, a cross-sectional width of the barrier portion along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.

Advantages

(25) An embodiment of the present application provides a cover plate and a display screen, the cover plate comprises: a cover plate body, an ink portion and a barrier portion. The cover plate body comprises a display region and a frame region. The frame region is disposed to surround the display region, and an infrared sensing hole sub-region is defined in the frame region. The ink portion is disposed in the frame region and comprises a white ink layer covering the infrared sensing hole sub-region. The barrier portion is disposed in the frame region and is located on a side of the infrared sensing hole sub-region away from the display region. By such configuration, disposing the barrier portion between edges of the ink portion and the cover plate prevents the white ink on an edge of the infrared sensing hole from overflowing to the edge of the cover plate, which can solve an issue of the glowing edge of the cover plate to improve a display effect.

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a top view of a cover plate provided by the embodiment of the present application.
- (2) FIG. 2a is a first cross-sectional view of the cover plate in FIG. 1 along an AA' line.
- (3) FIG. 2b is a first top view of the cover plate in FIG. 1 along the AA' line.
- (4) FIG. 3 is a second cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (5) FIG. 4 is a third cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (6) FIG. 5 is a fourth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (7) FIG. 6 is a fifth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (8) FIG. 7 is a sixth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (9) FIG. 8 is a seventh cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (10) FIG. 9 is an eighth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (11) FIG. 10 is a ninth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (12) FIG. 11 is a tenth cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (13) FIG. 12 is an eleventh cross-sectional view of the cover plate in FIG. 1 along the AA' line.
- (14) FIG. 13 is a twelfth cross-sectional view of the cover plate in FIG. 1 along the AA' line.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(15) The following will describe the technical solution in the embodiment of the present application, in conjunction with the attached drawings in the embodiment of the present

application. The described embodiment is only used to explain and illustrate the idea of the present application and should not be construed as limiting the protection range of the present application.

(16) An embodiment of the present application provides a display screen, comprising a cover plate and a display panel. The cover plate is bonded to a light exiting surface of the display panel. The display panel comprises an infrared sensor.

(17) With reference to FIGS. **1** to **2b**, FIG. **1** is a top view of a cover plate provided by the embodiment of the present application; FIG. **2a** is a first cross-sectional view of the cover plate in FIG. **1** along an AA' line; and FIG. **2b** is a first top view of the cover plate in FIG. **1** along the AA' line. With reference to FIG. **1** and FIG. **2a**, the embodiment of the present application provides a cover plate **100** comprising: a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA is disposed to surround the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region NA. An infrared sensor is disposed in the infrared sensing hole sub-region IR. The ink portion **20** is disposed on a surface of the cover plate body **10** away from a light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**, the white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed on the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA. A boundary of the white ink layer **21** away from the display region AA does not extend beyond a boundary of the barrier portion **30** away from the display region AA.

(18) In the embodiment of the present application, disposing the barrier portion **30** between edges of the ink portion **20** and cover plate prevents the white ink on an edge of the infrared sensing hole from overflowing an edge of a cover plate, which can avoid change of refractive and reflection paths of light to further avoid glowing of the edge of the cover plate.

(19) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22** and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. In particular, ink portion is disposed on a surface of the cover plate body **10** away from the light emitting side.

(20) In particular, the translucent black ink layer **23** is configured to shield the bottom portion structure and visible light. The white ink layer **21** is configured to make light passing through the infrared sensing hole sub-region IR become even white light. The first black ink layer **22**, the translucent black ink layer **23** and the white ink layer **21** all comprise resin, hardener, auxiliary, and solvent. The resin is an ink main body structure, hardener is configured to ensure crosslinking degree and printing performance of the resin. The auxiliary and solvent are configured to ensure printing performance of the ink. The first black ink layer **22**, the translucent black ink layer **23**, and the white ink layer **21** all further comprise pigments. The pigment is configured to adjust a color of the ink. A pigment of the first black ink layer **22** is black, a pigment of the translucent black ink layer **23** is gray, and a pigment of the white ink layer **21** is white.

(21) In the embodiment of the present application, a first ink region **201**, a the first through hole **221** and a second ink region **202** are arranged along a first direction X. A cross-sectional width of the barrier portion **30** along a second direction Y is greater than a cross-sectional width of the ink portion **20** along the second direction Y. The first direction X is perpendicular to the second direction Y. Preferably, a cross-sectional width of the barrier portion **30** along the second direction Y is greater than the white ink layer **21** along a cross-sectional width of the second direction Y. The first direction X means a length direction of the display panel, and the second direction Y means a width direction of the display panel.

(22) Furthermore, a height of the barrier portion **30** along a thickness direction of the cover plate body **10** is greater than or equal to the thickness of the ink portion **20**. Preferably, with reference to

FIG. 2a, a height H1 of the barrier portion 30 along the thickness direction of the cover plate body 10 is greater than a thickness of the ink portion 20 H2. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(23) In the embodiment of the present application, the ink portion 20 further comprises a second black ink layer 24. The second black ink layer 24 is disposed on a side of the first black ink layer 22 away from the cover plate body 10. A first through hole 221 is defined in the first black ink layer 22 corresponding to the infrared sensing hole sub-region IR. A second through hole 241 is defined in the second black ink layer 24 corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer 23 covers surfaces of the first through hole 221 and the second through hole 241 and partially covers the second black ink layer 24. In particular, the translucent black ink layer 23 covers bottom surfaces of the first through hole 221 and the second through hole 241, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer 24. A cross-sectional width of the first through hole 221 along the first direction X is greater than or equal to a cross-sectional width of the second through hole 241 along the first direction X.

(24) In particular, material of the first black ink layer 22 and the second black ink layer 24 comprises black ink or dark ink. The first black ink layer 22 and the second black ink layer 24 can be a single layer structure or a multi-layer structure. Namely, the first black ink layer 22 can only comprise one film layer, and can comprise at least two stacked film layers. Correspondingly, the second black ink layer 24 can only comprise one film layer, and can comprise at least two stacked film layers. The first through hole 221 and the second through hole 241 are infrared sensing holes. The translucent black ink layer 23 and the white ink layer 21 cover a surface of the infrared sensing hole, are configured to shield visible light and allow infrared to pass. Material of the second black ink layer 24 is the same as material of the first black ink layer 22.

(25) In the embodiment of the present application, the barrier portion 30 comprises a barrier recess 31, the barrier recess 31 is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA. With reference to FIG. 2b, a cross-sectional width W1 of the barrier recess 31 along the second direction Y is greater than the cross-sectional width W2 of white ink layer 21 along the second direction Y. With reference to FIG. 2a, a depth of the barrier recess 31 along the thickness direction of the cover plate body 10 is greater than the thickness of the ink portion 20. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate. FIG. 2b, for example, only illustrates a size relationship of the cross-sectional width W1 of the barrier recess 31 along the second direction Y and the cross-sectional width W2 of white ink layer 21 along the second direction Y and would not limit a formation of the barrier recess 31 along the thickness direction of the display panel.

(26) As a specific embodiment of the present application, with reference to FIG. 3, FIG. 3 is a second cross-sectional view of the cover plate in FIG. 1 along the AA' line. With reference to FIG. 3, the embodiment of the present application provides a cover plate 200, and a difference of the cover plate 200 from the cover plate 100 is that: the barrier portion 30 comprises a barrier column 32, and the barrier column 32 is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(27) In the embodiment of the present application, the barrier column 32 is disposed on the surface of the cover plate body 10 away from the light emitting side, and a cross-sectional shape of the barrier column 32 along a thickness direction of the cover plate body 10 can be a trapezoidal

structure such as isosceles trapezoid, and right angle trapezoid. A shape of the barrier column **32** comprises but is not limited to rectangular prism, cylinder, conical frustum, and hemisphere.

(28) In the embodiment of the present application, a silkscreen printing process is used to form the first black ink layer **22**, the second ink layer **24**, the translucent black ink layer **23**, and the white ink layer **21** on the cover plate body **10**. Also, the barrier column **32** is formed on a side of the infrared sensing hole sub-region IR away from the display region AA by multi-printing the first black ink layer **22** or the second black ink layer **24**. Namely, material of the barrier column **32** is the same as material of the first black ink layer **22** or the second black ink layer **24**.

(29) The cover plate **200** further comprises a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA surrounds the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region. The ink portion **20** is disposed on a surface of the cover plate body **10** away from the light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**. The white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(30) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22** and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. The second black ink layer **24** is disposed on a side of the first black ink layer **22** away from the cover plate body **10**. A first through hole **221** is defined in the first black ink layer **22** corresponding to the infrared sensing hole sub-region IR. A second through hole **241** is defined in the second black ink layer **24** corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer **23** covers surfaces of the first through hole **221** and the second through hole **241** and partially covers the second black ink layer **24**. In particular, the translucent black ink layer **23** covers bottom surfaces of the first through hole **221** and the second through hole **241**, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer **24**. A cross-sectional width of the first through hole **221** along the first direction X is greater than or equal to a cross-sectional width of the second through hole **241** along the first direction X.

(31) In the embodiment of the present application, the infrared sensing hole sub-region IR and the barrier column **32** are arranged along the first direction X. A cross-sectional width of the barrier column **32** along the second direction Y is greater than a cross-sectional width of the white ink layer **21** along the second direction Y. The first direction X is perpendicular to the second direction Y. Furthermore, a height of the barrier column **32** along a thickness direction of the cover plate body **10** is greater than or equal to a thickness of the ink portion **20**. Preferably, the height of the barrier column **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(32) As a specific embodiment of the present application, with reference to FIG. 4, FIG. 4 is a third cross-sectional view of the cover plate in FIG. 1 along the AA' line. With reference to FIG. 4, the embodiment of the present application provides a cover plate **300**, and a difference of the cover plate **300** from the cover plate **100** is that: the barrier portion **30** comprises a barrier recess **31** and a barrier column **32**, and the barrier recess **31** and the barrier column **32** are disposed adjacently.

(33) In particular, the barrier recess **31** and the barrier column **32** can be disposed adjacently or be disposed at intervals. In FIG. 4, the barrier recess **31** and the barrier column **32** are disposed

adjacent, and the barrier column **32** disposed on a side of the barrier recess **31** away from the second ink region **202** is taken as an example, in actual applications, the barrier recess **31** can also be on a side of the barrier column **32** away from the second ink region **202**.

(34) The cover plate **300** further comprises a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA surrounds the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region. The ink portion **20** is disposed on a surface of the cover plate body **10** away from the light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**. The white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(35) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22** and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. The second black ink layer **24** is disposed on a side of the first black ink layer **22** away from the cover plate body **10**. A first through hole **221** is defined in the first black ink layer **22** corresponding to the infrared sensing hole sub-region IR. A second through hole **241** is defined in the second black ink layer **24** corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer **23** covers surfaces of the first through hole **221** and the second through hole **241** and partially covers the second black ink layer **24**. In particular, the translucent black ink layer **23** covers bottom surfaces of the first through hole **221** and the second through hole **241**, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer **24**. A cross-sectional width of the first through hole **221** along the first direction X is greater than or equal to a cross-sectional width of the second through hole **241** along the first direction X.

(36) In the embodiment of the present application, the infrared sensing hole sub-region IR, the barrier recess **31** and the barrier column **32** are arranged along the first direction X. A cross-sectional width of at least one of the barrier recess **31** and the barrier column **32** along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y. Alternatively, a sum of cross-sectional widths of the barrier recess **31** and the barrier column **32**, staggered along the first direction X, along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y. Furthermore, a height of at least one of the barrier recess **31** and the barrier column **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**. Alternatively, a sum of heights of the barrier recess **31** and the barrier column **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**. Preferably, the height of the barrier column **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(37) As a specific embodiment of the present application, with reference to FIGS. 5 to 7, FIG. 5 is a fourth cross-sectional view of the cover plate in FIG. 1 along the AA' line; FIG. 6 is a fifth cross-sectional view of the cover plate in FIG. 1 along the AA' line; and FIG. 7 is a sixth cross-sectional view of the cover plate in FIG. 1 along the AA' line. With reference to FIG. 5, the embodiment of the present application provides a cover plate **400**, and a difference of the cover plate **400** from the cover plate **100** is that: the barrier portion **30** comprises at least two barrier recesses **31**, the at least two barrier recesses **31** are disposed at intervals in the frame region NA and are located on a side of the infrared sensing hole sub-region IR away from the display region AA. The barrier portion **30** in

FIG. 5 comprises two barrier recesses **31**.

(38) In the embodiment of the present application, the cover plate **400** further comprises a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA surrounds the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region. The ink portion **20** is disposed on a surface of the cover plate body **10** away from the light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**. The white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(39) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22** and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. The second black ink layer **24** is disposed on a side of the first black ink layer **22** away from the cover plate body **10**. A first through hole **221** is defined in the first black ink layer **22** corresponding to the infrared sensing hole sub-region IR. A second through hole **241** is defined in the second black ink layer **24** corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer **23** covers surfaces of the first through hole **221** and the second through hole **241** and partially covers the second black ink layer **24**. In particular, the translucent black ink layer **23** covers bottom surfaces of the first through hole **221** and the second through hole **241**, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer **24**. A cross-sectional width of the first through hole **221** along the first direction X is greater than or equal to a cross-sectional width of the second through hole **241** along the first direction X.

(40) In the embodiment of the present application, the infrared sensing hole sub-region IR and two barrier recesses **31** are arranged along the first direction X, Preferably, with reference to FIG. 5, cross-sectional widths of two barrier recesses **31** along the second direction Y are equal, and depths of two barrier recesses **31** along the thickness direction of the cover plate body **10** are equal. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(41) Furthermore, with reference to FIG. 6, the cross-sectional widths of the at least two barrier recesses **31** along the second direction Y are unequal. In particular, FIG. 6 takes two barrier recesses **31** for example, the cross-sectional width of at least one of the two barrier recesses **31** along the second direction Y is greater than a cross-sectional width of white ink layer **21** along the second direction Y. Alternatively, a sum of the cross-sectional widths of two barrier recesses **31** staggered along the first direction X along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y. In FIG. 6, a cross-sectional width W1 of the barrier recess **31** away from the second ink region **202** along the second direction Y is greater than the cross-sectional width W2 of the barrier recess **31** near the second ink region **202** along the second direction Y, the cross-sectional width W2 of the barrier recess **31** near the second ink region **202** along the second direction Y is greater than a cross-sectional width W3 of the white ink layer **21** along the second direction Y. FIG. 6, for example, only illustrates a size relationship of the cross-sectional width W1 of the barrier recess **31** along the second direction Y and the cross-sectional width W2 of the white ink layer **21** along the second direction Y and would not limit a formation of the barrier recess **31** along the thickness direction of the display panel.

(42) Furthermore, with reference to FIG. 7, depths of the at least two barrier recesses **31** along the thickness direction of the cover plate body **10** are unequal. In particular, FIG. 7 takes two barrier

recesses **31** for example, a depth of at least one of the two barrier recesses **31** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**.

Alternatively, a sum of the depths of the two barrier recesses **31** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**.

(43) As a specific embodiment of the present application, with reference to FIGS. **8** to **10**, FIG. **8** is a seventh cross-sectional view of the cover plate in FIG. **1** along the AA' line; FIG. **9** is an eighth cross-sectional view of the cover plate in FIG. **1** along the AA' line; and FIG. **10** is a ninth cross-sectional view of the cover plate in FIG. **1** along the AA' line. With reference to FIG. **8**, the embodiment of the present application provides a cover plate **500**, and a difference of the cover plate **500** from the cover plate **100** is that: the barrier portion **30** comprises at least two barrier columns **32**. The at least two barrier columns **32** are disposed at intervals in the frame region NA and are located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(44) In the embodiment of the present application, the cover plate **500** further comprises a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA surrounds the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region. The ink portion **20** is disposed on a surface of the cover plate body **10** away from the light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**. The white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(45) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22** and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. The second black ink layer **24** is disposed on a side of the first black ink layer **22** away from the cover plate body **10**. A first through hole **221** is defined in the first black ink layer **22** corresponding to the infrared sensing hole sub-region IR. A second through hole **241** is defined in the second black ink layer **24** corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer **23** covers surfaces of the first through hole **221** and the second through hole **241** and partially covers the second black ink layer **24**. In particular, the translucent black ink layer **23** covers bottom surfaces of the first through hole **221** and the second through hole **241**, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer **24**. A cross-sectional width of the first through hole **221** along the first direction X is greater than or equal to a cross-sectional width of the second through hole **241** along the first direction X.

(46) In the embodiment of the present application, the infrared sensing hole sub-region IR and two barrier columns **32** are arranged along the first direction X. Preferably, with reference to FIG. **8**, cross-sectional widths of two barrier columns **32** along the second direction Y are equal, and heights of two barrier columns **32** along the thickness direction of the cover plate body **10** are equal. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(47) Furthermore, with reference to FIG. **9**, cross-sectional widths of at least two barrier columns **32** along the second direction Y are unequal. In particular, FIG. **9** takes two barrier columns **32** as an example, a cross-sectional width of at least one of the two barrier columns **32** along the second direction Y is greater than a cross-sectional width of white ink layer **21** along the second direction Y. Alternatively, a sum of cross-sectional widths of the two barrier columns **32**, staggered along the

first direction X, along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y. In FIG. **9**, the cross-sectional width **W1** of the barrier column **32** away from the second ink region **202** along the second direction Y is greater than the cross-sectional width **W2** of the barrier column **32** near the second ink region **202** along the second direction Y, and the cross-sectional width **W2** of the barrier column **32** near the second ink region **202** along the second direction Y is greater than the cross-sectional width **W3** of white ink layer **21** along the second direction Y. FIG. **9**, for example, only illustrates a size relationship of the cross-sectional width **W1** of the barrier recess **31** along the second direction Y and the cross-sectional width **W2** of white ink layer **21** along the second direction Y and would not limit a formation of the barrier recess **31** along the thickness direction of the display panel.

(48) Furthermore, with reference to FIG. **10**, heights of at least two barrier columns **32** along the thickness direction of the cover plate body **10** are unequal. In particular, FIG. **10** takes two barrier columns **32** for example, a depth of at least one of the two barrier columns **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**.

Alternatively, a sum of heights of the two barrier columns **32** along the thickness direction of the cover plate body **10** is greater than the thickness of the ink portion **20**.

(49) As a specific embodiment of the present application, with reference to FIG. **11** to FIG. **13**, FIG. **11** is a tenth cross-sectional view of the cover plate in FIG. **1** along the AA' line; FIG. **12** is an eleventh cross-sectional view of the cover plate in FIG. **1** along the AA' line; and FIG. **13** is a twelfth cross-sectional view of the cover plate in FIG. **1** along the AA' line. With reference to FIG. **11**, the embodiment of the present application provides a cover plate **600**, and a difference of the cover plate **600** from the cover plate **400** is in that: the barrier portion **30** comprises the at least two barrier recesses **31** and at least two barrier columns **32**, and the at least two barrier recesses **31** and at least two barrier columns **32** are disposed at intervals in the frame region NA and are located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(50) In the embodiment of the present application, the cover plate **500** further comprises: a cover plate body **10**, an ink portion **20** and a barrier portion **30**. The cover plate body **10** comprises a display region AA and a frame region NA. The frame region NA surrounds the display region AA, and an infrared sensing hole sub-region IR is disposed in the frame region. The ink portion **20** is disposed on the surface of the cover plate body **10** away from the light emitting side and is located in the frame region NA. The ink portion **20** comprises a white ink layer **21**, and the white ink layer **21** covers the infrared sensing hole sub-region IR. The barrier portion **30** is disposed in the frame region NA and is located on a side of the infrared sensing hole sub-region IR away from the display region AA.

(51) In the embodiment of the present application, the ink portion **20** further comprises a first black ink layer **22**, a second black ink layer **24**, and a translucent black ink layer **23**. The first black ink layer **22** is disposed in the frame region NA and surrounds the infrared sensing hole sub-region IR. The translucent black ink layer **23** is disposed in the frame region NA and covers the infrared sensing hole sub-region IR. The white ink layer **21** covers the translucent black ink layer **23**. The second black ink layer **24** is disposed on a side of the first black ink layer **22** away from the cover plate body **10**. A first through hole **221** is defined in the first black ink layer **22** corresponding to the infrared sensing hole sub-region IR. A second through hole **241** is defined in the second black ink layer **24** corresponding to the infrared sensing hole sub-region IR. The translucent black ink layer **23** covers surfaces of the first through hole **221** and the second through hole **241** and partially covers the second black ink layer **24**. In particular, the translucent black ink layer **23** covers bottom surfaces of the first through hole **221** and the second through hole **241**, are disposed along two sidewalls of the first direction X, and extends from the sidewalls to partially cover the second black ink layer **24**. A cross-sectional width of the first through hole **221** along the first direction X is greater than or equal to a cross-sectional width of the second through hole **241** along the first direction X.

(52) In the embodiment of the present application, the infrared sensing hole sub-region IR, two barrier recesses **31** and two barrier columns **32** along the first direction X. Preferably, with reference to FIG. **11**, cross-sectional widths of the two barrier recesses **31** and the two barrier columns **32** along the second direction Y are equal, and heights of the two barrier recesses **31** and the two barrier columns **32** along the thickness direction of the cover plate body **10** are equal. Such configuration advantages blocking the excessive white ink in the edge of the cover plate during silkscreen printing to prevent the white ink from overflowing to the edge of the cover plate, leading to change of refractive and reflection paths of light, and resulting in reflective light of the white ink more than that of a normal product to cause glowing of the edge of the cover plate.

(53) Furthermore, with reference to FIG. **12**, the cross-sectionals width of the at least two barrier recesses **31** along the second direction Y are unequal, and cross-sectional widths of at least two barrier columns **32** along the second direction Y are unequal. In particular, FIG. **12** takes two barrier recesses **31** and two barrier columns **32** for example, the cross-sectional width of at least one of the two barrier recesses **31** and two barrier columns **32** along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y. In FIG. **12**, the cross-sectional width W1 of the barrier column **32** away from the second ink region **202** along the second direction Y is greater than a cross-sectional width W2 of the barrier column **32** near the second ink region **202** along the second direction Y, a cross-sectional width W3 of the barrier recess **31** away from the second ink region **202** along the second direction Y is greater than a cross-sectional width W4 of the barrier recess **31** near the second ink region **202** along the second direction Y, and a cross-sectional width W4 of the barrier recess **31** near the second ink region **202** along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y W5. FIG. **12**, for example, only illustrates a size relationship of the cross-sectional width W1 of the barrier recess **31** along the second direction Y and the cross-sectional width W2 of white ink layer **21** along the second direction Y and would not limit a formation of the barrier recess **31** along the thickness direction of the display panel.

(54) In particular, it also can be that a sum of cross-sectional widths of two barrier recesses **31**, staggered along the first direction X, and two barrier columns **32**, staggered along the first direction X, along the second direction Y is greater than the cross-sectional width of white ink layer **21** along the second direction Y.

(55) Furthermore, with reference to FIG. **13**, depths of the at least two barrier recesses **31** along the thickness direction of the cover plate body **10** are unequal, and heights of at least two barrier columns **32** along the thickness direction of the cover plate body **10** are unequal. In particular, FIG. **13** takes two barrier recesses **31** and two barrier columns **32** for example, a height of at least one of the two barrier recesses **31** and the two barrier columns **32** along the thickness direction of the cover plate body **10** is greater than a height of the ink portion **20** along the thickness direction of the cover plate body **10**. FIG. **13** takes gradually increasing heights of the two barrier recesses **31** and the two barrier columns **32** along the thickness direction of the cover plate body **10** for example. In particular, it can also be that a sum of heights of the two barrier recesses **31** and the two barrier columns **32** along the thickness direction of the cover plate body **10** is greater than a height of the ink portion **20** along the thickness direction of the cover plate body **10**.

(56) The cover plate and the display screen provided by the embodiment of the present application are described in detail as above. In the specification, the specific examples are used to explain the principle and embodiment of the present application. The above description of the embodiments is only used to help understand the method of the present application and its spiritual idea.

Meanwhile, for those skilled in the art, according to the present idea of invention, changes will be made in specific embodiment and application. In summary, the contents of this specification should not be construed as limiting the present application.

Claims

1. A cover plate, comprising: a cover plate body comprising a display region and a frame region surrounding the display region, wherein an infrared sensing hole sub-region is disposed in the frame region; an ink portion disposed on a surface of the cover plate body, located in the frame region, and comprising a white ink layer covering the infrared sensing hole sub-region; and a barrier portion disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region; wherein a boundary of the white ink layer away from the display region does not extend beyond a boundary of the barrier portion away from display region.
2. The cover plate according to claim 1, wherein the ink portion further comprises a first black ink layer and a translucent black ink layer, and the first black ink layer is disposed in the frame region and surrounds the infrared sensing hole sub-region; and the translucent black ink layer is disposed in the frame region and covers the infrared sensing hole sub-region, and the white ink layer covers the translucent black ink layer.
3. The cover plate according to claim 2, wherein the ink portion further comprises a second black ink layer disposed on a side of the first black ink layer away from the cover plate body; a first through hole is defined in the first black ink layer corresponding to the infrared sensing hole sub-region; a second through hole is defined in the second black ink layer corresponding to the infrared sensing hole sub-region, the translucent black ink layer covers surfaces of the first through hole and the second through hole and partially covers the second black ink layer; and a cross-sectional width of the first through hole along a first direction is greater than or equal to a cross-sectional width of the second through hole along the first direction.
4. The cover plate according to claim 1, wherein the barrier portion comprises a barrier recess disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region.
5. The cover plate according to claim 4, wherein the infrared sensing hole sub-region and the barrier recess are arranged along a first direction, a cross-sectional width of the barrier recess along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
6. The cover plate according to claim 5, wherein a depth of the barrier recess is greater than or equal to a thickness of the ink portion.
7. The cover plate according to claim 5, wherein a height of the barrier column is greater than or equal to a thickness of the ink portion.
8. The cover plate according to claim 5, wherein material of the barrier column is the same as material of the first black ink layer.
9. The cover plate according to claim 1, wherein the barrier portion comprises a barrier column disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region.
10. The cover plate according to claim 9, wherein the infrared sensing hole sub-region and the barrier column are arranged along a first direction, a cross-sectional width of the barrier column along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
11. The cover plate according to claim 1, wherein the barrier portion comprises a barrier recess and a barrier column, and the barrier column is disposed adjacent to the barrier recess.
12. The cover plate according to claim 11, wherein the infrared sensing hole sub-region, the barrier recess, and the barrier column are arranged along a first direction, a cross-sectional width of at least one of the barrier recess and the barrier column along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.

13. The cover plate according to claim 12, wherein a depth of the barrier recess is greater than or equal to a thickness of the ink portion; or a height of the barrier column is greater than or equal to a thickness of the ink portion.
14. The cover plate according to claim 12, wherein the barrier portion comprises at least two barrier recesses, and/or, the barrier portion comprises at least two barrier columns.
15. The cover plate according to claim 14, wherein cross-sectional widths of the at least two barrier recesses along the second direction are unequal; and/or cross-sectional widths of at least two of the barrier columns along the second direction are unequal.
16. The cover plate according to claim 14, wherein heights of the at least two barrier recesses along a thickness direction of the cover plate body are unequal; and/or heights of at least two of the barrier columns along the cover plate body thickness direction are unequal.
17. A display screen, comprising a cover plate and a display panel, wherein the cover plate is bonded to a light exiting surface of the display panel and comprises: a cover plate body comprising a display region and a frame region, the frame region surrounds the display region, and an infrared sensing hole sub-region is defined in the frame region; an ink portion disposed on a surface of the cover plate body, located in the frame region, and comprising a white ink layer covering the infrared sensing hole sub-region; and a barrier portion disposed in the frame region and located on a side of the infrared sensing hole sub-region away from the display region; wherein a boundary of the white ink layer away from the display region does not extend beyond a boundary of the barrier portion away from display region.
18. The display screen according to claim 17, wherein the ink portion further comprises a first black ink layer and a translucent black ink layer, and the first black ink layer is disposed in the frame region and surrounds the infrared sensing hole sub-region; and the translucent black ink layer is disposed in the frame region and covers the infrared sensing hole sub-region, and the white ink layer covers the translucent black ink layer.
19. The display screen according to claim 18, wherein the barrier portion comprises a barrier recess or a barrier column, and the barrier portion is disposed in the frame region and is located on a side of the infrared sensing hole sub-region away from the display region.
20. The display screen according to claim 19, wherein the infrared sensing hole sub-region and the barrier portion are arranged along a first direction, a cross-sectional width of the barrier portion along a second direction is greater than a cross-sectional width of the white ink layer along the second direction, and the first direction is perpendicular to the second direction.
-