

(12) **United States Patent**
Pickard et al.

(10) **Patent No.:** **US 12,388,056 B1**
(45) **Date of Patent:** **Aug. 12, 2025**

(54) **LINEAR LIGHTING SYSTEMS AND PROCESSES**

(71) Applicant: **Korrus, Inc.**, Los Angeles, CA (US)

(72) Inventors: **Paul Pickard**, Acton, CA (US); **Noam Meir**, Herzliya (IL); **Raghuram L. V. Petluri**, Cerritos, CA (US); **Ariel Meir**, North Miami Beach, FL (US)

(73) Assignee: **KORRUS, INC.**, Los Angeles, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/348,991**

(22) Filed: **Jul. 7, 2023**

Related U.S. Application Data

(60) Continuation-in-part of application No. 18/303,849, filed on Apr. 20, 2023, now Pat. No. 12,062,645, (Continued)

(51) **Int. Cl.**
H01L 25/075 (2006.01)
F21K 9/64 (2016.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01L 25/0753** (2013.01); **F21K 9/64** (2016.08); **F21K 9/90** (2013.01); **F21S 4/20** (2016.01);
(Continued)

(58) **Field of Classification Search**
CPC H01L 25/0753; F21K 9/64; F21K 9/90; F21S 4/20; F21V 9/35; H05B 45/20
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,262,250 A 7/1966 Fowler
3,434,897 A 3/1969 Caretta
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2623604 8/2009
CN 101592291 A 12/2009
(Continued)

OTHER PUBLICATIONS

International Patent Application No. PCT/US2018/015449; Int'l Preliminary Report on Patentability; dated Aug. 8, 2019; 8 pages.
(Continued)


Primary Examiner — Joseph L Williams

(74) *Attorney, Agent, or Firm* — Jay M. Brown

(57) **ABSTRACT**

Linear lighting system including tray extended along elongation directions and having base forming bottom interior surface of tray; first sidewall extending upward from base towards emission aperture of linear lighting system and second sidewall spaced apart across base from first sidewall and extending upward from base towards emission aperture. System further includes circuit board located on first sidewall in tray, plurality of LEDs located on circuit board and mutually spaced apart on first sidewall along elongation directions of tray and positioned for light emissions in directions facing toward second sidewall; and protuberance on base and interposed between LEDs and second sidewall, protuberance positioned for diverting light emissions from plurality of LEDs toward emission aperture. System having tray with first sidewall including angled reflective face and second sidewall including further angled reflective face, the faces positioned for reflecting light emissions toward the emission aperture.

22 Claims, 16 Drawing Sheets



Related U.S. Application Data

which is a division of application No. 17/653,988, filed on Mar. 8, 2022, now Pat. No. 11,658,163, which is a continuation of application No. 16/480,867, filed as application No. PCT/US2018/015449 on Jan. 26, 2018, now Pat. No. 11,296,057.

- (60) Provisional application No. 63/511,841, filed on Jul. 3, 2023, provisional application No. 62/451,612, filed on Jan. 27, 2017, provisional application No. 62/451,616, filed on Jan. 27, 2017.

(51) **Int. Cl.**

F21K 9/90 (2016.01)

F21S 4/20 (2016.01)

F21V 9/35 (2018.01)

H05B 45/20 (2020.01)

H10H 20/851 (2025.01)

(52) **U.S. Cl.**

CPC **F21V 9/35** (2018.02); **H05B 45/20** (2020.01); **H10H 20/8513** (2025.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,445,164 A 4/1984 Giles, III
4,580,859 A 4/1986 Frano
4,603,496 A 8/1986 Latz
4,727,648 A 3/1988 Savage, Jr.
4,837,927 A 6/1989 Savage, Jr.
5,087,212 A 2/1992 Hanami
5,174,649 A 12/1992 Alston
5,241,457 A 8/1993 Sasajima
5,387,901 A 2/1995 Hardt
5,436,809 A 7/1995 Brassier
5,450,664 A 9/1995 Babow
5,490,048 A 2/1996 Brassier
5,628,557 A 5/1997 Huang
5,632,551 A 5/1997 Roney
5,658,066 A 8/1997 Hirsch
5,821,695 A 10/1998 Vilanilam
6,283,612 B1 9/2001 Hunter
6,354,714 B1 3/2002 Rhodes
6,426,704 B1 7/2002 Hutchison
6,439,743 B1 8/2002 Hutchison
6,450,662 B1 9/2002 Hutchison
6,450,664 B1 9/2002 Kelly
6,473,002 B1 10/2002 Hutchison
6,474,839 B1 11/2002 Hutchison
6,481,130 B1 11/2002 Wu
6,527,422 B1 3/2003 Hutchison
6,530,674 B2 3/2003 Grierson
6,582,103 B1 6/2003 Popovich
6,590,235 B2 7/2003 Carey
6,601,970 B2 8/2003 Ueda
6,676,284 B1 1/2004 Wynne Willson
6,773,138 B2 8/2004 Coushaine
6,824,296 B2 11/2004 Souza
6,827,469 B2 12/2004 Coushaine
6,851,832 B2 2/2005 Tieszen
6,880,952 B2 4/2005 Kiraly
6,882,111 B2 4/2005 Kan
6,893,144 B2 5/2005 Fan
6,979,097 B2 12/2005 Elam
7,093,958 B2 8/2006 Coushaine
7,111,964 B2 9/2006 Suehiro
7,112,926 B2 9/2006 Himori
7,132,804 B2 11/2006 Lys
7,150,553 B2 12/2006 English
7,159,997 B2 1/2007 Reo
7,161,311 B2 1/2007 Mueller
7,210,957 B2 5/2007 Mrakovich
7,221,104 B2 5/2007 Lys

7,229,192 B2 6/2007 Mayfield, III
7,261,435 B2 8/2007 Gould
7,267,461 B2 9/2007 Kan
7,360,925 B2 4/2008 Coushaine
7,414,269 B2 8/2008 Groetsch
7,455,422 B2 11/2008 Gould
7,456,499 B2 11/2008 Loh
7,481,552 B2 1/2009 Mayfield, III
7,481,566 B2 1/2009 Han
7,530,716 B2 5/2009 Mayfield, III
7,540,761 B2 6/2009 Weber
7,549,786 B2 6/2009 Higley
7,575,332 B2 8/2009 Cok
7,595,113 B2 9/2009 Miyoshi
7,604,365 B2 10/2009 Chang
7,654,703 B2 2/2010 Kan
7,700,965 B2 4/2010 Chang
7,703,951 B2 4/2010 Piepgras
7,712,926 B2 5/2010 Matheson
7,727,009 B2 6/2010 Goto
7,731,396 B2 6/2010 Fay
7,744,266 B2 6/2010 Higley
7,766,518 B2 8/2010 Piepgras
7,806,562 B2 10/2010 Behr
7,810,955 B2 10/2010 Stimac
7,810,995 B2 10/2010 Fadler
7,841,753 B2 11/2010 Liu
7,857,482 B2 12/2010 Reo
7,866,847 B2 1/2011 Zheng
7,878,683 B2 2/2011 Logan
7,918,589 B2 4/2011 Mayfield, III
7,922,364 B2 4/2011 Tessnow
7,923,907 B2 4/2011 Tessnow
7,952,114 B2 5/2011 Gingrich, III
7,961,113 B2 6/2011 Rabiner
7,972,038 B2 7/2011 Albright
7,988,336 B1 8/2011 Harbers
7,997,758 B2 8/2011 Zhang
8,033,680 B2 10/2011 Sharrah
8,052,310 B2 11/2011 Gingrich, III
8,066,403 B2 11/2011 Sanfilippo
8,076,683 B2 12/2011 Xu
8,113,680 B2 2/2012 O'Brien
8,118,454 B2 2/2012 Rains, Jr.
8,154,864 B1 4/2012 Nearman
8,172,436 B2 5/2012 Coleman
8,207,546 B2 6/2012 Harada
8,256,930 B2 9/2012 Cheng
8,262,250 B2 9/2012 Li
8,272,758 B2 9/2012 Meir
8,297,788 B2 10/2012 Bishop
8,314,566 B2 11/2012 Steele
8,348,460 B2 1/2013 Bachl
8,371,723 B2 2/2013 Nall
8,434,897 B2 5/2013 Logan
8,434,898 B2 5/2013 Sanfilippo
8,449,128 B2 5/2013 Ko
8,454,193 B2 6/2013 Simon
8,525,190 B2 9/2013 Donofrio
8,545,045 B2 10/2013 Tress
8,552,456 B1 10/2013 Sun
8,575,646 B1 11/2013 Shum
8,598,778 B2 12/2013 Allen
8,616,720 B2 12/2013 Carney
8,676,284 B2 3/2014 He
8,690,368 B1 4/2014 Shipman
8,697,458 B2 4/2014 Nolan
8,702,265 B2 4/2014 May
8,748,202 B2 6/2014 Kwon
8,755,665 B2 6/2014 Hong
8,764,220 B2 7/2014 Chan
8,791,485 B2 7/2014 Ohbayashi
8,820,964 B2 9/2014 Gould
8,858,607 B1 10/2014 Jones
8,876,322 B2 11/2014 Alexander
8,876,325 B2 11/2014 Lu
8,893,144 B2 11/2014 Haham
8,969,894 B2 3/2015 Lee
8,998,448 B2 4/2015 Chang

(56)

References Cited

U.S. PATENT DOCUMENTS

9,016,895	B2	4/2015	Handsaker	2009/0310354	A1	12/2009	Zampini, II
9,022,603	B1	5/2015	Moghal	2009/0321766	A1	12/2009	Chang
9,052,075	B2	6/2015	Demuynck	2010/0002414	A1	1/2010	Meir
9,091,422	B2	7/2015	Greenfield	2010/0008090	A1	1/2010	Li
9,157,622	B2	10/2015	Yanping	2010/0033948	A1	2/2010	Harbers
9,188,290	B2	11/2015	Lay	2010/0060157	A1	3/2010	Shi
9,285,085	B2	3/2016	Carney	2010/0060202	A1	3/2010	Melanson
9,295,855	B2	3/2016	Jones	2010/0072488	A1	3/2010	Bierhuizen
9,518,706	B2	12/2016	Chan	2010/0141557	A1	6/2010	Gruhlke
9,605,812	B2	3/2017	Van De Ven	2010/0237766	A1	9/2010	Baumgartner
9,651,227	B2	5/2017	Pickard	2010/0246179	A1	9/2010	Long
9,666,772	B2	5/2017	Ibbetson	2010/0254134	A1	10/2010	McCanless
9,713,371	B1 *	7/2017	Luu A45D 29/00	2010/0308354	A1	12/2010	David
9,722,158	B2	8/2017	Chan	2011/0013387	A1	1/2011	Kanade
9,874,333	B2	1/2018	Lay	2011/0025951	A1	2/2011	Jones
9,976,710	B2	5/2018	Meir	2011/0051394	A1	3/2011	Bailey
9,995,444	B2	6/2018	Leichner	2011/0051407	A1	3/2011	St Ives
10,030,828	B2	7/2018	Meir	2011/0051425	A1	3/2011	Tsuchiya
10,100,988	B2	10/2018	Rodgers	2011/0062470	A1	3/2011	Bierhuizen
10,132,476	B2	11/2018	Meir	2011/0089453	A1	4/2011	Min
10,228,099	B2	3/2019	Meir	2011/0122643	A1	5/2011	Spork
10,378,705	B2	8/2019	Meir	2011/0134634	A1	6/2011	Gingrich, III
10,465,864	B2	11/2019	Leichner	2011/0136374	A1	6/2011	Mostoller
10,584,860	B2	3/2020	Dungan	2011/0164426	A1	7/2011	Lee
10,612,747	B2	4/2020	Rodgers	2011/0193490	A1	8/2011	Kumar
10,989,372	B2	4/2021	Meir	2011/0198067	A1	8/2011	Hada
2002/0114155	A1	8/2002	Katogi	2011/0210364	A1	9/2011	Nolan
2002/0117692	A1	8/2002	Lin	2011/0222270	A1	9/2011	Porciatti
2003/0058658	A1	3/2003	Lee	2011/0255287	A1	10/2011	Li
2003/0072156	A1	4/2003	Pohlert	2011/0280020	A1	11/2011	Chen
2003/0198049	A1	10/2003	Hulse	2011/0286222	A1	11/2011	Coleman
2003/0223235	A1	12/2003	Mohacsi	2011/0303935	A1	12/2011	Chern
2004/0052076	A1	3/2004	Mueller	2012/0002417	A1	1/2012	Li
2004/0070855	A1	4/2004	Benitez	2012/0025241	A1	2/2012	Xiao
2004/0105261	A1	6/2004	Ducharme	2012/0025729	A1	2/2012	Melanson
2004/0218386	A1	11/2004	Doll	2012/0051048	A1	3/2012	Smit
2005/0092517	A1	5/2005	Fan	2012/0051056	A1	3/2012	Derks
2005/0221518	A1	10/2005	Andrews	2012/0051068	A1	3/2012	Pelton
2005/0225985	A1	10/2005	Catalano	2012/0087124	A1	4/2012	Ravillisetty
2005/0280016	A1	12/2005	Mok	2012/0106152	A1	5/2012	Zheng
2005/0286265	A1	12/2005	Zampini	2012/0113676	A1	5/2012	Van Dijk
2006/0077687	A1	4/2006	Higashiyama	2012/0113678	A1	5/2012	Cornelissen
2006/0134440	A1	6/2006	Crivello	2012/0140474	A1	6/2012	Jurik
2006/0141851	A1	6/2006	Matsui	2012/0146066	A1	6/2012	Tischler
2006/0146531	A1	7/2006	Reo	2012/0147621	A1	6/2012	Holten
2006/0181903	A1	8/2006	Okuwaki	2012/0170303	A1	7/2012	Meir
2006/0187653	A1	8/2006	Olsson	2012/0218750	A1	8/2012	Klase
2007/0058377	A1	3/2007	Zampini, II	2012/0250309	A1	10/2012	Handsaker
2007/0064428	A1	3/2007	Beauchamp	2012/0267650	A1	10/2012	Schubert
2007/0092736	A1	4/2007	Boardman	2012/0286304	A1	11/2012	Letoquin
2007/0103902	A1	5/2007	Hsiao	2013/0021775	A1	1/2013	Veerasamy
2007/0205425	A1	9/2007	Harada	2013/0021797	A1	1/2013	Kubo
2007/0206375	A1	9/2007	Piepgas	2013/0021811	A1	1/2013	Goldwater
2007/0235751	A1	10/2007	Radkov	2013/0063939	A1	3/2013	Kondo
2007/0279727	A1	12/2007	Gandhi	2013/0083524	A1	4/2013	Devorris
2008/0048200	A1	2/2008	Mueller	2013/0093980	A1	4/2013	Goto
2008/0080196	A1	4/2008	Ruud	2013/0134445	A1	5/2013	Tarsa
2008/0144322	A1	6/2008	Norfidathul	2013/0214691	A1	8/2013	Chen
2008/0165530	A1	7/2008	Hendrikus	2013/0249387	A1	9/2013	Hsin
2008/0212319	A1	9/2008	Klipstein	2013/0265750	A1	10/2013	Pickard
2008/0239755	A1	10/2008	Parker	2013/0272000	A1	10/2013	Pearson
2008/0244944	A1	10/2008	Nall	2013/0274398	A1	10/2013	Shiobara
2008/0266900	A1	10/2008	Harbers	2013/0292709	A1	11/2013	Tong
2008/0267572	A1	10/2008	Sampsel	2013/0313965	A1	11/2013	Chiang
2008/0298058	A1	12/2008	Kan	2014/0001952	A1	1/2014	Harris
2008/0315228	A1	12/2008	Krames	2014/0036500	A1	2/2014	Eggleton
2009/0021936	A1	1/2009	Stimac	2014/0043812	A1	2/2014	Moreau
2009/0026913	A1	1/2009	Mrakovich	2014/0112003	A1	4/2014	Lacroix
2009/0109539	A1	4/2009	Devos	2014/0168997	A1	6/2014	Lee
2009/0126792	A1	5/2009	Gruhlke	2014/0176016	A1	6/2014	Li
2009/0167203	A1	7/2009	Dahlman	2014/0177262	A1	6/2014	Lai
2009/0185389	A1	7/2009	Tessnow	2014/0211448	A1	7/2014	Wang
2009/0195168	A1	8/2009	Greenfeld	2014/0268720	A1	9/2014	Dungan
2009/0225546	A1	9/2009	Pearson	2014/0268748	A1	9/2014	Lay
2009/0272996	A1	11/2009	Chakraborty	2014/0268810	A1	9/2014	Marquardt
				2014/0334142	A1	11/2014	Levante
				2014/0367633	A1	12/2014	Bibl
				2015/0003105	A1	1/2015	Goto
				2015/0034976	A1	2/2015	Kim

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0036387	A1	2/2015	Myers
2015/0041839	A1	2/2015	Sakai
2015/0062892	A1	3/2015	Krames
2015/0062965	A1	3/2015	Oh
2015/0117022	A1	4/2015	Meir
2015/0144918	A1	5/2015	Cho
2015/0145406	A1	5/2015	Li
2015/0241034	A1	8/2015	Dankelmann
2015/0252982	A1	9/2015	Demuynck
2015/0276170	A1	10/2015	Motoyanagi
2015/0283768	A1	10/2015	Marquardt
2015/0316219	A1	11/2015	Mallory
2015/0326767	A1	11/2015	Kim
2016/0003424	A1	1/2016	Wu
2016/0035944	A1	2/2016	Spanard
2016/0076741	A1	3/2016	Rong
2016/0076743	A1	3/2016	Deutsch
2016/0093780	A1	3/2016	Beppu
2016/0170120	A1	6/2016	Shani
2016/0195225	A1	7/2016	Carney
2016/0201861	A1	7/2016	Meir
2016/0230958	A1	8/2016	Pickard
2016/0327249	A1	11/2016	Pearson
2016/0327256	A1	11/2016	Hall
2017/0009957	A1	1/2017	Lim
2017/0038015	A1	2/2017	Lunz
2017/0137627	A1	5/2017	Szwarcman
2017/0219170	A1	8/2017	Petluri
2017/0250319	A1	8/2017	Yajima
2017/0256693	A1	9/2017	Yoshizawa
2017/0261186	A1	9/2017	Meir
2017/0261187	A1	9/2017	Meir
2017/0309795	A1	10/2017	Kim
2017/0311422	A1	10/2017	Arai
2017/0343167	A1	11/2017	Petluri
2018/0100959	A1	4/2018	Vasylyev
2018/0113244	A1	4/2018	Vasylyev
2018/0238501	A1	8/2018	Honda
2019/0203889	A1	7/2019	Petluri
2019/0212492	A1	7/2019	Meng
2019/0219251	A1	7/2019	Meir
2019/0267523	A1	8/2019	Min
2019/0338918	A1	11/2019	Ashraf
2019/0383450	A1	12/2019	Meir
2020/0096178	A1	3/2020	Aviram
2020/0098732	A1	3/2020	Meir
2020/0141546	A1	5/2020	Meir
2020/0144468	A1	5/2020	Meir
2020/0158299	A1	5/2020	Meir
2020/0191370	A1	6/2020	Shohat
2021/0338861	A1	11/2021	Harrison
2021/0341134	A1	11/2021	May
2022/0057049	A1	2/2022	Hikmet

FOREIGN PATENT DOCUMENTS

CN	101614329	12/2009
CN	101714604 A	5/2010
CN	201590432 U	9/2010

CN	201739849 U	2/2011
CN	101997074 A	3/2011
CN	202040752 U	11/2011
CN	102269351 A	12/2011
EP	0592746 B1	3/1997
EP	2256833 B1	4/2013
EP	2474775 B1	11/2013
EP	2484956 B1	6/2014
ES	1211538 U	5/2018
FR	3058203 A1	5/2018
GB	2457016 A	8/2009
JP	2011508406 T	3/2011
JP	2011204495 A	10/2011
JP	2011204658 A	10/2011
KR	20070039683	4/2007
KR	20090013704 A	2/2009
KR	100974942 B1	8/2010
KR	20110106033	9/2011
KR	20120050280	5/2012
WO	0215281	2/2002
WO	2013059298 A1	4/2013
WO	2014082262 A1	6/2014
WO	2014099681 A2	6/2014
WO	2014099681 A3	12/2014
WO	2015066184 A1	5/2015
WO	2018015449	1/2018
WO	2018140727 A1	8/2018
WO	2019193218 A1	10/2019
WO	2019213299 A1	11/2019
WO	2020131933 A1	6/2020
WO	2021021234 A1	2/2021

OTHER PUBLICATIONS

International Patent Application No. PCT/US2018/015449; Int'l Search Report and the Written Opinion; dated Jun. 14, 2018; 16 pages.

International Patent Application No. PCT/US2019/030252; Int'l Search Report and the Written Opinion; dated Oct. 4, 2019; 13 pages.

International Search Report and Written Opinion for Application No. PCT/US14/62905 dated Jan. 22, 2015, 10 pages.

International Search Report and Written Opinion mailed on Nov. 27, 2013 in PCT Application No. PCT/US2013/045708, 3 pages.

PCT /US2012/060588, "International Application Serial No. PCT/US2012/060588, International Preliminary Report on Patentability and Written Opinion dated May 1, 2014", Ecosense Lighting Inc. et al, 7 Pages.



PCT/US2012/060588, International Application Serial No. PCT/US2012/060588, International Search Report and Written Opinion dated Mar. 29, 2013, Ecosense Lighting Inc. et al, 10 pages.




PCT/US2013/075172, "International Application Serial No. PCT/US2013/075172, International Search Report and Written Opinion dated Sep. 26, 2014", Ecosense Lighting Inc., 16 Pages.

PCT/US2014/062905, International Preliminary Report on Patentability dated May 3, 2016 (7 pp).

PCT/US2014/062905, Written Opinion of the Int'l Searching Authority dated Jan. 22, 2015 (6 pp).

* cited by examiner








FIG. 3





FIG. 4






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

1

LINEAR LIGHTING SYSTEMS AND PROCESSES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of copending U.S. patent application Ser. No. 63/511,841 filed on Jul. 3, 2023, titled LINEAR LIGHTING SYSTEMS AND PROCESSES. This application is also a continuation-in-part of copending U.S. patent application Ser. No. 18/303,849 filed on Apr. 20, 2023, titled LIGHTING SYSTEMS WITH HIGH COLOR RENDERING INDEX AND UNIFORM PLANAR ILLUMINATION, which is a divisional of U.S. patent application Ser. No. 17/653,988 filed on Mar. 8, 2022 and issued as U.S. Pat. No. 11,658,163 on May 23, 2023, titled LIGHTING SYSTEMS WITH HIGH COLOR RENDERING INDEX AND UNIFORM PLANAR ILLUMINATION, which is a continuation of U.S. patent application Ser. No. 16/480,867 filed on Jul. 25, 2019 and issued as U.S. Pat. No. 11,296,057 on Apr. 5, 2022 titled LIGHTING SYSTEMS WITH HIGH COLOR RENDERING INDEX AND UNIFORM PLANAR ILLUMINATION, which is a U.S. National Stage patent application based on International Application No. PCT/US2018/015449 filed on Jan. 26, 2018 titled LIGHTING SYSTEMS WITH HIGH COLOR RENDERING INDEX AND UNIFORM PLANAR ILLUMINATION, which claims the benefit under 35 U.S.C. § 119 (e) of U.S. Provisional Application Ser. No. 62/451,612, titled “FLEXIBLE LED LINEAR STRIP” filed on Jan. 27, 2017 and of U.S. Provisional Application Ser. No. 62/451,616, titled “RECESS SLOT LIGHTING” filed on Jan. 27, 2017. Each one of the foregoing patent applications is co-owned by the Applicant herein and is hereby incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the field of linear lighting systems and processes related to such linear lighting systems.

2. Background of the Invention

Numerous linear lighting systems have been developed. Despite the existence of these lighting systems, further improvements are still needed in linear lighting systems and in processes related to such lighting systems.

SUMMARY

In an example of an implementation a linear lighting system is provided, including a tray being extended along elongation directions and having a base forming a bottom interior surface of the tray, a first sidewall extending upward from the base towards an emission aperture of the linear lighting system, and a second sidewall being spaced apart across the base from the first sidewall and extending upward from the base towards the emission aperture of the linear lighting system. In that example, the linear lighting system further includes: a circuit board being located on the first sidewall in the tray; a plurality of light emitting diodes (LEDs) being located on the circuit board and mutually spaced apart on the first sidewall along the elongation directions of the tray and being positioned for light emis-

2

sions in directions facing toward the second sidewall; and a protuberance being located on the base and interposed between the LEDs and the second sidewall, the protuberance being positioned for diverting light emissions from the plurality of the LEDs toward the emission aperture.

In some examples of the implementation, the tray may be triaxially or biaxially flexible.

In further examples of the implementation, the circuit board may be triaxially or biaxially flexible.

In additional examples of the implementation, the protuberance may include a raised mound located on the base and extending along the elongation directions of the tray, the raised mound being positioned to intersect pathways of some of the light emissions.

In other examples of the implementation, the protuberance may have an angled or convex surface for diverting light emissions toward the emission aperture.

In some examples of the implementation, the convex surface of the protuberance may be smoothly convex.

In further examples of the implementation, the angled surface of the protuberance may have a geometric prismatic shape.

In additional examples of the implementation, the geometric prismatic shape of the protuberance may include a triangular prism, a rectangular prism, a pentagonal prism, or a hexagonal prism.

In other examples of the implementation, the protuberance may include a plurality of raised mounds located on the base and being mutually spaced apart along the elongation directions of the tray, each one of the plurality of the raised mounds being positioned to intersect pathways of some of the light emissions.

In some examples of the implementation, each one of the plurality of the raised mounds may have an angled or convex surface for diverting light emissions toward the emission aperture.

In further examples of the implementation, each one of the convex surfaces of the protuberances may be smoothly convex.

In additional examples of the implementation, each one of the angled surfaces of the protuberances may have a geometric prismatic shape.

In other examples of the implementation, the geometric prismatic shape of each one of the protuberances may include a triangular prism, a rectangular prism, a pentagonal prism, or a hexagonal prism.

In some examples of the implementation, the protuberance may have a highly light reflective surface for reflecting light emissions toward the emission aperture.

In further examples of the implementation, the protuberance may be a light-transmissive protuberance having a higher refractive index than air, for refracting light emissions toward the emission aperture.

In additional examples of the implementation, the linear lighting system may include another circuit board being located on the second sidewall in the tray, and may include a further plurality of light emitting diodes (LEDs) being located on the another circuit board and mutually spaced apart on the second sidewall along the elongation directions of the tray and being positioned for further light emissions in directions facing toward the first sidewall; and the protuberance may be positioned for diverting further light emissions from the further plurality of LEDs toward the emission aperture.

In other examples of the implementation, an interior of the tray may have a highly light reflective surface.

3

In some examples of the implementation, the linear lighting system may further include a plurality of lenses, each one of the plurality of lenses being located over a respective one of the plurality of the LEDs for increasing a maximum light emission angle of the LED from a first value to a second value that is larger than the first value.

In further examples of the implementation, the linear lighting system may further include a diffuser located over the plurality of the lenses, and the plurality of the lenses and the diffuser may cause the linear lighting system to emit the light emissions as a line of light.

In additional examples of the implementation, the first value of the maximum light emission angle may be no more than about sixty (60) degrees and the second value of the maximum emission angle may be at least about eighty (80) degrees.

In other examples of the implementation, the linear lighting system may include a further plurality of lenses, each one of the further plurality of lenses being located over a respective one of the another plurality of the LEDs for increasing a maximum light emission angle from a first value to a second value that may be larger than the first value.

In some examples of the implementation, the linear lighting system may further include another diffuser located over the further plurality of the lenses, and the further plurality of the lenses and the another diffuser may cause the linear lighting system to emit the further light emissions as a line of light.

In an example of another implementation, a linear lighting system is provided, having a tray being extended along elongation directions and having a base forming a bottom interior surface of the tray, a first sidewall including an angled reflective face and extending upward from the base towards an emission aperture of the linear lighting system, and a second sidewall including a further angled reflective face and extending upward from the base towards the emission aperture of the linear lighting system, the second sidewall being spaced apart across the base from the first sidewall. In the example of the another implementation, the linear lighting system further includes: a circuit board being located on the first sidewall in the tray, and another circuit board being located on the second sidewall in the tray; and a plurality of light emitting diodes (LEDs) being located on the circuit board and mutually spaced apart on the first sidewall along the elongation directions of the tray and being positioned for light emissions in directions facing toward the second sidewall, and another plurality of light emitting diodes (LEDs) being located on the another circuit board and mutually spaced apart on the second sidewall along the elongation directions of the tray and being positioned for further light emissions in directions facing toward the first sidewall; wherein the further angled reflective face of the second sidewall is positioned for reflecting light emissions from the plurality of the LEDs toward the emission aperture; and wherein the angled reflective face of the first sidewall is positioned for reflecting further light emissions from the another plurality of the LEDs toward the emission aperture.

In some examples of the another implementation, the tray may be triaxially or biaxially flexible.

In further examples of the another implementation, the circuit board may be triaxially or biaxially flexible.

In additional examples of the another implementation, the angled reflective face of the first sidewall may be oriented at an acute or obtuse angle relative to the directions of further light emissions toward the first sidewall, and the further

4

angled reflective face of the second sidewall may be oriented at another acute or obtuse angle relative to the directions of the light emissions toward the second sidewall.

In other examples of the another implementation, the angled reflective face of the first sidewall may be oriented at an acute angle of less than about 45 degrees relative to the directions of further light emissions toward the first sidewall, and the further angled reflective face of the second sidewall may be oriented at another acute angle of less than 45 degrees relative to the directions of the light emissions toward the second sidewall.

In further examples of the another implementation, the angled reflective face of the first sidewall may be oriented at an obtuse angle of between about 90 degrees and about 180 degrees relative to the directions of further light emissions toward the first sidewall, and the further angled reflective face of the second sidewall may be oriented at another obtuse angle of between about 90 degrees and about 180 degrees relative to the directions of the light emissions toward the second sidewall.

In some examples of the another implementation, the angled reflective face of the first sidewall may include a reflective bar extended along the elongation directions of the tray and located below the plurality of the LEDs in the tray.

In further examples of the another implementation, the angled reflective face of the first sidewall may include a reflective bar extended along the elongation directions of the tray and located above the plurality of the LEDs in the tray.

In additional examples of the another implementation, the angled reflective face of the first sidewall may be formed by a plurality of reflective rings each encircling a respective one of the plurality of LEDs in the tray.

In other examples of the another implementation, the plurality of the reflective rings may have reflective surfaces being oriented at acute or obtuse angles relative to the directions of further light emissions toward the first sidewall.

In some examples of the another implementation, the further angled reflective face of the second sidewall may be formed by a further plurality of reflective rings each encircling a respective one of the another plurality of LEDs in the tray.

In further examples of the another implementation, the further plurality of reflective rings may have reflective surfaces being oriented at further acute or obtuse angles relative to the directions of light emissions toward the second sidewall.

Other systems, devices, processes, features and advantages of the invention will be or will become apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, devices, processes, features and advantages be included within this description, be within the scope of the invention, and be protected by the accompanying claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention can be better understood with reference to the following figures. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. Moreover, in the figures, like reference numerals designate corresponding parts throughout the different views.

FIG. 1A shows a top view of an example linear lighting system, according to some embodiments of the technology described herein;

5

FIG. 1B shows a bottom view of the example linear lighting system of FIG. 1A, according to some embodiments of the technology described herein;

FIG. 2A shows a cross-sectional view of an example linear lighting system, according to some embodiments of the technology described herein;

FIG. 2B shows a cross-sectional view of another example linear lighting system, according to some embodiments of the technology described herein;

FIG. 2C shows a cross-sectional view of another example linear lighting system, according to some embodiments of the technology described herein;

FIG. 3 shows a cross-sectional view of an example linear lighting system with integrated lenses, according to some embodiments of the technology described herein;

FIG. 4 shows a top view of a deconstructed version of the linear lighting system of FIG. 3, according to some embodiments of the technology described herein;

FIG. 5 shows a cross-sectional view of an example lens, according to some embodiments of the technology described herein;

FIG. 6 is a graph showing the power efficiency requirements of high color rendering index (CRI) light sources, according to some embodiments of the technology described herein;

FIG. 7 is a graph showing the spectrum of light emitted by example linear lighting systems with different elastomer configurations, according to some embodiments of the technology described herein;

FIG. 8 is a graph showing the spectrum of light emitted by example linear lighting systems with different photoluminescent materials, according to some embodiments of the technology described herein;

FIG. 9 is a graph showing the spectrum of light emitted by each component of an example linear lighting system for a back lighting unit (BLU), according to some embodiments of the technology described herein;

FIG. 10 is a graph showing the spectrum of another example linear lighting system for a BLU, according to some embodiments of the technology described herein; and

FIG. 11 is a graph showing the spectrum of light emitted by an example linear lighting system compared with the spectrum of light absorbed by different chlorophylls and beta carotene, according to some embodiments of the technology described herein.

FIG. 12 presents a cross-sectional view of an example of a linear lighting system according to some embodiments of the technology described herein.

FIG. 13 presents a top view, taken from the direction of the arrow 13, of the example of a linear lighting system shown in FIG. 12.

FIG. 14 presents a cross-sectional view of another example of the linear lighting system according to some embodiments of the technology described herein.

FIG. 15 presents a top view, taken from the direction of the arrow 15, of the another example of the linear lighting system shown in FIG. 14.

FIG. 16 presents a cross-sectional view of an example of another linear lighting system according to some embodiments of the technology described herein.

FIG. 17 presents a top view, taken from the direction of the arrow 17, of the example of a linear lighting system shown in FIG. 16.

DETAILED DESCRIPTION

Linear lighting systems have been developed for a variety of end-use applications. As examples, linear lighting sys-

6

tems may be installed indoors on walls, ceilings, or floors, and may also be installed on building exteriors. Further, linear lighting systems may be utilized for achieving particular lighting needs, such as lighting for offices, industrial environments, residential kitchens, building exteriors, landscape lighting, and vehicle lighting. In many of these end-use applications and in pursuing many of these particular needs, glare is a significant detractor to such linear lighting systems. Additionally, a line of light may be called for in response to various functional needs such as achieving particular decorative values, or safe working conditions. In some examples, a line of light having substantially uniform intensity may be useful.

According to an example of an implementation of the invention, a linear lighting system is provided including a tray being extended along elongation directions and having a base forming a bottom interior surface of the tray, a first sidewall extending upward from the base towards an emission aperture of the linear lighting system, and a second sidewall being spaced apart across the base from the first sidewall and extending upward from the base towards the emission aperture of the linear lighting system. In that example, the linear lighting system further includes: a circuit board being located on the first sidewall in the tray; a plurality of light emitting diodes (LEDs) being located on the circuit board and mutually spaced apart on the first sidewall along the elongation directions of the tray and being positioned for light emissions in directions facing toward the second sidewall; and a protuberance being located on the base and interposed between the LEDs and the second sidewall, the protuberance being positioned for diverting light emissions from the plurality of the LEDs toward the emission aperture.

According to an example of another implementation of the invention, a linear lighting system is provided having a tray being extended along elongation directions and having a base forming a bottom interior surface of the tray, a first sidewall including an angled reflective face and extending upward from the base towards an emission aperture of the linear lighting system, and a second sidewall including a further angled reflective face and extending upward from the base towards the emission aperture of the linear lighting system, the second sidewall being spaced apart across the base from the first sidewall. In the example of the another implementation, the linear lighting system further includes: a circuit board being located on the first sidewall in the tray, and another circuit board being located on the second sidewall in the tray; and a plurality of light emitting diodes (LEDs) being located on the circuit board and mutually spaced apart on the first sidewall along the elongation directions of the tray and being positioned for light emissions in directions facing toward the second sidewall, and another plurality of light emitting diodes (LEDs) being located on the another circuit board and mutually spaced apart on the second sidewall along the elongation directions of the tray and being positioned for further light emissions in directions facing toward the first sidewall; wherein the further angled reflective face of the second sidewall is positioned for reflecting light emissions from the plurality of the LEDs toward the emission aperture; and wherein the angled reflective face of the first sidewall is positioned for reflecting further light emissions from the another plurality of the LEDs toward the emission aperture.

Inexpensive white LEDs generally are constructed as white phosphor-converted LEDs where a blue LED is covered with a phosphor coating that converts a portion of the blue light from the LED to yellow light so as to create white

light. However, these white phosphor-converted LEDs generally emit white light with a low color rendering index (CRI) value because the phosphor coating may allow a substantial portion of the blue light emitted from the LED to remain unconverted. As a result, the white light emitted from such inexpensive LEDs has a large blue component that decreases the CRI value of the white light. Conventionally, the CRI value of the white light emitted by a phosphor-converted LED is improved by adding a red LED that emits red light that mixes with the white light emitted by the phosphor-converted LED to increase the red component of the white light. The increased red component may balance out the large blue component of the white light emitted from the phosphor-converted LED and, thereby, increase the CRI value of the white light.

The inventors have appreciated that the conventional approach to produce white light with a high CRI value is expensive, complex, and inefficient. In particular, pairing the white phosphor-converted LEDs with red LEDs increases the total LED count in a linear lighting system, which increases the total cost of the system and the complexity of the electrical connections between each of the LEDs in the system. Further, the addition of the red LED decreases the power efficiency of the system (e.g., measured in lumens per watt) because the power consumption of the red LED is not balanced out by the small boost to the total lumens provided by the additional red light.

Accordingly, aspects of the present disclosure relate to linear lighting systems that produce broad spectrum light (e.g., white light) with a high CRI value (e.g., a CRI value of at least 95) using only broad spectrum LEDs (e.g., white phosphor-converted LEDs). Thereby, the additional cost, complexity, and power inefficiency created by pairing white phosphor-converted LEDs with red LEDs may be eliminated. Further, the linear lighting systems disclosed herein may have high power efficiency ratings that exceed the present and upcoming standards for linear lighting system power efficiency standards. FIG. 6 shows the power efficiency requirements for linear lighting systems proposed as part of the Codes and Standards Enhancement (CASE) Initiative Program. As shown, the minimum power efficiency for linear lighting systems with a minimum CRI of 95 on sale between 2017 and 2019 is approximately 55 lumens per watt and the minimum power efficiency for linear lighting systems with a minimum CRI of 95 sold in 2019 and thereafter is 65 lumens per watt. The lighting systems described herein may provide high CRI white light with power efficiencies that far exceed these standards. For example, the lighting systems described herein may have power efficiencies in excess of 100 lumens per watt.

In some embodiments, the CRI value of white light emitted by white LEDs (e.g., white phosphor-converted LEDs) is improved through the use of photo-luminescent materials. The photo-luminescent materials may be configured to be emit light in a first spectrum in response to being excited by light in a second different spectrum. For example, the photo-luminescent materials may be configured to absorb blue light and emit light with a longer wavelength (e.g., yellow light, red light, etc.). Thereby, the photo-luminescent materials may reduce the large blue component of the white light emitted by the white phosphor-converted LED and increase the components of light with longer wavelengths (e.g., red light). The resulting white light may have a substantially higher CRI than the white light emitted by the white phosphor-converted LED. Any of a variety of photo-luminescent materials may be employed. Example photo-luminescent material may include a phosphor (e.g.,

neodymium-doped yttrium aluminum garnet (Nd:YAG)), a silicate, and quantum dots (e.g., Cadmium-free quantum dots). The photo-luminescent material may be an organic material and/or include organic compounds. Additionally (or alternatively), the photo-luminescent material may be an inorganic material and/or include inorganic compounds.

The white LED in combination with the photo-luminescent material may be integrated into a lighting system in any of a variety of ways. In some embodiments, the lighting system may be implemented as an LED linear system including a plurality of interconnected Linear lighting systems. In these embodiments, the Linear lighting systems may include a circuit board onto which an LED may be mounted. The LED may be configured to emit broad spectrum light (e.g., light has a spectrum that is at least 200 nanometers in size such as white light) having a first CRI value. A photo-luminescent material may be disposed between the LED mounted to the circuit board and the top surface of the lighting system to increase the CRI of the broad spectrum light emitted by the LED from the first CRI value (e.g., no more than 80) to a higher, second CRI value (e.g., at least 95). The components of the Linear lighting system may, for example, be partially encapsulated with an elastomer, such as silicone, to protect the components from the environment.

The inventors have additionally appreciated that linear lighting systems are generally unsuitable for direct viewing. In particular, the individual LEDs integrated into the system are generally discernable to a viewer because of their light intensity relative to other locations on the linear lighting system. As a result, linear lighting systems are generally employed in applications where the lighting system is not directly visible. For example, the linear lighting system may be positioned such that only the reflected light from the LEDs can be seen by a viewer.

Aspects of the present disclosure relate to linear lighting systems that provide a line of light along the linear lighting system. In some examples, the linear lighting systems disclosed herein may provide a line of light along the linear lighting system having a substantially uniform intensity. It is understood throughout this specification that the terms “approximately,” “about,” and “substantially” may be used to mean within $\pm 20\%$ of a target value in some embodiments, within $\pm 10\%$ of a target value in some embodiments, within $\pm 5\%$ of a target value in some embodiments, and yet within $\pm 2\%$ of a target value in some embodiments. The terms “approximately,” “about,” and “substantially” may include the target value.

These linear lighting systems may be employed in direct view applications, such as in recessed slots, unlike conventional linear lighting systems. The linear lighting systems may be configured to provide a line of light in any of a variety of ways. In some embodiments, a lens may be placed over each LED in the lighting system that increases the maximum emission angle of the light from the LED to improve the distribution of the light. For example, the LED may emit light with a maximum emission angle of no more than ± 60 degrees and the lens may increase the maximum emission angle of at least ± 80 degrees. Additionally, a diffuser may be employed that diffuses the light from the lenses using any of a variety of materials, such as scattering particles.

The lens in combination with the diffuser may be integrated into a lighting system in any of a variety of ways. In some embodiments, the lighting system may be implemented as a linear lighting system including a plurality of interconnected Linear lighting systems. In these embodi-

ments, the Linear lighting systems may include a tray having a base that is parallel to the bottom surface of the lighting system, a first sidewall that extends from the base towards the top surface of the lighting system, and a second sidewall that extends from the base towards the top surface of the lighting system and is parallel to the first sidewall. A circuit board may be disposed in the tray with an LED mounted thereon that faces the top of the lighting system. A lens may be disposed over the LED that is configured to increase the maximum emission angle of the light from the LED. The linear lighting system may, for example, be partially encapsulated with an elastomer that is in contact with the circuit board, the sidewalls of the tray, and only a portion of the lens such that part of the lens is left exposed (e.g., exposed to air). A diffuser may be disposed above the lens and configured to diffuse the light.

It should be appreciated that the embodiments described herein may be implemented in any of numerous ways. Examples of specific implementations are provided below for illustrative purposes only. It should be appreciated that these embodiments and the features/capabilities provided may be used individually, all together, or in any combination of two or more, as aspects of the technology described herein are not limited in this respect.

FIG. 1A shows a top view of an example lighting system, according to some embodiments of the technology described herein. FIG. 1B shows a bottom view of the example lighting system of FIG. 1A, according to some embodiments of the technology described herein. FIG. 2A shows a cross-sectional view of an example lighting system, according to some embodiments of the technology described herein. FIG. 2B shows a cross-sectional view of another example lighting system, according to some embodiments of the technology described herein. FIG. 2C shows a cross-sectional view of another example lighting system, according to some embodiments of the technology described herein. FIG. 3 shows a cross-sectional view of an example lighting system with integrated lenses, according to some embodiments of the technology described herein. FIG. 4 shows a top view of a deconstructed version of the lighting system of FIG. 3, according to some embodiments of the technology described herein. FIG. 5 shows a cross-sectional view of an example lens, according to some embodiments of the technology described herein. FIG. 6 is a graph showing the power efficiency requirements of high color rendering index (CRI) light sources, according to some embodiments of the technology described herein. FIG. 7 is a graph showing the spectrum of light emitted by example lighting systems with different elastomer configurations, according to some embodiments of the technology described herein. FIG. 8 is a graph showing the spectrum of light emitted by example lighting systems with different photo-luminescent materials, according to some embodiments of the technology described herein. FIG. 9 is a graph showing the spectrum of light emitted by each component of an example lighting system for a back lighting unit (BLU), according to some embodiments of the technology described herein. FIG. 10 is a graph showing the spectrum of light emitted by another example lighting system for a BLU, according to some embodiments of the technology described herein. FIG. 11 is a graph showing the spectrum of light emitted by an example lighting system compared with the spectrum of light absorbed by different chlorophylls and beta carotene, according to some embodiments of the technology described herein. FIG. 12 presents a cross-sectional view of an example of a linear lighting system according to some embodiments of the technology described herein. FIG. 13 presents a top view, taken from the

direction of the arrow 13, of the example of a linear lighting system shown in FIG. 12. FIG. 14 presents a cross-sectional view of another example of the linear lighting system according to some embodiments of the technology described herein. FIG. 15 presents a top view, taken from the direction of the arrow 15, of the another example of the linear lighting system shown in FIG. 14. FIG. 16 presents a cross-sectional view of an example of another linear lighting system according to some embodiments of the technology described herein. FIG. 17 presents a top view, taken from the direction of the arrow 17, of the example of a linear lighting system shown in FIG. 16.

Examples [100], [200], [300], [400] of lighting systems are discussed herein in connection with FIGS. 1-11. Examples [1200] of lighting systems are discussed herein in connection with FIGS. 12-15. Examples [1600] of lighting systems are discussed herein in connection with FIGS. 16-17. It is understood throughout this specification that a lighting system [100], [200], [300], [400] may include any of the features or combinations of features that are disclosed in connection with the examples [1200] of lighting systems or the examples [1600] of lighting systems. It is further understood throughout this specification that a lighting system [1200] or [1600] may include any of the features or combinations of features that are disclosed in connection with the Examples [100], [200], [300], [400] of lighting systems. Accordingly, FIGS. 12-17 and the entirety of the discussion of the examples [1200] and [1600] of lighting systems are hereby incorporated into the following discussion of the examples [100], [200], [300], [400] of an implementation of the lighting system.

FIGS. 1A and 1B show top and bottom views, respectively, of an example lighting system 100. As shown, the lighting system 100 is constructed as a linear lighting system that includes a plurality of electrically coupled lighting systems 102. Thereby, the length of the lighting system 100 may be customized by adding (or removing) lighting systems 102. Each of the lighting systems 102 may include LED assemblies 106 mounted to a circuit board that may, for example, be partially encapsulated in an elastomer (e.g., silicone). The LED assemblies 106 may be electrically coupled via the circuit board to connectors 104 mounted on each end of the circuit board. In turn, the connector 104 may electrically couple each LED assemblies 106 to an external system such as another lighting system 102 or a power adapter. The LED assemblies 106 may receive power from the external system via the connector 104 and emit light.

The lighting systems 102 in the lighting system 100 may have particular dimensions to enable a wide range of applications. In some embodiments, the lighting systems 102 may be sized for mounting in recessed slots that are no more than 1 inch deep. In these embodiments, the lighting systems 102 may have, for example, a length of no more than approximately 6 inches, a width of no more than approximately 3 inches, and/or a height of no more than approximately 5/8 inches. Thereby, the lighting systems 102 may easily fit within the recessed slots. It should be appreciated that the lighting systems 102 may be constructed with other dimensions.

The LED assemblies 106 may include an LED that is configured to emit light, such as a white phosphor-converted LED. The LED assemblies 106 may (or may not) include additional elements that may change a characteristic of the light emitted by the LED. Example characteristics of the light emitted by the LED that may be changed include: a color correlated temperature (CCT) value, a CRI value, an R9 color index value, and an angle of emission. Any of a

11

variety of elements may be employed to change the characteristics of the light emitted by the LED such as lenses, photo-luminescent materials, and/or scattering particles.

One or more components of the lighting system **102** may be mounted to a circuit board (e.g., a printed circuit board). For example, the LED assemblies **106** and/or the connectors **104** may be mounted to the circuit board. The circuit board may include one or more conductors to electrically couple the components mounted to the circuit board. The circuit board may be flexible to enable the lighting system **102** to bend to conform to uneven surfaces.

The circuit board may, for example, be partially encapsulated in an elastomer, such as a silicone and/or a rubber. The elastomer may insulate the circuit board and/or components mounted to the circuit board, such as the LED assembly **106** and the connector **104**, from the external environment. Thereby, the lighting system **100** may be employed in both indoor and outdoor applications.

Each of FIGS. 2A-2C shows a cross-section of an example implementation of the lighting system **102** shown in FIG. 1 that is designed to provide white light with a high CRI. As shown, the lighting system includes a tray **202** that is configured to receive a circuit board **210** with an LED **212** mounted thereon. An elastomer **214** may, for example, be potted over the circuit board **210** to partially encapsulate the circuit board **210** and secure the circuit board **210** to the lighting system. A photo-luminescent material layer **216** is disposed on top of the elastomer **214** and may be configured to change a characteristic of the light emitted by the LED **212** such as CRI, R9 color rendering value, and/or CCT. Another elastomer **218** may be potted over the photo-luminescent material layer **216** to separate the photo-luminescent material layer **216** from the environment.

The tray **202** may include a base **206** onto which the circuit board **210** may be disposed and sidewalls **208** that extend upward from the base **206**. It is understood throughout this specification that the term "upward" denotes an orientation of a sidewall relative to a base. The sidewalls **208** may be parallel to each other and/or perpendicular to the base **206**. The base **206** may form a bottom surface of the lighting system while the sidewalls **208** may form the lateral surfaces of the lighting system. The tray **202** may be constructed from any of a variety of materials. For example, the tray **202** may be constructed from an elastomer such as silicone. In this example, the elastomer may be manufactured through an extrusion process (e.g., a silicone extrusion process). The elastomer employed to construct the tray **202** may be different from the elastomers **214** and/or **218**. For example, the elastomer in the tray **202** may be more porous than the elastomers **214** and/or **218** to provide greater heat dissipation capability to dissipate heat from the circuit board **210** and/or the LED **212**.

In some embodiments, the tray **202** may include an overhang **220** that extends from one of the sidewalls **208** towards another sidewall **208** as shown in FIG. 2C. The overhang **220** may be parallel to the base **206**. In these embodiments, the LED **212** may be mounted to the circuit board **210** at a location that is under the overhang **220**. Thereby, the LED **212** may be obscured from view. Further, the overhang **220** may be long enough such that the light ray **222** emitted at the maximum emission angle of the LED **212** does not directly leave the lighting system. Instead, the light ray **222** may reach the top surface of the elastomer **218** at such an angle that the light ray **222** is reflected back from the top surface (e.g., because the angle is above the critical angle for total internal reflection (TIR)). Thereby, the light emitted

12

by the LED **212** may be reflected off of a surface in the lighting system before leaving the top surface of the elastomer **218**.

The circuit board **210** may be configured to electrically couple the LED **212** to one or more other components. For example, the circuit board may include conductors that electrically couple the LED **212** to a connector mounted to the circuit board (e.g., connector **204** in FIG. 1A). The circuit board **210** may be, for example, an FR4 printed circuit board (PCB). Additionally (or alternatively), the circuit board may be a flexible circuit board **210** to permit the lighting system to bend without breaking.

The LED **212** may be configured to emit broad spectrum light, such as light with a spectrum that is at least 200 nanometers (nm) in size (e.g., 200 nm, 225 nm, 250 nm, 275 nm, 300 nm, etc.). The broad spectrum light may be, for example, white light. The LED **212** may be construed in any of a variety of ways to generate the broad spectrum light. For example, the LED **212** may be constructed as a white phosphor-converted LED. It should be appreciated that the LED **212** may be configured to emit narrow spectrum light in some embodiments, such as light with a spectrum that is less than 200 nm in size. For example, the LED **212** may be constructed as a blue LED without a phosphor coating.

The elastomer **214** may be potted over the circuit board **210** to hold the circuit board **210** in-place in the lighting system. The elastomer **214** may, in some embodiments, be in direct contact with the LED **212**. Allowing the elastomer **214** to be in direct contact with the LED **212** may, for example, change the spectrum of the light emitted by the LED **212** because the elastomer **214** may have a refractive index that is higher than air (e.g., a refractive index of approximately 1.5). FIG. 7 shows the difference between the spectrums of the light emitted from the LED **212** when the light is emitted directly into elastomer **214** instead of air. In particular, a first line **702** shows the spectrum of light from the LED **212** that is emitted directly into elastomer **214** and a second line **704** shows the spectrum of light from the LED **212** that is emitted directly into air. As shown, the blue component between approximately 425 nm and 475 nm of the light from the LED **212** is substantially increased when the light is emitted directly into the elastomer **214**. The additional blue component of the light from the LED **212** may be advantageously employed to excite photo-luminescent materials in the photo-luminescent material layer **216**. Thereby, the blue component of the light from the LED **212** may be converted into light with longer wavelengths, such as yellow and/or red light, by the photo-luminescent material layer **216**.

The photo-luminescent material layer **216** may include one or more photo-luminescent materials that are configured to emit light in a first spectrum in response to being excited by light in a second different spectrum. For example, the photo-luminescent materials may be configured to absorb light with a shorter wavelength, such as blue light, and emit light with a longer wavelength, such as yellow and/or red light. The particular photo-luminescent materials and their respective proportions in the photo-luminescent material layer **216** may depend on, for example, the desired spectrum of light to be generated by the lighting system. Example photo-luminescent materials include a phosphor (e.g., neodymium-doped yttrium aluminum garnet (Nd: YAG)), a silicate, and a quantum dot (e.g., a Cadmium free quantum dot). The photo-luminescent material may be an organic material and/or include organic compounds such as any of the color conversion materials described in U.S. Patent Publication No. 2017/0137627. Additionally (or alternatively,

tively), the photo-luminescent material may be an inorganic material and/or include inorganic compounds.

The photo-luminescent material layer **216** may be constructed in any of a variety of ways. For example, the photo-luminescent material layer **216** may be formed as a sheet (e.g., as a foil) that is sandwiched between elastomer **214** and **218** and includes a set of one or more photo-luminescent materials as shown in FIGS. **2A** and **2C**. In another example, the photo-luminescent material layer **216** may be constructed as a plurality of separate elements (e.g., separate circular sheets) that are each disposed over an LED on the circuit board **210**. Thereby, the separate elements may be uniquely configured for the specific LED that the respective element is disposed over (e.g., a first element with a first composition may be disposed over a first LED and a second element with a second, different composition may be disposed over a second, different LED). In yet another example, the photo-luminescent material layer **216** may include a set of one or more photo-luminescent materials distributed through a polymer (e.g., silicone) that is sandwiched between elastomer **214** and **218** as shown in FIG. **2B**.

FIG. **8** shows the changes to the light spectrum that may be created by the photo-luminescent materials in the photo luminescent layer **216**. In particular, a first line **802** shows the spectrum of light from a white phosphor-converted LED without any change from a photo-luminescent material, a second line **804** shows the spectrum of light from the white phosphor-converted LED after passing through a first quantum dot material, and a third line **806** shows the spectrum of light from the white phosphor-converted LED after passing through a different, second quantum dot material. A summary of the changes in the spectrum caused by each of the first and second quantum dot materials is shown in Table 1 below:

TABLE 1

Element in FIG. 8	Light Source	CCT	CRI	R9
802	No photo-luminescent material	4000	86	25
804	First Quantum Dot material	3300	91	45
806	Second Quantum Dot material	2000	96	80

As shown, the first quantum dot material increases the CRI, CCT, and R9 color rendering value of the white light by reducing the blue component of the white light and the second quantum dot material further increases the CRI, CCT, and R9 color rendering value of the white light by further reducing the blue component of the white light in addition to increasing the red component of the white light.

The composition of the photo-luminescent material layer **216** may be customized to achieve a desired light spectrum for any of a variety of different applications. For example, the photo-luminescent material layer **216** may be designed to provide light suitable for black light units (BLUs) in display applications. In this example, the LED **212** may be configured to emit narrow spectrum light (e.g., blue light) and the photo-luminescent material layer **216** may be configured to absorb some of the blue light and, in turn, emit light with a longer wavelength (e.g., green, yellow, orange, and/or red light). FIG. **9** shows the spectrum of light emitted by each component of such a lighting system that employs a red quantum dot material, a green quantum dot material, and yellow green (e.g., CIE Color Coordinates of $x=3.14$ and $y=0.584$) phosphor material in the photo-luminescent material layer **216**. The ratio of the red quantum dot material to the green quantum dot material may be 80:20 (i.e., there

are 80 parts of red quantum dot material for every 20 parts of green quantum dot material). In FIG. **9**, line **902** shows the spectrum of light from a blue LED, line **904** shows the spectrum light from the yellow green phosphor material, line **906** shows the spectrum of light emitted by the excited red quantum dot material, line **908** shows the spectrum of light emitted by the excited green quantum dot material, and line **910** that shows the resulting spectrum of the lighting system (e.g., a combination of the spectrums of the blue LED, the phosphor, the red quantum dot material, and the green quantum dot material). Other combinations of materials may be employed to achieve a similar spectrum. For example, the green quantum dot material may be removed entirely and replaced with additional red quantum dot material. Thereby, the photo-luminescent layer **216** may omit the green quantum dot material altogether.

The photo-luminescent material layer **216** for a lighting system being employed in BLUs where the LED **212** emits light with a broad spectrum (instead of a narrow spectrum) may be designed differently. FIG. **10** shows the spectrum of another example lighting system suitable for a BLU that is constructed using a broad spectrum LED. In particular, line **1002** shows the light spectrum of a white phosphor-converted LED formed from a blue LED coated in a yellow phosphor coating and line **1004** shows the light spectrum of a white phosphor-converted LED formed from a blue LED coated in a red phosphor coating paired with a photo-luminescent material in the photo-luminescent material layer **216** that is configured to absorb some of the blue light and emit green light. As shown, the light spectrum of the light from the phosphor-converted LED and photo-luminescent material layer **216** produces light with a warmer color temperature than employing the white phosphor-converted LED alone.

As should be appreciated from the foregoing description, the spectrum of a lighting system may be adjusted to achieve a desired light spectrum by varying the types and/or concentrations of photo-luminescent materials in the photo-luminescent material layer **216**. For example, the red component of the light emitted by the lighting system may be increased by adding a red quantum dot material to the photo-luminescent material layer **216**. Thereby, the lighting system described herein may be employed to create light for any of a variety of applications.

In some embodiments, the composition of the photo-luminescent material layer **216** may be designed for grow light applications. Thereby, the lighting systems described herein may be constructed as grow lights configured to stimulate plant growth. In these embodiments, the spectrum of the light generated by the lighting system may, for example, closely match the spectrum of light absorbed by plants. Such a spectrum may be achieved by, for example, selecting a narrow spectrum LED that emits light with a wavelength below 500 nm (e.g., a blue LED) or a broad spectrum LED that emits a substantial portion light with a wavelength below 500 nm (e.g., a phosphor-converted white LED) for the LED **212** and adding photo-luminescent materials to the photo-luminescent material layer **216** that absorb some of the light below 500 nm from the LED and emit orange and/or red light (e.g., light with a spectrum between 600 nm and 700 nm). Further, the LED **212** may be in direct contact with the elastomer **214** to increase the component of short wavelength light (e.g., light with a wavelength below 500 nm) as described above with reference to FIG. **7**. FIG. **11** shows the spectrum of light emitted by an example grow light compared with the spectrum of light absorbed by different chlorophylls and beta carotene. In particular, line

15

1102 shows the spectrum of light absorbed by beta carotene, line 1104 shows the spectrum of light absorbed by chlorophyll A, line 1106 shows the spectrum of light absorbed by chlorophyll B, and line 1108 shows the spectrum of light the example grow light. As shown, the spectrum of the light from the example grow light closely approximates the light absorbed by chlorophyll A and chlorophyll B. Further, the spectrum includes little light in portions of the spectrum that a plant would not absorb (e.g., between 525 and 600 nm) to improve the power efficiency of the grow light.

As should be appreciated from the foregoing, the photo-luminescent material layer 216 may include any of a variety of photo-luminescent materials. Further, the particular composition of the photo-luminescent material layer 216 may vary based on the desired light spectrum, which may vary based on the particular application.

Returning to FIGS. 2A-2C, the photo-luminescent material layer 216 may be covered by the elastomer 218. The elastomer 218 may be, for example, silicone. The elastomer 218 may have the same or different characteristics, such as refractive index, relative to the elastomer 214. For example, the elastomer 218 may have a different (e.g., higher or lower) refractive index than the elastomer 214.

It should be appreciated that photo-luminescence materials may be integrated into portions of the lighting system separate from the photo-luminescence material layer 216. For example, the elastomer 218 and/or the elastomer 214 may include a photo-luminescence material such as a phosphor. Additionally (or alternatively), other materials separate from photo-luminescence materials, such as scattering particles and/or pigments, may be integrated into any of the following components of the lighting system: the elastomer 214, the elastomer 218, the photo-luminescence material layer 216, and/or the tray 202.

The lighting system shown in FIGS. 2A-2C may be manufactured in any of a variety of ways. The lighting system may be manufactured by, for example, performing the following steps: (1) mounting the electronic components (e.g., the LED 212) to the circuit board 210; (2) inserting the circuit board into the tray 202; (3) potting the elastomer 214 over the circuit board 210 in the tray 202; (4) depositing the photo-luminescent material layer 216 on the elastomer 214; and (5) potting the elastomer 218 over the photo-luminescent material layer 216; and (6) packaging the lighting system.

As discussed above, the lighting system may be configured to provide a line of light in some embodiments. In some examples, the linear lighting systems disclosed herein may provide a line of light along the linear lighting system having a substantially uniform intensity. Thereby, the location of the LEDs within the lighting system may be indistinguishable to a viewer. These lighting systems may be employed in any of a variety of direct view applications including architectural lighting, commercial lighting, hospitality lighting, residential lighting, office lighting, hallway lighting, bath lighting, and vanity lighting. For example, the lighting system may be employed in 1 inch slot to create a glare free, architectural lighting accent. These lighting systems may be constructed as connected strips, such as the linear lighting systems shown in FIGS. 1A and 1B, that may advantageously allow the lighting systems to achieve continuous runs in various installation situations such as: outside corners, inside corners, T-connections, and fully seamless corners.

The lighting system may employ any of a variety of systems to provide a line of light, such as lenses and diffusive elements. FIGS. 3 and 4 shows an example implementation of lighting system 102 that provides a line of

16

light. In particular, FIG. 3 shows an example cross-section of the example lighting system and FIG. 4 shows a deconstructed version of the example lighting system. As shown, the lighting system includes a tray 302 into which a circuit board 304 with LEDs 306 mounted thereon may be disposed. The tray 302, circuit board 304, and LEDs 306 may be constructed similarly (or identically) to the tray 202, the circuit board 210, and the LED 212, respectively, described above. The circuit board 306 may include a connector 402 that may electrically couple the LEDs 306 mounted on the circuit board 306 to an external power source. A lens 308 may be disposed over the LEDs 306 (e.g., so as to provide an air gap between the LEDs 306 and an inner surface of the lens 308) and configured to increase a maximum emission angle of light from the LED 306. The lens 308 may, for example, be partially encapsulated in an elastomer 312 so as to expose a top portion of the lens 308 to air. A sleeve 310 may be slid over the tray 302 so as to provide an air gap 314 between the top of the lens 308 and the top side of the sleeve 310. A diffuser 316 may be disposed on the sleeve 310 that is configured to diffuse light from the LEDs 308.

The lenses 308 may be configured to increase a maximum emission angle of light from the LEDs 308. For example, the maximum emission angle of light from the LEDs 308 may be no more than ± 60 degrees and the lens 308 may increase the maximum emission angle of the light from the LEDs to at least ± 80 degrees. Additionally, the lens 308 may be configured to increase a light intensity at higher angles. For example, the light intensity from the LED 306 at ± 60 degrees may be a first value and the lens 308 may increase the light intensity at ± 60 degrees to a second value that is higher than the first value. An example construction of the lenses 308 is shown in FIG. 5 by lens 504 that is disposed over the LED 502. As shown, the lens 504 includes a cavity 503 into which the LED 502 may be disposed. The cavity 503 may form an air gap between the LED 502 and an inner surface of the lens 504. Additional materials may be disposed in the cavity 503 between the LED 502 and the inner surface of the lens 504 that are configured to change a characteristic of the light from the LED such as any of the scattering particles, photo-luminescence materials, and/or pigments described herein. These materials may be, for example, integrated into a polymer to form a monolithic element that may be disposed between the LED 502 and the inner surface of the lens 504.

The lens 504 is configured to increase the maximum angle of emission to ± 80 degrees resulting in light being emitted over a span of 160 degrees in the light distribution pattern 500. It should be appreciated that the example construction of the lens 308 in FIG. 5 is only one possible implementation and that the lens 504 may be implemented in any of a variety of ways.

The elastomer 312 may encapsulate the top surface of the circuit board 304 and only a portion of the lenses 308. For example, the elastomer 312 may only be in contact with a bottom portion of the outer surface of the lens 308 while leaving an upper portion of the outer surface of the lens 308 exposed to air. Leaving a portion of the lens 308 may advantageously improve the performance the lens by, for example, maximizing a difference in refractive index of the lens 308 itself and the material into which the light from the lens propagates (e.g., air). The elastomer 312 may be constructed from any of a variety of materials, such as silicone. The elastomer 312 may have a lower refractive index such as a refractive index of approximately 1.4.

The sleeve 310 may be constructed as to be a hollow rectangle prism that surrounds the tray 302 and the compo-

nents mounted therein. The sleeve **310** may be constructed from an elastomer, such as silicone. The sleeve **310** may be constructed from an extruding process (e.g., a silicone extruding process).

The diffuser **316** may be constructed to diffuse the light from the lenses **308** so as to provide a line of light. In some examples, the linear lighting systems disclosed herein may provide a line of light along the linear lighting system having a substantially uniform intensity. The diffuser **316** may be configured to diffuse light using any of a variety of techniques. In some embodiments, the diffuser **316** may include scattering particles that are configured to scatter light that are distributed throughout an elastomer (e.g., silicone) with a different (e.g., lower or higher) refractive index than the elastomer **312**. For example, the refractive index of the elastomer **312** may have a refractive index of approximately 1.4 and the refractive index of the elastomer in the diffuser **316** may be approximately 1.5. The scattering particles may advantageously allow the diffuser **316** to be thin while still allowing the diffuser to effectively diffuse the light from the LEDs. Any of a variety of scattering particles may be employed such as Barium Sulfate (BaSO₄) and/or Titanium Dioxide (TiO₂). Additionally (or alternatively), the diffuser **316** may include one or more materials that are configured to change a characteristic of the light such as any of the photo-luminescence materials described herein and/or pigments.

The lighting system shown in FIGS. **3** and **4** may be manufactured in any of a variety of ways. The lighting system may be manufactured by, for example, performing the following steps: (1) mounting the electronic components (e.g., the LED **306** and/or the connector **402**) to the circuit board **304**; (2) inserting the circuit board into the tray **302**; (3) placing the lenses **308** over the LEDs **306**; (4) potting the elastomer **312** over the circuit board **304** in the tray **302**; (5) inserting the tray **302** into the sleeve **310**; (6) potting the material that includes the diffuser **316** (e.g., an elastomer with scattering particles, photo-luminescence materials, and/or pigments) over the sleeve **310**; and (7) packaging the lighting system.

It should be appreciated that the lighting systems described herein may be designed to achieve any of a variety of desired light output characteristics. For example, the lighting systems described herein may be designed for a range of CCT values such as, 2,700 degrees K, 3,000 degrees K, 3,500 degrees K, 4,000 degrees K, and 5,000 degrees K; a range of CRI values such as any value between 90 and 100; a range of R9 color rendering values such as any value between 90 and 100; a range of light intensity values such as a range of 270-480 lumens per 12 inch section of lighting systems (e.g., per pair of two 6 inch lighting systems); a range of power consumption levels such as any wattage up to 9 Watts; and a range of voltage levels such as 24 Volts. Further, the lighting systems may be configured to be dimmable via any of a variety of external dimmable electronic drivers. Still yet further, the lighting system may be configured to provide light within a 3-step Macadam ellipse and/or a 2-step Macadam ellipse of a predefined color coordinate. For example, the linear lighting system may be configured as a lighting strip configured to provide light within a 3-step Macadam ellipse and/or a 2-step Macadam ellipse of a predefined color coordinate along the length of the lighting strip.

Examples **[100]**, **[200]**, **[300]**, **[400]** of lighting systems are discussed herein in connection with FIGS. **1-11**. Examples **[1200]** and **[1600]** of lighting systems are discussed herein in connection with FIGS. **12-17**. It is under-

stood throughout this specification that a lighting system **[100]**, **[200]**, **[300]**, **[400]** may include any of the features or combinations of features that are disclosed in connection with the examples **[1200]** or **[1600]** of lighting systems. It is further understood throughout this specification that a lighting system **[1200]** may include any of the features or combinations of features that are disclosed in connection with the Examples **[100]**, **[200]**, **[300]**, **[400]** or **[1600]** of lighting systems. It is additionally understood throughout this specification that a lighting system **[1600]** may include any of the features or combinations of features that are disclosed in connection with the Examples **[100]**, **[200]**, **[300]**, **[400]** or **[1200]** of lighting systems. Accordingly, FIGS. **1-11** and the entireties of the discussions of the examples **[100]**, **[200]**, **[300]**, **[400]** of lighting systems are hereby incorporated into the following discussions of the examples **[1200]** and **[1600]** of implementations of the lighting system. In addition, the entirety of the discussion below of the examples **[1600]** of lighting systems is hereby incorporated into the following discussion of the examples **[1200]** of implementations of the lighting system; and the entirety of the discussion below of the examples **[1200]** of lighting systems is hereby incorporated into the following discussion of the examples **[1600]** of implementations of the lighting system.

Referring now to FIGS. **12-15**, FIG. **12** presents a cross-sectional view of an example of a linear lighting system according to some embodiments of the technology described herein. FIG. **13** presents a top view, taken from the direction of the arrow **13**, of the example of a linear lighting system shown in FIG. **12**. FIG. **14** presents a cross-sectional view of another example of the linear lighting system **[1200]** according to some embodiments of the technology described herein. FIG. **15** presents a top view, taken from the direction of the arrow **15**, of the another example of the linear lighting system **[1200]** shown in FIG. **14**. Referring to FIGS. **12-15**, a linear lighting system **[1200]** is provided, including a tray **[1202]** being extended along elongation directions **[1204]** and having a base forming a bottom interior surface **[1207]** of the tray **[1202]**, a first sidewall **[1208]** extending upward from the base **[1206]** towards an emission aperture **[1210]** of the linear lighting system **[1200]**, and a second sidewall **[1212]** being spaced apart across the base **[1206]** from the first sidewall **[1208]** and extending upward from the base **[1206]** towards the emission aperture **[1210]** of the linear lighting system **[1200]**. In these examples, the linear lighting system **[1200]** further includes: a circuit board **[1214]** being located on the first sidewall **[1208]** in the tray **[1202]**; a plurality of light emitting diodes (LEDs) **[1216]** being located on the circuit board **[1214]** and mutually spaced apart on the first sidewall **[1208]** along the elongation directions **[1204]** of the tray **[1202]** and being positioned for light emissions in directions **[1215]** facing toward the second sidewall **[1212]**; and a protuberance **[1218]** being located on the base **[1206]** and interposed between the LEDs **[1216]** and the second sidewall **[1212]**, the protuberance **[1218]** being positioned for diverting light emissions from the plurality of the LEDs **[1216]** toward the emission aperture **[1210]**.

In some examples **[1200]** of the lighting system, the tray **[1202]** may be triaxially or biaxially flexible. Referring to FIGS. **12-15**, throughout this specification “triaxial” flexibility denotes flexibility in the directions of the arrows X, Y and Z; and “biaxial” flexibility denotes flexibility in two of the three directions of the arrows X, Y and Z. In further examples **[1200]** of the lighting system, the circuit board

[1214] may be triaxially or biaxially flexible in the directions of the arrows X, Y and Z.

In some examples [1200] of the lighting system, the protuberance [1218] shown in FIGS. 12-15 may have an angled or convex surface [1220] for diverting light emissions from the LEDs [1216] toward the emission aperture [1210]. In some examples [1200] of the lighting system, the convex surface [1220] of the protuberance [1218] shown in FIGS. 12-13 may be smoothly convex. In further examples [1200] of the lighting system, the angled surface of the protuberance [1218] may have a geometric prismatic shape as shown in FIGS. 14-15. In additional examples [1200] of the lighting system, the geometric prismatic shape of the protuberance [1218] may include a triangular prism as shown in FIGS. 14-15, or (not shown) may be likewise substituted by a rectangular prism, a pentagonal prism, or a hexagonal prism. In additional examples [1200] of the lighting system, the protuberance [1218] may include a raised mound [1218] as shown in FIGS. 12-13 and located on the base [1206] and extending along the elongation directions [1204] of the tray [1202], the raised mound [1218] being positioned to intersect pathways of some of the light emissions from the LEDs [1216]. In other examples [1200] of the lighting system, the protuberance [1218] may include a plurality of raised mounds [1218] as shown in FIGS. 14-15 being located on the base [1216] and being mutually spaced apart along the elongation directions [1204] of the tray [1202], each one of the plurality of the raised mounds [1218] being positioned to intersect pathways of some of the light emissions from the LEDs [1216]. In some examples [1200] of the lighting system, each one of the plurality of the raised mounds [1218] as shown in FIGS. 14-15 may have an angled or convex surface [1220] for diverting light emissions from the LEDs [1216] toward the emission aperture [1210]. In further examples [1200] of the lighting system, each one of the convex surfaces [1220] of the raised mounds [1218] as shown in FIGS. 14-15 may be smoothly convex. In additional examples [1200] of the lighting system, each one of the angled surfaces [1220] of the raised mounds [1218] may have a geometric prismatic shape as shown in FIGS. 14-15. In some examples [1218] of the lighting system, the geometric prismatic shape of each one of the protuberances [1218] may include a triangular prism as shown in FIGS. 14-15, or may likewise be substituted by a rectangular prism, a pentagonal prism, or a hexagonal prism. In some examples [1200] of the lighting system, the protuberance [1218] as shown in FIGS. 14-15 may have a highly light reflective surface [1220] for reflecting light emissions toward the emission aperture [1210]. In further examples [1200] of the lighting system, the protuberance [1218] as shown in FIGS. 14-15 may be a light-transmissive protuberance [1218] having a higher refractive index than air, for refracting light emissions toward the emission aperture [1210].

In additional examples [1200] of the lighting system as shown in FIGS. 12-15, the linear lighting system may include another circuit board [1222] being located on the second sidewall [1212] in the tray [1202], and may include a further plurality of light emitting diodes (LEDs) [1224] being located on the another circuit board [1222] and mutually spaced apart on the second sidewall [1212] along the elongation directions [1204] of the tray [1202] and being positioned for further light emissions in directions [1225] facing toward the first sidewall [1208]; and the protuberances [1218] may be positioned for diverting further light emissions from the further plurality of LEDs [1224] toward the emission aperture [1210]. In further examples [1200],

the circuit board [1222] may be triaxially or biaxially flexible. In other examples [1200] of the lighting system, an interior [1207] of the tray [1202] may have a highly light reflective surface.

In some examples [1200], the linear lighting system may further include a plurality of lenses [1226] as shown in FIGS. 12-15, each one of the plurality of lenses [1226] being located over a respective one of the plurality of the LEDs [1216] for increasing a maximum light emission angle of the LED [1216] from a first value to a second value that is larger than the first value. As an example, each one of a plurality of lenses [1226] may be positioned on a one of the LEDs [1216]. In further examples, the linear lighting system [1200] may further include a diffuser located over the plurality of the lenses [1226]; and the plurality of the lenses [1226] and the diffuser may cause the linear lighting system [1200] to emit the light emissions as a line of light. In some examples, the linear lighting systems [1200] disclosed herein may provide a line of light extended in the directions [1204] along the linear lighting system [1200] having a substantially uniform intensity. It is understood throughout this specification that a diffuser may be formed as, for example, a sheet positioned in the tray [1202] facing and over the LEDs [1216], or a volumetric body that fills a portion or all of the tray [1202], or a sheet positioned inside the tray [1202] having one side facing the bottom [1207] and another opposite side facing the emission aperture [1210], or a sheet placed over the top of the tray [1202]. In additional examples [1200] of the lighting system, the first value of the maximum light emission angle may be no more than about sixty (60) degrees and the second value of the maximum emission angle may be at least about eighty (80) degrees. In other examples [1200], the linear lighting system may include a further plurality of lenses [1228] as shown in FIGS. 12-15, each one of the further plurality of lenses [1228] being located over a respective one of the another plurality of the LEDs [1224] for increasing a maximum light emission angle from a first value to a second value that may be larger than the first value. In some examples, the linear lighting system [1200] as shown in FIGS. 12-15 may further include another diffuser located over the further plurality of the lenses [1228], and the further plurality of the lenses [1228] and the another diffuser may cause the linear lighting system [1220] to emit the further light emissions as a line of light. In some examples, the linear lighting systems [1200] disclosed herein may provide a line of light extended in the directions [1204] along the linear lighting system having a substantially uniform intensity.

Referring now to FIGS. 16-17, FIG. 16 presents a cross-sectional view of an example of another linear lighting system [1600] according to some embodiments of the technology described herein. FIG. 17 presents a top view, taken from the direction of the arrow 17, of the example of a linear lighting system [1600] shown in FIG. 16. Referring to FIGS. 16-17, a linear lighting system [1600] is provided, having a tray [1602] being extended along elongation directions [1604] and having a base [1606] forming a bottom interior surface [1607] of the tray [1602], a first sidewall [1608] including an angled reflective face [1609] and extending upward from the base [1606] towards an emission aperture [1610] of the linear lighting system, and a second sidewall [1612] including a further angled reflective face [1611] and extending upward from the base [1606] towards the emission aperture [1610] of the linear lighting system, the second sidewall [1612] being spaced apart across the base [1606] from the first sidewall [1608].

In some examples [1600], the angled reflective face(s) [1609] may form a portion but not all of the first sidewall [1608], and the further angled reflective face(s) [1611] may form a portion but not all of the second sidewall [1612]. In further examples [1600], the second sidewall [1612] may, referring to FIG. 16, include an angled reflective face [1611] forming an obtuse angle relative to the direction of the arrow [1625], for reflecting light emissions in the direction of an arrow [1613] toward the emission aperture [1610]. In additional examples [1600], the second sidewall [1612] may, referring to FIG. 16, include another angled reflective face [1611] forming an acute angle relative to the direction of the arrow [1625], for likewise reflecting light emissions toward the emission aperture [1610]. In further examples [1600] (not all shown), the first or second sidewalls [1608], [1612] may each independently include one or more angled reflective faces [1609], [1611] each independently forming either an acute or obtuse angle relative to the direction of an arrow [1615] or [1625].

In the example [1600], the linear lighting system further includes: a circuit board [1614] being located on the first sidewall [1608] in the tray [1602], and another circuit board [1622] being located on the second sidewall [1612] in the tray [1602]; and a plurality of light emitting diodes (LEDs) [1616] being located on the circuit board [1614] and mutually spaced apart on the first sidewall [1608] along the elongation directions [1604] of the tray [1602] and being positioned for light emissions in directions [1615] facing toward the second sidewall [1612], and another plurality of light emitting diodes (LEDs) [1624] being located on the another circuit board [1622] and mutually spaced apart on the second sidewall [1612] along the elongation directions [1604] of the tray [1602] and being positioned for further light emissions in directions [1625] facing toward the first sidewall [1608]; wherein the further angled reflective face [1611] of the second sidewall [1612] is positioned for reflecting light emissions from the plurality of the LEDs [1616] toward the emission aperture [1610]; and wherein the angled reflective face [1608] of the first sidewall [1608] is positioned for reflecting further light emissions from the another plurality of the LEDs [1624] toward the emission aperture [1610].

In some examples of the another implementation [1600], the tray [1602] may be triaxially or biaxially flexible. In further examples of the another implementation [1600], the circuit board [1614] may be triaxially or biaxially flexible. In additional examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall [1608] may be oriented at an acute or obtuse angle relative to the directions [1625] of further light emissions toward the first sidewall [1608], and the further angled reflective face [1611] of the second sidewall [1612] may be oriented at another acute or obtuse angle relative to the directions [1615] of the light emissions toward the second sidewall [1612]. It is understood throughout this specification that an obtuse angle is an angle of greater than 90 degrees and of less than 180 degrees. In other examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall [1608] may be oriented at an acute angle of less than about 45 degrees relative to the directions [1625] of further light emissions toward the first sidewall [1608], and the further angled reflective face [1611] of the second sidewall [1612] may be oriented at another acute angle of less than 45 degrees relative to the directions [1615] of the light emissions toward the second sidewall [1612]. In further examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall [1608] may be

oriented at an obtuse angle of between about 90 degrees and about 180 degrees relative to the directions [1625] of further light emissions toward the first sidewall [1608], and the further angled reflective face [1611] of the second sidewall [1612] may be oriented at another obtuse angle of between about 90 degrees and about 180 degrees relative to the directions [1615] of the light emissions toward the second sidewall [1612]. In some examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall may include a reflective bar [1609] extended along the elongation directions [1604] of the tray [1602] and located below the plurality of the LEDs [1616] in the tray [1602]. In further examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall [1608] may include a reflective bar [1609] extended along the elongation directions [1604] of the tray [1602] and located above the plurality of the LEDs [1616] in the tray. In additional examples [1600] of the another implementation, the angled reflective face [1609] of the first sidewall [1608] may be formed by a plurality of reflective rings [1909] each encircling a respective one of the plurality of LEDs [1616] in the tray [1602]. In other examples [1600] of the another implementation, the plurality of the reflective rings [1609] may have reflective surfaces being oriented at acute or obtuse angles relative to the directions [1625] of further light emissions toward the first sidewall [1608]. In some examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1612] may be formed by a further plurality of reflective rings [1611] each encircling a respective one of the another plurality of LEDs [1624] in the tray. In further examples [1600] of the another implementation, the further plurality of reflective rings [1611] may have reflective surfaces being oriented at further acute or obtuse angles relative to the directions [1615] of light emissions toward the second sidewall [1612].

In further examples of the another implementation [1600], the circuit board [1622] may be triaxially or biaxially flexible. In additional examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1612] may be oriented at an acute or obtuse angle relative to the directions [1615] of light emissions toward the second sidewall [1612], and the angled reflective face [1609] of the first sidewall [1608] may be oriented at another acute or obtuse angle relative to the directions [1625] of the further light emissions toward the first sidewall [1608].

In other examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1612] may be oriented at an acute angle of less than about 45 degrees relative to the directions [1615] of light emissions toward the second sidewall [1612], and the angled reflective face [1609] of the first sidewall [1608] may be oriented at another acute angle of less than 45 degrees relative to the directions [1625] of the further light emissions toward the first sidewall [1608]. In further examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1608] may be oriented at an obtuse angle of between about 90 degrees and about 180 degrees relative to the directions [1615] of light emissions toward the second sidewall [1612], and the angled reflective face [1609] of the first sidewall [1608] may be oriented at another obtuse angle of between about 90 degrees and about 180 degrees relative to the directions [1625] of the further light emissions toward the first sidewall [1608]. In some examples [1600] of the another implementation, the further angled reflective face [1611] of the second

sidewall [1612] may include a reflective bar [1611] extended along the elongation directions [1604] of the tray [1602] and located below the plurality of the LEDs [1624] in the tray [1602]. In further examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1612] may include a reflective bar [1611] extended along the elongation directions [1604] of the tray [1602] and located above the plurality of the LEDs [1624] in the tray [1602]. In additional examples [1600] of the another implementation, the further angled reflective face [1611] of the second sidewall [1612] may be formed by a plurality of reflective rings [1611] each encircling a respective one of the plurality of LEDs [1624] in the tray [1602]. In other examples [1600] of the another implementation, the plurality of the reflective rings [1611] may have reflective surfaces being oriented at acute or obtuse angles relative to the directions [1615] of light emissions toward the second sidewall [1612].

In some examples [1600], the linear lighting system may further include a plurality of lenses [1626] as shown in FIGS. 16-17, each one of the plurality of lenses [1626] being located over a respective one of the plurality of the LEDs [1616] for increasing a maximum light emission angle of the LED [1616] from a first value to a second value that is larger than the first value. As an example, each one of a plurality of lenses [1626] may be positioned on a one of the LEDs [1616]. In further examples, the linear lighting system [1600] may further include a diffuser located over the plurality of the lenses [1626]; and the plurality of the lenses [1626] and the diffuser may cause the linear lighting system [1600] to emit the light emissions as a line of light. In some examples, the linear lighting systems [1600] disclosed herein may provide a line of light extended in the directions [1604] along the linear lighting system [1600] having a substantially uniform intensity. The diffuser may be formed as, for example, a sheet positioned in the tray [1602] facing and over the LEDs [1616], or a volumetric body that fills a portion or all of the tray [1602], or a sheet positioned inside the tray [1602] having one side facing the bottom [1607] and another opposite side facing the emission aperture [1610], or a sheet placed over the top of the tray [1602]. In additional examples [1600] of the lighting system, the first value of the maximum light emission angle may be no more than about sixty (60) degrees and the second value of the maximum emission angle may be at least about eighty (80) degrees. In other examples [1600], the linear lighting system may include a further plurality of lenses [1628], each one of the further plurality of lenses [1628] being located over a respective one of the another plurality of the LEDs [1624] for increasing a maximum light emission angle from a first value to a second value that may be larger than the first value. In some examples, the linear lighting system [1600] may further include another diffuser located over the further plurality of the lenses [1628], and the further plurality of the lenses [1628] and the another diffuser may cause the linear lighting system [1600] to emit the further light emissions as a line of light. In some examples, the linear lighting systems [1600] disclosed herein may provide a line of light extended in the directions [1604] along the linear lighting system having a substantially uniform intensity.

The linear lighting systems disclosed herein may be installed indoors on walls, ceilings, or floors, and may also be installed on building exteriors, as examples. Further, the linear lighting systems may be utilized for achieving particular lighting needs, such as lighting for offices, industrial environments, kitchens, building exteriors, landscape lighting, and vehicle lighting. The protuberances and angled

reflective faces of the linear lighting systems disclosed herein may redirect some of the light emissions of the LEDs, thereby reducing glare that may be caused by light being directly emitted from the linear lighting systems. Various aspects of the present disclosure may be used alone, in combination, or in a variety of arrangements not specifically discussed in the embodiments described in the foregoing and is therefore not limited in its application to the details and arrangement of components set forth in the foregoing description or illustrated in the drawings. For example, aspects described in one embodiment may be combined in any manner with aspects described in other embodiments.

Use of ordinal terms such as “first,” “second,” “third,” etc., in the claims to modify a claim element does not by itself connote any priority, precedence, or order of one claim element over another or the temporal order in which acts of a method are performed, but are used merely as labels to distinguish one claim element having a certain name from another element having a same name (but for use of the ordinal term) to distinguish the claim elements.

The terms “approximately,” “about,” and “substantially” may be used to mean within $\pm 20\%$ of a target value in some embodiments, within $\pm 10\%$ of a target value in some embodiments, within $\pm 5\%$ of a target value in some embodiments, and yet within $\pm 2\%$ of a target value in some embodiments. The terms “approximately,” “about,” and “substantially” may include the target value.

Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having,” “containing,” “involving,” and variations thereof herein, is meant to encompass the items listed thereafter and equivalents thereof as well as additional items.

While the present invention has been disclosed in a presently defined context, it will be recognized that the present teachings may be adapted to a variety of contexts consistent with this disclosure and the claims that follow. For example, the lighting systems shown in the figures and discussed above can be adapted in the spirit of the many optional parameters described.

What is claimed is:

1. A linear lighting system, comprising:

a tray being extended along elongation directions and having a base forming a bottom interior surface of the tray, a first sidewall connected to the base and extending upward from the base towards an emission aperture of the linear lighting system, and a second sidewall connected to the base and being spaced apart across the base from the first sidewall and extending upward from the base towards the emission aperture of the linear lighting system;

a circuit board being located on the first sidewall in the tray;

a plurality of light emitting diodes (LEDs) being located on the circuit board and mutually spaced apart on the first sidewall along the elongation directions of the tray and being positioned for light emissions in directions facing toward the second sidewall; and

a protuberance being located on the base and interposed between the LEDs and the second sidewall, the protuberance being positioned for diverting light emissions from the plurality of the LEDs toward the emission aperture.

2. The linear lighting system of claim 1, wherein the tray is triaxially or biaxially flexible.

3. The linear lighting system of claim 1, wherein the circuit board is triaxially or biaxially flexible.

25

4. The linear lighting system of claim 1, wherein the protuberance includes a raised mound located on the base and extending along the elongation directions of the tray, the raised mound being positioned to intersect pathways of some of the light emissions.

5. The linear lighting system of claim 4, wherein the protuberance has an angled or convex surface for diverting light emissions toward the emission aperture.

6. The linear lighting system of claim 5, wherein the convex surface of the protuberance is smoothly convex.

7. The linear lighting system of claim 6, wherein the angled surface of the protuberance has a geometric prismatic shape.

8. The linear lighting system of claim 7, wherein the geometric prismatic shape of the protuberance includes a triangular prism, a rectangular prism, a pentagonal prism, or a hexagonal prism.

9. The linear lighting system of claim 1, wherein the protuberance includes a plurality of raised mounds located on the base and being mutually spaced apart along the elongation directions of the tray, each one of the plurality of the raised mounds being positioned to intersect pathways of some of the light emissions.

10. The linear lighting system of claim 9, wherein each one of the plurality of the raised mounds has an angled or convex surface for diverting light emissions toward the emission aperture.

11. The linear lighting system of claim 10, wherein each one of the convex surfaces of the raised mounds is smoothly convex.

12. The linear lighting system of claim 11, wherein each one of the angled surfaces of the raised mounds has a geometric prismatic shape.

13. The linear lighting system of claim 12, wherein the geometric prismatic shape of each one of the protuberances includes a triangular prism, a rectangular prism, a pentagonal prism, or a hexagonal prism.

14. The linear lighting system of claim 1, wherein the protuberance has a highly light reflective surface for reflecting light emissions toward the emission aperture.

15. The linear lighting system of claim 1, wherein the protuberance is a light-transmissive protuberance having a

26

higher refractive index than air, for refracting light emissions toward the emission aperture.

16. The linear lighting system of claim 1, including another circuit board being located on the second sidewall in the tray, and including a further plurality of light emitting diodes (LEDs) being located on the another circuit board and mutually spaced apart on the second sidewall along the elongation directions of the tray and being positioned for further light emissions in directions facing toward the first sidewall; wherein the protuberance is positioned for diverting further light emissions from the further plurality of LEDs toward the emission aperture.

17. The linear lighting system of claim 1, wherein an interior of the tray has a highly light reflective surface.

18. The linear lighting system of claim 1, further including a plurality of lenses, each one of the plurality of lenses being located over a respective one of the plurality of the LEDs for increasing a maximum light emission angle of the LED from a first value to a second value that is larger than the first value.

19. The linear lighting system of claim 18, further including a diffuser located over the plurality of the lenses, wherein the plurality of the lenses and the diffuser cause the linear lighting system to emit the light emissions as a line of light.

20. The linear lighting system of claim 18, wherein the first value of the maximum light emission angle is no more than about sixty (60) degrees and the second value of the maximum emission angle is at least about eighty (80) degrees.

21. The linear lighting system of claim 18, including a further plurality of lenses, each one of the further plurality of lenses being located over a respective one of the another plurality of the LEDs for increasing a maximum light emission angle from a first value to a second value that is larger than the first value.

22. The linear lighting system of claim 19, further including another diffuser located over the further plurality of the lenses, wherein the further plurality of the lenses and the another diffuser cause the linear lighting system to emit the further light emissions as a line of light.

* * * * *