

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398356
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kuiper; Wouter et al.

Systems and methods for centering a circular object

Abstract

The present disclosure describes systems and methods for centering a circular object, such as a petri dish, between a plurality of pins. For example, in one embodiment, a method comprises placing a circular object on a rotatable platform surrounded by three moveable pins. In order to roughly center the circular object, the method further comprises moving, for a first time, all of the pins toward the circular object until at least two out of the three pins are touching the circular object. In order to more accurately center the circular object, the method further comprises: moving all of the pins away from the circular object so that it can be rotated without substantial inference; rotating the platform approximately 60 degrees, wherein rotating the platform causes the circular object to also rotate by approximately 60 degrees; and moving, for a second time, all of the pins toward the circular object.

Inventors:	Kuiper; Wouter (Marum, NL), van der Dong; Harm W. (Den Ham, NL), Van Der Vijver; Jan Bart (Groningen, NL), Kleefstra; Martijn (Surhuisterveen, NL)
Applicant:	BD Kiestra B.V. (Drachten, NL)
Family ID:	1000008780251
Assignee:	BD Kiestra B.V. (Drachten, NL)
Appl. No.:	17/259408
Filed (or PCT Filed):	July 10, 2019
PCT No.:	PCT/EP2019/068588
PCT Pub. No.:	WO2020/011875
PCT Pub. Date:	January 16, 2020

Prior Publication Data

Related U.S. Application Data

us-provisional-application US 62697197 20180712

Publication Classification

Int. Cl.: **B01L3/00** (20060101); **B01L9/00** (20060101); **C12M1/00** (20060101); **C12M1/22** (20060101)

U.S. Cl.:

CPC **C12M23/50** (20130101); **B01L9/52** (20130101); **C12M23/10** (20130101); **B01L2200/025** (20130101); **B01L2300/021** (20130101); **B01L2300/0803** (20130101)

Field of Classification Search

CPC: B01L (2200/02); B01L (2200/025); B01L (2200/18); B01L (2300/021); B01L (2300/0803); B01L (2300/0851); B01L (9/52); B01L (9/56); C12M (23/10); C12M (23/50); G01N (2035/00801)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4222577	12/1979	Giffin	279/151	B28B 1/025
5531549	12/1995	Fossella	279/151	B25B 13/467
6394691	12/2001	Stephan	403/374.2	B23B 31/18
7105338	12/2005	Holmes et al.	N/A	N/A
9446411	12/2015	Manian et al.	N/A	N/A
10464794	12/2018	Figa	N/A	F16B 2/185
2009/0142992	12/2008	Takahashi	451/36	B24B 41/068
2014/0050619	12/2013	Meller	422/549	G01N 35/00
2014/0377038	12/2013	Malin	N/A	N/A
2015/0010996	12/2014	Tsumura et al.	N/A	N/A
2015/0276566	12/2014	Berntsen et al.	N/A	N/A
2015/0299639	12/2014	Kleefstra et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2602030	12/2003	CN	N/A
1908154	12/2009	CN	N/A
106064121	12/2015	CN	N/A
3228691	12/2016	EP	N/A
2759563	12/2019	ES	N/A
2948945	12/2011	FR	N/A
2010515439	12/2009	JP	N/A

114529	12/2011	RU	N/A
2008083439	12/2007	WO	N/A
2015131662	12/2014	WO	N/A
2016191646	12/2015	WO	N/A

OTHER PUBLICATIONS

Office action from corresponding Chinese Patent Application No. 2019800462069 dated Feb. 16, 2022, 9 pp. cited by applicant

PCT International Preliminary Report on Patentability and Written Opinion issued in PCT application No. PCT/EP2019/068588 on Jan. 12, 2021. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/EP2019/068588 dated Oct. 11, 2019 (12 pp.). cited by applicant

Office Action issued in corresponding Australian Patent Application No. 2019300262 dated Sep. 20, 2022 (3 pp.). cited by applicant

Office Action issued in corresponding Indian Patent Application No. 202117002374 dated Aug. 25, 2022 (6 pp.). cited by applicant

International Search Report for International Application No. PCT/EP2019/068588 dated Oct. 11, 2019 (4 pages). cited by applicant

Office Action from corresponding Japanese Patent Application No. 2021-500917 dated May 30, 2023 (8 pp.). cited by applicant

Brazilian Office Action issued in BR application No. BR112021000382-7 on Mar. 25, 2025, pp. 17. cited by applicant

Mexican Office Action issued in corresponding MX application No. MX/a/2021/000424 on Jul. 26, 2024, pp. 10. cited by applicant

Decision of Rejection issued in corresponding JP application No. 2021-500917 on Nov. 28, 2024, pp. 8. cited by applicant

Communication from corresponding European Patent Application No. 19749204.4 dated Jul. 13, 2023 (6 pp.). cited by applicant

Office Action from corresponding Brazilian Application No. BR112021000382-7 dated Dec. 19, 2022 (7 pp.). cited by applicant

Office Action from corresponding Russian Application No. 2021102584 dated Nov. 25, 2022 (9 pp.). cited by applicant

Mexican Office Action issued in Mexican Patent Application No. MX/a/2021/000424 on Mar. 5, 2025, pp. 14. cited by applicant

Primary Examiner: Bowers; Nathan A

Attorney, Agent or Firm: Botos Churchill IP Law LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure describes systems and methods for centering a circular object, such as a petri dish, between a plurality of pins.

BACKGROUND

(2) With advancements in computers, networking, and robotics, automation has become a useful tool in streamlining a wide array of workflow processes. For example, automation has been employed in laboratory settings to streamline various processes for preparing biological samples

(e.g., patient samples, environmental samples, etc.) for laboratory analysis. Automating such tasks can (a) reduce personnel costs, (b) reduce operator errors (e.g., human errors) that may result, for example, when the operators are tired, distracted, or otherwise unfocused, and (c) reduce the time it takes to analyze samples and report results.

(3) For example, U.S. application Ser. No. 14/674,827 (“the '827 Application”), which was filed on Mar. 31, 2015 and published as U.S. Publication No. 2015/0276566 A1, the disclosure of which is incorporated herein by reference, describes an automated platform for inoculating a variety of receptacles with biological samples for testing and analysis. In some embodiments, the automated platform includes an inoculation module and a streaking module. The inoculation module inoculates receptacles (e.g., petri dishes, plates, broth tubes, slides, etc.), with biological samples. This may be accomplished with a pipette unit, a wire loop, a swab, etc. While inoculating petri dishes, the inoculation module may also dispense a magnetic bead into the petri dishes. After the petri dishes have been inoculated, they may be conveyed along a conveyor system to the streaking module. In some embodiments, the streaking module includes magnets that can cause the magnetic beads deposited in the petri dishes to streak the inoculated media (e.g., blood agar, chocolate agar, MacConkey agar, etc.) with the sample according to a prescribed pattern. After the petri dishes have been streaked, they may be conveyed into an incubation system. Additional details regarding this automated platform may be found in the '827 Application.

(4) As another example, U.S. application Ser. No. 14/687,400 (“the '400 Application”), which was filed on Apr. 15, 2015 and published as U.S. Publication No. 2015/0299639 A1, the disclosure of which is incorporated herein by reference, describes an integrated incubator and image capture module that regulates the incubator atmosphere and obtains high-resolution digital images of sample specimens. In some embodiments, the incubator has a cabinet type enclosure that enables the provision of a controlled environment to the contents of the incubator. In some embodiments, the incubator houses petri dishes that contain nutrient media that has been inoculated by a biological sample. The nutrient media and controlled atmosphere provided to the incubator support the growth of at least certain microbes in the media if present in the sample with which the media has been inoculated. In some embodiments, the image capture module is an enclosed unit immediately adjacent to the incubator. This enables direct transport of petri dishes from the incubator into the image capture module. Once in the image capture module, a lid of a petri dish may be removed such that an image capture unit may electronically image (e.g. digitally photographs) the petri dish. Afterwards, the lid may be replaced and the petri dish may be conveyed back to the incubator. In some embodiments, the images may be automatically analyzed using a software program that can determine if microbial growth has occurred. Additional details regarding this incubator and image capture module may be found in the '400 Application.

(5) As yet another example, International Application No. PCT/US2016/034554 (“the '554 Application”), which was filed on May 27, 2016 and published as International Publication No. WO 2016/191646 A2, the disclosure of which is incorporated herein by reference, describes automated systems for preparing biological samples for both identification (e.g., Matrix Assisted Laser Desorption and Ionization Time-of-Flight Mass Spectrometry (“MALDI-TOF-MS”)) and antibiotic susceptibility testing (“AST”). In some embodiments, the automated systems may: locate and select a colony of microorganisms on a culture dish; obtain a sample of the selected colony of microorganisms; prepare a suspension for the obtained sample; dispense a portion of the obtained sample onto a target plate and place the target plate in an apparatus for performing MALDI for identification of the sample of the selected colony of microorganisms; and use or transfer another portion of the suspension for another test, such as AST. The AST could be Kirby-Baur/disk diffusion, disk dilution, broth and agar dilution or other methods. Additional details regarding this automated system may be found in the '554 Application.

(6) In all of the automated systems described above, a petri dish or another similar object may need to be accurately centered. For example, with respect to the '827 Application, a petri dish may need

to be accurately centered before it can be inoculated with a biological sample. As another example, with respect to the '400 Application, a petri dish may need to be accurately centered in the image capture module so that the digital images can be accurately compared to detect microbial growth. As yet another example, with respect to the '554 Application, a petri dish may need to be accurately centered before samples can be accurately transferred from the petri dish to a common suspension. (7) Prior art systems for centering circular objects, such as petri dishes, sometimes include three or more pins. During operation, the pins are moved centrically toward the petri dish until the petri dish is squeezed between all of the pins. However, in such systems, there is a chance that the pins may stop moving when only some (not all) of the pins are touching the petri dish. This may be caused by the friction of the bottom or sides of the petri dish or the pins. In such cases, the petri dish may not be centered properly. As a result, a need exists for systems and methods for robustly and accurately centering circular objects, such as petri dishes.

BRIEF SUMMARY

(8) The present disclosure describes systems and methods for robustly and accurately centering a circular object, such as a petri dish, between a plurality of pins. For example, in one embodiment, a method comprises placing a circular object on a rotatable platform surrounded by three moveable pins. In order to roughly center the circular object, the method further comprises moving, for a first time, all of the pins toward the circular object until at least two out of the three pins are touching the circular object. In order to more accurately center the circular object, the method further comprises: moving all of the pins away from the circular object so that it can be rotated without substantial interference; rotating the platform approximately 60 degrees, wherein rotating the platform causes the circular object to also rotate by approximately 60 degrees; and moving, for a second time, all of the pins toward the circular object.

(9) One aspect of the present disclosure relates to a method comprising: (a) placing a circular object on a platform between three or more pins, wherein the pins are positioned approximately equidistantly from each other, and wherein the pins are in a first open position; (b) moving, for a first time, all of the pins toward the circular object to a closed position, wherein at least two of the pins are in contact with the circular object when the pins are in the closed position; (c) moving all of the pins away from the circular object to the first open position or a second open position, wherein the circular object can be rotated on the platform without interference from the pins when the pins are in the first open position or the second open position; (d) rotating the circular object approximately θ degrees or approximately θ degrees plus one or more complete rotations of 360 degrees, wherein θ is equal to 360 degrees divided by twice the number of pins; and (e) moving, for a second time, all of the pins toward the circular object to the closed position, wherein the circular object is approximately centered between all of the pins after all of the pins have been moved to the closed position for the second time.

(10) In some embodiments, the platform is rotatable and the circular object is rotated by rotating the platform. In some embodiments, the circular object is a petri dish. In some embodiments, the method further comprises inoculating the petri dish with a biological sample after the petri dish has been approximately centered between all of the pins. In some embodiments, the method further comprises capturing an image of the petri dish with an image capture module after the petri dish has been approximately centered between all of the pins. In some embodiments, the method further comprises picking one or more colonies of bacteria in the petri dish after the petri dish has been approximately centered between all of the pins.

(11) Another aspect of the present disclosure relates to a method comprising: (a) placing a circular object on a rotatable platform positioned between three pins, wherein the pins are positioned approximately equidistantly from each other, and wherein the pins are in a first open position; (b) moving, for a first time, all of the pins toward the circular object to a closed position, wherein at least two of the pins are in contact with the circular object when the pins are in the closed position; (c) moving, for a first time, all of the pins away from the circular object to the first open position or

a second open position, wherein the circular object can be rotated on the platform without interference from the pins when the pins are in the first open position or the second open position; (d) rotating the platform approximately 60 degrees or approximately 60 degrees plus one or more complete rotations of 360 degrees, wherein rotating the platform causes the circular object to also rotate; and (e) moving, for a second time, all of the pins toward the circular object to the closed position, wherein the circular object is approximately centered between all of the pins after all of the pins have been moved to the closed position for the second time.

(12) In some embodiments, the circular object is a petri dish. In some embodiments, the method further comprises removing a lid covering the petri dish from the petri dish. In some embodiments, the method further comprises inoculating the petri dish with a biological sample after the petri dish has been approximately centered between all of the pins. In some embodiments, the method further comprises: (a) moving, for a second time, all of the pins away from the circular object to the first open position or the second open position after the petri dish has been approximately centered between all of the pins; and (b) orienting the petri dish by rotating the petri dish and aligning a label on the petri dish with a reader positioned near the platform. In some embodiments, the method further comprises capturing an image of the petri dish with an image capture module after the petri dish has been approximately centered between all of the pins and oriented. In some embodiments, the method further comprises picking one or more colonies of bacteria in the petri dish after the petri dish has been approximately centered between all of the pins and oriented.

(13) Yet another aspect of the present disclosure relates to a system comprising: (a) a rotatable platform having a top surface and a bottom surface; (b) a first idler pulley having a top surface and a bottom surface, wherein the top surface of the first idler pulley is fixed to the bottom surface of the platform; (c) a second idler pulley having a top surface and a bottom surface, wherein the second idler pulley is positioned beneath the bottom of the first idler pulley, and wherein three posts are fixed to the bottom of the second idler pulley; and (d) three pins positioned around the rotatable platform, wherein the pins are positioned approximately equidistantly from each other, and wherein each of the pins is fixed to a flap having an arm that extends beneath the second idler pulley, and wherein each of the flaps are connected to a fixed shaft and rotatable about that fixed shaft, and wherein each of the arms of the flaps has a hole surrounding a different one of the posts fixed to the bottom of the second idler pulley, wherein the platform can be rotated by rotating the first idler pulley, and wherein the pins can be moved towards the platform by rotating the second idler pulley.

(14) In some embodiments, the system further comprises: (a) a first motor having a first drive pulley fixed to a shaft of the first motor; (b) a second motor having a second drive pulley fixed to a shaft of the second motor; (c) a first belt connected to the first idler pulley and the first drive pulley; and (d) a second belt connected to the second idler pulley and the second drive pulley, wherein rotational power of the first drive pulley is transferred to first idler pulley through the first belt, and wherein rotational power of the second drive pulley is transferred to second idler pulley through the second belt.

(15) In some embodiments, the system further comprises one or more processors configured to control rotation of the first and second idlers pulleys by controlling the first and second motors. In some embodiments, the one or more processors are configured to: (a) move, for a first time, all of the pins toward a petri dish placed on the platform to a closed position, wherein at least two of the pins are in contact with the petri dish when the pins are in the closed position; (b) move, for a first time, all of the pins away from the petri dish to the first open position or a second open position, wherein the petri dish can be rotated on the platform without interference from the pins when the pins are in the first open position or the second open position; (c) rotate the platform approximately 60 degrees or approximately 60 degrees plus one or more complete rotations of 360 degrees; and (d) move, for a second time, all of the pins toward the petri dish to the closed position, wherein the circular object is approximately centered between all of the pins after all of the pins have been

moved to the closed position for the second time.

(16) In some embodiments, the system further comprises a reader and the one or more processors are further configured to: (a) move, for a second time, all of the pins away from the petri dish to the first open position or the second open position after the petri dish has been approximately centered between all of the pins; and (b) orient the petri dish by rotating the platform and aligning a label on the petri dish with the reader. In some embodiments, the system further comprises an image capture module and the one or more processors are further configured to capture an image of the petri dish with the image capture module after the petri dish has been approximately centered between all of the pins and oriented. In some embodiments, the system further comprises an automated pipettor and the one or more processors are further configured to: pick one or more colonies of bacteria in the petri dish after the petri dish has been approximately centered between all of the pins and oriented.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1(a) illustrates a side-view of an embodiment of a system for centering a circular object as described herein.

(2) FIG. 1(b) illustrates another side-view of the system of FIG. 1(a).

(3) FIG. 1(c) illustrates a side-view of the system of FIG. 1(a) with a petri dish placed on a platform of the system of FIG. 1(a).

(4) FIG. 1(d) illustrates another side-view of the system of FIG. 1(c).

(5) FIG. 1(e) illustrates a bottom-view of the system of FIG. 1(a).

(6) FIG. 2(a) is an image of an embodiment of a system for centering a circular object as described herein.

(7) FIG. 2(b) is another image of the system of FIG. 2(a).

(8) FIG. 3 is a block diagram of a method for centering a circular object as described herein.

(9) FIGS. 4(a)-(l) illustrate a method for centering a circular object as described herein.

(10) FIG. 5 is an image of a test performed to demonstrate the operation of the system of FIGS. 2(a)-(b).

DETAILED DESCRIPTION

(11) Embodiments of the present disclosure are described in detail with reference to the drawing figures wherein like reference numerals identify similar or identical elements. It is to be understood that the disclosed embodiments are merely examples of the disclosure, which may be embodied in various forms. Well-known functions or constructions are not described in detail to avoid obscuring the present disclosure in unnecessary detail. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present disclosure in virtually any appropriately detailed structure.

(12) FIGS. 1(a)-(e) illustrate an embodiment of a system for centering a circular object in accordance with the present technology. As shown, system **100** includes platform **110**, pin **122**, pin **132**, pin **142**, sensor **150**, motor **160**, and motor **170**. As shown in FIGS. 1(c) and 1(d), petri dish **190** can be placed on platform **110**. In some embodiments, a robotic arm may automatically place petri dish **190** on platform **110**. Once on platform **110**, pins **122**, **132**, and **142** may be used to center petri dish **190** on platform **110**.

(13) During the centering process, pins **122**, **132**, and **142** may be moved by motor **160**. Motor **160** comprises a shaft (not shown) fixed to drive pulley **164**. As used herein, a pulley may be a rotatable structure that is used to transmit power by means of a band, belt, cord, rope, chain, etc. passing over its rim. For example, a pulley may be a smooth wheel-like structure that is configured to

transmit power by means of a rubber band or belt. As another example, a pulley may be a gear-like structure that is configured to transmit power by means of a chain. During operation, drive pulley **164** is rotated in a clock-wise or counter-clock-wise direction by the shaft of motor **160**. As shown, platform **110** may be positioned above idler pulley **112**, divider **114**, and idler pulley **116**. Divider **114** separates idler pulley **112** and idler pulley **116**. While idler pulleys **112** and **116** may be connected through a common shaft (not shown), idler pulleys **112** and **116** rotate independently of one another. During operation, when drive pulley **164** is rotated by motor **160**, the rotational power of drive pulley **164** is transferred to idler pulley **116** by belt **184**. Belt **184** may be any band, belt, cord, rope, chain, etc. that is capable of transferring the rotational power of drive pulley **164** to idler pulley **116**. In other embodiments, idler pulley **116** may be a separate structure positioned, for example, underneath idler pulley **112**. In such embodiments, divider **114** may be eliminated.

(14) As shown, the rotation of idler pulley **116** in a clock-wise or counter-clock-wise direction causes pins **122**, **132**, and **142** to move in an inward or outward direction with respect to platform **110**. As best shown in FIGS. **1(a)-(d)**, pins **122**, **132**, and **142** are fixed to flaps **124**, **134**, and **144**, respectively. Flaps **124**, **134**, and **144** are connected to and may rotate about shafts **126**, **136**, and **146**, respectively. Shafts **126**, **136**, and **146** may have fixed positions. For example, shafts **126**, **136**, and **146** may be fixed to one or more objects (not shown). As best shown in FIG. **1(e)**, flaps **124**, **134**, and **144** may comprise arms **128**, **138**, and **148**, respectively. Furthermore, arms **128**, **138**, and **148** may comprise holes **129**, **139**, and **149**, respectively. Holes **129**, **139** and **149** are sized and positioned such that posts **102**, **103**, and **104**, respectively, are positioned inside them. As shown, posts **102**, **103**, and **104** are fixed to idler pulley **116**. As a result, when idler pulley **116** is rotated in a clock-wise or counter-clock-wise direction, posts **102**, **103**, and **104** also move. In other embodiments, idler pulley **116** and posts **102**, **103**, and **104** may be formed as a single integrated object. As shown, when pulley **116** is rotated by motor **160**, the rotational power of idler pulley **116** is transferred to flaps **124**, **134**, and **144** through posts **102**, **103**, and **104**, respectively, and arms **128**, **138**, and **148**, respectively. Furthermore, when flaps **124**, **134**, and **144** move, pins **122**, **132**, and **142**, respectively, may move in an inward or outward direction with respect to platform **110**.

(15) During the centering process, platform **110** may be rotated in a clock-wise or counter-clock-wise direction by motor **170**. Motor **170** comprises shaft **172** fixed to drive pulley **174**. During operation, drive pulley **174** is rotated in a clock-wise or counter-clock-wise direction by shaft **172**. As shown, the underside of platform **110** is fixed to the topside of idler pulley **112**. In other embodiments, platform **110** and idler pulley **112** may be formed as a single integrated object. Furthermore, as shown, idler pulley **112** is connected to drive pulley **174** by belt **182**. During operation, when drive pulley **174** is rotated by motor **170**, the rotational power of drive pulley **174** is transferred to idler pulley **112** by belt **182**. Moreover, when idler pulley **112** is rotated in a clock-wise or counter-clock-wise direction, platform **110** also rotates in the same direction because it is fixed to idler pulley **112**. Much like belt **184**, belt **182** may also be any band, belt, cord, rope, chain, etc. that is capable of transferring the rotational power of drive pulley **174** to idler pulley **112**.

(16) In some embodiments, after petri dish **190** has been centered, petri dish **190** may be inoculated with a biological sample. In some embodiments, one or more of the systems and/or methods disclosed in the '827 Application may be used to inoculate petri dish **190**. For example, an automated pipettor may be used to inoculate petri dish **190**. In some embodiments, sensor **150** (e.g., an infrared (ID) sensor or an imaging device) may be used to orient petri dish **190**. For example, in some embodiments, sensor **150** may be used to determine where a label (e.g., a barcode) on petri dish **190** begins and ends. In some embodiments, after petri dish **190** has been centered and oriented, a reader (not shown) (e.g., a barcode reader or an imaging device) may be used to read (e.g., scan) a label (e.g., a barcode) on petri dish **190**. In some embodiments, a reader (not shown) may also be used to further orient petri dish **190**. In some embodiments, after petri dish **190** has been centered and oriented, one of more images of petri dish **190** may be captured by an image capture device (not shown) and/or one or more colonies of bacteria may be picked by a robot (not

shown). In some embodiments, one or more of the systems and/or methods disclosed in the '400 Application may be used to capture images of petri dish **190**. In some embodiments, one or more of the systems and/or methods disclosed in the '554 Application may be used to pick one or more colonies of bacteria in petri dish **190**. For example, an automated pipettor may be used to pick one or more colonies of bacteria in petri dish **190**.

(17) FIGS. **2(a)-(b)** are photographs of an embodiment of a system for centering a circular object in accordance with the present technology. As shown, system **200** includes platform **210**, pin **220**, pin **230**, pin **240**, cover **250**, sensor **262**, reader **264**, robot **280**, and automated pipettor **290**. Cover **250** includes slits **252**, **254**, and **256**. Underneath cover **250**, system **200** may include motors, pulleys, belts, and/or other components much like system **100** of FIGS. **1(a)-(e)**.

(18) As shown in FIGS. **2(a)-(b)**, slits **252**, **254**, and **256** are curved and sized such that the diameters of slits **252**, **254**, and **256** correspond to the diameters of pins **210**, **220**, and **230**. As a result, pins **220**, **230** and **240** can traverse approximately the entire length of the slits **252**, **254** and **256**. Furthermore, in this embodiment, slits **252**, **254**, and **256** extend 15 millimeters away from platform **210**. However, in other embodiments, the length of slits **252**, **254**, and **256** can be increased or decreased. For example, the lengths of slits **252**, **254** and **256** can be selected to allow a petri dish to be placed onto platform **210** and rotated without substantial interference from pins **220**, **230** and **240**. As another example, the lengths of slits **252**, **254** and **256** may significantly exceed (e.g., by a factor of two or more) the length required to allow a petri dish to be placed onto platform **210** and rotated without substantial interference from the **220**, **230** and **240**.

(19) During a centering operation, slits **252**, **254**, and **256** guide pins **210**, **220**, and **230** as they are advanced toward platform **210**. As shown, slits **252**, **254**, and **256** are curved and have a consistent diameter corresponding to the diameters of pins **210**, **220**, and **230**. In other embodiments, slits **252**, **254**, and **256** may have different shapes. For example, slits **252**, **254**, and **256** may be generally straight and have a consistent diameter corresponding to the diameters of pins **210**, **220**, and **230**. As another example, slits **252**, **254**, and **256** may have conical shapes with variable diameters. In such embodiments, slits **252**, **254**, and **256** may have narrow portions near platform **210** with diameters corresponding to the diameters of pins **210**, **220**, and **230**.

(20) As shown in FIG. **2(b)**, petri dish **270** can be placed on platform **210** by robot **280**. Once on platform **210**, pins **220**, **230**, and **240** may be used to center petri dish **270** on platform **210**. After petri dish **270** has been centered, sensor **262** may also be used to orient petri dish **270**. After petri dish **270** has been centered and oriented, reader **264** may be used to read a label on petri dish **270**. Reader **264** may also be used to further orient petri dish **270**. After petri dish **270** is centered and/or oriented, automated pipettor **290** may be used to inoculate petri dish **270** with a biological sample and/or pick one or more colonies of bacteria in petri dish **270**.

(21) FIG. **3** is a block diagram of a method for centering a circular object in accordance with the present technology. Method **300** may be performed with a system, such as system **100** of FIGS. **1(a)-(e)** or system **200** of FIGS. **2(a)-(b)**. In such embodiments, system **100** may include one or more processors configured to control sensor **150**, motor **160**, and motor **170**. Similarly, in such embodiments, system **200** may include one or more processors configured to control sensor **262**, reader **264**, and/or one or more motors underneath cover **250** that are configured to move platform **210** and pins **220**, **230**, and **240**. It is to be understood that the arrows in FIG. **3** are meant to illustrate one possible order in which the various processes of method **300** may be performed. However, in some embodiments, the blocks illustrated in FIG. **3** may be rearranged. Moreover, in some embodiments, one or more blocks may be added and/or removed.

(22) In block **310**, a system comprising a rotatable platform surrounded by three moveable pins is initialized by moving the pins away from the platform to an open position. For example, in an embodiment performed with system **200**, pins **220**, **230**, and **240** may be moved into the open position shown in FIGS. **2(a)-(b)**. As shown, pins **220**, **230**, and **240** are moved 15 millimeters away from platform **210**. As another example, in an embodiment performed with system **200**, pins

220, **230**, and **240** may be moved to an open position that is only 8 millimeters away from platform **210**. In some embodiments, one or more processors may control the movement of the pins by controlling one or more motors connected to the pins.

(23) In block **320**, a petri dish is placed on the platform. For example, in an embodiment performed with system **200**, robot **280** may place petri dish **270** on platform **210**. As another example, in some embodiments, the petri dish may be conveyed onto the platform through the use of a conveyor system. In some embodiments, one or more processors may control the transfer mechanism (e.g., a robot or a conveyor system) used to place the petri dish on the platform. Since the transfer mechanism may not be configured to accurately center the petri dish on the platform, the petri dish may initially be off-centered.

(24) In block **330**, the petri dish is roughly centered by moving all of the pins toward the petri dish into closed positioned. As explained above, some prior art systems use a similar technique to center circular objects, such as petri dishes. However, in contrast to those prior art systems, method **300** includes additional processes for more accurately centering circular objects such as petri dishes, in the systems described herein.

(25) In block **340**, a lid covering the petri dish is removed. In other embodiments, this block may be performed at a different place in the illustrated sequence, such as before block **310**. In other embodiments, this block may be unnecessary and removed entirely from method **300**. For example, in some embodiments, the system may be handling one or more petri dishes that do not have lids or the system may have the capability to obtain an image through a transparent lid, in which case the lid would not need to be removed.

(26) In block **350**, all of the pins are moved away from the petri dish to an open position. For example, in an embodiment performed with system **200**, pins **220**, **230**, and **240** may be moved into the position shown in FIGS. 2(a)-(b). As shown, the pins are moved to their original open position, but that is not required. As another example, in some embodiments, the pins may only be moved far enough away so as to allow the petri dish to be rotated without substantial interference. For example, in an embodiment performed with system **200**, pins **220**, **230**, and **240** may be moved to an open position that is only 8 millimeters away from platform **210**, instead of an open position that is 15 millimeters away from platform **210** as shown in FIGS. 2(a)-(b).

(27) In block **360**, the petri dish is rotated in a clock-wise or counter-clock-wise direction by 60 degrees. For example, in an embodiment performed with system **200**, platform **210** may be rotated in a clock-wise or counter-clock-wise direction by 60 degrees in order to rotate petri dish **270** by 60 degrees in the same direction. In some embodiments, one or more processors may control the movement of the platform by controlling one or more motors connected to the pins. Although less time efficient, one skilled in the art will readily appreciate that a similar result can be achieved by adding one or more complete rotations of 360 degrees. For example, the petri dish can be effectively rotated in a clock-wise or counter-clock-wise direction by 60 degrees by rotating the petri dish 420 degrees in a clock-wise or counter-clock-wise direction.

(28) In block **370**, the petri dish is accurately centered by moving all of the pins toward the petri dish. As described in more detail below with respect to FIGS. 4(a)-(l), during block **330**, at least two of the three pins should contact the petri dish. Therefore, the edge of the petri dish that is farthest from the center of platform is located between the two contacting pins. As a result, by rotating the petri dish, one of the pins that contacted the petri dish during block **330** can be used during block **370** to more accurately urge the petri dish into the center of the platform.

(29) In block **380**, all of the pins are moved away from the petri dish. This block is optional. In some embodiments, it may be advantageous to move the pins away from the petri dish before one or more additional processes are performed on the petri dish. For example, if the petri dish needs to be rotated again in order to be oriented properly, it may be advantageous to move the pins away from the petri dish before rotating it. In other embodiments, it may be more advantageous to keep the pins in a position that is close the petri dish and the platform in order to prevent the petri dish

from moving and becoming off-center.

(30) In block **390**, one or more processes are performed on the accurately centered petri dish. For example, in block **390**, the petri dish may be inoculated with a biological sample. In some embodiments, one or more of the systems and/or methods disclosed in the '827 Application may be used to inoculate the petri dish. As another example, in block **390**, one or more images of the petri dish may be captured by an image capture device. In some embodiments, one or more of the systems and/or methods disclosed in the '400 Application may be used to capture the images of the petri dish. As yet another example, in block **390**, one or more colonies of bacteria in the petri dish may be picked by a robot. In some embodiments, one or more of the systems and/or methods disclosed in the '554 Application may be used to pick one or more colonies of bacteria in petri dish **190**.

(31) FIGS. **4(a)-(l)** illustrate a method for centering a circular object in accordance with the present technology. More specifically, with reference to method **300** of FIG. **3**, the processes illustrated in FIGS. **4(a)-(d)** correspond to block **330**, the processes illustrated in FIG. **4(e)** correspond to block **350**, the processes illustrated in FIGS. **4(f)-(g)** correspond to block **360**, the processes illustrated in FIGS. **4(h)-(j)** correspond to block **370**, and the processes illustrated in FIGS. **4(k)-(l)** correspond to block **380**. As shown, FIGS. **4(a)-(l)** illustrate petri dish **410** positioned between moveable pins **420**, **430**, and **440**. As shown in FIG. **4(a)**, pins **420**, **430**, and **440** are in an open position.

(32) In FIGS. **4(b)-(d)**, pins **420**, **430**, and **440** are moved toward petri dish **410** to a closed position. As shown in FIG. **4(c)**, during this process, pin **440** contacts petri dish **410** before the other pins. Furthermore, as shown in FIG. **4(d)**, pin **420** eventually contacts petri dish **410**, but pin **430** does not make contact with petri dish **410** because it has reached the limit of its travel trajectory through its respective slit (not shown) before making contact with petri dish **410**. As a result, petri dish **410** is not accurately centered in FIG. **4(d)**. More specifically, the edge of petri dish that is farthest from the center of pins **420**, **430**, and **440** is located between pins **440** and **420**. Furthermore, the edge of petri dish that is closest to the center of pins **420**, **430**, and **440** is located by pin **430**.

(33) In order to more accurately center petri dish **410**, in FIG. **4(e)**, pins **420**, **430**, and **440** are moved away from petri dish **410** to an open position. Subsequently, in FIGS. **4(f)-(g)**, petri dish **410** is rotated 60 degrees in a clock-wise direction. As a result, the edge of petri dish that is farthest from the center of pins **420**, **430**, and **440** is now located by pin **420**. In FIGS. **4(h)-(j)**, pins **420**, **430**, and **440** are again moved toward petri dish **410** to a closed position. As shown in FIG. **4(i)**, during this process, pin **420** contacts petri dish **410** before the other pins. As a result, pin **420** is able to push petri dish **410** into a position that is more accurately centered between all of the pins. Lastly, in FIGS. **4(k)-(l)**, pins **420**, **430**, and **440** are again moved away from petri dish **410** to an open position.

(34) FIG. **5** is a photograph of a simple experiment performed with the system of FIGS. **2(a)-(b)** in order to demonstrate some of the advantages of the present technology. As shown, a piece of double-sided tape **510** was wrapped around petri dish **270**. Furthermore, at the time the image was taken, petri dish **270** had only been placed on platform **210** (see, e.g., block **320** of FIG. **3**) and pins **220**, **230**, and **240** had only been moved toward petri dish once (see, e.g., block **330** of FIG. **3**). As can be seen, at this point in time, there is a significant gap between pin **220** and petri dish **270**, which indicates that petri dish **270** is not accurately centered.

(35) As mentioned above, some prior art systems for centering a petri dish include three or more pins. During operation, the pins are moved toward the petri dish until the petri dish is squeezed between all of the pins. However, without more, these types of prior art systems may fail to accurately center the petri dish because of the friction of the bottom or sides of the petri dish or the pins. Although petri dishes often have smooth low-friction surfaces, various situations may arise that change this. For example, some of the agar in the petri dish may spill and make the sides of the petri dish sticky. As another example, a label printed onto a petri dish may begin to peel and some of the adhesive on the back of that label may become exposed. As yet another example, a label may

be printed unevenly onto a petri dish. As a result, as shown in FIG. 5, there is chance that the pins may stop moving when only some (not all) of the pins are touching the petri dish. Embodiments of the present technology mitigate these risks.

(36) Moreover, some of the advantages of the present technology over the prior art can be realized despite certain inaccuracies. For example, in block **360** of FIG. 3, the petri dish is rotated by 60 degrees in a clock-wise or counter-clock-wise direction. However, with respect to the position of the petri dish after performing block **330**, the petri dish can be more accurately centered even if it is only rotated, for example, by 55 degrees in a clock-wise or counter-clock-wise direction. Similarly, with respect to the position of the petri dish after performing block **330**, the petri dish can be more accurately centered even if it is rotated, for example, by 65 degrees in a clock-wise or counter-clock-wise direction. Therefore, as used herein, “approximately 60 degrees” is equivalent to saying “60 degrees plus or minus five degrees.” Thus, “approximately 60 degrees” is equivalent to, for example, 55 degrees, 56.7 degrees, 57.1 degrees, 59.021 degrees, 61.78 degrees, 62.35 degrees, and 64.99 degrees.

(37) From the foregoing and with reference to the various figure drawings, those skilled in the art will appreciate that certain modifications can also be made to the present disclosure without departing from the scope of the same. For example, different mechanisms can be used to rotate a circular object. For example, in some embodiments, a circular object, such as a petri dish, may be placed on a stationary platform between a plurality of pins. In such embodiments, a robot positioned above the circular object may grab the petri dish and rotate it.

(38) As another example, the present technology can be readily adapted to systems with four or more pins. For example, a system may comprise a rotatable platform surrounded by four moveable pins. Such a system could be used in method **300** of FIG. 3 if, in block **360**, the petri dish is only rotated approximately 45 degrees in a clock-wise or counter-clock-wise direction. In fact, the amount of rotation performed in block **360** can be stated more generally as:

$$(39) \quad \theta = \frac{360^\circ}{2P},$$

where θ is the amount by which the petri dish is rotated and P is the number of pins surrounding the petri dish. Furthermore, one skilled in the art will readily appreciate that one or more complete rotations of 360 degrees can be added to θ . As with the previous embodiment, “approximately 45 degrees” is equivalent to saying “45 degrees plus or minus five degrees.”

(40) Furthermore, while several embodiments of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

Claims

1. A method comprising: placing a circular object on a platform between three or more pins, wherein the pins are positioned approximately equidistantly from each other, and wherein the pins are in a first open position; moving, for a first time, all of the pins toward the circular object to a closed position, wherein at least two of the pins are in contact with the circular object when the pins are in the closed position; moving all of the pins away from the circular object to the first open position or a second open position, wherein the circular object can be rotated on the platform without interference from the pins when the pins are in the first open position or the second open position; rotating the circular object approximately θ degrees or approximately θ degrees plus one or more complete rotations of 360 degrees, wherein θ is equal to 360 degrees divided by twice a number of pins; and moving, for a second time, all of the pins toward the circular object to the closed position, wherein the circular object is approximately centered between all of the pins after

all of the pins have been moved to the closed position for the second time.

2. The method of claim 1, wherein the platform is rotatable, and wherein the circular object is rotated by rotating the platform.
 3. The method of claim 1, wherein the circular object is a petri dish.
 4. The method of claim 3, further comprising: inoculating the petri dish with a biological sample after the petri dish has been approximately centered between all of the pins.
 5. The method of claim 3, further comprising: capturing an image of the petri dish with an image capture module after the petri dish has been approximately centered between all of the pins.
 6. The method of claim 3, further comprising: picking one or more colonies of bacteria in the petri dish with an automated pipettor after the petri dish has been approximately centered between all of the pins.
 7. A method comprising: placing a circular object on a rotatable platform positioned between three pins, wherein the pins are positioned approximately equidistantly from each other, and wherein the pins are in a first open position; moving, for a first time, all of the pins toward the circular object to a closed position, wherein at least two of the pins are in contact with the circular object when the pins are in the closed position; moving, for a first time, all of the pins away from the circular object to the first open position or a second open position, wherein the circular object can be rotated on the platform without interference from the pins when the pins are in the first open position or the second open position; rotating the platform approximately 60 degrees or approximately 60 degrees plus one or more complete rotations of 360 degrees, wherein rotating the platform causes the circular object to also rotate; and moving, for a second time, all of the pins toward the circular object to the closed position, wherein the circular object is approximately centered between all of the pins after all of the pins have been moved to the closed position for the second time.
 8. The method of claim 7, wherein the circular object is a petri dish.
 9. The method of claim 8 further comprising: removing a lid covering the petri dish from the petri dish.
 10. The method of claim 9 further comprising: inoculating the petri dish with a biological sample after the petri dish has been approximately centered between all of the pins.
 11. The method of claim 9 further comprising: moving, for a second time, all of the pins away from the circular object to the first open position or the second open position after the petri dish has been approximately centered between all of the pins; and orienting the petri dish by rotating the petri dish and aligning a label on the petri dish with a reader positioned near the platform.
 12. The method of claim 11 further comprising: capturing an image of the petri dish with an image capture module after the petri dish has been approximately centered between all of the pins and oriented.
 13. The method of claim 11 further comprising: picking one or more colonies of bacteria in the petri dish after the petri dish has been approximately centered between all of the pins and oriented.
-