

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398940
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Chen; Jianquan et al.

Air-cooled refrigerator supplying air through centrifugal fan

Abstract

An air-cooled refrigerator supplying air through a centrifugal fan, comprising a bottom liner, an air duct back plate, and the centrifugal fan. A cooling chamber and a storage space are defined in the bottom liner; the air duct back plate is provided in front of a back wall of the bottom liner, and defines an air supply duct with the back wall of the bottom liner; the centrifugal fan comprises a volute and an impeller; the volute is arranged obliquely upwards from front to back at the back of the cooling chamber, and a fan cavity and a gradually widened exhaust cavity are defined in the volute; the fan cavity is formed into a continuous spiral; the gradually widened exhaust cavity is gradually widen backwards from the fan cavity; the impeller is provided in the fan cavity; and the inner wall face of the fan cavity is continuous and smooth.

Inventors:	Chen; Jianquan (Qingdao, CN), Zhu; Xiaobing (Qingdao, CN), Fei; Bin (Qingdao, CN), Wang; Changzhi (Qingdao, CN), Feng; Chen (Qingdao, CN)
Applicant:	QINGDAO HAIER REFRIGERATOR CO., LTD. (Shandong, CN); HAIER SMART HOME CO., LTD. (Shandong, CN)
Family ID:	1000008780214
Assignee:	QINGDAO HAIER REFRIGERATOR CO., LTD. (Shandong, CN); HAIER SMART HOME CO., LTD. (Shandong, CN)
Appl. No.:	18/042085
Filed (or PCT Filed):	June 15, 2021
PCT No.:	PCT/CN2021/100125
PCT Pub. No.:	WO2021/228277
PCT Pub. Date:	November 18, 2021

Prior Publication Data

Document Identifier

US 20230243568 A1

Publication Date

Aug. 03, 2023

Foreign Application Priority Data

CN

202010832823.6

Aug. 18, 2020

Publication Classification

Int. Cl.: F25D17/06 (20060101); F04D17/08 (20060101); F04D29/42 (20060101); F04D29/66 (20060101); F25D17/08 (20060101)

U.S. Cl.:

CPC F25D17/062 (20130101); F04D17/08 (20130101); F04D29/4233 (20130101); F04D29/668 (20130101); F25D17/08 (20130101); F25D2323/0028 (20130101)

Field of Classification Search

CPC: F25D (17/062); F25D (17/067); F25D (17/08); F25D (2317/068); F25D (2317/0681); F25D (2323/0028); F04D (17/08); F04D (29/4233); F04D (29/668)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5531267	12/1995	Ahmed et al.	N/A	N/A
5911750	12/1998	Mandel et al.	N/A	N/A
9456706	12/2015	Nguyen et al.	N/A	N/A
2016/0298652	12/2015	Saturley	N/A	H05K 7/20172
2019/0368507	12/2018	Xu	N/A	F04D 29/444
2022/0163250	12/2021	Wang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
203641106	12/2013	CN	N/A
104930790	12/2014	CN	N/A
106152663	12/2015	CN	N/A
110375491	12/2018	CN	N/A
209893738	12/2019	CN	N/A
110905854	12/2019	CN	N/A
210832696	12/2019	CN	N/A
213040840	12/2020	CN	N/A
213040841	12/2020	CN	N/A
2628416	12/2014	EP	N/A

OTHER PUBLICATIONS

Machine translation of CN210832696 (Year: 2020). cited by examiner
Machine translation of CN 110905854 (Year: 2020). cited by examiner
International Search Report and Written Opinion for PCT/CN2021/100125 (ISA/CN) mailed Aug. 27, 2021 w/partial English translation (10 pages). cited by applicant
1.SUP.st .Office Action for China Application No. 202010832823.6 dated Sep. 6, 2022 (9 pages). cited by applicant
European Search Report for European Patent Application No. 21803711.7 dated Oct. 24, 2023 (4 pages). cited by applicant
1.SUP.st .Office Action for European Patent Application No. 21803711.7 dated Nov. 17, 2023 (6 pages). cited by applicant
1.SUP.st .Examination Report for Australian Patent Application No. 2021270948 dated Nov. 30, 2023 (3 pages). cited by applicant

Primary Examiner: Trpisovsky; Joseph F

Attorney, Agent or Firm: troutman pepper locke

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is a national phase entry of International Application No. PCT/CN2021/100125, filed Jun. 15, 2021, which claims priority to Chinese Application No. 202010832823.6, filed Aug. 18, 2020, which are each incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

(2) The present invention relates to a refrigerating and freezing technology, and more particularly relates to an air-cooled refrigerator supplying air through a centrifugal fan.

BACKGROUND OF THE INVENTION

(3) A fan is one of essential devices of a refrigerator, and is commonly arranged in a fan volute so as to supercharge cooling airflow. But the fan volute in the prior art does not belong to an optimal helix design and has a wall surface turning point, and thus, fluid pressure cannot be naturally transferred on an inner wall surface via transition. When a fluid passes through the turning point, a flow state and a flow rate of the fluid will obviously change, which causes a pressure section difference and aerodynamic noise, thereby influencing user experience feeling.

BRIEF DESCRIPTION OF THE INVENTION

(4) An objective of the present invention aims to overcome at least one defect in the prior art, and provide an air-cooled refrigerator supplying air through a centrifugal fan.

(5) A further objective of the present invention aims to optimize flow characteristics of refrigeration airflow and reduce energy consumption.

(6) Another further objective of the present invention aims to simplify an installation process of the refrigerator.

(7) Particularly, the present invention provides an air-cooled refrigerator supplying air through a centrifugal fan, including: a bottom liner defining a cooling chamber and a storage space, where the cooling chamber is arranged below the storage space; an air duct back plate which is arranged in front of a rear wall of the bottom liner and defines, with the rear wall of the bottom liner, an air supply duct, where the air duct back plate is provided with at least one air supply port used for communicating with the air supply duct and the storage space; and the centrifugal fan, including: a

volute arranged at a rear portion of the cooling chamber in a manner of upwards inclining from front to back and internally defining a fan cavity located in a front portion and a gradually-widened exhaust cavity located at a rear portion of the fan cavity, where the fan cavity is in a continuous helix shape, an upper cover of the fan cavity is provided with an air inlet towards a front-upper direction, the gradually-widened exhaust cavity is gradually widened backwards from the fan cavity, and an air outlet connected to a lower end of the air supply duct is formed in a rear end of the exhaust cavity; and an impeller arranged in the fan cavity, where an axis of the impeller is opposite to the air inlet, to promote formation of refrigeration airflow exhausted to the air supply duct from the cooling chamber, and an inner wall surface of the fan cavity is in continuous and smooth transition so as to avoid a turning point.

(8) Furthermore, starting from the air outlet, a side wall of a transverse side of the gradually-widened exhaust cavity is inwards gradually concaved from back to front and is finally connected to a side wall of the fan cavity so as to form a volute tongue with the side wall of the fan cavity, and a side wall of the other transverse side of the gradually-widened exhaust cavity is in a plane shape extending front and back; and the side wall of the fan cavity is in a continuous logarithmic spiral from the volute tongue, and is finally connected to a front end of the plane-shaped side wall of the gradually-widened exhaust cavity.

(9) Furthermore, a distance between a center of the air inlet and the side wall of the fan cavity is gradually increased from the volute tongue to a position connected to the plane-shaped side wall of the gradually-widened exhaust cavity.

(10) Furthermore, distances between the center of the air inlet and side plates on two sides of the bottom liner are different, where the distance between the center of the air inlet and the side plate on the side, close to the volute tongue, of the bottom liner is greater than the distance between the center of the air inlet and the side plate on the side, close to the plane-shaped side wall of the gradually-widened exhaust cavity, of the bottom liner.

(11) Furthermore, the volute includes: a fan bottom shell fixed to a rear portion of a bottom wall of the bottom liner; and a fan upper cover obliquely downwards extending into the cooling chamber from a lower end of the air duct back plate and covering and buckling the fan bottom shell.

(12) Furthermore, the fan upper cover and the air duct back plate are an integrally-formed part.

(13) Furthermore, a position, below the air supply port, of the air duct back plate is further provided with at least one transversely extending water stop rib used for stopping condensate water at the air supply port from downwards flowing into the volute.

(14) Furthermore, the air-cooled refrigerator further includes: an evaporator which is integrally in a flat cuboid shape and is arranged at a front portion of the cooling chamber.

(15) The bottom wall of the bottom liner includes: an evaporator support portion used for supporting the evaporator; and a fan support portion, from a rear end of the evaporator support portion, upwards obliquely arranged from front to back, where the fan bottom shell is fixed to the fan support portion.

(16) Furthermore, a bottom of the fan bottom shell is provided with a plurality of damping sticky pads, and the fan bottom shell is bonded with the fan support portion through the plurality of damping sticky pads.

(17) Furthermore, the fan bottom shell is further provided with a wiring channel used for accommodating a cable connecting the impeller.

(18) In the air-cooled refrigerator of the present invention, the fan cavity and the gradually-widened exhaust cavity are formed in the volute for accommodating the centrifugal fan, the fan cavity is in the continuous helix shape, the gradually-widened exhaust cavity is configured to be backwards gradually widened from the fan cavity, the inner wall surface of the fan cavity is in continuous and smooth transition so as to smoothly guide refrigeration airflow supercharged by the centrifugal fan to the gradually-widened exhaust cavity, thereby avoiding an airflow turning point, and reducing energy losses of the refrigeration airflow as much as possible, and technical effects of the air-

cooled refrigerator have been verified by trial products.

(19) Furthermore, in the air-cooled refrigerator of the present invention, the air duct back plate and the fan upper cover are the integrally-formed part so as to form modularization and facilitate batched production. During assembling, an installer can firstly install the integrally-formed part, and then can directly connect an evaporator upper cover with the integrally-formed part, which not only can simplify an installation process and reduce costs, but also make a whole air duct structure more stable.

(20) Specific embodiments of the present invention are described in detail as below by combining drawings, and those skilled in the art will more clearly understand the above and other purposes, advantages and features of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Some specific embodiments of the present invention are exemplarily described without limitation in detail by referring to the drawings below. Same reference numerals in the drawings mark same or similar components or parts. Those skilled in the art should understand that the drawings are unnecessarily drawn to scale. In the drawings:

(2) FIG. 1 is a schematic diagram of a refrigerator according to an embodiment of the present invention;

(3) FIG. 2 is an exploded view of a refrigerator according to an embodiment of the present invention, in which a shell is hidden;

(4) FIG. 3 is a section view of a refrigerator according to an embodiment of the present invention, in which a shell is hidden;

(5) FIG. 4 is a position relationship diagram of a fan bottom shell, an impeller, a fan upper cover and an air duct back plate of a refrigerator according to an embodiment of the present invention, in which a bending section above the air duct back plate is hidden;

(6) FIG. 5 is a schematic diagram of an installation relationship of a fan upper cover and an air duct back plate observed facing a bottom of the fan upper cover in a refrigerator according to an embodiment of the present invention; and

(7) FIG. 6 is a bottom view of a fan bottom shell in a refrigerator according to an embodiment of the present invention, which shows damping sticky pads and a wiring channel.

DETAILED DESCRIPTION

(8) In the description of the embodiments, it needs to be understood that directions or position relationships indicated by terms “longitudinal”, “transverse”, “length”, “width”, “thickness”, “upper”, “lower”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “depth”, etc. refer to directions in a normal usage state of a refrigerator and can be determined by referring to directions or position relationships shown in drawings. For example, “front” indicating the direction refers to a side, towards a user, of the refrigerator. The directions or position relationships are merely used for conveniently describing the present invention and simplifying the description, but do not indicate or imply that referred devices or components must be in specific directions or structured and operated in specific directions, and thus should not be understood as limitations to the present invention.

(9) Referring to FIG. 1, a refrigerator 1 in the embodiment commonly may include a cabinet 10, and the cabinet 10 may include a shell, a liner, a thermal insulation layer, other accessories, etc. The shell is an outer-layer structure of the refrigerator, and protects the whole refrigerator. To isolate heat conduction to an outside, the thermal insulation layer is additionally arranged between the shell and the liner of the cabinet 10 and is commonly formed by a foaming technology. There may be one or more liners. The liners may be divided into a refrigeration liner, a variable-

temperature liner, a freezing liner, etc. according to functions at will, and the specific number and functions of the liners may be configured according to usage requirements of the refrigerator. In the embodiment, the liner at least includes a bottom liner **100** commonly being the freezing liner.

(10) Referring to FIG. 2 and FIG. 3, an air-cooled refrigerator **1** in the embodiment may further include a bottom liner **100**, a storage space **110** and a cooling chamber **120** are defined in the bottom liner **100**, and the cooling chamber **120** is arranged below the storage space **110**. An evaporator upper cover **250** is arranged below the bottom liner **100**, transversely arranged in the bottom liner **100** and used for defining the storage space **110** and the cooling chamber **120** in the liner **100**. The cooling chamber **120** is arranged below the storage space **110**, and an evaporator **300** is arranged in the cooling chamber **120**.

(11) Namely, the evaporator **300** in the embodiment is located at a lower part of the bottom liner **100**, which avoids a situation that an evaporator of a conventional refrigerator occupies a rear space of a freezing chamber, and consequently a depth of the freezing chamber is reduced; and especially for a side-by-side refrigerator, it is particularly important to increase a depth of a freezing chamber in response to a small transverse size of the freezing chamber. Thus, a space utilization rate of the refrigerator **1** is improved, thereby facilitating storage of large objects difficult to be divided.

(12) In addition, a bottommost freezing chamber in the conventional refrigerator is located at a low position, and thus a user needs to deeply stoop or squat down so as to take and place objects in the freezing chamber, which is inconvenient for the user, particularly for old people. However, in the embodiment, the cooling chamber **120** occupies a lower space of the bottom liner **100**, as a result, a height of the storage space **110** above the cooling chamber **120** is increased, and a stoop degree when the user takes and places the objects in the storage space **110** is reduced, thereby improving use experience of the user.

(13) In the embodiment, the evaporator **300** is integrally in a flat cuboid shape, is arranged at a front portion of the cooling chamber **120**, and is obliquely arranged in the cooling chamber **120**. The manner breaks through a technical constraint that an evaporator needs to be horizontally placed to reduce a depth in the prior art. Inclined placement of the flat-cuboid evaporator **300** increases a length in a front-back direction, but makes arrangement of other components in the cooling chamber **120** more reasonable; and in addition, a practical airflow field analysis proves that air circulation efficiency is higher and water drainage is smoother. A layout manner of inclined arrangement of the evaporator **300** is one of main technological improvements made by the embodiment. In some specific embodiments, an inclination angle of the evaporator **300** ranges from 7 degrees to 8 degrees, e.g., 7 degrees, 7.5 degrees and 8 degrees, preferably 7.5 degrees.

(14) Referring to FIG. 2 to FIG. 5, the air-cooled refrigerator **1** in the embodiment may further include an air duct back plate **230** and a centrifugal fan. The air duct back plate **230** is arranged in front of a rear wall **112** of the bottom liner **100**, may serve as at least one part of an air duct plate of the bottom liner **100**, is roughly parallel to the rear wall **112** of the bottom liner **100**, and defines, with the rear wall **112** of the bottom liner **100**, an air supply duct **130**. In addition, the air duct back plate **230** is provided with at least one air supply port **232** used for communicating with the air supply duct **130** and the storage space **110**.

(15) The centrifugal fan may further include a volute and an impeller **220**. The volute is arranged at a rear portion of the cooling chamber **120** in a manner of upwards inclining from front to back and internally defines a fan cavity **242** in a front portion and a gradually-widened exhaust cavity **246** located at a rear portion of the fan cavity **242**, where the fan cavity **242** is in a continuous helix shape, and an upper cover of the fan cavity is provided with an air inlet **244** towards a front-upper direction; and the gradually-widened exhaust cavity **246** is backwards widened gradually from the fan cavity **242**, and an air outlet **140** connected to a lower end of the air supply duct **130** is formed in a rear end of the exhaust cavity. The impeller **220** is arranged in the fan cavity **242**, an axis **222** of the impeller **220** is opposite to the air inlet **244** so as to promote formation of refrigeration airflow exhausted towards the air supply duct **130** from the cooling chamber **120**, and an inner wall

surface **242a** of the fan cavity **242** is in continuous and smooth transition so as to avoid a turning point.

(16) In the embodiment, the centrifugal fan can exhaust airflow from the air inlet **244** in a direction perpendicular to the air inlet **244**. After airflow in the cooling chamber **120** is sucked by the centrifugal fan from the air inlet **244**, the airflow is exhausted into the fan cavity **242** in a direction perpendicular to the air inlet **244**, and then enters the gradually-widened exhaust cavity **246** through the fan cavity **242**. The gradually-widened exhaust cavity **246** connects the fan cavity **242** with the air supply duct **130**, and finally, the refrigeration airflow supercharged by the centrifugal fan is exhausted into the air supply duct **130**.

(17) The air supply duct **130** is jointly defined by the air duct back plate **230** and the rear wall **112** of the bottom liner **100**. The air duct back plate **230** is provided with at least one air supply port **232** used for communicating the air supply duct **130** with the storage space **110**. The refrigeration airflow exhausted into the air supply duct **130** can be exhausted into the storage space **110** from the air supply port **232** so as to exchange heat with hot air in the storage space **110**, thereby cooling the storage space **110**. A front side of the evaporator upper cover **250** may be further provided with an air return port (unshown in drawings) communicating the storage space **110** with the cooling chamber **120**. Hot air subjected to heat exchange may flow back into the cooling chamber **120** from the air return port to continuously exchange heat with the evaporator **300**, thereby forming a circulating airflow path.

(18) In the embodiment, the inner wall surface **242a** of the fan cavity **242** for accommodating the impeller **220** is in continuous and smooth transition. Continuous and smooth transition mentioned herein may be understood as the inner wall surface **242a** of the fan cavity **242** being a section of continuous and smooth arc wall surface so as to smoothly guide the refrigeration airflow supercharged by the centrifugal fan into the gradually-widened exhaust cavity **246**, thereby reducing probability of turning point occurrence, greatly reducing vortexes generated due to a turning point in an airflow field, and reducing energy losses of the refrigeration airflow as much as possible.

(19) In some embodiments of the present invention, starting from the air outlet **140**, a side wall of a transverse side of the gradually-widened exhaust cavity **246** is inwards gradually concaved from back to front and is finally connected to a side wall of the fan cavity **242** so as to form a volute tongue **248** with the inner wall surface **242a** of the fan cavity **242**, and a side wall of the other transverse side of the gradually-widened exhaust cavity **246** is in a plane shape extending front and back; and the inner wall surface **242a** of the fan cavity **242** is in a continuous logarithmic spiral from the volute tongue **248**, and is finally connected to a front end of the plane-shaped side wall of the gradually-widened exhaust cavity **246**.

(20) Referring to FIG. 5, the side walls of the gradually-widened exhaust cavity **246** in the embodiment may include a first side wall **246a** close to the volute tongue **248** and a second side wall **246b** away from the volute tongue **248**, and the first side wall **246a** and the second side wall **246b** are located at opposite positions so as to jointly define the gradually-widened exhaust cavity **246**. Starting from one side of the air outlet **140**, the first side wall **246a** is inwards gradually concaved from back to front. The second side wall **246b** is in a plane shape extending front and back and extends to the inner wall surface **242a** of the fan cavity **242** from the other side of the air outlet **140**. Namely, the first side wall **246a**, the inner wall surface **242a** of the fan cavity **242** and the second side wall **246b** are sequentially arranged. The volute tongue **248** is formed at a joint of the first side wall **246a** and the inner wall surface **242a** of the fan cavity **242** so that part of airflow in the fan cavity **242** can internally and circularly flow nearby the volute tongue **248**, thereby optimizing flow characteristics of the airflow. Technical effects achieved by the volute tongue **248** formed in the volute and the inner wall surface **242a** of the fan cavity **242** in a logarithmic spiral in the embodiment have been verified by trial products.

(21) It needs to be explained that the direction from back to front may be understood as a direction

from the air supply duct **130** to the storage space **110**, and an inward direction may be understood as a direction towards the inner wall surface **242a** of the fan cavity **242**.

(22) In some specific embodiments, a distance between a center of the air inlet **244** and the inner wall surface **242a** of the fan cavity **242** is gradually increased from the volute tongue **248** to a position connected to the plane-shaped side wall of the gradually-widened exhaust cavity **246**.

(23) Referring to FIG. 5, a point O in FIG. 5 represents the center of the air inlet **244**, and R represents the distance between the center of the air inlet **244** and the inner wall surface **242a** of the fan cavity **242**. Obviously, the inner wall surface **242a** of the fan cavity **242** may be gradually widened from an end close to the volute tongue **248** to an end away from the volute tongue **248**, which further optimizes the flow characteristics of airflow, and technical effects have been verified by trial products.

(24) In some embodiments of the present invention, distances between the center of the air inlet **244** and side plates **114** on two sides of the bottom liner **100** are different, where the distance between the center of the air inlet **244** and the side plate **114** on the side, close to the volute tongue **248**, of the bottom liner **100** is greater than the distance between the center of the air inlet **244** and the side plate **114** on the side, close to the plane-shaped side wall of the gradually-widened exhaust cavity **246**, of the bottom liner **100**.

(25) Referring to FIG. 2 and FIG. 5, L1 in FIG. 5 represents a distance between the center O of the air inlet **244** and a side edge, close to the volute tongue **248**, of the air duct back plate **230**, and L2 represents a distance between the center O of the air inlet **244** and a side edge, away from the volute tongue **248**, of the air duct back plate **230**. The air duct back plate **230** is located in front of the rear wall **112** of the bottom liner **100**, and the side edges of the air duct back plate **230** are connected to the side plates **114** of the bottom liner **100** respectively. Namely, L1 may represent the distance between the center O of the air inlet **244** and the side plate **114** on the side, close to the volute tongue **248**, of the bottom liner **100**, and L2 may represent the distance between the center O of the air inlet **244** and the side plate **114** on the side, away from the volute tongue **248**, of the bottom liner **100**. Obviously, as shown in FIG. 5, L1 is longer than L2. In other words, the air inlet **244** is not located in a middle below the air duct back plate **230**, and the unique arrangement is concluded by an inventor via multi-time experiments, thereby further optimizing the flow characteristics of the airflow. In addition, the arrangement manner can make the centrifugal fan located on one side of the cooling chamber **120** so as to vacate a part of space below the centrifugal fan, thereby conveniently arranging a pipe section of the evaporator **300** or other components, and then arranging the whole cooling chamber **120** more reasonably and compactly.

(26) Referring to FIG. 2 to FIG. 6, in some embodiments of the present invention, the volute includes a fan bottom shell **210** and a fan upper cover **240**. The fan bottom shell **210** is fixed to a rear portion of a bottom wall of the bottom liner **100**; and the fan upper cover **240** obliquely downwards extends into the cooling chamber **120** from a lower end of the air duct back plate **230** and covers and buckles the fan bottom shell **210**.

(27) In the embodiment, the fan upper cover **240** is located above the fan bottom shell **210**, namely, the air inlet **244** may be formed in the fan upper cover **240**, and the fan bottom shell **210** and the fan upper cover **240** may jointly define the fan cavity **242** and the gradually-widened exhaust cavity **246** in the above embodiments. After being connected, the fan bottom shell **210** and the fan upper cover **240** may obliquely downwards extend into the cooling chamber **120** as well, and the air outlet **140** is formed in a position where a rear end of the fan bottom shell **210** is connected to the air duct back plate **230**.

(28) Referring to FIG. 6, the fan bottom shell **210** and the fan upper cover **240** may be connected together in a clamping connection form. Specifically, a plurality of clamp hooks **215** are arranged on an outer edge of the fan bottom shell **210**. Correspondingly, the fan upper cover **240** may be provided with a plurality of buckles (unshown in drawings) matched with the clamp hooks **215**. Through the clamp hooks **215** and the buckles, the fan bottom shell **210** and the fan upper cover

240 may be fixedly connected together and are convenient to dismount and mount. Of course, connection may be performed through other fixing manners which are not repeated.

(29) Furthermore, the fan upper cover **240** and the air duct back plate **230** are an integrally-formed part. The manner is different from an air duct plate and a fan volute in the prior art. In the existing refrigerator, an air duct plate and a fan volute arranged in an air duct are commonly two devices relatively independent. During assembling, an installer commonly needs to connect the air duct plate with the fan volute through a large number of fasteners, which will cause a complex installing technology, increases costs and does not facilitate batched production.

(30) However, the air duct back plate **230** and the fan upper cover **240** in the embodiment are the integrally-formed part so as to form modularization and facilitate batched production. During assembling, the installer can firstly install the integrally-formed part, and then can directly connect the evaporator upper cover **250** with the integrally-formed part, which not only can simplify an installation process and reduce costs, but also make a whole air duct structure more stable.

(31) Referring to FIG. 4, in some embodiments of the present invention, a position, below the air supply port **232**, of the air duct back plate **230** is further provided with at least one transversely extending water stop rib **235** used for stopping condensate water at the air supply port **232** from downwards flowing into the volute.

(32) In the embodiment, the water stop rib **235** may be arranged on one side, towards the storage space **110**, of the air duct back plate **230**. Since airflow contains part of condensate water, the condensate water can be attached to a surface of the air duct back plate **230** when the airflow encounters the air duct back plate **230**, and the water stop rib **235** can reduce a falling speed of the condensate water to make all the condensate water evaporate as much as possible, and prevent the condensate water from falling into the fan cavity **242** and causing faults.

(33) In the embodiment, transversely extending may refer to horizontal extension and may also be understood that the water stop rib **235** has a certain inclination angle. The two above manners both can reduce the falling speed of the condensate water on the water stop rib **235**.

(34) Referring to FIG. 3, in some embodiments of the present invention, the bottom wall of the bottom liner **100** may include an evaporator support portion **150** and a fan support portion **160**. The evaporator support portion **150** is used for supporting the evaporator **300**; and the fan support portion **160**, from a rear end of the evaporator support portion **150**, is upwards obliquely arranged from front to back, and the fan bottom shell **210** is fixed to the fan support portion **160**, so that the fan cavity **242** is integrally obliquely disposed at a rear portion of the evaporator **300**.

(35) In the embodiment, the evaporator support portion **150** and the fan support portion **160** are connected and may serve as a part of a partition plate for dividing a liner **100** and a compressor chamber **180** in the cabinet **10**. A front portion of the evaporator support portion **150** may further be provided with an inclined portion **170**. The inclined portion **170**, from a front end of the bottom wall of the bottom liner **100**, is downwards obliquely arranged from front to back. The evaporator support portion **150**, from a rear end of the inclined portion **170**, is upwards obliquely arranged from front to back so that the evaporator **300** can be obliquely arranged in the cooling chamber **120**. A drainage channel **152** is formed in a position where the inclined portion **170** is connected to the evaporator support portion **150** so as to receive defrosted water on the evaporator **300**.

(36) The fan support portion **160**, from a rear end of the evaporator support portion **150**, is upwards obliquely arranged from front to back. In some preferable embodiments, an inclination angle of the fan support portion **160** is greater than that of the evaporator support portion **150**, the inclination angle of the fan support portion **160** relative to a horizontal direction is set as 36-37 degrees, e.g., 36 degrees, 36.5 degrees and 37 degrees, preferably 36.7 degrees. Correspondingly, the fan bottom shell **210** acts on the fan support portion **160** and may similarly has the above angle inclination setting.

(37) Referring to FIG. 6, in some embodiments of the present invention, a bottom of the fan bottom shell **210** is provided with a plurality of damping sticky pads **212**, and the fan bottom shell **210** is

bonded with the fan support portion **160** through the plurality of damping sticky pads **212**.

(38) The damping sticky pads **212** may be made from flexible materials with viscous force. The bottom of the fan bottom shell **210** is provided with three outwards-protruding damping sticky pads **212** roughly distributed at a lower portion of the fan bottom shell **210** by 120 degrees so as to bond the fan support portion **160** and the fan bottom shell **210**. Meanwhile, the damping sticky pads **212** made from the flexible materials can further effectively reduce noise generated during operation of fan blades **220**, and simultaneously reduce vibration transfer efficiency during operation of the fan blades **220**, improving user experience feeling. It needs to be explained that two, or four, or five or more damping sticky pads **212** may be set, and the present invention does not specially limit the specific number and distribution positions of the damping sticky pads **212**.

(39) Referring to FIG. 6, in some embodiments of the present invention, the fan bottom shell **210** is further provided with a wiring channel **214** used for accommodating a cable connecting the impeller **220**.

(40) Specifically, the bottom of the fan bottom shell **210** is inwards concaved to form the wiring channel **214**, and in other words, the wiring channel **214** is located in an outer surface of the fan bottom shell **210**. An elastic wire pressing plate **216** may be arranged above a surface of the wiring channel **214**, and a front portion of the wiring channel **214** may also be provided with a wire hole **218**. The cable of the impeller **220** may be arranged in the wiring channel **214** in a length direction, and the elastic wire pressing plate **216** may fix the cable of the impeller **220**, thereby preventing the cable from loosening and sliding out of the wiring channel **214**. The cable of the impeller **220** enters an inner surface of the fan bottom shell **210** (namely, enters the fan cavity **242**) through the wire hole **218** after being fixed by the wiring channel **214** and the elastic wire pressing plate **216**, and then may be electrically connected to the impeller **220**.

(41) Referring to FIG. 2 to FIG. 4, in some embodiments of the present invention, the air duct back plate **230** is a single-layer board integrally formed by injection molding. An upper portion of the air duct back plate **230** is provided with a folding groove **236**, and accordingly, the air duct back plate **230** can be conveniently bent by the folding groove **236** during installation.

(42) In the embodiment, the upper portion of the air duct back plate **230** is provided with a bending section **238**, a lower portion of the bending section **238** may stretch into the folding groove **236** and can rotate around the folding groove **236** by a certain angle so as to shorten a height of the air duct back plate **230**. During installation, the installer can stretch the bending section **238** into the folding groove **236** and outwards rotate the bending section **238** by a certain angle so as to shorten the height of the air duct back plate **230**. Then, the installer can connect the rest of positions of the air duct back plate with the liner **100** or other components, and then overturns and restores the bending section **238** so as to simplify an installation process.

(43) Herein, those skilled in the art can realize that although the Description has shown and described a plurality of exemplary embodiments of the present invention in detail, many other variations or modifications conforming to the principle of the present invention still can be directly determined or deduced according to the content disclosed by the present invention without departing from the spirit and the scope of the present invention. Thus, the scope of the present invention should be understood and affirmed to cover all these other variations or modifications.

Claims

1. An air-cooled refrigerator supplying air through a centrifugal fan, comprising: a bottom liner defining a cooling chamber and a storage space, wherein the cooling chamber is arranged below the storage space; an air duct back plate which is arranged in front of a rear wall of the bottom liner and defines, with the rear wall of the bottom liner, an air supply duct, wherein the air duct back plate is provided with at least one air supply port used for communicating with the air supply duct and the storage space; and the centrifugal fan, comprising: a volute arranged at a rear portion of the

cooling chamber in a manner of upwards inclining from front to back and internally defining a fan cavity located in a front portion and a gradually-widened exhaust cavity located at a rear portion of the fan cavity, wherein the fan cavity is in a continuous helix shape, an upper cover of the fan cavity is provided with an air inlet towards a front-upper direction, the gradually-widened exhaust cavity is gradually widened backwards from the fan cavity, and an air outlet connected to a lower end of the air supply duct is formed in a rear end of the exhaust cavity; and an impeller arranged in the fan cavity, wherein an axis of the impeller is opposite to the air inlet, to promote formation of refrigeration airflow exhausted to the air supply duct from the cooling chamber, and an inner wall surface of the fan cavity is in continuous and smooth transition so as to avoid a turning point, wherein starting from the air outlet, a side wall of a transverse side of the gradually-widened exhaust cavity is inwards gradually concaved from back to front and is finally connected to a side wall of the fan cavity so as to form a volute tongue with the side wall of the fan cavity, and a side wall of the other transverse side of the gradually-widened exhaust cavity is in a plane shape extending front and back; and the side wall of the fan cavity is in a continuous logarithmic spiral from the volute tongue, and is finally connected to a front end of the plane-shaped side wall of the gradually-widened exhaust cavity.

2. The air-cooled refrigerator according to claim 1, wherein a distance between a center of the air inlet and the side wall of the fan cavity is gradually increased from the volute tongue to a position connected to the plane-shaped side wall of the gradually-widened exhaust cavity.

3. The air-cooled refrigerator according to claim 1, wherein distances between a center of the air inlet and side plates on two sides of the bottom liner are different, wherein the distance between the center of the air inlet and the side plate on the side, close to the volute tongue, of the bottom liner is greater than the distance between the center of the air inlet and the side plate on the side, close to the plane-shaped side wall of the gradually-widened exhaust cavity, of the bottom liner.

4. The air-cooled refrigerator according to claim 1, wherein the volute comprises: a fan bottom shell fixed to a rear portion of a bottom wall of the bottom liner; and a fan upper cover obliquely downwards extending into the cooling chamber from a lower end of the air duct back plate and covering and buckling the fan bottom shell.

5. The air-cooled refrigerator according to claim 4, wherein the fan upper cover and the air duct back plate are an integrally-formed part.

6. The air-cooled refrigerator according to claim 5, wherein a position, below the air supply port, of the air duct back plate is further provided with at least one transversely extending water stop rib used for stopping condensate water at the air supply port from downwards flowing into the volute.

7. The air-cooled refrigerator according to claim 4, further comprising: an evaporator which is integrally in a flat cuboid shape and is arranged at a front portion of the cooling chamber; and the bottom wall of the bottom liner comprising: an evaporator support portion used for supporting the evaporator; and a fan support portion, from a rear end of the evaporator support portion, upwards obliquely arranged from front to back, wherein the fan bottom shell is fixed to the fan support portion.

8. The air-cooled refrigerator according to claim 7, wherein a bottom of the fan bottom shell is provided with a plurality of damping sticky pads, and the fan bottom shell is bonded with the fan support portion through the plurality of damping sticky pads.

9. The air-cooled refrigerator according to claim 4, wherein the fan bottom shell is further provided with a wiring channel used for accommodating a cable connecting the impeller.

10. The air-cooled refrigerator according to claim 7, wherein the bottom wall of the bottom liner further comprises: an inclined portion provided in front of the evaporator and downwards obliquely arranged from front to back from a front end of the bottom wall of the bottom liner; the evaporator support portion is upwards obliquely arranged from front to back so that the evaporator is obliquely arranged in the cooling chamber; and a drainage channel is formed between the inclined portion and the evaporator support portion to receive defrosted water from the evaporator.

11. The air-cooled refrigerator according to claim 9, wherein the wiring channel is located in an outer surface of the fan bottom shell and is formed by concaving a bottom of the fan bottom shell inwards.

12. The air-cooled refrigerator according to claim 11, wherein the fan bottom shell is further provided with an elastic wire pressing plate on the wiring channel, and a wire hole located at an end of the wiring channel extending towards a center of the fan bottom shell.
