

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398951
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ji; Lisheng et al.

Control method for refrigerating and freezing device, and refrigerating and freezing device

Abstract

Provided are a control method for a refrigerating and freezing device, and the refrigerating and freezing device. The refrigerating and freezing device includes a cabinet provided with a groove communicating with a surrounding environment and sunken inwards, and at least one fan for promoting air of the surrounding environment to flow into the groove. The control method includes: judging whether a temperature in the groove is less than or equal to a dew point temperature; and if yes, controlling the fan to operate at a first preset rotation speed. The temperature in the groove is increased by controlling the fan to operate to introduce hot air of the surrounding environment into the groove when the temperature in the groove is less than or equal to the dew point temperature, which avoids condensation in the groove and improves safety and reliability of electrical parts in the groove.

Inventors:	Ji; Lisheng (Qingdao, CN), Li; Chunyang (Qingdao, CN), Han; Zhiqiang (Qingdao, CN), Cui; Zhanpeng (Qingdao, CN), Qi; Feifei (Qingdao, CN), Wang; Kai (Qingdao, CN)
Applicant:	CHONGQING HAIER REFRIGERATION ELECTRIC APPLIANCE CO., LTD. (Chongqing, CN); QINGDAO HAIER REFRIGERATOR CO., LTD. (Shandong, CN); HAIER SMART HOME CO., LTD. (Shandong, CN)
Family ID:	1000008780164
Assignee:	CHONGQING HAIER REFRIGERATION ELECTRIC APPLIANCE CO., LTD. (Chongqing, CN); QINGDAO HAIER REFRIGERATOR CO., LTD. (Shandong, CN); HAIER SMART HOME CO., LTD. (Shandong, CN)
Appl. No.:	18/004536
Filed (or PCT Filed):	June 29, 2021

PCT No.: PCT/CN2021/103181

PCT Pub. No.: WO2021/223779

PCT Pub. Date: November 11, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230243584 A1	Aug. 03, 2023

Foreign Application Priority Data

CN	202010653070.2	Jul. 08, 2020
----	----------------	---------------

Publication Classification

Int. Cl.: F25D29/00 (20060101); F25D11/02 (20060101); F25D23/00 (20060101); F25D31/00 (20060101)

U.S. Cl.:

CPC F25D29/00 (20130101); F25D11/02 (20130101); F25D23/003 (20130101); F25D31/005 (20130101); F25D2317/068 (20130101); F25D2600/02 (20130101); F25D2600/06 (20130101)

Field of Classification Search

CPC: F25D (29/00); F25D (11/02); F25D (23/003); F25D (31/005); F25D (2600/06); F25D (2600/02); F25D (21/04); F25D (23/12); F25B (2600/11); Y02B (30/70); H05B (6/62)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10935301	12/2020	Sung	N/A	N/A
2003/0041614	12/2002	Burn	N/A	N/A
2018/0274825	12/2017	Choi et al.	N/A	N/A
2019/0107296	12/2018	Clark	N/A	F24F 11/30

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2619366	12/2003	CN	N/A
107543351	12/2017	CN	N/A
107782044	12/2017	CN	N/A
109990562	12/2018	CN	N/A
209893721	12/2019	CN	N/A
209893723	12/2019	CN	A23L 3/365
211041170	12/2019	CN	N/A

H08-205999	12/1995	JP	N/A
2006-114532	12/2005	JP	N/A
2013-029220	12/2012	JP	N/A
20180114591	12/2017	KR	N/A
WO-2011135863	12/2010	WO	F25D 17/065

OTHER PUBLICATIONS

Office Action issued for Japan Patent Application No. 2023501228 mailed Jun. 24, 2024, with English translation (9 pages). cited by applicant

European Search Report for European Patent Application No. 21799887.1 dated Oct. 11, 2023 (4 pages). cited by applicant

1.SUP.st .Office Action for European Patent Application No. 21799887.1 dated Nov. 6, 2023 (9 pages). cited by applicant

1.SUP.st .Examination Report for Australian Patent Application No. 2021268441 dated Oct. 19, 2023 (2 pages). cited by applicant

International Search Report and Written Opinion for PCT/CN2021/103181 (ISA/CN) mailed Aug. 23, 2021 (8 pages). cited by applicant

Primary Examiner: Ma; Kun Kai

Attorney, Agent or Firm: troutman pepper locke

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is a national phase entry of International Application No. PCT/CN2021/103181, filed Jun. 29, 2021, which claims priority to Chinese Application No. 202010653070.2, filed Jul. 8, 2020, which are each incorporated herein by reference in entirety.

FIELD OF THE INVENTION

(2) The present invention relates to the field of refrigerating and freezing, and particularly relates to a control method for a refrigerating and freezing device, and the refrigerating and freezing device.

BACKGROUND OF THE INVENTION

(3) In order to facilitate heat dissipation of part of electrical parts of a refrigerator, in the prior art, the part of electrical parts that need to dissipate heat are arranged on the outer side of a thermal insulating layer of the refrigerator. But, since the electrical parts themselves need to occupy a certain space, there is a need for a heat-dissipating gap between the electrical parts and a cover plate, while taking into account that the overall height or thickness of the refrigerator cannot be arbitrarily changed, a cabinet of the refrigerator is provided with a groove communicating with the surrounding environment, which is used to accommodate the part of electrical parts that need to dissipate heat and a fan for heat dissipation. However, the arrangement of the groove results in that a corresponding thermal insulating layer is relatively thin. When the humidity of the surrounding environment is high and the electrical parts are not started, a phenomenon of condensation would occur, leading to a malfunction of the electrical parts and even potential safety hazards. All things considered, there is a need for a control method capable of improving safety and reliability and used for a refrigerating and freezing device, and the refrigerating and freezing device in devising.

BRIEF DESCRIPTION OF THE INVENTION

(4) One objective of a first aspect of the present invention is to overcome at least one technical

defect of the prior art and to provide a control method for a refrigerating and freezing device.

(5) One further objective of the first aspect of the present invention is to prevent a fan from being started frequently.

(6) Another further objective of the first aspect of the present invention is to shorten the continuous working time of the fan.

(7) One objective of a second aspect of the present invention is to provide a refrigerating and freezing device.

(8) According to the first aspect of the present invention, provided is a control method for a refrigerating and freezing device. The refrigerating and freezing device includes a cabinet provided with a groove communicating with a surrounding environment and recessed inwards, and at least one fan for promoting air of the surrounding environment to flow into the groove. The control method includes: judging whether a temperature in the groove is less than or equal to a dew point temperature; and if yes, controlling the fan to operate at a first preset rotation speed.

(9) Optionally, after the step of controlling the fan to operate at a first preset rotation speed, the control method also includes: judging whether the temperature in the groove is greater than or equal to an ambient temperature; and if yes, controlling the fan to stop operating after a first preset time.

(10) Optionally, after the step of controlling the fan to operate at a first preset rotation speed, the control method also includes: controlling, when the temperature in the groove is greater than or equal to an ambient temperature, the fan to stop operating.

(11) Optionally, the refrigerating and freezing device includes an electromagnetic wave generation system. A power supply module of the electromagnetic wave generation system is at least partially arranged in the groove. After the step of controlling the fan to operate at a first preset rotation speed, the control method also includes: judging whether the temperature in the groove is greater than or equal to an ambient temperature; and if not, powering on the power supply module to produce heat.

(12) Optionally, after performing the step of controlling the fan to operate at a first preset rotation speed for a second preset time, the step of judging whether the temperature in the groove is greater than or equal to the ambient temperature is performed.

(13) Optionally, the control method further includes: stopping powering on the power supply module when the temperature in the groove is greater than or equal to the ambient temperature.

(14) Optionally, the refrigerating and freezing device includes an electromagnetic wave generation system. An electromagnetic wave generation module of the electromagnetic wave generation system is at least partially arranged in the groove. Before the step of judging whether the temperature in the groove is less than or equal to a dew point temperature, the control method further includes: judging whether the electromagnetic wave generation module works; if yes, controlling the fan to operate at a second preset rotation speed; and if not, performing the step of judging whether the temperature in the groove is less than or equal to a dew point temperature, wherein the second preset rotation speed is greater than the first preset rotation speed.

(15) Optionally, a temperature of the electromagnetic wave generation module is used as the temperature in the groove.

(16) According to the second aspect of the present invention, provided is a refrigerating and freezing device, including: a cabinet, provided with a groove communicating with a surrounding environment and recessed inwards; at least one fan, configured to promote air of the surrounding environment to flow into the groove; and a controller, including a processing unit and a storage unit storing a computer program which, when executed by the processing unit, is used to implement the control method according to any one of the embodiments of the present invention.

(17) Optionally, the refrigerating and freezing device further includes: an electromagnetic wave generation system, including an electromagnetic wave generation module and a power supply module which are at least partially arranged in the groove; a heat-dissipating fin, including a

plurality of ribbed plates perpendicular to the electromagnetic wave generation module and thermally connected with the electromagnetic wave generation module, at least one of the ribbed plates thermally connected with the middle of the electromagnetic wave generation module being provided with an accommodating portion sunken in a direction close to the electromagnetic wave generation module for accommodating the at least one fan; a housing, configured to house the electromagnetic wave generation module, the power supply module and the at least one fan; and a separation plate, arranged in the housing and located on a side of the at least one fan away from the electromagnetic wave generation module, so as to separate a space in the housing into an air inlet area and an air outlet area, wherein the electromagnetic wave generation module, the power supply module and the at least one fan are arranged in the air outlet area; the air inlet area and the air outlet area are provided with at least one air inlet and at least one air outlet in a circumferential direction of the at least one fan, respectively, and the separation plate is provided with at least one ventilation opening at a position corresponding to the at least one fan; airflow flowing directions from the at least one air inlet to the at least one ventilation opening are all perpendicular to airflow flowing directions from the at least one ventilation opening to each of the air outlets; and the power supply module is located on a side of the electromagnetic wave generation module perpendicular to the airflow flowing directions from the at least one ventilation opening to each of the air outlets, and thermally connected with the separation plate through a heat conduction material.

(18) In the present invention, the temperature in the groove is increased by controlling the fan to operate to introduce the hot air of the surrounding environment into the groove when the temperature in the groove is less than or equal to the dew point temperature, which avoids condensation in the groove and improves safety and reliability of electrical parts in the groove. Furthermore, compared with an anti-condensation mode of arranging a heating wire or a heat pipe in the groove, this mode is low in cost and simple in process, and the production cost is reduced.

Further, in the present invention, an original heat-dissipating fan may be utilized for anti-condensation, and the technical bias in the prior art that the heat-dissipating fan does not work when electrical parts are not started is overcome, such that the production cost is further reduced.

(19) Further, in the present invention, when the temperature in the groove is greater than or equal to the ambient temperature, after a first preset time, the fan is controlled to stop operating, which can effectively prevent condensation in the groove, prevent the fan from being started frequently, and prolong the service life of the fan.

(20) Further, in the present invention, the groove is further heated by powering on the power supply module to produce heat, which fully utilizes the original structure of the refrigerating and freezing device, shortens the continuous working time of the fan, further prolongs the service life of the fan, and reduces noise.

(21) Further, in the present invention, the temperature of the electromagnetic wave generation module is used as the temperature in the groove for control, which can more accurately judge whether there would be condensation in the groove, thus effectively preventing condensation, since the inventors of the present application inventively recognize that condensation will not occur on the bottom wall of the groove at lowest temperature, but will occur on the electromagnetic wave generation module at the hot and cold junction of the middle of the groove.

(22) These and other objectives, advantages and features of the present invention will be better understood by those skilled in the art in the light of the detailed description of specific embodiments of the present invention in conjunction with the accompanying drawings below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Some specific embodiments of the present invention will be described below in detail in an

exemplary rather than a limiting manner with reference to the accompanying drawings.

(2) Identical reference numerals in the accompanying drawings indicate identical or similar components or parts. It should be understood by those skilled in the art that these accompanying drawings are not necessarily drawn to scale. In the accompanying drawings,

(3) FIG. 1 is a schematic exploded view of a refrigerating and freezing device according to an embodiment of the present invention;

(4) FIG. 2 is a schematic structural diagram of a heating unit according to an embodiment of the present invention;

(5) FIG. 3 is a schematic structural diagram of a controller in FIG. 2;

(6) FIG. 4 is a schematic partial cutaway view of the refrigerating and freezing device shown in FIG. 1;

(7) FIG. 5 is a schematic top view of an air outlet area in FIG. 4;

(8) FIG. 6 is a schematic flow chart of a control method for a refrigerating and freezing device according to an embodiment of the present invention; and

(9) FIG. 7 is a schematic detailed flow chart of a control method for a refrigerating and freezing device according to an embodiment of the present invention.

DETAILED DESCRIPTION

(10) FIG. 1 is a schematic exploded view of a refrigerating and freezing device **200** according to an embodiment of the present invention. FIG. 2 is a schematic structural diagram of a heating unit **100** according to an embodiment of the present invention. Referring to FIG. 1 and FIG. 2, the refrigerating and freezing device **200** may include a cabinet **210** defining at least one storage compartment, at least one door for opening and closing the at least one storage compartment, a heating unit **100** and a controller. In the present invention, the refrigerating and freezing device **200** may be a device having a refrigerating or freezing function, such as a refrigerator, a freezer, a cooler and a wine cabinet.

(11) The cabinet **210** may include an inner liner defining the at least one storage compartment, an outer container, and a thermal insulating layer arranged between the inner liner and the outer container.

(12) The heating unit **100** may include a cylinder body **110** arranged in one storage compartment of the cabinet **210**, a door and an electromagnetic wave generation system.

(13) Specifically, the cylinder body **110** may define a heating chamber for placing of an object to be handled **170**, and may be provided with a taking and placing opening in its front wall for taking and placing the object to be handled **170**.

(14) The door may be mounted together with the cylinder body **110** by appropriate means, such as sliding rail connection and hinging, for opening and closing the taking and placing opening.

(15) The electromagnetic wave generation system may be at least partially arranged in the cylinder body **110** or reach the inside of the cylinder body **110**, so as to produce electromagnetic waves in the cylinder body **110** to heat the object to be handled **170**.

(16) The cylinder body **110** and the door may be provided with electromagnetic shielding features respectively, such that the door is conductively connected with the cylinder body **110** in a closed state to prevent electromagnetic leakage.

(17) FIG. 3 is a schematic structural diagram of the controller in FIG. 2. Referring to FIG. 3, the controller **140** may include a processing unit **141** and a storage unit **142**. The storage unit **142** stores a computer program **143** which, when executed by the processing unit **141**, is used to implement the control method according to an embodiment of the present invention.

(18) In some embodiments, the electromagnetic wave generation system may include an electromagnetic wave generation module **120**, a power supply module **180**, a radiating antenna **150** and a matching module **160**.

(19) The electromagnetic wave generation module **120** may be configured to generate an electromagnetic wave signal. The power supply module **180** may be configured to be electrically

connected with the electromagnetic wave generation module **120**, so as to supply electric energy to the electromagnetic wave generation module **120** to make the electromagnetic wave generation module **120** generate the electromagnetic wave signal.

(20) The radiating antenna **150** may be arranged in the cylinder body **110** and is electrically connected with the electromagnetic wave generation module **120**, so as to produce electromagnetic waves at a corresponding frequency according to the electromagnetic wave signal to heat the object to be handled **170** in the cylinder body **110**.

(21) The matching module **160** may be connected in series between the electromagnetic wave generation module **120** and the radiating antenna **150** and is configured to adjust load impedance of the electromagnetic wave generation module **120** by adjusting its own impedance, so as to achieve load matching and improve the heating efficiency.

(22) In some further embodiments, the cylinder body **110** may be made of metal to serve as a receiving pole of the radiating antenna **150**. In this embodiment, the cylinder body **110** itself is the electromagnetic shielding feature of the cylinder body **110**.

(23) In some other further embodiments, the electromagnetic wave generation system also includes a receiving polar plate arranged opposite to the radiating antenna **150** and electrically connected with the electromagnetic wave generation module **120**. In this embodiment, the inner wall of the cylinder body **110** may be coated with a metal coating or attached with a metal mesh, etc., to serve as the electromagnetic shielding feature of the cylinder body **110**.

(24) FIG. **4** is a schematic partial cutaway view of the refrigerating and freezing device **200** shown in FIG. **1**. Referring to FIG. **4**, the electromagnetic wave generation module **120** and the power supply module **180** may be arranged on the outer side of the thermal insulating layer of the cabinet **210** to reduce the influence of heat produced by the electromagnetic wave generation module **120** and the power supply module **180** on the storage compartment.

(25) The cabinet **210** may be provided with a groove **211** communicating with a surrounding environment and sunken inwards. The electromagnetic wave generation module **120** and the power supply module **180** may be at least partially arranged in the groove **211** to reduce the magnitude of change of the overall height or thickness of the cabinet **210**.

(26) The refrigerating and freezing device **200** may also include at least one fan **190** for promoting air of the surrounding environment to flow into the groove **211**.

(27) Particularly, the processing unit **141** may be configured to control the fan **190** to operate at a first preset rotation speed when the temperature in the groove **211** is less than or equal to a dew point temperature, so as to introduce the hot air of the surrounding environment into the groove **211** to increase the temperature in the groove **211**, which avoids condensation in the groove **211** and improves safety and reliability of the electromagnetic wave generation module **120** and the power supply module **180**. Furthermore, compared with an anti-condensation mode of arranging a heating wire or a heat pipe in the groove **211**, the mode is low in cost and simple in process.

(28) In some embodiments, the processing unit **141** may be further configured to judge, after controlling the fan **190** to operate at the first preset rotation speed, whether the temperature in the groove **211** is greater than or equal to an ambient temperature, and control, if the temperature in the groove **211** is greater than or equal to the ambient temperature, the fan **190** to stop operating after a first preset time, so as to effectively prevent condensation in the groove **211**, prevent the fan **190** from being started frequently, and prolong the service of the fan **190**.

(29) In some other embodiments, the processing unit **141** may be further configured to judge, after controlling the fan **190** to operate at the first preset rotation speed, whether the temperature in the groove **211** is greater than or equal to the ambient temperature, and instantly control, if the temperature in the groove **211** is greater than or equal to the ambient temperature, the fan **190** to stop operating. That is, when the temperature in the groove **211** is greater than or equal to the ambient temperature, the fan **190** is controlled to stop operating.

(30) In some embodiments, the processing unit **141** may be configured to power on the power

supply module **180** (which does not supply electric energy to the electromagnetic wave generation module **120**, and thus the electromagnetic wave generation module **120** does not work) when it is judged that the temperature in the groove **211** is less than the ambient temperature, so as to produce heat, shorten the continuous working time of the fan **190**, further prolong the service life of the fan **190** and reduce noise.

(31) In some further embodiments, the processing unit **141** may be further configured to stop powering on the power supply module **180** when the temperature in the groove **211** is greater than or equal to the ambient temperature, so as to save energy and avoid overheating in the groove **211**.

(32) In some further embodiments, the processing unit **141** may be further configured to judge, after controlling the fan **190** to operate at the first preset rotation speed for a second preset time, whether the temperature in the groove **211** is greater than or equal to the ambient temperature, so as to further prevent condensation in the groove **211** and prevent the fan **190** from being started frequently.

(33) In some embodiments, the processing unit **141** may be further configured to judge, before judging whether the temperature in the groove **211** is less than or equal to the dew point temperature, whether the electromagnetic wave generation module **120** is in a working state, and control, if the electromagnetic wave generation module is in the working state, the fan **190** to operate at a second preset rotation speed to dissipate heat of the electromagnetic wave generation module **120** and the power supply module **180**; and judge, if the electromagnetic wave generation module is not in the working state, whether the temperature in the groove **211** is less than or equal to the dew point temperature.

(34) The second preset rotation speed may be greater than the first preset rotation speed, so as to improve the heat-dissipating efficiency and reduce energy consumption and noise of the fan **190** during anti-condensation.

(35) In the present invention, the ambient temperature refers to a temperature around the refrigerating and freezing device **200**. For example, the refrigerating and freezing device **200** is placed indoors, and the ambient temperature is an indoor temperature. The dew point temperature may be calculated according to the ambient temperature and ambient gas pressure, which will not be described in detail.

(36) In some embodiments, the processing unit **141** may be configured to use the temperature of the electromagnetic wave generation module **120** as the temperature in the groove **211** for control, so as to accurately judge whether condensation will be produced in the groove **211**, thus effectively preventing condensation.

(37) In some other embodiments, the processing unit **141** may be configured to use the temperature of a bottom wall of the groove **211** or an average temperature of a plurality of positions in the groove **211** as the temperature in the groove **211** for control.

(38) In the present invention, there may be one, two, or more fans **190**. In order to facilitate the understanding of the present invention, the present invention will be introduced later with one fan **190** as an example.

(39) In some embodiments, the refrigerating and freezing device **200** may also include a heat-dissipating fin **240** thermally connected with the electromagnetic wave generation module **120**, so as to increase the heat-dissipating area of the electromagnetic wave generation module **120**, thus improving the heat-dissipating efficiency of the electromagnetic wave generation module **120**.

(40) The heat-dissipating fin **240** may include a plurality of ribbed plates perpendicular to the electromagnetic wave generation module **120**. That is, each ribbed plate extends from the electromagnetic wave generation module **120** in a direction away from the electromagnetic wave generation module **120**, and is perpendicular to a mounting surface of the ribbed plate.

(41) The heat-dissipating fin **240** may also include a base plate made integrally with the plurality of ribbed plates for thermal connection with the electromagnetic wave generation module **120**.

(42) The fan **190** may be arranged on a side of the heat-dissipating fin **240** away from the

electromagnetic wave generation module **120**, and is configured to blow out airflow towards the electromagnetic wave generation module **120**. That is, the electromagnetic wave generation module **120** is arranged downstream of fan **190** to reduce wind resistance and improve the heat-dissipating efficiency of the electromagnetic wave generation module **120**.

(43) The extending direction of the plurality of ribbed plates may be further set perpendicular to the direction of the electromagnetic wave generation module **120** getting close to the power supply module **180**, so as to reduce the influence of heat produced by the electromagnetic wave generation module **120** on the power supply module **180**.

(44) At least one of the ribbed plates thermally connected with the middle of the electromagnetic wave generation module **120** is provided with an accommodating portion sunken in the direction close to the electromagnetic wave generation module **120**.

(45) The fan **190** may be arranged in the accommodating portion, and the projection of the fan **190** in the extending direction perpendicular to the plurality of ribbed plates is at least within at least one ribbed plate, so as to further reduce the influence of the heat on the power supply module **180**, and to further improve the heat-dissipating efficiency of the electromagnetic wave generation module **120**.

(46) The fan **190** may be configured to draw airflow via the power supply module **180** and promote the airflow to be blown out towards the electromagnetic wave generation module **120**, so as to overall improve the heat-dissipating efficiency of the electromagnetic wave generation module **120** and the power supply module **180** while improving structure compactness.

(47) The refrigerating and freezing device **200** may also include a housing **220** and a separation plate. The housing **220** may be configured to house the electromagnetic wave generation module **120**, the power supply module **180** and the fan **190**.

(48) The separation plate may be arranged in the housing **220** and located on a side of the fan **190** away from the electromagnetic wave generation module **120**, so as to separate the space in the housing **220** into an air inlet area and an air outlet area. The fan **190** and the electromagnetic wave generation module **120** may be arranged in the air outlet area.

(49) FIG. 5 is a schematic top view of the air outlet area in FIG. 4. Referring to FIG. 4 and FIG. 5, the air inlet area and the air outlet area are provided with at least one air inlet **221** and at least one air outlet **222** in the circumferential direction of the fan **190**, respectively, and the separation plate is provided with at least one ventilation opening **231** at a position corresponding to the at least one fan **190**, so as to prevent water and dust from entering the housing **220** via the air inlet **221** and the air outlet **222** to make the electromagnetic wave generation module **120** and the power supply module **180** damp and dusty, thereby avoiding potential safety hazards.

(50) The airflow flowing directions from the at least one air inlet **221** to the at least one ventilation opening **231** are all perpendicular to the airflow flowing directions from the at least one ventilation openings **231** to each of the air outlets **222**, so as to further reduce wind resistance and improve heat-dissipating efficiency.

(51) The power supply module **180** may be arranged in the air outlet area, and is located on a side of the electromagnetic wave generation module **120** perpendicular to the airflow flowing direction from the at least one ventilation opening **231** to each air outlet **222**, so as to make the fan **190** dissipate heat of the power supply module **180** and the electromagnetic wave generation module **120** respectively in the process of drawing and blowing out airflow to further reduce the influence of the heat on the power supply module **180** and improve the heat-dissipating efficiency.

(52) Further, the refrigerating and freezing device **200** also includes a heat conduction material **250** thermally connected with the power supply module **180** and the separation plate, so as to improve the heat-dissipating efficiency of the power supply module **180**.

(53) The fan **190** may be arranged above the electromagnetic wave generation module **120**. That is, the electromagnetic wave generation module **120** may be arranged above the thermal insulating layer, so as to improve the stability of the electromagnetic wave generation module **120** and the fan

190.

(54) FIG. 6 is a schematic flow chart of a control method for the refrigerating and freezing device **200** according to an embodiment of the present invention (in the figures of the description of the present invention, “Y” represents “Yes”, and “N” represents “No”). Referring to FIG. 6, the control method for the refrigerating and freezing device **200** in the present invention may include the following steps.

(55) At step **S602**, whether the temperature in the groove **211** is less than or equal to the dew point temperature is judged. If yes, step **S604** is performed.

(56) At step **604**, the fan **190** is controlled to operate at a first preset rotation speed.

(57) As for the control method of the present invention, the temperature in the groove **211** is increased by controlling the fan to operate to introduce air of the surrounding environment into the groove **211** when the temperature in the groove **211** is less than or equal to the dew point temperature, which avoids condensation in the groove **211** and improves safety and reliability of electrical parts in the groove **211**. Furthermore, compared with an anti-condensation mode of arranging a heating wire or a heat pipe in the groove **211**, this mode is low in cost and simple in process, and the production cost is reduced.

(58) In some embodiments, after the step **S604**, the control method may also include the following steps: judging whether the temperature in the groove **211** is greater than or equal to the ambient temperature; and if yes, controlling the fan **190** to stop operating after a first preset time, so as to effectively prevent condensation in the groove **211**, prevent the fan **190** from being started frequently, and prolong the service life of the fan **190**.

(59) In some other embodiments, after step **S604**, the control method may also include the following step: instantly controlling, when the temperature in the groove **211** is greater than or equal to the ambient temperature, the fan **190** to stop operating.

(60) In some embodiments, after the step **S604**, the control method may also include the following steps: judging whether the temperature in the groove **211** is greater than or equal to the ambient temperature; and if not, powering on the power supply module **180** (which does not supply electric energy to the electromagnetic wave generation module **120**, and thus the electromagnetic wave generation module **120** does not work), so as to produce heat, shorten the continuous working time of the fan **190**, further prolong the service life of the fan **190** and reduce noise.

(61) In some further embodiments, the control method of the present invention may also include: stopping powering on the power supply module **180** when the temperature in the groove **211** is greater than or equal to the ambient temperature, so as to save energy and avoid overheating in the groove **211**.

(62) In some further embodiments, the control method of the present invention may also include: judging whether the temperature in the groove **211** is greater than or equal to the ambient temperature after performing step **S604** for a second preset time, so as to further prevent condensation in the groove **211** and prevent the fan **190** from being started frequently.

(63) In some embodiments, after step **S602**, the control method may also include the following steps: judging whether the electromagnetic wave generation module **120** works; if yes, controlling the fan **190** to operate at a second preset rotation speed to dissipate heat of the electromagnetic wave generation module **120** and the power supply module **180**; and if not, performing step **S602** to judge whether there is a need for anti-condensation.

(64) The second preset rotation speed may be greater than the first preset rotation speed, so as to improve the heat-dissipating efficiency and reduce energy consumption and noise of the fan **190** during anti-condensation.

(65) In the present invention, the temperature of the electromagnetic wave generation module **120** may be used as the temperature in the groove **211** for judging and control, so as to more accurately judge whether there would be condensation in the groove **211**, thus effectively preventing condensation.

(66) FIG. 7 is a schematic detailed flow chart of a control method for the refrigerating and freezing device **200** according to an embodiment of the present invention. Referring to FIG. 7, the control method for the refrigerating and freezing device **200** of the present invention may include the following detailed steps.

(67) At step **S702**, whether the electromagnetic wave generation module **120** is in a working state is judged. If yes, step **S718** is performed; and if not, step **S704** is performed.

(68) At step **S704**, whether the temperature of the electromagnetic wave generation module **120** is less than or equal to the dew point temperature is judged. If yes, step **S706** is performed; and if not, it returns to step **S702**.

(69) At step **S706**, the fan **190** is controlled to operate at a first preset rotation speed.

(70) At step **S708**, whether step **S706** is performed for a second preset time is judged. If yes, step **S710** is performed; and if not, it returns to step **S706**.

(71) At step **S710**, whether the temperature of the electromagnetic wave generation module **120** is greater than or equal to an ambient temperature is judged. If yes, step **S714** is performed; and if not, step **S712** is performed.

(72) At step **S712**, the power supply module **180** is powered on.

(73) At step **S714**, the power supply module **180** stops being powered on. Step **S716** is performed.

(74) At step **S716**, after a first preset time, the fan **190** is controlled to stop operating. It returns to step **S702**.

(75) At step **S718**, the fan **190** is controlled to operate at a second preset rotation speed. It returns to step **S702**.

(76) In the present invention, if the electromagnetic wave generation module **120** starts to work in the process of performing step **S704** to step **S716**, it instantly skips to step **S718**.

(77) As understood by those skilled in the art, the control method of the present invention is also suitable for other electrical parts arranged in the groove **211**.

(78) At this point, it should be recognized by those skilled in the art that, although multiple exemplary embodiments of the present invention have been exhaustively shown and described herein, many other variations or modifications in accordance with the principles of the present invention may still be directly determined or derived from the disclosure of the present invention without departing from the spirit and scope of the present invention. Therefore, the scope of the present invention should be understood and recognized as covering all these other variations or modifications.

Claims

1. A control method for a refrigerating and freezing device, the refrigerating and freezing device comprising a cabinet provided with a groove communicating with a surrounding environment and recessed inwards, and at least one fan for promoting air of the surrounding environment to flow into the groove, wherein the control method comprises: judging whether a temperature in the groove is less than or equal to a dew point temperature; if yes, controlling the fan to operate at a first preset rotation speed; judging whether the temperature in the groove is greater than or equal to an ambient temperature; and controlling the fan to stop operating if the temperature in the groove is greater than or equal to the ambient temperature.
2. The control method according to claim 1, comprising: after performing the step of controlling the fan to operate at a first preset rotation speed for a second preset time, performing the step of judging whether the temperature in the groove is greater than or equal to an ambient temperature.
3. A refrigerating and freezing device, comprising: a cabinet, provided with a groove communicating with a surrounding environment and recessed inwards; at least one fan, configured to promote air of the surrounding environment to flow into the groove; and a controller configured to implement the control method according to claim 1.

4. The control method according to claim 1, wherein a temperature of a bottom wall of the groove or an average of temperatures of a plurality of positions in the groove is used as the temperature in the groove.
 5. A control method for a refrigerating and freezing device, the refrigerating and freezing device comprising a cabinet provided with a groove communicating with a surrounding environment and recessed inwards, and at least one fan for promoting air of the surrounding environment to flow into the groove, wherein the control method comprises: judging whether a temperature in the groove is less than or equal to a dew point temperature; if yes, controlling the fan to operate at a first preset rotation speed; judging whether the temperature in the groove is greater than or equal to an ambient temperature; and if yes, controlling the fan to stop operating after a first preset time.
 6. The control method according to claim 5, comprising: after performing the step of controlling the fan to operate at a first preset rotation speed for a second preset time, performing the step of judging whether the temperature in the groove is greater than or equal to an ambient temperature.
 7. The control method according to claim 5, wherein a temperature of a bottom wall of the groove or an average of temperatures of a plurality of positions in the groove is used as the temperature in the groove.
-