

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399679
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Takimoto; Yuuji

Information processing apparatus and information processing method

Abstract

provided is an information processing apparatus includes a first input unit configured to input that inputs first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields. The information processing apparatus further includes second input unit that inputs second data belonging to an attribute of a second input field in the first data, to a second input field, in response to an operation of moving the first data from the first input field to the second input field.

Inventors:	Takimoto; Yuuji (Tokyo, JP)
Applicant:	SONY GROUP CORPORATION (Tokyo, JP)
Family ID:	1000008780166
Assignee:	SONY GROUP CORPORATION (Tokyo, JP)
Appl. No.:	18/005025
Filed (or PCT Filed):	July 08, 2021
PCT No.:	PCT/JP2021/025837
PCT Pub. No.:	WO2022/019145
PCT Pub. Date:	January 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230297328 A1	Sep. 21, 2023

Foreign Application Priority Data

JP	2020-124047	Jul. 20, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: G10L15/22 (20060101); G06F3/0484 (20220101); G06F3/16 (20060101); G06F40/174 (20200101); G10L15/18 (20130101)

U.S. Cl.:

CPC G06F3/167 (20130101); G06F3/0484 (20130101); G06F40/174 (20200101); G10L15/1815 (20130101); G10L15/22 (20130101); G10L2015/228 (20130101)

Field of Classification Search

CPC: G10L (15/1822); G10L (15/22); G06F (40/174); H04W (4/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7913184	12/2010	Zhang	715/224	G06F 40/174
2004/0024842	12/2003	Witt	709/219	H04L 67/02
2004/0181749	12/2003	Chellapilla	715/222	G06F 40/174
2005/0091577	12/2004	Torres	715/225	G06F 40/174
2009/0183090	12/2008	Fujimoto	715/780	G06F 40/174
2011/0172989	12/2010	Moraes	704/260	G06Q 30/0251
2019/0163341	12/2018	Jeon	N/A	G06F 3/04842
2020/0301552	12/2019	Maeng	N/A	G06F 3/0484
2021/0074275	12/2020	Fritz	N/A	G10L 15/1822

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-218092	12/2001	JP	N/A
2003-256384	12/2002	JP	N/A
2008-052676	12/2007	JP	N/A
2015-146075	12/2014	JP	N/A
2016-102920	12/2015	JP	N/A
2018-072508	12/2017	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of PCT Application No. PCT/JP2021/025837, issued on Oct. 12, 2021, 09 pages of ISRWO. cited by applicant

Primary Examiner: Abebe; Daniel

Attorney, Agent or Firm: CHIP LAW GROUP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase of International Patent Application No. PCT/JP2021/025837 filed on Jul. 8, 2021, which claims priority benefit of Japanese Patent Application No. JP 2020-124047 filed in the Japan Patent Office on Jul. 20, 2020. Each of the above-referenced applications is hereby incorporated herein by reference in its entirety.

FIELD

(2) The present disclosure relates to an information processing apparatus, an information processing method, and an information processing program.

BACKGROUND

(3) In recent years, an apparatus is known that enables voice input in response to a user's utterance. For example, Patent Literature 1 discloses a technique in which text data that is generated from an audio signal and serves as an object being input to an input field is acquired from divisional text data and is input to its corresponding input field.

CITATION LIST

Patent Literature

(4) Patent Literature 1: JP 2018-72508 A

SUMMARY

Technical Problem

(5) However, in the conventional art, in performing voice input to a plurality of input fields, data is not input to an intended input field in some cases. Thus, in the conventional art, there is a demand for improvement in operability in moving data input to an input field, to another input field.

(6) In view of this, according to the present disclosure, there is proposed an information processing apparatus, an information processing method, and an information processing program that can improve operability in moving data automatically input to an input field, to another input field.

Solution to Problem

(7) To solve the problems described above, an information processing apparatus according to an embodiment of the present disclosure includes: a first input unit configured to input first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and a second input unit configured to input second data belonging to an attribute of a second input field in the first data, to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(8) Moreover, an information processing method according to an embodiment of the present disclosure performed by a computer, includes: inputting first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields, based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and inputting second data belonging to an attribute of a second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(9) Moreover, an information processing program according to an embodiment of the present disclosure causes a computer to perform: inputting first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields, based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and inputting second data belonging to an attribute of a second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a view for explaining an example of an information processing system according to an embodiment.
- (2) FIG. 2 is a view for explaining an example of an overview of operations of the information processing system according to the embodiment.
- (3) FIG. 3 is a view illustrating an example of a configuration of an information processing terminal according to the embodiment.
- (4) FIG. 4 is a view illustrating an example of a configuration of an information processing apparatus according to the embodiment.
- (5) FIG. 5 is a view illustrating an example of input-screen transition in the information processing apparatus according to the embodiment.
- (6) FIG. 6 is a view illustrating an example of an overview of information processing regarding the example of input-screen transition illustrated in FIG. 5.
- (7) FIG. 7 is a view illustrating another example of input-screen transition in the information processing apparatus according to the embodiment.
- (8) FIG. 8 is a view illustrating an example of an overview of information processing regarding the example of input-screen transition illustrated in FIG. 7.
- (9) FIG. 9 is a flowchart illustrating an example of information processing (1) of the information processing apparatus according to the embodiment.
- (10) FIG. 10 is a view illustrating an example of operations of the information processing apparatus according to the embodiment.
- (11) FIG. 11 is a view illustrating an example of input-screen transition regarding information processing (2) according to the embodiment.
- (12) FIG. 12 is a flowchart illustrating an example of the information processing (2) of the information processing apparatus according to the embodiment.
- (13) FIG. 13 is a view illustrating an example of information processing (3) of the information processing apparatus according to the embodiment.
- (14) FIG. 14 is a view illustrating an example of information processing (4) of the information processing apparatus according to the embodiment.
- (15) FIG. 15 is a hardware configuration diagram illustrating an example of a computer that performs functions of the information processing apparatus.

DESCRIPTION OF EMBODIMENTS

(16) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the drawings. In each of the following embodiments, the same components are denoted by the same reference signs, and duplicated description will be omitted.

EMBODIMENTS

(17) [Overview of Information Processing System According to Embodiment]

(18) FIG. 1 is a view for explaining an example of an information processing system according to an embodiment. The information processing system 1 illustrated in FIG. 1 is a voice input system in which data is input to a plurality of input fields by a voice uttered by a user U. The information processing system 1 includes, for example, an information processing terminal 10 and an information processing apparatus 100. The following description will discuss an example in which the information processing system 1 achieves voice input of the user U through cooperation between the information processing terminal 10 and the information processing apparatus 100. The user U is an example of a speaker, and is a person who performs voice input on the information processing system 1.

(19) The information processing terminal 10 is an electronic apparatus to which the user U can provide inputs. Examples of the electronic apparatus include a smartphone, a tablet terminal, a game console, a head-mounted display (HMD), a television, a home speaker, a home electrical

appliance, and the like. The information processing terminal **10** is configured to be capable of collecting voices of the user U and the like. The information processing terminal **10** has a function of supplying utterance data in which voices of the user U are collected, to the information processing apparatus **100**. The utterance data includes data indicating the content of utterance obtained by capture of the user U's voices. The information processing terminal **10** may include various sensors not only for collecting surrounding voices, but also for acquiring other various kinds of information, for example. The information processing terminal **10** includes, for example, a touch panel, and is configured to be capable of detecting a touch, a position where a touch has been detected, a change in position where a touch has been detected, and the like. The information processing terminal **10** has a function of detecting the user U's operation based on a result of detection in the touch panel.

(20) The information processing apparatus **100** is a so-called cloud server, and is a server apparatus that performs information processing in cooperation with the information processing terminal **10**. The information processing terminal **10** and the information processing apparatus **100** are configured to be capable of communicating via a network or directly communicating without intermediation of a network, for example. The information processing apparatus **100** may be incorporated in the information processing terminal **10**, for example.

(21) The information processing apparatus **100** has functions of acquiring utterance data of the user U from the information processing terminal **10** and semantically analyzing the utterance data. In semantic analysis, analysis can be performed using natural language understanding (NLU), natural language processing (NLP), or the like, for example.

(22) The information processing system **1** displays an input screen having a plurality of input fields on the information processing terminal **10**, and the information processing terminal **10** collects utterance data of the user U. In the information processing system **1**, the information processing apparatus **100** semantically analyzes the utterance data of the user U and automatically inputs the utterance data according to the respective attributes of the input fields in the input screen. Inputting utterance data to an input field includes setting utterance data at an input field, displaying utterance data in an input field, and the like, for example.

(23) For example, in a case where an input screen includes a single input field, the information processing system **1** is only required to input utterance data of the user U to the single input field. However, in a case where an input screen includes a plurality of input fields, the information processing system **1** semantically analyzes utterance data, selects an input field suitable for the utterance data from the plurality of input fields, and automatically inputs the utterance data to the selected input field. Thus, the information processing system **1** may probably input utterance data to an input field not intended by the user U.

(24) The present disclosure provides a technique that can improve operability in moving data automatically input to an input field to another input field when the information processing system **1** inputs utterance data to an input field not intended by the user U.

(25) FIG. **2** is a view for explaining an example of an overview of operations of the information processing system **1** according to the embodiment. In the example illustrated in FIG. **2**, the user U gives utterance **C11** to the information processing terminal **10**. The utterance **C11** is, for example, "E-mail Mr. Sato to say, 'Would you like to go out for a meal?'". In the information processing system **1**, the information processing apparatus **100** semantically analyzes utterance data of the utterance **C11**, and as a result, starts a mail application in the information processing terminal **10**. The information processing system **1** inputs the utterance data, "Mr. Sato, would you like to go out for a meal?" to a title input field **311** in an input screen **300** for a new mail. The mail application provides, for example, a mailing function for preparing, sending, receiving, displaying, and the like of an electronic mail. In the information processing system **1**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** for the new mail.

(26) In the example illustrated in FIG. **2**, the input screen **300** is a screen (object) to which the user

U can provide inputs, and is displayed so as to be visually recognizable by the user U on the information processing terminal **10**. The input screen **300** may be displayed in a virtual space in a case where the information processing terminal **10** is an HMD, for example. The input screen **300** includes an input field **311** of which attribute is a recipient and an input field **312** of which attribute is a title. Hereinafter, the input field **311** and the input field **312** will be referred to as an “input field **310**” unless the input field **311** and the input field **312** are distinguished from each other. Further, for the purpose of simplifying the description, illustration of a body, a send button, a cancel button, and the like is omitted in the input screen **300** illustrated in FIG. 2.

(27) In the information processing system **1**, the information processing apparatus **100** recognizes the utterance data, “Mr. Sato, would you like to go out for a meal?”, as a title of the new mail. Thus, as illustrated in a step **S1**, in the information processing system **1**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which the utterance data, “Mr. Sato, would you like to go out for a meal?”, is input to the input field **312** of which attribute is a title in the input screen **300**. Further, in the information processing system **1**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which the input field **311** of which attribute is a recipient in the input screen is blank.

(28) The information processing system **1** causes a graphical user interface (GUI) **400** operable by the user U to be displayed on the input screen **300** such that the GUI **400** can move. The GUI **400** is displayed so as to be positioned near an input field that can be operated in the input screen **300**. That is, in the step **S1**, the information processing system **1** causes the GUI **400** to be displayed near the input field **312**, to indicate to the user U that the input field **312** is activated and the input field **312** can be operated.

(29) In the step **S1**, the user U refers to the input screen **300** of the information processing terminal **10**, and then determines that the utterance data is not correctly input to the input field **310** in the input screen **300**. Specifically, the user U has desired that data, “Mr. Sato”, in the utterance data is input to the recipient input field **311** of the new mail in the form of an e-mail address. Thus, the user U performs a moving operation of moving the GUI **400** on the input screen **300** from the title input field **312** to the vicinity of the recipient input field **311**.

(30) When detecting the moving operation of moving the GUI **400** from the input field **312** to the vicinity of the input field **311**, the information processing system **1** performs processing of moving the utterance data input to the input field **312** that is a source, to the input field **311** that is a destination. The information processing system **1** semantically analyzes again the utterance data, “Mr. Sato, would you like to go out for a meal?”. As a result, the information processing system **1**, which has accepted the operation of moving the utterance data to the input field **311** of which attribute is a recipient, performs semantic analysis while focusing on a recipient, and extracts data, “Mr. Sato” or “Sato”, corresponding to a recipient, from the utterance data. The information processing system **1** acquires an address of the extracted Sato, sato@xxx.com (e-mail address), from address book data or the like, for example.

(31) As illustrated in a step **S2**, in the information processing system **1**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which sato@xxx.com (e-mail address) is input to the input field **311** of which attribute is a recipient, as second data. Furthermore, “Mr. Sato” in the utterance data, “Mr. Sato, would you like to go out for a meal?”, has been moved to the input field **301**, and hence, the information processing system **1** changes the utterance data to “Would you like to go out for a meal?”. In the information processing system **1**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which the utterance data input to the title input field **312** has been changed so that the changed utterance data can be displayed. Specifically, in the input screen **300** illustrated in the step **S2**, the data, sato@xxx.com (e-mail address), is input to the input field **311** of which attribute is a recipient, and the data, “Would you like to go out for a

meal?”), is input to the input field **312** of which attribute is a title. As a result, the user U confirms that the utterance data has been input to the input field **311** and input field **312** in the input screen **300** as intended thereby.

(32) As described above, the information processing system **1** (the information processing apparatus **100**) inputs utterance data (first data) to the input field **312** selected from the plurality of input fields **310** based on the meaning of the content of utterance indicated by the utterance data and the attributes of the plurality of input fields **310**. The information processing system **1** inputs the second data belonging to the attribute of the destination input field **310** in the utterance data, to the destination input field **310**, in response to an operation of moving the utterance data from the input field **312** to the input field **311**. Thus, in a case where utterance data fails to be input to the input field **310** intended by a user, the information processing system **1** can easily move data between the plurality of input fields **310** in response to the operation of moving the utterance data to another input field. Consequently, the information processing system **1** can improve operability in moving data automatically input to the input field **310** to another input field **319**.

(33) [Configuration Example of Information Processing Terminal According to Embodiment]

(34) FIG. **3** is a view illustrating an example of a configuration of the information processing terminal **10** according to the embodiment. As illustrated in FIG. **3**, the information processing terminal **10** includes a sensor unit **11**, an input unit **12**, a touch panel **13**, a communication unit **14**, a storage unit **15**, and a control unit **16**. The control unit **16** is electrically connected to the sensor unit **11**, the input unit **12**, the touch panel **13**, the communication unit **14**, and the storage unit **15**.

(35) The sensor unit **11** has a function of collecting various kinds of sensor information regarding the user U and the surroundings. The sensor unit **11** according to the present embodiment includes, for example, a microphone, a camera, a time of flight (ToF) sensor, an inertial sensor, and the like. The sensor unit **11** may include various sensors such as a geomagnetic sensor, a touch sensor, an infrared sensor, a temperature sensor, and a humidity sensor, for example. The sensor unit **11** supplies collected sensor information to the control unit **16**. The sensor unit **11** supplies utterance data obtained by capture of the user U's voices, to the control unit **16**.

(36) The input unit **12** has a function of detecting a physical inputting operation performed by the user U. The input unit **12** includes operation devices such as a power switch and an operation button, for example. The input unit **12** supplies input information indicating an inputting operation as detected, to the control unit **16**.

(37) The touch panel **13** is an electronic apparatus in which a display device and a position input device are combined. The display device includes a liquid crystal display (LCD) device or the like, for example. The position input device includes a touch pad or the like, for example. The touch panel **13** has functions of displaying various kinds of information and detecting a touch on the touch panel **13**. The touch panel **13** displays various kinds of information under the control of the control unit **16**, for example. The touch panel **13** supplies a result of detection of a touch, a position where a touch has been detected, or the like, for example, to the control unit **16**.

(38) The communication unit **14** communicates with, for example, the information processing apparatus **100**, other external apparatuses, and the like. The communication unit **14** transmits and receives various data via a wired or wireless network, for example. For example, when utterance is collected, the communication unit **14** transmits the utterance data to the information processing apparatus **100**. The communication unit **14** may transmit not only utterance data but also identification information or the like for identifying the user U, for example, to the information processing apparatus **100**. The communication unit **14** supplies, for example, various data received from the information processing apparatus **100** to the control unit **16**.

(39) The storage unit **15** stores therein various data and programs. For example, the storage unit **15** is a semiconductor memory element such as a random access memory (RAM) or a flash memory, for example, a hard disk, an optical disk, or the like. The storage unit **15** stores therein, for example, various application data such as a mail application **15A**, a message application **15B**, a

browser application **15C**, and a calendar application **15D**. The mail application **15A** provides, for example, a mailing function for preparing, sending, receiving, displaying, and the like of an electronic mail. The message application **15B** provides, for example, a messaging function for preparing, sending, receiving, displaying, and the like of a message. The browser application **15C** provides, for example, a browsing function for displaying a web page or the like. The calendar application **15D** provides, for example, a calendar function for managing a schedule. The storage unit **15** can store therein applications other than the mail application **15A**, the message application **15B**, the browser application **15C**, and the calendar application **15D**. Other applications include, for example, applications for changing a postal address, reserving a hotel room for travel, reserving a train ticket or an airplane ticket, and the like. The storage unit **15** can store therein utterance data **D1** detected by the sensor unit **11** in time series.

(40) The control unit **16** controls the information processing terminal **10** by executing a program. The control unit **16** has a function of controlling each component included in the information processing terminal **10**. The control unit **16** controls, for example, start and stop of each component. The control unit **16** executes, for example, an application designated by the user **U**, the information processing apparatus **100**, or the like. The control unit **16** controls the touch panel **13** such that various kinds of information designated by the information processing apparatus **100** are displayed. For example, the control unit **16** controls the touch panel **13** such that display of the input screen **300**, input of data to the input field **310**, and the like are performed in accordance with instructions from the information processing apparatus **100**. When the sensor unit **11** collects utterance of the user **U**, the control unit **16** performs control in which utterance data indicating the content of the utterance is transmitted to the information processing apparatus **100**. The control unit **16** performs control in which operation information about the user **U** is detected based on a touch, a change in a touch position, or the like detected by the touch panel **13**, and the operation information is transmitted to the information processing apparatus **100**. The operation information includes, for example, information with which the input field **310** that is a destination of the GUI **400** can be identified.

(41) Hereinabove, the example of a functional configuration of the information processing terminal **10** according to the embodiment has been described. Note that the configuration described above with reference to FIG. 3 is merely an example, and the functional configuration of the information processing terminal **10** according to the present embodiment is not limited to the example. The functional configuration of the information processing terminal **10** according to the present embodiment can be flexibly modified according to specifications and operations.

(42) [Configuration Example of Information Processing Apparatus according to Embodiment]

(43) FIG. 4 is a view illustrating an example of a configuration of the information processing apparatus **100** according to the embodiment. As illustrated in FIG. 4, the information processing apparatus **100** includes a communication unit **110**, a storage unit **120**, and a control unit **130**. The control unit **130** is electrically connected to the communication unit **110** and the storage unit **120**.

(44) The communication unit **110** communicates with, for example, the information processing terminal **10**, other external apparatuses, and the like. The communication unit **110** transmits and receives data via a wired or wireless network, for example. The communication unit **110** supplies, for example, various data received from the information processing terminal **10** to the control unit **130**. The communication unit **110** transmits data designated by the control unit **130** to a designated destination of transmission, for example.

(45) The storage unit **120** stores therein various data and programs. For example, the storage unit **120** is a semiconductor memory element such as a RAM or a flash memory, for example, a hard disk, an optical disk, or the like. The storage unit **120** stores therein data received via the communication unit **110**. The storage unit **120** stores therein various data such as attribute data **D100**, user data **D200**, and the utterance data **D1**, for example.

(46) The attribute data **D100** includes, for example, data indicating the input field **310** included in

the input screen **300**, the attribute of the input field **310**, the item of the input field **310**, and the like. The attribute data **D100** includes, for example, data indicating an attribute (type) of a user interface for input of data to the input field **310**, a display position in a screen, and the like. The attribute data **D100** includes, for example, data capable of identifying an interface, such as a recipient, a title, a body, a text, a numerical value, a date, a time, a search text, a telephone number, a uniform resource locator (URL), and a password. For example, in a case where the input screen **300** is described in hypertext markup language (HTML), the input field **310** is associated with the attribute information based on the HTML source code in the attribute data **D100**. The attribute data **D100** can be configured to include data such as a table or a database indicating a relationship between the input field **310** and the attribute.

(47) The present embodiment will discuss a case where the attribute of the input field **310** includes a type, an item (name), and the like of an interface, but the attribute is not limited thereto. The attribute of the input field **310** can be configured to include, for example, data that can identify a type of data being input to the input field **310**, a method of changing the data, and the like.

(48) In the case of the input screen **300** illustrated in FIG. 2, the attribute data **D100** has a configuration having data that indicates a recipient as the attribute of the input field **311** and indicates a title (text) as the attribute of the input field **312**. The attribute data **D100** can include data corresponding to a plurality of input screens.

(49) Referring back to FIG. 3, the user data **D200** includes data regarding the user **U**. The user data **D200** includes, for example, personal information about the user **U**, information about the information processing terminal **10** used by the user **U**, and the like. The user data **D200** includes data indicating correspondence between the user **U** and the information processing terminal **10** used by the user **U**. The user data **D200** includes information capable of identifying an application or the like executable in the information processing terminal **10**.

(50) The storage unit **120** stores therein the utterance data **D1** received from the information processing terminal **10** in association with the user data **D200**. The utterance data **D1** is the utterance data **D1** supplied from the information processing terminal **10**, and can be correlated with information indicating an analysis result of the utterance data **D1** or the like. The storage unit **120** can store therein an analysis program, model data, and the like for analyzing the utterance data **D1**.

(51) The control unit **130** is, for example, a dedicated or general-purpose computer. The control unit **130** is, for example, an integrated control unit that controls the information processing apparatus **100**. The control unit **130** includes functional units that achieve voice input of the user **U** in the information processing terminal **10** through cooperation with the information processing terminal **10**.

(52) The control unit **130** includes functional units of a first input unit **131**, a second input unit **132**, an analysis unit **133**, a change unit **134**, and a display control unit **135**. The functional units of the control unit **130** are implemented by execution of a program stored in the information processing apparatus **100** using a RAM or the like as a work area by a central processing unit (CPU) or a microprocessing unit (MPU), or the like, for example. Further, the functional units may be implemented by an integrated circuit such as an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA), for example.

(53) The first input unit **131** inputs the utterance data **D1** (first data) obtained by capture of the user **U**'s voices to the input field **310** (first input field) selected from the plurality of input fields **310**, based on the meaning of the content of utterance indicated by the utterance data **D1**, and the attributes of the plurality of input fields. The first input unit **131** performs control for inputting data to the input field **310**. For example, the first input unit **131** selects the input field **310** with an attribute to which the meaning of the utterance data **D1** belongs, based on the attribute data **D100**, and inputs the utterance data **D1** to the selected input field **310**. In a case where there are a plurality of attributes to which the meaning of the utterance data **D1** belongs, the first input unit **131** selects the input field **310** with an attribute to which the meaning belongs with the strongest probability.

The first input unit **131** has a function of recognizing a relationship between the input field **310** and the attribute of the input field **310** in the input screen **300** of an application started by the utterance data **D1** of the user **U**, based on the attribute data **D100** and the like.

(54) The second input unit **132** inputs the second data belonging to the attribute of the destination input field **310** in the utterance data **D1**, to the destination input field **310**, in response to an operation of moving the utterance data **D1** from the source input field **310** to the destination input field **310**. The source input field **310** is, for example, an example of the first input field, and is the input field **310** to which data required to be moved has been input. The destination input field **310** is, for example, an example of a second input field, and is the input field **310** to which data required to be moved is to be input. The second input unit **132** inputs the second data belonging to the attribute of the destination input field **310** in the utterance data **D1** to the destination input field **310**. The second input unit **132** performs control for inputting the second data to the destination input field **310**.

(55) The second input unit **132** inputs the second data corresponding to partial data of the utterance data **D1** having been changed so as to have the attribute of the destination input field **310**, to the destination input field **310**, based on the meaning of the utterance data **D1** analyzed by the analysis unit **133** and the attribute of the destination input field **310**. In a case where the respective attributes of the source input field **310** and the destination input field **310** are the same, the second input unit **132** moves all of the utterance data **D1** to the destination input field **310**, as the second data.

(56) The second input unit **132** inputs the second data based on the attribute of the destination input field **310** and the partial data of the utterance data **D1**, to the destination input field **310**, in response to a moving operation (second operation) of moving the partial data of the utterance data **D1** from the source input field **310** to the destination input field **310**. The second operation includes, for example, an operation of selecting and moving a part of the utterance data **D1**. The second input unit **132** inputs the partial data selected from the utterance data **D1** to the destination input field **310**, as the second data. In this case, the second input unit **132** may semantically analyze the partial data selected from the utterance data **D1** by using the analysis unit **133**.

(57) The second input unit **132** can provide a function of combining input data having already been input to the destination input field **310** with the utterance data **D1** or the second data, in response to a moving operation of moving the utterance data **D1** from the source input field **310** to the destination input field **310**. In other words, the second input unit **132** inputs new second data including a combination of the second data or the utterance data **D1** from the source input field **310** with the input data, to the destination input field **310**.

(58) The analysis unit **133** analyzes the meanings of the utterance data **D1** and the partial data of the utterance data **D1**. For example, the analysis unit **133** analyzes character information representing the content of the user **U**'s utterance, to understand the meaning of the user's utterance, and generates semantic information for the utterance based on a result of the understanding. For example, the analysis unit **133** decomposes the character information representing the content of utterance into words for each part of speech by word decomposition, and analyzes the sentence structure from the part-of-speech information about the decomposed words. The analysis unit **133** can generate semantic information indicated by the user **U**'s utterance by referring to the meaning of each word included in the content of the user **U**'s utterance and the analyzed sentence structure.

(59) The analysis unit **133** may generate semantic information indicated by the user **U**'s utterance by analyzing the character information representing the content of the user **U**'s utterance using, for example, a machine learning technique such as deep learning. The analysis unit **133** may generate semantic information indicated by the user **U**'s utterance by analyzing the character information representing the content of the user **U**'s utterance using known semantic analysis techniques. The analysis unit **133** can generate semantic information indicating start of an application, input to an input field in the input screen, and the like, from text information in which the user **U** indicates the content of utterance using a character string, based on the user data **D200** or the like.

(60) The change unit **134** changes the utterance data **D1** in the source input field **310** such that the partial data having been moved to the destination input field **310** is deleted from the utterance data **D1** input to the source input field **310**. For example, consider a case in which the utterance data **D1**, “Mr. Sato, would you like to go out for a meal?”, is input to the source input field **310**, and “Mr. Sato” is moved to the destination input field **310**, as the partial data. In this case, the change unit **134** changes the utterance data **D1** in the source input field **310** to “Would you like to go out for a meal?” in consideration of the meaning of the sentence, the sentence structure, and the like.

(61) The display control unit **135** controls the display device such that the input screen **300** including the plurality of input fields **310** is displayed. In the present embodiment, the display control unit **135** controls the information processing terminal **10** such that the input screen **300** is displayed on the touch panel **13**. The display control unit **135** controls the information processing terminal **10** such that the input screen **300** in which the second input unit **132** has input the second data to the second input field, is displayed. The display control unit **135** controls the information processing terminal **10** such that the GUI **400** that is an object for allowing the user **U** to designate the destination input field **310** is displayed near the input field **310**. The present embodiment will discuss a case where the display control unit **135** performs control in which the GUI **400** is displayed, but the present disclosure is not limited thereto. For example, the display control unit **135** may perform control in which the input field **310** in an active state is displayed in a display form different from the other input fields **310**.

(62) Hereinabove, the example of the functional configuration of the information processing apparatus **100** according to the embodiment has been described. Note that the configuration described above with reference to FIG. **4** is merely an example, and the functional configuration of the information processing apparatus **100** according to the present embodiment is not limited to the example. The functional configuration of the information processing apparatus **100** according to the present embodiment can be flexibly modified according to specifications and operations.

(63) [Overview of Information Processing according to Embodiment]

(64) FIG. **5** is a view illustrating an example of input-screen transition in the information processing apparatus **100** according to the embodiment. FIG. **5** illustrates an example of transition in a case where the utterance data **D1** is moved to another input field **310**. FIG. **6** is a view illustrating an example of an overview of information processing regarding the example of transition of the input screen **300** illustrated in FIG. **5**. The information processing illustrated in FIG. **6** is performed by execution of a program by the information processing apparatus **100**.

(65) In the example illustrated in FIG. **5**, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300**. The input screen **300** includes the input field **311** of which item is a recipient and of which attribute is an address, the input field **312** of which item is a title and of which attribute is a text, and an input field **313** of which item is a body and of which attribute is a text. The information processing apparatus **100** inputs the utterance data **D1**, “go out for a meal”, to the input field **313** based on a result of semantic analysis.

(66) In a step **S11**, the user **U** performs an operation **R1** of moving the GUI **400** on the input screen **300** from the body input field **313** to the vicinity of the title input field **312**. In this case, as illustrated in FIG. **6**, when detecting the operation **R1** of moving the utterance data **D1** to the input field **312**, the information processing apparatus **100** performs semantic analysis based on the utterance data **D1**, “go out for a meal”, and the attributes of the input field **312** and the input field **313**. The respective attributes of the input field **312** and the input field **313** are the same, and hence the information processing apparatus **100** moves and inputs the utterance data **D1**, “go out for a meal”, in the input field **313**, to the input field **312**.

(67) In a step **S12** illustrated in FIG. **5**, the information processing apparatus **100** controls the information processing terminal **10** such that the input screen **300** in which the utterance data **D1**, “go out for a meal”, is input to the input field **312**, and the input field **311** and the input field **313** are blank, is displayed. As described above, when a destination of input of the utterance data **D1** is

incorrect, but the attributes of the source and destination input fields **310** are the same, the information processing apparatus **100** can move the utterance data **D1** as it is.

(68) FIG. 7 is a view illustrating another example of input-screen transition in the information processing apparatus **100** according to the embodiment. FIG. 7 illustrates an example of transition in a case where the utterance data **D1** is moved to another input field **310**. FIG. 8 is a view illustrating an example of an overview of information processing regarding the example of transition of the input screen **300** illustrated in FIG. 7. The information processing illustrated in FIG. 8 is performed by execution of a program by the information processing apparatus **100**.

(69) In the example illustrated in FIG. 7, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300**. The input screen **300**, like the input screen **300** illustrated in FIG. 5, includes the input field **311**, the input field **312**, and the input field **313**. The information processing apparatus **100** inputs the utterance data **D1**, “Mr. Sato, would you like to go out for a meal?”, to the title input field **312** based on a result of semantic analysis.

(70) In a step **S21**, the user **U** performs an operation **R2** of moving the GUI **400** on the input screen **300** from the body input field **312** to the vicinity of the recipient input field **311**. In this case, as illustrated in FIG. 8, when detecting the operation **R2** of moving the utterance data **D1** to the input field **311**, the information processing apparatus **100** performs semantic analysis based on the utterance data **D1**, “Mr. Sato, would you like to go out for a meal?”, and the attributes of the input field **311** and the input field **312**. The respective attributes of the input field **311** and the input field **312** are different, and hence the information processing apparatus **100** extracts data that is to be moved, based on the utterance data **D1** and the attribute of the destination. The information processing apparatus **100** extracts data, “Mr. Sato”, regarding a recipient from the utterance data **D1**, and acquires address data corresponding to “Mr. Sato” from the address book data or the like. The information processing apparatus **100** inputs the address data, “sato@xxx.com”, to the recipient input field **313**, and changes the data in the title input field **312** to data, “Would you like to go out for a meal?”.

(71) In a step **S22** illustrated in FIG. 7, the information processing apparatus **100** controls the information processing terminal **10** such that the input screen **300** in which the address data is input to the input field **311**, the data in the input field **312** is changed to the data, “Would you like to go out for meal?”, and the input field **313** is blank, is displayed. As described above, when a destination of input of the utterance data **D1** is incorrect while the attributes of the source and destination input fields **310** are different, the information processing apparatus **100** can move partial data suitable for the attribute of the destination input field **310** in the utterance data **D1**.

(72) [Information Processing (1) according to Embodiment] FIG. 9 is a flowchart illustrating an example of information processing (1) of the information processing apparatus **100** according to the embodiment. A processing procedure illustrated in FIG. 9 is performed by execution of a program by the control unit **130** of the information processing apparatus **100**. The processing procedure illustrated in FIG. 9 is repeatedly performed when the information processing apparatus **100** controls voice input. In other words, the processing procedure illustrated in FIG. 9 is repeatedly performed by the information processing apparatus **100** when the utterance data **D1** of the user **U** is received from the information processing terminal **10**, for example.

(73) As illustrated in FIG. 9, the control unit **130** of the information processing apparatus **100** acquires the utterance data **D1** (step **S101**). For example, the control unit **130** acquires the utterance data **D1** received by the communication unit **110** from the information processing terminal **10**, for example, and stores the utterance data **D1** in the storage unit **120**. For example, the control unit **130** may spontaneously acquire the utterance data **D1** from the information processing terminal **10** via the communication unit **110**. When the processing in the step **S101** ends, the control unit **130** proceeds to a step **S102**.

(74) The control unit **130** semantically analyzes the utterance data **D1** (step **S102**). For example, the control unit **130** executes a semantic analysis program, to decompose the character information

representing the content of utterance indicated by the utterance data D1 into words for each part of speech by word decomposition, and analyzes the sentence structure from the part-of-speech information about the decomposed words. The control unit 130 refers to the meaning of each word included in the content of the user U's utterance and the analyzed sentence structure, to generate analysis information indicating a result of the analysis of the utterance data D1 of the user U, and stores the analysis information into the storage unit 120. When the processing in the step S102 ends, the control unit 130 proceeds to a step S103.

(75) The control unit 130 starts an application based on the analysis information (step S103). For example, in a case where the analysis information indicates sending of a mail, the control unit 130 instructs the information processing terminal 10 to start the mail application 15A via the communication unit 110. For example, in a case where the analysis information indicates sending of a message, the control unit 130 instructs the information processing terminal 10 to start the message application 15B via the communication unit 110. For example, in a case where the analysis information indicates browsing of a web page, the control unit 130 instructs the information processing terminal 10 to start the browser application 15C via the communication unit 110. For example, in a case where the analysis information indicates registration, change, or the like of a schedule, the control unit 130 instructs the information processing terminal 10 to start the calendar application 15D via the communication unit 110. After starting the application, the control unit 130 proceeds to a step S104.

(76) The control unit 130 selects the input field 310 from the plurality of input fields 310 based on the meaning of the utterance data D1 (step S104). For example, the control unit 130 selects the input field 310 that conforms to the meaning of the utterance data D1 with the strongest probability by performing matching between the meaning of the utterance data D1 and the items, the attributes, and the like of the plurality of input fields 310. When the processing in the step S104 ends, the control unit 130 proceeds to a step S105.

(77) The control unit 130 displays the input screen 300 in which the utterance data D1 is input to the selected input field 310 (step S105). For example, the control unit 130 instructs the information processing terminal 10 via the communication unit 110 to display the input screen 300 in which the utterance data D1 is input to the selected input field 310. As a result, the information processing terminal 10 displays the input screen 300 in which the utterance data D1 is input to the input field 310, on the touch panel 13. When the processing in the step S105 ends, the control unit 130 proceeds to a step S106.

(78) The control unit 130 determines whether a moving operation has been detected (step S106). For example, when operation information received from the information processing terminal 10 via the communication unit 110 indicates a moving operation, the control unit 130 determines that a moving operation has been detected. For example, when operation information indicates movement, a destination of movement, or the like of the above-described GUI 400, the control unit 130 determines that a moving operation has been detected. When determining that a moving operation is not detected (No in step S106), the control unit 130 ends the processing procedure illustrated in FIG. 9.

(79) Meanwhile, when determining that a moving operation has been detected (Yes in step S106), the control unit 130 proceeds to a step S107. The control unit 130 semantically analyzes the utterance data D1 based on the attribute of the destination input field 310 (step S107). For example, the control unit 130 executes a semantic analysis program, to analyze the content of utterance conforming to the attribute of the destination input field 310 from the utterance data D1. For example, the control unit 130 analyzes the content (data) of utterance suitable for the attribute of the destination input field 310 in the utterance data D1, the presence or absence of such content of utterance, and the like. After storing analysis information indicating the analysis result in the storage unit 120, the control unit 130 proceeds to a step S108.

(80) The control unit 130 designates the second data that is to be input to the destination input field

310 in the utterance data **D1** based on the analysis information (step **S108**). For example, when the analysis information indicates that data conforming to the attribute of the destination input field **310** is included in the utterance data **D1**, the control unit **130** designates the data conforming to the attribute in the utterance data **D1** as the second data. For example, when the analysis information indicates that all of the utterance data **D1** is data conforming to the attribute of the destination input field **310**, the control unit **130** may designate the utterance data **D1** as the second data. When the processing in the step **S108** ends, the control unit **130** proceeds to a step **S109**.

(81) The control unit **130** determines whether the attributes of the destination and source input fields **310** are the same (step **S109**). For example, the control unit **130** compares the attribute of the destination input field **310** with the attribute of the source input field **310** based on the attribute data **D100**, and determines that the attributes of the destination and source input fields **310** are the same when the compared attributes agree with each other. When determining that the attributes of the destination and source input fields **310** are the same (Yes in step **S109**), the control unit **130** proceeds to a step **S110**.

(82) The control unit **130** inputs the second data to the destination input field **310** (step **S110**). For example, since the attributes of the destination and source input fields **310** are the same, the control unit **130** extracts the second data from the utterance data **D1** and inputs the second data to the destination input field **310** in the input screen **300** without changing the second data. When the processing in the step **S110** ends, the control unit **130** proceeds to a step **S113** described later.

(83) Meanwhile, when determining that the attributes of the destination and source input fields **310** are not the same (No in step **S109**), the control unit **130** proceeds to a step **S111**. The control unit **130** changes the second data so that it has the attribute of the destination input field **310**. For example, the control unit **130** performs change processing on the second data (step **S111**). For example, in a case where the input screen **300** for an e-mail is displayed, the change processing includes, for example, processing of changing the second data so that the attribute thereof is changed to a recipient from a title, a body, or the like, processing of changing the sentence structure of the data, and the like. When the processing in the step **S111** ends, the control unit **130** proceeds to a step **S112**.

(84) The control unit **130** inputs the changed second data to the destination input field **310** (step **S112**). For example, the control unit **130** inputs the second data to the destination input field **310** in the input screen **300**. When the processing in the step **S112** ends, the control unit **130** proceeds to the step **S113**.

(85) The control unit **130** determines whether partial data of the utterance data **D1** has been moved to the destination input field **310** (step **S113**). For example, in a case where the second data is a part of the utterance data **D1**, the control unit **130** determines that the partial data has been moved to the destination input field **310**. When determining that the partial data has been moved to the destination input field **310**, (Yes in step **S113**), the control unit **130** proceeds to a step **S114**.

(86) The control unit **130** deletes the partial data from the utterance data **D** in the source (step **S114**). For example, the control unit **130** deletes the partial data from the utterance data **D1** input to the source input field **310**. For example, the control unit **130** may perform processing of correcting the sentence structure of the utterance data **D1** from which the partial data has been deleted. For example, in a case where data, “Mr. Sato”, in the utterance data **D1**, “Mr. Sato, would you like to go out for a meal?”, is moved, the control unit **130** corrects the sentence structure such that “, would you like to go out for a meal?” is changed to “Would you like to go out for a meal?”. When the processing in the step **S114** ends, the control unit **130** proceeds to a step **S116** described later.

(87) Meanwhile, when determining that the partial data is not moved to the destination input field **310**, (No in step **S113**), the control unit **130** proceeds to a step **S115**. The control unit **130** deletes the utterance data **D1** in the source input field **310** (step **S115**). For example, the control unit **130** deletes the utterance data **D1** input to the source input field **310** and leaves the input field **310** blank. When the processing in the step **S115** ends, the control unit **130** proceeds to a step **S116**.

(88) The control unit **130** controls the display such that the input field **310** in the input screen **300** is updated (step **S116**). For example, the control unit **130** instructs the information processing terminal **10** via the communication unit **110** to display the input screen **300** in which the input field **310** is updated. As a result, the information processing terminal **10** displays the input screen **300** in which the utterance data **D1** has been moved, on the touch panel **13**. When the processing in the step **S116** ends, the control unit **130** ends the processing procedure illustrated in FIG. **9**.

(89) In the processing procedure illustrated in FIG. **9**, the control unit **130** functions as the first input unit **131** by performing the processing in the step **S103** to the step **S104**. The control unit **130** functions as the second input unit **132** by performing the processing in the step **S108** to the step **S112**, and the step **S116**. The control unit **130** functions as the analysis unit **133** by performing the processing in the step **S102** and the step **S107**. The control unit **130** functions as the change unit **134** by performing the processing in the step **S113** to the step **S115**. The control unit **130** functions as the display control unit **135** by performing the processing in the step **S105** and the step **S116**.

(90) [Example of Operations of Information Processing Apparatus according to Embodiment]

(91) FIG. **10** is a view illustrating an example of operations of the information processing apparatus according to the embodiment. In a step **S31** illustrated in FIG. **10**, the user **U** gives utterance **C21** to the information processing terminal **10**. The utterance **C21** is, for example, “E-mail Fuji-san.”. The information processing apparatus **100** semantically analyzes the utterance data **D1** of the utterance **C21**, then erroneously recognizes a person's name, “Fuji-san”, as “Mt. Fuji”, and recognizes that an instruction for starting the mail application **15A** is given. The information processing apparatus **100** starts the mail application **15A**, and inputs the utterance data **D1**, “Mt. Fuji”, to the body input field **313** based on the result of the semantic analysis and the attributes of the plurality of input fields **310** while leaving the recipient input field **311** and the title input field **312** blank. The information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** for an e-mail. The information processing apparatus **100** controls the information processing terminal **10** such that the GUI **400** is displayed near the destination input field **313** in the input screen **300**.

(92) In the example shown in FIG. **10**, the input screen **300** includes the input field **311** of which attribute is a recipient, the input field **312** of which attribute is a title, and the input field **313** of which attribute is a body. In the input screen **300**, the utterance data **D1**, “Mt. Fuji”, is input to the body input field **313**. Hereinafter, the input field **313** will be referred to as an “input field **310**” unless the input field **313** is distinguished from the other input fields **310**.

(93) The user **U** refers to the input screen **300** in the step **S31**, and then determines that the utterance data is not correctly input to the input field **310** in the input screen **300**. Specifically, the user **U** has desired that the utterance data **D1**, “Mt. Fuji”, is input to the recipient input field **311** for an e-mail in the form of an e-mail address. Thus, the user **U** performs a correcting operation in which the GUI **400** on the input screen **300** is moved from the title input field **313** to the vicinity of the recipient input field **311**. Note that the user **U** may perform a moving operation of selecting and moving the data, “Fuji”, in the utterance data **D1**, “Mt. Fuji”, in the input field **313**, to the input field **311**.

(94) When detecting the moving operation of moving the GUI **400** from the input field **313** to the vicinity of the input field **311**, the information processing apparatus **100** performs processing of moving the utterance data **D1** input to the input field **313**, to the input field **311**. The information processing apparatus **100** semantically analyzes the utterance data **D1** again based on the attribute of the destination input field **310** while considering the possibility of an error in the semantic analysis. Consequently, the information processing apparatus **100**, which has accepted the operation of moving the utterance data **D1** to the input field **311** of which attribute is a recipient, extracts the second data, “Fuji” or “Mr. Fuji”, corresponding to the recipient, from the utterance data **D1**. The information processing apparatus **100** acquires an address of the extracted Fuji, fuji@xxx.com (e-mail address), from the address book data or the like, for example.

(95) As illustrated in a step S32, the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which the second data that has been changed to fuji@xxx.com (e-mail address) is input to the input field **311** of which attribute is a recipient, and the body input field **315** is changed to blank. The information processing apparatus **100** controls the information processing terminal **10** such that the GUI **400** is displayed near the recipient input field **311** in the input screen **300**. As a result, the user U confirms that the utterance data **D1** has been input to the intended recipient input field **311** in the input screen **300**.

(96) As described above, when detecting a moving operation of the utterance data **D1** in the input field **310**, the information processing apparatus **100** inputs the second data corresponding to a part of the utterance data **D1** to the destination input field **310** based on the attribute of the destination input field **310**. Consequently, in a case where the utterance data **D1** fails to be input to the input field **310** intended by the user U, the information processing apparatus **100** can easily change data between the plurality of input fields **310** in response to a moving operation of moving the utterance data **D1** to another input field **310**. As a result, the information processing apparatus **100** can improve operability regarding correction of voice input to the plurality of input fields **310**.

(97) [Overview of Information Processing (2) according to Embodiment]

(98) For example, in the case of voice input, the information processing apparatus **100** starts an application different from an application that is requested to be started by the user U, and inputs the utterance data **D1** to the input field **310** of the application in some cases. Thus, the information processing apparatus **100** can provide a function of moving data to the input field **310** of another application in response to the user U's operation.

(99) FIG. **11** is a view illustrating an example of input-screen transition regarding information processing (2) according to the embodiment. FIG. **11** illustrates an example of transition in a case where the utterance data **D1** is moved to the input field **310** of another application.

(100) In a step S41 illustrated in FIG. **11**, the user U gives utterance **C31** to the information processing terminal **10**. The utterance **C31** is, for example, "Make contact with Mr. Sato.". The information processing apparatus **100** semantically analyzes the utterance data **D1** of the utterance **C31**, and then starts the message application **15B**. The information processing apparatus **100** acquires address data of Mr. Sato based on the result of the semantic analysis, and inputs the address data to a recipient input field **314** in an input screen **300A** for a new message. The information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300A** for the new message. The information processing apparatus **100** controls the information processing terminal **10** such that the GUI **400** is displayed near the recipient input field **314** in the input screen **300A**.

(101) In the example shown in FIG. **11**, the input screen **300A** includes the input field **314** of which attribute is a recipient and an input field **315** of which attribute is a message. In the recipient input field **314**, "Address data of Mr. Sato" is input. The message input field **315** is blank. As a result, the user U recognizes the input screen **300A** for the message on the touch panel **13** of the information processing terminal **10**. Hereinafter, the input field **314** and the input field **315** will be referred to as an "input field **310**" unless the input field **314** and the input field **315** are distinguished from each other. Further, the information processing apparatus **100** causes the information processing terminal **10** to display an icon **500** for starting the mail application **15A** at a position off the input screen **300A**. For example, the icon **500** is displayed on a home screen, a background screen, or the like of the information processing terminal **10**.

(102) The user U refers to the input screen **300A** in the step S41, and then recognizes that the mail application **15A** is not started and the message application **15B** is started. Thus, in order to move the utterance data **D1** to the input field **310** of the mail application **15A**, the user U performs an operation **R3** of moving the GUI **400** in the vicinity of the input field **314** so that the GUI **400** overlaps the icon **500**.

(103) In this case, when detecting the operation **R3** of moving the utterance data **D1** to the input

field **310** of the mail application **15A**, the information processing apparatus **100** starts the mail application **15A** and performs semantic analysis based on the utterance data **D1** and the attributes of the plurality of input fields **310** of the mail application **15A**. The information processing apparatus **100** extracts data, “Mr. Sato” or “Sato”, as a recipient of a new mail from the utterance data **D1**, “Make contact with Mr. Sato.”. The information processing apparatus **100** acquires address data of the extracted Sato, sato@xxx.com (e-mail address), from the address book data or the like.

(104) As illustrated in a step **S42**, in the information processing apparatus **100** causes the information processing terminal **10** to display the input screen **300** in which sato@xxx.com (e-mail address) is input to the input field **311** of which attribute is a recipient. The information processing apparatus **100** controls the information processing terminal **10** such that the title input field **312** and the body input field **313** in the input screen **300** are blank and the GUI **400** is displayed near the recipient input field **311**. Consequently, the information processing apparatus **100** can change the content being displayed in the information processing terminal **10** from the input screen **300A** of the message application **15B** to the input screen **300** in which the e-mail address is input to the recipient input field **311** of the mail application **15A**. Then, the information processing apparatus **100** continues the voice input of the user **U** to the input screen **300** of the mail application **15A**.

(105) [Example of Processing Procedure for Information Processing (2) according to Embodiment]

(106) FIG. **12** is a flowchart illustrating an example of information processing (2) of the information processing apparatus **100** according to the embodiment. A processing procedure illustrated in FIG. **12** is performed by execution of a program by the control unit **130** of the information processing apparatus **100**. The processing procedure illustrated in FIG. **12** is repeatedly performed when the information processing apparatus **100** controls voice input. In other words, the processing procedure illustrated in FIG. **12** is repeatedly performed by the information processing apparatus **100** when the utterance data **D1** of the user **U** is received from the information processing terminal **10**, for example.

(107) In the processing procedure illustrated in FIG. **12**, the processing in the step **S101** to the step **S106** is the same as the processing in the step **S101** to the step **S106** illustrated in FIG. **9**, and thus a detailed description thereof will be omitted.

(108) As illustrated in FIG. **12**, the control unit **130** of the information processing apparatus **100** acquires the utterance data **D1** (step **S101**). The control unit **130** semantically analyzes the utterance data **D1** (step **S102**). The control unit **130** starts an application based on the analysis information (step **S103**). The control unit **130** selects the input field **310** from the plurality of input fields **310** based on the meaning of the utterance data **D1** (step **S104**). The control unit **130** displays the input screen **300** in which the utterance data **D1** is input to the selected input field **310** (step **S105**).

(109) The control unit **130** determines whether a moving operation has been detected (step **S106**). When determining that a moving operation is not detected (No in step **S106**), the control unit **130** ends the processing procedure illustrated in FIG. **12**. Meanwhile, when determining that a moving operation has been detected (Yes in step **S106**), the control unit **130** proceeds to a step **S131**.

(110) The control unit **130** determines whether a destination is another application (step **S131**). For example, in a case where a destination of the GUI **400** is an icon, the input screen **300**, or the like of another application, the control unit **130** determines that a destination is another application. For example, the control unit **130** may determine that a destination is another application when receiving an instruction, a voice, or the like for a change to another application, from the user **U**. When the control unit **130** determines that a destination is not another application (No in step **S131**), the control unit **130** proceeds to a step **S132**.

(111) The control unit **130** performs the change processing in response to the moving operation (step **S132**). The change processing includes a series of processing in the step **S107** to the step **S116** illustrated in FIG. **9**, for example. Specifically, the change processing includes processing of

moving the utterance data **D1** input to the source input field **310** to the destination input field **310** and blanking the source input field **310** or changing the utterance data **D1**, in response to a moving operation by the user **U**. When the processing in the step **S132** ends, the control unit **130** ends the processing procedure illustrated in FIG. **12**.

(112) Meanwhile, when determining that a destination is another application (Yes in step **S131**), the control unit **130** proceeds to a step **S133**. The control unit **130** closes the application being run and starts an application that is a destination (step **S133**). For example, in a case where another application that is a destination is the mail application **15A**, the control unit **130** causes the information processing terminal **10** to close the application being run and start the mail application **15A** via the communication unit **110**. When the processing in the step **S133** ends, the control unit **130** proceeds to a step **S134**.

(113) The control unit **130** selects the input field **310** from the plurality of input fields **310** based on the meaning of the utterance data **D1** (step **S134**). For example, the control unit **130** selects the input field **310** that conforms to the meaning of the utterance data **D1** with the strongest probability by performing matching between the plurality of input fields **310** of the newly-started application and the meaning of the utterance data **D1**. When the processing in the step **S134** ends, the control unit **130** proceeds to a step **S135**.

(114) The control unit **130** displays the input screen **300** in which the utterance data **D1** is input to the selected input field **310** (step **S135**). For example, the control unit **130** instructs the information processing terminal **10** via the communication unit **110** to display the input screen **300** in which the utterance data **D1** is input to the selected input field **310**. As a result, the information processing terminal **10** displays the input screen **300** in which the utterance data **D1** is input to the input field **310** of the newly-started application, on the touch panel **13**. When the processing in the step **S135** ends, the control unit **130** proceeds to a step **S136**.

(115) The control unit **130** determines whether a moving operation has been detected (step **S136**). For example, when operation information received from the information processing terminal **10** via the communication unit **110** indicates a moving operation performed on the newly-started application, the control unit **130** determines that a moving operation has been detected. When determining that a moving operation is not detected (No in step **S136**), the control unit **130** ends the processing procedure illustrated in FIG. **12**. Meanwhile, when determining that a moving operation has been detected (Yes in step **S136**), the control unit **130** proceeds to the step **S132** described above.

(116) The control unit **130** performs the change processing in response to the moving operation (step **S132**). Consequently, the control unit **130** moves the utterance data **D1** input to the source input field **310**, to the destination input field **310** in the same input screen **300**, in response to the moving operation by the user **U**. When the processing in the step **S132** ends, the control unit **130** ends the processing procedure illustrated in FIG. **12**.

(117) In the processing procedure illustrated in FIG. **12**, the control unit **130** functions as the second input unit **132** by performing the processing in the step **S131** and in the step **S133** to the step **S134**. The control unit **130** functions as the display control unit **135** by performing the processing in the step **S135**.

(118) As described above, when detecting a moving operation of moving the utterance data **D1** in the input field **310** to another application, the information processing apparatus **100** starts another application and inputs the utterance data **D1** to the destination input field **310** based on the attribute of the input field **310** of another application. Consequently, in a case where the utterance data **D1** fails to be input to the input field **310** intended by the user **U**, the information processing apparatus **100** can move the utterance data **D1** between different applications in response to a moving operation of moving the utterance data **D1** to another application. As a result, the information processing apparatus **100** can improve operability regarding correction of voice input to the input field **310** of an application.

(119) [Information Processing (3) According to Embodiment]

(120) FIG. 13 is a view illustrating an example of information processing (3) of the information processing apparatus according to the embodiment. The information processing (3) illustrated in FIG. 13 shows an example of a case where data in the input field 310 is moved to another input field 310 by the user U's voice.

(121) In a step S51 illustrated in FIG. 13, the user U gives utterance C41 to the information processing terminal 10 while the mail application 15A is started. The utterance C41 is, for example, "Have a meal with Mr. Sato.". The information processing apparatus 100 semantically analyzes first utterance data of the utterance C41, and then inputs the first utterance data to the title input field 312 while leaving the recipient input field 311 and the body input field 313 blank. The information processing apparatus 100 causes the information processing terminal 10 to display the input screen 300. The information processing apparatus 100 controls the information processing terminal 10 such that the GUI 400 is displayed near the title input field 312 in the input screen 300.

(122) The user U refers to the input screen 300 in the step S51, and thereafter gives utterance C42 to the information processing terminal 10. The utterance C42 is, for example, "Mr. Sato is a recipient.". Alternatively, the user U may give utterance, "Mr. Sato is allocated to an input field at a level higher by one", or the like, for example. The information processing apparatus 100 semantically analyzes second utterance data of the utterance C42, and recognizes that "Mr. Sato" is included in the first utterance data. The information processing apparatus 100 detects the content of the utterance, "Mr. Sato is a recipient.", as a second operation, and performs processing of moving partial data of the utterance data D1 (i.e., data, Mr. Sato). Consequently, the information processing apparatus 100 acquires address data corresponding to the data, "Mr. Sato", from the first utterance data, and inputs the address data to the recipient input field 310. The information processing apparatus 100 changes the first utterance data to "Have a meal" so that the data, "Mr. Sato", having been moved is deleted from the first utterance data.

(123) As illustrated in a step S52, the information processing apparatus 100 causes the information processing terminal 10 to display the input screen 300 in which the data, "Mr. Sato", is input to the recipient input field 311 and the first utterance data in the title input field 312 is changed to "Have a meal.". As a result, the user U confirms that the part of the first utterance data has been input to the recipient input field 311 in the input screen 300 as instructed by a voice.

(124) As described above, when detecting a moving operation performed on the utterance data D1 in the input field 310 by a voice, the information processing apparatus 100 inputs partial data of the utterance data D1 to the destination input field 310 based on the attribute of the destination input field 310. Consequently, in a case where the utterance data D1 fails to be input to the input field 310 intended by the user U, the information processing apparatus 100 can easily change data between the plurality of input fields 310 in response to a voice for moving the utterance data D1 to another input field 310. As a result, the information processing apparatus 100 can improve operability regarding correction of voice input to the plurality of input fields 310.

(125) The above-described information processing (3) has discussed the case where the information processing apparatus 100 detects a moving operation in which the partial data of the utterance data D1 is moved by a voice, but the present disclosure is not limited thereto. For example, the information processing apparatus 100 can be configured to detect a moving operation based on the user U's gesture of selecting and moving partial data on the touch panel 13.

(126) [Information Processing (4) According to Embodiment]

(127) FIG. 14 is a view illustrating an example of information processing (4) of the information processing apparatus according to the embodiment. The information processing (4) illustrated in FIG. 14 shows an example in which data is input to the plurality of input fields 310 by a voice.

(128) In a step S61 illustrated in FIG. 14, the user U gives utterance C51 to the information processing terminal 10 while the mail application 15A is started. The utterance C51 is, for example, "Have a meal with Mr. Sato.". The information processing apparatus 100 semantically analyzes

first utterance data of the utterance C51, and then inputs the first utterance data to the title input field 312 while leaving the recipient input field 311 and the body input field 313 blank. The information processing apparatus 100 causes the information processing terminal 10 to display the input screen 300. The information processing apparatus 100 controls the information processing terminal 10 such that the GUI 400 is displayed near the title input field 312 in the input screen 300. (129) The user U refers to the input screen 300 in the step S61 to recognize that voice input has been properly achieved, and thereafter gives utterance C52 to the information processing terminal 10. The utterance C52 is, for example, “A recipient is Mr. Suzuki.”. The information processing apparatus 100 semantically analyzes second utterance data of the utterance C52 and selects the recipient input field 312 as a destination of input. The information processing apparatus 100 acquires address data of “Mr. Suzuki”, from the address book or the like, and inputs the address data of Mr. Sato to the recipient input field 311.

(130) As illustrated in a step S62, the information processing apparatus 100 causes the information processing terminal 10 to display the input screen 300 in which the address data of Mr. Suzuki is input to the recipient input field 311 and the first utterance data, “Have a meal with Mr. Sato.”, is input to the title input field 312. The information processing apparatus 100 controls the information processing terminal 10 such that the GUI 400 is displayed near the recipient input field 311 in the input screen 300. As a result, the user U confirms that the part of the first utterance data has been input to the recipient input field 311 in the input screen 300 as instructed by a voice.

(131) Note that the information processing apparatus 100 may cause the GUI 400 to be displayed near the title input field 312 in the input screen 300, or may cause the two GUIs 400 to be displayed near the input field 311 and the input field 312, respectively.

(132) As described above, when detecting a moving operation performed on the utterance data D1 in the input field 310, the information processing apparatus 100 inputs partial data of the utterance data D1 to the destination input field 310 based on the attribute of the destination input field 310. Consequently, in a case where the utterance data D1 fails to be input to the input field 310 intended by the user U, the information processing apparatus 100 can easily change data between the plurality of input fields 310 in response to a voice for moving the utterance data D1 to another input field 310. As a result, the information processing apparatus 100 can improve operability regarding correction of voice input to the plurality of input fields 310.

(133) [Hardware Configuration]

(134) Information equipment such as the information processing system 1 according to the embodiment described above is implemented by a computer 1000 having a configuration illustrated in FIG. 15, for example. Below, description will be given by taking as an example the information processing apparatus 100 according to the embodiment. FIG. 15 is a hardware configuration diagram illustrating an example of the computer 1000 that performs the functions of the information processing apparatus 100. The computer 1000 includes a CPU 1100, a RAM 1200, a read only memory (ROM) 1300, a hard disk drive (HDD) 1400, a communication interface 1500, and an input/output interface 1600. Each unit of the computer 1000 is connected by a bus 1050.

(135) The CPU 1100 operates in accordance with a program stored in the ROM 1300 or the HDD 1400, and controls each unit. For example, the CPU 1100 loads the programs stored in the ROM 1300 or the HDD 1400 into the RAM 1200, and performs processing corresponding to various programs.

(136) The ROM 1300 stores therein a boot program such as basic input output system (BIOS) executed by the CPU 1100 at startup of the computer 1000, a program depending on the hardware of the computer 1000, and the like.

(137) The HDD 1400 is a computer-readable recording medium in which programs executed by the CPU 1100, data used in the programs, and the like are non-transiently stored. Specifically, the HDD 1400 is a recording medium in which an information processing program according to the present disclosure, which is an example of a program data 1450, is recorded.

(138) The communication interface **1500** is an interface for connecting the computer **1000** to an external network **1550** (for example, the Internet). For example, the CPU **1100** receives data from another apparatus and transmits data generated by the CPU **1100** to another apparatus via the communication interface **1500**.

(139) The input/output interface **1600** is an interface for connecting an input/output device **1650** and the computer **1000**. For example, the CPU **1100** receives data from an input device such as a keyboard and a mouse via the input/output interface **1600**. Further, the CPU **1100** transmits data to an output device such as a display, a speaker, or a printer, via the input/output interface **1600**. Moreover, the input/output interface **1600** may function as a medium interface that reads a program or the like recorded in a predetermined recording medium (medium). Examples of the medium include an optical recording medium such as a digital versatile disc (DVD), a magneto-optical recording medium such as a magneto-optical disk (MO), a tape medium, a magnetic recording medium, a semiconductor memory, and the like.

(140) For example, in a case where the computer **1000** functions as the information processing apparatus **100** according to the embodiment, the CPU **1100** of the computer **1000** executes the information processing program loaded into the RAM **1200**, to perform the functions of the first input unit **131**, the second input unit **132**, the analysis unit **133**, the change unit **134**, the display control unit **135**, and the like. Further, the HDD **1400** stores therein the information processing program according to the present disclosure and the data in the storage unit **120**. Whereas the CPU **1100** executes the program data **1450** after reading it from the HDD **1400**, the program may be obtained from another apparatus via the external network **1550** in an alternative example.

(141) In the present embodiment described above, the case where the information processing apparatus **100** performs information processing in cooperation with the information processing terminal **10** in the information processing system **1** has been described, but the present disclosure is not limited thereto. For example, the information processing apparatus **100** may perform information processing solely. In other words, the information processing apparatus **100** may incorporate therein the functions of the information processing terminal **10**. For example, the information processing terminal **10** may be configured such that the control unit **16** implements the first input unit **131**, the second input unit **132**, the analysis unit **133**, the change unit **134**, and the like of the information processing apparatus **100**.

(142) While the preferred embodiment of the present disclosure has been described above in detail with reference to the accompanying drawings, the technical scope of the present disclosure is not limited to the embodiment. It is obvious that a person having ordinary knowledge in the technical field of the present disclosure can conceive various changes or modifications within the scope of the technical idea described in the claims, and it is naturally understood that these also fall within the technical scope of the present disclosure.

(143) Further, the effects described in the present specification are merely illustrative or exemplary, and are not restrictive. That is, the techniques according to the present disclosure can produce other effects obvious to those skilled in the art from the description of the present specification, in addition to, or in place of, the above-described effects.

(144) Furthermore, it is also possible to create a program for causing hardware such as a CPU, a ROM, and a RAM built in a computer to exhibit functions equivalent to those of the components of the information processing apparatus **100**, and to provide also a computer-readable recording medium in which the program is recorded.

(145) Furthermore, the respective steps regarding the processing of the information processing apparatus **100** in the present specification are not necessarily required to be performed in time series in the order described in the flowchart. For example, the respective steps regarding the processing of the information processing apparatus **100** may be performed in an order different from the order described in the flowchart, or may be performed in parallel.

(146) The above-described embodiment has discussed the case where the information processing

apparatus **100** displays the input screen **300** having the plurality of input fields **310** on the touch panel **13** of the information processing terminal **10**, but the present disclosure is not limited thereto. The information processing apparatus **100** may be configured to display the plurality of input fields **310** and the GUI **400** in a predetermined area in a virtual space.

(147) The above-described embodiment has discussed the case where the information processing apparatus **100** detects a moving operation in response to a touch operation on the GUI **400** or a voice, but the present disclosure is not limited thereto. The information processing apparatus **100** may be configured to detect a moving operation in response to sign language, brain waves, a gesture made on the touch panel **13**, or the like, for example.

(148) (Effects)

(149) The information processing apparatus **100** includes: the first input unit **131** configured to input first data obtained by capture of a speaker's voice to a first input field selected from the plurality of input fields **310** based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields **310**; and the second input unit **132** configured to input second data belonging to an attribute of a second input field in the first data, to a second input field in response to an operation of moving the first data from the first input field to the second input field.

(150) Thus, in a case where the first data fails to be input to the input field **310** intended by the user U, the information processing apparatus **100** can easily move data between the plurality of input fields **310** in response to the operation of moving the first data to another input field **310**.

Consequently, in the information processing apparatus **100**, it is only required that the user U designates a destination input field of the first data, and hence, it is possible to improve operability in moving the first data automatically input to the input field **310**, to another input field.

(151) In the information processing apparatus **100**, when the attributes of the first input field and the second input field are different, the second input unit **132** inputs the second data belonging to the attribute of the second input field in the first data to the second input field.

(152) Thus, the information processing apparatus **100** can input the second data belonging to the attribute of the second input field in the first data, to the second input field, in response to the operation of moving the first data to the second input field having a different attribute. As a result, in the information processing apparatus **100**, the user U does not need to pay attention to the attribute of the destination input field of the first data, and hence, it is possible to improve operability regarding correction of voice input to the plurality of input fields **310**.

(153) The information processing apparatus **100** further includes the analysis unit **133** capable of semantically analyzing the first data based on the attribute of the destination input field. The second input unit **132** inputs the second data corresponding to partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, based on the meaning of the first data analyzed by the analysis unit **133** and the attribute of the second input field.

(154) Thus, the information processing apparatus **100** can input the second data corresponding to the partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, in response to the operation of moving the first data to the second input field having a different attribute. As a result, the information processing apparatus **100** can move data conforming to the attribute of the destination input field **310** in the first data to the second input field, and hence, it is possible to further improve operability regarding correction of voice input to the plurality of input fields **310**.

(155) In the information processing apparatus **100**, the second input unit **132** inputs the second data corresponding to partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(156) Thus, the information processing apparatus **100** can input the second data corresponding to

the partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, in response to the operation of moving the first data from the first input field to the second input field. As a result, in moving the first data to the second input field in the information processing apparatus **100**, the user U does not need to pay attention to the attribute of the destination input field, and hence, it is possible to further improve operability regarding correction of voice input to the plurality of input fields **310**.

(157) The information processing apparatus **100** further includes the change unit **134** configured to change the first data such that the partial data having been moved to the second input field is deleted from the first data input to the first input field.

(158) Thus, the information processing apparatus **100** can change the first data in the first input field when the partial data of the first data is moved from the first input field to the second input field. As a result, in moving the partial data of the first data to the second input field in the information processing apparatus **100**, the user U does not need to correct data in the source input field, and hence, it is possible to further improve operability regarding correction of voice input to the plurality of input fields **310**.

(159) In the information processing apparatus **100**, when the attributes of the first input field and the second input field are the same, the second input unit **132** inputs the first data to the second input field, as the second data.

(160) Thus, in a case where the first data fails to be input to the input field **310** intended by the user U, the information processing apparatus **100** can move the first data to the second input field in response to the operation of moving the first data to the second input field. As a result, the information processing apparatus **100** can move the first data in the first input field to the second input field only by the user U's designation of the input field of which attribute is the same as that of the first input field, as a destination of movement of the first data. Hence, it is possible to improve operability regarding correction of voice input to the plurality of input fields **310**.

(161) In the information processing apparatus **100**, the second input unit **132** inputs the second data based on the partial data of the first data to the second input field, in response to a second operation of moving partial data of the first data from the first input field, to the second input field.

(162) Thus, the information processing apparatus **100** can input the partial data of the first data to the second input field in response to the second operation of moving the partial data of the first data from the first input field to the second input field. As a result, in the information processing apparatus **100**, the user U can easily input the partial data of the first data in the first input field to the second input field, and hence, it is possible to improve an efficiency of voice input to the plurality of input fields **310**.

(163) The information processing apparatus **100** further includes the display control unit **135** configured to control the display device such that the input screen including the plurality of input fields **310** is displayed. The display control unit **135** controls the display device such that the input screen in which the second input field inputs the second data to the second input field, is displayed.

(164) Thus, the information processing apparatus **100** can cause the display device to display the input screen in response to the input of the second data to the second input field. As a result, the information processing apparatus **100** allows the user U to confirm a result of movement of the first data to the second input field, to thereby assist in an operation of moving the first data automatically input to the input field **310** to another input field.

(165) In the information processing apparatus **100**, the display control unit **135** controls the display device such that an object capable of designating the destination input field **310** is displayed near the input field to which the first data is input. The second input unit **132** detects an operation of moving the first data from the first input field to the second input field in accordance with an instruction for moving the object.

(166) Thus, the information processing apparatus **100** can detect an operation of moving the first data from the first input field to the second input field in response to movement of the object from

the first input field to the second input field. As a result, in the information processing apparatus **100**, the user U is only required to move the object from the first input field to the second input field, and hence, it is possible to improve an efficiency of voice input to the plurality of input fields **310**.

(167) In the information processing apparatus **100**, in response to a third operation of moving the first data from the first input field in a first screen to a second screen different from the first screen, the second input unit **132** inputs the first data to the third input field selected from the plurality of input fields in the second screen based on the meaning of the content of utterance indicated by the first data.

(168) Thus, the information processing apparatus **100** can input the first data to the third input field of which attribute is suitable for the first data in the second screen, in response to the third operation of moving the first data to the first input field in the first screen to the second screen. As a result, the information processing apparatus **100** can input the first data to the input field in the second screen suitable for the first data only by the user U's designation of the second screen as a destination of movement of the first data. Hence, it is possible to improve an efficiency of voice input to the plurality of input fields **310** in the plurality of screens.

(169) In the information processing apparatus **100**, the third operation includes an operation of moving the first data from the first input field in the first screen to an application using the a second screen, and the second input unit starts the application in response to the third operation and inputs the first data to the third input field selected from the plurality of input fields in the second screen based on the meaning of content of utterance indicated by the first data.

(170) Thus, when starting the application in response to the third operation, the information processing apparatus **100** can input the first data to the second input field suitable for the first data among the plurality of input fields in the second screen of the application. As a result, only by the user U's selection of the application as a destination of movement of the first data, the information processing apparatus **100** can start the application and input the first data to the input field in the second screen suitable for the first data. Hence, it is possible to improve an efficiency of voice input to the plurality of input fields **310** in the plurality of screens.

(171) In the information processing apparatus **100**, the second screen includes the third input field and a fourth input field. The second input unit **132** inputs the second data belonging to the attribute of the fourth input field in the first data to the fourth input field, in response to a fourth operation of moving the first data from the third input field to the fourth input field.

(172) Thus, in a case where the first data fails to be input to the input field **310** intended by the user U in the second screen, the information processing apparatus **100** can easily move data between the plurality of input fields **310** in response to the operation of moving the first data to another input field **310** in the second screen. As a result, in the information processing apparatus **100**, it is only required that the user U designates a destination input field of the first data, and hence, it is possible to improve operability in moving the first data automatically input to the input field **310**, to another input field, in the plurality of input screens.

(173) In the information processing apparatus **100**, the operation of moving the first data from the first input field to the second input field includes a voice-activated operation.

(174) Thus, the information processing apparatus **100** can accept the operation of moving the first data from the first input field to the second input field, in a voice. As a result, only by the user U's voice designation of the destination second input field of the first data, the information processing apparatus **100** can move the first data in the first input field to the second input field. Hence, it is possible to improve operability regarding correction of voice input to the plurality of input fields **310**.

(175) An information processing method performed by a computer, includes: inputting first data obtained by capture of a speaker's voice to the first input field selected from the plurality of input fields **310**, based on the meaning of content of utterance indicated by the first data and the

attributes of the plurality of input fields; and inputting the second data belonging to the attribute of the second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(176) Thus, with the information processing method, in a case where the first data fails to be input to the input field **310** intended by the user U, the computer can easily move data between the plurality of input fields **310** in response to the operation of moving the first data to another input field **310**. As a result, in the information processing method, it is only required that the user U designates a destination input field of the first data, and hence, it is possible to improve operability in moving the first data automatically input to the input field **310**, to another input field.

(177) An information processing program that causes a computer to perform: inputting the first data obtained by capture of a speaker's voice to the first input field selected from the plurality of input fields **310**, based on the meaning of content of utterance indicated by the first data and the attributes of the plurality of input fields; and inputting the second data belonging to the attribute of the second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(178) Thus, with the information processing program, in a case where the first data fails to be input to the input field **310** intended by the user U, the computer can easily move data between the plurality of input fields **310** in response to the operation of moving the first data to another input field **310**. As a result, in the information processing method, it is only required that the user U designates a destination input field of the first data, and hence, it is possible to improve operability in moving the first data automatically input to the input field **310**, to another input field.

(179) Note that also the following configurations are included in the technical scope of the present disclosure.

(180) (1)

(181) An information processing apparatus including: a first input unit configured to input first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and a second input unit configured to input second data belonging to an attribute of a second input field in the first data, to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(2)

(182) The information processing apparatus according to (1), wherein when the attributes of the first input field and the second input field are different, the second input unit inputs the second data belonging to the attribute of the second input field in the first data, to the second input field.

(183) (3)

(184) The information processing apparatus according to (1) or (2), further including an analysis unit capable of semantically analyzing the first data based on an attribute of a destination input field, wherein, the second input unit inputs the second data corresponding to partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, based on a meaning of the first data analyzed by the analysis unit and the attribute of the second input field.

(4)

(185) The information processing apparatus according to any one of (1) to (3), wherein the second input unit inputs the second data corresponding to partial data of the first data having been changed so as to have the attribute of the second input field, to the second input field, in response to the operation of moving the first data from the first input field to the second input field.

(186) (5)

(187) The information processing apparatus according to (4) further including a change unit configured to change the first data such that the partial data having been moved to the second input field is deleted from the first data input to the first input field.

(188) (6)

(189) The information processing apparatus according to any one of (1) to (5), wherein when the attributes of the first input field and the second input field are the same, the second input unit inputs the first data to the second input field, as the second data.

(190) (7)

(191) The information processing apparatus according to any one of (1) to (6), wherein the second input unit inputs the second data based on the attribute of the second input field and partial data of the first data, to the second input field, in response to a second operation of moving the partial data from the first input field to the second input field.

(192) (8)

(193) The information processing apparatus according to any one of (1) to (7), further including a display control unit configured to control a display device such that an input screen including the plurality of input fields is displayed, wherein the display control unit controls the display unit such that the input screen in which the second input unit inputs the second data to the second input field is displayed.

(9)

(194) The information processing apparatus according to (8), wherein the display control unit controls the display device such that an object capable of designating the input field that is a destination is displayed near the input field to which the first data is input, and the second input unit detects the operation of moving the first data from the first input field to the second input field in accordance with an instruction for moving the object.

(10)

(195) The information processing apparatus according to any one of (1) to (9), wherein, in response to a third operation of moving the first data from the first input field in a first screen to a second screen different from the first screen, the second input unit inputs the first data to a third input field selected from the plurality of input fields in the second screen based on the meaning of the content of utterance indicated by the first data.

(196) (11)

(197) The information processing apparatus according to (10), wherein the third operation includes an operation of moving the first data from the first input field in the first screen to an application using the second screen, the second input unit starts the application in response to the third operation, and inputs the first data to the third input field selected from the plurality of input fields in the second screen based on the meaning of the content of utterance indicated by the first data.

(12)

(198) The information processing apparatus according to (10) or (11), wherein the second screen includes the third input field and a fourth input field, the second input unit inputs the second data belonging to an attribute of the fourth input field in the first data, to the fourth input field, in response to a fourth operation of moving the first data from the third input field to the fourth input field.

(13)

(199) The information processing apparatus according to any one of (1) to (12), wherein the operation of moving the first data from the first input field to the second input field includes a voice-activated operation.

(200) (14)

(201) An information processing method performed by a computer, including: inputting first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields, based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and inputting second data belonging to an attribute of a second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(15)

(202) An information processing program that causes a computer to perform: inputting first data obtained by capture of a speaker's voice to a first input field selected from a plurality of input fields, based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and inputting second data belonging to an attribute of a second input field in the first data to the second input field, in response to an operation of moving the first data from the first input field to the second input field.

(16)

(203) An information processing system including: an information processing terminal configured to acquire first data by capturing a speaker's voice; and an information processing apparatus capable of communicating with the information processing terminal, wherein the information processing apparatus includes: a first input unit configured to input the first data to a first input field selected from a plurality of input fields based on a meaning of content of utterance indicated by the first data, and attributes of the plurality of input fields; and a second input unit configured to input second data belonging to an attribute of a second input field in the first data, to a second input field, in response to an operation of moving the first data from the first input field to the second input field.

REFERENCE SIGNS LIST

(204) **1** INFORMATION PROCESSING SYSTEM **10** INFORMATION PROCESSING TERMINAL **11** SENSOR UNIT **12** INPUT UNIT **13** TOUCH PANEL **14** COMMUNICATION UNIT **15** STORAGE UNIT **15A** MAIL APPLICATION **15B** MESSAGE APPLICATION **16** CONTROL UNIT **100** INFORMATION PROCESSING APPARATUS **110** COMMUNICATION UNIT **120** STORAGE UNIT **130** CONTROL UNIT **131** FIRST INPUT UNIT **132** SECOND INPUT UNIT **133** ANALYSIS UNIT **134** CHANGE UNIT **135** DISPLAY CONTROL UNIT **D1** UTTERANCE DATA **D100** ATTRIBUTE DATA **D200** USER DATA

Claims

1. An information processing apparatus, including: a central processing unit (CPU) configured to: acquire first data from a user terminal, wherein the acquired first data corresponds to voice of a user associated with the user terminal; input the acquired first data to a first input field from a plurality of input fields, based on a meaning of content of utterance indicated by the first data and attributes of the plurality of input fields; extract partial data from the first data in the first input field; change the extracted partial data into second data, wherein the second data has an attribute of a second input field; and input, based on a first movement of data from the first input field to the second input field, the second data to the second input field.
2. The information processing apparatus according to claim 1, wherein the CPU is further configured to input, based on attributes of the first input field and the second input field are different, the second data, belonging to the attribute of the second input field, to the second input field.
3. The information processing apparatus according to claim 2, wherein the CPU is further configured to: semantically analyze the first data based on the attribute of the second input field; and input the second data to the second input field, based on a meaning of the semantically analyzed first data and the attribute of the second input field.
4. The information processing apparatus according to claim 1, wherein the CPU is further configured to change the first data such that the partial data is deleted from the first data input to the first input field.
5. The information processing apparatus according to claim 1, wherein CPU is further configured to input, based on attributes of the first input field and a third input field are same, the first data to the third input field.

6. The information processing apparatus according to claim 2, wherein CPU is further configured to input the second data to the second input field, based on a second movement of data from the first input field to the second input field, the attribute of the second input field, and partial data of the first data.
 7. The information processing apparatus according to claim 2, wherein the CPU is further configured to control a display device to display an input screen including the plurality of input fields.
 8. The information processing apparatus according to claim 7, wherein the CPU is further configured to: control the display device to display an object, to designate an input field as the second input field, near the first input field, and detect the first movement of data from the first input field to the second input field, based on an instruction to move the object.
 9. The information processing apparatus according to claim 1, wherein, based on a third movement of data from the first input field in a first screen to a second screen different from the first screen and the meaning of the content of utterance indicated by the first data, the CPU is further configured to input the first data to a third input field from a plurality of input fields in the second screen.
 10. The information processing apparatus according to claim 9, wherein the third movement of data includes an operation to move the first data from the first input field in the first screen to an application using the second screen, and the CPU is further configured to: start the application in response to the third movement of data, and input the first data to the third input field from the plurality of input fields in the second screen based on the meaning of the content of utterance indicated by the first data.
 11. The information processing apparatus according to claim 10, wherein the second screen includes the third input field and a fourth input field, third data belongs to an attribute of the fourth input field, and the CPU is further configured to input third data in the first data, to the fourth input field, based on a fourth movement of data from the third input field to the fourth input field.
 12. The information processing apparatus according to claim 1, wherein the first movement of data from the first input field to the second input field includes a voice-activated operation.
 13. An information processing method, including: acquiring first data from a user terminal, wherein the acquired first data corresponds to voice of a user associated with the user terminal; inputting the acquired first data to a first input field from a plurality of input fields, based on a meaning of content of utterance indicated by the first data and attributes of the plurality of input fields; extracting partial data from the first data in the first input field; changing the extracted partial data into second data, wherein the second data has an attribute of a second input field; and inputting, based on a first movement of data from the first input field to the second input field, the second data to the second input field.
 14. A non-transitory computer-readable medium having stored thereon, computer-executable instructions which, when executed by a computer, cause the computer to execute operations, the operations comprising: acquiring first data from a user terminal, wherein the acquired first data corresponds to voice of a user associated with the user terminal; inputting the acquired first data to a first input field from a plurality of input fields, based on a meaning of content of utterance indicated by the first data and attributes of the plurality of input fields; extracting partial data from the first data in the first input field; changing the extracted partial data into second data, wherein the second data has an attribute of a second input field; and inputting, based on a first movement of data from the first input field to the second input field, the second data to the second input field.
-