

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400177
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kim; Tae Kyung

Systems and methods for interconnecting network devices based on queuing and servicing responses

Abstract

A system for interconnecting network devices based on queuing and servicing responses includes one or more processors configured to receive, from a first computer system, an order request for a product or service associated with a second computer system of a plurality of second computer systems. Instantiate an order messaging queue associated with the order request and add an identifier of the first computer system to the order messaging queue. Add an identifier of the second computer system and one of the third computer systems to the order messaging queue. Determine the contents of the communication and based on determining contents of the communication, consult a response rule table to determine a response to the communication. Access the order messaging queue to identify server devices corresponding with servicing the determined response and publish, to the identified server devices.

Inventors:	Kim; Tae Kyung (Seoul, KR)
Applicant:	COUPANG CORP. (Seoul, KR)
Family ID:	1000008780246
Assignee:	COUPANG CORP. (Seoul, KR)
Appl. No.:	17/235803
Filed:	April 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210272062 A1	Sep. 02, 2021

Related U.S. Application Data

continuation parent-doc US 16806631 20200302 US 11010707 child-doc US 17235803

Publication Classification

Int. Cl.: G06Q30/00 (20230101); G06Q10/083 (20230101); G06Q30/0601 (20230101);
H04L51/02 (20220101); H04L65/1066 (20220101)

U.S. Cl.:

CPC G06Q10/0838 (20130101); G06Q30/0635 (20130101); G06Q30/0637 (20130101);
H04L51/02 (20130101); H04L65/1066 (20130101);

Field of Classification Search

CPC: G06Q (30/0601-0645); G06Q (10/0838); G06Q (30/0635); G06Q (10/0834); G06Q
(10/0835); G06Q (10/107); H04L (51/02); H04L (65/1066)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5729594	12/1997	Klingman	379/93.12	G06Q 20/00
8117086	12/2011	Utz	705/26.81	G06Q 30/0635
8473316	12/2012	Panzitta	705/26.81	G06Q 30/0234
8774087	12/2013	Tapia et al.	N/A	N/A
10013293	12/2017	Schofield et al.	N/A	N/A
10977751	12/2020	Bernstein	N/A	G06Q 10/0832
11308536	12/2021	Adler	N/A	G06Q 10/083
2007/0106568	12/2006	Asher et al.	N/A	N/A
2008/0281676	12/2007	Stahura	705/7.29	G06Q 30/0201
2016/0063435	12/2015	Shah	705/44	G06Q 30/0633
2017/0208014	12/2016	Chattaraj et al.	N/A	N/A
2018/0107979	12/2017	Westover	N/A	G06Q 30/0611
2018/0295084	12/2017	Gourevitch et al.	N/A	N/A
2019/0238495	12/2018	Zhang et al.	N/A	N/A
2020/0184011	12/2019	Bastide	N/A	H04L 51/046

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106779183	12/2016	CN	N/A
102467701	12/2016	CN	N/A
105512244	12/2018	CN	N/A

10-2011-0065448	12/2010	KR	N/A
10-2014-0133048	12/2013	KR	N/A
10-2017-0131572	12/2016	KR	N/A
10-2017-0131572	12/2016	KR	N/A
10-2020-0003059	12/2019	KR	N/A
WO 2016/153540	12/2015	WO	N/A

OTHER PUBLICATIONS

Won, Jaeyeon. "Order Batching and Picking Optimization in Terms of Supply Chain Management (SCM)." Order No. 3158379 Iowa State University, 2004. Ann Arbor: ProQuest. Web. Aug. 25, 2022. (Year: 2004). cited by examiner

"HeyWire Highlights LiveText Business Messenger Customer Momentum and New Features as Business Texting Becomes a Key Channel in the Customer Experience Economy . . ." PR Newswire, Apr. 22, 2015, p. n/a. ProQuest. Web. Feb. 21, 2023 . (Year: 2015). cited by examiner

Soto Setzke, David, et al. "Matching drivers and transportation requests in crowdsourced delivery systems." (2017). (Year: 2017). cited by examiner

Hirschberg, Carsten, et al. "The changing market for food delivery." (2016). (Year: 2016). cited by examiner

Lee, Min Kyung, et al. "Working with machines: The impact of algorithmic and data-driven management on human workers." Proceedings of the 33rd annual ACM conference on human factors in computing systems. 2015. (Year: 2015). cited by examiner

Tokopedia, TK., et al. "Logistic Courier Machine." InnovationQTM Powered by Ip.Com Prior Art Database, Dec. 15, 2021, ip.com/IPCOM/000267996. (Year: 2021). cited by examiner

Examination Notice in counterpart Hong Kong Application No. 22021024459.0 dated Mar. 4, 2022 (8 pages). cited by applicant

Search Report issued Aug. 18, 2020, for Korean Patent Application No. 10-2020-0055451 (9 pp.). cited by applicant

Notice of Preliminary Rejection in corresponding Korean Patent Application No. 2020-0055451 mailed Dec. 18, 2020 (19 pages). cited by applicant

IP packet transmission and performance analysis technique (Reference: <https://seokr.tistory.com/158>), (May 3, 2016). cited by applicant

Notice of Allowance, issued by the Taiwan Intellectual Property Office in counterpart R.O.C. application No. 109146604, Mar. 2, 2020, 3 pp. cited by applicant

PCT International Search Report and Written Opinion in counterpart International Application No. PCT/IB2020/062329, filed on Dec. 22, 2020, 9 pp. cited by applicant

Notice of Preliminary Rejection in counterpart Korean Patent Application No. 10-2021-0142707 dated Jul. 11, 2022 (17 pages). cited by applicant

"[Data Communication and Networking] Chapter 10. IP Packet Transmission and Performance Analysis Techniques" dated May 3, 2016 (12 pages). cited by applicant

Notice of Final Rejection in counterpart Korean Application No. 10-2021-0142707 dated Nov. 21, 2022 (7 pages). cited by applicant

Notice of Final Rejection in counterpart Korean Application No. 10-2021-0142707 dated Mar. 2, 2023 (7 pages). cited by applicant

Further examination notice in Hong Kong Application No. 22021024459.0 dated Jun. 27, 2023 (8 pages). cited by applicant

Primary Examiner: Smith; Jeffrey A.

Assistant Examiner: Gibson-Wynn; Kennedy

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/806,631, filed Mar. 2, 2020, the disclosure of which is expressly incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) Embodiments of the present disclosure relate to systems and methods for interconnecting network devices. More particularly, embodiments of the present disclosure relate to enabling users to order items online and deliver the items, by interconnecting network devices based on queuing and servicing responses.

BACKGROUND

(2) Users (e.g., online customers, online merchants, delivery personnel) often use online website portals or mobile applications to order items (e.g. order food, grocery). By way of example, users maintain profiles that includes user information (e.g. location information, menu, name) at the online websites. An online ordering process requires multiple stages of online order processing, from when an order is placed to when the order is delivered.

(3) In a situation where a user places an online order requesting food to be delivered, a first stage (of multiple stages) may be for a merchant (e.g. a restaurant) to confirm the order or reject the order based on their availability to process the order. Upon receiving a confirmation of the order from the merchant, a request is sent to a delivery personnel to confirm or reject a pickup of order from the merchant based on their availability, as part of a second stage. Similarly, through the various stages of processing of the online order there are various requests pushed and received across a network that results in utilization of numerous network resources. As these requests are pushed and received there are network delays between the responses that effect the network performance and thus negatively impacting user experience, which leads to inconvenience to the users.

(4) Current solutions for managing online orders are generally ineffective in reducing and managing delays from the time an order is placed to the time the order is received by the user. In the current marketplace, processing of online orders is performed by various network devices across multiple networks, however there is no systematic method available that would reduce time delays between processing of orders across multiple network devices. Accordingly, current solutions for managing online order processing do not have the ability to consolidate, track, or analyze time delays and thus are ineffective, inflexible, and/or inefficient, resulting in reduced network processing efficiency. Moreover, there is a need for a system that monitors and reduces time delays incurred by merchants and delivery personnel.

SUMMARY

(5) In accordance with embodiments of the present disclosure, there is provided a system for interconnecting network devices based on queuing and servicing responses, the system comprising: a memory storing instructions; and at least one processor configured to execute the instructions to: receive, from a first computer system of a plurality of first computer systems via a network, an order request for a product or service associated with a second computer system of a plurality of second computer systems; instantiate an order messaging queue associated with the order request and add an identifier of the first computer system to the order messaging queue; forward a confirmation request comprising the order request, via the network, to the second computer system; add an identifier of the second computer system to the order messaging queue; forward a second confirmation request associated with a plurality of tasks to a plurality of third systems; add an identifier of one of the third computer systems to the order messaging queue; upon receiving a

communication from one of the first, second, or third computer systems: determine the contents of the communication; based on determining contents of the communication, consult a response rule table to determine a response to the communication; determine which of the first, second or third computer systems are associated with servicing the determined response; access the order messaging queue to identify server devices corresponding with the first, second or third computer systems for servicing the determined response; and publish, to the identified server devices, the determined response for servicing.

(6) In accordance with embodiments of the present disclosure, there is also provided a computer implemented method for interconnecting network devices based on queuing and servicing responses, the method comprising: receiving, from a first computer system of a plurality of first computer systems via a network, an order request for a product or service associated with a second computer system of a plurality of second computer systems; instantiating an order messaging queue associated with the order request and add an identifier of the first computer system to the order messaging queue; forwarding a confirmation request comprising the order request, via the network, to the second computer system; adding an identifier of the second computer system to the order messaging queue; forwarding a second confirmation request associated with a plurality of tasks to a plurality of third systems; adding an identifier of one of the third computer systems to the order messaging queue; upon receiving a communication from one of the first, second, or third computer systems: determining the contents of the communication; based on determining contents of the communication, consult a response rule table to determine a response to the communication; determining which of the first, second or third computer systems are associated with servicing the determined response; accessing the order messaging queue to identify server devices corresponding with the first, second or third computer systems for servicing the determined response; and publishing, to the identified server devices, the determined response for servicing.

(7) In accordance with embodiments of the present disclosure, there is provided a system for interconnecting network devices based on queuing and servicing responses, the system comprising: a memory storing instructions; and at least one processor configured to execute the instructions to: receive, from a first computer system of a plurality of first computer systems via a network, an order request for a product or service associated with a second computer system of a plurality of second computer systems; instantiate an order messaging queue associated with the order request and add an identifier of the first computer system to the order messaging queue; forward a confirmation request comprising the order request, via the network, to the second computer system; receive a response to the confirmation request from second computer system; add an identifier of the second computer system to the order messaging queue; forward a second confirmation request associated with a plurality of tasks to a plurality of third systems; receive a response to the second confirmation request from one of the third computer system; add an identifier of the one of the third computer systems to the order messaging queue; upon receiving a communication from one of the first, second, or third computer systems: determine the contents of the communication; based on determining contents of the communication, consult a response rule table to determine a response to the communication; determine which of the first, second or third computer systems are associated with servicing the determined response; access the order messaging queue to identify server devices corresponding with the first, second or third computer systems for servicing the determined response; and publish, to the identified server devices, the determined response for servicing.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The accompanying drawings, which are incorporated in and constitute a part of his

specification, illustrate disclosed embodiments and, together with the description, serve to explain the disclosed embodiments. In the drawings:

- (2) FIG. 1 is a block diagram of an exemplary system, consistent with disclosed embodiments;
- (3) FIG. 2A is a block diagram of an exemplary interconnection service device, consistent with disclosed embodiments;
- (4) FIG. 2B is a block diagram of an exemplary server device, consistent with disclosed embodiments;
- (5) FIG. 3 is a block diagram of an exemplary user device, consistent with disclosed embodiments; and
- (6) FIGS. 4A-4E contains a detailed flowchart of an exemplary process of interconnecting network devices based on queuing and servicing responses, consistent with disclosed embodiments.

DETAILED DESCRIPTION

(7) Reference will now be made in detail to the disclosed embodiments, examples of which are illustrated in the accompanying drawings. Wherever convenient, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

(8) While the following description is directed to receiving and propagating efficient search updates in real time, these embodiments are made by example only. It should be appreciated that the present disclosure is not limited to the specific disclosed embodiments and details, which are exemplary only. It is further understood that one possessing ordinary skill in the art, in light of known systems and methods, would appreciate the use of the embodiments of the present disclosure for their intended purposes and benefits in any number of alternative embodiments, depending on specific design and other needs.

(9) FIG. 1 is a block diagram of an exemplary system **100**, for performing one or more operations consistent with disclosed embodiments. In some embodiments, system **100** includes one or more customer devices **102(1)**, . . . **102(n)** located at corresponding customer location **104(1)**, . . . **104(n)** respectively, one or more item delivery provider devices **106(1)**, . . . **106(n)** located in corresponding delivery transportations **108(1)**, . . . **108(n)** respectively, one or more item service provider devices **110(1)**, . . . **110(n)** located at corresponding merchant stores **112(1)**, . . . **112(n)**. Further, system **100** includes server devices **122(1)**, **122(2)**, . . . **122(n)**, an interconnection service device **116**, a remote database **120** and a communication network **114**. The system **100** may also include a plurality of interconnection service devices **116** (not shown in drawings) and a plurality of remote databases **120** (not shown in drawings) communicating with each other directly and further communicating with the customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, item service provider devices **110(1)-110(n)**, server devices **122(1)**, **122(2)**, . . . **122(n)**, via the communication network **114**. The components and arrangement of the components included in system **100** may vary. Thus, system **100** may include other components that perform or assist in the performance of one or more operations consistent with the disclosed embodiments.

(10) As more fully described below, customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, item service provider devices **110(1)-110(n)**, interconnection service device **116**, server devices **122(1)**, **122(2)**, . . . **122(n)**, and remote database **120** may include one or more computing devices (e.g., computer(s), server(s), etc.), memory storing data and/or software instructions (e.g., database(s), memory devices, etc.), and other known computing components. In some embodiments, the one or more computing devices may be configured to execute software instructions stored in the memory to perform one or more operations consistent with the disclosed embodiments. Aspects of customer device(s) **102(1)-102(n)**, item delivery provider device(s) **106(1)-106(n)**, item service provider devices **110(1)-110(n)**, server devices **122(1)**, **122(2)**, . . . **122(n)**, interconnection service device **116** and remote database **120** may be configured to communicate with one or more other components of system **100** via communication network **114**, for example. In certain aspects, customers associated with the customer location **104(1)-104(n)** are respectively associated with and operate customer devices **102(1)-102(n)**, drivers associated with

the delivery transportations **108(1)-108(n)** are respectively associated with and operate item delivery provider devices **106(1)-106(n)**, merchants associated with the merchant stores **112(1)-112(n)** are respectively associated with and operate item service provider devices **110(1)-110(n)**, to interact with one or more components of system **100** by sending and receiving communications, initiating operations, and/or providing input for one or more operations consistent with the disclosed embodiments.

(11) Interconnection service device **116** may be associated with an online ordering entity that receives, processes, manages, or otherwise offers ordering services for items. For example, the items that may be ordered via the online ordering entity may include prepared food, groceries, furniture, books, computers, and/or clothes, although any other type of items may also be ordered. For example, the interconnection service device **116** may receive order requests from customers using customer devices **102(1)-102(n)** and process the received order request by transmitting the request to item service provider devices **110(1)-110(n)** associated with merchant stores **112(1)-112(n)** that would provide the ordered item. Interconnection service device **116** receives an order confirmation communication from item service provider devices **110(1)-110(n)**. Upon receiving the order confirmation from the item service provider devices **110(1)-110(n)**, interconnection service device **116** transmits a request to item delivery provider devices **106(1)-106(n)** via server devices **122(1), 122(2), . . . 122(n)**, to collect the order from the merchant stores **112(1)-112(n)** and deliver the order to customer location **104(1)-104(n)**. Item delivery provider devices **106(1)-106(n)** accepts the requests and collects the requested item and delivers it to the customer location **104(1)-104(n)**.

(12) Remote database **120** of system **100** may be communicatively coupled to integration service system **116** directly or via communication network **114**. Further, the remote database **120** of system **100** may be communicatively coupled to customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)** and item service provider devices **110(1)-110(n)**, server devices **122(1), 122(2), . . . 122(n)**, via the communication network **114**. Remote database **120** may include one or more memory devices that store information and are accessed and/or managed by one or more components of system **100**. By way of example, remote database **120** may include Rabbit MQ, Oracle™ databases, Sybase™ databases, or other relational databases or nonrelational databases, such as Hadoop sequence files, HBase, or Cassandra. Remote database **120** may include computing components (e.g., database management system, database server, etc.) configured to receive and process requests for data stored in memory devices of remote database **120** and to provide data from remote database **120**.

(13) Remote database **120** is configured to store, among another things, merchant profile information for merchants associated with the item service provider devices **110(1)-110(n)** located at the merchant stores **112(1)-112(n)**, customer profile information for customers associated with the customer devices **102(1)-102(n)** located at the customer locations **104(1)-104(n)** and driver profile information for the drivers associated with the item delivery provider devices **106(1)-106(n)**. Remote database **120**, in some embodiments, stores data entries that include, for example, merchant profile information, customer profile information, and driver profile information.

(14) The merchant stores **112(1)-112(n)** may include a restaurant, coffee shop, bookstore, clothing stores, although any other type of stores can also be included. Further, merchant profile information includes merchant store name, store menu, list of items offered by the merchant, pictures of food, pictures of merchant store, categories of items, categories of food, merchants address, merchant store hours, and/or merchants phone number, although any other type of information associated with the merchant can also be included. The customer location **104(1)-104(n)** may include a residential location, an office building, an apartment, although any other type of residence can also be included. Further, customer profile information in remote database **120** may include customer name, customers home address, pictures of customer, and/or customer phone number, although any

other type of information associated with the merchant can also be included. The delivery transportation **108(1)-108(n)** may include a car, bike, truck, bus, although any other type of delivery transportation can also be included. Further, driver profile information includes drivers name, drivers home address, pictures of driver, and/or drivers phone number, make and model of a delivery transportation the driver drives, although any other type of information associated with the driver can also be included.

(15) In one aspect, interconnection service device **116** may include one or more computing devices, configured to perform one or more operations consistent with disclosed embodiments as described more fully below in relation to FIGS. **4A-4E**. In one aspect, interconnection service device **116** may include one or more servers or server systems. Interconnection service device **116** may include one or more processors configured to execute software instructions stored in a memory or other storage device. The one or more processors may be configured to execute the stored software instructions to perform internet-related communication, online order-based processes, and receiving and propagating efficient search updates in real time. The one or more computing devices of interconnection service device **116** may be configured to modify and store customer profile information, merchant profile information and/or driver profile information. The one or more computing devices of interconnection service device **116** may also be configured to communicate with other components of system **100** to receive and propagate efficient search updates in real time. In some embodiments, interconnection service device **116** may provide one or more mobile applications, web-sites or online portals that are accessible by customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, item service provider device **110(1)-110(n)**, server devices **122(1), 122(2), . . . 122(n)**, over communication network **114**. The disclosed embodiments are not limited to any particular configuration of interconnection service device **116**.

(16) Server devices **122(1), 122(2), . . . 122(n)**, may be associated with servicing online ordering requests. Servicing online ordering requests may include receives, processes, manages, or otherwise offers ordering services for products or services. For example, the products or services that may be ordered via the online ordering entity may include, prepared food, groceries, furniture, books, computers, and/or clothes, although any other type of items may also be ordered. For example, the server devices **122(1), 122(2), . . . 122(n)**, may receive order requests from customers using customer devices **102(1)-102(n)** and process the received order request by transmitting responses to item service provider devices **110(1)-110(n)** associated with merchant stores **112(1)-112(n)** that would provide the ordered item. In another example, the server devices **122(1), 122(2), . . . 122(n)**, receive from item delivery provider devices **106(1)-106(n)** associated with delivery transportation **108(1)-108(n)** and transmit responses for order requests to customers using customer devices **102(1)-102(n)**. In another example, the server devices **122(1), 122(2), . . . 122(n)**, receive from item service provider devices **110(1)-110(n)** associated with merchant stores **112(1)-112(n)** and transmit responses for order requests to customers using customer devices **102(1)-102(n)**.

(17) Communication network **114** may comprise any type of computer networking arrangement configured to provide communications or exchange data, or both, between components of system **100**. For example, communication network **114** may include any type of network (including infrastructure) that provides communications, exchanges information, and/or facilitates the exchange of information, such as the Internet, a private data network, a virtual private network using a public network, a LAN or WAN network, a Wi-Fi™ network, and/or other suitable connections that may enable information exchange among various components of system **100**. Communication network **114** may also include a public switched telephone network (“PSTN”) and/or a wireless cellular network. Communication network **114** may be a secured network or unsecured network. In some embodiments, one or more components of system **100** may communicate directly through a dedicated communication link(s).

(18) Customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, item service

provider devices **110(1)-110(n)**, server devices **122(1), 122(2), . . . 122(n)**, may be one or more computing devices configured to perform one or more operations consistent with the disclosed embodiments, as described more fully below in relation to FIGS. 2A, 2B and 3. Customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, item service provider devices **110(1)-110(n)** may execute browser or related mobile display software that displays an online portal for placing online orders for delivery of items, receiving orders and delivering items that are ordered, on a display included in, or connected to, customer devices **102(1)-102(n)**. Customer devices **102(1)-102(n)** may also store and execute other mobile applications that allow customers, merchants, and/or drivers to interact with an online portal provided by the interconnection service device **116**.

(19) It is to be understood that the configuration of the functional blocks of system **100** has been defined herein for convenience of description. The components and arrangement of the components included in system **100** may vary. For example, in some embodiments, system **100** may include other components that perform or assist in the performance of one or more processes consistent with disclosed methods. System **100** includes a number of components generally described as computing devices. Each of the computing devices may include any number of computing components particularly configured as a special purpose computing device to perform the functionality disclosed herein. Alternatives (including equivalents, extensions, variations, deviations, etc., of those described herein) will be apparent to persons skilled in the relevant art(s) based on the teachings contained herein. Such alternatives fall within the scope and spirit of the disclosed embodiments.

(20) FIG. 2A shows an exemplary interconnection service device **116** consistent with the disclosed embodiments. Variations of exemplary interconnection service device **116** may constitute one or more components of interconnection service device **116**. In one embodiment, interconnection service device **116** includes one or more memories **202**, one or more I/O devices **206**, and one or more processors **208**. In some embodiments, interconnection service device **116** may be a part of interconnection service device **116**. In some embodiments, interconnection service device **116** may take the form of a specially programmed server or computing system used by interconnection service device **116** to perform complete functions of interconnection service device **116**. In some embodiments, interconnection service device **116** may be configured as an apparatus, embedded system, dedicated circuit, or the like based on the storage, execution, and/or implementation of software instructions that perform one or more operations consistent with the disclosed embodiments.

(21) Memory **202** may include one or more storage devices configured to store instructions used by processor **208** to perform functions related to disclosed embodiments. For example, memory **202** may be configured with one or more software instructions, such as program(s) **204** that may perform one or more operations when executed by processor **208**. The disclosed embodiments are not limited to separate programs or computers configured to perform dedicated tasks. For example, memory **202** may include a single program **204** that performs the functions of server device **200**, or program **204** may comprise multiple programs. In certain embodiments, memory **202** may store sets of instructions or programs **204** for performing functions of interconnection service device **116**. These sets of instructions may be executed by processor **208** to perform communication and/or processes consistent with disclosed embodiments.

(22) In certain embodiments, when interconnection service device **116** constitutes one or more of the components of interconnection service device **116**, memory **202** includes programs **204**, the programs **204** include applications **210**. By way of example, the applications **210** may include a decision rules table or a classification lookup table, as described in detail below. In other embodiments, each of a decision rules table and classification lookup table may be implemented as separate servers. In another embodiment, each of decision rules table and classification lookup table may be hosted on the remote database **120**.

(23) Input/output (I/O) **206** may include various input/output devices, such as a keyboard, a mouse-type device, a gesture sensor, an action sensor, a physical button, switch, microphone, touchscreen panel, stylus, etc., that may be manipulated by customer devices **102(1)-102(n)**, item delivery provider device **106(1)** and/or item service provider device **110(1)-110(n)**. I/O devices **206** may also include an audio output device. Exemplary communication modules of I/O devices **206** may include, for example, a short-range or near field wireless communication modem, a Wi-Fi™ communication modem, or a cellular communication modem. I/O devices **206** may include a transceiver or transmitter configured to communicate using one or more wireless technologies/protocols that may include, without limitation, cellular (e.g., 3G, 4G, etc.) technology, Wi-Fi™ hotspot technology, RFID, near-field communication (NFC) or BLUETOOTH® technologies, etc. More generally, any uni- or bi-directional communication technology known to one of ordinary skill in the art may be implemented in interconnection service device **116** to exchange information with customer devices **102(1)-102(n)**, item delivery provider device **106(1)**, item service provider device **110(1)-110(n)**, server devices **122(1), 122(2), . . . 122(n)**, or remote database **120** via communication network **114**.

(24) Processor **208** may include one or more known processing devices, such as a microprocessor from the Pentium™ or Xeon™ family manufactured by Intel™, or the Turion™ family manufactured by AMD™, for example. The disclosed embodiments are not limited to any type of processor(s) otherwise configured to meet the computing demands required of different components of system **100**.

(25) FIG. 2B shows an exemplary server device **122(1)** consistent with the disclosed embodiments. Configuration of server devices **122(2) . . . 122(n)** are similar to server device **122(1)**. Variations of exemplary server device **122(1)** may constitute one or more components of interconnection service device **116**. In one embodiment, server device **122(1)** includes one or more memories **216**, one or more I/O devices **220**, and one or more processors **222**. In some embodiments, server device **122(1)** may be a part of interconnection service device **116**. In some embodiments, server device **122(1)** may take the form of a specially programmed server or computing system used by server device **122(1)** to perform complete functions of server device **122(1)**. In some embodiments, server device **122(1)** may be configured as an apparatus, embedded system, dedicated circuit, or the like based on the storage, execution, and/or implementation of software instructions that perform one or more operations consistent with the disclosed embodiments.

(26) Memory **216** may include one or more storage devices configured to store instructions used by processor **222** to perform functions related to disclosed embodiments. For example, memory **216** may be configured with one or more software instructions, such as program(s) **218** that may perform one or more operations when executed by processor **222**. The disclosed embodiments are not limited to separate programs or computers configured to perform dedicated tasks. For example, memory **216** may include a single program **218** that performs the functions of server device **122(1)**, or program **218** may comprise multiple programs. In certain embodiments, memory **216** may store sets of instructions or programs **218** for performing functions of server device **122(1)**. These sets of instructions may be executed by processor **208** to perform communication and/or processes consistent with disclosed embodiments.

(27) In certain embodiments, when server device **122(1)** constitutes one or more of the components of interconnection service device **116**, application **210** includes a decision rules table and classification lookup table, as described in detail below.

(28) Input/output (I/O) **220** may include various input/output devices, such as a keyboard, a mouse-type device, a gesture sensor, an action sensor, a physical button, switch, microphone, touchscreen panel, stylus, etc., that may be manipulated by customer devices **102(1)-102(n)**, item delivery provider device **106(1)** and/or item service provider device **110(1)-110(n)**. I/O devices **220** may also include an audio output device. Exemplary communication modules of I/O devices **220** may include, for example, a short-range or near field wireless communication modem, a Wi-Fi™

communication modem, or a cellular communication modem. I/O devices **220** may include a transceiver or transmitter configured to communicate using one or more wireless technologies/protocols that may include, without limitation, cellular (e.g., 3G, 4G, etc.) technology, Wi-Fi™ hotspot technology, RFID, near-field communication (NFC) or BLUETOOTH® technologies, etc. More generally, any uni- or bi-directional communication technology known to one of ordinary skill in the art may be implemented in server device **122(1)** to exchange information with interconnection service device **116**, customer devices **102(1)-102(n)** item delivery provider device **106(1)**, item service provider device **110(1)-110(n)**, server devices **112(2)-112(n)**, or remote database **120** via communication network **114**.

(29) Processor **218** may include one or more known processing devices, such as a microprocessor from the Pentium™ or Xeon™ family manufactured by Intel™, or the Turion™ family manufactured by AMD™, for example. The disclosed embodiments are not limited to any type of processor(s) otherwise configured to meet the computing demands required of different components of system **100**.

(30) FIG. **3** shows an exemplary configuration of user device **300**, consistent with disclosed embodiments. User device **300** of FIG. **3** represents an exemplary configuration of each of the customer devices **102(1)-102(n)**, the item delivery provider devices **106(1)-106(n)** and item service provider devices **110(1)-110(n)**.

(31) User device **300** may enable associated customers, drivers and merchants associated with customer devices **102(1)-102(n)**, the item delivery provider devices **106(1)-106(n)** and item service provider devices **110(1)-110(n)**, respectively to, for example, perform remote interactions or mobile transactions with interconnection service device **116**, or receive information from interconnection service device **116**. In some embodiments, user device **300** may be a personal computing device. For example, user device **300** may be a smartphone, a laptop or notebook computer, a tablet, a multifunctional watch, a pair of multifunctional glasses, or any mobile or wearable device with computing ability, or any combination of these computers and/or affiliated components.

(32) User device **300** includes one or more processors **308** configured to execute software instructions stored in memory, such as a memory **312**. Memory **312** may store one or more software programs **314** that when executed by processor **308** perform known Internet-related communication, content display processes, and other interactive processes for customers, drivers and/or merchants. For instance, user device **300** may execute a browser or related mobile display software that generates and displays interfaces including content on a display device **302** included in, or in communication with, user device **300**. User device **300** may be a mobile device that executes mobile device applications and/or mobile device communication software, included in programs **314**, that allows user device **300** to communicate with interconnection service device **116** and other components via communication network **114**, to generate and display content in interfaces via display device **302**. The disclosed embodiments are not limited to any particular configuration of user device **300**. User device **300** may include any arrangement of one or more computing devices configured to perform one or more operations consistent with disclosed embodiments.

(33) User device **300** may be configured to store, in memory **312**, one or more operating systems that perform known operating system functions when executed by processor **308**. By way of example, the operating systems may include Microsoft Windows™, Unix™, Linux™, Android™, Apple™ Mac OS operating systems, iOS, Chrome OS, or other types of operating systems. Accordingly, disclosed embodiments may operate and function with computer systems running any type of operating system. User device **300** may also include communication software stored in memory **312** that, when executed by processor **308**, provides communications with communication network **114**, such as Web browser software, tablet or smart handheld device networking software, etc.

(34) Display device **302** may include, for example, a liquid crystal displays (LCD), a light emitting

diode screens (LED), an organic light emitting diode screen (OLED), a touch screen, and other known display devices. Display device **302** may display various information to customers, drivers and merchants. For example, display device **302** may display an interactive interface enabling customers, drivers and merchants to operate user device **300** to perform certain aspects of the disclosed methods. Display device **302** may display touchable or selectable options for customers, drivers and merchants to select and may receive customer selection of options through a touch screen.

(35) User device **300** includes I/O devices **304** that allows to send and receive information or interact with customers, drivers and merchants or another device. For example, I/O devices **304** may include various input/output devices, such as a keyboard, a mouse-type device, a gesture sensor, an action sensor, a physical button, switch, microphone, touchscreen panel, stylus, etc., that may be manipulated by customers, drivers and merchants to input information using user device **300**. I/O devices **304** may also include an audio output device, such as a speaker configured to provide sound and audio feedback to customers, drivers and merchants operating user device **300**. In some embodiments, I/O devices **304** may include a light emitting component, such as a LED or other component capable of providing a visible signal to customers, drivers and merchants. I/O devices **304** may also include haptic output devices, to provide haptic feedback to customers, drivers and merchants. I/O devices **304** may also include one or more communication modules (not shown) for sending and receiving information from other components in system **100** by, for example, establishing wired or wireless connectivity between user device **300** and communication network **114**. I/O devices **304** may include radio frequency, infrared, or other near-field communication interfaces, for communicating with other devices associated with communication network **114**. Exemplary communication modules of I/O devices **304** may include, for example, a short-range or near field wireless communication modem, a Wi-Fi™ communication modem, or a cellular communication modem. I/O devices **304** may include a transceiver or transmitter configured to communicate using one or more wireless technologies/protocols that may include, without limitation, cellular (e.g., 3G, 4G, etc.) technology, Wi-Fi™ hotspot technology, RFID, near-field communication (NFC) or BLUETOOTH® technologies, etc. More generally, any uni- or bi-directional communication technology known to one of ordinary skill in the art may be implemented in user device **300** to exchange information with interconnection service device **116** or remote database **120** via communication network **114**.

(36) As described above, user device **300** may be a device that executes mobile applications for performing operations consistent with disclosed embodiments. Thus, in some embodiments, programs **314** stored on user device **300** may include one or more software applications **316** installed thereon, that enable user device **300** to communicate with interconnection service device **116** via communication network **114** and perform aspects of the disclosed methods. For example, user device **300** may connect to interconnection service device **116** by using browser software to access and receive information or perform other operations associated with an internet service provider.

(37) According to an exemplary embodiment, software applications **316** associated with interconnection service device **116** may be installed on user device **300**, as shown in FIG. 3. For example, interconnection service device **116** may receive a request from customer device **102(1)** to download one or more software applications **316** to user customer device **102(1)**. In one embodiment, interconnection service device **116** may receive the request from a customer associated with customer device **102(1)**, using a web browser application installed on customer device **102(1)** respectively. In another embodiment, interconnection service device **116** may receive the request to download one or more software applications **316** associated with interconnection service device **116** onto customer device **102(1)** from a webpage or another portal associated with interconnection service device **116** accessed via, e.g., customer device **102(1)**. In this embodiment, interconnection service device **116** may store software instructions corresponding to one or more

software applications **316** in remote database **120**. For responding to the download request, interconnection service device **116** may receive additional information from customer device **102(1)** regarding the particular device specifications of customer device **102(1)** to enable customer device **102(1)** to download software instructions corresponding to the particular specifications. Alternatively, interconnection service device **116** may push a download request link to customer device **102(1)** or transmit software code corresponding to one or more software applications **316** directly to customer device **102(1)** in, for example, an e-mail, a text or short message service (SMS) message, a prompt through an app, or other suitable method. Customer device **102(1)** may receive the software code related to one or more software applications **316**, such as via communication network **114**, to download and install the software code. Similarly, in another example, interconnection service device **116** may receive a request from a driver associated with item delivery provider device **106(1)** to download one or more software applications **316** onto the item delivery provider device **106(1)**. Further, similarly, in another example, interconnection service device **116** may receive a request from a merchant associated with item service provider device **110(1)** to download one or more software applications **316** onto the item service provider device **110(1)**.

(38) FIGS. **4A-4E** contain a flowchart of an exemplary process **400** implemented by interconnection service device **116** for interconnecting network devices based on queuing and servicing responses, consistent with the disclosed embodiments. Interconnection service device **116** is implemented to execute software instructions that perform one or more of the operations of process **400**. Operations of process **400** are explained in association with FIGS. **4A-4E**.

(39) In accordance with process **400**, in step **402**, interconnection service device **116** receives an order request for a product or service associated with a second computer system upon payment approval from first computer system. The first computer system may be customer devices **102(1)-102(n)** and the second computer system may be item service provider devices **110(1)-110(n)**. By way of example, with reference to FIG. **4A**, a customer associated with the customer device **102(1)** initiates application **316** to access an online ordering portal to order food from merchant stores **112(1)-112(n)**. In this example, the customer makes his/her selection of food using the online ordering portal and then makes a payment for the selected food. Upon successful authorization of the payment, a request to order food from merchant store **112(1)** is generated and transmitted to interconnection service device **116**. Interconnection service device **116** upon receiving the order request, determines that the request from the customer device **102(1)** is requesting the food from merchant store **112(1)**, and determines that the order request is to be transmitted to the item service provider device **110(1)** associated with merchant store **112(1)**. The order request may include, name of the customer, name of the restaurant or merchant stores **112(1)-112(n)**, names of food dishes requested, price of the food dishes and time the order was placed.

(40) In another example, interconnection service device **116** may receive the order request from customer device **102(1)** via server device **122(1)**. In this scenario, customer device **102(1)** may transmit the order request to server device **122(1)** and server device **122(1)** may transmit the order request to interconnection service device **116**.

(41) In step **404**, interconnection service device **116** instantiates an order messaging queue associated with the order request. Upon receiving the order request from the customer device **102(1)**, interconnection service device **116** accesses an order messaging queue storage at remote database **120** and creates an order messaging queue. Upon creating the order messaging queue, interconnection service device **116** adds an identifier associated with customer device **102(1)** in the order messaging queue.

(42) By way of example, in this embodiment, the interconnection service device **116** may communicate with remote database **120** by utilizing Streaming Text Oriented Messaging Protocol (STOMP), although any other type of communication protocol may also be utilized. In other

embodiments, interconnection service device **116** may create and store an order messaging queue locally in memory **202** of the interconnection service device **116**.

(43) The order messaging queue is a data queue utilized to add identifiers associated with network devices that participate in processing of online order request. In this example, the network devices include customer devices **102(1)-102(n)**, item service provider devices **110(1)-110(n)**, and/or item delivery provider devices **106(1)-106(n)**, and may be added into the order messaging queue, as explained in detail below. Further, order messaging queue stores a lookup table that includes each of the server devices **122(1)-122(n)** associated with the at least one of an identifier corresponding to the customer devices **102(1)-102(n)**, item service provider devices **110(1)-110(n)**, and/or item delivery provider devices **106(1)-106(n)**. Lookup table provides for each of the customer devices **102(1)-102(n)**, item service provider devices **110(1)-110(n)**, and/or item delivery provider devices **106(1)-106(n)** a corresponding one or more server devices **122(1)-122(n)** that would service order requests corresponding to the customer devices **102(1)-102(n)**, item service provider devices **110(1)-110(n)**, and/or item delivery provider devices **106(1)-106(n)**. Interconnection service device **116** may access the order messaging queue to determine the identifier stored in the order messaging queue, and then access the lookup table to identify which one of the server devices **122(1)-122(n)** are assigned to that identifier to service the device corresponding to that identifier.

(44) The lookup table may be previously stored on remote database **120** by a system administrator. In other embodiments, the lookup table may be automatically created by interconnection service device **116**, upon receiving an order request. Interconnection service device **116**, may create the lookup table based on network traffic load associated with each of server devices **122(1)-122(n)**, in order to balance the network traffic load. In another embodiment, the lookup table may be updated periodically by interconnection service device **116** to provide network traffic load balancing. This update may be performed periodically at regular time intervals. Time intervals may include 1 second, 30 second, 1 minute or 1 hour, although any other time period may also be included.

(45) In step **406**, interconnection service device **116** forwards a confirmation request comprising the order request to the second computer system. In this example, interconnection service device **116** forwards or transmits a confirmation request to the item service provider device **110(1)**, requesting the item service provider device **110(1)** to either accept or deny preparing of the requested items in the order request.

(46) In step **408**, interconnection service device **116** receives a confirmation request response from the second computer system. In this example, interconnection service device **116** receives a response to the confirmation request from the item service provider device **110(1)**.

(47) In step **410**, interconnection service device **116**, determines if the response received from item service provider device **110(1)** includes a “Merchant Accept” message identifier. If the received response does not include a “Merchant Accept” message identifier, then the interconnection service device **116** determines that the item service provider device **110(1)** has declined to prepare the requested items in the order request. The method takes the No branch and moves to step **412**.

(48) In step **412**, the interconnection service device **116** transmits a cancel order notification to the customer device **102(1)** and further issues a refund for the amount of payment made for the order request and the method ends here.

(49) Back in step **408**, if the received response includes a “Merchant Accept” message identifier, then the interconnection service device **116** determines that the item service provider device **110(1)** has accepted to prepare the requested items in the order request, and the method takes the Yes branch and the method flow moves to step **416**.

(50) In step **416**, interconnection service device **116**, adds an identifier associated with second computer system to the order messaging queue. In this example, interconnection service device **116** determines an identifier of the item service provider device **110(1)** from the response received in step **408**. The received response may include an internet protocol packet that includes an identifier. An identifier may include username associated with the merchant corresponding to the item service

provider device **110(1)**, internet protocol (IP) address of the item service provider device **110(1)**, Media access control (MAC) address of the item service provider device **110(1)**, International Mobile Equipment Identity (IMEI) item service provider **110(1)**, although any other type of identifier associated with a network device may also be included. The interconnection service device **116** determines the identifier and adds it into the order messaging queue and the method moves to step **418**.

(51) In step **418**, interconnection service device **116** forwards a second confirmation request associated with a plurality of tasks to a plurality of third computer systems. In this example, the plurality of third computer systems may be item delivery provider devices **106(1)-106(n)**. The interconnection service device **116** forwards or transmits the second confirmation request to the item delivery provider devices **106(1)-106(n)**, requesting the item delivery provider devices **106(1)-106(n)** to either accept or deny pickup of the requested item from the merchant stores **112(1)-112(n)** and delivery the requested item to customer devices **102(1)-102(n)** at customer locations **104(1)-104(n)**.

(52) In step **420**, interconnection service device **116** receives a response from one of the plurality of item delivery provider devices **106(1)-106(n)**.

(53) In step **422** (FIG. **4B**), interconnection service device **116** determines if the response received from one of the pluralities of item delivery provider devices **106(1)-106(n)** includes a “Delivery Accept” message identifier. If the received response does not include a “Delivery Accept” message identifier, then the interconnection service device **116** determines that the one of the plurality of item delivery provider devices **106(1)-106(n)** has declined to pick up and deliver the requested items in the order request. The method takes the No branch and moves to step **426**.

(54) In step **424**, the interconnection service device **116** determines if a response to the second confirmation request is received from another one of the plurality of item delivery provider devices **106(1)-106(n)**. If the interconnection service device **116** determines that no response is received to the second confirmation request from another one of the pluralities of item delivery provider devices **106(1)-106(n)**, then the method proceeds to step **426**.

(55) In step **426**, the interconnection service device **116**, transmits a cancel order notification to the customer device **102(1)** and further issues a refund for the amount of payment made for the order request and the method ends here.

(56) Back in step **424**, if the interconnection service device **116** determines that a response is received to the second confirmation request from another one of the pluralities of item delivery provider devices **106(1)-106(n)**, then the method loops back to step **422**.

(57) Back in step **422**, if the received response includes a “Delivery Accept” message identifier, then the interconnection service device **116** that the one of the plurality of item delivery provider devices **106(1)-106(n)** has accepted to pick up and deliver the requested items in the order request. The method takes the Yes branch and moves to step **428**.

(58) In step **428**, interconnection service device **116**, instantiates a first task associated with preparation of product or service and generates a food task interface. Interconnection service device **116** establishes a first connection link with the second computer system over a network protocol and instantiates a first task. For example, interconnection service device **116** establishes a first open transmission control protocol (TCP) connection link with the second computer system over a WebSocket protocol and instantiates a first task, although any other type of network protocol may also be used. The second computer system in this example is item service provider device **110(1)** as explained above in step **410**. Upon instantiating the first task, the first task causes the interconnection service device **116** to monitor communications received from item service provider device **110(1)** over the first open TCP connection link, and based on the updates of the status of the order request, interconnection service device **116** updates the food task interface to display a real time status of the order request. Food task interface may be displayed on customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and/or item service provider devices

110(1)-110(n), associated with the order request.

(59) In step **430**, interconnection service device **116**, instantiates a second task associated with delivery of product or service and generates a delivery task interface, interconnection service device **116**, upon determining that one of the plurality of item delivery provider devices **106(1)-106(n)** has accepted to pickup and delivery the requested items in the order request, the interconnection service device **116** establishes a second connection link with the one of the plurality of item delivery provider devices **106(1)-106(n)** over a network protocol and instantiates a second task. For example, interconnection service device **116** establishes a second open transmission control protocol (TCP) connection link with the one of the plurality of item delivery provider devices **106(1)-106(n)** over a WebSocket protocol and instantiates a second task, although any other type of network protocol may also be used. Upon instantiating the second task, the second task causes the interconnection service device **116** to monitor communications received from one of the plurality of item delivery provider devices **106(1)-106(n)** over the second open TCP connection link, and based on the updates of the status of the order request, interconnection service device **116** updates the delivery task interface to display a real time status of the order request. Food task interface may be displayed on customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and/or item service provider devices **110(1)-110(n)**, associated with the order request.

(60) In step **432**, interconnection service device **116**, adds an identifier associated with one of the third computer systems to the order messaging queue. In this example, interconnection service device **116** determines an identifier of the item delivery provider device **106(1)** from the response received in step **422** or step **424**. The received response may include an Internet Protocol packet that includes an identifier. An identifier may include username associated with the merchant corresponding to the item delivery provider device **106(1)**, internet protocol (IP) address of the item delivery provider device **106(1)**, Media access control (MAC) address of the item delivery provider device **106(1)**, International Mobile Equipment Identity (IMEI) associated with item delivery provider device **106(1)**, although any other type of identifier associated with a network device may also be included. The interconnection service device **116** determines the identifier and adds it into the order messaging queue and the method moves to step **434**.

(61) In step **434**, interconnection service device **116**, receive a communication from one of the first, second, or third computer systems. Received communication may include messages from item services provider devices **110(1)-110(n)**, messages from item delivery provider devices **106(1)-106(n)**, messages from customer devices **102(1)-102(n)**, or messages from any other network devices may also be included.

(62) Messages from item services provider devices **110(1)-110(n)**, may include message identifiers and device identifiers. Message identifiers may include “Merchant Ready”, “Merchant Delay”, “Merchant Cancel”, or any other message identifier may also be included. Further, “Merchant Ready” identifier provides an indication to interconnection service device **116** that the item requested in the request order is ready to be picked up by a delivery personnel. “Merchant Delay” identifier provides an indication to interconnection service device **116** that the item requested in the request order has been delayed to pick up by a delivery personnel, further the message also includes a new time, when the item requested in the request order will be available to pick up. “Merchant Cancel” identifier provides an indication to interconnection service device **116** that the merchant store has canceled the request order and would not service the request order.

(63) Messages from item delivery provider devices **106(1)-106(n)**, may include message identifiers. Message identifiers may include “Pick up complete”, “Delivery complete”, “Delivery Cancel”, or any other message identifier may also be included. Further, “Pick up complete” identifier provides an indication to interconnection service device **116** that the item requested in the request order has been picked up by a delivery personnel associated with item delivery provider device **106(1)**. “Delivery complete” identifier provides an indication to interconnection service

device **116** that the item requested in the request order has been delivered by the delivery personnel, further the message also includes a time when the item requested in the request order has been delivered. “Delivery Cancel” identifier provides an indication to interconnection service device **116** that the delivery personnel associated with item delivery provider device **106(1)** has canceled the request order and would not service the request order.

(64) Messages from customer devices **102(1)-102(n)** may include message identifiers. Message identifiers may include a “Partially Cancel”, “Complete Cancel”, or any other message identifier may also be included. Further, “Partially Cancel” identifier provides an indication that, by way of example, customer device **102(1)** would request a refund of an earlier requested order. Further, message identifier “Complete Cancel” provides an indication that, by way of example, customer device **102(1)** has requested to cancel a pending order request that has not been complete serviced.

(65) The devices identifiers received in communication may include device identifiers associated with customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**. The device identifiers may include username, internet protocol (IP) address, Media access control (MAC) address, International Mobile Equipment Identity (IMEI) associated with customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, although any other type of identifier associated with a network device may also be included.

(66) In step **436**, interconnection service device **116**, classifies the received communication based on determining the type of contents received in the communication in step **434**. Interconnection service device **116** accesses a classification lookup table stored at the remote database **120** to classify the received communication into a request classified to be coming from a second computer system, or classify the received communication into a request classified to be coming from a third computer system, or classify the received communication into a request classified to be coming from a first computer system.

(67) The classification lookup table stores association between a received message identifier and associated a first computer system, second computer system or third computer system. By way of example, the lookup table associates the message identifiers of “Merchant Ready”, “Merchant Delay”, “Merchant Cancel”, to be corresponding with item service provider devices **110(1)-110(n)**. Further, the lookup table associates the message identifiers of include “Pick up complete”, “Delivery complete”, “Delivery Cancel”, to be corresponding with item delivery provider devices **106(1)-106(n)**. Additionally, the lookup table associates the message identifiers of include “Partially Cancel”, “Complete Cancel”, to be corresponding with customer devices **102(1)-102(n)**. Accordingly, interconnection service device **116**, classifies the received communication to coming from either item service provider devices **110(1)-110(n)**, item delivery provider devices **106(n)**, or customer devices **102(1)-102(n)**.

(68) When in step **436** (FIG. **4B**), interconnection service device **116**, determines that the received communication is from one of the item service provider devices **110(1)-110(n)**, then the interconnection service device **116**, proceeds to step **438** to follow step **440** (FIG. **4C**).

(69) In step **440**, interconnection service device **116**, determines if the received message identifier in the received communication is “Merchant Ready”. If interconnection service device **116** determines that the received communication includes a “Merchant ready” identifier, then the method proceeds to take the yes branch to step **442**.

(70) In step **442**, interconnection service device **116**, consults a decision rule table to determine a response to the received communication based on the “Merchant Ready” identifier.

(71) The decision rule table is a table stored in the remote database **120**. The decision rule table includes rules for providing a response based on the received identifier in the message. By way of example, a rule may be, for a “Merchant Ready” identifier, interconnection service device **116** is programmed to transmit a food task completed message to customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**. As food

task complete message causes to update food task interface that was generated on customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, to display a message such as “Food is ready to be picked up”.

(72) Another rule may be, for a “Merchant Delay” identifier, interconnection service device **116** is programmed to transmit a response for estimated time for food to be ready to customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**. Upon receiving this response food task interface that was generated on customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, is updated to display a new time for when the food would be ready.

(73) In this step **442**, based on consulting decision rule table, interconnection service device **116** determines a response to message identifier “Merchant Ready”, is to transmit a food task complete message to, by way of example, to customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** and the method proceeds to step **444**.

(74) In step **444**, interconnection service device **116** accesses order messaging queue to identify server devices **122(1)-122(n)** associated with, in this example, customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to transmit the response determined in step **442**. Interconnection service device **116** accesses the order messaging queue to identify identifiers associated with customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to and further identifies corresponding server devices **122(1)-122(n)** associated with servicing customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. In this example, interconnection service device **116**, identifies server device **122(1)** to be associated with servicing customer **102(1)**, server device **122(2)** to be associated with servicing item delivery provider device **106(1)**, and server device **122(3)** to be associated with servicing item service provider device **110(1)**.

(75) In step **446**, interconnection service device **116** publishes the determined response to the server devices **122(1)-122(n)** associated with servicing the response. By way of example, interconnection service device **116** publishes or transmits the determined response of transmit a food task complete message to server device **122(1)** associated with servicing customer **102(1)**, server device **122(2)** associated with servicing item delivery provider device **106(1)**, and server device **122(3)** associated with servicing item service provider device **110(1)**. Upon publishing the determined responses, the server devices **122(1)**, **122(2)**, and **122(n)** updates food task interface and delivery task interface associated with customer devices **102(1)**, item delivery provider devices **106(1)**, and item service provider devices **110(1)**, to display a message such as “Food is ready to be picked up”, respectively. The method then ends at step **448**.

(76) Back in step **440**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Merchant Ready”. Then the method proceeds to take the no branch to step **450**.

(77) In step **450**, interconnection service device **116**, determines if the received message identifier in the received communication is “Merchant Delay”. If interconnection service device **116** determines that the received communication includes a “Merchant Delay” identifier, then the method proceeds to take the yes branch to step **452**.

(78) In this step **452**, interconnection service device **116** determines a response to message identifier “Merchant Delay”, is to transmit an updated estimate time for food to be ready to, based on consulting the decision rule table. By way of example, interconnection service device **116** transmits an updated estimate time for food to be ready to customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. Further, when the customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** receive this response from corresponding server devices **122(1)-122(n)**, the received response updates food task interface at the customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to display a new time of the food would be ready and the method proceeds

to step **454**.

(79) In step **454**, interconnection service device **116** accesses order messaging queue to identify which of the server devices **122(1)-122(n)** associated with, in this example, customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to transmit the response determined in step **452**. Interconnection service device **116** accesses the order messaging queue to identify identifiers associated with customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to and further identifies corresponding server devices **122(1)-122(n)** associated with servicing customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. In this example, interconnection service device **116**, identifies server device **122(1)** to be associated with servicing customer **102(1)**, server device **122(2)** to be associated with servicing item delivery provider device **106(1)**, and server device **122(3)** to be associated with servicing item service provider device **110(1)**.

(80) In step **456**, interconnection service device **116** publishes the determined response to the server devices **122(1)-122(n)** associated with servicing the response. By way of example, interconnection service device **116** publishes or transmits the determined response to transmit updated estimate time for food to be ready to server device **122(1)** associated with servicing customer **102(1)**, server device **122(2)** associated with servicing item delivery provider device **106(1)**, and server device **122(3)** associated with servicing item service provider device **110(1)**. Upon publishing the determines responses, the server devices **122(1)**, **122(2)**, and **122(n)** updates food task interface and delivery task interface associated with customer devices **102(1)**, item delivery provider devices **106(1)**, and item service provider devices **110(1)**, to display a display a new time of the food would be ready. The method then ends at step **458**.

(81) Back in step **450**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Merchant Delay”. Then the method proceeds to take the no branch to step **458**.

(82) In step **458**, interconnection service device **116**, determines if the received message identifier in the received communication is “Merchant Cancel”. If interconnection service device **116** determines that the received communication includes a “Merchant Cancel” identifier, then the method proceeds to take the yes branch to step **460**.

(83) In step **460**, interconnection service device **116**, determines a transmit a cancel order notification to customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. Interconnection service device **116** further issues a refund for the amount of payment made for the order request and the method proceeds to end at step **448**.

(84) Back in step **458**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Merchant Cancel”, then the method takes the No branch to step **459** and transmits an error message, such as, “Invalid input” to, by way of example, item service provider device **110(1)** from which the communication was received.

(85) Back in step **436** (FIG. 4B), when interconnection service device **116**, determines that the received communication is from one of the item delivery provider devices **106(1)-106(n)**, then the interconnection service device **116**, proceeds to step **462** to follow step **464** (FIG. 4D).

(86) In step **464**, interconnection service device **116**, determines if the received message identifier in the received communication is “Pick up complete”. If interconnection service device **116** determines that the received communication includes a “Pick up complete” identifier, then the method proceeds to take the yes branch to step **466**.

(87) In step **466**, interconnection service device **116**, consults a decision rule table to determine a response to the received communication based on the “Pick up complete” identifier.

(88) Decision rule table is a table stored in the remote database **120**. The decision rule table includes rules for providing a response based on the received identifier in the message. By way of example, a rule may be, for a “Pick up complete” identifier is to transmit an updated delivery time

message to customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, Updated delivery time message causes to update delivery task interface previously generated and displayed at customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**,

(89) Another rule may be, for a “Delivery complete” identifier transmit a response for transmitting a message that the delivery has been successfully completed to customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, this response causes to update delivery task interface, that was generated on customer devices **102(1)-102(n)**, item delivery provider devices **106(1)-106(n)**, and item service provider devices **110(1)-110(n)**, to display delivery completed message.

(90) In this step **466**, based on consulting decision rule table, interconnection service device **116** determines a response to message identifier “Pick up complete”, is to transmit an updated delivery time message to, by way of example, to customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** and the method proceeds to step **468**.

(91) In step **468**, interconnection service device **116** accesses order messaging queue to identify server devices **122(1)-122(n)** associated with, in this example, customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to transmit the response determined in step **466**. Interconnection service device **116** accesses the order messaging queue to identify identifiers associated with customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to and further identifies corresponding server devices **122(1)-122(n)** associated with servicing customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. In this example, interconnection service device **116**, identifies server device **122(1)** to be associated with servicing customer **102(1)**, server device **122(2)** to be associated with servicing item delivery provider device **106(1)**, and server device **122(3)** to be associated with servicing item service provider device **110(1)**.

(92) In step **470**, interconnection service device **116** publishes the determined response to the server devices **122(1)-122(n)** associated with servicing the response. By way of example, interconnection service device **116** publishes or transmits updated delivery time message to, by way of example, to server device **122(1)** associated with servicing customer **102(1)**, server device **122(2)** associated with servicing item delivery provider device **106(1)**, and server device **122(3)** associated with servicing item service provider device **110(1)**. Upon publishing the responses, the server devices **122(1)**, **122(2)**, and **122(n)** updates delivery task interface and food task interface associated with customer devices **102(1)**, item delivery provider devices **106(1)**, and item service provider devices **110(1)**, to display a message such as “Food has been picked up”, respectively. The method then ends at step **472**.

(93) Back in step **464**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Pick up complete”. Then the method proceeds to take the no branch to step **474**.

(94) In step **474**, interconnection service device **116**, determines if the received message identifier in the received communication is “Delivery Complete”. If interconnection service device **116** determines that the received communication includes a “Merchant Complete” identifier, then the method proceeds to take the yes branch to step **476**.

(95) In this step **476**, based on consulting decision rule table, interconnection service device **116** determines a response to message identifier “Delivery complete”, is to transmit a response for transmitting a message that the delivery has been successfully completed to, by way of example, customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. Further, when the customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** receive this response, causes to update delivery task interface to display a message, such as, for example, “Item has been successfully delivered” and the method proceeds to step **478**.

(96) In step **478**, interconnection service device **116** accesses order messaging queue to identify which of the server devices **122(1)-122(n)** associated with, in this example, customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to transmit the response determined in step **452**. Interconnection service device **116** accesses the order messaging queue to identify identifiers associated with customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)** to and further identifies corresponding server devices **122(1)-122(n)** associated with servicing customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. In this example, interconnection service device **116**, identifies server device **122(1)** to be associated with servicing customer **102(1)**, server device **122(2)** to be associated with servicing item delivery provider device **106(1)**, and server device **122(3)** to be associated with servicing item service provider device **110(1)**.

(97) In step **480**, interconnection service device **116** publishes the determined response to the server devices **122(1)-122(n)** associated with servicing the response. By way of example, interconnection service device **116** publishes or transmits a response for transmitting a message that the delivery has been successfully completed to server device **122(1)** associated with servicing customer **102(1)**, server device **122(2)** associated with servicing item delivery provider device **106(1)**, and server device **122(3)** associated with servicing item service provider device **110(1)**. Server devices **122(1)**, **122(2)**, and **122(n)** updates food task interface and delivery task interface, upon publishing the determines responses, associated with customer devices **102(1)**, item delivery provider devices **106(1)**, and item service provider devices **110(1)**, to display a display, for example, “item has been successfully delivered”. The method then ends at step **472**.

(98) Back in step **474**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Delivery complete”. Then the method proceeds to take the no branch to step **484**.

(99) In step **484**, interconnection service device **116**, determines if the received message identifier in the received communication is “Delivery Cancel”. If interconnection service device **116** determines that the received communication includes a “Delivery Cancel” identifier, then the method proceeds to take the yes branch to step **484**.

(100) In step **484**, interconnection service device **116**, determines a transmit a cancel order notification to customer device **102(1)**, item delivery provider device **106(1)**, and item service provider device **110(1)**. Interconnection service device **116** further issues a refund for the amount of payment made for the order request and the method proceeds to end at step **472**.

(101) Back in step **482**, when interconnection service device **116**, determines that the received message identifier in the received communication is not “Delivery Cancel”, then the method takes the No branch to step **483** and transmits an error message, such as, “Invalid input” to, by way of example, item service provider device **110(1)** from which the communication was received and the method ends here.

(102) When in step **436** (FIG. 4B), interconnection service device **116**, determines that the received communication is from one of the customer devices **102(1)-102(n)**, then the interconnection service device **116**, proceeds to step **486** to follow step **488** (FIG. 4E).

(103) In step **488**, interconnection service device **116**, determines if the received message identifier is “Partially Cancel”, then the method takes the yes branch and proceeds to step **490**.

(104) In step **490**, interconnection service device **116**, determines if the received message is received after a pre-defined time period after completion of the order. Pre-defined time period may include 30 days after the item was successfully delivered. When interconnection service device **116**, determines that the received message is received after 30 days of completion of the order, then the method proceeds to step **492**.

(105) In step **492**, interconnection service device **116**, issues a partial refund to customer device **102(1)** associated with the order request.

(106) When back in step **490**, interconnection service device **116**, determines that the received message is received within 30 days of completion of the order, then the method takes the no branch and proceeds to step **494**.

(107) Further, back in step **488**, when interconnection service device **116**, determines that the received message does not include a message identifier of “Partially Cancel”, then the method takes the no branch and proceeds to step **494**.

(108) In step **494**, interconnection service device **116**, determines that the received communication is to complete cancel the order, and in response transmits a cancel order notification to the customer devices **102(1)**, item delivery provider devices **106(1)**, and item service provider devices **110(1)** and further issues a full refund, and the method ends here.

(109) The disclosed embodiments provide an improved method of interconnecting network devices based on queuing and servicing responses. By providing technical advantages of an optimized process of queuing to identify network responses by reducing data overhead and delays. As this technology provides a real time search queueing system to identify server devices **122(1)-112(n)** that service request and responses, this technology provides a fast and reliable process of processing responses, which results in optimized user experience. Thus, this technology reduces delays caused during transmission of responses. Thus, this technology reduces data overhead, by utilizing queues to quickly identify server devices **122(1)-112(n)** responsible for servicing requests.

(110) In contrast, in the prior art, other strategies that have been implemented are inefficient as they require extra data overhead, which may not be beneficial to efficiently utilize network resources and thus increase network load. Further the prior art causes significant delays during a transmission of responses, while the disclosed embodiments provides a real time network interconnection, that reduces network delays between transmission of responses.

(111) While illustrative embodiments have been described herein, the scope thereof includes any and all embodiments having equivalent elements, modifications, omissions, combinations (e.g., of aspects across various embodiments), adaptations and/or alterations as would be appreciated by those in the art based on the present disclosure. For example, the number and orientation of components shown in the exemplary systems may be modified. Thus, the foregoing description has been presented for purposes of illustration only. It is not exhaustive and is not limiting to the precise forms or embodiments disclosed. Modifications and adaptations will be apparent to those skilled in the art from consideration of the specification and practice of the disclosed embodiments.

(112) The elements in the claims are to be interpreted broadly based on the language employed in the claims and not limited to examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive. It is intended, therefore, that the specification and examples be considered as exemplary only, with a true scope and spirit being indicated by the following claims and their full scope of equivalents.

Claims

1. A computer-implemented system for interconnecting network devices based on queuing and servicing responses, the system comprising: a memory storing instructions; and at least one processor configured to execute the instructions to perform steps comprising: receiving, from a first computer system of a plurality of first computer systems via a network, an order request for a product or service associated with a second computer system of a plurality of second computer systems; instantiating a queue associated with the order request and adding first computer system data to the queue; displaying a confirmation request associated with the order request on the second computer system via the network; in response to receiving a first response to the confirmation request from the second computer system, adding second computer system data to the queue; displaying a second confirmation request associated with a plurality of tasks on a plurality of third computer systems; in response to receiving a second response from a third computer system of the

plurality of third computer systems, instantiating a first task associated with the order request, wherein instantiating the first task includes establishing a first connection link with the second computer system; instantiating a second task associated with the order request, wherein instantiating the second task includes establishing a second connection link with the third computer system, wherein the first connection link comprises a first open transmission control protocol (TCP) connection link and the second connection link comprises a second open transmission control protocol (TCP) connection link; monitoring communications received from the second computer system and the third computer system via the first connection link and the second connection link; identifying a status update associated with the order request via the first connection link and the second connection link; generating at least one interface based on the status update; displaying the at least one generated interface on at least one of the first computer system, second computer system, or third computer system; adding third computer system data to the queue; receiving a communication from one of the first, second, or third computer systems, the communication comprising a message identifier and a device identifier; determining, based on at least one of the message identifier and the device identifier, a classification of the communication; determining, based on the classification, a third response to the communication, one of the first, second, or third computer systems being associated with servicing the third response; accessing the queue to identify server devices corresponding with the first, second, or third computer system data for servicing the third response; and publishing the third response to the identified server devices for servicing.

2. The system of claim 1, wherein the steps further comprise instantiating the queue upon receiving the order request, wherein the queue comprises an order messaging queue associated with the order request, and wherein first computer system data comprises an identifier of the first computer system.

3. The system of claim 2, wherein the second response comprises an acceptance message to service the plurality of tasks or a message declining to service the plurality of tasks.

4. The system of claim 3, wherein the steps further comprise: if the second response comprises an acceptance message, adding an identifier of the third computer system to the order messaging queue.

5. The system of claim 1, wherein the first response comprises an acceptance message to service the order request or a message declining to service the order request.

6. The system of claim 5, wherein the steps further comprise: if the first response comprises an acceptance message, adding an identifier of the second computer system to the order messaging queue.

7. The system of claim 1, wherein the message identifier comprises a merchant ready identifier, a merchant delay identifier, a merchant cancel identifier, a pickup complete identifier, a delivery complete identifier, a delivery cancel identifier, or partially cancel identifier.

8. The system of claim 1, wherein instantiating the first task is associated with preparation of the product or service; and instantiating the second task is associated with delivery of the product or service.

9. A computer implemented method for interconnecting network devices based on queuing and servicing responses, the method comprising: receiving, from a first computer system of a plurality of first computer systems via a network, an order request for a product or service associated with a second computer system of a plurality of second computer systems; instantiating a queue associated with the order request and adding first computer system data to the queue; displaying a confirmation request associated with the order request on the second computer system via the network; in response to receiving a first response to the confirmation request from the second computer system, adding second computer system data to the queue; displaying a second confirmation request associated with a plurality of tasks on a plurality of third computer systems; in response to receiving a second response from a third computer system of the plurality of third

computer systems, instantiating a first task associated with the order request, wherein instantiating the first task includes establishing a first connection link with the second computer system; instantiating a second task associated with the order request, wherein instantiating the second task includes establishing a second connection link with the third computer system, wherein the first connection link comprises a first open transmission control protocol (TCP) connection link and the second connection link comprises a second open transmission control protocol (TCP) connection link; monitoring communications received from the second computer system and the third computer system via the first connection link and the second connection link; identifying a status update associated with the order request via the first connection link and the second connection link; generating at least one interface based on the status update; displaying the at least one generated interface on at least one of the first computer system, second computer system, or third computer system; adding third computer system data to the queue; receiving a communication from one of the first, second, or third computer systems, the communication comprising a message identifier and a device identifier; determining, based on at least one of the message identifier and the device identifier, a classification of the communication; determining, based on the classification, a third response to the communication, one of the first, second, or third computer systems being associated with servicing the third response; accessing the queue to identify server devices corresponding with the first, second, or third computer system data for servicing the third response; and publishing the third response to the identified server devices for servicing.

10. The method of claim 9, further comprising: instantiating the queue upon receiving the order request, wherein the queue comprises an order messaging queue associated with the order request, and wherein first computer system data comprises an identifier of the first computer system.

11. The method of claim 10, wherein the second response comprises an acceptance message to service the plurality of tasks or a message declining to service the plurality of tasks.

12. The method of claim 11, further comprising: if the second response comprises an acceptance message, adding an identifier of the third computer system to the order messaging queue.

13. The method of claim 9, wherein the first response comprises an acceptance message to service the order request or a message declining to service the order request.

14. The method of claim 13, further comprising: if the first response comprises an acceptance message, adding an identifier of the second computer system to the order messaging queue.

15. The method of claim 9, wherein the message identifier comprises a merchant ready identifier, a merchant delay identifier, a merchant cancel identifier, a pickup complete identifier, a delivery complete identifier, a delivery cancel identifier, or partially cancel identifier.

16. The method of claim 9, wherein, instantiating the first task is associated with preparation of the product or service; and instantiating the second task is associated with delivery of the product or service.
