

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400540
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hattori; Miri et al.

First aid presentation system, first aid presentation method, and program

Abstract

The first aid presentation system comprises: a storage unit that stores one or more pieces of notification information associated with one another from among notification information received from one or more monitoring targets, and one or more pieces of registration information registered by a user and information representing a first aid for the monitoring target that correspond to the notification information; a presentation unit that acquires, from the storage unit, one or more pieces of registration information and a first aid that correspond to notification information associated with specified notification information and that presents the one or more pieces of registration information and the first aid; and a registration unit that newly registers registration information in association with the specified notification information.

Inventors:	Hattori; Miri (Yokohama, JP), Ishigaki; Hiroyasu (Yokohama, JP), Goto; Daisuke (Yokohama, JP)
Applicant:	MITSUBISHI HEAVY INDUSTRIES, LTD. (Tokyo, JP)
Family ID:	1000008780210
Assignee:	MITSUBISHI HEAVY INDUSTRIES, LTD. (Tokyo, JP)
Appl. No.:	18/037507
Filed (or PCT Filed):	November 25, 2021
PCT No.:	PCT/JP2021/043213
PCT Pub. No.:	WO2022/163102
PCT Pub. Date:	August 04, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

JP

2021-013814

Jan. 29, 2021

Publication Classification

Int. Cl.: G08B29/20 (20060101); G16H30/40 (20180101)

U.S. Cl.:

CPC G08B29/20 (20130101); G16H30/40 (20180101);

Field of Classification Search

CPC: A63F (13/30); G05B (19/4083); G05B (23/027); G05B (23/0272); G05B (2219/24086); G05B (2219/24091); G06F (11/00); G06F (16/29); G06F (21/32); G06Q (10/02); G06Q (10/06); G06Q (10/06313); G06Q (30/00); G06Q (30/02); G06Q (30/0201); G08B (29/20); G16H (30/40); H04M (7/0012)

USPC: 340/506

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6450818	12/2001	Ogawa et al.	N/A	N/A
9348332	12/2015	Morita	N/A	G06F 11/2257
10698398	12/2019	Kishi et al.	N/A	N/A
2010/0228364	12/2009	Ohashi et al.	N/A	N/A
2010/0228725	12/2009	Ohashi et al.	N/A	N/A
2011/0276985	12/2010	Takatsu	719/318	H04L 69/329
2014/0267566	12/2013	Hamada	348/14.08	H04L 65/4038
2016/0027288	12/2015	Toda	N/A	N/A
2016/0078750	12/2015	King	340/506	A61B 5/002
2016/0085235	12/2015	Kamijo	N/A	N/A
2016/0328954	12/2015	Ramadoss et al.	N/A	N/A
2018/0017959	12/2017	Pandian et al.	N/A	N/A
2019/0014004	12/2018	Horiuchi	N/A	H04L 41/0893
2020/0061768	12/2019	Morita et al.	N/A	N/A
2020/0096984	12/2019	Kishi et al.	N/A	N/A
2020/0169483	12/2019	Kursun	N/A	G06Q 20/3678
2020/0327029	12/2019	Prakash et al.	N/A	N/A
2023/0386629	12/2022	Pfister	N/A	G16H 15/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110874913	12/2019	CN	N/A
110994788	12/2019	CN	H02B 15/02
2000-194414	12/1999	JP	N/A
2001-022441	12/2000	JP	N/A
2010-182142	12/2009	JP	N/A
2010-204887	12/2009	JP	N/A
2010-211377	12/2009	JP	N/A
2011-154456	12/2010	JP	N/A
2012-059151	12/2011	JP	N/A
2014-203116	12/2013	JP	N/A
2016-031604	12/2015	JP	N/A
2016-066200	12/2015	JP	N/A
2016-212875	12/2015	JP	N/A
2017-097628	12/2016	JP	N/A
2018-097494	12/2017	JP	N/A
2018-120456	12/2017	JP	N/A
2020-038464	12/2019	JP	N/A
2020-173683	12/2019	JP	N/A
201631426	12/2015	TW	N/A
2018/139586	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Jan. 25, 2022, issued in counterpart Application No. PCT/JP2021/043213, with English Translation. (6 pages). cited by applicant

Written Opinion dated Jan. 25, 2022, issued in counterpart Application No. PCT/JP2021/043213, with English Translation. (8 pages). cited by applicant

Primary Examiner: Burgdorf; Stephen R

Attorney, Agent or Firm: WHDA, LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a first aid presentation system, a first aid presentation method, and a program. The present application claims priority based on Japanese Patent Application No. 2021-013814 filed in Japan on Jan. 29, 2021, the contents of which are incorporated herein by reference.

BACKGROUND ART

(2) PTL 1 discloses the following remote monitoring control system. That is, a remote monitoring control system described in PTL 1 is a remote monitoring control system including: a terminal that is connected to a plurality of remote monitoring control devices via a transmission path and that is connected to any remote monitoring control device, in which the terminal includes a failure recovery database that records known failure contents in the past; a recovery history database that records a history of recovery handling; an input unit that inputs the failure content; a dialog guiding unit that provides a recovery procedure related to a failure content in a dialog guiding manner; and

an output unit in which a malfunction state is notified and a failure status is displayed.

CITATION LIST

Patent Literature

(3) [PTL 1] Japanese Unexamined Patent Application Publication No. 2014-203116

SUMMARY OF INVENTION

Technical Problem

(4) In the remote monitoring control system disclosed in PTL 1, the recovery procedure that is related to a failure content is provided in a dialog guiding manner. Therefore, there is a problem that an inappropriate recovery procedure may be presented when there is an error in a response at the time of guiding a dialogue or it may take an inappropriate amount of time at the time of guiding a dialogue.

(5) The present disclosure has been made to solve the above problems, and an object of the present disclosure is to provide a first aid presentation system, a first aid presentation method, and a program capable of appropriately presenting a first aid.

Solution to Problem

(6) In order to solve the above-described problem, a first aid presentation system according to the present disclosure includes: a storage unit that stores one or a plurality of pieces of notification information associated with notification information received from one or a plurality of monitoring targets, information representing a first aid for the monitoring target with respect to the notification information, and one or a plurality of pieces of registration information registered by a user; a presentation unit that acquires, from the storage unit, the first aid with respect to notification information associated with designated notification information and the one or the plurality of pieces of registration information, and that presents the first aid and the one or the plurality of pieces of registration information; and a registration unit that newly registers the registration information with respect to the designated notification information.

(7) A first aid presentation method according to the present disclosure includes: by using a storage unit that stores one or a plurality of pieces of notification information associated with notification information received from one or a plurality of monitoring targets, information representing a first aid for the monitoring target with respect to the notification information, and one or a plurality of pieces of registration information registered by a user, a presentation step of acquiring, from the storage unit, the first aid with respect to notification information associated with designated notification information and the one or the plurality of pieces of registration information, and presenting the first aid and the one or the plurality of pieces of registration information; and a registration step of newly registering the registration information with respect to the designated notification information.

(8) A program according to the present disclosure for causing a computer to execute: by using a storage unit that stores one or a plurality of pieces of notification information associated with notification information received from one or a plurality of monitoring targets, information representing a first aid for the monitoring target with respect to the notification information, and one or a plurality of pieces of registration information registered by a user, a presentation step of acquiring, from the storage unit, the first aid with respect to notification information associated with designated notification information and the one or the plurality of pieces of registration information, and presenting the first aid and the one or the plurality of pieces of registration information; and a registration step of newly registering the registration information with respect to the designated notification information.

Advantageous Effects of Invention

(9) According to a first aid presentation system, a first aid presentation method, and a program of the present disclosure, a first aid can be appropriately presented.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a system diagram illustrating an example of a configuration of a first aid presentation system according to an embodiment of the present disclosure.
- (2) FIG. 2 is a block diagram illustrating an example of a configuration of a web server illustrated in FIG. 1.
- (3) FIG. 3 is a schematic diagram illustrating an example of a configuration of a first aid database illustrated in FIG. 2.
- (4) FIG. 4 is a flowchart illustrating an outline of an example of an operation of the first aid presentation system according to the embodiment of the present disclosure.
- (5) FIG. 5 is a schematic diagram illustrating an example of display in a user terminal illustrated in FIG. 1.
- (6) FIG. 6 is a schematic diagram illustrating an example of display in the user terminal illustrated in FIG. 1.
- (7) FIG. 7 is a schematic diagram illustrating an example of search in the first aid database illustrated in FIG. 2.
- (8) FIG. 8 is a flowchart illustrating an example of an operation of the first aid presentation system according to the embodiment of the present disclosure.
- (9) FIG. 9 is a schematic diagram illustrating an example of display in the user terminal illustrated in FIG. 1.
- (10) FIG. 10 is a schematic diagram for describing an example of an operation of the first aid presentation system according to the embodiment of the present disclosure.
- (11) FIG. 11 is a schematic diagram for describing an example of an operation of the first aid presentation system according to the embodiment of the present disclosure.
- (12) FIG. 12 is a system diagram of the first aid presentation system according to an embodiment of the present disclosure.
- (13) FIG. 13 is a schematic block diagram illustrating a configuration of a computer according to at least one embodiment.

DESCRIPTION OF EMBODIMENTS

(14) Hereinafter, a first aid presentation system, a first aid presentation method, and a program according to an embodiment of the present disclosure will be described with reference to the drawings. It should be noted that the same reference numerals are used for the same or corresponding configurations in the respective drawings, and the description thereof will be omitted as appropriate.

First Embodiment

(15) FIG. 1 is a system diagram of a first aid presentation system according to a first embodiment of the present disclosure. FIG. 2 is a block diagram illustrating an example of a configuration of a web server 12 illustrated in FIG. 1. FIG. 3 is a schematic diagram illustrating an example of a configuration of the first aid database 125 illustrated in FIG. 2. FIG. 4 is a flowchart illustrating an outline of an example of an operation of the first aid presentation system 1 according to a first embodiment. FIG. 5 and FIG. 6 are schematic diagrams illustrating an example of display in a user terminal 4 illustrated in FIG. 1. FIG. 7 is a schematic diagram illustrating an example of search in the first aid database 125 illustrated in FIG. 2. FIG. 8 is a flowchart illustrating an example of an operation of the first aid presentation system 1 according to the embodiment of the present disclosure. FIG. 9 is a schematic diagram illustrating an example of display in the user terminal 4 illustrated in FIG. 1. FIG. 10 and FIG. 11 are schematic diagrams for describing an example of an operation of the first aid presentation system 1 according to the embodiment of the present disclosure.

Example of Configuration of First Aid Presentation System

(16) The first aid presentation system **1** illustrated in FIG. **1** includes a database server **11** and a web server **12** as a functional configuration composed of a combination of a computer, hardware such as a peripheral device of the computer, and software such as a program executed by the computer and data processed by the computer. In this case, the first aid presentation system **1** is configured as one element of a remote monitoring system **100** that remotely monitors alarm/event data generated from a monitoring target such as a unit **3** provided in a plant **2** such as a power plant. The first aid presentation system **1** is a system that searches for and presents a first aid with respect to an alarm/event generated from the plant **2**.

(17) The database server **11** receives the alarm/event data transmitted from the plant **2**, accumulates the received alarm/event data in a database, and manages the received alarm/event data. The alarm/event data is information generated by a computer (not illustrated) that monitors the monitoring target and represents, for example, date and time when an abnormality is recognized, identification information of the monitoring target, a content of the abnormality, and the like, when a predetermined abnormality (an event indicating an abnormal state) is recognized, or when a predetermined state or a predetermined status change (an event indicating a normal state, an abnormal state, or the like) is recognized, using the unit **3**, an apparatus, a device, facility, or the entire plant as the monitoring target. The alarm/event data is notification information that includes alarm data, which is information related to an alarm generated from the monitoring target, and event data, which is information related to an event generated from the monitoring target, (or at least one of those), and that is notified from the monitoring target to the first aid presentation system **1** or the like.

(18) The web server **12** provides functions such as search, browsing, and registration to the user terminal **4** on a web system through a network and provides information indicating a first aid. The user terminal **4** is, for example, a terminal such as a server, a desktop personal computer, a notebook personal computer, or a tablet terminal, and includes a display unit **4a**. For example, as illustrated in FIG. **2**, the web server **12** includes a presentation unit **121**, a registration unit **122**, a database management unit **123**, and a storage unit **124** as a functional configuration composed of a combination of hardware and software. Further, the storage unit **124** stores the first aid database **125**. Here, an example of a configuration of the first aid database **125** will be described with reference to FIG. **3**.

(19) The first aid database **125** illustrated in FIG. **3** is configured as a graph database. The graph database is a database having a graph structure and represents a “relationship” between nodes by using three elements of a “node”, an “edge”, and a “property”. The node represents a target object, the edge represents a relationship between the nodes, and the property represents attributes of the node and the edge. The graph database has a high-speed search that traces the connection, is less susceptible to growth in data amount as compared to a relational database, or the like, which search the entire database, and has a high-speed search that traces the connection. Further, the data definition is easy to visually understand from the developer's point of view. The first aid database **125** illustrated in FIG. **3** has nodes **N11** to **N17** and edges **E11** to **E19**. Further, in FIG. **3**, only one of each type of node, which is classified by a label, is shown for each type. However, the number of nodes is not limited to one, and is normally plural.

(20) The node **N11** is a node that represents the monitoring target such as the plant or the unit. The node **N11** is associated with (or related to) the node **N12** through the edge **E11**.

(21) The node **N12** is a node that represents master information of alarm/event (alarm/event master information). It is the basic data of alarm data or the event data. For example, the node **N12** has properties such as an alarm name, a unit name, a device name, and an alarm category. The node **N12** is associated with the node **N13** by using the edge **E12** of instruction and is associated with the node **N14** by using the edge **E13** of occurrence.

(22) The node **N13** is a node representing a first aid (the first aid) and represents the first aid or the

like for the alarm/event represented by the node N12. The node N13 has, for example, properties such as an alarm name (an alarm title), a behavior, a factor, and a first aid.

(23) The node N14 is a node representing an alarm or an event that has occurred in the plant 2. The node N14 has properties such as an occurrence date and time, an alarm name (an event name), a state, a unit, and a device name. The node N14 is associated with the node N15 by using the edge E15 of comment and is associated with the node N16 by using the edge E16 of attached document. Note that, the node N14 does not extend the edge E14 of master, which is toward the node N12 indicated with the dashed line, and the connection to the node N12 is defined by tracing back the edge E13 of occurrence. According to this, the amount of information can be saved, but when the frequency of tracing is high, the edge may be defined.

(24) The node N15 is a node representing a comment (the registration information) registered by the user with respect to the alarm/event of the node N14. The comment is, for example, a sentence related to the first aid for the alarm/event. The node N15 has properties such as character information representing a content of the comment. The node N16 is a node representing document information (the registration information) registered by the user with respect to the alarm/event of the node N14. The document information is, for example, a document (a document, a document file that can be downloaded on a website, a web page, or the like) referred to at the time of the first aid for the alarm/event. The node N16 has properties such as a document name and a uniform resource locator (URL) of a reference destination of the document.

(25) Further, in the present embodiment, the registration information is information representing at least one of a comment, which is related to the first aid for the alarm/event designated by the user, or a document, which is referred at the time of the first aid for the designated alarm/event. The registration information is, for example, information that includes at least one of the comment and the document information registered by the user. Further, the registration information is information that represents at least one of a comment, which is related to the first aid for the monitoring target related to the designated notification information by the user, or a document, which is referenced at the time of the first aid for the monitoring target related to the designated notification information.

(26) The node N17 is a node representing a user. The node N17 has, for example, properties such as years of experience of the user and a department to which the user belongs. When the comment or the document information is registered or browsed, or when “Like” (or “Favorite”) that represents helpful feedback with respect to the comment or the document is registered, the node N17 is used to record a behavior history thereof. The node N17 is associated with the node N16 by using the edge E17 of registration/browsing, is associated with the node N15 by using the edge E18 of registration/browsing, and is associated with the node N12 by using the edge E19 of browsing/“Favorite”.

(27) In the present embodiment, the first aid database 125 has the following associations. That is, each node of alarm/event (data) (for example, node N14) is associated with each node of alarm/event master (for example, the node N12). Further, the node of alarm/event master (for example, the node N12) is associated with the node of first aid (for example, the node N13). Further, the node of alarm/event master (for example, the node N12) is associated with one or a plurality of nodes of alarm/event (for example, the node N14 and a plurality of nodes of alarm/event other than the node N14 (not illustrated)). Further, the node of alarm/event (for example, the node N14) is associated with the node of comment (for example, the node N15) and the node of document information (the node N16). In this case, the node of alarm/event (for example, the node N14) is associated with another node of alarm/event and is associated with the node of the comment or the node of document information, which is associated with the other node of alarm/event, via the node of alarm/event master (for example, the node N12). Summarizing these associations together, the first aid database 125 stores one or a plurality of pieces of notification information associated with notification information received from one or a plurality of

monitoring targets, information representing a first aid for the monitoring target with respect to the notification information, and one or a plurality of pieces of registration information registered by the user.

(28) Returning to FIG. 2, the presentation unit **121** refers to the first aid database **125**, acquires, from the storage unit **124**, the first aid associated with the alarm/event master information corresponding to the alarm/event designated by the user and one or a plurality of comments or a plurality of pieces of document information (the registration information) recorded in association with one or a plurality of same or similar alarms/events associated with the relevant alarm/event master information, and presents the first aid and the one or the plurality of comments or the plurality of pieces of document information to the user terminal **4**. That is, the presentation unit **121** acquires, from the storage unit **124**, the first aid with respect to the notification information associated with the designated notification information and one or a plurality of pieces of registration information, and presents the first aid and the registration information.

(29) Further, the registration unit **122** newly registers the comment or the document information (the registration information) in the first aid database **125** in association with the alarm/event designated by the user. That is, the registration unit **122** newly registers the registration information with respect to the designated notification information.

(30) Further, the database management unit **123** searches for and updates the first aid database **125** in accordance with instructions from the presentation unit **121**, the registration unit **122**, and the like.

Example of Operation of First Aid Presentation System

(31) Next, an example of an operation of the first aid presentation system **1** illustrated in FIG. 1 and FIG. 2 will be described with reference to FIG. 4 to FIG. 11. FIG. 4 illustrates a flow of processing of accessing a website screen displayed by the web server **12** from the user terminal **4** by the user (step S1), for example, selecting an alarm/event that is currently occurring and checking detailed information and a first aid for that alarm/event (step S2), and further registering a comment for the alarm/event (step S3).

(32) In step S1, the web server **12** (the presentation unit **121**) presents information for displaying a screen **40a** illustrated in FIG. 5, for example, on the user terminal **4**. The screen **40a** illustrated in FIG. 5 includes a list **41** of alarm/event data (two in this example) displayed by the user by designating, for example, the plant **2**, the unit **3**, or the like. In this case, in the list **41**, each record representing the alarm/event data includes each item of the occurrence date and time, the alarm name, the state (whether or not the state is continued), the unit, and the device name.

(33) In step S2, assuming that the user selects, for example, the top alarm/event data ("abnormality A") on the screen **40a**, the web server **12** (the presentation unit **121**) presents information for displaying a screen **40b** illustrated in FIG. 6 on the user terminal **4**, for example. The screen **40b** illustrated in FIG. 6 includes a list **42** of alarm/event data and a display region **43** representing the first aid (the first aid) information corresponding to the selected alarm/event data. Here, processing of searching for the first aid corresponding to the designated alarm/event data from the first aid database **125** will be described with reference to FIG. 7. The first aid database **125** illustrated in FIG. 7 is different from the first aid database **125** described with reference to FIG. 3 in that the node **N14** is changed to two nodes of the node **N14a** and the node **N14b**. The node **N14b** is a node that corresponds to the node **N14** illustrated in FIG. 3 that is registered in the past (however, assuming the node representing an alarm/event B), and the node **N14a** is a node that represents an alarm/event A that has newly occurred this time. Note that, the node **N14a** and the node **N14b** are alarm/event data of the same type or the same category, and an edge (not illustrated) is extended from the node **N12** to the node **N14a**. In the example illustrated in FIG. 7, as indicated by an arrow **S101**, by tracing from node **N14a** to node **N12** and from node **N12** to node **N13**, the first aid with respect to the alarm/event data of node **N14a** can be searched.

(34) Next, in step S2, assuming that a tag **43t**, which displays the alarm/event detailed information,

is clicked on the screen **40b** illustrated in FIG. 6, in the flow of processing illustrated in FIG. 8, the web server **12** (the presentation unit **121**) presents information for displaying, for example, a screen **40c** illustrated in FIG. 9 in the user terminal **4**. First, the web server **12** (the presentation unit **121**) acquires the alarm/event master information to which the alarm/event that has occurred this time corresponds (step **S11**). Next, the web server **12** (the presentation unit **121**) acquires a list of the alarms/events, which have occurred in the past, associated with the alarm/event master information (step **S12**). Next, the web server **12** (the presentation unit **121**) acquires the comment/document information associated with each acquired list of alarms/events (step **S13**). In this case, by tracing each node as indicated by an arrow **S201** and an arrow **S202** in FIG. 10, the list of alarms/events, which have occurred in the past, associated with the alarm/event master information can be acquired. Note that, the screen **40c** illustrated in FIG. 9 includes a display region **45** for the alarm/event master information and a display region **46** for an alarm/event occurrence history (the list of alarms/events) associated with the same node **N12** of alarm/event master in the display region **44** related to the alarm/event details. Further, the display region **46** includes occurrence time of each alarm/event included in the list and the content (a part) of the comment registered in association with each alarm/event. Further, the display region **44** includes an input region **47** of a document title, an input region **48** of a document URL, and an input region **49** of a comment to be registered with respect to the alarm/event that has occurred this time. Furthermore, the display region **46** includes a ring button **50** (a download button) for the document registered in association with the past alarm/event selected in the alarm/event occurrence history, a display region **51** for all contents of the comment, and the “Like” button **52** for the comment (or the document). When the user, who has browsed the comment (or the document), finds the comment helpful, it is recommended that the user clicks the “Like” button **52**.

(35) Next, in step **S3** in FIG. 4, when the comment or the document URL is input on the screen **40c** illustrated in FIG. 9, the comment or the document is registered for the alarm/event that has occurred this time. In this case, a node of new comment and a node of document information, which are associated with the node **N14a** of alarm/event that has occurred this time illustrated in FIG. 10, are generated, and further, edges as indicated by the arrow **S203** and the arrow **S204** are set between the node of comment and the node of document information (nodes in this case are new nodes, which are not the node **N15** and the node **N16**).

Update of Weighting Based on Behavior History of User, Reflection in Display Order

(36) The web server **12** (the presentation unit **121**) can be configured to acquire the following logs as a behavior history of the user with respect to the comment or the document.

(37) (1) most recent browsing date and time, (2) number of times of browsing/downloading, (3) browsing time (converted per page), (4) the number of times “Like” is received by users as feedback when the users felt “helpful”.

(38) Based on these, the web server **12** (the presentation unit **121**) can update the weighting of each comment/document. Further, the web server **12** (the presentation unit **121**) can reflect the weighting on each item on the screen, such as “A document that has been referred to in the past”, and display the weights in descending order. A location where the weighting is updated in the first aid database **125** is indicated by a thick arrow in FIG. 11.

(39) In this case, for example, the presentation unit **121** can update the weighting of each comment or the document information (the registration information) based on the behavior history of the user for the comment or the document information (the registration information), which is information that represents at least one of the most recent browsing date and time, the number of times of browsing, browsing time, and the number of times that helpful feedback is received, and for example, can present each comment or the document information (the registration information) in descending order of the weighting when there are a plurality of comments or a plurality of pieces of document information (the registration information) to be presented.

(40) (Update of Weighting based on Attribute Information of User and Document, Reflection in

Display Order) Also, the web server **12** (the presentation unit **121**) may update the above-described weighting according to the attributes (years of experience, department to which the user belongs, or the like) of the user who browsed (or registered) the first aid or the document information, or the like. According to this, each item on the screen, such as a “document that has been referred to in the past”, is displayed in descending order of the weighting.

(41) Further, the weighting of the document may be updated according to the creation date and time of the document that is registered with respect to the alarm/event based on the concept that “relatively new documents have higher quality of information than documents that have old creation date and time”. According to this, each item on the screen, such as a “document that has been referred to in the past”, is displayed in descending order of the weighting.

(42) In this case, for example, the presentation unit **121** can update the weighting of each comment or the document information (the registration information) based on at least one of the creation date and time of the document information (the registration information) or the attribute of the user who browsed or registered the comment or the document information (the registration information), and for example, can present each comment or the document information (the registration information) in descending order of the weighting when there are a plurality of comments or a plurality of pieces of document information (the registration information) to be presented.

Action/Effects

(43) According to the first embodiment, it can be expected that the knowledge database will automatically grow by using the system, so that more accurate and necessary information can be quickly provided. That is, according to the first embodiment, a first aid can be appropriately presented.

Second Embodiment

(44) FIG. **12** is a system diagram of a first aid presentation system according to a second embodiment of the present disclosure. The first aid presentation system **1a** illustrated in FIG. **12** is difference from the first aid presentation system **1** according to the first embodiment illustrated in FIG. **1**, which uses the alarm/event data generated in the plant **2** as the monitoring target, in that the alarm/event data, which is generated by a simulator **5** simulating the plant **2**, is used as the monitoring target. In the second embodiment, for example, by utilizing the simulator **5**, it is possible to build a mechanism capable of accumulating and utilizing knowledge for an alarm (hereinafter, referred to as a “rare alarm”) that occurs less frequently in actual operation. The web server **12a** has basically the same configuration as the web server **12** illustrated in FIG. **2**, and one first aid database **125** is shared for alarm/event data from the plant **2** and alarm/event data from the simulator **5**.

(45) The simulator **5** simulates an operation of each unit of the plant **2** and generates alarm data by, for example, using a machine learning model or using a model in which a physical model and a simple model are combined. The operation of the simulator **5** is performed, for example, from a user terminal **6**. In this case, it is desirable that the simulator **5** has, for example, the following functions.

(46) That is, the simulator **5** desirably includes a plant operation (activate/stop), execution speed change of the simulation, a backtrack function (return a simulator state to a past state and retrain), setting change of an operation condition (for example: atmospheric temperature, cooling water temperature, or the like), a setting of accident item, and a pseudo generation function.

(47) Further, the first aid presentation system **1a** can select an “actual operation mode” and a “training mode”, and can be switched between an “actual plant environment” by the database server **11** and a “simulator environment” by the database server **13** according to the mode. That is, the first aid presentation system **1a** newly includes the database server **13** that accumulates the alarm data generated by the simulator **5**. Further, the web server **12a** performs presentation of a first aid with respect to the user terminal **4** and update of the first aid database **125** based on the alarm data generated by the plant **2** in the “actual operation mode”, and performs presentation of a

first aid with respect to the user terminal **6** and update of the first aid database **125** based on the alarm data generated by the simulator **5** in the “training mode”.

(48) In this case, it is possible to accumulate knowledge for an alarm first aid by utilizing the training data generated by the simulator **5**. When the “training mode” is selected, for example, the rare alarm that is pseudo-generated on a simulator side is displayed in a list on the “alarm/event feed” screen **40a** illustrated in FIG. **5**. For example, when it is desired to perform operation training related to the alarm first aid, a trainee selects each rare alarm on the feed screen **40a**. Accordingly, by checking the first aid for each alarm (hereinafter, referred to as the first aid) and the recommended document, training of an alarm first aid can be performed.

(49) By registering the comment as knowledge, a cause/first aid content or the like for the rare alarm that is trained during training can be referenced when the same alarm occurs in actual operation. Note that, the document/comment information that is obtained in each mode may be identified, and in particular, the document/comment information that is obtained in the “actual operation mode” may be given a higher weight and displayed higher on the screen.

Action/Effects

(50) According to the second embodiment, it is possible to improve the accuracy of knowledge by aggregating knowledge for the pseudo-generated rare alarm in one knowledge base, in addition to knowledge for the alarm that occur in actual operation. Further, since an operator can check, register, and update the knowledge for various alarms including the rare alarm, it can be expected that the operator's ability to deal with troubles will be improved.

Other Embodiments

(51) The embodiments of the present disclosure have been described in detail with reference to the drawings. However, the specific configuration is not limited to the embodiments of the present disclosure, and includes design changes and the like without departing from the gist of the present disclosure.

(52) In the above embodiment, although only one plant **2** is used as the monitoring target, the present disclosure is not limited to this, and for example, a plurality of plants **2** may be used as monitoring targets. Further, the monitoring target is not limited to the plant **2**, and a device, an apparatus, or a unit that is not installed in the plant may be used as the monitoring target. Further, the first aid database **125** is not limited to the graph database, and may be a database of another format or may be a combination of a database of another format and the graph database.

Computer Configuration

(53) FIG. **13** is a schematic block diagram showing a configuration of a computer according to at least one embodiment.

(54) The computer **90** includes a processor **91**, a main memory **92**, a storage **93**, and an interface **94**.

(55) The above-described first aid presentation systems **1** and **1a** are implemented in the computer **90**. An operation of each processing unit described above is stored in the storage **93** in the form of a program. The processor **91** reads the program from the storage **93**, loads the program into the main memory **92**, and executes the above process according to the program. Further, the processor **91** secures a storage area corresponding to each of the above-mentioned storage units in the main memory **92** according to the program.

(56) The program may be a program for realizing a part of the functions exerted by the computer **90**. For example, the program may exhibit its function by using a combination with other programs already stored in storage or by using a combination with other programs implemented on other devices. In another embodiment, the computer may include a custom large scale integrated circuit (LSI) such as a programmable logic device (PLD) in addition to or instead of the above configuration. Examples of the PLD include a programmable array logic (PAL), a generic array logic (GAL), a complex programmable logic device (CPLD), and a field programmable gate array (FPGA). In this case, a part or all of the functions realized by the processor may be realized by the

integrated circuit.

(57) Examples of the storage **93** include a hard disk drive (HDD), a solid state drive (SSD), a magnetic disk, a magneto-optical disk, a compact disc read only memory (CD-ROM), a digital versatile disc read only memory (DVD-ROM), and a semiconductor memory. The storage **93** may be an internal medium directly connected to a bus in the computer or may be an external medium connected to the computer via an interface **94** or via a communication line. Further, when this program is distributed to the computer **90** by using the communication line, the computer **90**, in which the program is distributed, may load the program in the main memory **92** and execute the above process. In at least one embodiment, the storage **93** is a non-temporary tangible storage medium.

Additional Notes

(58) The first aid presentation systems **1** and **1a** described in each embodiment are grasped as follows, for example.

(59) (1) A first aid presentation system (**1**, **1a**) according to a first aspect includes: a storage unit **124** that stores one or a plurality of pieces of notification information (node **N14b**) associated with notification information (alarm/event data, node **N14a**) received from one or a plurality of monitoring targets (plant **2**, unit **3**), information (node **N13**) representing a first aid for the monitoring target with respect to the notification information, and one or a plurality of pieces of registration information (nodes **N15**, **N16**) registered by a user; a presentation unit **121** that acquires, from the storage unit, the first aid with respect to notification information (node **N14b**) associated with designated notification information (node **N14a**) and the one or the plurality of pieces of registration information, and that presents the first aid and the one or the plurality of pieces of registration information; and a registration unit **122** that newly registers the registration information with respect to the designated notification information. According to the present aspect and each of the following aspects, the first aid can be appropriately presented.

(60) (2) In the first aid presentation system (**1**, **1a**) of a second aspect according to the first aid presentation system (**1**, **1a**) of (1), the registration information is information that represents at least one of a comment (node **N15**), which is related to the first aid for the monitoring target related to the designated notification information, or a document (node **N16**), which is referenced at the time of the first aid for the monitoring target related to the designated notification information.

(61) (3) In the first aid presentation system (**1**, **1a**) of a third aspect according to the first aid presentation system (**1**, **1a**) of (1) or (2), the presentation unit **121** updates a weighting of each of pieces of the registration information based on a behavior history of the user with respect to the registration information, which represents at least one of a most recent browsing date and time, the number of times of browsing, browsing time, and the number of times that helpful feedback is received, and presents each of pieces of the registration information in descending order of weight when a plurality of pieces of the registration information to be presented are present.

(62) (4) In the first aid presentation system (**1**, **1a**) of a fourth aspect according to the first aid presentation system (**1**, **1a**) of any one of (1) to (3), the presentation unit **121** updates a weighting of each of pieces of the registration information based on at least one of creation date and time of the registration information or an attribute of the user who browsed or registered the registration information, and presents each of pieces of the registration information in descending order of weight when a plurality of pieces of the registration information to be presented are present.

(63) (5) In the first aid presentation system (**1a**) of a fifth aspect according to the first aid presentation system (**1a**) of any one of (1) to (4), the storage unit **124** further stores one or a plurality of pieces of notification information associated with notification information received from a simulator **5** and one or a plurality of pieces of the registration information registered by the user with respect to the notification information.

(64) (6) In the first aid presentation system (**1**, **1a**) of a sixth aspect according to the first aid presentation system (**1a**) of any one of (1) to (5), the notification information is information that

includes at least one of information related to an event generated from the monitoring target or information related to an alarm.

INDUSTRIAL APPLICABILITY

(65) According to each aspect of the present invention, a first aid can be appropriately presented.

REFERENCE SIGNS LIST

(66) **1, 1a**: first aid presentation system **2**: plant **3**: unit **4, 6**: user terminal **11, 13**: database server **12**: web server **121**: presentation unit **122**: registration unit **123**: database management unit **124**: storage unit **125**: first aid database

Claims

1. A first aid presentation system comprising: a storage unit that stores a plurality of pieces of notification information which are the same or similar with notification information received from one or a plurality of monitoring targets and thereby associated with the notification information received from the one or the plurality of monitoring targets, information representing a first aid for the monitoring target with respect to each of the plurality of pieces of notification information, and one or a plurality of pieces of registration information registered by a user with respect to each of the plurality of pieces of notification information; a presentation unit that acquires, from the storage unit, information indicating the first aid with respect to the plurality of pieces of notification information associated with designated notification information designated by the user and the one or the plurality of pieces of registration information, and that presents the first aid and the one or the plurality of pieces of registration information; and a registration unit that newly registers the registration information with respect to the designated notification information designated by the user, wherein the registration information includes information that represents a document which is referenced at the time of the first aid for the monitoring target related to the designated notification information, wherein the storage unit includes a first aid database, wherein the first aid database includes a graph database which is represented by a node which represents a target object of information, an edge which represents a relationship between the nodes, and a property which represents attributes of the node and the edge, wherein the graph database includes: a notification information node which represents the notification information; a notification information master node which represents a master information of the notification information; a document information node which represents information which represents the document; an edge which represents a relationship between the notification information node and the notification information master node; and an edge which represents a relationship between the notification information node and the document information node; wherein the presentation unit, from the graph database: acquires a notification information master information corresponding to the notification information designated by the user; acquires a plurality of pieces of notification information associated with the notification information master information which is acquired; and acquires and presents information which represents the document which is associated with respect to each of the plurality of pieces of notification information.

2. The first aid presentation system according to claim 1, wherein the registration information includes information that represents a comment, which is related to the first aid for the monitoring target related to the designated notification information designated by the user.

3. The first aid presentation system according to claim 1, wherein the presentation unit updates a weighting of each of pieces of the registration information based on a behavior history of the user with respect to the registration information, which represents at least one of a most recent browsing date and time, the number of times of browsing, browsing time, and the number of times that helpful feedback is received, and presents each of pieces of the registration information in descending order of weight when a plurality of pieces of the registration information to be presented are present.

4. The first aid presentation system according to claim 1, wherein the presentation unit updates a weighting of each of pieces of the registration information based on at least one of creation date and time of the registration information or an attribute of the user who browsed or registered the registration information, and presents each of pieces of the registration information in descending order of weight when a plurality of pieces of the registration information to be presented are present.
5. The first aid presentation system according to claim 1, wherein the storage unit further stores one or a plurality of pieces of notification information associated with notification information received from a simulator and one or a plurality of pieces of the registration information registered by the user with respect to the notification information.
6. The first aid presentation system according to claim 1, wherein the notification information is information that includes at least one of information related to an event generated from the monitoring target or information related to an alarm.
7. A first aid presentation method comprising: by using a storage unit that stores a plurality of pieces of notification information which are the same or similar with notification information received from one or a plurality of monitoring targets and thereby associated with the notification information received from the one or the plurality of monitoring targets, information representing a first aid for the monitoring target with respect to each of the plurality of pieces of notification information, and one or a plurality of pieces of registration information registered by a user with respect to each of the plurality of pieces of notification information; a presentation step of acquiring, from the storage unit, information indicating the first aid with respect to the plurality of pieces of notification information associated with designated notification information designated by the user and the one or the plurality of pieces of registration information, and presenting the first aid and the one or the plurality of pieces of registration information; and a registration step of newly registering the registration information with respect to the designated notification information designated by the user, wherein the registration information includes information that represents a document which is referenced at the time of the first aid for the monitoring target related to the designated notification information, wherein the storage unit includes a first aid database, wherein the first aid database includes a graph database which is represented by a node which represents a target object of information, an edge which represents a relationship between the nodes, and a property which represents attributes of the node and the edge, wherein the graph database includes: a notification information node which represents the notification information; a notification information master node which represents a master information of the notification information; a document information node which represents information which represents the document; an edge which represents a relationship between the notification information node and the notification information master node; and an edge which represents a relationship between the notification information node and the document information node; wherein, in the presentation step, from the graph database: acquiring a notification information master information corresponding to the notification information designated by the user; acquiring a plurality of pieces of notification information associated with the notification information master information which is acquired; and acquiring and presenting information which represents the document which is associated with respect to each of the plurality of pieces of notification information.
8. A non-transitory computer-readable recording medium storing a program for causing a computer to execute: by using a storage unit that stores a plurality of pieces of notification information which are the same or similar with notification information received from one or a plurality of monitoring targets and thereby associated with the notification information received from the one or the plurality of monitoring targets, information representing a first aid for the monitoring target with respect to each of the plurality of pieces of notification information, and one or a plurality of pieces of registration information registered by a user with respect to each of the plurality of pieces of notification information; a presentation step of acquiring, from the storage unit, information

indicating the first aid with respect to the plurality of pieces of notification information associated with designated notification information designated by the user and the one or the plurality of pieces of registration information, and presenting the first aid and the one or the plurality of pieces of registration information; and a registration step of newly registering the registration information with respect to the designated notification information designated by the user, wherein the registration information includes information that represents a document which is referenced at the time of the first aid for the monitoring target related to the designated notification information, wherein the storage unit includes a first aid database, wherein the first aid database includes a graph database which is represented by a node which represents a target object of information, an edge which represents a relationship between the nodes, and a property which represents attributes of the node and the edge, wherein the graph database includes: a notification information node which represents the notification information; a notification information master node which represents a master information of the notification information; a document information node which represents information which represents the document; an edge which represents a relationship between the notification information node and the notification information master node; and an edge which represents a relationship between the notification information node and the document information node; wherein, in the presentation step, from the graph database: acquiring a notification information master information corresponding to the notification information designated by the user; acquiring a plurality of pieces of notification information associated with the notification information master information which is acquired; and acquiring and presenting information which represents the document which is associated with respect to each of the plurality of pieces of notification information.
