

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396848
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Gross; Yossi et al.

Method for use at a heart valve

Abstract

First and second atrial arms and first and second ventricular arms are advanced to the heart. The first ventricular arm is moved distally by applying a pulling force to the first ventricular arm at a first fixed connection point that is at a portion of the first ventricular arm that is farthest from a first articulation site of the first atrial arm and the first ventricular arm, and the second ventricular arm is moved distally by applying a pulling force to the second ventricular arm at a second fixed connection point that is at a portion of the second ventricular arm that is farthest from a second articulation site of the second atrial arm and the second ventricular arm. Subsequently, the first native leaflet is clamped between the first arms, and the second native leaflet is clamped between the second arms. Other embodiments are also described.

Inventors:	Gross; Yossi (Moshav Mazor, IL), Hacohe; Gil (Ramat Gan, IL)
Applicant:	CARDIOVALVE LTD. (Or Yehuda, IL)
Family ID:	1000008781433
Assignee:	CARDIOVALVE LTD. (Or Yehuda, IL)
Appl. No.:	18/197337
Filed:	May 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240299161 A1	Sep. 12, 2024

Related U.S. Application Data

continuation parent-doc US 16881350 20200522 US 11690712 child-doc US 18197337
continuation parent-doc US 16460313 20190702 US 10695173 child-doc US 16881350
continuation parent-doc US 16045059 20180725 US 10376361 child-doc US 16460313
continuation parent-doc US 15213791 20160719 US 10245143 child-doc US 16045059
continuation parent-doc US 14237264 ABANDONED WO PCT/IL2012/000292 20120805 child-doc US 15213791
continuation-in-part parent-doc US 13412814 20120306 US 8852272 child-doc US 14237264
us-provisional-application US 61515372 20110805
us-provisional-application US 61525281 20110819
us-provisional-application US 61537276 20110921

Publication Classification

Int. Cl.: A61F2/24 (20060101); A61F2/848 (20130101)

U.S. Cl.:

CPC A61F2/2418 (20130101); A61F2/2409 (20130101); A61F2/2436 (20130101); A61F2/2439 (20130101); A61F2/246 (20130101); A61F2/2433 (20130101); A61F2/2442 (20130101); A61F2/848 (20130101); A61F2220/0008 (20130101); A61F2220/0016 (20130101); A61F2220/0025 (20130101); A61F2220/0091 (20130101); A61F2230/0013 (20130101); A61F2230/005 (20130101); A61F2230/0054 (20130101); A61F2230/0078 (20130101); A61F2250/0015 (20130101); A61F2250/006 (20130101); A61F2250/0069 (20130101); A61F2250/0071 (20130101)

Field of Classification Search

CPC: A61F (2/2418); A61F (2/2409); A61F (2/2436); A61F (2/2439); A61F (2/246); A61F (2/2433); A61F (2/2442); A61F (2/848)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3874388	12/1974	King et al.	N/A	N/A
4222126	12/1979	Boretos et al.	N/A	N/A
4261342	12/1980	Aranguren	N/A	N/A
4340091	12/1981	Skelton et al.	N/A	N/A
4423525	12/1983	Vallana et al.	N/A	N/A
4853986	12/1988	Allen	N/A	N/A
4892541	12/1989	Alonso	N/A	N/A
4972494	12/1989	White et al.	N/A	N/A
5108420	12/1991	Marks	N/A	N/A
5314473	12/1993	Godin	N/A	N/A
5405378	12/1994	Strecker	N/A	N/A
5443500	12/1994	Sigwart	N/A	N/A
5607444	12/1996	Lam	N/A	N/A
5607470	12/1996	Milo	N/A	N/A
5647857	12/1996	Anderson et al.	N/A	N/A
5702397	12/1996	Goble et al.	N/A	N/A
5713948	12/1997	Uflacker	N/A	N/A
5716417	12/1997	Girard et al.	N/A	N/A
5741297	12/1997	Simon	N/A	N/A
5765682	12/1997	Bley et al.	N/A	N/A
5776140	12/1997	Cottone	N/A	N/A
5868777	12/1998	Lam	N/A	N/A
5873906	12/1998	Lau et al.	N/A	N/A
5954766	12/1998	Zadno-Azizi et al.	N/A	N/A
5957949	12/1998	Leonhardt et al.	N/A	N/A
5980565	12/1998	Jayaraman	N/A	N/A
6010530	12/1999	Goicoechea	N/A	N/A
6019787	12/1999	Richard et al.	N/A	N/A

6042607	12/1999	Williamson, IV	N/A	N/A
6074417	12/1999	Peredo	N/A	N/A
6113612	12/1999	Swanson et al.	N/A	N/A
6120534	12/1999	Ruiz	N/A	N/A
6126686	12/1999	Badylak et al.	N/A	N/A
6152937	12/1999	Peterson et al.	N/A	N/A
6165183	12/1999	Kuehn et al.	N/A	N/A
6165210	12/1999	Lau et al.	N/A	N/A
6187020	12/2000	Zegdi et al.	N/A	N/A
6193745	12/2000	Fogarty et al.	N/A	N/A
6264700	12/2000	Kilcoyne et al.	N/A	N/A
6287339	12/2000	Vasquez et al.	N/A	N/A
6312465	12/2000	Griffin et al.	N/A	N/A
6332893	12/2000	Mortier et al.	N/A	N/A
6334873	12/2001	Lane et al.	N/A	N/A
6346074	12/2001	Roth	N/A	N/A
6350278	12/2001	Lenker et al.	N/A	N/A
6352561	12/2001	Leopold et al.	N/A	N/A
6391036	12/2001	Berg et al.	N/A	N/A
6402780	12/2001	Williamson, IV	N/A	N/A
6409755	12/2001	Vrba	N/A	N/A
6419696	12/2001	Ortiz et al.	N/A	N/A
6428550	12/2001	Vargas et al.	N/A	N/A
6440164	12/2001	Dimatteo et al.	N/A	N/A
6454799	12/2001	Schreck	N/A	N/A
6458153	12/2001	Bailey et al.	N/A	N/A
6511491	12/2002	Grudem et al.	N/A	N/A
6530952	12/2002	Vesely	N/A	N/A
6540782	12/2002	Snyders	N/A	N/A
6551350	12/2002	Thornton et al.	N/A	N/A
6558396	12/2002	Inoue	N/A	N/A
6558418	12/2002	Carpentier et al.	N/A	N/A
6569196	12/2002	Vesely	N/A	N/A
6582464	12/2002	Gabbay	N/A	N/A
6602263	12/2002	Swanson et al.	N/A	N/A
6616675	12/2002	Evard et al.	N/A	N/A
6629534	12/2002	St. Goar et al.	N/A	N/A
6652556	12/2002	VanTessel et al.	N/A	N/A
6669724	12/2002	Park et al.	N/A	N/A
6682558	12/2003	Tu et al.	N/A	N/A
6699256	12/2003	Logan et al.	N/A	N/A
6716244	12/2003	Klaco	N/A	N/A
6719781	12/2003	Kim	N/A	N/A
6730118	12/2003	Spenser et al.	N/A	N/A
6730121	12/2003	Ortiz et al.	N/A	N/A
6733525	12/2003	Yang et al.	N/A	N/A
6752813	12/2003	Goldfarb et al.	N/A	N/A
6764514	12/2003	Li et al.	N/A	N/A
6764518	12/2003	Godin	N/A	N/A
6767362	12/2003	Schreck	N/A	N/A
6797002	12/2003	Spence et al.	N/A	N/A
6821297	12/2003	Snyders	N/A	N/A
6830585	12/2003	Artof et al.	N/A	N/A
6830638	12/2003	Boylan et al.	N/A	N/A
6893460	12/2004	Spenser et al.	N/A	N/A

6926715	12/2004	Hauck et al.	N/A	N/A
6951571	12/2004	Srivastava	N/A	N/A
6960217	12/2004	Bolduc	N/A	N/A
6964684	12/2004	Ortiz et al.	N/A	N/A
6974476	12/2004	McGuckin et al.	N/A	N/A
7011681	12/2005	Vesely	N/A	N/A
7018406	12/2005	Seguin et al.	N/A	N/A
7041132	12/2005	Quijano et al.	N/A	N/A
7077861	12/2005	Spence	N/A	N/A
7101336	12/2005	Miller	N/A	N/A
7101395	12/2005	Tremulis et al.	N/A	N/A
7101396	12/2005	Artof et al.	N/A	N/A
7112207	12/2005	Allen et al.	N/A	N/A
7137184	12/2005	Schreck	N/A	N/A
7172625	12/2006	Shu et al.	N/A	N/A
7198646	12/2006	Figulla et al.	N/A	N/A
7201772	12/2006	Schwammenthal	N/A	N/A
7226467	12/2006	Lucatero et al.	N/A	N/A
7226477	12/2006	Cox	N/A	N/A
7261686	12/2006	Couvillon, Jr.	N/A	N/A
7288097	12/2006	Séguin	N/A	N/A
7288111	12/2006	Holloway et al.	N/A	N/A
7316716	12/2007	Egan	N/A	N/A
7329279	12/2007	Haug et al.	N/A	N/A
7335213	12/2007	Hyde et al.	N/A	N/A
7351256	12/2007	Hojeibane et al.	N/A	N/A
7374571	12/2007	Pease et al.	N/A	N/A
7374573	12/2007	Gabbay	N/A	N/A
7377938	12/2007	Sarac et al.	N/A	N/A
7381218	12/2007	Schreck	N/A	N/A
7381219	12/2007	Salahieh et al.	N/A	N/A
7404824	12/2007	Webler et al.	N/A	N/A
7422306	12/2007	Lane	N/A	N/A
7429269	12/2007	Schwammenthal	N/A	N/A
7442204	12/2007	Schwammenthal	N/A	N/A
7445630	12/2007	Lashinski et al.	N/A	N/A
7455677	12/2007	Vargas et al.	N/A	N/A
7455688	12/2007	Furst et al.	N/A	N/A
7462162	12/2007	Phan et al.	N/A	N/A
7481838	12/2008	Carpentier et al.	N/A	N/A
7510575	12/2008	Spenser et al.	N/A	N/A
7513909	12/2008	Lane et al.	N/A	N/A
7524331	12/2008	Birdsall	N/A	N/A
7527646	12/2008	Rahdert et al.	N/A	N/A
7556632	12/2008	Zadno	N/A	N/A
7556646	12/2008	Yang et al.	N/A	N/A
7563267	12/2008	Goldfarb et al.	N/A	N/A
7563273	12/2008	Goldfarb et al.	N/A	N/A
7582111	12/2008	Krolik et al.	N/A	N/A
7585321	12/2008	Cribier	N/A	N/A
7597711	12/2008	Drews et al.	N/A	N/A
7608091	12/2008	Goldfarb et al.	N/A	N/A
7611534	12/2008	Kapadia et al.	N/A	N/A
7621948	12/2008	Hermann et al.	N/A	N/A
7625403	12/2008	Krivoruchko	N/A	N/A

7632302	12/2008	Vreeman et al.	N/A	N/A
7635329	12/2008	Goldfarb et al.	N/A	N/A
7648528	12/2009	Styrc	N/A	N/A
7655015	12/2009	Goldfarb et al.	N/A	N/A
7666204	12/2009	Thornton et al.	N/A	N/A
7682380	12/2009	Thornton et al.	N/A	N/A
7708775	12/2009	Rowe et al.	N/A	N/A
7717952	12/2009	Case et al.	N/A	N/A
7717955	12/2009	Lane et al.	N/A	N/A
7731741	12/2009	Eidenschink	N/A	N/A
7736388	12/2009	Goldfarb et al.	N/A	N/A
7748389	12/2009	Salahieh et al.	N/A	N/A
7753922	12/2009	Starksen	N/A	N/A
7753949	12/2009	Lamphere et al.	N/A	N/A
7758595	12/2009	Allen et al.	N/A	N/A
7758632	12/2009	Hojeibane et al.	N/A	N/A
7758640	12/2009	Vesely	N/A	N/A
7771467	12/2009	Svensson	N/A	N/A
7771469	12/2009	Liddicoat	N/A	N/A
7776083	12/2009	Vesely	N/A	N/A
7780726	12/2009	Seguin	N/A	N/A
7799069	12/2009	Bailey et al.	N/A	N/A
7803181	12/2009	Furst et al.	N/A	N/A
7811296	12/2009	Goldfarb et al.	N/A	N/A
7811316	12/2009	Kalmann et al.	N/A	N/A
7824442	12/2009	Salahieh et al.	N/A	N/A
7837645	12/2009	Bessler et al.	N/A	N/A
7837727	12/2009	Goetz et al.	N/A	N/A
7842081	12/2009	Yadin	N/A	N/A
7850725	12/2009	Vardi et al.	N/A	N/A
7871432	12/2010	Bergin	N/A	N/A
7871436	12/2010	Ryan et al.	N/A	N/A
7887583	12/2010	Macoviak	N/A	N/A
7892281	12/2010	Seguin et al.	N/A	N/A
7896915	12/2010	Guyenot et al.	N/A	N/A
7914544	12/2010	Nguyen et al.	N/A	N/A
7914569	12/2010	Nguyen et al.	N/A	N/A
7927370	12/2010	Webler et al.	N/A	N/A
7942927	12/2010	Kaye et al.	N/A	N/A
7947072	12/2010	Yang et al.	N/A	N/A
7947075	12/2010	Goetz et al.	N/A	N/A
7951195	12/2010	Antonsson et al.	N/A	N/A
7955375	12/2010	Agnew	N/A	N/A
7955377	12/2010	Melsheimer	N/A	N/A
7955384	12/2010	Rafiee et al.	N/A	N/A
7959666	12/2010	Salahieh et al.	N/A	N/A
7959672	12/2010	Salahieh et al.	N/A	N/A
7967833	12/2010	Sterman et al.	N/A	N/A
7967857	12/2010	Lane	N/A	N/A
7981151	12/2010	Rowe	N/A	N/A
7981153	12/2010	Fogarty et al.	N/A	N/A
7992567	12/2010	Hirotsuka et al.	N/A	N/A
7993393	12/2010	Carpentier et al.	N/A	N/A
8002825	12/2010	Letac et al.	N/A	N/A
8002826	12/2010	Seguin	N/A	N/A

8016877	12/2010	Seguin et al.	N/A	N/A
8016882	12/2010	Macoviak	N/A	N/A
8021420	12/2010	Dolan	N/A	N/A
8021421	12/2010	Fogarty et al.	N/A	N/A
8025695	12/2010	Fogarty et al.	N/A	N/A
8029518	12/2010	Goldfarb et al.	N/A	N/A
8029557	12/2010	Sobrinho-Serrano et al.	N/A	N/A
8029564	12/2010	Johnson et al.	N/A	N/A
8034104	12/2010	Carpentier et al.	N/A	N/A
8038720	12/2010	Wallace et al.	N/A	N/A
8043360	12/2010	McNamara et al.	N/A	N/A
8048138	12/2010	Sullivan et al.	N/A	N/A
8048140	12/2010	Purdy	N/A	N/A
8048153	12/2010	Salahieh et al.	N/A	N/A
8052592	12/2010	Goldfarb et al.	N/A	N/A
8052741	12/2010	Bruszewski et al.	N/A	N/A
8052749	12/2010	Salahieh et al.	N/A	N/A
8057493	12/2010	Goldfarb et al.	N/A	N/A
8057532	12/2010	Hoffman	N/A	N/A
8057540	12/2010	Letac et al.	N/A	N/A
8062355	12/2010	Figulla et al.	N/A	N/A
8062359	12/2010	Marquez et al.	N/A	N/A
8070708	12/2010	Rottenberg et al.	N/A	N/A
8070800	12/2010	Lock et al.	N/A	N/A
8070802	12/2010	Lamphere et al.	N/A	N/A
8070804	12/2010	Hyde	N/A	N/A
8075611	12/2010	Milwee et al.	N/A	N/A
8080054	12/2010	Rowe	N/A	N/A
8083793	12/2010	Lane et al.	N/A	N/A
D652927	12/2011	Braido et al.	N/A	N/A
D653341	12/2011	Braido et al.	N/A	N/A
8092518	12/2011	Schreck	N/A	N/A
8092520	12/2011	Quadri	N/A	N/A
8092521	12/2011	Figulla et al.	N/A	N/A
8105377	12/2011	Liddicoat	N/A	N/A
8109996	12/2011	Stacchino et al.	N/A	N/A
8118866	12/2011	Herrmann et al.	N/A	N/A
8133270	12/2011	Kheradvar et al.	N/A	N/A
8136218	12/2011	Millwee et al.	N/A	N/A
8137398	12/2011	Tuval et al.	N/A	N/A
8142492	12/2011	Forster et al.	N/A	N/A
8142494	12/2011	Rahdert et al.	N/A	N/A
8142496	12/2011	Berrekouw	N/A	N/A
8142497	12/2011	Friedman	N/A	N/A
8147504	12/2011	Ino et al.	N/A	N/A
8157852	12/2011	Bloom et al.	N/A	N/A
8157853	12/2011	Laske et al.	N/A	N/A
8157860	12/2011	McNamara et al.	N/A	N/A
8163008	12/2011	Wilson et al.	N/A	N/A
8163014	12/2011	Lane et al.	N/A	N/A
D660433	12/2011	Braido et al.	N/A	N/A
D660967	12/2011	Braido et al.	N/A	N/A
8167894	12/2011	Miles et al.	N/A	N/A
8167932	12/2011	Bourang et al.	N/A	N/A
8167935	12/2011	McGuckin, Jr. et al.	N/A	N/A

8172896	12/2011	McNamara et al.	N/A	N/A
8172898	12/2011	Alferness et al.	N/A	N/A
8177836	12/2011	Lee et al.	N/A	N/A
8182528	12/2011	Salahieh et al.	N/A	N/A
8211169	12/2011	Lane et al.	N/A	N/A
8216256	12/2011	Raschdorf, Jr. et al.	N/A	N/A
8216301	12/2011	Bonhoeffer et al.	N/A	N/A
8221492	12/2011	Case et al.	N/A	N/A
8221493	12/2011	Boyle et al.	N/A	N/A
8226710	12/2011	Nguyen et al.	N/A	N/A
8231670	12/2011	Salahieh et al.	N/A	N/A
8236045	12/2011	Benichou et al.	N/A	N/A
8236049	12/2011	Rowe et al.	N/A	N/A
8252042	12/2011	McNamara et al.	N/A	N/A
8252051	12/2011	Chau et al.	N/A	N/A
8252052	12/2011	Salahieh et al.	N/A	N/A
8257390	12/2011	Carley et al.	N/A	N/A
8267988	12/2011	Hamer et al.	N/A	N/A
8277501	12/2011	Chalekian et al.	N/A	N/A
8287591	12/2011	Keidar et al.	N/A	N/A
8298280	12/2011	Yadin et al.	N/A	N/A
8303653	12/2011	Bonhoeffer et al.	N/A	N/A
8308798	12/2011	Pintor et al.	N/A	N/A
8317853	12/2011	Agnew	N/A	N/A
8317855	12/2011	Gregorich et al.	N/A	N/A
8323335	12/2011	Rowe et al.	N/A	N/A
8328868	12/2011	Paul et al.	N/A	N/A
8337541	12/2011	Quadri et al.	N/A	N/A
8343174	12/2012	Goldfard et al.	N/A	N/A
8343213	12/2012	Salahieh et al.	N/A	N/A
8348999	12/2012	Kheradvar et al.	N/A	N/A
8366767	12/2012	Zhang	N/A	N/A
8372140	12/2012	Hoffman et al.	N/A	N/A
8377119	12/2012	Drews et al.	N/A	N/A
8398708	12/2012	Meiri et al.	N/A	N/A
8403981	12/2012	Forster et al.	N/A	N/A
8403983	12/2012	Quadri et al.	N/A	N/A
8408214	12/2012	Spenser	N/A	N/A
8414644	12/2012	Quadri et al.	N/A	N/A
8425593	12/2012	Braido	N/A	N/A
8430934	12/2012	Das	N/A	N/A
8444689	12/2012	Zhang	N/A	N/A
8449599	12/2012	Chau et al.	N/A	N/A
8449625	12/2012	Campbell et al.	N/A	N/A
8454686	12/2012	Alkhatib	N/A	N/A
8460365	12/2012	Haverkost et al.	N/A	N/A
8474460	12/2012	Barrett et al.	N/A	N/A
8500821	12/2012	Sobrinho-Serrano et al.	N/A	N/A
8512400	12/2012	Tran et al.	N/A	N/A
8529431	12/2012	Baker et al.	N/A	N/A
8539662	12/2012	Stacchino et al.	N/A	N/A
8545544	12/2012	Spenser et al.	N/A	N/A
8551160	12/2012	Figulla et al.	N/A	N/A
8551161	12/2012	Dolan	N/A	N/A
8562672	12/2012	Bonhoeffer et al.	N/A	N/A

8568475	12/2012	Nguyen et al.	N/A	N/A
8579964	12/2012	Lane et al.	N/A	N/A
8579965	12/2012	Bonhoeffer et al.	N/A	N/A
8585755	12/2012	Chau et al.	N/A	N/A
8585756	12/2012	Bonhoeffer et al.	N/A	N/A
8591460	12/2012	Wilson et al.	N/A	N/A
8591570	12/2012	Revuelta et al.	N/A	N/A
8623075	12/2013	Murray et al.	N/A	N/A
8623080	12/2013	Fogarty et al.	N/A	N/A
8628569	12/2013	Benichou et al.	N/A	N/A
8628570	12/2013	Seguin	N/A	N/A
8628571	12/2013	Hacohen et al.	N/A	N/A
8652203	12/2013	Quadri et al.	N/A	N/A
8652204	12/2013	Quill et al.	N/A	N/A
8657872	12/2013	Seguin	N/A	N/A
8663322	12/2013	Keranen	N/A	N/A
8673020	12/2013	Sobrinho-Serrano et al.	N/A	N/A
8679174	12/2013	Ottma et al.	N/A	N/A
8685086	12/2013	Navia et al.	N/A	N/A
8696742	12/2013	Pintor et al.	N/A	N/A
8728155	12/2013	Montorfano et al.	N/A	N/A
8734507	12/2013	Keranen	N/A	N/A
8747460	12/2013	Tuval et al.	N/A	N/A
8771345	12/2013	Tuval et al.	N/A	N/A
8784472	12/2013	Eidenschink	N/A	N/A
8784479	12/2013	Antonsson et al.	N/A	N/A
8784481	12/2013	Alkhatib et al.	N/A	N/A
8795355	12/2013	Alkhatib	N/A	N/A
8795356	12/2013	Quadri et al.	N/A	N/A
8795357	12/2013	Yohanan et al.	N/A	N/A
8801776	12/2013	House et al.	N/A	N/A
8808366	12/2013	Braido et al.	N/A	N/A
8840663	12/2013	Salahieh et al.	N/A	N/A
8840664	12/2013	Karapetian et al.	N/A	N/A
8845722	12/2013	Gabbay	N/A	N/A
8852261	12/2013	White	N/A	N/A
8852272	12/2013	Gross et al.	N/A	N/A
8870948	12/2013	Erzberger et al.	N/A	N/A
8870949	12/2013	Rowe	N/A	N/A
8870950	12/2013	Hacohen	N/A	N/A
8876800	12/2013	Behan	N/A	N/A
8888843	12/2013	Khairkhahan et al.	N/A	N/A
8894702	12/2013	Quadri et al.	N/A	N/A
8900294	12/2013	Paniagua et al.	N/A	N/A
8900295	12/2013	Migliazza et al.	N/A	N/A
8906083	12/2013	Obermiller et al.	N/A	N/A
8911455	12/2013	Quadri et al.	N/A	N/A
8911489	12/2013	Ben-Muvhar	N/A	N/A
8911493	12/2013	Rowe et al.	N/A	N/A
8932343	12/2014	Alkhatib et al.	N/A	N/A
8945177	12/2014	Dell et al.	N/A	N/A
8961595	12/2014	Alkhatib	N/A	N/A
8979922	12/2014	Jayasinghe et al.	N/A	N/A
8986370	12/2014	Annest	N/A	N/A
8986373	12/2014	Chau et al.	N/A	N/A

8986375	12/2014	Garde et al.	N/A	N/A
8992599	12/2014	Thubrikar et al.	N/A	N/A
8992604	12/2014	Gross et al.	N/A	N/A
8992608	12/2014	Haug et al.	N/A	N/A
8998982	12/2014	Richter et al.	N/A	N/A
9005273	12/2014	Salahieh et al.	N/A	N/A
9011468	12/2014	Ketai et al.	N/A	N/A
9011527	12/2014	Li et al.	N/A	N/A
9017399	12/2014	Gross et al.	N/A	N/A
D730520	12/2014	Braido et al.	N/A	N/A
D730521	12/2014	Braido et al.	N/A	N/A
9023100	12/2014	Quadri et al.	N/A	N/A
9034032	12/2014	McLean et al.	N/A	N/A
9034033	12/2014	McLean et al.	N/A	N/A
9039757	12/2014	McLean et al.	N/A	N/A
D732666	12/2014	Nguyen et al.	N/A	N/A
9050188	12/2014	Schweich et al.	N/A	N/A
9060858	12/2014	Thornton et al.	N/A	N/A
9072603	12/2014	Tuval et al.	N/A	N/A
9084676	12/2014	Chau et al.	N/A	N/A
9095434	12/2014	Rowe	N/A	N/A
9119719	12/2014	Zipory et al.	N/A	N/A
9125738	12/2014	Figulla et al.	N/A	N/A
9125740	12/2014	Morriss et al.	N/A	N/A
9132006	12/2014	Spenser et al.	N/A	N/A
9132009	12/2014	Hacohen et al.	N/A	N/A
9138312	12/2014	Tuval et al.	N/A	N/A
9155619	12/2014	Liu et al.	N/A	N/A
9173659	12/2014	Bodewadt et al.	N/A	N/A
9173738	12/2014	Murray et al.	N/A	N/A
9220594	12/2014	Braido et al.	N/A	N/A
9226820	12/2015	Braido et al.	N/A	N/A
9226839	12/2015	Kariniemi et al.	N/A	N/A
9232995	12/2015	Kovalsky et al.	N/A	N/A
9241790	12/2015	Lane et al.	N/A	N/A
9241791	12/2015	Braido et al.	N/A	N/A
9241792	12/2015	Benichou et al.	N/A	N/A
9241794	12/2015	Braido et al.	N/A	N/A
9248014	12/2015	Lane et al.	N/A	N/A
9277994	12/2015	Miller et al.	N/A	N/A
9289290	12/2015	Alkhatib et al.	N/A	N/A
9289291	12/2015	Gorman et al.	N/A	N/A
9295550	12/2015	Nguyen et al.	N/A	N/A
9295551	12/2015	Straubinger et al.	N/A	N/A
9295552	12/2015	McLean et al.	N/A	N/A
9301836	12/2015	Buchbinder et al.	N/A	N/A
D755384	12/2015	Pesce et al.	N/A	N/A
9326852	12/2015	Spenser	N/A	N/A
9326876	12/2015	Acosta et al.	N/A	N/A
9345573	12/2015	Nyuli et al.	N/A	N/A
9387078	12/2015	Gross et al.	N/A	N/A
9421098	12/2015	Gifford et al.	N/A	N/A
9427303	12/2015	Liddy et al.	N/A	N/A
9427316	12/2015	Schweich, Jr. et al.	N/A	N/A
9439757	12/2015	Wallace et al.	N/A	N/A

9463102	12/2015	Kelly	N/A	N/A
9474599	12/2015	Keranen	N/A	N/A
9474638	12/2015	Robinson et al.	N/A	N/A
9480559	12/2015	Vidlund et al.	N/A	N/A
9492273	12/2015	Wallace et al.	N/A	N/A
9498314	12/2015	Behan	N/A	N/A
9532870	12/2016	Cooper et al.	N/A	N/A
9554897	12/2016	Lane et al.	N/A	N/A
9554899	12/2016	Granada et al.	N/A	N/A
9561103	12/2016	Granada et al.	N/A	N/A
9566152	12/2016	Schweich et al.	N/A	N/A
9629716	12/2016	Seguin	N/A	N/A
9662203	12/2016	Sheahan et al.	N/A	N/A
9681952	12/2016	Hacohen et al.	N/A	N/A
9717591	12/2016	Chau et al.	N/A	N/A
9743932	12/2016	Amplatz et al.	N/A	N/A
9763657	12/2016	Hacohen et al.	N/A	N/A
9763817	12/2016	Roeder	N/A	N/A
9770256	12/2016	Cohen et al.	N/A	N/A
D800908	12/2016	Hariton et al.	N/A	N/A
9788941	12/2016	Hacohen	N/A	N/A
9895226	12/2017	Harari et al.	N/A	N/A
9987132	12/2017	Hariton et al.	N/A	N/A
10010414	12/2017	Cooper et al.	N/A	N/A
10105222	12/2017	Metchik et al.	N/A	N/A
10123873	12/2017	Metchik et al.	N/A	N/A
10143552	12/2017	Wallace et al.	N/A	N/A
10149761	12/2017	Granada et al.	N/A	N/A
10154906	12/2017	Granada et al.	N/A	N/A
10182908	12/2018	Tubishevitz et al.	N/A	N/A
10206668	12/2018	Mcgoldrick et al.	N/A	N/A
10226341	12/2018	Gross et al.	N/A	N/A
10245143	12/2018	Gross et al.	N/A	N/A
10258471	12/2018	Lutter et al.	N/A	N/A
10292816	12/2018	Raanani et al.	N/A	N/A
10321995	12/2018	Christianson et al.	N/A	N/A
10322020	12/2018	Lam et al.	N/A	N/A
10327895	12/2018	Lozonschi et al.	N/A	N/A
10376361	12/2018	Gross et al.	N/A	N/A
10390952	12/2018	Hariton et al.	N/A	N/A
10456256	12/2018	Braido et al.	N/A	N/A
10507108	12/2018	Delgado et al.	N/A	N/A
10512456	12/2018	Hacohen et al.	N/A	N/A
10517719	12/2018	Miller et al.	N/A	N/A
10531866	12/2019	Hariton et al.	N/A	N/A
10531872	12/2019	Hacohen et al.	N/A	N/A
10548731	12/2019	Lashinski et al.	N/A	N/A
10575948	12/2019	Iamberger et al.	N/A	N/A
10595992	12/2019	Chambers	N/A	N/A
10610358	12/2019	Vidlund et al.	N/A	N/A
10631871	12/2019	Goldfarb et al.	N/A	N/A
10667912	12/2019	Dixon et al.	N/A	N/A
10695173	12/2019	Gross et al.	N/A	N/A
10702385	12/2019	Hacohen	N/A	N/A
10835377	12/2019	Hacohen et al.	N/A	N/A

10842627	12/2019	Delgado et al.	N/A	N/A
10856972	12/2019	Hariton et al.	N/A	N/A
10874514	12/2019	Dixon et al.	N/A	N/A
10888422	12/2020	Hariton et al.	N/A	N/A
10888425	12/2020	Delgado et al.	N/A	N/A
10888644	12/2020	Ratz et al.	N/A	N/A
10905552	12/2020	Dixon et al.	N/A	N/A
10905554	12/2020	Cao	N/A	N/A
10918483	12/2020	Metchnik et al.	N/A	N/A
10925732	12/2020	Delgado et al.	N/A	N/A
10945843	12/2020	Delgado et al.	N/A	N/A
10945844	12/2020	McCann et al.	N/A	N/A
10959846	12/2020	Marr et al.	N/A	N/A
10993809	12/2020	McCann et al.	N/A	N/A
11065114	12/2020	Raanani et al.	N/A	N/A
11083582	12/2020	McCann et al.	N/A	N/A
11147672	12/2020	McCann et al.	N/A	N/A
11179240	12/2020	Delgado et al.	N/A	N/A
11291545	12/2021	Hacohen	N/A	N/A
11291546	12/2021	Gross et al.	N/A	N/A
11291547	12/2021	Gross et al.	N/A	N/A
11304806	12/2021	Hariton et al.	N/A	N/A
11369469	12/2021	Gross	N/A	A61F 2/2418
11389297	12/2021	Franklin et al.	N/A	N/A
2001/0002445	12/2000	Vesely	N/A	N/A
2001/0005787	12/2000	Oz	N/A	N/A
2001/0021872	12/2000	Bailey et al.	N/A	N/A
2001/0056295	12/2000	Solem	N/A	N/A
2002/0013571	12/2001	Goldfarb et al.	N/A	N/A
2002/0032481	12/2001	Gabbay	N/A	N/A
2002/0099436	12/2001	Thornton et al.	N/A	N/A
2002/0151970	12/2001	Garrison et al.	N/A	N/A
2002/0177894	12/2001	Acosta et al.	N/A	N/A
2003/0009236	12/2002	Godin	N/A	N/A
2003/0036791	12/2002	Bonhoeffer et al.	N/A	N/A
2003/0060846	12/2002	Egnelov et al.	N/A	N/A
2003/0060875	12/2002	Wittens	N/A	N/A
2003/0069635	12/2002	Cartledge	N/A	N/A
2003/0074052	12/2002	Besselink	N/A	N/A
2003/0083742	12/2002	Spence et al.	N/A	N/A
2003/0105519	12/2002	Fasol et al.	N/A	N/A
2003/0120340	12/2002	Liska et al.	N/A	N/A
2003/0158578	12/2002	Pantages et al.	N/A	N/A
2004/0010272	12/2003	Manetakis et al.	N/A	N/A
2004/0030382	12/2003	St. Goar et al.	N/A	N/A
2004/0039414	12/2003	Carley et al.	N/A	N/A
2004/0039442	12/2003	St. Goar et al.	N/A	N/A
2004/0093060	12/2003	Seguin et al.	N/A	N/A
2004/0122503	12/2003	Campbell et al.	N/A	N/A
2004/0122514	12/2003	Fogarty et al.	N/A	N/A
2004/0133267	12/2003	Lane	N/A	N/A
2004/0143315	12/2003	Bruun et al.	N/A	N/A
2004/0176839	12/2003	Huynh et al.	N/A	N/A
2004/0186558	12/2003	Pavcnik et al.	N/A	N/A
2004/0186565	12/2003	Schreck	N/A	N/A

2004/0186566	12/2003	Hindrichs et al.	N/A	N/A
2004/0210244	12/2003	Vargas et al.	N/A	N/A
2004/0210304	12/2003	Seguin et al.	N/A	N/A
2004/0220593	12/2003	Greenhalgh	N/A	N/A
2004/0225354	12/2003	Allen et al.	N/A	N/A
2004/0236354	12/2003	Seguin	N/A	N/A
2004/0249433	12/2003	Freitag	N/A	N/A
2004/0260389	12/2003	Case et al.	N/A	N/A
2004/0260394	12/2003	Douk et al.	N/A	N/A
2005/0004668	12/2004	Aklog et al.	N/A	N/A
2005/0021056	12/2004	St. Goar et al.	N/A	N/A
2005/0027305	12/2004	Shiu et al.	N/A	N/A
2005/0027348	12/2004	Case et al.	N/A	N/A
2005/0038494	12/2004	Eidenschink	N/A	N/A
2005/0055086	12/2004	Stobie	N/A	N/A
2005/0075731	12/2004	Artof et al.	N/A	N/A
2005/0080430	12/2004	Wright et al.	N/A	N/A
2005/0085900	12/2004	Case et al.	N/A	N/A
2005/0137686	12/2004	Salahieh et al.	N/A	N/A
2005/0137688	12/2004	Salahieh et al.	N/A	N/A
2005/0137689	12/2004	Salahieh et al.	N/A	N/A
2005/0137690	12/2004	Salahieh et al.	N/A	N/A
2005/0137691	12/2004	Salahieh et al.	N/A	N/A
2005/0137692	12/2004	Haug et al.	N/A	N/A
2005/0137693	12/2004	Haug et al.	N/A	N/A
2005/0137695	12/2004	Salahieh et al.	N/A	N/A
2005/0137697	12/2004	Salahieh et al.	N/A	N/A
2005/0137699	12/2004	Salahieh et al.	N/A	N/A
2005/0143809	12/2004	Salahieh et al.	N/A	N/A
2005/0149160	12/2004	McFerran	N/A	N/A
2005/0154443	12/2004	Linder et al.	N/A	N/A
2005/0182486	12/2004	Gabbay	N/A	N/A
2005/0197695	12/2004	Stacchino et al.	N/A	N/A
2005/0203549	12/2004	Realyvasquez	N/A	N/A
2005/0203618	12/2004	Sharkawy et al.	N/A	N/A
2005/0216079	12/2004	MaCoviak	N/A	N/A
2005/0234508	12/2004	Cummins et al.	N/A	N/A
2005/0240200	12/2004	Bergheim	N/A	N/A
2005/0251251	12/2004	Cribier	N/A	N/A
2005/0256566	12/2004	Gabbay	N/A	N/A
2005/0267573	12/2004	Macoviak et al.	N/A	N/A
2006/0004439	12/2005	Spenser et al.	N/A	N/A
2006/0004469	12/2005	Sokel	N/A	N/A
2006/0015171	12/2005	Armstrong	N/A	N/A
2006/0020275	12/2005	Goldfarb et al.	N/A	N/A
2006/0020327	12/2005	Lashinski et al.	N/A	N/A
2006/0020333	12/2005	Lashinski et al.	N/A	N/A
2006/0041189	12/2005	Vancaillie	N/A	N/A
2006/0047297	12/2005	Case	N/A	N/A
2006/0052867	12/2005	Revuelta et al.	N/A	N/A
2006/0089627	12/2005	Burnett et al.	N/A	N/A
2006/0111773	12/2005	Rittgers et al.	N/A	N/A
2006/0116750	12/2005	Herbert et al.	N/A	N/A
2006/0122692	12/2005	Gilad et al.	N/A	N/A
2006/0135964	12/2005	Vesley	N/A	N/A

2006/0155357	12/2005	Melsheimer	N/A	N/A
2006/0178700	12/2005	Quinn	N/A	N/A
2006/0178740	12/2005	Stacchino et al.	N/A	N/A
2006/0184203	12/2005	Martin et al.	N/A	N/A
2006/0190036	12/2005	Wendel et al.	N/A	N/A
2006/0190038	12/2005	Carley et al.	N/A	N/A
2006/0195183	12/2005	Navia et al.	N/A	N/A
2006/0195184	12/2005	Lane et al.	N/A	N/A
2006/0201519	12/2005	Frazier et al.	N/A	N/A
2006/0212111	12/2005	Case et al.	N/A	N/A
2006/0229708	12/2005	Powell et al.	N/A	N/A
2006/0241656	12/2005	Starksen et al.	N/A	N/A
2006/0241745	12/2005	Solem	N/A	N/A
2006/0241748	12/2005	Lee et al.	N/A	N/A
2006/0247680	12/2005	Amplatz et al.	N/A	N/A
2006/0253191	12/2005	Salahieh et al.	N/A	N/A
2006/0259136	12/2005	Nguyen et al.	N/A	N/A
2006/0259137	12/2005	Artof et al.	N/A	N/A
2006/0271166	12/2005	Thill et al.	N/A	N/A
2006/0271171	12/2005	McQuinn et al.	N/A	N/A
2006/0282150	12/2005	Olson et al.	N/A	N/A
2006/0287719	12/2005	Rowe et al.	N/A	N/A
2007/0016286	12/2006	Herrmann et al.	N/A	N/A
2007/0016288	12/2006	Gurskis et al.	N/A	N/A
2007/0027528	12/2006	Agnew	N/A	N/A
2007/0027549	12/2006	Godin	N/A	N/A
2007/0038293	12/2006	St. Goar et al.	N/A	N/A
2007/0038295	12/2006	Case et al.	N/A	N/A
2007/0043435	12/2006	Seguin et al.	N/A	N/A
2007/0055340	12/2006	Pryor	N/A	N/A
2007/0056346	12/2006	Spenser et al.	N/A	N/A
2007/0078510	12/2006	Ryan	N/A	N/A
2007/0112422	12/2006	Dehdashtian	N/A	N/A
2007/0118151	12/2006	Davidson	N/A	N/A
2007/0162103	12/2006	Case et al.	N/A	N/A
2007/0162107	12/2006	Haug et al.	N/A	N/A
2007/0162111	12/2006	Fukamachi et al.	N/A	N/A
2007/0173932	12/2006	Cali et al.	N/A	N/A
2007/0197858	12/2006	Goldfarb et al.	N/A	N/A
2007/0198077	12/2006	Cully et al.	N/A	N/A
2007/0198097	12/2006	Zegd	N/A	N/A
2007/0213810	12/2006	Newhauser et al.	N/A	N/A
2007/0213813	12/2006	Von Segesser et al.	N/A	N/A
2007/0219630	12/2006	Chu	N/A	N/A
2007/0225759	12/2006	Thommen et al.	N/A	N/A
2007/0225760	12/2006	Moszner et al.	N/A	N/A
2007/0233186	12/2006	Meng	N/A	N/A
2007/0233237	12/2006	Krivoruchko	N/A	N/A
2007/0239272	12/2006	Navia et al.	N/A	N/A
2007/0239273	12/2006	Allen	N/A	N/A
2007/0244546	12/2006	Francis	N/A	N/A
2007/0255400	12/2006	Parravicini et al.	N/A	N/A
2008/0004688	12/2007	Spenser et al.	N/A	N/A
2008/0004697	12/2007	Lichtenstein et al.	N/A	N/A
2008/0051703	12/2007	Thornton et al.	N/A	N/A

2008/0065204	12/2007	Macoviak et al.	N/A	N/A
2008/0071361	12/2007	Tuval et al.	N/A	N/A
2008/0071363	12/2007	Tuval et al.	N/A	N/A
2008/0071366	12/2007	Tuval et al.	N/A	N/A
2008/0071369	12/2007	Tuval et al.	N/A	N/A
2008/0077235	12/2007	Kirson	N/A	N/A
2008/0082083	12/2007	Forde et al.	N/A	N/A
2008/0082159	12/2007	Tseng et al.	N/A	N/A
2008/0082166	12/2007	Styrc et al.	N/A	N/A
2008/0086204	12/2007	Rankin	N/A	N/A
2008/0091261	12/2007	Long et al.	N/A	N/A
2008/0097595	12/2007	Gabbay	N/A	N/A
2008/0132989	12/2007	Snow et al.	N/A	N/A
2008/0140003	12/2007	Bei et al.	N/A	N/A
2008/0147182	12/2007	Righini et al.	N/A	N/A
2008/0161910	12/2007	Revuelta et al.	N/A	N/A
2008/0167705	12/2007	Agnew	N/A	N/A
2008/0167714	12/2007	St. Goar et al.	N/A	N/A
2008/0188929	12/2007	Schreck	N/A	N/A
2008/0195200	12/2007	Vidlund et al.	N/A	N/A
2008/0200980	12/2007	Robin et al.	N/A	N/A
2008/0208328	12/2007	Antocci et al.	N/A	N/A
2008/0208332	12/2007	Lamphere et al.	N/A	N/A
2008/0221672	12/2007	Lamphere et al.	N/A	N/A
2008/0234814	12/2007	Salahieh et al.	N/A	N/A
2008/0243245	12/2007	Thambar et al.	N/A	N/A
2008/0255580	12/2007	Hoffman et al.	N/A	N/A
2008/0262609	12/2007	Gross et al.	N/A	N/A
2008/0269879	12/2007	Sathe et al.	N/A	N/A
2008/0281411	12/2007	Berrekouw	N/A	N/A
2008/0294234	12/2007	Hartley et al.	N/A	N/A
2009/0005863	12/2008	Goetz et al.	N/A	N/A
2009/0036966	12/2008	O'Connor et al.	N/A	N/A
2009/0054969	12/2008	Salahieh et al.	N/A	N/A
2009/0082844	12/2008	Zacharias et al.	N/A	N/A
2009/0088836	12/2008	Bishop et al.	N/A	N/A
2009/0099554	12/2008	Forster et al.	N/A	N/A
2009/0099650	12/2008	Bolduc et al.	N/A	N/A
2009/0112159	12/2008	Slattery et al.	N/A	N/A
2009/0125098	12/2008	Chuter	N/A	N/A
2009/0157175	12/2008	Benichou	N/A	N/A
2009/0163934	12/2008	Raschdorf, Jr. et al.	N/A	N/A
2009/0171363	12/2008	Chocron	N/A	N/A
2009/0177278	12/2008	Spence	N/A	N/A
2009/0210052	12/2008	Forster et al.	N/A	N/A
2009/0222081	12/2008	Linder et al.	N/A	N/A
2009/0240320	12/2008	Tuval et al.	N/A	N/A
2009/0241656	12/2008	Jacquemin	N/A	N/A
2009/0259306	12/2008	Rowe	N/A	N/A
2009/0264859	12/2008	Mas	N/A	N/A
2009/0264994	12/2008	Saadat	N/A	N/A
2009/0276040	12/2008	Rowe et al.	N/A	N/A
2009/0281619	12/2008	Le et al.	N/A	N/A
2009/0287304	12/2008	Dahlgren et al.	N/A	N/A
2009/0299449	12/2008	Styrc	N/A	N/A

2009/0306768	12/2008	Quardi	N/A	N/A
2009/0319037	12/2008	Rowe et al.	N/A	N/A
2010/0022823	12/2009	Goldfarb	N/A	N/A
2010/0023117	12/2009	Yoganathan et al.	N/A	N/A
2010/0023120	12/2009	Holecek et al.	N/A	N/A
2010/0036479	12/2009	Hill et al.	N/A	N/A
2010/0049313	12/2009	Alon et al.	N/A	N/A
2010/0069852	12/2009	Kelley	N/A	N/A
2010/0076548	12/2009	Konno	N/A	N/A
2010/0100167	12/2009	Bortlein et al.	N/A	N/A
2010/0114299	12/2009	Ben-Muvhar et al.	N/A	N/A
2010/0131054	12/2009	Tuval et al.	N/A	N/A
2010/0137979	12/2009	Tuval et al.	N/A	N/A
2010/0160958	12/2009	Clark	N/A	N/A
2010/0161036	12/2009	Pintor et al.	N/A	N/A
2010/0161042	12/2009	Maisano et al.	N/A	N/A
2010/0174363	12/2009	Castro	N/A	N/A
2010/0179643	12/2009	Shalev	N/A	N/A
2010/0179648	12/2009	Richter et al.	N/A	N/A
2010/0179649	12/2009	Richter et al.	N/A	N/A
2010/0185277	12/2009	Braido et al.	N/A	N/A
2010/0217382	12/2009	Chau et al.	N/A	N/A
2010/0222810	12/2009	DeBeer et al.	N/A	N/A
2010/0228285	12/2009	Miles et al.	N/A	N/A
2010/0234940	12/2009	Dolan	N/A	N/A
2010/0249908	12/2009	Chau et al.	N/A	N/A
2010/0249917	12/2009	Zhang	N/A	N/A
2010/0256737	12/2009	Pollock et al.	N/A	N/A
2010/0262232	12/2009	Annest	N/A	N/A
2010/0280603	12/2009	Maisano et al.	N/A	N/A
2010/0280606	12/2009	Naor	N/A	N/A
2010/0312333	12/2009	Navia et al.	N/A	N/A
2010/0324595	12/2009	Linder et al.	N/A	N/A
2010/0331971	12/2009	Keranen et al.	N/A	N/A
2011/0004227	12/2010	Goldfarb et al.	N/A	N/A
2011/0004296	12/2010	Lutter et al.	N/A	N/A
2011/0004299	12/2010	Navia et al.	N/A	N/A
2011/0015729	12/2010	Jimenez et al.	N/A	N/A
2011/0015731	12/2010	Carpentier et al.	N/A	N/A
2011/0015739	12/2010	Cheung et al.	N/A	N/A
2011/0021985	12/2010	Spargias	N/A	N/A
2011/0022165	12/2010	Oba et al.	N/A	N/A
2011/0029067	12/2010	McGuckin, Jr. et al.	N/A	N/A
2011/0029072	12/2010	Gabbay	N/A	N/A
2011/0040374	12/2010	Goetz et al.	N/A	N/A
2011/0040375	12/2010	Letac et al.	N/A	N/A
2011/0046662	12/2010	Mosznier et al.	N/A	N/A
2011/0054466	12/2010	Rothstein et al.	N/A	N/A
2011/0054596	12/2010	Taylor	N/A	N/A
2011/0054598	12/2010	Johnson	N/A	N/A
2011/0066233	12/2010	Thornton et al.	N/A	N/A
2011/0071626	12/2010	Wright et al.	N/A	N/A
2011/0077730	12/2010	Fenster	N/A	N/A
2011/0082538	12/2010	Dahlgren et al.	N/A	N/A
2011/0087322	12/2010	Letac et al.	N/A	N/A

2011/0093063	12/2010	Schreck	N/A	N/A
2011/0098525	12/2010	Kermode et al.	N/A	N/A
2011/0106247	12/2010	Miller et al.	N/A	N/A
2011/0112625	12/2010	Ben-Muvhar et al.	N/A	N/A
2011/0112632	12/2010	Chau et al.	N/A	N/A
2011/0113768	12/2010	Bauer et al.	N/A	N/A
2011/0118830	12/2010	Liddicoat et al.	N/A	N/A
2011/0125257	12/2010	Seguin et al.	N/A	N/A
2011/0125258	12/2010	Centola	N/A	N/A
2011/0137326	12/2010	Bachman	N/A	N/A
2011/0137397	12/2010	Chau et al.	N/A	N/A
2011/0137409	12/2010	Yang et al.	N/A	N/A
2011/0137410	12/2010	Hacohen	N/A	N/A
2011/0144742	12/2010	Madrid et al.	N/A	N/A
2011/0166636	12/2010	Rowe	N/A	N/A
2011/0172784	12/2010	Richter	N/A	N/A
2011/0178597	12/2010	Navia et al.	N/A	N/A
2011/0184510	12/2010	Maisano et al.	N/A	N/A
2011/0190877	12/2010	Lane et al.	N/A	N/A
2011/0190879	12/2010	Bobo et al.	N/A	N/A
2011/0202076	12/2010	Richter	N/A	N/A
2011/0208283	12/2010	Rust	N/A	N/A
2011/0208293	12/2010	Tabor	N/A	N/A
2011/0208298	12/2010	Tuval et al.	N/A	N/A
2011/0213459	12/2010	Garrison et al.	N/A	N/A
2011/0213461	12/2010	Seguin et al.	N/A	N/A
2011/0218619	12/2010	Benichou et al.	N/A	N/A
2011/0218620	12/2010	Meiri et al.	N/A	N/A
2011/0224785	12/2010	Hacohen	N/A	N/A
2011/0238159	12/2010	Guyenot et al.	N/A	N/A
2011/0245911	12/2010	Quill et al.	N/A	N/A
2011/0245917	12/2010	Savage et al.	N/A	N/A
2011/0251675	12/2010	Dwork	N/A	N/A
2011/0251676	12/2010	Sweeney et al.	N/A	N/A
2011/0251678	12/2010	Eidenschink et al.	N/A	N/A
2011/0251679	12/2010	Weimeyer et al.	N/A	N/A
2011/0251680	12/2010	Tran et al.	N/A	N/A
2011/0251682	12/2010	Murray, III et al.	N/A	N/A
2011/0251683	12/2010	Tabor	N/A	N/A
2011/0257721	12/2010	Tabor	N/A	N/A
2011/0257729	12/2010	Spenser et al.	N/A	N/A
2011/0257736	12/2010	Marquez et al.	N/A	N/A
2011/0257737	12/2010	Fogarty et al.	N/A	N/A
2011/0264191	12/2010	Rothstein	N/A	N/A
2011/0264196	12/2010	Savage et al.	N/A	N/A
2011/0264198	12/2010	Murray, III et al.	N/A	N/A
2011/0264199	12/2010	Tran et al.	N/A	N/A
2011/0264200	12/2010	Tran et al.	N/A	N/A
2011/0264201	12/2010	Yeung	N/A	N/A
2011/0264202	12/2010	Murray, III et al.	N/A	N/A
2011/0264203	12/2010	Dwork et al.	N/A	N/A
2011/0264206	12/2010	Tabor	N/A	N/A
2011/0264208	12/2010	Duffy	N/A	N/A
2011/0270276	12/2010	Rothstein et al.	N/A	N/A
2011/0271967	12/2010	Mortier et al.	N/A	N/A

2011/0282438	12/2010	Drews et al.	N/A	N/A
2011/0282439	12/2010	Thill et al.	N/A	N/A
2011/0282440	12/2010	Cao	N/A	N/A
2011/0283514	12/2010	Fogarty et al.	N/A	N/A
2011/0288632	12/2010	White	N/A	N/A
2011/0288634	12/2010	Tuval et al.	N/A	N/A
2011/0295354	12/2010	Bueche et al.	N/A	N/A
2011/0295363	12/2010	Girard et al.	N/A	N/A
2011/0301688	12/2010	Dolan	N/A	N/A
2011/0301698	12/2010	Miller et al.	N/A	N/A
2011/0301701	12/2010	Padala et al.	N/A	N/A
2011/0301702	12/2010	Rust et al.	N/A	N/A
2011/0306916	12/2010	Nitzan et al.	N/A	N/A
2011/0307049	12/2010	Kao	N/A	N/A
2011/0313452	12/2010	Carley et al.	N/A	N/A
2011/0313515	12/2010	Quadri et al.	N/A	N/A
2011/0319989	12/2010	Lane et al.	N/A	N/A
2011/0319991	12/2010	Hariton et al.	N/A	N/A
2012/0010694	12/2011	Lutter et al.	N/A	N/A
2012/0016468	12/2011	Robin et al.	N/A	N/A
2012/0022629	12/2011	Perera et al.	N/A	N/A
2012/0022633	12/2011	Olson et al.	N/A	N/A
2012/0022637	12/2011	Ben-Movhar et al.	N/A	N/A
2012/0022639	12/2011	Hacohen et al.	N/A	N/A
2012/0022640	12/2011	Gross et al.	N/A	N/A
2012/0035703	12/2011	Lutter et al.	N/A	N/A
2012/0035713	12/2011	Lutter et al.	N/A	N/A
2012/0035722	12/2011	Tuval et al.	N/A	N/A
2012/0041547	12/2011	Duffy et al.	N/A	N/A
2012/0041551	12/2011	Spenser et al.	N/A	N/A
2012/0046738	12/2011	Lau et al.	N/A	N/A
2012/0046742	12/2011	Tuval et al.	N/A	N/A
2012/0053676	12/2011	Ku et al.	N/A	N/A
2012/0053680	12/2011	Bolling et al.	N/A	N/A
2012/0053682	12/2011	Kovalsky et al.	N/A	N/A
2012/0053688	12/2011	Fogarty et al.	N/A	N/A
2012/0059454	12/2011	Millwee et al.	N/A	N/A
2012/0059458	12/2011	Buchbinder et al.	N/A	N/A
2012/0065464	12/2011	Ellis et al.	N/A	N/A
2012/0078237	12/2011	Wang et al.	N/A	N/A
2012/0078353	12/2011	Quadri et al.	N/A	N/A
2012/0078357	12/2011	Conklin	N/A	N/A
2012/0083832	12/2011	Delaloye et al.	N/A	N/A
2012/0083839	12/2011	Letac et al.	N/A	N/A
2012/0083879	12/2011	Eberhardt et al.	N/A	N/A
2012/0089223	12/2011	Nguyen et al.	N/A	N/A
2012/0101570	12/2011	Tuval et al.	N/A	N/A
2012/0101571	12/2011	Thambar et al.	N/A	N/A
2012/0101572	12/2011	Kovalsky et al.	N/A	N/A
2012/0123511	12/2011	Brown	N/A	N/A
2012/0123529	12/2011	Levi et al.	N/A	N/A
2012/0123530	12/2011	Carpentier et al.	N/A	N/A
2012/0130473	12/2011	Norris et al.	N/A	N/A
2012/0130474	12/2011	Buckley	N/A	N/A
2012/0130475	12/2011	Shaw	N/A	N/A

2012/0136434	12/2011	Carpentier et al.	N/A	N/A
2012/0150218	12/2011	Sandgren et al.	N/A	N/A
2012/0165915	12/2011	Melsheimer et al.	N/A	N/A
2012/0165930	12/2011	Gifford, III et al.	N/A	N/A
2012/0179244	12/2011	Schankereli et al.	N/A	N/A
2012/0197292	12/2011	Chin-Chen et al.	N/A	N/A
2012/0283824	12/2011	Lutter et al.	N/A	N/A
2012/0290062	12/2011	McNamara et al.	N/A	N/A
2012/0296360	12/2011	Norris et al.	N/A	N/A
2012/0296418	12/2011	Bonyuet et al.	N/A	N/A
2012/0300063	12/2011	Majkrzak et al.	N/A	N/A
2012/0310328	12/2011	Olson et al.	N/A	N/A
2012/0323316	12/2011	Chau et al.	N/A	N/A
2012/0330408	12/2011	Hillukka et al.	N/A	N/A
2013/0006347	12/2012	McHugo	N/A	N/A
2013/0018450	12/2012	Hunt	N/A	N/A
2013/0018458	12/2012	Yohanan et al.	N/A	N/A
2013/0030519	12/2012	Tran et al.	N/A	N/A
2013/0035759	12/2012	Gross et al.	N/A	N/A
2013/0041451	12/2012	Patterson et al.	N/A	N/A
2013/0046373	12/2012	Cartledge et al.	N/A	N/A
2013/0066341	12/2012	Ketai et al.	N/A	N/A
2013/0066342	12/2012	Dell	N/A	N/A
2013/0079872	12/2012	Gallagher	N/A	N/A
2013/0116780	12/2012	Miller et al.	N/A	N/A
2013/0123896	12/2012	Bloss et al.	N/A	N/A
2013/0123900	12/2012	Eblacas et al.	N/A	N/A
2013/0150945	12/2012	Crawford et al.	N/A	N/A
2013/0150956	12/2012	Yohanan et al.	N/A	N/A
2013/0158647	12/2012	Norris et al.	N/A	N/A
2013/0165930	12/2012	Lehmann	N/A	N/A
2013/0166017	12/2012	Cartledge et al.	N/A	N/A
2013/0166022	12/2012	Conklin	N/A	N/A
2013/0172978	12/2012	Vidlund et al.	N/A	N/A
2013/0172992	12/2012	Gross et al.	N/A	N/A
2013/0190861	12/2012	Chau et al.	N/A	N/A
2013/0211501	12/2012	Buckley et al.	N/A	N/A
2013/0245742	12/2012	Norris	N/A	N/A
2013/0253543	12/2012	Rolando et al.	N/A	N/A
2013/0253643	12/2012	Rolando et al.	N/A	N/A
2013/0261737	12/2012	Costello	N/A	N/A
2013/0261738	12/2012	Clague et al.	N/A	N/A
2013/0274870	12/2012	Lombardi et al.	N/A	N/A
2013/0282059	12/2012	Ketai et al.	N/A	N/A
2013/0289711	12/2012	Liddy et al.	N/A	N/A
2013/0289740	12/2012	Liddy et al.	N/A	N/A
2013/0297013	12/2012	Klima et al.	N/A	N/A
2013/0304197	12/2012	Buchbinder et al.	N/A	N/A
2013/0304200	12/2012	McLean et al.	N/A	N/A
2013/0310928	12/2012	Morriss et al.	N/A	N/A
2013/0325114	12/2012	McLean et al.	N/A	N/A
2013/0331929	12/2012	Mitra et al.	N/A	N/A
2014/0000112	12/2013	Braido et al.	N/A	N/A
2014/0005778	12/2013	Buchbinder et al.	N/A	N/A
2014/0018911	12/2013	Zhou et al.	N/A	N/A

2014/0018915	12/2013	Biadillah et al.	N/A	N/A
2014/0031928	12/2013	Murphy et al.	N/A	N/A
2014/0046430	12/2013	Shaw	N/A	N/A
2014/0052237	12/2013	Lane et al.	N/A	N/A
2014/0067050	12/2013	Costello et al.	N/A	N/A
2014/0067054	12/2013	Chau	N/A	N/A
2014/0081376	12/2013	Burkart et al.	N/A	N/A
2014/0106951	12/2013	Brandon	N/A	N/A
2014/0120287	12/2013	Jacoby et al.	N/A	N/A
2014/0121749	12/2013	Roeder	N/A	N/A
2014/0121763	12/2013	Duffy et al.	N/A	N/A
2014/0135894	12/2013	Norris et al.	N/A	N/A
2014/0135895	12/2013	Andress et al.	N/A	N/A
2014/0142681	12/2013	Norris	N/A	N/A
2014/0142688	12/2013	Duffy et al.	N/A	N/A
2014/0148891	12/2013	Johnson	N/A	N/A
2014/0163690	12/2013	White	N/A	N/A
2014/0172069	12/2013	Roeder et al.	N/A	N/A
2014/0172077	12/2013	Bruchman et al.	N/A	N/A
2014/0172082	12/2013	Bruchman et al.	N/A	N/A
2014/0188210	12/2013	Beard et al.	N/A	N/A
2014/0188221	12/2013	Chung et al.	N/A	N/A
2014/0194981	12/2013	Menk et al.	N/A	N/A
2014/0194983	12/2013	Kovalsky et al.	N/A	N/A
2014/0207231	12/2013	Hacohen et al.	N/A	N/A
2014/0214157	12/2013	Börtlein et al.	N/A	N/A
2014/0214159	12/2013	Vidlund et al.	N/A	N/A
2014/0222136	12/2013	Geist et al.	N/A	N/A
2014/0222142	12/2013	Kovalsky et al.	N/A	N/A
2014/0236287	12/2013	Clague et al.	N/A	N/A
2014/0236289	12/2013	Alkhatib	N/A	N/A
2014/0249622	12/2013	Carmi et al.	N/A	N/A
2014/0257461	12/2013	Robinson et al.	N/A	N/A
2014/0257467	12/2013	Lane et al.	N/A	N/A
2014/0257475	12/2013	Gross et al.	N/A	N/A
2014/0257476	12/2013	Montorfano et al.	N/A	N/A
2014/0277358	12/2013	Slazas	N/A	N/A
2014/0277409	12/2013	Bortlein et al.	N/A	N/A
2014/0277411	12/2013	Börtlein et al.	N/A	N/A
2014/0277412	12/2013	Börtlein et al.	N/A	N/A
2014/0277418	12/2013	Miller	N/A	N/A
2014/0277422	12/2013	Ratz et al.	N/A	N/A
2014/0277427	12/2013	Ratz et al.	N/A	N/A
2014/0296962	12/2013	Cartledge et al.	N/A	N/A
2014/0296969	12/2013	Tegels et al.	N/A	N/A
2014/0324164	12/2013	Gross et al.	N/A	N/A
2014/0331475	12/2013	Duffy et al.	N/A	N/A
2014/0336744	12/2013	Tani et al.	N/A	N/A
2014/0343670	12/2013	Bakis et al.	N/A	N/A
2014/0350662	12/2013	Vaturi	N/A	N/A
2014/0350670	12/2013	Keränen	N/A	N/A
2014/0358222	12/2013	Gorman, III et al.	N/A	N/A
2014/0358224	12/2013	Tegels et al.	N/A	N/A
2014/0379065	12/2013	Johnson et al.	N/A	N/A
2014/0379074	12/2013	Spence et al.	N/A	N/A

2014/0379076	12/2013	Vidlund et al.	N/A	N/A
2015/0018944	12/2014	O'Connor et al.	N/A	N/A
2015/0032205	12/2014	Matheny	N/A	N/A
2015/0045880	12/2014	Hacohen	N/A	N/A
2015/0045881	12/2014	Lim	N/A	N/A
2015/0094802	12/2014	Buchbinder et al.	N/A	N/A
2015/0119970	12/2014	Nakayama et al.	N/A	N/A
2015/0127097	12/2014	Neumann et al.	N/A	N/A
2015/0142100	12/2014	Morriss et al.	N/A	N/A
2015/0142103	12/2014	Vidlund	N/A	N/A
2015/0157457	12/2014	Hacohen	N/A	N/A
2015/0157458	12/2014	Thambar et al.	N/A	N/A
2015/0164640	12/2014	McLean et al.	N/A	N/A
2015/0173896	12/2014	Richter et al.	N/A	N/A
2015/0173897	12/2014	Raanani et al.	N/A	N/A
2015/0196390	12/2014	Ma et al.	N/A	N/A
2015/0196393	12/2014	Vidlund et al.	N/A	N/A
2015/0216661	12/2014	Hacohen et al.	N/A	N/A
2015/0238313	12/2014	Spence et al.	N/A	N/A
2015/0245934	12/2014	Lombardi et al.	N/A	N/A
2015/0272730	12/2014	Melnick et al.	N/A	N/A
2015/0272731	12/2014	Racchini et al.	N/A	N/A
2015/0272734	12/2014	Sheps et al.	N/A	N/A
2015/0282964	12/2014	Beard et al.	N/A	N/A
2015/0320556	12/2014	Levi et al.	N/A	N/A
2015/0327994	12/2014	Morriss et al.	N/A	N/A
2015/0328000	12/2014	Ratz et al.	N/A	N/A
2015/0335429	12/2014	Morriss et al.	N/A	N/A
2015/0342736	12/2014	Rabito et al.	N/A	N/A
2015/0351903	12/2014	Morriss et al.	N/A	N/A
2015/0351904	12/2014	Cooper et al.	N/A	N/A
2015/0351906	12/2014	Hammer et al.	N/A	N/A
2015/0359629	12/2014	Ganesan et al.	N/A	N/A
2016/0008129	12/2015	Siegel	N/A	N/A
2016/0030169	12/2015	Shahriari	N/A	N/A
2016/0030171	12/2015	Quijano et al.	N/A	N/A
2016/0089482	12/2015	Siegenthaler	N/A	N/A
2016/0095700	12/2015	Righini	N/A	N/A
2016/0100939	12/2015	Armstrong et al.	N/A	N/A
2016/0106539	12/2015	Buchbinder et al.	N/A	N/A
2016/0113766	12/2015	Ganesan et al.	N/A	N/A
2016/0113768	12/2015	Ganesan et al.	N/A	N/A
2016/0125160	12/2015	Heneghan et al.	N/A	N/A
2016/0157862	12/2015	Hernandez et al.	N/A	N/A
2016/0175095	12/2015	Dienno et al.	N/A	N/A
2016/0213473	12/2015	Hacohen et al.	N/A	N/A
2016/0220367	12/2015	Barrett	N/A	N/A
2016/0228247	12/2015	Maimon et al.	N/A	N/A
2016/0242902	12/2015	Morriss et al.	N/A	N/A
2016/0270911	12/2015	Ganesan et al.	N/A	N/A
2016/0296330	12/2015	Hacohen	N/A	N/A
2016/0310268	12/2015	Oba et al.	N/A	N/A
2016/0310274	12/2015	Gross et al.	N/A	N/A
2016/0317301	12/2015	Quadri et al.	N/A	N/A
2016/0317305	12/2015	Pelled et al.	N/A	N/A

2016/0324633	12/2015	Gross et al.	N/A	N/A
2016/0324635	12/2015	Vidlund et al.	N/A	N/A
2016/0324640	12/2015	Gifford et al.	N/A	N/A
2016/0331526	12/2015	Schweich et al.	N/A	N/A
2016/0331527	12/2015	Vidlund et al.	N/A	N/A
2016/0338706	12/2015	Rowe	N/A	N/A
2016/0367360	12/2015	Cartledge et al.	N/A	N/A
2016/0367368	12/2015	Vidlund et al.	N/A	N/A
2016/0374801	12/2015	Jimenez et al.	N/A	N/A
2016/0374802	12/2015	Levi et al.	N/A	N/A
2017/0042678	12/2016	Ganesan et al.	N/A	N/A
2017/0049435	12/2016	Sauer et al.	N/A	N/A
2017/0056166	12/2016	Ratz et al.	N/A	N/A
2017/0056171	12/2016	Cooper et al.	N/A	N/A
2017/0065407	12/2016	Hacohen et al.	N/A	N/A
2017/0065411	12/2016	Grundeman et al.	N/A	N/A
2017/0100236	12/2016	Robertson et al.	N/A	N/A
2017/0128205	12/2016	Tamir et al.	N/A	N/A
2017/0135816	12/2016	Lashinski et al.	N/A	N/A
2017/0189174	12/2016	Braido et al.	N/A	N/A
2017/0196688	12/2016	Christianson et al.	N/A	N/A
2017/0196692	12/2016	Kirk et al.	N/A	N/A
2017/0209264	12/2016	Chau et al.	N/A	N/A
2017/0216026	12/2016	Quill et al.	N/A	N/A
2017/0224323	12/2016	Rowe et al.	N/A	N/A
2017/0231757	12/2016	Gassler	N/A	N/A
2017/0231759	12/2016	Geist et al.	N/A	N/A
2017/0231760	12/2016	Lane et al.	N/A	N/A
2017/0231766	12/2016	Hariton et al.	N/A	N/A
2017/0239048	12/2016	Goldfarb et al.	N/A	N/A
2017/0252159	12/2016	Hacohen et al.	N/A	N/A
2017/0266003	12/2016	Hammer et al.	N/A	N/A
2017/0333183	12/2016	Backus	N/A	N/A
2017/0333187	12/2016	Hariton et al.	N/A	N/A
2017/0360426	12/2016	Hacohen et al.	N/A	N/A
2017/0367823	12/2016	Hariton et al.	N/A	N/A
2018/0000580	12/2017	Wallace et al.	N/A	N/A
2018/0014930	12/2017	Hariton et al.	N/A	N/A
2018/0014932	12/2017	Hammer et al.	N/A	N/A
2018/0021129	12/2017	Peterson et al.	N/A	N/A
2018/0028215	12/2017	Cohen	N/A	N/A
2018/0049873	12/2017	Manash et al.	N/A	N/A
2018/0055628	12/2017	Patel et al.	N/A	N/A
2018/0055630	12/2017	Patel et al.	N/A	N/A
2018/0098850	12/2017	Rafiee et al.	N/A	N/A
2018/0116790	12/2017	Ratz et al.	N/A	N/A
2018/0132999	12/2017	Perouse	N/A	N/A
2018/0147059	12/2017	Hammer et al.	N/A	N/A
2018/0153687	12/2017	Hariton et al.	N/A	N/A
2018/0153689	12/2017	Maimon et al.	N/A	N/A
2018/0161159	12/2017	Lee et al.	N/A	N/A
2018/0177594	12/2017	Patel et al.	N/A	N/A
2018/0206983	12/2017	Noe et al.	N/A	N/A
2018/0214263	12/2017	Rolando et al.	N/A	N/A
2018/0243086	12/2017	Barbarino et al.	N/A	N/A

2018/0250126	12/2017	O'connor et al.	N/A	N/A
2018/0250147	12/2017	Syed	N/A	N/A
2018/0296333	12/2017	Dixon et al.	N/A	N/A
2018/0296336	12/2017	Cooper et al.	N/A	N/A
2018/0296341	12/2017	Noe et al.	N/A	N/A
2018/0325671	12/2017	Abunassar et al.	N/A	N/A
2018/0344457	12/2017	Gross et al.	N/A	N/A
2018/0344490	12/2017	Fox et al.	N/A	N/A
2018/0353294	12/2017	Calomeni et al.	N/A	N/A
2018/0360457	12/2017	Ellis et al.	N/A	N/A
2019/0000613	12/2018	Delgado et al.	N/A	N/A
2019/0015200	12/2018	Delgado et al.	N/A	N/A
2019/0021852	12/2018	Delgado et al.	N/A	N/A
2019/0021857	12/2018	Hacohen et al.	N/A	N/A
2019/0053896	12/2018	Adamek-bowers et al.	N/A	N/A
2019/0060060	12/2018	Chau et al.	N/A	N/A
2019/0060068	12/2018	Cope et al.	N/A	N/A
2019/0060070	12/2018	Groothuis et al.	N/A	N/A
2019/0069997	12/2018	Ratz et al.	N/A	N/A
2019/0083261	12/2018	Perszyk et al.	N/A	N/A
2019/0105153	12/2018	Barash et al.	N/A	N/A
2019/0117391	12/2018	Humair	N/A	N/A
2019/0167423	12/2018	Hariton et al.	N/A	N/A
2019/0175339	12/2018	Vidlund	N/A	N/A
2019/0175342	12/2018	Hariton et al.	N/A	N/A
2019/0183639	12/2018	Moore	N/A	N/A
2019/0183644	12/2018	Hacohen	N/A	N/A
2019/0192295	12/2018	Spence et al.	N/A	N/A
2019/0216602	12/2018	Lozonschi	N/A	N/A
2019/0321172	12/2018	Gross et al.	N/A	N/A
2019/0336280	12/2018	Naor	N/A	N/A
2019/0350701	12/2018	Adamek-bowers et al.	N/A	N/A
2019/0365530	12/2018	Hoang et al.	N/A	N/A
2019/0388218	12/2018	Vidlund et al.	N/A	N/A
2019/0388220	12/2018	Vidlund et al.	N/A	N/A
2020/0000449	12/2019	Goldfarb et al.	N/A	N/A
2020/0000579	12/2019	Manash et al.	N/A	N/A
2020/0015964	12/2019	Noe et al.	N/A	N/A
2020/0060818	12/2019	Geist et al.	N/A	N/A
2020/0078002	12/2019	Hacohen et al.	N/A	N/A
2020/0163761	12/2019	Hariton et al.	N/A	N/A
2020/0246140	12/2019	Hariton et al.	N/A	N/A
2020/0261094	12/2019	Goldfarb et al.	N/A	N/A
2020/0330221	12/2019	Hacohen	N/A	N/A
2020/0330227	12/2019	Hacohen	N/A	N/A
2021/0093449	12/2020	Hariton et al.	N/A	N/A
2021/0106419	12/2020	Abunassar	N/A	N/A
2021/0113331	12/2020	Quadri et al.	N/A	N/A
2021/0137680	12/2020	Kizuka et al.	N/A	N/A
2021/0259835	12/2020	Tyler, II et al.	N/A	N/A
2022/0000612	12/2021	Hacohen	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2822801	12/2005	CA	N/A
103974674	12/2013	CN	N/A

0170262	12/1985	EP	N/A
1264582	12/2001	EP	N/A
1768630	12/2014	EP	N/A
2739214	12/2017	EP	N/A
3417813	12/2017	EP	N/A
S53152790	12/1977	JP	N/A
20010046894	12/2000	KR	N/A
1998/043557	12/1997	WO	N/A
1999/030647	12/1998	WO	N/A
2000047139	12/1999	WO	N/A
2001062189	12/2000	WO	N/A
01/82832	12/2000	WO	N/A
2003/020179	12/2002	WO	N/A
2003/028558	12/2002	WO	N/A
2004/108191	12/2003	WO	N/A
2005/107650	12/2004	WO	N/A
2006/007401	12/2005	WO	N/A
06/054930	12/2005	WO	N/A
2006/070372	12/2005	WO	N/A
2006/086434	12/2005	WO	N/A
2006/089236	12/2005	WO	N/A
2006/116558	12/2005	WO	N/A
2006/128193	12/2005	WO	N/A
2007/059252	12/2006	WO	N/A
08/013915	12/2007	WO	N/A
2008/029296	12/2007	WO	N/A
2008/070797	12/2007	WO	N/A
2008/103722	12/2007	WO	N/A
09/033469	12/2008	WO	N/A
09/053497	12/2008	WO	N/A
2009/091509	12/2008	WO	N/A
2010/005827	12/2009	WO	N/A
2010/006627	12/2009	WO	N/A
2010/037141	12/2009	WO	N/A
2010/045297	12/2009	WO	N/A
2010/057262	12/2009	WO	N/A
2010/073246	12/2009	WO	N/A
2010/081033	12/2009	WO	N/A
2010/121076	12/2009	WO	N/A
2011/025972	12/2010	WO	N/A
2011/069048	12/2010	WO	N/A
2011/089601	12/2010	WO	N/A
2011/106137	12/2010	WO	N/A
2011/111047	12/2010	WO	N/A
01/87190	12/2010	WO	N/A
2011/137531	12/2010	WO	N/A
2011143263	12/2010	WO	N/A
2011/154942	12/2010	WO	N/A
2012/011108	12/2011	WO	N/A
2012/024428	12/2011	WO	N/A
2012/036740	12/2011	WO	N/A
2012/048035	12/2011	WO	N/A
2012/127309	12/2011	WO	N/A
2012/177942	12/2011	WO	N/A
2013/021374	12/2012	WO	N/A

2013/021375	12/2012	WO	N/A
2013021384	12/2012	WO	N/A
2013/059747	12/2012	WO	N/A
2013/072496	12/2012	WO	N/A
2013/078497	12/2012	WO	N/A
2013114214	12/2012	WO	N/A
2013/128436	12/2012	WO	N/A
2013/175468	12/2012	WO	N/A
2014/022124	12/2013	WO	N/A
2014/076696	12/2013	WO	N/A
2014/115149	12/2013	WO	N/A
2014/121280	12/2013	WO	N/A
2014/145338	12/2013	WO	N/A
2014/164364	12/2013	WO	N/A
2014/194178	12/2013	WO	N/A
2015/173794	12/2014	WO	N/A
2015/191923	12/2014	WO	N/A
2016/016899	12/2015	WO	N/A
2016/093877	12/2015	WO	N/A
2016/125160	12/2015	WO	N/A
2017/223486	12/2016	WO	N/A
2018/025260	12/2017	WO	N/A
2018/025263	12/2017	WO	N/A
2018/029680	12/2017	WO	N/A
2018/039631	12/2017	WO	N/A
2018/106837	12/2017	WO	N/A
2018/112429	12/2017	WO	N/A
2018/118717	12/2017	WO	N/A
2018/131042	12/2017	WO	N/A
2018/131043	12/2017	WO	N/A
2019/026059	12/2018	WO	N/A
2019/030753	12/2018	WO	N/A
2019027507	12/2018	WO	N/A
2019/077595	12/2018	WO	N/A
2019/116369	12/2018	WO	N/A
2019/138400	12/2018	WO	N/A
2019/195860	12/2018	WO	N/A
2019/202579	12/2018	WO	N/A
2020/058972	12/2019	WO	N/A
2021/156866	12/2020	WO	N/A
2021/186424	12/2020	WO	N/A

OTHER PUBLICATIONS

An Office Action dated Nov. 23, 2012, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

An Office Action dated Dec. 31, 2012, which issued during the prosecution of U.S. Appl. No. 13/044,694. cited by applicant

An Office Action dated Feb. 6, 2013, which, issued during the prosecution of U.S. Appl. No. 13/412,814. cited by applicant

Langer F et al., "Ring plus String: 'Papillary muscle repositioning as an adjunctive repair technique for ischemic mitral regurgitation," J Thorac Cardiovasc Surg 133:247-9, Jan. 2007. cited by applicant

Langer F et al., "Ring+String: Successful repair technique for ischemic mitral regurgitation with severe leaflet tethering," Circulation 120[suppl 1]: S85-S91, Sep. 2009. cited by applicant

"Transcatheter Valve-in-Valve Implantation for Failed Bioprosthetic Heart Valves", J Webb et al., Circulation. Apr. 2010; 121: 1848-1857. cited by applicant

Jansen, J., Willeke, S., Reul, H. and Rum, G. (1992), Detachable Shape-Memory Sewing Ring for Heart Valves. Artificial Organs, 16:294-297, 1992 (an abstract). cited by applicant

Alexander S. Geha, et al., Replacement of degenerated mitral and aortic bioprostheses without explantation Ann Thorac Surg. Jun. 2001; 72:1509-1514. cited by applicant

An International Search Report and a Written Opinion both dated Oct. 13, 2011 which issued during the prosecution of Applicant's PCT/IL11/00231. cited by applicant

An Office Action dated Jul. 1, 2016, which issued during the prosecution of U.S. Appl. No. 14/161,921. cited by applicant

An International Search Report and a Written Opinion both dated Dec. 5, 2011, which issued during the prosecution of Applicant's PCT/IL11/00582. cited by applicant

An Office Action dated May 29, 2012, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

U.S. Appl. No. 61/555,160, filed Nov. 3, 2011. cited by applicant

U.S. Appl. No. 61/525,281, filed Aug. 19, 2011. cited by applicant

U.S. Appl. No. 61/537,276, filed Sep. 21, 2011. cited by applicant

U.S. Appl. No. 61/515,372, filed Aug. 5, 2011. cited by applicant

U.S. Appl. No. 61/492,449, filed Jun. 2, 2011. cited by applicant

U.S. Appl. No. 61/588,892, filed Jan. 20, 2012. cited by applicant

An International Search Report and a Written Opinion both dated Feb. 6, 2013, which issued during the prosecution of Applicant's PCT/IL12/00292. cited by applicant

An International Search Report and a Written Opinion both dated Feb. 6, 2013, which issued during the prosecution of Applicant's PCT/IL12/00293. cited by applicant

An Office Action dated Nov. 28, 2012, which issued during the prosecution of U.S. Appl. No. 12/961,721. cited by applicant

An Office Action dated Feb. 15, 2013, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

An Office Action dated Feb. 10, 2014, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

An Office Action dated Sep. 19, 2014, which issued during the prosecution of U.S. Appl. No. 13/044,694. cited by applicant

An International Search Report and a Written Opinion both dated Sep. 4, 2014 which issued during the prosecution of Applicant's PCT/IL2014/050087. cited by applicant

Invitation to Pay Additional Fees dated Jun. 12, 2014 PCT/IL2014/050087. cited by applicant

An Office Action dated Jun. 17, 2014, which issued during the prosecution of U.S. Appl. No. 12/961,721. cited by applicant

An Office Action dated Jul. 3, 2014, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

An Office Action dated May 23, 2014, which issued during the prosecution of U.S. Appl. No. 13/412,814. cited by applicant

Dominique Himbert; Mitral Regurgitation and Stenosis from Bioprosthesis and Annuloplasty Failure: Transcatheter approaches and outcomes, 24 pages Oct. 28, 2013. cited by applicant

An International Search Report and a Written Opinion both dated Mar. 17, 2014 which issued during the prosecution of Applicant's PCT/IL2013/050937. cited by applicant

An International Preliminary Report on patentability dated Dec. 2, 2013, which issued during the prosecution of Applicant's PCT/IL11/00582. cited by applicant

An Office Action dated Sep. 12, 2013, which issued during the prosecution of U.S. Appl. No. 13/412,814. cited by applicant

An Office Action dated Aug. 2, 2013, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

An International Preliminary Report on patentability dated Sep. 11, 2012, which issued during the prosecution of Applicant's PCT/IL2011/000231. cited by applicant

An Office Action dated Jul. 2, 2014, which issued during the prosecution of U.S. Appl. No. 13/811,308. cited by applicant

An Office Action dated Jan. 20, 2016, which issued during the prosecution of U.S. Appl. No. 14/161,921. cited by applicant

An Office Action dated Jul. 23, 2013, which issued during the prosecution of U.S. Appl. No. 12/961,721. cited by applicant

An Office Action dated Jul. 18, 2013, which issued during the prosecution of U.S. Appl. No. 13/044,694. cited by applicant

An Office Action dated Nov. 8, 2013, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

An Office Action dated Jun. 4, 2014, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

An Office Action dated Aug. 13, 2012, which issued during the prosecution of U.S. Appl. No. 13/044,694. cited by applicant

An Office Action dated Jul. 2, 2012, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

An Office Action dated Feb. 3, 2014, which issued during the prosecution of U.S. Appl. No. 13/811,308. cited by applicant

An International Preliminary Report on patentability dated Feb. 11, 2014, which issued during the prosecution of Applicant's PCT/IL12/00292. cited by applicant

An International Preliminary Report on patentability dated Feb. 11, 2014, which issued during the prosecution of Applicant's PCT/IL12/00293. cited by applicant

A Notice of Allowance dated Aug. 15, 2014. which issued during the prosecution of U.S. Appl. No. 13/412,814. cited by applicant

An Office Action dated Aug. 14, 2012, which issued during the prosecution of U.S. Appl. No. 12/961,721. cited by applicant

U.S. Appl. No. 61/283,819, filed Dec. 8, 2009. cited by applicant

Notice of Allowance dated Apr. 8, 2016, which issued during the prosecution of U.S. Appl. No. 14/237,258. cited by applicant

U.S. Appl. No. 61/756,034, filed Jan. 24, 2013. cited by applicant

U.S. Appl. No. 61/756,049, filed Jan. 24, 2013. cited by applicant

An International Preliminary Report on Patentability dated Jan. 31, 2017, which issued during the prosecution of Applicant's PCT/IL2015/050792. cited by applicant

U.S. Appl. No. 61/312,412, filed Mar. 10, 2010. cited by applicant

U.S. Appl. No. 62/139,854, filed Mar. 30, 2015. cited by applicant

Notice of Allowance dated Apr. 20, 2018, which issued during the prosecution of U.S. Appl. No. 15/878,206. cited by applicant

An Office Action dated Dec. 10, 2015, which issued during the prosecution of U.S. Appl. No. 14/237,258. cited by applicant

An International Preliminary Report on Patentability dated Jul. 28, 2015, which issued during the prosecution of Applicant's PCT/IL2014/050087. cited by applicant

An Office Action dated Nov. 27, 2015, which issued during the prosecution of U.S. Appl. No. 14/626,267. cited by applicant

An Office Action dated Jan. 21, 2016, which issued during the prosecution of U.S. Appl. No. 14/237,264. cited by applicant

An Office Action dated Jan. 30, 2015, which issued during the prosecution of UK Patent Application No. 1413474.6. cited by applicant

An International Search Report and a Written Opinion both dated May 30, 2016, which issued during the prosecution of Applicant's PCT/IL2016/050125. cited by applicant

An Office Action dated Sep. 26, 2016, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant

An Office Action dated Jan. 18, 2017, which issued during the prosecution of U.S. Appl. No. 14/626,267. cited by applicant

An Office Action dated Feb. 7, 2017, which issued during the prosecution of U.S. Appl. No. 14/689,608. cited by applicant

An Office Action dated Feb. 8, 2017, which issued during the prosecution of UK Patent Application No. 1613219.3. cited by applicant

An Office Action together dated Feb. 10, 2017, which issued during the prosecution of European Patent Application No. 12821522.5. cited by applicant

An International Search Report and a Written Opinion both dated Oct. 27, 2015, which issued during the prosecution of Applicant's PCT/IL2015/050792. cited by applicant

European Search Report dated Feb. 18, 2015, which issued during the prosecution of Applicant's European App No. 12821522.5. cited by applicant

Saturn Project—a novel solution for transcatheter heart valve replacement specifically designed to address clinical therapeutic needs on mitral valve: Dec. 2016. cited by applicant

Righini presentation EuroPCR. May 2015 (Saturn)—(downloaded from: <https://www.pcronline.com/Cases-resources/images/Resources/Course-videos-slides/2015/Cardiovascularinnovation-pipeline-Mitral-and-tricuspid-valve-interventions>). cited by applicant

An Advisory Action dated Apr. 2, 2018, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant

An Office Action dated Jul. 26, 2018, which issued during the prosecution of U.S. Appl. No. 15/872,501. cited by applicant

An Office Action dated May 4, 2018, which issued during the prosecution of U.S. Appl. No. 15/872,501. cited by applicant

An Office Action dated Apr. 20, 2018, which issued during the prosecution of U.S. Appl. No. 15/886,517. cited by applicant

An Office Action dated Aug. 9, 2018, which issued during the prosecution of U.S. Appl. No. 15/899,858. cited by applicant

An Office Action dated Aug. 9, 2018, which issued during the prosecution of U.S. Appl. No. 15/902,403. cited by applicant

An Office Action dated Jun. 28, 2018, which issued during the prosecution of U.S. Appl. No. 29/635,658. cited by applicant

An Office Action dated Jun. 28, 2018, which issued during the prosecution of U.S. Appl. No. 29/635,661. cited by applicant

U.S. Appl. No. 62/030,715, filed Jul. 30, 2014. cited by applicant

An Office Action dated Jun. 6, 2018, which issued during the prosecution of UK Patent Application No. 1720803.4. cited by applicant

An International Search Report and a Written Opinion both dated Jun. 20, 2018, which issued during the prosecution of Applicant's PCT/IL2018/050024. cited by applicant

An Office Action dated Jun. 18, 2018, which issued during the prosecution of UK Patent Application No. 1800399.6. cited by applicant

An Office Action dated Oct. 23, 2017, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant

An Office Action dated Dec. 7, 2017, which issued during the prosecution of U.S. Appl. No. 15/213,791. cited by applicant

Interview Summary dated Feb. 8, 2018, which issued during the prosecution of U.S. Appl. No. 15/213,791. cited by applicant

An Office Action dated Feb. 7, 2018, which issued during the prosecution of U.S. Appl. No. 15/197,069. cited by applicant

An Office Action dated Jan. 5, 2018, which issued during the prosecution of U.S. Appl. No. 15/541,783. cited by applicant

An Office Action dated Feb. 2, 2018, which issued during the prosecution of U.S. Appl. No. 15/329,920. cited by applicant

An Invitation to pay additional fees dated Jan. 2, 2018, which issued during the prosecution of Applicant's PCT/IL2017/050849. cited by applicant

An Invitation to pay additional fees dated Sep. 29, 2017, which issued during the prosecution of Applicant's PCT/IL2017/050873. cited by applicant

European Search Report dated Jun. 29, 2017, which issued during the prosecution of Applicant's European App No. 11809374.9. cited by applicant

An Invitation to pay additional fees dated Oct. 11, 2018, which issued during the prosecution of Applicant's PCT/IL2018/050725. cited by applicant

An Office Action dated Dec. 4, 2018, which issued during the prosecution of U.S. Appl. No. 16/045,059. cited by applicant

An Office Action together with the English translation dated Nov. 5, 2018 which issued during the prosecution of

Chinese Patent Application No. 201680008328.5. cited by applicant

Notice of Allowance dated Sep. 25, 2018. which issued during the prosecution of U.S. Appl. No. 15/188,507. cited by applicant

European Search Report dated Sep. 26, 2018 which issued during the prosecution of Applicant's European App No. 18186784.7. cited by applicant

An Office Action dated Jun. 30, 2015, which issued during the prosecution of U.S. Appl. No. 14/522,987. cited by applicant

An Office Action dated Sep. 29, 2017, which issued during the prosecution of U.S. Appl. No. 15/197,069. cited by applicant

Notice of Allowance dated Oct. 30, 2018, which issued during the prosecution of U.S. Appl. No. 15/197,069. cited by applicant

An Office Action dated Jan. 17, 2018, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant

An Office Action dated Mar. 25, 2015, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

An Office Action dated Feb. 25, 2016, which issued during the prosecution of U.S. Appl. No. 14/522,987. cited by applicant

An Office Action dated Apr. 13, 2016, which issued during the prosecution of U.S. Appl. No. 14/626,267. cited by applicant

An Office Action dated Aug. 28, 2015, which issued during the prosecution of U.S. Appl. No. 14/237,264. cited by applicant

An Office Action dated Apr. 21, 2017, which issued during the prosecution of U.S. Appl. No. 15/213,791. cited by applicant

Maisano (2015) TCR presentation re Cardiovalve. cited by applicant

Notice of Allowance dated Nov. 19, 2018, which issued during the prosecution of U.S. Appl. No. 15/197,069. cited by applicant

Notice of Allowance dated May 10, 2016, which issued during the prosecution of U.S. Appl. No. 14/237,258. cited by applicant

Notice of Allowance dated May 20, 2016, which issued during the prosecution of U.S. Appl. No. 14/237,258. cited by applicant

Notice of Allowance dated Jul. 6, 2017, which, issued during the prosecution of U.S. Appl. No. 14/689,608. cited by applicant

Notice of Allowance dated Aug. 18, 2017, which issued during the prosecution of U.S. Appl. No. 14/689,608. cited by applicant

Notice of Allowance dated May 22, 2017, which issued during the prosecution of U.S. Appl. No. 14/689,608. cited by applicant

Notice of Allowance dated Feb. 11, 2015, which issued during the prosecution of U.S. Appl. No. 13/033,852. cited by applicant

Notice of Allowance dated May 5, 2015, which issued during the prosecution of U.S. Appl. No. 12/840,463. cited by applicant

Notice of Allowance dated Mar. 10, 2015, which issued during the prosecution of U.S. Appl. No. 13/811,308. cited by applicant

Notice of Allowance dated Mar. 18, 2020, which issued during the prosecution of U.S. Appl. No. 16/284,331. cited by applicant

An Office Action dated Jan. 14, 2020, which issued during the prosecution of U.S. Appl. No. 16/284,331. cited by applicant

Notice of Allowance dated May 7, 2020, which issued during the prosecution of U.S. Appl. No. 16/637,166. cited by applicant

An International Search Report and a Written Opinion both dated Nov. 9, 2018, which issued during the prosecution of Applicant's PCT/IL2018/050869. cited by applicant

An Office Action dated Jan. 9, 2020, which issued during the prosecution of U.S. Appl. No. 15/600,190. cited by applicant

An International Search Report and a Written Opinion both dated May 13, 2019, which issued during the prosecution of Applicants PCT/IL2018/051350. cited by applicant

An International Search Report and a Written Opinion both dated Apr. 25, 2019, which issued during the

prosecution of Applicant's PCT/IL2019/050142. cited by applicant
An International Search Report and a Written Opinion both dated Jan. 25, 2019, which issued during the prosecution of Applicant's PCT/IL2018/051122. cited by applicant
An International Search Report and a Written Opinion both dated Dec. 5, 2018, which issued during the prosecution of Applicant's PCT/IL2018/050725. cited by applicant
An International Preliminary Report on Patentability dated Feb. 12, 2019, which issued during the prosecution of Applicant's PCT/IL2017/050873. cited by applicant
An International Preliminary Report on Patentability dated Feb. 5, 2019, which issued during the prosecution of Applicant's PCT/IL2017/050849. cited by applicant
An Office Action dated Nov. 26, 2019, which issued during the prosecution of U.S. Appl. No. 16/532,945. cited by applicant
An Office Action dated Nov. 1, 2019, which issued during the prosecution of U.S. Appl. No. 15/872,501. cited by applicant
An Office Action dated Mar. 25, 2019, which issued during the prosecution of European Patent Application No. 14710060.6. cited by applicant
An Office Action dated Oct. 25, 2018, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant
An Office Action dated Mar. 4, 2019, which issued during the prosecution of U.S. Appl. No. 14/763,004. cited by applicant
An Office Action dated Jan. 9, 2019, which issued during the prosecution of U.S. Appl. No. 15/329,920. cited by applicant
An Office Action dated Jan. 30, 2019, which issued during the prosecution of U.S. Appl. No. 15/872,501. cited by applicant
An Office Action dated Feb. 5, 2019, which issued during the prosecution of U.S. Appl. No. 15/899,858. cited by applicant
An Office Action dated May 23, 2019, which issued during the prosecution of U.S. Appl. No. 15/668,659. cited by applicant
An Office Action dated May 1, 2019, which issued during the prosecution of U.S. Appl. No. 15/691,032. cited by applicant
An Office Action dated Jun. 25, 2019, which issued during the prosecution of U.S. Appl. No. 15/329,920. cited by applicant
An Office Action dated Aug. 23, 2019, which issued during the prosecution of U.S. Appl. No. 15/600,190. cited by applicant
An Office Action dated May 16, 2019, which issued during the prosecution of U.S. Appl. No. 15/433,547. cited by applicant
An Office Action dated Aug. 1, 2019, which issued during the prosecution of U.S. Appl. No. 15/668,559. cited by applicant
An Office Action dated Aug. 16, 2019, which issued during the prosecution of U.S. Appl. No. 15/668,659. cited by applicant
An Office Action dated Jun. 19, 2019, which issued during the prosecution of U.S. Appl. No. 15/682,789. cited by applicant
An Office Action dated Jun. 14, 2019, which issued during the prosecution of U.S. Appl. No. 15/703,385. cited by applicant
An Office Action dated Oct. 4, 2019, which issued during the prosecution of U.S. Appl. No. 16/183,140. cited by applicant
An Office Action dated Jun. 13, 2019, which issued during the prosecution of U.S. Appl. No. 16/388,038. cited by applicant
An Office Action dated Sep. 13, 2019, which issued during the prosecution of U.S. Appl. No. 16/460,313. cited by applicant
Notice of Allowance dated Sep. 10, 2020, which issued during the prosecution of U.S. Appl. No. 15/600,190. cited by applicant
An International Search Report and a Written Opinion both dated Jun. 24, 2020, which issued during the prosecution of Applicant's PCT/IL2019/051398. cited by applicant
Sundermann, Simon H., et al. "Feasibility of the Engager*** aortic transcatheter valve system using a flexible over-the-wire design," European Journal of Cardio-Thoracic Surgery 42.4 (2012): e48-e52. cited by applicant

Serruys, P. W., Piazza, N., Cribier, A., Webb, J., Laborde, J. C., & de Jaegere, P. (Eds.). (2009). Transcatheter aortic valve implantation: tips and tricks to avoid failure. CRC Press.—Screenshots from Google Books downloaded from https://books.google.co.il/books?id=FLzLBQAAQBAJ&Ipg=PA198&ots=soqWrDH-y_&dq=%20%22Edwards%20SAPIEN%22&lr&pg=PA20#v=onepage&q=%22Edwards%20SAPIEN%22&f=false Downloaded on Jun. 18, 2020. cited by applicant

Tchetché, D. and Nicolas M. Van Mieghem: “New-generation TAVI devices: description and specifications” *EuroIntervention*, 2014, No. 10:U90-U100. cited by applicant

Symetis S.A.: “Acurate neo™ Aortic Bioprosthesis for Implantation using the Acurate neo™ TA Transapical Delivery System in Patients with Severe Aortic Stenosis,” Clinical Investigation Plan, Protocol No. Jan. 2015, Vs. No. 2, 2015:1-76. cited by applicant

An Office Action dated Jul. 29, 2020, which issued during the prosecution of U.S. Appl. No. 16/269,328. cited by applicant

Notice of Allowance dated Aug. 26, 2020, which issued during the prosecution of U.S. Appl. No. 16/269,328. cited by applicant

An Office Action dated Jul. 14, 2020, which issued during the prosecution of U.S. Appl. No. 16/324,339. cited by applicant

Notice of Allowance dated Aug. 28, 2020, which issued during the prosecution of U.S. Appl. No. 16/324,339. cited by applicant

An Office Action summarized English translation and Search Report dated Jul. 3, 2020, which issued during the prosecution of Chinese Patent Application No. 201780061210.3. cited by applicant

An Office Action dated Aug. 7, 2020, which issued during the prosecution of U.S. Appl. No. 15/668,659. cited by applicant

Notice of Allowance dated Jul. 29, 2020, which issued during the prosecution of U.S. Appl. No. 16/132,937. cited by applicant

Notice of Allowance dated Apr. 24, 2019, which issued during the prosecution of U.S. Appl. No. 16/045,059. cited by applicant

Notice of Allowance dated Mar. 12, 2020, which issued during the prosecution of U.S. Appl. No. 16/460,313. cited by applicant

An International Preliminary Report on Patentability dated Oct. 20, 2020, which issued during the prosecution of Applicant's PCT/IL2019/050142. cited by applicant

An Office Action dated Oct. 5, 2020, which issued during the prosecution of Canadian Patent Application No. 2,973,940. cited by applicant

Notice of Allowance dated Nov. 19, 2020, which issued during the prosecution of U.S. Appl. No. 16/318,025. cited by applicant

An Office Action dated Sep. 24, 2020, which issued during the prosecution of U.S. Appl. No. 16/811,732. cited by applicant

An Office Action summarized English translation and Search Report dated Nov. 25, 2020, which issued during the prosecution of Chinese Patent Application No. 201910449820.1. cited by applicant

An Office Action dated Nov. 30, 2020, which issued during the prosecution of U.S. Appl. No. 16/138,129. cited by applicant

Condado, José Antonio, et al. “Percutaneous edge-to-edge mitral valve repair: 2-year follow-up in the first human case.” *Catheterization and cardiovascular interventions* 67.2 (2006): 323-325. cited by applicant

An Office Action dated Dec. 24, 2020, which issued during the prosecution of U.S. Appl. No. 16/144,054. cited by applicant

An Office Action dated Feb. 2, 2021, which issued during the prosecution of U.S. Appl. No. 16/811,732. cited by applicant

An Office Action dated Jan. 13, 2021, which issued during the prosecution of European Patent Application No. 15751089.2. cited by applicant

Maisano, F., et al. “The edge-to-edge technique: a simplified method to correct mitral insufficiency.” *European journal of cardio-thoracic surgery* 13.3 (1998): 240-246. cited by applicant

Declaration of Dr. Ivan Vesely, Ph.D. in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,226,341—dated Dec. 17, 2020. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 10,226,341 and Exhibits 1001-1013—dated Dec. 29, 2020. cited by applicant

An Office Action together with an English summary dated Mar. 3, 2021, which issued during the prosecution of

Chinese Patent Application No. 201780047391.4. cited by applicant

Fucci, C., et al. "Improved results with mitral valve repair using new surgical techniques." *European journal of cardio-thoracic surgery* 9.11 (1995): 621-627. cited by applicant

An Office Action dated Sep. 6, 2018, which issued during the prosecution of U.S. Appl. No. 15/213,791. cited by applicant

Declaration of Ivan Vesely, Ph.D., in Support of Petition for Inter Partes review of U.S. Pat. No. 7,563,267—dated May 29, 2019. cited by applicant

U.S. Appl. No. 60/128,690, filed Apr. 9, 1999. cited by applicant

Batista, Randas JV, et al. "Partial left ventriculectomy to treat end-stage heart disease." *The Annals of thoracic surgery* 64.3 (1997): 634-638. cited by applicant

Beall Jr, Arthur C., et al. "Clinical experience with a dacron velour-covered teflon-disc mitral-valve prosthesis." *The Annals of thoracic surgery* 5.5 (1968): 402-410. cited by applicant

Kalbacher, D., et al. "1000 MitraClip™ procedures: Lessons learnt from the largest single-centre experience worldwide." (2019): 3137-3139. cited by applicant

U.S. Appl. No. 60/613,867, filed Sep. 27, 2004. cited by applicant

Mitral Valve Academic Research Consortium. "Clinical Trial Design Principles and Endpoint Definitions for Transcatheter Mitral Valve Repair and Replacement: Part 1: Clinical Trial Design Principles A Consensus Document from the Mitral Valve Academic Research Consortium." *Journal of the American College of Cardiology* 66.3 (2015): 278-307. cited by applicant

Notice of Allowance dated Oct. 3, 2019, which issued during the prosecution of U.S. Appl. No. 15/691,032. cited by applicant

Notice of Allowance dated Mar. 29, 2017, which issued during the prosecution of U.S. Appl. No. 14/161,921. cited by applicant

Feldman, Ted, et al. "Percutaneous mitral repair with the MitraClip system: safety and midterm durability in the initial EVEREST (Endovascular Valve Edge-to-Edge REpair Study) cohort." *Journal of the American College of Cardiology* 54.8 (2009): 686-694. cited by applicant

Notice of Allowance dated Nov. 21, 2018, which issued during the prosecution of U.S. Appl. No. 15/213,791. cited by applicant

Notice of Allowance dated Jul. 3, 2019, which issued during the prosecution of U.S. Appl. No. 15/691,032. cited by applicant

An Office Action dated Jan. 6, 2020, which issued during the prosecution of U.S. Appl. No. 16/660,231. cited by applicant

Notice of Allowance dated Jan. 13, 2020, which issued during the prosecution of U.S. Appl. No. 15/956,956. cited by applicant

European Search Report dated Mar. 5, 2020 which issued during the prosecution of Applicant's European App No. 17752184.6. cited by applicant

An Office Action dated Dec. 31, 2019, which issued during the prosecution of U.S. Appl. No. 16/183,140. cited by applicant

An Office Action dated Feb. 6, 2020, which issued during the prosecution of U.S. Appl. No. 15/668,659. cited by applicant

European Search Report dated Mar. 4, 2020 which issued during the prosecution of Applicant's European App No. 16706913.7. cited by applicant

Urena, Marina, et al. "Transseptal transcatheter mitral valve replacement using balloon-expandable transcatheter heart valves: a step-by-step approach." *JACC: Cardiovascular Interventions* 10.19 (2017): 1905-1919. cited by applicant

An Office Action dated Mar. 29, 2021, which issued during the prosecution of U.S. Appl. No. 16/738,516. cited by applicant

An Office Action dated Jan. 3, 2020, which issued during the prosecution of U.S. Appl. No. 16/678,355. cited by applicant

Ando, Tomo, et al. "Iatrogenic ventricular septal defect following transcatheter aortic valve replacement: a systematic review." *Heart, Lung and Circulation* 25.10 (2016): 968-974. cited by applicant

Poirier, Nancy C., et al. "A novel repair for patients with atrioventricular septal defect requiring reoperation for left atrioventricular valve regurgitation." *European journal of cardio-thoracic surgery* 18.1 (2000): 54-61. cited by applicant

Petitioner's Reply to Patent Owner's Response dated Jan. 5, 2022 in IPR2021-00383. cited by applicant

Petitioner's Opposition to Patent Owner's Contingent Motion to Amend dated Jan. 5, 2022 in IPR2021-00383. cited by applicant

Decision Granting Institution of Inter Partes Review dated Dec. 10, 2021 in IPR2021-01051 (42 pages total). cited by applicant

Notice of Allowance issued Dec. 7, 2021 in U.S. Appl. No. 17/394,807. cited by applicant

Office Action issued Nov. 4, 2021 in U.S. Appl. No. 17/366,711. cited by applicant

Extended European Search Report issued Oct. 11, 2021 in European Application No. 21176010.3. cited by applicant

Fann et al., "Beating Heart Catheter-Based Edge-to-Edge Mitral Valve Procedure in a Porcine Model", *Circulation*, 2004, vol. 110, pp. 988-993, Cardiovalve Exhibit 2006 (6 pages total). cited by applicant

Feldman et al., "Percutaneous Mitral Leaflet Repair: MitralClip Therapy for Mitral Regurgitation", Informa Healthcare, 2012, CRC Press, pp. 31-44, Cardiovalve Exhibit 2009 (8 pages total). cited by applicant

Feldman et al., "Percutaneous Mitral Valve Repair Using the Edge-to-Edge Technique", *Journal of the American College of Cardiology*, 2005, vol. 46, No. 11, pp. 2134-2140 (7 pages total). cited by applicant

IPR2021-00383 "Patent Owner's Contingent Motion to Amend", dated Oct. 13, 2021 (35 pages total). cited by applicant

IPR2021-00383 "Patent Owner's Response", dated Oct. 13, 2021 (75 pages total). cited by applicant

Maisano et al., "The Evolution From Surgery to Percutaneous Mitral Valve Interventions", *Journal of the American College of Cardiology*, 2011, vol. 58, No. 21, pp. 2174-2182 (9 pages total). cited by applicant

Notice of Allowance issued Sep. 15, 2021 in U.S. Appl. No. 16/135,599. cited by applicant

Office Action issued Oct. 14, 2021 in U.S. Appl. No. 16/680,739. cited by applicant

Office Action issued Oct. 21, 2021 in U.S. Appl. No. 17/306,231. cited by applicant

Office Action issued Oct. 21, 2021 in U.S. Appl. No. 17/335,845. cited by applicant

Office Action issued Sep. 9, 2021 in U.S. Appl. No. 16/768,909. cited by applicant

Second Declaration of Dr. Michael Sacks, Oct. 13, 2021, IPR2021-00383, U.S. Pat. No. 10,226,341, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Cardiovalve Exhibit 2014 (28 pages total). cited by applicant

Transcript of Dr. Vesely, Sep. 22, 2021, Case No. IPR2021-00383, U.S. Pat. No. 10,226,341 United States Patent and Trademark Office Before the Patent Trial and Appeal Board, Cardiovalve Exhibit 2010 (170 pages total). cited by applicant

IPR2021-00383 "Petitioners' Authorized Reply to Patent Owner's Preliminary Response", dated May 27, 2021, 9 pages. cited by applicant

Exhibit 1014, "Transcript of proceedings" held May 20, 2021, 15 pages. cited by applicant

Exhibit 1015, "Facilitate", Meriam-Webster.com, <https://www.merriamwebster.com/dictionary/facilitate>, retrieved May 26, 2021, 5 pages. cited by applicant

IPR2021-00383, "Patent Owner's Authorized Surreply to Petitioner's Reply to Patent Owner's Preliminary Response", dated Jun. 4, 2021, 8 pages. cited by applicant

IPR2021-00383, "Institution decision" dated Jul. 20, 2021, 51 pages. cited by applicant

An extended European search report dated Jun. 10, 2021 in application No. 21157988.3. cited by applicant

International Search Report and Written Opinion dated Jul. 12, 2021 from the International Searching Authority in International Application No. PCT/IL2021/050132. cited by applicant

An Office Action dated May 4, 2021, which issued during the prosecution of U.S. Appl. No. 16/636,204. cited by applicant

Notice of Allowance dated May 17, 2021, which issued during the prosecution of U.S. Appl. No. 16/138,129. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 10,702,385—dated Jun. 4, 2021. cited by applicant

Declaration of Ivan Vesely, Ph.D. In Support of Petition for Inter Partes Review of U.S. Pat. No. 10,702,385—dated Jun. 4, 2021. cited by applicant

An English summary of an Official Action dated Mar. 29, 2021, which issued during the prosecution of Chinese Patent Application No. 201780061210.3. cited by applicant

An International Search Report and a Written Opinion both dated Jan. 28, 2020, which issued during the prosecution of Applicant's PCT/IL2019/051031. cited by applicant

An International Preliminary Report on Patentability dated Mar. 9, 2021, which issued during the prosecution of Applicant's PCT/IL2019/051031. cited by applicant

An Office Action dated May 12, 2021, which issued during the prosecution of Canadian Patent Application No. 2,973,940. cited by applicant

Notice of Allowance dated Jun. 4, 2021, which issued during the prosecution of U.S. Appl. No. 16/802,353. cited by applicant

An Office Action dated Aug. 1, 2022, which issued during the prosecution of European Patent Application No. 18826823.9. cited by applicant

An Office Action dated Aug. 5, 2022, which issued during the prosecution of U.S. Appl. No. 16/760,147. cited by applicant

An Office Action dated Jul. 20, 2022, which issued during the prosecution of U.S. Appl. No. 17/101,787. cited by applicant

An Office Action dated Jul. 27, 2022, which issued during the prosecution of U.S. Appl. No. 16/881,350. cited by applicant

An Office Action dated Sep. 16, 2022, which issued during the prosecution of U.S. Appl. No. 16/135,466. cited by applicant

An Office Action dated Sep. 21, 2022, which issued during the prosecution of U.S. Appl. No. 16/776,581. cited by applicant

An Office Action dated Sep. 8, 2022, which issued during the prosecution of U.S. Appl. No. 16/896,858. cited by applicant

European Search Report dated Sep. 6, 2022 which issued during the prosecution of Applicant's European App No. 22161862.2. cited by applicant

IPR2021-01051 Patent Owner's Sur-Reply to Petitioners' Reply to Preliminary Guidance dated Aug. 23, 2022. cited by applicant

IPR2021-01051 Petitioners' Reply to Preliminary Guidance dated Aug. 2, 2022. cited by applicant

An International Search Report and a Written Opinion both dated May 3, 2022, which issued during the prosecution of Applicant's PCT/IL2021/051433. cited by applicant

An Office Action dated Jul. 8, 2022, which issued during the prosecution of U.S. Appl. No. 16/144,054. cited by applicant

An Office Action dated Jun. 28, 2022, which issued during the prosecution of U.S. Appl. No. 16/135,969. cited by applicant

An Office Action together with an English Summary dated May 7, 2022 which issued during the prosecution of Chinese Patent Application No. 201880058940.2. cited by applicant

Ex Parte Quayle dated May 2, 2022, which issued during the prosecution of U.S. Appl. No. 16/879,952. cited by applicant

IPR2021-00383 Final Written Decision dated Jul. 18, 2022. cited by applicant

IPR2021-01051 Preliminary Guidance Patent Owner's Motion to Amend dated Jun. 24, 2022. cited by applicant

Notice of Allowance dated May 4, 2022, which issued during the prosecution of U.S. Appl. No. 16/680,739. cited by applicant

An Office Action dated Jan. 26, 2022, which issued during the prosecution of U.S. Appl. No. 16/888,210. cited by applicant

Notice of Allowance dated Jan. 31, 2022, which issued during the prosecution of U.S. Appl. No. 17/479,418. cited by applicant

An Office Action dated Mar. 18, 2022, which issued during the prosecution of U.S. Appl. No. 16/746,489. cited by applicant

Notice of Allowance dated Mar. 22, 2022, which issued during the prosecution of U.S. Appl. No. 17/366,711. cited by applicant

Notice of Allowance dated Mar. 4, 2022, which issued during the prosecution of U.S. Appl. No. 16/768,909. cited by applicant

An Office Action dated Dec. 9, 2021, which issued during the prosecution of U.S. Appl. No. 16/135,969. cited by applicant

An Office Action dated Jan. 24, 2022, which issued during the prosecution of U.S. Appl. No. 16/135,466. cited by applicant

An Office Action dated Apr. 11, 2022, which issued during the prosecution of U.S. Appl. No. 17/473,472. cited by applicant

IPR2021-00383 Preliminary Guidance dated Jan. 31, 2022. cited by applicant

Notice of Allowance issued Dec. 29, 2021 in U.S. Appl. No. 17/210,183. cited by applicant

An invitation to pay additional fees dated May 19, 2021, which issued during the prosecution of Applicant's PCT/IL2021/050132. cited by applicant

An Office Action dated Aug. 18, 2021, which issued during the prosecution of U.S. Appl. No. 17/210,183. cited by applicant
Edwards reply to Preliminary Guidance filed Aug. 2, 2022 in IPR2021-01051 (17 pages total). cited by applicant
Cardiovalve's Sur-reply to EDW's Reply to Preliminary Guidance dated Aug. 23, 2022 in IPR2021-01051 (10 pages total). cited by applicant
An Office Action dated Sep. 29, 2022, which issued during the prosecution of U.S. Appl. No. 17/010,886. cited by applicant
An Office Action dated Sep. 29, 2022, which issued during the prosecution of U.S. Appl. No. 16/656,790. cited by applicant
IPR2021-01051 final written decision dated Dec. 6, 2022. cited by applicant
European Search Report dated Mar. 20, 2023 which issued during the prosecution of Applicant's European App No. 22204764.9. cited by applicant
An Office Action dated Apr. 14, 2023, which issued during the prosecution of U.S. Appl. No. 16/144,054. cited by applicant

Primary Examiner: Stewart; Alvin J

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. Ser. No. 16/881,350 to HaCohen, filed May 22, 2020, which published as US 2020/0330221 and which is a Continuation of U.S. Ser. No. 16/460,313 to Gross et al., filed Jul. 2, 2019 (now U.S. Pat. No. 10,695,173), which is a Continuation of U.S. Ser. No. 16/045,059 to Gross et al., filed Jul. 25, 2018 (now U.S. Pat. No. 10,376,361), which is a Continuation of U.S. Ser. No. 15/213,791 to Gross et al., filed Jul. 19, 2016 (now U.S. Pat. No. 10,245,143), which is a Continuation of U.S. Ser. No. 14/237,264 to Gross et al., filed May 23, 2014 (now abandoned), which published as US 2014/0324164 and which is the US National Phase of PCT Application IL2012/000292 to Gross et al., filed Aug. 5, 2012, which published as WO 2013/021374 and which: (1) claims priority from: U.S. 61/515,372 to Gross et al., filed Aug. 5, 2011; U.S. 61/525,281 to Gross et al., filed Aug. 19, 2011; U.S. 61/537,276 to Gross et al., filed Sep. 21, 2011; U.S. 61/555,160 to Gross et al., filed Nov. 3, 2011; U.S. 61/588,892 to Gross et al., filed Jan. 20, 2012; and U.S. Ser. No. 13/412,814 to Gross et al., filed Mar. 6, 2012, (now U.S. Pat. No. 8,852,272) all of which are incorporated herein by reference; and (2) is a Continuation-In-Part of U.S. Ser. No. 13/412,814 to Gross et al., filed Mar. 6, 2012 (now U.S. Pat. No. 8,852,272). (2) This application is related to International Patent Application IL2012/000293 to Gross et al., entitled, "Percutaneous mitral valve replacement and sealing," filed Aug. 5, 2012, which published as WO 2013/021375.

FIELD OF THE INVENTION

(1) Some applications of the present invention relate in general to valve replacement. More specifically, some applications of the present invention relate to prosthetic valves for replacement of a cardiac valve.

BACKGROUND

(2) Ischemic heart disease causes regurgitation of a heart valve by the combination of ischemic dysfunction of the papillary muscles, and the dilatation of the ventricle that is present in ischemic heart disease, with the subsequent displacement of the papillary muscles and the dilatation of the valve annulus.

(3) Dilation of the annulus of the valve prevents the valve leaflets from fully coapting when the valve is closed. Regurgitation of blood from the ventricle into the atrium results in increased total stroke volume and decreased cardiac output, and ultimate weakening of the ventricle secondary to a volume overload and a pressure overload of the atrium.

SUMMARY OF THE INVENTION

(4) For some applications of the invention, a prosthetic valve support is provided for facilitating transluminal implantation of a prosthetic valve at a native valve (e.g., a native heart valve) of a subject. The prosthetic valve support is configured to be placed at the native valve, such as by placing an upstream support portion (e.g., an annular portion) of the prosthetic valve support against an upstream surface of the native valve (e.g.,

against a native valve annulus). The prosthetic valve is subsequently implanted at the native valve by coupling the prosthetic valve to the prosthetic valve support, such as by expanding the prosthetic valve in an opening defined by the prosthetic valve support. For some applications, the prosthetic valve support is couplable to the native valve, independently of the prosthetic valve. The implantation of the prosthetic valve at the native valve replaces native check valve functionality of the native valve with substitute check valve functionality of the prosthetic valve. For some applications, the prosthetic valve support and/or the prosthetic valve comprise tissue-engaging elements (e.g., support-anchoring elements, and valve-anchoring elements, respectively), such as anchors or clips.

(5) Typically, the prosthetic valve is expanded within one or more openings defined by the prosthetic valve support, and coupling of the prosthetic valve to the prosthetic valve support is facilitated by radially-expansive force applied by the prosthetic valve against the prosthetic valve support. For some applications, additional coupling techniques, such as support-engaging elements, coupling leads, ratchet mechanisms, protrusions, and/or pockets are used.

(6) For some applications, the prosthetic valve support is configured to receive, at different periods, more than one prosthetic valve. For example, a first prosthetic valve may be removed from the prosthetic valve support, and replaced with a second prosthetic valve. Alternatively, the first prosthetic valve may be left in place when the second prosthetic valve is implanted. For example, the prosthetic valve support may define more than one lumen, each lumen configured to receive a respective prosthetic valve. Alternatively, the prosthetic valve support may define a lumen that is configured (e.g., shaped) to receive a first valve at a first period, and a second valve at a second period.

(7) For some applications, the prosthetic valve support comprises support-anchoring elements that are flexibly-coupled to the upstream support portion. For some such applications, the support-anchoring elements are configured to anchor the prosthetic valve support to the native valve, while allowing the leaflets of the native valve to continue to function, at least in part. For some applications, the prosthetic valve support comprises support-anchoring elements whose length is variable (e.g., adjustable).

(8) For some applications of the invention, a cross-sectional area of the opening defined by the prosthetic valve support is adjustable.

(9) For some applications of the invention, delivery apparatus for implantation of a medical device (e.g., a prosthetic valve and/or a prosthetic valve support) is provided, the delivery apparatus and/or the medical device being configured to allow retrievability of the medical device during one or more stages of delivery and/or deployment of the medical device.

(10) There is therefore provided, in accordance with an application of the present invention, apparatus for use with a first prosthetic valve and a second prosthetic valve at a native heart valve of a subject, the apparatus including: a prosthetic valve support, shaped to define at least one lumen, and configured: to be implanted at the native valve, to facilitate, at a first period, implantation at the native valve of the first prosthetic valve, and to facilitate, at a second period, implantation at the native valve of the second prosthetic valve without removal of the first valve.

(11) In an application, the prosthetic valve support is configured to facilitate the implantation of the first prosthetic valve by being configured to receive the first prosthetic valve in the at least one lumen.

(12) In an application, the prosthetic valve support includes a seal, which: does not cover at least a first region of the at least one lumen, covers at least a second region of the at least one lumen, and is configured to be openable at at least the second region,

and the prosthetic valve support is configured: to facilitate the implantation of the first prosthetic valve by being configured to receive the first prosthetic valve in the first region, and to facilitate the implantation of the second prosthetic valve by being configurable, by opening of the seal, to receive the second prosthetic valve in the second region.

(13) In an application, the at least one lumen is shaped to define at least a first lumen and a second lumen, and the seal covers the second lumen.

(14) In an application, the first region and the second region are defined by the same lumen.

(15) In an application, the apparatus includes a covering that covers the prosthetic valve support, and the seal is defined by a portion of the covering.

(16) In an application, the prosthetic valve support is configured to receive the first prosthetic valve in the lumen, and is configured to facilitate the implantation of the second prosthetic valve by being configured to receive the second prosthetic valve in the same lumen.

(17) In an application, the apparatus further includes the first and second prosthetic valves, the first prosthetic

valve defines a lumen therethrough, and the second prosthetic valve is configured to be implanted in the lumen of the first prosthetic valve.

(18) In an application: the second prosthetic valve defines a lumen therethrough, after the first period, and before the second period, the lumen of the first prosthetic valve has a first diameter, and the prosthetic valve support is configured such that, after the second period, the lumen of the second prosthetic valve has a diameter that is at least as great as the first diameter.

(19) In an application, the prosthetic valve support is configured such that, after the second period, the lumen of the second prosthetic valve has a diameter that is greater than the first diameter.

(20) In an application, the prosthetic valve support includes a weak zone that circumscribes and defines the lumen, and is configured to facilitate enlarging of the lumen.

(21) In an application, the prosthetic valve support is configured to facilitate enlarging of the lumen by being configured to be deformed by a radially-expansive force applied from within the lumen.

(22) In an application, the prosthetic valve support includes a cylindrical element: shaped to define the lumen, configured to receive the first prosthetic valve at a first portion of the lumen, and configured to receive the second prosthetic valve support at a second portion of the lumen.

(23) In an application, the cylindrical element is configured to receive the first prosthetic valve at a first longitudinal portion of the lumen, and to receive the second prosthetic valve at a second longitudinal portion of the lumen.

(24) There is further provided, in accordance with an application of the present invention, apparatus for use with a prosthetic heart valve for implantation at a native heart valve of a subject, the apparatus including: a core, shaped to define at least one conduit therethrough; and one or more control filaments, slidable through the conduit, and reversibly couplable to the prosthetic valve, the apparatus being configured such that sliding the control filaments in a first direction through the conduit facilitates expansion of the prosthetic valve, and sliding the control filaments in a second direction through the conduit facilitates compression of the prosthetic valve.

(25) In an application, the apparatus is configured such that sliding the control filaments in the first direction through the conduit facilitates radial expansion of the prosthetic valve away from the core.

(26) In an application, the apparatus further includes the prosthetic valve, a delivery tube and a pushing member, and: the prosthetic valve has an expanded configuration and a compressed configuration, the delivery tube is configured to be transluminally delivered to the native valve, the pushing member includes the core, the pushing member is configured: to be disposed within the delivery tube, to be fixedly coupled, within the delivery tube, to the prosthetic valve in the compressed configuration thereof, when fixedly coupled to the prosthetic valve, to facilitate movement of the prosthetic valve with respect to the delivery tube, and to be decouplable from the prosthetic valve.

(27) In an application, the apparatus further includes one or more release wires, configured to facilitate decoupling of the control filaments from the prosthetic valve.

(28) In an application, the apparatus further includes one or more guide elements, radially extendable from the core, and configured to guide expansion of the prosthetic valve away from the core.

(29) In an application, the guide elements are configured to automatically radially retract when the control filaments are decoupled from the prosthetic valve.

(30) There is further provided, in accordance with an application of the present invention, apparatus for use at a native heart valve of a subject, the apparatus including: a prosthetic valve, configured to be transluminally delivered to, and implantable at, the native valve of the subject; a prosthetic valve support, configured to be transluminally delivered to the native valve of the subject, and to facilitate implantation of the prosthetic valve; at least one coupling lead, extending between the prosthetic valve and the prosthetic valve support; and a ratchet housing, slidably coupled to the coupling lead, and configured to be slidable over the coupling lead in a first direction, and inhibited from sliding over the coupling lead in an opposite direction, the apparatus being configured such that sliding of the ratchet housing over the coupling lead in the first direction facilitates coupling of the prosthetic valve to the prosthetic valve support.

(31) In an application, the coupling lead extends between a proximal portion of the prosthetic valve, and the prosthetic valve support.

(32) In an application, the prosthetic valve support includes one or more support-anchoring elements, configured to couple the prosthetic valve support to the native valve, and the coupling lead extends between the prosthetic valve and the support-anchoring elements.

(33) There is further provided, in accordance with an application of the present invention, apparatus for use

with a native heart valve of a subject, the apparatus including: a first expandable prosthetic valve component, including a crimpable frame, and configured to be transcatheterally advanceable toward the native valve while the first prosthetic valve component is in a crimped state thereof; a second expandable prosthetic valve component, including a crimpable frame, and configured to be transcatheterally advanceable toward the native valve, placeable in the native valve while the second prosthetic valve component is in a crimped state thereof, and couplable to the first prosthetic valve component, expansion of the second prosthetic valve component facilitating coupling of the second prosthetic valve component to the first prosthetic valve component; and one or more tissue-engagement elements, coupled to at least one of the prosthetic valve components, the tissue-engagement elements configured, when the prosthetic valve component is in an expanded state thereof, to extend from the prosthetic valve component, and to inhibit a proximal movement of the prosthetic valve component.

(34) There is further provided, in accordance with an application of the present invention, apparatus for use with a prosthetic valve for implantation at a native valve of a subject, the native valve (1) defining an orifice, (2) including at least one native leaflet, having a native beating, and (3) having a native blood flow regulation functionality, the apparatus including: a prosthetic valve support, including: an upstream support portion, configured to be placed against an upstream side of the native valve, to have an inner perimeter that defines an opening that is configured to receive the prosthetic valve, and at least one clip, configured to be coupled to a native leaflet of the native valve, the clip including a plurality of clip arms, at least one clip arm coupled to a clip-controller interface; and a clip controller, couplable to the clip-controller interface, and configured to control a relative angular disposition between the clip arms.

(35) For some applications, techniques described herein are practiced in combination with techniques described in one or more of the references cited in the Background section and Cross-references section of the present patent application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A-H are schematic illustrations of sequential steps in the implantation of an implant comprising a prosthetic valve and a prosthetic valve support, in accordance with some applications of the present invention;

(2) FIG. 2 is a schematic illustration of a prosthetic valve support, comprising adjustable prosthetic valve support, in accordance with some applications of the invention;

(3) FIG. 3 is a schematic illustration of a prosthetic valve support, comprising an adjustable prosthetic valve support, in accordance with some applications of the invention;

(4) FIG. 4 is a schematic illustration of a prosthetic valve support, comprising an adjustable prosthetic valve support, in accordance with some applications of the invention;

(5) FIG. 5 is a schematic illustration of a prosthetic valve support, comprising a graduated prosthetic valve support, in accordance with some applications of the invention;

(6) FIG. 6 is a schematic illustration of a prosthetic valve support, comprising a flexibly-anchored prosthetic valve support, in accordance with some applications of the invention;

(7) FIG. 7 is a schematic illustration of a prosthetic valve support, comprising a flexibly-anchored prosthetic valve support, in accordance with some applications of the invention;

(8) FIGS. 8A-B are schematic illustrations of a prosthetic valve support, and a prosthetic valve, the prosthetic valve comprising an integrally-anchoring prosthetic valve, in accordance with some applications of the invention;

(9) FIGS. 9A-E are schematic illustrations of delivery apparatus, used to deploy a medical device, in accordance with some applications of the invention;

(10) FIG. 10 is a schematic illustration of a prosthetic valve support, comprising a multi-lumen prosthetic valve support, in accordance with some applications of the invention;

(11) FIG. 11 is a schematic illustration of a prosthetic valve, comprising an extended-lumen prosthetic valve support, in accordance with some applications of the invention;

(12) FIGS. 12A-B are schematic illustrations of a prosthetic valve support, comprising an adjustable-lumen prosthetic valve support, in accordance with some applications of the invention;

(13) FIGS. 13A-D are schematic illustrations of a prosthetic valve support, comprising an asymmetric prosthetic valve support, in accordance with an application of the invention;

(14) FIG. 14 is a schematic illustration of a prosthetic valve support, in accordance with some applications of the invention;

(15) FIGS. 15A-E are schematic illustrations of the implantation of a prosthetic valve support and a prosthetic valve, in accordance with some applications of the invention;

(16) FIG. 16 is a schematic illustration of a prosthetic valve support being deployed in a native heart valve, in accordance with some applications of the invention;

(17) FIGS. 17A-D are schematic illustrations of prosthetic valve supports, comprising tissue-engaging elements, which comprise support-anchoring elements, comprising length-adjustable holding elements, in accordance with some applications of the invention;

(18) FIGS. 18A-B are schematic illustrations of prosthetic valve supports, comprising tissue-engaging elements, which comprise support-anchoring elements, comprising length-adjustable holding elements, in accordance with some applications of the invention;

(19) FIG. 19 is a schematic illustration of a prosthetic valve support, comprising tissue-engaging elements, which comprise support-anchoring elements, comprising length-adjustable holding elements, in accordance with some applications of the invention;

(20) FIGS. 20A-F are schematic illustrations of prosthetic valve supports, comprising tissue-engaging elements, which comprise support-anchoring elements, comprising flexible support-anchoring elements, in accordance with some applications of the invention;

(21) FIGS. 21A-C are schematic illustrations of a prosthetic valve support, comprising an inflatable support-engaging element, in accordance with some applications of the invention;

(22) FIGS. 22A-C are schematic illustrations of sequential steps in the implantation of an implant, comprising a prosthetic valve and a prosthetic valve support, coupled via coupling leads;

(23) FIGS. 23A-B are schematic illustrations of a prosthetic valve support, shaped to define at least one pocket, and the coupling thereto of a prosthetic valve, in accordance with some applications of the invention;

(24) FIG. 24 is a schematic illustration of a prosthetic valve support, shaped to define at least one pocket, and the coupling thereto of a prosthetic valve, in accordance with some applications of the invention;

(25) FIGS. 25A-E are schematic illustrations of a retrieval device, and sequential steps in the use thereof, in accordance with some applications of the invention;

(26) FIGS. 26A-C are schematic illustrations of a prosthetic valve support comprising a braided structure, and the deployment thereof, in accordance with some applications of the invention;

(27) FIGS. 27A-D are schematic illustrations of delivery apparatus, in accordance with some applications of the invention;

(28) FIGS. 28A-D are schematic illustrations of the deployment of a prosthetic valve in the lumen of another prosthetic valve, in accordance with some applications of the invention;

(29) FIGS. 29A-F are schematic illustrations of the deployment of a prosthetic valve in the lumen of another prosthetic valve, and of a prosthetic valve support configured to facilitate such deployment, in accordance with some applications of the invention;

(30) FIGS. 30A-B are schematic illustrations of the deployment of a second prosthetic valve in the lumen of a prosthetic valve support, in which a first prosthetic valve is already disposed, in accordance with some applications of the invention;

(31) FIGS. 31A-C are schematic illustrations of a flexible delivery tube, configured to facilitate removal thereof from a subject, in accordance with some applications of the invention;

(32) FIGS. 32A-C are schematic illustrations of a compressible delivery tube, configured to facilitate removal thereof from a subject, in accordance with some applications of the invention;

(33) FIGS. 33A-C are schematic illustrations of a dismantling delivery tube, configured to facilitate removal thereof from a subject, in accordance with some applications of the invention;

(34) FIG. 34 is a schematic illustration of a prosthetic valve, comprising a leaflet-engaging element, in accordance with some applications of the invention;

(35) FIGS. 35A-C are schematic illustrations of a prosthetic valve support comprising temporary valve components, and sequential steps in the coupling of a prosthetic valve to the support, in accordance with some applications of the invention;

(36) FIGS. 36A-D are schematic illustrations of a prosthetic valve support, comprising support-anchoring elements and stabilizing legs, in accordance with some applications of the invention;

(37) FIGS. 37A-H are schematic illustrations of a prosthetic valve support, comprising support-anchoring elements and stabilizing legs, and sequential steps in the implantation thereof, in accordance with some

applications of the invention;

(38) FIGS. 38A-H are schematic illustrations of a prosthetic valve support, comprising support-anchoring elements and stabilizing legs, and sequential steps in the implantation thereof, in accordance with some applications of the invention;

(39) FIGS. 39A-D are schematic illustrations of a medical device, comprising one or more coupling tabs, in accordance with some applications of the invention;

(40) FIGS. 40A-C are schematic illustrations of a prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(41) FIGS. 41A-B are schematic illustrations of a prosthetic valve, and a prosthetic valve support, comprising support-anchoring elements that are couplable to the prosthetic valve, in accordance with some applications of the invention;

(42) FIGS. 42A-B are schematic illustrations of a prosthetic valve, and a prosthetic valve support, comprising support-anchoring elements that are couplable to the prosthetic valve, in accordance with some applications of the invention;

(43) FIGS. 43A-C are schematic illustrations of a prosthetic valve, and a prosthetic valve support, comprising support-anchoring elements that are couplable to the prosthetic valve, in accordance with some applications of the invention;

(44) FIGS. 44A-B are schematic illustrations of a prosthetic valve support, comprising support-anchoring elements, and a prosthetic valve, comprising valve-anchoring elements that are couplable to the tissue-engaging elements of the prosthetic valve support, in accordance with some applications of the invention;

(45) FIGS. 45A-C are schematic illustrations of a lock for facilitating delivery of a medical device, in accordance with some applications of the invention;

(46) FIGS. 46A-B are schematic illustrations of a prosthetic valve support, comprising one or more support-anchoring elements, coupled to a stabilizing strip, in accordance with some applications of the invention;

(47) FIGS. 47A-C are schematic illustrations of sequential steps in the implantation of an implant, comprising a prosthetic valve and a prosthetic valve support, in accordance with some applications of the invention;

(48) FIGS. 48A-C are schematic illustrations of sequential steps in the implantation of an implant, comprising a prosthetic valve and a prosthetic valve support, in accordance with some applications of the invention;

(49) FIG. 49 is a schematic illustration of the prosthetic valve support, in accordance with some applications of the invention;

(50) FIG. 50 is a schematic illustration of a step in the implantation of the implant, in accordance with some applications of the invention;

(51) FIGS. 51A-B are schematic illustrations of the prosthetic valve support, in accordance with some applications of the invention;

(52) FIG. 52 is a schematic illustration of the prosthetic valve, in accordance with some applications of the invention;

(53) FIGS. 53A-C are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(54) FIGS. 54A-D are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(55) FIGS. 55A-E are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(56) FIGS. 56A-D are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(57) FIGS. 57A-D are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(58) FIGS. 58A-D are schematic illustrations of the prosthetic valve support, comprising tissue-engaging elements, in accordance with some applications of the invention;

(59) FIGS. 59A-B are schematic illustrations of the prosthetic valve support, comprising tissue-engaging elements, in accordance with some applications of the invention;

(60) FIGS. 60A-B are schematic illustrations of the prosthetic valve support, comprising tissue-engaging elements, in accordance with some applications of the invention;

(61) FIGS. 61A-C are schematic illustrations of the prosthetic valve support, comprising tissue-engaging elements, in accordance with some applications of the invention;

(62) FIGS. 62A-D are schematic illustrations of a delivery device for the delivery and deployment of an

expandable medical device, in accordance with some applications of the invention;

(63) FIGS. **63A-B** are schematic illustrations of the delivery device for the delivery and deployment of an expandable medical device, in accordance with some applications of the invention;

(64) FIGS. **64A-C**, **65A-B**, **66A-B**, and **67A-B** are schematic illustrations of a locking mechanism for delivery of an expandable medical device, in accordance with some applications of the invention;

(65) FIGS. **68A-B** and **69A-E** are schematic illustrations of a retrievable prosthetic valve support, and sequential steps in the retrieval of the retrievable prosthetic valve support, in accordance with some applications of the invention;

(66) FIGS. **70A-C** are schematic illustrations of the prosthetic valve, comprising tissue-engaging elements, in accordance with some applications of the invention;

(67) FIG. **71** is a schematic illustration of an implant comprising a prosthetic valve and a prosthetic valve support, in accordance with some applications of the present invention;

(68) FIGS. **72A-D** are schematic illustrations of an implant, comprising a prosthetic valve support and a prosthetic valve, in accordance with some applications of the invention;

(69) FIG. **73** is a schematic illustration of a prosthetic valve support, for use with a prosthetic valve, in accordance with some applications of the invention;

(70) FIGS. **74A-L** are schematic illustrations of steps in the implantation of an implant, comprising a prosthetic valve and a prosthetic valve support, in a native valve of a subject, in accordance with some applications of the invention;

(71) FIGS. **75A-D** are schematic illustrations of an implant, comprising a prosthetic valve support and a prosthetic valve, and steps in the implantation thereof, in accordance with some applications of the invention;

(72) FIGS. **76A-F** are schematic illustrations of steps in the implantation of an implant, comprising a prosthetic valve and a prosthetic valve support, in a native valve of a subject, in accordance with some applications of the invention;

(73) FIG. **77** is a schematic illustration of an implant, implanted at the mitral valve of a subject, in accordance with some applications of the invention;

(74) FIG. **78** is a schematic illustration of an implant, implanted at the tricuspid valve of a subject, in accordance with some applications of the invention;

(75) FIG. **79** is a schematic illustration of an implant, implanted at the pulmonary valve of a subject, in accordance with some applications of the invention; and

(76) FIG. **80** is a schematic illustration of an implant, implanted at the aortic valve of a subject, in accordance with some applications of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS

(77) Reference is made to FIGS. **1A-H**, which are schematic illustrations of sequential steps in the implantation in a native heart valve **23** of the heart **22** of a subject **20** of an implant **30**, comprising (1) a first prosthetic valve component, i.e., prosthetic valve support **40**, and (2) a second prosthetic valve component, i.e., a prosthetic valve **42**, in accordance with some applications of the present invention. For such applications of the present invention, native valve **23** includes a native mitral valve **24** by way of illustration and not limitation; the scope of the present invention includes implanting implant **30** in other valves of the heart (e.g., the tricuspid valve, the pulmonary valve, or the aortic valve). FIG. **1A** illustrates a cross-section through heart **22** of the subject which is used throughout FIGS. **1B-G** to illustrate the implantation procedure. As shown in the cross-sectional illustration, native mitral valve **24** includes native leaflets **82**, which are supported by native chordae tendineae **80**.

(78) FIG. **1B** shows prosthetic valve support **40** being deployed in a left atrium **26**. Prior to deployment, support **40** is percutaneously (e.g., transcatheterally) advanced into left atrium **26**, typically via overtube **44**. In some applications of the present invention, the advancement of overtube **44** toward heart valve **23** is preceded by advancement of a guidewire **45** through vasculature of the subject. Typically, guidewire **45** is used to guide overtube **44** through the vasculature. During its deployment, support **40** is moved distally (e.g., by a pushing coupling element, not shown for clarity of illustration and described hereinbelow), such that support **40** emerges from the distal end of overtube **44**. Support **40** is typically expandable, and typically comprises a wire frame which comprises a shape-memory material such as, but not limited to, nickel titanium (nitinol). For some applications of the invention, support **40** comprises nickel cobalt, stainless steel and/or titanium. As support **40** gradually emerges from overtube **44**, it gradually expands to assume an expanded configuration.

(79) FIG. **1C** shows support **40** reversibly coupled to one or more holding members **46**, which exert a distal

pushing force that causes support **40** to emerge from within overtube **44**. Once fully exposed from within overtube **44**, support **40** expands to assume the expanded configuration, as shown. In its expanded state, support **40** is annular and is shaped so as to define a lumen therethrough. Typically, prosthetic valve support **40** is shaped to define an outer edge **69** and an inner edge **68** (see FIG. 1H). Outer edge **69** typically defines the diameter of the annular prosthetic valve support, and inner edge **68** typically defines the diameter of the lumen in which prosthetic valve **42** is typically disposed. As shown in FIG. 1C, once support **40** is fully exposed from within overtube **44**, holding members **46** continue to push support **40** distally (i.e., in the direction as indicated by the arrows) until support **40** is positioned against an annulus of native heart valve **23**. (80) Support **40** is held against the annulus of native valve **23** (e.g., by holding members **46**) such that the lumen of support **40** aligns with the lumen of the native valve, and such that atrium **26** and ventricle **28** remain in fluid communication.

(81) Following the positioning of support **40** against the annulus of the native valve, prosthetic valve **42** is percutaneously (e.g., transcatheterally) advanced and delivered toward the native valve, typically along guidewire **45**, as shown in FIG. 1D.

(82) Prosthetic valve **42** is typically expandable, and typically comprises a wire frame which comprises a shape-memory material such as, but not limited to, nickel titanium (nitinol). For some applications of the invention, prosthetic valve **42** comprises nickel cobalt, stainless steel and/or titanium. During the advancing, prosthetic valve **42** is disposed in a distal portion of a delivery tube **60**, which holds the prosthetic valve in a compressed (e.g., crimped) configuration. Delivery tube **60** is slidably advanceable within overtube **44**. Prosthetic valve **42** is typically delivered through the native valve and into ventricle **28**, as shown in FIG. 1D. Typically, prosthetic valve **42** is delivered to the native valve while support **40** is held against the annulus of native valve **23** by holding members **46**.

(83) FIG. 1E shows prosthetic valve **42** being partially deployed from within delivery tube **60**. As prosthetic valve **42** expands, prosthetic valve **42** expands toward assuming an expanded configuration. Prosthetic valve **42** comprises a primary structural element **130**, which is typically cylindrical, prismatic, or any other suitable shape, and is shaped so to define a lumen. Prosthetic valve components (e.g., leaflets; not shown for clarity of illustration) are typically disposed within the lumen of the prosthetic valve, are coupled to a surface of structural element **130** defining the lumen, and regulate blood flow therethrough.

(84) Typically, a plurality of tissue-engaging elements **62** are disposed at a distal portion of the primary structural element **130** of prosthetic valve **42**. For applications in which prosthetic valve **42** comprises tissue-engaging elements **62**, tissue-engaging elements **62** comprise valve-anchoring elements **64**. For such applications of the present invention, primary structural element **130** of prosthetic valve **42** is generally cylindrical (e.g., shaped so as to define a right circular cylinder), and anchoring elements **64** protrude radially from a surface of the cylinder. It is to be noted that although prosthetic valve **42** is shown comprising tissue-engaging elements **62**, the scope of the present application includes prosthetic valves with no tissue-engaging elements **62**.

(85) FIG. 1F shows prosthetic valve **42** being moved proximally, such that at least part of primary structural element **130** is disposed in the respective lumens of native valve **23** and prosthetic valve support **40**, and such that valve-anchoring elements **64** contact the ventricular side of the native valve. Such contacting of elements **64** with the ventricular side of the native valve restricts further undesired atrial (i.e., proximal) movement of the prosthetic valve. Typically, the contact between valve-anchoring elements **64** and the ventricular side of the native valve occurs by valve-anchoring elements **64** protruding between chordae tendineae **80** and capturing leaflets **82** of the native valve. Responsively to the capturing by valve-anchoring elements **64**, leaflets **82** are typically pushed proximally and/or outward by the prosthetic valve. In some applications of the invention, leaflets **82** are held against the outer surface of primary structural element **130** by valve-anchoring elements **64**, so as to reduce blood flow between native leaflets **82** and prosthetic valve **42**. In an alternative application of the invention, rather than being partially deployed in the ventricle and subsequently moved proximally (as described with reference to FIGS. 1E-F), prosthetic valve **42** is deployed directly in the lumen of the native valve.

(86) Following the capturing of native leaflets **82**, prosthetic valve **42** is then fully exposed from within delivery tube **60** (by pushing valve **42** relative to delivery tube **60** or by retracting delivery tube **60** with respect to valve **42**) and is allowed to expand further. FIG. 1G shows prosthetic valve **42** in a deployed and expanded configuration after being fully exposed from within delivery tube **60**. The expansion of prosthetic valve **42** exerts a radial force against support **40**, thereby facilitating coupling of prosthetic valve **42** to support **40**. Implant **30**, comprising prosthetic valve **42** and support **40**, is secured in place by sandwiching the

native valve by the components of implant **30**. That is, (1) implant **30** is inhibited from ventricular (i.e., distal) movement by support **40** and the radial force of prosthetic valve **42** exerted on support **40**, and (2) implant **30** is inhibited from atrial (i.e., proximal) movement by valve-anchoring elements **64**.

(87) For some applications of the present invention, support **40** prevents valve **42** from expanding to assume a fully-expanded configuration (i.e., a configuration to which valve **42** would otherwise expand without being impeded by support **40** or tissue). In such applications, the radial force exerted by support **40** on valve **42** facilitates coupling and sealing between support **40** and valve **42** (for example, by increasing friction between support **40** and valve **42**), and facilitates implantation of implant **30** at native valve **23**.

(88) FIG. 1H shows implant **30** following implantation in the mitral valve of the subject. This figure is a transverse atrial cross-section, showing prosthetic valve support **40** in contact with the atrial side of the native valve. Prosthetic valve **42** is expanded, and is disposed in, and coupled to, prosthetic valve support **40**. Tissue-engaging elements **62**, comprising valve-anchoring elements **64**, are disposed on the ventricular side of the native valve (as described hereinabove with reference to FIGS. 1F-G), and are therefore illustrated in phantom. Valve-anchoring elements **64** are typically arranged in two clusters, each cluster being disposed on opposite sides of prosthetic valve **42**.

(89) Typically, when deployed as shown, prosthetic valve **42** is configured to be aligned with the native valve such that valve-anchoring elements **64** protrude toward, and engage leaflets **82** of the native valve. In some applications of the present invention, valve-anchoring elements **64** protrude toward, and engage, commissures **84** of the native valve. In some applications of the invention, a single valve-anchoring element **64** is disposed on each side of the prosthetic valve. It is to be noted that the scope of the present application includes any other suitable arrangement of valve-anchoring elements **64** with respect to valve **42**. Typically, valve-anchoring elements **64** capture leaflets **82** of the native valve, holding them clear of the flow of blood through the prosthetic valve and the left ventricular outflow tract (LVOT).

(90) For clarity of illustration, the lumen defined by prosthetic valve **42** is shown as being empty, such that ventricle **28** is visible. However, as described hereinabove, prosthetic valve **42** typically comprises valve components (e.g., prosthetic valve leaflets, not shown in FIG. 1H), that are disposed in the lumen of prosthetic valve **42**, coupled to structural element **130**, and configured to regulate blood flow through prosthetic valve **42**.

(91) Reference is again made to FIGS. 1A-H. For some applications, as described hereinabove, valve-anchoring elements **64** function so as to (1) prevent proximal migration of prosthetic valve **42** into the subject's atrium, while (2) creating a seal between the native valve **23** and prosthetic valve **42** by generally clamping native leaflets **82** between valve-anchoring elements **64** and primary structural element **130**, valve support **40**, and/or native valve annulus.

(92) For other applications, prevention of proximal migration of valve **42** is maintained, while movement of native leaflets **82** with respect to prosthetic valve **42** is allowed. For example, valve-anchoring elements **64** may have the aforementioned functionalities by having lengths of less than 5 mm, and/or by having a total width of each cluster of valve-anchoring elements (corresponding to respective leaflets of the native valve) being less than 5 mm. For example, the valve may include a single valve-anchoring element **64** corresponding to each leaflet of the native valve, the width of each of the single valve-anchoring elements being less than 1 mm. Thus, the valve may be stopped from proximally migrating into the atrium by the valve-coupling elements preventing the distal end of the valve from migrating further proximally than edges of native leaflets of the valve. Furthermore, the valve-anchoring elements may allow movement of the native leaflets with respect to the prosthetic valve by not generally squeezing the native leaflets between the valve-coupling elements and primary structural element **130** of the prosthetic valve. In other applications of the invention, prosthetic valve support **40** comprises support-anchoring elements (such as clips), and is directly coupled to the native valve. For some such applications, no valve-anchoring elements are used; rather, implant **30** is coupled to the native valve via prosthetic valve support **40** (e.g., as described hereinbelow, such as with reference to FIGS. 37A-H and 38A-H). For some applications, both valve-anchoring elements and support-anchoring elements are used. For some applications, by allowing movement of the native leaflets with respect to the prosthetic valve, sealing of the native leaflets against the outer surface of the primary structural element of the prosthetic valve is facilitated, in accordance with the techniques described herein.

(93) For some applications of the invention, the implantation of implant **30** follows an alternative order to that described with reference to FIGS. 1A-H. For these applications of the invention, prosthetic valve **42** is initially delivered to ventricle **28**. Subsequently, prosthetic valve support **40** is deployed within atrium **26**. In these applications of the invention, following deployment and positioning of prosthetic valve support **40**

against the annulus of native valve **23**, prosthetic valve **42** is moved atrially (i.e., proximally) into the respective lumens of the native valve and prosthetic valve support **40**, and is deployed, as described hereinabove.

(94) For some applications of the invention, valve-anchoring elements **64** anchor prosthetic valve **42** to the native valve in a manner that restricts both proximal and distal movement of the prosthetic valve. For such applications of the invention, deployment of prosthetic valve **42** may occur in the reverse orientation, such that, following positioning in the native valve of prosthetic valve **42** compressed in delivery tube **60**, the delivery tube is moved distally (i.e., ventricularly) as prosthetic valve **42** is deployed from the delivery tube. Delivery tube **60** is then removed from the subject via the lumen of the deployed prosthetic valve. It is hypothesized that this approach facilitates maneuvering of implant components and delivery apparatus, both for delivery of implant **30** and for withdrawal of delivery apparatus. For example, this approach is hypothesized to require less space on the proximal side of the native valve (e.g., in the atrium), compared to techniques whereby the prosthetic valve is deployed from the proximal side of the native valve. An example of this approach is described with reference to FIGS. **15A-E**.

(95) For some applications of the invention, surfaces of one or more components of implant **30** are covered at least in part with a covering (not shown). For example, surfaces of prosthetic valve support and prosthetic valve **42** may be covered so as to direct substantially all blood flowing through the valve, to flow through the lumen of prosthetic valve **42**. For some applications, the surface of prosthetic valve support **40** (or another component) that is placed in contact with the native valve is covered; the covering is configured to facilitate coupling of support **40** to the native valve, by enhancing fibrosis at the interface between the prosthetic valve support and the native valve.

(96) The covering may comprise polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), or pericardial tissue. Typically, a thickness of the covering is less than 0.2 mm, e.g., less than 0.1 mm, or less than 0.05 mm.

(97) For some applications, one or more dimensions of native valve **23** (e.g., of leaflets **82**, and/or of the annulus of the native valve) is measured (e.g., by using imaging techniques) prior to deployment of valve **42**. Taking this measuring into account, a suitably-sized prosthetic valve is chosen to be placed in the annulus, in a manner in which a cross-sectional area of the prosthetic valve in its deployed state is less than 90% (e.g., less than 80%, or less than 60%) of the area defined by the annulus.

(98) For some applications, the cross-sectional area of the prosthetic valve in its deployed state has a longest length of less than 25 mm, e.g., less than 20 mm, and/or more than 15 mm, e.g., 15-25 mm.

(99) For some applications, placing a prosthetic valve inside the native valve, with the dimensions of the native valve annulus and the prosthetic valve as described, facilitates sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve. In such applications, prosthetic valve **42** is implanted directly within native valve **23** (i.e., without support **40**).

(100) For some applications, prosthetic valve support **40**, that is shaped to define a lumen, is placed against the annulus of native valve **23** (e.g., as described with reference to FIGS. **1A-H**). The lumen of support **40** has a cross-sectional area that is less than 90% (e.g., less than 80%, or less than 60%) of an area defined by native valve **23** (e.g., area **A1**, FIG. **71**). As described hereinabove, prosthetic valve **42** is typically coupled to prosthetic valve support **40** and, thereby, to native valve **23**, at least in part by expansion of the prosthetic valve such that primary structural element **130** exerts a radial force against inner edge **68** of prosthetic valve support **40**. The cross-sectional area defined by the primary structural element **130** of the prosthetic valve, upon expansion of the prosthetic valve, is limited by the cross-sectional area of the lumen of the prosthetic valve support **40** to less than 90% (e.g., less than 80%, or less than 60%) of the area defined by the annulus of the native valve. For some applications, placing a prosthetic valve support **40** at the native valve, as described, facilitates sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve.

(101) Typically, placing a prosthetic valve inside the native valve with the dimensions of the native valve annulus, the prosthetic valve **42**, and/or valve support **40** as described in the above paragraphs, facilitates sealing of the prosthetic valve with respect to the native valve. For some applications, the sealing is facilitated by the native leaflets being pushed against, and closing against, the outer surface of the frame of the valve during systole, in a similar manner to the manner in which native valve leaflets coapt during systole, in a healthy mitral valve.

(102) Typically, as the diameter of the prosthetic valve is increased, the proportion of the native leaflets that is

pushed against the outer surface of the valve during systole is increased, thereby enhancing the sealing of the native leaflets with respect to the frame of the prosthetic valve. However, beyond a given diameter, as the diameter of the prosthetic valve is increased, the native valve leaflets are pushed apart at the commissures, thereby causing retrograde leakage of blood through the commissures. Therefore, in accordance with some applications of the present invention, prosthetic valve **42**, and/or valve support **40** are chosen such that the cross-sectional area of the prosthetic valve (when expanded inside the valve support) is less than 90% (e.g., less than 80%, or less than 60%) of the area defined by the annulus of native valve **23**. Thus, the valve support facilitates additional sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve, while not causing retrograde leakage of blood through the commissures.

(103) For some applications, in order to facilitate the sealing of the native valve around the outer surface of the prosthetic valve, a material is placed on the outer surface of the prosthetic valve in order to provide a sealing interface between the prosthetic valve and the native valve. For example, a smooth material that prevents tissue growth (e.g., polytetrafluoroethylene (PTFE), and/or pericardium) may be placed on the outer surface of the prosthetic valve. Alternatively or additionally, a material that facilitates tissue growth (such as polyethylene terephthalate; PET) may be placed on the outer surface of the prosthetic valve, in order to (a) act as a sealing interface between the native valve and the prosthetic valve, and (b) facilitate tissue growth around the prosthetic valve to facilitate anchoring and/or sealing of the prosthetic valve.

(104) For some applications, one or more dimensions of native valve **23** (e.g., of leaflets **82**, and/or of the annulus of the native valve) are measured (e.g., by using imaging techniques) prior to deployment of prosthetic valve **42** and/or prosthetic valve support **40**. Taking this measuring into account, a suitably-sized and/or suitably-configured prosthetic valve and/or prosthetic valve support is selected for implantation. For example, a prosthetic valve or prosthetic valve support comprising tissue-engaging elements **62** with appropriate configurations and/or dimensions may be selected.

(105) Reference is made to FIG. 2, which is a schematic illustration of prosthetic valve support **40**, comprising adjustable prosthetic valve support **40e**, which comprises tissue-engaging elements **62**, comprising support-anchoring elements **66e**, in accordance with some applications of the invention. Each support anchoring element **66e** comprises, or is coupled to, a holding wire **522**, which is slidably coupled to an upstream support portion **41** (e.g., an annular portion) of support **40e**. During implantation, support **40e** is anchored to native valve **23** via support-anchoring elements **66e**. For example, elements **66e** may engage commissures **84** or leaflets **82** of the native valve, as described hereinabove. The distance between upstream support portion **41** of support **40e** and a coupling portion **70** of anchoring element **66e**, is adjustable by adjusting the length of the portion of holding wire **522** that couples the upstream support portion to the coupling portion. Some examples of techniques for adjusting this length are described hereinbelow, with reference to FIGS. 3 and 4.

(106) For some applications of the invention, at least part of holding wire **522** is disposed in a connector **540**, which further couples coupling portion **70** to upstream support portion **41**. Holding wire **522** may be slidable through connector **540**. For some applications, connector **540** is more rigid than holding wire **522**.

(107) Reference is made to FIG. 3, which is a schematic illustration of prosthetic valve support **40**, comprising adjustable prosthetic valve support **40f**, which comprises tissue-engaging elements **62**, comprising support-anchoring elements **66f**, in accordance with some applications of the invention. Each support anchoring element **66f** comprises, or is coupled to, a holding wire **522f**, which is slidably coupled to upstream support portion **41** of support **40f**. During implantation, support **40f** is anchored to native valve **23** via support-anchoring elements **66f**. For example, elements **66f** may engage commissures **84** or leaflets **82** of the native valve, as described herein. The distance between upstream support portion **41** of support **40f** and a coupling portion of anchoring element **66f**, is adjustable by adjusting the length of holding wire **522f**.

Typically, holding wire **522f** is slidably coupled to upstream support portion **41** of support **40f** via a ratchet **526**, wherein holding wire **522f** is slidable through a ratchet housing **524**, and comprises a plurality of teeth **523** which allow the holding wire to slide through the ratchet housing in one direction, and restrict such sliding in another direction. Such adjustment of holding wire **522f** may be performed while support **40f** is partially deployed, or after the support has been fully deployed.

(108) FIG. 3 shows ratchet housing **524** being slidable over holding wire **522f**, such that the ratchet housing is movable with respect to upstream support portion **41** of support **40f**. For this application of the invention, a controller tube **528** is typically used to slide (e.g., push) ratchet housing **524** over holding wire **522f**, so as to adjust the distance between upstream support portion **41** of support **40f** and the coupling portion. For other

applications of the invention, ratchet housing 524 is substantially stationary with respect to upstream support portion 41 (e.g., ratchet housing 524 is attached to and/or embedded in portion 41), and holding wire 522 is slid (e.g., pulled) through housing 524, so as to adjust the distance between upstream support portion 41 of support 40f and coupling portion 70.

(109) As described with reference to FIG. 2, for some applications of the invention, at least part of holding wire 522 (e.g., wire 522f) is disposed in a connector 540 (e.g., connector 540f), which further couples coupling portion 70 to upstream support portion 41 of support 40f. Holding wire 522f may be slidable through connector 540f. Connector 540f is typically more rigid than holding wire 522f.

(110) It is hypothesized that adjusting the position of coupling portion 70 of support-anchoring elements 66f, with respect to upstream support portion 41 of prosthetic valve support 40f, allows prosthetic valve support 40f to be adapted to the anatomy of the subject during and/or subsequent to the implantation procedure.

(111) Reference is made to FIG. 4, which is a schematic illustration of prosthetic valve support 40, comprising adjustable prosthetic valve support 40g, which comprises tissue-engaging elements 62, comprising support-anchoring elements 66g, in accordance with some applications of the invention. Each support anchoring element 66g comprises, or is coupled to, a holding wire 522, which is slidably coupled to upstream support portion 41 of support 40g. During implantation, support 40g is anchored to native valve 23 via support-anchoring elements 66g. For example, elements 66g may engage commissures 84 or leaflets 82 of the native valve, as described herein. The distance between upstream support portion 41 of support 40g and a coupling portion 70 (not shown) of anchoring element 66g, is adjustable by adjusting the length of holding wire 522g. Holding wire 522g is coupled to a spool 460, such that operation (e.g., turning) of spool 460 withdraws and/or ejects portions of the holding wire, thereby adjusting the length of holding wire 522g that couples the upstream support portion to the coupling portion, thereby adjusting the distance between upstream support portion 41 and coupling portion 70. Such adjustment of holding wire 522g may be performed while support 40g is partially deployed, or after the support has been fully deployed.

(112) As described with reference to FIG. 2, for some applications of the invention, at least part of holding wire 522 (e.g., wire 522g) is disposed in a connector 540 (e.g., connector 540g), which further couples coupling portion 70 to upstream support portion 41 of support 40g. Holding wire 522g may be slidable through connector 540g. In some applications, connector 540g is more rigid than holding wire 522g.

(113) It is hypothesized that adjusting the position of coupling portion 70 of support-anchoring elements 66g, with respect to upstream support portion 41 of prosthetic valve support 40g, allows prosthetic valve support 40g to be adapted to the anatomy of the subject during and/or subsequent to the implantation procedure.

(114) Reference is made to FIG. 5, which is a schematic illustration of prosthetic valve support 40, comprising graduated prosthetic valve support 40h, which comprises tissue-engaging elements 62, comprising support-anchoring elements 66h, in accordance with some applications of the invention. Each support-anchoring element 66h is coupled to upstream support portion 41 of support 40h via a graduated connector 542. Graduated connector 542 comprises a plurality of coupling points 543, to which coupling portion 70 of element 66h is couplable. Prior to implantation of prosthetic valve support 40h, the distance between upstream support portion 41 of support 40h and coupling portion 70 is adjustable, by selecting the coupling point 543 to which each coupling portion 70 is coupled.

(115) It is hypothesized that adjusting the position of coupling portion 70 of support-anchoring elements 66h, with respect to upstream support portion 41 of prosthetic valve support 40h, allows prosthetic valve support 40h to be adapted to the anatomy of the subject during and/or subsequent to the implantation procedure.

(116) Reference is made to FIG. 6, which is a schematic illustration of prosthetic valve support 40, comprising flexibly-anchored prosthetic valve support 40i, which comprises tissue-engaging elements 62, comprising support-anchoring elements 66i, in accordance with some applications of the invention. Each support-anchoring element 66i is coupled to upstream support portion 41 of support 40i via a connector 540, such as flexible connector 544. Flexible connector 544 typically comprises a flexible material which typically, but not necessarily, comprises polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), silicone (e.g., silicone rubber), and/or or pericardial tissue. Flexible connector 544 facilitates movement of coupling portion 70 of elements 66i to move with respect to upstream support portion 41 of support 40i. It is hypothesized that this flexibility allows elements 66i to anchor prosthetic valve support 40i to the native valve (e.g., by coupling to leaflets 82), whilst allowing leaflets 82 to continue to function, at least in part.

(117) Reference is made to FIG. 7, which is a schematic illustration of prosthetic valve support 40, comprising flexibly-anchored prosthetic valve support 40j, which comprises tissue-engaging elements 62,

comprising support-anchoring elements **66j**, in accordance with some applications of the invention. Coupling portion **70** of each element **66j** is coupled to upstream support portion **41** of support **40j** via at least one connector ring **548**. Connector ring **548** typically facilitates movement of coupling portion **70** with respect to upstream support portion **41**. Each support-anchoring element **66j** typically comprises a connector **540**, such as flexible connector **546**. Flexible connector **546** typically comprises a flexible material which typically, but not necessarily, comprises polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), silicone (e.g., silicone rubber), and/or or pericardial tissue. Flexible connector **546** typically further facilitates coupling portion **70** to move with respect to upstream support portion **41** of support **40j**. It is hypothesized that this flexibility allows elements **66j** to anchor prosthetic valve support **40j** to the native valve (e.g., by coupling to leaflets **82**), whilst allowing leaflets **82** to continue to function, at least in part. (118) Reference is made to FIGS. **8A-B**, which are schematic illustrations of prosthetic valve support **40**, and prosthetic valve **42**, the prosthetic valve comprising an integrally-anchoring prosthetic valve **42a**, which comprises support-engaging elements **422** comprising a plurality of integral support-engaging elements **424**, in accordance with some applications of the invention. For some applications of the invention, support-engaging elements **422** comprise other valve-anchoring elements described herein, such as valve-anchoring elements **64**.

(119) Reference is now made to FIG. **8A**. Prosthetic valve **42a** comprises a lattice structure, comprising a plurality of struts which typically collectively define a tessellation of shapes and voids. In some regions of the prosthetic valve, there is a separation between adjacent shapes. This separation allows a portion of the shape to move or be moved out of the plane of the lattice, thereby protruding from primary structural element **130** of prosthetic valve **42a** when the prosthetic valve is expanded. The protruding portion of the shapes thereby form integral support-engaging elements **424**, which are typically configured to anchor prosthetic valve **42a** to the distal side of prosthetic valve support **40**.

(120) Reference is made to FIG. **8B**, which shows implant **30**, comprising prosthetic valve **42a** and prosthetic valve support **40**, implanted in native valve **23**. FIG. **8B** shows implant **30**, comprising prosthetic valve support **40** and prosthetic valve **42a**, implanted in native valve **23**, comprising mitral valve **24**. Prosthetic valve support **40** typically comprises a plurality of tissue-engaging elements **62**, comprising support-anchoring elements **66**, which engage leaflets **82** and/or chordae tendineae **80**, and/or commissures **84**, thereby anchoring support **40** to the native valve. Prosthetic valve **42a** is compressible (e.g., crimpable) and expandable, and typically comprises a shape-memory material, as described hereinabove with reference to prosthetic valve **42**. Prosthetic valve **42a** is configured (e.g., shape-set) such that support-engaging elements **422**, comprising integral support-engaging elements **424**, are biased to protrude from the surface of primary structural element **130**. In this application of the present invention, primary structural element **130** of prosthetic valve **42a** is generally cylindrical, and integral support-engaging elements **424** protrude radially from the surface of the cylinder. Because integral support-engaging elements **424** are formed from the regular repeating structure of the lattice that forms prosthetic valve **42a**, support-engaging elements **424** fit back into the plane of structural element **130** when valve **42a** is crimped into delivery tube **60**, prior to and even during implantation. Integral support-engaging elements **424**, thereby typically do not increase the length nor the transverse cross-sectional longest dimension of the crimped configuration of prosthetic valve **42**, as compared to those of any other prosthetic valves that do not comprise support-engaging elements **422**, or that comprise elements **422** at a proximal end thereof.

(121) As described hereinabove, prosthetic valve **42** is deployed by distal movement out of delivery tube **60**. FIG. **8B** shows prosthetic valve **42a** in a fully-deployed state, such that integral support-engaging elements **424** have emerged from delivery tube **60**, and have assumed an unconstrained, expanded, resting configuration in which the integral support-engaging elements **424** protrude radially from the surface of primary structural element **130** of the prosthetic valve. In an expanded state of at least the proximal portion of valve **42a**, as shown in FIG. **8B**, integral support-engaging elements **424** typically protrude up to and including 110 degrees (e.g., between 10 and 60 degrees, such as between 15 and 30 degrees) from the surface of primary structural element **130**, in a resting state of support-engaging elements **424**. That is, in the protruded state, the proximal portions of support-engaging elements **424** are distanced further from structural element **130** than the distal portions of support-engaging elements **424** which function as the pivot joints **74** between support-engaging elements **424** and structural element **130**, as shown in FIG. **8A**.

(122) In the expanded state of support-engaging elements **424**, the radially-protruding proximal portions thereof typically define a cross-sectional area, the longest dimension of which is typically longer than a transverse cross-sectional longest dimension of the lumen defined by prosthetic valve support **40**. That is, in

the expanded state, support-engaging elements **424** increase a longest transverse cross-sectional length of prosthetic valve **42a**, such that the longest transverse cross-sectional length is longer than a longest transverse cross-sectional length of the lumen defined by prosthetic valve support **40**. Thereby, the radially-protruding support-engaging elements **424** restrict proximal movement of prosthetic valve **42a** with respect to prosthetic valve support **40**, thereby anchoring prosthetic valve **42a** to the distal side of prosthetic valve support **40**, and to native valve **23**.

(123) Reference is made to FIGS. **9A-E**, which are schematic illustrations of delivery apparatus **438**, used to deploy a medical device **150**, in accordance with some applications of the invention. Delivery apparatus **438** comprises a delivery tube **154** and a pushing member **140**. Pushing member **140** comprises a support **142** and one or more coupling tabs **146**, extending from the support. In the application of the invention shown in FIG. **9A**, support **142** comprises a core **144**, and coupling tabs **146** extend radially from the core.

(124) In some applications of the invention, support **142** is shaped to define a plate **148** at the proximal end of support **142**. The dimensions and relative positions of support **142**, tabs **146**, and plate **148** may be adjusted for the specific medical device **150** to be deployed using delivery apparatus **438**. Support **142** is shaped to define a plurality of conduits **492** (e.g., holes). Delivery apparatus **438** further comprises one or more control filaments, such as retrieval wires **490**, slidably disposed in conduits **492**. Typically, conduits **492** provide communication between a proximal side of support **142** and a circumference of the support, such that a proximal end of each retrieval wire **490** is disposed at a site proximal to delivery tube **154**, and a distal end of each wire is reversibly coupled to medical device **150**, retrieval wires **490** extending through conduits **492**.

(125) For some applications of the invention, retrieval wires **490** are coupled to medical device **150** by being looped around parts of the medical device (e.g., looped around a strut of the lattice structure, as shown in FIG. **9D**), and are uncouplable from the medical device by being unlooped. For some applications of the invention, retrieval wires **490** are coupled to medical device **150** via a lock, such as a lock comprising a plug disposed in a tubular member (e.g., as described with reference to FIGS. **45A-C** and/or **64A-C**, mutatis mutandis). It is to be noted that the scope of the present application includes other techniques for coupling retrieval wires **490** to medical device **150**, and decoupling the retrieval wires. In the application of the invention described with reference to FIGS. **9A-E**, medical device **150** comprises prosthetic valve **42**.

(126) FIG. **9B** shows prosthetic valve **42** in a compressed (i.e., crimped) configuration for delivery and deployment using delivery apparatus **438**. Prosthetic valve **42** typically has a lattice structure that defines a plurality of shapes, and respective voids **126** (FIG. **9C**), and has shape memory (described in more detail hereinbelow, such as with reference to FIGS. **53A-C** and **62A-D**, mutatis mutandis). Prosthetic valve **42** is shown in a compressed (e.g., crimped) configuration, and as shown in the enlarged image, a proximal portion of valve **42** is disposed around (e.g., against) core **144** of pushing member **140** such that each of coupling tabs **146** is disposed within a respective void **126** defined by the lattice structure of the prosthetic valve.

(127) Prosthetic valve **42** and pushing member **140** are disposed within the lumen of delivery tube **154**. Delivery tube **154** restricts expansion of prosthetic valve **42**, thereby holding the proximal portion of prosthetic valve **42** around core **144** of pushing member **140**, in the configuration described herein. Coupling tabs **146** restrict movement of prosthetic valve **42** with respect to pushing member **140**. Delivery tube **154** therefore facilitates coupling of prosthetic valve **42** to pushing member **140** via coupling tabs **146**. In applications of the invention where pushing member **140** is shaped to define plate **148**, the plate typically further facilitates this coupling by restricting proximal movement of prosthetic valve **42** with respect to the pushing member (i.e., by functioning as a cap). Thereby, in the compressed configuration thereof, prosthetic valve **42** is configured to be fixedly coupled to pushing member **140**.

(128) A control tube **152** is typically coupled at a distal end thereof to pushing member **140** (e.g., control tube **152** is coupled to support **142**). Control tube **152** is shaped so as to define a lumen through which a guidewire tube **153** passes, and control tube **152** is slidable with respect to and along guidewire tube **153**. Guidewire tube **153** houses guidewire **45** described hereinabove. Control tube **152** is slidably disposed within a lumen of an overtube **155**.

(129) FIG. **9C** shows prosthetic valve **42** partially deployed from delivery tube **154**. Pushing member **140**, and, thereby, prosthetic valve **42**, are moved distally through delivery tube **154**.

(130) Reference is again made to FIG. **9C**. Pushing member **140** is pushed distally by pushing control tube **152** along guidewire tube **153** such that pushing member **140** pushes prosthetic valve **42**. As pushing member **140** pushes valve **42** distally, distal portions of the prosthetic valve expand toward the expanded configuration as they become exposed from delivery tube **154**, while the proximal end of valve **42** remains coupled to pushing member **140** via tabs **146**.

(131) FIG. 9D shows prosthetic valve 42 having been fully deployed from within delivery tube 154. Pushing member 140 and prosthetic valve 42 are moved further distally through delivery tube 154 by control tube 152. When the proximal portion of prosthetic valve 42 emerges from within delivery tube 154, expansion of the proximal portion of prosthetic valve 42 uncouples the prosthetic valve from coupling tabs 146 by expanding voids 126 away from tabs 146, thereby releasing the prosthetic valve from pushing member 140. For some applications, retrieval wires 490 are generally loose, such that expansion of prosthetic valve 42 pulls the wires through conduits 492, and radially outward from core 144. For some applications, retrieval wires 490 are under tension, and are released gradually, so as to control expansion of prosthetic valve 42. That is, for some applications, the expansion of prosthetic valve 42 is restricted (e.g., controlled) by the distal advancement of retrieval wires 490.

(132) Should it be necessary and/or desirable during deployment, until medical device 150 (e.g., prosthetic valve 42) is released from pushing member 140 (i.e., while the proximal portion of medical device 150 is crimped within delivery tube 154), the deployed, expanded portions of medical device 150 (i.e., the portions of medical device 150 that are exposed from delivery tube 154) may be drawn back into delivery tube 154 (e.g., for repositioning or withdrawal of the medical device).

(133) Subsequent to deployment of prosthetic valve 42, should it be necessary and/or desirable, the prosthetic valve may be drawn back against support 142 (e.g., radially inward) by proximally pulling retrieval wires 490. Subsequently, prosthetic valve 42 may be drawn back, along with pushing member 140, into delivery tube 154. That is, for some applications, prosthetic valve 42 is recompressible (i.e., the expansion of prosthetic valve 42 is at least in part reversible) by proximal retraction of retrieval wires 490.

(134) FIG. 9E shows retrieval wires 490 having been pulled proximally (e.g., by a user), such that wires 490 pull at least part of prosthetic valve 42 into a compressed configuration around and against support 142. Prosthetic valve 42 is thereby recoupled to pushing member 140. Pushing member 140 and prosthetic valve 42 are moved proximally and drawn into delivery tube 154. Prosthetic valve 42 may subsequently redeployed, or removed from the subject along with delivery tube 154.

(135) That is, (1) retrieval wires 490 are slidable through conduits 492 of core 144, and reversibly couplable to prosthetic valve 42, and (2) delivery apparatus 438 is configured to control and/or facilitate (a) expansion of prosthetic valve 42, by the retrieval wires being advanced distally through the conduits, and (b) recompression of prosthetic valve 42, by the retrieval wires being retracted proximally through the conduits.

(136) Reference is now made to FIGS. 9A-E and 1D-F. It is to be noted that delivery tube 154 of FIGS. 9A-E is similar to, and/or may comprise, delivery tube 60 of FIGS. 1D-F.

(137) Reference is made to FIG. 10, which is a schematic illustration of prosthetic valve support 40, comprising multi-lumen prosthetic valve support 40a, in accordance with some applications of the invention. As described hereinabove, prosthetic valve support 40 is generally annular and shaped to define a lumen, in which prosthetic valve 42 is deployed and expanded. In the application of the invention illustrated in FIG. 10, prosthetic valve support 40, comprising multi-lumen prosthetic valve support 40a, is shaped to define two or more lumens. That is, the wire frame of support 40a defines two or more lumens. Prosthetic valve support 40a is typically couplable to the native valve using techniques described herein for coupling other prosthetic valve supports to the native valve. For example, prosthetic valve support 40a may comprise tissue-engaging elements (e.g., support-anchoring elements). Similarly, other prosthetic valve supports described herein may comprise prosthetic valve support 40a.

(138) Prosthetic valve support 40a is typically covered with a covering 440, such as a fabric. Covering 440 may comprise polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), or pericardial tissue. Typically, a thickness of covering 440 is less than 0.2 mm, e.g., less than 0.1 mm, or less than 0.05 mm. When support 40a is supplied and/or implanted, covering 440 typically covers support 40a such that only a first lumen 444 is open and configured to receive a prosthetic valve, and the second lumen 446 is closed. That is, the wire frame of support 40a defines two or more lumens but the covering defines only one lumen, thereby covering 440 functions as a seal 442.

(139) In some applications of the invention, covering 440 is not disposed over second lumen 446; rather a different element functions as seal 442. For example, a weaker and/or softer material (e.g., pericardial tissue) or a removable plug may be coupled to prosthetic valve support 40a, and disposed over second lumen 446 to function as seal 442.

(140) Implant 30, comprising prosthetic valve 42 and prosthetic valve support 40a, is implanted in native valve 23 (e.g., as described with reference to FIGS. 1A-H, mutatis mutandis), whereby prosthetic valve 42 is deployed in first lumen 444 of the support. At a later time, a second prosthetic valve

may be introduced by deploying the second prosthetic valve in second lumen **446**. That is, at a first period, prosthetic valve support **40a** facilitates implantation of a first prosthetic valve at the native valve, and at a second period, the prosthetic valve support facilitates implantation of a second prosthetic valve at the native valve. In some applications of the invention, seal **442** is opened, and thereby configured to receive a prosthetic valve (e.g., by being broken, cut and/or torn) by the introduction of the second prosthetic valve. In other applications, seal **442** is opened with a cutting tool (not shown) prior to deployment of the second prosthetic valve. In some applications of the invention, seal **442** is uncoupled from support **40a**, prior to deployment of the second prosthetic valve.

(141) For some applications of the invention, following the deployment of the second prosthetic valve, the first prosthetic valve (i.e., prosthetic valve **42**) is disabled (e.g., sealed). For example, an expandable plug may be expanded in the lumen of the first prosthetic valve.

(142) Prosthetic cardiac valves typically require replacement after several years (e.g., after 2-20 years, such as after 5-10 years). For example, the condition of the subject may change and/or components of the prosthetic valve (e.g., prosthetic valve leaflets) may suffer fatigue. It is hypothesized that multi-lumen prosthetic valve support **40a** allows a second prosthetic valve to be implanted in the native valve, the second prosthetic valve being supported by the originally-implanted prosthetic valve support **40a**. The first prosthetic valve may be sealed, for example, if the original prosthetic valve allows, or is predicted to allow, retrograde leakage.

Implantation of a second prosthetic valve is hypothesized to increase the lifespan of implant **30**.

(143) Reference is made to FIG. **11**, which is a schematic illustration of prosthetic valve support **40**, comprising extended-lumen prosthetic valve support **40e**, in accordance with some applications of the invention. As described hereinabove, prosthetic valve support **40** is generally annular and shaped to define a lumen, in which prosthetic valve **42** is deployed and expanded. Extended-lumen prosthetic valve support **40e** is shaped to define a lumen **448**, which has an extended dimension. That is, the wire frame of support **40e** typically defines lumen **448**, which has (1) a primary region **447**, and (2) a secondary region **449** that is generally not filled by expansion of prosthetic valve **42** in the lumen. Typically, lumen **448** has a first length that is longer than, and generally orthogonal to, a second length, and has one or more concave portions. For example, lumen **448** may be generally shaped to define an oval or ellipse with one or more concave portions generally midway along the first length (e.g., a Cassini oval or a hippopedé). Prosthetic valve support **40e** is typically couplable to the native valve using techniques described herein for coupling other prosthetic valve supports to the native valve. For example, prosthetic valve support **40e** may comprise tissue-engaging elements (e.g., support-anchoring elements). Similarly, other prosthetic valve supports described herein may comprise prosthetic valve support **40e**.

(144) Prosthetic valve support **40e** is typically covered with a covering **440**, such as a fabric. Covering **440** may comprise polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), or pericardial tissue. Typically, a thickness of covering **440** is less than 0.2 mm, e.g., less than 0.1 mm, or less than 0.05 mm. When support **40e** is supplied and/or implanted, covering **440** typically covers support **40e** such that secondary region **449** is closed. That is, the wire frame of support **40e** defines a generally elongated lumen **448**, whilst covering **440** defines a generally round primary region **447**. In this manner, covering **440** functions as a seal **442** over secondary region **449**.

(145) In some applications of the invention, covering **440** is not disposed over secondary region **449**; rather a different element functions as seal **442**. For example, a weaker and/or softer material (e.g., pericardial tissue) or a removable plug may be coupled to prosthetic valve support **40e**, and disposed over secondary region **449**, so as to function as seal **442**.

(146) Implant **30**, comprising prosthetic valve **42** and prosthetic valve support **40e**, is implanted in native valve **23** (e.g., as described with reference to FIGS. **1A-H**), whereby prosthetic valve **42** is deployed in primary region **447** of the support. At a later time, a second prosthetic valve may be introduced by deploying the second prosthetic valve in secondary region **449**. That is, at a first period, prosthetic valve support **40e** facilitates implantation of a first prosthetic valve at the native valve, and at a second period, the prosthetic valve support facilitates implantation of a second prosthetic valve at the native valve. In some applications of the invention, seal **442** is opened (e.g., broken, cut and/or torn) by the introduction of the second prosthetic valve. In other applications, seal **442** is opened with a cutting tool (not shown) prior to deployment of the second prosthetic valve. In some applications of the invention, seal **442** is uncoupled from support **40e**, prior to deployment of the second prosthetic valve.

(147) Typically, expansion of the second prosthetic valve during deployment deforms the first prosthetic valve (i.e., a radially-expansive force of the second prosthetic valve is stronger than that of the first prosthetic

valve). For example, following deployment of the second valve, the first valve may assume a lune shape or a generally semicircular shape. In some applications of the invention, the second prosthetic valve is shaped to fit into secondary region **449** without deforming the first prosthetic valve.

(148) Prosthetic cardiac valves typically require replacement after several years (e.g., after 2-20 years, such as after 5-10 years). For example, the condition of the subject may change and/or components of the prosthetic valve (e.g., prosthetic valve leaflets) may suffer fatigue. It is hypothesized that extended-lumen prosthetic valve support **40** allows a second prosthetic valve to be implanted in the native valve, the second prosthetic valve being supported by the originally-implanted prosthetic valve support **40**. The first prosthetic valve may be sealed, as described hereinabove, for example, if the original prosthetic valve allows, or is predicted to allow, retrograde leakage. Implantation of a second prosthetic valve is hypothesized to increase the lifespan of implant **30**.

(149) Reference is made to FIGS. **12A-B**, which are schematic illustrations of prosthetic valve support **40**, comprising adjustable-lumen prosthetic valve support **40b**, in accordance with some applications of the invention. As described hereinabove, expansion of prosthetic valve **42** is restricted by the lumen of prosthetic valve support **40**. As further described hereinabove, the optimum lumen size may depend on the individual subject and/or condition being treated. Adjusting the size of the lumen of prosthetic valve **42** is hypothesized to alter the flow of blood through the prosthetic valve, and the sealing of leaflets **82** of the native valve against the outer surface of the prosthetic valve. In some applications of the invention, the size of the area defined by the annulus of the native valve is measured (e.g., using a measuring ring and/or using imaging techniques), and appropriately-sized prosthetic valve **42** and prosthetic valve support **40** are selected for implantation. FIGS. **12A-B** show adjustable-lumen prosthetic valve support **40b**, which comprises a spool **461** and a tightening wire **462**. Tightening wire **462** typically forms a loop around a central portion of support **40b** (e.g., threadedly coupled around an inner edge **68**), and is coupled to spool **461** such that the tightening wire can be tightened (i.e., shortened) via spool **461**. FIG. **12A** shows support **40b** with a larger lumen (i.e., when tightening wire **462** is relatively loose) and FIG. **12B** shows support **40b** with a smaller lumen, following tightening of tightening wire **462** with a tightening tool **464**.

(150) For some applications, prosthetic valve support **40b** and prosthetic valve **42** are implanted as described herein (e.g., with reference to FIGS. **1A-H**), and tightening wire **462** is subsequently tightened. For some applications, the annulus of the native valve is measured, and tightening wire **462** is responsively adjusted, prior to implantation. For some applications, following measurement of the native valve, and prior to implantation, a support **40b** of appropriate size is selected from a range.

(151) Reference is made to FIGS. **13A-D**, which are schematic illustrations of prosthetic valve support **40**, comprising asymmetric prosthetic valve support **40c**, in accordance with an application of the invention. As described hereinabove, support **40** is generally annular, and shaped to define a lumen. FIG. **13A** shows that the lumen defined by support **40c** (i.e., oblique lumen **480**) is typically not central with respect to the support. That is, support **40c** is typically rotationally asymmetric. Support **40c** typically defines a total cross-sectional area of between 16 cm^2 and 38 cm^2 (e.g., between 22 cm^2 and 28 cm^2). Typically, the cross-sectional area of lumen **480** is less than 70% (e.g., less than 60%, or less than 40%) of the cross-sectional area of area of support **40c**. For example, for some applications, the cross-sectional area of lumen **480** has a longest length of less than 25 mm, e.g., less than 20 mm, and/or more than 15 mm, e.g., 15-25 mm. As described hereinabove, for some applications, surfaces of prosthetic valve support **40** are covered with a covering so as to direct substantially all blood to flow through the lumen of prosthetic valve **42**. Asymmetric prosthetic valve support **40c** is typically not covered, i.e., the lattice structure of which the support is comprised, is exposed.

(152) FIG. **13B** shows prosthetic valve support **40c** having been deployed to the annulus of native valve **23**, as described herein (e.g., with reference to FIGS. **1A-H**). For the applications of the invention described with reference to FIGS. **13A-D**, prosthetic valve support typically comprises a plurality of tissue-engaging elements (e.g., support-anchoring elements), such as those described herein (not shown in FIGS. **13A-D**). Support-anchoring elements **66** are typically configured and oriented to engage commissures **84** of the native valve, so as to anchor support **40** to the native valve whilst allowing leaflets **82** to continue to function. Prosthetic valve support **40c** is typically deployed to native valve **23** such that lumen **480** is positioned over (i.e., proximal to) a place of coaptation of the two leaflets **82** of the native valve. Subsequently, prosthetic valve **42** is deployed in lumen **480** (as described hereinabove; e.g., with reference to FIGS. **1A-H**), such that, in the expanded state, prosthetic valve **42** is disposed between leaflets **82**.

(153) FIG. **13C** shows implant **30**, comprising prosthetic valve support **40c** and prosthetic valve **42**,

implanted in native valve **23**, in accordance with an application of the invention. Typically, but not necessarily, prosthetic valve **42** does not comprise valve-anchoring elements **64**. Rather, prosthetic valve **42** is typically anchored to native valve **23** by being coupled to support **40c**, which is, itself, anchored to the native valve, as described hereinabove. Prosthetic valve **42** is positioned between leaflets **82** of the native valve, due to the oblique position of lumen **480** of support **40c**. Typically, leaflets **82** are generally free to move with respect to the prosthetic valve, and move proximally and distally with the beating of the heart, coapting and sealing around prosthetic valve **42**. This movement of leaflets **82** is facilitated by support **40c** being uncovered and fluid communication being maintained between atrium **26** and ventricle **28** through the lattice structure of support **40c**. For example, when native valve **23** comprises mitral valve **24**, during diastole, leaflets **82** open, and left atrial blood moves into the left ventricle, both through and around prosthetic valve **42** (i.e., through the lumen of prosthetic valve **42** and through the exposed lattice structure of support **40c**). During systole, leaflets **82** close, i.e., coapt together, and seal around prosthetic valve **42**, restricting retrograde movement of blood.

(154) It is hypothesized that over a period of time (e.g., a week, e.g., a month, e.g., a year) following implantation of implant **30** comprising support **40c**, movement of leaflets **82** is reduced (e.g., due to tissue growth and/or calciferous deposits), such that the functionality of native valve **23** is gradually reduced, and the proportion of blood that flow through prosthetic valve **42**, relative to that which flows around the prosthetic valve, is increased. That is, over time, prosthetic valve **42** takes over the function of native valve **23**.

(155) Reference is made to FIG. **14**, which is a schematic illustration of prosthetic valve support **40**, comprising prosthetic valve support **40d**, which comprises tissue-engaging elements **62**, comprising a plurality of support-anchoring elements **66a**, in accordance with some applications of the invention. Typically, support **40d** comprises two elements **66a**, typically coupled to inner edge **68**, and positioned generally opposite each other. Elements **66a** typically comprise two or more (e.g., three) coupling portions **70**, which extend radially from a structural component **71**. FIG. **14** shows elements **66a** comprising three coupling portions **70**, arranged in a T-shape. Support **40d** is typically deployed in the native valve such that elements **66a** are oriented toward commissures **84** of the native valve, and engage both the commissures and the closest regions of leaflets **82**. It is hypothesized that this structure and positioning of elements **66a** anchor support **40d** to the native valve, whilst allowing leaflets **82** to move, thereby allowing native valve **23** to continue to function, at least partly, until prosthetic valve **42** is deployed.

(156) Reference is made to FIGS. **15A-E**, which are schematic illustrations of the implantation of prosthetic valve support **40** and prosthetic valve **42**, in accordance with some applications of the invention. Prosthetic valve **42** is compressible (e.g., crimpable) and expandable, and typically comprises a shape-memory material, as described hereinabove. FIG. **15A** shows prosthetic valve support **40** having been deployed to the annulus of native valve **23**, and prosthetic valve **42** having been delivered, in the crimped configuration thereof, within delivery tube **60a**, to the native valve. Prosthetic valve **42** and delivery tube **60a** are disposed in the lumen of native valve **23**. Leaflets **82** of the native valve typically coapt and seal around delivery tube **60a**. The proximal end of delivery tube **60a** is shown open.

(157) FIG. **15B** shows delivery tube **60a** being moved distally while prosthetic valve **42** remains relatively stationary, thereby exposing the prosthetic valve from the delivery tube. As portions of prosthetic valve **42** are exposed, they expand from the crimped configuration to an expanded configuration. Typically, expansion of the proximal portion of prosthetic valve **42** facilitates coupling of the prosthetic valve to prosthetic valve support **40**. In the application of the invention illustrated by FIGS. **15A-E**, prosthetic valve **42** is shaped to define a widened proximal end, which facilitates coupling of prosthetic valve **42** to prosthetic valve support **40**. It is to be noted that the scope of the present application includes other configurations of prosthetic valve **42**, such as those included herein.

(158) FIG. **15C** shows delivery tube **60a** having been removed entirely from prosthetic valve **42**, and prosthetic valve **42** having expanded to its expanded configuration, the expansion facilitating coupling of the prosthetic valve to support **40** and, thereby, native valve **23**. Delivery tube **60a** is shown in left ventricle **28** of the heart.

(159) FIGS. **15D** and **15E** show delivery tube **60a** being withdrawn proximally, through the lumen of prosthetic valve **42**. Delivery tube **60a** is subsequently removed from the subject. Typically, delivery tube **60a** is withdrawn between leaflets of prosthetic valve **42** (not shown), which are typically disposed in the lumen of the prosthetic valve. Typically, delivery tube **60a** is withdrawn into overtube **44** prior to removal from the subject. It is to be noted that the scope of the present application includes deployment of the prosthetic valve

from the distal (i.e., ventricular) side of native valve **23**, and the withdrawal of the delivery tube via the lumen of the prosthetic valve. It is hypothesized that this approach facilitates maneuvering of implant components and delivery apparatus, both for delivery of implant **30** and for withdrawal of delivery apparatus. For example, this approach is hypothesized to require less space on the proximal side of the native valve (e.g., in atrium **26**), compared to techniques whereby the prosthetic valve is deployed from the proximal side of the native valve.

(160) Reference is made to FIG. **16**, which is a schematic illustration of prosthetic valve support **40** being deployed in native valve **23**, comprising mitral valve **24**, in accordance with some applications of the invention. Support **40** is typically delivered to the native valve in a compressed (e.g., crimped) configuration, within overtube **44**. In the compressed configuration, support **40** typically assumes a tubular shape, having a proximal end and a distal end. Typically, the distal end is defined by inner edge **68** (described hereinabove), and tissue-engaging elements **62**, comprising support-anchoring elements **66**, extend distally from the distal end. To deploy support **40**, the support is moved (e.g., pushed) through overtube **44**, such that support-anchoring elements **66** emerge from the overtube. Support-anchoring elements **66** engage native valve **23**, typically by grasping leaflets **82**, commissures **84**, and/or chordae tendineae **80** of the native valve. Subsequently, the remaining portions of support **40** (e.g., upstream support portion **41**) are moved out of overtube **44**, and support expands to assume its expanded, generally annular, shape. Prosthetic valve support **40** is thereby anchored to the native valve, typically with upstream support portion **41** held against the annulus of the native valve, by support-anchoring elements **66** (e.g., as described hereinabove).

(161) In some applications of the invention, support-anchoring elements **66** are configured and/or arranged so as to anchor prosthetic valve support **40** to the native valve (e.g., by engaging leaflets **82**, and/or commissures **84**, and/or chordae tendineae **80**), whilst allowing leaflets **82** to continue to function, at least in part.

(162) In some applications of the invention, should it be necessary and/or desirable, support **40** is retrievable before it is fully deployed, by withdrawing the support proximally, back into overtube **44**.

(163) In some applications, should it be necessary and/or desirable, support **40** is retrievable after it has been fully deployed. For example, support **40** may be drawn back around and against a pushing member of delivery apparatus, recompressing support **40** for withdrawal into a delivery tube, in a similar way to the technique described with reference to FIGS. **9A-E**, mutatis mutandis. Prosthetic valve support **40** may subsequently be removed from the subject, and/or repositioned, and/or redeployed.

(164) Reference is made to FIGS. **17A-D**, which are schematic illustrations of support **40**, comprising tissue-engaging elements **62**, which comprise support-anchoring elements **66**, comprising length-adjustable holding elements **600**, in accordance with some applications of the invention. Native heart valves vary naturally in various dimensions, such as, but not limited to, the length, width and/or thickness of leaflets **82**, the distance between commissures **84**, and/or the distance between fibrous trigones. In this context, in the specification and in the claims, these varying parameters are referred to as “dimensions.” Length-adjustable holding elements **600** are configured such that the distance between coupling portion **70** and upstream support portion **41** of prosthetic valve support **40** is adjustable. This adjustability typically facilitates placement (i.e., implantation) of the prosthetic valve support at native valves of different dimensions, such that (1) upstream support portion **41** is placeable against the proximal (i.e., atrial) side of the prosthetic valve, and (2) coupling portion **70** is placeable on the distal (i.e., ventricular) side of the native valve (e.g., to engage the native leaflets and/or commissures, as described hereinabove).

(165) For some applications, coupling portions **70** engage (e.g., are coupled to) leaflets **82** and/or commissures **84** of native valve **23** while prosthetic valve support **40** is still in a partially-deployed configuration (e.g., as described with reference to FIGS. **1B** and **16**). For some applications, support is first expanded, upstream support portion **41** is then placed against the annulus of the native valve, and coupling portions **70** subsequently engage (e.g., are coupled to) the leaflets and/or commissures.

(166) In the applications of the invention described with reference to FIGS. **17A-D**, holding elements **600** are typically biased to assume a contracted configuration, and are typically expanded (e.g., stretched) so as to couple portions **70** to the native valve. This bias thereby provides a pulling force, which is hypothesized to facilitate coupling of prosthetic valve support **40** to native valve **23** by sandwiching the native valve between upstream support portion **41** and coupling portion **70**, in some applications of the invention.

(167) Typically, adjustment and/or other manipulation of support-anchoring elements **66**, comprising length-adjustable holding elements **600**, may be performed prior to the implantation procedure, e.g., following imaging-based sizing of one or more dimensions of native valve **23** (e.g., of leaflets **82**, and/or of the annulus of the native valve), and/or during the implantation procedure (e.g., when the prosthetic valve support is at the

site of implantation).

(168) FIG. 17A shows prosthetic valve support **40**, comprising prosthetic valve support **40n**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66n**. Each support-anchoring element **66n** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40n** via a length-adjustable holding element **600**, comprising a stretchable holding element **600n**. Stretchable holding element **600n** comprises a tension spring, typically comprising a coil spring. Stretchable holding element **600n** facilitates adjusting the distance between coupling portion **70** and upstream support portion **41** such that, for native valves of different dimensions, (1) upstream support portion **41** is placeable against the proximal (i.e., atrial) side of the prosthetic valve, and (2) coupling portion **70** is placeable on the distal (i.e., ventricular) side of the native valve (e.g., to engage the native leaflets and/or commissures, as described hereinabove).

(169) FIG. 17B shows prosthetic valve support **40**, comprising prosthetic valve support **40p**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66p**. Each support-anchoring element **66p** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40p** via length-adjustable holding element **600**, comprising a stretchable holding element **600p**. Stretchable holding element **600p** comprises a tension spring, typically comprising a zigzag-shaped piece of material, such as a shape-memory material, e.g., nitinol. Stretchable holding element **600p** facilitates adjusting the distance between coupling portion **70** and upstream support portion **41** such that, for native valves of different dimensions, (1) upstream support portion **41** is placeable against the proximal (i.e., atrial) side of the prosthetic valve, and (2) coupling portion **70** is placeable on the distal (i.e., ventricular) side of the native valve (e.g., to engage the native leaflets and/or commissures, as described hereinabove).

(170) FIG. 17C shows prosthetic valve support **40**, comprising prosthetic valve support **40q**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66q**. Each support-anchoring element **66q** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40q** via length-adjustable holding element **600**, comprising a stretchable holding element **600q**. Stretchable holding element **600q** comprises a tension spring, typically comprising an elastic tube **602**, such as a tube of elastic silicone. Stretchable holding element **600q** facilitates adjusting the distance between coupling portion **70** and upstream support portion **41** such that, for native valves of different dimensions, (1) upstream support portion **41** is placeable against the proximal (i.e., atrial) side of the prosthetic valve, and (2) coupling portion **70** is placeable on the distal (i.e., ventricular) side of the native valve (e.g., to engage the native leaflets and/or commissures, as described hereinabove).

(171) For some applications of the invention, stretchable holding element **600q** further comprises a limiting wire **604**, typically coupled to upstream support portion **41** and coupling portion **70**. Limiting wire **604** is generally non-elastic, and is configured to limit the expansion (i.e., stretching) of holding element **600q**. For example, limiting wire may be configured to prevent overstretching of holding element **600q**, e.g., to prevent failure of the holding element. Typically, limiting wire **604** is longer than the length of elastic tube **602** in the relaxed (i.e., contracted) configuration thereof, and is shorter than the length of elastic tube **602** in a maximally-expanded (i.e., maximally-stretched) configuration thereof. In the relaxed (i.e., contracted) configuration of elastic tube **602**, limiting wire **604** is typically loose (e.g., generally bent, crumpled, flexed). When elastic tube **602** is expanded (i.e., stretched), limiting wire **604** typically becomes taut (e.g., generally straight), thereby limiting the expansion of elastic tube **602** to generally the length of limiting wire **604**.

(172) It is to be noted that the scope of the present invention includes the use of limiting wire **604** in combination with other length-adjustable holding elements including, but not limited to, stretchable holding element **600n**, described with reference to FIG. 17A.

(173) FIG. 17D shows prosthetic valve support **40**, comprising prosthetic valve support **40u**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66u**. Each support-anchoring element **66u** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40u** via a length-adjustable holding element **600**, comprising a stretchable holding element **600u**. Stretchable holding element **600u** facilitates adjusting the distance between coupling portion **70** and upstream support portion **41** such that, for native valves of different dimensions, (1) upstream support portion **41** is placeable against the proximal (i.e., atrial) side of the prosthetic valve, and (2) coupling portion **70** is placeable on the distal (i.e., ventricular) side of the native valve (e.g., to engage the native leaflets and/or commissures, as described hereinabove). Stretchable holding element **600u** comprises a tension spring, typically comprising a coil spring **610**. For some applications of the invention, coil spring **610** is generally similar to the coil spring of stretchable holding element **600n**, as described hereinabove. Stretchable holding element **600u** further comprises, or is coupled to, a restrictor **612**. Restrictor **612** typically holds spring **610** in an expanded (i.e.,

stretched) configuration. Typically, restrictor **612** is decouplable from spring **610**. For some applications, restrictor **612** may be mechanically removed by the user. For some applications, restrictor **612** may comprise a material that disintegrates in the body (e.g., a material that is at least in part soluble and/or biodegradable and/or bioresorbable). For these applications, restrictor **612** typically disintegrates over a predictable period of time e.g., between 15 minutes and 1 week, such as between 30 minutes and 3 days, for example, between 1 h and 1 day. For some applications, restrictor **612** is configured to decouple from (i.e., release) spring **610** gradually, e.g., in stages. For some applications, restrictor **612** is coupled to spring **610** and/or another part of prosthetic valve support **40u**, such that, following the release of spring **610**, the restrictor is retained so as not to enter the vasculature of the subject.

(174) When spring **610** is released from restrictor **612**, the spring relaxes (i.e., contracts), and provides a pulling force that sandwiches the native valve between support **40u** and coupling portion **70**, e.g., as described hereinabove, *mutatis mutandis*.

(175) Reference is made to FIGS. **18A-B**, which are schematic illustrations of prosthetic valve support **40**, which comprises support-anchoring elements **66**, comprising length-adjustable holding elements **600**, in accordance with some applications of the invention.

(176) FIG. **18A** shows prosthetic valve support **40**, comprising prosthetic valve support **40r**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66r**. Each support-anchoring element **66r** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40r** via length-adjustable holding element **600**, comprising a telescopic holding element **600r**. Telescopic holding element **600r** comprises a plurality of portions, typically cylinders, which are slidable over and/or through each other. FIG. **18A** shows telescopic holding element **600r** comprising two externally-threaded cylinders connected by an internally-threaded cylinder, and configured such that rotation of the internally-threaded cylinder with respect to the externally-threaded cylinders adjusts the distance between the externally-threaded cylinders. Thereby, rotation of the internally-threaded cylinder adjusts the distance between coupling portion **70** and upstream support portion **41**. Adjustment of this distance may be performed prior to implantation of prosthetic valve support **40r**, and/or during the implantation procedure (e.g., after deployment of support **40r**).

(177) Reference is again made to FIGS. **17A-D**, and **18A-B**. The applications of the invention described with reference to FIGS. **17A-D**, comprise support-anchoring elements **66** that comprise length-adjustable holding elements **600**, such as stretchable holding elements **600n**, **600p**, and **600q**. In addition to being axially stretchable, these holding elements are typically laterally flexible. This flexibility is hypothesized to be advantageous in some applications of the invention. For example, in some applications, leaflets **82** of the native valve may continue to function, at least in part, after support-anchoring elements **66** are coupled to the leaflets. In contrast, the adjustable holding elements **600** described with reference to FIGS. **18A-B** (i.e., elements **600r** and **600t**) are typically laterally rigid.

(178) Reference is again made to FIG. **18B**, which shows prosthetic valve support **40**, comprising prosthetic valve support **40t**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66t**, in accordance with some applications of the invention. Each support-anchoring element **66t** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40t** via length-adjustable holding element **600**, comprising a telescopic holding element **600t**. Telescopic holding element **600r** comprises a plurality of portions, typically cylinders, which are slidable over and/or through each other. FIG. **18B** shows telescopic holding element **600t** comprising two overlapping cylinders. Sliding of the cylinders over each other adjusts the distance between coupling portion **70** and upstream support portion **41**. Adjustment of this distance may be performed prior to implantation of prosthetic valve support **40t**, and/or during the implantation procedure (e.g., after deployment of support **40t**).

(179) Typically, telescopic holding element **600t** further comprises another element (not shown), which controls and/or adjusts the sliding of the cylinders described hereinabove. For example, element **600t** may comprise a tension spring, such as those described with reference to FIGS. **17A-D**, typically disposed inside the lumen defined by the overlapping cylinders. The combination of the tension spring with the overlapping cylinders combines the stretchability described with reference to FIGS. **17A-D**, with the rigidity described with reference to FIGS. **18A-B**.

(180) Reference is made to FIG. **19**, which is a schematic illustration of prosthetic valve support **40**, comprising prosthetic valve support **40v**, which comprises support-anchoring elements **66**, comprising support-anchoring elements **66v**, in accordance with some applications of the invention. Each support-anchoring element **66v** comprises a coupling portion **70**, coupled to upstream support portion **41** of support **40v** via length-adjustable holding element **600**, comprising length-adjustable holding element **600v**. Element

600v comprises a strap **630** and a strap adjuster **632** (e.g., a buckle, a ladder lock, a tri-glide). Strap **630** and adjuster **632** are configured and arranged such that the distance between coupling portion **70** and upstream support portion **41** is adjustable by sliding adjuster **632** along strap **630**, and/or by sliding at least part of strap **630** through adjuster **632**. That is, strap **630** and strap adjuster **632** are generally similar to the strap and adjuster of a bag, such as a backpack. Adjustment of element **600v** may be performed prior to implantation of prosthetic valve support **40v**, and/or during the implantation procedure (e.g., after deployment of support **40v**).

(181) Non-limiting examples of materials which strap **630** and/or strap adjuster **632** may comprise, include polyester, PTFE (e.g., ePTFE), nylon, cotton, nitinol, stainless steel, nickel cobalt, and cobalt chrome.

(182) Reference is made to FIGS. **20A-F**, which are schematic illustrations of prosthetic valve support **40**, comprising support-anchoring elements **66**, comprising flexible support-anchoring elements **720**, in accordance with some applications of the invention. Elements **720** comprise a coupling portion **70** and a connector **540**, which comprises (1) a flexible material **722**, such as a fabric (e.g., covering **440**), pericardial tissue, and/or a polymer, and (2) one or more stiffening filaments **724**. Filaments **724** typically comprise a material that is stiffer and/or more resilient than flexible material **722**. For example, filaments **724** may comprise a metallic or plastic wire. Filaments **724** are coupled to material **722**, such as by weaving and/or by gluing. The absolute and relative quantities and configurations of material **722** and filaments **724**, may be generated and/or selected so as to provide a desired stiffness of an element **720**. For example, an element **720** that comprises more and/or more densely-woven stiffening filaments **724** may be selected for applications that require a stiffer element **720**. Conversely, an element **720** that comprises fewer and/or less densely-woven stiffening filaments **724** may be selected for applications that require a more flexible element **720**. FIGS. **20A-F** show elements **720** comprising flexible support-anchoring elements **720a-f**, comprising various relative quantities of material **722** and filaments **724**, in accordance with respective applications of the invention. These figures are not intended to limit the scope of the invention but, rather, to illustrate the variability of the invention as a whole, and of elements **720** in particular.

(183) For some applications, a kit is provided, containing a plurality of prosthetic valve supports **40**, each prosthetic valve support comprising a flexible support-anchoring element **720** having a different configuration of material **722** and filaments **724**, and thereby a different flexibility (e.g., elements **720a-720f**). A user typically selects a support **40** that comprises a support-anchoring element **720** of a desired configuration for a particular application.

(184) For some applications, a kit is provided, containing (1) at least one prosthetic valve support (i.e., upstream support portion **41**), and (2) a plurality of flexible support-anchoring elements **720**, each element **720** having a different configuration of material **722** and filaments **724**, and thereby a different flexibility. A user typically (1) selects a support-anchoring element **720** of a desired configuration for a particular application, and (2) couples the selected element **720** to the upstream support portion **41**.

(185) For some applications, a kit is provided, containing (1) at least one prosthetic valve support (i.e., upstream support portion **41**), (2) at least one coupling portion **70**, and (3) a plurality of connectors **540**, each connector **540** having a different configuration of material **722** and filaments **724**, and thereby a different flexibility. A user typically (1) selects a connector **540** of a desired configuration for a particular application, and (2) couples the selected connector **540** to the coupling portion **70**, and to the upstream support portion **41**.

(186) Reference is made to FIGS. **21A-C**, which are schematic illustrations of prosthetic valve **42**, comprising prosthetic valve **42j**, in accordance with some applications of the invention. Prosthetic valve **42j** comprises at least one support-engaging element **422**, comprising inflatable support-engaging element **426**, disposed on the outer surface of primary structural element **130** of prosthetic valve **42j**. FIGS. **21A-B** show prosthetic valve **42j** comprising one annular inflatable support-engaging element **426**, disposed circumferentially around primary structural element **130**. Typically, prosthetic valve support **40** comprises one or more support-anchoring elements (not shown; e.g., support-anchoring elements **66**, as described herein) which anchor the prosthetic valve support to native valve **23**.

(187) FIG. **21A** shows prosthetic valve **42j** and prosthetic valve support **40**. Following the deployment of prosthetic valve support **40** against the annulus of native valve **23**, prosthetic valve **42j** is passed through the lumen of the prosthetic valve support as described hereinabove (e.g., with reference to FIGS. **1A-H**). As described hereinabove, prosthetic valve **42j** is typically less than fully expanded (e.g., prosthetic valve **42j** is partially expanded) when it is passed through the lumen of the prosthetic valve. Accordingly, FIG. **21A** shows prosthetic valve **42j** in a partially-expanded configuration.

(188) FIG. **21B** shows prosthetic valve **42j** having been expanded in the lumen of prosthetic valve support **40**,

such that inflatable support-engaging element **426** is disposed distal (e.g., ventriculally) to prosthetic valve support **40**. Element **426** is inflated (e.g., with saline) and thereby expands, thereby increasing a longest transverse cross-sectional length of prosthetic valve **42j**, such that the transverse cross-sectional length is longer than a longest transverse cross-sectional length of the lumen defined by prosthetic valve support **40**. Thereby, inflatable support-engaging element **426** restricts proximal movement of prosthetic valve **42j** with respect to prosthetic valve support **40**, thereby anchoring prosthetic valve **42j** to the distal side of prosthetic valve support **40**, and to native valve **23**.

(189) Inflatable support-engaging element **426** is typically coupled to prosthetic valve **42** such that the prosthetic valve is compressible (i.e., crimpable) for delivery, as described hereinabove. For some applications, inflatable support-engaging element **426** is coupled to the prosthetic valve using sutures. Typically, such sutures are arranged in a single circumferential suture line, so as to facilitate deformation (e.g., flattening) of element **426** during crimping of the prosthetic valve for delivery. For some applications, element **426** is coupled to the prosthetic valve using an adhesive.

(190) FIG. **21C** shows implant **30**, comprising prosthetic valve support **40** and prosthetic valve **42j**, implanted at native valve **23**, comprising mitral valve **24**. Support **40** is deployed against the proximal (i.e., atrial) surface of the annulus of the native valve, and is typically coupled to the valve via support-anchoring elements **66** (not shown). Prosthetic valve **42j** is deployed in the lumen of support **40** such that, when inflated, element **426** restricts proximal movement of the prosthetic valve with respect to support **40**. *Ibis* restriction, combined with the coupling of support **40** to the native valve, couples implant **30** to the native valve.

(191) For some applications of the invention, prosthetic valve **42j** is deployed in the lumen of support **40**, such that element **426** is disposed on the proximal side of support **40**. It is hypothesized that, when in this position and inflated, element **426** restricts distal movement of the prosthetic valve with respect to the support.

(192) For some applications of the invention, prosthetic valve **42j** is deployed in the lumen of support **40**, such that element **426** is planar with upstream support portion **41** of the support, and such that at least part of element **426** is disposed proximal to portion **41**, and at least part of element **426** is disposed distal to portion **41**. It is hypothesized that, when in this position and inflated, element **426**: (1) applies a radially-expansive force on support **40** (i.e., supplements radially-expansive forces applied by prosthetic valve **42** on support **40**), and (2) restricts proximal and distal movement of the prosthetic valve with respect to the support.

(193) Reference is made to FIGS. **22A-C**, which are schematic illustrations of the implantation of implant **30**, comprising prosthetic valve support **40** and prosthetic valve **42**, coupled by one or more (e.g., 2 or more, such as 4) coupling leads **840** (e.g., coupling wires), in accordance with some applications of the invention. For delivery, coupling leads **840** are coupled to prosthetic valve support and prosthetic valve **42**. For some applications, coupling leads **840** are slidably coupled to support and/or prosthetic valve **42**. For example, within overtube **44**, prosthetic valve **42** may be disposed proximally to support **40**, and coupled to support **40** by being slidably coupled to coupling leads **840**.

(194) FIG. **22A** shows prosthetic valve support **40**, having been coupled to native valve **23**, comprising mitral valve **24**. For example, support **40** may be coupled to the native valve using techniques described herein (e.g., via support-anchoring elements **66**). Support **40** is coupled to coupling leads **840**, which extend from support **40** to at least prosthetic valve **42**, which remains disposed within overtube **44**.

(195) FIG. **22B** shows prosthetic valve **42** having been deployed in the lumen of support **40**, and in the lumen of native valve **23**, as described herein, mutatis mutandis. Coupling leads **840** extend from support **40**, through a proximal portion (e.g., an upstream portion and/or proximal portion **110**) of prosthetic valve **42**, and into overtube **44**. Typically, coupling lead **840** comprises a plurality of teeth **846**, typically disposed at a distal end of the coupling lead. A controller tube **844** is typically used to slide (e.g., push) ratchet housing **842** over coupling lead **840**, and over teeth **846**, such that the proximal portion of prosthetic valve **42** is pushed against support **40**. Teeth **846** allow ratchet housing **842** to slide over coupling lead **840** in one direction, and inhibit (e.g., restrict) such sliding in another (e.g., the opposite) direction. Pushing prosthetic valve **42** against support **40** using controller tube **844** and ratchet housing **842**, thereby facilitates coupling of prosthetic valve **42** to support **40**. Thereby, sliding of ratchet housing **842** over coupling lead **840** facilitates coupling of the prosthetic valve to the prosthetic valve support.

(196) Reference is made to FIG. **22C**. Following the coupling of prosthetic valve **42** to prosthetic valve support **40**, and thereby the implantation of implant **30** in native valve **23**, coupling leads are typically cut at a point proximal to ratchet housing **842**, and overtube **44** is withdrawn from the subject.

(197) Reference is made to FIGS. **23A-24**, which are schematic illustrations of prosthetic valve support **40**,

comprising prosthetic valve support **40w**, which is shaped to define at least one pocket **640**, in accordance with some applications of the invention. Prosthetic valve support **40** (i.e., support **40w**) typically comprises a wire frame, such as an expandable wire frame. For some applications, the wire frame of support **40w** is shaped to define pocket **640**. For some applications, the wire frame of prosthetic valve support **40** (i.e., support **40w**) is generally covered with a covering (such as a fabric, e.g., as described herein). For some applications, the covering may form at least one wall of pocket **640**.

(198) FIG. **23A** shows an application of support **40w**, comprising upstream support portion **41** that comprises a wire frame **642**, generally covered with a covering **644**. In this application, pocket **640** is generally annular, and circumscribes the lumen defined by support **40w** (i.e., the lumen defined by upstream support portion **41** of support **40w**). That is, the lumen defined by support **40w** can be considered to be defined by two holes: (1) a proximal (i.e., upper) hole defined by a proximal (i.e., upper) wall of pocket **640**, and (2) a distal (i.e., lower) hole defined by a distal (i.e., lower) wall of pocket **640**. FIGS. **23A-24** show both walls of pocket **640** as having a generally similar depth. That is, a longest dimension of the distal hole is generally equal to the longest dimension of the proximal hole. For some applications, the two holes are generally not equally dimensioned. For example, to facilitate deployment of prosthetic valve **42** and/or coupling of prosthetic valve **42** to support **40w**, one of the holes that defines the lumen of support **40w** may have a smaller longest dimension than the other hole.

(199) FIG. **23B** shows prosthetic valve **42** comprising support-engaging elements **422** (e.g., prosthetic valve **42a** comprising integral support-engaging elements **424**, as described with reference to FIG. **8A**), coupled to prosthetic valve support **40w**. Elements **422** typically define a cross-sectional area, the longest dimension of which is typically longer than a transverse cross-sectional longest dimension of the lumen defined by prosthetic valve support **40w** (i.e., of the upper and/or lower holes described with reference to FIG. **23A**). During deployment, elements **422** are placed within pocket **640**. Thereby, in addition to the radially-expansive force that typically couples prosthetic valve **42** to support **40**, the radially-protruding support-engaging elements **422** restrict axial (i.e., proximal and distal) movement of prosthetic valve **42** with respect to support **40w**, thereby anchoring prosthetic valve **42** to support **40w**, and to native valve **23**.

(200) For some applications, prosthetic valve is provisionally expanded (1) sufficiently such that elements **422** protrude into pocket **640** and prevent axial movement of prosthetic valve **42**, but (2) insufficiently for radially-expansive forces to fixedly couple the prosthetic valve to prosthetic valve support **40w**. In this configuration, a user may rotate the prosthetic valve to a desired orientation, before finally allowing the prosthetic valve to expand and become coupled to support **40w**.

(201) FIG. **24** shows prosthetic valve **42**, configured to comprise an expanded proximal portion **110** of primary structural element **130**. Proximal portion **110** defines a cross-sectional area with a longest length that is longer than a transverse cross-sectional longest dimension of the lumen defined by prosthetic valve support **40w** (i.e., of the upper and/or lower holes described with reference to FIG. **23A**). During deployment, portion **110** is placed within pocket **640**. Thereby, in addition to the radially-expansive force that typically couples prosthetic valve **42** to support **40**, portion **110** restricts axial (i.e., proximal and distal) movement of prosthetic valve **42** with respect to support **40w**, thereby anchoring prosthetic valve **42** to support **40w**, and to native valve **23**.

(202) Reference is made to FIGS. **25A-E**, which are schematic illustrations of sequential steps in the use of a retrieval device **800**, in accordance with some applications of the invention. Retrieval device **800** comprises a plurality of struts **804**, and typically comprises a shaft **802**, with which struts **804** are axially aligned, and around which the struts are circumferentially disposed. A coupling element **805**, such as a hook **806**, is coupled to a middle portion of each strut.

(203) Reference is made to FIGS. **25A-B**. At some time subsequent to implantation of a prosthetic valve (i.e., prosthetic valve **42**), it may be necessary and/or desirable to retrieve the prosthetic valve (i.e., to remove the prosthetic valve from the subject). Typically, retrieval device **800** is delivered to the site of the prosthetic valve (i.e., to the native valve) in and/or using an overtube **808**. Retrieval device **800** is advanced toward prosthetic valve **42**, and into the lumen defined by the prosthetic valve.

(204) FIG. **25C** shows middle portions of struts **804** being extended radially outward from shaft **802**. Typically, one or more middle portions of struts **804** are extended radially outward by reducing the distance between the proximal end and the distal end of each strut. For example, struts **804** may be bent and/or folded. In the application of the invention shown in FIGS. **25A-E**, retrieval device further comprises a cuff **810**, coupled to the proximal ends of struts **804**, and slidably coupled to shaft **802**. Movement of cuff **810** distally, reduces the distance between the proximal and distal ends of struts **804**, thereby extending the middle

portions of the struts radially outward.

(205) FIG. 25D shows two, respectively orthogonal, cross-sectional views of retrieval device **800** in the lumen of prosthetic valve **42**. The middle portions of struts **804** have been extended radially outward, and typically make contact with prosthetic valve **42**. Prosthetic valve **42** is typically covered with a covering, which facilitates the desired flow of blood through the prosthetic valve. The covering may comprise polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), pericardial tissue, or any other suitable material. Hooks **806** protrude through wire frame **812** of prosthetic valve **42**, and typically do not extend through covering **814**. Following the extension of the middle portions of struts **804**, coupling element **805** is coupled to (e.g., hooks **806** are hooked around) wire frame **812** of prosthetic valve **42**. For example, hooks **806** are arranged to point in the same direction as each other (e.g., such that all hooks point clockwise, or all hooks point anticlockwise). Following extension of the middle portions of struts **804**, retrieval device **800** is rotated, such that hooks **806** hook around wire frame **812**, between the wire frame and covering **814**.

(206) Reference is made to FIG. 25E. Following coupling of coupling elements **805** (i.e., hooks **806**) to wire frame **812** of prosthetic valve **42**, the middle portions of struts **804** are retracted radially inward, i.e., toward shaft **802**. For example, the distance between proximal and distal ends of struts **804** is increased, e.g., by sliding cuff **810** proximally. Because struts **804** are coupled to the wire frame, prosthetic valve **42** is drawn radially inward. That is, prosthetic valve **42** is compressed (i.e., re-crimped). Retrieval device **800** and prosthetic valve **42** are drawn into overtube **808**, and subsequently removed from the subject.

(207) FIGS. 25A-E illustrate each strut **804** having two outwardly-extendable middle portions, in order to couple to, and compress prosthetic valve **42** at/from two sites (i.e., a proximal site and a distal site). It is hypothesized that the use of device **800** comprising struts **804** with different numbers and/or configurations of outwardly-extendable middle portions, allows the compression and/or retrieval of prosthetic valve of different dimensions and/or configurations.

(208) Reference is again made to FIGS. 25A-E. For some applications, a hem **820** is disposed within, and slidable through overtube **808**. Hem **820** is advanced out of the overtube during or after the advancement of retrieval apparatus, and expands, such that a distal portion of the hem defines a lumen that has a longer transverse cross-sectional area than that of overtube **808** (e.g., as shown in FIGS. 25B-C). When retrieval device **800** and prosthetic valve **42** are drawn into overtube **808**, at least proximal portions of the retrieval apparatus and prosthetic valve are first drawn into hem **820**. Hem **820** facilitates the drawing in of the retrieval apparatus and prosthetic valve, by widening the effective open end of the overtube, and/or by reducing resistance between the prosthetic valve **42** and overtube **808**. Although hem **820** is described herein with respect to the use of retrieval device **800**, it is to be noted that the scope of the present invention includes the use of hem **820** in combination with any retrieval apparatus.

(209) Reference is made to FIGS. 26A-C, which are schematic illustrations of prosthetic valve support **40**, comprising a braided prosthetic valve support **860**, in accordance with some applications of the invention. As described hereinabove, support **40** is typically expandable, and typically comprises a shape-memory material. Support **860** typically further comprises a braided structure, comprising a plurality of intertwining strands **862**. At least some regions of strands **862** are slidable past (e.g., over, under) each other. Typically, strands **862** comprise a shape-memory material such as, but not limited to, nitinol. In an expanded state (i.e., uncompressed), support **40** is annular, and is shaped to define a lumen therethrough. For delivery, support **860** is typically advanced through the vasculature of the subject in a compressed configuration, e.g., within an overtube **44**. FIG. 26A shows support **860** being deployed from overtube **44** at native valve **23** (i.e., proximal to the native valve). Typically, support **860** is deployed proximal to the native valve.

(210) FIG. 26B shows sequential illustrations of the expansion of support **860** as it is deployed from overtube **44**. Support **860** is typically coupled to a restricting element, such as drawstring **864**, in a manner that at least partly restricts expansion of the support. FIG. 26B shows drawstring **864** threaded through a plurality of rings **866**, disposed at the proximal end of support **860**, whereby both ends of drawstring **864** are disposed proximal to the open distal end of overtube **44** (e.g., within overtube **44**, and/or outside the body of the subject).

Drawstring **864** thereby forms a closed loop that is coupled to rings **866** and, thereby, to support **860**. Once support **860** has been fully ejected from overtube **44**, tension on drawstring **864** typically restricts expansion of support **860**. Subsequently, at least one end of drawstring **864** is moved distally (i.e., the drawstring is at least partially loosened), such that support **860** moves toward its uncompressed, expanded shape. When support **860** is successfully positioned (i.e., when a user determines that the support is in the desired position), one end of drawstring **864** is released, typically in combination with drawing (i.e., retracting) the other end of

drawstring **864** proximally, thereby releasing support **860** from the drawstring.

(211) FIG. **26C** shows prosthetic valve support **860** in its fully-expanded configuration, against the proximal (i.e., atrial) side of the annulus of native valve **23**. One end of drawstring **864** has been released, and the drawstring is shown being retracted proximally.

(212) Throughout the deployment of prosthetic valve support **860**, until the release of one end of drawstring **864**, support **860** may be retrieved by moving drawstring **864** proximally (i.e., pulling the drawstring). Pulling the drawstring (1) tightens the loop formed by the drawstring, thereby bringing rings **866** closer to each other, and compressing the proximal portion of support **860**, and (2) draws support **860** into overtube **44**. Thus, a user can determine if and/or when to release support **860**, throughout the deployment procedure.

(213) Reference is made to FIGS. **27A-D**, which are schematic illustrations of delivery apparatus **880**, and the use thereof, in accordance with some applications of the invention. FIGS. **27A-D** show apparatus **880** being used to deliver and deploy a medical device **150**, comprising prosthetic valve **42**, to native valve **23**.

Apparatus **880** comprises a plurality of control filaments **882**, disposed and slidable within respective guide elements, such as rail-pairs **884** (e.g., between individual rails thereof). Rail-pairs **884** are typically extendable. For example, rail-pairs **884** may comprise sections that are slidable over and/or through each other, such that the rail-pairs are telescopically extendable. Apparatus **880** typically comprises a core **886**, from which rail-pairs **884** typically protrude radially, such that extension of rail-pairs **884** comprises outwardly-radial extension of the rail-pairs from core **886**.

(214) Apparatus **880** has a contracted configuration and an extended configuration, is typically reversibly movable between these two configurations, and is further typically movable into continuous configurations between the contracted and extended configurations. FIG. **27A** shows apparatus **880** in the contracted configuration. In the contracted configuration, rail-pairs **884** are typically telescopically retracted, such that apparatus **880** is disposable in delivery tube **60**. That is, in the contracted configuration, a longest length of a transverse cross-section of apparatus **880** is smaller than a longest length of a transverse cross-section of delivery tube **60**.

(215) FIG. **27B** shows medical device **150**, comprising prosthetic valve **42**, being deployed from delivery tube **60**, at native valve **23**, using apparatus **880**. Apparatus **880** is coupled to a portion (e.g., a proximal portion) of prosthetic valve **42**, and is disposed within delivery tube **60**. Apparatus **880** is thereby not visible in FIG. **27B**. A distal portion of prosthetic valve **42** has been exposed from delivery tube **60**, and has begun to expand toward its expanded configuration. Typically, prosthetic valve **42** is moved with respect to delivery tube **60** (e.g., is pushed out of the delivery tube) by core **886**, which thereby acts as a pushing member.

(216) As described hereinabove, prosthetic valve **42** typically comprises a shape-memory material, and expands toward its expanded configuration as it is exposed from delivery tube **60**. In the application of the invention described with reference to FIGS. **27A-D**, apparatus **880** typically controls this expansion. Control filaments **882** are typically coupled (e.g., slidably coupled) to prosthetic valve **42**, e.g., via respective coupling pins **888**, which are couplable to prosthetic valve **42**, and slidably couplable to control filaments **882**. Release wires **892** facilitate the coupling of control filaments **882** to prosthetic valve **42**, e.g., by facilitating the coupling of coupling pins **888** to prosthetic valve **42**.

(217) Control filaments **882** (e.g., proximal portions thereof) are distally advanceable, and proximally retractable, through a control tube **890**, e.g., using a control unit external to the subject. Control filaments **882** are slidably couplable to core **886** and/or control tube **890**, such as being slidable through respective conduits (e.g., holes) in the core or the control tube. The expansion of apparatus **880**, and thereby that of prosthetic valve **42**, is restricted and/or facilitated (e.g., controlled) by the distal advancement and/or proximal retraction of control filaments **882**. In the application of the invention illustrated in FIGS. **27A-D**, control filaments **882** form respective loops. The size of the loops is increased when the control filaments are distally advanced, and reduced when the control filaments are proximally retracted. When the loops are small, control filaments **882** restrict expansion of prosthetic valve **42**. Distal advancement of control filaments **882**, and the resulting enlargement of the loops formed thereof, facilitates the expansion of prosthetic valve **42**.

(218) FIG. **27C** shows apparatus **880** in its expanded configuration. FIG. **27D** shows apparatus **880** in its expanded configuration, coupled to prosthetic valve **42**, during the deployment of the prosthetic valve. Rail-pairs **884** protrude radially from core **886**, and control filaments **882** remain coupled to the prosthetic valve, facilitated by release wires **892**, as described hereinabove. Rail-pairs **884** typically facilitate (e.g., guide) the expansion of prosthetic valve **42**.

(219) When prosthetic valve **42** is successfully positioned (i.e., when a user determines that the prosthetic valve is in the desired position), prosthetic valve **42** is released from control filaments **882**, e.g., by pulling

release wires **892** proximally. Release of prosthetic valve **42** allows (1) the prosthetic valve to expand further (e.g., until it couples to, and is restricted by, support **40**), and/or (2) control filaments **882** to be retracted, and rail-pairs **884** to be telescopically retracted, such that apparatus **880** is retractable into delivery tube **60**.

(220) For some applications, rail-pairs **884** are biased toward moving into the contracted configuration thereof, are pulled radially outward by the expansion of prosthetic valve **42**, and automatically return to the contracted configuration upon release of the prosthetic valve. For example, the rail-pairs may provide a contractive force, and the prosthetic valve may provide an expansive force that is sufficient to overcome the contractive force, and thereby to pull the rail-pairs radially outward. Upon release of the prosthetic valve, the contractive force automatically returns the rail-pairs to the contracted configuration thereof. Alternatively or additionally, rail-pairs **884** may be actively controllable (e.g., extracorporeally) by a user.

(221) For some applications of the invention, proximal portions of control filaments **882** are coupled to each other (e.g., fixedly coupled to each other, such as adhered and/or welded to each other), such that the plurality of control filaments are synchronously distally advanceable, and synchronously proximally retractable, e.g., via a control rod and/or control unit.

(222) For some applications of the invention, proximal portions of release wires **892** are coupled to each other (e.g., fixedly coupled to each other, such as adhered and/or welded to each other), such that the plurality of release wires are pullable synchronously, e.g., via a control rod and/or control unit, thereby facilitating synchronous release of control filaments **882**.

(223) Throughout the deployment of prosthetic valve **42** using apparatus **880**, until the release of the prosthetic valve from control filaments **882**, prosthetic valve **42** may be re-compressed (e.g., for repositioning and/or retrieval into delivery tube **60**) by proximally retracting control filaments **882**. Thus, a user can determine if and/or when to release prosthetic valve **42**, throughout the deployment procedure. That is, prosthetic valve **42** is recompressible (i.e., the expansion of prosthetic valve **42** is at least in part reversible) by proximal retraction of control filaments **882**.

(224) That is, (1) control filaments **882** are slidable through conduits of core **886**, and reversibly couplable to prosthetic valve **42**, and (2) delivery apparatus **880** is configured to control and/or facilitate (a) expansion of prosthetic valve **42**, by the control filaments being advanced distally through the conduits, and (b) recompression of prosthetic valve **42**, by the control filaments being retracted proximally through the conduits.

(225) Reference is made to FIGS. **28A-30B**, which are schematic illustrations of techniques for replacement of a prosthetic valve, in accordance with some applications of the invention. It is noted that in the context of the present patent application, the term “replacement” with respect to a prosthetic valve includes both (a) placement at a valve site of a new prosthetic valve while removing or disabling a prosthetic valve that was already at the valve site, as well as (b) placement of a new prosthetic valve at the valve site without removing or disabling a prosthetic valve that was already at the site.

(226) Prosthetic cardiac valves typically require replacement after a duration (e.g., after between 1 month and 10 years, such as after between 1 and 5 years). For example, the condition of the subject may change, components of the prosthetic valve (e.g., prosthetic valve leaflets, sutures, frame) may suffer fatigue, and/or tissue growth may block blood flow or otherwise interfere with prosthetic valve function.

(227) The prosthetic valve supports described with reference to FIGS. **28A-30B** are typically couplable to the native valve using techniques described herein for coupling other prosthetic valve supports to the native valve. For example, the prosthetic valve supports described with reference to FIGS. **28A-30B** may comprise tissue-engaging elements (e.g., support-anchoring elements), such as those described herein. Similarly, other prosthetic valve supports described herein may comprise the upstream support portions and/or the cylindrical elements of the prosthetic valve supports described with reference to FIGS. **28A-30B**.

(228) Reference is now made to FIGS. **28A-D**. FIGS. **28A-B** show implant **30**, comprising prosthetic valve **42** coupled to prosthetic valve support **40**, such as described hereinabove with reference to the implantation of implant **30** (e.g., with reference to FIGS. **1A-H**). FIG. **28A** shows a side view and FIG. **28B** shows a top view. At such a time that it is deemed necessary and/or desirable to replace prosthetic valve **42**, a second prosthetic valve **42'** is delivered to the lumen of the first prosthetic valve, and deployed therein. Generally, delivery and deployment of prosthetic valve **42'** is performed using similar techniques to those used to deploy prosthetic valve **42**.

(229) FIGS. **28C-D** show second prosthetic valve **42'** in an expanded configuration within the lumen of prosthetic valve **42**. FIG. **28C** shows a side view and FIG. **28D** shows a top view. Both prosthetic valve **42** and prosthetic valve **42'** comprise valve components, typically valve leaflets **660**, disposed in the lumen of the

prosthetic valve. As it expands, prosthetic valve 42' typically pushes aside leaflets 660 of prosthetic valve 42. Prosthetic valve 42' exerts radially-expansive forces against the inner surface of prosthetic valve 42, thereby coupling prosthetic valve 42' to prosthetic valve 42. In some applications, leaflets 660 are sandwiched between prosthetic valve 42 and prosthetic valve 42' (i.e., between the primary structural elements 130 of the prosthetic valves). In some applications, leaflets 660 facilitate sealing between the two prosthetic valves. Following the deployment of prosthetic valve 42', leaflets 660' of prosthetic valve 42' begin to function, thereby replacing the function of leaflets 660. Typically, diameter d2 of deployed prosthetic valve 42' is smaller than diameter d1 of deployed prosthetic valve 42. Typically, the difference in diameter is caused at least in part by prosthetic valve 42 restricting the expansion of prosthetic valve 42'.

(230) Reference is now made to FIGS. 29A-F. FIGS. 29A-B show implant 30, comprising prosthetic valve 42 coupled to prosthetic valve support 40, comprising prosthetic valve support 40x. FIG. 29A shows a side view and FIG. 29B shows a top view. As described hereinabove, prosthetic valve support is generally annular, and typically comprises a wire frame and/or a shape-memory material. For some applications, the wire frame of prosthetic valve support 40 (i.e., wire frame 672 of support 40x) is generally covered with covering 440 (such as a fabric, e.g., as described herein). Support 40x typically comprises a weak zone 670 that circumscribes the lumen defined by the support (i.e., the lumen defined by upstream support portion 41 of support 40x).

(231) For some applications, wire frame 672 does not extend into weak zone 670; rather the weak zone only comprises covering 440. For some applications, a stretchable and/or breakable reinforcing-wire 674 is disposed at or near inner edge 68 of upstream support portion 41 of support 40x. For some applications, wire frame 672 has a different structure in weak zone 670 than in other regions of upstream support portion 41 of support 40x. For example, wire frame 672 may comprise fewer struts in weak zone 670.

(232) FIG. 29C shows an expanding device, such as a balloon 678, having been delivered to the lumen of prosthetic valve 42, and being used to expand (e.g., to enlarge) the lumen of the prosthetic valve and the lumen of prosthetic valve support 40x. FIG. 29D shows a transverse cross-sectional view of support 40x and prosthetic valve 42, following the expansion of the lumen of the prosthetic valve with balloon 678. At such a time that it is deemed necessary and/or desirable to replace prosthetic valve 42, balloon 678 is delivered to the prosthetic valve and inflated (e.g., using saline), such that it applies a radially-expansive force, from within the lumen of prosthetic valve 42, to the prosthetic valve and support 40x. Typically, the radially-expansive force applied by the balloon is greater than the radially-expansive force applied by prosthetic valve 42 on support 40 (i.e., support 40x), that typically couples prosthetic valve 42 to support 40. For some applications, balloon 678 is shaped to define a lumen, so that blood can continue to flow while the balloon is expanded. For some such applications, balloon 678 comprises a temporary prosthetic valve (i.e., one or more temporary prosthetic valve leaflets), disposed in the lumen of the balloon, and configured to further facilitate continued blood flow while the balloon is expanded.

(233) The radially-expansive force applied by balloon 678 increases the lumen of prosthetic valve 42, typically by increasing the lumen of support 40x by deforming (e.g., crushing) weak zone 670. For example, a material which weak zone 670 comprises may be compressed, broken, bent, stretched and/or torn (e.g., reinforcing wire 674 may be broken and/or covering 440 may be stretched and/or torn). Balloon 678 is subsequently removed from the subject. Typically, leaflets 660 continue to function at least in part until second prosthetic valve 42' is deployed.

(234) For some applications, leaflets 660 are disposed in a portion of prosthetic valve 42 that is distal (i.e., ventricular) to the portion of prosthetic valve 42 that is coupled to prosthetic valve support 40x. For these applications, balloon 678 is typically disposable in a proximal portion of valve 42, and thereby may be used to increase the lumen of prosthetic valve 42, without damaging (e.g., crushing) leaflets 660.

(235) FIGS. 29E-F show second prosthetic valve 42' in an expanded configuration within the lumen of prosthetic valve 42. FIG. 29E shows a side view and FIG. 29F shows a top view. Prosthetic valve 42' exerts radially-expansive forces against the inner surface of prosthetic valve 42, thereby coupling prosthetic valve 42' to prosthetic valve 42. Because the lumen of prosthetic valve 42 is initially expanded, as described hereinabove, a diameter d3 of the lumen defined by prosthetic valve 42' may not be smaller than the diameter d1 of the lumen originally defined by prosthetic valve 42 (i.e., d3 may be at least as great as d1). For example, diameter d3 may be equal to, or larger than, diameter d1.

(236) Reference is again made to FIGS. 28A-29F. For some applications of the invention, prosthetic valve 42' comprises a second prosthetic valve 42. That is, a second (i.e., new) prosthetic valve 42 is used to replace a first prosthetic valve 42. Alternatively, prosthetic valve 42' may be different to prosthetic valve 42. For some applications, prosthetic valve 42' may comprise a sealing element, such as a circumferential seal (e.g., a soft

material and/or a balloon), that facilitates sealing and/or coupling between prosthetic valve 42' and prosthetic valve 42. For some applications, prosthetic valve 42' comprises protruding barbs, which facilitate coupling between the two prosthetic valves.

(237) For some applications, a distal portion of prosthetic valve 42' defines a cross-sectional area with a longest length that is longer than a transverse cross-sectional longest dimension of the lumen defined by prosthetic valve 42 (i.e., defined by primary structural element 130 of prosthetic valve 42). During deployment of prosthetic valve 42', the distal portion is placed distal to the open distal end of prosthetic valve 42 (i.e., in the ventricle). Thereby, in addition to the radially-expansive force that typically couples prosthetic valve 42' to prosthetic valve 42, the distal portion restricts proximal movement of prosthetic valve 42' with respect to prosthetic valve 42, thereby anchoring prosthetic valve 42' to prosthetic valve 42, and to native valve 23.

(238) Reference is made to FIGS. 30A-B, which are schematic illustrations of implant 30, comprising prosthetic valve 42 and prosthetic valve support 40y, being restored by the addition of a second prosthetic valve 42', in accordance with some applications of the invention. Prosthetic valve support 40y comprises upstream support portion 41 coupled to a cylindrical element 690 that is typically configured to extend distally through native valve 23. Alternatively, cylindrical element 690 may be configured to extend away from the native valve. Prosthetic valve support 40y is typically couplable to the native valve using techniques described herein for coupling other prosthetic valve supports to the native valve. For example, prosthetic valve support 40y may comprise tissue-engaging elements (e.g., support-anchoring elements). Cylindrical element 690 is typically configured to (1) facilitate coupling of prosthetic valve support 40y to the native valve, and/or sealing therebetween, (2) to facilitate coupling of prosthetic valves to prosthetic valve support 40y, and/or sealing therebetween, and/or (3) to push aside native leaflets 82 of native valve 23.

(239) FIG. 30A shows prosthetic valve 42 having been deployed in the lumen of prosthetic valve support 40y. Typically, prosthetic valve 42 is deployed in a distal (i.e., more ventricular and/or downstream) portion of the lumen.

(240) FIG. 30B shows prosthetic valve 42' having been deployed in the lumen of prosthetic valve support 40y. At such a time that it is deemed necessary and/or desirable to perform a replacement of prosthetic valve 42, prosthetic valve 42' is delivered to, and deployed in, another portion of prosthetic valve support 40y. Typically, prosthetic valve 42' is deployed in a portion of the lumen that is proximal to (e.g., upstream of) prosthetic valve 42. That is, prosthetic valve support 40y is configured to receive, at a first period, a first prosthetic valve at a first longitudinal portion of the lumen of cylindrical element 690, and to receive, at a second period, a second prosthetic valve at a second longitudinal portion of the lumen.

(241) For some applications, prosthetic valve 42 continues to function at least in part, and at least temporarily. That is, prosthetic valve 42 and prosthetic valve 42' operate generally simultaneously. For some applications, prosthetic valve 42 is disabled in conjunction with deployment of prosthetic valve 42'. For example, leaflets 660 of prosthetic valve 42 may be disabled, removed and/or restrained, by using a separate device (not shown) and/or by using a part (e.g., an extending element; not shown) of prosthetic valve 42'.

(242) For some applications, the primary structural element 130 of prosthetic valve 42' is longer than the primary structural element of prosthetic valve 42, and the leaflets of prosthetic valve 42' are disposed in a proximal portion of the primary structural element thereof. A distal portion of the primary structural element of prosthetic valve 42' is deployed in the lumen of prosthetic valve 42, such that the leaflets of prosthetic valve 42 are crushed upon expansion of prosthetic valve 42'.

(243) Reference is made to FIGS. 31A-33C, which are schematic illustrations of delivery tube 60, in accordance with some applications of the invention. Deployment of a medical device 150, such as prosthetic valve 42, as described with reference to FIGS. 1A-H, typically comprises proximal movement of delivery tube 60 relative to prosthetic valve 42, as described hereinabove. Immediately prior to the release of prosthetic valve 42 from the delivery tube, the length of the delivery tube-plus-prosthetic valve may be double or more than that of the delivery tube or prosthetic valve alone. For some applications, this extra length can hinder the movement of, and removal of, the delivery tube from the body. A delivery tube that takes up less room during and/or following deployment of prosthetic valve 42 would thereby be advantageous.

(244) FIGS. 31A-C show delivery tube 60, comprising a flexible delivery tube 60b being used to deliver prosthetic valve 42, in accordance with some applications of the invention. Delivery tube 60b comprises a flexible material, such as a fabric or polymer. FIG. 31A shows prosthetic valve 42 in a compressed (i.e., crimped) configuration within delivery tube 60b. Prosthetic valve 42 exerts an expansive force on tube 60b,

and tube **60b** provides a reciprocal compressive force on prosthetic valve **42**. Delivery tube **60b** is typically not rigid; rather prosthetic valve **42** provides (i.e., dictates) the shape to which the delivery tube conforms. That is, prosthetic valve **42** functions as a scaffold on which delivery tube **60b** is disposed.

(245) FIG. **31B** shows prosthetic valve **42** partially deployed from delivery tube **60b**. For example, prosthetic valve **42** may be pushed distally out of the delivery tube using a pushing member (e.g., pushing member **140**). FIG. **31C** shows prosthetic valve **42** fully deployed from delivery tube **60b**. Prosthetic valve **42** has expanded toward its expanded configuration. The reciprocal expansive and compressive forces are thereby no longer exerted, and delivery tube **60b** no longer conforms to a rigid shape. That is, delivery tube **60b** becomes flaccid, facilitating its removal from the subject. For example, delivery tube **60b** may be moved around corners and/or into an overtube such as a catheter.

(246) FIGS. **32A-C** show delivery tube **60**, comprising a compressible delivery tube **60c** being used to deliver prosthetic valve **42**, in accordance with some applications of the invention. Delivery tube **60c** comprises a flexible material, such as a fabric or polymer, and one or more pulling wires **740**. Delivery tube **60c** typically further comprises an aperture ring **742**. FIG. **32A** shows prosthetic valve **42** in a compressed (i.e., crimped) configuration within delivery tube **60c**. Prosthetic valve **42** exerts an expansive force on tube **60c**, and tube **60c** provides a reciprocal compressive force on prosthetic valve **42**. Delivery tube **60c** is typically not rigid; rather prosthetic valve **42** provides (i.e., dictates) the shape to which the delivery tube conforms. That is, prosthetic valve **42** functions as a scaffold on which delivery tube **60c** is disposed. Pulling wires **740** extend from a proximal site (e.g., outside the subject) and are coupled to a distal portion of delivery tube **60c** (e.g., to aperture ring **742**).

(247) FIG. **32B** shows prosthetic valve **42** partially deployed from delivery tube **60c**. Typically, following placement of delivery tube **60c** (and thereby prosthetic valve **42**) in the lumen of native valve **23**, pulling wires **740** are pulled, drawing the distal portion of the delivery tube (e.g., aperture ring **742**) proximally. Delivery tube **60c** is thereby compressed (i.e., shortened) and a distal portion of prosthetic valve **42** is exposed, and typically expands at least in part responsively. For example, a proximal end of delivery tube **60c** may be generally closed, such that compressing (i.e., shortening) of the delivery tube, exposes the distal portion of prosthetic valve **42** from the distal end of the delivery tube. FIG. **32C** shows prosthetic valve **42** fully deployed from delivery tube **60c**. Prosthetic valve **42** has expanded toward its expanded configuration. Delivery tube **60c** is generally compressed such that it has a length of less than 50% (e.g., less than 30%, such as less than 10%) of its length when containing prosthetic valve **42**, thereby facilitating its removal from the subject. For example, delivery tube **60c** may be moved around corners and/or into an overtube such as a catheter.

(248) FIGS. **33A-C** show delivery tube **60**, comprising a dismantling delivery tube **60d** being used to deliver prosthetic valve **42**, in accordance with some applications of the invention. Delivery tube **60d** comprises a flexible material, such as a fabric or polymer, and a pullstring **750**. FIG. **33A** shows prosthetic valve **42** in a compressed (i.e., crimped) configuration within delivery tube **60d**. Prosthetic valve **42** exerts an expansive force on tube **60d**, and tube **60d** provides a reciprocal compressive force on prosthetic valve **42**. Delivery tube **60d** is typically not rigid; rather prosthetic valve **42** provides (i.e., dictates) the shape to which the delivery tube conforms. That is, prosthetic valve **42** functions as a scaffold on which delivery tube **60d** is disposed. Pullstring **750** is coupled to the flexible material of delivery tube **60d**, typically along the length of the delivery tube. Typically, delivery tube **60d** comprises a sheet of the flexible material, held in a generally cylindrical shape by pullstring **750**. For example, pullstring **750** may weave between two parts of the flexible material, stitching them together. Alternatively, pullstring **750** may be coupled to the two parts of the flexible material via a weakened (e.g., perforated) join.

(249) FIG. **33B** shows prosthetic valve **42** partially deployed from delivery tube **60d**. Typically, following placement of delivery tube **60d** (and thereby prosthetic valve **42**) in the lumen of native valve **23**, pullstring **750** is pulled, decoupling the two parts of the flexible material, and thereby opening delivery tube **60d**. Typically, regions of prosthetic valve **42** expand as regions of delivery tube **60d** are opened. FIG. **33C** shows prosthetic valve **42** fully deployed from delivery tube **60d**. Prosthetic valve **42** has expanded toward its expanded configuration. Pullstring **750** has been pulled sufficiently, such that the flexible material of delivery tube **60d** becomes a generally open sheet. That is, delivery tube **60d** typically loses its cylindrical shape and becomes flaccid, thereby facilitating its removal from the subject. For example, delivery tube **60d** may be moved around corners and/or into an overtube such as a catheter.

(250) Reference is made to FIG. **34**, which is a schematic illustration of prosthetic valve **42**, comprising a tissue-engaging element **62**, comprising a leaflet-engaging element **760**, coupled to a distal portion of primary

structural element **130** of the prosthetic valve, in accordance with some applications of the invention. For some applications, leaflet-engaging element **760** is similar in structure to a valve-anchoring element **64**, such as a loop-shaped valve-anchoring element **200**. Element **760** is positioned and configured so as to engage a single leaflet, typically the anterior leaflet, of native valve **23**. The engagement of the leaflet is hypothesized to reduce undesired interference with blood flow. Specifically, holding the anterior leaflet clear of the LVOT is hypothesized to reduce interference with blood flowing from the left ventricle into the aorta.

(251) Although element **760** is described with reference to FIG. **34** as being coupled to the primary structural element of prosthetic valve **42**, it is to be noted that the scope of the present invention includes an element **760** being additionally or alternatively coupled to prosthetic valve support **40**.

(252) Reference is made to FIGS. **35A-C**, which are schematic illustrations of sequential steps in the implantation of prosthetic valve **42**, and prosthetic valve support **40**, comprising prosthetic valve support **40z**, in accordance with some applications of the invention. As described hereinabove, support **40** comprises an upstream support portion **41** which is shaped to define a lumen. During implantation of implant **30**, prosthetic valve **42** is deployed in this lumen. As described herein, for some applications of the invention, support **40** is coupled to native valve **23** prior to delivery and/or deployment of prosthetic valve **42**. For example, support **40** may comprise tissue-engaging elements **62**, comprising support-anchoring elements **66** (not shown in FIGS. **35A-C**). In some applications, support **40** and/or the coupling thereof to native valve **23**, interferes with the functioning of leaflets **82** of the native valve. For example, in some applications, support **40** is coupled to the native valve via support-anchoring elements **66** engaging (i.e., coupling to) leaflets **82**, thereby disrupting native valve function. For further example, in some applications, elements **66** move leaflets **82**, so as to sandwich the leaflets against prosthetic valve **42**. For applications such as these, there is typically a period after the coupling of support **40** to the native valve, and before deployment of prosthetic valve **42**, that the native valve has significantly reduced functionality. Prosthetic valve support **40z** comprises one or more temporary valve components, such as temporary leaflets **700**, and advantageously provides temporary valve functionality during this period.

(253) FIG. **35A** shows prosthetic valve support **40z**, which comprises one or more temporary valve components, such as temporary leaflets **700**, typically disposed in the lumen defined by support **40z**. Leaflets **700** provide temporary valve functionality to support **40z**, thereby facilitating pumping of blood by the heart in the absence of native valve function. Temporary leaflets **700** may comprise a biological material, such as pericardial tissue, and/or a synthetic material, such as silicone, polyethylene terephthalate (e.g., polyester), and/or polytetrafluoroethylene (e.g., Teflon). Temporary leaflets are typically coupled to upstream support portion **41** using sutures. It is noted that, although prosthetic valve support **40z** is illustrated in FIGS. **35A-C** as not comprising tissue-engaging elements such as support-anchoring elements **66**, prosthetic valve support **40z** typically does comprise support-anchoring elements **66**, such as those described elsewhere herein.

(254) FIG. **35B** shows prosthetic valve **42** being deployed in the lumen of support **40z**. For some applications, prosthetic valve **42** is deployed as described with reference to FIGS. **1A-H**, mutatis mutandis. For some applications, prosthetic valve **42** is deployed as described with reference to FIGS. **15A-L**, mutatis mutandis. As it expands, prosthetic valve **42** typically pushes aside temporary leaflets **700**.

(255) FIG. **35C** shows prosthetic valve **42** having been fully deployed (i.e., expanded) in the lumen of support **40z**. In some applications, leaflets **700** are sandwiched between prosthetic valve **42** and support **40z**. In some applications, leaflets **700** facilitate sealing between prosthetic valve **42** and support **40z**. As prosthetic valve **42** is deployed, it begins to function, thereby replacing the temporary valve functionality of leaflets **700**. Thereby, the techniques described with reference to FIGS. **35A-C** provide ongoing valve functionality throughout the implantation of a prosthetic valve.

(256) Reference is made to FIGS. **36A-D**, which are schematic illustrations of prosthetic valve support **40**, comprising a prosthetic valve support **1040**, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **1040** is analogous to other prosthetic valve supports described herein. For some applications of the invention, prosthetic valve support **1040** comprises prosthetic valve support **40**. Support **1040** comprises upstream support portion **41**, which is shaped to define a lumen. Support **1040** comprises one or more support-anchoring elements **900** and one or more stabilizing legs **910**. Typically, support **1040** comprises two support-anchoring elements **900** and two stabilizing legs **910**. Typically, support-anchoring elements **900** and stabilizing legs **910** are coupled to inner edge **68** of upstream support portion **41**. For some applications of the invention, support-anchoring elements **900** are embodiments of support-anchoring elements **66**, which are embodiments of tissue-engaging elements **62**, as described hereinabove. For some applications of the invention, stabilizing legs **910** are embodiments of support-

anchoring elements and/or of tissue-engaging elements **62**, as described hereinabove.

(257) FIG. **36A** shows a lower side view of support **1040**. Typically, support-anchoring elements **900** comprise clips and/or clip functionality. Elements **900** are illustrated in FIG. **36A** as generic clips, and may comprise any of the clips described herein, and/or any other clips that are couplable to the leaflets of the native valve (e.g., support-anchoring elements **900a** and **900b** and the clip functionalities thereof, described hereinbelow with reference to FIGS. **37A-H**, and **38A-H**). For some applications of the invention, support-anchoring element **900** comprises two clip elements, (1) coupled at a coupling point, and (2) between which, during implantation, leaflets **82** of the native valve are typically clamped. Clamping of a leaflet between the two clip elements couples element **900** to the leaflet. Typically, one clip element is substantially immobile, and the other clip element is (1) biased to assume a first configuration, and (2) movable between the first configuration and another configuration.

(258) Element **900** typically has (1) an open configuration, in which leaflets **82** of the native valve may be moved between the two clip elements, and (2) a closed configuration, in which the clip elements typically clamp (i.e., couple to) the leaflets. Element **900** is typically moved between the open and closed configurations thereof (i.e., is opened and closed) by moving at least one clip element between the first configuration thereof, and the other configuration thereof.

(259) Typically, the clip elements are disposed at a distal portion of each support-anchoring element **900**, and a proximal portion (e.g., a proximal end) of each element **900** is coupled to upstream support portion **41**. Typically, support-anchoring elements **900** have a length (i.e., a distance from (1) the point of coupling of the element **900** to upstream support portion **41**, to (2) a distal end of the element **900**) of between 3 and 20 mm, (e.g., between 5 and 12 mm). Typically, the proximal portion has a length (i.e., a distance between (1) the point of coupling of element **900** to upstream support portion **41**, and (2) a clip element) of between 2 and 10 mm, (e.g., between 2 and 8 mm).

(260) Support **1040** typically comprises two support-anchoring elements **900** and two stabilizing legs **910**. Typically, elements **900** and legs **910** are disposed at inner edge **68** in an alternating manner, i.e., such that each leg **910** is between two elements **900**, and each element **900** is between two legs **910**.

(261) Typically, stabilizing leg **910** is longer than support-anchoring element **900**. That is, a distance between (1) a coupling point **911** of upstream support portion **41** and a stabilizing leg **910** and (2) a distal end of the stabilizing leg, is typically greater than a distance between (1) a coupling point of upstream support portion **41** and an element **900** and (2) a distal end of the element **900**. Typically, stabilizing leg **910** has a length of between 5 mm and 30 mm (e.g., between 5 mm and 20 mm), and a width of between 0.4 mm and 5.0 mm.

(262) For some applications of the invention, each stabilizing leg **910** comprises a proximal portion **912** and a distal portion **914**, whereby the proximal portion is coupled at coupling point **913** between the stabilizing leg and the distal portion. For some such applications, stabilizing leg **910** comprises a bend, such that an axis defined by distal portion **914** is divergent to an axis defined by the proximal portion. Typically, proximal portion **912** has a length of between 5 mm and 20 mm.

(263) Typically, stabilizing legs **910** have a stabilizing configuration, in which they stabilize prosthetic valve support **1040** at the native valve. Typically, in the stabilizing configuration, the proximal portion **912** of each leg **910** is disposed on a plane between (1) a plane that is orthogonal to a plane defined by upstream support portion **41**, and (2) a position in which the leg touches a part of upstream support portion **41** that is peripheral to inner edge **68**. That is, in the stabilizing configuration, proximal portion **912** typically forms an acute angle with a portion of upstream support portion **41**.

(264) Stabilizing legs **910** are hypothesized to increase the stability of prosthetic valve support **1040** at the native valve. For example, legs **910** are hypothesized to at least partly inhibit (1) lateral rotation (i.e., rotation around an atrial-ventricular axis) of the prosthetic valve support, and/or (2) movement of the parts of upstream support portion **41** that are disposed against the proximal (e.g., atrial) side of the native valve, from moving away from, or through, the native valve. Following deployment (e.g., implantation) of prosthetic valve **42**, legs **910** are further hypothesized to reduce rolling movement (e.g., movement around a lateral axis, e.g., an axis between two elements **900**, such as an axis that is generally orthogonal to an axis between the stabilizing legs) of the prosthetic valve and/or implant **30**, including inversion (e.g., ‘flipping’) of the implant.

(265) For some applications of the invention, support **1040** is configured such that legs **910** and/or elements **900** are biased to reside in a particular (e.g., a pre-selected) configuration. For example, legs **910** and/or elements **900** and/or a coupling point (e.g., coupling point **911**) may comprise a shape-memory material (e.g., nitinol, stainless steel, nickel cobalt, cobalt chrome, and/or titanium) or a spring mechanism. For some applications of the invention, the pre-selected configuration of legs **910** comprises the stabilizing

configuration of legs **910**.

(266) For some applications of the invention, legs **910** and/or elements **900** are rotatable around coupling point **911**. For example, legs **910** and/or elements **900** may be coupled to upstream support portion **41** via a hinge point (e.g., a hinge element), which may comprise a flexible material and/or moving components. For some applications of the invention, legs **910** and/or elements **900** rotate freely around coupling point **911** as far as their shape and juxtaposition allows.

(267) For some applications where elements **900** rotate freely, following the coupling of elements **900** to leaflets **82** of the native valve, the leaflets continue to function, at least in part.

(268) For some applications where stabilizing legs **910** rotate freely, the stabilizing legs have (1) a floating configuration, in which the stabilizing legs rotate freely, and (2) a stabilizing configuration, in which the stabilizing legs assume the pre-selected configuration, and are movable from the floating configuration to the pre-selected configuration. For some such applications, stabilizing legs assume the floating configuration when support **1040** is implanted, and are moved to the stabilizing configuration when the prosthetic valve is deployed in the lumen of the support.

(269) FIG. **36B** shows a top (i.e., atrial side) view of implant **30**, comprising support **1040** and prosthetic valve **42**, following implantation in native valve **23**, comprising mitral valve **24**, in accordance with some applications of the invention. Zones (scallop) **P1**, **P2** and **P3** of posterior leaflet **82p**, and zones **A1** and **A3** of anterior leaflet **82a** are labeled. As described hereinabove, elements **900** and legs **910** are disposed at inner edge **68** in an alternating manner. For the applications of the invention illustrated in FIG. **36B**, elements **900** and legs **910** are typically arranged such that (1) the two elements **900** are disposed opposite each other, (2) the two legs **910** are disposed opposite each other, and (3) each leg **910** is generally midway between the two elements **900**. That is, inner edge **68** is typically elliptical (e.g., circular), and each leg **910** is disposed at edge **68** generally between 80 degrees and 100 degrees (e.g., 90 degrees) to an element **900**.

(270) Typically, support-anchoring elements **900** are coupled to leaflets **82**, i.e., one element **900** is coupled to anterior leaflet **82a**, and one element **900** is coupled to posterior leaflet **82p**. Typically, stabilizing legs **910** are oriented toward zones (scallop) **P1** and **P3** of the posterior leaflet. This configuration and orientation of elements **900** and legs **910** with respect to each other, and with respect to the native valve, is hypothesized to facilitate the stable placement and coupling (i.e., implantation) of prosthetic valve support **1040** at/to the native valve, and thereby is hypothesized to facilitate the stable implantation of implant **30** at the native valve.

(271) FIG. **36C** shows a top (i.e., atrial side) view of implant **30**, comprising support **1040** and prosthetic valve **42**, following implantation in native valve **23**, comprising mitral valve **24**, in accordance with some applications of the invention. Zones (scallop) **P1**, **P2** and **P3** of posterior leaflet **82p**, and zones **A1** and **A3** of anterior leaflet **82a** are labeled. As described hereinabove, elements **900** and legs **910** are disposed at inner edge **68** in an alternating manner. For the applications of the invention illustrated in FIG. **36C**, support-anchoring elements **900** are coupled to leaflets **82**, i.e., one element **900** is coupled to anterior leaflet **82a**, and one element **900** is coupled to posterior leaflet **82p**. Elements **900** and legs **910** are typically arranged such that (1) the two elements **900** are disposed opposite each other, and (2) each leg **910** is disposed between 30 degrees and 120 degrees (e.g., between 60 degrees and 120 degrees) from the element **900** that is coupled to the posterior leaflet.

(272) Stabilizing legs **910** are thereby typically oriented toward parts of posterior leaflet **82p**. This configuration and orientation of elements **900** and legs **910** with respect to each other, and with respect to the native valve, is hypothesized to facilitate the stable placement and coupling (i.e., implantation) of prosthetic valve support **1040** at/to the native valve, and thereby is hypothesized to facilitate the stable implantation of implant **30** at the native valve.

(273) FIG. **36D** shows a top (i.e., atrial side) view of implant **30**, comprising support **1040** and prosthetic valve **42**, following implantation in native valve **23**, comprising mitral valve **24**, in accordance with some applications of the invention. Zones (scallop) **P1**, **P2** and **P3** of posterior leaflet **82p**, and zones **A1** and **A3** of anterior leaflet **82a** are labeled. As described hereinabove, elements **900** and legs **910** are disposed at inner edge **68** in an alternating manner. For the applications of the invention illustrated in FIG. **36D**, support-anchoring elements **900** are coupled to leaflets **82**, i.e., one element **900** is coupled to anterior leaflet **82a**, and one element **900** is coupled to posterior leaflet **82p**. Elements **900** and legs **910** are typically arranged such that (1) the two elements **900** are disposed opposite each other, and (2) each leg **910** is disposed between 30 degrees and 120 degrees (e.g., between 60 degrees and 120 degrees) from the element **900** that is coupled to the anterior leaflet.

(274) Stabilizing legs **910** are thereby typically oriented toward parts of anterior leaflet **82a**. This

configuration and orientation of elements **900** and legs **910** with respect to each other, and with respect to the native valve, is hypothesized to facilitate the stable placement and coupling (i.e., implantation) of prosthetic valve support **1040** at/to the native valve, and thereby is hypothesized to facilitate the stable implantation of implant **30** at the native valve.

(275) Reference is made to FIGS. **37A-H**, which are schematic illustrations of prosthetic valve support **1040**, comprising a prosthetic valve support **1040a**, and the implantation thereof in a native valve, in accordance with some applications of the invention. For some applications of the invention, support **1040a** is an embodiment of prosthetic valve support **40**, described hereinabove. FIG. **37A** shows a lower side view, and some detailed views, of support **1040a**. Support **1040a** comprises two support-anchoring elements **900**, comprising support-anchoring elements **900a**, and two stabilizing legs **910**. Typically, elements **900a** and legs **910** are disposed at inner edge **68** such that (1) the two elements **900a** are disposed opposite each other, (2) the two legs **910** are disposed opposite each other, and (3) each leg **910** is generally midway between the two elements **900a**. That is, inner edge **68** is typically elliptical (e.g., circular), and each leg **910** is disposed at edge **68** generally at a right angle (e.g., between 80 degrees and 100 degrees, such as 90 degrees) to an element **900a**.

(276) Support-anchoring element **900a** comprises two clip elements, such as plate **920** and plate **922**, (1) coupled at a coupling point, and (2) between which, during implantation, leaflets **82** of the native valve are clamped. Typically, plate **920** is substantially immobile, and plate **922** is (1) biased to assume a first configuration, and (2) movable between the first configuration and another configuration. Typically, the first configuration of plate **922** is a closed configuration. Typically, the other configuration of plate **922** is an open configuration, whereby a portion of plate **922** that is furthest from the coupling point is disposed (1) further from plate **920** than is the same portion in the first, closed configuration, and (2) further from plate **920** than a portion of plate **922** that is closest to the coupling point. When plate **922** is in the closed configuration thereof, element **900a** is in a closed configuration thereof. When plate **922** is in the open configuration thereof, element **900a** is in an open configuration thereof. That is, element **900a** is movable between open and closed configurations thereof, by plate **922** moving between open and closed configurations thereof. FIG. **37A** shows detailed illustrations of support-anchoring element **900a** in the open and closed configurations, and further shows an exploded view of the components of element **900a**.

(277) Support-anchoring element **900a** further comprises, or is coupled to, an actuator, typically comprising a pull-wire **924**, which facilitates movement of plate **922** between the closed and open configurations. Pull-wire **924** is typically coupled to plate **922**, and controlled from outside the subject. For example, pull-wire **924** may be coupled to plate **922**, and extend to a control unit outside the body of the subject, for use by a physician. Typically, pull-wire **924** is coupled to the portion of plate **922** that is furthest from the coupling point, such that movement of the pull-wire proximally (e.g., by pulling) moves plate **922** toward the open configuration. For some applications of the invention, pull-wire **924** is slidably coupled to another part of element **900a**, such as plate **920**, and/or to another part of support **1040a**, and/or to a part of delivery apparatus, such as core **926**, as shown in FIGS. **37C-E**. That is, plate **922**, and thereby element **900a**, are configured to be biased toward assuming a closed configuration, such that the user (1) actively opens element **900a** to envelop a leaflet **82**, and (2) releases element **900a** to couple the element to the leaflet (i.e., to clamp the leaflet between plates **920** and **922**).

(278) For some applications of the invention, both support-coupling elements **900a** are controlled simultaneously by a user (e.g., support-coupling elements **900a** are configured to operate simultaneously). For some applications, each element **900a** is controllable independently. For some applications, element **900a** further comprises one or more grips, such as teeth **928**, which facilitate the clamping of leaflets **82** when element **900a** is closed.

(279) FIG. **37B** shows a top side view of prosthetic valve support **1040a**. Support-coupling elements **900a** are shown in their closed configuration.

(280) FIG. **37C** shows prosthetic valve support **1040a** being delivered to native valve **23**, comprising mitral valve **24**. Support **1040a** is shown in a partially deployed configuration, whereby upstream support portion **41** is compressed within an overtube **1044**, and support-anchoring elements **900a** and stabilizing legs **910** are exposed from the distal end of the overtube. Support-anchoring elements **900a** are shown in the closed configuration thereof. Typically, prior to deployment, at least part of support **1040a** is coupled to (e.g., disposed around) a scaffold, such as a core **926**. For some applications of the invention, core **926** is configured to facilitate the opening of elements **900a** (i.e., movement of elements **900a** and/or plate **922** to the open configuration), and/or to facilitate the enveloping of leaflets **82** of the native valve by elements **900a**.

For example, and as shown in FIG. 37C, core **926** may support elements **900a** at an angle that facilitates the movement of plate **922** by pull-wire **924**.

(281) FIG. 37D shows, in cross-section, support **1040a** in a partially-deployed configuration within native valve **23**. Upstream support portion **41** of support **1040a** is in a compressed configuration thereof, and is partially disposed within overtube **1044**. Support-anchoring elements **900a** and stabilizing legs **910** are exposed from the distal end of the overtube (i.e., have been deployed from the overtube). Arrows indicate the movement of pull-wire **924**, caused by proximally pulling the pull-wire. Support-anchoring elements **900a** are shown having been moved to the open configuration thereof, by the movement of pull-wire **924**. A part of each leaflet **82** is shown within the 'clip' of a respective element **900a** (i.e., enveloped by and/or disposed between plate **920** and plate **922** of a respective element **900a**). For some applications, the entry of leaflets **82** between the plates is facilitated by the movement of the leaflets caused by the beating of heart **22**. For some applications, the entry of leaflets **82** between the plates is facilitated by movement of support **1040a**, and/or iterative opening and closing of elements **900a**.

(282) FIG. 37E shows support-anchoring elements **900a** having moved to the closed configuration thereof, following the release of pull-wire **924**. Arrows indicate the movement of pull-wire **924** following the release thereof. The part of each leaflet **82** that was previously disposed between plate **920** and plate **922** is thereby clamped between the two plates. That is, elements **900a** are coupled to leaflets **82** of the native valve. Once elements **900a** have been successfully coupled to leaflets **82** (e.g., once a physician is satisfied with the position and coupling of support **1040a**), the remainder of the support (e.g., upstream support portion **41**) is typically deployed.

(283) FIG. 37F shows prosthetic valve support **1040a** in a fully-deployed configuration thereof. Following coupling of elements **900a** to leaflets **82**, overtube **1044** is retracted proximally, and/or support **1040a** is moved distally, such that the support emerges from the overtube, and expands to its expanded configuration. For some applications, the expansion of support **1040a** automatically decouples the support from the scaffold (e.g., core **926**), which is subsequently removed from the subject. Annular portion **41** of support **1040a** is shown disposed against the proximal side (e.g., the atrial surface) of the native valve, as described hereinabove with respect to upstream support portion **41** of other prosthetic valve supports. FIG. 37D shows native valve **23** in an open configuration thereof, whereby leaflets **82** generally extend into ventricle **28**. As described hereinabove, mutatis mutandis, with reference to elements **900**, illustrated in FIGS. 36A-D, for some applications, elements **900a** are configured to allow leaflets **82** to continue to function, at least in part. For such applications, FIG. 37F illustrates a snapshot of the position of leaflets **82** during diastole. As also described hereinabove, mutatis mutandis, with reference to elements **900**, illustrated in FIGS. 36A-D, for some applications, elements **900a** are configured to be biased to assume a pre-selected position with respect to upstream support portion **41**. For such applications, FIG. 37F illustrates leaflets **82** being held in the open configuration thereof, by elements **900a** that are configured to be biased to assume the position shown.

(284) For some applications, following deployment of support **1040a**, pull-wire **924**, or a portion thereof, is decoupled from the support, or a portion thereof, (e.g., from element **900a**). For example, the pull-wire may be coupled to element **900a** using a lock described herein (e.g., with reference to FIGS. 45A-C and/or 64A-C, mutatis mutandis), and decoupled from element **900a** by moving the lock to the open configuration. Alternatively, the pull-wire may be coupled to element **900a** by being looped around the element, and decoupled from the element by being unlooped from the element, e.g., by subsequent to a portion of the pull-wire being cut and/or released.

(285) FIG. 37G shows prosthetic valve **42**, having been deployed (e.g., delivered and expanded) in the lumen of prosthetic valve support **1040a**, and coupled thereto, as described herein (e.g., with reference to other prosthetic valve supports).

(286) FIG. 37H is a top (e.g., atrial) view of prosthetic valve **42**, having been deployed (e.g., delivered and expanded) in the lumen of prosthetic valve support **1040a**, and coupled thereto, as described herein (e.g., with reference to other prosthetic valve supports). Support-anchoring elements **900a** are coupled to leaflets **82**, i.e., one element **900a** is coupled to anterior leaflet **82a**, and one element **900a** is coupled to posterior leaflet **82p**. Elements **900a** and legs **910** are typically arranged such that (1) the two elements **900a** are disposed opposite each other, and (2) each leg **910** is disposed between 60 degrees and 120 degrees from the element **900a** that is coupled to the posterior leaflet.

(287) Reference is made to FIGS. 38A-H, which are schematic illustrations of prosthetic valve support **1040**, comprising a prosthetic valve support **1040b**, and the implantation thereof in a native valve, in accordance with some applications of the invention. For some applications of the invention, support **1040b** is an

support of prosthetic valve support **40**, described hereinabove. FIG. **38A** shows a lower side view, and some detailed views, of support **1040b**. Support **1040b** comprises two support-anchoring elements **900**, comprising support-anchoring elements **900b**, and two stabilizing legs **910**. Typically, elements **900b** and legs **910** are disposed at inner edge **68** such that (1) the two elements **900b** are disposed opposite each other, (2) the two legs **910** are disposed opposite each other, and (3) each leg **910** is generally midway between the two elements **900b**.

(288) Support-anchoring element **900b** comprises two clip elements, such as plate **940** and plate **942**, (1) coupled at a coupling point, and (2) between which, during implantation, leaflets **82** of the native valve are clamped. Typically, plate **940** is substantially immobile, and plate **942** is (1) biased to assume a first configuration, and (2) movable between the first configuration and another configuration. Typically, the first configuration of plate **942** is an open configuration, whereby a portion of plate **942** that is furthest from the coupling point is disposed further from plate **940** than a portion of plate **942** that is closest to the coupling point. Typically, the other configuration of plate **942** is a closed configuration, whereby a portion of plate **942** that is furthest from the coupling point is disposed closer to plate **940** than is the same portion in the first, open configuration. When plate **942** is in the closed configuration thereof, element **900b** is in a closed configuration thereof. When plate **942** is in the open configuration thereof, element **900b** is in an open configuration thereof. That is, element **900b** is movable between open and closed configurations thereof, by plate **942** moving between open and closed configurations thereof.

(289) FIG. **38A** shows detailed illustrations of support-anchoring element **900b** in the open and closed configurations, and further shows an exploded view of the components of element **900b**. As shown in the exploded view, for some applications, plate **942** comprises more than one element, including a spring element **942a**, and a face element **942b**. Spring element **942a** typically comprises a strip of shape-memory material (e.g., nitinol, stainless steel, nickel cobalt, cobalt chrome, and/or titanium), that is configured such that plate **942** is biased to assume the open configuration. Spring element **942a** is typically configured to provide a force that is (1) sufficiently strong to provide this bias, but (2) sufficiently weak so as to facilitate (e.g., to not inhibit) sliding of cuff **944** over plate **942**. Typically, this configuration is provided by selecting an appropriate thickness of the strip of shape-memory material of spring element **942a**. Face element **942b** is typically configured to increase the rigidity of at least part of plate **942**, thereby facilitating clamping of the native leaflets when cuff **944** is slid over plate **942**.

(290) Support-anchoring element **900b** further comprises an actuator, typically comprising a restraint, such as cuff **944**, which facilitates movement of plate **922** between the closed and open configurations. Cuff **944** is typically coupled to plate **940** and/or plate **942**, and controlled from outside the subject (e.g., controlled from outside the body of the subject by a physician, such as via a control unit). Typically, cuff **944** is coupled to plate **940** via a spring **950**, and is slidable over (e.g., onto and off of) at least a portion of plate **942**. Support-anchoring element **900b** is configured such that (1) spring **950** applies a force (i.e., a first force) to cuff **944**, that slides cuff **944** over plate **942**, and (2) sliding of cuff **944** over plate **942** moves the portion of plate **942** that is furthest from the coupling point closer to plate **940** (i.e., moves plate **942**, and thereby element **900b**, into the closed configuration). A user typically opens element **900b** (e.g., so as to clamp leaflets of the native valve, e.g., as described hereinbelow with reference to FIGS. **38D-E**) by sliding cuff **944** off of plate **942**. For example, a control rod **952** may be used to slide cuff **944** off of plate **942** (e.g., by distal movement of the control rod), and may be controlled, by a physician, via a control unit outside the body of the subject. That is, (1) plate **942** itself is configured to be biased toward assuming an open configuration, (2) cuff **944** and spring **950** are configured to move plate **942** toward a closed configuration, and (3) the user (a) actively opens element **900b** by sliding cuff **944** off of plate **942**, so as to envelop a leaflet **82**, and (b) releases cuff **944** to couple the element to the leaflet (i.e., to clamp the leaflet between plates **940** and **942**).

(291) For some applications of the invention, both support-coupling elements **900b** are controlled simultaneously by a user (e.g., support-coupling elements **900b** are configured to operate simultaneously). For some applications, each element **900b** is controllable independently. For some applications, element **900b** further comprises one or more grips, such as teeth **948**, which facilitate the clamping of leaflets **82** when element **900b** is closed. For some applications, control rod **952** is moved distally using a pusher (not shown), disposed within delivery apparatus (e.g., overtube **1044**), and typically not fixedly coupled to the control rod. (292) FIG. **38B** shows a top side view of prosthetic valve support **1040b**. Support-coupling elements **900b** are shown in their open configuration.

(293) FIG. **38C** shows prosthetic valve support **1040b** being delivered to native valve **23**, comprising mitral valve **24**. Support **1040b** is shown in a partially deployed configuration, whereby upstream support portion **41**

is compressed between **1044**, and support-anchoring elements **900b** and stabilizing legs **910** are exposed from the distal end of the overtube. Support-anchoring elements **900b** are shown in the closed configuration thereof. Typically, prior to deployment, at least part of support **1040b** is coupled to (e.g., disposed around) a scaffold, such as a core **946**. For some applications of the invention, core **946** is configured to facilitate the opening of elements **900b** (i.e., movement of elements **900b** and/or plate **942** to the open configuration), and/or to facilitate the enveloping of leaflets **82** of the native valve by elements **900b**. For example, and as shown in FIG. **38C**, core **946** may support elements **900b** at a pre-selected angle.

(294) FIG. **38D** shows support **1040b** in a partially-deployed configuration within native valve **23**. Annular portion **41** of support **1040b** is in a compressed configuration thereof, and is partially disposed within overtube **1044**. Support-anchoring elements **900b** and stabilizing legs **910** are exposed from the distal end of the overtube (i.e., have been deployed from the overtube). Arrows indicate the movement of cuff **944**, caused by distal movement (e.g., pushing) of control rod **952**. Support-anchoring elements **900b** are shown having been moved to the open configuration thereof, by the movement of cuff **944**. A part of each leaflet **82** is shown within the 'clip' of a respective element **900b** (i.e., enveloped by and/or disposed between plate **940** and plate **942** of a respective element **900b**). For some applications, the entry of leaflets **82** between the plates is facilitated by the movement of the leaflets caused by the beating of heart **22**. For some applications, the entry of leaflets **82** between the plates is facilitated by movement of support **1040b**, and/or iterative opening and closing of elements **900b**.

(295) FIG. **38E** shows support-anchoring elements **900b** having moved to the closed configuration thereof, following the release of cuff **944** (e.g., caused by the release of control rod **952**). Arrows indicate the movement of cuff **944** following the release thereof. The part of each leaflet **82** that was previously enveloped by (i.e., disposed between) plate **940** and plate **942** is thereby clamped between the two plates. That is, elements **900b** are coupled to leaflets **82** of the native valve. Once elements **900b** have been successfully coupled to leaflets **82** (e.g., once a physician is satisfied with the position and coupling of support **1040b**), the remainder of prosthetic valve support **1040b** (e.g., upstream support portion **41**) is typically deployed.

(296) FIG. **38F** shows prosthetic valve support **1040b** in a fully-deployed configuration thereof. Following coupling of elements **900b** to leaflets **82**, overtube **1044** is retracted proximally, and/or support **1040b** is moved distally, such that the support emerges from the overtube, and expands to its expanded configuration. For some applications, the expansion of support **1040b** automatically decouples the support from the scaffold (e.g., core **946**), which is subsequently removed from the subject. Annular portion **41** of support **1040b** is shown disposed against the proximal side (e.g., the atrial surface) of the native valve, as described hereinabove with respect to upstream support portion **41** of other prosthetic valve supports. FIG. **38D** shows native valve **23** in an open configuration thereof, whereby leaflets **82** generally extend into ventricle **28**. As described hereinabove, mutatis mutandis, with reference to elements **900**, illustrated in FIGS. **36A-D**, for some applications, elements **900b** are configured to allow leaflets **82** to continue to function, at least in part. For such applications, FIG. **38F** illustrates a snapshot of the position of leaflets **82** during diastole. As also described hereinabove, mutatis mutandis, with reference to elements **900**, illustrated in FIGS. **36A-D**, for some applications, elements **900b** are configured to be biased to assume a pre-selected position with respect to upstream support portion **41**. For such applications, FIG. **38F** illustrates leaflets **82** being held in the open configuration thereof, by elements **900b** that are configured to be biased to assume the position shown.

(297) As described hereinabove, for some applications, control rod **952** is moved distally using a pusher, disposed within delivery apparatus (e.g., overtube **1044**), and typically not fixedly coupled to the control rod. For such applications, the pusher remains within the delivery apparatus, and is removed with the delivery apparatus, following full deployment of prosthetic valve support **1040b**. FIG. **38F** thus shows a proximal end **953** of each control rod **952**, previously disposed within overtube **1044**, now exposed and not in contact with the pusher, following removal of the overtube.

(298) FIG. **38G** shows prosthetic valve **42**, having been deployed (e.g., delivered and expanded) in the lumen of prosthetic valve support **1040b**, and coupled thereto, as described herein (e.g., with reference to other prosthetic valve supports).

(299) FIG. **38H** is a top (e.g., atrial) view of prosthetic valve **42**, having been deployed (e.g., delivered and expanded) in the lumen of prosthetic valve support **1040b**, and coupled thereto, as described herein (e.g., with reference to other prosthetic valve supports). Support-anchoring elements **900b** are coupled to leaflets **82**, i.e., one element **900b** is coupled to anterior leaflet **82a**, and one element **900b** is coupled to posterior leaflet **82p**. Elements **900b** and legs **910** are typically arranged such that (1) the two elements **900b** are disposed opposite each other, and (2) each leg **910** is disposed between 60 degrees and 120 degrees from the element **900b** that

is coupled to the posterior leaflet.

(300) Reference is again made to FIGS. 36A-38H. Typically, support-anchoring elements **900** (e.g., elements **900a** and **900b**) and stabilizing legs **910** are configured to be movable independently from each other, and to be at least in part flexible and/or movable with respect to upstream support portion **41**. That is, elements **900** and legs **910** are typically positionable according to the individual anatomy of the subject in which the implant is implanted. For some applications of the invention, this is conferred at least in part by the connection between (1) the element **900** and/or leg **910**, and (2) upstream support portion **41**. For some applications of the invention, this is conferred at least in part by the composition of the element **900** and/or leg **910** itself. For example, for some applications, techniques and/or elements described with reference to FIGS. 2-7 and 17A-20F, may be used in combination with those described with reference to FIGS. 36A-37H (e.g., in combination with support-anchoring elements **900**, **900a**, and/or **900b**, and stabilizing legs **910**).

(301) For some applications of the invention, during the deployment (e.g., implantation) of prosthetic valve support **1040** (e.g., support **1040a**, and/or support **1040b**), the user (e.g., physician) may determine the quality (e.g., strength) of coupling of support-anchoring elements **900** (e.g., elements **900a**, and/or **900b**) by applying a force (e.g., pushing, pulling, twisting) to the device, and/or using imaging techniques to visualize the device in situ.

(302) Typically, support-anchoring elements **900** (e.g., elements **900a** and/or **900b**) are operable (i.e., openable, and/or closable) repeatedly. Should coupling of elements **900** to leaflets **82** be determined to be suboptimal, elements **900** may be opened (e.g., decoupled from the leaflets) and reclosed (e.g., re-coupled to the leaflets), until optimal coupling has been achieved.

(303) Should it be necessary and/or desirable during deployment, until prosthetic valve support **1040** (e.g., support **1040a**, and/or support **1040b**) is fully deployed (e.g., from overtube **1044**), the deployed, expanded portions of the support (i.e., the portions of the support, including elements **900**) that are exposed from the overtube may be drawn back into the overtube (e.g., for repositioning, or for withdrawal from the body of the subject).

(304) It is to be noted that, although the support-anchoring elements described with reference to FIGS. 36A-38H (e.g., elements **900**, **900a** and **900b**) are described and/or illustrated in the context of prosthetic valve supports that comprise two support-anchoring elements and two stabilizing legs (e.g., as described with reference to FIGS. 36A-D), the scope of the invention includes other contexts for these support-anchoring elements, and the clip functionality thereof. For example, for some applications of the invention, a prosthetic valve support comprises two support-anchoring elements **900a** and/or support-anchoring elements **900b**, and does not comprise stabilizing legs **910**. For some applications of the invention, a prosthetic valve support comprises greater or fewer than two such support-anchoring elements. Furthermore, for some applications of the invention, the structure and/or function of element **900a** and/or **900** may be incorporated in a valve-anchoring element (e.g., valve-anchoring element **64**). That is, for some applications of the invention, a prosthetic valve comprises at least one valve-anchoring element, which is described as a support-anchoring element with reference to one or more of FIGS. 36A-38H, mutatis mutandis.

(305) Reference is made to FIGS. 39A-D, which are schematic illustrations of a medical device **150**, comprising one or more coupling tabs **1100**, in accordance with some applications of the invention. Coupling tabs **1100** facilitate delivery of medical device **150**, by facilitating reversible coupling of the medical device to a delivery apparatus, such as, but not limited to, delivery apparatus **880** (described with reference to FIGS. 27A-D). FIGS. 39A-D illustrate medical device **150** as comprising prosthetic valve **42**. However, it should be noted that the scope of the invention includes coupling tabs **1100** that facilitate delivery of other medical devices (e.g., expandable medical devices). FIGS. 39A-B show coupling tabs **1100** comprising T-shaped coupling tabs **1100a**, and FIG. 39C-D show coupling tabs **1100** comprising box-shaped coupling tabs **1100b**. Tabs **1100a** and **1100b** are configured, respectively, to be reversibly couplable to delivery apparatus of a respective, complimentary configuration.

(306) As described hereinabove, prosthetic valve **42** has (1) a compressed configuration, in which it is typically delivered, within a delivery tube (e.g., tube **60**), to the implantation site (e.g., native valve **23**), and (2) an expanded configuration, toward which the prosthetic valve moves during deployment. Coupling tabs **1100** are configured such that (1) in the compressed configuration of the prosthetic valve, the tabs assume a restrained configuration (FIGS. 39A and 39C), and (2) in the expanded configuration of the prosthetic valve, the tabs assume an unconstrained configuration, e.g., a pre-selected configuration (FIGS. 39B and 39D).

Typically, in the restrained configuration, coupling tabs **1100** extend collinearly from an end of prosthetic valve **42**. For example, and as illustrated in FIGS. 39A and 39C, coupling tabs **1100** extend proximally from

the proximal end of the prosthetic valve. Typically, in the unconstrained configuration, at least part of each coupling tab **1100** protrudes radially from primary structural element **130** of the prosthetic valve. For some applications, and as illustrated in FIGS. **39B** and **39D**, in the unconstrained configuration, coupling tabs **1100** extend radially outward from primary structural element **130** of the prosthetic valve. The arrows indicate the direction of the movement of coupling tabs **1100** from the constrained to the unconstrained configuration. This movement is typically between 5 degrees and 180 degrees (e.g., between 80 degrees and 180 degrees). For some applications, this movement is greater than 180 degrees, whereby coupling tabs **1100** protrude into voids defined by prosthetic valve **42**.

(307) Typically, coupling tabs **1100** comprise a shape-memory material (e.g., nitinol, stainless steel, nickel cobalt, cobalt chrome, and/or titanium), and the unconstrained configuration is pre-selected by shape-setting the material.

(308) It is hypothesized that, when prosthetic valve **42** is implanted in the native valve, coupling tabs **1100** (e.g., tabs **1100a** and tabs **1100b**), advantageously, disturb blood flow less than some coupling tabs that do not move into a configuration in which at least part of the tabs protrude radially from the prosthetic valve. For example, for some applications, coupling tabs **1100** protrude less far proximally into the atrium from the proximal part of primary structural element **130**, and/or are disposed further peripherally to a flow of blood through the prosthetic valve. It is hypothesized that this reduced blood flow disturbance of tabs **1100** reduces the likelihood of inducing hemodynamic disorders such as thrombus formation. It is further hypothesized that this reduced proximal protrusion into the atrium, increases the available space in the atrium, thereby facilitating the delivery, removal and/or other movement of medical devices and/or delivery apparatus in the vicinity of the prosthetic valve.

(309) For some applications of the invention, coupling tabs **1100** (e.g., coupling tabs **1100a**, and/or coupling tabs **1100b**) further facilitate coupling of the prosthetic valve to the prosthetic valve support (e.g., prosthetic valve support **40**). As described herein, the size of the lumen of support **40** typically determines the size to which prosthetic valve **42** expands, when implanted in this lumen. Thus, when implanted and expanded in the lumen of prosthetic valve support **40**, the primary structural element of prosthetic valve **42** typically has a longest transverse cross-sectional length that generally corresponds to a longest transverse cross-sectional length of the lumen of support **40**. A transverse cross section of prosthetic valve **42** at the position of radially-protruding coupling tabs **1100**, typically has a longest length that is greater than the longest transverse cross-sectional length of the lumen of support **40**. That is, in the region of coupling tabs **1100**, prosthetic valve **42** is typically wider than in other (e.g., more distal) regions of the prosthetic valve. This extra width provides axial resistance against undesired distal (e.g., ventricular) movement of prosthetic valve **42** with respect to support **40**, in addition to the resistance typically provided by radially expansive forces of prosthetic valve against the support.

(310) For some applications of the invention, coupling tabs **1100** (e.g., coupling tabs **1100a**, and/or coupling tabs **1100b**) increase the rigidity of prosthetic valve **42** (e.g., the rigidity of primary structural element **130** of the prosthetic valve). For example, for some applications, when primary structural element **130** is generally cylindrical, coupling tabs **1100** inhibit deformation of element **130**.

(311) Reference is made to FIGS. **40A-C**, which are schematic illustrations of prosthetic valve **42**, comprising prosthetic valve **2000**, which comprises one or more tissue-engaging elements **2002**. For some applications, elements **2002** are embodiments of tissue-engaging elements **62**. For some applications, elements **2002** are embodiments of valve-anchoring elements **64**. Tissue-engaging elements **2002** protrude laterally from primary structural element **130** of prosthetic valve **2000**.

(312) Tissue-engaging elements **2002** are configured to couple to leaflets **82** of the native valve, subsequent to the deployment (e.g., implantation) of prosthetic valve **2000**. Typically, elements **2002** are configured to couple to the leaflets by piercing the leaflets, at least in part.

(313) For some applications, prosthetic valve **2000** comprises two elements **2002**, that are disposed at sites on the circumference of primary structural element **130** that are generally opposite each other. For some applications of the invention, prosthetic valve **2000** comprises more than two (e.g., four or more, such as six or more) elements **2002**, that are disposed circumferentially around primary structural element **130**.

(314) For some applications, tissue-engaging elements **2002** protrude generally orthogonally to the outer surface of primary structural element **130** (i.e., generally straight outward laterally from element **130**). For some applications, elements **2002** protrude at an acute angle from the outer surface of primary structural element **130**. For example, and as illustrated in FIGS. **40A-C**, elements **2002** may protrude proximally, such that a portion (e.g., a tip) of elements **2002** that is further from a point of coupling between the element **2002**

and primary structural element **130**, is closer to the proximal end of element **130** than is a portion of elements **2002** that is closer to that point of coupling.

(315) FIG. **40A** shows prosthetic valve **2010**, comprising a plurality of tissue-engaging elements **2012**. Prosthetic valve **2010** is an embodiment of prosthetic valve **2000**, and elements **2012** are embodiments of tissue-engaging elements **2002**. Elements **2012** are typically configured to protrude at an acute angle from the outer surface of primary structural element **130** of prosthetic valve **2010**. Tip **2014** is the portion of element **2012** that is furthest from a point of coupling between the element **2012** and element **130**. For some applications of the invention, tip **2014** is sharp (e.g., pointed) so as to facilitate piercing of the native leaflets.

(316) FIG. **40B** shows prosthetic valve **2020**, comprising a plurality of tissue-engaging elements **2022**. Prosthetic valve **2020** is an embodiment of prosthetic valve **2000**, and elements **2022** are embodiments of tissue-engaging elements **2002**. For some applications of the invention, prosthetic valve **2020** and elements **2022** are analogous to, and/or comprise, prosthetic valve **2010** and elements **2012**, respectively. Elements **2022** are typically configured to protrude at an acute angle from the outer surface of primary structural element **130** of prosthetic valve **2020**. For some applications of the invention, elements **2022** are formed from a lattice structure that the prosthetic valve comprises. For example, a separation in the structure may allow a portion of the structure to be moved out of the plane of the structure, thereby protruding from element **130**.

Element **2022** thereby comprises the protruding portion of the structure. Tip **2024** is the portion of element **2022** that is furthest from a point of coupling between the element **2022** and element **130**. For some applications of the invention, tip **2024** is sharp (e.g., pointed) so as to facilitate piercing of the native leaflets.

(317) FIG. **40C** shows implant **30**, comprising prosthetic valve support **2030** and prosthetic valve **2000**, following implantation thereof in native valve **23**. Prosthetic valve support **2030** typically comprises support-anchoring elements **2032**. For some applications of the invention, prosthetic valve support **2030** and/or support-anchoring elements **2032** are analogous, respectively, to other prosthetic valve supports and support-anchoring elements described herein. For some applications of the invention, prosthetic valve support **2030** comprises prosthetic valve support **40**.

(318) Immediately following the implantation of support **2030** and prosthetic valve **2000**, leaflets **82** of the native valve typically continue to function, at least in part. For example, support-anchoring elements **2032** may be configured to rotate around a coupling point with upstream support portion **41** of the prosthetic valve, so as to allow the leaflets to continue to function, at least in part (e.g., as described herein for several support-anchoring elements). When leaflets **82** move against prosthetic valve **2000** (e.g., during systole), tissue-engaging elements **2002** couple to (e.g., by piercing) the leaflets.

(319) For some applications of the invention, tissue-engaging elements **2032** are configured to move leaflets **82** against prosthetic valve **2000**, and thereby onto tissue-engaging elements **2002**. For example, elements **2032** may be configured to move toward each other, such that following implantation of prosthetic valve support **2030** and coupling of elements **2032** to leaflets **82**, when prosthetic valve **2000** is deployed in the lumen of support **2030**, elements **2032** push leaflets **82** against the prosthetic valve.

(320) It is hypothesized that such coupling of leaflets **82** to elements **2002**, and thereby to prosthetic valve **2000**, facilitates (1) stable implantation of implant **30** in the native valve, and/or (2) sealing of leaflets **82** around the prosthetic valve, thereby inhibiting retrograde leakage of blood between the leaflets and the implant.

(321) FIG. **40C** shows, by way of illustration and not limitation, prosthetic valve **2000** being used in combination with a prosthetic valve support that comprises support-anchoring elements. It is to be noted that, for some applications, prosthetic valve **2000** is used in combination with other prosthetic valve supports that comprise support-anchoring elements, and/or with prosthetic valve supports that do not comprise support-anchoring elements.

(322) Reference is made to FIGS. **41A-B**, **42A-B**, **43A-C**, and **44A-B**, which are schematic illustrations of prosthetic valves and prosthetic valve supports, comprising a coupling functionality for coupling support-anchoring elements of the prosthetic valve support to the prosthetic valve.

(323) Reference is now made to FIGS. **41A-B**, which are schematic illustrations of prosthetic valve support **40**, comprising a prosthetic valve support **1122**, which comprises one or more support-anchoring elements **1124**, in accordance with some applications of the invention. FIG. **41A** shows support **1122**, and FIG. **41B** shows, implanted in a native valve **23**, an implant **30**, which comprises support **1122** and prosthetic valve **42**, comprising a prosthetic valve **1120**. For some applications of the invention, support-anchoring elements **1124** comprise (1) other support-anchoring elements described herein (e.g., support-anchoring elements **66**), and/or (tissue-engaging elements **62**). Support-anchoring elements **1124** comprise one or more barbs **1126**, which

comprise the coupling functionality for coupling the support-anchoring elements of the prosthetic valve support to the prosthetic valve. Typically, each barb **1126** protrudes from another part of element **1124** at between degrees and 80 degrees (e.g., between 15 degrees and 60 degrees). Typically, a tip of each barb is thereby disposed more distally (e.g., ventricularly) than a base of that barb. Typically, each barb **1136** has a length of between 0.5 and 5 mm.

(324) Prosthetic valve support **1122** is typically delivered to, and deployed at, native valve **23**, as described herein for other prosthetic valve supports. Support-anchoring elements **1124** are typically coupled to leaflets **82** of the native valve, as described herein for other support-anchoring elements. Subsequent to the deployment and coupling of support **1122** to the native valve, prosthetic valve **1120** is deployed in the lumen of the prosthetic valve support, as described herein for other prosthetic valves. As prosthetic valve **1120** expands, barbs **1126** engage and couple to the prosthetic valve, typically by protruding into voids defined by the prosthetic valve. For some applications of the invention, elements **1124** are configured to assume a pre-selected configuration, such as that shown in FIG. **41A**, and to restrain leaflets **82**. For some applications of the invention, elements **1124** are configured to allow leaflets **82** to continue to function, at least in part. For some such applications, movement of leaflets **82** and elements **1124**, caused by the beating of the heart, is hypothesized to facilitate engagement of the prosthetic valve by barbs **1126**.

(325) Typically, barbs **1126** are configured to protrude into the voids defined by prosthetic valve **1120**, but to not protrude further into the prosthetic valve, e.g., into the lumen defined by the prosthetic valve. Typically, prosthetic valve **1120** comprises a wire frame, and a covering **1128**, which covers at least part of the inner surface of the prosthetic valve (i.e., the walls of the lumen), so as to facilitate blood flow through the prosthetic valve. Typically, barbs **1126** are dimensioned so as to protrude into the voids defined by the prosthetic valve, but to not protrude into and/or through covering **1128**. That is, prosthetic valve **1120** and prosthetic valve support **1122** are configured so as to be couplable to each other using barbs **1126**, without the barbs contacting (and possibly damaging) covering **1128**.

(326) For some applications of the invention, and as illustrated in FIG. **41B**, the prosthetic valve is coupled to prosthetic valve support only by (1) a radially-expansive force exerted by the prosthetic valve on the prosthetic valve support, and (2) barbs **1126** protruding into the voids defined by the prosthetic valve. For such applications of the invention, the prosthetic valve (e.g., prosthetic valve **1120**) is typically couplable to the prosthetic valve support at a plurality of relative positions. That is, the prosthetic valve is typically implantable in the native valve at a plurality of depths i.e., a physician may decide on the depth at which the prosthetic valve is implanted in the native valve.

(327) Reference is now made to FIGS. **42A-B**, which are schematic illustrations of prosthetic valve support **40**, comprising a prosthetic valve support **1132**, which comprises one or more support-anchoring elements **1134**, in accordance with some applications of the invention. FIG. **42A** shows support **1132**, and FIG. **42B** shows, implanted in a native valve **23**, an implant **30**, which comprises support **1132** and prosthetic valve **42**, comprising a prosthetic valve **1130**. For some applications of the invention, support-anchoring elements **1134** comprise (1) other support-anchoring elements described herein (e.g., support-anchoring elements **66**), and/or (2) tissue-engaging elements **62**. Support-anchoring elements **1134** comprise one or more barbs **1136**, which comprise the coupling functionality for coupling the support-anchoring elements of the prosthetic valve support to the prosthetic valve. Typically, each barb **1136** protrudes from another part of element **1134** at between degrees and 80 degrees (e.g., between 15 degrees and 60 degrees). Typically, a tip of each barb is thereby disposed more distally (e.g., ventricularly) than a base of that barb. Typically, each barb **1136** has a length of between 0.5 and 5 mm.

(328) The structure, function and implantation method of prosthetic valve support **1132** and prosthetic valve **1130**, are typically similar to those of prosthetic valve support **1122** and prosthetic valve **1120**. However, each support-anchoring element **1134** of prosthetic valve support **1132** typically comprises no more than 4 barbs **1136** (e.g., 2 barbs **1136**). Prosthetic valve **1130** comprises a wire frame, and a covering **1138**, which covers at least part of the inner surface of the prosthetic valve (i.e., the walls of the lumen), so as to facilitate blood flow through the prosthetic valve. Typically, the inner surface of a portion (e.g., a distal portion **1139**) of prosthetic valve **1130** is not covered with covering **1138**. Typically, barbs **1136** are positioned and/or configured to engage and couple distal portion **1139**. That is, prosthetic valve **1130** and prosthetic valve support **1132** are configured so as to be couplable to each other using barbs **1136**, without the barbs contacting (and possibly damaging) covering **1138**.

(329) Reference is now made to FIGS. **43A-C**, which are schematic illustrations of a prosthetic valve support **1142**, comprising one or more support-anchoring elements **1144**, which are couplable to a prosthetic valve

1140, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **1142** comprises, and/or is analogous to, another prosthetic valve support described herein (e.g., prosthetic valve support **40**). For some applications of the invention, prosthetic valve **1140** comprises, and/or is analogous to, another prosthetic valve described herein (e.g., prosthetic valve **42**).

(330) Prosthetic valve support **1142** comprises one or more support-anchoring elements **1144**, which, for some applications of the invention, comprise, and/or are analogous to, (1) other support-anchoring elements described herein (e.g., support-anchoring elements **66**), and/or (2) tissue-engaging elements **62**. Support-anchoring elements **1144** comprise a coupling lead **1146** (e.g., a coupling wire) and a stopper **1147**, which is slidably coupled to the coupling lead. Coupling lead **114** and stopper **1147** comprise the coupling functionality for coupling the support-anchoring elements of the prosthetic valve support to the prosthetic valve. One end (e.g., a distal end) of coupling lead **1146** is typically coupled to element **1144**, and portion (e.g., a proximal portion) of the coupling lead is slidably coupled to prosthetic valve **1140**. For some applications of the invention, prosthetic valve **1140** is shaped to define an eyelet (not shown), through which coupling lead is slidable.

(331) FIG. **43A** shows prosthetic valve support **1142** having been deployed (e.g., implanted) in native valve **23**, and prosthetic valve **1140** in a compressed configuration within delivery tube **60**, prior to deployment. A coupling lead **1146** is coupled to each support-anchoring element **1144**, and extends proximally, through prosthetic valve **1140**.

(332) FIG. **43B** shows prosthetic valve **1140** following deployment thereof in the lumen defined by prosthetic valve support **1142**. Prosthetic valve **1140** has been slid over coupling leads **1146**. That is, the length of each coupling lead that is disposed between an element **1144** and a closest portion of the prosthetic valve, has been shortened. Each stopper **1147** has been slid distally over coupling lead **1146** (e.g., using a pusher; not shown), thereby sandwiching a portion of the prosthetic valve between each stopper and a respective element **1144**. Typically, coupling lead **1146** and stopper **1147** are configured to inhibit movement of the stopper in the opposite direction. For example, stopper **1147** may comprise a ratchet housing (e.g., may contain a ratchet mechanism), and coupling lead **1146** may comprise ratchet teeth. Thereby, sliding of stopper **1147** over coupling lead **1146** facilitates coupling of the prosthetic valve to the prosthetic valve support.

(333) For some applications of the invention, coupling leads **1146** facilitate rotational orientation of prosthetic valve **1140** with respect to support **1142** during deployment of the prosthetic valve in the lumen of the support. For example, coupling leads **1146** may act as guidewires, along which the prosthetic valve is slid during deployment thereof.

(334) For some applications of the invention, prosthetic valve **1140** is coupled to prosthetic valve support **1142** using coupling leads **1146** and stoppers **1147** (i.e., stoppers **1147** are slid distally, sandwiching the portions of the prosthetic valve between the stoppers and elements **1144**) before the prosthetic valve is fully deployed. For example, this coupling may be performed when the prosthetic valve is semi-deployed from delivery tube **60**, i.e., when a proximal portion of the prosthetic valve is still compressed within the delivery tube.

(335) Coupling of prosthetic valve **1140** to elements **1144** with coupling lead **1146** is hypothesized to inhibit lateral rotation (e.g., rotation around an atrial-ventricular axis), and/or axial movement, of the prosthetic valve, with respect to the support.

(336) Following coupling of prosthetic valve **1140** to support-anchoring elements **1144**, a proximal portion of coupling lead **1146** is typically subsequently removed from the subject. FIG. **43C** shows a distal portion of coupling lead **1146** having been decoupled from a proximal portion of the coupling lead. For some applications of the invention, coupling lead **1146** is cut. For some applications of the invention, the proximal portion of the coupling lead comprises a loop, which is (1) coupled to the distal portion of the coupling lead by being looped around an element of the distal portion of the coupling lead, and (2) decoupled from the distal portion of the coupling lead by being unlooped from the distal portion of the coupling lead. For some applications, the proximal portion of the coupling lead is (1) coupled to the distal portion of the guidewire using a lock described herein (e.g., with reference to FIGS. **45A-C** and/or **64A-C**, mutatis mutandis), and (2) decoupled from the distal portion of the coupling lead by moving the lock to the open configuration.

(337) Reference is made to FIGS. **44A-B**, which are schematic illustrations of (1) a prosthetic valve support **1162**, comprising one or more support-anchoring elements **1164**, and (2) a prosthetic valve **1160**, comprising one or more valve-anchoring elements **1166**, which are couplable to prosthetic valve support **1162**, in accordance with some applications of the invention. Typically, valve-anchoring elements **1166** are couplable to the prosthetic valve support by being couplable to support-anchoring elements **1164**. For some applications

of the invention, prosthetic valve support **1142** comprises, and/or is analogous to, another prosthetic valve support described herein (e.g., prosthetic valve support **40**). For some applications of the invention, prosthetic valve **1160** comprises, and/or is analogous to, another prosthetic valve described herein (e.g., prosthetic valve **42**). For some applications of the invention, support-anchoring elements **1164** comprise, and/or are analogous to, (1) other support-anchoring elements described herein (e.g., support-anchoring elements **66**), and/or (2) tissue-engaging elements **62**. For some applications of the invention, valve-anchoring elements **1166** comprise, and/or are analogous to, other valve-anchoring elements described herein (e.g., valve-anchoring elements **64**). For some applications of the invention, valve-anchoring elements **1166** comprise, and/or are analogous to, support-engaging elements, such as support-engaging elements **422**.

(338) FIG. **44A** shows prosthetic valve support **1162** having been deployed (e.g., implanted) in native valve **23**, and at least part of prosthetic valve **1160** in a compressed configuration within delivery tube **60**, prior to deployment. Valve-anchoring elements **1166** are typically coupled to a distal portion (e.g., a distal end) of the primary structural element of prosthetic valve **1160**, and, in the compressed configuration of the prosthetic valve, elements **1166** extending distally from the prosthetic valve. Elements **1166** are shown emerging from delivery tube **60**. For some applications of the invention, valve-anchoring elements **1166** are formed from the regular repeating structure of the lattice that forms the prosthetic valve, e.g., as described with reference to support-engaging elements **424** (FIGS. **8A-B**), *mutatis mutandis*.

(339) FIG. **44B** shows prosthetic valve **1160** following deployment thereof in the lumen defined by prosthetic valve support **1162**. Valve-anchoring elements **1166** are deployed on the distal (e.g., ventricular) side of the native valve, and are coupled to support-anchoring elements **1164**. Typically, support-anchoring elements **1164** are configured to facilitate coupling (1) of elements **1164** to the native valve (e.g., to leaflets **82**), and (2) of valve-anchoring elements **1166** to support-anchoring elements **1164**. Valve-anchoring elements **1166** thereby restrict proximal movement of prosthetic valve **1160**, i.e., elements **1166** couple the prosthetic valve to support **1162**, and to the native valve.

(340) Reference is made to FIGS. **45A-C**, which are schematic illustrations of a lock **1170** for facilitating delivery of a medical device, in accordance with some applications of the invention.

(341) Reference is now made to FIG. **45A**. Lock **1170** comprises a tubular member **1172** and a plug **1174**. Plug **1174** is dimensioned such that it is disposable in, and slidable through (e.g., into and out of) the lumen of tubular member **1172**. Plug **1174** comprises a restricting portion **1190** and a second portion **1192**. Lock **1170** has a locking configuration, in which (1) at least part of restricting portion **1190** is disposed inside the lumen of tubular member **1172**, and (2) a coupling lead **1180** (e.g., a coupling wire) that is coupled to the lock, is generally not decouplable from the lock. Lock **1170** further has an open configuration, in which (1) at least restricting portion **1190** is disposed outside the lumen of tubular member **1172**, and (2) coupling lead **1180** is decouplable from the lock. Typically, at least part of plug **1174** (e.g., restricting portion **1190**) is dimensioned so as to fit tightly in the lumen of tubular member **1172**, in a manner in which an outer surface of plug **1174** (e.g., an outer surface of portion **1190**) is disposed very close to an inner surface of tubular member **1172**, i.e., such that little space exists between the at least part of the plug and the tubular member. Typically, a surface of second portion **1192** is disposed further from the inner surface of tubular member **1172**, than is the surface of the at least part of portion **1190**.

(342) For some applications of the invention, second portion **1192** is shaped to define at least part of a trough, and the surface of the second portion that is disposed further from the inner surface of the tubular member, comprises a surface of the trough.

(343) FIG. **45A** shows coupling lead **1180** comprising a loop, and coupled to lock **1170** by at least part of the loop being disposed against second portion **1192** when the lock is in the locking configuration. Restricting portion **1190** inhibits axial movement of the coupling lead, and tubular member **1172** inhibits lateral movement of the coupling lead (e.g., the inner surface of tubular member holds the coupling lead against second portion **1192**). Tubular member **172** thereby facilitates coupling of coupling lead **1180** to plug **1174**, and thereby to lock **1170**.

(344) As is described hereinbelow, coupling lead **1180** is typically coupled to a medical device **150** and facilitates (1) coupling of medical device **150** to delivery apparatus during delivery of the medical device and (2) decoupling of medical device **150** from the delivery apparatus following implantation of device **150**.

(345) Reference is now made to FIG. **45B**. Plug **1174** is slid distally through tubular member **1172**, such that lock **1170** is in an open configuration. Typically, plug **1174** is moved using control wire **1175**. In this open configuration, restricting portion **1190**, and typically at least part of second portion **1192**, are exposed from the tubular member (i.e., are outside the lumen of the tubular member). Coupling lead **1180** is shown in FIG.

45B as being disposed against a surface of second portion **1192**, by way of illustration and not limitation, as a temporary configuration prior to disengagement of coupling lead **1180** from plug **1174** (i.e., decoupling of the coupling lead from lock **1170**; disengagement of coupling lead **1180** is described hereinbelow).

(346) FIG. **45C** shows lock **1170** in the open configuration, and coupling lead **1180** decoupled from the lock. In the open configuration of the lock, coupling lead **1180** is allowed to move away from plug **1174** (e.g., tubular member **1172** does not restrict lateral movement of the coupling lead away from second portion **1192**). That is, in the open configuration of the lock, coupling lead **1180** is decouplable from the lock.

Typically, coupling lead **1180** is moved away from plug **1174** by moving the former with respect to the latter (e.g., by applying a moving force to coupling lead **1180** and/or to plug **1174**). In some applications of the invention, at least a portion of coupling lead **1180** is configured such that it automatically moves out of the trough upon being exposed from the tubular member (i.e., when lock **1170** moves to the open configuration). For example, the coupling lead may comprise a shape-memory material such as nitinol, stainless steel, nickel cobalt, cobalt chrome, and/or titanium. In some applications of the invention, portions **1190** and **1192** are shaped to facilitate the decoupling of coupling lead **1180** from the lock. For example, a boundary between portions **1190** and **1192** may be sloped.

(347) Reference is made to FIGS. **46A-B**, which are schematic illustrations of prosthetic valve support **40**, comprising prosthetic valve support **1060**, which comprises one or more support-anchoring elements, such as support-anchoring elements **900**, coupled to a stabilizing element **1062** (e.g., a stabilizing strip or a stabilizing element), in accordance with some applications of the invention. FIG. **46A** shows a lower side view of support **1060**. As described hereinabove, the support-anchoring elements are typically coupled to inner edge **68**, which defines the lumen of upstream support portion **41**. That is, a first portion (e.g., a proximal end) of each support-anchoring element is typically coupled to inner edge **68**. A second portion of each support-anchoring element is typically coupled to stabilizing element **1062**. Typically, stabilizing element **1062** comprises an annular band. Further typically, a distal portion of each support-anchoring elements is coupled to the stabilizing element. Stabilizing element **1062** defines an opening (e.g., an aperture), and is typically inelastic and at least partly flexible. Non-limiting examples of materials that stabilizing element **1062** may comprise include polyester, PTFE (e.g., ePTFE), nylon, cotton, nitinol, stainless steel, nickel cobalt, cobalt chrome, titanium, tantalum and palladium. The flexibility of element **1062** typically facilitates the compressibility of the prosthetic valve support (e.g., for transvascular delivery). For some applications of the invention, the support-anchoring elements are configured to rotate freely around the point at which they couple to upstream support portion **41**, e.g., so as to allow leaflets of the native valve to continue to function (i.e., to move), at least in part. For some such applications, the flexibility of stabilizing element **1062** typically allows (i.e., does not generally inhibit) this movement of the support-anchoring elements and the leaflets.

(348) Stabilizing element **1062** is hypothesized to increase the stability of prosthetic valve support **1060** at the native valve. For example, stabilizing element **1062** is hypothesized to at least partly inhibit lateral rotation (e.g., rotation around an atrial-ventricular axis, e.g., ‘yaw’) of the support and/or support-anchoring elements. Following deployment (e.g., implantation) of the prosthetic valve, stabilizing element **1062** is further hypothesized to reduce rolling movement (e.g., movement around a lateral axis, e.g., an axis between two elements **900**, e.g., ‘pitch’ and ‘roll’) of the prosthetic valve and/or implant **30**, including inversion (e.g., ‘flipping’) of the implant.

(349) For some applications of the invention, stabilizing element **1062** is further hypothesized to stabilize elements **900** during deployment of the elements, e.g., by facilitating coupling thereof to delivery apparatus.

(350) FIG. **46B** shows implant **30**, comprising prosthetic valve support **1060** and prosthetic valve **42**, following implantation in native valve **23**. The prosthetic valve support and the prosthetic valve are typically implanted as described hereinabove, mutatis mutandis. Prosthetic valve **42** is deployed (e.g., delivered and expanded) in the lumen of support **1060**, and in the opening defined by stabilizing element **1062**. That is, when prosthetic valve **42** is deployed at the native valve, it is expanded such that (1) a proximal portion of the prosthetic valve couples to inner edge **68** of support **1060**, and (2) a distal portion of the prosthetic valve is disposed within the opening of the stabilizing element. For some applications of the invention, and as illustrated in FIG. **46B**, the distal portion of the prosthetic valve makes contact with the stabilizing element.

(351) For some applications of the invention, stabilizing element **1062** is configured (e.g., dimensioned) such that, when the prosthetic valve is expanded within the opening of the stabilizing element, the stabilizing element limits the expansion of the distal portion of primary structural element **130** of the prosthetic valve. That is, for some applications, the cross-sectional area defined by the primary structural element **130** of the prosthetic valve, upon expansion of the prosthetic valve, is determined by the cross-sectional area of the

opening of the stabilizing element. For some applications, the cross-sectional area of the opening of the stabilizing element is substantially equal to the cross-sectional area of the lumen defined by upstream support portion **41**, thereby the expansion of both the distal and proximal portions of the primary structural element are limited to the same diameter, thereby facilitating the primary structural element to assume a cylindrical shape.

(352) For applications where stabilizing element **1062** limits the expansion of prosthetic valve **42**, a radially-expansive force is thereby applied by prosthetic valve **42** to stabilizing element **1062**. The radially-expansive force typically couples the prosthetic valve to the stabilizing element. That is, for some applications, prosthetic valve **42** is couplable to the stabilizing element. For some applications, the prosthetic valve is coupled to the stabilizing element by alternative or additional means. For example, the stabilizing element may comprise barbs and/or hooks, which facilitate coupling to the prosthetic valve.

(353) For some applications of the invention, at least part (e.g., an inner surface) of stabilizing element **1062** comprises a friction coating, that is configured to increase friction, and thereby coupling, between the stabilizing element and the prosthetic valve.

(354) For some applications of the invention, at least part of stabilizing element **1062** is shaped to define ridges, which are configured (e.g., dimensioned) to protrude between struts of the lattice structure of the prosthetic valve (i.e., into voids defined by the lattice structure). The protruding parts facilitate coupling of the stabilizing element to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through the opening defined by the stabilizing element.

(355) For some applications of the invention, a soft (e.g., crushable) material is disposed on the inner surface of stabilizing element **1062** (e.g., the stabilizing element comprises the soft material). When prosthetic valve **42** expands, and applies radially-expansive force to the stabilizing element, (1) the struts of the lattice structure of the prosthetic valve compress (e.g., crush) the parts of the soft material against which the struts apply the force, and (2) the parts of the soft material that are disposed between the struts (i.e., that are disposed at voids defined by the lattice structure), form ridges that protrude between the struts (i.e., protrude into the voids). The protruding parts of the soft material facilitate coupling of the stabilizing element to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through the opening defined by the band, such as by increasing friction.

(356) For some applications of the invention, prosthetic valve **42** (e.g., the primary structural element of prosthetic valve **42**) is shaped to define a circumferential groove that is configured (e.g., dimensioned) to receive stabilizing element **1062**. That is, for some applications of the invention, stabilizing element **1062** is configured (e.g., dimensioned) to be placeable in a circumferential groove defined by prosthetic valve **42**. When prosthetic valve **42** is deployed, and expands in the opening defined by stabilizing element **1062**, stabilizing element **1062** is disposed in the groove, thereby further facilitating coupling of the stabilizing element to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through the opening defined by the stabilizing element.

(357) It is to be noted that, although stabilizing element **1062** is described with reference to FIGS. **46A-B** as being coupled to support-anchoring elements **900**, the scope of the present invention includes stabilizing elements coupled to other support-anchoring elements described herein, such as support-anchoring elements **66**.

(358) Reference is made to FIGS. **47A-C**, which are schematic illustrations of sequential steps in the implantation of implant **30**, comprising prosthetic valve **42** and prosthetic valve support **1040**, which comprises prosthetic valve support **1080**, in accordance with some applications of the invention. Prosthetic valve support **1080** comprises two stabilizing legs **910**, which comprise stabilizing legs **910a**. Support **1080** and/or legs **910a** are configured such that, during deployment of support **1080** (e.g., from an overtube), legs **910a** automatically move toward a pre-defined stabilizing configuration thereof. For example, legs **910a** may comprise a shape-memory material that is biased (e.g., shape-set) to move the legs toward the stabilizing configuration thereof.

(359) FIG. **47A** shows support **1080** during deployment thereof. Annular portion **41** is disposed against the proximal (e.g., atrial) side of native valve **23**, and stabilizing legs **910a** are moving toward the stabilizing configuration thereof. That is, FIG. **47A** is a ‘snapshot’ of support **1080** immediately following the release thereof from a delivery tube.

(360) FIG. **47B** shows support **1080** following deployment thereof at native valve **23**. Stabilizing legs **910a** have moved into the stabilizing configuration thereof. As described hereinabove, mutatis mutandis, for stabilizing legs **910**, with reference to FIG. **36A**, proximal portion **912** of each leg is disposed on a plane

between (1) a plane **999** that is orthogonal to a plane defined by upstream support portion **41**, and (2) a position in which the leg touches a part of upstream support portion **41** that is peripheral to inner edge **68**. (361) FIG. **47C** shows prosthetic valve **42** following deployment thereof in the lumen of support **1080**. Typically, and as shown in FIG. **47C**, the primary structural element of prosthetic valve **42** defines plane **999**, that is orthogonal to the plane defined by upstream support portion **41**. That is, in the stabilizing configuration thereof, stabilizing legs **910a** are typically disposed on a plane between (1) a plane defined by the primary structural element of prosthetic valve **42**, and (2) a plane defined by upstream support portion **41**.

(362) Reference is made to FIGS. **48A-C**, which are schematic illustrations of sequential steps in the implantation of implant **30**, comprising prosthetic valve **42** and prosthetic valve support **1040**, which comprises prosthetic valve support **1090**, in accordance with some applications of the invention. Prosthetic valve support **1090** comprises two stabilizing legs **910**, which comprise stabilizing legs **910b**.

(363) FIG. **48A** shows prosthetic valve support **1090** in an at-rest configuration thereof, subsequent to deployment of the support at native valve **23**. Support **1090** and/or legs **910b** are configured such that, subsequent to deployment of support **1090** (e.g., from an overtube), legs **910b** are disposed proximal to upstream support portion **41** (e.g., atrially). For example, legs **910b** may comprise a shape-memory material that is biased (e.g., shape-set) to move the legs toward the at-rest configuration.

(364) FIG. **48B** shows prosthetic valve **42**, in a compressed configuration thereof, disposed within a delivery tube **60**, being delivered to native valve **23**. Prosthetic valve **42** is moved distally into the lumen defined by upstream support portion **41**. Stabilizing legs **910b** move (e.g., rotate) through the lumen, responsively to the movement of the prosthetic valve. For example, distal movement of the prosthetic valve may directly push the stabilizing legs through the lumen. Alternatively or additionally, prosthetic valve **42** and/or stabilizing legs **910b** may comprise engaging elements (e.g., barbs and/or levers) which facilitate the movement of the stabilizing legs in response to the movement of the prosthetic valve.

(365) FIG. **48C** shows prosthetic valve **42** following deployment thereof in the lumen of support **1090**. Stabilizing legs **910b** have moved into the stabilizing configuration thereof. Typically, and as shown in FIG. **48C**, the primary structural element of prosthetic valve **42** defines plane **999**, that is orthogonal to the plane defined by upstream support portion **41**. That is, in the stabilizing configuration thereof, stabilizing legs **910b** are typically disposed on a plane between (1) a plane defined by the primary structural element of prosthetic valve **42**, and (2) a plane defined by upstream support portion **41**.

(366) Reference is made to FIG. **49**, which is a schematic illustration of prosthetic valve support **40**, embodied as a prosthetic valve support **4040a**, in accordance with some applications of the invention. Prosthetic valve support **4040a** comprises a cylindrical element **90** that is configured to extend distally through native valve **23**. Cylindrical element **90** is typically configured to (1) facilitate coupling of prosthetic valve support **4040a** to the native valve, and/or sealing therebetween, (2) to facilitate coupling of prosthetic valve support **4040a** to prosthetic valve **42** (or any other prosthetic valve described herein), and/or sealing therebetween, and/or (3) to push aside native leaflets **82** of native valve **23**. For such applications of the present invention in which prosthetic valve support **40** (i.e., prosthetic valve support **4040a**) comprises cylindrical element **90**, support **40** and prosthetic valve **42** may be implanted in a manner as described hereinabove with reference to FIGS. **1A-H**.

(367) Reference is made to FIG. **50**, which is a schematic illustration of an alternative technique for the implantation of implant **30**, in accordance with some applications of the invention. FIG. **50** shows a technique in which prosthetic valve **42** (shown crimped within delivery tube **60**) is advanced within ventricle **28** prior to and/or in conjunction with the deployment of support **40**.

(368) Reference is now made to FIGS. **1A-H** and **50**. FIGS. **1A-H** illustrate the implantation of implant **30**, whereby prosthetic valve support **40** is initially delivered and placed against the annulus of the native valve, and subsequently, prosthetic valve **42** is delivered to the native valve. In some applications of the invention, as shown in FIG. **50**, these two components of implant **30** are delivered in reverse order. FIG. **50** illustrates (1) the undeployed prosthetic valve **42**, having been initially delivered to ventricle **28**, and (2) prosthetic valve support **40** being subsequently and/or in conjunction, delivered and deployed within atrium **26**. In these applications of the invention, following deployment and positioning of prosthetic valve support **40** against the annulus of native valve **23**, prosthetic valve **42** is moved atrially (i.e., proximally) into the respective lumens of the native valve and prosthetic valve support **40**, and is deployed, as described hereinabove with reference to FIGS. **1G-H**.

(369) It is to be noted that implants **30** described herein may be implanted using the method described hereinabove with reference to FIGS. **1A-H**, or using the method described hereinabove with reference to FIG.

50.

(370) Reference is made to FIGS. 51A-B, which are schematic illustrations of prosthetic valve support **40**, comprising respective prosthetic valve supports **4040b** and **4040c** which each comprise one or more wings **100**, in accordance with respective applications of the invention. Prosthetic valve support **40** is generally annular and is shaped to define a lumen. Wings **100** are configured and positioned with respect to prosthetic valve supports **4040b** and **4040c** so as to provide one or more of the following advantages: (1) Increasing the stability of the support on the atrial surface of the native valve annulus during the implantation procedure and/or post-implantation. (2) Distributing forces more evenly across the annulus of the native valve. (3) Restricting movement of native valve leaflets. (4) Preventing tilting of support **40** and subsequent interference with the LVOT.

(371) Wings **100** typically increase a ratio of surface area of the support to annular tissue. Wings **100** typically protrude between 5 mm and 40 mm (e.g., between 10 mm and 30 mm) from outer edge **69** of the support. Prosthetic valve support **4040b** comprises two wings, as shown in FIG. 51A, typically positioned spaced apart from each other by 80-150 degrees, as shown. Prosthetic valve support **4040c** comprises three wings, as shown in FIG. 51B, typically positioned spaced apart from each other by 80-150 degrees (e.g., by 120 degrees, as shown). Other quantities and configurations of wings **100** may be used in order to optimize the positioning and/or stability of prosthetic valve support **40**.

(372) In some applications of the invention, prosthetic valve support **40** (e.g., prosthetic valve supports **4040a**, **4040b**, **4040c**) comprises barbs **102**, which protrude into the lumen defined by support **40**. During the expansion of prosthetic valve **42** within the lumen of support **40**, as described hereinabove, barbs **102** protrude into and engage prosthetic valve **42**. Barbs **102** thereby facilitate coupling between support **40** and prosthetic valve **42** in addition to the radial forces between support and prosthetic valve **42**. In some applications of the invention, some or all of barbs **102** may be curved, as shown in the enlarged images of FIGS. 51A-B. Typically, the curved barbs curve away from the transverse plane of prosthetic valve support **40**, such that, when implanted, barbs **102** point proximally (i.e., into atrium **26**). The applications of the invention described with reference to FIGS. 51A-B may be used in combination with other applications of the invention described herein (i.e., applications described herein in which prosthetic valve support **40** is used).

(373) Reference is made to FIG. 52, which is a schematic illustration of prosthetic valve **42** which comprises a variable-dimensioned valve **4042a**, in accordance with some applications of the present invention. As described hereinabove, expansion of prosthetic valve **42** in the lumen of prosthetic valve support **40** creates radial force between prosthetic valve support **40** and prosthetic valve **42**, which facilitates coupling of prosthetic valve **42** to prosthetic valve support **40**. In some applications of the present invention, a proximal portion **110** (e.g., the atrial end) of structural element **130** of prosthetic valve **4042a** expands such that it assumes a dimension larger than the lumen defined by support **40** (i.e., such that portion **110** has a longest length measured from a first point of portion **110** to a second point of portion **110** opposite the first point of portion **110** at a transverse cross-section of portion **110**, which is larger than a longest length of the lumen of support **40** measured from a first point on support **40** to a second point of support **40** opposite the first point of support **40** at the transverse cross-section). Typically, proximal portion **110** expands more than distal portions of prosthetic valve **4042a**. For example, portion **110** expands more than at least the portion of prosthetic valve **4042a** that is disposed within the lumen of support **40**. For some applications of the present invention, portion **110** expands more than at least the distal end of valve **4042a** (e.g., the portion of valve **42** designated for positioning within ventricle **28**).

(374) As illustrated in FIG. 52, proximal portion **110** may be trumpet-shaped. Alternatively, proximal portion **110** may be frustoconical, or may be any other configuration that has a dimension larger than the lumen defined by prosthetic valve support **40**. The extra expansion of proximal portion **110** described hereinabove provides axial resistance against undesired distal (i.e., ventricular) movement of prosthetic valve **4042a** with respect to support **40**, in addition to the resistance provided by the radially expansive forces between prosthetic valve **42** (i.e., prosthetic valve **4042a**) and prosthetic valve support **40**, as described hereinabove. The extra expansion of proximal portion **110** is further hypothesized to facilitate release of proximal portion **110** from delivery apparatus (e. g., from a pushing member, from coupling tabs **4146**, and/or from troughs **222**, described hereinbelow with reference to FIGS. 62A-D and 63A-B) thereby facilitating deployment of prosthetic valve **4042a**. Furthermore, the shape of prosthetic valve **4042a** is hypothesized to facilitate its alignment with respect to prosthetic valve support **40** and/or native valve **23** (e.g., to be at least in part self-righting, at least during deployment).

(375) In FIG. 52, prosthetic valve **4042a** is illustrated by a solid surface for clarity of illustration. It is to be

noted that, typically, prosthetic valve **42** comprises a lattice structure as described hereinabove. The application of the present invention described with reference to FIG. **52** may be used in combination with applications of the present invention described herein (i.e., applications for which prosthetic valve **42** is used). (376) Reference is made to FIGS. **53A-C**, which are schematic illustrations of prosthetic valve **42** comprising an integrally-anchoring prosthetic valve **42b**, which comprises valve-anchoring elements **64** comprising a plurality of integral anchors **300**, in accordance with some applications of the present invention.

(377) Reference is now made to FIG. **53A**, which is a schematic illustration of prosthetic valve **42b**, in planar/flattened view in which prosthetic valve **42b** is cut longitudinally and flattened, for clarity of illustration. It is to be noted, however, that the configuration shown in FIG. **53B** defines the configuration of valve **42b** in an assembled, crimped state. Prosthetic valve **42b** comprises a lattice structure, comprising a plurality of struts which typically collectively define a tessellation of shapes **128**, e.g., generally-quadrilateral shapes, as shown. In the application of the present invention illustrated in FIGS. **53A-C**, the shapes **128** that form the lattice structure include crude diamonds **120** or crude kite-shapes (i.e., deltoids) **122**, or a combination thereof. It is to be noted that the scope of the present invention includes prosthetic valves having a tessellation of one or a combination of other shapes.

(378) The lattice structure of prosthetic valve **42b** further defines a plurality of voids **126**. Shapes **128** are typically arranged in columns **118**, each shape connected to the next in each column. In some regions of the prosthetic valve, there is a separation **124** between a distal shape and an adjacent shape (e.g., between the final shape in a column and a respective penultimate shape in the column that is longitudinally proximal to the distal quadrilateral). This separation **124** allows a portion of the shape to move or be moved out of the plane of the lattice, thereby protruding from primary structural element **130** of prosthetic valve **42b** when the distal portion of prosthetic valve **42b** is expanded. The protruding portion of shapes **128** thereby form integral anchors **300**, which are typically configured to anchor prosthetic valve **42b** to native valve **23**. Valve-anchoring elements **64** are thereby formed from integral parts of the lattice structure that forms prosthetic valve **42b**, and are disposed between a proximal end **251** and a distal end **252** of primary structural element **130** of prosthetic valve **42b**. That is, prosthetic valve **42b** has a functional length (i.e., a length selected so as to facilitate prosthetic valve function), and integral anchors **300** typically do not increase the length of prosthetic valve **42b** to be greater than the functional length.

(379) Reference is made to FIGS. **53B-C**, which are schematic illustrations of sequential steps of prosthetic valve **42b** being implanted.

(380) Reference is now made to FIG. **53B**. Prosthetic valve **42b** is compressible (e.g., crimpable) and expandable, and typically comprises a shape-memory material (e.g., nitinol). Prosthetic valve **42b** is configured (e.g., shape-set) such that valve-anchoring elements **64**, embodied as integral anchors **300**, are biased to protrude from the surface of primary structural element **130**. In this application of the present invention, primary structural element **130** of prosthetic valve **42b** is generally cylindrical, and integral anchors **300** protrude radially from the surface of the cylinder. Because integral anchors **300** are formed from the regular repeating structure of the lattice that forms prosthetic valve **42b**, anchors **300** fit back into the plane of structural element **130** when valve **42b** is crimped into delivery tube **60**, prior to and even during implantation. Integral anchors **300**, thereby typically do not increase the length nor the transverse cross-sectional longest dimension of the crimped configuration of prosthetic valve **42**, as compared to those of any other prosthetic valves that do not comprise valve-anchoring elements **64** or that comprise elements **64** at a distal end thereof.

(381) As described hereinabove, prosthetic valve **42** is deployed by distal movement out of delivery tube **60**. FIG. **53B** shows prosthetic valve **42b** in a partially-deployed state, such that integral anchors **300** have emerged from delivery tube **60**, and have assumed an unconstrained, expanded, resting configuration in which the integral anchors **300** protrude from the surface of primary structural element **130** of the prosthetic valve. In an expanded state of at least the distal portion of valve **42b**, as shown in FIG. **53B**, integral anchors **300** typically protrude up to and including 110 degrees (e.g., between 45 and 90, such as between 45 and 60 degrees) from the surface of primary structural element **130**, in a resting state of anchors **300**. That is, in the protruded state, the proximal portions of anchors **300** are distanced further from structural element than the distal portions of anchors **300** which function as the pivot joints **4074** between anchors **300** and structural element **130**, as shown in the enlarged image of FIG. **53B**. Typically, this partial deployment of prosthetic valve **42** is performed on the distal side of native heart valve **23** (e.g., the ventricular side of mitral valve **24**).

(382) Reference is now made to FIG. **53C**. Following the movement of integral anchors **300** into their unconstrained, protruding, configuration, prosthetic valve **42b** is pulled proximally (i.e., toward atrium **26**),

along with delivery tube **60**. This proximal movement causes integral anchors **300** to abut against and capture leaflets **82** of the native valve in order to anchor prosthetic valve **42b** to the ventricular side of the native valve. Typically, integral anchors **300** capture leaflets **82** of the native valve by sandwiching leaflets **82** against primary structural element **130** of prosthetic valve **42b** and/or against the wall of ventricle **28**. Typically, but not necessarily, integral anchors **300** protrude between chordae tendineae **80** of the native valve.

(383) Typically, the anchoring of the prosthetic valve and/or the capturing of leaflets of the native valve are performed while prosthetic valve **42b** is partially deployed from delivery tube **60**, as shown in FIG. **53C**. Prosthetic valve **42b** is then fully deployed by moving delivery tube **60** proximally with respect to valve **42b**, thereby sliding the delivery tube off of the prosthetic valve and allowing the prosthetic valve to expand. Such expanding of prosthetic valve **42b** facilitates coupling of the prosthetic valve to support **40**, as described with reference to FIG. **1G**.

(384) Reference is made to FIGS. **54A-D**, which are schematic illustrations of prosthetic valve **42** comprising an integrally-anchoring prosthetic valve **42c**, which comprises valve-anchoring elements **64** comprising a plurality of integral anchors **310**, in accordance with some applications of the present invention.

(385) Integral anchors **310** are similar in form and function to integral anchors **300**, and are typically formed by separations **124** in the lattice structure of structural element **130**, as described with reference to FIGS. **53A-C**. Integral anchors **310** are configured (e.g., shape-set) so as protrude from primary structural element **130** of prosthetic valve **42c**, typically at a more acute angle than integral anchors **300** of FIGS. **53A-C** protrude from prosthetic valve **42b**. For example, integral anchors **310** may have an unconstrained, expanded, resting configuration in an expanded state of at least the distal portion of prosthetic valve **42c**, in which anchors **310** protrude up to and including 110 degrees (e.g., up to and including 60 degrees, or between 5 and 80 degrees, or between 5 and 40 degrees) from the surface of primary structural element **130** in a resting state of anchors **310**. Integral anchors **310** can be deformed by a deforming force (e.g., by pushing tube **60** distally against pivot joints **4074** between anchors **310** and structural element **130**, as described hereinbelow) into a further-expanded configuration, in which anchors **310** protrude at a greater angle from the surface of primary structural element **130** than the angle of the resting configuration of anchors **310**; thus, integral anchors **310** may be considered more open in this configuration than they are in their resting configuration. In this further-expanded, open configuration, integral anchors **310** typically are made to protrude up to and including 160 degrees (e.g., between 30 and 110 degrees, such as between 60 and 110 degrees) from the surface of structural element **130** of prosthetic valve **42c**. Since anchors **310** have a shape memory of assuming the resting state in the absence of force applied thereto, integral anchors **310** return toward the resting state upon removal of the deforming force (e.g., once tube **60** is not pushed distally against pivot joints **4074**).

(386) As described hereinabove, prosthetic valve **42** is deployed by distal movement out of delivery tube **60**. FIG. **54A** shows prosthetic valve **42c** in a partially-deployed state, such that integral anchors **310** have emerged from delivery tube **60**, and have assumed the unconstrained, expanded resting configuration described hereinabove. Typically, this partial deployment of prosthetic valve **42** is performed on the distal side of native heart valve **23** (e.g., the ventricular side of mitral valve **24**).

(387) Reference is now made to FIG. **54B**. Following partial deployment of prosthetic valve **42c**, the prosthetic valve is moved proximally with respect to delivery tube **60** (e.g., prosthetic valve **42c** is moved proximally while delivery tube **60** remains stationary, or prosthetic valve **42c** remains stationary while delivery tube **60** is moved distally, or prosthetic valve **42c** is moved proximally while delivery tube **60** is moved distally). The distal end of delivery tube **60** is thereby pushed between primary structural element **130** and integral anchors **310**, and provides the deforming force that pushes the integral anchors toward their further-expanded open configuration, described hereinabove.

(388) Reference is now made to FIG. **54C**. Delivery tube **60** and prosthetic valve **42c** are pulled proximally (i.e., toward atrium **26**). This proximal movement causes the open integral anchors **310** to engage leaflets **82** of the native valve, as described hereinabove.

(389) Reference is now made to FIG. **54D**. Delivery tube **60** is moved proximally with respect to prosthetic valve **42c** (e.g., by withdrawing delivery tube **60** proximally), thereby removing the deforming force on anchors **310**. As described hereinabove, this removal of the deforming force releases integral anchors **310**, which are thereby allowed to return toward their resting state, to (1) clamp the chordae tendineae **80** and/or leaflets **82** of native valve **23** against primary structural element **130** of prosthetic valve **42c**, and (2) anchor the prosthetic valve to the ventricular side of the native valve. Typically, prosthetic valve **42** is then fully deployed from delivery tube **60** (e.g., by retracting tube **60** with respect to valve **42**), thereby allowing radial

expansion of the prosthetic valve to couple prosthetic valve **42** to prosthetic valve support **40**, as described hereinabove.

(390) Reference is now made to FIGS. **53A-C** and **54A-C**. For such applications of the present invention in which prosthetic valve **42** (i.e., prosthetic valves **42b** and/or **42c**) comprises integral anchors **300** and/or **310**, prosthetic valve support **40** and prosthetic valve **42** may be implanted in a manner as described hereinabove with reference to FIGS. **1A-H**. The scope of the present invention includes implantation of implant **30** in a manner whereby prosthetic valve **42** is delivered to native valve **23** and/or at least partially deployed, prior to the deployment of support **40** (e.g., as described hereinabove with reference to FIG. **50**).

(391) Reference is made to FIGS. **55A-E**, which are schematic illustrations of prosthetic valve **42** comprising a twisted-anchor-based prosthetic valve **42d**, which comprises valve-anchoring elements **64** comprising twisted anchors **320**, in accordance with some application of the invention.

(392) FIGS. **55A-B** show valve-anchoring elements **64**, comprising twisted anchors **320**, in their constrained and unconstrained configurations, respectively. Prosthetic valve **42d** typically comprises a shape-memory material (e.g., nitinol), shaped to define a lattice structure. The lattice structure comprises a plurality of struts which typically collectively define a tessellation of shapes **128** (e.g., crude diamonds **120**). Prosthetic valve **42d** comprises one or more twisted anchors **320**, disposed at the distal end of prosthetic valve **42d**.

(393) As described hereinabove, valve-anchoring elements **64** typically have a constrained configuration for delivery, and an unconstrained configuration whereby they protrude radially from primary structural element **130** of prosthetic valve **42**. For some applications, in the constrained configuration of elements **64**, during delivery, elements **64** are typically but not necessarily disposed distal to the generally-cylindrical structure of valve **42** at an angle that is between 165 and 180 degrees with respect to the generally-cylindrical structure. In order to achieve these constrained and unconstrained configurations for prosthetic valve **42d**, comprising twisted anchors **320**, a distal portion of prosthetic valve **42d** is typically torsionally bent to define twisted anchors **320**. For some applications of the present invention, in order to achieve these configurations for prosthetic valve **42d** comprising twisted anchors **320**, a distal portion of prosthetic valve **42d** is typically bent to define twisted anchors **320**.

(394) The material comprising the lattice structure of prosthetic valve **42** has a depth **242** and each strut of the lattice structure has a width **244** (shown in FIG. **55B**). Typically, depth **242** is greater than width **244**. Depth **242** is typically between 0.15 mm and 1.1 mm (e.g., between 0.3 mm and 0.6 mm) and width **244** is typically between 0.05 mm and 0.9 mm, (e.g., between 0.1 mm and 0.4 mm). In this application of the invention, the bending comprises twisting in the vicinity of a bending region **240**, such that a bend axis **246** (shown in FIG. **55B**) is substantially parallel to depth **242** in a vicinity of a distal portion of bending region **240**. That is, a bend radius **248** lies on a plane that is substantially parallel to the relatively smaller width **244**, thereby allowing a smaller thickness of material to be bent, compared to if bend radius **248** were parallel with the relatively greater depth **242**. It is hypothesized that this configuration allows a greater bend angle to be imparted, such that twisted anchors **320** can (1) be disposed distal to (e.g., planar with) primary structural element **130** of prosthetic valve **42d** when the twisted anchors are in their constrained configuration (i.e., when compressed in delivery tube **60** for delivery) as shown in FIG. **55A**, and (2) pivot greater than 90 degrees (e.g., greater than 110 degrees, greater than 120 degrees, or greater than 150 degrees), to protrude radially from primary structural element **130** when in their unconstrained configuration (i.e., following deployment of at least the distal portion of prosthetic valve **42d**).

(395) It is to be noted, that during delivery of prosthetic valve **42d** toward mitral valve **24**, valve **42d** is crimped within delivery tube **60** such that anchors **320** assume a constrained and compressed state within tube **60**.

(396) Reference is now made to FIGS. **55C-E**, which are schematic illustrations of sequential steps in the deployment and retrieval of prosthetic valve **42d** that comprises twisted anchors **320**. FIG. **55C** shows delivery tube **60** being moved proximally with respect to prosthetic valve **42d** (e.g., prosthetic valve **42d** is moved distally while delivery tube **60** remains stationary, or prosthetic valve **42d** remains stationary while delivery tube **60** is moved proximally, or prosthetic valve **42d** is moved distally while delivery tube **60** is moved proximally). Twisted anchors **320** (disposed at a distal portion of valve **42**), emerge first from within tube **60** and begin to move from their constrained and compressed configuration toward their unconstrained and expanded configuration once exposed from within tube **60**.

(397) Reference is now made to FIG. **55D**. Delivery tube **60** is moved further proximally, such that prosthetic valve **42d** is partially deployed toward its expanded configuration. Because delivery tube **60** clears anchors **320**, twisted anchors **320** typically assume their resting unconstrained configuration. The physician may

proceed to couple prosthetic valve **42d** to the native valve and/or to prosthetic valve support **40**, as described with reference to FIGS. **1F-G**.

(398) Reference is now made to FIG. **55E**. Valve-anchoring elements **64** comprising twisted anchors **320**, facilitate retrieval of prosthetic valve **42d** into delivery tube **60**. Should it be necessary and/or desirable, while a proximal portion of valve **42d** is still crimped within tube **60**, delivery tube **60** may be moved distally with respect to prosthetic valve **42d** (e.g., prosthetic valve **42d** is moved proximally while delivery tube **60** remains stationary, prosthetic valve **42d** remains stationary while delivery tube **60** is moved distally, or prosthetic valve **42d** is moved proximally while delivery tube **60** is moved distally), thereby recompressing prosthetic valve **42d** into the delivery tube. Twisted anchors **320** are pushed distally by delivery tube **60**, such that they may also be straightened, as shown, and subsequently enter the delivery tube. Prosthetic valve **42d** may then be repositioned and redeployed, or may be removed from the subject.

(399) In some applications of the invention, twisted anchors **320** comprise more than one bending region **240**. For such applications, the material comprising prosthetic valve **42d** is bent and twisted in each respective bending region, as described with reference to FIGS. **55A-B**. For example, one bending region may be longitudinally proximal (i.e., coaxial) with respect to another bending region. Twisted anchors **320** that comprise more than one bending region are hypothesized to have enhanced pivoting ability compared to valve-anchoring elements that comprise one bending region. That is, twisted anchors **320** having more than one bending region enable anchors **320** to move more than 90 degrees, e.g., more than 160 degrees, with respect to a surface of structural element **130**. For example, twisted anchors **320** may pivot such that they clamp leaflets **82** of the native valve against primary structural element **130** of prosthetic valve **42**, thereby anchoring the prosthetic valve to the native valve.

(400) Reference is made to FIGS. **56A-D**, which are schematic illustrations of prosthetic valve **42** comprising a clip-on prosthetic valve **42e**, which comprises valve-anchoring elements **64** that comprise loop-shaped valve-anchoring elements **200** arranged in pairs **132** to form clips **65a**, in accordance with some applications of the invention.

(401) Reference is now made to FIG. **56A**. As described hereinabove, prosthetic valve **42** is compressible (e.g., crimpable) and expandable, and typically comprises a shape-memory material (e.g., nitinol). In this application of the invention, prosthetic valve **42e** comprises loop-shaped valve-anchoring elements **200**, arranged in pairs **132**. Typically, a first loop-shaped valve-anchoring element **200a** in each pair is smaller than a second loop-shaped valve-anchoring element **200b**, such that first loop-shaped element **200a** is disposable within and/or passable through a space defined by the larger loop shape of second loop-shaped valve-anchoring element **200b**. It is to be noted that the scope of the present invention includes other configurations and arrangements of elements **200**.

(402) It is to be noted that the scope of the present invention includes a first loop-shaped valve-anchoring element **200a** being larger than second loop-shaped valve-anchoring element **200b**, such that second loop-shaped element **200b** is disposable within and/or passable through a space defined by the larger loop shape of first loop-shaped valve-anchoring element **200a**.

(403) As described hereinabove, valve-anchoring elements **64** have a constrained and compressed configuration for delivery of prosthetic valve **42e** (as shown in FIG. **56A**), and an unconstrained, expanded configuration when prosthetic valve **42e** is deployed (as shown in FIG. **56B**).

(404) Loop-shaped valve-anchoring elements **200** are shown in FIG. **56A** in their constrained configuration in which second loop-shaped valve-anchoring element **200b** of each pair **132** is typically disposed distal to primary structural element **130**, and first loop-shaped valve-anchoring element **200a** of each pair **132** is typically disposed against the surface of primary structural element **130**. That is, in their constrained configuration, loop-shaped valve-anchoring elements **200** are typically longitudinally aligned.

(405) FIG. **56B** shows loop-shaped valve-anchoring elements **200** in their unconstrained, expanded configuration. Movement from the constrained configuration to the unconstrained configuration of elements **200** typically comprises (1) pivoting proximally of second valve-anchoring element **200b** of each pair **132**, and (2) pivoting distally of first valve-anchoring element **200a** of each pair **132**. In some applications of the invention, in the unconstrained configuration, the planes defined by the two valve-anchoring elements **200** of each pair **132** are generally aligned (e.g., within 20 degrees of each other).

(406) In some applications of the invention, in the unconstrained configuration, a rounded end of second valve-anchoring element **200b** of each pair **132** is disposed more proximally than a rounded end of first valve-anchoring element **200a**. In such applications, movement of valve-anchoring elements **200** from the constrained configuration to the unconstrained configuration comprises movement of the rounded ends of the

second valve-anchoring elements **200b** of each pair **132** proximally past the respective rounded ends of the first valve anchoring elements **200a** of each pair **132**.

(407) In either application, movement of valve-anchoring elements **200** from the constrained configuration to the unconstrained configuration allows elements **200a** and **200b** to capture material (e.g., leaflets **82** of the native valve) between them, i.e., in a manner in which elements **200a** and **200b** function together as a clip **65a**.

(408) FIGS. **56C-D** show sequential steps in the implantation of prosthetic valve **42e**. FIG. **56C** shows prosthetic valve **42e** disposed in a crimped configuration in delivery tube **60**. Delivery tube **60** is moved proximally with respect to prosthetic valve **42e**, such that only loop-shaped valve-anchoring elements **200b** (i.e., the first-deployed anchoring elements) of each pair **132** are released and move toward their unconstrained configuration, typically by pivoting in a proximal direction and in a direction toward the ventricular surface of respective leaflets **82**.

(409) Typically, following the deployment of elements **200b** at the respective ventricular surfaces of leaflets **82**, elements **200a** are positioned within tube **60** in a manner in which during their expansion from within tube **60**, elements **200a** move toward respective atrial surfaces of leaflets **82**. For some applications, following the deploying of elements **200b**, valve **42e** is pulled proximally (e.g., by pulling proximally on both valve **42e** and tube **60**) in order to adjust the positioning of valve **42e** with respect to leaflets **82** and so as to ensure that, once deployed from within tube **60**, elements **200a** will press against respective atrial surfaces of leaflets **82**.

(410) FIG. **56D** shows delivery tube **60** having been removed (i.e., by being retracted) from the body of the subject. During the retracting of tube **60** loop-shaped valve-anchoring elements **200a** (i.e., the second-deployed anchoring elements) of each pair are deployed such that elements **200a** move toward their unconstrained configuration, typically by pivoting in a distal direction and in a direction toward the atrial surfaces of respective leaflets **82**. Leaflets **82** of the native valve are thereby clamped between the two loop-shaped valve-anchoring elements **200a** and **200b** of each pair **132**, thereby anchoring prosthetic valve **42e** to native valve **23**. Thus, pairs **132** of loop-shaped valve-anchoring elements **200** function as clips **65a**.

(411) Reference is made to FIGS. **57A-D**, which are schematic illustrations of prosthetic valve **42** comprising a clip-on prosthetic valve **42f**, which comprises valve-anchoring elements **64** that comprise clips **65b**, in accordance with some applications of the invention.

(412) FIG. **57A** shows clips **65b** being typically coupled to the distal end of primary structural element **130** of prosthetic valve **42f**. Typically, clips **65b** are flexibly coupled to prosthetic valve **42f**, i.e., valve-coupling elements **64** are configured such that clips **65b** are able to move with respect to prosthetic valve **42f**. During the implantation of prosthetic valve **42f**, clips **65b** are clipped to leaflets **82** and/or chordae tendineae **80** of the native valve, thereby anchoring the prosthetic valve to the native valve. FIG. **57A** shows two valve-anchoring elements **64** comprising respective clips **65b**, disposed on opposite sides of the distal end of prosthetic valve **42f**. It is to be noted that the scope of the present invention includes prosthetic valves **42f** having any suitable quantity and arrangement of clips **65b**, depending on the technique used and the individual anatomy of the subject.

(413) Typically, during advancement of valve **42f**, valve **42f** is crimped within delivery tube **60**.

(414) FIG. **57B** shows prosthetic valve **42f** being partially deployed from delivery tube **60**, such that clips **65b** are disposed outside of the delivery tube. Clips **65b** are coupled to leaflets **82** of the native valve, holding the leaflets and drawing them close to the primary structural element **130** of prosthetic valve **42f**. For some applications, clips **65b** have a tendency to close, and are held open during delivery of valve **42f** by a force applied to clips **65b** (e.g., by a pull wire). In the absence of the force applied to clips **65b**, clips **65b** close around respective leaflets **82**. For other applications, the opening and closing of clips **65b** are remotely controlled by the operating physician. Typically, clips **65b** may be opened and closed repeatedly until a firm grasping of leaflets **82** is achieved. Clips **65b** are typically configured such that they do not cause substantial damage to leaflets **82**.

(415) FIG. **57C** is a top-view schematic illustration of prosthetic valve **42f** in the partially-deployed state, as described hereinabove with reference to FIG. **57B**. While prosthetic valve **42f** is in a compressed configuration within delivery tube **60**, it has a cross-sectional diameter smaller than that of the lumen defined by prosthetic valve support **40**. Typically, clips **65b** couple parts of leaflets **82** (e.g., central parts, or part of leaflets **82** adjacent one another) to prosthetic valve **42f**, the remaining portions of leaflets **82** remain relatively free. This arrangement typically results in a double-orifice configuration of native valve **23**, whereby native valve **23** (comprising a pair of leaflets **82**) can be considered to be divided into two orifices

86, on opposite sides of prosthetic valve **42f**, each orifice **86** being surrounded by respective pairs of remaining portions of leaflets **82**. It is hypothesized that, in this arrangement, the native valve can continue to function until prosthetic valve **42f** is fully deployed. It is further hypothesized that this double-orifice state provides even greater advantage in applications of the invention where the prosthetic valve is delivered before prosthetic valve support (such as the application of the invention described with reference to FIG. **50**). In such applications in which the prosthetic valve is delivered before support **40**, the interval between delivery and full deployment of the prosthetic valve is typically longer than in applications where prosthetic valve support **40** is delivered and deployed before delivery of the prosthetic valve. Thus, for these applications, the double orifice created by the prosthetic valve facilitates blood flow from the atrium to the ventricle during the implantation procedure.

(416) FIG. **57D** is a side-view schematic illustration of prosthetic valve **42f**, fully deployed in the annulus of the native valve. Valve-anchoring elements **64**, comprising clips **65b**, couple leaflets **82** of the native valve to the primary structural element **130** of prosthetic valve **42**, thereby anchoring the prosthetic valve to the native valve.

(417) It is to be noted that the technique described with reference to FIGS. **57A-D**, in particular the 'double-orifice' configuration described with reference to FIG. **57C**, may be used in combination with other prosthetic valves comprising tissue-engagement elements **62**. In particular, the technique may be used where valve-anchoring elements **64** comprise clips **65** or clip functionality, such as integral anchors **310**, described with reference to FIGS. **54A-D**, and/or twisted anchors **320**, described with reference to FIGS. **55A-E**, and/or pairs **132** loop-shaped valve-anchoring elements **200**, described with reference to FIGS. **56A-D**.

(418) Reference is now made to FIGS. **52**, **53A-C**, **54A-C**, **55A-E**, **56A-D**, and **57A-D**. It is to be noted that the scope of the present invention includes implanting the respective prosthetic valves **42** disclosed herein at native valve **23** prior to implanting support **40**. In such applications of the present invention, anchoring elements **64** enable prosthetic valves **42** described herein to remain coupled to native valve **23** until support **40** is positioned at the annulus of native valve **23**. In such applications, leaflets **82** are brought closer together, temporarily in a manner which forms a double orifice in native valve **23** for blood to pass from the atrium to the ventricle during the implantation procedure (as described hereinabove with reference to FIG. **57C**).

Following the coupling of prosthetic valve **42** to leaflets **82**, support **40** is then positioned around the proximal portion of prosthetic valve **42** in order to facilitate coupling of support **40** to valve **42** and provide the radial force against valve **42** in order to maintain implanting of prosthetic valve **42** at native valve **23**, as described hereinabove. In such applications, support **40** is positioned around the proximal portion of prosthetic valve **42** when the proximal portion of prosthetic valve **42** is crimped and compressed within tube **60** (for ease of positioning support **40** around the proximal portion of valve **42**).

(419) Reference is made to FIGS. **58A-61C**, which are schematic illustrations of prosthetic valve support **40**, embodied as anchoring prosthetic valve supports **4040d**, **4040e**, and **4040f**, comprising tissue-engaging elements **62**, in accordance with respective applications of the invention. In these applications of the invention, tissue-engaging elements **62** comprise support-anchoring elements **66**, which anchor prosthetic valve support **40** to native valve **23**. As described hereinabove, prosthetic valve support **40** is typically used in combination with prosthetic valve **42**. The anchoring of prosthetic valve support **40** to the native valve provides one or more of the following advantages: (1) The delivery apparatus used to deploy the prosthetic valve support (e.g., holding members **46**, described with reference to FIGS. **1C-F**) may be removed following implantation of support **40** and prior to delivering and/or deploying prosthetic valve **42**, thereby providing more space in atrium **26** for the delivery and/or deployment of the prosthetic valve; (2) Implant **30**, comprising prosthetic valve **42** and prosthetic valve support **40**, is anchored more securely to the native valve; and (3) Support-anchoring elements **66** contribute toward the capture of leaflets **82** of the native valve.

(420) For some applications of the invention, it is hypothesized that the anchoring of support **40** to the native valve by support-anchoring elements **66** may be sufficient to anchor implant **30** to the native valve, thereby minimizing or even eliminating the need for supplemental anchoring of implant by valve-securing elements **64**. Therefore, for such applications of the invention, prosthetic valve **42** does not comprise valve-anchoring elements **64**. In some such applications of the invention, leaflets **82** of the native valve are allowed to function, at least in part, following implantation of the prosthetic valve.

(421) Reference is now made to FIGS. **58A-D**, which are schematic illustrations of prosthetic valve support **40** comprising anchoring prosthetic valve support **4040d**, which comprises support-anchoring elements **66** comprising fixed anchors **330**, in accordance with some applications of the invention.

(422) During delivery of support **4040d** to the native valve, support **4040d** is crimped within overtube **44**, as

described hereinabove with reference to support **40** of FIGS. **1B-C**. FIG. **58A** shows prosthetic valve support **4040d** in its expanded configuration, as described hereinabove with reference to support **40** in FIG. **1B**. Typically, prosthetic valve support **4040d** is annular and is shaped to define an outer edge **69** and an inner edge **68**. Outer edge **69** typically defines the diameter of the annular prosthetic valve support, and inner edge **68** typically defines the diameter of the lumen in which prosthetic valve **42** is typically disposed, as described hereinabove. Support-anchoring elements **66** comprising fixed anchors **330**, are typically coupled to inner edge **68**.

(423) In some applications of the invention, fixed anchors **330** comprise coupling-portion **70** configured to engage tissue of the native valve. Coupling-portion **70** is illustrated as an extension of fixed anchors **330** such that fixed anchors **330** assume a generally L-shape. In other applications of the invention, coupling-portion **70** may be disposed differently (e.g., at an angle other than the angle as shown), or may comprise clips **65a** or **65b**, or another means for engaging native valve **23**. In some applications of the invention, fixed anchors **330** do not comprise a coupling-portion.

(424) FIG. **58B** shows prosthetic valve support **4040d**, partially deployed proximal to native valve **23** (i.e., in atrium **26**), as described hereinabove (e.g., with reference to FIG. **1B**). Fixed anchors **330** extend distally from the semi-deployed prosthetic valve support, and are moved distally, between the leaflets of the native valve.

(425) Reference is now made to FIG. **58C**. Fixed anchors **330** move apart as prosthetic valve support **4040d** expands to its fully-deployed, expanded configuration at native valve **23**. That is, as inner edge **68** expands to assume its expanded state, the lumen of support **4040d** expands thereby moving apart anchors **330**. Fixed anchors **330** engage leaflets **82** of the native valve, thereby anchoring prosthetic valve support **4040d** to the native valve. In some applications of the invention, fixed anchors **330** are configured such that native leaflets **82** continue to function, at least in part when support **4040d** is implanted. For example, in some applications, the dimensions and relative positions of fixed anchors **330** do not substantially restrict the movement of leaflets **82**. For example, the total width of each of the fixed anchors **330** elements may be less than 1 mm. Furthermore, in some applications of the invention, the forces exerted on leaflets **82** by the flow of blood are hypothesized to overcome at least some of the force applied to leaflets **82** by the rigidity of fixed anchors **330**, i.e., in order to cause fixed anchors **330** to flex as leaflets **82** move.

(426) FIG. **58D** is a schematic illustration of a transverse atrial cross-section of the fully-deployed prosthetic valve support described with reference to FIG. **58C**. Fixed anchors **330** engage leaflets **82** of the native valve, thereby anchoring prosthetic valve support **4040d** to the native valve. Coupling-portions **70** are disposed on the distal (i.e., ventricular) side of the native valve, and are therefore illustrated in phantom.

(427) Reference is now made to FIGS. **59A-B**, which are schematic illustrations of anchoring prosthetic valve support **4040d** comprising support-anchoring elements **66** comprising fixed anchors **330**, in accordance with some applications of the invention.

(428) Anchoring prosthetic valve support **4040d** is anchored to native valve **23** in a different orientation to that described with reference to FIGS. **58A-D**. FIG. **59A** shows prosthetic valve support fully deployed and anchored to native valve **23**. Fixed anchors **330** extend toward, and engage, commissures **84** of the native valve, thereby anchoring prosthetic valve support **4040d** to the native valve.

(429) FIG. **59B** is a schematic illustration of a transverse atrial cross-section of the fully-deployed prosthetic valve support **4040d** described with reference to FIG. **59A**. Fixed anchors **330** engage commissures **84** of the native valve, holding the leaflets apart at commissures **84** and anchoring prosthetic valve support **4040d** to the native valve. Coupling-portions **70** are disposed on the distal (i.e., ventricular) side of the native valve, and are therefore illustrated in phantom. It is hypothesized that the orientation of prosthetic valve support **4040d** and positioning of fixed anchors **330**, described with reference to FIGS. **59A-B**, interferes less with leaflets **82**, as compared to the orientation and positioning of fixed anchors **330** described with reference to FIGS. **58C-D** (i.e., fixed anchors **330** engaging respective portions of leaflets **82**). This positioning of anchors **330** at commissures **84**, thereby allows the native valve to continue to function, at least in part, until prosthetic valve **42** is deployed.

(430) Reference is made to FIGS. **60A-B** and **61A-C**, which are schematic illustrations of prosthetic valve support **40** comprising prosthetic valve support **4040e** and **4040f**, respectively, in accordance with some applications of the invention. Support-anchoring elements **66** in such applications comprise hinged anchors **340** that are typically coupled to inner edge **68** of support **40**. In some applications of the invention, hinged anchors **340** comprise a coupling-portion **70**, configured to engage tissue of the native valve. Coupling-portion **70** is illustrated as an extension of hinged anchors **340**, thereby forming the hinged anchors into

generally L-shapes. In other applications of the invention, coupling-portion **70** may be disposed differently (e.g., at an angle different to that as shown in FIGS. **60A-B** and **61A-C**), or may comprise clips **65a** or **65b**, or another means for engaging native valve **23**. In some applications of the invention, hinged anchors **340** do not comprise a coupling-portion.

(431) Hinged anchors **340** are typically coupled to prosthetic valve support **40** via a hinge point **72**. Hinge point **72** may comprise a flexible material and/or moving components. For some applications of the invention, hinged anchors **340** rotate freely around hinge point **72** as far as their shape and juxtaposition allows. For some applications of the invention, hinged anchors **340** are biased to reside in a particular configuration. For example, hinged anchors **340** and/or hinge point **72** and/or prosthetic valve support **40** may comprise a shape-memory material (e.g., nitinol) or a spring mechanism, configured to push hinged anchors **340** radially outward.

(432) The use of hinge points **72** for coupling support-anchoring elements **66** to prosthetic valve support **40** is hypothesized to provide one or more of the following advantages: (1) Improving compressibility of prosthetic valve support **40**, for transcatheter delivery. (2) Improving movement of native leaflets **82** following deployment of prosthetic valve support **40** to the native valve. (3) Increasing adjustability of the dimensions and configuration of support-anchoring elements **66**.

(433) Reference is now made to FIGS. **60A-B**, which are schematic illustrations of prosthetic valve support **40** comprising hinged prosthetic valve support **4040e**, comprising hinged anchors **340**, in accordance with some applications of the invention. FIG. **60A** shows prosthetic valve support **4040e** in a fully-expanded configuration. Prosthetic valve **4040e** is configured such that hinged anchors **340** are biased to extend radially outward.

(434) FIG. **60B** shows prosthetic valve support **4040e** fully deployed at native valve **23**. As described with reference to FIGS. **58C-D** and **59A-B**, support-anchoring elements **66** may be positioned to engage commissures **84** (FIGS. **59A-B**) and/or leaflets **82** of the native valve (FIGS. **58C-D**). In the application of the invention illustrated in FIG. **60B**, prosthetic valve support **4040e** and hinged anchors **340** are configured such that the hinged anchors extend radially to engage the commissures **84** of the native valve. For other applications, hinged anchors **340** are freely rotatable, and are coupled to leaflets **82** such that support **40** is anchored to the native valve whilst allowing leaflets **82** to move.

(435) Reference is made to FIGS. **61A-C**, which are schematic illustrations of prosthetic valve support **40** comprising free-hinged prosthetic valve support **40f**, comprising hinged anchors **340** comprising clamping-hinged-anchors **350**, in accordance with some applications of the invention.

(436) FIG. **61A** shows prosthetic valve support **4040f**, comprising hinged anchors **350**, in a fully-expanded configuration and a resting state thereof. Clamping-hinged-anchors **350** are coupled to prosthetic valve support **4040f** via hinge point **72** and are typically free to pivot around the hinge point as far as their shape and juxtaposition allows. Coupling-portion **70** is shown in an unconstrained clamped configuration, in which it is typically configured to extend from structural component **71** of clamping-hinged-anchor **350**, at an acute angle (e.g., less than 80 degrees, less than 45 degrees, or less than 20 degrees). In some applications of the invention, coupling-portion **70** may be configured to extend at less than 1 degree, i.e., to touch the structural component **71** of clamping-hinged-anchor **350**. Clamping-hinged-anchors **350** typically comprise a shape-memory material (e.g., nitinol), such that they are compressible into a compressed (e.g., crimped) configuration for delivery, and are deformable and expandable at the site of implantation.

(437) FIG. **61B** shows clamping-hinged anchors **350** of prosthetic valve support **4040f**, in a compressed configuration, e.g., for delivery toward the native valve within overtube **44** (e.g., as described hereinabove with reference to support **40** in FIG. **1B**). It is to be noted that overtube **44** is not shown for clarity of illustration. Clamping-hinged-anchors **350** are disposed distally to other parts of prosthetic valve support **4040f**. Prior to delivery, coupling-portions **70** are typically in an unclamped configuration, in which they extend further distally from prosthetic valve support **4040f** and from structural component **71** of clamping-hinged-anchor **350**. During deployment of prosthetic valve support **4040f** from overtube **44**, clamping-hinged-anchors **350** are extended from within overtube **44** (coupling-portion **70** first followed by structural component **71**) and between leaflets **82** of native valve **23**. As clamping-hinged-anchors **350** are fully exposed from within overtube **44**, they move toward their clamped configuration, and are allowed to assume their resting state (as shown in FIG. **61A**) in which coupling-portion **70** moves toward structural component **71** in order to clamp a portion of leaflet **82** therebetween and to thereby anchor prosthetic valve support **4040f** to the native valve.

(438) FIG. **61C** shows prosthetic valve support **4040f** fully deployed at native valve **23**. Coupling-portions **70**

clamp leaflets **82** against respective structural components **71** of clamping-hinged-anchors **350**, as described hereinabove. Thus, clamping-hinged-anchors **350** function as clips **65c**. As described hereinabove, clamping-hinged-anchors **350** are typically able to rotate freely about hinge point **72** as far as their shape and juxtaposition allows. Leaflets **82** are thereby able to move proximally and distally (i.e., atrially and ventricularly), as illustrated by the upper and lower panels of FIG. **61C**. Clamping-hinged-anchors **350** thereby allow native valve **23** to continue to function until prosthetic valve **42** is deployed, as described hereinabove.

(439) For some applications of the invention, prosthetic valve support **4040f** is configured such that clamping hinged anchors **350** are biased to extend radially inward (i.e., toward each other). This configuration is illustrated by the upper panel of FIG. **61C**. In such applications of the invention, leaflets **82** of the native valve are held together, forming a double-orifice configuration, as described herein (e.g., with reference to FIG. **57C**). Clamping hinged anchors **350** thereby allow native valve **23** to continue to function, at least in part, until prosthetic valve **42** is deployed.

(440) Reference is again made to FIGS. **58A-D**, **59A-B**, **60A-B** and **61A-C**. It is to be noted that supports **40** described herein comprise two support-anchoring elements **66** by way of illustration and not limitation. That is, the scope of the present invention includes the supports **40** comprising any suitable number and configuration of anchoring elements **66**. For example, valve support **40** may comprise four support-anchoring elements **66** configured such that a pair of elements **66** are anchored to commissures **84** and a pair of elements **66** are anchored to leaflets **82** of the native valve.

(441) Reference is now made to FIGS. **1**, **49-61**. It is to be noted that applications of tissue-engaging elements **62** described herein are interchangeable as valve-anchoring elements **64**, and/or as support-anchoring elements **66**. For example, pairs **132** of loop-shaped anchoring elements **200**, described with reference to FIGS. **56A-D** as valve-anchoring elements **64**, may be coupled to prosthetic valve support **40** to the native valve (i.e., so as to function as support-anchoring elements **66**). Similarly, clamping-hinged-anchors-**350**, for example, described with reference to FIGS. **61A-C** as support-anchoring elements **66**, may be employed to couple prosthetic valve **42** to the native valve (i.e., and function as valve-anchoring elements **64**).

(442) Reference is made to FIGS. **62A-D**, which are schematic illustrations of delivery apparatus **4138a**, used to deploy a medical device **150**, in accordance with some applications of the invention. As shown in FIG. **62A**, delivery apparatus **4138a** comprises a delivery tube **154** and a pushing member **140a**. Pushing member **140a** comprises a support **4142a** and one or more coupling tabs **4146**, extending from the support. In the application of the invention shown in FIG. **62A**, support **4142a** comprises a core **144**, and coupling tabs **4146** extend radially from the core. In some applications of the invention, support **4142a** is shaped to define a plate **4148** at the proximal end of support **4142a**. The dimensions and relative positions of support **4142a**, tabs **4146**, and plate **4148** may be adjusted for the specific medical device **150** to be deployed using delivery apparatus **4138a**.

(443) In the application of the invention described with respect to FIGS. **62A-D**, medical device **150** comprises prosthetic valve **42** (e.g., any one of prosthetic valves **42** described herein).

(444) FIG. **62B** shows prosthetic valve **42** in a compressed (i.e., crimped) configuration for delivery and deployment using delivery apparatus **4138a**. As described hereinabove, prosthetic valve **42** typically has a lattice structure that defines a plurality of shapes, and voids **4126**, and has elastic memory. Prosthetic valve **42** is shown in a compressed (e.g., crimped) configuration, and as shown in the enlarged image, a proximal portion of valve **42** is disposed around core **144** of pushing member **140a** such that each of coupling tabs **4146** is disposed within a respective void **4126** defined by the lattice structure of the prosthetic valve.

(445) Prosthetic valve **42** and pushing member **140a** are disposed within the lumen of delivery tube **154**. Delivery tube **154** restricts expansion of prosthetic valve **42**, thereby holding the proximal portion of prosthetic valve **42** around core **144** of pushing member **140a**, in the configuration described herein. Coupling tabs **4146** restrict movement of prosthetic valve **42** with respect to pushing member **140a**. Delivery tube **154** therefore facilitates coupling of prosthetic valve **42** to pushing member **140a** via coupling tabs **4146**. In applications of the invention where pushing member **140a** is shaped to define plate **4148**, the plate typically further facilitates this coupling by restricting proximal movement of prosthetic valve **42** with respect to the pushing member (e.g., by functioning as a cap).

(446) FIG. **62C** shows prosthetic valve **42** partially deployed from delivery tube **154**. Pushing member **140a**, and, thereby, prosthetic valve **42**, are moved distally through delivery tube **154**.

(447) A control tube **4152** is coupled at a distal end thereof to pushing member **140a** (e.g., control tube **4152** is coupled to support **4142a**). Control tube **4152** is shaped so as to define a lumen through which a guidewire

tube **4153** passes, and control tube **4152** is slidable with respect to and along guidewire tube **4153**. Guidewire tube **4153** houses guidewire **45** described hereinabove. Control tube **4152** is slidably disposed within a lumen of an overtube **4155**.

(448) Reference is again made to FIG. **62C**. Pushing member **140a** is pushed distally by pushing control tube **4152** along guidewire tube **4153** such that pushing member **140a** pushes prosthetic valve **42**. As pushing member **140a** pushes valve **42** distally, distal portions of the prosthetic valve expand toward the expanded configuration as they become exposed from delivery tube **154**, while the proximal end of valve **42** remains coupled to pushing member **140a** via tabs **4146**.

(449) FIG. **62D** shows prosthetic valve **42** having been fully deployed from within delivery tube **154**. Pushing member **140a** and prosthetic valve **42** are moved further distally through delivery tube **154** by control tube **4152**. When the proximal portion of prosthetic valve **42** emerges from within delivery tube **154**, expansion of the proximal portion of prosthetic valve **42** uncouples the prosthetic valve from coupling tabs **4146** by expanding voids **4126** away from tabs **4146**, thereby releasing the prosthetic valve from pushing member **140a**.

(450) Should it be necessary and/or desirable during the procedure, until medical device **150** (e.g., prosthetic valve **42**) is released from pushing member **140a** (i.e., while the proximal portion of medical device **150** is crimped within delivery tube **154**), the remaining portions of medical device **150** may be drawn back into delivery tube **154** (e.g., for repositioning or withdrawal of the medical device).

(451) Reference is now made to FIGS. **54A-D** and **62A-D**. It is to be noted that for some applications, withdrawing of a portion of prosthetic valve **42** within delivery tube **154** facilitates deforming of integral anchors **310** toward their constrained, further-expanded open configuration. This occurs when a distal end of tube **154** pushes against pivot joint **4074** between anchor **310** and structural element **130** as the portion of prosthetic valve **42** is withdrawn.

(452) In the application of the invention described with reference to FIGS. **62A-D**, voids **4126** are defined by the lattice structure of medical device **150** (i.e., prosthetic valve **42**). In other applications of the invention, voids in medical device **150** may be defined by other structural features of the medical device and not necessarily by a lattice structure. Typically, as described herein, coupling tabs **4146** couple medical device **150** to pushing member **140a** at a proximal portion of the medical device, thereby retaining coupling of the medical device to pushing member **140a** until the medical device is fully deployed from delivery tube **154**. It is to be noted that the scope of the present invention includes tabs which alternatively or additionally couple medical device **150** to pushing member **140a** at portions of the medical device other than the proximal portion thereof.

(453) It is hypothesized that utilization of pushing member **140a**, comprising coupling tabs **4146** that are disposable in voids **4126** defined by an expandable medical device **150**, (1) reduces the overall length of the apparatus (i.e., the combined lengths of medical device **150** and delivery tube **154**) being advanced into the subject, and/or (2) reduces the requirement for additional components of medical device **150** which function as coupling structures of medical device **150**. That is, medical device **150** has an integral coupling system by which voids **4126** are coupled to tabs **4146**. The applications of the invention described with reference to FIGS. **62A-D** may be used in combination with applications of the invention described hereinabove, as well as for the delivery of other expandable medical devices.

(454) Reference is again made to FIGS. **1A-H**, **9A-E**, and **62A-D**. It is to be noted that delivery tube **154** of FIGS. **9A-E** and **62A-D** may be similar to, may act as, and/or may comprise, overtube **44** and/or delivery tube **60** of FIGS. **1A-H**.

(455) Reference is made to FIGS. **63A-B**, which are schematic illustrations of delivery apparatus **4138b**, used to deploy an expandable medical device **150**, in accordance with some applications of the invention.

Reference is now made to FIG. **63A**. Delivery apparatus **4138b** comprises delivery tube **154** and a pushing member **140b**, which comprises a support **4142b**. In this application of the invention, pushing member **140b** is shaped to define a plurality of troughs **222**. Typically, troughs **222** run along the surface of pushing member **140b**, from one end of the pushing member (e.g., a distal end) to a point along the length of the pushing member. Typically, troughs **222** are shaped so as to define a respective widened part **224** (e.g., at a proximal end of the trough) or is configured to open into a larger widened part **224** (as shown). In the application of the invention described with reference to FIGS. **63A-B**, widened part **224** comprises a single circumferential groove surrounding the circumference of pushing member **140b**, into which all troughs **222** open.

Alternatively, each trough **222** may be shaped so as to define a respective widened part.

(456) Reference is now made to FIG. **63B**. Medical device **150**, embodied in this application of the invention

as expandable prosthetic valve **42**, comprises a plurality of coupling tabs **220**. Coupling tabs **220** are configured to be disposable in respective troughs **222** of pushing member **140b**, such that troughs **222** restrict distal movement of medical device **150**. In the application of the invention described with reference to FIGS. **63A-B**, coupling tabs **220** are T-shaped, so as to be disposable in respective troughs **222** and in the circumferential groove that forms widened part **224**. The disposition of coupling tabs **220** in troughs **222** couples prosthetic valve **42** to pushing member **140b**. Coupling tabs **220**, troughs **222**, and widened part **224** may assume any shape that allows such coupling.

(457) Prior to delivery, prosthetic valve **42** is compressed (e.g., crimped) such that all coupling tabs **220** are disposed in respective troughs **222**. Prosthetic valve **42** and pushing member **140b** are disposed within the lumen of delivery tube **154**. Delivery tube **154** restricts expansion of prosthetic valve **42**, thereby holding coupling tabs **220** in troughs **222**, in the configuration described herein. Coupling tabs **220** restrict movement of prosthetic valve **42** with respect to pushing member **140b**. Delivery tube **154** therefore facilitates coupling of prosthetic valve **42** to pushing member **140b** via coupling tabs **220**. As described with reference to FIGS. **62C-D**, prosthetic valve **42** (or another medical device **150**) is advanced to the site of implantation, where pushing member **140b** pushes prosthetic valve **42** out of delivery tube **154**. When coupling tabs **220** emerge from delivery tube **154**, expansion of prosthetic valve **42** releases coupling tabs **220** from troughs **222**, thereby releasing prosthetic valve **42** from the pushing member.

(458) Reference is made to FIGS. **64A-C**, which are schematic illustrations of a lock **170** for facilitating delivery of a medical device, in accordance with some applications of the invention.

(459) Reference is now made to FIG. **64A**. Lock **170** comprises a tubular member **4172** and a plug **174**. Plug **174** is dimensioned such that it is disposable in, and slidable through the lumen of tubular member **4172**. Typically, plug **174** is dimensioned so as to fit tightly in the lumen of tubular member **4172** in a manner in which an outer surface of plug **174** is disposed very close to an inner surface of tubular member **4172**, i.e., such that little space exists between the plug and the tubular member. Plug **174** is shaped to define a trough **176**. Trough **176** typically runs along the surface of the plug from one end of the plug to a point along the length of the plug. Typically, trough **176** is shaped so as to define a widened part **178**.

(460) A coupling lead **4180** (e.g., a coupling wire) is disposable in trough **176**, and is reversibly couplable thereto (and thereby to lock **170**), as described hereinbelow. As is described hereinbelow, coupling lead **4180** is coupled to a medical device **150** and facilitates (1) coupling of medical device **150** to a delivery mechanism during delivery of the medical device and (2) decoupling of medical device **150** from the delivery mechanism following implantation of device **150**. Typically, a region at an end of coupling lead **4180** is shaped to define a stopper **182**, which is thicker than other regions of the coupling lead, and is configured to be disposable in widened part **178** of trough **176**, typically when tubular member **4172** surrounds plug **174**. Alternatively, stopper **182** may comprise a distinct component that is coupled to coupling lead **4180**. Trough **176**, coupling lead **4180**, widened part **178**, and stopper **182** are dimensioned such that when the coupling lead and the stopper are disposed in trough **176**, plug **174** remains disposable in, and slidable through, tubular member **4172**. FIG. **64A** shows trough **176** disposed within the lumen of tubular member **4172** such that lock **170** assumes a locking configuration. In this locking configuration, coupling lead **4180** is held in the trough by the inner surface of the tubular member. Tubular member **4172** therefore facilitates coupling of coupling lead **4180** to plug **174**.

(461) Reference is now made to FIG. **64B**. Plug **174** is slid distally through tubular member **4172**, such that lock **170** is in an open configuration. Typically, plug **174** is moved using control wire **175**. In this open configuration, trough **176** and stopper **182** are exposed from the tubular member (i.e., are outside the tubular member). Coupling lead **4180** and stopper **182** are shown in FIG. **64B** as being disposed within trough **176**, by way of illustration and not limitation, as a temporary configuration prior to disengaging wire **4180** and stopper **182** from trough **176** (disengaging of wire **4180** and stopper **182** are described hereinbelow).

(462) Reference is now made to FIG. **64C**. In the open configuration, coupling lead **4180** (and stopper **182**) are allowed to leave trough **176**. Typically, coupling lead **4180** is released from trough **176** by moving the former with respect to the latter (e.g., by applying a moving force to either coupling lead **4180**, directly or indirectly, or by applying a moving force to plug **174** away from wire **4180**). In some applications of the invention, at least a portion of coupling lead **4180** is configured such that it automatically moves out of the trough upon being exposed from the tubular member (e.g., the coupling lead comprises a shape-memory material such as nitinol). In some applications of the invention, trough **176** and widened part **178** are shaped to facilitate release of coupling lead **4180** from trough **176**. For example, a distal edge of widened part **178** may be sloped such that distal movement of coupling lead **4180** facilitates the release.

(463) Reference is made to FIGS. 65A-B, which are schematic illustrations of sequential steps in lock 170 being used to facilitate the delivery of a medical device 150, the medical device embodied by prosthetic valve support 40, in accordance with some applications of the invention. FIG. 65A shows a coupling lead 4180 (e.g., a coupling wire) extending from a holding member 4046 (e.g., a holding member 4046a) to another holding member 4046 (e.g., a holding member 4046b). For some applications, holding members 4046 comprise holding members 46, described hereinabove with reference to FIGS. 1C-F. Coupling lead 4180 is coupled to medical device 150. For example, coupling lead 4180 may loop around a part of medical device 150. Alternatively, coupling lead 4180 may weave through at least a portion of medical device 150, as shown in FIG. 65A. At least one holding member 4046 (e.g., holding member 4046a) comprises lock 170 at a distal end of holding member 4046. Holding member 4046 is shaped to define a lumen and defines tubular member 4172 of lock 170. Holding member 4046a is reversibly coupled to a first portion of coupling lead 4180 (e.g., an end portion of wire 4180, as shown) via lock 170. The remaining portions of wire 4180 are threaded through support 40, as shown, and extend through a lumen, of holding member 4046b, as shown.

Alternatively, a second portion of coupling lead 4180 is coupled to a portion of holding member 4046b.

(464) In the application of the invention illustrated in FIG. 65A, two holding members 4046a are coupled to coupling lead 4180 via respective locks 170, and one holding member 4046b is coupled to coupling lead 4180 without a lock 170. That is, a first holding member 4046a holds a first end of wire 4180, and a second holding member 4046a holds a second end of wire 4180. Portions of wire 4180 extending from the first and second ends thereof are threaded through respective portions of support 40 and extend through a lumen of holding member 4046b, as shown. Alternatively, each holding member 4046a is coupled to respective first ends of respective first and second coupling leads 4180. Respective portions of the first and second coupling leads 4180 extending from the respective first ends thereof are threaded through respective portions of support 40, and extend through a lumen of holding member 4046b. Alternatively, respective second portions of the first and second coupling leads 4180 are coupled to a portion of holding member 4046b.

(465) Reference is now made to FIG. 65B. At the site of implantation, lock 170 is moved into its open configuration, thereby releasing coupling lead 4180 from holding member 4046a. Coupling lead 4180 is then decoupled (e.g., unthreaded or unlooped) from medical device 150 (e.g., by pulling on a portion of coupling lead 4180). In some applications of the invention, holding member 4046b is slidably coupled to coupling lead 4180, and the decoupling of coupling lead 4180 from medical device 150 is performed by withdrawing coupling lead 4180 proximally, through holding member 4046b. In other applications of the invention, holding member 4046b is substantially attached to coupling lead 4180, and the decoupling of coupling lead 4180 from medical device 150 is performed by withdrawing holding members 4046 proximally following the decoupling of holding members 4042a from coupling lead 4180. Medical device 150 is typically left at the site of implantation following the decoupling.

(466) Reference is made to FIGS. 66A-B, which are schematic illustrations of sequential steps in lock 170 facilitating the delivery of a medical device 150, the medical device embodied by prosthetic valve support 40, in accordance with some applications of the invention. Reference is now made to FIG. 66A. In this application of the invention, both ends of each coupling lead 4180 are coupled to one respective holding member 4046. Each one of holding members 4046 comprises a respective lock 170. A respective coupling lead 4180 is coupled to each holding member 4046. For each holding member 4046, one end of coupling lead 4180 (i.e., the end of wire 4180 comprising stopper 182) is reversibly coupled to the holding member via lock 170, as described hereinabove with reference to FIG. 65A. The other end of the coupling lead is coupled to the holding member in a substantially fixed manner (e.g., attached to the holding member, or attached to a second part of lock, such as a second part of plug 174). In such a manner, each coupling lead 4180 forms a loop around a part of medical device 150 (as shown in the enlarged image of FIG. 66A), thereby coupling each coupling lead 4180, and thereby coupling each holding member 4046, to medical device 150.

(467) Reference is now made to FIG. 66B. At the site of implantation, each lock 170 is moved into its open configuration (described hereinabove), thereby releasing one end of each coupling lead 4180 (i.e., the end of wire 4180 comprising stopper 182), and thereby opening the loop formed by coupling lead 4180. Each coupling lead 4180 is withdrawn proximally (i.e., by pulling proximally on each holding member 4046, as shown), thereby uncoupling (e.g., unthreading or unlooping) coupling lead 4180 from medical device 150.

(468) For some applications of the present invention, the other end of coupling lead 4180 is attached to a portion of holding member 4046. In such applications, withdrawal of coupling lead 4180 typically comprises withdrawing holding member 4046 proximally.

(469) For some applications of the invention, the other end of coupling lead 4180 is attached to a portion

(e.g., an outer surface of) of plug **174**. For such applications, withdrawal of coupling lead **4180** may comprise withdrawing the plug into tubular member **4172** (i.e., holding member **4046**).

(470) In either application, following the decoupling of holding members **4046** and wires **4180** from device **150**, medical device **150** is typically left at the site of implantation.

(471) Reference is made to FIGS. **67A-B**, which are schematic illustrations of sequential steps in lock **170** facilitating the delivery of a medical device **150**, the medical device embodied by prosthetic valve support **40**, in accordance with some applications of the invention. Reference is now made to FIG. **67A**. One end of coupling lead **4180** (i.e., the end of wire **4180** comprising stopper **182**) is reversibly coupled to holding member **4046** via lock **170**, as described hereinabove with reference to FIG. **65A**. The other end of the coupling lead is coupled to medical device **150** in a substantially fixed manner. Typically, but not necessarily, coupling lead **4180** is short in comparison to the coupling lead described with reference to FIGS. **65A-B** and **66A-B**.

(472) Reference is now made to FIG. **67B**. At the site of implantation, lock **170** is moved into its open configuration, releasing one end of coupling lead **4180** (i.e., the end of wire **4180** comprising stopper **182**). Holding members **4046** are withdrawn proximally, releasing coupling lead **4180** and medical device **150** from holding members **4046**. Following the decoupling of holding members **4046** from device **150**, medical device **150** is typically left at the site of implantation. In this application of the invention, coupling leads **4180** typically remain coupled to medical device **150**.

(473) The applications of the invention described with reference to FIGS. **64A-C**, **65A-B**, **66A-B**, and **67A-B** may be used in combination with each other, and/or in combination with applications of the invention described herein, including those comprising delivery and/or deployment of prosthetic valve **42**, prosthetic valve support **40**, and/or medical device **150**. These applications of the invention may also be used to deliver and/or deploy medical devices not described herein.

(474) Reference is made to FIGS. **68A-B** and **69A-E**, which are schematic illustrations of prosthetic valve support **40** comprising a retrievability functionality, in accordance with some applications of the invention.

(475) FIGS. **68A-B** show prosthetic valve support **40** is coupled to one or more holding members **4046** via one or more coupling retrieving wires **4180**, in accordance with respective applications of the invention. Typically, prosthetic valve support **40** is coupled to 2 or more (e.g., 3) holding members **4046** via 2 or more (e.g., 3) coupling leads **4180**. Typically, the ends of each coupling lead **4180** are disposed within holding members **4046**, or more proximally (e.g., outside a body of the subject). A portion (e.g., a middle portion) of each coupling lead is disposed through respective portions of prosthetic valve support **40** (e.g., threaded through support **40**), thereby coupling the prosthetic valve support to holding members **4046**. Since (1) the respective ends of coupling leads **4180** are coupled to or extend beyond a proximal end of holding members **4046**, and (2) respective middle portions of wires **4180** are threaded through respective portions of support **40**, each coupling lead forms a loop. Typically, this middle portion of each coupling lead is disposed through a peripheral region (e.g., close to an outer edge **69**) of the prosthetic valve support.

(476) FIGS. **68A-B** show two configurations of coupling leads **4180**, coupling holding members **4046** to prosthetic valve support **40**, in accordance with respective applications of the invention. For these applications of the invention, three coupling leads **4180** (e.g., coupling wires) are used, and are illustrated as coupling leads **4180a**, **4180b**, and **4180c**, for clarity. Prosthetic valve support **40** is typically deployed in the atrium **26** of the subject, e.g., as described with reference to FIGS. **1B-D**.

(477) FIG. **68A** shows the middle portions of wires **4180a-c** forming respective pulling loops (e.g., closed loops) around and threaded through support **40**. That is, a respective pulling force is applied annularly to the entire support **40** by each one of wires **4180a-c**.

(478) FIG. **68B** shows the middle portions of wires **4180a-c** threaded through portions of support **40** in a manner in which the respective middle portions of wires **4180a-c** collectively form a pulling loop. That is, a respective pulling force is applied to respective portions of support **40** (i.e., to respective thirds of support **40**) corresponding to the portions of support **40** through which the respective middle portions of wires **4180a-c** are threaded.

(479) Reference is now made to FIGS. **69A-E**, which are schematic illustrations of sequential steps in the retrieval of prosthetic valve support **40** described hereinabove with reference to FIGS. **68A-B**, in accordance with some applications of the invention. Should it be required (e.g., for repositioning of the prosthetic valve support, or abortion of the procedure), the deployed prosthetic valve support may be retrieved into overtube **44**. FIG. **69A** shows prosthetic valve support **40** in a fully deployed configuration, still coupled to holding members **4046** via coupling leads **4180**. In this configuration, prosthetic valve support **40** is typically flat, but

may have a different shape (e.g., a saddle shape).

(480) Reference is now made to FIG. 69B. A user moves coupling leads **4180** proximally with respect to holding members **4046** and prosthetic valve support **40** (e.g., the user pulls coupling leads **4180** through holding members **4046**). Due to the configuration of coupling leads **4180** (as described with reference to FIGS. 68A-B) the portion of each coupling lead that passes through the prosthetic valve support becomes shortened, thereby reducing a perimeter of the peripheral region (e.g. of outer edge **69**) of prosthetic valve support **40**, through which coupling leads **4180** are disposed.

(481) FIG. 69C shows the perimeter of outer edge **69** of prosthetic valve support **40** having been reduced further, thereby deforming prosthetic valve support toward a cylindrical shape, with outer edge **69** defining a proximal end of the further-reduced support **40**. FIG. 69D shows the diameter of outer edge **69** having been reduced, such that the proximal end comprising outer edge **69** of prosthetic valve support **40** is slidable and disposable in overtube **44**. As the user pulls coupling leads **4180**, he/she pushes overtube **44** distally over successive portions of support **40**. FIG. 69E shows holding members **4046** and prosthetic valve support **40** being moved proximally with respect to overtube **44** (e.g., the prosthetic valve support is moved proximally and/or the overtube is moved distally). As overtube **44** slides over prosthetic valve support **40**, it compresses more distal portions of the prosthetic valve support, until the prosthetic valve support has been entirely retrieved into overtube **44**. Prosthetic valve support **40** may be redeployed or may be removed from the subject. Retrieval and/or deployment may be halted and/or reversed at any stage in the process described with reference to FIGS. 69A-E.

(482) The applications of the invention described with reference to FIGS. 68A-B and 69A-E may be used in combination with each other, and/or in combination with applications of the invention described herein, including those which include prosthetic valve support **40**.

(483) Reference is made to FIGS. 70A-C, which are schematic illustrations of prosthetic valve **42**, comprising tissue-engagement elements **62**, in accordance with some applications of the invention. In these applications of the invention, tissue-engagement elements **62** comprise valve-anchoring elements **64**, disposed at the distal end of prosthetic valve **42**. Each valve-anchoring element **64** may comprise a loop-shaped valve-anchoring element **200** or a stick-shaped valve-anchoring element **202**. Loop-shaped valve-anchoring elements **200** have a larger surface area with which to grasp leaflets **82**, and are hypothesized to be facilitate more atraumatic advancement with respect to tissue than are stick-shaped valve-anchoring elements **202**. Stick-shaped valve-anchoring elements **202** are hypothesized to more easily, be insertable between chordae tendineae **80** (e.g., comb between chordae tendineae), than are loop-shaped valve-anchoring elements **200**.

(484) Prosthetic valve **42** may be coupled to one or more valve-anchoring elements **64**, comprising loop-shaped valve-anchoring elements **200**, stick-shaped valve-anchoring elements **202**, or a combination thereof, in order to facilitate deployment of prosthetic valve **42** and coupling of the prosthetic valve to native heart valve **23**. For example, stick-shaped valve-anchoring elements **202** may be used in areas of heart valve **23** in which chordae tendineae **80** are disposed more densely, whereas loop-shaped valve-anchoring elements **200** may be used to capture relatively exposed regions of leaflets **82**. Loop-shaped valve-anchoring elements **200** and stick-shaped valve-anchoring elements **202** are illustrated here as fixed anchors. In some applications of the invention, elements **200** and **202** may be alternatively or additionally used as hinged anchors (e.g., hinged anchors **340**) and/or clamping hinged anchors (e.g., clamping hinged anchors **350**), as described hereinabove.

(485) Reference is now made to FIG. 71, which is a schematic illustration of prosthetic valve **42**, for placing inside native heart valve **23** of the patient, in accordance with some applications of the present invention. For this application of the invention, native valve **23** includes mitral valve **24**. The primary structural element **130** of the prosthetic valve has a diameter d , and a corresponding cross-sectional area. The annulus of the native valve, which is typically saddle-shaped, defines an area $A1$, as shown. For some applications, area $A1$ is measured, e.g., using a measuring ring prior to deployment of valve **42**. Taking this measuring into account, a suitably-sized prosthetic valve is chosen to be placed in the annulus, in a manner in which the cross-sectional area of the prosthetic valve in its deployed state is less than 90% (e.g., less than 80%, or less than 60%) of area $A1$.

(486) For some applications, diameter d of the prosthetic valve is less than 25 mm, e.g., less than 20 mm, and/or more than 15 mm, e.g., 15-25 mm. For some applications, placing a prosthetic valve inside the native valve, with the dimensions of the native valve annulus and the prosthetic valve as described, facilitates sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve. In such applications, prosthetic valve **42** is implanted directly within native valve **23** (i.e., without support **40**).

(487) For some applications, a prosthetic valve support **40**, that is shaped to define a lumen, is placed against the annulus of native valve **23** (e.g., as described with reference to FIGS. 1A-H). The lumen of support **40** has a cross-sectional area **A2** that is less than 90% (e.g., less than 80%, or less than 60%) of area **A1** of native valve **23**. As described hereinabove, prosthetic valve **42** is typically coupled to prosthetic valve support **40** and, thereby, to native valve **23**, at least in part by expansion of the prosthetic valve such that primary structural element **130** exerts a radial force against inner edge **68** of prosthetic valve support **40**. The cross-sectional area defined by the primary structural element **130** of the prosthetic valve, upon expansion of the prosthetic valve, is limited by the cross-sectional area **A2** of the lumen of the prosthetic valve support **40** to less than 90% (e.g., less than 80%, or less than 60%) of area **A1** of native valve **23**. For some applications, placing a prosthetic valve support **40** at the native valve, as described, facilitates sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve.

(488) Typically, placing a prosthetic valve inside the native valve with the dimensions of the native valve annulus, the prosthetic valve **42**, and/or valve support **40** as described in the above paragraphs, facilitates sealing of the prosthetic valve with respect to the native valve. For some applications, the sealing is facilitated by the native leaflets being pushed against, and closing against, the outer surface of the frame of the valve during systole, in a similar manner to the manner in which native valve leaflets coapt during systole, in a healthy mitral valve.

(489) Typically, as the diameter **d** of the prosthetic valve is increased, the proportion of the native leaflets that is pushed against the outer surface of the valve during systole is increased, thereby enhancing the sealing of the native leaflets with respect to the frame of the prosthetic valve. However, beyond a given diameter, as the diameter **d** of the prosthetic valve is increased, the native valve leaflets are pushed apart at the commissures, thereby causing retrograde leakage of blood through the commissures. Therefore, in accordance with some applications of the present invention, prosthetic valve **42**, and/or valve support **40** are chosen such that the cross-sectional area of the prosthetic valve (when expanded inside the valve support) is less than 90% (e.g., less than 80%, or less than 60%) of area **A1** of native valve **23**. Thus, the valve support facilitates additional sealing of the prosthetic valve with respect to the native valve, by the native valve leaflets closing around the outer surface of the prosthetic valve, while not causing retrograde leakage of blood through the commissures.

(490) For some applications, in order to facilitate the sealing of the native valve around the outer surface of the prosthetic valve, a material is placed on the outer surface of the prosthetic valve in order to provide a sealing interface between the prosthetic valve and the native valve. For example, a smooth material that prevents tissue growth (e.g., polytetrafluoroethylene (PTFE), and/or pericardium) may be placed on the outer surface of the prosthetic valve. Alternatively or additionally, a material that facilitates tissue growth (such as polyethylene terephthalate; PET) may be placed on the outer surface of the prosthetic valve, in order to (a) act as a sealing interface between the native valve and the prosthetic valve, and (b) facilitate tissue growth around the prosthetic valve to facilitate anchoring and/or sealing of the prosthetic valve.

(491) Reference is made to FIGS. 72A-D, which are schematic illustrations of an implant **2030**, comprising a prosthetic valve support **2040**, and a prosthetic valve **2042**, in accordance with some applications of the invention. Implant **2030** is configured to be implanted at a native heart valve of a subject, such as the mitral valve **2024** of the subject.

(492) FIG. 72A shows support **2040** and prosthetic valve **2042** of implant **2030** in respective fully uncompressed configurations thereof. Support **2040** comprises an upstream support portion **2041**, which is shaped to define an opening **2045**, and configured to be placed against an upstream side of the native valve of the subject (e.g., against an atrial side of the mitral valve of the subject, such as against the annulus of the mitral valve of the subject). Typically, upstream support portion **2041** is configured to be placed against the upstream side of the native valve such that the entire of opening **2045** is disposed above (i.e., upstream and within a periphery defined by) the orifice of the native valve. Typically, upstream support portion **2041** is configured and/or selected such that opening **2045** has a greatest diameter that is less than 90% (e.g., less than 80%, e.g., as less than 60%, such as less than 50%) of a greatest diameter of the orifice of the native valve. Typically, upstream support portion **2041** is generally annular (e.g., portion **2041** and opening **2045** are generally elliptical, circular, and/or oval).

(493) In the fully uncompressed configuration thereof, upstream support portion **2041** typically has an outer perimeter **2069** of length between 125 and 190 mm (e.g., between 140 and 170 mm, such as between 140 and 150 mm), and an inner perimeter **2068** (that defines opening **2045**) of length between 62 and 105 mm (e.g., between 65 and 80 mm, such as between 75 and 80 mm). When upstream support portion **2041** is annular, the

upstream support portion, in the fully uncompressed configuration thereof, typically has an outer diameter **d10** (e.g., a greatest outer diameter) of between 40 and 80 mm (e.g., between 40 and 70 mm, such as between 40 and 60 mm), and an inner diameter **d11** (e.g., a greatest inner diameter) of between 20 and 35 mm (e.g., between 23 and 32 mm, such as between 25 and 30 mm). That is, opening **2045** typically has a diameter of between 20 and 35 mm (e.g., between 23 and 32 mm, such as between 25 and 30 mm). Typically, outer perimeter **2069** has a length that is at least 10% (e.g., at least 50%, such as at least 80%) greater than inner perimeter **2068**.

(494) In the fully uncompressed configuration thereof, upstream support portion **2041** is typically (but not necessarily) generally flat (e.g., laminar, and/or planar). For some applications, in the fully uncompressed configuration, portion **2041** assumes a frustoconical shape, typically arranged from the generally flat composition of the portion. Portion **2041** has a thickness of less than 5 mm, such as less than 2 mm. Opening **2045** has a depth (e.g., a height) **d12** from an upstream side **2047** of the upstream support portion to a downstream side **2049** of the upstream support portion. Depth **d12** of opening **2045** is less than 5 mm, such as less than 2 mm. Typically, therefore, inner diameter **d11** is more than 4 times (e.g., more than 6 times, such as more than 10 times) greater than depth **d12**. That is, opening **2045** is more than 4 times (e.g., more than 6 times, such as more than 10 times) wider than it is deep. Typically, in the fully uncompressed configuration, upstream support portion **2041** has a total height of less than 10 mm (e.g., less than 5 mm, such as less than 2 mm).

(495) Typically, inner perimeter **2068** comprises, or is defined by, a free inner edge of upstream support portion **2041**. That is, opening **2045** resembles a hole cut out of a lamina (e.g., out of a disc). For some applications, inner perimeter **2068** comprises, or is defined by, a curved and/or folded inner edge of upstream support portion **2041**. If the inner perimeter of upstream support portion **2041** comprises, or is defined by, a curved or folded edge, then a radius of curvature of the curved or folded edge is typically less than 2.5 mm, such as less than 1 mm. That is, the curve or fold of the edge is generally sharp, such that when viewed from within opening **2045**, the curved or folded edge looks generally like a free edge.

(496) It is to be noted that, for simplicity, upstream support portion **2041** is generally described herein in terms of symmetrical geometric shapes (e.g., ellipse and frustum), but that the upstream support portion may assume a symmetrical or an unsymmetrical shape.

(497) Prosthetic valve **2042** comprises a generally tubular (e.g., cylindrical) primary structural element **2130**, shaped to define a lumen **2043** therethrough, and at least one check valve element (not shown), configured to regulate blood flow through the prosthetic valve. Typically, the check valve element comprises one or more prosthetic valve leaflets, disposed in lumen **2043**, and coupled (e.g., sutured) to the primary structural element. For some applications of the invention, the check valve element comprises a ball, disc, or other check valve component. For some applications of the invention, prosthetic valve **2042** comprises a commercially-available stent-based prosthetic valve.

(498) Prosthetic valve **2042** is configured to be placeable in opening **2045** of support **2040**, and couplable to the support by being expandable within this opening, e.g., as described in more detail hereinbelow. Typically, support **2040** comprises tissue-engaging elements (e.g., support-anchoring elements), such as those described herein (not shown in FIGS. 72A-D), and is couplable to the native valve, such that coupling of prosthetic valve **2042** to the support, couples the prosthetic valve to the native valve. For some applications, prosthetic valve **2042** comprises tissue-engaging elements (e.g., valve-anchoring elements), such as those described herein (not shown in FIGS. 72A-D), and is alternatively or additionally directly couplable to the native valve.

(499) In the fully uncompressed configuration thereof, prosthetic valve **2042** typically has a perimeter **2051** of length between 62 and 110 mm (e.g., between 70 and 90 mm, such as between 80 and 90 mm), and a height **d14**, (i.e., a length from an upstream end to a downstream end) of between 15 and 40 mm (e.g., between 20 and 35 mm, such as between 25 and 25 mm). When structural element **2130** is cylindrical, prosthetic valve **2042**, in the fully uncompressed configuration thereof, typically has a diameter **d13** of between 20 and 35 mm (e.g., between 25 and 35 mm, such as between 25 and 30 mm). Typically, support **2040** and prosthetic valve **2042** are configured and/or selected (e.g., paired), such that perimeter **2051** is slightly (e.g., between 1 and 15 mm, such as between 1 and 7 mm) greater than perimeter **2068**, and/or that diameter **d13** is slightly (e.g., between 1 and 5 mm, such as between 1 and 3 mm) greater than diameter **d11**.

(500) In the respective fully uncompressed configurations thereof, height **d14** of prosthetic valve **2042** is typically at least 1.5 times greater (e.g., at least 3 times greater, such as at least 5 times greater) than the total height of upstream support portion **2041**.

(501) Typically, support **2040** comprises a lattice structure which defines a plurality of struts **2120**, typically

in a repeating arrangement, and a plurality of voids between the struts. Typically, upstream support portion **2041** comprises the lattice structure of support **2040**. Typically, prosthetic valve **2042** comprises a lattice structure which defines a plurality of struts **2124**, and a plurality of voids between the struts. Support **2040** and prosthetic valve **2042** typically have shape-memory (e.g., resilient, pseudoelastic and/or superelastic) properties. Typically, struts **2120** and/or struts **2124** comprise a shape-memory (e.g., resilient, pseudoelastic and/or superelastic) material, such that support **2040** and/or prosthetic valve **2042** are compressible when a compressive force is applied (e.g., prior to implantation), and re-expandable when the compressive force is removed (e.g., during implantation), as described hereinbelow. Non-limiting examples of materials that the support (e.g., struts **2120**) and/or prosthetic valve (e.g., struts **2124**) may comprise include nickel-titanium (Nitinol), stainless steel, nickel cobalt, cobalt chrome, titanium, tantalum, and palladium.

(502) Typically, support **2040** and/or prosthetic valve **2042** are at least in part covered with a covering **2440** (for clarity, covering **2440** is only shown on support **2040**). Non-limiting examples of materials that covering **2440** may comprise include polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), and pericardial tissue. For some applications, covering **2440** comprises a fabric. Typically, a thickness of the covering is less than 0.5 mm, such as less than 0.2 mm, e.g., less than 0.1 mm, or less than 0.05 mm. In FIG. 72A, struts **2120** are shown in phantom, as they are covered by covering **2440**.

(503) For some applications of the invention, covering **2440** is configured to facilitate blood flow through the prosthetic valve, e.g., to channel blood through lumen **2043** defined by prosthetic valve **2042**, and/or to prevent leakage (1) between the prosthetic valve and support **2040**, and/or (2) between implant **2030** and the native valve. For some applications of the invention, the covering is configured to mask sharp and/or hard surfaces (e.g., metal surfaces, such as surfaces of struts **2120** and/or **2124**), and thereby to protect native tissues from being damaged by such surfaces. For some applications of the invention, the covering is configured to facilitate (e.g., to enhance) coupling between support **2040** and prosthetic valve **2042** (e.g., as described hereinbelow), such as by increasing friction. For some applications of the invention, the covering is configured to facilitate (e.g., to encourage) growth of tissue (e.g., fibrosis) over one or more components of implant **2030**.

(504) FIG. 72B shows support **2040** and prosthetic valve **2042** of implant **2030** in respective compressed configurations thereof, typically for delivery to the native valve. Typically, support **2040** and prosthetic valve **2042** are delivered percutaneously (e.g., transcatheterally). Typically, the support and the valve component are delivered to the native valve transluminally (e.g., transfemorally). For some applications, support **2040** and prosthetic valve **2042** are delivered to the native valve transatrially. For some applications, support **2040** and prosthetic valve **2042** are delivered to the native valve transapically. In the compressed configuration thereof, upstream support portion **2041** is typically generally cylindrical, and is typically delivered to a site that is upstream of the native valve of the subject (e.g., the left atrium, upstream of the mitral valve of the subject), such that a downstream (e.g., distal) end **2053** of the support has a perimeter **2068b**, which is a compressed inner perimeter **2068**, and an upstream end **2055** of the support comprises perimeter **2069b**, which is a compressed outer perimeter **2069**.

(505) In the compressed configuration thereof, upstream support portion **2041** typically has (e.g., perimeters **2068b** and **2069b** have) a perimeter of length between 9 and 30 mm (e.g., between 15 and 25 mm, such as between 18 and 22 mm), and a height **d15** of between 11 and 30 mm (e.g., between 15 and 30 mm, such as between 15 and 25 mm). When upstream support portion **2041**, in the compressed configuration thereof, is cylindrical, portion **2041** typically has a diameter of between 3 and 9 mm (e.g., between 5 and 8 mm, such as between 6 and 7 mm).

(506) In the compressed configuration thereof, prosthetic valve **2042** is typically generally cylindrical. Compression of the prosthetic valve typically comprises inwardly-radial compression, such that the component is narrower and taller in the compressed configuration than in the fully uncompressed configuration thereof. In the compressed configuration thereof, prosthetic valve **2042** typically has a perimeter **2051b** (a compressed perimeter **2051**) of between 9 and 30 mm (e.g., between 10 and 20 mm, such as between 15 and 20 mm), and a height **d16** of between 16 and 41 mm (e.g., between 20 and 35 mm, such as between 20 and 30 mm). When prosthetic valve **2042**, in the compressed configuration thereof, is cylindrical, prosthetic valve **2042** typically has a diameter of between 2 and 9 mm (e.g., between 3 and 8 mm, such as between 3 and 6 mm).

(507) Support **2040** (e.g., portion **2041**) and prosthetic valve **2042** typically have shape-memory properties, and are compressed (e.g., crimped) into their respective compressed configurations prior to (e.g., immediately prior to) the implantation procedure. Typically, the support and prosthetic valve are retained (e.g.,

‘constrained’) in this configuration by a constraining member, such as an overtube, a delivery tube, and/or other delivery apparatus. Support **2040** and prosthetic valve **2042** are typically subsequently expanded (e.g., ‘deployed’) close to the site of implantation by releasing the constraining (e.g., compressive) force (e.g., by removing the constraining member). That is, the compressed configurations of prosthetic valve support **2040** (e.g., of upstream support portion **2041**) and prosthetic valve **2042**, described with reference to FIG. 72B, typically comprise constrained compressed configurations, and the fully uncompressed configurations, described with reference to FIG. 72A, are unconstrained uncompressed configurations.

(508) FIG. 72C shows an end-view of implant **2030**, with prosthetic valve **2042** coupled to prosthetic valve support **2040** by being disposed and expanded within opening **2045** (not shown in FIG. 72C) defined by portion **2041**. FIG. 72C shows downstream side **2049** of support **2040**, therefore struts **2120** are shown in solid form. Typically, prosthetic valve **2042** is delivered to opening **2045** in a constrained compressed configuration thereof (e.g., as described with reference to FIG. 72B), and expanded (e.g., released) in the opening, such that prosthetic valve **2042** applies a radially-expansive force against inner perimeter **2068** of portion **2041**. Typically, this radially-expansive force facilitates coupling of prosthetic valve **2042** to portion **2041**.

(509) So as to provide the radially-expansive force, and as described hereinabove, prosthetic valve **2042** and support **2040** (e.g., portion **2041**) are typically configured and/or selected (e.g., paired) such that perimeter **2051** of prosthetic valve **2042**, in the fully uncompressed configuration thereof, is slightly greater than inner perimeter **2068** of portion **2041**. When prosthetic valve **2042** is expanded within opening **2045**, portion **2041** (e.g., inner perimeter **2068**) thereby restricts the full expansion of prosthetic valve **2042**. Therefore, in the coupled configuration shown in FIG. 72C, a perimeter **2051c** of prosthetic valve **2042** is typically smaller than perimeter **2051** of the prosthetic valve in the fully uncompressed configuration thereof.

(510) As described hereinabove (e.g., with reference to FIG. 72A), upstream support portion **2041** is configured to be placed against an upstream side of the native valve. As further discussed hereinbelow (e.g., with reference to FIG. 72K), it should be noted, that radial expansion of prosthetic valve **2042** against inner perimeter **2068** of upstream support portion **2041**, thereby typically does not cause the prosthetic valve support to apply a radially-expansive force to the native valve.

(511) For some applications, the prosthetic valve is couplable to the upstream support portion at a continuum of positions along the axial length of the prosthetic valve. That is, a physician can couple the prosthetic valve to the support at a continuum of depths within the support. For example, in applications in which the prosthetic valve is configured to be coupled to the upstream support portion solely by the radially-expansive force, the prosthetic valve may be coupled to the upstream support portion at a continuum of positions along the length of the prosthetic valve.

(512) As described hereinabove, the lattice structures of prosthetic valve **2042** and portion **2041** typically define a repeating arrangement of struts, e.g., a repeating arrangement of shapes. For some applications, and as shown in FIG. 72C, prosthetic valve **2042** and portion **2041** comprise the same number of arrangement repeats. For some such applications, this matching number of repeats facilitates coupling of prosthetic valve **2042** and portion **2041**. For example, and as shown in FIG. 72C, a number of inwardly-protruding ridges **2057** of portion **2041** protrude (e.g., interpose) within an equal number of corresponding circumferential voids defined by the lattice structure of prosthetic valve **2042**. These ridges facilitate coupling of support **2040** and prosthetic valve **2042**, e.g., by inhibiting axial movement of the prosthetic valve through opening **2045** of upstream support portion **2041**.

(513) Typically, the arrangement of repeating circumferential voids defined by the lattice structure of the prosthetic valve is repeated axially, thereby defining a prismatic (e.g., cylindrical) shape of the prosthetic valve. For some applications, the prosthetic valve is thereby couplable to the upstream support portion at a plurality of positions along the axial length of the prosthetic valve. That is, a physician can couple the prosthetic valve is couplable to the upstream support portion at a plurality of depths within the support. For example, in applications in which when a circumferential arrangement of voids is repeated four times along the axial length of the prosthetic valve, the prosthetic valve is typically couplable to the upstream support portion at four positions along the axial length of the prosthetic valve.

(514) It is noted that, for some applications, the above descriptions of prosthetic valve **2042** and support **2040** are applicable to (e.g., the applications described above are combinable with) other embodiments of prosthetic valves and prosthetic valve supports described herein.

(515) FIG. 72D shows an end view of an implant **2030a**, comprising prosthetic valve **2042** coupled to a prosthetic valve support **2040a**. For some applications of the invention, prosthetic valve support **2040a**

comprises, and/or is analogous to, another prosthetic valve support (e.g., prosthetic valve support **2040**) described herein, and implant **2030a** comprises, and/or is analogous to, other implants (e.g., implant **2030**) described herein. Prosthetic valve support **2040a** comprises an upstream support portion **2041a**. For some applications of the invention, upstream support portion **2041a** comprises, and/or is analogous to, other upstream support portions described herein. Upstream support portion **2041a** comprises a plurality of inwardly-protruding barbs **2102**, protruding from inner perimeter **2068** into opening **2045**, such that, when prosthetic valve **2042** is expanded within opening **2045**, barbs **2102** protrude (e.g., interpose) into voids defined by the lattice structure of prosthetic valve **2042**. Similarly to the protrusion of ridges **2057** (described with reference to FIG. 72C) the protrusion of barbs **2102** further facilitates coupling of prosthetic valve support **2040a** and prosthetic valve **2042**. For some applications, barbs **2102** are disposed on (e.g., protrude from) ridges **2057**. For some applications, barbs **2102** are disposed between ridges **2057** (e.g., protrude from sites between ridges **2057**).

(516) Reference is made to FIG. 73, which is a schematic illustration of a prosthetic valve support **2040b**, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040b** comprises, and/or is analogous to, other prosthetic valve supports described herein. For some applications, prosthetic valve support **2040b** comprises prosthetic valve support **2040**, described hereinabove. Support **2040b** comprises upstream support portion **2041**, coupled to one or more clips **2900**, configured to be couplable to one or more native leaflets **2082** of the native valve. For some applications of the invention, clips **2900** comprise tissue-engaging elements and/or support-anchoring elements (e.g., as described hereinabove). For some applications, prosthetic valve support **2040b** alternatively or additionally comprises other tissue-engaging elements. Typically, support **2040b** comprises two clips **2900**, coupled to portion **2041** at or near inner perimeter **2068**. Typically, clips **2900** are disposed opposite each other.

(517) Typically, clips **2900** are articulatably coupled to portion **2041**. That is, typically, clips **2900** can move, at least in part, with respect to portion **2041**. Typically, each clip **2900** is coupled to portion **2041** via a connector **2540**, which facilitates this movement. Typically, but not necessarily, connector **2540** comprises a flexible material, such as a fabric and/or polymer. For some applications, connector **2540** comprises one or more hinge points, to facilitate the movement of the clips.

(518) Each clip **2900** typically comprises two or more clip elements, such as a clip arm **2920** and a clip arm **2922**, movable with respect to each other. Typically, the clip arms are articulatably-coupled at an articulation point **2921**, and are movable with respect to each other by the relative angular disposition of the clip arms being controllable. Typically, clip **2900** is configured to be biased (e.g., pre-set, such as shape-set) to be in a closed configuration, such that arms **2920** and **2922** are relatively disposed at a generally small angle (e.g., less than 45 degrees, such as less than 20 degrees, such as less than 5 degrees) to each other. For some applications, in the closed configuration of clip **2900**, arms **2920** and **2922** touch each other at a site that other than the articulation point. Each clip **2900** is configured to be couplable to a native leaflet **2082** of the native valve by enveloping the native leaflet when the clip is in the open configuration thereof, and clipping the leaflet between the clip arms when the clip subsequently moves toward the closed configuration thereof.

(519) Typically, arm **2920** is substantially immobile, and arm **2922** is (1) biased to assume a first configuration, and (2) movable between the first configuration and another configuration. Typically, the first configuration of arm **2922** is a closed configuration. Typically, the other configuration of arm **2922** is an open configuration, whereby a portion of arm **2922** that is furthest from articulation point **2921** is disposed (1) further from arm **2920** than is the same portion in the first, closed configuration, and (2) further from arm **2920** than a portion of arm **2922** that is closest to the articulation point. That is, an angular disposition of arm **2922** to arm **2920** is greater when arm **2922** is in the open configuration thereof, than when arm **2922** is in the closed configuration thereof. When arm **2922** is in the closed configuration thereof, clip **2900** is in the closed configuration thereof. When arm **2922** is in the open configuration thereof, clip **2900** is in the open configuration thereof. That is, clip **2900** is movable between open and closed configurations thereof, by arm **2922** moving between open and closed configurations thereof. FIG. 73 shows detailed illustrations of clip **2900** in the open and closed configurations, and further shows an exploded view of the components of clip **2900**.

(520) Clip **2900** further comprises a clip-controller interface, typically comprising a pull-wire **2924**, which facilitates movement of arm **2922** between the closed and open configurations, i.e., relative angular movement of arms **2920** and **2922**. Pull-wire **2924** is typically coupled to arm **2922**, and controlled from outside the body of the subject. For example, pull-wire **2924** may be coupled to arm **2922**, and extend to a clip controller (e.g., clip controller **2930**, described with reference to FIGS. 74A-L) disposed within delivery

apparatus, and ultimately controlled by a physician. Typically, pull-wire **2924** is coupled to arm **2922** such that (1) placing the pull-wire under tension (e.g., by pulling) moves arm **2922** toward the open configuration, and (2) releasing the tension, at least in part, allows the arm to return toward the closed configuration. (521) For some applications of the invention, both clips **2900** are controlled simultaneously by a user (e.g., clips **2900** are configured to operate simultaneously). For some applications, each clip **2900** is controllable independently. For some applications, clip **2900** further comprises one or more grips, such as teeth **2928**, which facilitate the clamping of leaflets **2082** when clip **2900** is closed. For some applications, clips **2900** may alternatively or additionally be directly coupled to the prosthetic valve, and configured to couple the prosthetic valve directly to the native valve.

(522) Reference is made to FIGS. **74A-L**, which are schematic illustrations of steps in the implantation of implant **2030b**, comprising prosthetic valve **2042** and prosthetic valve support **2040b**, in a native heart valve, such as mitral valve **2024** of a subject, in accordance with some applications of the invention.

(523) Prosthetic valve support **2040b** is implanted using support-delivery apparatus, such as support-delivery apparatus **2960**. As described hereinabove with reference to FIG. **73**, each clip **2900** comprises a clip-controller interface, typically pull-wire **2924**, which is configured to open the clip when pulled (i.e., placed under tension). For some applications of the invention, and as shown in FIG. **74A**, support-delivery apparatus **2960** comprises at least one clip controller **2930**, one end of pull-wire **2924** is coupled to clip arm **2922**, and another end of the pull-wire is coupled to controller **2930**. Controller **2930** comprises a tubular member **2172**, shaped to define a lumen, and a plug **2174**. Plug **2174** is dimensioned such that it is disposable in, and slidable through (e.g., within, into, and out of) the lumen of tubular member **2172**. Plug **2174** comprises a restricting portion **2190** and a second portion **2192**.

(524) Typically, at least part of plug **2174** (e.g., restricting portion **2190**) is dimensioned so as to fit tightly in the lumen of tubular member **2172**, in a manner in which an outer surface of plug **2174** (e.g., an outer surface of portion **2190**) is disposed very close to an inner surface of tubular member **2172**, i.e., such that little space exists between the at least part of the plug and the tubular member. For example, the widest space between portion **2190** and member **2172** may be smaller than a thickness of pull-wire **2924**. Typically, a surface of second portion **2192** is disposed further from the inner surface of tubular member **2172**, than is the surface of the at least part of portion **2190**.

(525) Controller **2930** typically has at least three controller configurations, each configuration having a different relative disposition of plug **2174** within tubular member **2172**. In a first controller configuration, plug **2174** is disposed at a first longitudinal position within tubular member **2172**. In a second controller configuration, the plug is disposed at a second longitudinal position within the tubular member, the second position being more proximal (e.g., closer to a position outside the body; typically upstream) than the first longitudinal position. In a third controller configuration, the plug is disposed at a third longitudinal position, distal (e.g., downstream) to the first longitudinal position, such that at least restricting portion **2190** is disposed outside of (e.g., distal to) the tubular member.

(526) Controller **2930** has at least one locking configuration, in which (1) at least part of restricting portion **2190** is disposed inside the lumen of tubular member **2172**, and (2) pull-wire **2924**, when coupled to the controller, is generally not decouplable from the controller. Typically, the first and second controller configurations, described hereinabove, are locking configurations. Controller **2930** further has at least one open configuration, in which (1) at least restricting portion **2190** is disposed outside the lumen of tubular member **2172**, and (2) pull-wire **2924** is decouplable from the controller. Typically, the third controller configuration, described hereinabove, is an open configuration.

(527) Typically, and as shown in FIG. **74A**, pull-wire **2924** comprises, and/or is shaped to define, a loop, and is coupled to controller **2930** by at least part of the loop being disposed against second portion **2192** when the lock is in, or moves into, a locking configuration thereof. For some applications, pull-wire **2924** is generally flat (e.g., has an elongate transverse cross-section, e.g., is a strip), is shaped to define a hole, and is coupled to controller **2930** by at least part of restricting portion **2190** being disposed within the hole when the lock is in, or moves into, a locking configuration thereof. Restricting portion **2190** inhibits distal axial movement of the coupling lead, and tubular member **2172** inhibits lateral movement of the coupling lead (e.g., the inner surface of the tubular member holds the coupling lead against second portion **2192**). Tubular member **2172** thereby facilitates coupling of pull-wire **2924** to plug **2174**, and thereby to controller **2930**.

(528) Controller **2930** is typically controlled (e.g., the configurations of the controller, such as the disposition of plug **2174** within tubular member **2172**, are typically selected), via a control rod **2175**, using an extracorporeal controller, such as a control handle **2932**, typically disposed at a proximal end of support-

delivery apparatus **2960**. Control handle **2932** comprises at least one adjuster **2934**, each adjuster configured to control at least one clip **2900** of prosthetic valve support **2040b**. Typically, control handle **2932** comprises two adjusters **2934**, each adjuster configured to independently control one clip **2900**. For clarity, however, adjusters **2934** are shown operating simultaneously. Typically, but not necessarily, adjuster **2934** has pre-defined positions in which it can reside, each pre-defined position of the adjuster corresponding to a respective configuration of controller **2930**. That is, moving adjuster **2934** between the pre-defined positions thereof, moves controller **2930** between the configurations thereof. For illustrative purposes only, example pre-defined positions (A), (B) and (C) are indicated.

(529) FIG. **74A** shows support **2040b** having been delivered, using support-delivery apparatus **2960**, to left atrium **2026** of the heart of a subject (i.e., to a site upstream of native mitral valve **2024** of the subject). Support **2040b** is typically delivered transcatheterally (e.g., transvascularly, such as transfemorally), while in a compressed configuration thereof (e.g., as described with reference to FIG. **72B** for support **2040**). Typically, support **2040b** is delivered within an overtube **2044**, which provides a constraining (e.g., compressive) force, to constrain the support in the compressed configuration thereof. Typically, upstream support portion **2041** of support **2040b** is coupled to a scaffold, such as a core **2946**, and constrained in the compressed configuration by being disposed within an overtube **2044** of the delivery apparatus. In the compressed configuration of support **2040b**, clips **2900** are typically disposed downstream (e.g., distal) to the cylinder of upstream support portion **2041**, and coupled to core **2946**.

(530) During delivery of support **2040b**, and as shown in FIG. **74A**, clips **2900** are typically in the closed configuration thereof. FIG. **74A** shows clips **2900** exposed from the distal end of overtube **2044**, overtube **2044** having been retracted (e.g., overtube **2044** having been moved proximally, and/or support **2040b** having been moved distally). Adjuster **2934** of control handle **2932** is in a first position (A) (typically a middle position) thereof, and controller **2930** is in the first configuration thereof, whereby pull-wire **2924** is coupled to plug **2174**, which is disposed within tubular member **2172**.

(531) FIG. **74B** shows support **2040b** and core **2946** having been moved closer to the native valve, and clips **2900** enveloping leaflets **2082** of the native valve. Adjuster **2934** of control handle **2932** is in a second position (B) thereof (typically more proximal than the first position), and controller **2930** is in the second configuration thereof. Movement of controller **2930** into the second configuration thereof (i.e., moving plug **2174** proximally) places pull-wire **2924** under tension (i.e., pulls the pull-wire), thereby pulling clip arm **2922**, and opening clip **2900**. Using support-delivery apparatus **2960**, the position of prosthetic valve support **2040b** is adjusted, so as to envelope native leaflets **2082** between the clip arms of clips **2900**.

(532) FIG. **74C** shows clips **2900**, coupled (i.e., clipped) to native leaflets **2082**. The user (e.g., the physician) couples the clips to the native leaflets by closing the clips while the leaflets are enveloped by the arms of the clips. Adjuster **2934** of control handle **2932** is in first position (A) thereof (i.e., has been returned to first position (A)), and controller **2930** is in the first configuration thereof (i.e., has been returned to the first configuration thereof). For some applications of the invention, control handle **2932** comprises a spring, which facilitates the return of adjuster **2934** to first position (A). For example, a user may apply a force to adjuster **2934** so as to move the adjuster to second position (B), and remove the force (e.g., release the adjuster) so as to return the adjuster to first position (A). Movement of controller **2930** into the first configuration thereof (i.e., moving plug **2174** distally) at least partly releases the tension on pull-wire **2924**, allowing the bias of clip **2900** (e.g., of clip arm **2922**) to return the clip toward the closed configuration. If a native leaflet **2082** is enveloped by the clip arms, the leaflet is sandwiched between the arms, thereby coupling the clip to the leaflet.

(533) For some applications, visualization (e.g., imaging) techniques such as ultrasound are used to facilitate and/or confirm the coupling of clips **2900** to leaflets **2082**. For example, an echocardiogram may be used to observe native leaflets **2082**, and movement thereof. For some applications, coupling of both native leaflets by clips **2900** is accompanied by a generally lemniscate (e.g., 'FIG. **8**') arrangement of the native leaflets, as shown in View A of FIG. **74C**. Clips **2900** may be repeatedly opened and closed until coupling of the clips to leaflets **2082** has been achieved.

(534) For some applications of the invention, clips **2900** further comprise a securing element (not shown), configured to secure the clips in the closed configuration, following coupling of the clips to the native leaflets. For some applications of the invention, the securing element is configured to secure the clips in one or a pre-defined selection of closed configurations (e.g., in a partially-closed configuration).

(535) Reference is made to FIG. **74D**. Following coupling of clips **2900** to native leaflets **2082**, the clips are released (e.g., decoupled) from support-delivery apparatus **2960** (e.g., from core **2946**) by decoupling pull-

wire **2924** from controller **2930**. To decouple the pull-wire from the controller, the user moves adjuster **2394** of control handle **2932** to third position (C) thereof (typically a distal position), thereby moving controller **2930** in the third configuration thereof, whereby at least restricting portion **2190** of plug **2174** is disposed outside of tubular member **2172**. For some applications of the invention, control handle **2932** comprises a safety device, such as a safety lock **2936**, configured to prevent inadvertent movement of adjuster **2394** into position (C), and thereby inadvertent release of clips **2900**. For such applications, safety lock is disabled (e.g., removed) prior to releasing clips **2900**.

(536) Movement of controller **2930** into the third position thereof (i.e., moving at least part of plug **2174** outside of tubular member **2172**) allows pull-wire **2924** to decouple from the controller. For some applications, pull-wire **2924** is configured to automatically decouple from the controller when the controller moves into the third position. For example, the pull-wire may comprise a shape-memory (e.g., resilient, pseudoelastic and/or superelastic) material configured to lift the loop of the pull-wire away (e.g., laterally away) from plug **2174** when restricting portion **2190** moves outside of the tubular member. Non-limiting examples of materials that pull-wire **2924** may comprise include nickel-titanium (Nitinol), stainless steel, nickel cobalt, cobalt chrome, titanium, tantalum, palladium, polyester, PTFE, nylon, and cotton. For some applications of the invention, pull-wire **2924** is biodegradable (e.g., bioabsorbent).

(537) Reference is now made to FIG. **74E**. Following the decoupling of clips **2900** from controller **2930**, upstream support portion **2041** of prosthetic valve support **2040b** is deployed (e.g., released from overtube **2044**). Typically, overtube **2044** is withdrawn proximally, exposing successively more proximal (e.g., upstream) parts of portion **2041**. As described hereinabove (e.g., with reference to FIG. **72A**), portion **2041** typically comprises a shape-memory material, and is compressed prior to implantation. Portion **2041** thereby automatically expands upon removal of the constraining (e.g., compressive) force, i.e., when overtube **2044** is withdrawn.

(538) Immediately prior to the release of prosthetic valve support **2040b** from the overtube, the total length of overtube **2044** and support **2040b** may be double or more than that of the overtube or support alone. For some applications, this extra length can hinder the movement and/or removal of the overtube from the body of the subject. For some applications, overtube **2044** comprises a flexible and/or soft material, such as a fabric or polymer, thereby becoming flexible as support **2040b** is removed from within the overtube. It is hypothesized that this composition/configuration of overtube **2044** facilitates deployment of support **2040b**, and removal of the overtube from the body of the subject.

(539) FIG. **74F** shows prosthetic valve support **2040b** during full deployment thereof. Typically, and as described hereinabove, when upstream support portion **2041** is delivered to the native valve in the cylindrical, compressed configuration, downstream (e.g., distal) end **2053** of the cylinder has perimeter **2068b**, which is a compressed inner perimeter **2068**. Distal end **2053**, and therefore the inner perimeter of portion **2041**, is thereby coupled to the native valve before deploying (e.g., expanding) upstream (e.g., proximal) end **2055**, and therefore the outer perimeter of portion **2041**. That is, the inner perimeter of portion **2041** typically engages the native valve before the outer perimeter.

(540) The two phases illustrated in FIG. **74F** illustrate typical behavior of upstream support portion **2041** during deployment thereof. As downstream end **2053**, moves out of overtube **2044**, it expands toward becoming and/or defining inner perimeter **2068** of portion **2041**. As upstream end **2055** moves out of overtube **2044**, it expands to become outer perimeter **2069**. Due to this arrangement, during deployment, upstream end **2055** typically expands more than does downstream end **2053**. For some applications, upstream end **2055** expands more than 1.5 times (e.g., more than twice) as much as does downstream end **2053**.

(541) Reference is now made to FIGS. **74G-H**, which show support **2040b** in the implanted configuration thereof. Upstream support portion **2041** is described hereinabove (e.g., with reference to FIG. **72A**) as being generally flat when in its fully uncompressed configuration. However, portion **2041** is typically at least partly resilient. For example, as described hereinabove, portion **2041** typically comprises a shape-memory material. Implanting support **2040b**, as described with reference to FIGS. **74A-F**, disposes portion **2041** against the upstream side of the native valve (e.g., the upstream side of the native valve annulus). Typically, portion **2041** is held tightly against the upstream side of the native valve by clips **2900**, and deforms responsively to the contours of the native tissue (e.g., conforms to the native annulus), thereby assuming an implanted configuration. For some applications, portion **2041** repeatedly deforms responsively to the contours of the native tissue, as the native tissue repeatedly changes shape with the cardiac cycle.

(542) Upstream support portion **2041** and clips **2900** are typically configured such that, when support **2040b** is implanted at the native valve, upstream support portion inhibits downstream (e.g., ventricular) movement

of support **2040b**, and clips **2900** inhibit upstream (e.g., atrial) movement of the support. Typically, clips **2900** are configured to couple the prosthetic valve support to the native valve such that upstream support portion **2041** is in contact with the upstream side of the native valve (e.g., with the upstream side of the native annulus). For some applications, clips **2900** are the only component of prosthetic valve support **2040b** that inhibits upstream movement of prosthetic valve support.

(543) The dimensions of upstream support portion **2041** in the implanted configuration thereof are typically similar to those of the same portion in the fully uncompressed configuration thereof, with any difference between the configurations typically due to the portion being implanted. For example, in some applications in which upstream support portion **2041** is generally flat in the fully uncompressed (e.g., unconstrained uncompressed) configuration thereof, when support **2040b** is implanted at the native valve, clips **2900** apply a downstream force to inner perimeter **2068** of upstream support portion **2041**, thereby inducing portion **2041** to assume a frustoconical shape in the implanted configuration thereof. When upstream support portion **2041** is generally frustoconical in the implanted configuration thereof, a surface of portion **2041** typically has an angle of less than 60 degrees (e.g., less than 45 degrees) from a plane of the smaller base of the frustum. (As shown in FIG. 74G, for example, this angle is approximately 10 degrees.) That is, when upstream support portion **2041** is generally frustoconical in the implanted configuration thereof, portion **2041** is closer to being planar than it is to being cylindrical. Alternatively, the surface of portion **2041** has an angle of greater than 60 degrees from the smaller base of the frustum. It is to be noted that, although upstream support portion **2041** is generally described herein in terms of symmetrical geometric shapes (e.g., ellipse and frustum), when conforming to native tissue, the upstream support portion may assume a symmetrical or an unsymmetrical shape.

(544) Thus, in general, as shown in and described with reference to FIGS. 72A-74L, (1) the fully uncompressed configurations of upstream support portion **2041** described with reference to FIG. 72A are typically unconstrained uncompressed configurations, (2) the compressed configurations of portion **2041** described with reference to FIG. 72B are typically constrained compressed configurations, and (3) the implanted configurations of portion **2041** described with reference to FIG. 74F are typically constrained uncompressed configurations.

(545) When implanted at the native valve, and thereby in the implanted configuration thereof, no part of upstream support portion **2041** is disposed downstream of native leaflets **2082** (e.g., no part of portion **2041** is disposed in ventricle **2028**). Typically, when prosthetic valve support **2040b** is implanted at the native valve, no part of support **2040b** that circumscribes a space (e.g., opening **2045**) is disposed downstream of the native leaflets. For some applications, when prosthetic valve support **2040b** is implanted at the native valve, no part of support **2040b** that circumscribes a space is disposed downstream of the native annulus.

(546) When implanted at the native valve, and thereby in the implanted configuration thereof, a height (i.e., a length along an upstream-to-downstream axis **ax1** from a most upstream end to a most downstream end) of upstream support portion **2041**, is typically less than 20 mm (e.g., less than 10 mm, such as less than 5 mm). Typically, when prosthetic valve support **2040b** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 20 mm. For some applications, when prosthetic valve support **2040b** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 10 mm. For some applications, when prosthetic valve support **2040b** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 5 mm.

(547) As described hereinabove with reference to FIG. 73, clips **2900** are articulatably-coupled to upstream support portion **41** of prosthetic valve support **2040b**. Following the implantation (e.g., delivery, coupling and deployment) of prosthetic valve support **2040b**, clips **2900** can move, at least in part, with respect to portion **2041**, thereby allowing native leaflets **2082** to continue to function, at least in part. That is, implantation of prosthetic valve support **2040b** at a native valve, does not eliminate the native blood flow regulation functionality of the native valve. FIGS. 74G-H show such movement of native leaflets **2082**, and clips **2900**. FIG. 74G shows support **2040b** implanted at mitral valve **2024**, with native leaflets **2082** open (e.g., during ventricular diastole), clips **2900** having moved away from each other. FIG. 74H shows support **2040b** implanted at mitral valve **2024**, with native leaflets **2082** closed (e.g., during ventricular systole), clips **2900** having moved toward each other. Typically, each clip moves through an arc of greater than 45 degrees (e.g., greater than 60 degrees, such as greater than 80 degrees) during each cardiac cycle.

(548) FIGS. 74I-L show steps in the implantation of prosthetic valve **2042** in opening **2045** of prosthetic valve support **2040b**. As described hereinabove, prosthetic valve **2042** is typically delivered transcatheterally. Typically, prosthetic valve **2042** is delivered to the native valve from an upstream side (e.g., the atrial side of

the mitral valve), in a compressed configuration, and constrained within a delivery tube **2060**, as shown in **3I**. The prosthetic valve and delivery tube are typically placed within opening **2045**. Delivery tube **2060** is then withdrawn from the prosthetic valve. Typically, the delivery tube is withdrawn in a downstream direction (e.g., distally and/or ventricularly), as shown in **FIG. 74J**. For some applications, the delivery tube is withdrawn in an upstream direction (e.g., proximally and/or atrially).

(549) As regions of prosthetic valve **2042** are successively exposed as they exit delivery tube **2060**, they expand (e.g., radially). When delivery tube **2060** is withdrawn in the downstream direction, the upstream end of the prosthetic valve is exposed, and expands, thereby coupling the prosthetic valve to the upstream support portion of prosthetic valve support **2040b**, as shown in **FIG. 74K** (in which prosthetic valve **2042** is represented by a trapezoid/frustum). As described hereinabove (e.g., with reference to **FIG. 72C**), for some applications, the prosthetic valve is couplable to the upstream support portion at a plurality of positions along the axial length of the prosthetic valve. For such applications, a physician can typically implant (e.g., couple to support **2040b**) the prosthetic valve at a plurality of depths with respect to upstream support portion **2041** and/or the native valve. For some such applications, the prosthetic valve prosthetic valve is implantable at a continuum of depths with respect to upstream support portion **2041** and/or the native valve.

(550) As shown in **FIG. 74K**, upstream support portion **2041** is placed against the upstream side of the native valve, and prosthetic valve **2042** is radially expanded within opening **2045** defined by the upstream support portion. Radially-expansive force applied by prosthetic valve **2042** to upstream support portion **2041** (and which typically couples the prosthetic valve to the upstream support portion), is typically not transferred to the native valve via the prosthetic valve support. That is, and as described hereinabove (e.g., with reference to **FIGS. 72A** and **72C**), radial expansion of prosthetic valve **2042** against inner perimeter **2068** of upstream support portion **2041**, typically does not cause the prosthetic valve support to apply a radially-expansive force to the native valve.

(551) Once delivery tube **2060** is fully withdrawn from prosthetic valve **2042**, and the prosthetic valve is fully deployed (e.g., in the implanted configuration thereof), delivery tube **2060** is removed from the body of the subject. For some applications, when the delivery tube is withdrawn in the downstream direction (e.g., ventricularly), it is removed from the body via the lumen of the prosthetic valve, as shown in **FIG. 74L**.

(552) As described hereinabove (e.g., with reference to **FIGS. 73**, and **74G-H**), following the implantation (e.g., delivery, coupling and deployment) of prosthetic valve support **2040b**, clips **2900** and native leaflets **2082** can move, at least in part, thereby not eliminating the native blood flow regulation functionality of the native valve. In experiments conducted by the inventors, prosthetic valve support **2040b** has been implanted in two pigs. Both animals remained alive and stable (e.g., had stable blood pressure, pulse, breathing rate and oxygen saturation) for a duration of sufficient length to withdraw the support-delivery apparatus, introduce a valve-delivery system (e.g., delivery tube **2060**), and deploy (e.g., implant) prosthetic valve **2042** in opening **2045** of the support. The period between implanting support **2040b** and implanting prosthetic valve **2042** was between 5 and 10 minutes.

(553) It is thereby hypothesized that, following implantation of prosthetic valve support **2040b**, the heart of the subject is able to continue pumping blood sufficiently to support the subject for longer than a minute, e.g., longer than 2 minutes, e.g., longer than 5 minutes, such as longer than an hour. It is thereby hypothesized that a period of generally normal physiological activity of the subject of up to a minute, e.g., up to 2 minutes, e.g., up to 5 minutes, such as up to an hour, between implantation of support **2040b** and implantation of prosthetic valve **2042** (e.g., as described with reference to **FIGS. 74I-L** and/or **76D-E**), is supported by prosthetic valve support **2040b**. It is thereby hypothesized that the implantation of implant **2030b**, comprising support **2040b** and prosthetic valve **2042**, may be performed without the use of cardiopulmonary bypass. It is thereby hypothesized that replacement of a native valve with implant **2030b**, may be performed in a human, ‘off-pump,’ as was performed in the pig experiments.

(554) Reference is again made to **FIGS. 73** and **74A-L**. It should be noted that clips **2900**, clip-controller interface (e.g., pull-wire **2924**), clip controller **2930**), and/or the support-delivery apparatus (e.g., support-delivery apparatus **2960**) are typically configured such that the clips are controllable independently of the deployment (e.g., expansion) of the prosthetic valve support (e.g., the withdrawal of overtube **2044** from upstream support portion **2041**). That is, clips **2900** are typically configured to be controllable independently of a state of deployment of the prosthetic valve support (e.g., prosthetic valve support **2040b**). Thus, a physician may independently control (1) the coupling (e.g., ‘clipping’) of clips **2900** to the leaflets of the native valve, and (2) the deployment of the prosthetic valve support (e.g., expansion of the upstream support

portion).

(555) Reference is made to FIGS. 75A-E, which are schematic illustrations of implant **2030c**, comprising prosthetic valve **2042** and prosthetic valve support **2040c**, and the implantation thereof, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040c** comprises, and/or is analogous to, other prosthetic valve supports (e.g., prosthetic valve support **2040**), and implant **2030c** comprises, and/or is analogous to, other implants (e.g., implant **2030**) described herein. Support **2040c** comprises upstream support portion **2041**, coupled to one or more clips **2900**, described hereinabove (e.g., with reference to FIGS. 73 and 74A-L), and configured to be couplable to one or more native leaflets **2082** of the native valve. Typically, support **2040c** comprises two clips **2900**, coupled to portion **2041** at or near inner perimeter **2068**. Typically, clips **2900** are disposed opposite each other. Support **2040c** further comprises a stabilizing element **3062** (e.g., a stabilizing strip or a stabilizing band), coupled to clips **2900**.

(556) Reference is now made to FIG. 75A, which shows a lower side view of support **2040c**. Typically, stabilizing element **3062** is coupled to a downstream (e.g., distal) portion of clips **2900**, and forms a ring shape downstream (e.g., distal) to upstream support portion **2041**. Stabilizing element **3062** defines an opening **3064** (e.g., an aperture), and is typically inelastic and at least partly flexible. Non-limiting examples of materials that element **3062** may comprise include polyester, PTFE (e.g., ePTFE), nylon, cotton, nitinol, stainless steel, nickel cobalt, cobalt chrome, titanium, tantalum and palladium. The flexibility of element **3062** typically facilitates the compressibility of the prosthetic valve support (e.g., for delivery) and/or movement (e.g., articulation) of clips **2900** with respect to upstream support portion **2041**.

(557) Stabilizing element **3062** is hypothesized to increase the stability of prosthetic valve support **2040c** at the native valve. For example, element **3062** is hypothesized to at least partly inhibit lateral movement (e.g., rotation around an atrial-ventricular axis, e.g., ‘yaw’) of the support and/or clips, when the support is implanted at the native valve. Element **3062** is further hypothesized to reduce rolling movement (e.g., movement around a lateral axis, e.g., an axis between two clips **2900**, e.g., ‘pitch’ and ‘roll’) of implant **2030c**, including inversion (e.g., ‘flipping’) of the implant, following deployment (e.g., implantation) of prosthetic valve **2042**.

(558) For some applications of the invention, stabilizing element **3062** is further hypothesized to stabilize clips **2900** during deployment of the elements, e.g., by facilitating coupling thereof to delivery apparatus, such as apparatus **2960**.

(559) FIGS. 75B-C show prosthetic valve support **2040c**, following implantation thereof at mitral valve **2024**. As described hereinabove, the upstream support portion is disposed upstream of the native valve. Stabilizing element is disposed downstream of the native valve (i.e., in ventricle **2028**). Prosthetic valve support **2040c** is typically implanted as described elsewhere herein for other prosthetic valve supports, mutatis mutandis. As described hereinabove, stabilizing element **3062** is typically at least partly flexible, such that clips **2900** are movable with respect to upstream support portion **2041**. Typically, element **3062** is sufficiently flexible to allow native leaflets **2082** to continue to function, at least in part. FIG. 75B shows support **2040c** implanted at mitral valve **2024**, with native leaflets **2082** open (e.g., during ventricular diastole). FIG. 75C shows support **2040c** implanted at mitral valve **2024**, with native leaflets **2082** closed (e.g., during ventricular systole). For some applications, when the native leaflets close, stabilizing element **3062** deforms toward a generally lemniscate (e.g., ‘figure-8’ or ‘butterfly’) configuration (e.g., as shown in FIG. 75C).

(560) For some applications of the invention, a similar generally lemniscate configuration is formed by element **3062** when prosthetic valve support **2040c** is coupled to delivery apparatus, during delivery to the native valve (e.g., as described for support **2040b** with reference to FIGS. 74A-B). For some such applications, stabilizing element **3062** protrudes from the compressed prosthetic valve support, and facilitates positioning and/or orientation of the support. For example, the ‘limbs’ of the lemniscate are typically oriented at right angles to clips **2900**, and protrude from the compressed support. When the clips are in close proximity to the native leaflets, the ‘limbs’ are typically downstream of the leaflets, and interact (e.g., touch) chordae tendineae of the native valve. By orienting the prosthetic valve support such that the ‘limbs’ have the least interaction with chordae tendineae (typically when the ‘limbs’ are oriented toward commissures of the native valve), a user automatically orients clips **2900** toward leaflets **2082** of the native valve.

(561) Similarly to support **2040b** (described with reference to FIGS. 74A-L), implantation of prosthetic valve support **2040c** at a native valve does not eliminate the native blood flow regulation functionality of the native valve. It is thereby hypothesized that, following implantation of prosthetic valve support **2040c**, the heart of the subject is able to continue pumping blood sufficiently well to support the physiological systems of the

subject for longer than a minute, e.g., longer than 2 minutes, e.g., longer than 5 minutes, such as longer than an hour. It is thereby hypothesized that a period of up to a minute, e.g., up to 2 minutes, e.g., up to 5 minutes, such as up to an hour, between implantation of support **2040c** and implantation of a prosthetic valve (e.g., prosthetic valve **2042**), is supported by prosthetic valve support **2040c**. It is thereby hypothesized that the implantation of implant **2030c**, comprising support **2040c** and prosthetic valve **2042**, may be performed without the use of cardiopulmonary bypass. That is, it is hypothesized that replacement of a native valve with implant **2030c**, may be performed ‘off-pump’.

(562) When implanted at the native valve, and thereby in the implanted configuration thereof, no part of stabilizing element **3062** is disposed upstream of native leaflets **2082** (e.g., no part of element **3062** is disposed in atrium **2026**). Typically, when prosthetic valve support **2040c** is implanted at the native valve, no part of support **2040c** that circumscribes a space (e.g., portion **2041**, which circumscribes opening **2045** and/or element **3062**, which circumscribes opening **3064**) traverses (e.g., fully traverses) the native annulus.

(563) When implanted at the native valve, and thereby in the implanted configuration thereof, a height (i.e., a length along an upstream-to-downstream axis **ax2** from a most upstream part to a most downstream part) of stabilizing element **3062**, is typically less than 20 mm (e.g., less than 10 mm, such as less than 5 mm). For example, stabilizing element **3062** typically has a thickness of less than 20 mm (e.g., less than 10 mm, e.g., less than 5 mm, such as less than 1 mm). Typically, when prosthetic valve support **2040c** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 20 mm. For some applications, when prosthetic valve support **2040c** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 10 mm. For some applications, when prosthetic valve support **2040c** is implanted at the native valve, no part of the support that circumscribes a space has a height of more than 5 mm.

(564) FIG. 75D shows implant **2030**, comprising prosthetic valve support **2040c** and prosthetic valve **2042**, following implantation at mitral valve **2024**. The prosthetic valve is typically implanted as described elsewhere herein (e.g., with reference to FIGS. 74I-L), mutatis mutandis. Prosthetic valve **2042** is deployed (e.g., delivered and expanded) in opening **2045**, defined by upstream support portion **2041**, and in opening **3064**, defined by stabilizing element **3062**. That is, when prosthetic valve **2042** is deployed at the native valve, it is expanded such that (1) an upstream (e.g., proximal) portion of the prosthetic valve engages (e.g., couples to) inner perimeter **2068** of support **2040c**, and (2) a downstream (e.g., distal) portion of the prosthetic valve is disposed within the opening of the stabilizing element. For some applications of the invention, and as illustrated in FIG. 75D, the distal portion of the prosthetic valve engages (e.g., couples to) the stabilizing element.

(565) For some applications of the invention, stabilizing element **3062** is configured (e.g., dimensioned) such that, when the prosthetic valve is expanded within the opening of the stabilizing element, the stabilizing element restricts the full expansion of the downstream portion of the prosthetic valve. That is, for some applications, upon expansion of the prosthetic valve, a transverse cross-sectional dimension (e.g., area) defined by a downstream portion of the prosthetic valve is determined (e.g., restricted) by a transverse cross-sectional dimension (e.g., area) of opening **3064** of the stabilizing element. For some applications, one or more dimensions of opening **3064**, defined by stabilizing element **3062**, are substantially equal to one or more dimensions of opening **2045**, defined by upstream support portion **2041**. For some such applications, the expansion of both the downstream and upstream portions of the prosthetic valve are restricted to substantially the same transverse cross-sectional dimensions, thereby facilitating the primary structural element of the prosthetic valve to assume a generally prismatic (e.g., generally cylindrical) shape.

(566) For applications where stabilizing element **3062** limits the expansion of prosthetic valve **2042**, a radially-expansive force is thereby applied by prosthetic valve **2042** to stabilizing element **3062**. The radially-expansive force typically couples the prosthetic valve to the stabilizing element. That is, for some applications, prosthetic valve **2042** is couplable to the stabilizing element. For some applications, the prosthetic valve is coupled to the stabilizing element by alternative or additional means. For example, the stabilizing element may comprise barbs and/or hooks, which facilitate coupling to the prosthetic valve.

(567) For some applications of the invention, at least part (e.g., an inner surface) of stabilizing element **3062** comprises a friction coating that is configured to increase friction and, thereby, coupling between the stabilizing element and the prosthetic valve.

(568) For some applications of the invention, at least part of stabilizing element **3062** is shaped to define ridges, which are configured (e.g., dimensioned) to protrude (e.g., interpose) within corresponding voids defined by the lattice structure of the prosthetic valve. The ridges facilitate coupling of the stabilizing element

to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through opening **3064**. (569) For some applications of the invention, a soft (e.g., crushable) material is disposed on the inner surface of stabilizing element **3062** (e.g., the stabilizing element comprises the soft material). When prosthetic valve **2042** expands, and applies radially-expansive force to the stabilizing element, (1) the struts of the lattice structure of the prosthetic valve compress (e.g., crush) the parts of the soft material against which the struts apply the force, and (2) the parts of the soft material that are disposed between the struts (i.e., that are disposed at voids defined by the lattice structure), form ridges that protrude between the struts (i.e., protrude into the voids). The protruding parts of the soft material facilitate coupling of the stabilizing element to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through opening **3064**, such as by increasing friction.

(570) For some applications of the invention, prosthetic valve **2042** (e.g., the primary structural element of prosthetic valve **2042**) is shaped to define a circumferential groove that is configured (e.g., dimensioned) to receive stabilizing element **3062**. That is, for some applications of the invention, stabilizing element **3062** is configured (e.g., dimensioned) to be placeable in a circumferential groove defined by prosthetic valve **2042**. When prosthetic valve **2042** is deployed, and expands within opening **3064**, element **3062** is disposed in the groove, thereby further facilitating coupling of the stabilizing element to the prosthetic valve, e.g., by inhibiting axial movement of the prosthetic valve through the opening **3064**.

(571) Reference is made to FIGS. **76A-E**, which are schematic illustrations of steps in the implantation of implant **2030h**, comprising prosthetic valve **2042** and prosthetic valve support **2040h**, in a native heart valve, such as mitral valve **2024** of a subject, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040h** comprises, and/or is analogous to, other prosthetic valve supports described herein. Prosthetic valve support **2040h** comprises upstream support portion **2041** and clips **2900**, and typically comprises, and/or is analogous to prosthetic valve support **2040b**. FIGS. **76A-E** show steps in the transapical implantation of implant **2030h**.

(572) FIG. **76A** shows support **2040h** being delivered, using support-delivery apparatus **2970**, via the apex of the heart, to left ventricle **2028** of the subject. During delivery, portion **2041** is disposed, in the compressed configuration thereof, within an overtube **2972** of the delivery apparatus. Typically, portion **2041** is disposed within a delivery tube **2976**, which itself is disposed within the overtube.

(573) FIG. **76B** shows clips **2900** in the open configuration thereof, and coupled to a scaffold, such as core **2974**. Clips **2900** are typically operated and coupled to native leaflets **2082** as described hereinabove, mutatis mutandis. Upstream support portion **2041** is advanced, in the compressed configuration thereof, such that upstream end **2055** is upstream of downstream end **2053**. Upstream end **2055** of portion **2041** is advanced between native leaflets **2082**. Typically, coupling clips **2900** to leaflets **2082** automatically advances at least part of portion **2041** (e.g., upstream end **2055**) between the native leaflets. FIG. **76C** shows clips **2900** in the closed configuration thereof, coupled to native leaflets **2082**.

(574) After clips **2900** have been coupled to native leaflets **2082**, delivery tube **2976** is withdrawn distally (e.g., atrially) from upstream support portion **2041**, such that downstream end **2053** of portion **2041** is exposed, and expands to define inner perimeter **2068** as described hereinabove, mutatis mutandis. As successively more distal (e.g., upstream) parts of portion **2041** are exposed as they exit delivery tube **2976**, they expand (e.g., radially). When portion **2041** is sufficiently exposed from the delivery tube (e.g., when upstream end **2055** is exposed from the delivery tube), upstream end **2055** expands to define outer perimeter **2068**, as described hereinabove, mutatis mutandis. As shown in FIG. **76D**, support **2040h** thereby assumes its implanted configuration, as described hereinabove, whereby clips **2900** are coupled to the native leaflets, and upstream support portion **2041** is disposed against the upstream side of the native valve (e.g., the upstream side of the native valve annulus). Delivery tube **2976** is subsequently withdrawn from atrium **2026** via opening **2045** of upstream support portion **2041**, and support-delivery apparatus **2970** (including delivery tube **2976**) is withdrawn from the body of the subject.

(575) FIG. **76E** shows prosthetic valve **2042** being coupled to support **2040h** (i.e., implanted). Prosthetic valve **2042** is delivered transapically, to ventricle **2028** of the subject. During delivery, prosthetic valve **2042** is disposed, in a compressed configuration thereof, within a delivery tube **2986** of the delivery apparatus. The delivery tube containing the prosthetic valve is disposed in opening **2045** of upstream support portion **2041**. The delivery tube is subsequently withdrawn proximally (e.g., ventricularly) from prosthetic valve **2042**, such that the upstream end of the prosthetic valve is exposed. As successively more proximal (e.g., downstream) parts of prosthetic valve **2042** are exposed as they exit delivery tube **2986**, they expand (e.g., radially). When prosthetic valve **2042** is sufficiently exposed from the delivery tube, the prosthetic valve engages inner

perimeter **2068** of upstream support portion **2041** of support **2040h**, and couples the prosthetic valve thereto, as described hereinabove, *mutatis mutandis*.

(576) Once prosthetic valve **2042** is completely exposed (e.g., deployed), the prosthetic valve thereby assumes its implanted configuration, as described hereinabove. Support-delivery apparatus **2980** (including delivery tube **2986**) is subsequently withdrawn from the body of the subject.

(577) Reference is made to FIGS. **77-80**, which are schematic illustrations of implants, each comprising a prosthetic valve support and a prosthetic valve, implanted at native valves of a heart **2020** of a subject, in accordance with some applications of the invention. FIGS. **77-80** are not intended to limit the scope of the invention, but to indicate some placements of the implants with respect to the anatomy of the heart and/or native valve, and to illustrate commonalities between such placements. Other prosthetic valves and prosthetic valve supports described herein may be implanted at the native valves, as described with reference to FIGS. **77-80**, *mutatis mutandis*.

(578) FIG. **77** shows implant **2030d**, comprising a prosthetic valve support **2040d** and a prosthetic valve **2042d**, implanted at mitral valve **2024** of heart **2020** of a subject, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040d** comprises, and/or is analogous to, other prosthetic valve supports described herein, and implant **2030d** comprises, and/or is analogous to, other implants described herein. Implant **2030d** (e.g., support **2040d** and prosthetic valve **2042d**) are configured (e.g., dimensioned) to be implanted at mitral valve **2024**. Implant **2030d** is typically implanted at mitral valve **2024** as described elsewhere herein (e.g., with reference to FIGS. **74A-L** and/or **76A-E**). An upstream support portion **2041d** of support **2040d** is disposed against the upstream (i.e., atrial) side of mitral valve **2024**, and is coupled to the native valve, e.g., using clips or another support-anchoring element. Prosthetic valve **2042d** is disposed and expanded in the opening defined by portion **2041d**, thereby traversing the annulus of the native valve.

(579) FIG. **78** shows implant **2030e**, comprising a prosthetic valve support **2040e** and a prosthetic valve **2042e**, implanted at tricuspid valve **2010** of heart **2020** of a subject, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040e** comprise, and/or is analogous to, other prosthetic valve supports described herein, and implant **2030e** comprises, and/or is analogous to, other implants described herein. Implant **2030e** (e.g., support **2040e** and prosthetic valve **2042e**) are configured (e.g., dimensioned) to be implanted at tricuspid valve **2010**. For example, and as shown in FIG. **78**, an upstream support portion **2041e** of support **2040e** typically defines a concavity **2121**, configured to be oriented toward the atrioventricular (AV) node, so as to reduce a likelihood of support **2040e** interfering with electrical activity of the heart. Upstream support portion **2041e** of support **2040e** is disposed against the upstream (i.e., atrial) side of tricuspid valve **2010**, and is coupled to the native valve, e.g., using clips or another support-anchoring element. Prosthetic valve **2042e** is disposed and expanded in the opening defined by portion **2041e**, thereby traversing the annulus of the native valve.

(580) FIG. **79** shows implant **2030f**, comprising a prosthetic valve support **2040f** and a prosthetic valve **2042f**, implanted at pulmonary valve **2012** of heart **2020** of a subject, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040f** comprises, and/or is analogous to, other prosthetic valve supports described herein, and implant **2030f** comprises, and/or is analogous to, other implants described herein. Implant **2030f** (e.g., support **2040f** and prosthetic valve **2042f**) are configured (e.g., dimensioned) to be implanted at pulmonary valve **2012**. For example, and as shown in FIG. **79**, an outer perimeter of upstream support portion **2041f** of support **2040f** may be dimensioned to be small enough to fit within the downstream portion of right ventricle **2013**, but large enough to inhibit movement of implant **2030f** downstream through the pulmonary valve. Upstream support portion **2041f** of support **2040f** is disposed against the upstream (i.e., ventricular) side of pulmonary valve **2012**, and is coupled to the native valve, e.g., using clips or another support-anchoring element. Prosthetic valve **2042f** is disposed and expanded in the opening defined by portion **2041f**, thereby traversing the annulus of the native valve.

(581) FIG. **80** shows implant **2030g**, comprising a prosthetic valve support **2040g** and a prosthetic valve **2042g**, implanted at aortic valve **2014** of heart **2020** of a subject, in accordance with some applications of the invention. For some applications of the invention, prosthetic valve support **2040g** comprises, and/or is analogous to, other prosthetic valve supports described herein, and implant **2030g** comprises, and/or is analogous to, other implants described herein. Implant **2030g** (e.g., support **2040g** and prosthetic valve **2042g**) are configured (e.g., dimensioned) to be implanted at aortic valve **2014**. For example, and as shown in FIG. **80**, an outer perimeter of upstream support portion **2041g** of support **2040g** may be dimensioned to be

sufficiently large to inhibit movement of implant **2030g** downstream through the aortic valve, and/or prosthetic valve **2042g**, and prosthetic valve **2042g** may be dimensioned to reduce a likelihood of interference with (e.g., reduction of) blood flow into the coronary arteries of the subject. Upstream support portion **2041g** of support **2040g** is disposed against the upstream (i.e., ventricular) side of aortic valve **2014**, and is coupled to the native valve, e.g., using clips or another support-anchoring element. Prosthetic valve **2042g** is disposed and expanded in the opening defined by portion **2041g**, thereby traversing the annulus of the native valve.

(582) Reference is again made to FIGS. **77-80**. It is thereby to be noted that although some apparatus and methods are described herein to facilitate replacement of a native mitral valve of the subject, apparatus (and subcomponents thereof) and methods described herein may also be used to replace a native cardiac valve other than the native mitral valve, such as the tricuspid valve, the aortic valve, and the pulmonary valve.

(583) Reference is again made to FIGS. **1A-80**. For each of the prosthetic valve supports described, at least a part of the prosthetic valve support circumscribes (e.g., encloses on all lateral sides) a space. For example, the upstream support portions and stabilizing elements described hereinabove, define respective openings (e.g., apertures). These openings are thereby spaces that the upstream support portions and stabilizing elements circumscribe.

(584) For some applications of the invention, following implantation at the native valve, no part of the prosthetic valve support that circumscribes a space, traverses the native leaflets and/or annulus. For example, following implantation, the upstream support portions described hereinabove (e.g., upstream support portions **41** and **2041**) are typically disposed only upstream of the native leaflets and/or annulus. Similarly, for applications in which the prosthetic valve support comprises a stabilizing element (e.g., stabilizing element **1062** or **3062**), following implantation, the stabilizing element is typically disposed only downstream to the native leaflets and/or annulus. It is hypothesized that this advantageously facilitates continued function of the native leaflets following implantation of the prosthetic valve support, and prior to the implantation of a prosthetic valve, as described hereinabove.

(585) Typically, the perimeter (e.g., the circumference) of the spaces defined by the upstream support portions and stabilizing elements described hereinabove, is greater than 60 mm. Typically, the upstream support portions and stabilizing elements have respective heights of less than 10 mm. For some applications of the invention, no part of the prosthetic valve support that circumscribes a space that has a perimeter that is greater than 60 mm, has a height (e.g., a depth) that is greater than 10 mm. For example, prosthetic valve supports that do not comprise a cylindrical element (e.g., cylindrical element **90** or **690**), do not comprise a part that (1) circumscribes a space that has a perimeter that is greater than 60 mm, and (2) has a height (e.g., a depth) that is greater than 10 mm.

(586) Reference is again made to FIGS. **1A-80**. It is to be noted that the apparatus and techniques described hereinabove are not limited to the combinations described hereinabove. For example: (1) Any of the prosthetic valves described hereinabove (including features and/or components thereof) may be used in combination with any of the prosthetic valve supports (including features and/or components thereof) described hereinabove (e.g., any of the prosthetic valve supports described hereinabove may be used to facilitate implantation of any of the prosthetic valves described hereinabove), mutatis mutandis; (2) any of the prosthetic valve supports described hereinabove may comprise any of the upstream support portions, tissue-engaging elements (e.g., support-anchoring elements and/or clips), connectors (e.g., flexible and/or length-adjustable connectors), holding wires and/or stabilizing elements described hereinabove, mutatis mutandis; (3) any of the prosthetic valves or prosthetic valve supports described hereinabove may comprise any of the coupling functionalities (e.g., barbs, coupling leads and/or support-engaging elements) described hereinabove, for coupling a prosthetic valve support (e.g., support-anchoring elements thereof) to a prosthetic valve, mutatis mutandis; (4) any of the tissue-engaging elements, and/or elements thereof, described hereinabove may be used in combination with any one of prosthetic valve supports or prosthetic valves described herein, mutatis mutandis. For example, tissue-engaging elements (e.g., support-anchoring elements) that are described hereinabove for coupling a prosthetic valve support to the native valve, may be alternatively or additionally used to couple a prosthetic valve to the native valve (the tissue-engaging element thereby acting as a valve-anchoring element), mutatis mutandis. Similarly, tissue-engaging elements (e.g., valve-anchoring elements) that are described hereinabove for coupling a prosthetic valve to the native valve, may be alternatively or additionally used to couple a prosthetic valve support to the native valve (the tissue-engaging element thereby acting as a support-anchoring element), mutatis mutandis; (5) any of the implantation techniques described hereinabove (e.g., those described with reference to FIGS. **1A-H**, **15A-E**, **16**, **28A-30B**, **37A-H**, **38A-H**, **50**, **74A-L**, **75A-D** and **76A-F**) may be used in combination with any of the

implants (e.g., any of the prosthetic valves and/or prosthetic valve supports) described hereinabove, mutatis mutandis; (6) any of the delivery apparatus described hereinabove (e.g., those described with reference to FIGS. 9A-E, 27A-D, 31A-33C, 37A-H, 38A-H, 62A-D, 63A-B, 64A-67B and 74A-L) may be used to facilitate delivery of any of the implants (e.g., any of the prosthetic valves and/or prosthetic valve supports) described hereinabove, mutatis mutandis; and (7) any of the techniques and apparatus described hereinabove (e.g., those described with reference to FIGS. 9A-F, 25A-E, 27A-D, and 68A-69E), for retrieval of a prosthetic valve or prosthetic valve support, may be used in combination with (e.g., may be used to retrieve) any of the prosthetic valves and/or prosthetic valve supports described hereinabove, mutatis mutandis.

(587) Reference is again made to FIGS. 1A-80. It is to be noted that for some applications of the present invention that comprise tissue-engaging elements 62, movement of tissue-engaging elements 62 from their constrained configuration to their unconstrained configuration during deployment, comprises movement of over 180 degrees. For some applications, tissue-engaging elements, comprising valve-anchoring elements, move from a constrained configuration distal to the primary structural element of the prosthetic valve, to an unconstrained configuration wherein a portion of each valve-anchoring element is disposed inside the generally-cylindrical structure of the primary structural element of the prosthetic valve (e.g., valve-anchoring elements protrude through voids defined by the lattice structure of the primary structural element).

(588) Reference is again made to FIGS. 1A-80. For some applications of the invention, apparatus such as the prosthetic valves and/or prosthetic valve supports described hereinabove (e.g., the primary structural elements, upstream support portions, and tissue-engaging elements thereof), are covered at least in part with a covering. The covering may comprise polyethylene terephthalate (e.g., polyester), polytetrafluoroethylene (e.g., Teflon, ePTFE), a fabric, and/or or pericardial tissue. Typically, a thickness of the covering is less than 0.2 mm, e.g., less than 0.1 mm, or less than 0.05 mm. The covering may be selected according to requirements. For example, for some applications, a surface of the apparatus that is placed in contact with the native valve is covered; the covering being configured to facilitate coupling of the prosthetic valve support to the native valve, by enhancing tissue growth at the interface between the prosthetic valve support and the native valve. Conversely, for some applications, the covering may be configured to inhibit tissue growth thereon. For some applications, a surface of the apparatus is covered with the covering so as to inhibit (e.g., prevent) leakage of blood between the prosthetic valve and the native valve, and/or between the prosthetic valve and the prosthetic valve support.

(589) For some applications, the prosthetic valve support (e.g., the upstream support portion thereof) is not covered with the covering, and is configured to allow flow of blood therethrough. For example, the prosthetic valve support may be configured to allow flow of blood through the interface between the valve support and the prosthetic valve, in order to accommodate antegrade flow of blood between the subject's atrium and the subject's ventricle that is greater than can be accommodated by blood flowing through the prosthetic valve alone. For some such application of the invention, the prosthetic valve support is not covered with the covering and is configured to support prosthetic valve, such that the leaflets of the native valve (1) move in response to the beating of the heart, (2) coapt with each other and/or with the primary structural element of the prosthetic valve, and (3) inhibit (e.g., prevent) retrograde flow of blood through the prosthetic valve support.

(590) Reference is yet again made to FIGS. 1A-80. It is to be noted that although some apparatus and methods are described herein to replace a native heart valve (e.g., a native mitral valve) of the subject, apparatus (and subcomponents thereof) and methods described herein may also be used at any other site in the body of the subject. For example, delivery apparatus and/or locks described herein may be used to facilitate implantation and/or adjustment of any suitable implant at a given implantation site of a body of the subject, e.g., the stomach.

(591) Reference is made to FIGS. 1A-80. It is to be noted that for some applications of the present invention, medical device 150 comprises an implant that comprises a prosthetic valve support and a prosthetic valve. For other applications, medical device 150 comprises a prosthetic valve support. For yet other applications, medical device 150 comprises a prosthetic valve.

(592) Reference is again made to FIGS. 1A-80. It is to be noted that at least some of the tissue-engaging elements that are described herein as adjustable (e.g., length-adjustable), may be adjusted prior to implantation, during the implantation procedure, or following implantation.

(593) It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove, as well as variations and

modifications thereof that are not in the prior art, which would occur to persons skilled in the art upon reading the foregoing description.

Claims

1. A method, comprising: (A) transcatheterally advancing, toward a native heart valve of a heart of a patient, in a proximal to distal direction, apparatus comprising: (a) a first atrial arm and a first ventricular arm on a first side of a central longitudinal axis of the apparatus; (b) a second atrial arm and a second ventricular arm on a second side of the central longitudinal axis of the apparatus; and (c) a core, (i) the first atrial arm, the first ventricular arm, and a first articulation site of the first atrial arm and the first ventricular arm, being on a first side of the core, and (ii) the second atrial arm, the second ventricular arm, and a second articulation site of the second atrial arm and the second ventricular arm, being on a second side of the core; (B) subsequently, preparing the apparatus to (i) clamp a first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm, and (ii) clamp a second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm by: distally moving the first ventricular arm with respect to the central longitudinal axis by applying, via a distal opening in the core, a pulling force to the first ventricular arm at a first fixed connection point that is at a portion of the first ventricular arm that is farthest from the first articulation site of the first atrial arm and the first ventricular arm; and distally moving the second ventricular arm with respect to the central longitudinal axis by applying, via the distal opening in the core, a pulling force to the second ventricular arm at a second fixed connection point that is at a portion of the second ventricular arm that is farthest from the second articulation site of the second atrial arm and the second ventricular arm; and (C) subsequently: clamping the first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm; and clamping the second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm.
2. The method according to claim 1, wherein the steps of clamping the first native leaflet and clamping the second native leaflet comprise forming the first and second native leaflets into a generally lemniscate arrangement.
3. The method according to claim 1, wherein the steps of clamping the first native leaflet and clamping the second native leaflet are performed in a manner that does not eliminate native blood flow regulation functionality of the native heart valve.
4. The method according to claim 1, wherein distally moving the first ventricular arm comprises distally moving the first ventricular arm while the first atrial arm is held in place, and distally moving the second ventricular arm comprises distally moving the second ventricular arm while the second atrial arm is held in place.
5. The method according to claim 1, wherein distally moving the first ventricular arm and distally moving the second ventricular arm comprises simultaneously distally moving the first ventricular arm and distally moving the second ventricular arm.
6. The method according to claim 1, wherein distally moving the first and second ventricular arms comprises distally moving the first and second ventricular arms while the first and second ventricular arms and the first and second atrial arms are disposed in an atrium of the heart.
7. The method according to claim 6, further comprising, subsequently to the steps of distally moving the first and second ventricular arms and before the steps of clamping the first native leaflet and clamping the second native leaflet: moving the first and second ventricular arms into a ventricle of the heart.
8. The method according to claim 1, wherein: applying the pulling force to the first ventricular arm at the first fixed connection point comprises applying the pulling force to the first ventricular arm via a conduit in the core, and applying the pulling force to the second ventricular arm at the second fixed connection point comprises applying the pulling force to the second ventricular arm via the conduit in the core.
9. The method according to claim 1, wherein distally moving the first and second ventricular arms comprises distally moving the first and second ventricular arms while the first and second atrial arms are held in place adjacent to the core.
10. The method according to claim 1, further comprising, subsequently to the steps of distally moving the first and second ventricular arms: advancing at least the first and second ventricular arms and the distal end of the core into a ventricle of the heart; and subsequently, raising the first and second ventricular arms toward the central longitudinal axis.
11. The method according to claim 1, wherein the core has: (1) a first portion having a first perimeter in a first

plane to a central longitudinal axis of the core, and (2) a second portion having a second perimeter in a second transverse plane to the central longitudinal axis of the core that is distal to the first transverse plane, the second perimeter being a smallest perimeter of the core.

12. The method according to claim 11, wherein the first and second articulation sites are adjacent to the smallest perimeter of the core.

13. The method according to claim 11, wherein the core tapers in a distal direction from the first portion to the second portion of the core, and wherein the tapering of the core defines a minimum nonzero angle of the first and second atrial arms with respect to the central longitudinal axis.

14. The method according to claim 1, wherein: the core is shaped so as to define a conduit therethrough, and the method further comprises controlling the first and second ventricular arms using an elongate controller that is slidably disposed within the conduit.

15. The method according to claim 14, wherein controlling the first and second ventricular arms using the elongate controller comprises controlling the first and second ventricular arms using the elongate controller while not controlling the first and second atrial arms using the elongate controller.

16. The method according to claim 14, wherein the elongate controller comprises a control rod.

17. A method, comprising: (A) transcatheterally advancing, toward a native heart valve of a heart of a patient, in a proximal to distal direction, apparatus comprising: (a) a first atrial arm and a first ventricular arm on a first side of a central longitudinal axis of the apparatus; (b) a second atrial arm and a second ventricular arm on a second side of the central longitudinal axis of the apparatus; and (c) a core, (i) the first atrial arm, the first ventricular arm, and a first articulation site of the first atrial arm and the first ventricular arm, being on a first side of the core, and (ii) the second atrial arm, the second ventricular arm, and a second articulation site of the second atrial arm and the second ventricular arm, being on a second side of the core; (B) subsequently, preparing the apparatus to (i) clamp a first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm, and (ii) clamp a second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm by: distally moving the first ventricular arm with respect to the central longitudinal axis by applying a pulling force to the first ventricular arm at a first fixed connection point that is at a portion of the first ventricular arm that is farthest from the first articulation site of the first atrial arm and the first ventricular arm; and distally moving the second ventricular arm with respect to the central longitudinal axis by applying a pulling force to the second ventricular arm at a second fixed connection point that is at a portion of the second ventricular arm that is farthest from the second articulation site of the second atrial arm and the second ventricular arm; and (C) subsequently: clamping the first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm; and clamping the second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm, wherein distally moving the first and second ventricular arms comprises distally moving the first and second ventricular arms while the first and second ventricular arms, the first and second atrial arms, and a distal end of the core are disposed in an atrium of the heart.

18. A method, comprising: (A) transcatheterally advancing, toward a native heart valve of a heart of a patient, in a proximal to distal direction, apparatus comprising: (a) a first atrial arm and a first ventricular arm on a first side of a central longitudinal axis of the apparatus; (b) a second atrial arm and a second ventricular arm on a second side of the central longitudinal axis of the apparatus; and (c) a core, (i) the first atrial arm, the first ventricular arm, and a first articulation site of the first atrial arm and the first ventricular arm, being on a first side of the core, and (ii) the second atrial arm, the second ventricular arm, and a second articulation site of the second atrial arm and the second ventricular arm, being on a second side of the core; (B) subsequently, preparing the apparatus to (i) clamp a first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm, and (ii) clamp a second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm by: distally moving the first ventricular arm with respect to the central longitudinal axis by applying a pulling force to the first ventricular arm at a first fixed connection point that is at a portion of the first ventricular arm that is farthest from the first articulation site of the first atrial arm and the first ventricular arm; and distally moving the second ventricular arm with respect to the central longitudinal axis by applying a pulling force to the second ventricular arm at a second fixed connection point that is at a portion of the second ventricular arm that is farthest from the second articulation site of the second atrial arm and the second ventricular arm; and (C) subsequently: clamping the first native leaflet of the native heart valve between the first atrial arm and the first ventricular arm; and clamping the second native leaflet of the native heart valve between the second atrial arm and the second ventricular arm, wherein preparing the apparatus further comprises positioning the core between the first and second native

leaflets of the native heart valve.

19. The method according to claim 18, wherein positioning the core comprises: positioning the first atrial arm and the first ventricular arm such that the first native leaflet is disposed between the first atrial arm and the first ventricular arm, and positioning the second atrial arm and the second ventricular arm such that the second native leaflet is disposed between the second atrial arm and the second ventricular arm.

20. The method according to claim 19, wherein (1) positioning the first atrial arm and the first ventricular arm and (2) positioning the second atrial arm and the second ventricular arm comprises positioning the first atrial arm and the first ventricular arm and the second atrial arm and the second ventricular arm while a proximal end portion of the core is disposed at an atrial side of the native heart valve and a distal portion of the core is disposed at a ventricular side of the native heart valve.
