

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12398352
B2
August 26, 2025
Fearnot; Neal et al.

Differential pressure material processing systems, apparatus, methods, and products

Abstract

Differential pressure material processing systems, apparatus, methods, and products are described. An example embodiment of a differential pressure material processing system includes a tank, a holding member, and a sheet of tissue disposed within the holding member. The holding member defines a first holding member chamber and a second holding member chamber. The first holding member chamber has a first pressure when a fluid is disposed within the first holding member chamber. The second holding member chamber has a second pressure when a fluid is disposed within the second holding member chamber. The second pressure is different than the first pressure.

Inventors: Fearnot; Neal (West Lafayette, IN), Robbins; Sarah (Lafayette, IN), Buhrmester; Marc (Dayton, IN), Krieger; Joshua (Topsfield, MA), Converse; Gabriel (Lafayette, IN)

Applicant: Cook Medical Technologies LLC (Bloomington, IN); Muffin Incorporated (West Lafayette, IN)

Family ID: 1000008781422

Assignee: Cook Medical Technologies LLC (Bloomington, IN); Muffin Incorporated (West Lafayette, IN)

Appl. No.: 17/291757

Filed (or PCT Filed): November 08, 2019

PCT No.: PCT/US2019/060429

PCT Pub. No.: WO2020/097436

PCT Pub. Date: May 14, 2020

Prior Publication Data

Related U.S. Application Data

us-provisional-application US 62757783 20181109

Publication Classification

Int. Cl.: C12M3/00 (20060101); C12M1/00 (20060101); C12M1/34 (20060101)

U.S. Cl.:

CPC C12M21/08 (20130101); C12M23/44 (20130101); C12M23/46 (20130101);
C12M29/00 (20130101); C12M41/40 (20130101);

Field of Classification Search

CPC: C12M (21/08); C12M (35/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4804628	12/1988	Cracauer et al.	N/A	N/A
6048723	12/1999	Banes	435/305.4	C12M 35/04
6060306	12/1999	Flatt	435/297.2	C12M 23/34
8507266	12/2012	Welter et al.	N/A	N/A
2004/0191906	12/2003	Holzer	435/383	C12M 35/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004009757	12/2003	WO	N/A

OTHER PUBLICATIONS

Australian Examination Report No. 1 for standard patent application, Application No. 2019377857, dated Aug. 4, 2022. cited by applicant

PCT Search Report and Written Opinion, Application No. PCT/US2019/060429, dated Mar. 25, 2020. cited by applicant

Australian Examination report No. 2, Application No. 2019377857, dated Jan. 19, 2023. cited by applicant

Primary Examiner: Hurst; Jonathan M

Attorney, Agent or Firm: MacMillan, Sobanski & Todd, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of U.S. Provisional Application No. 62/757,783, filed on Nov. 9, 2018. The entire disclosure of this related application is hereby incorporated by reference into this disclosure.

FIELD

(1) The disclosure relates generally to the field of material processing for manufacturing and/or assembly environments. More particularly, the disclosure relates to differential pressure material processing systems, apparatus, methods, and products. Specific examples described herein relate to differential pressure tissue fixation useful in the manufacture of medical devices.

BACKGROUND

(2) Generally, tissue fixation for medical products is utilized to preserve the properties of the tissue, such as mechanical properties, through cross-linking during chemical fixation, for example, and to render the tissue relatively inert for use in implantation. Currently, differential pressure processing systems are used to fix heart valves that include a tubular wall and valve leaflets. These systems allow fluid to flow through the tubular wall and past the valve during the fixation process, which presents significant drawbacks for processing other types of tissue. For example, current systems are passive and fail to maintain control of the forces exerted on the tissue over time or a constant differential pressure across the tissue, which may leak or diffuse fluid during processing as a result of the inherent permeability of the tissue. In addition, current systems fail to provide a mechanism for processing sheets of tissue and for attaching a sheet of tissue to the system without causing deformation during attachment. Highly distensible and low thickness tissues pose unique challenges related to attachment of the tissue to a system for processing. Specifically, due to the very low forces required to cause deformation of these tissues, large deformations can be imparted onto the tissue during attachment, which can impact the mechanical behavior of the tissue after processing. Tissues with highly consistent mechanical properties are desired for medical device manufacturing. Deformations imparted during attachment, uniform or not, can alter the internal stress and strain state and change the collagen configuration of the tissue during processing, often in an unpredictable or unknown manner, resulting in a less constituent material after processing. (3) Therefore, a need exists for new and useful differential pressure material processing systems, apparatus, methods, and products.

SUMMARY OF SELECTED EXAMPLE EMBODIMENTS

(4) Various differential pressure material processing systems, apparatus, methods, and products are described herein.

(5) An example differential pressure material processing system for processing tissue using a fluid comprises a tank and a holding member. The tank defines a first portion and a second portion. The holding member includes a loading member and a clamping member releasably attached to the loading member. The holding member defines a first holding member chamber in fluid communication with the first portion of the tank, a second holding member chamber in fluid communication with the second portion of the tank, and a passageway in fluid communication with the first holding member chamber and the second holding member chamber. The fluid has a first pressure when disposed within the first portion of the tank and the first holding member chamber. The fluid has a second pressure when disposed within the second portion of the tank and the second holding member chamber. The second pressure is different than the first pressure. The tissue is disposed between the loading member and the clamping member such that a portion of the tissue spans an entire cross-section of the passageway to obstruct the passageway defined by the holding member.

(6) An example method of loading a sheet of tissue comprises: positioning a sheet of tissue on a loading member such that a portion of the sheet of tissue is separated from the loading member by a fluid layer disposed between the portion of the sheet of tissue and the loading member; adjusting the position of the sheet of tissue; positioning a clamping member on the loading member; and

releasably attaching the clamping member to the loading member such that the sheet of tissue is disposed between the clamping member and the loading member and contacts the loading member.

(7) An example method of processing tissue comprises: adjusting the position of a first tank relative to a second tank and a holding member along a vertical axis, the holding member has tissue disposed between a loading member and a clamping member; connecting the first tank to a pump such that the first portion of the first tank is in fluid communication with the pump; connecting the second tank to the pump such that the first portion of the second tank is in fluid communication with the pump; connecting the first tank to a holding member such that the first portion of the first tank is in fluid communication with the holding member; connecting the second tank to the holding member such that the first portion of the second tank is in fluid communication with the holding member; connecting the first tank to a reservoir such that the first tank is in fluid communication with the reservoir; connecting the second tank to the reservoir such that the second tank is in fluid communication with the reservoir; connecting the pump to the reservoir such that the pump is in fluid communication with the reservoir; introducing fluid into the tank; opening a vent on the loading member; opening a vent on the clamping member; activating the pump; introducing fluid into reservoir while the pump is in an on state; closing the vent on the loading member; closing the vent on the clamping member; maintaining the pump in the on state for a period of time such that a differential pressure is applied to the tissue; deactivating the pump; draining the holding member; disassembling the holding member; removing the clamping member; removing the tissue from the loading member; placing the tissue in a fluid for a period of time.

(8) Additional understanding of the example differential pressure material processing systems, apparatus, methods, and products can be obtained by review of the detailed description, below, and the appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of an example differential pressure material processing system.
- (2) FIG. 2 is a bottom view of the tank of the system illustrated in FIG. 1.
- (3) FIG. 3 is a front view of a sheet of tissue that can be positioned within the holding member of the system illustrated in FIG. 1.
- (4) FIG. 4 is an exploded perspective view of the holding member of the system illustrated in FIG. 1.
- (5) FIG. 5 is an exploded perspective view of the holding member and sheet of tissue of the system illustrated in FIG. 1.
- (6) FIG. 6 is a perspective view of another example differential pressure material processing system.
- (7) FIG. 7 is a perspective view of the first tank of the system illustrated in FIG. 6.
- (8) FIG. 8 is a top view of the second tank of the system illustrated in FIG. 6.
- (9) FIG. 9 is a perspective view of the second tank illustrated in FIG. 8.
- (10) FIG. 10 is a perspective view of the holding member of the system illustrated in FIG. 6.
- (11) FIG. 11 is another perspective view of the holding member illustrated in FIG. 10.
- (12) FIG. 12 is an exploded perspective view of the holding member illustrated in FIG. 10.
- (13) FIG. 13 is another exploded perspective view of the holding member illustrated in FIG. 10.
- (14) FIG. 14 is a perspective view of the loading member and the clamping member of the system illustrated in FIG. 6.
- (15) FIG. 15 is an exploded perspective view of the loading member and the clamping member illustrated in FIG. 14.
- (16) FIG. 16 is another exploded perspective view of the loading member and the clamping

member illustrated in FIG. 14.

(17) FIG. 17 is a perspective view of another example differential pressure material processing system.

(18) FIG. 18 is a front view of the holding member of the system illustrated in FIG. 17.

(19) FIG. 19 is a perspective view of another example differential pressure material processing system.

(20) FIG. 20 is a perspective view of the holding member of the system illustrated in FIG. 19.

(21) FIG. 21 is another perspective view of the holding member illustrated in FIG. 20.

(22) FIG. 22 is an exploded perspective view of the holding member illustrated in FIG. 20.

(23) FIG. 23 is a perspective view of the loading member of the system illustrated in FIG. 19.

(24) FIG. 24 is another perspective view of the loading member illustrated in FIG. 23.

(25) FIG. 25 is a perspective view of the clamping member of the system illustrated in FIG. 19.

(26) FIG. 26 is a schematic illustration of an example method of loading tissue into a holding member.

(27) FIG. 27 is a partial sectional view of a sheet of tissue positioned on a loading member.

(28) FIG. 28 is a partial sectional view of a sheet of tissue positioned between a clamping member and a loading member.

(29) FIG. 29 is a schematic illustration of another example method of loading tissue into a holding member.

(30) FIG. 30 illustrates a loading member positioned on a surface of a table.

(31) FIG. 31 is a schematic illustration of another example method of loading tissue into a holding member.

(32) FIG. 32 illustrates an example loading member disposed on an example loading tool.

(33) FIG. 33 is an exploded view of the loading member and loading tool illustrated in FIG. 32.

(34) FIG. 33A is a perspective view of the base of the loading tool illustrated in FIG. 32.

(35) FIG. 34 is a perspective view of the cap of the loading tool illustrated in FIG. 32.

(36) FIG. 35 is a schematic illustration of an example method of processing tissue.

(37) FIG. 35A is a partial sectional view of a sheet of tissue prior to the application of differential pressure.

(38) FIG. 35B is a partial sectional view of a sheet of tissue that is being processed under differential pressure.

(39) FIG. 36 is a schematic illustration of another example method of processing tissue.

(40) FIG. 37 is a schematic illustration of another example method of processing tissue.

(41) FIG. 38 is a schematic illustration of another example method of processing tissue.

(42) FIG. 39 is a graphical representation of a load response over time in the x-axis of tissue fixed in a fixative using current processing techniques.

(43) FIG. 40 is a graphical representation of a load response over time in the y-axis of tissue fixed in a fixative using currently available processing techniques.

(44) FIG. 41 is a graphical representation of a load response over time in the x-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 0.25 millimeters of mercury.

(45) FIG. 42 is a graphical representation of a load response over time in the y-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 0.25 millimeters of mercury.

(46) FIG. 43 is a graphical representation of a load response over time in the x-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 0.5 millimeters of mercury.

(47) FIG. 44 is a graphical representation of a load response over time in the y-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 0.5 millimeters of mercury.

- (48) FIG. **45** is a graphical representation of a load response over time in the x-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 1.0 millimeter of mercury.
- (49) FIG. **46** is a graphical representation of a load response over time in the y-axis of tissue fixed in a fixative using the differential pressure material processing systems and methods described herein. The differential pressure applied to the tissue is 1.0 millimeter of mercury.
- (50) FIG. **47** is a perspective view of an alternative holding member that can be used in a differential pressure material processing system.
- (51) FIG. **48** is an exploded view of the holding member illustrated in FIG. **47**.
- (52) FIG. **49** is a sectional view of the holding member illustrated in FIG. **48**. The support member of the loading member is in a first position.
- (53) FIG. **50** is another sectional view of the holding member illustrated in FIG. **48**. The support member of the loading member is in a first position.
- (54) FIG. **51** is another sectional view of the holding member illustrated in FIG. **48**. The support member of the loading member is in a second position.
- (55) FIG. **52** is a magnified view of area I-I illustrated in FIG. **51**.

DETAILED DESCRIPTION

- (56) The following detailed description and the appended drawings describe and illustrate various example embodiments of differential pressure material processing systems, apparatus, methods, and products. The description and illustration of these examples are provided to enable one skilled in the art to make and use a differential pressure material processing system, an apparatus, to practice a method of using a differential pressure material processing system, and to create a product. They are not intended to limit the scope of the claims in any manner.
- (57) FIGS. **1**, **2**, **3**, **4**, and **5** illustrate a first example differential pressure material processing system **10** that can be used to process tissue using a fluid. The differential pressure material processing system **10** includes a tank **12**, a holding member **14**, a pump **16**, and a sheet of tissue **18** disposed within the holding member **14**.
- (58) The tank **12** has a main body **22** that defines a first non-permeable wall **24**, a second non-permeable wall **26**, a first recess **28**, a second recess **30**, a third recess **32**, a first passageway **34** in communication with the first recess **28**, a second passageway **36** in communication with the first recess **28**, a third passageway **38** in communication with the second recess **30**, and a fourth passageway **40** in communication with the third recess **32**. The first recess **28** defines a first portion of the tank **12**. When fluid is disposed within the first recess **28** to a level at which the fluid has a height greater than the height of the first non-permeable wall **24** and the fluid flows into the second recess **30** the fluid has a first pressure creating a high-pressure portion **42** of the tank **12**. The second recess **30** defines a second portion of the tank **12**. When fluid is disposed within the second recess **30** to level at which the fluid has a height greater than the height of the second non-permeable wall **26** and the fluid flows into the third recess **32** the fluid has a second pressure that is less than the first pressure creating a low-pressure portion **44** of the tank **12**. The third recess **32** defines a tank reservoir **46** that is in fluid communication with the inlet port **108** of the pump **16**, as described in more detail herein. The third recess **32** defines a third portion of the tank **12**. Each of the first passageway **34** and the second passageway **36** extends through the main body **22** and provides access between the first recess **28** and an environment exterior to the first recess **28**. The third passageway **38** extends through the main body **22** and provides access between the second recess **30** and an environment exterior to the second recess **30**. The fourth passageway **40** extends through the main body **22** and provides access between the third recess **32** and an environment exterior to the third recess **32**. An attachment member **41** is attached to the tank **12** within each of the passageways **34**, **36**, **38**, and **40** and provides a mechanism to attach the tank **12** to another component, such as the holding member **14** and/or pump **16**, as described in more detail herein.
- (59) When a fluid is disposed within the recesses **28**, **30**, **32** defined by the tank **12**, the pressure

differentiation of the fluid within the first and second recesses **28, 30** can be controlled by manipulating the height of the first and second impermeable walls **24, 26**. This can be accomplished by calculating a desired pressure differential and configuring the first and second impermeable walls **24, 26** accordingly. For example, the height of an impermeable wall included in a tank can be manipulated such that modifications to the pressure differential can be imparted on the system by increasing or decreasing the height of an impermeable wall. This can be accomplished by forming an impermeable wall of multiple sections and adding or removing sections and/or by forming a portion of an impermeable wall as a telescoping member.

(60) In the illustrated embodiment, the tank **12** includes a cap **48** that is releasably attached to the main body **22** of the tank **12**. The cap **48** has a main body **50** that defines a vent **52**. A vent **52** can comprise any suitable structure capable of providing fluid communication between the recesses defined by the tank **12** and an environment exterior to the tank **12**. In the illustrated embodiment, the vent **52** comprises a recess **54** that extends from a first edge of the cap **48** into the main body **12** and toward an opposing edge of the cap **48**. However, alternative embodiments can include any suitable vent or can omit the inclusion of a cap. Optionally, in embodiments that include a vent, a vent can be in fluid communication with a filter system and/or a filter could be disposed within the vent to accomplish a closed, or substantially closed, system that can prevent contaminants or particulate from entering the system and provide a mechanism to filter chemical fumes.

(61) A cap can be releasably attached to a main body of a tank using any suitable technique or method of attachment and selection of a suitable technique or method of attachment between a cap and a tank can be based on various considerations, including the material that forms the cap and/or tank. Examples of techniques and methods of attachment considered suitable between a cap and a tank include using threaded connections, snap fit attachments, using one or more connectors, one or more mating slots and projections, one or more sealed unions, tapered attachments, adhesives, and any other technique or method of attachment considered suitable for a particular embodiment. In the illustrated embodiment, the cap **48** is attached to the main body **22** of the tank **12** using two threaded screws **56, 58**. Alternatively, a cap can be positioned on a tank and not be releasably attached to the tank. For example, one or more guide members (e.g., guide pins, guide holes) can be used to position a cap on a tank.

(62) While the tank **12** has been illustrated as including a first non-permeable wall **24** and a second non-permeable wall **26**, a tank can include any suitable number of walls that have any suitable permeability and selection of a suitable number of walls to include in a tank of a differential pressure material processing system and of a suitable permeability for each wall can be based on various considerations, including the intended use of the tank. Examples of numbers of walls considered suitable to include in a tank include one, at least one, two, a plurality, three, four, five, more than five, and any other number considered suitable for a particular embodiment. In embodiments in which a wall is permeable, the wall can have any suitable degree of permeability and can be based on the desired differential pressure intended to be achieved.

(63) The holding member **14** includes a loading member **60**, a clamping member **62** releasably attached to the loading member **60**, and defines a first holding member chamber **64**, a second holding member chamber **66**, a plurality of passageways **68, 70, 72** in communication with the first holding member chamber **64** and second holding member chamber **66**, a first input port **74**, a second input port **76**, a first drain **78**, a second drain **80**, a first vent **82**, and a second vent **84**. In the illustrated embodiment, the loading member **60** has a main body **86** that defines the first holding member chamber **64**, a first portion **88** of each passageway of the plurality of passageways **68, 70, 72**, the first input port **74**, the first drain **78**, the first vent **82**, a first guide member **90**, and a support member **92** spanning each passageway of the plurality of passageways **68, 70, 72**. In the illustrated embodiment, the support member **92** is perforated.

(64) In the illustrated embodiment, the clamping member **62** has a main body **94** that defines the second holding member chamber **66**, a second portion **96** of each passageway of the plurality of

passageways **68, 70, 72**, the second input port **76**, the second drain **80**, the second vent **84**, a second guide member **98**, and a plurality of sealing members **100**. The first portion **88** of each passageway of the plurality of passageways **68, 70, 72** and the second portion **96** of each passageway of the plurality of passageways **68, 70, 72** cooperatively define each passageway of the plurality of passageways **68, 70, 72** of the holding member **14**. A sealing member of the plurality of sealing members **100** surrounds each portion of the passageway of the plurality of passageways **68, 70, 72** defined by the clamping member **62** and provides a mechanism to seal the tissue **18** between the loading member **60** and the clamping member **62** (e.g., prevent leakage around the sealing member **100**) and maintain the position of the tissue **18** during use.

(65) The first input port **74** provides access between the first holding member chamber **64** and an environment exterior to the first holding member chamber **64** and includes an attachment member **75** to provide attachment to an elongate tubular member, as described in more detail herein. The second input port **76** provides access between the second holding member chamber **66** and an environment exterior to the second holding member chamber **66** and includes an attachment member **77** to provide attachment to an elongate tubular member, as described in more detail herein. The first drain **78** provides access between the first holding member chamber **64** and an environment exterior to the first holding member chamber **64** and includes a valve **79** that is moveable between an open configuration and a closed configuration to allow the first holding member **64** to be drained, as described in more detail herein. The second drain **80** provides access between the second holding member chamber **66** and an environment exterior to the second holding member chamber **66** and includes a valve **81** that is moveable between an open configuration and a closed configuration to allow the second holding member **66** to be drained, as described in more detail herein. The first vent **82** provides access between the first holding member chamber **64** and an environment exterior to the first holding member chamber **64** and includes a valve **83** moveable between an open configuration and a closed configuration. The second vent **84** provides access between the second holding member chamber **66** and an environment exterior to the second holding member chamber **66** and includes a valve **85** moveable between an open configuration and a closed configuration.

(66) An attachment member included in a differential pressure material processing system can include any suitable feature, device, or component capable of providing attachment between two components and selection of a suitable attachment member can be based on various considerations, including the type of attachment desired between two components. Examples of suitable attachment members include any suitable connector and/or adapter, threaded connectors, conical connectors (e.g., cones, sockets), connectors with barbed ends, combinations of the attachment members described herein, adhesives, and any other connector and/or adapter considered suitable for a particular embodiment. In the illustrated embodiment, each of the attachment members comprises a connector with a barbed end that is sized and configured to be received within a passageway defined by an elongate tubular member, as described in more detail herein. A valve included in a differential pressure material processing system can include any suitable feature, device, or component capable of moving between an open configuration and a closed configuration and selection of a suitable valve can be based on various considerations, including the material forming a feature, device, or component to which a valve is attached. Examples of suitable valves include butterfly valves, gate valves, globe valves, ball valves, three-way valves, stopcocks, and any other valve considered suitable for a particular embodiment. In the illustrated embodiment, each of the valves comprises a ball valve.

(67) A first guide member and a second guide member included on a holding member can include any suitable feature, device, or component capable of maintaining the position of a loading member relative to a clamping member along an x-axis and a y-axis, as shown in FIGS. **4** and **5**, while the clamping member is being attached to the loading member. For example, a loading member can include a first guide member and the clamping member can include a second guide member that

mates with the first guide member to prevent movement of the loading member relative to the clamping member along the x-axis and the y-axis during releasable attachment of the clamping member to the loading member. It is considered advantageous to include a first guide member and a second guide member to reduce, or eliminate, any unintentional deformation and/or stress imparted on tissue positioned between a loading member and a clamping member. Selection of suitable first and second guide members to include on a holding member can be based on various considerations including the intended use of the holding member. Examples of suitable guide members include a plurality of guide pins and a plurality of guide holes, a first track that is received by a second track, use of one or more magnets, combinations of the guide members described herein, and any other guide member considered suitable for a particular embodiment. In the illustrated embodiment, the first guide member **90** comprises a plurality of guide pins **91** and the second guide member **98** comprises a plurality of guide holes **99**. A guide pin of the plurality of guide pins **91** is disposed within a guide hole of the plurality of guide holes **99** when the holding member **14** is assembled. Each guide hole of the plurality of guide holes **99** is sized and configured to receive a guide pin of the plurality of guide pins **91**.

(68) A support member included on a loading member can comprise any suitable feature, device, or component capable of providing support to tissue intended to be disposed on the member and/or permeability across the material such that a first portion of a passageway defined by a loading member is in fluid communication with a second portion of a passageway defined by a clamping member when tissue is not disposed between the loading member and the clamping member. For example, a support member can be formed by defining a plurality of openings within a material that forms a loading member, attaching a material that defines a plurality of openings to a loading member, or using any other suitable technique or method. A support member included in a differential pressure material processing system can have any suitable rigidity. For example, a support member can have a rigidity that does not deform under the differential pressures applied during processing. In the illustrated embodiment, the support member **92** comprises a plurality of openings **93** defined in the material that forms the loading member **60** such that the remainder of the material that defines the loading member **60** creates a continuous, uninterrupted, surface **95** for positioning tissue, as described in more detail herein. In alternative embodiments, surface **95** of a loading member could be curved and a clamping member could define a mating surface to assist with positioning tissue on a loading member in a resting state, as described in more detail herein.

(69) A sealing member **100** can comprise any suitable feature, device, or component capable of sealing tissue between a loading member and a clamping member when the loading member is releasably attached to the clamping member. Selection of a suitable sealing member to include in a holding member can be based on various considerations, including the intended use of the holding member. Examples of suitable sealing members include forming a portion of a loading member or clamping member as a raised projection, forming a recess in a loading member and/or a clamping member and positioning a gasket (e.g., O-ring) within the recess, and any other sealing member considered suitable for a particular embodiment. In the illustrated embodiment, the sealing member comprises an O-ring disposed within a recess defined by the clamping member **62**. While a sealing member of the plurality of sealing members **100** has been illustrated as surrounding each portion of the passageway of the plurality of passageways **68, 70, 72** defined by the clamping member **62**, alternative embodiments can include a plurality of sealing members such that a sealing member of the plurality of sealing members surrounds each portion of a passageway of a plurality of passageways defined by a loading member. Alternatively, a holding member can include a first plurality of sealing members on a clamping member, as described herein, and a second plurality of sealing members on a loading member, as described herein, that are positioned such that a sealing member of the clamping member mates with a sealing member of the loading member, or such that a sealing member of the clamping member does not contact a sealing member of the loading member, when the clamping member is releasably attached to the loading member.

(70) A loading member and a clamping member can be releasably attached to one another using any suitable technique or method of attachment and selection of a suitable technique or method of attachment between a loading member, or portions of a loading member, and a clamping member, or portions of a clamping member, can be based on various considerations, including the material that forms the loading member and/or the clamping member. Examples of techniques and methods of attachment considered suitable between a loading member, or portions of a loading member, and a clamping member, or portions of a clamping member, include using threaded connections, snap fit attachments, using one or more connectors, one or more mating slots and projections, one or more sealed unions, tapered attachments, external clamps, pneumatic clamping mechanisms, adhesives, and any other technique or method of attachment considered suitable for a particular embodiment. In the illustrated embodiment, the loading member **60** is releasably attached to the clamping member **62** using four threaded screws.

(71) While the holding member **14** has been illustrated as defining a plurality of passageways **68**, **70**, **72**, a holding member can define any suitable number of passageways having any suitable diameter and selection of a suitable number of passageways to define on a holding member and of a suitable diameter for each passageway can be based on various considerations, including the intended use of a holding member and/or the total number of sheets of material intended to be processed by the differential pressure material processing system. Examples of numbers of passageways considered suitable for a holding member to define include one, at least one, two, a plurality, three, four, five, more than five, and any other number considered suitable for a particular embodiment. Examples of diameters considered suitable for each passageway defined by a holding member, or one or more passageways defined by a holding member, include diameters equal to, greater than, less than, or about 50 millimeters, 60 millimeters, 63 millimeters, 70 millimeters, between about 50 millimeters and about 70 millimeters, diameters that are less than the length, width, and/or diameter of a sheet of tissue intended to be disposed between a loading member and a clamping member, diameters that define a passageway that has an area that is less than the area of a sheet of tissue intended to be disposed between a loading member and a clamping member, and any other diameter considered suitable for a particular embodiment.

(72) In the illustrated embodiment, the first recess **28** is in fluid communication with the first holding member chamber **64** such that the high-pressure portion **42** is in fluid communication with the first holding member chamber **64** and the second recess **30** is in fluid communication with the second holding member chamber **66** such that the low-pressure portion **44** is in fluid communication with the second holding member chamber **66**. The fluid within the first holding member chamber **64** has a first pressure and the fluid within the second holding member chamber **66** has a second pressure that is different than the first pressure. In the illustrated embodiment, the first pressure is greater than the second pressure. Any suitable technique or method of accomplishing fluid communication between a recess and a holding member chamber can be utilized and selection of a suitable technique or method can be based on various considerations, including the type of tissue intended to be positioned within a holding member. Examples of techniques and methods considered suitable include using one or more tubular members, manifolds, forming the various features as a single, integrated, unit, and any other technique or method considered suitable for a particular embodiment. In the illustrated embodiment, the first recess **28** is in fluid communication with the first holding member chamber **64** using a first elongate tubular member **102** and the second recess **30** is in fluid communication with the second holding member chamber **64** using a second elongate tubular member **104**. The first elongate tubular member **102** has a first end in fluid communication with the first passageway **34** and a second end in fluid communication with the first input port **74** of the holding member **14**. The second elongate tubular member **104** has a first end in fluid communication with the third passageway **38** and a second end in fluid communication with the second input port **76** of the holding member **14**.

(73) The pump **16** includes an outlet port **106**, an inlet port **108**, and has an on state and an off state. The outlet port **106** is in fluid communication with the first recess **28** such that the high-pressure portion **42** is in fluid communication with the pump **16** and the inlet port **108** is in fluid communication with the tank reservoir **46**. Any suitable technique or method of connecting a recess to a pump can be utilized and selection of a suitable technique or method can be based on various considerations, including the type of tissue intended to be positioned within a holding member. Examples of techniques and methods considered suitable include using one or more tubular members, manifolds, forming the various features as a single, integrated unit, and any other technique or method considered suitable for a particular embodiment. In the illustrated embodiment, the outlet port **106** is in fluid communication with the first recess **28** using a third elongate tubular member **110** and the inlet port **108** is in fluid communication with the third recess **32** using a fourth elongate tubular member **114**. The third elongate tubular member **110** has a first end in fluid communication with the outlet port **106** of the pump **16** and a second end in fluid communication with the second passageway **36** defined by the main body **22** of the tank **12**. The fourth elongate tubular member **114** has a first end in fluid communication with the inlet port **108** and a second end in fluid communication with the fourth passageway **40** defined by the main body **22** of the tank **12**.

(74) Any suitable pump can be included in a differential pressure material processing system and selection of a suitable pump to include in a differential pressure material processing system can be based on various considerations, including the intended use of the system. Examples of pumps considered suitable to include in a differential pressure material processing system include peristaltic pumps, sealed pumps, and any other pump considered suitable for a particular embodiment.

(75) The tissue **18** is disposed within the holding member **14** between the loading member **60** and the clamping member **62** such that each passageway of the plurality of passageways **68, 70, 72**, is obstructed by a portion of the tissue **18** that spans the entire cross section of the passageway defined by the loading member **60** and a clamping member **62**. Depending on the type of processing being completed on the tissue, the tissue **18** can be disposed within the holding member **14** between the loading member **60** and the clamping member **62** such that each passageway of the plurality of passageways **68, 70, 72**, is obstructed by a portion of the tissue **18** that spans the entire cross section of the passageway defined by the loading member **60** and a clamping member **62** prior to the application of differential pressure (e.g., when the pump **16** is in the off state). Alternatively, or in combination with being positioned prior to the application of differential pressure, the tissue **18** can be disposed within the holding member **14** between the loading member **60** and the clamping member **62** such that each passageway of the plurality of passageways **68, 70, 72**, is obstructed by a portion of the tissue **18** that spans the entire cross section of the passageway defined by the loading member **60** and a clamping member **62** during the application of differential pressure (e.g., when the pump **16** is in the on state). Alternatively, or in combination with being positioned prior to and/or during the application of differential pressure, the tissue **18** can be disposed within the holding member **14** between the loading member **60** and the clamping member **62** such that each passageway of the plurality of passageways **68, 70, 72**, is obstructed by a portion of the tissue **18** that spans the entire cross section of the passageway defined by the loading member **60** and a clamping member **62** subsequent to the application of differential pressure (e.g., when the pump **16** is in the off state). In the illustrated embodiment, the tissue **18** comprises a single piece, or sheet, of tissue **120**.

(76) While the differential pressure material processing system **10** has been illustrated as including a sheet of tissue **18**, the material processed using a differential pressure material processing system, such as those described herein, can comprise any suitable material. Selection of a suitable material to process using a differential pressure material processing system can be based on various considerations, including the intended use of the material subsequent to processing. Examples of

suitable materials to process using a differential pressure material processing system include natural materials, allogeneic materials, xenogeneic materials, synthetic materials, and combinations of natural and synthetic materials. Examples of suitable natural materials include extracellular matrix (ECM) materials, such as small intestine submucosa (SIS), and other bioremodelable materials, such as bovine pericardium. Other examples of suitable ECM materials that can be used include stomach submucosa, liver basement membrane, urinary bladder submucosa, tissue mucosa, and dura mater. Other examples of suitable natural materials include renal capsule matrix, abdominal fascia, parenchyma, such as abdominal parenchyma, connective tissue, pulmonary or lung ligament, tissue laminates, and natural valve leaflets with or without adjacent vessel wall. Pleura is also considered a suitable natural material, including visceral pleura. Examples of suitable synthetic materials include polymeric materials, such as expanded polytetrafluoroethylene, polyurethane, polyurethane urea, polycarbonate, and polyesters.

(77) While the differential pressure material processing system **10** has been illustrated as including a single sheet of tissue **18**, a differential pressure material processing system can include any suitable number of sheets of material and selection of a suitable number of sheets of material to include in a system can be based on various considerations, including the type of processing being performed on the material. Examples of numbers of sheets of material considered suitable to include in a differential pressure material processing system include zero, one, at least one, two, a plurality, three, four, five, six, seven, eight, nine, ten, more than ten, and any other number considered suitable for a particular embodiment. For example, a differential pressure material processing system, such as those described herein can omit the inclusion of a tissue, or material, such that the tissue, or material, is provided separately.

(78) To complete processing of the tissue **18**, such as fixation, a fluid is pumped into the tank **12** until the level of fluid reaches the top of the each of the first and second non-permeable walls **24**, **26**, the fluid travels into both the first holding member chamber **64** and the second holding member chamber **66**, and is applied to the tissue **18**. The recesses **28**, **30** defined by the tank **12** maintain a constant, or substantially constant, head height and pressure differential across the tissue **18** when the fluid is constantly pumped into the tank **12** resulting in the tissue being processed under differential pressure. This is considered advantageous at least because it provides a mechanism for accounting for any tissue permeability, which would allow fluid to travel through the tissue from a first holding member chamber to a second holding member chamber.

(79) Any suitable differential pressure can be applied to tissue being processed in a differential pressure material processing system, such as those described herein, and selection of a suitable differential pressure to apply to a tissue can be based on various considerations, including the type of tissue being processed and/or the process being completed on the tissue. Examples of suitable differential pressures considered suitable to apply to tissue being processed using a differential pressure material processing system, such as those described herein, include differential pressures that are equal to, less than, greater than, or about 0.25 millimeters of mercury, 0.5 millimeters of mercury, 1 millimeter of mercury, 1.5 millimeters of mercury, 1.75 millimeters of mercury, 5 millimeters of mercury, 10 millimeters of mercury, 20 millimeters of mercury, differential pressures that are greater than 1.75 millimeters of mercury, differential pressures that are between about 0.25 millimeters of mercury and about 20 millimeters of mercury, between about 0.25 millimeters of mercury and about 10 millimeters of mercury, between about 0.25 millimeters of mercury and about 5 millimeters of mercury, between about 0.25 millimeters of mercury and about 2 millimeters of mercury, between about 0.25 millimeters of mercury and about 1.75 millimeters of mercury, between about 0.25 millimeters of mercury and about 1.0 millimeters of mercury, between about 0.25 millimeters of mercury and about 0.5 millimeters of mercury, between about 0.25 millimeters of mercury and about 0.5 millimeters of mercury for visceral pleura tissue, and any other differential pressure considered suitable for a particular embodiment. In embodiments in which a higher differential pressure is applied to tissue (e.g., 10 millimeters of mercury), greater residual

permanent deformation can be imparted into the tissue relative to embodiments in which a lower differential pressure (e.g., 1 millimeter of mercury) is applied to the tissue. In addition, in some embodiments, the application of differential pressure to tissue (e.g., 1 millimeter of mercury) results in more consistent mechanical behavior under biaxial loading relative to tissue that is not processed under differential pressure.

(80) Any suitable fluid can be used to process tissue using a differential pressure material processing system, such as those described herein, and selection of a suitable fluid for use with a differential pressure material processing system can be based on various considerations, including the intended use of the tissue subsequent to processing. Examples of suitable fluids for use with a differential pressure material processing system include chemical fixatives, such as aldehydes, e.g., formaldehyde, glutaraldehyde, and formalin, and carbodiimides, such as ethyl dimethylaminopropyl carbodiimide, dicyclohexylcarbodiimide, solutions, tanning agents, tanning agents in a buffering solution, and any other fluid considered suitable for a particular embodiment. The differential pressure material processing systems described herein can be used to perform any suitable process on the tissue, such as fixation and/or sterilization.

(81) FIGS. 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, and 16 illustrate another example differential pressure material processing system **210**. The differential pressure material processing system **210** is similar to the differential pressure material processing system **10** illustrated in FIGS. 1, 2, 3, 4, and 5 and described above, except as detailed below. The differential pressure material processing system **210** includes a first tank **212**, a second tank **320**, a holding member **214**, a pump **216**, a plurality of sheets of tissue **218** disposed within the holding member **214**, and a reservoir **322**.

(82) In the illustrated embodiment, each of the first tank **212** and the second tank **320** is moveable vertically to adjust the differential pressure applied to the plurality of sheets of tissue **218** disposed within the holding member **214**, as described in more detail herein. The first tank **212** is disposed relatively higher than the second tank **320** along a vertical axis. The first tank **212** is releasably attached to a first support post **323** and the second tank **320** is releasably attached to a second support post **324**. Movement of a tank **212**, **320** along a support post **323**, **324** can be accomplished using any suitable technique or method. For example, in the illustrated embodiment, a crank **325** can be used to adjust the height of a tank along a support post. While support posts **323**, **324** have been illustrated, a tank can alternatively be attached to any suitable structure capable of maintaining the position of the tank relative to a holding member during use. For example, a tank can be mounted to a wall or other vertical structure.

(83) The first tank **212** has a main body **222** that defines a first non-permeable wall **224**, a first recess **228**, a second recess **230**, a first passageway **234** in communication with the first recess **228**, a second passageway **236** in communication with the first recess **228**, and a third passageway **238** in communication with the second recess **230**. The first recess **228** defines a first portion of the first tank **212**. When fluid is disposed within the first recess **228** to a level at which the fluid has a height greater than the height of the first non-permeable wall **224** and the fluid flows into the second recess **230** the fluid has a first pressure creating a high-pressure portion **242** of the tank **212**. The second recess **230** defines a tank reservoir **326** that is in fluid communication with the reservoir **322**, as described in more detail herein. The second recess **230** defines a second portion of the first tank **212**. Each of the first passageway **234** and the second passageway **236** extends through the main body **222** and provides access between the first recess **228** and an environment exterior to the first recess **228**. The third passageway **238** extends through the main body **222** and provides access between the second recess **230** and an environment exterior to the second recess **230**.

(84) The second tank **320** has a main body **332** that defines a first non-permeable wall **334**, a first recess **336**, a second recess **338**, a first passageway **340** in communication with the first recess **336**, a second passageway **342** in communication with the first recess **336**, and a third passageway **344** in communication with the second recess **338**. The first recess **336** defines a first portion of the

second tank **320**. When fluid is disposed within the first recess **336** to a level at which the fluid has a height greater than the height of the first non-permeable wall **334** and the fluid flows into the second recess **338** the fluid has a second pressure that is less than the first pressure creating a low-pressure portion **244** of the tank **320**. In the illustrated embodiment, the second tank **320** defines a low-pressure portion **244** as a result of its position relative to the first tank **212**. The second recess **338** defines a tank reservoir **346** that is in fluid communication with the reservoir **322**, as described in more detail herein. The second recess **338** defines a second portion of the second tank **320**. Each of the first passageway **340** and the second passageway **342** extends through the main body **332** and provides access between the first recess **336** and an environment exterior to the first recess **336**. The third passageway **344** extends through the main body **332** and provides access between the second recess **338** and an environment exterior to the second recess **338**. An attachment member **241** is attached to the tanks **212**, **320** within each of the passageways **234**, **236**, **238**, **340**, **342**, and **344** to provide a mechanism to attach the tanks **212**, **320** to another component, such as the holding member **214**, pump **216**, and/or reservoir **322**, as described in more detail herein.

(85) In the illustrated embodiment, the holding member **214**, as shown in FIGS. **12**, **13**, **14**, **15**, and **16** includes a loading member **260**, a clamping member **262** releasably attached to the loading member **260**, a plurality of gaskets **350**, a first spacer **352**, a second spacer **354**, a first face plate **356**, a second face plate **358**, a first reinforcing bracket **360**, a second reinforcing bracket **362**, and defines a first holding member chamber **264**, a second holding member chamber **266**, a plurality of passageways **268**, **270**, **272** in communication with the first holding member chamber **264** and second holding member chamber **266**, a first input port **274**, a second input port **276**, a first drain **278**, a second drain **280**, a first vent **282**, and a second vent **284**.

(86) The loading member **260** has a main body **286** that defines a first portion of the first holding member chamber **264**, a first portion **288** of each passageway of the plurality of passageways **268**, **270**, **272** and a first guide member **290**. The clamping member **262** comprises a first member **263**, a second member **265**, and a third member **267**. Each of the first member **263**, the second member **265**, and the third member **267** has a main body **294** that defines a portion of the second holding member chamber **266**, a second portion **296** of a passageway of the plurality of passageways **268**, **270**, **272**, a second guide member **298**, and a sealing member **300**. The first portion **288** of each passageway of the plurality of passageways **268**, **270**, **272** and the second portion **296** of each passageway of the plurality of passageways **268**, **270**, **272** cooperatively define each passageway of the plurality of passageways **268**, **270**, **272** of the holding member **214**. A sealing member of the plurality of sealing members **300** surrounds each portion of the passageway of the plurality of passageways **268**, **270**, **272** defined by the clamping member **262** and provides a mechanism to seal the tissue **218** between the loading member **260** and the clamping member **262** (e.g., prevent leakage around the sealing member **300**) and maintain the position of the tissue **218** during use.

(87) In the illustrated embodiment, the first guide member **290** comprises a plurality of guide pins **291** and a plurality of guide holes **293** and the second guide member **298** comprises a plurality of guide holes **299** and a plurality of guide pins **301**. A guide pin of the plurality of guide pins **291** is disposed within a guide hole of the plurality of guide holes **299** and a guide pin of the plurality of guide pins **301** is disposed within a guide hole of the plurality of guide holes **293** when the clamping member **262** is releasably attached to the loading member **260**. Each guide hole of the plurality of guide holes **293** is sized and configured to receive a guide pin of the plurality of guide pins **301** and each guide hole of the plurality of guide holes **299** is sized and configured to receive a guide pin of the plurality of guide pins **291**.

(88) The first spacer **352** is releasably attached to the loading member **260** and has a main body **364** that defines a passageway **366**, a second portion of the first holding member chamber **264**, the first input port **274**, the first drain **278**, and the first vent **282**. The second spacer **354** is releasably attached to the loading member **260** and has a main body **368** that defines a passageway **370**, a second portion of the second holding member chamber **266**, the second input port **276**, the second

drain **280**, and the second vent **284**. A first gasket **372** of the plurality of gaskets **350** is disposed between the loading member **260** and the first spacer **352** and a second gasket **373** of the plurality of gaskets **350** is disposed between the loading member **260** and the second spacer **354**.

(89) The first face plate **356** is releasably attached to the first spacer **352** and has a main body **376** that defines a wall **378**. The second face plate **358** is releasably attached to the second spacer **354** and has a main body **380** that defines a wall **382**. Each of the first face plate **356** and the second face plate **358** is formed of a transparent material to allow for visualization of the tissue during processing. However, alternative embodiments can include a face plate that is formed of an opaque material. A third gasket **392** of the plurality of gaskets **350** is disposed between the first spacer **352** and the first face plate **356** and a fourth gasket **394** of the plurality of gaskets **350** is disposed between the second spacer **354** and the second face plate **358**. The loading member **260**, the first spacer **352**, and the first face plate **356** cooperatively define the first holding member chamber **264**. The clamping member **262**, the second spacer **354**, and the second face plate **358** cooperatively define the second holding member chamber **266**. The first reinforcing bracket **360** is releasably attached to the first face plate **356** and has a main body **384** that defines a passageway **386**. The first reinforcing bracket **360** provides a mechanism for distributing the load on the first face plate **356** to prevent leaks (e.g., leaks through the gasket **392**). The second reinforcing bracket **362** is releasably attached to the second face plate **358** and has a main body **388** that defines a passageway **390**. The second reinforcing bracket **362** provides a mechanism for distributing the load on the second face plate **358** to prevent leaks (e.g., leaks through the gasket **394**).

(90) A loading member, a clamping member, a plurality of gaskets, a first spacer, a second spacer, a first face plate, a second face plate, a first reinforcing bracket, and a second reinforcing bracket can be releasably attached to one another using any suitable technique or method of attachment.

Selection of a suitable technique or method of attachment between one or more components of a holding member can be based on various considerations, including the material that forms a component. Examples of techniques and methods of attachment considered suitable include using threaded connections, snap fit attachments, using one or more connectors, one or more mating slots and projections, one or more sealed unions, tapered attachments, clamps, pneumatic clamps, adhesives, and any other technique or method of attachment considered suitable for a particular embodiment. In the illustrated embodiment, the loading member **260**, the plurality of gaskets **350**, the first spacer **352**, the second spacer **354**, the first face plate **356**, the second face plate **358**, the first reinforcing bracket **360**, and the second reinforcing bracket **362** are attached to one another using threaded screws. Alternatively, one or more of a loading member, a clamping member, a plurality of gaskets, a first spacer, a second spacer, a first face plate, a second face plate, a first reinforcing bracket, and/or a second reinforcing bracket can be permanently fixed to one another.

(91) In the illustrated embodiment, the first recess **228** defined by the first tank **212** is in fluid communication with the first holding member chamber **264** such that the high-pressure portion **242** is in fluid communication with the first holding member chamber **264** and the first recess **336** defined by the second tank **320** is in fluid communication with the second holding member chamber **266** such that the low-pressure portion **244** is in fluid communication with the second holding member chamber **266**. In the illustrated embodiment, the first recess **228** defined by the first tank **212** is in fluid communication with the first holding member chamber **264** using a first elongate tubular member **302** and the first recess **336** defined by the second tank **320** is in fluid communication with the second holding member chamber **266** using a second elongate tubular member **304**. The first elongate tubular member **302** has a first end in fluid communication with the first passageway **234** defined by the first tank **212** and a second end in fluid communication with the first input port **274** of the holding member **214**. The second elongate tubular member **304** has a first end in fluid communication with the first passageway **340** defined by the second tank **320** and a second end in fluid communication with the second input port **276** of the holding member **214**.

(92) When a fluid is disposed within the recesses **228**, **230**, **336**, **338** defined by the tanks **212**, **320**

the pressure differential between the fluid within the first holding member chamber **264** and the second holding member chamber **266** can be controlled by manipulating the relative height between the first tank **212** and the second tank **320**. This can be accomplished by calculating a desired pressure differential and configuring the relative heights of the first and second tanks **212**, **320**. Alternatively, if the type of tissue disposed between a loading member and a clamping member of a differential pressure material processing system has a permeability that degrades over time, the differential pressure material processing systems described herein provide a mechanism for adjusting the differential pressure applied to the tissue (e.g., such that a constant, substantially constant, or varied, differential pressure is applied to the tissue during processing).

(93) The reservoir **322** has a main body **396** that defines a recess **398**, a first input port **400**, a second input port **402**, and an outlet port **404**. The first input port **400** is in fluid communication with the second recess **230** defined by the first tank **212** such that the tank reservoir **246** is in fluid communication with the recess **398** defined by the reservoir **346**. The second input port **402** is in fluid communication with the second recess **338** defined by the second tank **320** such that the tank reservoir **346** is in fluid communication with the recess **398** defined by the reservoir **346**. The output port **404** is connected to the pump **216** such that the recess **398** defined by the reservoir **246** is in fluid communication with the pump **216**.

(94) In the illustrated embodiment, the pump **216** includes an outlet port **306**, an inlet port **308**, and has an on state and an off state. The outlet port **306** is in fluid communication with the first recess **228** defined by the first tank **212** and the first recess **336** defined by the second tank **320** such that the high-pressure portion **242** is in fluid communication with the pump **216** and the low-pressure portion **244** is in fluid communication with the pump **216**. The inlet port **308** is in fluid communication with the reservoir **346**.

(95) In the illustrated embodiment, the outlet port **306** is in fluid communication with the first recess **228** defined by the first tank **212** using a manifold **311** and a third elongate tubular member **310**. The manifold **311** has a first end in fluid communication with the outlet port **306** of the pump **316**. The third elongate tubular member **310** has a first end in fluid communication with a second end of the manifold **311** and a second end in fluid communication with the second passageway **236** defined by the main body **222** of the first tank **212**. The outlet port **306** is in fluid communication with the first recess **336** defined by the second tank **320** using the manifold **311** and a fourth elongate tubular member **314** that has a first end in fluid communication with a third end of the manifold **311** and a second end in fluid communication with the second passageway **342** defined by the main body **332** of the second tank **320**. The recess **398** defined by the reservoir **322** is in fluid communication with the second recess **230** defined by the first tank **212** using a fifth elongate tubular member **316** that has a first end in fluid communication with the first input port **400** and a second end in fluid communication with the third passageway **238** defined by the main body **222** of the first tank **212**. The recess **398** defined by the reservoir **322** is in fluid communication with the second recess **338** defined by the second tank **320** using a sixth elongate tubular member **318** that has a first end in fluid communication with the second input port **402** and a second end in fluid communication with the third passageway **344** defined by the main body **332** of the second tank **320**. The recess **398** defined by the reservoir **322** is in fluid communication with the inlet port **308** of the pump **216** using a ninth elongate tubular member **410** that has a first end in fluid communication with the outlet port **404** and a second end in fluid communication with the inlet port **308** of the pump **216**.

(96) While the outlet port **306** has been illustrated as being in fluid communication with the first recess **228** defined by the first tank **212** and the first recess **336** defined by the second tank **320** such that the high-pressure portion **242** is in fluid communication with the pump **216** and the low-pressure portion **244** is in fluid communication with the pump **216**, an alternative embodiment can include a pump that is only in fluid communication with a first recess defined by a first tank that is positioned higher than a second tank along a vertical axis. In other alternative embodiments, a

pump and/or a reservoir can be omitted from a differential pressure material processing system in embodiments in which the tissue being processed is impermeable, or substantially impermeable. (97) In the illustrated embodiment, as shown in FIGS. **10** and **11**, a first sheet of tissue **412** of the plurality of sheets of tissue **218**, a second sheet of tissue **414** of the plurality of sheets of tissue **218**, and a third sheet of tissue **416** of the plurality of sheets of tissue **218** are disposed within the holding member **214** between the loading member **260** and the clamping member **262**. The first sheet of tissue **412** is disposed between the first member **263** of the clamping member **262** and the loading member **260** such that the first passageway **268** is obstructed by a portion of the first sheet of tissue **412** that spans the entire cross section of the passageway **268** defined by the loading member **260** and the first member **263**. The second sheet of tissue **414** is disposed between the second member **265** of the clamping member **262** and the loading member **260** such that the second passageway **270** is obstructed by a portion of the second sheet of tissue **414** that spans the entire cross section of the passageway **270** defined by the loading member **260** and the second member **265**. The third sheet of tissue **416** is disposed between the third member **267** of the clamping member **262** and the loading member **260** such that the third passageway **272** is obstructed by a portion of the third sheet of tissue **416** that spans the entire cross section of the passageway **272** defined by the loading member **260** and the third member **267**. The sheets of tissue **412**, **414**, **416** can be positioned in these configurations at any suitable time. For example, prior to, during, and/or subsequent to the application of differential pressure (e.g., when the pump **216** is in the on state and the off state). Each sheet of tissue of the plurality of sheets of tissue **218** spans a passageway defined by the holding member **260** such that the entire sealing member **300** surrounding the passageway defined by the clamping member **262** fully engages the tissue when the loading member **260** and the clamping member **262** are releasably attached to one another.

(98) To complete processing of the tissue **218**, such as fixation, a fluid is pumped into the first tank **212** and the second tank **320**. The fluid is pumped into the first tank **212** until the level of fluid reaches the top of the first non-permeable wall **224** and travels into the second recess **230**, the fluid travels from the first recess **228** into the first holding member chamber **264**, and is applied to the plurality of sheets of tissue **218**. The fluid is pumped into the second tank **320** until the level of fluid reaches the top of the first non-permeable wall **334** and travels into the second recess **338**, the fluid travels from the first recess **336** into the second holding member chamber **266**, and is applied to the plurality of sheets of tissue **218**. The position of the tanks **212**, **320** (e.g., recesses **228**, **230**, **336**, **338** defined by the tanks **212**, **320**) relative to the holding member **214** maintain a constant, or substantially constant, head height and pressure differential across the plurality of sheets of tissue **218** when the fluid is constantly pumped into the tanks **212**, **320** resulting in the plurality of sheets of tissue **218** being processed under differential pressure. This is considered advantageous at least because it provides a mechanism for accounting for any tissue permeability, which would allow fluid to travel through the tissue from a first holding member chamber to a second holding member chamber. In the illustrated embodiment, the holding member **214** is not directionally dependent since it omits the inclusion of a support member, such as support member **92**. Therefore, in an alternative embodiment, the high-pressure portion of a tank can be in fluid communication with a second holding member chamber and a low-pressure portion of a tank can be in fluid communication with a first holding member chamber.

(99) While a single holding member **214** has been illustrated as being included in the differential pressure material processing system **210**, any suitable number of holding members can be included in a differential pressure material processing system and attached to the various components as described herein and selection of a suitable number of holding members to include in a differential pressure material processing system can be based on various considerations, including the number of sheets of tissue intended to be processed using the differential pressure material processing system. Examples of numbers of holding members considered suitable to include in a differential pressure material processing system include one, at least one, two, a plurality, three, four, five,

more than five, and any other number considered suitable for a particular embodiment. For example, a plurality of holding members can be used concurrently in a differential pressure material processing system to provide processing of a plurality of sheets of tissue. In embodiments in which a plurality of holding members are being used concurrently, each holding member can optionally be connected to a valved manifold such that differential pressure can be applied to individual holding members as desired.

(100) FIGS. **17** and **18** illustrate another example differential pressure material processing system **510**. The differential pressure material processing system **510** is similar to the differential pressure material processing system **10** illustrated in FIGS. **1**, **2**, **3**, **4**, and **5** and described above, except as detailed below. The differential pressure material processing system **510** includes a tank **512**, a holding member **514** disposed within the tank **512**, a pump **516**, a sheet of tissue **518** disposed within the holding member **514**, and a reservoir **622**.

(101) In the illustrated embodiment, the tank **512** has a main body **522** that defines a wall **524**, a recess **528**, a first passageway **534** in communication with the recess **528**, a second passageway **536** in communication with the recess **528**, a first track **620**, and a second track **622**. Each of the first passageway **534** and the second passageway **536** extends through the main body **522** and provides access between the recess **528** and an environment exterior to the recess **528**. Each of the first track **620** and the second track **622** is a u-shaped member defined within the recess **528**. The first track **620** is separated from the second track **622** a distance that is equal to, or slightly larger than, the thickness of the holding member **514**. Optionally, one or more gaskets can be included along one, or both the tracks to provide additional sealing between the track and a holding member during use. Alternatively, a first track and a second track can be separate members that are attached to a tank. An attachment member **541** is attached to the tank **512** within each of the passageways **534**, **536**, to provide a mechanism to attach the tank **512** to another component, such as the pump **516** and/or reservoir **622**, as described in more detail herein.

(102) In the illustrated embodiment, the holding member **514** is releasably disposed within the tank **512** and includes a loading member **560**, a clamping member **562** releasably attached to the loading member **560**, and a cartridge **559**. The cartridge **559** defines a passageway **561**, a plurality of blind passageways **626**, a plurality of through passageways **628**, and includes a plurality of pistons **624**. Each blind passageway of the plurality of blind passageways **626** is in communication with a through passageway of the plurality of through passageways **628**. Each through passageway of the plurality of through passageways **628** has an open configuration and a closed configuration. A piston of the plurality of pistons **624** is disposed within a blind passageway **626** and is moveable between a first position and a second position such that when the piston is in the first position the associated through passageway is in the open configuration and when the piston is in the second position the associated through passageway is in the closed configuration. The position of each through passageway of the plurality of through passageways **628** varies along the height of the holding member **514** such that the differential pressure between the first holding member chamber **564** and the second holding member chamber **566**, as described in more detail herein, can be manipulated during use. In the open configuration, each passageway of the plurality of through passageways **628** is in fluid communication with the first holding member chamber **564** and the second holding member chamber **566**.

(103) A piston included in a holding member **514** can be moveable between a first position and a second position using any suitable technique or method and selection of a suitable technique or method can be based on various consideration, including the material forming a holding member. Examples of techniques and methods considered suitable to move a piston between first and second configurations include threaded connections between a cartridge and a piston such that the piston can be moved manually or can be automated, the inclusion of linear drive pistons that can be moved manually or can be automated, and any other technique or method considered suitable for a particular embodiment.

(104) The passageway **561** defined by the cartridge **559** is sized and configured to receive a loading member **560** and a clamping member **562**. While an example loading member **560** and clamping member **562** have been illustrated as being disposed within passageway **561**, any suitable loading member and/or clamping member can be included in a holding member, such as those described herein. In the illustrated embodiment, the loading member **560** and the clamping member **562** are similar to the loading member **260** and clamping member **262** illustrated and described with respect to FIGS. **6, 7, 8, 9, 10, 11, 12, 13, 14, 15**, and **16**, except that they omit the inclusion of a first input port, a second input port, a first drain, a second drain, a first vent, a second vent, a first face plate, a second face plate, a first reinforcing member, a second reinforcing member, a third gasket, and a fourth gasket. Alternatively, a holding member, such as the holding member **814** illustrated and described with respect to FIGS. **19, 20, 21, 22, 23, 24**, and **25** could be utilized with differential pressure material processing system **510**.

(105) When the holding member **514** is disposed within the recess **528** defined by the tank **512** between the first track **620** and the second track **622**, a first holding member chamber **564** is defined on a first side **565** of the holding member **514** and a second holding member chamber **566** is defined on a second side **567** of the holding member **514**. The first holding member chamber **564** defines a first portion of the tank **512**. When fluid is disposed within the first holding member chamber **564** to a level at which the fluid has a height greater than the height of a through passageway of the plurality of through passageways **628** that is in the open configuration and the fluid flows into the second holding member chamber **566** the fluid has a first pressure creating a high-pressure portion **542** of the tank **512**. The second holding member chamber **566** defines a second portion of the tank **512**. When fluid is disposed within the second holding member chamber **566** to a level at which the fluid has a height greater than the height of the second passageway **536** and the fluid flows into the reservoir **622** the fluid has a second pressure that is less than the first pressure creating a low-pressure portion **544** of the tank **512**.

(106) When a fluid is disposed within the recess **528** defined by the tank **512**, the pressure differential of the fluid within the first holding member chamber **564** and the second holding member chamber **566** can be controlled by manipulating the through passageway of the plurality of through passageways **628** that is in the open configuration and/or the location of the second passageway **536** along the height of the tank **512**. For example, the pressure on the high-pressure portion **542** can be varied by manipulating the through passageway of the plurality of through passageways **628** that is in the open configuration and/or the pressure on the low-pressure portion **544** can be varied by varying the location of the second passageway **536** of the tank **512** along the height of the tank **512**. In an alternative embodiment, multiple passageways could be defined by a tank and in fluid communication with a low-pressure portion of a tank to provide additional mechanisms for controlling the pressure of a second holding member chamber, multiple through passageways could be positioned in an open configuration to manipulate the pressure of a first holding member chamber, and/or the height of a cartridge can be adjusted to manipulate the pressure between a first holding member chamber and a second holding member chamber.

(107) In the illustrated embodiment, the high-pressure portion **542** is in fluid communication with the pump **516** using a first elongate tubular member **602** that has a first end in fluid communication with the first passageway **534** and a second end in fluid communication with the outlet port **606** of the pump **516**. The low-pressure portion **544** is in fluid communication with the recess **698** defined by the reservoir **622** using a second elongate tubular member **604** that has a first end in fluid communication with the second passageway **536** and a second end in fluid communication with the input port **700** of the reservoir **622**. The recess **698** defined by the reservoir **622** is in fluid communication with the pump **516** using a third elongate tubular member **610** that has a first end in fluid communication with the outlet port **704** of the reservoir **622** and a second end in fluid communication with the input port **608** of the pump **516**. In alternative embodiments, a pump could be directly connected to a second portion of a tank (e.g., low-pressure portion of the tank) such that

a reservoir can be omitted from a system. In these alternative embodiments, the pump can be configured such that its pumping rate is balanced with the rate of fluid leakage across the tissue and/or through the one or more through passageways.

(108) Alternative to the inclusion of a plurality of blind passageways, a plurality of through passageways, and a plurality of pistons, a holding member can include other features, devices, or components to accomplish manipulation of the pressure differential between a first holding member chamber and a second holding member chamber. Selection of suitable features, devices, and/or components to include on a holding member to assist with manipulation of the pressure differential between a first holding member chamber and a second holding member chamber can be based on various considerations, including the structural arrangement of a holding member and/or tank. For example, alternative to the inclusion of a plurality of blind passageways, a plurality of through passageways, and a plurality of pistons, or in addition to these features and components, a holding member can include a cartridge that comprises a plurality of plates that can be stacked between a first track and a second track to assist with the manipulation of the pressure differential.

(109) FIGS. **19, 20, 21, 22, 23, 24, and 25** illustrate another example differential pressure material processing system **810**. The differential pressure material processing system **810** is similar to the differential pressure material processing system **10** illustrated in FIGS. **1, 2, 3, 4, and 5** and described above, except as detailed below. The differential pressure material processing system **810** includes a tank **812**, a holding member **814** disposed within the tank **812**, a sheet of tissue **818** disposed within the holding member **814**, an actuator **921**, a plunger **922**, a first pressure transducer **924**, a second pressure transducer **926**, and an ultrasound transducer **928**.

(110) In the illustrated embodiment, the tank **812** has a main body **822** that defines a wall **824**, a recess **828**, a first opening **834** in communication with the recess **828**, a second opening **836** in communication with the recess **828**, a first track **920**, and a second track **922**. Each of the first opening **834** and the second opening **836** extends through the main body **822** and provides access between the recess **828** and an environment exterior to the recess **828**. Depending on the pressure desired on a low-pressure portion of the tank **812**, a second opening can be configured such that it contacts any device disposed through the opening (e.g., the opening is sealed, or substantially sealed, to create a closed system), or such that the opening does not contact a device disposed through the opening and the system is not closed. Each of the first track **920** and the second track **922** is a rectangular member that defines a passageway. Each of the first track **920** and the second track **922** is disposed within the recess **828** and is similar to the tracks **620, 622** described above with respect to FIGS. **17 and 18**. The first track **920** is separated from the second track **922** a distance that is equal to, or slightly larger than, the thickness of the holding member **814**. In the illustrated embodiment, the first track **920** is fixed to the tank **812** and the second track **922** is releasably attached to the tank **812** such that the holding member **814** can be positioned within the tank **812**, as described in more detail herein. The second track **922** can be releasably attached using any suitable technique or method of attachment, such as those described herein.

(111) In the illustrated embodiment, the holding member **814** includes a loading member **860**, a clamping member **862** releasably attached to the loading member **860**, and defines a plurality of passageways **868, 870, 872**. In the illustrated embodiment, the loading member **860** has a main body **886** that defines a first portion **888** of each passageway of the plurality of passageways **868, 870, 872**, a first guide member **890**, and a support member **892** (e.g., perforated member) spanning each portion of a passageway of the plurality of passageways **868, 870, 872** defined by the loading member **860**. In the illustrated embodiment, the clamping member **862** has a main body **894** that defines a second portion **896** of each passageway of the plurality of passageways **868, 870, 872**, a second guide member **898**, and a plurality of sealing members **900**.

(112) When the holding member **814** is disposed within the recess **828** defined by the tank **812** between the first track **920** and the second track **922**, a first holding member chamber **864** is defined on a first side **865** of the holding member **814** and a second holding member chamber **866**

is defined on a second side **867** of the holding member **814**. The first holding member chamber **864** defines a first portion of the tank **812**. When fluid is disposed within the first holding member chamber **864** and pressure is applied using the actuator **921**, as described in more detail herein, the fluid has a first pressure creating a high-pressure portion **842** of the tank **812**. The second holding member chamber **866** defines a second portion of the tank **812**. When fluid is disposed within the second holding member chamber **866** within the second holding member chamber **866** above the holding member **814** the fluid has a second pressure that is less than the first pressure creating a low-pressure portion **844** of the tank **812**.

(113) The actuator **921** is disposed through the first opening **834** defined by the tank **812** and is moveable within the first opening **834** between a first position and a second position. The plunger **922** is disposed between the actuator **921** and the holding member **814** and is moveable within the high-pressure portion **842** between a first position and a second position. The plunger **922** is in the first position when the actuator **921** is in the first position and the plunger **922** is in the second position when the actuator **921** is in the second position. Any suitable actuator can be included in a differential pressure material processing system and selection of a suitable actuator can be based on various considerations, including the pressures intended to be applied to tissue being processed. Examples of actuators suitable for inclusion in a differential pressure material processing system include linear actuators, rotatable actuators, manually operated actuators, automated actuators, combinations of the actuators described herein, and any other actuator considered suitable for a particular embodiment. In the illustrated embodiment, the actuator **921** comprises a rotatable actuator **923** that is manually operated.

(114) When a fluid is disposed within the recess **828** defined by the tank **812**, the pressure of the fluid within the first holding member chamber **864** can be controlled by manipulating the position of the actuator **921** between its first and second positions and the pressure of the fluid within the second holding member chamber **866** can be controlled by manipulating the position of the holding member **812** within the recess **854** defined by the tank **812** and/or the level of fluid disposed above the holding member **814**.

(115) The first pressure transducer **924** is in communication with the high-pressure portion **842** and the second pressure transducer **926** is in communication with the low-pressure portion **844**. The inclusion of first and second pressure transducers **924**, **926** provides a mechanism for providing real-time data relating to the differential pressure being applied to tissue **818** disposed within the holding member **814** and allows for a user to adjust the pressure being applied to the tissue **818** accordingly. The ultrasound transducer **928** is disposed within the recess **828** and provides a mechanism for characterizing the tissue **818** in real time and monitoring the properties of the tissue **818** during processing. In the illustrated embodiment, the ultrasound transducer **928** is disposed within the second holding member chamber **866**. Any differential pressure material processing system described herein can include one or more pressure transducers in communication with a high-pressure portion of a tank, a low-pressure portion of a tank, a first holding member chamber, and/or a second holding member chamber. In addition, any differential pressure material processing system described herein can include one or more ultrasound transducers in communication with a high-pressure portion of a tank, a low-pressure portion of a tank, a first holding member chamber, and/or a second holding member chamber. Any suitable pressure transducer and/or ultrasound transducer can be included in a differential pressure material processing system and selection of a suitable pressure transducer and ultrasound transducer can be based on various considerations, including the amount of differential pressure being applied to a tissue and/or the type of tissue being processed. Examples of suitable pressure transducers considered suitable to include in a differential pressure material processing system include those that are within the sensitivity range of the differential pressure being applied to tissue, and any other pressure transducer considered suitable for a particular embodiment. Alternatively, a manometer in communication with a first holding member chamber and a second holding member can be used. Examples of suitable

ultrasound transducers considered suitable to include in a differential pressure material processing system include linear arrays, phased arrays, single element transducers with frequency ranges between about 20 kHz and about 100 MHz, a matrix of transducers, high-frequency transducers, multiple-frequency transducers, movable transducers, transducers disposed parallel, and/or perpendicular to, a tissue being processed, combinations of those described herein, and any other transducer considered suitable for a particular embodiment. For example, an array of transducers could be utilized to create a full x-y patterning of tissue characteristics. Alternative to, or in combination with use of an ultrasound transducer, optical measuring devices and/or laser measuring devices could be utilized to characterize tissue being processed.

(116) A tank and a holding member, or portions of a tank and holding member, or any other portion of a differential pressure material processing system, of the embodiments described herein can be formed of any suitable material and using any suitable method of manufacture. Selection of a suitable material and method of manufacture can be based on various considerations, including the intended use of the tank and/or holding member. Examples of materials considered suitable to form a tank and/or holding member of the embodiments described herein include biocompatible materials, materials that can be made biocompatible, metals, such as **316** stainless and **304** stainless, corrosion resistant materials, plastics, polymers, polyethylene, such as high-density polyethylene (HDPE), polypropylene, polycarbonates, silicone, Delrin, transparent materials, opaque materials, and any other material considered suitable for a particular embodiment.

(117) Various methods of treatment are described herein. While the methods described herein are shown and described as a series of acts, it is to be understood and appreciated that the methods are not limited by the order of acts, as some acts may in accordance with these methods, occur in the order shown and/or described, in different orders, and/or concurrently with other acts described herein.

(118) FIG. **26** is a schematic illustration of an example method **1000** of loading tissue into a holding member.

(119) A step **1002** comprises positioning a sheet of tissue on a loading member such that a portion of the tissue is separated from the loading member by a fluid layer disposed between the tissue and the loading member. Another step **1004** comprises adjusting the position of the tissue. Another step **1006** comprises positioning a clamping member on the loading member. Another step **1008** comprises releasably attaching the clamping member to the loading member.

(120) Step **1002** can be accomplished using any suitable loading member and selection of a suitable loading member can be based on various considerations, including the material that forms a loading member. Examples of loading members considered suitable to complete a method of loading tissue into a holding member include loading member **60**, loading member **260**, loading member **560**, loading member **860**, loading member **1760**, and any other loading member considered suitable for a particular embodiment.

(121) Step **1002** can be accomplished such that the tissue is positioned on the loading member in a resting state. The phrase “resting state” means the tissue is in a state in which the only non-naturally occurring forces being applied to the tissue occur from the tissue's contact with the fluid layer and the loading member when the tissue is positioned on the fluid layer and the loading member, occur from the tissue's contact with the fluid layer when the tissue is positioned on the fluid layer, or occur from the tissue's contact with the loading member when the tissue is positioned on the loading member. A resting state may include a state in which a sheet of tissue includes wrinkles and/or folds, a state in which a sheet of tissue is planar (e.g., a planar resting state) in which a surface of the tissue (e.g., top surface, bottom surface) is parallel, or substantially parallel, to a surface of a loading member (e.g., a surface of the loading member on which the tissue is intended to be disposed), a resting state in which a surface of the tissue is similar, or substantially similar, to a surface of a loading member (e.g., a curved surface of the loading member on which the tissue is intended to be disposed), and any other state considered suitable for a particular

embodiment. Depending on the material forming a loading member (e.g., low-friction materials, such as Teflon), in alternative embodiments step **1002** can comprise positioning a sheet of tissue on a loading member such that the tissue contacts the loading member.

(122) Step **1002** can be accomplished using any suitable technique or method of positioning tissue on a loading member and selection of a suitable technique or method can be based on various considerations, including the structural arrangement of a loading member. Examples of techniques and methods considered suitable include using the hands of an individual, using automated robotics systems, convention tools, such as hand tools, and any other technique or method considered suitable for a particular embodiment.

(123) A fluid layer disposed between tissue and a loading member can include any suitable fluid positioned between the tissue and the loading member using any suitable technique or method. Selection of a suitable fluid and technique or method to position the fluid layer between tissue and a loading member can be based on various considerations, including the type of tissue being positioned within a holding member. Examples of fluids considered suitable to position between tissue and a loading member include lubricious coatings, such as those that are applied to the loading member prior to step **1002**, saline, phosphate buffered saline, lactated ringers, fluids described herein, such as fixation solutions, water, neutral oils, and any other fluid considered suitable for a particular embodiment. Examples of suitable techniques and methods of positioning a fluid layer between tissue and a loading member include applying a fluid layer prior to, during, and/or subsequent to, step **1002**, activating a pump prior to and/or during step **1002** such that a fluid layer is positioned between tissue and a loading member (e.g., travels through a loading member and/or loading tool and onto a perforated surface), applying fluid to the loading member using an applicator, placing a loading member and/or other component within a fluid bath such that a top surface of the loading member and/or other component is disposed at, near, or below, the level of the fluid within the bath, and any other technique or method considered suitable for a particular embodiment. An optional step that can be completed prior to step **1002** comprises applying a fluid to the loading member to create a fluid layer. FIG. 27 illustrates a sheet of tissue **1020** positioned on a loading member **1022** such that the tissue **1020** is in its resting state and a portion of the tissue **1020** is separated from the loading member **1022** by a fluid layer **1024** disposed between the tissue **1020** and the loading member **1022**.

(124) While step **1002** has been described as being accomplished by positioning a sheet of tissue, tissue having any suitable configuration can be positioned on a loading member in a method of loading tissue into a holding member. While step **1002** has been described as being accomplished such that a portion of the tissue is separated from the loading member by a fluid layer disposed between the tissue and the loading member, any suitable amount of tissue can be separated from a loading member by a fluid layer disposed between the tissue and the loading member. Examples of suitable amounts of tissue include an entire sheet of tissue, a majority of a sheet of tissue, more than half of a sheet of tissue, more than one quarter of a sheet of tissue, less than one quarter of a sheet of tissue, and any other amount of tissue considered suitable for a particular embodiment.

(125) Step **1004** can be accomplished using any suitable technique or method of adjusting a position of the tissue and selection of a suitable technique or method can be based on various considerations, including the type of tissue being positioned within a holding member. Examples of techniques and methods considered suitable include using forceps, the hands of an individual, conventional tools, robotic systems, and any other technique or method considered suitable for a particular embodiment. Step **1004** is accomplished to remove any wrinkles in the tissue and/or to position the tissue such that it lays flat on the loading member and/or any other component.

(126) Step **1006** can be accomplished using any suitable technique or method of positioning a clamping member on a loading member and selection of a suitable technique or method can be based on various considerations, including the structural arrangement of a clamping member and/or loading member. Examples of techniques and methods considered suitable include using the hands

of an individual, using automated robotics systems, convention tools, such as hand tools, and any other technique or method considered suitable for a particular embodiment. It is considered advantageous to complete step **1006** such that the position of a loading member relative to a clamping member is maintained along an x-axis and a y-axis to reduce, or eliminate, any unintentional deformation and/or stress imparted on tissue positioned between a loading member and a clamping member during positioning of a clamping member relative a loading member and/or attachment of a clamping member to a loading member.

(127) Step **1008** can be accomplished using any suitable technique or method of releasably attaching a clamping member to a loading member and selection of a suitable technique or method can be based on various considerations, including the structural arrangement of a clamping member and/or loading member. Examples of techniques and methods considered suitable include using threaded connections, snap fit attachments, using one or more connectors, one or more mating slots and projections, one or more sealed unions, tapered attachments, external clamps, pneumatic clamping mechanisms, adhesives, and any other technique or method of attachment considered suitable for a particular embodiment.

(128) Step **1008** can be accomplished such that the tissue is in the clamped state. The phrase “clamped state” means the tissue is in a state in which forces are applied on the tissue by the clamping member and the loading member such that the portion of the tissue contacts the clamping member and the loading member. For example, a clamped state can include contact between a sealing member of a clamping member and the tissue such that the sealing member seals the tissue between the clamping member and the loading member to prevent leakage around the sealing member and maintain the position of the tissue during use. FIG. **28** illustrates a sheet of tissue **1020** positioned on a loading member **1022** such that the tissue **1020** is in its clamped state and a portion of the tissue **1020** contacts the clamping member **1026** and the loading member **1022**.

(129) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1000**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method **1100**, and/or example method **1200**.

(130) FIG. **29** is a schematic illustration of another example method **1100** of loading tissue into a holding member.

(131) A step **1102** comprises positioning a loading member on flat surface with a guide member of the loading member directed away from the surface. Another step **1104** comprises applying a fluid to the loading member. Another step **1106** comprises positioning a sheet of tissue on a loading member such that the tissue is in its resting state and a portion of the tissue is separated from the loading member by a fluid layer disposed between the tissue and the loading member. Another step **1108** comprises adjusting the position of the tissue. Another step **1110** comprises positioning a clamping member on the loading member. Another step **1112** comprises releasably attaching the clamping member to the loading member such that the tissue is in the clamped state.

(132) Step **1102** can be accomplished using any suitable loading member and selection of a suitable loading member can be based on various considerations, including the material that forms a loading member. Examples of loading members considered suitable to complete a method of loading tissue into a holding member include loading member **60**, loading member **860**, loading member **1760**, and any other loading member considered suitable for a particular embodiment. A loading member can be positioned on any suitable surface, such as the surface of a table. In embodiments in which holding member **1760** is being used to complete method **1100**, step **1102** can comprise positioning a loading member on a flat surface with a guide member of the loading member directed away from the surface such that the support member moves from the first position to the second position.

(133) Step **1104** can be accomplished using any suitable technique or method of applying any suitable fluid to a loading member and a fluid can be applied to any suitable portion of a loading

member. Examples of techniques and methods of applying a fluid to a loading member considered suitable include applying a fluid layer prior to, during, and/or subsequent to, step **1102**, activating a pump prior to and/or during step **1102** such that a fluid layer is positioned between tissue and a loading member, applying fluid to the loading member using an applicator, placing a loading member and/or other component within a fluid bath such that a top surface of the loading member and/or other component is disposed at, near, or below, the level of the fluid within the bath, and/or any other technique or method considered suitable for a particular embodiment. Examples of fluids considered suitable to apply to loading member include lubricious coatings, saline, phosphate buffered saline, those described herein, and any other fluid considered suitable for a particular embodiment. Examples of suitable portions of a loading member to apply a fluid include between a passageway and an edge defined by a loading member, on a support member of the loading member, on a perforated surface of the loading member, combinations of the portions described herein, and/or any other portion of a loading member considered suitable for a particular embodiment. FIG. **30** illustrates loading member **860** positioned on a surface **1120** of a table **1122** with the first guide member **890** directed away from the surface **1120**. A phosphate buffered saline **1124** has been applied to the loading member **860** between the first portion **888** of each passageway of the plurality of passageways **868**, **870**, **872** and the edges **1126** of the loading member **860** and on the support member **892** spanning each passageway of the plurality of passageways **868**, **870**, **872**. Optionally, step **1104** can be omitted from method **1100** in embodiments in which a fluid (e.g., lubricious coating) has already been applied to a loading member or in embodiments in which a loading member is formed of a non-stick material.

(134) Step **1106** can be accomplished by positioning a single sheet of tissue over each portion of a passageway defined by a loading member or by positioning separate sheets of tissue over each portion of a passageway defined by a loading member. Depending on the number of sheets of tissue being positioned on a loading member, this step can alternatively be accomplished by positioning multiple sheets of tissue on a loading member sequentially to one another or concurrently with one another. Each sheet could be precut such that when disposed on a loading member the sheets do not overlap.

(135) Step **1108** can be accomplished as described above with respect to step **1004**. Step **1108** can be accomplished such that all wrinkles are removed from the tissue and/or the tissue is centered on each portion of a passageway defined by the loading member or on one portion of a passageway defined by the loading member. An optional step comprises trimming the tissue in embodiments in which the tissue obstructs or contacts any guide member and/or obstructs or contacts any openings and/or passageways used to releasably attach a loading member to a clamping member. Another optional step comprises applying fluid to the tissue subsequent to being positioned on a loading member (e.g., in embodiments in which multiple sheets of tissue are being positioned on a loading member). Another optional step comprises confirming that the tissue is large enough to contact the sealing member of a holding member (e.g., sealing member of clamping member) such that the tissue will seal the passageway defined by the holding member when the loading member and clamping member are attached to one another.

(136) Step **1110** can be accomplished as described above with respect to step **1006**.

(137) Step **1112** can be accomplished as described above with respect to step **1008**.

(138) Depending on the structural arrangement of a clamping member (e.g., clamping member **262**), an optional step comprises repeating step **1110** and step **1112** to accomplish attachment between each member of a clamping member and a loading member.

(139) In embodiments in which holding member **1714** is being used to complete method **1100**, an optional step comprises moving each support member of the plurality of support members from the second position to the first position. This optional step can be accomplished by removing the loading member **1760** from the flat surface.

(140) While various steps, alternative steps, and optional steps have been described above with

respect to the example method **1100**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method **1000**, and/or example method **1200**.

(141) FIG. **31** is a schematic illustration of another example method **1200** of loading tissue into a holding member.

(142) A step **1202** comprises positioning a loading tool on flat surface. Another step **1204** comprises positioning a loading member on the loading tool with a guide member of the loading member directed away from the loading tool. Another step **1206** comprises applying a fluid to the loading member and the loading tool. Another step **1208** comprises positioning a sheet of tissue on the loading member and the loading tool such that the tissue is in its resting state and a portion of the tissue is separated from the loading member and loading tool by a fluid layer disposed between the tissue and the loading member. Another step **1210** comprises adjusting the position of the tissue. Another step **1212** comprises positioning a clamping member on the loading member. Another step **1214** comprises releasably attaching the clamping member to the loading member such that the tissue is in the clamped state. Another step **1216** comprises removing the loading member and clamping member from the loading tool.

(143) Step **1202** can be accomplished using any suitable loading tool and selection of a suitable loading tool can be based on various considerations, including the material that forms a loading member intended to be positioned on the loading tool. FIGS. **32**, **33**, **33A**, and **34** illustrate an example loading tool **1220**. In FIGS. **32** and **33**, loading member **260** is positioned on loading tool **1220**. The loading tool **1220** includes a base **1222** and a plurality of caps **1224**. The base **1222** has a main body **1226** that defines a plurality of passageways **1228**, **1230**, **1232** and a plurality of notches **1234**. Each passageway of the plurality of passageways **1228**, **1230**, **1232** extends through the main body **1226**. Each notch of the plurality of notches **1234** extends from a first edge of the main body **1226** to a second edge of the main body **1226**. Each cap of the plurality of caps **1224** has a first end **1236**, a second end **1238**, and a main body **1240** that defines a support member **1242**, a recess **1244**, and an elongate member **1246**. The support member **1242** is perforated and provides permeability across the material forming a cap such that the recess **1244** is in fluid communication with an environment exterior to the recess **1244** or with tissue when tissue is disposed on the first end of a cap. The elongate member **1246** provides a mechanism for attaching a cap **1224** to the base **1222** (e.g., using a threaded attachment). The support member **1242** defines a plurality of openings that are sized such that the fluid does not rapidly drain and the fluid remains on the support member **1242** during the loading process. A loading tool can be positioned on any suitable surface, such as the surface of a table. The outside diameter of each cap of the plurality of caps **1224** is less than the inside diameter of each passageway of the plurality of passageways defined by the loading member **260** (e.g., the outside diameters are undersized). This configuration along with the support member **1242** and the plurality of notches **1234** provide a mechanism for minimizing the vacuum that is created when that loading member **260** is removed from the loading tool **1220** and to avoid excessive tissue deformation. FIG. **32** illustrates loading tool **1220** positioned on a surface **1250** of a table **1252**. As shown in FIG. **32**, when the loading member **260** is positioned on the loading tool **1220**, the support member **1242** is flush with the top surface of the loading member **260**.

(144) Step **1204** can be accomplished using any suitable loading member and selection of a suitable loading member can be based on various considerations, including the material that forms a loading member. Examples of loading members considered suitable to complete a method of loading tissue into a holding member include loading member **260**, and any other loading member considered suitable for a particular embodiment. FIG. **32** illustrates loading member **260** positioned on the loading tool **1220** with the first guide member **290** directed away from the loading tool **1220**.

(145) Step **1206** can be accomplished using any suitable technique or method of applying any

suitable fluid to a loading member and/or loading tool and a fluid can be applied to any suitable portion of a loading member and/or loading tool. Examples of techniques and methods of applying fluid to a loading member and/or loading tool considered suitable include applying a fluid layer prior to, during, and/or subsequent to, step **1202** and/or step **1204**, activating a pump prior to and/or during step **1202** and/or step **1204** such that a fluid layer is positioned between tissue and a loading member and/or loading tool, applying fluid to the loading member and/or loading tool using an applicator, placing a loading member and/or loading tool within a fluid bath such that a top surface of the loading member and/or loading tool is disposed at, near, or below, the level of the fluid within the bath, and any other technique or method considered suitable for a particular embodiment. Examples of fluids considered suitable to apply to loading member and/or loading tool include lubricious coatings, saline, phosphate buffered saline, those described herein, and any other fluid considered suitable for a particular embodiment. Examples of suitable portions of a loading member and/or loading tool to apply a fluid include between a passageway and an edge defined by a loading member, on a support member of the loading member, on a perforated surface of a loading tool, and any other portion of a loading member and/or loading tool considered suitable for a particular embodiment. In embodiments in which loading tool **1220** is being utilized to complete method **1200**, step **1206** can be accomplished by attaching a pump to tubular member **1246** of each cap of the plurality of caps **1224** such that the pump and each cap of the plurality of caps **1224** are in fluid communication and activating the pump such that fluid is applied to the loading tool **1220** and the loading member **260**. Optionally, step **1206** can be omitted from method **1200** in embodiments in which a fluid (e.g., lubricious coating) has already been applied to a loading tool and/or loading member or in embodiments in which a loading tool and/or loading member is formed of a non-stick material.

(146) Step **1208** can be accomplished by positioning a single sheet of tissue over each portion of a passageway defined by a loading member or by positioning separate sheets of tissue over each portion of a passageway defined by a loading member. Depending on the number of sheets of tissue being positioned on a loading member, an optional step comprises positioning multiple sheets of tissue on a loading member sequentially or concurrently with one another.

(147) Step **1210** can be accomplished as described above with respect to step **1004** and/or step **1108**. Step **1212** can be accomplished as described above with respect to step **1006**. Step **1214** can be accomplished as described above with respect to step **1008**. Depending on the structural arrangement of a clamping member (e.g., clamping member **262**), an optional step comprises repeating step **1212** and step **1214** to accomplish attachment between each member of a clamping member and a loading member.

(148) Step **1216** can be accomplished by applying a force on the loading member and/or clamping member away from the loading tool such that the loading member and clamping member are removed from the loading tool. It is considered advantageous to use a loading member and/or loading tool that includes a support member (e.g., perforated surface) to prevent a vacuum from being created between the surface on which tissue is disposed and the tissue.

(149) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1200**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method **1000**, and/or example method **1100**.

(150) FIG. **35** is a schematic illustration of an example method **1300** of processing tissue.

(151) A step **1302** comprises adjusting the position of a tank relative to a holding member along a vertical axis. The holding member has tissue disposed between a loading member and a clamping member. Another step **1304** comprises connecting the tank to a pump such that a first portion of the tank is in fluid communication with the pump. Another step **1306** comprises connecting the tank to the holding member such that the first portion of the tank is in fluid communication with the

holding member. Another step **1308** comprises connecting the tank to the holding member such that a second portion of the tank is in fluid communication with the holding member. Another step **1310** comprises connecting the pump to a reservoir such that the pump is in fluid communication with the reservoir. Another step **1312** comprises introducing a fluid into the tank. Another step **1314** comprises opening a vent on the loading member. Another step **1316** comprises opening a vent on the clamping member. Another step **1318** comprises activating the pump. Another step **1320** comprises introducing fluid into the reservoir while the pump is in an on state. Another step **1322** comprises closing the vent on the loading member. Another step **1324** comprises closing the vent on the clamping member. Another step **1326** comprises maintaining the pump in the on state for a period of time such that a differential pressure is applied to the tissue. Another step **1328** comprises deactivating the pump. Another step **1330** comprises draining the holding member. Another step **1332** comprises disassembling the holding member. Another step **1334** comprises removing the clamping member from the loading member. Another step **1336** comprises removing tissue from the loading member. Another step **1338** comprises placing the tissue in a fluid for a period of time.

(152) Step **1302** can be accomplished by adjusting the position of any suitable tank relative to any suitable holding member. For example, the tank **12** illustrated in FIG. **1** can be adjusted relative to the holding member **14**. A holding member utilized in a method of processing tissue can be pre-loaded with tissue disposed between a loading member and a clamping member. For example, tissue can be positioned within a holding member using the methods described herein, such as method **1000**, method **1100**, and/or method **1200**.

(153) Step **1304** can be accomplished by attaching a first elongate tubular member to the tank and the pump such that the first portion of the tank is in fluid communication with the pump.

(154) Step **1306** can be accomplished by attaching a second elongate tubular member to the tank and the holding member such that the first portion of the tank is in fluid communication with the holding member (e.g., first holding member chamber).

(155) Step **1308** can be accomplished by attaching a third elongate tubular member to the tank and the holding member such that the second portion of the tank is in fluid communication with the holding member (e.g., second holding member chamber).

(156) Step **1310** can be accomplished by attaching a fourth elongate tubular member to the pump and a reservoir such that the pump is in fluid communication with the reservoir (e.g., third portion of tank). Depending on the structural arrangement of a differential pressure material processing system, in alternative embodiments steps **1304** through **1310** could be omitted from a method of processing tissue when a system is preconfigured as described with respect to steps **1302** through **1310**.

(157) Step **1312** can be accomplished by introducing any suitable type and amount of fluid into the tank. The amount of fluid introduced into a tank will vary and depend on the dimensions of the tank. Examples of amounts of fluid considered suitable to introduce into a tank include 0.5 liters, 1 liter, 1.5 liters, 2 liters, 2.5 liters, 3 liters, 4 liters, 5 liters, 6 liters, 7 liters, 8 liters, 9 liters, 10 liters, more than 4 liters, and any other amount considered suitable for a particular embodiment. Examples of suitable fluids considered suitable to introduce into a tank include chemical fixatives, such as aldehydes, e.g., formaldehyde, glutaraldehyde, and formalin, and carbodiimides, such as ethyl dimethylaminopropyl carbodiimide, dicyclohexylcarbodiimide, solutions, tanning agents, tanning agents in a buffering solution, and any other fluid considered suitable for a particular embodiment. Fluid can be introduced into any suitable portion of a tank (e.g., first portion, second portion, third portion). In the embodiment illustrated in FIG. **1**, fluid can be introduced into the first portion of the tank **12** such that it spills into the second portion of the tank **12** (e.g., second recess **30**) and the third portion of the tank **12** (e.g., third recess **32**).

(158) Step **1314** and step **1316** can be accomplished by applying a force on a vent to move it to an open configuration.

(159) Step **1318** can be accomplished by moving the pump from an off state to an on state. It is

considered advantageous to adjust the rate at which fluid is pumped into a tank such that it does not create turbulence within the tank. Once the pump is activated, fluid will flow from the first portion of the tank and into the second portion of the tank, from the second portion of the tank to the third portion of the tank, from the third portion of the tank to the pump inlet, from the first portion of the tank to the holding member (e.g., first holding member chamber), and from the second portion of the tank to the holding member (e.g., second holding member chamber).

(160) Step **1320** can be accomplished by introducing additional fluid into the reservoir. For example, additional fluid could be added such that the total fluid within the system is about **4** liters. In alternative embodiments, step **1320** could be omitted from method **1300** in which additional fluid is not needed.

(161) An optional step comprises adjusting the rate of pumping such that only a small amount of overflow from the first portion of the tank to the second portion of the tank is achieved. This optional step can be completed after the holding member fills and the tank has reached overflow capacity and a constant, or substantially constant, pressure differential is maintained within the holding member. Another optional step comprises preloading the tank with fluid. This step can be accomplished such that both the first portion and the second portion of the tank are filled at a similar rate to avoid excessive deformation of the tissue in one direction within the holding member.

(162) The differential pressure being applied to tissue can vary during a method of processing tissue due to the permeability of the tissue, which results in fluid passing through the tissue from a first holding member chamber to a second holding member chamber. Therefore, an optional step comprises adjusting the differential pressure being applied to the tissue. This optional step can be accomplished by adjusting the rate of fluid being pumped by the pump, adjusting the height of a first wall and/or second wall defined by a tank, and/or any other technique or method considered suitable for a particular embodiment. Another optional step comprises determining the pressure differential between the first holding member chamber and second holding member chamber. This optional step allows for a determination as to whether an adjustment to the differential pressure is necessary and can be accomplished using a first pressure transducer disposed within the first holding member chamber and a second pressure transducer disposed within the second holding member chamber or a manometer in communication with the first holding member chamber and the second holding member chamber. Another optional step comprises determining the characteristics of the tissue. This optional step can be accomplished using an ultrasound transducer in communication with one, or both, of the first holding member chamber and second holding member chamber. These optional steps can be accomplished while a pump is in an on state and a differential pressure is being applied to the tissue or in an off state (e.g., fluid is disposed between a transducer and the tissue). Any suitable characteristic can be determined and selection of a suitable characteristic can be based on various considerations, including the type of tissue being processed. Examples of characteristics considered suitable to determine include deformation of tissue, deformation over time, deformation over load, deformation over applied pressure, combinations of deformation over time, deformation over load, and deformation over applied pressure, detection of local defects within a tissue, fixation status, and any other characteristic considered suitable for a particular embodiment. For example, characteristics relating to deformation over time, deformation over load, and/or deformation over applied pressure can be used to calculate a modulus of a tissue being processed. In addition, detection of local defects within a tissue can be utilized during manufacture such that defective portion of the tissue are not used in a final product.

(163) Step **1322** and step **1324** can be accomplished by applying a force on a vent to move it to a closed configuration. Each of step **1322** and step **1324** can optionally be completed just before the holding member reaches full capacity. An optional step comprises removing air trapped within holding member (e.g., by tilting the holding member such that air bubbles migrate up the inlet tubing into the tanks).

(164) Step **1326** can be accomplished for any period of time, such as one or more minutes, one or more hours, and/or one or more days. For example, step **1326** can be accomplished for a period of time equal to, greater than, less than, or about four hours. Any suitable differential pressure can be applied to tissue and selection of a suitable differential pressure to apply to tissue can be based on various considerations, such as the desired characteristics intended to be imparted on the tissue. Examples of suitable differential pressures considered suitable to apply to tissue being processed using the methods described herein include those that are equal to, less than, greater than, or about 0.25 millimeters of mercury, 0.5 millimeters of mercury, 1 millimeter of mercury, 1.5 millimeters of mercury, 1.75 millimeters of mercury, between about 0.25 millimeters of mercury and about 1.75 millimeters of mercury, and any other differential pressure considered suitable for a particular embodiment. FIG. **35A** illustrates a sheet of tissue **1340** prior the application of differential pressure such that the tissue is in a first, undeformed configuration. As shown in FIG. **35A**, the first configuration of the tissue **1340** is generally planar. However, a tissue processed under differential pressure can have any suitable first, undeformed configuration. FIG. **35B** illustrates the tissue **1340** being processed under differential pressure such that the tissue is in a second, deformed configuration. As shown in FIG. **35B**, the second configuration of the tissue **1340** is different than the first configuration and is domed such that the tissue **1340** distends towards the second holding member chamber **66** (e.g., low-pressure portion). The degree of distension imparted on tissue during differential pressure treatment will vary depending on the stiffness of the tissue. In some embodiments, depending on the type of tissue being processed, the application of differential pressure provides a mechanism for imparting a constant, or substantially constant, and uniform, or substantially uniform, deformation on the tissue as it is crosslinked during fixation.

(165) Step **1328** can be accomplished by moving the pump from an on state to an off state.

(166) Step **1330** can be accomplished using any suitable technique or method of draining a holding member. For example, the fluid within a holding member can be removed by moving one or more vents of the holding member to an open configuration and draining the fluid through the one or more vents and/or moving one or more drains of the holding member to an open configuration and draining the fluid through the one or more drains.

(167) Step **1332** can be accomplished using any suitable technique or method of disassembling a holding member.

(168) Step **1334** can be accomplished using any suitable technique or method of removing a clamping member from a loading member and selection of a suitable technique or method can be based on various considerations, including the structural arrangement of a clamping member and/or loading member. Examples of techniques and methods considered suitable include using the hands of an individual, using automated robotics systems, convention tools, such as hand tools, and any other technique or method considered suitable for a particular embodiment. It is considered advantageous to complete step **1334** such that the position of a loading member relative to a clamping member is maintained along an x-axis and a y-axis to reduce, or eliminate, any unintentional deformation and/or stress imparted on tissue positioned between a loading member and a clamping member.

(169) Step **1336** can be accomplished using any suitable technique or method of removing tissue from a loading member and selection of a suitable technique or method can be based on various considerations, including the structural arrangement of a loading member. Examples of techniques and methods considered suitable include using the hands of an individual, using automated robotics systems, convention tools, such as hand tools, and any other technique or method considered suitable for a particular embodiment. In an alternative embodiment, an appropriately sized punch could be used to detach the tissue without removing a clamping member, which would complete any desired trimming while concurrently removing the tissue from a loading member.

(170) An optional step that can be completed prior to, or subsequent to, step **1336** comprises trimming the tissue into a desired geometry (e.g., circular). For example, in some embodiments, the

portion of tissue disposed between the clamping member and the loading member (e.g., adjacent an O-ring) will not have desired properties and can be discarded. Another optional step that can be completed prior to, or subsequent to, step **1336** comprises marking the orientation of the tissue. (171) Step **1338** can be accomplished by placing the tissue in any suitable fluid for any period of time. Examples of suitable fluids include chemical fixatives, such as aldehydes, e.g., formaldehyde, glutaraldehyde, and formalin, and carbodiimides, such as ethyl dimethylaminopropyl carbodiimide, dicyclohexylcarbodiimide, solutions, storage solutions, tanning agents, tanning agents in a buffering solution, and any other fluid considered suitable for a particular embodiment. Examples of suitable period of time include one or more minutes, hours, days, weeks, months, and any other period of time considered suitable for a particular embodiment. For example, the tissue can be placed within a fixation solution for twenty hours.

(172) An optional step that can be completed subsequent to step **1338** comprises placing the tissue in a storage solution and storing at about 4° C. Alternative embodiments, however, could store the tissue at other temperatures, such as those equal to, greater than, less than, or about 3° C., 4° C., 5° C., and any other temperature considered suitable for a particular embodiment.

(173) Any of the materials described herein (e.g., tissue) can be processed using the systems, apparatus, methods, steps, alternative steps, and/or optional steps described herein to produce a product, such as a tissue product, that is processed using differential pressure. For example, a sheet of tissue that is produced through the application of differential pressure using one or more of the systems and/or apparatus described herein and/or using one or more of the methods, steps, alternative steps, and/or optional steps described herein can be claimed.

(174) In alternative embodiments, depending on the permeability of the tissue being processed, step **1304**, step **1310**, step **1318**, step **1326**, and/or step **1328** can be omitted from method **1300**. For example, these steps can be omitted from a method of processing tissue in embodiments in which the tissue being processed is impermeable, or substantially impermeable, and/or a tank does not define a second passageway (e.g., second passageway **36**) and a fourth passageway (e.g., fourth passageway **40**).

(175) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1300**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method **1400**, example method **1500**, and/or example method **1600**.

(176) FIG. **36** is a schematic illustration of another example method **1400** of processing tissue.

(177) A step **1402** comprises adjusting the position of a first tank relative to a second tank and a holding member along a vertical axis. The holding member has tissue disposed between a loading member and a clamping member. Another step **1404** comprises connecting the first tank to a pump such that the first portion of the first tank is in fluid communication with the pump. Another step **1406** comprises connecting the second tank to the pump such that the first portion of the second tank is in fluid communication with the pump. Another step **1408** comprises connecting the first tank to a holding member such that the first portion of the first tank is in fluid communication with the holding member. Another step **1410** comprises connecting the second tank to the holding member such that the first portion of the second tank is in fluid communication with the holding member. Another step **1412** comprises connecting the first tank to a reservoir such that the first tank is in fluid communication with the reservoir. Another step **1414** comprises connecting the second tank to the reservoir such that the second tank is in fluid communication with the reservoir. Another step **1416** comprises connecting the pump to the reservoir such that the pump is in fluid communication with the reservoir. Another step **1418** comprises introducing fluid into the tank. Another step **1420** comprises opening a vent on the loading member. Another step **1422** comprises opening a vent on the clamping member. Another step **1424** comprises activating the pump. Another step **1426** comprises introducing fluid into reservoir while the pump is in an on state.

Another step **1428** comprises closing the vent on the loading member. Another step **1430** comprises closing the vent on the clamping member. Another step **1432** comprises maintaining the pump in the on state for a period of time such that a differential pressure is applied to the tissue. Another step **1434** comprises deactivating the pump. Another step **1436** comprises draining the holding member. Another step **1438** comprises disassembling the holding member. Another step **1440** comprises removing the clamping member. Another step **1442** comprises removing the tissue from the loading member. Another step **1444** comprises placing the tissue in a fluid for a period of time. (178) Step **1402** can be accomplished by adjusting the position of any suitable first tank relative to any suitable second tank and any suitable holding member. For example, the first tank **212** illustrated in FIG. **6** can be adjusted relative to the second tank **320** and the holding member **214**. An optional step comprises confirming that each of the first tank, the second tank, and/or the holding member is level.

(179) Step **1404** can be accomplished by attaching a first elongate tubular member to the first tank and the pump such that the first portion of the first tank is in fluid communication with the pump.

(180) Step **1406** can be accomplished by attaching a second elongate tubular member to the second tank and the pump such that the first portion of the second tank is in fluid communication with the pump.

(181) Step **1408** can be accomplished by attaching a third elongate tubular member to the first tank and the holding member such that the first portion of the first tank is in fluid communication with the holding member (e.g., first holding member chamber).

(182) Step **1410** can be accomplished by attaching a fourth elongate tubular member to the second tank and the holding member such that the first portion of the second tank is in fluid communication with the holding member (e.g., second holding member chamber).

(183) Step **1412** can be accomplished by attaching a fifth elongate tubular member to the first tank and the reservoir such that the second portion (e.g., second recess) of the first tank is in fluid communication with the reservoir.

(184) Step **1414** can be accomplished by attaching a sixth elongate tubular member to the second tank and the reservoir such that the second portion (e.g., second recess) of the second tank is in fluid communication with the reservoir.

(185) Step **1416** can be accomplished by attaching a seventh elongate tubular member to the reservoir and the pump such that the reservoir is in fluid communication with the pump. Depending on the structural arrangement of a differential pressure material processing system, in alternative embodiments steps **1402** through **1416** could be omitted from a method of processing tissue when a system is preconfigured as described with respect to steps **1402** through **1416**.

(186) Step **1418** can be accomplished as described above with respect to step **1312** but can be accomplished with respect to both the first portion of the first tank and the first portion of the second tank. Alternatively, or in combination with introducing fluid into the first tank and the second tank, another step comprises introducing fluid to the reservoir.

(187) Step **1420** and step **1422** can be accomplished as described above with respect to step **1314** and step **1316**. Step **1424** can be accomplished as described above with respect to step **1318**. Step **1426** can be accomplished as described above with respect to step **1320**. Step **1428** and step **1430** can be accomplished as described above with respect to step **1322** and step **1324**.

(188) Step **1432** can be accomplished as described above with respect to step **1326**. The differential pressure being applied to tissue can vary during a method of processing tissue due to the permeability of the tissue, which results in fluid passing through the tissue from a first holding member chamber to a second holding member chamber. Therefore, an optional step comprises adjusting the differential pressure being applied to the tissue. This optional step can be accomplished by adjusting the rate of fluid being pumped by the pump, adjusting the height of a first tank relative to a second tank and/or a holding member, and/or any other technique or method considered suitable for a particular embodiment. Another optional step comprises determining the

pressure differential between the first holding member chamber and second holding member chamber. This optional step allows for a determination as to whether an adjustment to the differential pressure is necessary and can be accomplished using a first pressure transducer disposed within the first holding member chamber and a second pressure transducer disposed within the second holding member chamber. Another optional step comprises determining the characteristics of the tissue. This optional step can be accomplished using an ultrasound transducer in communication with one, or both, of the first holding member chamber and second holding member chamber. These optional steps can be accomplished while a pump is in an on state and a differential pressure is being applied to the tissue.

(189) Step **1434** can be accomplished as described above with respect to step **1328**. Step **1436** can be accomplished as described above with respect to step **1330**. Step **1438** can be accomplished as described above with respect to step **1332**. Step **1440** can be accomplished as described above with respect to step **1334**. Step **1442** can be accomplished as described above with respect to step **1336**. Step **1444** can be accomplished as described above with respect to step **1338**.

(190) In alternative embodiments, depending on the permeability of the tissue being processed, step **1404**, step **1406**, step **1412**, step **1414**, step **1416**, step **1424**, step **1432**, and/or step **1434** can be omitted from method **1400**. For example, these steps can be omitted from a method of processing tissue in embodiments in which the tissue being processed is impermeable, or substantially impermeable, and/or a first tank does not define a second passageway (e.g., second passageway **236**) and a third passageway (e.g., third passageway **238**) and a second tank does not define a second passageway (e.g., second passageway **342**) and a third passageway (e.g., third passageway **344**).

(191) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1400**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method **1300**, example method **1500**, and/or example method **1600**.

(192) FIG. **37** is a schematic illustration of another example method **1500** of processing tissue.

(193) A step **1502** comprises positioning a holding member in a tank. The holding member has tissue disposed between a loading member and a clamping member. Another step **1504** comprises connecting the tank to a pump such that a first portion of the tank is in fluid communication with the pump. Another step **1506** comprises connecting the tank to a reservoir such that the second portion of the tank is in fluid communication with the reservoir. Another step **1508** comprises connecting the reservoir to the pump such that the reservoir is in fluid communication with the pump. Another step **1510** comprises introducing a fluid into the tank. Another step **1512** comprises adjusting the differential pressure between the first portion of the tank and the second portion of the tank. Another step **1514** comprises activating the pump. Another step **1516** comprises introducing fluid into the reservoir while the pump is in an on state. Another step **1518** comprises maintaining the pump in the on state for a period of time such that a differential pressure is applied to the tissue. Another step **1520** comprises deactivating the pump. Another step **1522** comprises removing the holding member from the tank. Another step **1524** comprises draining the holding member. Another step **1526** comprises disassembling the holding member. Another step **1528** comprises removing the clamping member from the loading member. Another step **1530** comprises removing tissue from the loading member. Another step **1532** comprises placing the tissue in a fluid for a period of time.

(194) Step **1502** can be accomplished by positioning any suitable holding member in any suitable tank. For example, the holding member **514** illustrated in FIG. **17** can be positioned within the tank **512**.

(195) Step **1504** can be accomplished by attaching a first elongate tubular member to the tank and the pump such that the first portion of the tank is in fluid communication with the pump.

(196) Step **1506** can be accomplished by attaching a second elongate tubular member to the tank and the reservoir such that the second portion of the tank is in fluid communication with the reservoir.

(197) Step **1508** can be accomplished by attaching a third elongate tubular member to the reservoir and the pump such that the reservoir is in fluid communication with the pump. Depending on the structural arrangement of a differential pressure material processing system, in alternative embodiments steps **1502** through **1508** could be omitted from a method of processing tissue when a system is preconfigured as described with respect to steps **1502** through **1508**.

(198) Step **1510** can be accomplished as described above with respect to step **1312**. In method **1500**, however, the fluid can be introduced into one, or both, of the first portion of the tank and the second portion of the tank.

(199) The differential pressure being applied to tissue can vary during a method of processing tissue due to the permeability of the tissue, which results in fluid passing through the tissue from a first holding member chamber to a second holding member chamber. Step **1512** can be accomplished by adjusting the rate of fluid being pumped by the pump, manipulating the position of one or more pistons of the plurality of pistons **624**, manipulating the position of the second passageway **536**, and/or any other technique or method considered suitable for a particular embodiment. An optional step comprises determining the pressure differential between the first holding member chamber and second holding member chamber. This optional step allows for a determination as to whether an adjustment to the differential pressure is necessary and can be accomplished using a first pressure transducer disposed within the first holding member chamber and a second pressure transducer disposed within the second holding member chamber. Another optional step comprises determining the characteristics of the tissue. This optional step can be accomplished using an ultrasound transducer in communication with one, or both, of the first holding member chamber and second holding member chamber. These optional steps can be accomplished while a pump is in an on state and a differential pressure is being applied to the tissue.

(200) Step **1514** can be accomplished as described above with respect to step **1318**. Step **1516** can be accomplished as described above with respect to step **1320**. Step **1518** can be accomplished as described above with respect to step **1326**. Step **1520** can be accomplished as described above with respect to step **1328**.

(201) Step **1522** can be accomplished by applying a force on the holding member away from the tank until the holding member is free of the tank.

(202) Step **1524** can be accomplished as described above with respect to step **1330**. Step **1526** can be accomplished as described above with respect to step **1332**. Step **1528** can be accomplished as described above with respect to step **1334**. Step **1530** can be accomplished as described above with respect to step **1336**. Step **1532** can be accomplished as described above with respect to step **1338**.

(203) In alternative embodiments, depending on the permeability of the tissue being processed, step **1504**, step **1506**, step **1508**, step **1514**, step **1518**, and/or step **1520** can be omitted from method **1500**. For example, these steps can be omitted from a method of processing tissue in embodiments in which the tissue being processed is impermeable, or substantially impermeable, and/or a tank does not define a first passageway (e.g., first passageway **534**) and a second passageway (e.g., third passageway **536**).

(204) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1500**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to the example method **1300**, example method **1400**, and/or example method **1600**.

(205) FIG. **38** is a schematic illustration of another example method **1600** of processing tissue.

(206) A step **1602** comprises positioning a holding member in a tank. The holding member has

tissue disposed between a loading member and a clamping member. Another step **1604** comprises introducing a fluid into the first portion of the tank. Another step **1606** comprises introducing fluid into a second portion of the tank. Another step **1608** comprises applying differential pressure to the tissue and between the first portion of the tank and the second portion of the tank. Another step **1610** comprises adjusting the differential pressure between the first portion of the tank and the second portion of the tank. Another step **1612** comprises maintaining the differential pressure on the tissue for a period of time. Another step **1614** comprises removing the differential pressure from the tissue. Another step **1616** comprises removing the holding member from the tank. Another step **1618** comprises draining the holding member. Another step **1620** comprises disassembling the holding member. Another step **1622** comprises removing the clamping member from the loading member. Another step **1624** comprises removing tissue from the loading member. Another step **1626** comprises placing the tissue in a fluid for a period of time.

(207) Step **1602** can be accomplished by positioning any suitable holding member in any suitable tank. For example, the holding member **814** illustrated in FIG. **19** can be positioned within the tank **812**.

(208) Step **1604** can be accomplished as described above with respect to step **1312** and relative to the first portion of the tank (e.g., first holding member chamber **864**).

(209) Step **1606** can be accomplished as described above with respect to step **1312** and relative to the second portion of the tank (e.g., second holding member chamber **866**).

(210) Step **1608** can be accomplished by applying a force (e.g., torque) on the actuator to move it to its second position.

(211) The differential pressure being applied to tissue can vary during a method of processing tissue due to the permeability of the tissue, which results in fluid passing through the tissue from a first holding member chamber to a second holding member chamber. Step **1610** can be accomplished by adjusting the rate of fluid being pumped by the pump, adjusting the position of the actuator between its first and second positions, and/or any other technique or method considered suitable for a particular embodiment. Optionally, step **1610** can be omitted from method **1600** in embodiments in which adjustment is not required. An optional step comprises determining the pressure differential between the first holding member chamber and second holding member chamber. This optional step allows for a determination as to whether an adjustment to the differential pressure is necessary and can be accomplished using a first pressure transducer disposed within the first holding member chamber and a second pressure transducer disposed within the second holding member chamber. Another optional step comprises determining the characteristics of the tissue. This optional step can be accomplished using an ultrasound transducer in communication with one, or both, of the first holding member chamber and second holding member chamber. These optional steps can be accomplished while a pump is in an on state and a differential pressure is being applied to the tissue.

(212) Step **1612** can be accomplished by maintaining the position of the actuator.

(213) Step **1614** can be accomplished by applying a force (e.g., torque) on the actuator to move it to its first position or a position in which no differential pressure is applied to the tissue.

(214) Step **1616** can be accomplished by applying a force on the holding member away from the tank until the holding member is free of the tank.

(215) Step **1618** can be accomplished as described above with respect to step **1330**. Step **1620** can be accomplished as described above with respect to step **1332**. Step **1622** can be accomplished as described above with respect to step **1334**. Step **1624** can be accomplished as described above with respect to step **1336**. Step **1626** can be accomplished as described above with respect to step **1338**.

(216) While various steps, alternative steps, and optional steps have been described above with respect to the example method **1600**, these steps, alternative steps, and optional steps can be included in, accomplished concurrently with, and/or accomplished in the alternative to, the method, steps, alternative steps, and/or optional steps described herein with respect to example method

1300, example method **1400**, and/or example method **1500**.

(217) FIGS. **39**, **40**, **41**, **42**, **43**, **44**, **45**, and **46** provide graphical representations illustrating a comparison of a load response over time in the x-axis and y-axis of tissue fixed in a fixative using currently available processing techniques and tissue fixed in a fixative using the differential pressure material processing systems, apparatus, and methods described herein. In each of the groups tested, the sample geometry, total deformation, and loading rate were the same.

(218) As shown, the data relating to the tissue processed using the differential pressure material processing systems, apparatus, and methods described herein, both for a given fixation pressure and across fixation pressures, is tightly grouped in terms of maximum load achieved and the shape of the curves and the data relating to the tissue processed using currently available processing techniques varies greatly. The consistency in the tissue processed using the differential pressure material processing systems, apparatus, and methods described herein is considered advantageous at least because it allows for repeatable tissue fabrication and tissue function, such as when the tissue is formed as a valve or a portion of a valve. In addition, the data indicates that tissues processed using currently available processing techniques are stiffer than tissues processed using the differential pressure material processing systems, apparatus, and methods described herein. It is considered advantageous to form low stiffness tissues at least because such tissues, when formed as a valve or a portion of a valve, are responsive to small pressure differentials in vivo.

(219) FIG. **39** is a graphical representation of a load response over time in the x-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde using current processing techniques (e.g., techniques known to those who are experts in the field). FIG. **40** is a graphical representation of a load response over time in the y-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde using current processing techniques (e.g., techniques known to those who are experts in the field). FIG. **41** is a graphical representation of a load response over time in the x-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 0.25 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein. FIG. **42** is a graphical representation of a load response over time in the y-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 0.25 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein. FIG. **43** is a graphical representation of a load response over time in the x-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 0.5 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein. FIG. **44** is a graphical representation of a load response over time in the y-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 0.5 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein. FIG. **45** is a graphical representation of a load response over time in the x-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 1.0 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein. FIG. **46** is a graphical representation of a load response over time in the y-axis under equibiaxial loading conditions of porcine visceral pleura fixed in phosphate buffered, 0.625% glutaraldehyde at a differential pressure of 1.0 millimeters of mercury for four hours using the differential pressure material processing systems and methods described herein.

(220) FIGS. **47**, **48**, **49**, **50**, **51**, **52** illustrate an alternative holding member **1714** that can be used in a differential pressure material processing system, such as differential pressure material processing system **10**. The holding member **1714** is similar to the holding member **14** illustrated in FIGS. **1**, **4**,

and 5 and described above, except as detailed below. The holding member **1714** includes a loading member **1760**, a clamping member **1762** releasably attached to the loading member **1760**, and defines a first holding member chamber **1764**, a second holding member chamber **1766**, a plurality of passageways **1768** in communication with the first holding member chamber **1764** and second holding member chamber **1766**, a first input port **1774**, and a second input port **1776**. The loading member **1760** defines a first guide member **1790**, the first input port **1774**, and a plurality of support members **1792** spanning each passageway of the plurality of passageways **1768** and the clamping member **1762** defines a second guide member **1798** and the second input port **1776**. FIGS. **48**, **49**, **50**, **51**, and **52** illustrate a single support member **1792** and associated structure for clarity. However, the position of the remaining support members of the plurality of support members **1792** has been illustrated. For clarity, the illustrated embodiment omits the inclusion of drains and vents, such as those described herein. However, holding member **1714** can include one or more drains and/or one or more vents, such as those described herein.

(221) In the illustrated embodiment, the loading member **1760** has a first portion **1802** and a second portion **1804** releasably attached to the first portion **1802**. Each support member of the plurality of support members **1792** is movable between a first position, as shown in FIGS. **51** and **52**, and a second position, as shown in FIGS. **48**, **49**, and **50**. The first holding member chamber **1764** is cooperatively defined by the first portion **1802** and the second portion **1804**.

(222) The first portion **1802** has a main body **1808** that defines a top surface **1810**, a bottom surface **1812**, a first plurality of passageways **1814**, and a second plurality of passageways **1816**. The figures illustrate a single passageway of the second plurality of passageways **1816**. However, a passageway of the plurality of second passageways **1816** will be defined for each support member of the plurality of support members **1792**. Each passageway of the first plurality of passageways **1814** extends through the main body **1808** from the top surface **1810** to the bottom surface **1812** and is sized and configured to receive a portion of a fastener **1818** such that releasable attachment between the first portion **1802** and the second portion **1804** can be accomplished. Each passageway of the second plurality of passageways **1816** extends through the main body **1808** from the top surface **1810** to the bottom surface **1812** and is sized and configured to a portion of a support member of the plurality of support members **1792**, as described in more detail herein. Each passageway of the second plurality of passageways **1816** has a first portion **1820**, a second portion **1822**, and a third portion **1824**. The first portion **1820** extends from the bottom surface **1812** to the second portion **1822** and has a first inside diameter **1821**. The second portion **1822** is disposed between the first portion **1820** and the third portion **1824** and has a second inside diameter **1823**. The third portion **1824** extends from the second portion **1822** to the top surface **1810** and has a third inside diameter **1825**. The first inside diameter **1821** is greater than the second inside diameter **1823**. The second inside diameter **1823** is less than the third inside diameter **1825**.

(223) The second portion **1804** has a main body **1830** that defines a top surface **1832**, a bottom surface **1834**, a first plurality of passageways **1836**, a second plurality of passageways **1838**, a recess **1840**, a plurality of support posts **1842**, and a plurality of recesses **1844**. Each passageway of the first plurality of passageways **1836** extends through the main body **1830** from the top surface **1832** to the bottom surface **1834** and is sized and configured to receive a portion of a fastener **1818** such that releasable attachment between the first portion **1802** and the second portion **1804** can be accomplished. Each passageway of the second plurality of passageways **1838** comprises a first portion **1839** of each passageway of the plurality of passageways **1768**, as described in more detail herein, and has an inside diameter **1841**. The recess **1840** extends from the bottom surface **1834** toward the top surface **1832** to a recess base **1846**. Each passageway of the second plurality of passageways **1838** extends from the top surface **1832** to the recess base **1846**. As shown in FIG. **52**, the main body **1830** defines an angled edge **1847** from the recess base **1846** to the opening defining a passageway of the second plurality of passageways **1838**, which allows for the shedding of air bubbles when the holding member **1714** is being filled with fluid. Each support post of the plurality

of support posts **1842** extends from the recess base **1846** to a hypothetical plane that includes the bottom surface **1834**. Each support post of the plurality of support posts **1842** is sized and configured to contact a support member and guide the support member toward the opening defining a passageway of the second plurality of passageways **1838**. Each recess of the plurality of recesses **1844** surrounds a passageway of the second plurality of passageways **1838**.

(224) As shown in FIG. **52**, each support member of the plurality of support members **1792** includes a plate **1850**, an elongate member **1852**, a spring **1854**, a first O-ring **1856**, a second O-ring **1858**, and a locking plate **1860**. The plate **1850** defines a support surface **1862** and a recess **1864**. In the illustrated embodiment, the plate **1850** has an outside diameter **1851** that is less than the inside diameter **1841** of a passageway of the second plurality of passageways **1768**. The support surface **1862** is not disposed on a hypothetical plane that includes the top surface **1832** of the second portion **1804** when the support member **1792** is in the first position and is disposed on a hypothetical plane that includes the top surface **1832** of the second portion **1804** when the support member **1792** is in the second position. In alternative embodiments, a plate can be perforated and/or sized such that the outside diameter is equal to, or substantially equal, the inside diameter of a passageway of a second plurality of passageways. The elongate member **1852** has a first end **1866** disposed within the recess **1864** and a second end **1868** disposed external to the first portion **1820** of a passageway of the second plurality of passageways **1816** when the support member **1792** is in the first position and within the first portion **1820** when in the second position. The second end **1868** has an outside diameter **1869** that is less than the first inside diameter **1821** and greater than the second inside diameter **1823**. The spring **1854** is a compression spring that is disposed between the second end **1868** of the elongate member **1852** and the second portion **1822** of a passageway of the second plurality of passageways **1816**. The spring **1854** biases the support member to the first position. The first O-ring **1856** is disposed within the first portion **1820** of a passageway of the second plurality of passageways **1816** between the first portion **1802** and the spring **1854**. The second O-ring **1858** is disposed within the third portion **1824** of a passageway of the second plurality of passageways **1816** between the first portion **1802** and the locking plate **1860**. The locking plate **1860** is disposed between the plate **1850** and the second O-ring **1858** when the support member **1792** is in the first position. The locking plate **1860** is attached to the first portion **1802** using fasteners **1861**.

(225) A loading member and/or support member can be formed of any suitable material and selection of a suitable material can be based on various considerations, including the tissue intended to be processed. Examples of materials considered suitable to form a loading member and/or a portion, or the entirety, of a support member include those described herein, low-friction materials, such as Teflon, materials that include a pre-applied lubricous coating, and any other material considered suitable for a particular embodiment.

(226) In the illustrated embodiment, the clamping member **1762** has a first portion **1870** and a second portion **1872** releasably attached to the first portion **1870**. The second holding member chamber **1766** is cooperatively defined by the first portion **1870** and the second portion **1872**.

(227) The first portion **1870** has a main body **1874** that defines a top surface **1876**, a bottom surface **1878**, and a first plurality of passageways **1880**. Each passageway of the first plurality of passageways **1880** extends through the main body **1874** from the top surface **1876** to the bottom surface **1878** and is sized and configured to receive a portion of a fastener **1818** such that releasable attachment between the first portion **1870** and the second portion **1872** can be accomplished.

(228) The second portion **1872** has a main body **1882** that defines a top surface **1884**, a bottom surface **1886**, a first plurality of passageways **1888**, a second plurality of passageways **1890**, a recess **1892**, a plurality of support posts **1894**, and a plurality of recesses **1896**. Each passageway of the first plurality of passageways **1888** extends through the main body **1882** from the top surface **1884** to the bottom surface **1886** and is sized and configured to receive a portion of a fastener **1818** such that releasable attachment between the first portion **1870** and the second portion **1872** can be

accomplished. Each passageway of the second plurality of passageways **1890** comprises a second portion **1891** of each passageway of the plurality of passageways **1768**, as described in more detail herein. The recess **1892** extends from the top surface **1884** toward the bottom surface **1886** to a recess base **1898**. Each support post of the plurality of support posts **1894** extends from the recess base **1898** toward a hypothetical plane that includes the top surface **1884**. Each recess of the plurality of recesses **1896** surrounds a passageway of the second plurality of passageways **1890**. A sealing member **1800** is disposed within each recess of the plurality of recesses **1896**. Each sealing member **1800** contacts a portion of the loading member **1760** disposed between a recess of the plurality of recesses **1844** and a passageway of the second plurality of passageways **1838** when the clamping member **1762** is releasably attached to the loading member **1760**. In the illustrated embodiment, each sealing member **1800** contacts the top surface **1832** of the second portion **1804** of the loading member **1760**. This arrangement allows for excess tissue to be disposed within a recess of the plurality of recesses **1844** when the clamping member **1762** is releasably attached to the loading member **1760**. In alternative embodiments, a plurality of recesses **1844** could be omitted from a second portion **1804** of a loading member **1760** and a main body of a second portion of a loading member could define a single recess that extends from a top surface defining an opening toward a bottom surface such that the openings to a plurality of passageways are defined by a plurality of projections.

(229) In use, each support member of the plurality of support members **1792** is in the first position when the bottom surface **1812** of the first portion **1802** is free of contact from a platform (e.g., a side **1715** of the holding member **1714** is positioned on a platform or table). Each support member of the plurality of support members **1792** is in the second position when the bottom surface **1812** of the first portion **1802** is positioned on a platform and contacts the platform resulting in the springs **1854** contracting and the plates **1850** being disposed on a hypothetical plane with the top surface **1832** of the second portion **1804**.

(230) Those with ordinary skill in the art will appreciate that various modifications and alternatives for the described and illustrated embodiments can be developed in light of the overall teachings of the disclosure. Accordingly, the particular arrangements disclosed are intended to be illustrative only and not limiting as to the scope of the invention, which is to be given the full breadth of the appended claims and any and all equivalents thereof.

Claims

1. A differential pressure material processing system for processing tissue using a fluid, the system comprising: a tank defining a first portion and a second portion; and a holding member comprising a loading member and a clamping member releasably attached to the loading member, the loading member defining a first holding member chamber in fluid communication with the first portion of the tank, the clamping member defining a second holding member chamber in fluid communication with the second portion of the tank, the loading member and the clamping member cooperatively defining a passageway in fluid communication with the first holding member chamber and the second holding member chamber, said fluid having a first pressure when disposed within the first portion of the tank and the first holding member chamber, said fluid having a second pressure when disposed within the second portion of the tank and the second holding member chamber, the second pressure being different than the first pressure; wherein said tissue is disposed between the loading member and the clamping member such that a portion of said tissue spans an entire cross-section of the passageway to obstruct the passageway; and wherein the first portion of the tank and the second portion of the tank are separated by a first non-permeable wall.

2. The system of claim 1, further comprising a reservoir; and further comprising a pump having an inlet port and an outlet port, the outlet port in fluid communication with the first portion of the tank and the inlet port in fluid communication with the reservoir.

3. The system of claim 2, wherein the pump has an on state and an off state; and wherein the passageway is obstructed by said tissue when the pump is in the on state and the off state.
 4. The system of claim 2, wherein the reservoir is defined by the tank.
 5. The system of claim 1, wherein the loading member defines a perforated support member across the passageway.
 6. The system of claim 1, wherein the loading member defines a support member across the passageway that is moveable between a first position and a second position.
 7. The system of claim 6, wherein the support member is perforated.
 8. The system of claim 1, wherein the loading member includes a first guide member and the clamping member includes a second guide member that mates with the first guide member to prevent movement of the loading member relative to the clamping member along an x-axis and a y-axis during releasable attachment of the clamping member to the loading member.
 9. The system of claim 1, wherein the loading member defines a first portion of the passageway and the clamping member defines a second portion of the passageway such that the first portion of the passageway and the second portion of the passageway cooperatively define the passageway.
 10. The system of claim 9, wherein the clamping member includes a sealing member that surrounds the second portion of the passageway defined by the clamping member.
 11. The system of claim 1, further comprising a first pressure transducer in communication with the first holding member chamber.
 12. The system of claim 1, further comprising an ultrasound transducer in communication with the first holding member chamber.
 13. The system of claim 1, wherein the holding member is releasably disposed within the tank.
 14. A differential pressure material processing system for processing tissue using a fluid, the system comprising: a tank defining a first portion and a second portion; a holding member comprising a loading member and a clamping member releasably attached to the loading member, the loading member defining a first holding member chamber in fluid communication with the first portion of the tank, the clamping member defining a second holding member chamber in fluid communication with the second portion of the tank, the loading member and the clamping member cooperatively defining a passageway in fluid communication with the first holding member chamber and the second holding member chamber, said fluid having a first pressure when disposed within the first portion of the tank and the first holding member chamber, said fluid having a second pressure when disposed within the second portion of the tank and the second holding member chamber, the second pressure being less than the first pressure; a reservoir; and a pump having an inlet port and an outlet port, the outlet port in fluid communication with the first portion of the tank and the inlet port in fluid communication with the reservoir; wherein said tissue is disposed between the loading member and the clamping member such that a portion of said tissue spans an entire cross-section of the passageway to obstruct the passageway; and wherein the first portion of the tank and the second portion of the tank are separated by a first non-permeable wall.
 15. The system of claim 1, wherein the first portion of the tank and the first holding member chamber are different; and wherein the second portion of the tank and the second holding member chamber are different.
-