

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398986
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Martin; Thomas

Firearm projectile device

Abstract

A firearm projectile device is provided. The device is comprised of a projectile body with a partially hollow area that allows air to travel through the projectile and reduces the projectile's coefficient of drag. Both ends of the device are preferably pointed to further reduce the coefficient of drag of the device. In addition, the second end attaches to a fitted gas block that seals the projectile from a propellant within the casing of the device.

Inventors:	Martin; Thomas (Emmett, ID)
Applicant:	Martin; Thomas (Emmett, ID)
Family ID:	1000008781406
Appl. No.:	18/600856
Filed:	March 11, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250198732 A1	Jun. 19, 2025

Related U.S. Application Data

us-provisional-application US 63584942 20230925

Publication Classification

Int. Cl.: F42B10/42 (20060101); F42B12/76 (20060101); F42B30/02 (20060101)

U.S. Cl.:

CPC F42B10/42 (20130101); F42B12/76 (20130101); F42B30/02 (20130101);

Field of Classification Search

CPC: F42B (10/42); F42B (12/76); F42B (30/02)

USPC: 102/501

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3881421	12/1974	Burczynski	N/A	N/A
4945836	12/1989	Michaels	102/517	F42B 10/34
5079814	12/1991	Moore	N/A	N/A
5208424	12/1992	Schluckebier	N/A	N/A
11378368	12/2021	Peterson	N/A	F42B 14/02
2016/0169644	12/2015	Ziegler	244/3.23	F42B 10/38
2020/0256656	12/2019	Thielen	N/A	F42B 10/46

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2589300	12/2017	CA	F42B 10/34
202005011174	12/2004	DE	F41A 21/16
1351666	12/1973	GB	F42B 10/54
2422419	12/2005	GB	F42B 10/34
20200070011	12/2019	KR	N/A
2730826	12/2023	KR	F16C 41/00
WO-2018176157	12/2017	WO	F42B 10/38
WO-2023272387	12/2022	WO	F42B 10/38

Primary Examiner: Abdosh; Samir

Attorney, Agent or Firm: Brennan, Manna & Diamond, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application claims priority to, and the benefit of, U.S. Provisional Application No. 63/584,942, which was filed on Sep. 25, 2023, and is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

(1) The present invention relates generally to the field of firearm projectiles. More specifically, the present invention relates to a firearm projectile device that in one embodiment is partially hollow such that the projectile has a reduced coefficient of drag. Accordingly, the present disclosure makes specific reference thereto. Nonetheless, it is to be appreciated that aspects of the present invention are also equally applicable to other like applications, devices, and methods of manufacture.

BACKGROUND

(2) Enhancing the aerodynamic properties of a projectile by decreasing its coefficient of drag (CdA) significantly improves its performance in flight. When the drag is minimized, the projectile can travel greater distances with reduced energy loss, thereby ensuring a more efficient trajectory.

Conversely, when a projectile is slowed down due to higher drag or other factors, its range diminishes. This reduction in speed compromises the effective distance the user can achieve, making it crucial to optimize the aerodynamic properties for maximum range and efficiency.

(3) Traditional bullets and many other types of projectiles have designs that have been refined over the centuries. Their shapes, while efficient for their intended purposes such as stability in flight or terminal performance, may not be perfectly optimized for aerodynamics. Traditional bullet designs prioritize stability and rotational balance. Spitzer or round-nose designs, while stable, may not be the most aerodynamic shapes. The boundary layer of air around the bullet can become turbulent, increasing drag and thus reducing the distance the projectile can travel.

(4) Therefore, there exists a long-felt need in the art for a projectile that increases the range and effectiveness of a firearm and/or artillery. There also exists a long-felt need in the art for a firearm projectile device. More specifically, there exists a long-felt need in the art for a firearm projectile device that increases the range and effectiveness of a firearm and/or artillery by decreasing the coefficient of drag on the projectile when fired.

(5) The subject matter disclosed and claimed herein, in one embodiment thereof, comprises a firearm projectile device. The device is comprised of a projectile body with a partially hollow area that allows air to travel through the projectile and reduces the projectile's coefficient of drag. Both ends of the device are preferably pointed to further reduce the coefficient of drag of the device. In addition, the second end attaches to a fitted gas block that seals the projectile from a propellant within the casing of the device.

(6) In this manner, the firearm projectile device of the present invention accomplishes all the foregoing objectives and provides an improved projectile that increases the range and effectiveness of a firearm and/or artillery. More specifically, the device increases the range and effectiveness of a firearm and/or artillery. To do so, the hollow configuration of the device decreases the coefficient of drag on the projectile when fired.

SUMMARY

(7) The following presents a simplified summary to provide a basic understanding of some aspects of the disclosed innovation. This summary is not an extensive overview, and it is not intended to identify key/critical elements or to delineate the scope thereof. Its sole purpose is to present some general concepts in a simplified form as a prelude to the more detailed description that is presented later.

(8) The subject matter disclosed and claimed herein, in one embodiment thereof, comprises a firearm projectile device. The device is comprised of a projectile body with a first pointed end and a second pointed end, wherein at least one gas block is fixedly attached to the second end. The device provides a projectile with a lower drag coefficient than existing projectiles/bullets to improve projectile performance.

(9) The body of the device may be made from any projectile material known in the art. The body may also be sized and dimensions for use with any caliber or type of firearm/artillery. In one embodiment, the body is a solid body of continuous construction. In another embodiment, the body is comprised of at least one hollow area that preferably runs the length of the body but terminates at the second end. This embodiment allows more air to pass through the body thus reducing drag and resistance when the device is traveling through the air.

(10) The first end and second end of the body are each comprised of a pointed angle. Said angle is preferably, but is not limited to, 1.74 degrees. The second is also fixedly attached to at least one gas block which seals exploding gases from the propellant such that the body is propelled out of the casing and barrel of the firearm. The device may also be comprised of a propellant and a primer.

(11) The present invention is also comprised of a method of using the device. First, a device is provided comprised of a body comprised of a hollow area, at least one gas block attached to a second end of the body, at least one primer, at least one propellant, and at least one casing. Then, the second end of the body is attached to the gas block. Next, the second end, gas block, propellant,

and primer are placed into the casing. Then, the device **100** can be fired from a firearm and/or artillery.

(12) Accordingly, the firearm projectile device of the present invention is particularly advantageous as it provides an improved projectile that increases the range and effectiveness of a firearm and/or artillery. More specifically, the device increases the range and effectiveness of a firearm and/or artillery. To do so, the hollow configuration of the device decreases the coefficient of drag on the projectile when fired. In this manner, the firearm projectile device overcomes the limitations of existing projectiles known in the art.

(13) To the accomplishment of the foregoing and related ends, certain illustrative aspects of the disclosed innovation are described herein in connection with the following description and the annexed drawings. These aspects are indicative, however, of but a few of the various ways in which the principles disclosed herein can be employed and are intended to include all such aspects and their equivalents. Other advantages and novel features will become apparent from the following detailed description when considered in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The description refers to provided drawings in which similar reference characters refer to similar parts throughout the different views, and in which:

(2) FIG. 1 illustrates a side cross-sectional view of one potential embodiment of a firearm projectile device of the present invention in accordance with the disclosed architecture; and

(3) FIG. 2 illustrates a flowchart of a method of using one potential embodiment of a firearm projectile device of the present invention in accordance with the disclosed architecture.

DETAILED DESCRIPTION

(4) The innovation is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth to provide a thorough understanding thereof. It may be evident, however, that the innovation can be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form to facilitate a description thereof. Various embodiments are discussed hereinafter. It should be noted that the figures are described only to facilitate the description of the embodiments. They are not intended as an exhaustive description of the invention and do not limit the scope of the invention. Additionally, an illustrated embodiment need not have all the aspects or advantages shown. Thus, in other embodiments, any of the features described herein from different embodiments may be combined.

(5) As noted above, there exists a long-felt need in the art for a projectile that increases the range and effectiveness of a firearm and/or artillery. There also exists a long-felt need in the art for a firearm projectile device. More specifically, there exists a long-felt need in the art for a firearm projectile device that increases the range and effectiveness of a firearm and/or artillery by decreasing the coefficient of drag on the projectile when fired.

(6) The present invention, in one exemplary embodiment, is comprised of a firearm projectile device comprised of a projectile body with a first pointed end and a second pointed end. Further, at least one gas block is fixedly attached to the second end. The device provides a projectile with a lower drag coefficient than existing projectiles/bullets to improve projectile performance.

(7) The body of the device may be made from any projectile material known in the art and may also be sized and dimensions for use with any caliber or type of firearm/artillery. In one embodiment, the body is a solid body of continuous construction. In another embodiment, the body is comprised of at least one hollow area that preferably runs the length of the body but terminates at the second end. This embodiment allows more air to pass through the body thus reducing drag and

resistance when the device is traveling through the air.

(8) The first end and second end of the body are each comprised of a pointed angle that is preferably, but is not limited to, 1.74 degrees. The second is also fixedly attached to at least one gas block which seals exploding gases from the propellant such that the body is propelled out of the casing and barrel of the firearm. The device may also be comprised of a propellant and a primer.

(9) The present invention is also comprised of a method of using the device. First, a device is provided comprised of a body comprised of a hollow area, at least one gas block attached to a second end of the body, at least one primer, at least one propellant, and at least one casing. Then, the second end of the body is attached to the gas block. Next, the second end, gas block, propellant, and primer are placed into the casing. Then, the device **100** can be fired from a firearm and/or artillery.

(10) Accordingly, the firearm projectile device of the present invention is particularly advantageous as it provides an improved projectile that increases the range and effectiveness of a firearm and/or artillery. More specifically, the device increases the range and effectiveness of a firearm and/or artillery. To do so, the hollow configuration of the device decreases the coefficient of drag on the projectile when fired. In this manner, the firearm projectile device overcomes the limitations of existing projectiles known in the art.

(11) Referring initially to the drawings, FIG. **1** illustrates a side cross-sectional view of one potential embodiment of a firearm projectile device **100** of the present invention in accordance with the disclosed architecture. The device **100** is comprised of a projectile body **110** with a first pointed end **120** and a second pointed end **130**, wherein at least one gas block **140** is fixedly attached to the second end **130**. The device **100** provides a projectile with a lower drag coefficient than existing projectiles/bullets to improve projectile performance.

(12) The body **110** of the device **100** may be made from any projectile material known in the art. Said material includes, but is not limited to, lead, copper, steel, tungsten, depleted uranium, bismuth, tin, polymer, rubber, aluminum, etc., or any combination thereof.

(13) The body **110** may be sized and dimensions for use with any caliber or type of firearm/artillery. This includes bullet/projectile sizes such as, but is not limited to, .22 LR, 9 mm Parabellum, .45 ACP, .380 ACP, .357 Magnum, .308 Winchester, .223 Winchester, 5.56×45 mm NATO, 7.62×39 mm, 7.62×51 mm, 12-gauge slug, .50 BMG, 20 mm, 105 mm Howitzer, 155 mm Howitzer, 88 mm, 40 mm, etc.

(14) In one embodiment, the body **110** is a solid body of continuous construction. In another embodiment, the body **110** is comprised of at least one hollow area **112**. The area **112** preferably runs the length **114** of the body **110** but terminates at the second end **130** (or maybe completely hollow in one embodiment). The diameter/size of the area **112** may be different in different embodiments. A hollow embodiment of the body **110** allows more air to pass through the body **110** reducing drag and resistance.

(15) The body **110** is comprised of a first end **120** with a first pointed angle **122**. The angle **122** is preferably, but is not limited to, 1.74 degrees. The second end **130** of the body **110** is also comprised of at least one pointed angle **132**. The angle **132** is preferably, but is not limited to, 1.74 degrees. The angles **122**, **132** further reduce the coefficient of drag of the body **110** during flight.

(16) The second **130** is also fixedly attached to at least one gas block **140**. The gas block **140** is preferably the same diameter as the body **110**. The gas block **140** seals exploding gases from the propellant **160** such that the body **110** is propelled out of the casing **170** and barrel of the firearm. The device **100** may also be comprised of a primer **150** of any type and strength such as, but not limited to, a boxer primer, a Berdan primer, a rimfire primer, a centerfire primer, an electric primer, a percussion primer, a stab primer, a tube primer, etc. The propellant **160** may be any type of firearm and/or artillery propellant known in the art such as, but not limited to, black powder, smokeless powder, single base powder, double base powder, triple base powder, cordite, ballistite, EC powder, extruded powder, ball powder, flake powder, composite propellants, etc. The second

end **130**, gas block **140**, primer **150**, and propellant **160** are stored within a casing **170** of any size and configuration.

(17) The present invention is also comprised of a method of using **200** the device **100**, as seen in FIG. **2**. First, a device **100** is provided comprised of a body **110** comprised of a first pointed end **120**, a second pointed end **130**, and a hollow area **112**, at least one gas block **140** attached to a second end **130** of the body **110**, at least one primer **150**, at least one propellant **160**, and at least one casing **170** [Step **202**]. Then, the second end **130** of the body **110** is attached to the gas block **140** [Step **204**]. Next, the second end **130**, gas block **140**, propellant **160**, and primer **150** are placed into the casing **170** [Step **206**]. Then, the device **100** can be fired from a firearm and/or artillery [Step **208**].

(18) Certain terms are used throughout the following description and claims to refer to particular features or components. As one skilled in the art will appreciate, different persons may refer to the same feature or component by different names. This document does not intend to distinguish between components or features that differ in name but not structure or function. As used herein “firearm projectile device” and “device” are interchangeable and refer to the firearm projectile device **100** of the present invention.

(19) Notwithstanding the foregoing, the firearm projectile device **100** of the present invention and its various components can be of any suitable size and configuration as is known in the art without affecting the overall concept of the invention, provided that they accomplish the above-stated objectives. One of ordinary skill in the art will appreciate that the size, configuration, and material of the firearm projectile device **100** as shown in the FIGS. are for illustrative purposes only, and that many other sizes and shapes of the firearm projectile device **100** are well within the scope of the present disclosure. Although the dimensions of the firearm projectile device **100** are important design parameters for user convenience, the firearm projectile device **100** may be of any size, shape, and/or configuration that ensures optimal performance during use and/or that suits the user's needs and/or preferences.

(20) Various modifications and additions can be made to the exemplary embodiments discussed without departing from the scope of the present invention. While the embodiments described above refer to particular features, the scope of this invention also includes embodiments having different combinations of features and embodiments that do not include all the described features. Accordingly, the scope of the present invention is intended to embrace all such alternatives, modifications, and variations as fall within the scope of the claims, together with all equivalents thereof.

(21) What has been described above includes examples of the claimed subject matter. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the claimed subject matter, but one of ordinary skill in the art may recognize that many further combinations and permutations of the claimed subject matter are possible. Accordingly, the claimed subject matter is intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims. Furthermore, to the extent that the term “includes” is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

Claims

1. A firearm projectile device comprising: a body comprised of a pointed first end comprised of a first angle and a pointed second end comprised of a second angle, wherein the first angle is 1.74 degrees; a gas block attached to the pointed second end; a primer; a propellant; and a casing.
2. The firearm projectile device of claim 1, wherein the body is comprised of a lead, copper, a steel, a tungsten, a depleted uranium, a bismuth, a tin, a polymer, a rubber, or an aluminum.

3. The firearm projectile device of claim 1, wherein the body is comprised of a .22 LR bullet, a 9 MM Parabellum bullet, a .45 ACP bullet, a .380 ACP bullet, a .357 Magnum bullet, a .308 Winchester bullet, a .223 Winchester bullet, a 5.56×45 mm NATO bullet, a 7.62×9 mm bullet, a 7.62×51 mm bullet, a 12 gauge slug, a .50 BMG bullet, a 20 mm projectile, a 105 mm Howitzer projectile, a 155 mm Howitzer projectile, an 88 mm projectile, or a 40 mm projectile.
 4. The firearm projectile device of claim 1, wherein the body is comprised of a hollow area.
 5. The firearm projectile device of claim 4, wherein the hollow area begins at the first end and terminates at the second end.
 6. The firearm projectile device of claim 4, wherein the hollow area extends from the first end to the second end.
 7. The firearm projectile device of claim 1, wherein the second angle is 1.74 degrees.
 8. The firearm projectile device of claim 1, wherein the second end fixedly attaches to the gas block.
 9. The firearm projectile device of claim 1, wherein the diameter of the gas block is equal to the diameter of the body.
-