

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400178
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Spitz; Stephan et al.

Provisioning control apparatus, system and method

Abstract

A provisioning control apparatus is configured to be coupled to a provisioning equipment server, which is electrically connectable with one or more electronic devices for provisioning the one or more electronic devices with first or second program codes. The provisioning control apparatus comprises: a communication interface configured to receive an electronic credit token having a credit counter; and a processor. The communication interface is configured to transmit the first and second program codes towards the provisioning equipment server. The processor is configured to update a value of the credit counter for each transmission of the first and second program codes to obtain an updated credit counter, and to prohibit a further transmission of the first or second program codes if the updated credit counter indicates that a number of transmissions is reached. A provisioning control system comprises the apparatus and a corresponding method for provisioning one or more electronic devices.

Inventors: Spitz; Stephan (Karlsfeld, DE), Woodruff; Tim (Cambridge, GB), Hoole; Tim (Foxton, GB), Bott; Andrew (Cambridge, GB)

Applicant: Secure Thingz Ltd. (Cambridge, GB)

Family ID: 1000008781415

Assignee: SECURE THINGZ LTD. (Cambridge, GB)

Appl. No.: 17/231243

Filed: April 15, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210326801 A1	Oct. 21, 2021

Foreign Application Priority Data

EP	20170178	Apr. 17, 2020
----	----------	---------------

Publication Classification

Int. Cl.: **G06Q10/087** (20230101); **G06F21/10** (20130101); **H04L9/32** (20060101); **H04L9/40** (20220101); **H04L41/0803** (20220101); **H04W12/30** (20210101)

U.S. Cl.:

CPC **G06Q10/087** (20130101); **G06F21/105** (20130101); **H04L9/3213** (20130101); **H04L9/3247** (20130101); **H04L41/0803** (20130101); **H04L63/126** (20130101); **H04W12/35** (20210101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8694763	12/2013	Thorsen	713/2	G06F 9/441
9692737	12/2016	Walters	N/A	G06Q 10/101
2007/0213134	12/2006	Aida	N/A	N/A
2008/0230601	12/2007	Suzuki et al.	N/A	N/A
2009/0300758	12/2008	Hauck	380/283	H04L 9/3271
2014/0164779	12/2013	Hartley	713/176	H04L 9/0866
2014/0205092	12/2013	Hartley	380/44	H04L 9/0897
2014/0233394	12/2013	Viljoen	370/236.2	H04L 45/64
2016/0174069	12/2015	Bruner	455/411	H04L 63/065
2018/0227282	12/2017	Lee	N/A	H04W 12/10
2019/0068576	12/2018	Ji et al.	N/A	N/A
2019/0334718	12/2018	Li et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101563880	12/2008	CN	N/A
102255917	12/2010	CN	N/A
105516948	12/2015	CN	N/A
107370668	12/2016	CN	N/A
108476226	12/2017	CN	N/A
110191112	12/2018	CN	N/A
2004295823	12/2003	JP	N/A

OTHER PUBLICATIONS

Extended European Search Report from corresponding European Application No. 20170178.6, Sep. 24, 2020. cited by applicant

Chinese Office Action from Corresponding Chinese Patent Application No. CN202110414156.4, Nov. 20, 2023. cited by applicant

Primary Examiner: Zeender; Florian M

Assistant Examiner: Bursum; Kimberly S.

Attorney, Agent or Firm: Workman Nydegger

Background/Summary

TECHNICAL FIELD

(1) The invention relates to the secure production and provisioning of electronic devices. More specifically, the invention relates to an apparatus, system and method for controlling the provisioning of electronic devices.

BACKGROUND OF THE INVENTION

(2) The production and assembly of state-of-the-art electronic consumer equipment, such as smartphones, tablet computers as well as other types of IoT devices, often happens in a distributed fashion in that the various electronic components or devices, including the electronic chips or microprocessors of the electronic consumer equipment are manufactured, provisioned or personalized and finally assembled at different locations and by different parties. For instance, an electronic chip or microprocessor for an electronic consumer equipment may be originally manufactured by a chip manufacturer and provisioned by another party with a suitable firmware, before being assembled into the final end product by the manufacturer of the electronic consumer equipment, e.g. an OEM.

(3) For such distributed processing chains of electronic equipment there is a need for apparatuses, systems and methods allowing for a secure and controlled provisioning of electronic components or devices, such as chips or microprocessors of the electronic equipment.

SUMMARY OF THE INVENTION

(4) It is therefore an object of the invention to provide apparatuses, systems and methods allowing for a secure and controlled provisioning of electronic devices, such as chips or microprocessors for electronic equipment.

(5) The foregoing and other objects are achieved by the subject matter of the independent claims. Further implementation forms are apparent from the dependent claims, the description and the figures.

(6) According to a first aspect of the invention a provisioning control apparatus configured to be coupled to a provisioning equipment server is provided, wherein the provisioning equipment server is electrically connectable with one or more electronic devices for provisioning the electronic devices with a first program code or a second program code. The electronic devices may comprise chips, microprocessors or other programmable electronic components, such as Flash memories, electrically erasable programmable read only memories (EEPROM), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), and microcontrollers incorporating non-volatile memory elements. The first program code may be a first firmware originally provided by a first remote server. The second program code may be a second firmware originally provided by a second remote server. The first program code may be provisioned on a first type of electronic devices, while the second program code may be provisioned on a different second type of electronic devices. The first and second program code may be provisioned on the same type of electronic devices, i.e. on the same chip type. The first and second program codes may be digitally signed. The first and second program codes may be personalized first and second program codes in that the personalized first and second program codes can only be used to provision, i.e. personalize one respective electronic device.

(7) The provisioning control apparatus according to the first aspect comprises a communication interface configured to receive an electronic credit token, wherein the electronic credit token comprises a credit counter and wherein the credit counter indicates a total allowed number of transmissions of the first program code and the second program code towards the provisioning equipment server. Moreover, the provisioning control apparatus according to the first aspect comprises a processor configured to retrieve the credit counter from the received electronic credit token. The communication interface is further configured to transmit the first program code and the second program code towards the provisioning equipment server. The processor is further configured to update a value of the credit counter for each transmission of the first program code and of the second program code to obtain an updated credit counter. For instance, the processor may be configured to decrement the credit counter for each respective transmission of the first program code and for each respective transmission of the second program code to the provisioning equipment server. Moreover, the processor is configured to prohibit a further transmission of the first program code or the second program code towards the provisioning equipment server, if the updated credit counter indicates that the total number of transmissions has been reached, for instance, in case the updated credit counter indicates that no allowed transmissions are left, e.g. the updated credit counter has reached zero.

(8) Advantageously, by means of the electronic credit token the provisioning control apparatus has control over the provisioning of the electronic devices by the provisioning equipment server, in particular about how many electronic devices are configured by the provisioning equipment server with the first program code and the second program code. The provisioning control apparatus and the provisioning equipment server may be under the control of different parties. The provisioning equipment server may provision a first type of electronic devices using the first program code for a first party and a second type of electronic devices using the second program code for a second party independent of the first party. Thus, advantageously the provisioning control apparatus using the electronic credit token with its credit counter has control over the provisioning of electronic devices by the provisioning equipment server for different parties, for instance, different electronic equipment manufacturers.

(9) In a further embodiment, the communication interface is configured to receive the electronic credit token over a communication network, such as the Internet, from a remote server or a token generator server. The remote server may be the server of or associated with an electronic equipment manufacturer (herein also referred to as OEM) that uses the electronic devices provisioned with its firmware for assembling electronic equipment, such as smartphones, tablet computers as well as other types of IoT devices. Advantageously, this allows the electronic equipment manufacturer to have control over the provisioning of the electronic devices with its firmware.

(10) In a further embodiment, the communication interface may be configured to communicate with the provisioning equipment server via a wired connection. In an embodiment, the provisioning equipment server may be implemented as a personal computer and the provisioning control apparatus may be implemented as a PC card inserted in the provisioning equipment server.

(11) In a further embodiment, the electronic credit token may comprise provisioning control data for controlling communications with the provisioning equipment server, wherein the processor is configured to retrieve the provisioning control data from the electronic credit token and to control communications of the communication interface with the provisioning equipment server according to the provisioning control data. In an embodiment, these provisioning control data may be provided in a header of the electronic credit token. Advantageously, this allows controlling the communication between the provisioning control apparatus and the provisioning equipment server, for instance, by selecting a secure communication protocol defined by the provisioning control data.

(12) In a further embodiment, the electronic credit token may further comprise data defining one or more validity time periods of the electronic credit token, wherein the processor is configured to

prohibit a transmission of the first program code and/or a transmission of the second program code towards the provisioning equipment server outside of the one or more validity time periods.

Advantageously, this allows restricting the provisioning of the electronic devices to specific times specified, for instance, by the electronic equipment manufacturer(s).

(13) In a further embodiment, the electronic credit token may further comprise a token identifier for identifying the electronic credit token, wherein the provisioning control apparatus further comprises an electronic memory, wherein the electronic memory is configured to store the token identifier in a list of electronic credit tokens already used or in use. Advantageously, this allows protecting the provisioning control apparatus against a replay attack, i.e. an attack, where an already used electronic credit token is provided again for provisioning electronic devices. In an embodiment, the token identifier may be a nonce generated when generating the electronic credit token.

(14) In a further embodiment, the electronic credit token may further comprise one or more electronic device type identifiers, wherein the processor is configured to prohibit a transmission of the first program code and/or a transmission of the second program code towards the provisioning equipment server for provisioning an electronic device not corresponding to the one or more electronic device types identified by the one or more electronic device type identifiers.

Advantageously, this allows making sure that only the intended electronic devices are provisioned with the first and/or second program codes using the electronic credit token. The electronic device type identifier may be, for instance, an identifier of a specific chip or microprocessor type.

(15) In a further embodiment, the electronic credit token may further comprise one or more program code identifiers, e.g. a first program code identifier and a second program code identifier, wherein the processor is configured to prohibit a transmission of the first program code towards the provisioning equipment server, if the first program code differs from the program code(s) identified by the one or more program code identifiers, and wherein the processor is configured to prohibit a transmission of the second program code towards the provisioning equipment server, if the second program code differs from the program code(s) identified by the one or more program code identifiers. Advantageously, this allows making sure that only the intended program code(s), e.g. firmware(s) is used for provisioning electronic devices by the provisioning equipment server.

(16) In a further embodiment, the communication interface is configured to receive the electronic credit token in encrypted form, wherein the processor is configured to decrypt the encrypted electronic credit token. A hybrid encryption scheme, such as PKCS#7, may be used.

Advantageously, this allows preventing a malicious party from using an intercepted electronic credit token.

(17) In a further embodiment, the electronic credit token comprises a digital signature based on a private key of a token generator server, wherein the processor is configured to verify the digital signature of the electronic credit token using a public key of the token generator server.

Advantageously, this allows the provisioning control apparatus to verify that the electronic credit token initially has been generated by a trustworthy source, namely the token generator server.

(18) In a further embodiment, the communication interface is further configured to receive an electronic provisioning token, wherein the electronic provisioning token comprises a provisioning counter and wherein the provisioning counter indicates a total number of allowable transmissions of the first program code towards the provisioning equipment server. The processor is further configured to retrieve the provisioning counter from the received electronic provisioning token. The communication interface is further configured to transmit the first program code towards the provisioning equipment server, wherein the processor is further configured to update a value of the provisioning counter for each transmission of the first program code towards the provisioning equipment server to obtain an updated provisioning counter. Moreover, the processor is configured to prohibit a further transmission of the first program code towards the provisioning equipment server, if the updated provisioning counter indicates that the total number of transmissions has been

reached. Advantageously, by means of the electronic provisioning token the provisioning control apparatus has control over the provisioning of electronic devices by the provisioning equipment server using the first program code, which may be the program code of a first electronic equipment manufacturer. Thereby, the first electronic equipment manufacturer can have remote control via the provisioning control apparatus over the number of electronic devices provisioned by the provisioning equipment server with its program code, e.g. firmware. In addition or alternatively to the electronic provisioning token tied to the first program code and, thus, a first electronic equipment manufacturer the provisioning control apparatus may receive and use a corresponding further electronic provisioning token tied to the second program code and, thus, a second electronic equipment manufacturer.

(19) According to a second aspect the invention relates to a provisioning control system comprising: a provisioning control apparatus according to the first aspect of the invention; a provisioning equipment server being electrically connectable with one or more electronic devices for provisioning the one or more electronic devices with a first program code or a second program code, wherein the provisioning control apparatus is coupled to the provisioning equipment server for controlling the provisioning of the one or more electronic devices; and a token generator server configured to generate the electronic credit token.

(20) In a further embodiment of the system according to the second aspect, the token generator server may be configured to generate the electronic credit token in response to a token request from a remote server, i.e. the remote server of the first or second electronic equipment manufacturer. Advantageously, this allows the token generator server to generate and provide the electronic credit token on demand. In response to the request the token generator server may provide the generated electronic credit token to the remote server, which, in turn, may forward the generated electronic credit token to the provisioning control apparatus. Alternatively, the token generator server may provide the generated electronic credit token directly to the provisioning control apparatus.

(21) In a further embodiment of the system according to the second aspect, the token generator server is configured to verify a digital signature of the token request using a public key of the remote server, before providing the electronic credit token to the remote server. Advantageously, this allows the token generator server to verify the remote server to be trustworthy.

(22) In a further embodiment of the system according to the second aspect, the token generator server is configured to digitally sign the electronic credit token using a private key. Advantageously, this allows the provisioning control apparatus to verify that the electronic credit token has been generated by a trustworthy source.

(23) According to a third aspect the invention relates to a corresponding method for provisioning one or more electronic devices with a first program code or a second program code. The method comprises the steps of: receiving an electronic credit token, wherein the electronic credit token comprises a credit counter and wherein the credit counter indicates a total number of transmissions of the first program code and the second program code towards a provisioning equipment server; retrieving the credit counter from the received electronic credit token; transmitting the first program code or the second program code towards the provisioning equipment server; updating a value of the credit counter for each transmission of the first program code and of the second program code to obtain an updated credit counter; and prohibiting a further transmission of the first program code and the second program code towards the provisioning equipment server, if the updated credit counter indicates that the total number of transmissions has been reached.

(24) The provisioning control method according to the third aspect of the invention can be performed by the provisioning control apparatus according to the first aspect of the invention and the provisioning control system according to the second aspect of the invention. Further features of the provisioning control method according to the third aspect of the invention result directly from the functionality of the provisioning control apparatus according to the first aspect of the invention, the provisioning control system according to the second aspect of the invention and their different

implementation forms described above and below.

(25) Embodiments of the invention can be implemented in hardware and/or software.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further embodiments of the invention will be described with respect to the following figures, wherein:

(2) FIG. 1 shows a schematic diagram illustrating a provisioning control system according to an embodiment of the invention, including a provisioning control apparatus according to an embodiment of the invention;

(3) FIG. 2 shows a schematic diagram illustrating an exemplary electronic credit token used by the provisioning control apparatus of FIG. 1;

(4) FIG. 3 shows a signaling diagram illustrating the interaction of the provisioning control apparatus of FIG. 1 with the other components of the provisioning control system of FIG. 1; and

(5) FIG. 4 shows a flow diagram illustrating steps of a provisioning control method according to an embodiment of the invention.

(6) In the figures, identical reference signs will be used for identical or at least functionally equivalent features.

DETAILED DESCRIPTION OF EMBODIMENTS

(7) In the following detailed description, reference is made to the accompanying drawings, which form part of the disclosure, and in which are shown, by way of illustration, specific aspects in which the present invention may be implemented. It is understood that other aspects may be utilized and structural or logical changes may be made without departing from the scope of the present invention. The following detailed description, therefore, is not to be taken in a limiting sense, as the scope of the present invention is defined by the appended claims.

(8) For instance, it is understood that a disclosure in connection with a described method may also hold true for a corresponding device or system configured to perform the method and vice versa. For example, if a specific method step is described, a corresponding device may include a unit to perform the described method step, even if such unit is not explicitly described or illustrated in the figures. Further, it is understood that the features of the various exemplary aspects described herein may be combined with each other, unless specifically noted otherwise.

(9) FIG. 1 shows a schematic diagram of a provisioning control system **100** according to an embodiment of the invention, including a provisioning control apparatus **140** according to an embodiment of the invention. As will be described in more detail further below, the provisioning control system **100** may comprise in addition to the provisioning control apparatus **140** a first remote server **110**, a second remote server **110'**, a token generator server **120** and a provisioning equipment server **160** for provisioning or personalizing electronic devices **170**, such as chips or microprocessors **170** with a first program code **150**, e.g. a first firmware **150**, and a second program code **150'**, e.g. a second firmware **150'**.

(10) As illustrated in FIG. 1, the provisioning control apparatus **140**, the remote servers **110**, **110'** and the token generator server **120** may be configured to communicate with each other via a communication network, such as the Internet. Thus, the provisioning control apparatus **140**, the remote servers **110**, **110'** and the token generator server **120** may be at different locations and under the control of different parties. As illustrated in FIG. 1, the provisioning control apparatus **140** and the provisioning equipment server **160** may be located within a production environment **130**, such as a personalization factory **130**. In an embodiment, the first remote server **110** may be under the control or associated with a first electronic equipment manufacturer, e.g. a first OEM, wherein the first electronic equipment manufacturer assembles electronic equipment, such as smartphones,

tablet computers or other types of IoT or electronic consumer equipment, using the electronic devices **170** provisioned by the provisioning equipment server **160** with the first program code **150**. Likewise, the second remote server **110'** may be under the control or associated with a different second electronic equipment manufacturer, e.g. a second OEM, wherein the second electronic equipment manufacturer assembles electronic equipment, such as smartphones, tablet computers or other types of IoT or electronic consumer equipment, using the electronic devices **170** provisioned by the provisioning equipment server **160** with the second program code **150'**.

(11) In an embodiment, the first program code **150** may be a firmware of the first electronic equipment manufacturer associated with the first remote server **110**. Likewise, the second program code **150'** may be a firmware of the second electronic equipment manufacturer associated with the second remote server **110'**.

(12) In an embodiment, the provisioning control apparatus **140**, the remote servers **110**, **110'** and the token generator server **120** are configured to securely communicate with each other using one or more cryptographic schemes, such as a public key infrastructure and/or a hybrid cryptographic scheme.

(13) The provisioning control apparatus **140** is configured to be coupled to the provisioning equipment server **160**, for instance, by a wired or a wireless connection. In an embodiment, the provisioning equipment server **160** may be implemented as a personal computer and the provisioning control apparatus **140** may be implemented as a PC card inserted in the provisioning equipment server **160**. The provisioning equipment server **160** may comprise an electrical and/or mechanical interface for interacting directly or indirectly via a provisioning equipment with the electronic devices **170**. For instance, the provisioning equipment server **160** may comprise a personalization tray for personalizing a batch of electronic devices **170** inserted therein.

(14) In the embodiment illustrated in FIG. 1 the provisioning control apparatus **140** comprises a processor **141**, a communication interface **143** and a non-transient memory **145**. The communication interface **143** of the provisioning control apparatus **140** is configured to receive an electronic credit token **180**. In an embodiment, the electronic credit token **180** is generated by the token generator server **120**. In an embodiment, the token generator server **120** may be configured to generate the electronic credit token **180** in response to a token request from the first remote server **110** associated with the first electronic equipment manufacturer or the second remote server **110'** associated with the second electronic equipment manufacturer. Advantageously, this allows the token generator server **120** to generate and provide the electronic credit token **180** on demand, i.e. when the first or second electronic equipment manufacturer wants to obtain electronic devices **170** provisioned with the first or second program code **150**, **150'** for assembling electronic equipment.

(15) In response to the request the token generator server **120** may provide the generated electronic credit token **180** to the requesting remote server **110**, **110'**, which, in turn, may forward the generated electronic credit token **180** to the provisioning control apparatus **140**. In a further embodiment, the token generator server **120** may provide the generated electronic credit token **180** directly to the provisioning control apparatus **140**.

(16) In an embodiment, the communication interface **143** of the provisioning control apparatus **140** is configured to receive the electronic credit token **180** in encrypted form, wherein the processor **141** is configured to decrypt the encrypted electronic credit token **180**. For instance, a hybrid encryption scheme, such as PKCS#7, may be used. Advantageously, this allows preventing a malicious party from successfully using an intercepted electronic credit token **180** for controlling the provisioning of electronic devices by the provisioning equipment server **160**.

(17) In an embodiment, the electronic credit token **180** comprises a digital signature **188** (as illustrated in FIG. 2) based on a private key **121a** of the token generator server **120**, wherein the processor **141** of the provisioning control apparatus **140** is configured to verify the digital signature **188** of the electronic credit token **180** using a public key **121b** of the token generator server **120**. Advantageously, this allows the provisioning control apparatus **140** to verify that the electronic

credit token **180** initially has been generated by a trustworthy source, namely the token generator server **120**. As illustrated in FIG. 1, the public key **121b** of the token generator server **120** may be stored in the memory **145** of the provisioning control apparatus **140**.

(18) As further illustrated in FIG. 2, the electronic credit token **180** comprises a credit counter **182** indicating a total number of allowed transmissions of the first program code **150** and the second program code **150'** towards the provisioning equipment server **160**. Once received by the communication interface **143**, the processor **141** of the provisioning control apparatus **140** is configured to retrieve the credit counter **182** from the received electronic credit token **180**, i.e. the total number of allowed transmissions of the first program code **150** and the second program code **150'** via the communication interface **143** to the provisioning equipment server **160**. For each transmission of the first program code **150** or the second program code **150'** via the communication interface **143** to the provisioning equipment server **160** the processor **141** of the provisioning control apparatus **140** is configured to update the value of the credit counter **182** and to obtain an updated value of the credit counter **182**. For instance, the processor **141** may be configured to decrement the current value of the credit counter **182** by one for each transmission of the first program code **150** or the second program code **150'** via the communication interface **143** to the provisioning equipment server **160**.

(19) The processor **141** of the provisioning control apparatus **140** is further configured to prohibit a further transmission of the first program code **150** or the second program code **150'** to the provisioning equipment server **160**, if the updated value of the credit counter **182** indicates that the total number of transmissions has been reached. In other words, once the total number of electronic devices **170** (as indicated by the initial credit counter **182**) have been provisioned with the first program code **150** or the second program code **150'** by the provisioning equipment server **160**, the provisioning control apparatus **140** blocks the provisioning of further electronic devices **170** with the first program code **150** or the second program code **150'** by the provision equipment server **160**. In an embodiment, each instance of the first program code **150** and/or the second program code **150'** may be digitally signed and/or personalized for only one respective electronic device **170**, such as by means of a unique firmware identifier. In an embodiment, the first program code **150** may be provided to the provisioning control apparatus **140** by the first remote server **110** associated with the first electronic equipment manufacturer and the second program code **150'** may be provided to the provisioning control apparatus **140** by the second remote server **110'** associated with the second electronic equipment manufacturer.

(20) As illustrated in FIG. 2, in addition to the credit counter **182** the electronic credit token **180** may comprise further data, such as provisioning control data **181** for controlling communications with the provisioning equipment server **160**. The processor **141** may be configured to retrieve the provisioning control data **181** from the electronic credit token **180** and to control communications of the communication interface **143** with the provisioning equipment server **160** according to the provisioning control data **181**. As illustrated in FIG. 2, these provisioning control data **181** may be provided in a header **181** of the electronic credit token **180**. Advantageously, this allows controlling the communication between the provisioning control apparatus **140** and the provisioning equipment server **160**, for instance, by selecting a secure communication protocol on the basis of the provisioning control data **181**.

(21) Moreover, the electronic credit token **180** may comprise data **187** defining one or more validity time periods of the electronic credit token **180**. The processor **141** may be configured to prohibit a transmission of the first program code **150** and/or the second program code **150'** towards the provisioning equipment server **160** outside of the one or more validity time periods.

Advantageously, this allows restricting the provisioning of the electronic devices **170** with the first program code **150** and/or the second program code **150'** to specific times specified, for instance, by the first electronic equipment manufacturer, the second electronic equipment manufacturer and/or the token generator server **120**.

(22) Furthermore, the electronic credit token **180** may comprise a token identifier **183** for uniquely identifying the electronic credit token **180**, wherein the electronic memory **145** of the provisioning control apparatus **140** is configured to store the token identifier **183** in a list (i.e. a black list) of electronic credit tokens **180** already used or in use. Advantageously, this allows protecting the provisioning control apparatus **140** against a replay attack, i.e. an attack, where an already used electronic credit token is provided again for provisioning electronic devices. In an embodiment, the token identifier **183** may be a nonce **183** generated by the token generator server **120** when generating the electronic credit token **180**.

(23) As illustrated in FIG. 2, the electronic credit token **180** may further comprise one or more electronic device type identifiers **186**. The processor **141** may be configured to prohibit a transmission of the first program code **150** and/or the second program code **150'** towards the provisioning equipment server **160** for provisioning an electronic device **170** not corresponding to the one or more electronic device types identified by the one or more electronic device type identifiers **186**. Advantageously, this allows making sure that only the intended electronic devices **170** are provisioned with the first program code **150** and/or the second program code **150'** using the electronic credit token **180**. The one or more electronic device type identifiers **186** may include, for instance, an identifier of a specific chip or microprocessor type.

(24) Moreover, the electronic credit token **180** may further comprise one or more program code identifiers **185**, including a first program code identifier and a second program code identifier. The processor **141** may be configured to prohibit a transmission of the first program code **150** and/or the second program code **150'** towards the provisioning equipment server **160**, if the first program code **150** and/or the second program code **150'** differs from the one more program codes identified by the one or more program code identifiers **185**. Advantageously, this allows making sure that only the intended program codes, e.g. firmware **150**, **150'** are used for provisioning the electronic devices **170**. As illustrated in FIG. 2, the electronic credit token **180** may further comprise one or more identifiers **184** for identifying the first electronic equipment manufacturer and/or the second electronic equipment manufacturer.

(25) In an embodiment, the communication interface **143** of the provisioning control apparatus **140** is further configured to receive an electronic provisioning token, wherein the electronic provisioning token comprises a provisioning counter indicating a total number of transmissions of the first program code **150** only. In an embodiment, the communication interface **143** of the provisioning control apparatus **140** is further configured to receive a further electronic provisioning token, wherein the further electronic provisioning token comprises a further provisioning counter indicating a total number of transmissions of the second program code **150'** only.

(26) The processor **141** of the provisioning control apparatus **140** is configured to retrieve the provisioning counter from the received electronic provisioning token. The communication interface **143** is further configured to transmit the first program code **150** towards the provisioning equipment server **160**, wherein the processor **141** is configured to update a value of the provisioning counter for each transmission of the first program code **150** to obtain an updated provisioning counter. The processor **141** is configured to prohibit a further transmission of the first program code **150** (but not of the second program code **150'**) towards the provisioning equipment server **160**, if the updated provisioning counter indicates that the total number of transmissions has been reached. Advantageously, this allows the provisioning control apparatus **140** to keep control over the number of electronic devices **170** provisioned by the provisioning equipment server **160** with a specific program code, e.g. the first program code **150**, and, thus, for a specific customer, e.g. the first electronic equipment manager associated with the first remote server **110**.

(27) FIG. 3 shows a signaling diagram illustrating the interaction of the provisioning control apparatus **140** with the other components of the provisioning control system **100**, i.e. the remote servers **110**, **110'**, the token generator server **120**, the provisioning equipment server **160** and the electronic device(s) **170** to be provisioned. In FIG. 3 the following steps are illustrated, some of

which already have been described in the context of FIG. 1 above.

(28) In step **301** of FIG. 3, by way of example the first remote server **110** (associated, for instance, with a specific electronic equipment manufacturer) sends a token request to the token generator server **120** (the request may be also send by the second remote server **110'**, however, in the following the scenario will be described by way of example in the context of the first remote server **110**). The token request may be digitally signed by the first remote server **110** using a private key **111a**. Thus, the token generator server **120** may be configured to verify the digital signature of the token request using a public key **111b** of the first remote server **110**, before providing the electronic credit token **180** to the first remote server **110**. Advantageously, this allows the token generator server **120** to verify the first remote server **110** to be trustworthy.

(29) In response to the request of step **301** the token generator server **120** in step **303** of FIG. 3 generates an electronic credit token **180**. In addition to the credit counter **182** the electronic credit token **180** may comprise one or more of the data elements illustrated in FIG. 2, as already described above. In an embodiment, the token generator server **120** is configured to digitally sign the electronic credit token **180** using the private key **121a**.

(30) In step **305** the token generator server **120** provides the electronic credit token **180** to the first remote server **110**, which, in turn, forwards the electronic credit token **180** to the provisioning control apparatus **140** (step **307** of FIG. 3). Once received the provisioning control apparatus **140** verifies the electronic credit token **180** in step **309** of FIG. 3, for instance, by verifying the digital signature **188** of the electronic credit token **180** using the public key **121b** of the token generator server **120**.

(31) If this verification is successful, the provisioning control apparatus **140** provides a personalized first program code **150** and/or a personalized second program code **150'** to the provisioning equipment server **160** (step **311** of FIG. 3), which, in turn, uses the personalized program code(s) **150**, **150'** for provisioning an electronic device **170** (step **313** of FIG. 3). For each transmission of a personalized program code **150**, **150'** the provisioning control apparatus **140** adjusts (step **315** of FIG. 3) the value of the credit counter **182**. This provisioning of the electronic devices **170** continues until the total number of allowed electronic devices **170** has been provisioned by the provisioning equipment server **160**. In step **317** of FIG. 3, the provisioning equipment server **160** sends a corresponding report to the provisioning control apparatus **140**. At this stage, the provisioning control apparatus **140** will block any further transmissions of personalized first or second program code **150**, **150'** to the provisioning equipment server **160** and, thus, block the personalized provisioning of any further electronic devices **170**, be it for the first electronic equipment manufacturer or be it for the second electronic equipment manufacturer.

(32) In step **319** of FIG. 3 the provisioning control apparatus **140** reports to the first remote server **110** associated with the first electronic equipment manufacturer that the total number of electronic devices **170** (as indicated by the initial credit counter **182** of the electronic credit token **180**) have been provisioned with a respective personalized program code **150**, **150'**. This may trigger the first remote server **110** to provide a further electronic credit token to the provisioning control apparatus **140** and/or to request a new electronic credit token from the token generator server **120**.

(33) FIG. 4 shows a flow diagram illustrating steps of a correspond provisioning control method **400** according to an embodiment of the invention. The provisioning control method **400** according to an embodiment of the invention comprises the following steps:

(34) Step **401**: receiving the electronic credit token **180**, wherein the electronic credit token comprises the credit counter **182** and wherein the credit counter **182** indicates a total number of transmissions of the first program code **150** and the second program code **150'** towards the provisioning equipment server **160**, wherein the provisioning equipment server **160** is electrically connectable with the one or more electronic devices **170** for provisioning the one or more electronic devices **170** with the first program code **150** or the second program code **150'**.

(35) Step **403**: retrieving the credit counter **182** from the received electronic credit token **180**.

(36) Step **405**: transmitting the first program code **150** or the second program code **150'** towards the provisioning equipment server **160**.

(37) Step **407**: updating a value of the credit counter **182** for each transmission of the first program code **150** and of the second program code **150'** to obtain an updated credit counter **182**.

(38) Step **409**: prohibiting a further transmission of the first program code **150** or the second program code **150'** towards the provisioning equipment server **160**, if the updated credit counter **182** indicates that the total number of transmissions has been reached.

(39) As will be appreciated, embodiments of the invention provide a higher flexibility with respect to the secure production and personalization of electronic devices and equipment. Moreover, embodiments of the invention allow delegating secure production of electronic devices and components for electronic equipment. Moreover, embodiments of the invention allow load balancing and on-demand production/personalization of security critical systems.

(40) While a particular feature or aspect of the disclosure may have been disclosed with respect to only one of several implementations or embodiments, such feature or aspect may be combined with one or more other features or aspects of the other implementations or embodiments as may be desired and advantageous for any given or particular application.

(41) Furthermore, to the extent that the terms “include”, “have”, “with”, or other variants thereof are used in either the detailed description or the claims, such terms are intended to be inclusive in a manner similar to the term “comprise”. Also, the terms “exemplary”, “for example” and “e.g.” are merely meant as an example, rather than the best or optimal. The terms “coupled” and “connected”, along with derivatives may have been used. It should be understood that these terms may have been used to indicate that two elements cooperate or interact with each other regardless whether they are in direct physical or electrical contact, or they are not in direct contact with each other.

(42) Although specific aspects have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a variety of alternate and/or equivalent implementations may be substituted for the specific aspects shown and described without departing from the scope of the present disclosure. This application is intended to cover any adaptations or variations of the specific aspects discussed herein.

(43) Although the elements in the following claims are recited in a particular sequence, unless the claim recitations otherwise imply a particular sequence for implementing some or all of those elements, those elements are not necessarily intended to be limited to being implemented in that particular sequence.

(44) Many alternatives, modifications, and variations will be apparent to those skilled in the art in light of the above teachings. Of course, those skilled in the art readily recognize that there are numerous applications of the invention beyond those described herein. While the present invention has been described with reference to one or more particular embodiments, those skilled in the art recognize that many changes may be made thereto without departing from the scope of the present invention. It is therefore to be understood that within the scope of the appended claims and their equivalents, the invention may be practiced otherwise than as specifically described herein.

Claims

1. A provisioning control system comprising: a provisioning control apparatus; a provisioning equipment server being electrically connectable with one or more electronic devices for provisioning the one or more electronic devices with a first program code or a second program code, wherein the provisioning control apparatus is under control of and configured to receive control communications from a first party and the provisioning equipment server is under control of and configured to receive control communications from a second party, the first party being different than the second party, wherein the first program code is provided to the provisioning control apparatus by a first remote server associated with a first electronic equipment manufacturer,

wherein the second program code is provided to the provisioning control apparatus by a second remote server associated with a second electronic equipment manufacturer, wherein the first and second program codes are personalized first and second program codes for provisioning one respective electronic device, wherein the provisioning control apparatus is coupled to the provisioning equipment server and controls the provisioning of the one or more electronic devices; and a token generator server configured to generate an electronic credit token; wherein the provisioning control apparatus comprises: a communication interface configured to receive the electronic credit token over a communication network from the first remote server, wherein the electronic credit token comprises a credit counter indicating a total number of the one or more electronic devices to be provisioned with the first program code or the second program code, the credit counter further indicating a total number of transmissions of the first program code and the second program code towards the provisioning equipment server; and a processor configured to retrieve the credit counter from the received electronic credit token; wherein the communication interface is further configured to transmit the first program code and the second program code towards the provisioning equipment server; wherein the processor is further configured to update a value of the credit counter for each transmission of the first program code and of the second program code to obtain an updated credit counter; wherein the processor is configured to prohibit a further transmission of the first program code and the second program code towards the provisioning equipment server if the updated credit counter indicates that the total number of transmissions of the first program code and the second program code towards the provisioning equipment server has been reached; wherein in addition to the credit counter the electronic credit token comprises provisioning control data as further data, which provisioning control data controls communications between the provisioning control apparatus and the provisioning equipment server, wherein the provisioning control data define a secure communication protocol, said controlling the communications between the provisioning control apparatus and the provisioning equipment server being performed by selecting the secure communication protocol on the basis of the provisioning control data, and wherein the processor is configured to retrieve the provisioning control data from the electronic credit token and to control communications of the communication interface with the provisioning equipment server according to the provisioning control data, the provisioning control data being provided in a header of the electronic credit token.

2. The provisioning control system of claim 1, wherein the communication interface is configured to communicate with the provisioning equipment server via a wired connection.
3. The provisioning control system of claim 1, wherein the electronic credit token further comprises data defining one or more validity time periods of the electronic credit token and wherein the processor is configured to prohibit a transmission of the first program code and/or the second program code towards the provisioning equipment server outside of the one or more validity time periods.
4. The provisioning control system of claim 1, wherein the electronic credit token further comprises a token identifier for identifying the electronic credit token and wherein the provisioning control apparatus further comprises an electronic memory, wherein the electronic memory is configured to store the token identifier in a list of electronic credit tokens already used or in use.
5. The provisioning control system of claim 1, wherein the electronic credit token comprises an electronic device type identifier and wherein the processor is configured to prohibit a transmission of the first program code and the second program code towards the provisioning equipment server for provisioning an electronic device not corresponding to the electronic device type identified by the electronic device type identifier.
6. The provisioning control system of claim 1, wherein the electronic credit token further comprises a first program code identifier and a second program code identifier and wherein the processor is configured to prohibit a transmission of the first program code towards the provisioning equipment server, if the first program code differs from the program code identified by the first program code

identifier, and to prohibit a transmission of the second program code towards the provisioning equipment server, if the second program code differs from the program code identified by the second program code identifier.

7. The provisioning control system of claim 1, wherein the communication interface is configured to receive the electronic credit token in encrypted form and wherein the processor is configured to decrypt the encrypted electronic credit token.

8. The provisioning control system of claim 1, wherein the electronic credit token comprises a digital signature based on a private key of a token generator server and wherein the processor is configured to verify the digital signature of the electronic credit token using a public key of the token generator server.

9. The provisioning control system of claim 1, wherein the communication interface is further configured to receive an electronic provisioning token, wherein the electronic provisioning token comprises a provisioning counter, the provisioning counter indicating a total number of transmissions of the first or second program code towards the provisioning equipment server; wherein the processor is further configured to retrieve the provisioning counter from the received electronic provisioning token; wherein the communication interface is further configured to transmit the respective first or second program code towards the provisioning equipment server; wherein the processor is further configured to update a value of the provisioning counter for each transmission of the respective first or second program code to obtain an updated provisioning counter; and wherein the processor is configured to prohibit a further transmission of the respective first or second program code towards the provisioning equipment server if the updated provisioning counter indicates that the total number of transmissions has been reached.

10. The provisioning control system of claim 1, wherein the token generator server is configured to generate the electronic credit token in response to a token request from a remote server.

11. The provisioning control system of claim 1, wherein the token generator server is configured to verify a digital signature of the token request using a public key of the remote server, before providing the electronic credit token to the remote server or the provisioning control apparatus.

12. The provisioning control system of claim 1, wherein the token generator server is configured to digitally sign the electronic credit token using a private key.

13. A method for provisioning one or more electronic devices with a first program code or a second program code, wherein the method comprises: generating an electronic credit token by a token generator server; receiving the electronic credit token by a communication interface of a provisioning control apparatus, wherein the electronic credit token comprises a credit counter, the credit counter indicating a total number of the one or more electronic devices to be provisioned with the first program code or the second program code and further indicating a total number of transmissions of the first program code and the second program code towards a provisioning equipment server, the provisioning control apparatus is under control of and configured to receive control communications from a first party and the provisioning equipment server is under control of and configured to receive control communications from a second party, the first party being different than the second party, wherein the provisioning equipment server is electrically connectable with the one or more electronic devices for provisioning the one or more electronic devices with the first program code or the second program code, the first program code being provided to the provisioning control apparatus by a first remote server associated with a first electronic equipment manufacturer, and the second program code being provided to the provisioning control apparatus by a second remote server associated with a second electronic equipment manufacturer, wherein the first and second program codes are personalized first and second program codes for provisioning one respective electronic device, wherein in addition to the credit counter the electronic credit token comprises provisioning control data as further data, which provisioning control data controls communications between the provisioning control apparatus and the provisioning equipment server, the provisioning control data being provided in a header of the

electronic credit token; retrieving the provisioning control data from the electronic credit token by a processor of the provisioning control apparatus; retrieving the credit counter from the received electronic credit token by the processor of the provisioning control apparatus; controlling communications of the communication interface of the provisioning control apparatus with the provisioning equipment server according to the provisioning control data defining a secure communication protocol, said controlling the communications between the provisioning control apparatus and the provisioning equipment server being performed by selecting the secure communication protocol on the basis of the provisioning control data; transmitting the first program code or the second program code towards the provisioning equipment server by the communication interface of the provisioning control apparatus; updating a value of the credit counter for each transmission of the first program code and of the second program code to obtain an updated credit counter by the processor of the provisioning control apparatus; and prohibiting a further transmission of the first program code and the second program code towards the provisioning equipment server by the processor of the provisioning control apparatus if the updated credit counter indicates that the total number of transmissions of the first program code and the second program code towards the provisioning equipment server has been reached.

14. The provisioning control system of claim 1, wherein the provisioning equipment server is configured to provision a first type of electronic devices using the first program code for a first party and a second type of electronic devices using the second program code for a second party, the second party being independent of the first party.

15. The provisioning control system of claim 1, wherein the provisioning equipment server is implemented as a personal computer.

16. The provisioning control system of claim 1, wherein the provisioning control apparatus is implemented as a PC card inserted in the provisioning equipment server.

17. The provisioning control system of claim 1, wherein the token generator server is configured to generate the electronic credit token in response to a token request from the first remote server associated with the first electronic equipment manufacturer and/or the second remote server associated with the second electronic equipment manufacturer.

18. The provisioning control system of claim 1, wherein the first program code is a first firmware originally provided by the first remote server, and wherein the second program code is a second firmware originally provided by the second remote server.

19. The provisioning control system of claim 1, wherein the provisioning control data enables a secured provisioning of the one or more electronic devices for a respective electronic equipment manufacturer.

20. The provisioning control system of claim 3, wherein the one or more validity time periods of the electronic credit token restrict the provisioning of the electronic devices with the first program code and/or the second program code to specific times specified by the first electronic equipment manufacturer and/or the second electronic equipment manufacturer.
