

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400651
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Shrivastava; Dhairya et al.

Controlling optically-switchable devices

Abstract

This disclosure relates generally to optically switchable devices, and more particularly, to methods for controlling optically switchable devices. In various embodiments, one or more optically switchable devices may be controlled via voice control and/or gesture control.

Inventors: Shrivastava; Dhairya (Los Altos, CA), Mendenhall; Mark David (Fremont, CA)

Applicant: View, Inc. (Milpitas, CA)

Family ID: 1000008781449

Assignee: View Operating Corporation (San Jose, CA)

Appl. No.: 18/215178

Filed: June 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240046928 A1	Feb. 08, 2024

Related U.S. Application Data

continuation parent-doc US 16096557 US 10964320 20210330 WO PCT/US2017/029476
20170425 child-doc US 17916986

continuation parent-doc US 14391122 US 10365531 20190730 WO PCT/US2013/036456
20130412 child-doc US 17916986

continuation-in-part parent-doc US 17916986 20221004 PENDING child-doc US 18215178

continuation-in-part parent-doc US 17249148 20210222 US 11735183 child-doc US 18215178

us-provisional-application US 62327880 20160426

us-provisional-application US 61624175 20120413

Publication Classification

Int. Cl.: **G10L15/22** (20060101); **E06B3/67** (20060101); **E06B9/24** (20060101); **G02F1/163** (20060101); **G06F3/04883** (20220101); **G06F3/04886** (20220101); **G06F3/16** (20060101); **G06F21/32** (20130101); **G10L15/26** (20060101)

U.S. Cl.:

CPC **G10L15/22** (20130101); **E06B3/6722** (20130101); **E06B9/24** (20130101); **G02F1/163** (20130101); **G06F3/04883** (20130101); **G06F3/04886** (20130101); **G06F3/16** (20130101); **G06F3/167** (20130101); **G06F21/32** (20130101); **G10L15/26** (20130101); **E06B2009/2464** (20130101); **G06F2203/0381** (20130101); **G10L2015/223** (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5124833	12/1991	Barton et al.	N/A	N/A
5170108	12/1991	Peterson et al.	N/A	N/A
5204778	12/1992	Bechtel	N/A	N/A
5220317	12/1992	Lynam et al.	N/A	N/A
5290986	12/1993	Colon et al.	N/A	N/A
5353148	12/1993	Eid et al.	N/A	N/A
5365365	12/1993	Ripoche et al.	N/A	N/A
5379146	12/1994	Defendini	N/A	N/A
5384578	12/1994	Lynam et al.	N/A	N/A
5402144	12/1994	Ripoche	N/A	N/A
5451822	12/1994	Bechtel et al.	N/A	N/A
5579149	12/1995	Moret et al.	N/A	N/A
5598000	12/1996	Popat	N/A	N/A
5621526	12/1996	Kuze	N/A	N/A
5673028	12/1996	Levy	N/A	N/A
5694144	12/1996	Lefrou et al.	N/A	N/A
5764402	12/1997	Thomas et al.	N/A	N/A
5822107	12/1997	Lefrou et al.	N/A	N/A
5867495	12/1998	Elliott et al.	N/A	N/A
5900720	12/1998	Kallman et al.	N/A	N/A
5956012	12/1998	Turnbull et al.	N/A	N/A
5973818	12/1998	Sjursen et al.	N/A	N/A
5973819	12/1998	Pletcher et al.	N/A	N/A
5978126	12/1998	Sjursen	N/A	N/A
6039850	12/1999	Schulz	N/A	N/A
6055089	12/1999	Schulz et al.	N/A	N/A
6084700	12/1999	Knapp et al.	N/A	N/A
6130448	12/1999	Bauer et al.	N/A	N/A

6130772	12/1999	Cava	N/A	N/A
6222177	12/2000	Bechtel et al.	N/A	N/A
6262831	12/2000	Bauer et al.	N/A	N/A
6386713	12/2001	Turnbull et al.	N/A	N/A
6407468	12/2001	LeVesque et al.	N/A	N/A
6407847	12/2001	Poll et al.	N/A	N/A
6449082	12/2001	Agrawal et al.	N/A	N/A
6471360	12/2001	Rukavina et al.	N/A	N/A
6535126	12/2002	Lin et al.	N/A	N/A
6567708	12/2002	Bechtel et al.	N/A	N/A
6614577	12/2002	Yu et al.	N/A	N/A
6795226	12/2003	Agrawal et al.	N/A	N/A
6829511	12/2003	Bechtel et al.	N/A	N/A
6856444	12/2004	Ingalls et al.	N/A	N/A
6897936	12/2004	Li et al.	N/A	N/A
6940627	12/2004	Freeman et al.	N/A	N/A
6988070	12/2005	Kawasaki	704/E15.045	G10L 15/26
7085609	12/2005	Bechtel et al.	N/A	N/A
7133181	12/2005	Greer	N/A	N/A
7137126	12/2005	Coffman	704/E15.04	G10L 15/285
7215318	12/2006	Turnbull et al.	N/A	N/A
7277215	12/2006	Greer	N/A	N/A
7304787	12/2006	Whitesides et al.	N/A	N/A
7391420	12/2007	Coyne	N/A	N/A
7417397	12/2007	Berman et al.	N/A	N/A
7542809	12/2008	Bechtel et al.	N/A	N/A
7548833	12/2008	Ahmed	N/A	N/A
7567183	12/2008	Schwenke	N/A	N/A
7610910	12/2008	Ahmed	N/A	N/A
7684105	12/2009	Lamontagne et al.	N/A	N/A
7800812	12/2009	Moskowitz	N/A	N/A
7817326	12/2009	Rennig et al.	N/A	N/A
7822490	12/2009	Bechtel et al.	N/A	N/A
7873490	12/2010	MacDonald	N/A	N/A
7941245	12/2010	Popat	N/A	N/A
7962326	12/2010	Tsourikov	707/706	G06F 40/30
7966078	12/2010	Hoffberg et al.	N/A	N/A
7972021	12/2010	Scherer	N/A	N/A
7990603	12/2010	Ash et al.	N/A	N/A
8004739	12/2010	Letocart	N/A	N/A
8018644	12/2010	Gustavsson et al.	N/A	N/A
8024073	12/2010	Imes et al.	N/A	N/A
8102586	12/2011	Albahri	N/A	N/A
8213074	12/2011	Shrivastava et al.	N/A	N/A
8214494	12/2011	Slavin	N/A	N/A
8254013	12/2011	Mehtani et al.	N/A	N/A
8292228	12/2011	Mitchell et al.	N/A	N/A

8340975	12/2011	Rosenberger	704/274	G10L 15/22
8456729	12/2012	Brown et al.	N/A	N/A
8509400	12/2012	Liu et al.	N/A	N/A
8533580	12/2012	Xu	N/A	N/A
8547624	12/2012	Ash et al.	N/A	N/A
8705162	12/2013	Brown et al.	N/A	N/A
8723467	12/2013	Berman et al.	N/A	N/A
8764950	12/2013	Wang et al.	N/A	N/A
8836263	12/2013	Berman et al.	N/A	N/A
8864321	12/2013	Mehtani et al.	N/A	N/A
8902486	12/2013	Chandrasekhar	N/A	N/A
8921473	12/2013	Hyman	524/495	C08K 3/04
8976440	12/2014	Berland et al.	N/A	N/A
9016630	12/2014	Mitchell et al.	N/A	N/A
9030725	12/2014	Pradhan et al.	N/A	N/A
9081247	12/2014	Pradhan et al.	N/A	N/A
9245229	12/2015	Fadell et al.	N/A	N/A
9390726	12/2015	Smus	N/A	G06F 3/017
9470947	12/2015	Nagel et al.	N/A	N/A
9536527	12/2016	Carlson	N/A	H04L 43/14
9677327	12/2016	Nagel	N/A	G02F 1/163
9749583	12/2016	Fineberg	N/A	H04L 67/52
9898912	12/2017	Jordan, II et al.	N/A	N/A
9948387	12/2017	Frankel et al.	N/A	N/A
9984686	12/2017	Mutagi	N/A	G10L 15/26
10031356	12/2017	Van Oosten et al.	N/A	N/A
10286839	12/2018	Mazuir et al.	N/A	N/A
10288971	12/2018	Phillips et al.	N/A	N/A
10316581	12/2018	Nagel	N/A	E06B 9/24
10329839	12/2018	Fasi et al.	N/A	N/A
10365531	12/2018	Shrivastava et al.	N/A	N/A
10532268	12/2019	Tran et al.	N/A	N/A
10768582	12/2019	Shrivastava et al.	N/A	N/A
10859983	12/2019	Shrivastava et al.	N/A	N/A
10867266	12/2019	Carlin et al.	N/A	N/A
10921675	12/2020	Barnum et al.	N/A	N/A
10964320	12/2020	Shrivastava	N/A	E06B 9/24
10982487	12/2020	Ramirez	N/A	N/A
11073800	12/2020	Shrivastava et al.	N/A	N/A
11205926	12/2020	Shrivastava et al.	N/A	N/A
11295743	12/2021	Bumberger	N/A	G10L 15/22
11579571	12/2022	Shrivastava et al.	N/A	N/A

11592723	12/2022	Shrivastava et al.	N/A	N/A
11687045	12/2022	Shrivastava et al.	N/A	N/A
11733660	12/2022	Shrivastava et al.	N/A	N/A
11735183	12/2022	Shrivastava et al.	N/A	N/A
2002/0027504	12/2001	Davis et al.	N/A	N/A
2002/0075472	12/2001	Holton	N/A	N/A
2002/0113168	12/2001	Rukavina et al.	N/A	N/A
2002/0152298	12/2001	Kikta et al.	N/A	N/A
2003/0046072	12/2002	Ramaswamy	704/240	G10L 17/02
2003/0210449	12/2002	Ingalls et al.	N/A	N/A
2003/0210450	12/2002	Yu et al.	N/A	N/A
2003/0227663	12/2002	Agrawal et al.	N/A	N/A
2003/0227664	12/2002	Agrawal et al.	N/A	N/A
2004/0001056	12/2003	Atherton et al.	N/A	N/A
2004/0102977	12/2003	Metzler	704/E15.04	G10L 15/22
2004/0135989	12/2003	Klebe	N/A	N/A
2004/0160322	12/2003	Stilp	N/A	N/A
2004/0215520	12/2003	Butler et al.	N/A	N/A
2004/0236620	12/2003	Chauhan et al.	N/A	N/A
2005/0063036	12/2004	Bechtel et al.	N/A	N/A
2005/0200934	12/2004	Callahan et al.	N/A	N/A
2005/0200937	12/2004	Weidner	N/A	N/A
2005/0225830	12/2004	Huang et al.	N/A	N/A
2005/0268629	12/2004	Ahmed	N/A	N/A
2005/0270620	12/2004	Bauer et al.	N/A	N/A
2005/0278047	12/2004	Ahmed	N/A	N/A
2006/0001683	12/2005	May et al.	N/A	N/A
2006/0007550	12/2005	Tonar et al.	N/A	N/A
2006/0018000	12/2005	Greer	N/A	N/A
2006/0107616	12/2005	Ratti et al.	N/A	N/A
2006/0170376	12/2005	Piepgras	315/295	H05B 47/105
2006/0179376	12/2005	Asaka	N/A	N/A
2006/0187608	12/2005	Stark	N/A	N/A
2006/0209007	12/2005	Pyo et al.	N/A	N/A
2006/0245024	12/2005	Greer	N/A	N/A
2007/0002007	12/2006	Tam	N/A	N/A
2007/0053053	12/2006	Moskowitz	N/A	N/A
2007/0067048	12/2006	Bechtel et al.	N/A	N/A
2007/0097484	12/2006	Libretto et al.	N/A	N/A
2007/0118831	12/2006	Kondo	N/A	N/A
2007/0162233	12/2006	Schwenke	N/A	N/A
2007/0285759	12/2006	Ash et al.	N/A	N/A
2008/0018979	12/2007	Mahe et al.	N/A	N/A
2008/0043316	12/2007	Moskowitz	N/A	N/A
2008/0048101	12/2007	Romig et al.	N/A	N/A
2008/0211682	12/2007	Hyland et al.	N/A	N/A
2008/0213904	12/2007	Sliwa et al.	N/A	N/A

2009/0015740	12/2008	Sagitov et al.	N/A	N/A
2009/0027759	12/2008	Albahri	N/A	N/A
2009/0066157	12/2008	Tarng et al.	N/A	N/A
2009/0143141	12/2008	Wells et al.	N/A	N/A
2009/0187405	12/2008	Bhogal	704/246	G10L 17/00
2009/0243732	12/2008	Tarng et al.	N/A	N/A
2009/0243802	12/2008	Wolf et al.	N/A	N/A
2009/0257576	12/2008	Wellard et al.	N/A	N/A
2010/0039410	12/2009	Becker et al.	N/A	N/A
2010/0057451	12/2009	Carraux	704/E15.04	G10L 15/30
2010/0066484	12/2009	Hanwright et al.	N/A	N/A
2010/0082081	12/2009	Niessen et al.	N/A	N/A
2010/0172009	12/2009	Matthews	N/A	N/A
2010/0172010	12/2009	Gustavsson et al.	N/A	N/A
2010/0188057	12/2009	Tarng	N/A	N/A
2010/0228854	12/2009	Morrison et al.	N/A	N/A
2010/0235206	12/2009	Miller et al.	N/A	N/A
2010/0243427	12/2009	Kozlowski et al.	N/A	N/A
2010/0245289	12/2009	Svajda	N/A	N/A
2010/0245972	12/2009	Wright	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0302624	12/2009	Moskowitz	N/A	N/A
2010/0315693	12/2009	Lam et al.	N/A	N/A
2011/0046810	12/2010	Bechtel et al.	N/A	N/A
2011/0063708	12/2010	Letocart	N/A	N/A
2011/0097081	12/2010	Gupta et al.	N/A	N/A
2011/0148218	12/2010	Rozbicki	N/A	N/A
2011/0164304	12/2010	Brown et al.	N/A	N/A
2011/0167617	12/2010	Letocart	N/A	N/A
2011/0184561	12/2010	Klasson et al.	N/A	N/A
2011/0235152	12/2010	Letocart	N/A	N/A
2011/0249313	12/2010	Letocart	N/A	N/A
2011/0255142	12/2010	Ash et al.	N/A	N/A
2011/0266419	12/2010	Jones et al.	N/A	N/A
2011/0292488	12/2010	McCarthy et al.	N/A	N/A
2011/0304898	12/2010	Letocart	N/A	N/A
2011/0307112	12/2010	Barrilleaux	N/A	N/A
2012/0026573	12/2011	Collins et al.	N/A	N/A
2012/0033287	12/2011	Friedman et al.	N/A	N/A
2012/0062975	12/2011	Mehtani et al.	N/A	N/A
2012/0089488	12/2011	Letchford	N/A	N/A
2012/0105257	12/2011	Murillo et al.	N/A	N/A
2012/0133315	12/2011	Berman	359/275	E06B 9/68
2012/0153868	12/2011	Gu et al.	N/A	N/A
2012/0190386	12/2011	Anderson	N/A	N/A
2012/0191789	12/2011	Endo	709/206	H04L 51/42
2012/0194895	12/2011	Podbelski et al.	N/A	N/A

2012/0200908	12/2011	Bergh et al.	N/A	N/A
2012/0232969	12/2011	Fadell et al.	N/A	N/A
2012/0236386	12/2011	Mehtani et al.	N/A	N/A
2012/0239209	12/2011	Brown et al.	N/A	N/A
2012/0268803	12/2011	Greer et al.	N/A	N/A
2012/0293855	12/2011	Shrivastava et al.	N/A	N/A
2013/0057937	12/2012	Berman	359/245	G05B 13/04
2013/0073681	12/2012	Jiang et al.	N/A	N/A
2013/0085614	12/2012	Wenzel et al.	N/A	N/A
2013/0158790	12/2012	McIntyre, Jr. et al.	N/A	N/A
2013/0196600	12/2012	Capers et al.	N/A	N/A
2013/0226353	12/2012	Park	N/A	N/A
2013/0242370	12/2012	Wang	N/A	N/A
2013/0263510	12/2012	Gassion	N/A	N/A
2013/0271812	12/2012	Brown et al.	N/A	N/A
2013/0271813	12/2012	Brown	N/A	N/A
2013/0271814	12/2012	Brown	N/A	N/A
2013/0271815	12/2012	Pradhan et al.	N/A	N/A
2013/0289999	12/2012	Hymel	704/273	G10L 21/0208
2013/0307771	12/2012	Parker	345/158	G06F 3/167
2014/0067733	12/2013	Humann	N/A	N/A
2014/0098007	12/2013	Delpier et al.	N/A	N/A
2014/0101573	12/2013	Kuo	N/A	N/A
2014/0108019	12/2013	Ehsani	704/275	G10L 21/06
2014/0142937	12/2013	Powledge	704/235	G06F 3/017
2014/0160550	12/2013	Brown et al.	N/A	N/A
2014/0169795	12/2013	Clough	398/106	H04W 88/02
2014/0172430	12/2013	Rutherford	704/273	G06F 3/167
2014/0172557	12/2013	Eden et al.	N/A	N/A
2014/0185284	12/2013	Hsu et al.	N/A	N/A
2014/0229174	12/2013	Graumann	704/231	G10L 15/183
2014/0236323	12/2013	Brown et al.	N/A	N/A
2014/0259931	12/2013	Plummer	N/A	N/A
2014/0268287	12/2013	Brown et al.	N/A	N/A
2014/0300945	12/2013	Parker	N/A	N/A
2014/0330538	12/2013	Conklin et al.	N/A	N/A
2014/0330569	12/2013	Kolavennu	704/275	G10L 15/1815
2014/0347190	12/2013	Grimm	N/A	N/A
2014/0349497	12/2013	Brown et al.	N/A	N/A
2014/0358553	12/2013	Helmke et al.	N/A	N/A
2014/0371931	12/2013	Lin et al.	N/A	N/A

2014/0379353	12/2013	Boies	704/275	G10L 15/22
2015/0002919	12/2014	Jack et al.	N/A	N/A
2015/0003822	12/2014	Fukada et al.	N/A	N/A
2015/0023661	12/2014	Borkenhagen et al.	N/A	N/A
2015/0049378	12/2014	Shrivastava et al.	N/A	N/A
2015/0060648	12/2014	Brown et al.	N/A	N/A
2015/0070745	12/2014	Pradhan	N/A	N/A
2015/0112667	12/2014	Kozuka	704/201	G06F 3/167
2015/0116811	12/2014	Shrivastava	359/275	H04Q 9/00
2015/0122474	12/2014	Petersen	N/A	N/A
2015/0162006	12/2014	Kummer	N/A	N/A
2015/0243283	12/2014	Halash	704/246	G10L 17/22
2015/0293422	12/2014	Pradhan et al.	N/A	N/A
2015/0327304	12/2014	Tinnakornsrisuphap et al.	N/A	N/A
2015/0331666	12/2014	Bucsa	704/275	G06F 3/167
2015/0348554	12/2014	Orr et al.	N/A	N/A
2016/0007431	12/2015	Bosua	315/307	F21V 23/023
2016/0040478	12/2015	Lundy	700/275	E06B 9/68
2016/0054633	12/2015	Brown et al.	N/A	N/A
2016/0154290	12/2015	Brown et al.	N/A	N/A
2016/0170206	12/2015	Osborne	345/8	G02B 27/017
2016/0203403	12/2015	Nagel et al.	N/A	N/A
2016/0261837	12/2015	Thompson et al.	N/A	N/A
2016/0266461	12/2015	Yamamoto	N/A	N/A
2016/0266878	12/2015	Mankovskii	N/A	N/A
2016/0299210	12/2015	Zeine	N/A	N/A
2016/0327293	12/2015	Grabowski et al.	N/A	N/A
2016/0358603	12/2015	Azam	N/A	G10L 15/26
2017/0075183	12/2016	Brown	N/A	N/A
2017/0076721	12/2016	Bargetzi	N/A	G10L 15/22
2017/0080341	12/2016	Mao et al.	N/A	N/A
2017/0082903	12/2016	Vigano et al.	N/A	N/A
2017/0092269	12/2016	Haubrich	N/A	H04R 25/554
2017/0097618	12/2016	Cipollo	N/A	G10L 15/22
2017/0188437	12/2016	Banta	N/A	G10L 15/22
2017/0234067	12/2016	Fasi et al.	N/A	N/A
2017/0251488	12/2016	Urban et al.	N/A	N/A

2017/0285432	12/2016	Shrivastava et al.	N/A	N/A
2018/0122366	12/2017	Nishikawa	N/A	G06F 3/167
2018/0129172	12/2017	Shrivastava et al.	N/A	N/A
2018/0259804	12/2017	Bae	N/A	G02F 1/13306
2018/0284555	12/2017	Klawuhn et al.	N/A	N/A
2018/0293981	12/2017	Ni	N/A	G06F 21/32
2018/0321042	12/2017	Brewer et al.	N/A	N/A
2018/0335939	12/2017	Karunamuni et al.	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0004677	12/2018	Madonna et al.	N/A	N/A
2019/0097827	12/2018	Angle et al.	N/A	N/A
2019/0138740	12/2018	Ricknas et al.	N/A	N/A
2019/0235451	12/2018	Shrivastava et al.	N/A	N/A
2019/0257150	12/2018	Fasi et al.	N/A	N/A
2019/0294018	12/2018	Shrivastava et al.	N/A	N/A
2019/0346734	12/2018	Shrivastava et al.	N/A	N/A
2019/0354071	12/2018	Turney et al.	N/A	N/A
2020/0022072	12/2019	Cho et al.	N/A	N/A
2020/0134773	12/2019	Pinter	N/A	G01N 21/8806
2020/0193155	12/2019	Keohane et al.	N/A	N/A
2020/0293186	12/2019	Barnum et al.	N/A	N/A
2020/0319765	12/2019	Badr et al.	N/A	N/A
2020/0387041	12/2019	Shrivastava et al.	N/A	N/A
2021/0088867	12/2020	Nagel et al.	N/A	N/A
2021/0126063	12/2020	Vanderveen et al.	N/A	N/A
2021/0174804	12/2020	Shrivastava et al.	N/A	N/A
2021/0210053	12/2020	Ng et al.	N/A	N/A
2021/0325754	12/2020	Brown et al.	N/A	N/A
2021/0373511	12/2020	Shrivastava et al.	N/A	N/A
2022/0159077	12/2021	Shrivastava et al.	N/A	N/A
2022/0365494	12/2021	Shrivastava et al.	N/A	N/A
2023/0333520	12/2022	Shrivastava et al.	N/A	N/A
2023/0393443	12/2022	Marquez et al.	N/A	N/A
2024/0329484	12/2023	Trikha et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2590732	12/2002	CN	N/A
1526132	12/2003	CN	N/A
1808505	12/2005	CN	N/A
101013211	12/2006	CN	N/A
101023711	12/2006	CN	N/A
101213788	12/2007	CN	N/A
101969207	12/2010	CN	N/A
102203370	12/2010	CN	N/A

102792764	12/2011	CN	N/A
103137128	12/2012	CN	N/A
103226950	12/2012	CN	N/A
104335595	12/2014	CN	N/A
104395677	12/2014	CN	N/A
104424947	12/2014	CN	N/A
105143586	12/2014	CN	N/A
105395166	12/2015	CN	N/A
106125444	12/2015	CN	N/A
10124673	12/2001	DE	N/A
0445314	12/1990	EP	N/A
0869032	12/1997	EP	N/A
0920210	12/1998	EP	N/A
0835475	12/2003	EP	N/A
1510854	12/2004	EP	N/A
1417535	12/2004	EP	N/A
1619546	12/2005	EP	N/A
2090961	12/2008	EP	N/A
2161615	12/2009	EP	N/A
2357544	12/2010	EP	N/A
2764998	12/2013	EP	N/A
3352053	12/2017	EP	N/A
3449341	12/2018	EP	N/A
S63208830	12/1987	JP	N/A
H02132420	12/1989	JP	N/A
H05178645	12/1992	JP	N/A
H1063216	12/1997	JP	N/A
2004245985	12/2003	JP	N/A
2009116352	12/2008	JP	N/A
4694816	12/2010	JP	N/A
4799113	12/2010	JP	N/A
2012028015	12/2011	JP	N/A
2013057975	12/2012	JP	N/A
2015009941	12/2014	JP	N/A
2015509204	12/2014	JP	N/A
2015129438	12/2014	JP	N/A
2016502355	12/2015	JP	N/A
2016516921	12/2015	JP	N/A
200412640	12/2005	KR	N/A
100752041	12/2006	KR	N/A
20080022319	12/2007	KR	N/A
20090026181	12/2008	KR	N/A
100904847	12/2008	KR	N/A
100931183	12/2008	KR	N/A
20100034361	12/2009	KR	N/A
20110003698	12/2010	KR	N/A
20110094672	12/2010	KR	N/A
20110128213	12/2010	KR	N/A
20150136981	12/2014	KR	N/A
2378672	12/2009	RU	N/A

2009132962	12/2010	RU	N/A
201115503	12/2010	TW	N/A
201535157	12/2014	TW	N/A
201631551	12/2015	TW	N/A
202248837	12/2021	TW	N/A
WO-9816870	12/1997	WO	N/A
WO-0213052	12/2001	WO	N/A
WO-2004003649	12/2003	WO	N/A
WO-2005098811	12/2004	WO	N/A
WO-2005103807	12/2004	WO	N/A
WO-2007016546	12/2006	WO	N/A
WO-2007146862	12/2006	WO	N/A
WO-2008030018	12/2007	WO	N/A
WO-2008147322	12/2007	WO	N/A
WO-2009042359	12/2008	WO	N/A
WO-2009124647	12/2008	WO	N/A
WO-2010079388	12/2009	WO	N/A
WO-2010120771	12/2009	WO	N/A
WO-2011020478	12/2010	WO	N/A
WO-2011087684	12/2010	WO	N/A
WO-2011087687	12/2010	WO	N/A
WO-2011124720	12/2010	WO	N/A
WO-2011127015	12/2010	WO	N/A
WO-2012079159	12/2011	WO	N/A
WO-2012080618	12/2011	WO	N/A
WO-2012080656	12/2011	WO	N/A
WO-2012080657	12/2011	WO	N/A
WO-2012145155	12/2011	WO	N/A

WO- 2013059674	12/2012	WO	N/A
WO- 2013101066	12/2012	WO	N/A
WO- 2013109881	12/2012	WO	N/A
WO- 2013155467	12/2012	WO	N/A
WO- 2013158365	12/2012	WO	N/A
WO- 2014121863	12/2013	WO	N/A
WO- 2014130471	12/2013	WO	N/A
WO- 2014134451	12/2013	WO	N/A
WO- 2014209812	12/2013	WO	N/A
WO- 2015077097	12/2014	WO	N/A
WO- 2015134789	12/2014	WO	N/A
WO- 2015168626	12/2014	WO	N/A
WO- 2015171886	12/2014	WO	N/A
WO- 2016004109	12/2015	WO	N/A
WO- 2016037772	12/2015	WO	N/A
WO- 2016094445	12/2015	WO	N/A
WO- 2017059362	12/2016	WO	N/A
WO- 2017075059	12/2016	WO	N/A
WO- 2017155833	12/2016	WO	N/A
WO- 2017189618	12/2016	WO	N/A
WO- 2017192881	12/2016	WO	N/A
WO- 2018098089	12/2017	WO	N/A
WO- 2018200740	12/2017	WO	N/A
WO- 2018200752	12/2017	WO	N/A
WO- 2020037055	12/2019	WO	N/A

WO- 2021067505	12/2020	WO	N/A
WO- 2021163552	12/2020	WO	N/A

OTHER PUBLICATIONS

“SageGlass helps Solar Decathlon- and AIA award-winning home achieve net-zero energy efficiency” in MarketWatch.com, <http://www.marketwatch.com/story/sageglass-helps-solar-decathlon-and-aia-award-winning-home-achieve-net-zero-energy-efficiency-2012-06-07>, Jun. 7, 2012. cited by applicant

APC by Schneider Electric, Smart-UPS 120V Product Brochure, 2013, 8 pp. cited by applicant

AU Examination Report mailed on Jun. 3, 2021, in the application No. AU2017257789. cited by applicant

AU Office action dated Dec. 5, 2022, in AU Application No. AU2017363581. cited by applicant

AU Office Action dated Dec. 7, 2021, in Application No. AU2017257789. cited by applicant

AU Office Action dated Jun. 1, 2022, in Application No. AU2017257789. cited by applicant

AU Office Action dated May 13, 2022, in Application No. AU2017257789. cited by applicant

Bannat, A., et al., “Artificial Cognition in Production Systems”, IEEE Transactions on Automation Science and Engineering, 2011, vol. 8, No. 1, pp. 148-174. cited by applicant

Chinese Office Action dated Jan. 15, 2018 in CN Application No. 201380025802.1. cited by applicant

Chinese Office Action dated Jun. 21, 2017 in CN Application No. 201380025802.1. cited by applicant

Chinese Office Action dated May 20, 2020 in CN Application No. 201810932986.4. cited by applicant

Chinese Office Action dated Nov. 23, 2020 in CN Application No. 201810932986.4. cited by applicant

CN Office Action dated Aug. 30, 2021, in CN Application No. 201780035569.3 with English translation. cited by applicant

CN Office Action dated Jan. 28, 2023 in Application No. CN201780035569.3 with English translation. cited by applicant

CN Office Action dated May 7, 2022, in Application No. CN201780035569.3 with English translation. cited by applicant

CN office action dated May 30, 2023, in application No. CN201780035569.3 with English Translation. cited by applicant

Communication re Third-Party Observation dated Dec. 4, 2014 and Third-Party Observation dated Dec. 3, 2014 in PCT/US2014/016974. cited by applicant

Duchon, Claude E. et al., “Estimating Cloud Type from Pyranometer Observations,” Journal of Applied Meteorology, vol. 38, Jan. 1999, pp. 132-141. cited by applicant

EP Office Action dated Apr. 13, 2022, in Application No. EP17874769.7. cited by applicant

EP Office Action dated Jul. 4, 2023, in application No. EP17874769.7. cited by applicant

EP Office Action dated Oct. 5, 2021, in application No. EP17874769.7. cited by applicant

European Extended Search Report and Opinion dated May 20, 2020 in European Application No. 17874769.7. cited by applicant

European Extended Search Report and Opinion dated Nov. 7, 2019 in European Application No. 17790290.5. cited by applicant

European (Extended) Search Report dated Aug. 25, 2017 in European Application No. 17156033.7. cited by applicant

European (extended) Search Report dated Dec. 4, 2015 in European Application No. 13775052.7. cited by applicant

European Office Action dated Aug. 30, 2022 in Application No. EP17790290.5. cited by applicant

European Search Report dated Aug. 11, 2014 in European Application No. 12757877.1. cited by applicant

European Search Report dated Jul. 23, 2014 in European Application No. 12756917.6. cited by applicant

European Search Report dated Jul. 29, 2014 in European Application No. 12758250.0. cited by applicant

European Search Report dated Mar. 5, 2015 in European Application No. 12841714.4. cited by applicant

Final Office Action dated Jun. 5, 2015 in U.S. Appl. No. 13/968,258. cited by applicant

Graham, Steve, "Clouds & Radiation," Mar. 1, 1999.
[<http://earthobservatory.nasa.gov/Features/Clouds/>]. cited by applicant

Haby, Jeff, "Cloud Detection (IR v. VIS)," (known as of Sep. 3, 2014)
[<http://theweatherprediction.com/habyhints2/512/>]. cited by applicant

Hoosier Energy, "How do they do that? Measuring Real-Time Cloud Activity" Hoosier Energy Current Connections, (known as of Sep. 3, 2014). (<http://members.questline.com/Article.aspx?articleID=18550&accountID=196000&nl=11774>). cited by applicant

"How Cleantech wants to make a 2012 comeback" <http://mountainview.patch.com/articles/how-cleantech-wants-to-make-a-2012-comeback>, Jan. 23, 2012. cited by applicant

IN Office Action dated Jun. 21, 2021, in IN Application No. 201817042037. cited by applicant

IN Office Action dated Oct. 7, 2022, in Application No. IN202118056857. cited by applicant

Indian Office Action dated Jul. 6, 2022, in IN Application No. 201917018642. cited by applicant

Indian Office Action dated Sep. 17, 2019 in Indian Application No. 2533/KOLNP/2014. cited by applicant

International Preliminary Report on Patentability dated Feb. 19, 2015 issued in PCT/US2013/053625. cited by applicant

International Preliminary Report on Patentability dated May 1, 2014 in PCT/US2012/061137. cited by applicant

International Preliminary Report on Patentability dated May 19, 2023 in PCT Application No. PCT/US2021/057678. cited by applicant

International Preliminary Report on Patentability dated Nov. 8, 2018 in PCT/US2017/29476. cited by applicant

International Preliminary Report on Patentability dated Oct. 23, 2014 issued in PCT/US2013/036456. cited by applicant

International Preliminary Report on Patentability dated Oct. 30, 2014 issued in PCT/US2013/034998. cited by applicant

International Preliminary Report on Patentability dated Oct. 30, 2014 issued in PCT/US2013/036235. cited by applicant

International Preliminary Report on Patentability dated Sep. 26, 2013, issued in PCT/US2012/027742. cited by applicant

International Preliminary Report on Patentability dated Sep. 26, 2013, issued in PCT/US2012/027828. cited by applicant

International Preliminary Report on Patentability dated Sep. 26, 2013, issued in PCT/US2012/027909. cited by applicant

International Preliminary Report on Patentability (ISA:KR) dated Jun. 6, 2019, issued in PCT/US2017/062634. cited by applicant

International Search Report and Written Opinion dated Apr. 19, 2022 in PCT Application No. PCT/US2021/057678. cited by applicant

International Search Report and Written Opinion dated Aug. 8, 2022, in Application No. PCT/US2022/023605. cited by applicant

International Search Report and Written Opinion dated Aug. 5, 2021 in PCT Application No. PCT/US2021/027418. cited by applicant

International Search Report and Written Opinion dated Dec. 26, 2013, issued in PCT/US2013/053625. cited by applicant

International Search Report and Written Opinion dated Jul. 6, 2022, in PCT Application No. PCT/US2022/020730. cited by applicant

International Search Report and Written Opinion dated Jul. 11, 2013, issued in PCT/US2013/034998. cited by applicant

International Search Report and Written Opinion dated Jul. 23, 2013, issued in PCT/US2013/036235. cited by applicant

International Search Report and Written Opinion dated Jul. 26, 2013, issued in PCT/US2013/036456. cited by applicant

International Search Report and Written Opinion dated Mar. 28, 2013 in PCT/US2012/061137. cited by applicant

International Search Report and Written Opinion dated May 26, 2014 in PCT/US2014/016974. cited by applicant

International Search Report and Written Opinion dated Oct. 16, 2014, issued in PCT/US2014/043514. cited by applicant

International Search Report and Written Opinion dated Sep. 24, 2012, issued in PCT/US2012/027742. cited by applicant

International Search Report and Written Opinion dated Sep. 24, 2012, issued in PCT/US2012/027909. cited by applicant

International Search Report and Written Opinion dated Sep. 26, 2012, issued in PCT/US2012/027828. cited by applicant

International Search Report and Written Opinion (ISA:KR) dated Jul. 18, 2017, issued in PCT/US2017/29476. cited by applicant

International Search Report and Written Opinion (ISA:KR) dated Mar. 19, 2018, issued in PCT/US2017/062634. cited by applicant

Japanese Office Action dated Mar. 23, 2021 in JP Application No. 2018-555922. cited by applicant

Japanese Office Action dated May 16, 2023 in JP Application No. JP2022-0031460. cited by applicant

JP Office Action dated Jul. 25, 2023, in Application No. JP2022-176255 with English Translation. cited by applicant

JP Office Action dated Nov. 2, 2021, in JP Application No. JP20180555922. cited by applicant

Kleissl, Jan et al., "Recent Advances in Solar Variability Modeling and Solar Forecasting at UC San Diego," Proceedings, American Solar Energy Society, 2013 Solar Conference, Apr. 16-20, 2013, Baltimore, MD. cited by applicant

KR Office Action dated Dec. 14, 2021, in Application No. KR1020187034166 with English translation. cited by applicant

KR Office Action dated Sep. 20, 2022, in Application No. KR10-2018-7034166 with English translation. cited by applicant

Laskar, S.H., et al., "Power Quality Monitoring by Virtual Instrumentation using LabVIEW", 2011 46th International Universities' Power Engineering Conference (UPEC), 2011, pp. 1-6. cited by applicant

Letter dated Dec. 1, 2014 re Prior Art re U.S. Appl. No. 13/772,969 from Ryan D. Ricks representing MechoShade Systems, Inc. cited by applicant

Lim, Sunnie H.N. et al., "Modeling of optical and energy performance of tungsten-oxide-based electrochromic windows including their intermediate states," Solar Energy Materials & Solar Cells, vol. 108, Oct. 16, 2012, pp. 129-135. cited by applicant

Lululemon athletica, "Mirror", The Mirror Gym product brochure, known Dec. 8, 2020, 9 pp,

><https://shop.lululemon.com/story/mirror-home-gym> , retrieved Jan. 29, 2021. cited by applicant
National Aeronautics & Space Administration, “Cloud Remote Sensing and Modeling,” (known as of Sep. 3, 2014), published date of Sep. 15, 2014,
[<http://atmospheres.gsfc.nasa.gov/climate/index.php?section=134>]. cited by applicant
“New from Pella: Windows with Smartphone-run blinds”, Pella Corp.,
<http://www.desmoinesregister.com/article/20120114/BUSINESS/301140031/0/biggame/?odyssey=nav%7Chead>, Jan. 13, 2012. cited by applicant
Office Action dated Oct. 6, 2014 in U.S. Appl. No. 13/968,258. cited by applicant
Science and Technology Facilities Council. “Cloud Radar: Predicting The Weather More Accurately.” ScienceDaily, Oct. 1, 2008.
[www.sciencedaily.com/releases/2008/09/080924085200.htm]. cited by applicant
Taiwanese Office Action dated Apr. 16, 2021 in TW Application No. 106140690. cited by applicant
Third-Party Submission dated Feb. 2, 2015 and Feb. 18, 2015 PTO Notice re Third-Party Submission for U.S. Appl. No. 13/772,969. cited by applicant
Tuokko, R., et al., “Micro and Desktop Factory Road Map”, Tampere University of Technology, 2012, pp. 1-114. cited by applicant
TW Office Action dated Jun. 30, 2023, in application No. TW112118232 with English translation. cited by applicant
TW Office Action dated Sep. 28, 2022, in Application No. TW111130926 with English translation. cited by applicant
U.S. Notice of Allowance dated Jan. 11, 2023 in U.S. Appl. No. 16/946,947. cited by applicant
U.S. Corrected Notice of Allowance dated May 26, 2023 in U.S. Appl. No. 17/355,086. cited by applicant
US Final Office Action dated Apr. 30, 2012 in U.S. Appl. No. 13/049,750. cited by applicant
U.S. Final Office Action dated Aug. 19, 2013 in U.S. Appl. No. 13/049,756. cited by applicant
US Final Office Action dated Feb. 26, 2015 in U.S. Appl. No. 13/479,137. cited by applicant
US Final Office Action dated Feb. 8, 2018 in U.S. Appl. No. 14/391,122. cited by applicant
US Final Office Action dated Jan. 27, 2014 in U.S. Appl. No. 13/479,137. cited by applicant
U.S. Final Office Action dated Jul. 2, 2015 in U.S. Appl. No. 13/049,756. cited by applicant
US Final Office Action dated Jul. 3, 2017 in U.S. Appl. No. 14/391,122. cited by applicant
US Final Office Action dated May 15, 2014 in U.S. Appl. No. 13/449,251. cited by applicant
US Final Office Action dated May 16, 2014 in U.S. Appl. No. 13/449,248. cited by applicant
US Final Office Action dated Nov. 20, 2018 in U.S. Appl. No. 14/391,122. cited by applicant
US Final Office Action dated Nov. 5, 2020 in U.S. Appl. No. 16/096,557. cited by applicant
U.S. Non-Final office Action dated Jan. 20, 2023 in U.S. Appl. No. 17/249,148. cited by applicant
U.S. Non-Final office Action dated Nov. 15, 2022 in U.S. Appl. No. 17/355,086. cited by applicant
U.S. Non-Final office Action dated Sep. 9, 2022 in U.S. Appl. No. 16/946,947. cited by applicant
US Notice of Allowance dated Apr. 13, 2015 in U.S. Appl. No. 14/657,380. cited by applicant
U.S. Notice of Allowance dated Apr. 13, 2023 in U.S. Appl. No. 17/249,148. cited by applicant
U.S. Notice of Allowance dated Dec. 20, 2022 in U.S. Appl. No. 16/946,947. cited by applicant
U.S. Notice of Allowance dated Feb. 14, 2023 in U.S. Appl. No. 17/355,086. cited by applicant
US Notice of Allowance dated Jan. 10, 2014 in U.S. Appl. No. 13/449,235. cited by applicant
US Notice of Allowance dated Jan. 13, 2021 in U.S. Appl. No. 16/096,557. cited by applicant
US Notice of Allowance dated Jan. 22, 2015 in U.S. Appl. No. 13/682,618. cited by applicant
U.S. Notice of Allowance dated Jul. 6, 2023 in U.S. Appl. No. 17/870,480. cited by applicant
US Notice of Allowance dated Jul. 20, 2012 in U.S. Appl. No. 13/049,623. cited by applicant
U.S. Notice of Allowance dated Jun. 7, 2023 in U.S. Appl. No. 17/870,480. cited by applicant
US Notice of Allowance dated Jun. 17, 2014 in U.S. Appl. No. 13/309,990. cited by applicant
US Notice of Allowance dated Mar. 11, 2019 in U.S. Appl. No. 14/391,122. cited by applicant
US Notice of Allowance dated Mar. 26, 2021 in U.S. Appl. No. 16/254,434. cited by applicant

US Notice of Allowance dated May 14, 2015 in U.S. Appl. No. 13/479,137. cited by applicant
US Notice of Allowance dated May 8, 2012 in U.S. Appl. No. 13/049,750. cited by applicant
US Notice of Allowance (supplemental) dated Jun. 12, 2015 in U.S. Appl. No. 13/479,137. cited by applicant
US Office Action dated Dec. 24, 2013 in U.S. Appl. No. 13/309,990. cited by applicant
US Office Action dated Feb. 24, 2015 in U.S. Appl. No. 14/163,026. cited by applicant
US Office Action dated Feb. 3, 2012 in U.S. Appl. No. 13/049,750. cited by applicant
US Office Action dated Jan. 16, 2015 in U.S. Appl. No. 14/468,778. cited by applicant
U.S. Office Action dated Jan. 18, 2013 in U.S. Appl. No. 13/049,756. cited by applicant
US Office Action dated Jul. 3, 2014 in U.S. Appl. No. 13/479,137. cited by applicant
US Office Action dated Jun. 22, 2018 in U.S. Appl. No. 14/391,122. cited by applicant
US Office Action dated Jun. 3, 2015 in U.S. Appl. No. 13/449,251. cited by applicant
US Office Action dated Mar. 27, 2012 in U.S. Appl. No. 13/049,623. cited by applicant
US Office Action dated May 18, 2020 in U.S. Appl. No. 16/096,557. cited by applicant
US Office Action dated Nov. 18, 2016 in U.S. Appl. No. 14/391,122. cited by applicant
US Office Action dated Nov. 29, 2013 in U.S. Appl. No. 13/449,248. cited by applicant
US Office Action dated Nov. 29, 2013 in U.S. Appl. No. 13/449,251. cited by applicant
US Office Action dated Oct. 11, 2013 in U.S. Appl. No. 13/449,235. cited by applicant
US Office Action dated Oct. 28, 2014 in U.S. Appl. No. 13/449,251. cited by applicant
U.S. Office Action dated Oct. 6, 2014 in U.S. Appl. No. 13/049,756. cited by applicant
US Office Action dated Sep. 1, 2017 in U.S. Appl. No. 14/391,122. cited by applicant
US Office Action dated Sep. 15, 2014 in U.S. Appl. No. 13/682,618. cited by applicant
US Office Action dated Sep. 23, 2013 in U.S. Appl. No. 13/479,137. cited by applicant
US Office Action dated Sep. 29, 2014 in U.S. Appl. No. 13/449,248. cited by applicant
US Office Action dated Sep. 30, 2020 in U.S. Appl. No. 16/254,434. cited by applicant
U.S. Appl. No. 14/468,778, filed Aug. 26, 2014. cited by applicant
U.S. Appl. No. 18/034,328, inventors Marquez et al., filed on Apr. 27, 2023. cited by applicant
U.S. Appl. No. 18/213,843, inventors Shrivastava D, et al., filed on Jun. 25, 2023. cited by applicant
U.S. Appl. No. 18/100,773, inventors Shrivastava et al., filed on Jan. 24, 2023. cited by applicant
Australian Examination Report dated Sep. 5, 2023, in Application No. AU2022231771. cited by applicant
CA Office Action dated Oct. 23, 2023, in CA Application No. 3044823. cited by applicant
CA Office Action dated Sep. 18, 2023, in Application No. CA3022396. cited by applicant
EP Extended European Search Report dated May 15, 2024 in EP Application No. 21787899.0. cited by applicant
International Preliminary Report on Patentability and Written Opinion dated Mar. 14, 2024 in PCT Application No. PCT/US2022/075717. cited by applicant
International Preliminary Report on Patentability dated Oct. 19, 2023, in PCT Application No. PCT/US2022/023605. cited by applicant
International Preliminary Report on Patentability dated Sep. 28, 2023, in PCT Application No. PCT/US2022/020730. cited by applicant
International Search Report and Written Opinion dated Dec. 19, 2022, in Application No. PCT/US2022/075717. cited by applicant
International Search Report and Written Opinion dated Oct. 17, 20223 in PCT Application No. PCT/US2023/026514. cited by applicant
Japanese Office Action dated May 16, 2023 in JP Application No. JP2022-0031460 awaiting English translation. cited by applicant
JP Office Action dated Mar. 5, 2024 in JP Application No. 2022-176255, with English translation. cited by applicant

JP Office Action dated Nov. 2, 2021, in JP Application No. JP20180555922 awaiting English translation. cited by applicant
U.S. Appl. No. 18/281,913 inventors Trikha N, et al, filed on Sep. 13, 2023. cited by applicant
U.S. Appl. No. 18/688,561, inventors Rasmus-Vorrath J.K, et al., filed on Mar. 1, 2024. cited by applicant
CA Office Action dated Sep. 19, 2024 in CA Application No. 3022396. cited by applicant
Lee E., et al., "The Design and Evaluation of Integrated Envelope and Lighting Control Strategies for Commercial Buildings," Energy & Environment division, 1994, pp. 1-23. cited by applicant
U.S. Notice of Allowance dated Sep. 12, 2024 in U.S. Appl. No. 18/213,843. cited by applicant
U.S. Appl. No. 18/898,810, inventors Shrivastava D, et al., filed on Sep. 27, 2024. cited by applicant
U.S. Restriction requirement dated Sep. 26, 2024 in U.S. Appl. No. 18/100,773. cited by applicant

Primary Examiner: Godbold; Douglas

Attorney, Agent or Firm: Cha & Reiter, LLC

Background/Summary

INCORPORATION BY REFERENCE

(1) An Application Data Sheet is filed concurrently with this specification as part of the present application. Each application that the present application claims benefit of or priority to as identified in the concurrently filed Application Data Sheet is incorporated by reference herein in their entireties and for all purposes.

TECHNICAL FIELD

(2) This disclosure relates generally to optically switchable devices, and more particularly, to methods and apparatus for controlling optically switchable devices

BACKGROUND

(3) The development and deployment of optically switchable windows have increased as considerations of energy efficiency and system integration gain momentum. Electrochromic windows are a promising class of optically switchable windows. Electrochromism is a phenomenon in which a material exhibits a reversible electrochemically-mediated change in one or more optical properties when stimulated to a different electronic state. Electrochromic materials and the devices made from them may be incorporated into, for example, windows for home, commercial, or other use. The color, tint, transmittance, absorbance, or reflectance of electrochromic windows can be changed by inducing a change in the electrochromic material, for example, by applying a voltage across the electrochromic material. Such capabilities can allow for control over the intensities of various wavelengths of light that may pass through the window. One area of relatively recent interest is in intelligent control systems and algorithms for driving optical transitions in optically switchable windows to provide desirable lighting conditions while reducing the power consumption of such devices and improving the efficiency of systems with which they are integrated.

SUMMARY

(4) Various embodiments herein relate to methods, systems, and networks for controlling optically switchable devices. In a number of cases, one or more optically switchable device may be controlled using voice control and/or gesture control.

(5) In one aspect of the disclosed embodiments, a method of controlling an optical state of an optically switchable device is provided, the method including: (a) receiving a voice command or a

gesture command from a user, the voice command or gesture command conveying information for changing the optical state of the optically switchable device to a desired optical state; (b) using voice recognition or gesture recognition to convert the voice command or gesture command, respectively, into a text command; (c) analyzing the text command from (b) to interpret the voice command or gesture command from the user in (a); and (d) executing the text command to cause the optically switchable device to transition to the desired optical state.

(6) In certain embodiments, the method may further include (e) generating a response to the user indicating whether the voice command or gesture command made in (a) is occurring. In these or other cases, the method may include (f) confirming whether the user is authorized to execute the voice command or gesture command received in (a). The method may be implemented on a network of optically switchable devices, and may be implemented to control the optical state of a plurality of optically switchable devices on the network.

(7) The voice command or gesture command may relate to a variety of different control options. In one example, the voice command or gesture command from the user in (a) describes the desired optical state based on a relative comparison to a starting optical state of the optically switchable device. For instance, the voice command or gesture command from the user in (a) may indicate that the optically switchable device should become darker or lighter. Similarly, the voice command or gesture command from the user in (a) may indicate that the optically switchable device should become more opaque or less opaque. In another example, the voice command or gesture command from the user in (a) indicates that the optically switchable device should become more reflective or less reflective. In some cases, the voice command or gesture command from the user in (a) indicates that a step change should be made to the optical state of the optically switchable device.

(8) In certain embodiments, the voice command or gesture command from the user in (a) describes the desired optical state as a distinct optical state of the optically switchable device, without reference to a starting optical state of the optically switchable device. In various implementations, the voice command or gesture command from the user in (a) is a voice command instructing the optically switchable device to switch to the desired optical state according to one or more rules. In one example, the rule relates to a schedule and the voice command instructs the optically switchable device to switch to the desired optical state at a scheduled time. In another example, the rule relates to weather and the voice command instructs the optically switchable device to switch to the desired optical state if a particular weather condition occurs. In another example, the optically switchable device is installed in a building, the rule relates to environmental conditions within the building, and the voice command instructs the optically switchable device to switch to the desired optical state if an internal condition within the building occurs. In some such cases, the internal condition within the building relates to a temperature within the building.

(9) The various operations may occur at a number of different locations. In some cases, each of (a)-(d) occur locally on one or more controllers installed in a building in which the optically switchable device is installed. In some such cases, each of (a)-(d) occur locally on one or more controllers installed onboard the optically switchable device. In some other embodiments, (c) occurs on a processor that is located remotely from a building in which the optically switchable device is installed.

(10) In certain implementations, the voice command or gesture command from the user in (a) includes a gesture command. The user may identify the optically switchable device by pointing at it in some embodiments. In various cases, the method may involve interpreting both the gesture command and the voice command, the gesture command identifying which optically switchable device the user desires to control, and the voice command indicating the desired optical state for the optically switchable device.

(11) One or more dictionaries may be used to implement the method. In certain embodiments, (b) includes using two or more dictionaries to convert the voice command or gesture command into the text command, where a first dictionary is used when converting a first portion of the voice

command or gesture command, and a second dictionary is used when converting a second portion of the voice command or gesture command. In these or other cases, (c) may include using two or more dictionaries to analyze the text command, where a third dictionary is used when analyzing a first portion of the text command and a fourth dictionary is used when analyzing a second portion of the text command.

(12) In a further aspect of the disclosed embodiments, a system for controlling an optical state of an optically switchable device in response to a voice command or gesture command from a user is provided, the system including: (a) at least one element selected from the group consisting of: a microphone, a video camera, and a motion sensor; (b) a controller communicatively coupled with the optically switchable device and configured to control the optical state of the optically switchable device; (c) either (i) a voice recognition module configured to convert the voice command to a text command, or (ii) a gesture recognition module configured to convert the gesture command to the text command, where the voice command is perceived by the microphone and/or where the gesture command is perceived by the video camera and/or by the motion sensor; (d) a command processing module configured to interpret the text command generated by the voice recognition module or gesture recognition module; and (e) a command execution module configured to execute the interpreted text command from the command processing module.

(13) In certain embodiments, the system may further include (f) a response generation module configured to generate a response to the user; and (g) a response communication module configured to communicate the response to the user, where the response is communicated to the user visually and/or aurally.

(14) In some cases, the system includes (h) an authentication module configured to confirm whether the user is authorized to control the optically switchable device as requested in the voice command or gesture command from the user. The authentication module may be configured to authorize the user for a particular duration, and to request an additional authorization after the particular duration has passed. In some cases, the authentication module confirms whether the user is authorized by requiring the user to log in with a passcode. In another example, the authentication module confirms whether the user is authorized by using facial recognition to identify the user. In another example, the authentication module confirms whether the user is authorized by using voice recognition to identify the user. In various embodiments, the authentication module is configured to confirm whether the user is authorized each time the user provides a new voice command or a new gesture command. In these or other implementations, the authentication module may influence which dictionary or dictionaries are used in the voice recognition module, the gesture recognition module, and/or the command processing module.

(15) The microphone, video camera, and/or motion sensor may be provided onboard the optically switchable device in some cases. In some other cases, the microphone, video camera, and/or motion sensor may be provided on an electronic device that communicates with the optically switchable device. For instance, the electronic device may be a smartphone, tablet, laptop, personal computer, fitness device, watch, or wall unit. In some embodiments, the gesture command is perceived by the motion sensor, and the motion sensor includes one or more accelerometers, gyroscopes, and/or magnetometers. The system may be configured to control the optical state of a plurality of optically switchable devices each installed on a network.

(16) In a further aspect of the disclosed embodiments, a method of querying a control system of an electrochromic device is provided, the method including: (a) receiving a query from a user, where the query is provided in spoken form, and where the query is received by a device that is part of the control system for the electrochromic device; (b) using voice recognition to convert the query into a text query; (c) analyzing the text query from (b) to interpret the query from the user in (a); (d) determining an answer to the query; and (e) providing the answer to the user.

(17) In some embodiments, the answer is provided to the user in (e) by (i) displaying the answer so that the user can perceive the answer visually, and/or (ii) reciting the answer so that the user can

perceive the answer aurally. The query may relate to the electrochromic device. In some cases, the query relates to a current optical state of the electrochromic device and/or to an ongoing optical transition on the electrochromic device. In some other cases, the query relates to a future optical state of the electrochromic device and/or to a future optical transition on the electrochromic device. In some embodiments, determining the answer to the query in operation (d) includes searching the Internet to determine the answer.

(18) These and other features will be described below with reference to the associated drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows a block diagram of example modules that may be used for implementing voice control in some implementations.
- (2) FIG. 2A shows a flowchart for a method of controlling electrochromic windows using voice control in certain implementations.
- (3) FIG. 2B shows a flowchart for a method of controlling electrochromic windows using voice control in certain implementations where multiple dictionaries are used.
- (4) FIG. 2C shows a flowchart for a method of implementing voice control according to a specific example.
- (5) FIG. 3A shows a user interacting with a wall device to control electrochromic windows.
- (6) FIGS. 3B-3E show various configurations of components that may be used to implement certain control methods described herein.
- (7) FIG. 4 shows a cross-sectional view of an example electrochromic window **100** in accordance with some implementations.
- (8) FIG. 5 illustrates an example control profile in accordance with some implementations.
- (9) FIG. 6 shows a block diagram of an example network system operable to control a plurality of IGUs in accordance with some implementations.
- (10) FIG. 7 shows a block diagram of an example master controller (MC) in accordance with some implementations.
- (11) FIG. 8 shows a block diagram of an example network controller (NC) in accordance with some implementations.
- (12) FIG. 9 shows a block diagram of example modules of a network controller in accordance with some implementations.
- (13) Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

(14) The following detailed description is directed to specific example implementations for purposes of disclosing the subject matter. Although the disclosed implementations are described in sufficient detail to enable those of ordinary skill in the art to practice the disclosed subject matter, this disclosure is not limited to particular features of the specific example implementations described herein. On the contrary, the concepts and teachings disclosed herein can be implemented and applied in a multitude of different forms and ways without departing from their spirit and scope. For example, while the disclosed implementations focus on electrochromic windows (also referred to as smart windows), some of the systems, devices and methods disclosed herein can be made, applied or used without undue experimentation to incorporate, or while incorporating, other types of optically switchable devices that are actively switched/controlled, rather than passive coatings such as thermochromic coatings or photochromic coatings that tint passively in response to the sun's rays. Some other types of actively controlled optically switchable devices include liquid crystal devices, suspended particle devices, and micro-blinds, among others. For example, some or all of such other optically switchable devices can be powered, driven or otherwise controlled or

integrated with one or more of the disclosed implementations of controllers described herein. Additionally, in the following description, the phrases “operable to,” “adapted to,” “configured to,” “designed to,” “programmed to,” or “capable of” may be used interchangeably where appropriate.

(15) Voice and Gesture Control

(16) In a number of embodiments, voice and/or gesture control may be used to interact with an optically switchable device. Such control methods may be more convenient compared to more conventional control methods that may require a user to touch or otherwise physically interact with a particular component (e.g., switch, knob, keypad, touchscreen, etc.). Voice control may be particularly beneficial for users with certain disabilities.

(17) Example Commands

(18) Generally speaking, voice and/or gesture control may be used to implement any type of command on an optically switchable device. For example, voice and/or gesture control may be used to implement tinting commands for a single optically switchable device (e.g., “change window 1 to tint 4” or “make window 1 darker”), or for a group or zone of optically switchable devices (e.g., “change the windows in zone 1 to tint 4” or “make the windows in zone 1 darker” or “make the windows in zone 1 much darker,” etc.). The commands may relate to discrete optical states to which the relevant optically switchable device(s) should change (e.g., discrete tint levels, or other discrete optical states) or relative changes in the optical states of the optically switchable device(s) (e.g., darker, lighter, more reflective, less reflective, e.g., or “my office is too dark, please lighten it up” or “I want to run the projector,” (letting the system know to darken the room) or “it's hot in here” (letting the system know to darken the windows and block heat gain) etc.). Where relative changes are used, the control system may be designed or configured to implement step changes (e.g., 10% darker or lighter) in the optical state of the optically switchable device to carry out the command. The degree of each step change may be pre-defined. Alternatively or in addition, the control system may be designed or configured to implement step changes of a size or degree specified by the user. Such commands may be modified by any relative words used in the command (e.g., “very” or “a little bit,” or “lighter” or “darker” etc.).

(19) Voice control can also be used to set a schedule for the optically switchable device. For instance, a user may direct the optically switchable device(s) to tint at particular times/days (e.g., “make the windows in zone 1 go to tint 4 at 2 pm Monday through Friday” or “the morning sun makes it hot in here” (letting the system know to tint the windows during the morning hours when the sun impinges on that side of the building) or “I can't see the mountains well in the afternoon” (letting the system know that the windows are tinted too much in the afternoon and to lighten them during the afternoon)). Similarly, voice control can be used to implement tinting rules for the optically switchable device (e.g., “tint the windows in zone 1 to tint 4 when it's sunny outside” or “tint the windows in this room if the temperature inside this room is above 70° F.”). Any rules that can be implemented on a network of optically switchable devices (including any other networked components such as thermostat, BMS, electronic device, etc.) can be initiated via voice control.

(20) Voice control can be implemented on various components of control architecture for the smart window system, e.g., onboard window controllers or other window controllers, network controllers, master controllers, wall switches (e.g., interfaces with control components) and/or a separate device that interfaces with any or all of the aforementioned devices and/or components.

(21) Gesture control may be more limited to some degree, due to a more limited dictionary of movements that can be recognized compared to the more expansive dictionary of words that can be recognized when using voice control. However, gesture control can still be used to implement many types of commands. For instance, gesture control can be used to indicate that a particular window or group of windows should change to a lighter or darker state (or other optical states if non-electrochromic optically switchable devices are used). The user may indicate the window(s) to be changed by standing in front of the relevant window(s) and/or pointing to the relevant window(s). The user may indicate the desired change by raising or lowering their hands or arms, or

by opening or closing their palms, for instance. A dictionary of recognized gestures may be created to define the types of commands that can be accomplished via gesture control. More expansive gesture dictionaries may enable finer, more complex control of the optically switchable devices. However, there is some degree of tradeoff in terms of ease of use, with smaller gesture dictionaries being easier for users to master.

(22) In some cases, the gestures may be perceived by a video camera. The camera may be provided on any available device, and in some examples is provided as part of a wall unit, as part of a device that interfaces with a wall unit (e.g., a smartphone, tablet, or other electronic device), as part of a hand-held device (e.g., smartphone, tablet, or other electronic device), on an electrochromic window or frame, or as part of any other device that is configured to control an electrochromic or other optically switchable window. Alternatively or in addition, a user may gesture while holding, wearing, or otherwise moving a sensing device that is configured to sense movement/acceleration/etc. The readings on the sensing device may be used to help determine what gesture a user has made. The movement sensing device may include one or more accelerometers, gyroscopes, and/or magnetometers, etc. In some embodiments, the sensing device may be a fitness device (e.g., any of various wearable devices from Fitbit Inc. or Jawbone, each in San Francisco, CA), watch (e.g., from Apple Inc. of Cupertino, CA or Pebble Technology Corporation in Palo Alto, CA), or similar wearable device. In certain embodiments, facial recognition software is used to determine changes in facial expressions as commands to change the tint level of windows.

(23) Another type of command that may be initiated via voice control is to turn off “listening mode.” When listening mode is on, the device that listens for commands is able to pick up oral commands. When listening mode is off, the device that listens for commands is not able to pick up/hear/record such commands. As explained further below, the device that listens for commands may be part of a window controller, IGU, wall device, and/or other electronic device (e.g., phone, tablet, etc.), for example. A user may desire to turn listening mode off for increased privacy, energy savings, etc. In some cases, the user may request that listening mode turn off for a specified time period (e.g., the duration of a meeting). In order to turn listening mode back on, the user may press a button/touchscreen (e.g., on the device that listens for commands, on the window controller, IGU, wall device, or other electronic device) or otherwise indicate that listening mode should turn back on. Devices may indicate when listening mode is on and/or off. In one example, one or more lights (e.g., LEDs) may indicate whether listening mode is on or off. The light may be turned on to indicate that listening mode is on, and off to indicate that listening mode is off (or vice versa). In another example, a first light or light color may indicate that listening mode is on, and a second light or light color may indicate that listening mode is off. In another example, devices can use an audio cue, e.g., may emit a tone, e.g., periodically, as a reminder to the user that listening mode is inactive (or active). In certain implementations, listening mode may be deactivated for a period of time (e.g., 1 minute, 10 minutes, 30 minutes, 1 hour, 2 hour, 3 hours, 1 day, etc.), after which listening mode may automatically be reactivated. The period of time over which listening mode remains deactivated may be chosen by the user, or may be preset. In some embodiments, listening mode is activated by default. In other words, listening mode is on unless it is turned off (e.g., permanently turned off, or turned off for a period of time, as mentioned above). In other embodiments, the default setting may be that listening mode is off. In these embodiments, listening mode does not activate unless a command is received to turn listening mode on.

(24) Analogously, where gesture command is used, the user may control whether a relevant device that interprets gesture commands is in a “watching mode.” Like the listening mode, the watching mode can be turned on and off. When a device is in watching mode, it is able to sense and interpret gesture commands. When the watching mode is off, the device is not able to sense, record, and/or process gesture commands. Generally speaking, details provided herein related to listening mode may similarly apply to watching mode.

(25) In certain implementations, voice commands may be used to ask a question to the system controlling the optically switchable device (or some component on the network on which the optically switchable device is installed). The questions may relate directly to the optically switchable device, or more generally, to any optically switchable device or group of devices on the network. For instance, a user may ask what the current optical state is for a particular optically switchable device (e.g., “what’s the tint level of window 1?”). Similarly, a user may ask what the upcoming behavior will be for a particular optically switchable device (e.g., “when is the next time the windows in my office will begin to get darker?”). The questions may also relate to any other information to which the network has access. For instance, a user may ask about weather data (e.g., temperature data, cloud data, precipitation data, forecast data, etc.), location data (e.g., “where am I?” or “how do I get from here to the nearest printer/exit/bathroom/etc.”), access data (e.g., “am I allowed to control the tint level of the windows in this room?”), etc. A user may also ask for an explanation of why the optically switchable device is performing in a certain way. In one example, a user might ask, “why is window 1 tinting?” and the system may explain in response to the query, “clouds expected to clear in 20 minutes, tinting in anticipation of bright sun.” This feature is particularly useful in cases where the optically switchable device is programmed to execute rules that might not be immediately observable/understandable to a user. The answer may be provided visually (e.g., on a screen) or aurally (e.g., through a speaker).

(26) Voice command may also be used to control the degree of privacy in the room with respect to wireless communications. In some embodiments, optically switchable windows may be patterned to include one or more antenna that may be used to block or allow particular wavelengths to pass through the windows. When activated, these patterned antennae can provide increased security/privacy by blocking cell phone communications, Wi-Fi communications, etc. Patterned antennae and related privacy considerations are discussed in P.C.T. Application No. PCT/US15/62387, filed Nov. 24, 2015, and titled WINDOW ANTENNAS, which is herein incorporated by reference in its entirety.

Dictionaries

(27) Where voice and/or gesture control are used, one or more dictionaries may be defined. For voice control, the dictionaries may define a set of words and/or phrases that the system is configured to interpret/understand. Similarly, for gesture control, the dictionaries may define a set of gestures that the system is configured to interpret/understand. Dictionaries may be tiered, e.g., given a command in a first level dictionary, a new dictionary at a second level may be initiated for receiving commands, and once received, yet another level dictionary may be actuated. In this way, individual dictionaries need not be overly complex and the end user can quickly get to the command structure they desire.

(28) Examples of words or phrases that may be defined include names/identifications for each optically switchable device or group of devices (e.g., “window 1,” “group 1,” “zone 1,” etc.). Such names/identifications may also be based on the location of the optically switchable devices. In this respect, the dictionaries may be defined to include words that identify optically switchable devices based on location (e.g., “first floor,” or “break room,” or “east-facing”), and/or words that provide a relation between the user (or some other person) and the optically switchable device being identified (e.g., “my office,” “the left window,” or “Deepa’s room”).

(29) The dictionaries may also define words related to the desired commands that can be instructed. For instance, the dictionaries may include words like “tint,” “clear,” “clearest,” “darker,” “darkest,” “lighter,” “lightest,” “more,” “less,” “very,” “a little,” “tint level,” “tint1,” “tint2,” etc. Any words likely to be used by a person when instructing the optically switchable device when using verbal commands can be included in the dictionary. In cases where the system is configured to allow a user to set a schedule or rules for the behavior of the optically switchable device, the dictionary or dictionaries can include any words needed to understand such commands (e.g., “Monday,” “Tuesday through Friday,” “morning,” “afternoon,” “bedtime,” “sunrise,” “if,” “then,” “when,”

“don't,” “cloudy,” “sunny,” “degreases,” “someone,” “no one,” “movement,” “only,” etc.). Similarly, in cases where the system is configured to allow a user to ask a question, the dictionary or dictionaries can include any words needed to understand the types of questions the system is designed to answer.

(30) As mentioned above, there is some tradeoff between larger dictionaries, which may enable finer control, more natural/flexible commands, and more complex functions (e.g., answering any question where the answer is available on the internet), compared to smaller dictionaries, which may be easier for people to master, and which may enable faster and/or more local processing. Smaller dictionaries may be used in a tiered format, where access to successive dictionaries is afforded by a user providing the proper voice or gesture command in one dictionary in order to be allowed access to the next dictionary.

(31) In some embodiments, a single dictionary may be used. In other cases, two or more dictionaries may be used, and the dictionary that is used at a particular time depends on what type of command, or what portion of a command a user is trying to convey. For instance, a first dictionary may be used when a user is identifying which optically switchable device they wish to control, and a second dictionary may be used when the user is identifying what they want the optically switchable device to do. The first dictionary could include any words needed to identify the relevant optically switchable device, while the second dictionary could include any words needed to interpret what the user wants the optically switchable device to do. Such contextual dictionaries can provide a limited sub-set of words that the system is configured to understand/interpret whenever the particular dictionary is being used. This may make it easier to interpret a user's commands. Further examples are provided below.

(32) In certain implementations, one or more dictionaries may be tailored to particular users. The dictionaries for defining/determining which electrochromic window(s) a user desires to switch may be limited based on which windows the user is authorized to switch, for instance. In one example, user A is allowed to switch windows 1-5, while user B is allowed to switch windows 6-10. The dictionary or dictionaries used to transcribe and/or interpret commands from user A may be limited to identifying windows 1-5, while the dictionary or dictionaries used to transcribe and/or interpret commands from user B may be limited to identifying windows 6-10.

(33) Each dictionary may include certain keywords that allow the user to navigate through the system more easily. Such keywords may include phrases such as “help,” “back,” “go back,” “previous,” “undo,” “skip,” “restart,” “start over,” “stop,” “abort,” etc. When a user requests help, the system may be configured to communicate to the user (e.g., visually and/or aurally) the words, phrases, commands, windows, etc. that the system is currently configured to accept/understand based on the dictionary that is being used at a given time. For instance, if a user requests help while the system is accessing a dictionary that defines the different windows available for switching, the system may communicate that the available inputs at that time are, e.g., “window 1,” “window 2,” “window 3,” “group 1,” etc.

(34) Security/Authorization

(35) In a number of embodiments, the system may act to ensure that a user is authorized to make a particular command before the command is executed. This can prevent unauthorized users from making changes to the optically switchable devices. One setting in which this is particularly valuable is conference rooms, where there may be many people present at once. In such cases, it may be desirable to ensure that people who do not have authority to change the optical state of the optically switchable devices are prevented from doing so. This can reduce the risk that the optically switchable devices will change based on overheard (typically non-relevant) comments made by those in the room. Another setting in which this feature is valuable is commercial office space, where it is desired that individual people can each control a limited number of optically switchable devices near their work spaces, for instance. In one example, each person may be authorized to control the optically switchable windows in their particular office, or on their particular floor, etc.

In any case, it may be beneficial to ensure that the only people who are able to initiate optical transitions via voice or gesture command are authorized to do so.

(36) The authorization may be done in a number of ways. In one example, a user may “log in” to the system to identify herself. This may be done by logging into an application on an electronic device (e.g., smartphone, tablet, etc.), by keying in or voicing a passcode, etc. In another example, voice recognition may be used to confirm the identity of a user. In a further example, facial recognition, fingerprint scanning, retinal scanning, or other biometric-based methods may be used to confirm the identity of a user. Different authorization procedures may be best suited for different applications/contexts. In a particular example, a user may be automatically authorized. Such authorization may be based on a physical authorization token (e.g., an RFID badge, a BLE beacon, UWB beacon, etc. having appropriate identification information), and the proximity of the physical authorization token to a sensor that reads the token. The sensor may be provided on an optically switchable device, on a controller in communication with the optically switchable device, on a wall unit in communication with the optically switchable device, etc. The verification may occur locally (e.g., on the sensor that reads the token, on an optically switchable device, on a controller, on a wall unit, etc.) or in the cloud.

(37) In some cases, authorization may occur whenever it is needed, and authorization may expire after a set amount of time has passed, or after the user has been idle for a set amount of time (e.g., after 24 hours, or after 1 hour, or after 10 minutes). The time period used for auto-logging out may depend on the setting in which the windows are installed (e.g., whether the windows are in a public area or a private area). In some cases, authorization may not expire until a user logs out (e.g., using any available method including, but not limited to, orally requesting a logout, pressing a logout button, etc.). In certain embodiments, authorization may occur each time a command is made. In some such embodiments, authorization may occur in stages even when interpreting a single command. In a first authorization stage, it may be determined whether the user has authorization to make any changes on the network, and in a second authorization stage, it may be determined whether the user has authorization to make the particular change that the user has requested/initiated.

(38) The authorization process may also be used to further limit the dictionaries used to interpret the voice and/or gesture commands. For example, the dictionary or dictionaries for a particular user may exclude optically switchable devices (or groups/zones of such devices) that the user is not authorized to control. In one example, a user is only authorized to control the optically switchable devices in zone1 and zone 2, so the dictionary or dictionaries used to interpret commands for this user may include “zone 1” and “zone 2” while excluding “zone 3.” Any other words needed to interpret/understand the command may also be included in the dictionary.

(39) Example Voice/Gesture Control Techniques

(40) FIG. 1 provides a block diagram of a voice/gesture control system **900**, which includes several modules that may be used when practicing the disclosed voice control embodiments. These modules may be implemented separately or together, as appropriate for a particular application. The modules may be provided in separate pieces of hardware, and may control a variety of processors. The modules may be executed concurrently or non-concurrently. Generally speaking, each module may be independently implemented on a controller (e.g., the window controller, the network controller, and/or the master controller), an optically switchable device, a wall device, a router, and/or a remote processor. In certain implementations, one or more of the modules may be implemented on processor **402** of FIG. 7, processor **502** of FIG. 8, and/or a processing unit of a window controller. Within each module, any relevant processing may be done locally or remotely, as discussed further below. The processing may be done in a central location/device, or it may be distributed throughout a number of locations/devices.

(41) The voice recognition module **902** converts/transcribes speech to text. In other words, the input to this module is typically speech (spoken by a user and captured/recorded by a microphone),

and the output from this module is typically a text string or file. This module may be implemented using a number of commercially available speech to text products/services/libraries. As one example, Carnegie Mellon University of Pittsburgh, PA provides a number of open source speech software resources that may be used such as CMU Sphinx. Additional examples include various Dragon products available from Nuance Communications, Inc. in Burlington, MA, and Tazti, available from Voice Tech Group, Inc. of Cincinnati, OH. The voice recognition module **902** may also be implemented using custom software designed specifically for voice control related to optically switchable devices.

(42) The command processing module **904** interprets text in order to determine the desired command instruction. In other words, the input to this module is typically a text file (which may be generated by the voice recognition module **902**), while the output is a set of commands/instructions that can be interpreted by the window controller (or another controller on the network) to cause the relevant optically switchable device to initiate the desired command. This function may also be referred to as language processing or natural language processing. Similar to the speech recognition module **902**, the command processing module **904** may be implemented using a number of available products/services, or using software specifically developed for the particular application.

(43) The authentication module **906** may be used to practice the authorization/security techniques discussed herein. Generally, the authorization module **906** may be used to ensure that the person giving the command is authorized to make the command. The module may compare the optically switchable device identified in the command to a list of optically switchable devices that the user is authorized to control. In cases where a user tries to control an optically switchable device that they are not authorized to control, the authentication module **906** may be configured to notify the user (e.g., visually and/or aurally) that they are not authorized to control the relevant optically switchable device. In other cases, no action is taken when an un-authorized command is given (e.g., no notification to the user, and no switching of the optically switchable device).

(44) The command execution module **908** executes the commands on the relevant optically switchable device(s). The command may be executed on a master controller, network controller(s), and/or window controller(s). In one example, the command may be executed by instructing the master controller to send all windows in a particular group or zone to a desired tint level. Generally, the command may be executed on/by any of the control apparatus/methods described herein.

(45) The response generation module **910** generates a response that will be communicated to the user by the response communication module **912**. The response generated by the response generation module **910** may be a text response. The text response may be displayed to the user, e.g., on a screen, using the response communication module **912**. Alternatively or in addition, the response communication module **912** may convert the text response into a speech response (e.g., in a sound file) that is played to the user. Any appropriate text-to-speech methods may be used to accomplish this. Generally, the response generation module **910** and the response communication module **912** may work together to generate and communicate a response to the user.

(46) One purpose of the response generation module **910** and the response communication module **912** may be to notify the user what command has been understood by the control system. Similarly, these modules can be used to notify the user regarding any action that the optically switchable device is taking in response to the user's command. In one example, the response generation module **910** may generate a response that repeats the basic command given by the user (e.g., "window 1 to tint 4" or "tint window 1 to tint 4 when it becomes sunny"). The response may then be communicated to the user via the response communication module **912**. The response generation module **910** and response communication module **912** may also be used to ask for clarification from the user. For instance, if it is unclear whether the user wants to change window 1 or window 2, the response generation module **910** may be used to prompt the user for clarification/further information.

(47) FIG. 2A illustrates a flowchart for a method **1000** of controlling one or more optically

switchable devices (e.g., electrochromic windows) using voice control. The method **1000** begins at operation **1001**, when a user provides a voice command. The voice command may be given in a variety of ways depending on the configuration of the voice control system and the robustness of the voice control processing, for instance. The voice control system includes at least one microphone configured and positioned to receive voice commands. The microphone may be located on an optically switchable device, on a wall device (as discussed above, a wall device may be positioned on a wall or at another location in a room such as a table, countertop, etc.), or on another electronic device such as a smartphone, tablet, laptop, PC, etc. One example command includes “turn window 1 to tint 4.”

(48) Next, at operation **1003** it is determined whether listening mode is on. When listening mode is on, the microphone is able to listen for/record voice commands from a user. When listening mode is off, the microphone is off or otherwise not accepting voice commands related to the optically switchable devices. One example where the microphone can remain “on” while listening mode is “off” is when the microphone is located in a user's cell phone and the user is making an unrelated call on their cell phone. The determination in operation **1003** may be made passively. If listening mode is not on, the microphone will not pick up/record the voice command that was made in operation **1001**, and nothing will happen, as indicated at operation **1004**. As described above, in certain embodiments a user may optionally activate listening mode manually, as indicated at operation **1002**. Where this is the case, the method may continue at operation **1001** where the user repeats the command. If listening mode is on at operation **1003**, the method continues with operation **1005**, where the voice command is converted/transcribed into a text command. The voice-to-text conversion may be done by the voice recognition module **902** from FIG. **1**.

(49) In certain implementations, the voice-to-text conversion may be influenced by one or more dictionaries as described above. For example, words or phrases that sound similar to words or phrases stored in the relevant dictionary may be converted to the words/phrases stored in the dictionary, even if not exactly the same. In a particular example, a user gives the command to “switch window 1 to tint 4,” but the voice recognition module initially interprets the command as “switch window 1 to tint floor.” If the relevant dictionary or dictionaries associated with the voice recognition module defines phrases such as “window 1,” “window 2,” “tint 1,” “tint 2,” “tint 3,” and “tint 4,” but does not include any phrases with the word “floor,” the voice recognition module may recognize that the user likely said “tint 4” rather than the initially understood “tint floor,” which has no relevant meaning in the associated dictionary or dictionaries. In other words, the results of the text-to-speech operation may be limited or otherwise influenced by the relevant dictionaries being used.

(50) Next, at operation **1007**, the text command is interpreted. This interpretation may be done by the command processing module **904** of FIG. **1**. Like the voice-to-text conversion discussed in relation to operation **1005**, the interpretation of the text command in operation **1007** may be influenced by the dictionary or dictionaries being used. This operation may involve specifically identifying which optically switchable device or devices the user is requesting to change, and identifying the particular requested change. For instance, if the command provided by the user is “switch window 1 to tint 4,” the interpretation may involve determining (1) that the user is requesting a change for window 1, and (2) that the requested change relates to switching the window to tint state 4.

(51) The text command interpretation at operation **1007** (as well as the voice-to-text conversion at operation **1005**) may be influenced by user preferences and/or user permissions. For instance, if a user makes a voice command to “make the windows darker,” the system may interpret which windows are desired to be switched based on which windows the user typically switches and/or based on which windows the user is allowed to switch.

(52) At operation **1009**, it is determined whether the user is authorized to make the requested command. The authorization may be initiated/verified in a number of ways as described above. The

authorization may be done by the authentication module **906** described in FIG. **1**. If the user is not authorized to make the requested command, the method ends at operation **1010** where either (1) nothing happens, or (2) a response is generated to notify the user that they are unauthorized to make the command. The response may be provided visually (e.g., through a visual display on an optically switchable window, a wall device, or other electronic device) and/or aurally (e.g., by playing a sound file via speakers on an optically switchable device, wall device, or other electronic device). Further details related to response generation are provided below.

(53) If the user is authorized to make the requested command, the method continues at operation **1011**, where the text command is executed. The command may be executed using any of the methods and systems described herein. The command may be executed using the command execution module **908** of FIG. **1**. In various cases, the command may be executed over a network on which the optically switchable device is installed, and may involve one or more window controllers, network controllers, and/or master controllers. Generally speaking, operation **1011** involves carrying out the command requested by the user in operation **1001**.

(54) At operation **1013**, a response to the user is generated. The response may be generated by the response generation module **910** of FIG. **1**. The response may confirm that the requested command is taking place. The response may specifically indicate the content of the command such that the user knows whether she was understood correctly. One example response may be “switching window 1 to tint 4.” A simpler positive response such as “ok,” or a green light and/or a tone may let the user know she was heard, without specifically repeating the content of the command (e.g., using the response generation module **910** and/or the response communication module **912**). In a particular example, the response may include a request that the user confirm that the system has correctly understood the desired command. In such a case, the command may not be executed until such confirmation is received from the user.

(55) At operation **1015**, the response is communicated to the user. The response may be communicated to the user by the response communication module **912** of FIG. **1**. The response may be presented to the user visually (e.g., on a display) and/or aurally (e.g., via speakers). The display and/or speakers may be provided on an optically switchable device, a wall device, or other electronic device (e.g., smartphone, tablet, laptop, PC, etc.). The display and/or speakers may be provided in the same unit as the microphone, or they may be provided in separate units. In certain cases where an aural response is provided, the response generation may involve generating the desired text of the response (e.g., using the response generation module **910**), and then generating and playing a sound file that corresponds to the desired text (e.g., using response communication module **912**). The method **1000** may be practiced in a variety of ways. In some embodiments, certain operations occur out-of-order from what is shown in FIG. **2A**.

(56) In certain implementations, the voice control method may involve using two or more dictionaries, as described above. FIG. **2B** illustrates a flowchart for a method **1020** of controlling one or more optically switchable devices using two or more voice-control-related dictionaries. The method **1020** of FIG. **2B** is similar to the method **1000** of FIG. **2A**, except that the command is interpreted in a piecemeal fashion, with different dictionaries applying to different portions of the command. Many of the operations illustrated in FIG. **2B** are the same as those presented in FIG. **2A**, and for the sake of brevity the description will not be repeated.

(57) For method **1020**, after it is determined that the listening mode is on in operation **1003**, part 1 of the voice command is converted to part 1 of the text command using a first dictionary. The particular dictionary that is used may correspond to the part of the text that is being interpreted. Next, it is determined whether there are additional parts of the voice command to interpret/convert to text. If there are additional parts of the voice command to interpret, the method continues at operation **1027**, where the dictionary is optionally switched to another dictionary. The next dictionary that is chosen may correspond to the next part of the command that is to be interpreted. The method then continues back at operation **1025**, where part 2 of the voice command is

converted to part 2 of the text command, optionally using a different dictionary than was used in connection with part 1 of the command. The loop of operations **1025/1026/1027** continues until all of the parts of the command have been converted to text using the appropriate dictionaries.

(58) In one example, the full voice command is “switch window 1 to tint 4.” One part of the voice command (e.g., part 1) may relate to identifying which optically switchable devices the user desires to switch, in this case “window 1.” Another part of the voice command (e.g., part 2) may relate to identifying what the desired command/ending optical state is, in this case switching to “tint 4.” The different parts of the command may be structured as desired for a particular system. More structured commands may be easier to process/interpret, which may make local processing a more attractive option. Less structured commands may be harder to process/interpret, which may make remote processing a more attractive option.

(59) After all parts of the voice command have been converted to text, the different parts of the text command are joined together to define the full text command, and the method continues at operation **1007**. The remaining portions of the method are the same as those described in relation to FIG. 2A.

(60) In a similar embodiment, the text command interpretation may be done in a piecemeal fashion (rather than the voice command to text command conversion being done in a piecemeal fashion). With reference to FIG. 2A, the text command interpretation in operation **1007** may be done iteratively as described in relation to operations **1025/1026/1027** of FIG. 2B, optionally with different dictionaries applied to different parts of the text command.

(61) In another similar embodiment, both the voice command to text command conversion in operation **1005** and the text command interpretation in operation **1007** may be done in a piecemeal fashion as described in relation to operations **1025/1026/1027** of FIG. 2B.

(62) Furthermore, the authentication described in relation to operation **1009** may be determined in piecemeal fashion. For instance, a first authentication check may determine whether the user is allowed to make any changes. A second authentication check may determine whether the user is allowed to switch the particular optically switchable device(s) that she is requesting to switch. A third authentication check may determine whether the user is allowed to make the particular change that was requested (e.g., to prevent the user from requesting a tint state that will damage the device, or to check whether there are any overriding rules governing the tint states of the optically switchable device(s) that would prevent the requested change from taking effect, even if the user is allowed some control over the relevant optically switchable device(s)). The authentications may all be done at the same time, or at different times. Depending upon a particular user's access authority, different dictionaries may be used for that user, versus other users.

(63) FIG. 2C depicts a flowchart similar to the one shown in FIG. 2A, in the context of a specific example where a user in an office building requests the control system to switch the windows in the user's office to a particular tint state. The method **1030** begins at operation **1031**, where the user requests, by voice, to “switch my windows to tint 4.” If listening mode is not on, the system will take no action in response to the user's request, as indicated at operation **1034**. In some cases, the user may optionally activate listening mode manually, as indicated in operation **1032**. Where this is the case, the method may continue with operation **1031** where the user repeats the command. When listening mode is on at operation **1033**, the method continues at operation **1035** where the voice command is converted to a text command. As mentioned above, this may be performed by the voice recognition module **902** of FIG. 1. At this point, the control system may have an audio recording of the voice command given by the user, as well as a text file that indicates the content of the voice command.

(64) Next, at operation **1037**, the text command is interpreted. This may be done by the command processing module **904** from FIG. 1. This operation may involve identifying which windows are to be changed. In this example, the user requested to change “my windows.” The control system may identify which windows to change by analyzing who is giving the command, which windows that

user is authorized to change, which windows that user frequently changes, which windows are associated with the user in a database, which windows the user is near when she makes the command, etc. Identification of the user may be done in a number of ways as described above with respect to authorization. In this particular example, the control system uses voice recognition to identify the user, and identifies which windows to change by utilizing a database that associates each employee with the windows that are in each employee's office. At the end of operation **1037**, the control system has identified that the user wishes to switch all the windows in the user's office to tint 4.

(65) At operation **1039**, it is determined whether the user is authorized to make the command. This may be done by the authentication module **906** of FIG. **1**. In this case, the authorization process involves voice recognition. The system may analyze the recorded voice command given by the user in operation **1031** and compare it against prior recordings from this user and other users. This process allows the system to identify who made the command in operation **1031**. The authorization process may also involve ensuring that the identified user is allowed to change the windows that she has requested to change. In this example, the control system checks whether the user is authorized to change the windows in her office by utilizing a database that associates each user with each window that the user is authorized to change. The user in this example works on floor **10**, and is authorized to switch all the windows on floor **10**. Therefore, the method continues with operation **1041**, where the command is executed (e.g., via the command execution module **908** of FIG. **1**), and all the windows in the user's office begin to switch to tint 4. In a case where the user makes an unauthorized command (e.g., the user is visiting a colleague on floor 9 and requests that the windows in the colleague's office go to tint 4, when the user is only authorized to switch windows on floor **10**, where the user's office is located), the method may continue with operation **1040**, where either nothing happens or the command system indicates that the user is not authorized to make the requested command. The system may or may not explain why the user is unauthorized to make the requested command, and/or may explain which windows, if any, the user is authorized to change.

(66) At operation **1043**, the control system generates a response indicating that “the windows in your office are darkening to tint 4.” This may be done by the response generation module **910** of FIG. **1**. The response may indicate which windows are going to be affected, as well as the particular action they will take (e.g., darkening, lightening, the final requested tint state, etc.). In this example, operation **1043** involves generating a text file indicating what the response will be. Next, at operation **1045**, the response is communicated to the user. This may be done by the response communication module **912** of FIG. **1**. The response may be communicated visually or aurally in various cases. In one example, this operation may involve generating a sound file that corresponds to the response in the text file for the response. The sound file may then be played to the user so that she knows her command has been heard, and that the system is acting on her request. Alternatively or in addition, the text file (or another file generated based on the text file) may be displayed to the user so that she can visually appreciate that her command has been heard.

(67) In cases where gesture command is used in place of voice command, a camera may be used instead of (or in addition to) a microphone in order to perceive and record the user's command. Instead of a voice recognition module such as module **902** of FIG. **1**, a gesture recognition module may be used.

(68) Arrangement of Components and Division of Processing Steps

(69) FIG. **3A** illustrates a user interacting with a device **1105** for controlling the optical state of electrochromic windows **1100a-1100d**. In this example, the device **1105** is a wall device as described above. In one example, the wall device is or includes a smart device such as an electronic tablet or similar device. Device **1105** may be any number of different electronic devices configured to control the electrochromic windows **1100a-1100d**, including but not limited to a smartphone, tablet, laptop, PC, etc. The device **1105** may run an application/program that is configured to

control the electrochromic windows. In certain embodiments, the device **1105** may communicate with access point **1110**, for example through a wired connection or a wireless connection (e.g., WiFi, Bluetooth, Bluetooth low energy, ZigBee, WiMax, etc.). The access point **1110** may be a networking hardware device that allows a Wi-Fi compliant device to connect to a wired network. The device **1105** may communicate with a controller (e.g., a window controller, network controller, and/or master controller) through a number of different connection schemes, some of which are illustrated in FIGS. 3B-3E.

(70) In FIG. 3B, the device **1105** is connected to access point **1110**, which is connected to switch **1115**. Switch **1115** is connected to both router **1120** and controller **1125**. The connections between the different elements may be wired or wireless, as appropriate for a particular application. In one example, access point **1110** is a wireless access point, and the connection between the access point **1110** and the device **1105** is wireless. As mentioned, the device **1105** may be any number of electronic devices configured to control the electrochromic windows. The router **1120** may include firewall protection to enhance security. The controller **1125** may be a window controller, network controller, or master controller. If the controller **1125** is not a window controller, the controller **1125** may relay instructions to relevant window controllers over the network, for example as described in relation to FIG. 6.

(71) In FIG. 3C, the device **1105** is connected to access point **1110**, which is connected to controller **1125**. Each of these connections may be wired or wireless. In FIG. 3D, the device **1105** is directly connected to the controller **1125**. This connection may be wired or wireless. In FIG. 3E, device **1105** is connected to the cloud **1130** (e.g., the Internet). The cloud **1130** is also connected with router **1120**, which is connected to switch **1115**, which is connected to controller **1125**. The connections may be wired or wireless, as appropriate for a particular application. In a particular example, the device **1105** is a smartphone, which connects wirelessly (e.g., via 3G, 4G, etc.) with the cloud **1130**.

(72) FIGS. 3B-3E show some of the possible arrangements for allowing a device **1105** to communicate with a controller **1125** to cause the controller **1125** to effect change on the relevant electrochromic windows. Certain arrangements may be preferable for certain situations. For example, different arrangements may be preferred depending on the intensity of the different processing steps, any hardware limitations for different components, a desired level of privacy, and other concerns. For example, if the device **1105** and controller **1125** (as well as related components on the network) have limited processing power, it may be desirable to perform much of the processing in the cloud **1130**, and the arrangement in FIG. 3E may be particularly beneficial. By contrast, if privacy is a top concern and it is desired to perform everything in-house (e.g., within a firewalled network), the arrangements in FIGS. 3B-3D (especially 3D where the device **1105** directly connects to the controller **1125**) may be relatively more beneficial. Relatedly, the arrangements shown in FIGS. 3B-3D may be particularly useful in cases where no external internet connection is available.

(73) Generally, the different processing steps may each independently occur on any device with sufficient processing power and connectivity to perform the relevant processing step. For example, one or more processors may be provided on each window controller, network controller, master controller, wall device (or related electronic device), and/or at a remote processing location (on the cloud, at a remote processing location maintained by a manufacturer/vendor/customer, etc.). In various cases the processors may be distributed among different components. In some other cases, the processors may be more centrally located (e.g., all within a wall device, or window controller, or network controller, or master controller). A few examples will be provided.

(74) In one example, device **1105** is connected with controller **1125** as shown in any of FIGS. 3B-3D. The device **1105** is provided with a relatively high degree of processing capability in this example. Device **1105** accepts voice commands regarding one or more electrochromic windows associated with controller **1125**. For the purposes of this example, controller **1125** is a master

controller, though in other examples it may be a network controller or window controller. With respect to the method **1000** shown in FIG. 2A, operation **1001** (user gives voice command) may occur at the device **1105**. The device **1105** may record the voice command for analysis. Operation **1003** (determining if listening mode is on) similarly occurs at the device **1105**, though this determination may be made passively. Operation **1005** (voice command converted to text command) may also happen on the device **1105**, assuming the device **1105** is provided with sufficient processing capability. Similarly, operation **1007** (text command interpreted) may happen on the device **1105** if the device **1105** has sufficient processing capability. Operation **1009** (authorization) may occur on the controller **1125**, which may store or otherwise access information related to different users and the permissions related to each user. Operation **1011** (text command executed) may also occur on controller **1125** (as well as related controllers and associated electrochromic windows), which causes the relevant electrochromic windows to change as directed in operation **1001**. Operation **1013** (response to user generated) may occur on the device **1105** assuming the device **1105** has sufficient processing power. Operation **1015** (response communicated to user) may occur at the device **1105** such that the user can perceive the response (e.g., visually or aurally).

(75) In a related example, the device **1105** may have relatively less processing capability. Therefore, some of the processing steps may be moved from the device **1105** to the controller **1125**. In this case, the controller **1125** may be any controller (e.g., master controller, network controller, window controller, or a combination thereof) that has sufficient processing capability. Examples of functions that may remain at the device **1105** include operation **1001** (user gives voice command), and operation **1015** (response communicated to user). Examples of functions that may be switched to the controller **1125** include operation **1005** (voice command converted to text command), operation **1007** (text command interpreted), and operation **1013** (response to user generated) may be performed on the controller **1125**. For instance, the content of the response to the user may be generated at the controller **1125**, and the response may then be displayed and/or played to the user at the device **1105**.

(76) In another example, the device **1105** communicates with the controller **1125** via the cloud **1130**, as shown in FIG. 3E. The processing capabilities of the cloud **1130** are essentially unlimited. As such, various processing steps may be performed in the cloud **1130**. With reference to the method **1000** of FIG. 2A, examples of processing steps that may be performed in the cloud **1130** include operation **1005** (voice command converted to text command), operation **1007** (text command interpreted), operation **1009** (authorization), and operation **1013** (response to user generated). One or more of these functions may also be performed at the controller **1125**. In a particular example, operation **1001** (user gives voice command) occurs at the device **1105**, operation **1003** (determining whether listening mode is on) occurs at the device **1105**, operation **1005** (voice command converted to text command) occurs on the cloud **1130**, operation **1007** (text command interpreted) occurs on the cloud **1130**, operation **1009** (authorization) occurs on the controller **1125**, operation **1011** (text command executed) occurs on the controller **1125** and the associated electrochromic windows, operation **1013** (generating response to user) occurs on the controller **1125** and/or cloud **1130** (either or both of which may be used to generate the content of the response), and operation **1015** occurs on the device **1105** (which displays and/or plays the response to the user).

(77) Example Electrochromic Window Architecture

(78) FIG. 4 shows a cross-sectional side view of an example electrochromic window **100** in accordance with some implementations. An electrochromic window is one type of optically switchable window that includes an electrochromic device (ECD) used to provide tinting or coloring. The example electrochromic window **100** can be manufactured, configured or otherwise provided as an insulated glass unit (IGU) and will hereinafter also be referred to as IGU **100**. This convention is generally used, for example, because it is common and because it can be desirable to

have IGUs serve as the fundamental constructs for holding electrochromic panes (also referred to as “lites”) when provided for installation in a building. An IGU lite or pane may be a single substrate or a multi-substrate construct, such as a laminate of two substrates. IGUs, especially those having double- or triple-pane configurations, can provide a number of advantages over single pane configurations; for example, multi-pane configurations can provide enhanced thermal insulation, noise insulation, environmental protection and/or durability when compared with single-pane configurations. A multi-pane configuration also can provide increased protection for an ECD, for example, because the electrochromic films, as well as associated layers and conductive interconnects, can be formed on an interior surface of the multi-pane IGU and be protected by an inert gas fill in the interior volume, **108**, of the IGU.

(79) FIG. **4** more particularly shows an example implementation of an IGU **100** that includes a first pane **104** having a first surface **S1** and a second surface **S2**. In some implementations, the first surface **S1** of the first pane **104** faces an exterior environment, such as an outdoors or outside environment. The IGU **100** also includes a second pane **106** having a first surface **S3** and a second surface **S4**. In some implementations, the second surface **S4** of the second pane **106** faces an interior environment, such as an inside environment of a home, building or vehicle, or a room or compartment within a home, building or vehicle.

(80) In some implementations, each of the first and the second panes **104** and **106** are transparent or translucent—at least to light in the visible spectrum. For example, each of the panes **104** and **106** can be formed of a glass material and especially an architectural glass or other shatter-resistant glass material such as, for example, a silicon oxide (SiO₂)-based glass material. As a more specific example, each of the first and the second panes **104** and **106** can be a soda-lime glass substrate or float glass substrate. Such glass substrates can be composed of, for example, approximately 75% silica (SiO₂) as well as Na₂O, CaO, and several minor additives. However, each of the first and the second panes **104** and **106** can be formed of any material having suitable optical, electrical, thermal, and mechanical properties. For example, other suitable substrates that can be used as one or both of the first and the second panes **104** and **106** can include other glass materials as well as plastic, semi-plastic and thermoplastic materials (for example, poly(methyl methacrylate), polystyrene, polycarbonate, allyl diglycol carbonate, SAN (styrene acrylonitrile copolymer), poly(4-methyl-1-pentene), polyester, polyamide), or mirror materials. In some implementations, each of the first and the second panes **104** and **106** can be strengthened, for example, by tempering, heating, or chemically strengthening.

(81) Generally, each of the first and the second panes **104** and **106**, as well as the IGU **100** as a whole, is rectangular. However, in some other implementations other shapes are possible and may be desired (for example, circular, elliptical, triangular, curvilinear, convex or concave shapes). In some specific implementations, a length “L” of each of the first and the second panes **104** and **106** can be in the range of approximately 20 inches (in.) to approximately 10 feet (ft.), a width “W” of each of the first and the second panes **104** and **106** can be in the range of approximately 20 in. to approximately 10 ft., and a thickness “T” of each of the first and the second panes **104** and **106** can be in the range of approximately 0.3 millimeter (mm) to approximately 10 mm (although other lengths, widths or thicknesses, both smaller and larger, are possible and may be desirable based on the needs of a particular user, manager, administrator, builder, architect or owner). In examples where thickness T of substrate **104** is less than 3 mm, typically the substrate is laminated to an additional substrate which is thicker and thus protects the thin substrate **104**. Additionally, while the IGU **100** includes two panes (**104** and **106**), in some other implementations, an IGU can include three or more panes. Furthermore, in some implementations, one or more of the panes can itself be a laminate structure of two, three, or more layers or sub-panes.

(82) The first and second panes **104** and **106** are spaced apart from one another by a spacer **118**, which is typically a frame structure, to form an interior volume **108**. In some implementations, the interior volume is filled with Argon (Ar), although in some other implementations, the interior

volume **108** can be filled with another gas, such as another noble gas (for example, krypton (Kr) or xenon (Xn)), another (non-noble) gas, or a mixture of gases (for example, air). Filling the interior volume **108** with a gas such as Ar, Kr, or Xn can reduce conductive heat transfer through the IGU **100** because of the low thermal conductivity of these gases as well as improve acoustic insulation due to their increased atomic weights. In some other implementations, the interior volume **108** can be evacuated of air or other gas. Spacer **118** generally determines the height “C” of the interior volume **108**; that is, the spacing between the first and the second panes **104** and **106**. In FIG. 4, the thickness of the ECD, sealant **120/122** and bus bars **126/128** is not to scale; these components are generally very thin but are exaggerated here for ease of illustration only. In some implementations, the spacing “C” between the first and the second panes **104** and **106** is in the range of approximately 6 mm to approximately 30 mm. The width “D” of spacer **118** can be in the range of approximately 5 mm to approximately 15 mm (although other widths are possible and may be desirable).

(83) Although not shown in the cross-sectional view, spacer **118** is generally a frame structure formed around all sides of the IGU **100** (for example, top, bottom, left and right sides of the IGU **100**). For example, spacer **118** can be formed of a foam or plastic material. However, in some other implementations, spacers can be formed of metal or other conductive material, for example, a metal tube or channel structure having at least 3 sides, two sides for sealing to each of the substrates and one side to support and separate the lites and as a surface on which to apply a sealant, **124**. A first primary seal **120** adheres and hermetically seals spacer **118** and the second surface S2 of the first pane **104**. A second primary seal **122** adheres and hermetically seals spacer **118** and the first surface S3 of the second pane **106**. In some implementations, each of the primary seals **120** and **122** can be formed of an adhesive sealant such as, for example, polyisobutylene (PIB). In some implementations, IGU **100** further includes secondary seal **124** that hermetically seals a border around the entire IGU **100** outside of spacer **118**. To this end, spacer **118** can be inset from the edges of the first and the second panes **104** and **106** by a distance “E.” The distance “E” can be in the range of approximately 4 mm to approximately 8 mm (although other distances are possible and may be desirable). In some implementations, secondary seal **124** can be formed of an adhesive sealant such as, for example, a polymeric material that resists water and that adds structural support to the assembly, such as silicone, polyurethane and similar structural sealants that form a water tight seal.

(84) In the particular configuration and form factor depicted in FIG. 4, the ECD coating on surface S2 of substrate **104** extends about its entire perimeter to and under spacer **118**. This configuration is functionally desirable as it protects the edge of the ECD within the primary sealant **120** and aesthetically desirable because within the inner perimeter of spacer **118** there is a monolithic ECD without any bus bars or scribe lines. Such configurations are described in more detail in U.S. Pat. No. 8,164,818, issued Apr. 24, 2012 and titled ELECTROCHROMIC WINDOW FABRICATION METHODS, U.S. patent application Ser. No. 13/456,056 filed Apr. 25, 2012 and titled ELECTROCHROMIC WINDOW FABRICATION METHODS, PCT Patent Application No. PCT/US2012/068817 filed Dec. 10, 2012 and titled THIN-FILM DEVICES AND FABRICATION, U.S. Pat. No. 9,454,053, issued Sep. 27, 2016 and titled THIN-FILM DEVICES AND FABRICATION, and PCT Patent Application No. PCT/US2014/073081, filed Dec. 13, 2014 and titled THIN-FILM DEVICES AND FABRICATION, all of which are hereby incorporated by reference in their entireties and for all purposes.

(85) In the implementation shown in FIG. 4, an ECD **110** is formed on the second surface S2 of the first pane **104**. In some other implementations, ECD **110** can be formed on another suitable surface, for example, the first surface S1 of the first pane **104**, the first surface S3 of the second pane **106** or the second surface S4 of the second pane **106**. The ECD **110** includes an electrochromic (“EC”) stack **112**, which itself may include one or more layers. For example, the EC stack **112** can include an electrochromic layer, an ion-conducting layer, and a counter electrode layer. In some

implementations, the electrochromic layer is formed of one or more inorganic solid materials. The electrochromic layer can include or be formed of one or more of a number of electrochromic materials, including electrochemically-cathodic or electrochemically-anodic materials. For example, metal oxides suitable for use as the electrochromic layer can include tungsten oxide (WO₃) and doped formulations thereof. In some implementations, the electrochromic layer can have a thickness in the range of approximately 0.05 μm to approximately 1 μm .

(86) In some implementations, the counter electrode layer is formed of an inorganic solid material. The counter electrode layer can generally include one or more of a number of materials or material layers that can serve as a reservoir of ions when the EC device **110** is in, for example, the transparent state. In certain implementations, the counter electrode not only serves as an ion storage layer but also colors anodically. For example, suitable materials for the counter electrode layer include nickel oxide (NiO) and nickel tungsten oxide (NiWO), as well as doped forms thereof, such as nickel tungsten tantalum oxide, nickel tungsten tin oxide, nickel vanadium oxide, nickel chromium oxide, nickel aluminum oxide, nickel manganese oxide, nickel magnesium oxide, nickel tantalum oxide, nickel tin oxide as non-limiting examples. In some implementations, the counter electrode layer can have a thickness in the range of approximately 0.05 μm to approximately 1 μm .

(87) The ion-conducting layer serves as a medium through which ions are transported (for example, in the manner of an electrolyte) when the EC stack **112** transitions between optical states. In some implementations, the ion-conducting layer is highly conductive to the relevant ions for the electrochromic and the counter electrode layers, but also has sufficiently low electron conductivity such that negligible electron transfer (electrical shorting) occurs during normal operation. A thin ion-conducting layer with high ionic conductivity enables fast ion conduction and consequently fast switching for high performance EC devices **110**. In some implementations, the ion-conducting layer can have a thickness in the range of approximately 1 nm to approximately 500 nm, more generally in the range of about 5 nm to about 100 nm thick. In some implementations, the ion-conducting layer also is an inorganic solid. For example, the ion-conducting layer can be formed from one or more silicates, silicon oxides (including silicon-aluminum-oxide), tungsten oxides (including lithium tungstate), tantalum oxides, niobium oxides, lithium oxide and borates. These materials also can be doped with different dopants, including lithium; for example, lithium-doped silicon oxides include lithium silicon-aluminum-oxide, lithium phosphorous oxynitride (LiPON) and the like.

(88) In some other implementations, the electrochromic layer and the counter electrode layer are formed immediately adjacent one another, sometimes in direct contact, without an ion-conducting layer in between and then an ion conductor material formed in situ between the electrochromic and counter electrode layers. A further description of suitable devices is found in U.S. Pat. No. 8,764,950, titled ELECTROCHROMIC DEVICES, by Wang et al., issued Jul. 1, 2014 and U.S. Pat. No. 9,261,751, titled ELECTROCHROMIC DEVICES, by Pradhan et al., issued Feb. 16, 2016, each of which is hereby incorporated by reference in its entirety and for all purposes. In some implementations, the EC stack **112** also can include one or more additional layers such as one or more passive layers. For example, passive layers can be used to improve certain optical properties, to provide moisture or to provide scratch resistance. These or other passive layers also can serve to hermetically seal the EC stack **112**. Additionally, various layers, including conducting layers (such as the first and the second TCO layers **114** and **116** described below), can be treated with anti-reflective or protective oxide or nitride layers.

(89) The selection or design of the electrochromic and counter electrode materials generally governs the possible optical transitions. During operation, in response to a voltage generated across the thickness of the EC stack **112** (for example, between the first and the second TCO layers **114** and **116**), the electrochromic layer transfers or exchanges ions to or from the counter electrode layer to drive the electrochromic layer to the desired optical state. In some implementations, to cause the EC stack **112** to transition to a transparent state, a positive voltage is applied across the

EC stack **112** (for example, such that the electrochromic layer is more positive than the counter electrode layer). In some such implementations, in response to the application of the positive voltage, the available ions in the stack reside primarily in the counter electrode layer. When the magnitude of the potential across the EC stack **112** is reduced or when the polarity of the potential is reversed, ions are transported back across the ion conducting layer to the electrochromic layer causing the electrochromic material to transition to an opaque state (or to a “more tinted,” “darker” or “less transparent” state). Conversely, in some other implementations using electrochromic layers having different properties, to cause the EC stack **112** to transition to an opaque state, a negative voltage can be applied to the electrochromic layer relative to the counter electrode layer. In such implementations, when the magnitude of the potential across the EC stack **112** is reduced or its polarity reversed, the ions are transported back across the ion conducting layer to the electrochromic layer causing the electrochromic material to transition to a clear or “bleached” state (or to a “less tinted,” “lighter” or “more transparent” state).

(90) In some implementations, the transfer or exchange of ions to or from the counter electrode layer also results in an optical transition in the counter electrode layer. For example, in some implementations the electrochromic and counter electrode layers are complementary coloring layers. More specifically, in some such implementations, when or after ions are transferred into the counter electrode layer, the counter electrode layer becomes more transparent, and similarly, when or after the ions are transferred out of the electrochromic layer, the electrochromic layer becomes more transparent. Conversely, when the polarity is switched, or the potential is reduced, and the ions are transferred from the counter electrode layer into the electrochromic layer, both the counter electrode layer and the electrochromic layer become less transparent.

(91) In one more specific example, responsive to the application of an appropriate electric potential across a thickness of EC stack **112**, the counter electrode layer transfers all or a portion of the ions it holds to the electrochromic layer causing the optical transition in the electrochromic layer. In some such implementations, for example, when the counter electrode layer is formed from NiWO, the counter electrode layer also optically transitions with the loss of ions it has transferred to the electrochromic layer. When charge is removed from a counter electrode layer made of NiWO (that is, ions are transported from the counter electrode layer to the electrochromic layer), the counter electrode layer will transition in the opposite direction.

(92) Generally, the transition of the electrochromic layer from one optical state to another optical state can be caused by reversible ion insertion into the electrochromic material (for example, by way of intercalation) and a corresponding injection of charge-balancing electrons. In some instances, some fraction of the ions responsible for the optical transition is irreversibly bound up in the electrochromic material. Some or all of the irreversibly bound ions are thought to have been used to compensate for “blind charge” in the material, i.e. sufficient ions are added to compensate for those that will be irreversibly bound, the fraction that are irreversibly bound constitute the blind charge. In some implementations, suitable ions include lithium ions (Li⁺) and hydrogen ions (H⁺) (i.e., protons). In some other implementations, other ions can be suitable. Intercalation of lithium ions, for example, into tungsten oxide (WO_{3-y} (0<y≤0.3)) causes the tungsten oxide to change from a transparent state to a blue state.

(93) The description below generally focuses on tinting transitions. One example of a tinting transition is a transition from a transparent (or “translucent,” “bleached” or “least tinted”) state to an opaque (or “fully darkened” or “fully tinted”) state. Another example of a tinting transition is the reverse—a transition from an opaque state to a transparent state. Other examples of tinting transitions includes transitions to and from various intermediate tint states, for example, a transition from a less tinted, lighter or more transparent state to a more tinted, darker or less transparent state, and vice versa. Each of such tint states, and the tinting transitions between them, may be characterized or described in terms of percent transmission. For example, a tinting transition can be described as being from a current percent transmission (% T) to a target % T. Conversely, in some

other instances, each of the tint states and the tinting transitions between them may be characterized or described in terms of percent tinting; for example, a transition from a current percent tinting to a target percent tinting.

(94) However, although the following description generally focuses on tint states and tinting transitions between tint states, other optical states and optical transitions also are achievable in various implementations. As such, where appropriate and unless otherwise indicated, references to tint states or tinting transitions also are intended to encompass other optical states and optical transitions. In other words, optical states and optical state transitions also will be referred to herein as tint states and tint state transitions, respectively, but this is not intended to limit the optical states and state transitions achievable by the IGUs **302**. For example, such other optical states and state transitions can include states and state transitions associated with various colors, intensities of color (for example, from lighter blue to darker blue and vice versa), reflectivity (for example, from less reflective to more reflective and vice versa), polarization (for example, from less polarization to more polarization and vice versa), and scattering density (for example, from less scattering to more scattering and vice versa), among others. Similarly, references to devices, control algorithms or processes for controlling tint states, including causing tinting transitions and maintaining tint states, also are intended to encompass such other optical transitions and optical states. Additionally, controlling the voltage, current or other electrical characteristics provided to an optically switchable device, and the functions or operations associated with such controlling, also may be described hereinafter as “driving” the device or the respective IGU, whether or not the driving involves a tint state transition or the maintaining of a current tint state.

(95) The ECD **110** generally includes first and second conducting (or “conductive”) layers. For example, the ECD **110** can include a first transparent conductive oxide (TCO) layer **114** adjacent a first surface of the EC stack **112** and a second TCO layer **116** adjacent a second surface of the EC stack **112**. In some implementations, the first TCO layer **114** can be formed on the second surface **S2**, the EC stack **112** can be formed on the first TCO layer **114**, and the second TCO layer **116** can be formed on the EC stack **112**. In some implementations, the first and the second TCO layers **114** and **116** can each be formed of one or more metal oxides including metal oxides doped with one or more metals. For example, some suitable metal oxides and doped metal oxides can include indium oxide, indium tin oxide (ITO), doped indium oxide, tin oxide, doped tin oxide, fluorinated tin oxide, zinc oxide, aluminum zinc oxide, doped zinc oxide, ruthenium oxide and doped ruthenium oxide, among others. While such materials are referred to as TCOs in this document, the term encompasses non-oxides as well as oxides that are transparent and electrically conductive such as certain thin film metals and certain non-metallic materials such as conductive metal nitrides and composite conductors, among other suitable materials. In some implementations, the first and the second TCO layers **114** and **116** are substantially transparent at least in the range of wavelengths where electrochromism is exhibited by the EC stack **112**. In some implementations, the first and the second TCO layers **114** and **116** can each be deposited by physical vapor deposition (PVD) processes including, for example, sputtering. In some implementations, the first and the second TCO layers **114** and **116** can each have a thickness in the range of approximately 0.01 microns (μm) to approximately 1 μm . A transparent conductive material typically has an electronic conductivity significantly greater than that of the electrochromic material or the counter electrode material.

(96) The first and the second TCO layers **114** and **116** serve to distribute electrical charge across respective first and second surfaces of the EC stack **112** to apply an electrical potential (voltage) across the thickness of the EC stack **112**. For example, a first applied voltage can be applied to a first one of the TCO layers and a second applied voltage can be applied to a second one of the TCO layers. In some implementations, a first bus bar **126** distributes the first applied voltage to the first TCO layer **114** and a second bus bar **128** distributes the second applied voltage to the second TCO layer **116**. In some other implementations, one of the first and the second bus bars **126** and **128** can

ground the respective one of the first and the second TCO layers **114** and **116**. In other implementations, the load can be floated with respect to the two TCOs. In various implementations, to modify one or more optical properties of the EC stack **112**, and thus cause an optical transition, a controller can alter one or both of the first and second applied voltages to bring about a change in one or both of the magnitude and the polarity of the effective voltage applied across the EC stack **112**. Desirably, the first and the second TCO layers **114** and **116** serve to uniformly distribute electrical charge over respective surfaces of the EC stack **112** with relatively little Ohmic potential drop from the outer regions of the respective surfaces to the inner regions of the surfaces. As such, it is generally desirable to minimize the sheet resistance of the first and the second TCO layers **114** and **116**. In other words, it is generally desirable that each of the first and the second TCO layers **114** and **116** behaves as a substantially equipotential layer across all portions of the respective layer. In this way, the first and the second TCO layers **114** and **116** can uniformly apply an electric potential across a thickness of the EC stack **112** to effect a uniform optical transition of the EC stack **112**.

(97) In some implementations, each of the first and the second bus bars **126** and **128** is printed, patterned, or otherwise formed such that it is oriented along a length of the first pane **104** along at least one border of the EC stack **112**. For example, each of the first and the second bus bars **126** and **128** can be formed by depositing a conductive ink, such as a silver ink, in the form of a line. In some implementations, each of the first and the second bus bars **126** and **128** extends along the entire length (or nearly the entire length) of the first pane **104**, and in some implementations, along more than one edge of the EC stack **112**.

(98) In some implementations, the first TCO layer **114**, the EC stack **112** and the second TCO layer **116** do not extend to the edges of the first pane **104**. For example, a laser edge delete (LED) or other operation can be used to remove portions of the first TCO layer **114**, the EC stack **112** and the second TCO layer **116** such that these layers are separated or inset from the respective edges of the first pane **104** by a distance “G,” which can be in the range of approximately 8 mm to approximately 10 mm (although other distances are possible and may be desirable). Additionally, in some implementations, an edge portion of the EC stack **112** and the second TCO layer **116** along one side of the first pane **104** is removed to enable the first bus bar **126** to be formed on the first TCO layer **114** to enable conductive coupling between the first bus bar **126** and the first TCO layer **114**. The second bus bar **128** is formed on the second TCO layer **116** to enable conductive coupling between the second bus bar **128** and the second TCO layer **116**. In some implementations, the first and the second bus bars **126** and **128** are formed in a region between spacer **118** and the first pane **104** as shown in FIG. 4. For example, each of the first and the second bus bars **126** and **128** can be inset from an inner edge of spacer **118** by at least a distance “F,” which can be in the range of approximately 2 mm to approximately 3 mm (although other distances are possible and may be desirable). This arrangement can be advantageous for a number of reasons including, for example, to hide the bus bars from view.

(99) As noted above, the usage of the IGU convention is for convenience only. Indeed, in some implementations the basic unit of an electrochromic window can be defined as a pane or substrate of transparent material, upon which an ECD is formed or otherwise arranged, and to which associated electrical connections are coupled (to drive the ECD). As such, references to an IGU in the following description do not necessarily include all of the components described with reference to the IGU **100** of FIG. 4.

(100) Example Control Profile for Driving Optical Transitions

(101) FIG. 5 illustrates an example control profile **200** in accordance with some implementations. The control profile **200** can be used to drive a transition in an optically switchable device, such as the ECD **110** described above. In some implementations, a window controller can be used to generate and apply the control profile **200** to drive an ECD from a first optical state (for example, a transparent state or a first intermediate state) to a second optical state (for example, a fully tinted

state or a more tinted intermediate state). To drive the ECD in the reverse direction—from a more tinted state to a less tinted state—the window controller can apply a similar but inverted profile. For example, the control profile for driving the ECD from the second optical state to the first optical state can be a mirror image of the voltage control profile depicted in FIG. 5. In some other implementations, the control profiles for tinting and lightening can be asymmetric. For example, transitioning from a first more tinted state to a second less tinted state can in some instances require more time than the reverse; that is, transitioning from the second less tinted state to the first more tinted state. In some other instances, the reverse may be true; that is, transitioning from the second less tinted state to the first more tinted state can require more time. In other words, by virtue of the device architecture and materials, bleaching or lightening is not necessarily simply the reverse of coloring or tinting. Indeed, ECDs often behave differently for each transition due to differences in driving forces for ion intercalation and deintercalation to and from the electrochromic materials.

(102) In some implementations, the control profile **200** is a voltage control profile implemented by varying a voltage provided to the ECD. For example, the solid line in FIG. 5 represents an effective voltage $V_{\text{sub.Eff}}$ applied across the ECD over the course of a tinting transition and a subsequent maintenance period. In other words, the solid line can represent the relative difference in the electrical voltages $V_{\text{sub.App1}}$ and $V_{\text{sub.App2}}$ applied to the two conducting layers of the ECD (for example, the first and the second TCO layers **114** and **116** of the ECD **110**). The dotted line in FIG. 5 represents a corresponding current (I) through the device. In the illustrated example, the voltage control profile **200** includes four stages: a ramp-to-drive stage **202** that initiates the transition, a drive stage that continues to drive the transition, a ramp-to-hold stage, and subsequent hold stage.

(103) The ramp-to-drive stage **202** is characterized by the application of a voltage ramp that increases in magnitude from an initial value at time $t_{\text{sub.0}}$ to a maximum driving value of $V_{\text{sub.Drive}}$ at time $t_{\text{sub.1}}$. In some implementations, the ramp-to-drive stage **202** can be defined by three drive parameters known or set by the window controller: the initial voltage at $t_{\text{sub.0}}$ (the current voltage across the ECD at the start of the transition), the magnitude of $V_{\text{sub.Drive}}$ (governing the ending optical state), and the time duration during which the ramp is applied (dictating the speed of the transition). Additionally or alternatively, the window controller also can set a target ramp rate, a maximum ramp rate or a type of ramp (for example, a linear ramp, a second degree ramp or an $n^{\text{sup.th}}$ -degree ramp). In some applications, the ramp rate can be limited to avoid damaging the ECD.

(104) The drive stage **204** is characterized by the application of a constant voltage $V_{\text{sub.Drive}}$ starting at time $t_{\text{sub.1}}$ and ending at time $t_{\text{sub.2}}$, at which point the ending optical state is reached (or approximately reached). The ramp-to-hold stage **206** is characterized by the application of a voltage ramp that decreases in magnitude from the drive value $V_{\text{sub.Drive}}$ at time $t_{\text{sub.2}}$ to a minimum holding value of $V_{\text{sub.Hold}}$ at time $t_{\text{sub.3}}$. In some implementations, the ramp-to-hold stage **206** can be defined by three drive parameters known or set by the window controller: the drive voltage $V_{\text{sub.Drive}}$, the holding voltage $V_{\text{sub.Hold}}$, and the time duration during which the ramp is applied. Additionally or alternatively, the window controller also can set a ramp rate or a type of ramp (for example, a linear ramp, a second degree ramp or an $n^{\text{sup.th}}$ -degree ramp).

(105) The hold stage **208** is characterized by the application of a constant voltage $V_{\text{sub.Hold}}$ starting at time $t_{\text{sub.3}}$. The holding voltage $V_{\text{sub.Hold}}$ is used to maintain the ECD at the ending optical state. As such, the duration of the application of the holding voltage $V_{\text{sub.Hold}}$ may be concomitant with the duration of time that the ECD is to be held in the ending optical state. For example, because of non-idealities associated with the ECD, a leakage current $I_{\text{sub.Leak}}$ can result in the slow drainage of electrical charge from the ECD. Such a drainage of electrical charge can result in a corresponding reversal of ions across the ECD, and consequently, a slow reversal of the optical transition. In such applications, the holding voltage $V_{\text{sub.Hold}}$ can be continuously applied to counter or prevent the leakage current. In some other implementations, the holding voltage

V.sub.Hold can be applied periodically to “refresh” the desired optical state, or in other words, to bring the ECD back to the desired optical state.

(106) The voltage control profile **200** illustrated and described with reference to FIG. 5 is only one example of a voltage control profile suitable for some implementations. However, many other profiles may be desirable or suitable in such implementations or in various other implementations or applications. These other profiles also can readily be achieved using the controllers and optically switchable devices disclosed herein. For example, in some implementations, a current profile can be applied instead of a voltage profile. In some such instances, a current control profile similar to that of the current density shown in FIG. 5 can be applied. In some other implementations, a control profile can have more than four stages. For example, a voltage control profile can include one or more overdrive stages. In one example implementation, the voltage ramp applied during the first stage **202** can increase in magnitude beyond the drive voltage V.sub.Drive to an overdrive voltage V.sub.OD. In some such implementations, the first stage **202** can be followed by a ramp stage **203** during which the applied voltage decreases from the overdrive voltage V.sub.OD to the drive voltage V.sub.Drive. In some other such implementations, the overdrive voltage V.sub.OD can be applied for a relatively short time duration before the ramp back down to the drive voltage V.sub.Drive.

(107) Additionally, in some implementations, the applied voltage or current profiles can be interrupted for relatively short durations of time to provide open circuit conditions across the device. While such open circuit conditions are in effect, an actual voltage or other electrical characteristics can be measured, detected or otherwise determined to monitor how far along an optical transition has progressed, and in some instances, to determine whether changes in the profile are desirable. Such open circuit conditions also can be provided during a hold stage to determine whether a holding voltage V.sub.Hold should be applied or whether a magnitude of the holding voltage V.sub.Hold should be changed. Additional information related to driving and monitoring an optical transition is provided in PCT Patent Application No. PCT/US14/43514 filed Jun. 20, 2014 and titled CONTROLLING TRANSITIONS IN OPTICALLY SWITCHABLE DEVICES, which is hereby incorporated by reference in its entirety and for all purposes.

(108) Example Controller Network Architecture

(109) In many instances, optically switchable windows can form or occupy substantial portions of a building envelope. For example, the optically switchable windows can form substantial portions of the walls, facades and even roofs of a corporate office building, other commercial building or a residential building. In various implementations, a distributed network of controllers can be used to control the optically switchable windows. FIG. 6 shows a block diagram of an example network system, **300**, operable to control a plurality of IGUs **302** in accordance with some implementations. For example, each of the IGUs **302** can be the same or similar to the IGU **100** described above with reference to FIG. 4. One primary function of the network system **300** is controlling the optical states of the ECDs (or other optically switchable devices) within the IGUs **302**. In some implementations, one or more of the windows **302** can be multi-zoned windows, for example, where each window includes two or more independently controllable ECDs or zones. In various implementations, the network system **300** is operable to control the electrical characteristics of the power signals provided to the IGUs **302**. For example, the network system **300** can generate and communicate tinting instructions (also referred to herein as “tint commands”) to control voltages applied to the ECDs within the IGUs **302**.

(110) In some implementations, another function of the network system **300** is to acquire status information from the IGUs **302** (hereinafter “information” is used interchangeably with “data”). For example, the status information for a given IGU can include an identification of, or information about, a current tint state of the ECD(s) within the IGU. The network system **300** also can be operable to acquire data from various sensors, such as temperature sensors, photosensors (also referred to herein as light sensors), humidity sensors, air flow sensors, or occupancy sensors,

whether integrated on or within the IGUs **302** or located at various other positions in, on or around the building.

(111) The network system **300** can include any suitable number of distributed controllers having various capabilities or functions. In some implementations, the functions and arrangements of the various controllers are defined hierarchically. For example, the network system **300** includes a plurality of distributed window controllers (WCs) **304**, a plurality of network controllers (NCs) **306**, and a master controller (MC) **308**. In some implementations, the MC **308** can communicate with and control tens or hundreds of NCs **306**. In various implementations, the MC **308** issues high level instructions to the NCs **306** over one or more wired or wireless links **316** (hereinafter collectively referred to as “link **316**”). The instructions can include, for example, tint commands for causing transitions in the optical states of the IGUs **302** controlled by the respective NCs **306**. Each NC **306** can, in turn, communicate with and control a number of WCs **304** over one or more wired or wireless links **314** (hereinafter collectively referred to as “link **314**”). For example, each NC **306** can control tens or hundreds of the WCs **304**. Each WC **304** can, in turn, communicate with, drive or otherwise control one or more respective IGUs **302** over one or more wired or wireless links **312** (hereinafter collectively referred to as “link **312**”).

(112) The MC **308** can issue communications including tint commands, status request commands, data (for example, sensor data) request commands or other instructions. In some implementations, the MC **308** can issue such communications periodically, at certain predefined times of day (which may change based on the day of week or year), or based on the detection of particular events, conditions or combinations of events or conditions (for example, as determined by acquired sensor data or based on the receipt of a request initiated by a user or by an application or a combination of such sensor data and such a request). In some implementations, when the MC **308** determines to cause a tint state change in a set of one or more IGUs **302**, the MC **308** generates or selects a tint value corresponding to the desired tint state. In some implementations, the set of IGUs **302** is associated with a first protocol identifier (ID) (for example, a BACnet ID). The MC **308** then generates and transmits a communication—referred to herein as a “primary tint command”—including the tint value and the first protocol ID over the link **316** via a first communication protocol (for example, a BACnet compatible protocol). In some implementations, the MC **308** addresses the primary tint command to the particular NC **306** that controls the particular one or more WCs **304** that, in turn, control the set of IGUs **302** to be transitioned.

(113) The NC **306** receives the primary tint command including the tint value and the first protocol ID and maps the first protocol ID to one or more second protocol IDs. In some implementations, each of the second protocol IDs identifies a corresponding one of the WCs **304**. The NC **306** subsequently transmits a secondary tint command including the tint value to each of the identified WCs **304** over the link **314** via a second communication protocol. In some implementations, each of the WCs **304** that receives the secondary tint command then selects a voltage or current profile from an internal memory based on the tint value to drive its respectively connected IGUs **302** to a tint state consistent with the tint value. Each of the WCs **304** then generates and provides voltage or current signals over the link **312** to its respectively connected IGUs **302** to apply the voltage or current profile.

(114) In some implementations, the various IGUs **302** can be advantageously grouped into zones of EC windows, each of which zones includes a subset of the IGUs **302**. In some implementations, each zone of IGUs **302** is controlled by one or more respective NCs **306** and one or more respective WCs **304** controlled by these NCs **306**. In some more specific implementations, each zone can be controlled by a single NC **306** and two or more WCs **304** controlled by the single NC **306**. Said another way, a zone can represent a logical grouping of the IGUs **302**. For example, each zone may correspond to a set of IGUs **302** in a specific location or area of the building that are driven together based on their location. As a more specific example, consider a building having four faces or sides: a North face, a South face, an East Face and a West Face. Consider also that the building

has ten floors. In such a didactic example, each zone can correspond to the set of electrochromic windows **100** on a particular floor and on a particular one of the four faces. Additionally or alternatively, each zone may correspond to a set of IGUs **302** that share one or more physical characteristics (for example, device parameters such as size or age). In some other implementations, a zone of IGUs **302** can be grouped based on one or more non-physical characteristics such as, for example, a security designation or a business hierarchy (for example, IGUs **302** bounding managers' offices can be grouped in one or more zones while IGUs **302** bounding non-managers' offices can be grouped in one or more different zones).

(115) In some such implementations, each NC **306** can address all of the IGUs **302** in each of one or more respective zones. For example, the MC **308** can issue a primary tint command to the NC **306** that controls a target zone. The primary tint command can include an abstract identification of the target zone (hereinafter also referred to as a “zone ID”). In some such implementations, the zone ID can be a first protocol ID such as that just described in the example above. In such cases, the NC **306** receives the primary tint command including the tint value and the zone ID and maps the zone ID to the second protocol IDs associated with the WCs **304** within the zone. In some other implementations, the zone ID can be a higher level abstraction than the first protocol IDs. In such cases, the NC **306** can first map the zone ID to one or more first protocol IDs, and subsequently map the first protocol IDs to the second protocol IDs.

(116) User or Third Party Interaction with Network

(117) In some implementations, the MC **308** is coupled to one or more outward-facing networks, **310**, (hereinafter collectively referred to as “the outward-facing network **310**”) via one or more wired or wireless links **318** (hereinafter “link **318**”). In some such implementations, the MC **308** can communicate acquired status information or sensor data to remote computers, mobile devices, servers, databases in or accessible by the outward-facing network **310**. In some implementations, various applications, including third party applications or cloud-based applications, executing within such remote devices can access data from or provide data to the MC **308**. In some implementations, authorized users or applications can communicate requests to modify the tint states of various IGUs **302** to the MC **308** via the network **310**. In some implementations, the MC **308** can first determine whether to grant the request (for example, based on power considerations or based on whether the user has the appropriate authorization) prior to issuing a tint command. The MC **308** can then calculate, determine, select or otherwise generate a tint value and transmit the tint value in a primary tint command to cause the tint state transitions in the associated IGUs **302**.

(118) For example, a user can submit such a request from a computing device, such as a desktop computer, laptop computer, tablet computer or mobile device (for example, a smartphone). In some such implementations, the user's computing device can execute a client-side application that is capable of communicating with the MC **308**, and in some instances, with a master controller application executing within the MC **308**. In some other implementations, the client-side application can communicate with a separate application, in the same or a different physical device or system as the MC **308**, which then communicates with the master controller application to effect the desired tint state modifications. In some implementations, the master controller application or other separate application can be used to authenticate the user to authorize requests submitted by the user. In some implementations, the user can select the IGUs **302** to be tinted, and inform the MC **308** of the selections, by entering a room number via the client-side application.

(119) Additionally or alternatively, in some implementations, a user's mobile device or other computing device can communicate wirelessly with various WCs **304**. For example, a client-side application executing within a user's mobile device can transmit wireless communications including tint state control signals to a WC **304** to control the tint states of the respective IGUs **302** connected to the WC **304**. For example, the user can use the client-side application to maintain or modify the tint states of the IGUs **302** adjoining a room occupied by the user (or to be occupied by the user or others at a future time). Such wireless communications can be generated, formatted or

transmitted using various wireless network topologies and protocols WC.

(120) In some such implementations, the control signals sent to the respective WC **304** from the user's mobile device (or other computing device) can override a tint value previously received by the WC **304** from the respective NC **306**. In other words, the WC **304** can provide the applied voltages to the IGUs **302** based on the control signals from the user's computing device rather than based on the tint value. For example, a control algorithm or rule set stored in and executed by the WC **304** can dictate that one or more control signals from an authorized user's computing device take precedence over a tint value received from the NC **306**. In some other instances, such as in high demand cases, control signals such as a tint value from the NC **306** may take precedence over any control signals received by the WC **304** from a user's computing device. In some other instances, a control algorithm or rule set may dictate that tint overrides from only certain users or groups or classes of users may take precedence based on permissions granted to such users, as well as in some instances, other factors including time of day or the location of the IGUs **302**.

(121) In some implementations, based on the receipt of a control signal from an authorized user's computing device, the MC **308** can use information about a combination of known parameters to calculate, determine, select or otherwise generate a tint value that provides lighting conditions desirable for a typical user, while in some instances also using power efficiently. In some other implementations, the MC **308** can determine the tint value based on preset preferences defined by or for the particular user that requested the tint state change via the computing device. For example, the user may be required to enter a password or otherwise login or obtain authorization to request a tint state change. In such instances, the MC **308** can determine the identity of the user based on a password, a security token or based on an identifier of the particular mobile device or other computing device. After determining the user's identity, the MC **308** can then retrieve preset preferences for the user, and use the preset preferences alone or in combination with other parameters (such as power considerations or information from various sensors) to generate and transmit a tint value for use in tinting the respective IGUs **302**.

(122) Wall Devices

(123) In some implementations, the network system **300** also can include wall switches, dimmers or other tint-state-controlling devices. A wall switch generally refers to an electromechanical interface connected to a WC. The wall switch can convey a tint command to the WC, which can then convey the tint command to the NC. Such devices also are hereinafter collectively referred to as “wall devices,” although such devices need not be limited to wall-mounted implementations (for example, such devices also can be located on a ceiling or floor, or integrated on or within a desk or a conference table). For example, some or all of the offices, conference rooms or other rooms of the building can include such a wall device for use in controlling the tint states of the adjoining IGUs **302**. For example, the IGUs **302** adjoining a particular room can be grouped into a zone. Each of the wall devices can be operated by an end user (for example, an occupant of the respective room) to control the tint state or other functions or parameters of the IGUs **302** that adjoin the room. For example, at certain times of the day, the adjoining IGUs **302** may be tinted to a dark state to reduce the amount of light energy entering the room from the outside (for example, to reduce AC cooling requirements). Now suppose that a user desires to use the room. In various implementations, the user can operate the wall device to communicate control signals to cause a tint state transition from the dark state to a lighter tint state.

(124) In some implementations, each wall device can include one or more switches, buttons, dimmers, dials or other physical user interface controls enabling the user to select a particular tint state or to increase or decrease a current tinting level of the IGUs **302** adjoining the room. Additionally or alternatively, the wall device can include a display having a touchscreen interface enabling the user to select a particular tint state (for example, by selecting a virtual button, selecting from a dropdown menu or by entering a tint level or tinting percentage) or to modify the tint state (for example, by selecting a “darken” virtual button, a “lighten” virtual button, or by turning a

virtual dial or sliding a virtual bar). In some other implementations, the wall device can include a docking interface enabling a user to physically and communicatively dock a portable device such as a smartphone, multimedia device, tablet computer or other portable computing device (for example, an IPHONE, IPOD or IPAD produced by Apple, Inc. of Cupertino, CA). In such implementations, the user can control the tinting levels via input to the portable device, which is then received by the wall device through the docking interface and subsequently communicated to the MC **308**, NC **306** or WC **304**. In such implementations, the portable device may include an application for communicating with an API presented by the wall device.

(125) For example, the wall device can transmit a request for a tint state change to the MC **308**. In some implementations, the MC **308** can first determine whether to grant the request (for example, based on power considerations or based on whether the user has the appropriate authorizations/permissions). The MC **308** can then calculate, determine, select or otherwise generate a tint value and transmit the tint value in a primary tint command to cause the tint state transitions in the adjoining IGUs **302**. In some such implementations, each wall device can be connected with the MC **308** via one or more wired links (for example, over communication lines such as CAN or Ethernet compliant lines or over power lines using power line communication techniques). In some other implementations, each wall device can be connected with the MC **308** via one or more wireless links. In some other implementations, the wall device can be connected (via one or more wired or wireless connections) with an outward-facing network **310** such as a customer-facing network, which then communicates with the MC **308** via link **318**.

(126) In some implementations, the MC **308** can identify the IGUs **302** associated with the wall device based on previously programmed or discovered information associating the wall device with the IGUs **302**. In some implementations, a control algorithm or rule set stored in and executed by the MC **308** can dictate that one or more control signals from a wall device take precedence over a tint value previously generated by the MC **308**. In some other instances, such as in times of high demand (for example, high power demand), a control algorithm or rule set stored in and executed by the MC **308** can dictate that the tint value previously generated by the MC **308** takes precedence over any control signals received from a wall device.

(127) In some other implementations or instances, based on the receipt of a tint-state-change request or control signal from a wall device, the MC **308** can use information about a combination of known parameters to generate a tint value that provides lighting conditions desirable for a typical user, while in some instances also using power efficiently. In some other implementations, the MC **308** can generate the tint value based on preset preferences defined by or for the particular user that requested the tint state change via the wall device. For example, the user may be required to enter a password into the wall device or to use a security token or security fob such as the IBUTTON or other 1-Wire device to gain access to the wall device. In such instances, the MC **308** can determine the identity of the user, based on the password, security token or security fob, retrieve preset preferences for the user, and use the preset preferences alone or in combination with other parameters (such as power considerations or information from various sensors) to calculate, determine, select or otherwise generate a tint value for the respective IGUs **302**.

(128) In some other implementations, the wall device can transmit a tint state change request to the appropriate NC **306**, which then communicates the request, or a communication based on the request, to the MC **308**. For example, each wall device can be connected with a corresponding NC **306** via one or more wired links such as those just described for the MC **308** or via a wireless link (such as those described below). In some other implementations, the wall device can transmit a request to the appropriate NC **306**, which then itself determines whether to override a primary tint command previously received from the MC **308** or a primary or secondary tint command previously generated by the NC **306** (as described below, the NC **306** can in some implementations generate tint commands without first receiving a tint command from an MC **308**). In some other implementations, the wall device can communicate requests or control signals directly to the WC

304 that controls the adjoining IGUs **302**. For example, each wall device can be connected with a corresponding WC **304** via one or more wired links such as those just described for the MC **308** or via a wireless link WC.

(129) In some specific implementations, the NC **306** or the MC **308** determines whether the control signals from the wall device should take priority over a tint value previously generated by the NC **306** or the MC **308**. As described above, in some implementations, the wall device can communicate directly with the NC **306**. However, in some other implementations, the wall device can communicate requests directly to the MC **308** or directly to a WC **304**, which then communicates the request to the NC **306**. In still other implementations, the wall device can communicate requests to a customer-facing network (such as a network managed by the owners or operators of the building), which then passes the requests (or requests based therefrom) to the NC **306** either directly or indirectly by way of the MC **308**. In some implementations, a control algorithm or rule set stored in and executed by the NC **306** or the MC **308** can dictate that one or more control signals from a wall device take precedence over a tint value previously generated by the NC **306** or the MC **308**. In some other instances, such as in times of high demand (for example, high power demand), a control algorithm or rule set stored in and executed by the NC **306** or the MC **308** can dictate that the tint value previously generated by the NC **306** or the MC **308** takes precedence over any control signals received from a wall device.

(130) As described above with reference to the MC **308**, in some other implementations, based on the receipt of a tint-state-change request or control signal from a wall device, the NC **306** can use information about a combination of known parameters to generate a tint value that provides lighting conditions desirable for a typical user, while in some instances also using power efficiently. In some other implementations, the NC **306** or the MC **308** can generate the tint value based on preset preferences defined by or for the particular user that requested the tint state change via the wall device. As described above with reference to the MC **308**, the user may be required to enter a password into the wall device or to use a security token or security fob such as the IBUTTON or other 1-Wire device to gain access to the wall device. In such instances, the NC **306** can communicate with the MC **308** to determine the identity of the user, or the MC **308** can alone determine the identity of the user, based on the password, security token or security fob, retrieve preset preferences for the user, and use the preset preferences alone or in combination with other parameters (such as power considerations or information from various sensors) to calculate, determine, select or otherwise generate a tint value for the respective IGUs **302**.

(131) In some implementations, the MC **308** is coupled to an external database (or “data store” or “data warehouse”) **320**. In some implementations, the database **320** can be a local database coupled with the MC **308** via a wired hardware link **322**. In some other implementations, the database **320** can be a remote database or a cloud-based database accessible by the MC **308** via an internal private network or over the outward-facing network **310**. In some implementations, other computing devices, systems or servers also can have access to read the data stored in the database **320**, for example, over the outward-facing network **310**. Additionally, in some implementations, one or more control applications or third party applications also can have access to read the data stored in the database via the outward-facing network **310**. In some cases, the MC **308** stores in the database **320** a record of all tint commands including the corresponding tint values issued by the MC **308**. The MC **308** also can collect status and sensor data and store it in the database **320**. In such instances, the WCs **304** can collect the sensor data and status data from the IGUs **302** and communicate the sensor data and status data to the respective NCs **306** over link **314** for communication to the MC **308** over link **316**. Additionally or alternatively, the NCs **306** or the MC **308** themselves also can be connected to various sensors such as light, temperature or occupancy sensors within the building as well as light or temperature sensors positioned on, around or otherwise external to the building (for example, on a roof of the building). In some implementations the NCs **306** or the WCs **304** also can transmit status or sensor data directly to the

database **320** for storage.

(132) Integration with Other Systems or Services

(133) In some implementations, the network system **300** also can be designed to function in conjunction with modern heating, ventilation, and air conditioning (HVAC) systems, interior lighting systems, security systems or power systems as an integrated and efficient energy control system for an entire building or a campus of buildings. Some implementations of the network system **300** are suited for integration with a building management system (BMS), **324**. A BMS is broadly a computer-based control system that can be installed in a building to monitor and control the building's mechanical and electrical equipment such as HVAC systems (including furnaces or other heaters, air conditioners, blowers and vents), lighting systems, power systems, elevators, fire systems, and security systems. The BMS can include hardware and associated firmware and software for maintaining conditions in the building according to preferences set by the occupants or by a building manager or other administrator. The software can be based on, for example, internet protocols or open standards. A BMS can typically be used in large buildings where it functions to control the environment within the building. For example, the BMS can control lighting, temperature, carbon dioxide levels, and humidity within the building. To control the building environment, the BMS can turn on and off various mechanical and electrical devices according to rules or in response to conditions. Such rules and conditions can be selected or specified by a building manager or administrator, for example. One function of a BMS can be to maintain a comfortable environment for the occupants of a building while minimizing heating and cooling energy losses and costs. In some implementations, the BMS can be configured not only to monitor and control, but also to optimize the synergy between various systems, for example, to conserve energy and lower building operation costs.

(134) Additionally or alternatively, some implementations of the network system **300** are suited for integration with a smart thermostat service, alert service (for example, fire detection), security service or other appliance automation service. One example of a home automation service is NEST®, made by Nest Labs of Palo Alto, California, (NEST® is a registered trademark of Google, Inc. of Mountain View, California). As used herein, references to a BMS can in some implementations also encompass, or be replaced with, such other automation services.

(135) In some implementations, the MC **308** and a separate automation service, such as a BMS **324**, can communicate via an application programming interface (API). For example, the API can execute in conjunction with a master controller application (or platform) within the MC **308**, or in conjunction with a building management application (or platform) within the BMS **324**. The MC **308** and the BMS **324** can communicate over one or more wired links **326** or via the outward-facing network **310**. In some instances, the BMS **324** can communicate instructions for controlling the IGUs **302** to the MC **308**, which then generates and transmits primary tint commands to the appropriate NCs **306**. In some implementations, the NCs **306** or the WCs **304** also can communicate directly with the BMS **324** (whether through a wired/hardware link or wirelessly through a wireless data link). In some implementations, the BMS **324** also can receive data, such as sensor data, status data and associated timestamp data, collected by one or more of the MC **308**, the NCs **306** and the WCs **304**. For example, the MC **308** can publish such data over the network **310**. In some other implementations in which such data is stored in a database **320**, the BMS **324** can have access to some or all of the data stored in the database **320**.

(136) Example Master Controller

(137) FIG. 7 shows a block diagram of an example master controller (MC) **400** in accordance with some implementations. For example, the MC **400** of FIG. 7 can be used to implement the MC **308** described above with reference to the network system **300** of FIG. 6. As used herein, references to “the MC **400**” also encompass the MC **308**, and vice versa; in other words, the two references may be used interchangeably. The MC **400** can be implemented in or as one or more computers, computing devices or computer systems (herein used interchangeably where appropriate unless

otherwise indicated). Additionally, reference to “the MC **400**” collectively refers to any suitable combination of hardware, firmware and software for implementing the functions, operations, processes or capabilities described. For example, the MC **400** can refer to a computer that implements a master controller application (also referred to herein as a “program” or a “task”).

(138) As shown in FIG. 7, the MC **400** generally includes one or more processors **402** (also collectively referred to hereinafter as “the processor **402**”). Processor **402** can be or can include a central processing unit (CPU), such as a single core or a multi-core processor. The processor **402** can additionally include a digital signal processor (DSP) or a network processor in some implementations. In some implementations, the processor **402** also can include one or more application-specific integrated circuits (ASICs). The processor **402** is coupled with a primary memory **404**, a secondary memory **406**, an inward-facing network interface **408** and an outward-facing network interface **410**. The primary memory **404** can include one or more high-speed memory devices such as, for example, one or more random-access memory (RAM) devices including dynamic-RAM (DRAM) devices. Such DRAM devices can include, for example, synchronous DRAM (SDRAM) devices and double data rate SDRAM (DDR SDRAM) devices (including DDR2 SDRAM, DDR3 SDRAM, and DDR4 SDRAM), thyristor RAM (T-RAM), and zero-capacitor (Z-RAM®), among other suitable memory devices.

(139) The secondary memory **406** can include one or more hard disk drives (HDDs) or one or more solid-state drives (SSDs). In some implementations, the memory **406** can store processor-executable code (or “programming instructions”) for implementing a multi-tasking operating system such as, for example, an operating system based on a Linux® kernel. In some other implementations, the operating system can be a UNIX®- or Unix-like-based operating system, a Microsoft Windows®-based operating system, or another suitable operating system. The memory **406** also can store code executable by the processor **402** to implement the master controller application described above, as well as code for implementing other applications or programs. The memory **406** also can store status information, sensor data or other data collected from network controllers, window controllers and various sensors.

(140) In some implementations, the MC **400** is a “headless” system; that is, a computer that does not include a display monitor or other user input device. In some such implementations, an administrator or other authorized user can log in to or otherwise access the MC **400** from a remote computer or mobile computing device over a network (for example, the network **310**) to access and retrieve information stored in the MC **400**, to write or otherwise store data in the MC **400**, and to control various functions, operations, processes or parameters implemented or used by the MC **400**. In some other implementations, the MC **400** also can include a display monitor and a direct user input device (for example, one or more of a mouse, a keyboard and a touchscreen).

(141) In various implementations, the inward-facing network interface **408** enables the MC **400** to communicate with various distributed controllers, and in some implementations, also with various sensors. The inward-facing network interface **408** can collectively refer to one or more wired network interfaces or one or more wireless network interfaces (including one or more radio transceivers). In the context of the network system **300** of FIG. 6, the MC **400** can implement the MC **308** and the inward-facing network interface **408** can enable communication with the downstream NCs **306** over the link **316**.

(142) The outward-facing network interface **410** enables the MC **400** to communicate with various computers, mobile devices, servers, databases or cloud-based database systems over one or more networks. The outward-facing network interface **410** also can collectively refer to one or more wired network interfaces or one or more wireless network interfaces (including one or more radio transceivers). In the context of the network system **300** of FIG. 6, the outward-facing network interface **410** can enable communication with various computers, mobile devices, servers, databases or cloud-based database systems accessible via the outward-facing network **310** over the link **318**. As described above, in some implementations, the various applications, including third

party applications or cloud-based applications, executing within such remote devices can access data from or provide data to the MC **400** or to the database **320** via the MC **400**. In some implementations, the MC **400** includes one or more APIs for facilitating communication between the MC **400** and various third party applications. Some example implementations of APIs that the MC **400** can enable are described in PCT Patent Application No. PCT/US15/64555 filed Dec. 8, 2015 and titled MULTIPLE INTERACTING SYSTEMS AT A SITE, which is hereby incorporated by reference in its entirety and for all purposes. For example, such third-party applications can include various monitoring services including thermostat services, alert services (for example, fire detection), security services or other appliance automation services. Additional examples of monitoring services and systems can be found in PCT Patent Application No. PCT/US2015/019031 filed Mar. 5, 2015 and titled MONITORING SITES CONTAINING SWITCHABLE OPTICAL DEVICES AND CONTROLLERS, which is hereby incorporated by reference in its entirety and for all purposes.

(143) In some implementations, one or both of the inward-facing network interface **408** and the outward-facing network interface **410** can include a BACnet compatible interface. BACnet is a communications protocol typically used in building automation and control networks and defined by the ASHRAE/ANSI 135 and ISO 16484-5 standards. The BACnet protocol broadly provides mechanisms for computerized building automation systems and devices to exchange information, regardless of the particular services they perform. For example, BACnet has traditionally been used to enable communication among heating, ventilating, and air-conditioning control (HVAC) systems, lighting control systems, access or security control systems, and fire detection systems as well as their associated equipment. In some other implementations, one or both of the inward-facing network interface **408** and the outward-facing network interface **410** can include an oBIX (Open Building Information Exchange) compatible interface or another RESTful Web Services-based interface. As such, while the following description is sometimes focused on BACnet implementations, in other implementations, other protocols compatible with oBIX or other RESTful Web Services can be used.

(144) The BACnet protocol is generally based on a server-client architecture. In some implementations, as viewed from the outward-facing network **310**, the MC **400** functions as a BACnet server. For example, the MC **400** can publish various information through the outward-facing network interface **410** over the network **310** to various authorized computers, mobile devices, servers or databases, or to various authorized applications executing on such devices. When viewed from the rest of the network system **300**, the MC **400** can function as a client. In some such implementations, the NCs **306** function as BACnet servers collecting and storing status data, sensor data or other data acquired from the WCs **304**, and publishing this acquired data such that it is accessible to the MC **400**.

(145) The MC **400** can communicate as a client to each of the NCs **306** using BACnet standard data types. Such BACnet data types can include analog values (AVs). In some such implementations, each NC **306** stores an array of AVs. The array of AVs can be organized by BACnet IDs. For example, each BACnet ID can be associated with at least two AVs; a first one of the AVs can be associated with a tint value set by the MC **400** and a second one of the AVs can be associated with a status indication value set (or received) from a respective WC **304**. In some implementations, each BACnet ID can be associated with one or more WCs **304**. For example, each of the WCs **304** can be identified by a second protocol ID such as a Controller Area Network (CAN) vehicle bus standard ID (referred to hereinafter as a “CAN ID”). In such implementations, each BACnet ID can be associated with one or more CAN IDs in the NC **306**.

(146) In some implementations, when the MC **400** determines to tint one or more IGUs **302**, the MC **400** writes a specific tint value to the AV in the NC **306** associated with the one or more respective WCs **304** that control the target IGUs **302**. In some more specific implementations, the MC **400** generates a primary tint command including a BACnet ID associated with the WCs **304**

that control the target IGUs **302**. The primary tint command also can include a tint value for the target IGUs **302**. The MC **400** can direct the transmission of the primary tint command through the inward-facing interface **408** and to the particular NC **306** using a network address of the NC **306**. For example, the network address of the NC **306** can include an Internet Protocol (IP) address (for example, an IPv4 or IPv6 address) or a Media Access Control (MAC) address (for example, when communicating over an Ethernet link **316**).

(147) The MC **400** can calculate, determine, select or otherwise generate a tint value for one or more IGUs **302** based on a combination of parameters. For example, the combination of parameters can include time or calendar information such as the time of day, day of year or time of season. Additionally or alternatively, the combination of parameters can include solar calendar information such as, for example, the direction of the sun relative to the IGUs **302**. In some instances, the direction of the sun relative to the IGUs **302** can be determined by the MC **400** based on time and calendar information together with information known about the geographical location of the building on the Earth and the direction that the IGUs face (for example, in a North-East-Down coordinate system). The combination of parameters also can include the outside temperature (external to the building), the inside temperature (within a room adjoining the target IGUs **302**), or the temperature within the interior volume of the IGUs **302**. The combination of parameters also can include information about the weather (for example, whether it is clear, sunny, overcast, cloudy, raining or snowing). Parameters such as the time of day, day of year, or direction of the sun can be programmed into and tracked by the MC **308**. Parameters such as the outside temperature, inside temperature or IGU temperature can be obtained from sensors in, on or around the building or sensors integrated on or within the IGUs **302**. Some information about the weather also can be obtained from such sensors. Additionally or alternatively, parameters such as the time of day, time of year, direction of the sun, or weather can be provided by, or determined based on information provided by, various applications including third party applications over the network **310**.

Additional examples of algorithms, routines, modules, or other means for generating tint values are described in U.S. patent application Ser. No. 13/772,969 filed Feb. 21, 2013 and titled CONTROL METHOD FOR TINTABLE WINDOWS, and in PCT Patent Application No. PCT/US15/029675 filed May 7, 2015 and titled CONTROL METHOD FOR TINTABLE WINDOWS, both of which are hereby incorporated by reference in their entireties and for all purposes.

(148) Generally, each ECD within each IGU **302** is capable of being tinted, responsive to a suitable driving voltage applied across the EC stack, to virtually any tint state within a continuous tint spectrum defined by the material properties of the EC stack. However, in some implementations, the MC **400** is programmed to select a tint value from a finite number of discrete tint values. For example, the tint values can be specified as integer values. In some such implementations, the number of available discrete tint values can be 4, 8, 16, 32, 64, 128 or 256 or more. For example, a 2-bit binary number can be used to specify any one of four possible integer tint values, a 3-bit binary number can be used to specify any one of eight possible integer tint values, a 4-bit binary number can be used to specify any one of sixteen possible integer tint values, a 5-bit binary number can be used to specify any one of thirty-two possible integer tint values, and so on. Each tint value can be associated with a target tint level (for example, expressed as a percentage of maximum tint, maximum safe tint, or maximum desired or available tint). For didactic purposes, consider an example in which the MC **400** selects from among four available tint values: 0, 5, 10 and 15 (using a 4-bit or higher binary number). The tint values 0, 5, 10 and 15 can be respectively associated with target tint levels of 60%, 40%, 20% and 4%, or 60%, 30%, 10% and 1%, or another desired, advantageous, or suitable set of target tint levels.

(149) Example Network Controller

(150) FIG. **8** shows a block diagram of an example network controller (NC) **500** in accordance with some implementations. For example, the NC **500** of FIG. **8** can be used to implement the NC **306** described above with reference to the network system **300** of FIG. **6**. As used herein, references to

“the NC **500**” also encompass the NC **306**, and vice versa; in other words, the two references may be used interchangeably. The NC **500** can be implemented in or as one or more network components, networking devices, computers, computing devices or computer systems (herein used interchangeably where appropriate unless otherwise indicated). Additionally, reference to “the NC **500**” collectively refers to any suitable combination of hardware, firmware and software for implementing the functions, operations, processes or capabilities described. For example, the NC **500** can refer to a computer that implements a network controller application (also referred to herein as a “program” or a “task”).

(151) As shown in FIG. **8**, the NC **500** generally includes one or more processors **502** (also collectively referred to hereinafter as “the processor **502**”). In some implementations, the processor **502** can be implemented as a microcontroller or as one or more logic devices including one or more application-specific integrated circuits (ASICs) or programmable logic devices (PLDs), such as field-programmable gate arrays (FPGAs) or complex programmable logic devices (CPLDs). If implemented in a PLD, the processor can be programmed into the PLD as an intellectual property (IP) block or permanently formed in the PLD as an embedded processor core. In some other implementations, the processor **502** can be or can include a central processing unit (CPU), such as a single core or a multi-core processor. The processor **502** is coupled with a primary memory **504**, a secondary memory **506**, a downstream network interface **508** and an upstream network interface **510**. In some implementations, the primary memory **504** can be integrated with the processor **502**, for example, as a system-on-chip (SOC) package, or in an embedded memory within a PLD itself. In some other implementations, the NC **500** alternatively or additionally can include one or more high-speed memory devices such as, for example, one or more RAM devices.

(152) The secondary memory **506** can include one or more solid-state drives (SSDs) storing one or more lookup tables or arrays of values. In some implementations, the secondary memory **506** can store a lookup table that maps first protocol IDs (for example, BACnet IDs) received from the MC **400** to second protocol IDs (for example, CAN IDs) each identifying a respective one of the WCs **304**, and vice versa. In some implementations, the secondary memory **506** can additionally or alternatively store one or more arrays or tables. In some implementations, such arrays or tables can be stored as comma-separated values (CSV) files or via another table-structured file format. For example, each row of the file can be identified by a timestamp corresponding to a transaction with a WC **304**. Each row can include a tint value (C) for the IGUs **302** controlled by the WC **304** (for example, as set by the MC **400** in the primary tint command); a status value (S) for the IGUs **302** controlled by the WC **304**; a set point voltage (for example, the effective applied voltage $V_{sub.Eff}$) an actual voltage level $V_{sub.Act}$ measured, detected or otherwise determined across the ECDs within the IGUs **302**; an actual current level $I_{sub.Act}$ measured, detected or otherwise determined through the ECDs within the IGUs **302**; and various sensor data. In some implementations, each row of the CSV file can include such status information for each and all of the WCs **304** controlled by the NC **500**. In some such implementations, each row also includes the CAN IDs or other IDs associated with each of the respective WC **304**.

(153) In some implementations in which the NC **500** is implemented in a computer that executes a network controller application, the secondary memory **506** also can store processor-executable code (or “programming instructions”) for implementing a multi-tasking operating system such as, for example, an operating system based on a Linux® kernel. In some other implementations, the operating system can be a UNIX®- or Unix-like-based operating system, a Microsoft Windows®-based operating system, or another suitable operating system. The memory **506** also can store code executable by the processor **502** to implement the network controller application described above, as well as code for implementing other applications or programs.

(154) In various implementations, the downstream network interface **508** enables the NC **500** to communicate with distributed WCs **304**, and in some implementations, also with various sensors. In the context of the network system **300** of FIG. **6**, the NC **500** can implement the NC **306** and the

downstream network interface **508** can enable communication with the WCs **304** over the link **314**. The downstream network interface **508** can collectively refer to one or more wired network interfaces or one or more wireless network interfaces (including one or more radio transceivers). In some implementations, the downstream interface **508** can include a CANbus interface enabling the NC **500** to distribute commands, requests or other instructions to various WCs **304**, and to receive responses including status information from the WCs **304**, according to a CANBus protocol (for example, via the CANopen communication protocol). In some implementations, a single CANbus interface can enable communication between the NC **500** and tens, hundreds or thousands of WCs **304**. Additionally or alternatively, the downstream interface **508** can include one or more Universal Serial Bus (USB) interfaces (or “ports”). In some such implementations, to enable communication via a CANbus communication protocol, a USB-to-CAN adapter can be used to couple the USB port of the downstream interface **508** with CANbus-compatible cables. In some such implementations, to enable the NC **500** to control even more WCs **304**, a USB hub (for example, having 2, 3, 4, 5 10 or more hub ports) can be plugged into the USB port of the downstream interface **508**. A USB-to-CAN adapter can then be plugged into each hub port of the USB hub.

(155) The upstream network interface **510** enables the NC **500** to communicate with the MC **400**, and in some implementations, also with various other computers, servers or databases (including the database **320**). The upstream network interface **510** also can collectively refer to one or more wired network interfaces or one or more wireless network interfaces (including one or more radio transceivers). In the context of the network system **300** of FIG. 6, the upstream network interface **510** can enable communication with the MC **308** over the link **318**. In some implementations, the upstream network interface **510** also can be coupled to communicate with applications, including third party applications and cloud-based applications, over the outward-facing network **310**. For example, in implementations in which the NC **500** is implemented as a network controller application executing as a task within a computer, the network controller application can communicate directly with the outward-facing network **310** via the operating system and the upstream network interface **510**. In some other implementations, the NC **500** may be implemented as a task running on the MC **308** and managing the CANbus devices via the CANbus interface. In such implementations, in addition or as an alternative to TCP/IP or UDP/IP communications to the MC, the communications could be via UNIX Domain Sockets (UDS) or other communication methods like shared memory, or other non-IP communication methods.

(156) In some implementations, the upstream interface **510** can include BACnet compatible interface, an oBIX compatible interface or another RESTful Web Services-based interface. As described above with reference to FIG. 7, in some implementations the NC **500** functions as a BACnet server collecting and storing status data, sensor data or other data acquired from the WCs **304**, and publishing this acquired data such that it is accessible to the MC **400**. In some implementations, the NC **500** also can publish this acquired data over the network **310** directly; that is, without first passing the data to the MC **400**. The NC **500** also functions in some respects similar to a router. For example, the NC **500** can function as a BACnet to CANBus gateway, receiving communications transmitted from the MC **400** according to the BACnet protocol, converting commands or messages from the BACnet protocol to a CANBus protocol (for example, the CANopen communication protocol), and distributing commands or other instructions to various WCs **304** according to the CANBus protocol.

(157) BACnet is built over the user datagram protocol (UDP). In some other implementations, a non-broadcast-based communication protocol can be used for communication between the MC **400** and the NCs **500**. For example, the transmission control protocol (TCP) can serve as the transport layer as opposed to UDP. In some such implementations, the MC **400** can communicate with the NCs **500** via an oBIX-compatible communication protocol. In some other implementations, the MC **400** can communicate with the NCs **500** via a WebSocket-compatible communication protocol. Such TCP protocols also can allow the NCs **500** to communicate directly with one another.

(158) In various implementations, the NC **500** can be configured to perform protocol translation (or “conversion”) between one or more upstream protocols and one or more downstream protocols. As described above, the NC **500** can perform translation from BACnet to CANopen, and vice versa. As another example, the NC **500** can receive upstream communications from the MC **400** via an oBIX protocol and translate the communications into CANopen or other CAN-compatible protocols for transmission to the downstream WCs **304**, and vice versa. In some wireless implementations, the NC **500** or the MC **400** also can translate various wireless protocols including, for example, protocols based on the IEEE 802.11 standard (for example, WiFi), protocols based on the IEEE 802.15.4 standard (for example, ZigBee, 6LoWPAN, ISA100.11a, WirelessHART or MiWi), protocols based on the Bluetooth standard (including the Classic Bluetooth, Bluetooth high speed and Bluetooth low energy protocols and including the Bluetooth v4.0, v4.1 and v4.2 versions), or protocols based on the EnOcean standard (ISO/IEC 14543-3-10). For example, the NC **500** can receive upstream communications from the MC **400** via an oBIX protocol and translate the communications into WiFi or 6LoWPAN for transmission to the downstream WCs **304**, and vice versa. As another example, the NC **500** can receive upstream communications from the MC **400** via WiFi or 6LoWPAN and translate the communications into CANopen for transmission to the downstream WCs **304**, and vice versa. In some other examples, the MC **400** rather than the NC **500** handles such translations for transmission to downstream WCs **304**.

(159) As described above with reference to FIG. 7, when the MC **400** determines to tint one or more IGUs **302**, the MC **400** can write a specific tint value to the AV in the NC **500** associated with the one or more respective WCs **304** that control the target IGUs **302**. In some implementations, to do so, the MC **400** generates a primary tint command communication including a BACnet ID associated with the WCs **304** that control the target IGUs **302**. The primary tint command also can include a tint value for the target IGUs **302**. The MC **400** can direct the transmission of the primary tint command to the NC **500** using a network address such as, for example, an IP address or a MAC address. Responsive to receiving such a primary tint command from the MC **400** through the upstream interface **510**, the NC **500** can unpackage the communication, map the BACnet ID (or other first protocol ID) in the primary tint command to one or more CAN IDs (or other second protocol IDs), and write the tint value from the primary tint command to a first one of the respective AVs associated with each of the CAN IDs.

(160) In some implementations, the NC **500** then generates a secondary tint command for each of the WCs **304** identified by the CAN IDs. Each secondary tint command can be addressed to a respective one of the WCs **304** by way of the respective CAN ID. Each secondary tint command also can include the tint value extracted from the primary tint command. The NC **500** transmits the secondary tint commands to the target WCs **304** through the downstream interface **508** via a second communication protocol (for example, via the CANOpen protocol). In some implementations, when a WC **304** receives such a secondary tint command, the WC **304** transmits a status value back to the NC **500** indicating a status of the WC **304**. For example, the tint status value can represent a “tinting status” or “transition status” indicating that the WC is in the process of tinting the target IGUs **302**, an “active” or “completed” status indicating that the target IGUs **302** are at the target tint state or that the transition has been finished, or an “error status” indicating an error. After the status value has been stored in the NC **500**, the NC **500** can publish the status information or otherwise make the status information accessible to the MC **400** or to various other authorized computers or applications. In some other implementations, the MC **400** can request status information for a particular WC **304** from the NC **500** based on intelligence, a scheduling policy, or a user override. For example, the intelligence can be within the MC **400** or within a BMS. A scheduling policy can be stored in the MC **400**, another storage location within the network system **300**, or within a cloud-based system.

(161) Integrated Master Controller and Network Controller

(162) As described above, in some implementations the MC **400** and the NC **500** can be implemented as a master controller application and a network controller application, respectively, executing within respective physical computers or other hardware devices. In some alternative implementations, each of the master controller application and the network controller application can be implemented within the same physical hardware. For example, each of the master controller application and the network controller application can be implemented as a separate task executing within a single computer device that includes a multi-tasking operating system such as, for example, an operating system based on a Linux® kernel or another suitable operating system.

(163) In some such integrated implementations, the master controller application and the network controller application can communicate via an application programming interface (API). In some particular implementations, the master controller and network controller applications can communicate over a loopback interface. By way of reference, a loopback interface is a virtual network interface, implemented through an operating system, which enables communication between applications executing within the same device. A loopback interface is typically identified by an IP address (often in the 127.0.0.0/8 address block in IPv4, or the 0:0:0:0:0:0:1 address (also expressed as ::1) in IPv6). For example, the master controller application and the network controller application can each be programmed to send communications targeted to one another to the IP address of the loopback interface. In this way, when the master controller application sends a communication to the network controller application, or vice versa, the communication does not need to leave the computer.

(164) In implementations in which the MC **400** and the NC **500** are implemented as master controller and network controller applications, respectively, there are generally no restrictions limiting the available protocols suitable for use in communication between the two applications. This generally holds true regardless of whether the master controller application and the network controller application are executing as tasks within the same or different physical computers. For example, there is no need to use a broadcast communication protocol, such as BACnet, which limits communication to one network segment as defined by a switch or router boundary. For example, the oBIX communication protocol can be used in some implementations for communication between the MC **400** and the NCs **500**.

(165) In the context of the network system **300**, each of the NCs **500** can be implemented as an instance of a network controller application executing as a task within a respective physical computer. In some implementations, at least one of the computers executing an instance of the network controller application also executes an instance of a master controller application to implement the MC **400**. For example, while only one instance of the master controller application may be actively executing in the network system **300** at any given time, two or more of the computers that execute instances of network controller application can have an instance of the master controller application installed. In this way, redundancy is added such that the computer currently executing the master controller application is no longer a single point of failure of the entire system **300**. For example, if the computer executing the master controller application fails or if that particular instance of the master controller application otherwise stops functioning, another one of the computers having an instance of the master network application installed can begin executing the master controller application to take over for the other failed instance. In some other applications, more than one instance of the master controller application may be executing concurrently. For example, the functions, processes or operations of the master controller application can be distributed to two (or more) instances of the master controller application.

(166) Example Window Controller

(167) An example window controller is further described in PCT Patent Application No. PCT/US16/58872, titled CONTROLLERS FOR OPTICALLY-SWITCHABLE DEVICES, filed Oct. 26, 2016, which is herein incorporated by reference in its entirety. Controllers for optically switchable devices are also described in U.S. patent application Ser. No. 15/334,832, titled

CONTROLLERS FOR OPTICALLY-SWITCHABLE DEVICES, filed Oct. 26, 2016, which is herein incorporate by reference in its entirety.

(168) Smart Network Controller

(169) In some implementations, the NC **500** described with reference to FIG. **8** can take over some of the functions, processes or operations that are described above as being responsibilities of the MC **400** of FIG. **7**. Additionally or alternatively, the NC **500** can include additional functionalities or capabilities not described with reference to the MC **400**. FIG. **9** shows a block diagram of example modules of a network controller in accordance with some implementations. For example, the modules of FIG. **9** can be implemented in the NC **500** in any suitable combination of hardware, firmware and software. In some implementations in which the NC **500** is implemented as a network controller application executing within a computer, each of the modules of FIG. **1** also can be implemented as an application, task or subtask executing within the network controller application.

(170) In some implementations, the NC **500** periodically requests status information from the WCs it controls. For example, the NC **500** can communicate a status request to each of the WCs it controls every few seconds, every few tens of seconds, every minute, every few minutes or after any desirable period of time. In some implementations, each status request is directed to a respective one of the WCs using the CAN ID or other identifier of the respective WC. In some implementations, the NC **500** proceeds sequentially through all of the WCs it controls during each round of status acquisition. In other words, the NC **500** loops through all of the WCs it controls such that a status request is sent to each of the WCs sequentially in each round of status acquisition. After a status request has been sent to a given WC, the NC **500** then waits to receive the status information from the respective WC before sending a status request to the next one of the WCs in the round of status acquisition.

(171) In some implementations, after status information has been received from all of the WCs that the NC **500** controls, the NC **500** then performs a round of tint command distribution. For example, in some implementations, each round of status acquisition is followed by a round of tint command distribution, which is then followed by a next round of status acquisition and a next round of tint command distribution, and so on. In some implementations, during each round of tint command distribution, the NC **500** proceeds to send a tint command to each of the WCs that the NC **500** controls. In some such implementations, the NC **500** also proceeds sequentially through all of the WCs it controls during the round of tint command distribution. In other words, the NC **500** loops through all of the WCs it controls such that a tint command is sent to each of the WCs sequentially in each round of tint command distribution.

(172) In some implementations, each status request includes instructions indicating what status information is being requested from the respective WC. In some implementations, responsive to the receipt of such a request, the respective WC responds by transmitting the requested status information to the NC **500** (for example, via the communication lines in an upstream set of cables). In some other implementations, each status request by default causes the WC to transmit a predefined set of information for the set of IGUs it controls. Either way, the status information that the WC communicates to the NC **500** responsive to each status request can include a tint status value (S) for the IGUs, for example, indicating whether the IGUs is undergoing a tinting transition or has finished a tinting transition. Additionally or alternatively, the tint status value S or another value can indicate a particular stage in a tinting transition (for example, a particular stage of a voltage control profile). In some implementations, the status value S or another value also can indicate whether the WC is in a sleep mode. The status information communicated in response to the status request also can include the tint value (C) for the IGUs, for example, as set by the MC **400** or the NC **500**. The response also can include a set point voltage set by the WC based on the tint value (for example, the value of the effective applied $V_{sub.Eff}$). In some implementations, the response also can include a near real-time actual voltage level $V_{sub.Act}$ measured, detected or

otherwise determined across the ECDs within the IGUs (for example, via the amplifier and the feedback circuit). In some implementations, the response also can include a near real-time actual current level $I_{sub.Act}$ measured, detected or otherwise determined through the ECDs within the IGUs (for example, via the amplifier and the feedback circuit). The response also can include various near real-time sensor data, for example, collected from photosensors or temperature sensors integrated on or within the IGUs.

(173) Some protocols such as CANOpen limit the size of each frame of data sent from the WC to the NC **500** and vice versa. In some instances, the sending of each status request and the receiving of status information responsive to such a request actually includes multiple two-way communications, and thus, multiple frames. For example, each status request described above can include a separate sub-request for each of the status values described above. As a more specific example, each status request from the NC **500** to a particular WC can include a first sub-request requesting the status value S . In response to the first sub-request, the WC can transmit to the NC **500** an acknowledgement and a frame including the status value S . The NC **500** can then transmit a second sub-request to the WC requesting the tint value C . In response to the second sub-request, the WC can transmit to the NC **500** an acknowledgement and a frame including the tint value C . The values of $V_{sub.Eff}$, $V_{sub.Act}$ and $I_{sub.Act}$ as well as sensor data can similarly be obtained with separate respective sub-requests and responses.

(174) In some other implementations, rather than polling or sending a status request to each of the WCs on a sequential basis, the NC **500** can asynchronously send status requests to particular WCs. For example, it may not be useful to receive status information (including C , S , $V_{sub.Eff}$, $V_{sub.Act}$ and $I_{sub.Act}$) from all of the WCs periodically. For example, it may be desirable to asynchronously request such information from only particular ones of the WCs that have recently received or implemented a tint command, that are currently undergoing a tinting transition, that have recently finished a tinting transition, or from which status information has not been collected for a relatively long duration of time.

(175) In some other implementations, rather than polling or sending status requests to each of the WCs individually, whether on a sequential basis or asynchronously, each of the WCs can periodically broadcast its status information (including C , S , $V_{sub.Eff}$, $V_{sub.Act}$ and $I_{sub.Act}$). In some such implementations, each of the WCs can broadcast the status information wirelessly. For example, each WC can broadcast the status information every few seconds, tens of seconds, minutes or tens of minutes. In some implementations, the WCs can be synchronized to broadcast their respective status information at certain times to avoid occupying a large amount of collective bandwidth. Additionally, the broadcast period can be different for different sets (such as the zones described above) of WCs and at different times, for example, based on the positions of the respective IGUs in the building and relative to the sun, or based on whether the rooms adjoining the IGUs are occupied.

(176) In some other implementations, each of the WCs can broadcast its status information in response to certain conditions, for example, when starting a tinting transition, when finishing a tinting transition, when $V_{sub.Act}$ changes by a threshold, when $I_{sub.Act}$ changes by a threshold, when sensor data (for example, light intensity or temperature) changes by a threshold, when an occupancy sensor indicates the adjoining room is occupied, or when entering or exiting a sleep mode. The NC **500** can listen for such broadcasted status information, and when it hears it, record the status information. Advantageously, in broadcasting implementations, the time required to receive status information from a set of WCs is approximately cut in half because there is no need to request the status information from the WCs, and thus, no roundtrip delay associated with each WC. Instead, there is only a one-way latency associated with the time required to transmit the status information from each WC to the NC **500**.

(177) In some other implementations, at power on or thereafter, each of the WCs can be configured to read device parameters, drive parameters and lite IDs or other ECD IDs for connected IGUs. The

WCs then broadcast their CAN IDs as well as the lite IDs and the associated device and drive parameters. That is, in some implementations, such broadcasting is initiated by one or more processors in a WC without or irrespective of any requests for such data by the NCs or other controllers. When the IDs and parameters are broadcast, the NC **500** can receive and process the IDs and parameters. In some implementations, lite IDs and parameters from messages broadcasted by the WC are then communicated from the NC to the MC, which stores them, for example, in a table including a list of known CAN IDs. For example, each row of the table can include a CAN ID, a WC location ID associated with the CAN ID, the connected lite IDs, the locations of the respective windows associated with the lite IDs, and the device and drive parameters for the respective ECDs. In some implementations, the MC can store the table in a cloud-based database system so that even if the MC fails, another MC can be instantiated and access the table in the cloud.

(178) In some instances, during commissioning, a field service technician may intervene and attempt to perform ad hoc lite-to-lite matching based on perceived differences in the tints of two or more neighboring windows. In such cases, the technician may determine that the drive parameters for one or more ECDs should be modified, and these modifications are then implemented. In some implementations, the WC is configured to broadcast the modified parameters to the corresponding NC, from which the parameters can be communicated to the MC. In situations where the WC then fails or experiences an error, the NC or MC can determine that the WC has failed, for instance, because the WC is no longer broadcasting in situations where the WC has been configured to periodically broadcast data such as the WC's CAN ID and/or WC location ID. When the failed WC is replaced with a new WC, which is then powered-on, the new WC will read the corresponding lite IDs and, as described above, broadcast the new WC's CAN ID and the connected lite IDs. When the NC or MC receives this information, the NC or MC can be configured to retrieve the modified drive parameters for the failed WC from a database table by performing a table look-up using the lite IDs. In such instances, the NC or MC is also configured to automatically update the table by assigning the new CAN ID to the WC location ID and associated lite IDs. The NC or MC will then automatically communicate the modified drive parameters to the new WC. In this way, the ECD which had its drive parameters modified during commissioning can still be driven by the modified drive parameters even when the respective WC has been replaced. Other techniques for automatically modifying, updating, and applying drive parameters can be performed in some implementations, as further described in PCT Patent Application No. PCT/US17/20805, titled METHOD OF COMMISSIONING ELECTROCHROMIC WINDOWS, by Shrivastava et al., filed Mar. 3, 2017, which is hereby incorporated by reference in its entirety and for all purposes,

(179) In some such implementations, rather than sending a tint command to each of the WCs on a sequential basis, the NC **500** can asynchronously send a tint command to a particular WC whether through a wired or wireless connection. For example, it may not be useful to send tint commands to all of the WCs periodically. For example, it may be desirable to asynchronously sent tint commands to only particular ones of the WCs that are to be transitioned to a different tint state, for which status information has just been (or has recently been) received, or to which a tint command has not been sent for a relatively long duration of time.

(180) Data Logger

(181) In some implementations, the NC **500** also includes a data logging module (or “data logger”) **802** for recording data associated with the IGUs controlled by the NC **500**. In some implementations, the data logger **802** records the status information included in each of some or all of the responses to the status requests. As described above, the status information that the WC communicates to the NC **500** responsive to each status request can include a tint status value (S) for the IGUs, a value indicating a particular stage in a tinting transition (for example, a particular stage of a voltage control profile), a value indicating whether the WC is in a sleep mode, a tint value (C), a set point voltage set by the WC based on the tint value (for example, the value of the effective

applied V.sub.Eff), an actual voltage level V.sub.Act measured, detected or otherwise determined across the ECDs within the IGUs, an actual current level I.sub.Act measured, detected or otherwise determined through the ECDs within the IGUs, and various sensor data, for example, collected from photosensors or temperature sensors integrated on or within the IGUs. In some other implementations, the NC **500** can collect and queue status information in a messaging queue like RabbitMC, ActiveMQ or Kafka and stream the status information to the MC for subsequent processing such as data reduction/compression, event detection, etc., as further described herein.

(182) In some implementations, the data logger **802** within the NC **500** collects and stores the various information received from the WCs in the form of a log file such as a comma-separated values (CSV) file or via another table-structured file format. For example, each row of the CSV file can be associated with a respective status request, and can include the values of C, S, V.sub.Eff, V.sub.Act and I.sub.Act as well as sensor data (or other data) received in response to the status request. In some implementations, each row is identified by a timestamp corresponding to the respective status request (for example, when the status request was sent by the NC **500**, when the data was collected by the WC, when the response including the data was transmitted by the WC, or when the response was received by the NC **500**). In some implementations, each row also includes the CAN ID or other ID associated with the respective WC.

(183) In some other implementations, each row of the CSV file can include the requested data for all of the WCs controlled by the NC **500**. As described above, the NC **500** can sequentially loop through all of the WCs it controls during each round of status requests. In some such implementations, each row of the CSV file is still identified by a timestamp (for example, in a first column), but the timestamp can be associated with a start of each round of status requests, rather than each individual request. In one specific example, columns 2-6 can respectively include the values C, S, V.sub.Eff, V.sub.Act and I.sub.Act for a first one of the WCs controlled by the NC **500**, columns 7-11 can respectively include the values C, S, V.sub.Eff, V.sub.Act and I.sub.Act for a second one of the WCs, columns 12-16 can respectively include the values C, S, V.sub.Eff, V.sub.Act and I.sub.Act for a third one of the WCs, and so on and so forth through all of the WCs controlled by the NC **500**. The subsequent row in the CSV file can include the respective values for the next round of status requests. In some implementations, each row also can include sensor data obtained from photosensors, temperature sensors or other sensors integrated with the respective IGUs controlled by each WC. For example, such sensor data values can be entered into respective columns between the values of C, S, V.sub.Eff, V.sub.Act and I.sub.Act for a first one of the WCs but before the values of C, S, V.sub.Eff, V.sub.Act and I.sub.Act for the next one of the WCs in the row. Additionally or alternatively, each row can include sensor data values from one or more external sensors, for example, positioned on one or more facades or on a rooftop of the building. In some such implementations, the NC **500** can send a status request to the external sensors at the end of each round of status requests.

(184) Compact Status

(185) As described above, some protocols such as CANopen limit the size of each frame sent from the WC to the NC **500** and vice versa. In some instances, the sending of each status request and the receiving of status information responsive to such a request actually includes multiple two-way communications and frames. For example, each status request described above can include a separate sub-request for each of the status values described above. In some implementations, each of two or more of the requested values C, S, V.sub.Eff, V.sub.Act and I.sub.Act can be transmitted together within a single response—a compact status response. For example, in some implementations, the values of two or more of C, S, V.sub.Eff, V.sub.Act and I.sub.Act are formatted so as to fit in one frame. For example, the CANopen protocol limits the size of the data payload that can be sent in each frame to 8 bytes (where each byte includes 8 bits). And in implementations in which the Service Data Object (SDO) sub-protocol of CAN open is used, the maximum size of the data payload portion of the CANopen frame is 4 bytes (32 bits). In some

implementations, the size of each of the values V.sub.Eff, V.sub.Act and I.sub.Act is 10 bits. Thus, each of the values of V.sub.Eff, V.sub.Act and I.sub.Act can be packaged within a single SDO frame. This leaves 2 bits left over. In some implementations, each of the values of C and S can be specified with one respective bit. In such case, all of the values of C, S, V.sub.Eff, V.sub.Act and I.sub.Act can be specified using only 32 bits, and thus, be packaged within one SDO CANopen frame.

(186) In some implementations, additional time savings can be achieved using a broadcast status request. For example, rather than sending a status request to each of the WCs on an individual (or “unicast” basis), the NC **500** can broadcast a single status request to all of the WCs it controls. As described above, responsive to receiving the status request, each WC can be programmed to respond by communicating status information such as the values C, S, V.sub.Eff, V.sub.Act and I.sub.Act in one or more compact status responses.

(187) Protocol Conversion Module

(188) As described above, one function of the NC **500** can be in translating between various upstream and downstream protocols, for example, to enable the distribution of information between WCs and the MC **400** or between the WCs and the outward-facing network **310**. In some implementations, a protocol conversion module **804** is responsible for such translation or conversion services. In various implementations, the protocol conversion module **904** can be programmed to perform translation between any of a number of upstream protocols and any of a number of downstream protocols. As described above, such upstream protocols can include UDP protocols such as BACnet, TCP protocols such as oBix, other protocols built over these protocols as well as various wireless protocols. Downstream protocols can include, for example, CANopen, other CAN-compatible protocol, and various wireless protocols including, for example, protocols based on the IEEE 802.11 standard (for example, WiFi), protocols based on the IEEE 802.15.4 standard (for example, ZigBee, 6LoWPAN, ISA100.11a, WirelessHART or MiWi), protocols based on the Bluetooth standard (including the Classic Bluetooth, Bluetooth high speed and Bluetooth low energy protocols and including the Bluetooth v4.0, v4.1 and v4.2 versions), or protocols based on the EnOcean standard (ISO/IEC 14543-3-10).

(189) Integrated Analytics

(190) In some implementations, the NC **500** uploads the information logged by the data logger **802** (for example, as a CSV file) to the MC **400** on a periodic basis, for example, every 24 hours. For example, the NC **500** can transmit a CSV file to the MC **400** via the File Transfer Protocol (FTP) or another suitable protocol over an Ethernet data link **316**. In some such implementations, the status information can then be stored in the database **320** or made accessible to applications over the outward-facing network **310**.

(191) In some implementations, the NC **500** also can include functionality to analyze the information logged by the data logger **802**. For example, an analytics module **906** can receive and analyze the raw information logged by the data logger **802** in real time. In various implementations, the analytics module **806** can be programmed to make decisions based on the raw information from the data logger **802**. In some other implementations, the analytics module **806** can communicate with the database **320** to analyze the status information logged by the data logger **802** after it is stored in the database **320**. For example, the analytics module **806** can compare raw values of electrical characteristics such as V.sub.Eff, V.sub.Act and I.sub.Act with expected values or expected ranges of values and flag special conditions based on the comparison. For example, such flagged conditions can include power spikes indicating a failure such as a short, an error, or damage to an ECD. In some implementations, the analytics module **806** communicates such data to the tint determination module **810** or to the power management module **812**.

(192) In some implementations, the analytics module **806** also can filter the raw data received from the data logger **802** to more intelligently or efficiently store information in the database **320**. For example, the analytics module **806** can be programmed to pass only “interesting” information to a

database manager **808** for storage in the database **320**. For example, interesting information can include anomalous values, values that otherwise deviate from expected values (such as based on empirical or historical values), or for specific periods when transitions are happening. More detailed examples of how raw data can be filtered, parsed, temporarily stored, and efficiently stored long term in a database are described in PCT Patent Application No. PCT/US15/029675 filed May 7, 2015 and titled CONTROL METHOD FOR TINTABLE WINDOWS, which is hereby incorporated by reference in its entirety and for all purposes.

(193) Database Manager

(194) In some implementations, the NC **500** includes a database manager module (or “database manager”) **808** configured to store information logged by the data logger **804** to a database on a periodic basis, for example, every hour, every few hours or every 24 hours. In some implementations, the database can be an external database such as the database **320** described above. In some other implementations, the database can be internal to the NC **500**. For example, the database can be implemented as a time-series database such as a Graphite database within the secondary memory **506** of the NC **500** or within another long term memory within the NC **500**. In some example implementations, the database manager **808** can be implemented as a Graphite Daemon executing as a background process, task, sub-task or application within a multi-tasking operating system of the NC **500**. A time-series database can be advantageous over a relational database such as SQL because a time-series database is more efficient for data analyzed over time

(195) In some implementations, the database **320** can collectively refer to two or more databases, each of which can store some or all of the information obtained by some or all of the NCs **500** in the network system **300**. For example, it can be desirable to store copies of the information in multiple databases for redundancy purposes. In some implementations, the database **320** can collectively refer to a multitude of databases, each of which is internal to a respective NC **500** (such as a Graphite or other times-series database). It also can be desirable to store copies of the information in multiple databases such that requests for information from applications including third party applications can be distributed among the databases and handled more efficiently. In some such implementations, the databases can be periodically or otherwise synchronized to maintain consistency.

(196) In some implementations, the database manager **808** also can filter data received from the analytics module **806** to more intelligently or efficiently store information in an internal or external database. For example, the database manager **808** can additionally or alternatively be programmed to store only “interesting” information to a database. Again, interesting information can include anomalous values, values that otherwise deviate from expected values (such as based on empirical or historical values), or for specific periods when transitions are happening. More detailed examples of how raw data can be filtered, parsed, temporarily stored, and efficiently stored long term in a database are described in PCT Patent Application No. PCT/US15/029675 filed May 7, 2015 and titled CONTROL METHOD FOR TINTABLE WINDOWS, which is hereby incorporated by reference in its entirety and for all purposes.

(197) Tint Determination

(198) In some implementations, the WC, NC **500** or the MC **400** includes intelligence for calculating, determining, selecting or otherwise generating tint values for the IGUs. For example, as similarly described above with reference to the MC **400** of FIG. 7, a tint determination module **810** can execute various algorithms, tasks or subtasks to generate tint values based on a combination of parameters. The combination of parameters can include, for example, the status information collected and stored by the data logger **802**. The combination of parameters also can include time or calendar information such as the time of day, day of year or time of season. Additionally or alternatively, the combination of parameters can include solar calendar information such as, for example, the direction of the sun relative to the IGUs. The combination of parameters also can include the outside temperature (external to the building), the inside temperature (within a

room adjoining the target IGUs), or the temperature within the interior volume of the IGUs. The combination of parameters also can include information about the weather (for example, whether it is clear, sunny, overcast, cloudy, raining or snowing). Parameters such as the time of day, day of year, or direction of the sun can be programmed into and tracked by the NC **500**. Parameters such as the outside temperature, inside temperature or IGU temperature can be obtained from sensors in, on or around the building or sensors integrated on or within the IGUs. In some implementations, various parameters can be provided by, or determined based on information provided by, various applications including third party applications that can communicate with the NC **500** via an API. For example, the network controller application, or the operating system in which it runs, can be programmed to provide the API.

(199) In some implementations, the tint determination module **810** also can determine tint values based on user overrides received via various mobile device applications, wall devices or other devices. In some implementations, the tint determination module **810** also can determine tint values based on commands or instructions received various applications, including third party applications and cloud-based applications. For example, such third party applications can include various monitoring services including thermostat services, alert services (for example, fire detection), security services or other appliance automation services. Additional examples of monitoring services and systems can be found in PCT/US2015/019031 filed 5 Mar. 2015 and titled MONITORING SITES CONTAINING SWITCHABLE OPTICAL DEVICES AND CONTROLLERS. Such applications can communicate with the tint determination module **810** and other modules within the NC **500** via one or more APIs. Some examples of APIs that the NC **500** can enable are described in PCT Patent Application No. PCT/US15/64555 filed Dec. 8, 2015 and titled MULTIPLE INTERFACING SYSTEMS AT A SITE.

(200) Power Management

(201) As described above, the analytics module **806** can compare values of $V_{sub.Eff}$, $V_{sub.Act}$ and $I_{sub.Act}$ as well as sensor data either obtained in real time or previously stored within the database **320** with expected values or expected ranges of values and flag special conditions based on the comparison. The analytics module **806** can pass such flagged data, flagged conditions or related information to the power management **812**. For example, such flagged conditions can include power spikes indicating a short, an error, or damage to an ECD. The power management module **812** can then modify operations based on the flagged data or conditions. For example, the power management module **812** can delay tint commands until power demand has dropped, stop commands to troubled WCs (and put them in idle state), start staggering commands to WCs, manage peak power, or signal for help.

CONCLUSION

(202) In one or more aspects, one or more of the functions described herein may be implemented in hardware, digital electronic circuitry, analog electronic circuitry, computer software, firmware, including the structures disclosed in this specification and their structural equivalents thereof, or in any combination thereof. Certain implementations of the subject matter described in this document also can be implemented as one or more controllers, computer programs, or physical structures, for example, one or more modules of computer program instructions, encoded on a computer storage media for execution by, or to control the operation of window controllers, network controllers, and/or antenna controllers. Any disclosed implementations presented as or for electrochromic windows can be more generally implemented as or for switchable optical devices (including windows, mirrors, etc.).

(203) Various modifications to the embodiments described in this disclosure may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, the claims are not intended to be limited to the implementations shown herein, but are to be accorded the widest scope consistent with this disclosure, the principles and the novel features disclosed

herein. Additionally, a person having ordinary skill in the art will readily appreciate, the terms “upper” and “lower” are sometimes used for ease of describing the figures, and indicate relative positions corresponding to the orientation of the figure on a properly oriented page, and may not reflect the proper orientation of the devices as implemented.

(204) Certain features that are described in this specification in the context of separate implementations also can be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also can be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

(205) Similarly, while operations are depicted in the drawings in a particular order, this does not necessarily mean that the operations are required to be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Further, the drawings may schematically depict one more example processes in the form of a flow diagram. However, other operations that are not depicted can be incorporated in the example processes that are schematically illustrated. For example, one or more additional operations can be performed before, after, simultaneously, or between any of the illustrated operations. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products. Additionally, other implementations are within the scope of the following claims. In some cases, the actions recited in the claims can be performed in a different order and still achieve desirable results.

(206) Certain documents are incorporated by reference herein. It should be understood that any disclaimers or disavowals made in such documents do not necessarily apply to the present embodiments. Similarly, features which are described as necessary in such documents may or may not be used in the present embodiments.

Claims

1. A method of controlling a tint state of an electrochromic device, the method comprising: (a) receiving, at a local controller, from a remote voice recognition module, a text command to cause the electrochromic device to transition to a desired tint state, wherein the text command results from the remote voice recognition module: receiving a voice command from a local user that conveys information for changing the tint state of the electrochromic device to the desired tint state, and converting the voice command into the text command and transmitting the text command to the local controller; and, with the local controller, executing the text command to cause the electrochromic device to transition to the desired tint state, and wherein converting the voice command into the text command comprises comparing the voice command to a list of devices in a first dictionary and a list of tint states in a second dictionary to determine the electrochromic device and the desired tint state in the voice command.
2. The method of claim 1, wherein the local controller is configured to receive the transmitted text command via an application programming interface (API).
3. The method of claim 1, further comprising providing authorization for the text command to cause the tint state of the electrochromic device to be changed.
4. The method of claim 3, wherein the authorization is based on whether the local user is authorized to change the tint state of the electrochromic device.

5. The method of claim 3, wherein the authorization is based on whether the local user is authorized to change the tint state of a group or zone of electrochromic devices containing the electrochromic device.
 6. The method of claim 3, wherein the authorization is for a duration.
 7. The method of claim 3, wherein the authorization is based on receiving a log in of the local user with a passcode and/or facial recognition.
 8. The method of claim 3, wherein the authorization is provided for each text command.
 9. The method of claim 1, wherein the voice command includes information related to making the electrochromic device lighter or darker.
 10. The method of claim 1, wherein the voice command includes information related to a name, location, group, or zone of optically switchable devices.
 11. The method of claim 1, wherein the text command instructs the electrochromic device to switch to the desired tint state according to one or more rules.
 12. The method of claim 11, wherein the one or more rules relate to a schedule and the text command instructs the electrochromic device to switch to the desired tint state at a scheduled time.
 13. The method of claim 1, wherein the text command indicates the desired tint state without reference to a starting tint state of the electrochromic device.
 14. The method of claim 1, further comprising providing information for a response generation module configured to generate a response to the local user, wherein the information relates to the transition of the electrochromic device to the desired tint state.
 15. A system for controlling a tint state of an electrochromic device, the system comprising: an optically switchable device; and a local controller communicatively coupled with the electrochromic device and configured to receive, from a remote voice recognition module, a text command to cause the electrochromic device to transition to a desired tint state, wherein the text command results from the remote voice recognition module: receiving a voice command from a local user that conveys information for changing the tint state of the electrochromic device to the desired tint state, and converting the voice command into the text command and transmitting the text command to the local controller; and the local controller is configured to execute the text command to cause the electrochromic device to transition to the desired tint state, and wherein converting the voice command into the text command comprises comparing the voice command to a list of devices in a first dictionary and a list of tint states in a second dictionary to determine the electrochromic device and the desired tint state in the voice command.
 16. The system of claim 15, wherein the voice command is received by a microphone on an electronic device.
 17. The system of claim 16, wherein the electronic device is a smartphone, tablet, laptop, personal computer, fitness device, watch, or wall unit.
 18. The system of claim 15, further comprising an authentication module configured to provide authorization for the text command to change the tint state of the electrochromic device.
 19. The system of claim 18, wherein the authorization is based on whether the local user is authorized to change the tint state of the optically switchable device.
 20. The system of claim 18, wherein the authorization is based on whether the local user is authorized to change the tint state of a group or zone of electrochromic devices containing the electrochromic device.
 21. The system of claim 18, wherein the authorization is based on receiving a log in of the local user with a passcode and/or facial recognition via a smartphone, tablet, laptop, personal computer, fitness device, watch, or wall unit.
-