

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401940
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Park; Youngbae et al.

Speaker module and electronic device including speaker module

Abstract

An electronic device comprises a speaker module which includes a speaker unit and a first speaker housing that is coupled to the speaker unit in a first direction. The first speaker housing accommodates the speaker unit, and is arranged in the inner space of the electronic device. An opening for radiating sound allows the inner space of the electronic device to communicate with the outside, and an acoustic passage connects the opening for radiating sound and a portion from which a sound is radiated by the speaker unit of the speaker module. The speaker module can further include an airtight member for sealing a gap between the speaker module and the acoustic passage so that the sound radiated from the speaker unit is transmitted to the acoustic passage.

Inventors: Park; Youngbae (Suwon-si, KR), Yoon; Changshik (Suwon-si, KR), Kim; Kiwon (Suwon-si, KR), Kim; Joohan (Suwon-si, KR), Kim; Taeon (Suwon-si, KR), Bae; Jinju (Suwon-si, KR), Baek; Incheol (Suwon-si, KR), Lee; Myungcheol (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008781410

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 18/164057

Filed: February 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230188888 A1	Jun. 15, 2023

Foreign Application Priority Data

KR	10-2020-0097104	Aug. 04, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/010146 20210803 PENDING child-doc US 18164057

Publication Classification

Int. Cl.: H04R1/28 (20060101); H04R1/44 (20060101)

U.S. Cl.:

CPC H04R1/28 (20130101); H04R1/44 (20130101); H04R2499/11 (20130101)

Field of Classification Search

CPC: H04R (1/28); H04R (1/44); H04R (2499/11)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6526150	12/2002	Kelley et al.	N/A	N/A
9036857	12/2014	Zellner, Jr. et al.	N/A	N/A
9661410	12/2016	Iwai et al.	N/A	N/A
9999149	12/2017	Jun et al.	N/A	N/A
10462557	12/2018	Chan	N/A	N/A
10602249	12/2019	Jung et al.	N/A	N/A
10609461	12/2019	Lo	N/A	N/A
10911848	12/2020	Yoon et al.	N/A	N/A
11109144	12/2020	Park et al.	N/A	N/A
2014/0369533	12/2013	Kim et al.	N/A	N/A
2016/0165327	12/2015	Crosby et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2000013880	12/1999	JP	N/A
2017117895	12/2016	JP	N/A
20000015523	12/1999	KR	N/A
20140145068	12/2013	KR	N/A
20170100368	12/2016	KR	N/A
20180045300	12/2017	KR	N/A
101922217	12/2017	KR	N/A
20190021056	12/2018	KR	N/A
20190127184	12/2018	KR	N/A
20200072056	12/2019	KR	N/A

OTHER PUBLICATIONS

International Search Report with Written Opinion for International Application No. PCT/KR2021/010146; Application Filing Date Aug. 3, 2021; Date of Mailing Nov. 18, 2021 (10 pages). cited by applicant

Primary Examiner: Fischer; Mark

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

TECHNICAL FIELD

(1) Various embodiments disclosed in the present document relate to a speaker module and an electronic device including the speaker module.

Background Art

(2) A speaker module including a speaker unit for reproducing a sound may be included in an electronic device. Also, the interest of users in acoustic performance is increasing because an increasing amount of content is being reproduced through electronic devices.

(3) In consideration of the convenience of assembling the electronic device, the speaker unit is manufactured in the form of a speaker module.

(4) An electronic device having dustproof and waterproof functions should be able to block external foreign substances and moisture that may be introduced through a hole for transmitting a sound radiated from the speaker unit to the outside of the electronic device. In consideration of such airtightness, an adhesive material having a waterproof function may be used.

DISCLOSURE OF INVENTION

Technical Problem

(5) In the case of using an adhesive material having a waterproof function in consideration of dust and water resistance, a compression process for attaching the adhesive material to an appliance may be required. Electronic components or speaker modules of the electronic device may be damaged during the compression process.

(6) In addition, a housing for accommodating the speaker unit may include a structure capable of separating a space through which sounds having opposite phases are transmitted so that sounds having opposite phases radiated from the speaker unit are not canceled. In the case that the volume occupied by the housing accommodating the speaker unit increases for space separation, the utilization efficiency of the inner space of the electronic device may decrease.

Solution to Problem

(7) According to various embodiments disclosed in the present document, it is possible to provide a speaker module and an electronic device capable of improving the inner space utilization of the electronic device, as well as providing an airtight structure that does not require a separate compression process while ensuring dustproof and waterproof functionality.

(8) An electronic device according to various embodiments disclosed in the present document may comprise a speaker module which includes a speaker unit and a first speaker housing that is coupled to the speaker unit in a first direction and accommodates the speaker unit, and which is arranged in the inner space of the electronic device; an opening for radiating sound which allows the inner space of the electronic device to communicate with the outside; and an acoustic passage connecting the opening for radiating sound and a portion from which sound is radiated by the speaker unit of the speaker module, wherein the speaker module can further include an airtight member which seals a gap between the speaker module and the acoustic passage so that the sound radiated from the speaker unit is transmitted to the acoustic passage.

(9) A speaker module according to various embodiments disclosed in the present document may

further include a speaker unit, a first speaker housing that is coupled to the speaker unit in a first direction and that accommodates the speaker unit, and an airtight member sealing the acoustic passage connecting the speaker unit and a portion from which a sound is radiated by the speaker unit.

Advantageous Effects of Invention

(10) According to various embodiments disclosed in the present document, because a compression process is not required in the process of installing the speaker module to the electronic device, the risk of damage to an electronic component and the speaker module that may occur in the compression process can be eliminated. In addition, it is possible to improve the utilization efficiency of the inner space of the electronic device.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) In connection with the description of the drawings, the same or similar reference numerals may be used for the same or similar components.
- (2) FIG. 1 is a block diagram of an electronic device in a network environment, according to various embodiments.
- (3) FIG. 2a is a perspective view of a speaker unit according to various embodiments disclosed in the present document.
- (4) FIG. 2b is a cross-sectional view of the speaker unit shown in FIG. 2a taken along line A-A.
- (5) FIG. 3a is an exploded perspective view of a speaker module according to various embodiments disclosed in the present document.
- (6) FIG. 3b is a perspective view of a speaker module according to various embodiments disclosed in the present document.
- (7) FIG. 3c is a cross-sectional view of the speaker module shown in FIG. 3b taken along line A-A.
- (8) FIG. 4a is a perspective view of an electronic device according to various embodiments disclosed in the present document.
- (9) FIG. 4b is a cross-sectional view of the electronic device shown in FIG. 4a taken along line B-B.
- (10) FIGS. 5a to 5d are cross-sectional views of a speaker module and peripheral components thereof according to various embodiments disclosed in the present document.
- (11) FIGS. 6a to 6c are diagrams for explaining a coupling relationship between a speaker unit and a first speaker housing according to various embodiments disclosed in the present document.

MODE FOR THE INVENTION

- (12) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment.
- (13) With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise.
- (14) As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1.sup.st” and “2.sup.nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., the first element) is referred to, with or without the term “operatively” or “communicatively”,

as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., the second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via the third element.

(15) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments. With reference to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(16) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(17) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural

network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(18) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**. In addition, the non-volatile memory **134** may include internal memory **136** and/or external memory **138**.

(19) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(20) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(21) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(22) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(23) The audio module **170** may convert a sound into an electrical signal and vice versa.

(24) According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(25) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(26) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(27) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(28) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(29) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(30) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(31) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(32) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™ wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(33) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(34) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(35) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(36) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI).

(37) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic device **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic device **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) on the basis of 5G communication technology or IoT-related technology.

(38) FIG. **2a** is a perspective view of a speaker unit according to various embodiments disclosed in the present document. FIG. **2b** is a cross-sectional view of the speaker unit shown in FIG. **2a** taken along line A-A.

(39) The speaker unit **200** according to various embodiments disclosed in the present document may refer to a device that is disposed in an electronic device (e.g., the electronic device **101** of FIG. **1**) and outputs a sound. The speaker unit **200** may receive an audio signal processed through an audio module (e.g., the audio module **170** of FIG. **1**) of the electronic device in accordance with

execution of an application or a function, and it may output the signal as a sound. For example, the speaker unit may be the sound output device of FIG. 1 (e.g., **155** of FIG. 1).

(40) According to various embodiments, a unit frame **210** may support various components included in the speaker unit **200**. The shape of the unit frame **210** shown in FIGS. **2a** and **2b** is only an example, and the shape of the unit frame **210** is not limited to the shape shown in FIGS. **2a** and **2b**. The unit frame **210** may be manufactured in various forms according to a space in which the speaker unit **200** is to be disposed. The unit frame **210** may be formed of various materials. For example, the unit frame **210** may be formed of a synthetic resin material.

(41) According to various embodiments, as shown in FIGS. **2a** and **2b**, a vibrating member **220** may be supported by at least a portion of the unit frame **210**. A voice coil **230** may be coupled to at least a portion of the vibrating member **220**. The vibrating member **220** may be vibrated by the movement of the voice coil **230**. In an embodiment, the vibrating member **220** may include a first vibrating unit **221** and a second vibrating unit **222**. At least a portion of the first vibrating unit **221** may be supported by the unit frame **210**. The first vibrating unit **221** may be formed of a flexible material. The first vibrating unit **221**, for example, may be formed of an elastomer, a synthetic resin, a thin metal plate, rubber, or a film. At least a portion of the second vibrating unit **222** may be coupled to the first vibrating unit **221**. The second vibrating unit **222** may be formed of a material that is relatively harder than the first vibrating unit **221** (e.g., a material having a relatively higher elastic modulus than that of the first vibrating unit **221**). For example, the second vibrating unit **222** may be formed of a metal, a synthetic resin, or an alloy. With reference to FIG. **2a**, the first vibrating unit **221** may be disposed on the outer periphery of the unit frame **210**, and the second vibrating unit **222** may be supported by the first vibrating unit **221**. The first vibrating unit **221** formed of a flexible material may vibrate by the movement of the voice coil **230** coupled to the vibrating member **220**, and the second vibrating unit **222** supported by the first vibrating unit **221** may vibrate together with the first vibrating unit **221** by the vibration of the first vibrating unit **221**. A sound may be generated by the vibration of the vibrating member **220**. In another embodiment, the vibrating member **220** may be formed of a single material without being divided into the first vibrating unit **221** and the second vibrating unit **222**.

(42) According to various embodiments, the voice coil **230** may be formed by winding an electric wire (not shown). In the case that a current flows in the voice coil **230**, the voice coil **230** may vibrate up and down because of the repulsive force between the magnetic field formed by the current flowing in the voice coil **230** and the magnet **240** adjacent to the voice coil **230**. As described above, the vibrating member **220** fixed to the voice coil **230** may vibrate by the vibration of the voice coil **230**. A sound may be output by vibration of the vibrating member **220**. Vibration of the voice coil **230** may be controlled by a current flowing in the voice coil **230**.

(43) According to various embodiments, an electronic circuit **280** may be electrically connected to a printed circuit board (not shown) of an electronic device (e.g., the electronic device **101** of FIG. **1**) to apply an electrical signal to the voice coil **230**. The electronic circuit **280** may be formed of a material having elasticity. The electronic circuit **280** may be disposed adjacent to the vibrating member **220** to regulate the degree of vibration (e.g., damping ratio) of the vibrating member **220**.

(44) According to various embodiments, a magnet **240** may be disposed on a yoke **250**. The yoke **250** may be formed of a magnetic material. For example, the yoke **250** may be formed of a magnetic metal or a material including a magnetic metal.

(45) According to various embodiments, the magnet **240** may include a first magnet **240-1** and a second magnet **240-2**. As shown in FIG. **2b**, the first magnet **240-1** may be a magnet disposed on the central portion of the yoke **250** and the second magnet **240-2** may be a magnet disposed on the side of the yoke **250**. The voice coil **230** may be disposed between the first magnet **240-1** and the second magnet **240-2**.

(46) According to various embodiments, a plate **270** may be disposed to cover at least a portion of the magnet **240**. The plate **270** may be formed of a material capable of shielding magnetic flux.

(47) According to various embodiments, the magnet **240**, the yoke **250**, and the plate **270** may form a magnetic circuit for driving the speaker unit **200**. The voice coil **230** may vibrate by repulsion of the magnetic circuit formed by the magnet **240**, the yoke **250**, and the plate **270**, and the magnetic field formed by the current flow of the voice coil **230**.

(48) The shape and structure of the speaker unit **200** shown in FIGS. **2a** and **2b** is only an example, and the speaker unit **200** described below is not limited to the shape and structure shown in FIGS. **2a** and **2b**. For example, the speaker unit **200** may be changed to the shape and structure shown in FIGS. **6a** to **6c**.

(49) FIG. **3a** is an exploded perspective view of a speaker module according to various embodiments disclosed in the present document. FIG. **3b** is a perspective view of a speaker module according to various embodiments disclosed in the present document. FIG. **3c** is a cross-sectional view of the speaker module shown in FIG. **3b** taken along line A-A.

(50) According to various embodiments, as shown in FIGS. **3a** to **3c**, the speaker module **300** may include a speaker unit **310** (e.g., the speaker unit **200** of FIGS. **2a** and **2b**), a first speaker housing **320**, a second speaker housing **330**, and an airtight member **340**. Some of the above-described components may be omitted from the speaker module **300**. For example, the speaker module **300** may not include the second speaker housing **330** (refer to FIG. **5a**).

(51) According to various embodiments, the first speaker housing **320** may be coupled to the speaker unit **310** in a first direction. The first direction may refer to a $-Z$ direction on the basis of FIGS. **3a** to **3c**. The first speaker housing **320** and the speaker unit **310** may be coupled in various ways. For example, the first speaker housing **320** and the speaker unit **310** may be coupled to each other through an adhesive material, and the speaker unit **310** may be inserted into the portion formed in the first housing **320** as a shape corresponding to the speaker unit **310**. The first speaker housing **320** may accommodate the speaker unit **310**. The first speaker housing **320** may be disposed inside an electronic device (e.g., the electronic device **101** of FIG. **1**). The first speaker housing **320** may be formed of various materials. For example, it may be formed of a synthetic resin, a metal, or a composite material.

(52) According to various embodiments, the second speaker housing **330** may be coupled to the first speaker housing **320** in the first direction. The second speaker housing **330** and the first speaker housing **320** may be coupled in various ways. For example, the first speaker housing **320** and the second speaker housing **330** may be coupled to each other through an adhesive material, and the first speaker housing **320** may be inserted into the portion formed in the second speaker housing **330** as a shape corresponding to the first speaker housing **320**. As another example, the first speaker housing **320** and the second speaker housing **330** may be screwed together. The second speaker housing **330** may be formed of various materials. For example, it may be formed of a synthetic resin, a metal, or a composite material. In an embodiment, the second speaker housing **330** may be formed of the same material as the first speaker housing **320**.

(53) According to various embodiments, at least one of electronic components included in the electronic device may be disposed in the second speaker housing **330**. For example, an antenna of the electronic device may be disposed in the second speaker housing **330**. An antenna may refer to a device connected to a communication module (e.g., the communication module **190** of FIG. **1**) of an electronic device to transmit or receive a communication-related signal. In addition, various electronic components may be disposed in the second speaker housing **330**.

(54) According to various embodiments, as shown in FIG. **3c**, a resonance space **350** may be formed between the first speaker housing **320** and the second speaker housing **330**. The resonance space **350** may be a space formed by being surrounded by a portion of the first speaker housing **320** and a portion of the second speaker housing **330**. At least a portion of the resonance space **350** may be connected to the speaker unit **310**. As shown in FIG. **3c**, the resonance space **350** may be disposed in a first direction with respect to the speaker unit **310**. The direction in which the main sound is radiated from the speaker unit **310** may be a second direction opposite to the first

direction. The first direction may refer to a -Z direction on the basis of FIGS. 3a to 3c. The second direction may refer to a +Z direction on the basis of FIGS. 3a to 3c. The sound generated by the vibration of the diaphragm of the speaker unit **310** may be radiated in the second direction and the first direction. Because the phases of the sound traveling in the second direction and the sound traveling in the first direction are opposite to each other, the sounds traveling in each direction need to be separated from each other. The resonance space **350** may be disposed in a first direction opposite to the second direction, which is the main sound radiation direction of the speaker unit **310**, so that the sound radiated in the first direction may be separated from the sound radiated in the second direction. In addition, the resonance space **350** may resonate the sound radiated in the first direction and increase the volume of the sound output to the outside of the electronic device.

(55) According to various embodiments, the first speaker housing **320** of the speaker module **300** may separate the space so that a sound radiated in a first direction from the speaker unit **310** and travelling to the resonance space **350** and a sound travelling in a second direction from the speaker unit **310** may not interfere with each other.

(56) According to various embodiments, the airtight member **340** may be coupled to the speaker unit **310** from the second direction to the first direction. The airtight member **340** may prevent a sound radiated from the speaker unit **310** in the second direction from leaking into an inner space of the electronic device. In addition, the airtight member **340** may block external foreign substances or moisture that may be introduced into the acoustic passage inside the electronic device not to be moved into the inner space by sealing the gap between the acoustic passage (e.g., the acoustic passage **410** of FIG. 4b) to be described later and the speaker unit **310**.

(57) According to various embodiments, the airtight member **340** may include an airtight frame **341** and an airtight part **342**. In an embodiment, the airtight frame **341** may be formed to correspond to the outer periphery of the speaker unit **310**. An opening **343** may be formed in the airtight frame **341** so that the sound radiated from the speaker unit **310** in the second direction passes through the airtight member **340**. The airtight frame **341** may be formed of a synthetic resin, a metal, or a composite material. In an embodiment, the airtight part **342** may be formed of a material having an elastic force. For example, the airtight part **342** may be formed of a material such as rubber, silicone, or liquid silicone rubber (LSR). The airtight part **342** may be disposed in the airtight frame **341** in a variety of ways. For example, the airtight part **342** may be formed in the airtight frame **341** through a double injection method. The airtight part **342** may seal the acoustic passage by being in close contact with a device forming the acoustic passage. In another embodiment, the airtight member **340** may be formed of a material having an elastic force. For example, the airtight frame **341** and the airtight part **342** described above may be integrally formed, and the airtight frame **341** and the airtight part **342** may be formed of a material having an elastic force. In another embodiment, the airtight frame may be divided into a first airtight frame and a second airtight frame. The second airtight frame may be formed in the first airtight frame through a double injection method, and the airtight part formed of a material having an elastic force may be formed in the first airtight frame or the second airtight frame through a double injection method.

(58) According to various embodiments disclosed in the present document, an acoustic passage through which foreign substances or moisture may be introduced may be sealed by the airtight member **340** coupled to the speaker unit **310**. Accordingly, there is no need to dispose a mechanism between the acoustic passage and an opening for radiating sound for blocking an external foreign substance or moisture; thus, the space utilization efficiency of the electronic device may be improved. In addition, because the airtight member **340** performs a sealing by a material having elasticity and does not use an adhesive material or a waterproof material, compression processing for bonding the waterproof material is unnecessary in the assembly process of the speaker module **300** disclosed in the present document. Accordingly, the risk of damage to the electronic component of the electronic device or the speaker module **300** because of the compression process may be eliminated.

(59) FIG. 4a is a perspective view of an electronic device according to various embodiments disclosed in the present document. FIG. 4b is a cross-sectional view of the electronic device shown in FIG. 4a taken along line B-B. In the following description, the same reference numerals as in FIGS. 3a to 3c are used for the same or similar components as those described in FIGS. 3a to 3c, and detailed descriptions thereof will be omitted.

(60) With reference to FIG. 4b, the speaker module 300 may be disposed in an inner space of the electronic device. The speaker module 300 may be disposed in the housing 401 of the electronic device so that the position thereof may be fixed. A plate 402 of the electronic device may be disposed in a first direction with respect to the speaker unit 310. The plate 402 of the electronic device may face the second speaker housing 330 of the speaker module 300. The display module 403 of the electronic device may be disposed in a second direction opposite to the first direction with respect to the speaker unit 310. The first direction may refer to a -Z direction on the basis of FIG. 4b, and the second direction may refer to a +Z direction on the basis of FIG. 4b. In an embodiment, in the second direction of the speaker unit 310, a front plate (not shown) supporting the electronic component (e.g., the display module 403) disposed in the housing of the electronic device or in the front direction of the electronic device (e.g., the +Z direction on the basis of FIG. 4b) may be disposed.

(61) According to various embodiments, the acoustic passage 410 may be a space provided between the housing 401 of the electronic device and the display module 403. In an embodiment, in the case that the housing or the front plate (not shown) of the electronic device is disposed in the second direction of the speaker unit 310, the acoustic passage may be a space provided between the housing or the front plate (not shown) of the electronic device. The acoustic passage 410 may be a space through which a sound radiated from the speaker unit 310 in the second direction is transmitted. The airtight member 340 of the speaker module 300 may be disposed between the acoustic passage 410 and the speaker unit 310. The airtight member 340 may seal the gap between the acoustic passage 410 and the speaker unit 310. The airtight member 340 may block external foreign substance or moisture that may be introduced through the acoustic passage 410 not to be transmitted between the acoustic passage 410 and the speaker unit 310. In another embodiment, the acoustic passage 410 may be a space provided between the device supporting the display module 403 and the housing 401 of the electronic device.

(62) According to various embodiments, as shown in FIG. 4a, an opening for radiating sound 411 may be an opening provided between the housing 401 of the electronic device and the display module 403. The opening for radiating sound 411 may connect the outside of the electronic device and the acoustic passage 410. In another embodiment, the opening for radiating sound 411 may be a space provided between the device supporting the display module 403 and the housing 401 of the electronic device.

(63) According to various embodiments, the sound radiated in the second direction of the speaker unit 310 may be transmitted to the acoustic passage 410 and output to the outside through the opening for radiating sound 411 connected to the acoustic passage 410. The sound radiated in the first direction of the speaker unit 310 may be radiated to the resonance space 350 formed by the first speaker housing 320 and the second speaker housing 330.

(64) FIGS. 5a to 5d are cross-sectional views of a speaker module and peripheral components thereof according to various embodiments disclosed in the present document. Hereinafter, differences from the speaker module and the electronic device described with reference to FIGS. 3a to 3c and FIG. 4b will be mainly described.

(65) According to various embodiments, as shown in FIG. 5a, the second speaker housing 330 of the speaker module 300 may be omitted. The first speaker housing 320 of the speaker module 300 may face the plate 402 of the electronic device. In this case, the resonance space 510 for a sound radiated in the first direction (e.g., -Z direction in FIG. 5a) of the speaker unit 310 may be a space surrounded by the first speaker housing 320 and the plate 402 of the electronic device.

(66) According to various embodiments, as shown in FIG. 5b, the speaker module **300** may include a conduit member **520** forming an acoustic passage **530**. The conduit member **520** may be coupled to the speaker unit **310** and form an acoustic passage **530** that transmits the sound radiated from the speaker unit **310** in the direction in which the opening for radiating sound (e.g., the opening for radiating sound **411** in FIG. 4b) is disposed. In this embodiment, the airtight member **540** may be disposed on the conduit member **520**. The airtight member **540** may be formed of a material having an elastic force. For example, the airtight member **540** may be formed of a material such as rubber, silicone, or liquid silicone rubber (LSR). The airtight member **540** may be formed in the conduit member **520** through a double injection method. The airtight member **540** may seal the gap between the conduit member **520** and the device in contact with the conduit member **520**.

(67) According to various embodiments, as shown in FIGS. 5c and 5d, the airtight member **550** may be disposed in the first speaker housing **320** of the speaker module **300**. The airtight member **550**, for example, may be disposed in the +Z direction on the basis of FIG. 5c in the first speaker housing **320** as shown in FIG. 5c, and it may be disposed in the +X direction and the -X direction on the basis of FIG. 5d in the first speaker housing **320** as shown in FIG. 5d. As such, the airtight member **550** may be disposed at a position capable of sealing the gap between the first speaker housing **320** and the housing **501** of the electronic device, and it may seal between the housing **501** and the first speaker housing **320** of the electronic device. The airtight member **550** may be formed of a material having an elastic force. For example, the airtight member **550** may be formed of a material such as rubber, silicone, or liquid silicone rubber (LSR). The airtight member **550** may be formed in the first speaker housing **320** through a double injection method.

(68) FIGS. 6a to 6c are diagrams for explaining a coupling relationship between a speaker unit and a first speaker housing according to various embodiments disclosed in the present document. The reference numbers of the speaker units described below use the reference numbers of the speaker units shown in FIGS. 2a and 2b.

(69) According to various embodiments, the speaker unit **200** may be coupled to the first speaker housing **320** in various ways. The shape of the speaker unit **200** may be variously changed in consideration of coupling with the first speaker housing **320**.

(70) For example, the yoke **250** of the speaker unit **200** may have a stepped design. As shown in FIG. 6a, the yoke **250** may include a first yoke part **250A** and a second yoke part **250B**. The thickness of the second yoke part **250B** may be smaller than the thickness of the first yoke part **250A**. A step may be formed between the first yoke part **250A** and the second yoke part **250B**. A portion of the first speaker housing **320** may be coupled to the second yoke unit **250B** of the yoke **250**. A portion of the first speaker housing **320** and the second yoke unit **250B** may be coupled in various ways. For example, the first speaker housing **320** and the second yoke unit **250B** may be bonded to each other by bonding using a material having an adhesive force.

(71) As another example, a portion of the first speaker housing **320** may be coupled to the unit frame **210** of the speaker unit **200**. The unit frame **210** of the speaker unit **200** may extend in the +Z direction on the basis of FIG. 6b to be coupled to a portion of the first speaker housing **320**. A portion of the first speaker housing **320** and the unit frame **210** may be coupled in various ways. For example, the first speaker housing **320** and the unit frame **210** may be bonded to each other by using a material having an adhesive force.

(72) As another example, a portion of the first speaker housing **320** may be coupled to the magnet **240** of the speaker unit **200**. The magnet **240** of the speaker unit **200** may extend in the X-axis direction on the basis of FIG. 6c. A portion of the first speaker housing **320** and the magnet **240** may be coupled in various ways. For example, the first speaker housing **320** and the magnet **240** may be bonded to each other by an adhesive material. In an embodiment, the portion coupled to the magnet **240** in the first speaker housing **320** may be formed of a material capable of shielding magnetic force.

(73) According to various embodiments, a sound may be radiated in a first direction (-Z direction

on the basis of FIGS. 6a to 6c) by vibration of the diaphragm included in the speaker unit **200**, and a sound may be radiated from the speaker unit **200** in a second direction (+Z direction on the base of FIGS. 6a to 6c) that is opposite to the first direction. The first speaker housing **320** may be coupled to the speaker unit **200**, and it may separate the space through which the sound radiated in the first direction is transmitted and the space through which the sound radiated in the second direction is transmitted so that the sound radiated in the first direction and the sound radiated in the second direction may not be canceled in meeting each other.

(74) An electronic device according to various embodiments disclosed in the present document comprises a speaker module which includes a speaker unit and a first speaker housing that is coupled to the speaker unit in a first direction and accommodates the speaker unit, and which is arranged in the inner space of the electronic device; an opening for radiating sound for allowing the inner space of the electronic device to communicate with the outside; and an acoustic passage for connecting the opening for radiating sound and a portion from which a sound is radiated by the speaker unit of the speaker module, wherein the speaker module can further include an airtight member for sealing a gap between the speaker module and the acoustic passage so that the sound radiated from the speaker unit is transmitted to the acoustic passage.

(75) In addition, the airtight member of the speaker module may be disposed in the first speaker housing.

(76) In addition, the speaker module may further include a conduit member forming the acoustic passage, and the airtight member of the speaker module may be disposed in the conduit member.

(77) In addition, the speaker module may further include a second speaker housing coupled to the first speaker housing in the first direction and a resonance space formed by the first speaker housing and the second speaker housing.

(78) In addition, at least one electronic component included in the electronic device may be disposed in the second speaker housing of the speaker module.

(79) In addition, an antenna of the electronic device may be disposed in the second speaker housing of the speaker module.

(80) In addition, the airtight member of the speaker module may include the airtight frame that is disposed on the speaker unit formed to correspond to the outer periphery of the speaker unit and the airtight part disposed in the airtight frame to seal the gap between the airtight frame and the acoustic passage and formed of a material having an elastic force.

(81) In addition, the speaker unit of the speaker module may include a unit frame, a diaphragm at least partially fixed to the unit frame, a voice coil coupled to the diaphragm, a magnet disposed adjacent to the voice coil, and a yoke accommodating the magnet.

(82) In addition, the yoke of the speaker unit of the speaker module may include a first yoke part and a second yoke part having a thickness smaller than a thickness of the first yoke part, and at least a portion of the first speaker housing of the speaker module may be disposed on the second yoke part of the yoke of the speaker unit.

(83) In addition, at least a portion of the first speaker housing of the speaker module may be disposed in a unit frame of the speaker unit.

(84) In addition, at least a portion of the first speaker housing of the speaker module may be disposed on a magnet of the speaker unit, at least a portion of which protrudes to an outer surface of the speaker unit.

(85) A speaker module according to various embodiments disclosed in the present document may further include a speaker unit, a first speaker housing that is coupled to the speaker unit in a first direction and accommodates the speaker unit, and an airtight member for sealing the acoustic passage connecting the speaker unit and a portion from which a sound is radiated by the speaker unit.

(86) In addition, the airtight member may include the airtight frame that is disposed on the speaker unit formed to correspond to the outer periphery of the speaker unit and the airtight part disposed in

the airtight frame to seal the gap between the airtight frame and the acoustic passage and formed of a material having an elastic force.

(87) In addition, the airtight member may be disposed in the first speaker housing.

(88) A conduit member forming the acoustic passage may be further included and the airtight member may be disposed on the conduit member.

(89) A second speaker housing coupled to the first speaker housing in the first direction and a resonance space formed by the first speaker housing and the second speaker housing may be further included.

(90) In addition, an antenna of an electronic device including the speaker module may be disposed in the second speaker housing.

(91) In addition, the speaker unit may include a unit frame, a diaphragm at least partially fixed to the unit frame, a voice coil coupled to the diaphragm, a magnet disposed adjacent to the voice coil, and a yoke accommodating the magnet.

(92) In addition, the yoke of the speaker unit may include a first yoke part and a second yoke part having a thickness smaller than a thickness of the first yoke part, and at least a portion of the first speaker housing may be disposed on the second yoke part of the yoke of the speaker unit.

(93) In addition, at least a portion of the first speaker housing may be disposed on a magnet of the speaker unit, at least a portion of which protrudes to an outer surface of the speaker unit

(94) Also, embodiments disclosed in the specification and drawings of this document are merely presented as specific examples to easily explain the technical content according to the embodiments of the disclosure and help an understanding of the embodiments of the disclosure, but they are not intended to limit the scope of the embodiments of the disclosure. Therefore, all changes or modifications derived from the technical ideals of the various embodiments of the disclosure should be interpreted to be included in the scope of the various embodiments of the disclosure in addition to the embodiments disclosed in the present document.

Claims

1. An electronic device comprising: a speaker module disposed in an inner space of the electronic device and including a speaker unit and a first speaker housing coupled to a first surface of the speaker unit; an opening for radiating sound connecting the inner space of the electronic device with an outside area external to the electronic device; an acoustic passage connecting the opening for radiating sound and a portion of a second surface of the speaker unit from which sound is radiated, the second surface being opposite to the first surface; and a resonance space formed by the first surface of the speaker unit and the first housing, wherein the speaker module further includes an airtight member which seals a gap between the speaker module and the acoustic passage so that the sound radiated from the second surface of the speaker unit is transmitted to the acoustic passage.
2. The electronic device of claim 1, wherein the airtight member of the speaker module is disposed at the speaker unit.
3. The electronic device of claim 1, wherein the speaker module comprises further a conduit member forming the acoustic passage, and the airtight member of the speaker module is disposed on the conduit member.
4. The electronic device of claim 1, wherein the speaker module comprises further a second speaker housing coupled to the first speaker housing, at least a portion of the second speaker housing facing the first surface of the speaker unit, and wherein the resonance space is formed by the first surface of the speaker unit, the first speaker housing, and the second speaker housing.
5. The electronic device of claim 4, wherein at least one electronic component is disposed at the second speaker housing of the speaker module.
6. The electronic device of claim 4, wherein an antenna of the electronic device is disposed at the

second speaker housing of the speaker module.

7. The electronic device of claim 1, wherein the airtight member of the speaker module comprises: an airtight frame corresponding to an outer periphery of the speaker unit and disposed at the speaker unit; and an airtight part disposed at the airtight frame to seal a gap between the airtight frame and the acoustic passage, the airtight part formed of a material having an elastic force.

8. The electronic device of claim 7, wherein the airtight frame is a single airtight frame having an opening configured to radiate the sound therethrough and towards the acoustic passage.

9. The electronic device of claim 7, wherein the airtight frame includes: a first airtight frame accommodating an outer periphery of the speaker unit; and a second airtight frame coupled in the first airtight frame portion, each of the first and second airtight frames having an opening configured to radiate the sound therethrough and towards the acoustic passage.

10. The electronic device of claim 1, wherein the speaker unit of the speaker module comprises: a unit frame; a diaphragm at least partially fixed to the unit frame; a voice coil coupled to the diaphragm; a magnet disposed adjacent to the voice coil; and a yoke accommodating the magnet.

11. The electronic device of claim 10, wherein the yoke of the speaker unit of the speaker module comprises: a first yoke part having a first thickness; and a second yoke part having a second thickness smaller than the first thickness of the first yoke part, wherein at least a portion of the first speaker housing of the speaker module is disposed on the second yoke part of the yoke of the speaker unit.

12. The electronic device of claim 10, wherein at least a portion of the first speaker housing of the speaker module is disposed on the unit frame of the speaker unit.

13. The electronic device of claim 10, wherein at least a portion of the first speaker housing of the speaker module is disposed on the magnet of the speaker unit, at least a portion of which protrudes toward an outer surface of the speaker unit.

14. The electronic device of claim 1, further comprising: a display module covering the speaker housing.

15. A speaker module comprising: a speaker unit; a first speaker housing coupled to a first surface of the speaker unit; and an acoustic passage extending from the speaker unit to radiate sound from a second surface of the speaker unit, the second surface being opposite to the first surface; a resonance space formed by the first surface of the speaker unit and the first housing; and an airtight member sealing a gap between the speaker unit and the acoustic passage so that the sound radiated from the second surface of the speaker unit is transmitted to the acoustic passage.

16. The speaker module of claim 15, wherein the airtight member comprises an airtight frame formed to correspond to an outer periphery of the speaker unit and disposed on the speaker unit.

17. The speaker module of claim 15, wherein the airtight member is disposed at the first speaker housing.

18. The speaker module of claim 15, further comprising a conduit member forming the acoustic passage, wherein the airtight member is disposed on the conduit member.
