

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278713

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Dhodapkar; Ashutosh Sham et al.

CONTEXT-BASED ACTIONS USING INTERACTIVE ELEMENTS

Abstract

In one aspect, a method includes configuring, a graphical user interface of an application executing on a first electronic device to provide instructions for scanning an interactive element; detecting, on the graphical user interface, that the interactive element is scanned; determining whether a token associated with the interactive element is claimed; updating the graphical user interface on the first electronic device for claiming the token associated with the interactive element; updating the graphical user interface on the first electronic device to receive one or more actions to be triggered when the interactive element is interacted with using a second electronic device; detecting one or more inputs on the graphical user interface indicative of the one or more actions; and updating, at the payment service system, a database to include the interactive element, the token claimed, and the one or more actions in association with the interactive element.

Inventors: Dhodapkar; Ashutosh Sham (Fremont, CA), Dai Zovi; Dino (Brooklyn, NY)

Applicant: Block, Inc. (Oakland, CA)

Family ID: 82323824

Appl. No.: 19/195806

Filed: May 01, 2025

Related U.S. Application Data

parent US continuation 17824273 20220525 parent-grant-document US 12321919 child US 19195806

parent US continuation 16698613 20191127 parent-grant-document US 11386418 child US 17824273

Publication Classification

Int. Cl.: G06Q20/32 (20120101); G06Q20/36 (20120101)

Background/Summary

PRIORITY [0001] This application which is a continuation of U.S. Non-Provisional patent application Ser. No. 17/824,273, entitled CONTEXT-BASED ACTIONS FROM MATRIX CODES, filed May 25, 2022, which is a continuation of U.S. Non-Provisional patent application Ser. No. 16/698,613, entitled DYNAMIC ACTIONS FROM MATRIX CODES, filed Nov. 27, 2019, now U.S. Pat. No. 11,386,418, the contents of which are incorporated herein by reference in their entireties.

BACKGROUND

[0002] Matrix barcodes, also known as two-dimensional barcodes, are machine-readable optical labels that may store a variety of information. Often, matrix barcodes store information about an object to which it is attached. Because of their two-dimensional nature, matrix barcodes can store significantly more information than a standard barcode. Increasingly, matrix barcodes have found a use in payments technology. A matrix barcode may be generated to include information about a transaction, such as the identity of the payee, an amount of the transaction etc. In this usage, the details of the transaction must often be known prior to the creation of the matrix barcode, because traditional matrix barcodes cannot be modified to include updated information.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Features of the present disclosure, its nature and various advantages, will be more apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings.

[0004] FIG. 1 illustrate an example payment service system network as described herein.

[0005] FIG. 2 illustrates an example system architecture for a payment service system as described herein.

[0006] FIG. 3 illustrates an example method for associating a pre-generated matrix barcode with a specified account action.

[0007] FIGS. 4A-4C illustrate example user interfaces relating to associating a pre-generated matrix barcode with an account action.

[0008] FIG. 5 illustrates an example method for modifying an account action associated with a pre-generated matrix barcode.

[0009] FIG. 6 illustrates an example method for modifying an account action associated with a pre-generated matrix barcode.

[0010] FIG. 7 illustrates an example method for initiating an account action based on interaction with a matrix barcode.

[0011] FIGS. 8A-8D illustrate example user interfaces relating to interacting with a matrix barcode to perform account actions.

[0012] FIG. 9 illustrates an example method for performing actions based on interactions with a matrix barcode.

[0013] FIG. 10 illustrates an example computer system.

DESCRIPTION OF EXAMPLE EMBODIMENTS

[0014] Particular embodiments described herein enable a user of an appropriate service to specify

actions to be performed by a computing system or systems when interaction with a matrix barcode is detected. Particular embodiments described herein enable a user to register or claim a matrix barcode to be associated with their requested action. The matrix barcode may have been generated by a party other than the user prior to the user requesting that the matrix barcode be associated with their requested action. In particular embodiments, the requested action may involve manipulation of or interaction with an account associated with the user, for example a payment account. In particular embodiments, the requested action may involve manipulation of or interaction with an account of a user that interacts with the matrix barcode. In particular embodiments, the requested action may involve a third-party account (e.g., one associated with neither the claiming nor interacting user). As an example and not by way of limitation, a user may specify that interaction with a chosen matrix barcode facilitates transfer of a specified amount of money to the payment account of the user from an account of the interacting user.

[0015] In contrast to previous techniques associated with matrix barcodes, the actions specified by the user can be arbitrarily specified after the matrix barcode has been created and embodied in or affixed to digital media (e.g., an image shown on a mobile device screen) or physical media (e.g., a sticker or paper flyer). In some previous systems, a user would specify text for a matrix barcode, such as a URL to be launched when the matrix barcode is interacted with (e.g., scanned by an appropriately configured computing device). That text would then be used to generate the matrix barcode itself. In contrast, embodiments described herein enable a user to receive a pre-generated barcode and specify the actions to be performed when the barcode is interacted with. Particular embodiments described herein further enable a user to change the action associated with the matrix barcode after making an initial selection of an action. Thus, embodiments described herein enable a single matrix barcode (or a single matrix barcode design) to be repeatedly re-used by the same user for a variety of different purposes. As will be appreciated, dynamically- and user-specified actions to be performed after detection of interaction with a matrix barcode allow for more efficient allocation and use of matrix barcodes for a host of actions.

[0016] Particular embodiments disclosed herein enable the user to specify a range of actions to be associated with a pre-generated matrix barcode based on information relating to the context of interaction with the matrix barcode. A device or application that interacts with the matrix barcode may report information associated with the time or place of the interaction, the identity of a user associated with the device, information associated with the user of the device and stored by the device or one or more third-party systems, and any other information that may inform the context of interaction with the matrix barcode. As will be appreciated, in addition to the advantages of dynamically-specified actions, the use of contextual information associated with the interaction with a matrix barcodes provides for even greater functionality of systems employing matrix barcodes to facilitate services to, and between, users.

[0017] Particular embodiments described herein enable the use of techniques to verify the identity of devices interacting with a matrix barcode. A computing system may log such interactions and use the information to provide recommendations for interactions or updates to interactions. Prior to the initiation of an action subsequent to interacting with a matrix barcode, the computing system may also verify the identity of an individual associated with a device that has interacted with a matrix barcode. Identity verification may prevent unwanted actors from performing the associated action. Additional embodiments described herein provide for matrix barcodes that are encrypted or randomized to avoid including sensitive information in the plaintext of the matrix barcode. For example, the matrix barcode itself may include a randomized token that is associated with token associated with a user's account. Thus, a user may manage matrix barcodes associated as needed with a particular token and may manage many tokens associated with their account. A system relying on randomized tokens, as described herein, provides additional security benefits in that the barcodes and tokens are difficult to counterfeit, because only the centralized manager knows that a randomized string is associated with a matrix barcode and/or a claimed token. The centralized

manager can control and deny access to actions accordingly.

[0018] Particular embodiments described herein describe variations on matrix barcodes and associated seeds. The seed or source from which a matrix barcode is generated may be configured to include information about the medium to which a matrix barcode is affixed. For example, a seed for a matrix barcode may include a so-called channel code that identifies the media. Thus a single token may be distributed with a number of varying channel codes corresponding to, for example, whether a matrix barcode was affixed to varieties of physical media or digital media. Channel codes may be used to identify advertising techniques or campaigns and can be used to track impressions generated by the campaigns, on a more granular level than a simple barcode association. Because the embodiments described herein support the association of pre-generated matrix barcodes to particular user accounts and account actions, the embodiments described herein facilitate the efficient mass production of physical media that uses the matrix barcodes. As described herein, this greatly improves the efficiency of systems employing these matrix barcodes.

[0019] Particular embodiments described herein relate to methods of improving the performance or rate of return from interactions with particular matrix barcodes. Systems employing the embodiments described herein may provide recommendations to users to improve the success of actions after a user has interacted with the matrix barcode based on information available to the system, but not necessarily any of the particular users. For example, one particular interaction with a matrix barcode may be to request that the interacting user transfer funds to the user who has claimed the matrix barcode and associated token. For example, a barista may have set up a matrix barcode as a digital tip jar. A payments service system may analyze, among other factors, a transaction history associated with the matrix barcode (for example, including transactions initiated based on interaction with the matrix barcode), a merchant at the same location of the matrix barcode, and the customers of the merchant (including those who do not interact with the matrix barcode) to determine a recommendation for improving the tips awarded to the barista. The payment service system may have access to a variety of transactional information related to the spending and money-transferring habits of the users of a payment service. For example, the payment service system may be able to compare transactions stemming from different barcodes for the purpose of determining effective additional messages or transaction amounts. The payment service system may identify trends in the available data that are relevant to the barista or to tipping in that location. The payment service system may provide recommendations based on commonalities between transaction amounts (or other action signifiers) associated with different tokens and corresponding matrix barcodes. The payment service system may provide recommendations responsive to particular performance indicators, such as amount of money transferred to the barista or number of transactions completed. These performance indicators may be specified by the user or may be applied on a system-wide level.

[0020] The payment service system described herein includes significant technical advantages and improvements over previous systems. As but one example of the technical advantages and improvements, the payment service system described herein enables distribution of functionality within a network to enhance the performance of matrix barcode-based systems and systems that interact with matrix barcodes generally. The system described herein allows for devices optimally situated to handle steps of the procedures described herein (based on, e.g., computing performance, available power usage, detected network availability) to perform those steps. As another example of the technical advantages and improvements, the present system enables enhanced security performance of matrix barcode-based systems and systems incorporating matrix barcodes because the matrix barcodes are linked to tokens stored in a centralized data structure maintained by the system to control access. Functionality of these systems is further improved because the centralized storage allows for the matrix barcodes to be reprogrammed, remapped, or reconfigured as needed for security or functionality reasons.

[0021] The embodiments disclosed herein are only examples, and the scope of this disclosure is not

limited to them. Particular embodiments may include all, some, or none of the components, elements, features, functions, operations, or steps of the embodiments disclosed above. Embodiments disclosed in the attached claims directed to a method, a storage medium, a system and a computer program product, wherein any feature mentioned in one claim category, e.g., method, may be claimed in another claim category, e.g., system, as well. The dependencies or references back in the attached claims are chosen for formal reasons only. However, any subject matter resulting from a deliberate reference back to any previous claims (in particular multiple dependencies) may be claimed as well, so that any combination of claims and the features thereof are disclosed and may be claimed regardless of the dependencies chosen in the attached claims. The subject matter which may be claimed comprises not only the combination of features as set out in the attached claims but also any other combination of features in the claims, wherein each feature mentioned in the claims may be combined with any other feature or combination of other features in the claims. Furthermore, any of the embodiments and features described or depicted herein may be claimed in a separate claim and/or in any combination with any embodiment or feature described or depicted herein or with any of the features of the attached claims.

[0022] FIG. 1 illustrates an example payment service system network environment **100**. A user **104** or “customer **104**” may conduct transactions with a merchant **102** for items **106** offered by the merchant **102**. The user **104** may also conduct transactions with a second user **154**, possibly for items **106** offered by the user **154**. The user **104** may use a user device **103**, the merchant **102** may use a point-of-sale (POS) device **105**, and the user **154** may use a user device **152**. FIG. 1A also illustrates a payment service system **108** (also referred to as “payment service”), coupled to the user devices **103** and **152** and merchant POS device **105** via a network **110-1**, to authorize payment instruments of user **104**. User **104** may engage in transactions with merchant **102** to obtain items **106**. User **104** may provide, as shown at **112**, payment instruments to merchant **102**, including cash, credit, check, or other suitable payment instruments along with requests for items or services offered by merchant **102** or user **154**.

[0023] Merchant **102** may utilize POS device **105** for accepting payment from customer **104**. POS device **105** may comprise any sort of mobile or non-mobile devices that include instances of a merchant application that executes on the devices. The merchant application may provide POS functionality to POS device **105** to enable merchant **102** (e.g., owners, employees, etc.) to accept payments from customers **104**. In some types of businesses, POS device **105** may correspond to a store or other place of business of the merchant, and thus, may be a fixed location that typically does not change on a day-to-day basis. In other types of businesses, however, the location of POS device **105** may change from time to time, such as in the case that a merchant operates a food truck, is a street vendor, is a cab driver, etc., or has an otherwise mobile business, e.g., in the case of a merchant who sells items at buyer's homes, places of business, and so forth.

[0024] User **154** may use mobile device **152** for accepting payment from customer **104**. Mobile device **152** may be executing an instance of an application **153** associated with the payment service **108**. The instance of the payment application **153** may provide wallet or even POS functionality to the user device **152** to enable user **154** to accept payments from other users **104**.

[0025] As used herein, a merchant may include any business engaged in the offering of goods or services for acquisition by customers. Actions attributed to a merchant may include actions performed by owners, employees, or other agents of the merchant, and thus no distinction is made herein unless specifically discussed. In addition, as used herein, a customer may include any entity that acquires goods or services from a merchant, such as by purchasing, renting, leasing, borrowing, licensing, or the like. Hereinafter, goods and/or services offered by merchants may be referred to as items, e.g., item **106**. Thus, a merchant and a customer may interact with each other to conduct a transaction in which the customer acquires item **106** from merchant **102**, and in return, customer **104** provides payment **112** to merchant **102**.

[0026] As used herein, a transaction may include a financial transaction for the acquisition of

item(s) that is conducted between customer **104** and merchant **102**. For example, when paying for a transaction, customer **104** may provide the amount that is due to the merchant using cash or other payment instrument **112** (e.g., a debit card, a credit card, a stored-value or gift card, a check, through an electronic payment application **107** on device **103** carried by the customer, or the like). The merchant may interact with POS device **105** to process the transactions, such as by inputting (e.g., manually, via a magnetic card reader, NFC reader, or an RFID reader, etc.) identifiers associated with payment instrument **112**. For example, a payment instrument of the customer may include a card having one or more magnetic strips for providing card and customer information when swiped in a card reader. In other examples, other types of payment instruments may be used, such as smart cards having a built-in memory chip that is read by the device when the card is inserted into the reader, such as chips that comply with the EMV standard, i.e., EMV smartcards. In other examples, other types of payment instruments include cards or computing devices that communicate via radio frequencies such as a radio frequency identification tags, and near field communication devices, etc. As appropriate, transaction may also include the transfer of funds from a first user **104** to a second user **152** for items **106**, services, or without a corresponding item at issue. For example, a user **104** may send a user **152** money as a gift through the instance of the payment application **107** executing on the mobile device **103** of the user **104**.

[0027] During a transaction, POS device **105** (or mobile device **152** with an appropriate instance of the payment application **153**) may determine transaction information describing the transaction, such as the identifier of the payment instrument, an amount of payment received from the user **104**, the item(s) acquired by the user **104**, a time, place and date of the transaction, a payment network **140** associated with the payment instrument, an issuing bank of the payment instrument, a name or user account of the user **104**, contact information of the user **104**, type of the currency, and so forth. POS device **105** (or mobile device **152**) may send the transaction information to payment service system **108** over network **110-1**, either substantially contemporaneously with the conducting of the transaction (in the case of online transactions) or later when POS device **105** (or mobile device **152**) is in the online mode (as in the case of offline transactions).

[0028] In an offline transaction, POS device **105** or the payment application **153** may store one or more characteristics associated with the transaction (i.e., the transaction information), such as a cost of the transaction, a time of day at which the transaction occurred, a day of the week at which the transaction occurred, a location at which the transaction took place, an item that the user **104** obtained, identity and/or contact information of the user **104**, and a payment instrument used in the transaction. After conducting an offline transaction with user **104**, POS device **105** may provide the stored information (or some subset of it) to the payment service system **108** over the network **110-1**. The network **110-1** may represent any one or more wired or wireless networks, such as a Wi-Fi network, a cellular network, or the like. In an online transaction, POS device **105** or mobile device **152** may send this information to payment service system **108** over network **110-1** substantially contemporaneously with the transaction with the user **104**.

[0029] After merchant **102** or user **154** receives the payment information from customer **104**, they may send respective authorization requests, along with information regarding the respective transactions, to payment service system **108**, as illustrated at **114**. Payment service system **108** may include payment processing service **126**, merchant profiles **130**, customer profiles **132**, and other support information, such as a token association structure **134**. Here, the merchant profiles **130** may comprise information about one or more merchants using the payment service system **108**. The customer profiles **132** may comprise information about one or more customers using the payment service system **108**. Each merchant or customer may otherwise be called a user of the payment service system **108**. A particular user may be a merchant, a customer, or either depending on the use case. As described herein, the token associations structure **134** may store information associating matrix barcodes with tokens and requested actions.

[0030] The payment processing service **126** may receive the information regarding a transaction

from POS device **105** of merchant **102** or the instance of the payment application **153** executing on the mobile device **152** and attempt to authorize the payment instrument used to conduct the transaction. Payment processing service **126** may then send an indication of whether the payment instrument has been approved or declined back to the requesting device, as illustrated at **116**.

[0031] When a user and a merchant enter into an electronic payment transaction, the transaction may be processed by electronically transferring funds from a financial account associated with the user to a financial account associated with the merchant or other user. As such, the payment processing service **126** may communicate with one or more computing devices of a payment card network **140** (or “card payment network”) over network(s) **110-2** to conduct financial transactions electronically. Payment processing service **126** may also communicate with one or more computing devices of one or more banks, processing/acquiring services, or the like over the network **110-2**. For example, payment processing service **126** may communicate with an acquiring bank, and/or an issuing bank, and/or a bank maintaining customer accounts for electronic payments. Payment processing service **126** may also communicate with, or access customer and merchant accounts maintained by payment service system **108**.

[0032] An acquiring bank may be a registered member of a card association and may be part of a card payment network **140**. An issuing bank may issue credit cards to buyers and may pay acquiring banks for purchases made by cardholders to which the issuing bank has issued a payment card. Accordingly, in some examples, the computing device(s) of an acquiring bank may be included in the card payment network and may communicate with the computing devices of a card-issuing bank to obtain payment. Further, in some examples, the customer may use a debit card instead of a credit card, in which case, the bank computing device(s) of a bank corresponding to the debit card may receive communications regarding a transaction in which the customer is participating. Additionally, there may be computing devices of other financial institutions involved in some types of transactions or in alternative system architectures, and thus, the foregoing are merely several examples for discussion purposes.

[0033] In transactions involving cryptocurrency, payment service system **108** may communicate over network(s) with one or more cryptocurrency networks. Such networks may include for example, the Bitcoin network, the Ethereum network, etc. Cryptocurrency networks are associated with a network of parties that cryptographically verify and validate transactions and record transactions on copies of a distributed ledger commonly called the blockchain. Once a transaction has been validated, a cryptocurrency network may approve the transaction by writing the transaction to the blockchain. The time for such processes to complete may be impractically long for many applications.

[0034] Networks **110-1** and **110-2** may represent any one or more wired or wireless networks, such as a Wi-Fi network, a cellular network, a wide area network, a local area network, or the like. For the purposes of illustration, networks **110-1** and **110-2** are shown as separate networks. In particular embodiments, networks **110-1** and **110-2** may be the same network, subnets of the same network, one or more separate networks, or other suitable arrangement.

[0035] While FIG. 1 illustrates merchants **102** and users **154** sending the transaction data directly to the payment service system **108** as part of the request to authorize the payment instrument, in some instances other entities (e.g., banks associated with the merchants or with customer payment instruments) may provide transaction data, such as part of a batched, periodic process.

[0036] While customer profiles **132** may store indications of user preferences, merchant profiles **130** may store information associated with respective profiles of the merchants **102**. For instance, the merchant profiles **130** may indicate a class of items offered by respective merchants (e.g., coffee items, collectibles, apparel, etc.), a type of business of the merchant (e.g., restaurant, coffee shop, retail store, etc.), a geographical location of the merchant, and the like.

[0037] In some instances, a computing device associated with the merchant (e.g., POS device **105**, servers of the merchant, etc.) or user **154** may determine when the customer visits physical

premises or a digital presence of the merchant or is in the vicinity of the user **154**. For instance, the device **103** of the customer **104** may include an application **107** (e.g., an application provided by payment service system **108**) that communicates with POS device **105** of merchant **102** or mobile device of the user **154** via near-field communication methods (e.g., Bluetooth, etc.). Therefore, when the customer visits the physical premises of merchant **102**, for example, POS device **105** may detect the presence of customer device **103**. The POS device may accordingly determine that the customer is present. In another example, POS device **105**, mobile device **152**, and user device **103** may share locations (e.g., GPS coordinates) to a common service for determining when the devices are located within a threshold proximity of one another, and for mediating a transaction between customer device **103** and POS device **105** or mobile device **152**.

[0038] In another example, customer **104** may utilize customer device **103** to “check in” at a merchant location, and POS device **105** may receive an indication of this check in. When the customer visits a digital presence of merchant **102** (e.g., a website, etc.), customer **104** may log in or otherwise provide information (e.g., a cookie on the device **103**) from which the merchant determines that the customer is at the merchant. Of course, while a few examples are listed, it is to be appreciated that the merchant and/or payment service system **108** may determine when the customer is present at the merchant in any other number of ways. In each instance, after payment service system **108** receives an indication that customer **104** is located at merchant **102**, the payment service system **108** may determine whether to send one or more previously expressed item preferences of the customer to the merchant.

[0039] In addition, customer **104** may desire to receive an instance of a payments application **107**, such as a mobile wallet application, from the payment service system **108**. FIG. 1 illustrates, at **118**, that the customer **104** may send payment-application requests to payment service system **108**. In response, at **120**, payment service system **108** may provide instances of the application **107** back to customer device **103**. In addition, payment service system **108** may map an identification of the instance of the application **107** to the customer profile.

[0040] In some embodiments, one or more of the applications **153** and **107** may be point-of-sale applications. In some embodiments, one or more of the applications **153** and **157** may be mobile wallet applications. In some embodiments, one or more of the applications **153** and **157** may be applications provided by a third party capable of accessing at least one payment account. The present technology contemplates that currency or assets may be sent from any party of any character (merchant, user, bank, etc.) to any other party of any character using the innovations described herein.

[0041] The payment service system **108**, in coordination with the POS system **105**, payment applications **153** and **107** allows, for a more expansive array of payment options, transactions that are completed more quickly and accurately by reducing the communication and processing times needed for computing systems of various parties to authorize and process the transactions and simplifies the interactions and interfaces that a user must engage with in order to prepare and request the transactions. Taken together, these improvements amount to an overall improvement over previous payment processing systems and related devices. The payment service system therefore includes significant technical advantages and improvements over previous devices. As but one example of the technical advantages and improvements, the present system enables distribution of functionality within a network to enhance the performance of matrix barcode-based systems and systems that interact with matrix barcodes generally. As another example, of the technical advantages and improvements, the present system enables enhanced security performance of matrix barcode-based systems and systems incorporating matrix barcodes because the matrix barcodes are linked to tokens stored in a centralized data structure maintained by the system to control access. Functionality of these systems is further improved because the centralized storage allows for the matrix barcodes to be reprogrammed, remapped, or reconfigured as needed for security or functionality reasons.

[0042] FIG. 2 illustrates an example system architecture for a payment service system **108** embodying aspects of the inventions described herein. In particular embodiments, the payment service system **108** may store customer profile **132** for each of a plurality of customers. Customer profile **132** may include customer data **201** that may include customer-identifying information (name, contact information, demographical data, etc.), a transaction log **202** including records of past transactions involving payment service system **108** by customer **104**, information regarding linked accounts (credit card information, bank account information, securities accounts, etc.), information regarding services utilized by customer profile **132** (e.g., an instance of a mobile wallet application). The customer data **201** may further comprise information associated with one or more social or peer-to-peer contacts of a user (e.g., friends, family members, online network connections). The information may comprise at least part of the profile information of such contacts.

[0043] The customer profile **132** may also include a record **204** for any accounts managed by payment service system **108** on behalf of customer **104**. It will be appreciated that customers having accounts managed by the payment service system **108** is an aspect of the technology that enables technical advantages of increased processing speed and improved security. For example, the customer profile **132** may include a currency account **204**. The currency account **204** may include information regarding one or more separate accounts of the user that each include currency owned by the customer. The currency account may include information regarding any valid payment method managed by the payment service system **132** on behalf of the customer, including, but not limited to, fiat currency, cryptocurrency, securities, etc. The currency accounts **204** may include a logical division of currency held by the payment service system **108** that is allocated for the customer's use.

[0044] An account may be funded by transferring currency in the form associated with the account from an external account (e.g., transferring a quantity of cash to payment service system **108**), or by purchasing currency in the form associated with the account from the payment service system **108** using currency in a different form (e.g., buying a value of a security asset from payment service system **108** using a value of fiat currency), or by conducting a transaction with another user (customer or merchant) of the payment service system **108** wherein the account receives incoming currency. An account may be funded by purchasing security assets via the payment service system **108**. When a customer requests to purchase security assets from the payment service system **108**, the payment service system **108** may debit a balance stored in the currency account **204** of a certain type and credit a balance stored in a security account. The customer profile **132** may also comprise preference settings as to a preferred asset for payments (e.g., a preference to use a particular currency to pay for day-to-day transactions).

[0045] Similarly, as introduced with respect to FIG. 1 payment service system **108** may store merchant profiles **132**. The merchant profiles **132** may comprise merchant data **207**, transaction log **208**, and currency account **210**. The merchant data **207** may comprise one or more preference settings associated with the merchant **102**, such as a type of currency or asset that the merchant prefer to receive as payment. The information stored in the merchant profile **132** may be made accessible and managed by a merchant **102** through a POS device **105** or other suitable devices associated with the merchant **102**. Operations, including maintenance and management operations, described with respect to the customer profile **132** and information included therein (e.g., the customer data **201**, transaction log **202**, currency account **204**) are as much applicable to the merchant profile **132** and the information included therein (e.g., the merchant data **207**, transaction log **208**, currency account **210**).

[0046] When two users (e.g., users **150** and **154**) engage in a transaction that involves a transfer of assets, such a transaction may be reflected in the accounts associated with each customer's profile **132**. As an example and not by way of limitation, a first user **104** may transfer a quantity of currency (e.g., fiat currency, cryptocurrency, security assets, etc.) to a second user **154**. The

payment service system **108** may accordingly debit the currency account **204** of the first user **150** and credit the currency account **204** of the second user **154**.

[0047] Additionally, customer **104** may also have one or more external payment cards registered with payment service system **108**. The external payment cards may be associated with external bank accounts **222**. The external payment card accounts may not be managed by payment service system **108**. Instead, an appropriate external payment network **224** may process transactions conducted with payment cards.

[0048] Additionally, customer **104** may also have one or more internal payment cards registered with payment service system **108**. Internal payment cards may be linked to all accounts associated with customer profile **132**. In some embodiments, options with respect to internal payment cards may be adjusted and managed using a payment application **107** installed on the customer device **103**. For example, when customer profile **132** includes multiple payment accounts (e.g., cryptocurrency and fiat currency), application **107** may set one of those accounts to be the default account for debits or credits when using an internal payment card.

[0049] Customer **104** may access and monitor customer profile **132** including payment cards registered with payment service system **108** and currency account **204** through the application **107** installed on the customer device **103**. The application **107** may be a customer facing application provided by payment service system **108**, or that is configured to access customer profile **132** through use of one or more APIs provided by payment service system **108**. In some embodiments, application **107** on the customer device **103** may provide digital wallet functionality including storing payment methods and permitting electronic payments by customer device **103** at the instruction of application **107**.

[0050] In particular embodiments, the payment service system **108** may maintain a token association data structure **134**. The payment service system **108** may use said structure **134** to provide a matrix barcode association service as described herein. The token association structure **134** may require generation and storage of a plurality of matrix barcodes **230** and corresponding tokens **232**. Tokens may be uniquely-assigned random or pseudo-random character strings generated by the payment service system **108**. Matrix barcodes may be generated based on the tokens (e.g., from a matrix barcode-generation algorithm). To identify a corresponding token, all that will be required is to decode (and possibly decrypt) the matrix barcode. Matrix barcodes may be generated from another set of uniquely-assigned random or pseudo-random character strings. The matrix barcodes (and corresponding strings) may be stored in association with a corresponding token. Thus, the matrix barcode database **230** and token **232** database may be linked as jointly maintained databases. To identify the token corresponding to a matrix barcode, the matrix barcode must first be decoded, then the payment service system **108** must determine the token corresponding to the decoded matrix barcode string. It will be appreciated that stored corresponding tokens within the control of the payment service system, rather than making them purely executable or plaintext storage enhances the security and flexibility of previous technologies. The payment service system may provide users the option to re-map existing matrix barcodes between different claimed tokens, and especially to associated dynamically-assigned actions to claimed tokens.

[0051] Token database **232** may store links to customer profiles **132** and/or customer accounts that are associated with a claimed token. A token may be considered claimed when it associated with an account or an account action. An unclaimed token may be available to be claimed by a user with a valid account who interacts with the claimed token. As described herein, interacting with a token may include interacting with a matrix barcode that corresponds to the token.

[0052] Token association data structure **134** may also include storage of account actions **234** to be performed after interaction with a matrix barcode and corresponding token. Account actions may include specification of particular actions for the payment service system **108** to take upon detection of interaction with the associated token. Account actions may involve one or more

customer profiles **132** or accounts. For example, an account action may involve only the account of the user that interacted with the token. Such account actions may include the creation of an association between the account of the interacting user and the token. An account action may include only the account of the user to whom the token is claimed. Such account actions may include sending a notification to the user or logging the interaction. Account interactions may include the account of the user to whom the token is claimed and the account of the interacting user. Such account actions may include the transfer of funds between one or more of the accounts (or the request for confirmation for such a transfer). An account action may involve a third-party account (e.g., neither the account of the interacting user nor the account to which the token is claimed).

[0053] Token association data structure **134** may also include storage of customer profiles **216** affiliated with a matrix barcode and corresponding token. The customer profiles database **216** may be updated with the customer profile or an identifier for a customer profile that has claimed a particular token (e.g., that has an updated record in the token database **232**) and matrix barcode (e.g., that has an updated record in the matrix barcode database **230**). In addition to claiming a token, an affiliated customer profiles may also be a customer profile that is the beneficiary or target of an account action that is not the customer profile that claimed the matrix barcode and claimable token. The customer profile database **216** of the token association data structure **134** may be linked to the customer profiles **132**. The token association data structure **134** therefore provides and records links between the stored matrix barcodes **230**, claimable and claimed tokens **232**, associated account actions **234**, and customer profiles **216**.

[0054] Although this disclosure describes the token association and matrix barcode matching service being maintained operated by the payment service system **108**, this disclosure contemplates that matrix barcode and token association may be operated by a separate system associated with the payment service system **108** controlled by the provider of the payment service or by a third-party. Combining the matrix barcode association service with the payment service may increase speed and reliability of access to the associated account actions. Maintaining the matrix barcode association service as a separate service from the payment service (e.g., accessible via one or more APIs) may provide for greater security to the payment service system.

[0055] Matrix barcodes may be generated using a variety of proprietary or publicly-available methods. One common approach is the Quick-Response or QR code which has been governed by a number of international standardized systems since it was first devised. Generally speaking, generating a matrix barcode includes taking in a seed as an input, validating the input, and converting it into a two-dimensional matrix barcode such that the output is uniquely matched to the input and vice versa. Thus, a system that is capable of interpreting the matrix barcode can reliably reconstruct the input from the matrix barcode. The input may be in a variety of suitable data formats, but common approaches include a plaintext string, a URL, a contact information card, login information, payment account information, a geographic location, calendar events, and other similar static information. The range of inputs tends to be restricted by the drive to universal adoption of a set of standards governing the use of matrix barcodes. Once a matrix barcode has been generated, it cannot be modified, for example, to update the information associated with that matrix barcode. Instead, a brand new matrix barcode must be generated.

[0056] To interpret the matrix barcode, it is imaged by a digital image sensor and analyzed by a computer processor. The matrix barcode is analyzed to determine the correct orientation of the matrix barcode. The image is normalized (e.g., for size, angle of viewing) and the elements of the matrix barcode are converted to binary code and validated using error-correction methods. From the binary numbers the input is determined. Depending on the application of the matrix barcode, some action may be taken. For example, the text string may be displayed, a phone call initiated based on a contact card, or a URL may be launched in a web browser. If the input was specially coded to work with a particular application, the application may be launched in response to the

execution of the inputs (e.g., through deeplinking). In some cases, the input may have been subject to additional encryption or encoding methods. The application interpreting the matrix barcode often is responsible for determining the encryption mechanism and decrypting the input or passing the binary code to another application that is capable of doing so.

[0057] In particular embodiments, when generated, each matrix barcode may be associated with a token uniquely identifying the matrix barcode. For example, the token may first be generated, with the matrix barcode generated based on the token (e.g., the token is the seed input). As another example, the matrix barcode may be generated from a randomized value (e.g., a random string or number) and an existing token may be associated with the barcode (e.g., the image) or the randomized value associated with the barcode (e.g., so that a system could re-generated the matrix barcode on-demand). The token and the matrix barcode may be stored in association in a database of a matrix barcode-identification system. Thus, to determine the token associated with a matrix barcode (or vice versa), the database may be queried with the matrix barcode. The token associated with the matrix barcode may be provided as the corresponding token.

[0058] The token corresponding to a matrix barcode may be used for a wide variety of purposes. The token may be associated with essentially arbitrary secondary information or commands that can be assigned at a later date. Because the token can be “re-programmed” or associated with a new command at a time after the creation of the matrix barcode, the barcodes may be referred to as “dynamic matrix barcodes” to differentiate from previous “static” matrix barcodes. For example, the token may be associated with contact information, a URL, payment account information, a text string, a workflow or sequence of commands, etc. Importantly, while the value of the token may change, the secondary information may be modified without affecting the value of the token or the appearance of the matrix barcode. Thus, a single matrix barcode may be used repeatedly for any number of uses without needing to be rewritten. As a simple example, a student could affix a matrix barcode to a business card and associate with the token with a command to provide a URL to the student's social media page. When the student begins interviewing for jobs, the student may update the command to provide a URL to download the student's resume. Later, the student may update the command to provide a URL to the webpage on their new employer's website. All of this may be done without the student needing to reprint business cards at each step of the way.

[0059] These principles may be used in a variety of industries. An advertising company may use a single matrix barcode for a company and update the associated command based on the advertising campaign run for the company. A teacher may use a single matrix barcode for a class and update the command to provide a link to the latest reading assignment. A payment service may provide matrix barcodes for use by customers who may associate the barcodes with methods of requesting or sending payment. For example, a store may use a different matrix barcode for each space on a shelf and update the information provided (e.g., information on the item or a link to pay for the item) by a person scanning the matrix barcode. While it is common to see traditional barcodes affixed to each item in a store, this is costly and requires orders of magnitude more barcodes to be generated than if only the store shelf were labeled. Although this disclosure describes embodiments relating to a payment service, the same techniques would be understood to be applicable to other industries that may benefit from the use of dynamic actions performed from interaction with a matrix barcode.

[0060] Because dynamic matrix barcodes may be re-associated with commands after they have been generated, the matrix barcodes may be more easily used in scenarios where they are affixed to physical media. For example, a charity may desire to present information and solicit donations through flyers. The charity may configure a matrix barcode to, for example, include a URL linking to a webpage for a particular campaign. The matrix barcode may be easily printed on paper flyers for distribution. When the campaign has ended, the matrix barcode, and all associated media, must be discarded in favor of a new matrix barcode used for a new campaign. However, suppose that the charity wishes to use more expensive physical media (e.g., shirts, hats, mugs, etc.). It would be

prohibitively expensive to include a single-use matrix barcode on more expensive physical media. [0061] According to particular embodiments, dynamic matrix barcodes may provide a solution. The charity may request a barcode-identifying service (or, e.g., a payment service supporting a barcode-identifying service) to generate a matrix barcode and corresponding token. The charity may use that matrix barcode on a wide variety of physical media. For each fund-raising or awareness campaign, the charity may re-program the dynamic matrix barcode (e.g., re-associate the token with a new command) to provide any updated information or donation opportunities. Thus, the same physical media could be re-used without waste. As described herein, interactions with the matrix barcode may be associated with contextual data, allowing the usage of the matrix barcode to be even further fine-tuned. For example, a charity may associate matrix barcode interactions at a specified location (e.g., within a particular city) to launch a first webpage, while interactions at a second location (e.g., within a different city) to launch a second webpage. Furthermore, the charity may use different channel codes embedded in the matrix barcode to detect the effectiveness of different advertising materials. The barcode-identifying service may report the interaction channel that led to the interaction to the charity.

[0062] A payment service may provide a method of receiving payments by matrix barcode to its users. In one example, a user may request a static matrix barcode be generated to facilitate payment. The user may request that the static matrix barcode be affixed to physical media, such as stickers, that the user can distribute to attach to other items as desired. However, due to manufacturing, processing, and shipping times, the delay between the user requesting the static matrix barcode and actually receiving it may be undesirable. According to particular embodiments, the payment service may instead provide dynamic matrix barcodes. The payment service may generate many tokens and corresponding matrix barcodes and affix them to stickers to be prepared to be distributed on notice from users. The payment service may maintain a warehouse of stickers (and other physical media) to be distributed on-demand. The payment service may even provide for the stickers to be sold in retail stores. To use such a dynamic matrix barcode, a user may need to be registered with the payment service. The user may then register the dynamic matrix barcode to their account by requesting that the corresponding token be associated with their account. The payment service may also allow a user to designate an action to be taken with respect to their account when a second user interacts with the matrix barcode. As an example only, the user may designate that when a second user scans the matrix barcode, they are provided the opportunity to transfer a specified amount of money to the user.

[0063] FIG. 3 illustrates interactions between devices for an example process involving generating and registering a matrix barcode and corresponding token to a particular action. At step 321, a payment service system 108 (e.g., payment service system 108) or one or more components of a payment service system 108 working in coordination, may generate a claimable token and associated matrix barcode using, for example, any of the previously-described methods. The payment service system 321 may provide the matrix barcode for use in a digital format (e.g., to be displayed by a computing device display) or in physical format (e.g., affixed to one or more physical objects).

[0064] At step 311, a first user device 103 may interact with the matrix barcode. In particular embodiments, the first user device 103 may interact with the matrix barcode through a variety of appropriate mechanisms. As an example only, a camera sensor of the first user device may image a visual representation of the matrix barcode. The camera sensor may create a digital image file or may simply process the matrix barcode as incoming image data. In particular embodiments, the camera sensor may process the matrix barcode through a specialized application for processing matrix barcodes, through a general camera application capable of processing matrix barcodes, or through an application associated with the payment service system or other matrix barcode provider. As another example, the first user device 103 may receive an image file including the matrix barcode from another computing system through a communication channel. For example,

the first user device **103** may receive the matrix barcode or any image of the matrix barcode through an email, short message, media message, through an application programming interface (API) call, from an application executing on the first user device **103**, or any other suitable communication protocol. After the first user device **103** interacts with the matrix barcode, the first user **103** may send a notification to the payment service system **108** indicating that the first user device **103** has interacted with the matrix barcode. The notification may be sent by any suitable method, including but not limited to, a short message, email, API call from third-party application or application associated with payment service system, etc. In particular embodiments, the notification may include the matrix barcode or the token associated with the matrix barcode, in which case the first user device **103** may interpret the matrix barcode to identify the claimed token prior to sending the notification.

[0065] At step **322**, the payment service system **108** may receive the notification that the first user device **103** has interacted with the matrix barcode. The notification may be received by a communication subsystem of the payment service system through an appropriate method corresponding to the method by which the notification had been sent by the first user device **103**. If the notification indicated only the matrix barcode, the payment service system **108** may identify the token associated with the matrix barcode. In particular embodiments, the payment service system, or an appropriate subsystem thereof, may directly interpret the received matrix barcode to identify the claimed token. In particular embodiments, the payment service system **108** may use the matrix barcode as a reference to otherwise search for the associated claimed token. For example, when generating the matrix barcode, the payment service system **108** may have performed a two-layer abstraction where a first token is generated and stored by the payment service system **108**. A second token may be generated and used to generate the matrix barcode. The second token, or an identifier therefor, may be stored in association with the first token so that the payment service system could identify the first token based on the identifier for the second token. In this way, the second token may be made available to the public without exposing additional details for how the token is used by the payment service system.

[0066] At step **323**, the payment service system **108** may determine that the matrix barcode is associated with an unclaimed token. For example, the payment service system **108** may maintain a data structure storing all generated tokens in association with one or more accounts of users of the payment service system. A token may be considered “claimed” when the token is matched to an account. A token may be considered “unclaimed” when the token is not matched to an account or is not included in the data structure. In particular embodiments, the payment service system **108** may search the data structure using the token associated with the matrix barcode for which the payment service system has received a notification of interaction. Finding no corresponding account the payment service system may determine that the matrix barcode (and corresponding token) is not claimed. The payment service system **108** may send a notification to the first user device **103** indicating that the matrix barcode is unclaimed and providing the first user device **103** with the opportunity to claim the token associated with the matrix barcode.

[0067] At step **312**, the first user device **103** may provide an indication to the user of the device that the matrix barcode and corresponding token are unclaimed. The first user device **103** may receive the notification from the payment service system **108** indicating that the matrix barcode and corresponding token are not currently claimed. The first user device **103** may display, for example, a pop-up or push notification in a user interface signifying that the matrix barcode has not been claimed. The first user device **103** may provide the indication through an application associated with the payment service executing on the phone. For example, upon receiving the notification, the first user device **103** may cause the application associated with the payment service to begin executing, or if it was previously operating in the background, may foreground the application. As another example, upon receiving the notification, the payment application may simply present a notification to the user without overriding the executing of other applications on the device. The

notification may provide a user of the device to request the initiation of a process to claim the matrix barcode to their account.

[0068] At step **3613**, the first user device **103** may initiate a request to associate the matrix barcode with an account of the first user. As described previously, the first user device **103** may cause an application associated with the payment service system **108** to begin executing on the first user device **103**. The application may provide a user interface through which a user may identify, for example, an account the user has with the payment service and one or more actions to be executed when a user having a different account interacts with the matrix barcode. Actions to be executed when a user with a different account interacts with the matrix barcode may include any suitable action involving one or more accounts of users of the payment system, including, but not limited to, the transfer of funds from a first account to a second account, the creation of an association between two accounts, notification of one or more of the accounts, presentation of information associated with one of the accounts, and many other suitable types of actions. The user may further specify an action to be executed when the user interacts with the matrix barcode again. The first user device **103** may send the request to the payment service system **108**.

[0069] At step **324**, the payment service system **108** may receive the request to associate the matrix barcode and corresponding token with the user account and account action. At step **325**, the payment service system **108** may mark the token associated with the matrix barcode as claimed. In particular embodiments, the payment service system **108** may add the token to the data structure storing associations with user accounts. In particular embodiments, the payment service system **108** may update the data structure record for the token to identify the user account. At step **326**, the payment service system **108** may further associate the token with the account actions or actions indicated with the request received from the first user device **103**.

[0070] FIG. **4A** illustrates several views of an example user interface of a device relating to the registration of a pre-generated matrix barcode to a user account. In interface **400a**, a payment application associated with a payment service is operating on a mobile device of a user. The payment application provides a camera application allowing a user to, e.g., scan matrix barcodes and display the scanned barcodes in the user interface. The interface **400a** provides instructions to the user to “Scan code” in element **405**. While using the payment application, the user has caused a matrix barcode **403** to be captured by the camera of the payment application. In this example, the matrix barcode **403** is affixed to a “Sticker Starter Pack” provided by the payment service. In this case, the pack includes a number of stickers, including sticker **401** that all include the same matrix barcode **403** or, if they include different matrix barcodes **403**, the matrix barcodes **403** are associated with the same token generated by the payment service and associated with the matrix barcode or barcodes.

[0071] After the payment application has scanned the matrix barcode **403**, the payment application may query the associated payment system to determine whether or not the token associated with the matrix barcode **403** is claimed. The payment service system may query a barcode-identifying database associated with the payment system to determine if the token is claimed (e.g., if the token is associated with an account or account action). In the example illustrated in FIG. **4A**, the payment service system may determine that the token is not claimed and inform the payment application. The payment application may transition to interface **410a**. Interface **410a** includes a detailed view **411** of the barcode **403**. The detailed view **411** of the barcode **403** may be retrieved from a barcode-identifying database of the payment system associated with the payment application prior to display on the screen **410a**. The detailed view **411** of the barcode **403** may be generated by the payment application once the payment application has identified the token associated with the barcode **403**. Screen **410a** further includes an interactive element **413** through which the user may initiate a request to claim the barcode or the token associated with the barcode. In particular embodiments, when the user interacts with the element **413**, the payment application may send a preliminary request to the payment service system to notify the system that the user will be

claiming the matrix barcode **403**. The payment application may do so to prevent another user from claiming the token associated with the matrix barcode **403** at the same time.

[0072] After the user selects the interactive element **413** to claim the matrix barcode **403** and associated token, the payment application may transition to interface **420a**. Interface **420a** provides the user to identify which account actions should be taken when another user interacts with the matrix barcode **403** at a later time. Instructions **420** have been provided to guide the user. As illustrated, interface **420a** includes several interactive elements **421** and **425** delineating possible actions. For example, interactive element **421** indicates that the action will be to transfer cash from the account of the other user to an account of the user. Elements **422** and **423** prompts the user to identify which of their accounts they would like to designate as the intended recipient. Element **423** provides the user the opportunity to specify an amount of cash to transfer. This may be used, for example, to specify a tip to be sent to the user. For example, the user is a musician who regularly performs at different coffee shops. The musician may accept cash tips from patrons of the coffee shop. However, the musician may have noticed that fewer and fewer people carry cash and are thus unable to tip. The musician may use the sticker **401** as a way to facilitate easy transfer of cash from the scanning user to the musician. Interactive element **425** indicates that the action will be to instruct a device of the other user to launch a webpage specified by the user. This may be used, for example, by the musician to quickly link the scanning user to their social media profile or to a website set up by the musician to advertise their music. After the user selects one of the interactive elements **421** or **425**, the payment application may send a request to the payment service system to request that the select action be associated with the token corresponding to the barcode **403**. The payment service system may update its records of the tokens and barcodes to indicate that the token is claimed to the account of the user and to indicate that when another user interacts with the barcode the selected action should be performed.

[0073] FIG. **4B** illustrates several views of an example user interface relating to the registration of a pre-generated matrix barcode to a user account. In interface **400b**, a third-party application is executing on a mobile device of a user. The third-party application includes a simulated view finder showing what is currently being imaged by a camera sensor of the mobile device. As shown in the interface **400b**, the user has caused the matrix barcode **403**, embodied again a sticker **401** to be captured by the camera sensor. Interface **400b** also includes an interactive element **407** that, when selected, causes the camera sensor to save the image shown in the view to the mobile device.

[0074] In the example shown in FIG. **4B**, the mobile device of the user does not have a version of the payment application supporting the claiming of matrix barcodes. In this example, the matrix barcode may include a URL that can be executed by a web browser of the computing device. When the third-party application scans the matrix barcode, the mobile computing device may prompt the user to launch a web browser to execute the URL. The URL may be uniquely matched to the matrix barcode or corresponding token so that when the web browser executes the URL, the payment service system may be notified. The payment service system may determine whether or not the token associated with the matrix barcode **403** is claimed, as described herein. Interface **410b** shows the web browser, having executed the URL **415** when the payment service system has determined that the token corresponding to the matrix barcode **403** is unclaimed. Interface **410b** includes a detailed view of the matrix barcode **411**. Because a user without a compatible version of the payment application may not be familiar with the notion of claimable matrix barcodes for dynamic actions, interface **410b** includes text **412** explaining the situation to the user. Interface **410b** also includes an interactive element **413** that, when selected, will allow the user to claim the matrix barcode and corresponding token to their account directly through the web browser. After the user interacts with the interactive element **413**, the user may be prompted to sign in to the payment service or create an account so that the system can identify the user.

[0075] After the user signs in or creates an account, the web browser may transition to show interface **420b**. Interface **420b** may include another webpage **427** accessible only to the user that

has claimed, or is claiming, the matrix barcode **403**. Like interface **420a**, interface **420b** includes instructions **420** guiding the user, and interactive elements **421** and **425** delineating actions that a user may request be performed when another user interacts with the matrix barcode **403** at a later time. Interactions with the elements of interface **420b** may be handled in a similar manner to those shown in **420a**, with the difference being that the payment service system is notified of the actions through the web browser, which may be provided by a third-party, and not through an application associated with the payment service system.

[0076] FIG. **4C** illustrates several views of an example user interface relating to the registration of a pre-generated matrix barcode to a user account. As with interface **400b**, interface **400c** shows a third-party application executing a mobile device of a user. The third-party application includes a simulated view finder showing what is being captured by a camera sensor of the mobile device. As shown in the interface **400b**, the user has caused the matrix barcode **403**, embodied again a sticker **401** to be captured by the camera sensor. Interface **400b** also includes an interactive element **407** that, when selected, causes the camera sensor to save the image shown in the view to the mobile device.

[0077] In the example shown in FIG. **4C**, the mobile device of the user does not have a version of the payment application supporting the claiming of matrix barcodes. In this example, the matrix barcode may include a URL that can be executed by a web browser of the computing device. When the third-party application scans the matrix barcode, the mobile computing device may prompt the user to launch a web browser to execute the URL. The URL may be uniquely matched to the matrix barcode or corresponding token so that when the web browser executes the URL, the payment service system may be notified. The payment service system may determine whether or not the token associated with the matrix barcode **403** is claimed, as described herein. Interface **410c** shows the web browser, having executed the URL **415** when the payment service system has determined that the token corresponding to the matrix barcode **403** is unclaimed. Because a user without a compatible version of the payment application may not be familiar with the notion of claimable matrix barcodes for dynamic actions, interface **410b** includes text **412** explaining the situation to the user. Interface **410c** includes an image **416** of the sticker **401** that the user scanned to cause the URL **415** to be executed. The sticker may be identified, for example, by a channel code included in the matrix barcode so that the token and individual sticker may be identified. As described herein, the channel code may be unique to the token or may be shared to indicate, for example, the type of media on which the token was embodied prior to the matrix barcode being interacted with. When the matrix barcode and corresponding token are saved by the payment service system, the payment service system may also note the channel codes and associated media in which the matrix barcode have been embodied. In the example shown in FIG. **4C**, for security purposes the payment service system may not support claiming matrix barcodes and corresponding tokens, or designating actions therefor, from a web browser alone. Interface **410c** may include text **417** prompting the user to claim the sticker by using an application associated with the payment service and may provide an interactive element **419** that, when interacted with, will cause the mobile device of the user to download (or otherwise acquire) the application.

[0078] In particular embodiments, a user may desire to modify the action associated with a matrix barcode and corresponding token after the user has claimed the matrix barcode and corresponding token to be associated with their account. For example, a user may want to modify the financial account to which funds will be transfer or may wish to modify the amount of funds to be suggested as the transfer amount. As another example, a user may want to modify the address of the webpage that is launched when another user scans the matrix barcode. FIG. **5** illustrates interactions between devices for an example process involving modifying the account action associated with a matrix barcode and corresponding token. At step **511**, a first user device **103** may interact with a matrix barcode. As described previously, the interaction may occur through a third-party application (e.g., a barcode scanner) or may occur through an application associated with a payment service. The

application may send notification of the interaction to the payment service system. In particular embodiments, first user device **103** may interpret the matrix barcode and act accordingly. For example, a third-party application may interpret the matrix barcode to include a URL and may execute said URL in a web browser. Executing the URL may cause notification of an interaction to be sent to the payment service system. As another example, the application associated with the payment service executing on the first user device may interpret the matrix barcode to determine the token associated with the matrix barcode and send the token to the payment service system. The notification may include an identification of a user account associated with the first user device **103** or with the interaction (e.g., if a user is signed onto a friend's mobile device).

[0079] At step **521**, the payment service system may receive the notification of interaction with the matrix barcode by any suitable method corresponding to the method by which the notification had been sent. At step **522**, the payment service system may determine that the matrix barcode is associated with a claimed token. In particular embodiments, the payment service system may query a data structure storing association of matrix barcodes and corresponding tokens with accounts of users of the payment service and related actions. To determine that the token corresponding to the matrix barcode has been claimed, the payment service system may query the data structure with the token (either received from the first user device **103** or interpreted from the matrix barcode) and determine that an associated with a user account already exists. At step **523**, the payment service system may compare the user account associated with the matrix barcode and corresponding token to the user account received in the notification from the first user device. If the accounts match, then the payment service system **108** may determine that the user interacting with the matrix barcode is the owner of the corresponding token. In particular embodiments, rather than receive the user account through the first notification, the payment service system **108** may send a separate request to the first user device **103** requesting the device to identify the user. In response the first user device **103** may identify the user or provide the user an opportunity to authenticate their account. The payment service system **108** may send a notification to the first user device **103** indicating the user of the first user device is the owner of the matrix barcode and the corresponding token.

[0080] At step **512**, the first user device may provide a user interface including an indication that the matrix barcode is associated with a token claimed by the user of the first user device. The indication may be a confirmation to the user that the user correctly configured the account action associated with the token. The interface may include options permitting the user to modify the account action or to remove the association between the matrix barcode and corresponding token and the user account.

[0081] At step **513**, the first user device **103** may receive input from the user indicating modifications to be made to the account action. The user may, for example, interact with one or more interactive elements in the user interface to modify the account action. Available modifications may be dependent on the type of account action that the user originally selected for the matrix barcode and corresponding token. For example, if the action was to transfer an amount of funds to an account of the user, the action may be to modify the target account or the amount of funds. Available modifications may include changing the type of the action. For example, the elements may allow the user to change the action from a funds transfer to an advertisement. At step **514**, based on the input received from the user, the first user device **103** may initiate a request to modify the account action involving the user account. The first user device **103** may collect the modifications requested from the user and transmit the modifications to the payment service system **108**.

[0082] In particular embodiments, the payment service system **108** may include methods to detect and prevent fraud or theft of a payment transaction. For example, a payment service system **108** may include techniques to detect irregular modification requests and require confirmation via a second, backup channel of communication. The payment service system **108** may receive

instructions that include a requested modification to an action associated with a token. The payment service system **108** may analyze the request and determine that additional verification is required before the payment service system **108** will make the request modifications. For example, the payment service system may receive a request to modify the designated receiving account for transfers of funds as a result of interaction with a matrix barcode. The payment service system may automatically determine that any such modification requires verification. As another example, the payment service system **108** may analyze contextual information associated with the modification request instructions. The payment service system **108** may determine that the request is associated with location not previously associated with the user, is made at an unusual time, or is made from a device not previously associated with the user's account. The payment service system may determine that there is an increased likelihood that the user's account has been comprised and may send a verification message to the user via a second (e.g., backup communication channel). A backup communication channel may be a push notification delivered to an instance of the payment application on a device other than the device from which the request initiated, a message delivered (e.g., via a short message service, electronic mail, or third-party application) to a designated backup address, or a request that the user verify their identity in some other way. Prior to receiving a confirmation message verifying the transaction, the payment service system **108** may prevent any transactions to occur that involve the modification. The payment service system **108** may even freeze all transactions with the account until the user is able to verify their identity. After receiving the confirmation message, the payment service system may proceed to step **524**.

[0083] At step **524**, the payment service system **108** may receive the request to modify the account action from the first user device **103**. The payment service system **108** may interpret the request to determine the nature of the modifications to be made. At step **525**, the payment service system **108** may apply the requested modifications to the account action involving the user account associated with the matrix barcode and corresponding token. The payment service system may update a data structure storing the claimed token in association with a list of actions to be performed when another user interacts with the token.

[0084] FIG. **6** illustrates interactions between devices for an example process involving modifying the account action associated with a matrix barcode and corresponding token. In the example interactions shown in FIG. **6**. The user is not required to first interact with the matrix barcode again before they can modify the account action associated with the matrix barcode and corresponding token. For example, the user may modify the account action associated with the matrix barcode and corresponding token through an application associated with the payment service and executing on the first user device or through a webpage associated with the payment service. Additionally, the user may be able to modify the account action based on recommendations for account modifications made by the payment service and sent to be reviewed by the user.

[0085] The interactions for the process shown in FIG. **6** may begin with the payment service system **108**. At step **621**, the payment service system **108** may analyze the transaction histories and market data related to the user. In particular embodiments, the payment service system may perform the analysis on data that is relevant to a particular user and to a particular account action that has been selected by a user to be associated with a matrix barcode and corresponding token. The payment service system **108** may perform the analysis with the intent of determining improvements that may be made to the associated account action. The payment service system **108** may have access to a variety of transactional information related to the spending and money-transferring habits of the users of the payment service. The payment service system **108** may analyze that information to determine possible improvements. The payment service system **108** may analyze transaction history, market data, and other relevant information to identify trends in the data that are relevant to a particular user or to a particular action associated with a matrix barcode and corresponding token. The trends may be based on any suitable data stored therein, including, but not limited to, times of transactions, dates of transactions, amounts of funds

transferred, the identities of users involved, the location of an interaction leading to the transaction, and other related information. The payment service system **108** may be given particular performance indicators, such as amount of money transfer to the particular user or number of transactions completed, to optimize. These performance indicators may be specified by the user or may be applied on a system-wide level. For example, a musician may have set up an account action so that users are provided an method to tip them \$3 via the payment service when they interact with the barcode. The payment service system **108** may analyze data such as a location and time of day when the musician typically receives the most tips. The payment service system **108** may compare that information for the musician to tipping transactions placed at the same or similar locations and at the same or similar times of day.

[0086] At step **622**, the payment service system **108** may generate one or more recommendations for modifications to the account action associated with a matrix barcode and corresponding token. The result of the analysis performed by the payment service system **108** may be one or more recommendations to optimize the performance indicators provided to the payment service system **108**. Continuing the example of the musician, the payment service system **108** may determine that the musician typically receives tips at a particular coffee shop during lunch on the weekdays. The payment service system **108** may recommend lowering the recommended tip amount associated with a matrix barcode and corresponding token based on a comparison of the amount tipped at similar coffee shops at the same time or at the same coffee shop at different times. The payment service system **108** may have concluded that the musician's suggested tip amount was causing users to prefer to cancel the transaction over completing the tip. The payment service system **108** may send the recommendation to modify the account action to the first user device **103**.

[0087] At step **611**, the first user device may present an interface through which a user may modify an account action associated with a matrix barcode and corresponding token. In particular embodiments, the first user device **103** may present the user interface as the result of receiving a recommended modification from the payment service system **108**. In particular embodiments, the first user device **103** may present the user interface as the result of a user's interaction with the first user device **103**. As noted in FIG. **6**, steps **621** and **622** are optional and are not required for a user to be able to modify an account action associated with a matrix barcode and claimed corresponding token. As part of the interface, the first user device **103** may present multiple matrix barcodes associated with tokens claimed by the user when the user has claimed multiple tokens. The user may want only to modify one account action, and thus the interface allows the user to choose which. At step **612** the first user device **103** may receive a selection of the matrix barcode associated with the token with an action that is to be modified. The first user device **103** will also receive a specification of the modification to be made. In particular embodiments, the modification may be the result of a recommendation provided by the payment service system **108** (e.g., in step **622**). At step **613**, the first user device **103** may initiate a request to modify the account action associated with the selection matrix barcode and corresponding token. The first user device **103** may send the request to the payment service system.

[0088] At step **623**, the payment service system may receive the request. If the payment service system **108** previous provided a recommendation, the request may merely be confirmation of the user's acquiescence to the recommendation. The request may include the claimed token (or identifier), the matrix barcode (or identifier), and details of the modification such as the specification of the account action or account-action dependent information. The account-action dependent information may include, for example, the amount of funds to be transferred, the identity of the account to which the funds will be transferred, the timing of the transaction, follow-up information to be delivered, and other suitable information. At step **624**, the payment service system **108** may modify the account action involving the user account associated with the matrix barcode and corresponding token indicated by the request. The payment service system may update records in a data structure that identify and provide the details for the account action.

[0089] In particular embodiments, a user may claim a matrix barcode and corresponding token. In claiming the matrix barcode and corresponding token, the user may specify that one or more actions occur, or are recommended, when another user interacts with (e.g., scans) the matrix barcode. The actions may be specified by the user when the first claim the matrix barcode and corresponding token and may further be modified by the user at will. The payment service system may communicate with an associated application executing on a mobile device of the user to facilitate specification and modification of actions associated with a particular matrix barcode and corresponding token.

[0090] In particular embodiments, the action specified may involve an interaction between an account of the first (e.g., claiming) user and an account of the second (e.g., scanning) user. Based on the type of action, confirmation may be required by one or more of the users. For example, if the action involves a transfer of funds from one user to another, then confirmation may be required by the transferring user before the transfer is initiated. Certain actions may provide merely a notification to one or more of the users, without requiring confirmation before it can proceed. For example, if the action involves a scanning user adding a claiming user to a contact list, the scanning user may simply be notified that the action has occurred. Actions may provide notification and confirmations mixed as appropriate. For example, a transferring user may receive both a confirmation of the transfer and may receive a notification once the transfer is completed. Similarly, the receiving user may receive a notification that the transfer has occurred.

[0091] The action involving accounts of the first user and the second user may be dependent on a context of the interaction with the matrix barcode and corresponding token. The context may include information about the time and location of the interaction. For example, the context may include the time of the interaction, the location of the interaction, identification of one or more merchants near the location associated with the interaction, identification of events registered to be occurring near the interaction (e.g., from a merchant's profile or from a user's profile), and other suitable information. The context may include information about the interacting user. For example, the context may include an identity of the interacting user, information from a customer profile associated with the user, an account of the interaction user, etc. The context may include information about the interacting device. For example, the context may include an identity of the device, including a manufacturer or model of the device, the application responsible for the interaction (e.g., a third-party application or an application associated with the payment service).

[0092] FIG. 7 illustrates interactions between devices for an example process involving the operation of an action involving accounts of a first and second user based on interactions with a matrix barcode. Prior to step **731**, a first user device **103** has been used to claim matrix barcode and corresponding token (e.g., according to the processes described above). As part of the claiming process, the user of the first user device has specified one or more accounts to be executed when another user interacts with the matrix barcode and corresponding token. A payment service system **108** or related subsystems may store the requested action and user account (or an identifier therefor) in association with the token corresponding to the matrix barcode.

[0093] At step **731**, a second user device **152** may interact with the matrix barcode. As described above, the second user device may interact with the matrix barcode through an application executing on the second user device **152**. The application may be an application associated with the payment service or may be a third-party application capable of interacting with a matrix barcode. At step **732**, the second user device **152** may determine a context of the interaction. The context may be determined based on the time or location of the interaction, the identity of the interacting user, the interacting device, or other suitable factors. The second user device **152** may send the matrix barcode and the associated context to the payment service system **108**. The second user device **152** may also interpret the matrix barcode to identify the corresponding token and transmit the corresponding token to the payment service system **108**. In particular embodiments, rather than determine the context of the interaction, the second user device **152** may merely collect the

contextual information, such as the time or location of the interaction, the identity of the interacting user, and interacting device, and other suitable factors, and send the collected information to the payment service system **108**. In such an embodiment, step **732** (determining the context) may be performed by the payment service system **108**.

[0094] Prior to step **721**, the payment service system **108** may receive the matrix barcode (or corresponding token) and determined context of the interaction. At step **721**, the payment service system may determine that the received matrix barcode is associated with a claimed token. To determine that the matrix barcode is associated with a claimed token, the payment service system **108** may interpret the matrix barcode to identify the claimed token. Alternatively, the payment service system **108** may not need to interpret the matrix barcode if the claimed token has been received from the second user device **152**. The payment service system **108** may query a data structure storing claimed tokens and associated information using the claimed token. The payment service system **108** may determine that the token is claimed if the query returns information, such as an identified account and account actions. On the contrary, if the query either returns no information or returns a positive identification that the token is not claimed, then the payment service system **108** may determine that the token is not claimed.

[0095] After determining that the received matrix barcode is associated with a claimed token, at step **722**, the payment service system **108** may identify the account associated with the token based on the information retrieved from the data structure. The payment service system **108** may further identify the account action associated with the claimed token. The account action may be the action that the first user requested to be associated with the claimed token when the first user claimed the token. The payment service system **108** may prepare to execute the identified action. The payment service system **108** may send a message to the second user device **152** identifying the action, the account associated with the claimed token (e.g., the account of the first user), and other pertinent information. For example, the payment service system **108** may send a confirmation message to the second user device **152** identifying the first user and a recommended amount to transfer to the user (e.g., a monetary amount as a tip).

[0096] The second user device **152** may display the received information to the user as a confirmation request message. The message may be displayed as a part of an interactive notification or other user interface including interactive elements. The message may include information about an account (e.g., financial account) of the second user. The information may include an identification of the account (e.g., if the second user maintains multiple accounts), a source of the funds (e.g., if the second user has an account with the payment service and another account with a third-party), and a current balance of the account of the second user. The second user may agree with the details of the transaction, such as the first user, the recipient account of the first user, and the amount to be transferred. The second user may acknowledge confirmation of the transaction through interaction with an interactive element of the user interface. At step **733**, the second user device **152** may register the second user's response to the confirmation request message. The second user device **152** may send a confirmation response message to the payment service system **108**. In particular embodiments, the second user may disagree with one or more details of the transaction. The user interface may provide interactive elements allowing the second user to refine or correct information. For example, the second user may be provided an interactive element allowing them to choose a different amount to be transferred. The second user may also refuse to complete the account action (e.g., may refuse to transfer funds to the first user). The second user device **152** may send a message to the payment service system **108** denying the account action.

[0097] At step **723**, the payment service system may receive a positive confirmation response message from the second user device **152**. The payment service system **108** may interpret this response as a authorization to perform the action (e.g., to transfer the amount of funds). At step **724**, the payment service system **108** may initiate the account action specified by the first user

involving the account of the first user and the second user. The payment service system **108** may send a notification to both the first user device **103** and the second user device **152** confirming that the action has been initiated. The payment service system **108** may send one or more other notifications over the processing of the account action. For example, the payment service system may send a notification confirming that the action has been completed. The first user device **103** may receive the notification or notifications. At step **711**, the first user device **103** may notify the first user of the account action occurring involving the account of the second user. The notification may take any suitable form, for example a push notification, electronic mail, short message, or message delivered through a payment application executing on the first user device **103**. The notification may be delivered substantially immediately, or may be delivered periodically (e.g., as part of a summary of transactions). Similarly, the second user device **152** may receive the notification or notifications. At step **734**, the second user device **152** may notify the second user of the account action occurring involving the account of the first user. The notification may be delivered in methods and at times similar to the messages to the first user.

[0098] FIG. **8A** illustrates several views of an example user interface of a device relating to interaction with a claimed matrix barcode and fulfillment of an associated account action. In interface **800a**, payment application associated with a payment service is operating on a mobile device of a user. The payment application provides a camera application allowing a user to, e.g., scan matrix barcodes and display the scanned barcodes in the user interface. The interface **800a** provides instructions to the user to “Scan code” in element **805**. While using the payment application, the user has scanned a sticker **801** including a matrix barcode **803** using the camera of the payment application.

[0099] After the payment application has scanned the matrix barcode **803**, the payment application may query the associated payment system to determine whether or not the token associated with the matrix barcode **803** is claimed. The payment application may also send information collected when the payment application scanned the matrix barcode **803**. For example, the payment application may send the time or the location of the device that scanned the barcode. The payment service system may query a barcode-identifying database associated with the payment system to determine if the token is claimed (e.g., if the token is associated with an account or account action). In the example illustrated in FIG. **8A**, the payment service system may determine that the token is claimed. The payment service system may further determine that the token is claimed by a user, John Public and has been associated with a particular action—transferring funds to a designated account. The payment service system may also analyze the contextual data received from the payment application to compare the contextual data with data specified by the user that claimed the token. Contextual information may include, as an example and not by way of limitation, date, time, device identity, location, scheduled events at the location, and various other information. For example, the user may have designated several locations and associated specific account actions with interactions with the matrix barcode and associated token. The payment service system may select an appropriate account action. The payment service system may inform the payment application of this information. The payment application may transition to interface **810a**. Interface **810a** includes an interactive interface of the payment app through which the user can send money to John Public, the user who claimed the token associated with the matrix barcode. Interface **810a** indicates at an element **812** the name of the user who claimed the token. Interface **810a** also includes a message from the user who claimed the token at element **811**. The message may have been set by the user when the user claimed the token associated with the matrix barcode or may have been modified by the user at a later time. Element **815** includes a recommended amount of money to send to John Public pre-filled in element **815**. Element **813** includes a field which the user may use to send a note to John Public or otherwise mark the transfer of funds for their records. The user may modify the information in any of the interactive fields, e.g., elements **813**, **815**. The user may confirm a transfer of funds by interacting with the “Pay” button, element **817**.

[0100] After the user interacts with element **817**, the payment application may send the information that was stored in the interactive fields to the payment service system to process the account action. In this example, the account action is to send a specified amount of money to the user that claimed the token corresponding to the matrix barcode. The payment service system may receive the information, such as the amount to be transferred, any accompanying note, the identity of the payor and recipient, and other associated information. The payment service system may initiate the transaction and send a notification to the payment application confirming that the transaction has been initiated. The payment application may transition to interface **820a** which shows a transfer initiated screen. Interface **820a** includes an image **826** associated with the recipient account and a message **827** explaining the details of the transaction including a customized note sent from the user to the recipient.

[0101] FIG. **8B** illustrates several views of an example user interface a device relating to interaction with a claimed matrix barcode and fulfillment of an associated account action. Interface **800b** shows a third-party application executing a mobile device of a user. The third-party application includes a simulated view finder showing what is being captured by a camera sensor of the mobile device. As shown in the interface **800b**, the user has caused the matrix barcode **803**, embodied in a sticker **801** to be captured by the camera sensor. Interface **800b** also includes an interactive element **807** that, when selected, causes the camera sensor to save the image shown in the view to a memory of the mobile device.

[0102] In the example shown in FIG. **B**, the mobile device of the user has a version of the payment application supporting the interaction with matrix barcodes. The third-party application may interpret a first portion of the matrix barcode and determine that the matrix barcode should be handled by the payment application. The third-party application may pass the matrix barcode (e.g., may decode the matrix barcode and pass the associated information) to the payment application. The third-party application or mobile device may cause the payment application to begin or resume execution on the mobile device of the user. The payment application may take the foreground of operation on the mobile device.

[0103] After beginning execution having received the matrix barcode, as described with respect to the example shown in FIG. **A**, the payment application may query the associated payment system to determine whether or not the token associated with the matrix barcode **803** is claimed. The payment service system may query a barcode-identifying database associated with the payment system to determine if the token is claimed (e.g., if the token is associated with an account or account action). In the example illustrated in FIG. **8B**, the payment service system may determine that the token is claimed. The payment service system may further determine that the token is claimed by a user, John Public and has been associated with a particular action-transferring funds to a designated account. The payment service system may also analyze the contextual data received from the payment application to compare the contextual data with data specified by the user that claimed the token. The payment service system may select an appropriate account action. The payment service system may inform the payment application of this information. The payment application may transition to interface **810b**. Interface **810b** includes an interactive interface of the payment app through which the user can send money to John Public, the user who claimed the token associated with the matrix barcode. Interface **810b** indicates at an element **812** the name of the user who claimed the token. Interface **810b** also includes a message from the user who claimed the token at element **811**. The message may have been set by the user when the user claimed the token associated with the matrix barcode or may have been modified by the user at a later time. Element **815** includes a recommended amount of money to send to John Public pre-filled in element **815**. Element **813** includes a field which the user may use to send a note to John Public or otherwise mark the transfer of funds for their records. The user may modify the information in any of the interactive fields, e.g., elements **813**, **815**. Note that, in this example, John has changed the action associated with the matrix barcode and associated token as he has moved to a new

performing location after the example shown in FIG. 8A. The user that scanned the matrix barcode did so at the second location. The payment service system presented a different pre-filled amount to transfer, shown in element **815** and a different pre-filled note including the location at element **813** based on John's modifications to the associated actions. The user may confirm a transfer of funds by interacting with the "Pay" button, element **817**.

[0104] After the user interacts with element **817**, the payment application may send the information that was stored in the interactive fields, e.g., **813** and **815**, to the payment service system to process the account action. In this example, the account action is to send a specified amount of money to the user that claimed the token corresponding to the matrix barcode. The payment service system may receive the information, such as the amount to be transferred, any accompanying note, the identity of the payor and recipient, and other associated information. The payment service system may initiate the transaction and send a notification to the payment application confirming that the transaction has been initiated. The payment application may transition to interface **820b** which shows a transfer initiated screen. Interface **820a** includes an image **826** associated with the recipient account and a message **827** explaining the details of the transaction including a customized note sent from the user to the recipient. The user in this case has modified both the pre-filled note from element **813** and the pre-filled amount to transfer **815** opting to increase the amount transferred.

[0105] FIG. 8C illustrates several views of an example user interface a device relating to interaction with a claimed matrix barcode and fulfillment of an associated account action. As with interface **800b**, interface **800c** shows a third-party application executing a mobile device of a user. The third-party application includes a simulated view finder showing what is being captured by a camera sensor of the mobile device. As shown in the interface **800c**, the user has caused a matrix barcode **804**, embodied in a sticker **802** to be captured by the camera sensor. Interface **800c** also includes an interactive element **807** that, when selected, causes the camera sensor to save the image shown in the view to a memory of the mobile device.

[0106] In the example shown in FIG. 8C, the mobile device of the user does not have a version of the payment application supporting interaction with matrix barcodes. In this example, the matrix barcode, when decoded by the third-party application, may include a URL that can be executed by a web browser of the computing device. When the third-party application scans the matrix barcode, the mobile computing device may prompt the user to launch a web browser to execute the URL. The URL may be uniquely matched to the matrix barcode or corresponding token so that when the web browser executes the URL, the payment service system may be notified (e.g., through communication with a web server associated with the payment service). The payment service system may determine whether or not the token associated with the matrix barcode **804** is claimed, as described herein. Interface **830c** shows the web browser, having executed the URL **831**. The interface shows that a web server associated with the payment service is preparing to redirect the web browser through an element **833**.

[0107] FIG. 8C illustrates two potential actions that may happen next, depending, for example, on context information sent to the payment service system when the web browser sends executes the URL. For example, the payment service system may have determined that the matrix barcode and corresponding token are claimed by a charity. The charity may have affixed this matrix barcode to a variety of their promotional materials. The payment service system may identify the matrix barcode or corresponding token in a data structure and may determine that the charity has established different actions to occur depending on context information. The charity may have set the action to depend on the date and time at which the matrix barcode **804** is interacted with. Similarly, the charity may have set the action to depend on the location of the device that interacts with the matrix barcode. This information may be sent by the device to the payment service system through the web page or after interaction with the webpage.

[0108] In a first illustrated example, the payment service system may have received the context

information and determined the date and time of the interaction with the matrix barcode **804**. The charity may be planning an event to occur on Saturday at 5 pm. The charity may have set the action associated with the token associated with the matrix barcode **804** to be to provide a URL to a landing page advertising the event when the interaction occurs prior to the start of the event. The payment service system may have determined that interaction with the matrix barcode **804** occurred on Thursday. The payment service system may therefore redirect the web browser to web page having a user interface as shown in **840**. The user interface **840** includes the URL **841** of the webpage to which the web browser was redirected. The user interface **840** includes information **842** announcing the charity event and providing other identifying information for the charity. The user interface **840** also includes a request **844** that the user submit their email address for more information through a number of interactive elements **845**. In another example, the action associated with the claimed token may have been to retrieve an identifier for a communication method (e.g., email address, phone number, social media handle) associated with the user who interacted with the matrix barcode **804** and automatically send the user detailed information via the communication method.

[0109] In a first illustrated example, the payment service system may have received the context information and determined the date and time of the interaction with the matrix barcode **804**. This time, the interaction may have occurred on Saturday at 6 pm, after the start of the charity event. Additionally, the payment service system may have determined the location of the interaction based on location information received from the interacting device. The charity may have established a location associated with the charity event, such as by designating a geo-fence around the event. The charity may have associated interactions with the matrix barcode **804** after the start of the event and at or near the location associated with the event with an action facilitating a transfer of money from the interacting user to the charity. The payment service system may determine that these conditions are satisfied and therefor redirect the web browser executing on the interacting device to a web page with a user interface **810c**. The user interface **810c** may be configured to facilitate financial transfer between persons who do not have a version of an application associated with the payment service that supports interacting with matrix barcodes. The user interface **810c** includes the URL **821** to which the web browser executing on the interacting device was directed. The user interface **810c** includes a field **812** with information identifying the charity as a recipient of a financial transfer and another field **811** where the charity may enter a custom note to potential donors. The user interface **810c** also includes an interactive element **813** through which a user may specify a note to send with the transfer and another interactive element **815** through which a user may select the amount of money they wish to transfer. After the user updates the information, the user may interact with the pay button element **817** to initiate the financial transfer.

[0110] FIG. **8D** illustrates several views of an example user interface a device relating to interaction with a claimed matrix barcode. As with interface **800b**, interface **800d** shows a third-party application executing on a mobile device of a user. The third-party application includes a simulated view finder showing what is being captured by a camera sensor of the mobile device. As shown in the interface **800b**, the user has caused a matrix barcode **803**, embodied in a sticker **801** to be captured by the camera sensor. Interface **800d** also includes an interactive element **807** that, when selected, causes the camera sensor to save the image shown in the view to a memory of the mobile device.

[0111] In the example shown in FIG. **8D**, the mobile device of the user does not have a version of the payment application supporting interaction with matrix barcodes. In fact, the mobile device of the user does not have the payment application associated with the payment service installed on the device. In this example, the matrix barcode, when decoded by the third-party application, may include a URL that can be executed by a web browser of the computing device. When the third-party application scans the matrix barcode, the mobile computing device may prompt the user to launch a web browser to execute the URL. The URL may be uniquely matched to the matrix

barcode or corresponding token so that when the web browser executes the URL, the payment service system may be notified (e.g., through communication with a web server associated with the payment service). The payment service system may determine whether or not the token associated with the matrix barcode **803** is claimed, as described herein. Interface **830c** shows the web browser, having executed the URL **831**. The interface shows that a web server associated with the payment service is preparing to redirect the web browser through an element **833**.

[0112] In this example, the payment service system may require that a user be registered through the payment service or have the application associated with the payment service installed on the interacting mobile device. Because the payment service system was prompted that the matrix barcode **803** had been interacted with through a web server (e.g., instead of the payment application handling the URL), the payment service system may determine that the user has not installed the payment application. The payment service system may cause the webserver to redirect the web browser executing on the mobile device of the user to a web page that prompts the user to install the payment application. In the example shown in FIG. **8D**, the payment service system may determine that the account action associated with the token associated with the matrix barcode **803** is to transfer funds to a specified user's account. The payment service system may, through the web server, redirect the web browser executing on the mobile device of the user to a web page having a user interface **850**. The user interface **850** includes a landing page URL **850** associated with the user. The payment service system may include elements such as **816** and **817** containing identifying information for the user. This may help the interacting user to understand why they were redirected to this web page. The user interface **850** may include elements such as **818** explaining the action associated with the token associated with the matrix barcode **803**. Finally, the user interface **850** includes an interactive element **819** that will prompt the user to install the payment application associated with the payment service on the mobile device. For example, interaction with the element **819** may cause the mobile device to launch an application store for the mobile device to the page from which the user may install the payment application.

[0113] FIG. **9** illustrates an example method **900** for performing actions based on interactions with a matrix barcode. In particular embodiments, the payment service system **108** may store or be associated with storage of a plurality of matrix barcodes stored in associated with tokens. For example, the matrix barcodes may be stored in a token association structure **134**. In particular embodiments, the payment service system **108** may have access to a token association structure **134** (e.g., through one or more APIs). The payment service system **108** may also be associated with one or more instances of a payment application (e.g., payment application **107**) executing on one or more user mobile devices (e.g., mobile device **103**).

[0114] The method may begin at step **910**, where the payment service system **108** may receive a notification of an interaction with a matrix barcode or a token corresponding to matrix barcode. The notification may be received from a device associated with a user, such as a mobile device **103**. The notification may be received through any suitable form of communication, including but not limitation to, communication over one or more APIs, short message electronic mail, and through one or more wired or wireless connections. The message of the notification may indicate a matrix barcode, associated token, or other suitable identifier for the matrix barcode. The payment service system **108** may receive the notification, e.g., from a mobile device **103**, webserver associated with the payment service system **108**, another system associated with the payment service system **108**, or a third-party system or service.

[0115] After receiving the notification, at step **915**, the payment service system **108** may determine the source of the interaction. As describe above, the payment service system **108** may be associated with one or more mobile applications (e.g., application **107**) executing on one or more mobile device **103**. The payment service system **108** may be in communication with the application **107**. The application may be configured to be capable of capturing and interpreting (e.g., interacting with) matrix barcodes. When the application interacts with the matrix barcode, the message

notifying the payment service system **108** of the interaction may be specially configured so that the payment service system **108** can determine that the interacting mobile device **103** has a suitable payment application **107** installed. In particular embodiments, the matrix barcode may be configured to be read using any suitable matrix barcode-reading application. For example, many smartphones have the functionality to read matrix barcodes pre-installed. If the mobile device **103** has the payment application **107** installed and interacts with the matrix barcode through any other method, the mobile device **103** may cause the payment application **107** to begin executing on the mobile device **103**. The payment application **107** may send the corresponding message to the payment service system **108**, allowing the payment service system **108** to determine the source of the notification as being from a mobile payment application **107** executing on a mobile device **103**. The payment service system **108** may then proceed to step **920**.

[0116] The payment service system **108** may also be associated and in communication with one or more web servers. The payment service system **108** may also be in communication with a variety of other related systems or applications. In particular embodiments, the matrix barcode may be configured to be read using any suitable matrix barcode-reading application. For example, many smartphones have the functionality to read matrix barcodes pre-installed. Thus, a mobile device may be able to interact with a matrix barcode regardless of whether an instance of the payment application **107** is installed on the mobile device. Interacting with the matrix barcode may, in this instance, cause a URL to be executing by a web browser executing on the mobile device. Executing the URL may cause a web server associated with the payment service system **108** to notify the payment service system **108** of the interaction. In response, the payment service system **108** may determine that the source of the interaction was through the web browser (or other suitable widely available matrix barcode interpreting function). In response to determining that the notification originated from a web browser or web server, the payment service system **108** may proceed to step **917**.

[0117] At step **917**, the payment service system **108** may prepare a message recommending the use of the mobile payment application **107** to the user **104**. The message may be delivered to the mobile device of the user through a web server, e.g., the web server may provide a webpage to the web browser containing the message. The message may provide methods for the user to install the payment application **107** on the mobile **103**. In some embodiments, the method may stop. For example, the payment service system may require the use of a mobile payment application **107** to interact with a matrix barcode provided by the payment service system **108**. In some embodiments, the method may continue to step **920**.

[0118] At step **920**, the payment service system **108** may determine the token associated with the matrix barcode. In particular embodiments, the notification received by the payment service system **108** may include the related token identifier (e.g., the matrix barcode may be encoded with the token identifier). The payment service system **108** may then verify that the token identifier is a valid token and/or is associated with a token. In particular embodiments, the notification may include the matrix barcode (e.g., as an image). The payment service system **108** may decode the matrix barcode and identifier from the barcode a token. The token may be one representing only the matrix barcode (e.g., if the matrix barcode and token are each randomly generated and later associated). The token decoded from the matrix barcode may directly indicate the associated token. The payment service system **108** use the information included in the notification of interaction with the matrix barcode to query a data structure containing the associations between matrix barcodes and tokens.

[0119] At step **925**, the matrix barcode may determine whether the token associated with the matrix barcode is claimed or available to be claimed. For example, in querying the data structure, the payment service system **108** may receive a null response. The payment service system **108** may receive a token “abc123” and query the data structure. The data structure may only store token associations when an association has been made. Therefore, the result from the data structure for

the unclaimed token “abc123” will be null. As another example, the data structure may store all tokens generated and may return a response indicating that the token has not been claimed (e.g., that it is available). If the token is available to be claimed, the payment service system **108** may proceed to step **930**.

[0120] At step **930**, the payment service system **108** may optionally initiate a process through which the token can be claimed by the account of the user **104** of the mobile device **103**. The payment service system **108** may determine the account of the user in a variety of methods. For example, the user may have been logged into the mobile payment application **107**. The account identifying information may be sent with or after the notification that the mobile device has interacted with the matrix barcode. Similarly, if the notification was delivered via interaction with a web browser, a user may have logged into a web page associated with the payment service system **108**. The account identifying information may likewise be sent to the payment service system **108**. In particular embodiments, after the token is identified as being available for claiming, the payment service system **108** may request the user to identify their account. The payment service system **108** may request the user to provide authentication credentials so that the user can manage their account. The payment service system **108** may request the user enter other identifying information (e.g., a unique identifier for the account such as an account name or number) without the necessarily providing authentication credentials. After identifying the account of the user, the payment service system **108** may update the data structure containing associations between user accounts and tokens to indicate an association between the identified account of the user and the token. The payment service system **108** may also indicate an account action to be taken when the matrix barcode is later interacted with. Possible account actions have been described herein. The payment service system **108** may indicate this account action by updating an appropriate data table in a related data structure. At step **932**, the payment service system **108** may provide a notification to the mobile device indicating that the token has been successfully claimed and that the matrix barcode will now be associated with their account.

[0121] Returning to step **925**, the payment service system **108** may have determined that the token is already associated with another account, e.g., that it is not available to be claimed. The payment service system **108** may proceed to step **940**. At step **940**, the payment service system **108** may determine a user account associated with the interacting device. As described above, the user may be logged into the instance of the payment application **107** executing on the mobile device **103**. The user may be logged into the web page that originated the notification to the payment service system **108**. The user may also be asked to provide authentication credentials or other account identifying information (e.g., an account name, a unique proxy, or account number).

[0122] At step **945**, the payment service system **108** may compare the account associated with the identified token (e.g., the token associated with the interacted with matrix barcode) to the token associated with the identifying device determined in step **940**. If the accounts match, or if the same user is responsible for both accounts, the payment service system **108** may proceed to step **950**. If the accounts do not match (or if different users are responsible accounts) the payment service system may proceed to step **960**.

[0123] At step **950**, the payment service system **108** may interpret the interaction as a request by the user to manage their matrix barcode. The payment service system **108** may provide instructions causing an interface through which the user may modify settings associated with the matrix barcode and corresponding token. For example, the user may be permitted to disassociate the claimed token and matrix barcode from their account. As another example, the user may desire to modify the account action associated with the token. Depending on the action chosen to be associated with the token, an account action modification may include modifying values (e.g., a recommended amount of money to transfer), or completely altering the action (e.g., changing the action from a money transfer to an advertisement or email collection).

[0124] At step **960**, the payment service system **108** may analyze contextual information associated

with the interaction with the matrix barcode. In particular embodiments, the contextual information may be collected and sent with the notification of the interaction of the matrix barcode, the identifying account information, or during any other suitable step of the method **900**. The contextual information may only be collected according to privacy policies of the user. For example, the user may preemptively authorize some information (e.g., time of interaction) to be sent when their mobile device interacts with a matrix barcode. The user may selectively authorize some information to be sent (e.g., the location of the device when they interact with the matrix barcode). The user may also block contextual information from being sent. Analyzing the contextual information may include comparing the contextual information to prespecified conditions associated with the claimed token. For example, the user to whom the token is claimed may have indicated that at a first time a first action should be taken, and at a second time a second action should be taken. The payment service system **108** may compare the contextual information and determine which action should be taken.

[0125] At step **970**, the payment service system **108** may initiate the account action associated with the claimed token based on any satisfied conditions. For example, the payment service **108** system may cause funds to be transferred from a first account (e.g., the account of the interacting user) to a second account (e.g., the account of the user who claimed the token). As another example, the payment service system **108** may provide a notification of one or both of the users according to the account. The action may be finally contingent on receiving approval or confirmation from A variety of other suitable account actions may be performed. The payment service system **108** may then await further notifications of interaction with matrix barcodes.

[0126] FIG. **10** illustrates an example computer system **1000**. The computer system **1000** may be a computer system associated with the payment service system **108**, POS device **105**, or customer device **103**. While these devices may have components in common, such as those illustrated in FIG. **10**, it should be appreciated that each of the payment service system **108**, POS device **105**, or customer device **103** may be specialized devices configured for their specific purposes. In particular embodiments, one or more computer systems **1000** perform one or more steps of one or more methods described or illustrated herein. In particular embodiments, one or more computer systems **1000** provide functionality described or illustrated herein. In particular embodiments, software running on one or more computer systems **1000** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Particular embodiments include one or more portions of one or more computer systems **1000**. Herein, reference to a computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

[0127] This disclosure contemplates any suitable number of computer systems **1000**. This disclosure contemplates computer system **1000** taking any suitable physical form. As an example and not by way of limitation, computer system **1000** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **1000** may include one or more computer systems **1000**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **1000** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example and not by way of limitation, one or more computer systems **1000** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer

systems **100** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate.

[0128] In particular embodiments, computer system **1000** includes a processor **1002**, memory **1004**, storage **1006**, an input/output (I/O) interface **1008**, a communication interface **1010**, and a bus **1012**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

[0129] In particular embodiments, processor **1002** includes hardware for executing instructions, such as those making up a computer program. As an example and not by way of limitation, to execute instructions, processor **1002** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **1004**, or storage **1006**; decode and execute them; and then write one or more results to an internal register, an internal cache, memory **1004**, or storage **1006**. In particular embodiments, processor **1002** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **1002** including any suitable number of any suitable internal caches, where appropriate. As an example and not by way of limitation, processor **1002** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **1004** or storage **1006**, and the instruction caches may speed up retrieval of those instructions by processor **1002**. Data in the data caches may be copies of data in memory **1004** or storage **1006** for instructions executing at processor **1002** to operate on; the results of previous instructions executed at processor **1002** for access by subsequent instructions executing at processor **1002** or for writing to memory **1004** or storage **1006**; or other suitable data. The data caches may speed up read or write operations by processor **1002**. The TLBs may speed up virtual-address translation for processor **1002**. In particular embodiments, processor **1002** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **1002** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **1002** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **1002**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

[0130] In particular embodiments, memory **1004** includes main memory for storing instructions for processor **1002** to execute or data for processor **1002** to operate on. As an example and not by way of limitation, computer system **1000** may load instructions from storage **1006** or another source (such as, for example, another computer system **1000**) to memory **1004**. Processor **1002** may then load the instructions from memory **1004** to an internal register or internal cache. To execute the instructions, processor **1002** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **1002** may write one or more results (which may be intermediate or final results) to the internal register or internal cache. Processor **1002** may then write one or more of those results to memory **1004**. In particular embodiments, processor **1002** executes only instructions in one or more internal registers or internal caches or in memory **1004** (as opposed to storage **1006** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **1004** (as opposed to storage **1006** or elsewhere). One or more memory buses (which may each include an address bus and a data bus) may couple processor **1002** to memory **1004**. Bus **1012** may include one or more memory buses, as described below. In particular embodiments, one or more memory management units (MMUs) reside between processor **1002** and memory **1004** and facilitate accesses to memory **1004** requested by processor **1002**. In particular embodiments, memory **1004** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM.

Memory **1004** may include one or more memories **1004**, where appropriate. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

[0131] In particular embodiments, storage **1006** includes mass storage for data or instructions. As an example and not by way of limitation, storage **1006** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **1006** may include removable or non-removable (or fixed) media, where appropriate. Storage **1006** may be internal or external to computer system **1000**, where appropriate. In particular embodiments, storage **1006** is non-volatile, solid-state memory. In particular embodiments, storage **1006** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **1006** taking any suitable physical form. Storage **1006** may include one or more storage control units facilitating communication between processor **1002** and storage **1006**, where appropriate. Where appropriate, storage **1006** may include one or more storages **1006**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

[0132] In particular embodiments, I/O interface **1008** includes hardware, software, or both, providing one or more interfaces for communication between computer system **1000** and one or more I/O devices. Computer system **1000** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **1000**. As an example and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **1008** for them. Where appropriate, I/O interface **1008** may include one or more device or software drivers enabling processor **1002** to drive one or more of these I/O devices. I/O interface **1008** may include one or more I/O interfaces **1008**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

[0133] In particular embodiments, communication interface **1010** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **1000** and one or more other computer systems **1000** or one or more networks. As an example and not by way of limitation, communication interface **1010** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a WI-FI network. This disclosure contemplates any suitable network and any suitable communication interface **1010** for it. As an example and not by way of limitation, computer system **1000** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **1000** may communicate with a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network), or other suitable wireless network or a combination of two or more of these. Computer system **1000** may include any suitable communication interface **1010** for any of these networks, where appropriate. Communication interface **1010** may include one or more communication interfaces **1010**, where appropriate. Although this disclosure describes and illustrates a particular communication interface,

this disclosure contemplates any suitable communication interface.

[0134] In particular embodiments, bus **1012** includes hardware, software, or both coupling components of computer system **1000** to each other. As an example and not by way of limitation, bus **1012** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **1012** may include one or more buses **1012**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

[0135] Herein, a computer-readable non-transitory storage medium or media may include one or more semiconductor-based or other integrated circuits (ICs) (such, as for example, field-programmable gate arrays (FPGAs) or application-specific ICs (ASICs)), hard disk drives (HDDs), hybrid hard drives (HHDs), optical discs, optical disc drives (ODDs), magneto-optical discs, magneto-optical drives, floppy diskettes, floppy disk drives (FDDs), magnetic tapes, solid-state drives (SSDs), RAM-drives, SECURE DIGITAL cards or drives, any other suitable computer-readable non-transitory storage media, or any suitable combination of two or more of these, where appropriate. A computer-readable non-transitory storage medium may be volatile, non-volatile, or a combination of volatile and non-volatile, where appropriate.

[0136] Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

[0137] The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

Claims

1. A method comprising: configuring, a graphical user interface of an application executing on a first electronic device of a first user associated with a payment service system, to provide instructions for scanning an interactive element; detecting, on the graphical user interface, that the interactive element is scanned; in response to detecting that the interactive element is scanned,

determining whether a token associated with the interactive element is claimed; updating the graphical user interface on the first electronic device for claiming the token associated with the interactive element; updating the graphical user interface on the first electronic device to receive one or more actions to be triggered when the interactive element is interacted with using a second electronic device; detecting one or more inputs on the graphical user interface indicative of the one or more actions; and updating, at the payment service system, a database to include the interactive element, the token claimed, and the one or more actions in association with the interactive element.

2. The method of claim 1, wherein the payment service system has a first database of interactive elements including the interactive element and a second database of tokens including the token.

3. The method of claim 1, further comprising: receiving, from the second electronic device of a second user of the payment service system, a scan of the interactive element and a set of contextual information; identifying the one or more actions associated with the interactive element based at least in part on the set of contextual information; configuring a graphical user interface on the second electronic device, the graphical user interface on the second electronic device being interactive for inputs corresponding to the one or more actions; detecting the inputs on the graphical user interface on the second electronic device; and initiating the one or more actions in response to detecting the inputs on the graphical user interface on the second electronic device.

4. The method of claim 3, wherein at least one of the one or more actions is associated with a specified time, wherein the set of contextual information comprises a current time, and wherein identifying the one or more actions associated with the interactive element includes comparing the current time and the specified time.

5. The method of claim 3, wherein at least one of the one or more actions is associated with a specified location, wherein the set of contextual information comprises a current location associated with the second electronic device, and wherein identifying the one or more actions associated with the interactive element includes comparing the current location and the specified location.

6. The method of claim 3, wherein the token and the set of contextual information are received from a third-party application executing on the second electronic device of the second user.

7. The method of claim 3, wherein the token and the set of contextual information are received from a second application associated with the payment service system executing on the second electronic device, and wherein the second application receives at least the token from a third-party application executing on the second electronic device.

8. A payment service system comprising: one or more memories having computer-readable instructions stored therein; and one or more processors configured to execute the computer-readable instructions to: configure, a graphical user interface of an application executing on a first electronic device of a first user associated with the payment service system, to provide instructions for scanning an interactive element; detect, on the graphical user interface, that the interactive element is scanned; in response to detecting that the interactive element is scanned, determine whether a token associated with the interactive element is claimed; update the graphical user interface on the first electronic device for claiming the token associated with the interactive element; update the graphical user interface on the first electronic device to receive one or more actions to be triggered when the interactive element is interacted with using a second electronic device; detect one or more inputs on the graphical user interface indicative of the one or more actions; and update, at the payment service system, a database to include the interactive element, the token claimed, and the one or more actions in association with the interactive element.

9. The payment service system of claim 8, wherein the payment service system has a first database of interactive elements including the interactive element and a second database of tokens including the token.

10. The payment service system of claim 8, wherein the one or more processors are further configured to execute the computer-readable instructions to: receive, from the second electronic

device of a second user of the payment service system, a scan of the interactive element and a set of contextual information; identify the one or more actions associated with the interactive element based at least in part on the set of contextual information; configure a graphical user interface on the second electronic device, the graphical user interface on the second electronic device being interactive for inputs corresponding to the one or more actions; detect the inputs on the graphical user interface on the second electronic device; and initiate the one or more actions in response to detecting the inputs on the graphical user interface on the second electronic device.

11. The payment service system of claim 10, wherein at least one of the one or more actions is associated with a specified time, wherein the set of contextual information comprises a current time, and wherein identifying the one or more actions associated with the interactive element includes comparing the current time and the specified time.

12. The payment service system of claim 10, wherein at least one of the one or more actions is associated with a specified location, wherein the set of contextual information comprises a current location associated with the second electronic device, and wherein identifying the one or more actions associated with the interactive element includes comparing the current location and the specified location.

13. The payment service system of claim 10, wherein the token and the set of contextual information are received from a third-party application executing on the second electronic device of the second user.

14. The payment service system of claim 10, wherein the token and the set of contextual information are received from a second application associated with the payment service system executing on the second electronic device, and wherein the second application receives at least the token from a third-party application executing on the second electronic device.

15. One or more non-transitory computer-readable media comprising computer-readable instructions, which when executed by one or more processors of a payment service system, cause the payment service system to: configure, a graphical user interface of an application executing on a first electronic device of a first user associated with the payment service system, to provide instructions for scanning an interactive element; detect, on the graphical user interface, that the interactive element is scanned; in response to detecting that the interactive element is scanned, determine whether a token associated with the interactive element is claimed; update the graphical user interface on the first electronic device for claiming the token associated with the interactive element; update the graphical user interface on the first electronic device to receive one or more actions to be triggered when the interactive element is interacted with using a second electronic device; detect one or more inputs on the graphical user interface indicative of the one or more actions; and update, at the payment service system, a database to include the interactive element, the token claimed, and the one or more actions in association with the interactive element.

16. The one or more non-transitory computer-readable media of claim 15, wherein the payment service system has a first database of interactive elements including the interactive element and a second database of tokens including the token.

17. The one or more non-transitory computer-readable media of claim 15, wherein execution of the computer-readable instructions further cause the one or more processors to: receive, from the second electronic device of a second user of the payment service system, a scan of the interactive element and a set of contextual information; identify the one or more actions associated with the interactive element based at least in part on the set of contextual information; configure a graphical user interface on the second electronic device, the graphical user interface on the second electronic device being interactive for inputs corresponding to the one or more actions; detect the inputs on the graphical user interface on the second electronic device; and initiate the one or more actions in response to detecting the inputs on the graphical user interface on the second electronic device.

18. The one or more non-transitory computer-readable media of claim 17, wherein at least one of the one or more actions is associated with a specified time, wherein the set of contextual

information comprises a current time, and wherein identifying the one or more actions associated with the interactive element includes comparing the current time and the specified time.

19. The one or more non-transitory computer-readable media of claim 17, wherein at least one of the one or more actions is associated with a specified location, wherein the set of contextual information comprises a current location associated with the second electronic device, and wherein identifying the one or more actions associated with the interactive element includes comparing the current location and the specified location.

20. The one or more non-transitory computer-readable media of claim 17, wherein the token and the set of contextual information are received from a third-party application executing on the second electronic device of the second user.
