

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication
Kind Code
Publication Date
Inventor(s)

20250280176
A1
September 04, 2025
TASHIRO; Nagisa

SERVER AND METHOD

Abstract

A server includes a relay unit relaying video data related to a live-stream from a user terminal where the video data is generated to a user terminal where the video data is reproduced, a generation unit generating electronic data based on a part of the live-stream recorded in accordance with an instruction by a user of the user terminal where the video data is generated while the video data is reproduced; and a reception unit receiving a designation of the generated electronic data by a user of the user terminal where the video data is reproduced while the video data is reproduced.

Inventors: TASHIRO; Nagisa (Tokyo, JP)
Applicant: 17LIVE Japan Inc. (Tokyo, JP)
Family ID: 81653409
Appl. No.: 19/213565
Filed: May 20, 2025

Foreign Application Priority Data

JP 2021-212061 Dec. 27, 2021

Related U.S. Application Data

parent US continuation 18453895 20230822 parent-grant-document US 12342049 child US 19213565
parent US continuation 17868028 20220719 parent-grant-document US 11778278 child US 18453895

Publication Classification

Int. Cl.: H04N21/4784 (20110101); H04N21/2187 (20110101); H04N21/433 (20110101)

U.S. Cl.:

CPC H04N21/4784 (20130101); H04N21/2187 (20130101); H04N21/4334 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation Application of U.S. Ser. No. 18/453,895, filed on Aug. 22, 2023, which is a Continuation Application of U.S. Ser. No.

17/868,028, filed on Jul. 19, 2022 now U.S. Pat. No. 11,778,278 and claims the benefit of priority from Japanese Patent Application Serial No. 2021-212061 (filed on Dec. 27, 2021), the contents of which are hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates to a server and a method.

BACKGROUND

[0003] With the development of information technology, the way information is exchanged has changed. In the Showa period (1926-1989), one-way information communication via newspapers and television was the main stream. In the Heisei period (1990-2019), with the widespread availability of cell phones and personal computers, and the significant improvement in Internet communication speed, instantaneous interactive communication services such as chat services emerged, and on-demand video distribution services also become popular as storage costs were reduced.

[0004] Nowadays, with the sophistication of smartphones and further improvements in network speed as typified by 5G, services that enable real-time communication through video, especially live-stream services, are gaining recognition. The number of users of live-stream services is expanding, especially among young people, as such services allow people to share fun moments even when they are in the separate locations from each other.

[0005] Japanese Patent Application Publication No. 2021-158612 describes a technique in which the most exciting parts of a live broadcast video are determined, cutting out those parts to make a short video, and providing that short video to viewers who are looking for live broadcast that they should watch, thereby helping them select a live video to watch.

[0006] Gifts, such as coins, may help live-streamers engage more with viewers. If a wide variety of gifts is offered and each gift can be elaborately designed, those gifts may make live-streams more exciting.

[0007] Conventional gifts used in live-streams are provided by the platform so that gifts selectable by viewers become the same for any live-streams. However, since it is impossible to know in advance the contents of live-streams, there may be a case in which the gifts prepared by the platform are not sufficient to meet demands from the live-streamers and viewers. It is desired to create a gifting system suitable for live-streaming.

SUMMARY

[0008] In view of the above, one object of the present disclosure is to provide a technology that can realize gifting designed in consideration of the nature of live-streaming.

[0009] One aspect of the invention relates to a server. The server includes: a relay unit relaying video data related to a live-stream from a user terminal where the video data is generated to a user terminal where the video data is reproduced; a gift generation unit generating a gift based on a part of the live-stream recorded while the video data is reproduced; and a processing unit performing processing for giving the generated gift to a distributor of the live-stream while the video data is reproduced.

[0010] Another aspect of the invention relates to A non-transitory computer-readable storage medium storing a program. The non-transitory computer-readable storage medium storing a program for causing a terminal to: receive an instruction from a user to record a part of a live-stream while video data related to the live-stream is reproduced; and show a gift on a display while the video data is reproduced, the gift being generated based on the recorded part of the live-stream.

[0011] It should be noted that the components described throughout this disclosure may be interchanged or combined. The components, features, and expressions described above may be replaced by devices, methods, systems, computer programs, recording media containing computer programs, etc. Any such modifications are intended to be included within the spirit and scope of the present disclosure.

Advantageous Effects

[0012] According to the aspects of the present disclosure, gifting adapted to the nature of live-streaming can be realized.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 schematically illustrates a configuration of a live-streaming system in one embodiment of the disclosure.

[0014] FIG. 2 schematically illustrates an example of live-streaming implemented by the live-streaming system of FIG. 1.

[0015] FIG. 3 is a block diagram showing functions and configuration of a user terminal of FIG. 1.
[0016] FIG. 4 is a block diagram showing functions and configuration of a server of FIG. 1.
[0017] FIG. 5 is a data structure diagram of an example of a stream DB in FIG. 4.
[0018] FIG. 6 is a data structure diagram of an example of an army DB in FIG. 4.
[0019] FIG. 7 is a data structure diagram showing an example of a user DB in FIG. 4.
[0020] FIG. 8 is a data structure diagram showing an example of a gift DB in FIG. 4.
[0021] FIG. 9 is a flowchart showing steps of a gift usage process on a server of FIG. 1.
[0022] FIG. 10 is a representative screen image of a live streaming selection screen displayed on a display of a viewer's user terminal.
[0023] FIG. 11 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0024] FIG. 12 is a representative screen image of a screenshot standby screen displayed on the viewer's user terminal display.
[0025] FIG. 13 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0026] FIG. 14 is a representative screen image of a live streaming room screen displayed on a display of a distributor's user terminal.
[0027] FIG. 15 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0028] FIG. 16 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0029] FIG. 17 is a block diagram showing an example of a hardware configuration of an information processing device according to the embodiment.
[0030] FIG. 18 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0031] FIG. 19 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0032] FIG. 20 is a representative screen image of a viewer selection screen displayed on the display of the distributor's user terminal.
[0033] FIG. 21 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0034] FIG. 22 is a representative screen image of a live streaming room screen displayed on the display of the viewer's user terminal.
[0035] FIG. 23 is a representative screen image of a live streaming room screen displayed on the display of the distributor's user terminal.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0036] Like elements, components, processes, and signals throughout the Figures are labeled with same or similar designations and numbering, and the description for the like elements will not be hereunder repeated. For purposes of clarity and brevity, some of the components that are less related and thus not described are not shown in Figures.

[0037] In a live-streaming system according to an embodiment of the

[0038] disclosure, distributors and/or viewers are able to generate a gift from a part of a live-stream during the live-streaming. For example, distributors and/or viewers are able to create a gift from a screenshot that captures a certain special moment within the live-stream. Such a gifting system may dramatically increase the originality of the gifting and the engagement between the distributors and the viewers.

Configuration of Live-Streaming System

[0039] FIG. 1 schematically illustrates a configuration of a live-streaming system 1 according one embodiment of the disclosure. The live-streaming system 1 provides an interactive live-stream service that allows a distributor LV (also referred to as a liver or streamer) and a viewer AU (also referred to as audience) (AU1, AU2 . . .) to communicate in real time. As shown in FIG. 1, the live-streaming system 1 includes a server 10, a user terminal 20 on the distributor side, and user terminals 30 (30a, 30b . . .) on the audience side. The distributor and viewers may be collectively referred to as users. The server 10 may be one or more information processing devices connected to a network NW. The user terminals 20 and 30 may be, for example, mobile terminal devices such as smartphones, tablets, laptop PCs, recorders, portable gaming devices, and wearable devices, or may be stationary devices such as desktop PCs. The server 10, the user terminal 20, and the user terminal 30 are interconnected so as to be able to communicate with each other over the various wired or wireless network NW.

[0040] The live-streaming system **1** involves the distributor LV, the viewers AU, an administrator (not shown) who manages the server **10**. The distributor LV is a person who broadcasts contents in real time by recording the contents with his/her user terminal **20** and uploading them directly to the server **1**. Examples of the contents may include the distributor's own songs, talks, performances, fortune-telling, gameplays, and any other contents. The administrator provides a platform for live-streaming contents on the server **10**, and also mediates or manages real-time interactions between the distributor LV and the viewers AU. The viewer AU accesses the platform at his/her user terminal **30** to select and view a desired content. During live-streaming of the selected content, the viewer AU performs operations to comment and cheer via the user terminal **30**, the distributor LV who is delivering the content responds to such a comment and cheer, and such response is transmitted to the viewer AU via video and/or audio, thereby establishing an interactive communication.

[0041] The term “live-streaming” may mean a mode of data transmission that allows a content recorded at the user terminal **20** of the distributor LV to be reproduced and viewed at the user terminals **30** of the viewers AU substantially in real time, or it may mean a live broadcast realized by such a mode of transmission. The live-streaming may be achieved using existing live delivery technologies such as HTTP Live Streaming, Common Media Application Format, Web Real-Time Communications, Real-Time Messaging Protocol and MPEG DASH. Live-streaming includes a transmission mode in which the viewers AU can view a content with a specified delay simultaneously with the recording of the content by the distributor LV. As for the length of the delay, it may be acceptable for a delay even with which interaction between the distributor LV and the viewers AU can be established. Note that the live-streaming is distinguished from so-called on-demand type transmission, in which the entire recorded data of the content is once stored on the server, and the server provides the data to a user at any subsequent time upon request from the user.

[0042] The term “video data” herein refers to data that includes image data (also referred to as moving image data) generated using an image capturing function of the user terminals **20** and **30**, and audio data generated using an audio input function of the user terminals **20** and **30**. Video data is reproduced in (played on) the user terminals **20** and **30**, so that the users can view the contents.

[0043] FIG. **2** schematically illustrates an example of live-streaming implemented by the live-streaming system of FIG. **1**. In the example in FIG. **2**, the distributor LV is live-streaming his/her talk. The user terminal **20** of the distributor LV generates video data by recording images and sounds of the distributor LV talking, and the generated data is transmitted to the server **10** (not shown in FIG. **2**) over the network NW. At the same time, the user terminal **20** displays a recorded video image VD of the distributor LV on the display of the user terminal **20** to allow the distributor LV to check the live stream currently performed.

[0044] The user terminals **30a**, **30b**, and **30c** of the viewers AU1, AU2, and AU3, respectively, who have requested the platform to view the live-stream of the distributor LV, receive video data related to the live-stream over the network NW and reproduce the received video data to display video images VD1, VD2, and VD3 on the displays and output audio through the speakers (“video-data related to the live-stream” may also be herein referred to as “live-streaming video data”). The videos VD1, VD2, and VD3 displayed at the user terminals **30a**, **30b**, and **30c**, respectively, are substantially the same as the video image VD captured by the user terminal **20** of the distributor LV, and the audio outputted at the user terminals **30a**, **30b**, and **30c** is substantially the same as the audio recorded by the user terminal **20** of the distributor LV.

[0045] Recording of the images and sounds at the user terminal **20** of the distributor LV and reproduction of the video data at the user terminals **30a**, **30b**, **30c** of the viewers AU1, AU2, AU3 are performed substantially simultaneously. Once the viewer AU1 types a comment about the talk of the distributor LV on the user terminal **30a**, the server **10** displays the comment on the user terminal **20** of the distributor LV in real time and also displays the comment on the user terminals **30a**, **30b**, and **30c** of the viewers AU1, AU2, and AU3, respectively. When the distributor LV read the comment and develops his/her talk to cover and respond the comment, the video and sound of the talk are displayed on the user terminals **30a**, **30b**, **30c** of the viewers AU1, AU2, AU3 respectively. This interactive action is recognized as establishment of a conversation between the distributor LV and the viewer AU1. In this way, the live-streaming system **1** realizes the live-streaming that enables the interactive communication, not one-way communication.

[0046] FIG. **3** is a block diagram showing functions and configuration of the user terminal **20** of FIG. **1**. The user terminal **30** has the same functions and configuration as the user terminal **20**. Each block in FIG. **3** and the subsequent block diagrams may be realized by elements such as a computer CPU or a mechanical device in terms of hardware, and can be realized by a computer program or the like in terms of software. Functional blocks realized by cooperative operation between these elements. Therefore, it is understood by those skilled in the art that these functional blocks can be realized in various forms by combining hardware and software.

[0047] The distributor LV and the viewers AU download and install a live-streaming application program

(hereinafter referred to as a live-streaming application) according to the embodiment to the user terminals **20** and **30** from a download site over the network NW. Alternatively, the live-streaming application may be pre-installed on the user terminals **20** and **30**. When the live-streaming application is executed on the user terminals **20** and **30**, the user terminals **20** and **30** communicate with the server **10** over the network NW to implement various functions. Hereinafter, the functions implemented by the user terminals **20** and **30** (processors such as CPUs) in which the live-streaming application is run will be described as functions of the user terminals **20** and **30**. These functions are realized in practice by the live-streaming application on the user terminals **20** and **30**. In any other embodiments, these functions may be realized by a computer program that is written in a programming language such as HTML (HyperText Markup Language), transmitted from the server **10** to web browsers of the user terminals **20** and **30** over the network NW, and executed by the web browsers.

[0048] The user terminal **20** includes a distribution unit **100** that generates video data in which the user's image and sound are recorded and provides the video data to the server **10**, and a viewing unit **200** to which the video data is provided from the server **10** to reproduce the video data. The user activates the distribution unit **100** when the user performs live-streaming, and activates the viewing unit **200** when the user views a video. The user terminal in which the distribution unit **100** is activated is the distributor's terminal, i.e., the user terminal that generates the video data, and the user terminal in which the viewing unit **200** is activated is the viewer's terminal, i.e., the user terminal in which the video data is reproduced or played.

[0049] The distribution unit **100** includes an image capturing control unit **102**, an audio control unit **104**, a video transmission unit **106**, and a distributor-side UI control unit **108**. The image capturing control unit **102** is connected to a camera (not shown in FIG. 3) and controls image capturing performed by the camera. The image capturing control unit **102** obtains image data from the camera. The audio control unit **104** is connected to a microphone (not shown in FIG. 3) and controls audio input from the microphone. The audio control unit **104** obtains audio data through the microphone. The video transmission unit **106** transmits video data including the image data obtained by the image capturing control unit **102** and the audio data obtained by the audio control unit **104** to the server **10** over the network NW. The video data is transmitted by the video transmission unit **106** in real time. That is, the generation of the video data by the image capturing control unit **102** and the audio control unit **104**, and the transmission of the generated video data by the video transmission unit **106** are performed substantially at the same time. The distributor-side UI control unit **108** controls an UI for the distributor. The distributor-side UI control unit **108** is connected to a display (not shown in FIG. 3), and displays a video on the display by reproducing the video data that is to be transmitted by the video transmission unit **106**. The distributor-side UI control unit **108** displays an operation object or an instruction-accepting object on the display, and accepts inputs from the distributor who taps on the object.

[0050] The viewing unit **200** includes a viewer-side UI control unit **202**, a superimposed information generation unit **204**, and an input information transmission unit **206**. The viewer-side UI control unit **202** controls the UI for the viewers. The viewing-side UI control unit **202** is connected to a display and speaker (not shown in FIG. 3), and reproduces the received video data to display video images on the display and output audio through the speaker. The state where the image is outputted to the display and the audio is outputted from the speaker can be referred to as "the video data is played". The viewer-side UI control unit **202** is also connected to input means (not shown in FIG. 3) such as touch panels, keyboards, and displays, and obtains user input via these input means. The superimposed information generation unit **204** superimposes a predetermined frame image on an image generated from the video data from the server **10**. The frame image includes various user interface objects (hereinafter simply referred to as "objects") for accepting inputs from the user, comments entered by the viewers, and information obtained from the server **10**. The input information transmission unit **206** transmits the user input obtained by the viewer-side UI control unit **202** to the server **10** over the network NW.

[0051] FIG. 4 is a block diagram showing functions and configuration of the server of FIG. 1. The server **10** has a distribution information providing unit **302**, a relay unit **304**, an army management unit **306**, a regular gift processing unit **308**, a special gift processing unit **310**, a gift delivering unit **312**, a payment processing unit **314**, a stream DB **316**, an army DB **318**, a user DB **320**, and a gift DB **322**.

[0052] FIG. 5 is a data structure diagram of an example of the stream DB **316** of FIG. 4. The stream DB **316** holds information regarding a live-stream currently taking place. The stream DB **316** stores a stream ID for identifying a live-stream on a live distribution platform provided by the live-streaming system **1**, a distributor ID, which is a user ID for identifying the distributor who provides the live-stream, and a viewer ID, which is a user ID for identifying a viewer of the live-stream, in association with each other.

[0053] FIG. 6 is a data structure diagram of an example of the army DB **318** of FIG. 4. The army DB **318** holds information regarding the army of each distributor. The army DB **318** stores the distributor ID of the distributor and an army ID, which is a user ID of the user who is the army of the distributor, in association with each other.

term “army” means a user who has subscribed to a subscription service for a distributor, in other words, a member of the distributor's fan club. If you are a member of the army, you need to pay the administrator a prescribed registration or subscription fee on a regular basis, such as every month or every three months. The distributor receives at least a part of the registration fee from the administrator. When a viewer is army of a distributor, he/she can receive a special gift, a special entry animation, and any other benefits while viewing the distributor's live-stream. The army may be realized by using the technique described in “Liver Army,” 17LIVE, URL: <https://helpfeel.com/17media-jp/%E3%83%A9%E3%82%A4%E3%83%90%E3%83%BC%E3%82%A2%E3%83%BC%E3%83%9F%E3%83%BC5d1b19ed60a44d0017857bf6>.

[0054] FIG. 7 is a data structure diagram showing an example of the user DB 320 of FIG. 4. The user DB 320 holds information regarding users. The user DB 320 stores a user ID for identifying a user, points that the user has, and information about special gifts given to or given by the user, in association with each other. The point is the electronic value circulated within the live-streaming platform. When a distributor receives a gift from a viewer during a live-stream, the distributor's points increase by the value of the gift. The points are used, for example, to determine the amount of reward or money the distributor receives from the administrator of the live-streaming platform.

[0055] The information regarding the special gift includes: a special gift ID for identifying a special gift; special gift data, which is image data of the special gift; a special gift expiration date, which is the expiration date of the special gift; a special gift giver ID, which is a user ID of the user (viewer) who presented the special gift; and a special gift recipient ID, which is a user ID of the user (distributor) who has received the special gift. The special gifts will be described later in detail. The expired special gift is deleted from the user DB 320.

[0056] FIG. 8 is a data structure diagram showing an example of the gift DB of FIG. 4. The gift DB 322 holds information regarding gifts available for the viewers in the live-streaming. A gift is electronic data with the following characteristics: [0057] It can be purchased in exchange for the points, or can be given for free. [0058] It can be given by a viewer to a distributor. [0059] Giving a gift to a distributor is also referred to as using the gift or throwing the gift. [0060] Some gifts may be purchased and used at the same time, and some gifts may be purchased and then used at any time later by the purchaser viewer. [0061] When a viewer gives a gift to a distributor, the distributor is awarded the amount of points corresponding to the gift and, in some cases, an effect associated with the gift is exerted. For example, an effect corresponding to the gift will appear on the live-streaming screen.

[0062] The gift DB 322 stores a gift ID for identifying a gift, the amount of points that are given to a distributor when the gift is given to the distributor, information whether the gift is an ordinary gift or a special gift, and a gift algorithm that specifies the operation or function of the gift when the gift is the special gift, in association with each other. A viewer is able to give a desired gift to a distributor by paying the price or value equivalent to the points given to the distributor for the gift while viewing the live-stream. This payment may be performed by the viewer by an appropriate electronic means of payment, for example, by paying, to the administrator, the amount of points equivalent to the points given to the distributor (e.g., the same amount of points as the points given to the distributor, or the amount of points calculated by multiplying the points given to the distributor by a predetermined factor such as 1.2, or the amount of points calculated by adding predetermined commission points to the points given to the distributor, etc.). Alternatively, bank transfers or credit card payments may be used.

[0063] The effects of the special gifts registered in the gift DB 322 of FIG. 8 are listed below. The gift algorithm for each special gift is a software module that is configured to be executed by the CPU of the server 10 or the like to realize the corresponding effect. [0064] TD01: A special gift is generated by allowing a viewer to take a screenshot (obtain a still image) of a live-stream whenever the viewer wishes and embedding the viewer's user ID in the screenshot image. [0065] VE01: A special gift is generated by allowing a viewer to take a screenshot of a live-stream whenever the viewer wishes and converting the screenshot image into an illustration. [0066] VD01: When the total number of viewers of a live-stream of a distributor reaches a milestone (e.g., 1,000 viewers), a special gift is generated from an image of a screenshot of the live-stream that has been automatically taken. [0067] SKK1: A special gift is generated by allowing a distributor to take a screenshot of a live-stream whenever the distributor wishes and embedding a predetermined text into the screenshot image. [0068] SKK3: A special gift is generated by allowing a viewer to short-time record a live-stream whenever the viewer wishes and creating the special gift from the recorded video. [0069] SKK4: A secret gift from a distributor to a viewer. [0070] SKK5: An open gift from a distributor to a viewer. [0071] SPG01: A special gift given to a specific distributor.

[0072] Referring again to FIG. 4, the army management unit 306 performs processing related to management of an army, including registration and deregistration to the army, periodic payment of points as compensation for

members of the army, and gifting special effects to the army. For example, upon reception of an application from the user terminal **30** on the viewer side for joining an army of a specific distributor, the army management unit **306** updates the army DB **318** such that the viewer ID of the viewer is added to the army ID corresponding to the distributor ID of the specific distributor.

[0073] Upon reception of a notification from the user terminal **20** on the distributor side to start a live-stream over the network NW, the distribution information providing unit **302** registers a stream ID for identifying this live-stream and the distributor ID of the distributor who performs the live-stream in the stream DB **316**. When the distribution information providing unit **302** receives a request to provide information about live-streams from the viewing unit **200** of the user terminal **30** on the viewer side over the network NW, the distribution information providing unit **302** retrieves currently available live-streams from the stream DB **316** and makes a list of the available live-streams. The distribution information providing unit **302** transmits the list to the requesting user terminal **30** over the network NW. The viewer-side UI control unit **202** of the requesting user terminal **30** generates a live-stream selection screen based on the received list and displays it on the display of the user terminal **30**.

[0074] Once the input information transmission unit **206** of the user terminal **30** receives the viewer's selection result of the live-stream on the live-stream selection screen, the input information transmission unit **206** generates a distribution request including the stream ID of the selected live-stream, and transmits the request to the server **10** over the network NW. The distribution information providing unit **302** starts providing, to the requesting user terminal **30**, the live-stream specified by the stream ID included in the received distribution request. The distribution information providing unit **302** updates the stream DB **316** to include the viewer ID of the viewer of the requesting user terminal **30** into the viewer IDs of the stream ID.

[0075] The relay unit **304** relays the video data from the distributor-side user terminal **20** to the viewer-side user terminal **30** in the live-streaming started by the distribution information providing unit **302**. The relay unit **304** receives from the input information transmission unit **206** a signal that represents user input by the viewer during reproduction of the video data on the viewer-side user terminal **30**. The signal representing the user input may be a gift usage signal. The gift usage signal includes the viewer ID of the viewer, the distributor ID of the distributor to whom the gift is given (the distributor ID of the distributor performing the live-stream that is being viewed by the viewer who gave the present), and the gift ID of the gift. The relay unit **304** refers to the gift DB **322** and determines whether the gift identified by the gift ID included in the received gift usage signal is a normal gift or a special gift.

[0076] When the gift identified by the gift ID included in the gift usage signal is a normal gift, the normal gift processing unit **308** updates the user DB **320** so as to increase the points of the distributor depending on the points of the normal gift. Specifically, the normal gift processing unit **308** refers to the gift DB **322** to specify the points to be given for the gift ID included in the received gift usage signal. The normal gift processing unit **308** then updates the user DB **320** to add the determined points to the points of the distributor ID included in the gift usage signal.

[0077] When the gift identified by the gift ID included in the gift usage signal is a special gift, the special gift processing unit **310** generates the special gift based on a part of the live-stream recorded during the reproduction of the video data related to the live-stream. In the embodiment, the special gift processing unit **310** is capable of generating the following five types of special gifts. [0078] (1) Paid gifts generated based on a part of a live-stream recorded according to a viewer's instruction (e.g.: TD01, VE01, SKK3) [0079] (2) Paid gifts generated based on a part of a live-stream recorded according to a distributor's instruction (e.g.: SKK1) [0080] (3) Paid gifts generated based on a part of a live-stream automatically recorded on condition that a condition related to the live-stream is satisfied (e.g.: VD01) [0081] (4) Free gifts generated based on a part of a live-stream recorded according to an Army's instruction (the free gifts can be generated without payment) [0082] (5) Paid gifts from a distributor to a specific viewer. (e.g.: SKK4, SKK5)

[0083] The above special gifts (1) to (4) will be now described, and the special gift (5) will be described in a modification example.

[0084] The gift delivering unit **312** performs processing for giving such a special gift generated by the special gift processing unit **310** to a distributor of the live-stream during reproduction of the video data related to the live-stream. When the special gift is a paid gift, the gift delivering unit **312** performs processing for giving the special gift to a distributor when the gift delivering unit **312** receives an instruction of payment associated with the generated special gift from a viewer. The gift delivering unit **312** performs the following four steps in order to give a special gift to a distributor. [0085] (1) Transmit image data for displaying the special gift to the distributor's user terminal **20** and the viewer's user terminal **30**. [0086] (2) Update the user DB **320** so as to increase the points of the distributor depending on the points of the special gift. [0087] (3) Generate special gift

information (the special gift ID, special gift expiration date, special gift giver ID, special gift recipient ID) for the special gift, and register the information in association with the giver viewer and the recipient distributor in the user DB **320**. [0088] (4) Register the special gift ID and the points of the special gift in the gift DB **322**.

[0089] The payment processing unit **314** processes the viewer's payment of the price or value equivalent to the generated special gift. The equivalent value may be paid in advance, for example, the payment of the value may be received before the special gift is generated, or the equivalent value may be paid after the special gift is generated and before the special gift is given to the distributor. When the payment processing unit **314** receives an instruction of paying the equivalent value for the special gift from a viewer, the payment processing unit **314** updates the user DB **320** to subtract the points of the equivalent value from the points of the viewer.

[0090] The payment processing unit **314** processes the viewer's payment of the price or value equivalent to a normal gift. When the gift identified by the gift ID included in the gift usage signal is a normal gift, the payment processing unit **314** updates the user DB **320** to subtract the points of the value equivalent to the normal gift from the points of the viewer identified by the viewer ID included in the gift usage signal.

[0091] The operation of the live-streaming system **1** with the above configuration will be now described. FIG. **9** is a flowchart showing steps of a gift usage process on the server **10**. This example describes usage of a prepaid or free special gift generated from a screenshot. In the example, it is assumed that the viewer accesses the live-stream platform from the user terminal **30**, selects a desired live-stream on the live-stream selection screen, and starts viewing the selected live-stream. While the viewer is watching the live-stream, the video data is continuously transmitted from the distributor's user terminal **20** to the viewer's user terminal **30** via (the relay unit **304** of) the server **10**.

[0092] During the reproduction of the video data, the viewer performs user input for requesting display of a gift via input means of the user terminal **30**. Upon receipt of this user input, the input information transmission unit **206** of the user terminal **30** generates a gift information request and transmits it to the server **10**. Upon receipt of the gift information request, the relay unit **304** of the server **10** refers to the gift DB **322** and specifies usable gift IDs. The relay unit **304** generates a gift information response including the specified gift IDs and transmits it to the user terminal **30**. The superimposed information generation unit **204** of the user terminal **30** includes, into the frame image, an image of a usable gift list that lists the gift icon images (hereinafter referred to as gift icons) specified by the gift IDs included in the gift information response. The viewer-side UI control unit **202** displays the video image on which the frame image is superimposed on the display.

[0093] Once the viewer-side UI control unit **202** of the user terminal **30** accepts the viewer's selection of the gift, that is, the designation of the gift icon, the input information transmission unit **206** generates the gift usage signal that includes the gift ID of the designated gift, the viewer ID, and the distributor ID, and transmits the gift usage signal to the server **10** over the network NW. The relay unit **304** of the server **10** receives the gift usage signal (S502). The relay unit **304** refers to the gift DB **322** and determines whether the gift identified by the gift ID included in the received gift usage signal is a normal gift or a special gift (S504). When the gift is a normal gift, the payment processing unit **314** performs the payment process (S506). The normal gift processing unit **308** performs processing for giving points to the distributor (S508). The process then returns to step S502.

[0094] When the gift is determined as a special gift in step S504, the payment processing unit **314** performs the payment process (S510). The payment processing unit **314** refers to the gift DB **322** and determines whether the special gift identified by the gift ID included in the gift usage signal received in step S502 is a free special gift exclusively given for army. When it is the free special gift exclusively given for army, the payment processing unit **314** refers to the army DB **318** to determine whether the viewer specified by the viewer ID included in the gift usage signal received in step S502 is the army of the distributor specified by the distributor ID included in the same gift usage signal. When it is determined that the viewer is not the army, the payment processing unit **314** generates an error signal and transmits it to the user terminal **30**. Upon receipt of the error signal, the viewer-side UI control unit **202** of the user terminal **30** displays a text indicating that the gift cannot be used unless the viewer is army on the display. When it is determined that the viewer is the army, the payment processing unit **314** completes the payment process without changing the viewer's points.

[0095] When the special gift specified by the gift ID included in the gift usage signal received in step S502 is not the free special gift exclusively given for army, the payment processing unit **314** updates the user DB **320** such that the points corresponding to the equivalent value or price of the special gift is deducted from the points of the viewer specified by the viewer ID included in the gift usage signal. The equivalent value for the special gift may be the same as the points given to the distributor or may be configured differently.

[0096] When the special gift is manually generated (manual in S512), the special gift processing unit **310** generates a usage permission signal that includes the gift ID of the special gift and the part of the gift algorithm

corresponding to the special gift that should be executed on the user terminal, and transmits the signal to the user terminal **30** that has transmitted the gift usage signal over the network NW (**S514**). Upon receipt of the usage permission signal, the viewing unit **200** of the user terminal **30** is allowed to capture a screenshot of the live-stream by executing the part of the gift algorithm included in the usage permission signal. The viewer inputs an instruction at a desired timing. Upon reception of the instruction, the viewing unit **200** captures a screenshot of the live-stream at that time. The input information transmission unit **206** transmits the obtained screenshot data to the server **10** over the network NW. The special gift processing unit **310** receives the data so transmitted (**S516**).

[0097] When the special gift is automatically generated (automatic in **S512**), the special gift processing unit **310** determines whether a record condition set in association with the special gift is satisfied (**S518**). The record condition is, for example, that the cumulative number of viewers of the live-stream performed by the distributor reaches a milestone (for example, **1000** people), the cumulative live-streaming time of the distributor reaches a threshold, or the like. In this way, the record condition may be a condition imposed on the parameters related to the live-streams, a condition imposed on the status of the distributor (e.g., winning an event), or a condition imposed on the behavior of the viewer (e.g., making more than a predetermined number of comments). When it is determined that the record condition is satisfied (YES in **S518**), the special gift processing unit **310** obtains a screenshot at that time during broadcast of the video data (**S520**).

[0098] When illustration is instructed (YES in **S522**), the special gift processing unit **310** converts the image of the received or obtained screenshot into an illustration (**S524**). The illustration may be realized by using a known image processing technique as described in “Actually easy! How to convert a photo into an illustration or painting style with Photoshop,” URL: <https://design-trekker.jp/design/photoshop/turn-photos-into-illustrations/>.

[0099] The special gift processing unit **310** generates a special gift based on the image of the screenshot received or obtained (**S526**). If the illustration is not performed, the special gift processing unit **310** generates an image of a special gift by embedding the ID of the giver viewer in the image of the screenshot. A new gift ID is then given to the image. When the illustration is performed, the special gift processing unit **310** uses the illustrated image as it is as an image of the special gift, and assigns a new gift ID to the image.

[0100] The gift delivering unit **312** gives points corresponding to the generated special gift to the distributor (**S528**). The gift delivering unit **312** updates the user DB **320** to add the points corresponding to the special gift are added to the points of the distributor specified by the distributor ID included in the gift usage signal received in step **S502**. The gift delivering unit **312** transmits the image of the special gift generated in step **S526** to the distributor's user terminal **20** and the viewer's user terminal **30** (**S530**). The gift delivering unit **312** also registers special gift information in the gift DB **322** and the user DB **320**. The user terminals **20** and **30** show the image of the special gift on the display during the reproduction of the video data related to the live-stream.

[0101] FIG. **10** is a representative screen image of the live-stream selection screen **602** displayed on the display of the viewer user terminal **30**. The live-stream selection screen **602** includes thumbnails **604** indicating live-streams in the list of currently available live streams. The viewer-side UI control unit **202** generates the live-stream selection screen **602** based on the list of live-streams obtained from the server **10** and shows the screen on the display.

[0102] FIG. **11** is a representative screen image of the live-stream selection screen **610** displayed on the display of the viewer user terminal **30**. Once the viewer taps one of the thumbnails **604** on the live-stream selection screen **602** of FIG. **10**, the live-streaming room screen **610** of FIG. **11** is shown on the display. The live-streaming room screen **610** includes a distributor image **612** obtained by reproducing the video data, and an image of an available gift list. The available gift list image includes a gift icon **614** for the normal gift, a gift icon **616** for the special gift identified by the gift ID “TD01” of FIG. **8**, and a gift icon **618** for the special gift identified by the gift ID “VE01” of FIG. **8**, a special gift icon **620** identified by the gift ID “VD01” of FIG. **8**, and a special gift icon **622** identified by the gift ID “SKK3” of FIG. **8**.

[0103] Once a viewer taps the gift icon **616** of the special gift on the live-streaming room screen **610** of FIG. **11**, the user terminal **30** accepts the designation of the special gift by the viewer. The user terminal **30** generates a gift usage signal including the gift ID (in this case, “TD01”) of the designated special gift, and transmits it to the server **10** over the network NW. The user terminal **30** receives, from the server **10**, a usage permission signal responding to the transmitted gift usage signal. The user terminal **30** allows the viewer to obtain a screenshot based on the usage permission signal. Specifically, the user terminal **30** causes the display to show a screenshot standby screen **624**.

[0104] FIG. **12** is a representative screen image of the screenshot standby screen displayed on the viewer's user terminal display. The screenshot standby screen **624** has a distributor image **612** obtained by reproducing the video data, and a screenshot icon **626**. The screenshot standby screen **624** is a screen for receiving an instruction

from the user to record an image of a screenshot that is a part of the live-stream during reproduction of the video data related to the live-stream. The viewer waits for a moment that may be unique to the live-stream while watching the image **612** of the distributor, and when the moment comes, the viewer taps the screenshot icon **626**. Upon detection of the tapping on the screenshot icon **626**, the user terminal **30** generates a screenshot of the image **612** of the distributor at that time. Here, the viewer may be allowed to retake the screenshot.

[0105] The user terminal **30** transmits the generated screenshot image to the server **10**. The server **10** generates a special gift image by embedding the viewer ID of the viewer who took the screenshot in the image of the screenshot. The server **10** transmits the generated special gift image to the user terminal **30**. The user terminal **30** superimposes the received image of the special gift on the image of the live-stream and shows it on the display.

[0106] FIG. **13** is a representative screen image of the live-stream selection screen **630** displayed on the display of the viewer user terminal **30**. Once the viewer taps the screenshot icon **626** on the screenshot standby screen **624** of FIG. **12**, the live-streaming room screen **630** of FIG. **13** is shown on the display. The live-streaming room screen **630** includes a distributor image **612** and a special gift image **628** displayed in association therewith. The image **628** of the special gift is displayed during the live-stream that has been being broadcast since the generation of the special gift. The image **628** of the special gift includes an image based on the image of the screenshot obtained by the viewer's instruction, and the viewer ID of the viewer. The special gift image **628** similarly appears on the user terminals of other viewers to whom the same live-stream is distributed and on the user terminal of the distributor of the same live-stream. By displaying the image **628** of the special gift in the live-streaming room of the distributor, the special moment in which the special gift is displayed in the room can be shared between the distributor and the viewer. In addition, by showing the viewer ID of the viewer who gave the special gift together with the gift, it is possible to inform to other viewers that the viewer is associated closer with the distributor relative to other viewers.

[0107] FIG. **14** is a representative screen image of a live-streaming room screen **632** shown on the display of the distributor's user terminal. The live-streaming room screen **632** includes a distributor image **634** obtained by reproducing the video data that is transmitted to the server **10**, a gift icon **636** of the special gift specified by the gift ID "SKK1" in FIG. **8**, a gift icon **638** of the special gift specified by the gift ID "SKK4" in FIG. **8**, and a gift icon **640** of the special gift specified by the gift ID "SKK5" in FIG. **8**.

[0108] The gift icon **636** is an object for receiving an instruction from the distributor to record an image of a screenshot that is a part of the live-stream during reproduction of the video data related to the live-stream. The distributor waits for a moment that may be unique to the live-stream while watching the image **634** of the distributor himself/herself, and when the moment comes, the distributor taps the gift icon **636**. Upon detection of the tapping on the gift icon **636**, the user terminal **20** generates a screenshot of the image **634** of the distributor at that time. The user terminal **20** transmits, to the server **10**, a special gift generation request that includes the generated screenshot image and the gift ID "SKK1". By referring to the gift DB **322**, the server **10** obtains and executes the gift algorithm of the special gift specified by the gift ID included in the special gift generation request. Specifically, the server **10** generates an image of the special gift by embedding a predetermined text specified by the distributor in the screenshot image included in the special gift generation request. The server **10** converts the generated special gift image into a gift icon **642**. The server **10** transmits the gift icon **642** to the user terminal **30** of the viewer. The user terminal **30** superimposes the received gift icon **642** on the image of the live-stream and shows it on the display.

[0109] FIG. **15** is a representative screen image of a live-stream selection screen **644** displayed on the display of the viewer user terminal **30**. The live-streaming room screen **644** includes the distributor image **634** and the gift icon **642** received from the server **10**. The distributor appeals to the viewers to purchase the special gift corresponding to the gift icon **642** during the live-stream. Once a viewer taps the gift icon **642** on the live-streaming room screen **644** of FIG. **15**, the user terminal **30** accepts the designation of the special gift by the viewer. The user terminal **30** generates a gift usage signal including the gift ID (in this case, "SKK1") corresponding to the designated gift icon **642**, and transmits it to the server **10** over the network NW. Upon receipt of the gift usage signal, the server **10** performs a payment process and a point giving process. The server **10** embeds the viewer ID included in the gift usage signal into the image of the special gift corresponding to the gift icon **642**. The server **10** transmits the image **648** of the special gift so processed to the user terminals **20** and **30**. The user terminals **20** and **30** superimpose the received image **648** of the special gift on the image of the live-stream and show it on the displays.

[0110] FIG. **16** is a representative screen image of a live-stream selection screen **646** shown on the display of the viewer user terminal **30**. Once the viewer taps the gift icon **642** on the live-stream selection screen **644** of FIG. **15**, the live-streaming room screen **646** of FIG. **16** is shown on the display. The live-streaming room screen **646** includes a distributor image **634** and a special gift image **648** displayed in association therewith.

[0111] In the above embodiment, an example of a holding unit includes a hard disk or semiconductor memory. It is understood by those skilled in the art that each element or component can be realized by a CPU not shown, a module of an installed application program, a module of a system program, or a semiconductor memory that temporarily stores the contents of data read from the hard disk, and the like.

[0112] With the live-streaming system **1**, a gift based on a part of the live-stream can be generated during the live-stream, and the gift can be given to the distributor during the same live-stream. This makes it possible to convert events and moments unique to live-streaming into gifts instantly, making the live-streaming much more exciting and increasing the engagement of the viewers and the distributor with the live-stream. In addition, decorating the live-streaming room with such gifts enables further personalization of the live-streaming room, and thus contributes to increasing the diversity of such live-streaming rooms.

[0113] The moments that are unique to the live-streaming are, for example, the moment when the distributor wins the first place in an event held on the live-streaming platform, the moment when the distributor gives a perfect performance, the moment when cards are laid out on the table and the hand is held over the crystal in the case of tarot reading, or the moment when the distributor wins in the case of game play.

[0114] In addition, the live-streaming system **1** enables automatic generation of special gifts based on predetermined conditions. This makes it possible to more accurately capture moments that are difficult to specify manually, for example, the moment the distributor reaches a milestone, and to convert the moment into a gift.

[0115] In addition, the live-streaming system **1** of the embodiment allows viewers to generate special gifts without paying for the gifts when they are members of the distributor's army. This allows the viewers in the distributor's army to give the special gifts unlimitedly, thus promoting the development of a culture unique to live-streaming, such as "always throw a special gift at a certain moment specific to the distributor."

Alternatively, for this purpose, the special gifts can be made as free gifts with no points and no payment. In this case, although no points are given to the distributor, it can greatly increase the excitement of the live-stream.

Hardware Configuration Example

[0116] Referring to FIG. **17**, the hardware configuration of the information processing device will be now described. FIG. **17** is a block diagram showing an example of a hardware configuration of the information processing device according to the embodiment. The illustrated information processing device **900** may, for example, realize the server **10** and the user terminals **20** and **30** in the embodiment.

[0117] The information processing device **900** includes a CPU **901**, ROM (Read Only Memory) **903**, and RAM (Random Access Memory) **905**. The information processing device **900** may also include a host bus **907**, a bridge **909**, an external bus **911**, an interface **913**, an input device **915**, an output device **917**, a storage device **919**, a drive **921**, a connection port **925**, and a communication device **929**. In addition, the information processing device **900** includes an image capturing device such as a camera (not shown). In addition to or instead of the CPU **901**, the information processing device **900** may also include a DSP (Digital Signal Processor) or ASIC (Application Specific Integrated Circuit).

[0118] The CPU **901** functions as an arithmetic processing device and a control device, and controls all or some of the operations in the information processing device **900** according to various programs stored in the ROM **903**, the RAM **905**, the storage device **919**, or the removable recording medium **923**. For example, the CPU **901** controls the overall operation of each functional unit included in the server **10** and the user terminals **20** and **30** in the embodiment. The ROM **903** stores programs, calculation parameters, and the like used by the CPU **901**. The RAM **905** serves as a primary storage that stores a program used in the execution of the CPU **901**, parameters that appropriately change in the execution, and the like. The CPU **901**, ROM **903**, and RAM **905** are interconnected to each other by a host bus **907** which may be an internal bus such as a CPU bus. Further, the host bus **907** is connected to an external bus **911** such as a PCI (Peripheral Component Interconnect/Interface) bus via a bridge **909**.

[0119] The input device **915** may be a user-operated device such as a mouse, keyboard, touch panel, buttons, switches and levers, or a device that converts a physical quantity into an electric signal such as a sound sensor typified by a microphone, an acceleration sensor, a tilt sensor, an infrared sensor, a depth sensor, a temperature sensor, a humidity sensor, and the like. The input device **915** may be, for example, a remote control device utilizing infrared rays or other radio waves, or an external connection device **927** such as a mobile phone compatible with the operation of the information processing device **900**. The input device **915** includes an input control circuit that generates an input signal based on the information inputted by the user or the detected physical quantity and outputs the input signal to the CPU **901**. By operating the input device **915**, the user inputs various data and instructs operations to the information processing device **900**.

[0120] The output device **917** is a device capable of visually or audibly informing the user of the obtained

information. The output device **917** may be, for example, a display such as an LCD, PDP, or OLED, etc., a sound output device such as a speaker and headphones, and a printer. The output device **917** outputs the results of processing by the information processing unit **900** as text, video such as images, or sound such as audio. [0121] The storage device **919** is a device for storing data configured as an example of a storage unit of the information processing equipment **900**. The storage device **919** is, for example, a magnetic storage device such as a hard disk drive (HDD), a semiconductor storage device, an optical storage device, or an optical magnetic storage device. This storage device **919** stores programs executed by the CPU **901**, various data, and various data obtained from external sources.

[0122] The drive **921** is a reader/writer for a removable recording medium **923** such as a magnetic disk, an optical disk, a photomagnetic disk, or a semiconductor memory, and is built in or externally attached to the information processing device **900**. The drive **921** reads information recorded in the mounted removable recording medium **923** and outputs it to the RAM **905**. Further, the drive **921** writes record in the attached removable recording medium **923**.

[0123] The connection port **925** is a port for directly connecting a device to the information processing device **900**. The connection port **925** may be, for example, a USB (Universal Serial Bus) port, an IEEE1394 port, an SCSI (Small Computer System Interface) port, or the like. Further, the connection port **925** may be an RS-232C port, an optical audio terminal, an HDMI (registered trademark) (High-Definition Multimedia Interface) port, or the like. By connecting the external connection device **927** to the connection port **925**, various data can be exchanged between the information processing device **900** and the external connection device **927**.

[0124] The communication device **929** is, for example, a communication interface formed of a communication device for connecting to the network NW. The communication device **929** may be, for example, a communication card for a wired or wireless LAN (Local Area Network), Bluetooth (trademark), or WUSB (Wireless USB).

[0125] Further, the communication device **929** may be a router for optical communication, a router for ADSL (Asymmetric Digital Subscriber Line), a modem for various communications, or the like. The communication device **929** transmits and receives signals and the like over the Internet or to and from other communication devices using a predetermined protocol such as TCP/IP. The communication network NW connected to the communication device **929** is a network connected by wire or wirelessly, and is, for example, the Internet, home LAN, infrared communication, radio wave communication, satellite communication, or the like. The communication device **929** realizes a function as a communication unit.

[0126] The image capturing device (not shown) is an imaging element such as a CCD (Charge Coupled Device) or CMOS (Complementary Metal Oxide Semiconductor), and a device that captures an image of the real space using various elements such as lenses for controlling image formation of a subject on the imaging element to generate the captured image. The image capturing device may capture a still image or may capture a moving image.

[0127] The configuration and operation of the live-streaming system **1** in the embodiment have been described. This embodiment is a merely example, and it is understood by those skilled in the art that various modifications are possible for each component and a combination of each process, and that such modifications are also within the scope of the present disclosure.

[0128] In the above embodiment described with reference to FIGS. **11**, **12**, and **13**, the special gift is generated by taking a screenshot of the live-stream by the viewer. But the embodiment is not limited to this. For example, the server **10** may be configured to allow the special gift generated in such a way to be purchased again by the viewer or other viewers. In this case, after the live-streaming room screen **630** of FIG. **13** is shown on the display of the user terminal **30** of the viewer, the viewer performs user input for requesting the display of the gift via the input means of the user terminal **30**. Upon receipt of this user input, the input information transmission unit **206** of the user terminal **30** generates a gift information request and transmits it to the server **10**. Upon receipt of the gift information request, the relay unit **304** of the server **10** refers to the gift DB **322** and specifies available gift IDs. At this time, the relay unit **304** determines whether the special gift “SPG01” that has been generated through the processes of FIGS. **11**, **12**, and **13** and registered in the gift DB **322** is usable by referring the user DB **320**. When the special gift “SPG01” is registered as a special gift given to the distributor identified by the distributor ID (the distributor of the live-stream being viewed by the viewer who has transmitted the gift information request) included in the gift information request, the relay unit **304** determines that the special gift “SPG01” can be used, otherwise it determines that it is not available. The relay unit **304** generates a gift information response including the gift IDs that have been determined as available and transmits it to the user terminal **30**. The superimposed information generation unit **204** of the user terminal **30** includes, into the frame image, an image of a usable gift list that lists the gift icon images specified by the gift IDs included in the gift

information response. The viewer-side UI control unit **202** displays the video image on which the frame image is superimposed on the display.

[0129] FIG. **18** is a representative screen image of a live-streaming room **660** shown on the display of the viewer user terminal **30**. The live-streaming room screen **660** includes a distributor image **612** obtained by reproducing the video data, and an image of an available gift list. The available gift list image has a gift icon **662** of the special gift identified by the gift ID “SPG01”. Once the viewer taps the gift icon **662** on the live-streaming room screen **660** of FIG. **18**, the user terminal **30** accepts the designation of the special gift icon **662** by the viewer. The user terminal **30** generates a gift usage signal including the gift ID (in this case, “SPG01”) corresponding to the designated gift icon **662**, and transmits it to the server **10** over the network NW. Upon receipt of the gift usage signal, the server **10** performs a payment process and a point giving process. The server **10** transmits the image **628** of the special gift “SPG01” to the user terminals **20** and **30**. The user terminals **20** and **30** superimpose the received image **628** of the special gift on the image of the live-stream and show it on the displays.

[0130] FIG. **19** is a representative screen image of a live-stream selection screen **664** shown on the display of the viewer user terminal **30**. Once the viewer taps the gift icon **662** on the live-stream selection screen **660** of FIG. **18**, the live-streaming room screen **664** of FIG. **19** is shown on the display. The live-streaming room screen **664** includes the distributor image **612** and two or more special gift images **628** displayed in association therewith. The live-streaming room screen **664** displays the images **628** of the same number of special gifts as were given to the distributor. In this way, it is possible to indicate favors from other viewers for the special gift generated by one viewer. In addition, when a viewer purchases the same special gift more than once, it can indicate the strength of the viewer's feeling toward the moment that the special gift represents.

[0131] In this modification example, it may be configured to display not only the special gift generated during the live-stream currently being delivered, but also a special gift generated in another past live-stream by the same distributor, and such a gift may be selectable.

[0132] A modification example of giving a paid gift from a distributor to a specific viewer will be described. Once the distributor taps the gift icon **640** of the special gift “SKK5” on the live-streaming room screen **632** of FIG. **14**, the user terminal **20** accepts the designation of the special gift by the distributor. The user terminal **20** generates a gift usage signal that includes the gift ID (in this case, “SKK5”) of the designated special gift, and transmits it to the server **10** over the network NW. By referring to the gift DB **322**, the server **10** obtains and executes the gift algorithm of the special gift specified by the gift ID included in the received gift usage signal. Specifically, the server **10** refers to the stream DB **316** to determine the viewer IDs of the viewers who are currently watching the live-stream specified by the stream ID included in the gift usage signal received (from the distributor). The server **10** obtains the information related to the specified viewer ID by referring to the user DB **320**. The server **10** generates viewer list information including the specified viewer IDs and the obtained information, and transmits the viewer list information to the user terminal **20** of the distributor. In this example, the case in which the recipient viewers are selected from among the viewers of the live-stream currently being distributed by the distributor is described. In other examples, the recipient viewers may be selected from among all the users of the live-streaming platform registered in the user DB **320**.

[0133] Based on the received viewer list information, the user terminal **20** generates a viewer selection screen **666** for the distributor to select viewers to whom the special gift should be given, and shows the screen on the display. FIG. **20** is a representative screen image of the viewer selection screen **666** shown on the display of the distributor's user terminal **20**. The viewer selection screen **666** shows the viewer IDs **668** of the viewers who are currently watching the live-stream of the distributor in association with the information **670** of those viewers. On the viewer selection screen **666**, the viewer information may be sorted and displayed according to a predetermined criterion (for example, in descending order of total gifting amount, longest viewing time, etc.). The distributor taps the viewer ID **668** or information **670** of the viewer to whom the distributor wishes to give the special gift. The user terminal **20** determines the viewer designated by the distributor through tapping as the recipient of the special gift. The user terminal **20** generates a public gift presenting request that includes the viewer ID of the designated viewer and sends the request to the server **10**. Upon receiving the public gift presenting request, the server **10** updates the user DB **320** to deduct the points equivalent to the special gift specified by the gift ID “SKK5” included in the public gift presenting request from the distributor's points. The server **10** updates the user DB **320** such that the points of the viewer specified by the viewer ID included in the public gift presenting request are increased by the points of the special gift “SKK5” given to the viewer. The server **10** generates a text indicating that the distributor has given the gift to the viewer, and transmits the text to the user terminal **20** of the distributor and to the user terminals **30** of the viewers including the viewer of the recipient. The user terminal **30** of the viewer superimposes and displays the received text as a comment on the

image of live-stream.

[0134] FIG. 21 is a representative screen image of a live-streaming room screen 672 shown on the display of the viewer user terminal 30. On the live-streaming room screen 672, a comment 674 is superimposed and shown on the image 612 of the distributor. The comment 674 includes a text received from the server 10 indicating that the distributor has given the viewer a gift. This comment 674 is displayed on the user terminals 30 of all the viewers who are watching the live-stream.

[0135] When the distributor taps the gift icon 638 of the special gift “SKK4” on the live-streaming room screen 632 of FIG. 14, the same processing as described above for the special gift “SKK5” is executed. The difference is that the text indicating that the distributor has given the gift to the viewer is transmitted only to the user terminal 30 of the viewer to whom the gift is given, and is displayed only on the user terminal 30 of the viewer.

[0136] Since the distributor is able to give a gift(s) to a viewer(s), it is possible to help the distributor to build a closer relationship with his/her viewers. For example, such gifting can be used as a tool to promote the distributor himself/herself to influential viewers.

[0137] In the embodiment, the case where a viewer gives a special gift to a distributor while the viewer is watching the live-stream has been described, but the present disclosure is not limited to this. For example, a viewer who has purchased a special gift may become a distributor and the distributor may advertise and sell the special gift in his/her live-stream. For example, in the example of FIG. 7, it is assumed that the user with the user ID “SS5” purchased and gave the special gift “SPG01” in a live-stream performed by the user with the user ID “001A” in the past. A viewer of a live-stream performed by the user of the user ID “SS5” may request display of the gift via the input means of the user terminal 30. Upon receipt of this user input, the input information transmission unit 206 of the user terminal 30 generates a gift information request and transmits it to the server 10. Upon receipt of the gift information request, the relay unit 304 of the server 10 refers to the gift DB 322 and specifies usable gift IDs. At this time, the relay unit 304 determines whether the special gift “SPG01” is available by referring the user DB320. When the special gift “SPG01” is registered as a special gift that has been given by the distributor identified by the distributor ID “SS5” included in the gift information request to other user, the relay unit 304 determines that the special gift “SPG01” can be used. The relay unit 304 generates a gift information response including the gift IDs that have been determined as available and transmits it to the user terminal 30. The superimposed information generation unit 204 of the user terminal 30 includes, into the frame image, an image of a usable gift list that lists the gift icon images specified by the gift IDs included in the gift information response. The viewer-side UI control unit 202 displays the video image on which the frame image is superimposed on the display.

[0138] FIG. 22 is a representative screen image of a live-streaming room screen 676 shown on the display of the viewer user terminal 30. The live-streaming room screen 676 includes an image 678 of the distributor “SS5” obtained by reproducing the video data, and an image of an available gift list. The available gift list image has a gift icon 680 of the special gift identified by the gift ID “SPG01”. On the live-streaming room screen 676, the distributor “001A” to whom the special gift “SPG01” indicated by the gift icon 680 is given is different from the distributor “SS5” of the distributor image 678 being reproduced in the live-streaming room screen 676. The distributor “SS5” of the giver of the special gift “SPG01” indicated by the gift icon 680 is identical to the distributor “SS5” of the distributor image 678 being reproduced on the live-streaming room screen 676. It can be known from the live-streaming room screen 676 that the distributor “SS5” supports another distributor “001A” and asks his/her viewers to purchase the special gift “SPG01” for the distributor “001A”.

[0139] Once the viewer taps the gift icon 680 on the live-streaming room screen 676 of FIG. 22, the user terminal 30 accepts the designation of the special gift icon 680 by the viewer. The user terminal 30 generates a gift usage signal including the gift ID (in this case, “SPG01”) corresponding to the designated gift icon 680, and transmits it to the server 10 over the network NW. Upon receipt of the gift usage signal, the server 10 updates the user DB 320 to deduct the points equivalent to the special gift specified by the gift ID “SPG01” included in the gift usage signal from the viewer's points. The server 10 updates the user DB 320 to increase the points of the user to whom the special gift “SPG01” is given (in this case, the user identified by the user ID “001A”) by the points of the special gift “SPG01”. Alternatively, the points of the gift may be apportioned between the user “001A” to whom the special gift “SPG01” is given and the live-stream distributor “SS5” from whom the special gift “SPG01” has been purchased. The server 10 transmits, to the user terminal 20 of the user “001A” to whom the special gift “SPG01” is given, a text indicating that the special gift “SPG01” has been sold in the live-stream of the distributor “SS5” and an image 628 of the special gift “SPG01”. The user terminal 20 superimposes and shows the received text as a comment on the image of the live-stream.

[0140] FIG. 23 is a representative screen image of a live-streaming room screen 682 shown on the display of the distributor's user terminal. The live-streaming room screen 682 includes the image 684 of the distributor “001A”

obtained by reproducing the video data, the images **628** of the special gifts as many as the number of the presented special gifts, and a comment **686** superimposed on the image **684** of the distributor “001A”. The comment **686** includes a text received from the server **10** indicating that the special gift “SPG01” has been sold in the live-stream of the distributor “SS5”. This comment **686** is displayed on the user terminals **30** of all the viewers who are watching the live-stream of the distributor “001A”. In this way, even when the giver of the special gift is performing live-stream and cannot participate in the live-stream of the recipient's distributor, the giver of the special gift can support the recipient's distributor through his/her own live-stream.

[0141] In the embodiment, the server **10** may be configured to allow the user terminals **20** and **30** to view the information on the special gifts given by a user and/or given to the user by requesting the server **10** from the user terminals **20** and **30** even when the live-stream is not performed.

[0142] The conversion rate from the value equivalent to the gift to the points of the gift in the embodiment is merely example, and the conversion rate may be appropriately set by the administrator of the live-streaming system **1**, for example.

[0143] The technical idea according to the embodiment may be applied to live commerce or virtual live-streaming using an avatar that moves in synchronization with the movement of the distributor instead of the image of the distributor.

[0144] The procedures described herein, particularly those described with a flowchart, are susceptible of omission of part of the steps constituting the procedure, adding steps not explicitly included in the steps constituting the procedure, and/or reordering the steps. The procedure subjected to such omission, addition, or reordering is also included in the scope of the present invention unless diverged from the purport of the present disclosure.

[0145] At least some of the functions realized by the server **10** may be realized by a device(s) other than the server **10**, for example, the user terminals **20** and **30**. At least some of the functions realized by the user terminals **20** and **30** may be realized by a device(s) other than the user terminals **20** and **30**, for example, the server **10**. For example, the superimposition of a predetermined frame image on an image of the video data performed by the user terminal where the video data is reproduced may be performed by the server **10** or may be performed by the user terminal where the video data is generated. In addition, at least a part of the generation of a special gift may be performed on the user terminal.

Claims

1. A server, comprising: a relay unit configured to relay video data related to a live-stream from a first user terminal of a first user where the video data is generated to a second user terminal of a second user where the video data is reproduced; a reception unit configured to receive, from the second user terminal of the second user, a signal indicating that a gift is used by the second user while the video data is reproduced; and a processing unit configured to perform, in response to reception of the signal, processing for giving said gift to a third user who is different from the first user.
2. The server of claim 1, further comprising: a gift generation unit configured to generate said gift in another, past live-stream in which the third user participates as a distributor and in which the first user participates as a viewer.
3. The server of claim 2, wherein said gift is generated based on a part of the another, past live-stream.
4. The server of claim 1, wherein the reception unit causes a display of the second user terminal of the second user to display an object to receive the designation of said gift while the video data is reproduced.
5. The server of claim 1, further comprising: a payment processing unit configured to process, in response to reception of the signal, payment of an equivalent value associated with said gift from the second user.
6. The server of claim 1, wherein the processing unit performs processing for apportioning said gift between the third user and the first user.
7. The server of claim 1, further comprising: a notification unit configured to notify, in response to reception of the signal, at least one viewer of another, current live-stream conducted by the third user of the fact that said gift is used in the live-stream conducted by the first user.
8. A method, including: relaying video data related to a live-stream from a first user terminal of a first user where the video data is generated to a second user terminal of a second user where the video data is reproduced; receiving, from the second user terminal of the second user, a signal indicating that a gift is used by the second user while the video data is reproduced; and performing, in response to reception of the signal, processing for giving said gift to a third user who is different from the first user.
9. The method of claim 8, further including: generating said gift in another, past live-stream in which the third

user participates as a distributor and in which the first user participates as a viewer.

10. The method of claim 9, wherein said gift is generated based on a part of the another, past live-stream.

11. The method of claim 8, wherein the receiving includes causing a display of the second user terminal of the second user to display an object to receive the designation of said gift while the video data is reproduced.

12. The method of claim 8, further including: processing, in response to reception of the signal, payment of an equivalent value associated with said gift from the second user.

13. The method of claim 8, wherein the performing includes performing processing for apportioning said gift between the third user and the first user.

14. The method of claim 8, further including: notifying, in response to reception of the signal, at least one viewer of another, current live-stream conducted by the third user of the fact that said gift is used in the live-stream conducted by the first user.
