

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414888
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lin; Tsung-Yi

Caring machine, overhanging machine and main unit module comprised therein

Abstract

The present invention provides a caring machine and an overhanging machine. A main unit module which included in the caring machine comprises a shifting module, a supporting frame module, and a coupling module. The shifting module, situated below the supporting frame module, allows for movement controlled by the opening and closing of wheel casters. The supporting frame module accommodates diverse caring modules, offering a range of care functions. The coupling module, positioned on the shifting module and the supporting frame module, comprises a plurality of coupling devices and a plurality of coupling interfaces. The caring machine integrating the main unit module is capable of addressing daily life activities and basic rehabilitation training for disabilities and elders. The overhanging machine, which using the caring machine, comprises support columns, overhanging arms, a receiving frame and a sling machine. This invention provides versatility and allows users to achieve plural functionalities within one machine.

Inventors:	Lin; Tsung-Yi (Tainan, TW)
Applicant:	FULL CARE TECHNOLOGY CO., LTD. (Taichung, TW)
Family ID:	1000008818940
Assignee:	FULL CARE TECHNOLOGY CO., LTD. (Taichung, TW)
Appl. No.:	18/697449
Filed (or PCT Filed):	September 29, 2021
PCT No.:	PCT/CN2021/121951
PCT Pub. No.:	WO2023/050227
PCT Pub. Date:	April 06, 2023

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Publication Classification

Int. Cl.: A61G7/10 (20060101)

U.S. Cl.:

CPC A61G7/1034 (20130101); A61G7/1019 (20130101); A61G7/1059 (20130101);

Field of Classification Search

CPC: A61G (7/1034); A61G (7/1019); A61G (7/1059); A61G (7/1015); A61G (5/0875); A61G (5/1013); A61G (5/1059); A61H (2003/043); A61H (3/04); A61H (2201/0192)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3889964	12/1974	Pitts, Jr.	248/407	A61G 5/1013
6430761	12/2001	Brandorff	5/81.1 R	A61G 7/053
6793232	12/2003	Wing	5/604	A61G 7/1067
2011/0138532	12/2010	Lin	5/86.1	A61G 7/1059
2012/0174314	12/2011	Clement	5/81.1 R	A61G 7/1051
2014/0068854	12/2013	Konishi	5/87.1	A61G 7/1019
2014/0265232	12/2013	Lin	280/287	A61G 7/1059
2015/0051519	12/2014	Morbi	601/26	A61G 7/1048
2015/0231017	12/2014	Kazemi Banyhashemi	N/A	N/A
2015/0290058	12/2014	Panzer	403/109.6	A61G 3/063
2016/0331610	12/2015	Brown et al.	N/A	N/A
2018/0161220	12/2017	Hong	N/A	A61G 7/1046

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102100623	12/2010	CN	N/A
204840050	12/2014	CN	N/A
205094871	12/2015	CN	N/A
106267773	12/2016	CN	N/A
208259894	12/2017	CN	N/A
210991600	12/2019	CN	N/A

211461087	12/2019	CN	N/A
212090001	12/2019	CN	N/A
216676228	12/2021	CN	N/A
115054493	12/2021	CN	N/A
10-2010-0121243	12/2009	KR	N/A
10-2011-0114233	12/2010	KR	N/A
M 583752	12/2018	TW	A61G 5/00
2008/096210	12/2007	WO	N/A

Primary Examiner: Mikowski; Justin C

Assistant Examiner: Labarge; Alison N

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) The present invention is a 35 U.S.C. § 371 National Phase conversion of International (PCT) Patent Application No. PCT/CN2021/121951, filed on Sep. 29, 2021, the disclosure of which is incorporated by reference herein. The PCT International Patent Application was filed and published in Chinese.

FIELD OF THE INVENTION

(2) The present invention pertains to a medical rehabilitation and health care assistive device, and in particular to a main unit module and an assistive device such as a caring machine and an overhanging machine that can be combined with the main unit module.

BACKGROUND OF THE INVENTION

(3) The population of developed countries and some developing nations worldwide is rapidly aging, the healthcare industry has emerged as one with significant development potential in the future. According to the World Health Organization, the global market size of the elderly industry is projected to reach an output value of US\$37.38 billion by 2025.

(4) Aging is frequently associated with functional decline and disability. The nature and extent of daily care, medical rehabilitation, and health care for individuals with disabilities vary, contingent upon the specific type and degree of disability. To aid individuals with limited mobility, healthcare professionals commonly utilize assistive mobility tools, such as hospital beds, wheelchairs, walkers, and similar devices to facilitate movement for those with disabilities.

(5) However, during the care, treatment, rehabilitation, and recovery processes for individuals with disabilities, diverse mobility and rehabilitation needs arise as body functions recover. As a result, each assistive mobility tool plays a specific role in the rehabilitation journey of the disabled. While these tools offer valuable assistance, their usage opportunities are often limited, and they are frequently discontinued after a period due to the improving physical functions of the disabled. Simultaneously, both the disabled individuals and their caregivers often find themselves needing to acquire assistive mobility tools with varying functions. This not only adds financial burden on the disabled, their families, and caregiving institutions but also introduces inconvenience into the realms of medical care and nursing.

(6) For the elderly, infirm, and disabled individuals, caring modules play a crucial role in facilitating quick completion of moving and transfer tasks in daily life. Utilizing caring modules not only enhances nursing staff efficiency but also reduces the risk of waist and back injuries that may arise during caregiving. Besides, for the elderly, frail, and disabled, regular standing and walking training are essential. Effective training not only diminishes the risk of limb muscle

atrophy but also improves walking ability, contributing to the rehabilitation of lower limbs.

(7) While the caring modules currently available in the market can generally fulfill the shifting module requirements of the elderly, infirm, and disabled individuals, their functionalities are often limited to specific tasks and may not meet the users' daily limb training needs, such as walking or squatting to maintain muscle strength and overall health. Additionally, these caring modules may prove inconvenient when engaged in other fundamental life activities, such as cleaning or using the toilet.

(8) Therefore, it is crucial to develop a multi-purposed caring machine capable of addressing the daily life activities and basic rehabilitation training needs of individuals with disabilities.

Integrating this caring module with a multi-modal caring module has become a challenge that experts in the field are actively seeking to resolve. Such a caring module should be adaptable for carrying the load-bearing module of the disabled or rehabilitated, and it should help users at different levels for various rehabilitation exercises. This facilitates a smooth transition for both the disabled and caregivers, from the initial stages of illness to the recovery process. This approach not only benefits a wide range of people by enhancing usability and functionality but also alleviates the economic burden on users and minimizes environmental resource wastage.

SUMMARY OF THE INVENTION

(9) The object of the present invention is to provide a main unit module, a caring machine, and an overhanging machine equipped with the main unit module. The main unit module is adjustable and can accommodate various caring modules to deliver diverse care functionalities. These caring modules can be positioned at different heights on the main unit module based on specific usage needs. The caring machine comprises the main unit module and various caring modules, allowing users to engage in activities such as riding, shifting, and exercising. The overhanging machine consists of, at least, the main unit module and a shelf module, enabling users to execute suspension movements, rehabilitation exercises, the like.

(10) In order to achieve at least one of the aforementioned or other advantages, one embodiment of the present invention provides a main unit module capable of integrating various caring modules to offer a range of caring functions, including operational features like shifting. The main unit module may comprise a shifting module, a supporting frame module, and a coupling module. The shifting module comprises at least one chassis unit and an auxiliary wheel caster set. The chassis unit includes a flat upper surface suitable for attaching, carrying other components, or serving as a pedal. The auxiliary wheel caster set is pivotally connected to two opposite sides of the chassis unit, allowing for opening and closing to facilitate the movement of the main unit module. The supporting frame module consists of multiple upright poles and connecting plates. One end of each upright pole is attached and secured to the chassis unit, while the other end is connected to the connecting plates and fixed beneath them. The coupling module comprises multiple coupling devices and coupling interfaces positioned on the supporting frame module. The coupling module can be utilized independently or in combination with the supporting frame module to attach and secure caring modules with diverse functionalities.

(11) A plurality of first keyholes are arranged along the vertical direction on the outer side of the upright pole to attach caring modules with various functions or a series of coupling modules. The connecting plate provides multiple first mounting holes, multiple second keyholes, and numerous fasteners. Once one end of the upright pole is connected to the first mounting hole, it is secured beneath the connecting plate through the second keyhole the fastener. It can be inferred that the multiple upright poles are employed to affix and stabilize multiple connecting plates above the chassis unit. This allows the main unit module to accommodate caring modules or other components with diverse functionalities by utilizing the multitude of upright poles and connecting plates.

(12) To explain further, the coupling interface of the coupling module may consist of, but is not restricted to, the first keyholes, the first mounting holes, the second keyholes. The coupling device

is slidably enclosed on the upright pole and secured onto it through the first keyholes. Caring modules provided with various functions can be attached and secured on the upright poles using the first keyholes and coupling devices, the caring modules are positioned on one side of the supporting frame module.

(13) The main unit module may comprise a support rod horizontally positioned and supported on multiple connecting plates. When the user stands on the chassis unit of the shifting module, the support rod can be utilized to provide additional support for the user.

(14) The main unit module may also include a support rod horizontally supported on multiple connecting plates. The support rod is provided with multiple braking handgrips for managing the movement of the main unit module. The braking handgrips may be integrally formed with the support rod. Alternatively, they may be individually molded and subsequently enclosed and secured onto the support rod. In this configuration, the support rod can function as a shifting module.

(15) In order to achieve at least one of the above-mentioned advantages or other advantages, one embodiment of the present invention provides a caring machine that can be equipped with caring modules with different functions. The caring machine comprises at least the aforementioned main unit module and a shifting module. The shifting module is installed on the main unit module and can control the operational process of the caring machine. The shifting module may include a mounting bracket, an armrest, and a plurality of braking handgrips. The mounting bracket is installed above the connecting plate of the supporting frame module through the first mounting holes. The armrest is generally U-shaped and is attached and fixed to one side of the mounting bracket, providing support for users or caregivers to hold onto. A plurality of braking handgrips are sleeved and fixed on the armrest, facing the mounting bracket, and are used to control the movement of the caring machine.

(16) In some embodiments, the caring machine may comprise a carrying module installed on the main unit module. The carrying module includes, at least, a plurality of attachment bases, two guardrails, and two load-bearing plates. The attachment bases are sleeve-mounted on the supporting frame module of the main unit module. Specifically, the attachment bases can be secured onto the upright poles of the supporting frame module through the first keyholes. The two guardrails are respectively pivotally connected to the attachment bases, allowing rotation in the horizontal direction around the attachment bases. The two guardrails can be expanded outward, to the left, to the right, or closed inward.

(17) The two load-bearing plates are detachably and rotatably installed at the bottom or below of the two guardrails, respectively. When the load-bearing plates are positioned horizontally, they can be used to carry weight, such as when users ride on them. When the load-bearing plates are shifting upward, they can be brought close to the guardrails and fixed onto them. In this configuration, the carrying module can be utilized as a support for the user.

(18) The carrying module can also include a backrest assembly that can be connected and locked with the two guardrails. When the two load-bearing plates are positioned horizontally, the user sits on them, the backrest assembly can provide support and protection for the user's back.

(19) Each of the guardrails includes two long poles. The two long poles are arranged vertically in parallel and connected and secured by several connecting rods with a specific spacing. Pivot-mounted locking devices are installed and locked at both ends of the long poles. One end of each long rod is pivotally connected and fixed to the attachment base, the other end is connected and fixed to the backrest assembly.

(20) The load-bearing plate is rotatably provided at the bottom of the guardrails through multiple limit pins on the rotating rod. When the load-bearing plate is lifted upward, it is brought close to the guardrail. When the load-bearing plate is placed horizontally, it can carry the load. Each load-bearing plate has an arc-shaped notch. When the two load-bearing plates are laid flat and closed, the two arc-shaped notches face each other, forming an opening. Thus, users can ride on the two load-bearing plates.

(21) In some embodiments, the caring machine may include a top support module mounted on the supporting frame module of the main unit module. More precisely, the caring machine can be secured on the upright poles of the supporting frame module through the first keyholes. The top support module is designed with an adjustment function, allowing its position to be modified upwards, downwards, forwards, or backwards based on the usage conditions.

(22) The top support module may comprise an attachment bracket and a seatback cushion. The attachment bracket is affixed to the upright poles of the supporting frame module through the first keyholes, the seatback cushion is mounted on the attachment bracket, facing the user and providing support for the user's knees and other body parts.

(23) In certain embodiments, the caring machine may include a support module, designed to be mounted on the main unit module, providing support and safeguarding for the user while standing on the caring machine. The support module is affixed to the supporting frame module of the main unit module and comprises a pair of receiving rods, two supporting devices, and two braking handles. Each receiving rod is equipped with multiple mounting pins and is horizontally affixed to the connecting plate through the first mounting holes the mounting pins. The two supporting devices are respectively mounted on the two receiving rods, and each of the supporting devices consists of an attachment bracket set, a support member, and a support pad. The attachment bracket set is securely encased on the receiving rod, while the support member and support pad are flexibly attached to the attachment bracket set. The support member provides horizontal adjustment, allowing alteration of the distance between the support member the attachment bracket set. Meanwhile, the support pad possesses a 360-degree rotational capability within a horizontal plane, enabling the adjustment of its fixed angle position relative to the attachment bracket set. The braking handles are respectively fixed onto the attachment bracket set and serve the purpose of maneuvering the caring machine.

(24) The attachment bracket set of each of the supporting devices comprises a sleeve member, a mounting bracket, a mounting plate, and a plurality of locking members. The sleeve member is slidably encased and secured on the receiving rod, serving as a receptacle for installing the mounting bracket. The mounting bracket is flexibly mounted within the sleeve member, enabling perpendicular alignment with the receiving rod. The installation height of the mounting bracket can be adjusted vertically relative to the receiving rod. Once installed and secured, the mounting plate is positioned on the mounting bracket along a horizontal plane to accommodate the support pad. Within this horizontal plane, the support pad has a 360-degree rotational capability for adjusting its fixed angle position. The mounting bracket is provided with multiple locking members that can interconnect and fix with the braking handles.

(25) The support module may comprise a supporting assembly, which consists of multiple adjustable rods arranged in a generally U-shaped configuration. The two ends of the supporting assembly are respectively installed on two attachment bracket sets, and are positioned above the supporting devices.

(26) The mounting bracket is generally T-shaped and comprises a horizontal rod and an upright rod. The mounting rods are installed at both ends of the horizontal rod, and these mounting rods can be adjustably connected and fixed to the adjustable rods of the supporting device. It allows the supporting assembly to be adjusted in height vertically and in width horizontally.

(27) When the user stands on the chassis unit of the caring machine, the two supporting members of the supporting device can be utilized to support the user's waist, while the two support pads can be used to support the user's hands. In cases where the user's upper torso strength is insufficient, the supporting assembly can provide support to the user's chest and abdomen, preventing the user from tripping while standing. This enables users with disabilities to perform simple body movement exercises such as standing more stably on the caring machine.

(28) In certain embodiments, the caring machine may include a primary wheel module installed on the main unit module. The primary wheel module, at times, is used to be the primary wheel of the

caring machine, allowing it to be used both indoors and outdoors as needed. In specific situations, it can function as a wheelchair. The primary wheel module comprises at least two mounting brackets and two primary wheels. The two mounting brackets are symmetrically installed on the upright poles of the supporting frame module the wheel caster set of the shifting module. Each wheel caster set consists of a long leg and a short leg, with the mounting bracket installed on the long leg. Besides, the primary wheel module may include a first crossbar and two actuation mechanisms. Both ends of the first crossbar are connected and fixed to the two mounting brackets, enhancing the stability of the connection between them. The two actuation mechanisms are implemented on the rotating rod of the primary wheel and are linked with it. The two primary wheels are connected and locked into the primary wheel shaft hole devices of the mounting bracket through the primary wheel shaft.

(29) The primary wheel module may also comprise a lifting device, symmetrically installed on the mounting bracket or the wheel caster set. By controlling the lifting device, the height of the wheel caster set connected to the mounting bracket can be adjusted. In other words, the height of the long leg in the wheel caster set can be modified through the lifting device, lifting the wheels installed at the long leg to a specific distance above the ground. Subsequently, the primary wheels are employed as the wheels for the long leg in the wheel caster set.

(30) The lifting device comprises an overhead frame and a set of limiting pins. The lifting device is used to elevate the wheel caster set connected to it, making it easier to install or disassemble the primary wheel from the mounting bracket.

(31) To achieve at least one of the aforementioned advantages or other benefits, an embodiment of the present invention provides an overhanging machine that comprises the aforementioned main unit module and a shelf module. The shelf module is installed and positioned above the main unit module, allowing users to engage in various exercise training, such as rehabilitation exercises. The shelf module includes multiple support columns and at least two overhanging arms. The support columns are vertically installed on the connecting plate through the first mounting holes, the two overhanging arms are mounted on the support columns, positioned above the connecting plate. One end of the overhanging arm may be equipped with a hook-shaped member for hanging objects.

(32) In certain embodiments, the shelf module may comprise a receiving frame positioned on the upper ends of multiple support columns to connect the two overhanging arms. The receiving frame comprises at least two long rods, at least two short rods, and multiple locking support members. The two long rods and two short rods are interconnected and secured through the locking support members, then horizontally positioned on the top or upper ends of the support columns.

(33) The locking support member is equipped with a groove and is positioned on a side distanced from the support column. The two overhanging arms are encompassed within the groove and secured on the locking support member to establish a connection above the receiving frame. To elaborate, along vertical direction, one end of the locking support member is connected and secured with the upper end of the support column, while the other end passes through the groove to accommodate and support the overhanging arm. Meanwhile, along horizontal direction, two opposite sides of the locking support member are connected and secured with the long rod the short rod, respectively. Additionally, one side of the locking support member may incorporate a hook-shaped member for hanging objects.

(34) In certain embodiments, the overhanging machine may also comprise a sling machine, positioned on the chassis unit of the shifting module, and including a retractable sling. The retractable sling can be suspended from the shelf module and employed for the purpose of suspending objects.

(35) In specific embodiments, the overhanging machine may comprise a second crossbar that is horizontally supported on the two overhanging arms. When this second crossbar is securely attached to the two overhanging arms, it can serve as a horizontal bar for users to engage in stretching exercises. Furthermore, the position of installation and locking for the second crossbar

on the two overhanging arms can be adjusted along the overhanging arms, both forward and backward. The second crossbar can also be suspended from the two overhanging arms using an elastic band. When the user holds the second crossbar, limb training can be performed through the telescopic movement facilitated by the retractable sling.

(36) In a specific embodiment, a roller can be affixed to the second crossbar, serving as a means to hang objects. The retractable sling from the sling machine can be wound around the outer surface of the roller to suspend objects. The retractable sling may include a hook for improved object suspension.

(37) In some embodiments, the overhanging machine may further include a pull rope assembly disposed on two overhanging arms. The pull rope assembly includes a plurality of hook members and a plurality of pull ropes. Multiple hook members are symmetrically locked on two overhanging arms, and multiple pull ropes are threaded through the hook members. One ends of the hook members are hooked to the head end of the retractable sling of the sling machine, the other ends of the hook members are used to suspend an object.

(38) In some embodiments, the overhanging machine may further include a suspension cloth module suspended from the shelf module. In one embodiment, the suspension cloth module can be hung on two overhanging arms for the user to perform shifting or perform other exercises and training with the help of the overhanging machine. In another embodiment, the suspension cloth module can be suspended from the shelf module through a sling machine and a sling.

(39) In certain embodiments, the caring machine may further comprise an electric module, securely fixed onto the chassis unit using fasteners and positioned on a plurality of second mounting holes. The electric module comprises a mounting bracket installed above the upper surface of the chassis unit through the second mounting holes. A column module is comprised of a fixed bracket and a lifting bracket, with the fixed bracket securely installed on the mounting bracket. The lifting bracket is positioned above the fixed bracket, and capable of vertical movement. Multiple apertures arranged vertically on the lifting bracket facilitate the installation of caring modules with different functions at adjustable heights. A driving module, mounted on the mounting bracket, is used to facilitate the vertical movement of the lifting bracket.

(40) In certain embodiments, the aforementioned electric module may additionally comprise a plurality of fastening devices located on the column module. The fastening devices can be securely locked at various heights of the lifting bracket through the apertures. The fastening devices are provided with multiple fastening interfaces designed for the installation of caring modules.

(41) The present invention provides a versatile main unit module designed to accommodate various care modules at adjustable heights, facilitating user customization and enhancing mobility. The overhanging machine allows users to be suspended and shifted, aiding in limb movement and contributing to the rehabilitation of individuals with mobility challenges. Furthermore, the caring machine offers a diverse range of care functions for users, including those with disabilities. The modular design allows for easy customization based on specific user needs, eliminating the need for frequent replacements and ultimately reducing overall healthcare costs.

(42) The aforementioned illustrations are exemplary for the purpose of further explaining the scope of the present invention. Other objectives and advantages related to the present invention will be illustrated in the subsequent descriptions and appended drawings. [0001]

Description

DESCRIPTION OF THE DRAWINGS

(1) The foregoing features of the present invention may be combined with the following drawings in various combinations without exclusivity, unless expressly indicated otherwise. Apparently, descriptions of drawings in the following may be some of embodiments of the present invention,

those of ordinary skill in the art may derive other drawings based on the following drawings without unduly experiments.

- (2) FIG. 1 is a perspective view of an embodiment of a main unit module of the present invention;
- (3) FIG. 2 is a perspective view of another embodiment of the main unit module according to the present invention;
- (4) FIG. 3 is a partial cross-sectional view of the pedal in FIG. 2;
- (5) FIG. 4 is a perspective view of an embodiment of a caring machine of the present invention;
- (6) FIG. 5 is a perspective view of an embodiment of a carrying module as shown in FIG. 2;
- (7) FIG. 5A is a perspective view of the carrying module as shown in FIG. 5 from another perspective;
- (8) FIG. 6 is a perspective view of a pivot-mounted locking devices as shown in FIG. 5;
- (9) FIG. 7 is a perspective view of another embodiment of a caring machine according to the present invention;
- (10) FIG. 8 is a perspective view of an embodiment of a support module of a caring machine as shown in FIG. 7 according to the present invention;
- (11) FIG. 9 is a top perspective view of the support module as shown in FIG. 7;
- (12) FIG. 10 is a perspective view of still another embodiment of a caring machine of the present invention;
- (13) FIG. 11 is a perspective view of an embodiment of a primary wheel module of the caring machine shown in FIG. 10;
- (14) FIG. 12 is a perspective view of the primary wheel module depicted in FIG. 11 during operation;
- (15) FIG. 13 is a perspective view of an embodiment of the overhanging machine according to the present invention;
- (16) FIG. 14 is a perspective view of an embodiment of a sling machine in the overhanging machine as shown in FIG. 13;
- (17) FIG. 15 is a perspective view of another embodiment of the sling machine in the overhanging machine as shown in FIG. 13;
- (18) FIG. 16 is a perspective view of an embodiment of the shelf module in the overhanging machine shown in FIG. 13; and
- (19) FIGS. 17 and 17A are perspective views of an electric module from different viewing angles according to the present invention.

NOTATIONS IN DRAWINGS

- (20) 1—main unit module, 2—caring machine, 3—push module, 4—overhanging machine, 100—shifting module, 10—coupling module, 110—chassis unit, 112—flat upper surface, 113—mounting locking plate, 114—receiving surface, 115—second mounting hole, 12—coupling device, 120—wheel caster set, 121—long leg, 122—universal wheel caster set, 123—short leg, 124—directional wheel caster set, 125—pivot shaft, 126—switching device, 127—directional wheel, 128—elastic device, 129—braking device, 1291—operating rod, 1292—activation rod, 130—support rod, 140—support rod, 142—handle, 144—braking handgrip, 150—chassis body, 151—guide unit, 152—guide unit, 154—locking member, 160—T-shaped sliding body, 161—straight bar, 162—crossbar, 170—moving pedal, 171—pedal, 20—support module, 200—supporting frame module, 202—attachment pin, 210—upright pole, 212—first keyhole, 22—receiving rod, 220—connecting plate, 222—first mounting hole, 224—second keyhole, 226—fastener, 24—supporting device, 242—mounting bracket set, 2422—sleeve member, 2424—mounting bracket, 2425—horizontal rod, 2426—attachment plate, 2427—upright rod, 2428—fastener, 2429—mounting rod, 244—support member, 246—support pad, 26—braking handgrip handle, 28—supporting device, 280—adjustable rod, 281—straight adjustable rod, 300—carrying module, 310—attachment base, 311—height adjustment device, 3110—positioning pin, 3111—switch operating member, 32—mounting bracket, 320—guardrail, 321—pivot device, 3210—pivot hole, 322—long rod, 323—long rod, 323

—rotating rod, **326**—pivot locking device, **3261**—pivot sleeve, **3262**—positioning groove, **328**—self-locking positioning device, **3281**—positioning hole, **3282**—positioning pin, **3283**—release button, **330**—backrest assembly, **332**—backrest seat, **334**—backrest, **336**—hook locking member, **337**—fastener, **338**—backrest mounting base frame, **34**—handrail, **340**—load-bearing plate, **342**—arc-shaped notch, **344**—opening, **345**—limiting pin, **346**—pivot groove, **347**—elongated hole, **348**—positioning pin, **36**—braking handgrip, **38**—safety hook, **500**—top support module, **501**—attachment bracket, **502**—seatback cushion, **600**—primary wheel module, **610**—mounting bracket, **612**—locking device, **615**—rotating rod, **616**—primary wheel rotating hole device, **620**—first crossbar, **630**—braking mechanism, **640**—primary wheel, **650**—lifting device, **651**—elevated frame, **652**—limiting pin, **660**—electric driving wheel, **700**—shelf module, **710**—support column, **711**—connecting rod, **720**—overhanging arm, **730**—receiving frame, **732**—long rod, **733**—handgrip rod, **734**—short rod, **736**—locking support member, **7361**—hook-shaped member, **738**—groove, **740**—second crossbar, **741**—locking component, **742**—roller, **750**—sling machine, **752**—retractable sling, **7521**—hook, **754**—pull rope assembly, **7541**—hook member, **7542**—pull rope, **760**—hanging cloth module, **800**—electric module, **810**—mounting base frame, **811**—coupling base, **8111**—positioning rod, **8112**—fastener, **812**—adapter base, **820**—column module, **821**—fixed bracket, **822**—lifting bracket, **830**—driving module, **840**—fastening device, **841**—fastening interface, **901**—health care module, **902**—health care module

DETAILED DESCRIPTION OF THE PREFERRED

Embodiments

(21) The structures and associated functions and following detailed descriptions are exemplary for the purpose of further explaining the scope of the present invention. Other objectives and advantages related to the present invention will be illustrated in the subsequent descriptions and appended drawings. Furthermore, the present invention may be embodied in various modifications, and descriptions and illustrations are not-limiting.

(22) It should be understood that the term used herein in embodiments to describe direction in terms of “central”, “lateral”, “up”, “down”, “right”, “left”, “upright”, “horizontal”, “top”, “bottom”, “inside”, and “outside” are used to illustrate the present invention and for clarity. It does not hint or imply that device or part mentioned should be assembled or operated in specific direction or setting. Thus, the terms used herein to describe direction are not limiting. In addition, terms “first”, and “second” is for descriptive purpose, and is not construed to or implies amount as described in technical feature of the present invention. Technical features with limitation terms “first” or “second” would illustrate or imply that one or more technical features can be included. As to detailed description of the present invention, the term “more” indicates two or more unless expressly indicated otherwise.

(23) Please refer to FIGS. 1, 2, and 3. FIG. 1 illustrates a perspective view of a main unit module according to one embodiment of the present invention. FIG. 2 displays a perspective view of the main unit module according to another embodiment of the present invention. FIG. 3 provides a partial cross-sectional view of the pedal as shown in FIG. 2. To achieve at least one of the aforementioned advantages or other benefits, an embodiment of the present invention provides a main unit module **1** capable of being combined with various caring modules to offer diverse care functions and perform actions such as shifting and moving.

(24) As depicted in FIGS. 1 and 3, the main unit module **1** comprises a shifting module **100**, a supporting frame module **200**, and a coupling module **10**. The shifting module **100** includes at least a chassis unit **110** and a wheel caster set **120**. The chassis unit **110** is positioned horizontally, the wheel caster sets **120** are pivotally connected to two opposite sides of the chassis unit **110**. The wheel caster sets **120** can open and close, driving the main unit module **1** to move. The chassis unit **110** is equipped with a flat upper surface **112** that can function as a pedal. In FIG. 3, the chassis unit **110** consists of a chassis body **150** and a moving pedal **170**. The chassis body **150**, forming a U-shaped structure, is used to accommodate the wheel caster set **120** the supporting frame module

200 while guiding the movement of the moving pedal 170. The moving pedal 170 comprises a T-shaped sliding body 160 and a pedal 171. The T-shaped sliding body 160 is composed of a straight bar 161 and a crossbar 162 perpendicular to each other. In this embodiment, the upper surface of the pedal 171 corresponds to the flat upper surface 112 of the chassis unit 110, but the present invention is not limited to this configuration. In the embodiment shown in FIG. 3, one end of the straight bar 161 is securely fitted into the groove in the center of the crossbar 162, forming a T-shaped structure that matches the chassis body 150. Together, they define the bottom frame of the chassis unit 110, which accommodates the pedal 171. The U-shaped structure of the chassis body 150 provides guide units 151/152 in the center and on two opposite sides, respectively. The guide unit 151 in the center of the U-shaped structure is designed to slidably receive the straight bar 161 of the T-shaped sliding body 160. The guide units 152 are intended to slidably receive both ends of the crossbar 162. The pedal 171 is positioned above the T-shaped sliding body 160, so that the pedal 171 can slide forward and backward on the guide unit 151/152 of the chassis body 150, moving between different positions. The guide unit 151 is equipped with a locking member 154, securing the straight rod 161 to fix the moving pedal 170 in various positions. The pedal 171 can meet multiple demands, such as acting as a pedal for the user to rest their feet or as a mounting surface for attaching and installing other modules and components. The form of the guide unit 151/152 may vary and is not restricted to a groove or rod shape, as long as it facilitates smooth sliding when coupled with the moving pedal. In one embodiment, the pedal 171 of the chassis unit 110 may comprise stripes to increase friction, enhancing its anti-slip properties. On two opposite sides of the chassis body 150, there are two mounting locking plates 113. These two mounting locking plates 113 have a receiving surface 114 aligned with the flat upper surface 112 of the chassis unit 110, allowing them to mount and carry other components.

(25) The wheel caster set 120 comprises at least multiple universal wheel caster sets 122, at least one directional wheel caster set 124, two long legs 121, and two short legs 123. The universal wheel caster sets 122 have unrestricted movement direction on the horizontal plane when rotating. In the depicted embodiment, the wheel caster set 120 consists of four universal wheel caster sets 122. The wheel caster sets are pivotally mounted on two opposite sides of the chassis unit 110 through two long legs 121, two short legs 123, and pivot shafts 125. The long legs 121 and short legs 123 are positioned beneath the chassis unit 110 through the mounting locking plates 113 the pivot shaft 125. That is, each side end of the chassis unit 110 is equipped with one long leg 121, one short leg 123, and two universal wheel sets 122. A universal wheel caster set 122 is attached to one end of each long leg 121 and each short leg 123, while the other end is fixed beneath the chassis unit 110. Two long legs 121 and two short legs 123 are positioned on the front and rear sides of the chassis unit 110. Please note that the diameter of the universal wheel caster set 122 installed on the short leg 123 is larger than the diameter of the universal wheel caster set 122 installed on the long leg 121. Control devices are provided on both the long leg 121 the short leg 123 to control the positioning and locking of the universal wheel caster sets 122. The two long legs 121 of the caster set 120 can swing open and close, facilitating compatibility with assistive devices such as wheelchairs. Opening the two long legs 121 enhances the overall stability of the main unit module 1.

(26) In order to enhance controllability and safety during shifting, the directional wheel caster set 124 is designed to only move in a predefined direction on the horizontal plane when it rotates. The directional wheel caster set 124 is positioned near the middle of the front side of the chassis unit 110 and enclosed within a horizontal area formed by the vertices of the universal wheel caster sets, and includes a directional wheel 127, an elastic device 128, and a switching device 126. The directional wheel 127 is movably installed beneath the directional wheel caster set 124 through the elastic device 128, allowing the axis position of the directional wheel 127 to be adjusted vertically. The directional wheel caster set 124 ensures continuous ground contact of the directional wheel 127 through the action of the elastic device 128, maintaining its effectiveness throughout the

movement. The switching device **126** is positioned near the directional wheel **127**, the switching device **126** is used to controls the directional wheel's orientation, enabling it to be fixed in a predefined direction or left in a freely rotatable state. In other words, activation of the switching device **126** stabilizes the forward direction of the directional wheel **127**, directing the shifting module **100** to move in the predefined direction. Conversely, deactivating the switching device **126** allows the directional wheel **127** to rotate freely, similar to a universal wheel, permitting movement in any direction. The switching between directional and non-directional states can be achieved through any suitable directional mechanism. For instance, the switching device **126** the directional wheel **127** may comprise positioning pins and corresponding positioning holes (not shown in the figure). By coupling or decoupling the two switching operations, the directional wheel **127** can be in a directional or non-directional state, thereby meet the shifting operation requirements of different applications. The directional wheel **127** can provide multiple directional positions, enabling the switching device **126** to alter its positioning direction. This configuration of the wheel caster set **120** enhances the stability and ease of movement for the shifting module **100** the main unit module **1**, providing more convenient control. Additionally, the directional wheel caster set **124** the moving pedal **170** have the capability to move relative to the long leg **121** toward the short leg **123**.

(27) The supporting frame module **200** comprises multiple upright poles **210** and multiple connecting plates **220**. One end of the upright poles **210** is attached and secured to the chassis unit **110** of the shifting module **100**, while the other end is connected and fixed below the multiple connecting plates **220**. In other words, the multiple connecting plates **220** are positioned above the chassis unit **110**, the upright poles **210** span between the chassis unit **110** the multiple connecting plates **220**. As illustrated, one end of the upright poles **210** is mounted and fixed on the receiving surface **114** of the mounting locking plates **113** of the chassis unit **110**. This configuration allows the moving pedal **170** of the chassis unit **110** to move towards the short leg **123** relative to the long leg **121** without hindrance.

(28) A plurality of first keyholes **212** are arranged along the vertical direction on the upright pole **210**, forming a coupling interface designed to install and lock caring modules with different functions. The number and spacing of these holes can be adjusted on the four upright poles **210** according to specific requirements. The first keyhole **212** creates four independent coupling interfaces that can collaborate with each other. The installation height of caring modules with different functions can be customized by utilizing the first keyholes **212** located at various heights on the four upright poles **210**. On the horizontal surface of the connecting plate **220**, there are multiple first mounting holes **222** (forming a coupling interface), and on the vertical surface, there are multiple second keyholes **224**. These can be utilized in conjunction with multiple fasteners **226** to establish another coupling module device and secure the components installed in the first mounting hole **222**. One end of the upright pole **210** is affixed to the first mounting holes **222** and secured beneath the connecting plate **220** using the second keyholes **224** and fasteners **226**. The arrangement of the first keyholes **212**, the first mounting holes **222**, the second keyholes **224** may be at equal intervals, but are not limited to. It can be understood that the multiple upright poles **210** are employed to fix the multiple connecting plates **220** above the chassis unit **110**, enabling the main unit module **1** to install care modules or other components with various functions through the multiple upright poles **210** and connecting plates **220**.

(29) To provide further clarification, in a specific embodiment, the connecting plates **220** are horizontally installed and perpendicular to the upright poles **210**. The upright pole **210** may be a hollow cylindrical tube and made of metal material, while the connecting plate **220** is generally elongated with a certain thickness to facilitate the arrangement of through holes. The multiple first mounting holes **222** on the connecting plate **220** are positioned vertically and are designed as through holes. The multiple second keyholes **224** the multiple fasteners **226** on the connecting plate **220** are arranged horizontally and perpendicular to the multiple first mounting holes **222**.

(30) The coupling module **10** comprises multiple coupling devices **12** and coupling interfaces that are disposed on the supporting frame module **200** and can be used independently or in conjunction with the supporting frame module **200** to attach and secure caring modules with various functions. The coupling device **12** is slidably encased on the and secured to upright pole **210** through the first keyholes **212**. Different caring modules with diverse functions can be mounted and secured on the pole **210** using the first keyholes **212** the coupling devices **12**. Different caring modules are positioned on one side of the supporting frame module **200**, enabling convenient and rapid adjustment of care at different heights. Additionally, besides the first keyhole, the first mounting hole on the connecting plate, the second mounting hole on the chassis unit can also serve as coupling interfaces for attaching the care module. That is, the coupling interface of the coupling module **10** may include, but is not restricted to, the first keyholes **212**, the first mounting holes **222**, the second mounting holes **115**. In certain applications, the caring module can be directly combined with the corresponding coupling interface and installed on the main unit module **1** without the need for a coupling device. Referring to FIGS. **1** and **2**, for quickly and swift height adjustment, the coupling device **12** also comprises a height adjustment device **311**. The height adjustment device **311** is slidably mounted on the upright pole **210** and comprises positioning pins **3110** for coupling and locking with the plurality of first keyholes **212** on the upright pole **210**. The number of positioning pins **3110** may be one or more, ensuring a secure lock of the guardrail **320** on the upright pole **210**. A switch operating member **3111** is utilized to operate the combination or disengagement of the positioning pins **3110** from the first keyholes **212**.

(31) Referring to FIG. **2** with reference to FIG. **1**, the main unit module **1** may also include a plurality of support rods **130** and **140** in different forms, the support rods **130** and **140** are horizontally supported on a plurality of connecting plates **220**. The support rod **130** can be installed and locked above the connecting plates **220** through the first mounting hole **222**, the second keyhole **224** the fastener **226**, the support rod **130** is placed horizontally and located in front of the user (using the upright pole **210** of the main unit module **1** as the reference point, the user's side is the front, the caregiver's standing side is the rear) for the user to hold, support, etc. In one embodiment, the support rod **130** may be a hollow cylindrical tube made of metal to maintain certain rigidity and load-bearing strength.

(32) The support rod **140** can be installed and secured through the first mounting hole **222**, the second keyhole **224**, the fastener **226**. The support rod **140** is positioned horizontally above the connecting plate **220** and located behind the user (with the upright pole **210** of the main unit module **1** as the reference point, where the user's side is the front, the caregiver's standing side is the rear), the support rod **140** enables the caregiver or user to control the movement of the main unit module **1**. The support rod **140** may symmetrically provide two handles **142** located at both ends of the support rod **140**. The handle **142** is generally L-shaped and positioned in the upper spatial area between the plurality of connecting plates **220**. The handle **142** can be either integrally formed with the support rod **140** or separately manufactured and then installed on the support rod **140**, either by welding and fixation or by being sleeved and locked. The two handles **142** can be equipped with braking handgrips **144**. The braking handgrips **144** are connected and can control the two braking devices **129** symmetrically installed on the chassis unit **110**, facilitating the caregiver or user in controlling the braking handgrips **144** to operate and control the movement of the main unit module **1**. At this point, the support rod **140** can function as a push module **3**.

(33) According to usage requirements, the support rod **140** can be installed on a plurality of connecting plates **220** with different orientations to achieve various functions. When the handle **142** the braking handgrips **144** of the support rod **140** face the caregiver, the caregiver can control the movement of the main unit module **1**. On the other hand, when the handle **142** the braking handgrips **144** of the support rod **140** face the user, the user can control the movement of the main unit module **1** or receive support by holding, supporting, etc. In this scenario, users can utilize the main unit module **1** for standing training and/or walking training. When the user stands on the

chassis unit **110** of the shifting module **100**, holding both hands on the support rod **130** the support rod **140**, the user can use the main unit module **1** to engage in standing training or perform simple walking exercises.

(34) Referring to FIG. **4**, in conjunction with FIGS. **1** and **2**, FIG. **4** depicts a perspective view of an embodiment of the caring machine of the present invention. To achieve at least one of the aforementioned advantages or other advantages, an embodiment of the present invention provides a caring machine **2** that can be equipped with caring modules with different functions. The caring machine **2** at least includes the previously mentioned main unit module **1** and a push module **3**. The push module **3** is installed on the main unit module **1** and can control the activation process of the caring machine **2**. The push module **3** may have different forms and structures, such as the aforementioned support rods **130** and **140**.

(35) The push module **3** may consist of a mounting bracket **32**, a handrail **34**, and multiple braking handgrips **36**. The mounting bracket **32** is installed above the connecting plate **220** of the supporting frame module **200** through multiple first mounting holes **222**. The handrail **34**, generally U-shaped, is attached and fixed to one side of the mounting bracket **32**, positioned above the short leg **123** of the wheel caster set **120** of the shifting module **100**. The handrail **34** is used to serve as a point for users or caregivers to hold and support. The multiple braking handgrips **36** are symmetrically arranged on the handrail **34**. After locking the braking handgrips **36**, they face the mounting bracket **32** and can be used to control the movement of the caring machine **2**. The braking handgrips **36** can connect to two braking devices **129** symmetrically installed on the chassis unit **110** to control the movement of the caring machine **2**. Referring to FIGS. **2** and **4**, in one embodiment, the braking device **129** consists of an operating rod **1291** and an activation rod **1292**. The operating rod **1291** is connected to the braking handgrips **36** through a brake line (not shown in the figure) and can be linked to the activation rod **1292** through a lever principle. In this way, the user can tighten or loosen the braking handgrips **36** on the handrail **34**, allowing the operating rod **1291** to move the activation rod **1292** closer to or farther from the ground, thereby completing the braking operation function. Therefore, the two symmetrically installed braking devices **129** the corresponding two braking handgrips **36** form a complete braking module, enhancing the safety of the caring machine **2** during movement. It's important to note that the brake module's components the combined actuation methods presented here are examples and can be replaced by other brake modules with similar functions. The mounting bracket **32** can be assembled using multiple rods and mounting parts, then installed above the connecting plate **220** of the supporting frame module **200** through multiple first mounting holes **222**. Both ends of the handrail **34** are attached and secured to the mounting bracket **32** through multiple mounting parts. The mounting bracket **32** is equipped with a safety hook **38**, providing the capability to hang straps and other items.

(36) When the user engages in standing training with the assistance of the caring machine **2**, they can stand on the chassis unit **110** of the shifting module **100** while gripping the mounting bracket **32** of the push module **3**. In this scenario, the user can utilize a retractable sling to support their buttocks. The two ends of the retractable sling are secured to the safety hook **38** on the mounting bracket **32**, providing a specific tension to maintain ample bearing capacity, thereby protecting and supporting the user

(37) Please refer to FIG. **4** again. In one embodiment, the caring machine **2** may also comprise a top support module **500** installed on the supporting frame module **200** of the main unit module **1**. Specifically, it can be secured to the upright poles **210** of the supporting frame module **200** through first keyholes **212**, the top support module **500** is locked in place through the first keyholes **212**. The top support module **500** can be adjustable, allowing for upward, downward, forward, and backward position adjustments based on usage conditions.

(38) The top support module **500** consists of an attachment bracket **501** and a seatback cushion **502**. The attachment bracket **501** is affixed to the upright poles **210** through the first keyholes **212**,

providing support to the supporting frame module **200**. The seatback cushion **502** is positioned on the attachment bracket **501** and oriented towards the user, providing support to the user's knees and assisting users in transitioning between sitting and standing or standing up. In various usage scenarios, the top support module **500** can serve not only to support the knees or legs but also other body parts such as the torso, head, and hands.

(39) As depicted in FIGS. **4** to **6**, in an embodiment, the caring machine **2** comprises a carrying module **300** mounted on the main unit module **1**. The carrying module **300** is designed to provide diverse care functionalities, the carrying module **300** comprises at least two attachment bases **310**, two guardrails **320**, a backrest assembly **330**, and two load-bearing plates **340**.

(40) The two attachment bases **310** are socket-mounted on the supporting frame module **200** of the main unit module **1**. Depending on the specific functions or utilization needs of the carrying module **300**, it can be securely positioned at various locations or heights on the main unit module **1**. As illustrated, the two attachment bases **310** can be slid onto and enclosed at the upright poles **210** and subsequently connected and secured through the first keyholes **212**, effectively attaching them to the upright poles **210** of the supporting frame module **200** of the main unit module **1**. Each end of the two guardrails **320** is pivotally connected to the respective attachment bases **310**, allowing horizontal rotation around the attachment bases **310**. The guardrails **320** can expand outward, to the left, to the right, or be brought close together. The opposite ends of the two guardrails **320** can be linked and secured to the backrest assembly **330**, respectively. Additionally, the carrying module **300** is equipped with a self-locking positioning device **328**, automatically securing the guardrail **320** when it is closed or positioned in a specific orientation, thereby constraining the horizontal rotation of the guardrails **320**.

(41) In certain embodiments, the attachment base **310** can be sleeved and mounted it onto the coupling device **12**. Additionally, each guardrail **320** is equipped with a pivot device **321** positioned at one end of the guardrail **320** near the upright pole **210**. The self-locking positioning device **328** comprises at least one positioning hole **3281** and at least one positioning pin **3282**, which are respectively and correspondingly located on the attachment base **310** the guardrail **320**. When the guardrails **320** are closed or positioned in a specific orientation on the attachment base **310**, the positioning pins **3282** on the attachment base **310** or the guardrail **320** will automatically engage and secure into the positioning holes **3281** on the guardrail **320** or the attachment base **310**. In the embodiment depicted in FIG. **5**, the attachment base **310** the coupling device **12** form an integral unit. In other words, the attachment base **310** in this embodiment integrates the functionalities of the coupling device **12**. The height of the carrying module **300** can be easily adjusted by manipulating the height adjustment device **311** and facilitating quick adjustments. The pivot device **321** includes a pivot hole **3210** for being fitted onto the rotating rod of the attachment base **310**. The self-locking positioning device **328** has a positioning hole **3281** located on the pivot device **321**, the positioning pin **3282** is disposed on the attachment base **310**. When the guardrails **320** are closed or positioned in a specific orientation, the positioning pin **3282** of the self-locking positioning device **328** automatically locks into the positioning hole **3281**, restricting the horizontal rotation of the guardrail **320**. To change the position of the guardrail **320** through rotation, the user simply needs to press the release button **3283** connected to the positioning pin **3282** on the attachment base **310**. This action disengages the positioning pin **3282** from the positioning hole **3281** so as to release the self-locking position.

(42) Each guardrail **320** comprises at least two long rods **322** and **323**. The two long rods **322** and **323** are arranged parallel to each other vertically, and can be interconnected and secured through multiple connecting rods (not shown in the figure). There is a specific distance between the two long rods **322** and **323**. The two ends of each long rod, **322** and **323** are equipped with pivot devices **321** and pivot locking devices **326**, respectively, for installation and locking so as to ensure that the two long rods **322** and **323** are provided in the same plane after attachment and fixation. One end of each guardrail **320** is pivotally connected and fixed to the attachment base **310** via a

pivoting device **321**, while the other end is connected and secured to the backrest assembly **330** via a pivot locking device **326**. In the embodiment illustrated in FIG. **6**, the pivot locking devices **326** consist of a pivot sleeve **3261** connected to a vertical connecting rod (not shown) and a hook locking member **336** installed on the side of the backrest assembly **330**. The pivot sleeve **3261** comprises a positioning groove **3262**. In addition to the connecting rod, in other embodiments, the pivot sleeve **3261** can also be sleeved on the vertical rod at one end of the guardrail.

(43) As shown in FIGS. **5** and **5A**, the lower long rod **323** of the two parallel long rods of each guardrail **340** is installed horizontally on the bottom of the guardrail **320** to serve as the rotating rod of the load-bearing plate **300**. The rotating rod **323** is provided with a plurality of limiting pins **345**. The two load-bearing plates **340** are rotatably mounted on the rotating rods **323** that is positioned at the bottom of the two guardrails **320** or below respectively. One side of each load-bearing plate **340** is provided with a pivot groove **346**, which can be a U-shaped groove. The load-bearing plate **340** is sleeved on the rotating rod **323**. The pivot groove **346** is provided with a plurality of elongated holes **347** for mounting a plurality of limit pins **345**, so that the load-bearing plate **340** can be placed horizontally to carry the load and can be lifted upward to get close to the guardrail **320**. When the load-bearing plate **340** is lifted upward, the pivot groove **346** rotates around the rotating rod **323**, and can be moved closer to the guardrail **320**. The guardrail **320** is fixed with positioning pin **348** to prevent the load-bearing plate **340** from falling during use and affecting the use of the guardrail **320**. When the load-bearing plate **340** is lifted up and close to the guardrail **320**, it will be convenient for the carrying module **300** to be used for other functions besides carrying the user. For example, the carrying module **300** can be used as a support for the user. When the two load-bearing plates **340** are placed horizontally the user sits on the load-bearing plates **340**, the backrest assembly **330** can support and protect the user's back for safety. When the load-bearing plate **340** is not needed, it can be quickly removed after being lifted up, so that the carrying module **300** can be used for other functions besides carrying the user.

(44) The load-bearing plates **340** are positioned beneath or at the bottom of the guardrail **320**. They can be detachably installed on the bottom of the guardrail **320** through the pivot groove **346**, allowing rotation relative to the rotating rod **323**. Each load-bearing plate **340** is designed with an arc-shaped notch **342**. When the two load-bearing plates **340** are laid flat and closed, the two arc-shaped notches **342** face each other to create an opening **344**. In this configuration, the two load-bearing plates **340** can be used to carry the user, essentially serving as a riding platform in the carrying module **300**. Additionally, when the two load-bearing plates **340** are laid flat and closed, an opening **344** is formed, corresponding to the size of a toilet seat cavity. This feature facilitates the use of the toilet by individuals with disabilities, adding versatility to the carrying module **300**.

(45) Referring to FIGS. **4** and **5** again, the backrest assembly **330** comprises a backrest seat **332** and a backrest **334**. The backrest seat **332** comprises multiple hook locking members **336** and a backrest mounting base frame **338**. Each hook locking member **336** is equipped with a fastener **337**, which securely connects and locks with the pivot sleeve **3261** of the guardrail **320**. The backrest mounting base frame **338** is positioned above the backrest seat **332** or at other suitable locations, the backrest mounting base frame **338** serves as a receptacle for various types of backrests **334**. Apart from the two backrest attachments on the backrest mounting base frame **338**, alternative structures can be employed to detachably affix the backrest **334** to the backrest seat **332**. In one embodiment, the backrest seat **332** consists of a flat plate, the hook locking members **336** are disposed on two opposite sides of the flat plate, engaging and securing with the positioning grooves **3262** on the pivot sleeve **3261** of the guardrail **320**, respectively. Consequently, the two guardrails **320** can maintain uniformity in their vertical and horizontal orientations. Furthermore, when only one side of the hook locking member **336** on the backrest seat **332** engages with the pivot sleeve **3261**, the backrest seat **332** the pivot sleeve **3261** can rotate at any angle. As depicted in FIG. **5A**, the backrest mounting base frame **338** consists of two backrest sockets and is positioned at the central location behind the backrest seat. The backrest socket **338** can

accommodate various types of backrests **334** to cater to diverse application scenarios or individual preferences. The hook locking members **336** and the pivot sleeves **3261** on two opposite sides of the backrest seat can be secured through fitting, snap-on locking, or other rapid installation and removal locking mechanisms.

(46) Please refer to FIGS. **7**, **8**, and **9** in conjunction with FIGS. **2** and **4**. FIG. **7** is a perspective view of another embodiment of the caring machine of the present invention. FIG. **8** depicts a perspective view of the embodiment of a support module in the caring machine shown in FIG. **7**. FIG. **9** is a top perspective view of the support module shown in FIG. **8**.

(47) Please refer to FIG. **7** in conjunction with FIG. **2** and FIG. **4**. When the caring machine **2** is loaded with the carrying module **300**, it can also include a support module **20**, which is installed on the supporting frame module **200** of the main unit module **1**. It can be used as an assistive device in conjunction with the carrying module **300**, or it can be used alone in conjunction with the main unit module **1**. The support module **20** includes at least two receiving rods **22**, two supporting devices **24**, and two braking handles **26**. Each receiving rod **22** has a plurality of attachment pins **202**. In the figure, the configuration of the receiving rod **22** is the same as or similar to the connecting plate **220**, but it may be different. The two receiving rods **22** are horizontally installed on the connecting plate **220** through the first mounting holes **222** and the attachment pins **202**, respectively, and are locked through the second keyholes **224** the fasteners **226**. The two supporting devices **24** are installed on the two receiving rods **22**, respectively.

(48) Each supporting device **24** comprises a mounting bracket set **242**, a support member **244**, and a support pad **246**. The mounting bracket set **242** is sleeved and secured on the receiving rod **22**, while the support member **244** the support pad **246** are adjustably fixed on the mounting bracket set **242**. The support member **244** can adjust the distance between itself the mounting bracket set **242** left and right along the horizontal direction, the support pad **246** can rotate 360 degrees relative to the mounting bracket set **242** in a horizontal plane to adjust its fixed angle position. The two braking handles **26** are respectively installed on the two mounting bracket sets **242** to control the movement of the caring machine **2**.

(49) Referring to FIG. **8** in conjunction with FIG. **7**, in one embodiment, the support module **20** may further comprise a supporting device **28**. The supporting device **28** is assembled from a plurality of adjustable rods **280** and is generally U-shaped. Its two ends are respectively installed on the two mounting bracket sets **242** and are positioned above the two supporting devices **24**.

(50) Please refer to FIG. **9** in conjunction with FIGS. **7** and **8**. To elaborate further, the mounting bracket sets **242** of the supporting devices **24** include a sleeve member **2422**, a mounting bracket **2424**, an attachment plate **2426**, and a plurality of fasteners **2428**. The sleeve member **2422** is slidably sleeved and locked on the receiving rod **22**, serving to receive and install the mounting bracket **2424**. The mounting bracket **2424** is adjustably installed on the sleeve member **2422**. Once installed and secured, the mounting bracket **2424** is perpendicular to the receiving rod **22** and can be adjusted up and down vertically relative to the receiving rod **22**. The attachment plate **2426** can be mounted on the mounting bracket **2424** along a horizontal plane to accommodate the support pad **246**. In this configuration, the support pad **246** can rotate 360 degrees relative to the attachment plate **2426** within this horizontal plane to adjust its fixed angle position. A plurality of fasteners **2428** are installed on the mounting bracket **2424** and can be used to connect and secure the braking handle **26**.

(51) The mounting bracket **2424** typically has a T-shaped configuration, comprising a horizontal rod **2425** and an upright rod **2427**. A mounting rod **2429** is disposed at each end of the horizontal rod **2425**. The mounting rods **2429** are adjustable and securely attached to the two ends of the adjustable rod **280** of the supporting device **28**. Consequently, the supporting device **28** can be adjusted in height along the vertical direction and in width along the horizontal direction.

(52) One side of the sleeve member **2422** of the mounting bracket set **242** is provided with a groove, while one side of the groove contains a keyhole. The sleeve member **2422** can smoothly

slide along the receiving rod **22** via the groove. Once it reaches a predetermined position, it securely locks onto the receiving rod **22** through the keyhole. The upright rod **2427** within the mounting bracket **2424** passes through a through hole in the sleeve member **2422** and is then locked in place. By adjusting the vertical position of the upright rod **2427**, the overall height of the support module **20** can be modified. The mounting plate **2426**, typically an oval-shaped thin plate, is affixed above the horizontal rod **2425** of the mounting bracket **2424** using screws or similar fasteners. The support pad **246** is then mounted onto the mounting plate **2426** in a manner that allows for rotation and adjustment. A plurality of fasteners **2428** are positioned at both ends of the horizontal rod **2425** within the mounting bracket **2424**, with one end connected and secured to the braking handle **26**. The fastener **2428** comprises a hook-shaped structure, which can support loads, such as hanging a sling for weight-bearing purposes. The braking handle **26** is outfitted with both a control handle bar and a control button, enhancing control over the actions of the caring machine **2**. The support member **244** comprises a support pad and a support mounting rod. An attachment base device is disposed at the junction between the horizontal rod **2425** the upright rod **2427** within the mounting bracket **2424**. The support mounting rod of the support member **244** possesses a specific length and can be adjusted for attachment to the mounting device located at the junction between the horizontal rod **2425** the upright rod **2427** within the mounting bracket **2424**. The adjustability is provided for the modification of the distance between the two support members **244** the support module **20** positioned on the same horizontal plane.

(53) One end of the mounting rod **2429** positioned at both ends of the horizontal rod **2425** within the mounting bracket **2424** is sleeved onto and secured at one end of the horizontal rod **2425**. A positioning pin is defined at the opposite end of the mounting rod **2429**. The supporting device **28** is composed of multiple adjustable rods **280** and generally takes on a U-shaped configuration. The supporting device **28** comprises two U-shaped adjustable rods **280**, each featuring multiple mounting holes at both ends. The mounting holes located at both ends of each U-shaped adjustable rod **280** are connected and secured with the positioning pins of the two mounting rods **2429** within the mounting bracket **2424**. Vertical installation height adjustment of the supporting device **28** is achieved by modifying the locking positions of the mounting holes on the U-shaped adjustable rod **280** in conjunction with the positioning pins on the mounting rod **2429**. The two U-shaped adjustable rods **280** are connected and secured by two straight adjustable rods **281**. One end of each straight adjustable rod **281** is connected and locked onto the U-shaped adjustable rod **280**, while the other end of the straight adjustable rods **281** is provided with an equal number of mounting holes, securing them horizontally via these mounting holes. Adjustment of the installation spacing of the supporting device **28** along the horizontal direction is accomplished by modifying the locking positions of the mounting holes on the two straight adjustable rods **281**. Multiple adjustable rods **280** and **281** may be provided with an elastic buffer sleeve to enhance the comfort of the supporting device **28**. The elastic buffer sleeve can be made from various materials possessing elastic properties.

(54) When the user stands on the chassis unit **110** of the caring machine **2**, the two support members **244** of the supporting devices **24** can provide support to the user's waist, while the two support pads **246** can offer support to the user's hands. In cases where the user lacks sufficient upper torso strength, to prevent the user from leaning dangerously while standing, the supporting device **28** can secure and stabilize the user's chest and abdomen, enhancing stability on the caring machine. For instance, the supporting device **28** may be positioned under the user's armpits to provide more effective support, grip, and protection. Through this configuration, individuals with disabilities can utilize the caring machine **2** for basic body movement exercises such as standing.

(55) Please refer to FIGS. **10** to **12** in conjunction with FIGS. **1** and **4**. FIG. **10** is a perspective view of another embodiment of the caring machine of the present invention. FIG. **11** is a perspective view of an embodiment of the primary wheel module of the caring machine shown in FIG. **10**. FIG. **12** is a perspective view of the primary wheel module shown in FIG. **11** during

operation.

(56) Please refer to FIG. **10** in conjunction with FIGS. **1** and **4**. To further enhance the versatility and functionality of the aforementioned caring machine **2**, additional features can be incorporated to serve multiple purposes. Specifically, the caring machine **2** can be provided with a primary wheel module **600** mounted on the main unit module **1**. The primary wheel module **600** comprises at least two mounting brackets **610**, a first crossbar **620**, two braking mechanisms **630**, and two primary wheels **640**. The two mounting brackets **610** are symmetrically positioned on the upright pole **210**, which supports the frame module **200** the wheel caster set **120** of the shifting module **100**. Each mounting bracket **610** is installed on the long leg **121** of the wheel caster set **120**. The two ends of the first crossbar **620** are connected and securely fixed to the two mounting brackets **610**, thereby reinforcing the stability of the connection between the mounting brackets **610**. The two braking mechanisms **630** are individually fitted onto the rotating rods **615** of the primary wheels **640** and are synchronized with the movement of the primary wheels **640**. The two primary wheels **640** are affixed and secured through the rotating rods **615** that are respectively installed on the primary wheel rotating hole devices **616** of the mounting brackets **610**, and two primary wheels **640** are positioned outside the mounting brackets **610**.

(57) As depicted in FIG. **11**, the primary wheel module **600** may comprises a lifting device **650** that is positioned on the locking device **612** beneath the mounting bracket **610** (or symmetrically positioned on the wheel caster set **120** of the shifting module **100**). The lifting device **650** enables adjustment of the height of the wheel caster set **120** connected to the mounting bracket **610** by controlling its operation. That is, manipulation of the lifting device **650** allows for the height adjustment of the long leg **121** in the wheel caster set **120**, thereby raising the universal wheel caster set **122** on the long leg **121** to a certain distance from the ground so as to facilitate the installation of the primary wheel **640** to the mounting bracket **610**. Subsequently, the primary wheel **640** is mounted onto the mounting bracket **610**, serving as a replacement for the wheel on the long leg **121** in the wheel caster set **120**. Each lifting device **650** comprises at least an elevated frame **651** and a set of limiting pins **652**, and is used to elevate the wheel caster set **120** and simplify the process of installing or removing the primary wheel **640** onto/from the mounting bracket **610**. In a word, the two elevated frames are lowered to make contact with the ground and are restricted by the limiting pins **652** from rotating upward. Subsequently, force is applied in the direction of the front wheels using the push module **3**. As a result, the universal wheel caster set **122** of the long leg **121** is lifted to a certain distance from the ground using the point where the elevated frames **651** touch the ground as a fulcrum. At this point, the elevated frame **651** surpasses the highest point and is secured in a stable stationary state by another limiting pin **652**. It facilitates the convenient installation or disassembly of the primary wheel **640** onto/from the mounting bracket **610**.

(58) Once the primary wheel **640** is installed, it serves as the wheel for the long leg **121** of the wheel caster set **120**. Consequently, the primary wheel module **600** in conjunction with the short leg **123** of the wheel caster set **120** from the shifting module **100** is used to be as a wheel in the caring machine **2**. It allows the caring machine **2** to function as a wheelchair outdoors, facilitating users in engaging in basic life activities outdoors.

(59) To elaborate further, each mounting bracket **610** of the primary wheel module **600** comprises at least an upper locking device **611** and a lower locking device **612**. The upper locking device **611** facilitates connection and locking with the upright pole **210** of the supporting frame module **200**, while the lower locking device **612** is utilized for connection and locking with the long leg **121** of the wheel caster set **120** from the shifting module **100**. The lifting device **650** can be installed on the lower locking device **612** under the mounting bracket **610**. Thus, it's possible for straightforward and swift assembly and disassembly of the primary wheel module **600**.

(60) The primary wheel module **600** may also comprise a first crossbar **620** and an electric driving wheel **660**. The first crossbar **620** is detachably affixed at both ends to the two mounting brackets **610**. The electric driving wheel **660** is positioned at the center of the first crossbar **620** and is used

to drive the movement of the main unit module **1**.

(61) The carrying module **300**, the top support module **500**, the primary wheel module **600**, the support module **20** of the caring machine **2** can be independently installed on the main unit module **1** or combined in various configurations depending on the specific requirements of the intended usage scenario. The present invention provides flexibility for allowing the caring machine **2** to serve multiple purposes within a single unit. By adjusting the combinations of the main unit module **1** and these modular components, users can tailor the caring machine **2** to suit different needs. Moreover, these modular components are designed for quick disassembly and assembly, enhancing portability and ease of use.

(62) Please refer to FIG. **13** in conjunction with FIG. **1** and FIG. **2**. FIG. **13** depicts a perspective view of an embodiment of the overhanging machine of the present invention. To achieve various advantages, an embodiment of the present invention provides an overhanging machine **4** comprising the main unit module **1** and a shelf module **700**. The shelf module **700** is positioned above the main unit module **1** to enable users to engage in diverse sports training activities, including rehabilitation exercises. The shelf module **700** comprises multiple support columns **710** and at least two overhanging arms **720**.

(63) A plurality of support columns **710** are vertically installed on the connecting plates **220** through the first mounting holes **222** and are secured with fasteners **226** through the second keyholes **224**. Depending on the specific usage scenarios or functions, the support columns **710** can be affixed to different first mounting holes **222** on the connecting plate **220**. That is, it allows for flexibility in adjusting the spacing between every two support columns **710** installed on the same connecting plate **220** based on varying usage requirements. One end of the two overhanging arms **720** is affixed to multiple support columns **710**, the two overhanging arms **720** are positioned above the connecting plates **220**.

(64) The plurality of support columns **710** may consist of cylindrical tubes with a fixed length the same diameter, but this is not limited to this configuration. The support columns **710** can also be telescopic functionality, allowing for adjustment of the installation height of the two overhanging arms **720** in the vertical direction. Meanwhile, the support columns **710** with telescopic features are typically equipped with multiple mounting holes, enabling adjustment of their installation height by altering the locking positions of these mounting holes, thus adjusting the height of the overhanging arm **720** along the vertical direction. In such embodiment, as depicted in FIG. **14**, a connecting rod **711** can be installed between two adjacent support columns **710** on the same connecting plate **220** to enhance the stability of the installation connection among multiple support columns **710** of the shelf module **700**. At the end of the overhanging arm **720**, away from the support column **710**, a hook-shaped member is provided, facilitating the suspension or hanging of objects.

(65) In a specific embodiment, the shelf module **700** may include a receiving frame **730** positioned on the upper ends of the plurality of support columns **710** so as to connect the two overhanging arms **720**. Alternatively, the two overhanging arms **720** can be directly mounted onto the support columns **710** using other attachment fasteners.

(66) The receiving frame **730** consists of at least two long rods **732**, at least two short rods **734**, and a plurality of locking support members **736**. The number of locking support members **736** corresponds to the number of support columns **710**, and each locking support member **736** is installed on top of a support column **710** (at the end opposite to the connecting plate **220**). The two long rods **732** and two short rods **734** are connected and locked through the locking support members **736**, then horizontally mounted on the tops of the support columns **710**. Once locked, the long rod **732** and short rod **734** are perpendicular and situated in the same plane. The locking support member **736** provides a groove **738** located on its top surface. Once the long rods **732**, short rods **734**, and locking support members **736** are installed on the support column **710**, one end of the overhanging arm **720** is threaded through and nestled into the groove **738** of the locking support **736** intended to receive it. Then, the locking support members **736** are secured to lock the

overhanging arm **720** onto them, followed by connection to the top of the receiving frame **730**.

Upon locking, the overhanging arm **720** aligns parallel to the short rod **734** of the receiving frame **730**, the overhanging arm **720** is positioned above the short rod **734**. The arrangement of the receiving frame **730** bolsters the stability and support strength of the shelf module **700**.

(67) To enhance the versatility and practicality of the overhanging machine **4**, the locking support member **736** of the receiving frame **730** may comprise a hook-shaped member **7361** capable of suspending or hanging objects. The hook-shaped member might take the form of a J-shaped hook or a shackle secured through threads. Additionally, handgrip rods **733** can be added to the two ends of the long rod **732** of the receiving frame **730**, providing users with support points to grasp. For increased installation flexibility across various usage scenarios, the handgrip rod **733** can be detachably affixed to both ends of the long rod **732**. In a typical scenario, users can stand on the chassis unit **110** of the shifting module **100** and grasp the handgrip rods **733** on the long rods **732** to engage in standing training or other bodily movement exercises.

(68) The overhanging machine **4** can also comprise a second crossbar **740**, horizontally supported by the two overhanging arms **720** and positioned at the end of the overhanging arms **720** opposite to the receiving frame **730** or the support column **710**. In a specific embodiment, the two ends of the second crossbar **740** can be securely affixed to the two overhanging arms **720** using a locking component **741**. This arrangement ensures that the second crossbar **740** remains fixed on the two overhanging arms **720** and is used to be a horizontal bar for users to engage in stretching exercises. For instance, an individual undergoing rehabilitation therapy could utilize the second crossbar **740** for upper limb or hand movement training. In one embodiment, handgrip rods **733** may be provided at both ends of the second crossbar **740**, offering users additional points of support to grasp. For example, users could stand between the two long legs **121** of the wheel caster set **120** and hold onto the second crossbar **740** the handgrip rods **733** while performing standing training or other limb movement exercises.

(69) One end of the locking member **741** provides a hook-shaped member, facilitating the hanging or suspension of objects. In practice, the attachment and locking position of the locking member **741** on the overhanging arm **720** can be adjusted along the arm's length to meet different exercise requirements. The adjustability allows users to customize the placement of the locking member **741** and, consequently, the position of the second crossbar **740**. By moving it forwards or backwards, users can conveniently tailor the overhanging machine **4** for performing limb-focused rehabilitation exercises.

(70) Referring to FIGS. **14** and **15** in conjunction with FIG. **13**, FIG. **14** depicts a perspective view of one implementation of the sling machine integrated into the overhanging machine shown in FIG. **13**, while FIG. **15** illustrates another embodiment of the sling machine in the overhanging machine. In FIG. **14**, the overhanging machine **4** further comprises a sling machine **750**, which is mounted either on the chassis unit **110** of the supporting frame module **200** or the shifting module **100**. Specifically, the short leg **123** of the wheel caster set **120** in the shifting module **100** is furnished with a carrying plate designed to accommodate the sling machine **750**. The sling machine **750** comprises a retractable sling **752**, which may consist of a single piece or multiple pieces. The retractable sling **752** is capable of being draped around the long rod **732** of the receiving frame **730** to suspend an object. Additionally, the overhanging machine **4** comprises a pull rope assembly **754**, positioned along the two overhanging arms **720**. The pull rope assembly **754** comprises numerous hook members **7541** affixed symmetrically to the two overhanging arms **720**, along with multiple pull ropes **7542** threaded through these hook members **7541**. One end of each pull rope **7542** is attached to the head end of the retractable sling **752** on the sling machine **750**, while the other end is utilized to suspend an object. In a specific embodiment, a hook **7521** may be provided with the retractable sling **752** to ensure secure attachment of the pull ropes **7542**. When the need arises to relocate a person with mobility challenges, a sling or suspension apparatus can be suspended from the ends of the pull ropes **7542**, allowing the individual to sit comfortably. In such a suspension

setup, the overhanging machine **4** facilitates the movement of the individual or the person under care.

(71) Referring to FIG. **15** alongside FIG. **13**, in one embodiment, a roller **742** may be disposed at the second crossbar **740**. The roller **742** serves as a mounting point for the retractable sling **752**. The retractable sling **752** from the sling machine **750** can be wound around the outer circumference of the roller **742** to suspend objects. Additionally, the retractable sling **752** may comprise a hook for improved object suspension, enhancing user convenience during movement or rehabilitation activities.

(72) Referring to FIG. **16** alongside FIGS. **13** and **14**, FIG. **16** illustrates an embodiment of the shelf module within the overhanging machine depicted in FIG. **13**. Once the two overhanging arms **720** are securely installed, the ends of the two overhanging arms **720** that are situated away from the receiving frame **730** or the support column **710** can be utilized to suspend either a hanging cloth module **760** or a shelf module. The hanging cloth module **760** or a shelf module are used to serve various purposes such as supporting the user's body or facilitating movement during rehabilitation exercises. The hanging cloth module **760**, for instance, can be suspended from the shelf module **700** utilizing the hook-shaped member of the overhanging arm **720** the hook-shaped member **7361** of the locking support member **736**, as demonstrated in FIG. **14**. Alternatively, in another embodiment depicted in FIG. **14**, the hanging cloth module **760** can be suspended from the shelf module **700** via the retractable sling **752** the pull rope assembly **754** installed on the sling machine **750**.

(73) Please refer to FIGS. **14** to **16** alongside FIG. **2**, FIG. **4**, and FIGS. **6** to **8**, the main unit module **1** of the overhanging machine **4** can accommodate various components such as the carrying module **300**, the top support module **500**, the support module **20**. These modules, when combined with the shelf module **700**, the second crossbar **740**, the sling machine **750**, the sling module **760**, and other elements, provide a versatile range of functionalities. Through different configurations of the main unit module **1**, the carrying module **300**, the top support module **500**, the support module **20**, the overhanging machine **4** can fulfill multiple roles akin to the caring machine **2** in specific scenarios. This adaptability allows for cost-effectiveness and ease of use, as the modular components can be swiftly assembled or disassembled, facilitating portability and convenience.

(74) The caring machine **2** further consists of an electric module **800**, designed to provide additional functionalities. The electric module **800** is affixed onto a plurality of second mounting holes **115** disposed on the chassis unit **110**, using fasteners **8112** for secure attachment. Comprising a mounting base frame **810**, a column module **820**, and a driving module **830**, the electric module **800** provides versatility and adaptability. The mounting base frame **810** consists of a coupling base **811** and an adapter base **812**, with the adapter base **812** capable of adjustable fixation to the coupling base **811**. Through positioning rods **8111**, the coupling base **811** securely connects to the second mounting hole **115**, ensuring stable installation above the chassis unit **110**, with fasteners **8112** securing it in place. The column module **820** comprises a fixed bracket **821** and a lifting bracket **822**. The fixed bracket **821** is mounted on the adapter base **812** of the mounting base frame **810**, while the lifting bracket **822** is positioned above the fixed bracket **821**, enabling vertical movement. Multiple apertures along the vertical axis of the lifting bracket **822** allow for the installation of various health care modules at different heights, catering to diverse user needs. Additionally, the driving module **830** is installed on the adapter base **812** of the mounting base frame **810**. It facilitates vertical movement of the lifting bracket **822**, enabling seamless adjustment of the installed health care modules to suit user requirements.

(75) FIG. **17** and FIG. **17A** depict perspective views of the electric module **800** from different angles, showcasing its features in accordance with the present invention. Within the electric module **800**, a set of fastening devices **840** are coupled with the column module **820**. The fastening devices **840** are securely fastened at any desired height along the lifting bracket **822** through the apertures. Each fastening device **840** is equipped with multiple fastening interfaces **841**, designed for the

installation of caring modules such as health care modules 901, 902, and so forth, as illustrated in the figures.

(76) In summary, the present invention provides a versatile main unit module capable of accommodating various caring functionalities and facilitating user movement. It also enables the adjustment of installation heights for different health care modules, enhancing adaptability. The overhanging machine provided by the present invention is used to suspend and mobilize users, aiding in limb movement and supporting disabled individuals in limb rehabilitation. Moreover, the caring machine of the present invention delivers a range of health care functions tailored to users, including those with disabilities. It allows for the customization of health care functionalities based on specific needs, offering a single solution for multiple purposes. This eliminates the need for multiple types of care machines, ultimately reducing care-related expenses for users.

(77) The descriptions illustrated above set forth simply the preferred embodiments of the present invention; however, the characteristics of the present invention are by no means restricted thereto. All changes, alterations, or modifications conveniently considered by those skilled in the art are deemed to be encompassed within the scope of the present invention set forth by the following claims.

Claims

1. A caring machine, capable of integrating various caring modules to offer a range of care functions, comprising a main unit module, a primary wheel module and a push module, wherein: the main unit module comprises a shifting module, a supporting frame module, and a coupling module; the shifting module comprises at least one chassis unit and a wheel caster set, wherein the wheel caster set is pivotally connected to two opposite sides of the chassis unit, the chassis unit comprises a flat upper surface suitable for a pedal; the chassis unit comprises a chassis body and a moving pedal, the chassis body is provided with a guide unit, the moving pedal is positioned on the chassis body, moving forward and securing at various locations through the guide unit; the wheel caster set comprises at least multiple universal wheel caster sets and a directional wheel caster set, the directional wheel caster set is mounted on side of the chassis unit and enclosed within a horizontal area formed by the vertices of the universal wheel caster sets, the directional wheel caster set comprises a directional wheel, an elastic device, and a switching device, wherein the continuous ground contact of the directional wheel through the action of the elastic device is maintained throughout the movement the switching device is used to controls the directional wheel's orientation so that the directional wheel is enabled to be fixed in a predefined direction or left in a freely rotatable state; the supporting frame module comprises multiple upright poles and multiple connecting plates, wherein one end of the upright poles is attached and secured to the chassis unit of the shifting module, while the other end of the upright poles is connected and fixed below the multiple connecting plates; and the coupling module comprising a plurality of coupling devices and coupling interfaces positioned on the shifting module the supporting frame module for attaching and securing caring modules with diverse functionalities; the coupling module comprises multiple first keyholes and a height adjustment device, the first keyholes are arranged on the upright pole along the vertical direction, and the height adjustment device is slidably mounted on the upright pole and locked with the upright pole through the first keyholes; the coupling interfaces further comprise multiple first mounting holes, and multiple second mounting holes, the multiple first mounting holes are provided on the connecting plate the multiple second mounting holes are arranged on the chassis unit; an electric module, positioned on the plurality of second mounting holes and securely fixed onto the chassis unit using fasteners, comprises a mounting base frame, a column module, a driving module, and a plurality of fastening devices; the mounting base frame, installed above the upper surface of the chassis unit through the second mounting hole; the column module, comprising a fixed bracket and a lifting bracket, with the fixed bracket securely installed

on the mounting base frame, the lifting bracket positioned above the fixed bracket and capable of vertical movement, wherein multiple apertures are arranged vertically on the lifting bracket to facilitate the installation of the caring modules with different functions at adjustable heights; the driving module, mounted on the mounting base frame and used to facilitate the vertical movement of the lifting bracket; and the plurality of fastening devices located on the column module and securely locked at various heights of the lifting bracket through the apertures, the fastening devices are provided with multiple fastening interfaces designed for the installation of the caring module; the primary wheel module, installed on the main unit module, comprises two mounting brackets, two primary wheels, and two lifting devices; the two mounting brackets, symmetrically installed on main unit module, comprising multiple primary wheel shaft hole devices for installing the two primary wheels; the two lifting devices that are symmetrically installed on the mounting bracket or the wheel caster set, and each of the lifting devices comprises an overhead frame and a set of limiting pins, wherein the lifting device is used to elevate the wheel caster set connected to it, for installing or disassembling the primary wheel from the mounting bracket; the push module is disposed at the supporting frame module of the main unit module for maneuvering the main unit module, and comprises a handrail which is installed on said plurality of connecting plates.

2. The caring machine according to claim 1, wherein the push module comprises a braking module, wherein the braking module comprises: two braking devices, symmetrically installed on the shifting module of the chassis unit; and two braking handgrips, symmetrically installed on the handrail for controlling the braking devices.

3. The caring machine according to claim 2, wherein the caring machine further comprises a top support module that is mounted on the supporting frame module and comprises an attachment bracket and a seatback cushion, the seatback cushion is mounted on the attachment bracket to provide support for the user's torso.

4. The caring machine according to claim 2, wherein the caring machine further comprises a carrying module installed on the main unit module, wherein the carrying module comprises: two attachment bases, sleeve-mounted on the supporting frame module of the main unit module; two guardrails, respectively pivotally connected to the attachment bases for allowing rotation in the horizontal direction around the attachment bases; and two load-bearing plates, detachably and rotatably installed at the bottom of the two guardrails respectively, wherein when the load-bearing plates are positioned horizontally, the load-bearing plates can be used to carry weight; the attachment bases are installed at the coupling device, each of the guardrails comprises a pivot device and a pivot hole, wherein the pivot hole for being fitted onto the attachment base and the pivot device is disposed at one end of the guardrail, and a self-locking positioning device installed at the attachment bases the guardrails, wherein when self-locking positioning device is positioned in a specific orientation, thereby constraining the horizontal rotation of the guardrails.

5. The caring machine according to claim 4, wherein each guardrail comprises a rotating rod that is installed on the bottom of the guardrail, the rotating rod is provided with a plurality of limiting pins, each load-bearing plate is provided with a pivot groove and is sleeved on the rotating rod, wherein the pivot groove is provided with a plurality of elongated holes for mounting the limit pins so that the load-bearing plate is placed horizontally to carry the load and is lifted upward to get close to the guardrail, and each load-bearing plate is designed with an arc-shaped notch, when the two load-bearing plates are laid flat and closed, the two arc-shaped notches face each other to create an opening.

6. The caring machine according to claim 5, wherein the carrying module further comprises a backrest assembly, the guardrails pivotally connected and fixed to one end of the attachment base is provided a pivoting locking device for connecting and locking the backrest assembly; each of the pivot locking devices comprises a pivot sleeve and a hook locking member, the pivot sleeve is pivotally installed on the guardrail and comprises a positioning groove, the hook locking member is installed on one side of the backrest assembly that comprises a backrest seat and a backrest, the

backrest seat comprises multiple hook locking members that securely connects and locks with the positioning groove of the pivot pipe sleeve respectively so as to maintain uniformity of the two guardrails in their vertical and horizontal orientations, and when only one side of the hook locking member of the backrest seat engages with the pivot sleeve, the backrest seat the pivot sleeve rotate at any angle.

7. The caring machine according to claim 4, wherein the caring machine further comprises a support module mounted on the main unit module, the support module comprises: at least two receiving rods, respectively disposed at the supporting frame module; two supporting devices, respectively mounted on the two receiving rods, and each of the supporting devices comprising an attachment bracket set, a support member, and a support pad, wherein the attachment bracket set is securely encased on the receiving rod, while the supporting member the support pad are adjustably attached to the attachment bracket set; the support module further comprises a braking handle respectively arranged on the attachment bracket set for controlling the movement of the caring machine, the attachment bracket set comprises a sleeve member, a mounting bracket, a mounting plate, and a plurality of locking members, wherein the sleeve member is slidably encased and secured on the receiving rod, the mounting bracket is flexibly mounted within the sleeve member, the mounting plate is positioned on the mounting bracket to accommodate the support pad, the multiple locking members are installed at the mounting bracket; the support module further comprises a supporting assembly that comprises a supporting device and multiple adjustable rods arranged in a generally U-shaped, and two ends of the supporting device are respectively installed on two attachment bracket sets, and are positioned above the supporting devices.

8. The caring machine according to claim 1, wherein the primary wheel module further comprises a first crossbar and an electric driving wheel, the crossbar is detachably affixed at both ends to the two mounting brackets, the electric driving wheel is positioned at the center of the first crossbar for driving the movement of the main unit module.

9. An overhanging machine, comprising the caring machine of claim 2, wherein the overhanging machine further comprises a shelf module installed and positioned above the main unit module, the shelf module comprises: multiple support columns, vertically installed on the connecting plate through the first mounting holes; and at least two overhanging arms, mounted on the support columns and positioned above the connecting plate, wherein one end of the overhanging arm is equipped with a hook-shaped member for hanging objects.

10. The overhanging machine of claim 9, wherein the shelf module further comprises a receiving frame that is positioned on the upper ends of the support columns to connect the two overhanging arms and comprises at least two long rods, at least two short rods, and multiple locking support members, wherein the two long rods and two short rods are interconnected and secured through the locking support members and horizontally positioned on the top or upper ends of the support columns, one side of the locking support member is provided with a hook-shaped member for hanging objects, the receiving frame further comprises at least two holding rods detachably connected to both ends of the long rod.

11. The overhanging machine of claim 10, wherein the overhanging machine further comprises a sling machine that is positioned on the main unit module and comprises a retractable sling that is suspended from the shelf module for suspending objects, the overhanging machine further comprises a second crossbar that is horizontally supported on the two overhanging arms, and a roller is affixed to second crossbar for hanging the sling.

12. The overhanging machine of claim 11, wherein the overhanging machine further comprises a pull rope assembly that is disposed on two overhanging arms and comprises a plurality of hook members and a plurality of pull ropes, wherein the hook members are symmetrically locked on two overhanging arms, the pull ropes are threaded through the hook members, and one ends of the hook members are hooked to the head end of the sling of the sling machine, the other ends of the hook members are used to overhang an object.

