

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415090
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Choi; Jong Seok et al.

Laser irradiation device

Abstract

A laser irradiation device for performing treatment on human skin includes a main body including a barrel part; a laser oscillator that is accommodated in the main body and configured to generate a laser beam to be irradiated through the barrel part; and a skin treatment unit including a lens unit detachably connected to the main body and including a multi-lens that processes the laser beam generated by the laser oscillator into a plurality of laser beams and a functional unit detachably connected to the lens unit.

Inventors: Choi; Jong Seok (Incheon, KR), Jeong; Bong Kyoong (Bucheon-si, KR), Jang; Myung Su (Seoul, KR), Lee; Ju Hun (Anyang-si, KR)

Applicant: Lameditech CO., LTD. (Seoul, KR)

Family ID: 1000008818917

Assignee: Lameditech CO., LTD. (Seoul, KR)

Appl. No.: 17/940669

Filed: September 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230381536 A1	Nov. 30, 2023

Foreign Application Priority Data

KR	10-2022-0065971	May. 30, 2022
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/012716 20220825 PENDING child-doc US 17940669

Publication Classification

Int. Cl.: A61N5/067 (20060101); A61N1/32 (20060101); A61N5/06 (20060101)

U.S. Cl.:

CPC A61N5/067 (20210801); A61N1/325 (20130101); A61N5/0616 (20130101); A61N2005/0626 (20130101)

Field of Classification Search

CPC: A61N (5/067); A61N (1/325); A61N (5/0616); A61N (2005/0626); A61N (1/08); A61N (1/30); A61N (1/32); A61N (1/36); A61N (5/00); A61N (5/06); A61N (2005/005); A61N (2005/0644); A61N (1/303); A61N (2005/002); A61N (2005/0664); A61B (18/00); A61B (18/20); A61L (2/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7194316	12/2006	Bousfield	607/139	A61N 5/0617
7890164	12/2010	Akiyama	604/20	A61N 1/303
2016/0361539	12/2015	Nathanson	N/A	A61N 1/325
2017/0172659	12/2016	Choi	N/A	A61B 18/203
2019/0274608	12/2018	Choi	N/A	A61B 5/150748

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109248384	12/2018	CN	N/A
2314245	12/2010	EP	A45D 26/0061
2015093109	12/2014	JP	N/A
2017156643	12/2016	JP	N/A
2019155067	12/2018	JP	N/A
2021137536	12/2020	JP	N/A
1020050005728	12/2004	KR	N/A
200426671	12/2005	KR	N/A
101386137	12/2013	KR	N/A
1020140140394	12/2013	KR	N/A
101824460	12/2017	KR	N/A
101826500	12/2017	KR	N/A
1020190106569	12/2018	KR	N/A
1020190113308	12/2018	KR	N/A
102094456	12/2019	KR	N/A
1020210110439	12/2020	KR	N/A

OTHER PUBLICATIONS

CN109248384A Translation (Year: 2019). cited by examiner
KR101826500B1_Translation (Year: 2018). cited by examiner
KR102094456B1 Translation (Year: 2020). cited by examiner
JP2017156643A_Translation (Year: 2017). cited by examiner
Office Action of KR Application No. 10-2022-0065971 dated May 20, 2024. cited by applicant
Office Action of JP Application No. 2022-563382 dated Jul. 16, 2024. cited by applicant

Primary Examiner: Patel; Niketa

Assistant Examiner: Hussaini; Attiya Sayyada

Attorney, Agent or Firm: Dinsmore & Shohl LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/012716 filed on Aug. 25, 2022, which claims priority to Korean Patent Application No. 10-2022-0065971 filed on May 30, 2022, the entire contents of which are herein incorporated by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a laser irradiation device for performing treatment on human skin.

BACKGROUND

(2) Recently, as various medical devices have been developed along with the development of various high technologies, high-tech laser devices are being used more often than ever before in the medical field to treat various diseases.

(3) One of the uses of a medical laser is to perforate skin by irradiating a laser to the skin in order to collect blood from the perforated skin, administer a drug into a perforation, or remove moles or freckles from the skin.

(4) Meanwhile, various treatments using various high-tech medical devices have recently been introduced for the purpose of not only medical treatment for diseases but also skin beauty. For example, there is galvanic or iontophoresis treatment which changes the electrical environment of the skin using the potential difference to increase the permeation of an ionic drug into the skin. Also, ultrasound treatment by which ultrasound is applied to the skin to stimulate skin regeneration or treatment is being used in various ways.

(5) As described above, in the medical and cosmetic fields, the demand for treatments using laser, iontophoresis and ultrasound has been increasing, and devices or methods for effectively providing such treatments are needed. (Patent Document 1) Korean Patent Laid-open Publication No. 10-2014-0140394 (published on Dec. 9, 2014) (Patent Document 2) Korean Patent Laid-open Publication No. 10-2005-0005728 (published on Jan. 14, 2005)

SUMMARY

Problems to be Solved by the Invention

(6) The present disclosure is conceived to solve the above-described problems in the prior art and provides a laser irradiation device configured to share a laser treatment unit and thus increase the convenience of each treatment.

(7) The present disclosure also provides a laser irradiation device capable of removing heat generated therein when in operation.

(8) However, problems to be solved by the present disclosure are not limited to the above-described

problems. There may be other problems to be solved by the present disclosure.

Means for Solving the Problems

(9) As a means for solving the problems, according to an aspect of the present disclosure, a laser irradiation device for performing treatment on human skin includes a main body including a barrel part; a laser oscillator that is accommodated in the main body and configured to generate a laser beam to be irradiated through the barrel part; and a skin treatment unit including a lens unit detachably connected to the main body and including a multi-lens that processes the laser beam generated by the laser oscillator into a plurality of laser beams and a functional unit detachably connected to the lens unit.

(10) The above-described aspects are provided by way of illustration only and should not be construed as limiting the present disclosure. Besides the above-described embodiments, there may be additional embodiments described in the accompanying drawings and the detailed description.

Effects of the Invention

(11) According to any one of the aspects of the present disclosure, various treatments such as iontophoresis treatment in combination with laser treatment can be quickly and conveniently switched and performed. Therefore, the subject's satisfaction and treatment effect can be increased, and the operator's convenience in use can be improved.

(12) Also, the laser irradiation device has a cooling function and thus is capable of removing heat generated therein when in operation. Therefore, the lifespan of internal components of the laser irradiation device can be increased.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a cross-sectional view of a laser irradiation device.
- (2) FIG. 2A is a perspective view of the laser irradiation device.
- (3) FIG. 2B is a perspective view of the laser irradiation device.
- (4) FIG. 3A is diagram for explaining functional units.
- (5) FIG. 3B is diagram for explaining functional units.
- (6) FIG. 3C is diagram for explaining functional units.
- (7) FIG. 3D is diagram for explaining functional units.
- (8) FIG. 4A is diagram for explaining functional units.
- (9) FIG. 4B is diagram for explaining functional units.
- (10) FIG. 4C is diagram for explaining functional units.
- (11) FIG. 4D is diagram for explaining functional units.
- (12) FIG. 5A is a diagram for explaining a lens unit.
- (13) FIG. 5B is a diagram for explaining a lens unit.
- (14) FIG. 6 is a diagram for explaining air circulation in a laser oscillator.
- (15) FIG. 7 is a cross-sectional view of the laser oscillator as taken along line A-A' of FIG. 6.
- (16) FIG. 8A is a diagram for explaining a charging stand.
- (17) FIG. 8B is a diagram for explaining a charging stand.
- (18) FIG. 9A is a diagram for explaining a tip stand.
- (19) FIG. 9B is a diagram for explaining a tip stand.

DETAILED DESCRIPTION OF THE INVENTION

(20) Hereafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings so that the present disclosure may be readily implemented by a person with ordinary skill in the art. However, it is to be noted that the present disclosure is not limited to the embodiments but may be embodied in various other ways. In drawings, parts irrelevant to the description are omitted for the simplicity of explanation, and like reference numerals denote like

parts through the whole document.

(21) Through the whole document, the term “comprises or includes” and/or “comprising or including” used in the document means that one or more other components, steps, operation and/or existence or addition of elements are not excluded in addition to the described components, steps, operation and/or elements unless context dictates otherwise. Further, through the whole document, the term “connected to” or “coupled to” that is used to designate a connection or coupling of one element to another element includes both a case that an element is “directly connected or coupled to” another element and a case that an element is “electronically connected or coupled to” another element via still another element. Furthermore, through the whole document, the term “on” that is used to designate a position of one element with respect to another element includes both a case that the one element is adjacent to the other element and a case that any other element exists between these two elements.

(22) Hereinafter, an embodiment of the present disclosure will be described in detail with reference to the accompanying drawings.

(23) FIG. 1 is a cross-sectional view of a laser irradiation device, and FIG. 2 is a perspective view of the laser irradiation device. Referring to FIG. 1 and FIG. 2, a laser irradiation device **100** for performing treatment on human skin may include a main body **110**, a laser oscillator **120**, a skin treatment unit **130**, a contact sensor unit **140**, a grip sensing unit **150**, a battery **160** and a main controller **170**. However, the laser irradiation device **100** illustrated in FIG. 1 and FIG. 2 is just an embodiment of the present disclosure and can be modified in various ways based on the components shown in FIG. 1 and FIG. 2.

(24) Referring to FIG. 1, the main body **110** forms the exterior of the laser irradiation device **100** and may include a barrel part **111**. The barrel part **111** may have a substantially cylindrical shape and its one side may be connected to the laser oscillator **120** and the other side may be connected to the skin treatment unit **130**.

(25) A forward lens **111a** configured to guide a laser beam forward and a backward lens **111b** may be provided in the barrel part **111**. Specifically, the forward lens **111a** and the backward lens **111b** may be provided at predetermined locations inside the barrel part **111** along a longitudinal direction of the barrel part **111**. For example, the forward lens **111a** may be disposed on the barrel part **111** and the backward lens **111b** may be disposed under the barrel part **111**.

(26) The forward lens **111a** and the backward lens **111b** may process a laser beam generated by the laser oscillator **120** and guide the laser beam in the longitudinal direction. In particular, the backward lens **111b** may be adjusted in location along the longitudinal direction. For example, the backward lens **111b** may be adjusted upwards or downwards along the longitudinal direction of the barrel part **111**. The location of the backward lens **111b** may be directly adjusted by an operator using an adjusting screw (not shown) provided on a predetermined outside surface of the main body **110**.

(27) The number, size and intensity of laser beams may be regulated based on the adjusted location of the backward lens **111b**. For example, the backward lens **111b** may process the laser beam generated by the laser oscillator **120** by dividing the laser beam into a plurality of laser beams and guide each laser beam to be irradiated in the longitudinal direction of the barrel part **111** (forward) in parallel with each other.

(28) The laser oscillator **120** is accommodated in the main body **110** and generates a laser beam to be irradiated through the barrel part **111**. Specifically, the laser oscillator **120** may include a laser charging capacitor. The laser oscillator **120** may be arranged in series side by side with the barrel part **111** so that the generated laser beam is directed toward the barrel part **111**.

(29) The skin treatment unit **130** is a component for performing laser treatment or iontophoresis treatment to a subject. In particular, the skin treatment unit **130** is detachably connected to the main body **110**, and, thus, the skin treatment unit **130** may perform laser treatment to the skin of the subject and then perform iontophoresis treatment to the laser treated area (irradiation target area) in

combination with the laser treatment.

(30) Specifically, after the operator performs the laser treatment to the irradiation target area, the skin treatment unit **130** may be mounted on the main body **110** and then operated to perform the treatment while being in contact with the irradiation target area (contact target area). Here, the skin treatment unit **130** may be electrically connected to a contact sensing unit **141** to transmit an electrical current for iontophoresis treatment to the contact target area.

(31) The skin treatment unit **130** can be detached from and attached to the main body **110** and includes a lens unit **131** and a functional unit **132**.

(32) Referring to FIG. 2A and FIG. 2B, the lens unit **131** includes a multi-lens **131a** that is detachably connected to the main body **110** and processes a laser beam generated by the laser oscillator **120** into a plurality of laser beams. For example, the multi-lens **131a** may be composed of a plurality of lenses that is spaced apart from each other in a longitudinal direction. The multi-lens **131a** can divide a laser beam into a plurality of laser beams.

(33) According to a conventional technology, a multi-lens used for a laser irradiation device is located inside the laser irradiation device. Therefore, it is difficult to replace the lens only.

(34) However, the laser irradiation device **100** according to the present disclosure includes the multi-lens **131a** in the lens unit **131** that can be detached from and attached to the main body **110** as shown in FIG. 2B. Therefore, if the lens is damaged by long-term use, the multi-lens **131a** can be replaced when the lens unit **131** is replaced. Accordingly, it is possible to suppress a decrease in energy efficiency of the laser irradiation device **100** caused by damage to the lens.

(35) Referring to FIG. 2B, the lens unit **131** may include a galvanic electrode **131c**, a galvanic sensor **131d**, contact sensing units **131e** and tip holding magnets **131f** on its upper surface.

(36) For example, if the combined functional unit **132** is an iontophoresis module, the functional unit **132** may be in contact with the galvanic electrode **131c** and the galvanic sensor **131d** may recognize the iontophoresis module.

(37) Also, the lens unit **131** may include a memory unit **131b**. When the memory unit **131b** receives a laser oscillation signal to generate a laser beam from the laser oscillator **120**, the memory unit **131b** may manage the replacement period of the lens unit **131** based on the number of laser oscillation signals.

(38) For example, the memory unit **131b** may store information of each laser oscillation signal and count the number of laser oscillation signals. For another example, if the lens unit **131** is replaced with a new one, the memory unit **131b** may deduct one for each laser oscillation signal from a predetermined count number, e.g., 500. Then, when the counter number becomes 0, the memory unit **131b** may transmit information that the lens unit **131** is to be replaced to the main controller **170**.

(39) Further, when the number of laser oscillation signals reaches a predetermined threshold value, the memory unit **131b** may transmit information that the functional unit **132** is to be replaced to the main controller **170**. For example, the memory unit **131b** may store information of each laser oscillation signal and count the number of laser oscillation signals.

(40) The functional unit **132** is detachably connected to the lens unit **131**. For example, the functional unit **132** may operate as a laser module or an iontophoresis module.

(41) The functional unit **132** includes the contact sensor unit **140** configured to sense a contact with a contact target area, and a tip **132d** on its upper surface. A laser beam may be irradiated through the tip **132d**. Herein, the tip **132d** may be designed in various shapes, and a laser beam may be irradiated in various forms depending on the shape of the tip **132d**.

(42) The contact sensor unit **140** includes the contact sensing unit **141** that is formed at an end portion of the main body **110** and senses a contact with a contact target area. For example, the contact sensor unit **140** may sense a contact with the subject's skin based on an electrical signal generated at the time of contact with a contact target area and at the same time, the contact sensor unit **140** may automatically oscillate laser beams at a predetermined time interval.

(43) The contact sensing unit **141** may be located at the end portion of the main body **110** to be exposed to the outside and may be made of a conductive material to allow an electrical current to flow. For example, the contact sensing unit **141** may be composed of a plurality of pins whose one ends are exposed to the outside.

(44) The contact sensor unit **140** may be connected to the contact sensing unit **141** and configured to sense an electrical current flowing through the contact sensing unit **141**. When the skin treatment unit **130** is in close contact with the skin around the irradiation target area of the subject, the contact sensor unit **140** senses an electrical current flowing through the contact sensing unit **141**. Thus, the contact sensor unit **140** may serve as a safety device that determines whether to allow the laser irradiation device **100** to irradiate a laser beam.

(45) The grip sensing unit **150** may be formed on a surface of the main body **110** to sense whether the operator is gripping the main body **110**. For example, the grip sensing unit **150** may be configured to sense a change in an optical signal or an electrical current signal caused by the operator's touch.

(46) Specifically, if the operator grips the main body **110** while forming a predetermined electrical pattern on the surface of the main body **110**, the grip sensing unit **150** may sense the operator's grip by measuring a change in resistance.

(47) When the condition in which the grip sensing unit **150** senses the operator's grip is satisfied, the operation of the skin treatment unit **130** may be allowed, and main controller **170** to be described later may determine whether or not the condition is satisfied.

(48) The battery **160** may be provided inside the main body **110** and may be configured to supply power to operate the laser oscillator **120** and supply power to the skin treatment unit **130**. For example, the battery **160** may be located inside the main body **110** and may be charged with power supplied from the outside.

(49) The main controller **170** may be located inside the main body **110**. The main controller **170** may be activated in a laser irradiation mode or an iontophoresis mode to control the operation of the laser oscillator **120**. For example, the main controller **170** may transmit an operation-related signal to the laser module or the iontophoresis module through the contact sensor unit **140**.

(50) Specifically, when the grip sensing unit **150** senses the operator's grip and the contact sensor unit **140** senses a contact between the operator and the contact sensing unit **141**, the main controller **170** may control a laser beam to be irradiated in response to an input of a shot button **171** of an interface unit (not shown).

(51) The interface unit is a component for the operator to operate the laser irradiation device **100** and check the status thereof. The interface unit may be configured to receive a signal for manipulating the main controller **170**. For example, a laser irradiation signal may be input through the shot button, and a signal for irradiating a laser beam or operating the skin treatment unit **130** may be input through a mode setting button. Further, a status display lamp may visually provide mode setting and detailed information of the laser irradiation device **100**.

(52) Specifically, when the functional unit **132** is combined with the main body **110**, the main controller **170** may control the functional unit **132** to operate in any one of a laser mode in which an electrical current of a first polarity is transmitted to the contact target area and an iontophoresis mode in which an electrical current of a second polarity different from the first polarity is transmitted to the contact target area.

(53) When the functional unit **132** is attached to the main body **110** and serves as a laser module, the main controller **170** operates the functional unit **132** in the laser mode, and when the functional unit **132** is attached to the main body **110** and serves as an iontophoresis module, the main controller **170** operates the functional unit **132** in the iontophoresis mode.

(54) As described above, the laser irradiation device **100** includes the skin treatment unit **130** that is mounted on the main body **110** and performs laser treatment or iontophoresis treatment. Accordingly, iontophoresis treatment in combination with laser treatment can be performed

conveniently without any equipment replacement or location movement. Since the combination of treatments is performed conveniently, the subject's satisfaction and treatment effect can be increased and the operator can efficiently perform a complex procedure.

(55) Hereinafter, a detailed configuration and function of the skin treatment unit **130** of the present disclosure will be described with reference to FIG. 3 and FIG. 4.

(56) FIG. 3 and FIG. 4 are diagrams for explaining functional units. FIG. 3 is a perspective view of the functional unit **132**. The functional unit **132** may include a laser module for laser treatment to the contact target area or an iontophoresis module that generates and controls an electrical current for iontophoresis treatment to the contact target area.

(57) A functional unit **132-1** shown in FIG. 3A is an iontophoresis module, and may include tip holding magnets **132a**, contact sensing unit contact surfaces **132b** and a contact surface **132c** on its lower surface **132-1a**.

(58) The functional unit **132-1** shown in FIG. 3A may be in contact with the galvanic electrode **131c** of the lens unit **131** through the contact surface **132c** on the lower surface **132-1a**, and may enable treatment to be performed in a galvanic mode.

(59) Functional units **132-2**, **132-3** and **132-4** shown in FIG. 3B to FIG. 3D are laser modules, and may include the tip holding magnets **132a** and the contact sensing unit contact surfaces **132b** on their lower surfaces **132-2a**, **132-3a** and **132-4a**. The contact surfaces **132c** may be hollow spaces.

(60) The functional units **132-2**, **132-3** and **132-4** shown in FIG. 3B to FIG. 3D have hollow spaces as the contact surfaces **132c** in their lower surfaces **132-2a**, **132-3a** and **132-4a** and thus cannot be in contact with the galvanic electrode **131c** of the lens unit **131**. Therefore, the functional units **132-2**, **132-3** and **132-4** may enable treatment to be performed in the laser mode.

(61) FIG. 4 is a plan view of the functional unit **132**. The functional unit **132-1** shown in FIG. 4A is an iontophoresis module, and the functional units **132-2**, **132-3** and **132-4** shown in FIG. 4B to FIG. 4D are laser modules. The functional unit **132-2** shown in FIG. 4B has a circular tip **132-2b**, the functional unit **132-3** shown in FIG. 4C has a rectangular tip **132-3b**, and the functional unit **132-4** shown in FIG. 4D has a square tip **132-4b**. The tip of the functional unit **132** may be designed in various shapes, and is not limited to the present embodiment.

(62) FIG. 5 is a diagram for explaining coupling of a lens unit. Referring to FIG. 2, the main body **110** has a lens unit contact surface **131g** to be in contact with the lens unit **131**. FIG. 5A illustrates the lens unit contact surface **131g**, and FIG. 5B illustrates a lower part of the lens unit contact surface **131g**.

(63) Referring to FIG. 5A, the lens unit contact surface **131g** may include a communication connector **131h**. For example, the communication connector **131h** may be an EEPROM or a touch sensor. Referring to FIG. 2 and FIG. 5, when the lens unit **131** is attached to the lens unit contact surface **131g** of the main body **110**, the laser irradiation device **100** may recognize the attachment of the lens unit **131** through the communication connector **131h**.

(64) FIG. 6 is a diagram for explaining air circulation in a laser oscillator, and FIG. 7 is a cross-sectional view of the laser oscillator as taken along line A-A' of FIG. 6. The laser irradiation device **100** itself has a cooling function and can remove heat generated in the laser oscillator **120** when in operation.

(65) Referring to FIG. 6, the laser irradiation device **100** may further include a fan **121** and at least one ventilation hole **123**. The fan **121** may introduce external air into the laser oscillator **120**.

(66) Herein, the fan **121** may be composed of a first fan **121a**, a second fan **121b** and a third fan **121c** and may form a flow of air. For example, the first fan **121a** may be located to be connected to the main body **110** and configured to suck external air into the laser oscillator **120**. The second fan **121b** is located between the laser oscillator **120** and an exhaust unit **122** to form a flow of the external air sucked by the first fan **121a** toward the exhaust unit **122**. Then, the third fan **121c** may discharge the sucked-in external air to the outside through the exhaust unit **122**.

(67) Referring to FIG. 7, the ventilation holes **123** are formed on one side of the laser oscillator **120**

and may discharge external air toward the exhaust unit **122**. For example, the ventilation holes **123** may be formed on both sides of the laser oscillator **120**. External air sucked by the first fan **121a** may be supplied into the laser oscillator **120** through the ventilation holes **123**, and, thus, heat generated therein may be removed by air cooling.

(68) As described above, the laser irradiation device **100** may remove internal heat generated when the laser oscillator **120** oscillates laser beams by discharging the internal heat to the outside. Therefore, it is possible to more effectively perform laser treatment with the laser irradiation device **100** and also possible to increase the lifespan of internal components of the laser irradiation device **100**.

(69) FIG. **8** is a diagram for explaining a charging stand. Referring to FIG. **8A**, the laser irradiation device **100** may include a charging stand **180** and a tip stand **190**. For example, the laser irradiation device **100** may be inserted into the charging stand **180** and the battery may be charged.

(70) As shown in FIG. **8A**, the charging stand **180** includes a groove in the middle, and the laser irradiation device **100** may be inserted and fixed through the groove. The charging stand **180** may include charging terminals **181** in an upper surface of the groove where the laser irradiation device **100** is to be inserted.

(71) For example, the laser irradiation device **100** may be inserted into the groove of the charging stand **180** and brought into contact with the charging terminals **181**, and, thus, the battery **160** provided therein may be charged.

(72) The laser irradiation device **100** inserted into the charging stand **180** may also be inserted into the tip stand **190**. The laser irradiation device **100** may sterilize the tip **132d** of the functional unit **132** through the tip stand **190** while the battery **160** is charged.

(73) The tip stand **190** is configured to retain the functional unit **132** of the skin treatment unit **130** that can be detached from and attached to the main body **110**, and may be coupled to a lower part of the charging stand **180**. FIG. **9** is a diagram for explaining the tip stand **190**. FIG. **9A** illustrates an upper surface of the tip stand **190**, and FIG. **9B** illustrates a lower surface of the tip stand **190**. The tip stand **190** may include a plurality of grooves to accommodate the functional unit **132**. For example, the functional unit **132** may be accommodated and retained in the grooves of the tip stand **190**.

(74) For example, referring to FIG. **9A**, the tip stand **190** may retain at least one of a functional unit **191** including an iontophoresis module detached from the lens unit **131**, a functional unit **192** having a circular tip, a functional unit **193** having a rectangular tip and a functional unit **194** having a square tip. The functional units **191** to **194** retained in the tip stand **190** may be coupled to the charging stand **180** and sterilized.

(75) Referring back to FIG. **8B**, the charging stand **180** may include a plurality of UV LEDs **182** and a UV safety unit **183** on its lower surface. The plurality of UV LEDs **182** may sterilize the functional units retained in the tip stand **190**, and the UV safety unit **183** may control the operation of the UV LEDs **182**.

(76) Specifically, referring to FIG. **8** and FIG. **9**, the tip stand **190** where the functional units **191** to **194** are retained may be coupled to the charging stand **180**. The lower surface of the charging stand **180** may be coupled to the upper surface of the tip stand **190**.

(77) After the coupling, the functional units **191** to **194** retained in the tip stand **190** may be sterilized by the plurality of UV LEDs **182** provided on the lower surface of the charging stand **180**.

(78) When the charging stand **180** is separated from the tip stand **190**, the UV LEDs **182** may stop the sterilization. For example, the UV safety unit **183** may sense whether the lower surface of the charging stand **180** is coupled to the tip stand **190** and is in a closed state. The UV safety unit **183** may control the UV LEDs **182** to operate only when the lower surface of the charging stand **180** is coupled to the tip stand **190** and is in a closed state.

(79) Alternatively, when charging of the battery of the laser irradiation device **100** is stopped in the

charging stand **180**, sterilization by the UV LEDs **182** may also be stopped. For example, when the laser irradiation device **100** is separated from the charging stand **180** coupled to the tip stand **190**, i.e., when charging of the battery is stopped, sterilization by the UV LEDs **182** may also be stopped.

(80) As described above, the laser irradiation device **100** can be kept clean by sterilizing the tip **132d** of the functional unit **132** while charging the internal battery. The laser irradiation device **100** sterilizes the tip **132d** by coupling between the charging stand **180** and the tip stand **190** where the functional unit **132** is retained. Thus, it is possible to easily and efficiently manage the functional unit **132**.

(81) The above description of the present disclosure is provided for the purpose of illustration, and it would be understood by a person with ordinary skill in the art that various changes and modifications may be made without changing technical conception and essential features of the present disclosure. Thus, it is clear that the above-described embodiments are illustrative in all aspects and do not limit the present disclosure. For example, each component described to be of a single type can be implemented in a distributed manner. Likewise, components described to be distributed can be implemented in a combined manner.

(82) The scope of the present disclosure is defined by the following claims rather than by the detailed description of the embodiment. It shall be understood that all modifications and embodiments conceived from the meaning and scope of the claims and their equivalents are included in the scope of the present disclosure.

Claims

1. A laser irradiation device for performing treatment on human skin, comprising: a main body including a barrel part; a laser oscillator that is accommodated in the main body and configured to generate a laser beam to be irradiated through the barrel part; and a skin treatment unit that is detachably connected to the main body and includes a lens unit including a multi-lens that processes the laser beam generated by the laser oscillator into a plurality of laser beams and a functional unit detachably connected to the lens unit, wherein the lens unit further includes: a memory unit configured to manage a replacement period of the lens unit based on the number of laser oscillation signals when the memory unit receives a laser oscillation signal to generate a laser beam from the laser oscillator.
2. The laser irradiation device of claim 1, further comprising: a contact sensor unit including a contact sensing unit that is formed at an end portion of the main body and configured to sense a contact with a contact target area.
3. The laser irradiation device of claim 1, further comprising: a fan configured to introduce external air into the laser oscillator; and at least one ventilation hole formed on one side of the laser oscillator and configured to discharge the external air toward an exhaust unit.
4. The laser irradiation device of claim 1, wherein the functional unit includes a laser module for laser treatment to a contact target area or an iontophoresis module that generates and controls an electrical current for iontophoresis treatment to the contact target area.
5. The laser irradiation device of claim 4, further comprising: a main controller that is located inside the main body and configured to control the functional unit to operate in any one of a laser mode in which a laser is transmitted to a contact target area and an iontophoresis mode in which an electrical current of a first polarity and a second polarity different from the first polarity is transmitted to a contact target area when the functional unit is coupled to the main body.
6. The laser irradiation device of claim 5, wherein the main controller operates the functional unit in the laser mode when the functional unit is attached to the main body as a laser module, and the main controller operates the functional unit in the iontophoresis mode when the functional unit is attached to the main body as an iontophoresis module.

7. The laser irradiation device of claim 5, further comprising: an interface unit configured to receive a signal for manipulating the main controller.
 8. The laser irradiation device of claim 1, further comprising: a grip sensing unit formed on a surface of the main body to sense whether an operator is gripping the main body.
 9. The laser irradiation device of claim 1, further comprising: a battery provided inside the main body and configured to supply power to operate the laser oscillator and supply power to the skin treatment unit.
 10. The laser irradiation device of claim 1, further comprising: a forward lens and a backward lens that are provided at predetermined locations inside the barrel part along a longitudinal direction of the barrel part and configured to process the laser beam generated by the laser oscillator and guide the laser beam in the longitudinal direction, wherein the backward lens is adjusted in location along the longitudinal direction.
 11. The laser irradiation device of claim 10, wherein the number, size and intensity of laser beams are regulated based on the adjusted location of the backward lens.
 12. The laser irradiation device of claim 1, wherein the memory unit transmits information that the functional unit is to be replaced to a main controller when the number of laser oscillation signals reaches a predetermined threshold value.
-