

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415977
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Niederbacher; Michael

Plug flow fermenter for a biogas plant

Abstract

The invention relates to a fermenter vessel (1) of a biogas plant, having at least one height-adjustable agitator (8), wherein the agitator (8), in the fermenter vessel (1), is guided with a guide element (17) on a guide rail (9) oriented approximately vertically in a vertical axis direction and is held in height-adjustable fashion by means of a traction cable (10). According to the invention, a traction force measuring device (22; 25) is provided for directly and/or indirectly measuring the traction force on the traction cable (10) in accordance with a cable tension, such that, by means of the traction force measuring device (22; 25), in the case of a preferably controlled height adjustment of the agitator (8), varying traction force measurement signals are generated in accordance with varying traction forces and are supplied to an evaluation device (20).

Inventors:	Niederbacher; Michael (Bruneck, IT)
Applicant:	Niederbacher; Michael (Bruneck, IT)
Family ID:	1000008818853
Appl. No.:	17/759658
Filed (or PCT Filed):	January 20, 2021
PCT No.:	PCT/EP2021/051127
PCT Pub. No.:	WO2021/151746
PCT Pub. Date:	August 05, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230066584 A1	Mar. 02, 2023

Foreign Application Priority Data

DE	DE102020102264.6	Jan. 30, 2020
----	------------------	---------------

Publication Classification

Int. Cl.: C12M1/107 (20060101); C12M1/00 (20060101); C12M1/06 (20060101); C12M1/34 (20060101); C12M1/36 (20060101)

U.S. Cl.:

CPC C12M21/04 (20130101); C12M27/02 (20130101); C12M27/18 (20130101); C12M41/40 (20130101); C12M41/42 (20130101); C12M41/48 (20130101);

Field of Classification Search

CPC: C12M (21/04); C12M (27/02); C12M (27/18); C12M (41/40); C12M (41/42); C12M (41/48); C12M (41/00); Y02E (50/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0009664	12/2011	Buerger	435/286.5	C12M 41/44

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202009005024	12/2008	DE	B01F 7/00733
2213720	12/2009	EP	B01F 7/00741

Primary Examiner: Hobbs; Michael L

Attorney, Agent or Firm: Southeast IP Group LLC

Background/Summary

FIELD OF THE INVENTION

(1) The invention relates to a fermenter vessel of a biogas plant having at least one height-adjustable agitator according to the preamble of claim 1, and to a method for operating a fermenter vessel according to the preamble of claim 17.

BACKGROUND OF THE INVENTION

(2) In a known fermenter vessel of the type in question of a biogas plant (DE 10 2007 009 451 A1), an agitator is held as a submersible motor agitator with guide elements on a vertical guide rail and is held in a height-adjustable fashion by means of a traction cable on a stationary cable pulley in the upper guide rail region. The agitator is height-adjustable by winding or unwinding the cable with a controllable cable pulley motor drive as a height actuator.

(3) In addition, a fill level measuring device is provided here, by means of which a fill level of a substrate is detected and a corresponding fill level measurement signal is generated as the actual height value signal. In addition, a control unit is provided, which is supplied with the fill level measurement signal, wherein a height actuator for the submersible motor agitator is controlled such that, if necessary, it is lowered to the extent that the agitator blades of the submersible motor

agitator are completely immersed in the substrate. Neither a shutdown of the cable pulley motor drive or of the height actuator at a lower or upper end position of the agitator, nor a recognition and detection of a floating or sinking layer and, if appropriate, of its thickness is thus possible.

SUMMARY OF THE INVENTION

(4) The object of the invention is to further develop a fermenter vessel of the type in question of a biogas plant having at least one height-adjustable agitator in such a way that a height adjustment of the agitator can be carried out in a functionally reliable manner with relatively little effort and relatively simple measures.

(5) This object is achieved with the features of the independent claims.

(6) According to claim 1, a fermenter vessel of a biogas plant having at least one height-adjustable agitator is provided, wherein the agitator, in the fermenter vessel, is guided with a guide element on a guide rail oriented approximately vertically in a vertical axis direction and is held in height-adjustable fashion by means of a traction cable. According to the invention, a traction force measuring device is provided for directly and/or indirectly measuring the traction force on the traction cable in accordance with a cable tension, such that, by means of the traction force measuring device, in the case of a preferably controlled height adjustment of the agitator, varying traction force measurement signals are generated in accordance with varying traction forces and are supplied to an evaluation device.

(7) This makes it possible to realize a shutdown of the height adjustment at end positions of the agitator and/or to determine heights and/or thicknesses and/or consistencies of floating and/or sinking layers in the substrate and, if necessary, to adapt measures in the plant control, in particular height positions, directional positions, run times and rotational speeds, etc. of one or more submersible motor agitators in a suitable manner to the fermentation process based on this information.

(8) According to a particularly preferred embodiment, it is proposed that the agitator be held in a height-adjustable fashion on a cable pulley by means of the traction cable, wherein the agitator is height-adjustable by winding or unwinding the traction cable with a controllable cable pulley motor drive as a height actuator. At least one traction force threshold value is predefined in the evaluation device; the cable pulley motor drive shuts down automatically when said threshold value is reached. If, for example, a lower predetermined stop point in the fermenter vessel is reached during a lowering process of the agitator, or if the agitator coming from above hits a floating or sinking layer with a particularly high consistency, the traction force on the traction cable downward decreases greatly according to the reduced cable tension, and the cable pulley motor drive is automatically shut down by the evaluation device.

(9) Accordingly, the shutdown function can, if appropriate, take place with a fault notification even when the height of the agitator is adjusted upward, if a predetermined upper stop on the guide rail or a largely impermeable floating or sinking layer is reached from below, causing the cable tension to increase.

(10) When passing downward or upward through a sinking or floating layer through which the agitator can still pass without a fault function and without being shut down, both the thickness and consistency of a sinking or floating layer may be determinable, if applicable, as a result of the local reduction or increase in the cable tension during passage.

(11) Simple shutdown processes in conjunction with high changes in cable tension can optionally be realized via simple limit switches and fixed wiring without complex evaluations having to be carried out in preferably programmable digital controls.

(12) An evaluation device for evaluating measured cable tension signals can regularly be easily integrated into a plant control for the biogas plant that is usually present anyway.

(13) According to a particularly preferred embodiment, the cable pulley is arranged in a stationary manner on the fermenter vessel, preferably arranged on an upper guide rail region of the guide rail. The stationary arrangement in particular on the upper guide rail region brings about good

accessibility and favorable geometric conditions with respect to the cable guidance to the agitator.

(14) In a preferred embodiment of the invention, the traction force measuring device is part of the controllable cable pulley motor drive, wherein a current traction force measurement signal or cable tension measurement signal is generated by measuring an actuator energy consumed by the cable pulley motor drive during a height adjustment, preferably taking into account the actuating direction downward or upward, which measurement signal is then evaluated in the evaluation device, if appropriate, for further measures.

(15) Preferably, an electric motor drive is used here as a controllable cable pulley motor drive, wherein a current measuring device, preferably an ammeter, is provided by means of which current consumption is measured during a height adjustment for generating a current traction force measurement signal and is supplied to the evaluation device.

(16) Further, alternatively or redundantly, a different traction force measuring device can be used, which may be arranged, for example, in a stationary manner in the region of the guide rail and/or, for example, below a cable pulley. Such a traction force measuring device preferably has a deflection device with at least one deflection element for the traction cable from its vertical tension direction, as a result of which a transverse force originating from the traction cable on the at least one deflection element is generated according to a current cable tension. The higher the traction force and thus the cable tension, the higher the transverse force resulting from the deflection. This transverse force is measured with a sensor element and supplied as a traction force measurement signal to an evaluation device.

(17) In a preferred specific embodiment, the deflection device comprises a plurality of deflection rollers as deflection elements, preferably three deflection rollers in a triangular arrangement, wherein an—in relation to the vertical axis direction—upper deflection roller and a lower deflection roller are located with contact surfaces in the vertical cable tension direction. A central deflection roller is arranged, preferably in an axially parallel manner, between the upper and the lower deflection roller in a manner offset in the transverse direction and movably guided. The traction cable is guided opposite the contact surfaces of the upper deflection roller and the lower deflection roller about the central deflection roller, so that, when a load is exerted on the cable, the central deflection roller is pushed in the direction of the vertical cable tension direction with a horizontal transverse force due to its transverse offset. Preferably, the traction force measuring device has a pressure sensor as sensor element, which pressure sensor is connected with its pressure-sensitive surface to the mounting of the central deflection roller for measuring its transverse force and generating a traction force measurement signal, wherein it is preferably provided for the pressure sensor to be fastened and/or supported in a stationary manner on the deflection device.

(18) Such a traction force measuring device is functionally reliable, relatively simply structured and inexpensive to produce.

(19) According to an advantageous embodiment variant, the mounting and movable transverse guidance of the central deflection roller can be easily carried out by means of a rocker arm which is fastened pivotably in the direction of the pressure sensor to the deflection device, preferably to a bearing block of the upper deflection roller. For a particularly stable arrangement, the rocker arm is designed as a fork arm with two fork parts spaced apart from one another, between which the central deflection roller is arranged with its axis. Furthermore, a cover, for example as a securing plate, can advantageously be attached to the outer side of the central deflection roller, which cover can be connected to the rocker arm in order to prevent the traction cable from falling off the central deflection roller when it is not under tension.

(20) The sensor element as the pressure sensor can be used in the manner of commercially available weighing cells which are available on the market as piezoresistive pressure sensors, in particular with strain gauges or as piezoelectric pressure sensors or as inductive pressure sensors or as capacitive pressure sensors.

(21) In a further embodiment, it is proposed that a rotational speed sensor be arranged on the cable pulley and/or on the cable pulley motor drive, by means of which rotational speed sensor the current number of cable windings and thus the currently unwound cable length can be measured in conjunction with the current height position of the agitator. A height position signal generated therewith can be evaluated in the evaluation device for a position determination and/or thickness determination of floating and/or sinking layers.

(22) According to a particularly preferred embodiment, varying traction force measurement signals can thus be supplyable to the evaluation device for determining the height position and/or the thickness and/or the consistency of a floating layer and/or sinking layer in the substrate, wherein it is preferably provided that the information obtained in this way with respect to the height position and/or the thickness and/or the consistency of a floating layer and/or sinking layer in the substrate is supplied to a plant control for the biogas plant and is taken into account and/or shown on a display as a control parameter when controlling the biogas plant, in particular when controlling the agitator.

(23) Furthermore, submersible motor agitators known per se can be used as one or more agitators with a preferably electric or hydraulic or pneumatic agitator motor in a tubular housing, from which an agitator shaft with a propeller with at least one agitator blade projects axially on one side. Even though this is the preferred embodiment, the term agitator is expressly to be understood in a broad sense in all embodiments of this invention and is therefore intended to include any type of submersible device which serves for generating flow, i.e., expressly also submersible devices without agitator blades, such as, for example, submersible pumps.

(24) In addition, a guide carriage encompassing the guide rail or a guide carriage engaging therein can be arranged as a guide element opposite the agitator blades, to which guide carriage the tubular housing is fastened and the traction cable is connected.

(25) The advantages achievable with the method according to the invention correspond to those of the fermenter vessel. In this respect, reference is made to the previous statements in order to avoid repetitions.

Description

BRIEF DESCRIPTION OF THE INVENTION

(1) The invention is explained in more detail only by way of example based on a drawing.

(2) In the drawing:

(3) FIG. 1 shows a schematic representation of a fermenter vessel of a biogas plant having at least one height-adjustable agitator, and

(4) FIG. 2 shows an enlarged representation of a traction force measuring device at position A of FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

(5) FIG. 1 shows, in a highly schematic manner, an upper partial region of a fermenter vessel 1 of a biogas plant with a portion of an upper region of an outer wall 2 of a film wall or ceiling wall 3 and a service shaft 4 mounted in a gas-tight manner as a covering hood above a film cut-out or ceiling cut-out. The fermenter vessel 1 is filled up to an upper region with a substrate 5 made of liquid biomass, wherein a floating layer 6 having a relatively dense consistency and a thickness 7 has already formed here. An agitator as a submersible motor agitator 8 is held in the fermenter vessel 1 in a side region on a guide rail 9 oriented approximately vertically in a vertical axis direction x by means of a traction cable 10 on a stationary cable pulley 11 in the upper guide rail region. The submersible motor agitator 8 is held on the guide rail 9 in a height-adjustable fashion by winding or unwinding the traction cable 10 by means of a controllable electric cable pulley motor drive 12.

(6) The guide rail 9 is pivotably mounted about its axis, on the one hand, in the film region or

ceiling region or in the region of the service shaft **4** and, on the other hand, on the base (not shown) of the fermenter vessel **1**, wherein these bearing points are designed in a conventional manner and are therefore not shown in detail.

(7) The submersible motor agitator **8** is equipped with an electric agitator motor **13** in a tubular housing **14**, from which an agitator shaft **15** with a propeller **16**, which in this case has two blades only by way of example, projects axially on one side. A guide carriage **17** encompassing the guide rail **9** is arranged opposite the propeller **16** as a guide element, to which both the tubular housing **14** and the lower end of the traction cable **10** are connected at a connection point **18**. The electrical energy for the electric agitator motor **13** is supplied in a controlled/regulated manner by means of a schematically indicated power line **19** of a control device **20**.

(8) In this case, the cable pulley motor drive **12** is also an electric motor drive and is supplied with current as actuator energy via the control device **20** and a power line **21**.

(9) In order to realize a traction force measuring device **22** for indirectly measuring the traction force on the traction cable **10** according to a cable tension, the current consumption of the cable pulley motor drive **12** is measured during a height adjustment by means of a (schematically shown) ammeter or current measuring device **23** and is supplied to the control device **20** via a signal line **24**. The control device **20** contains an evaluation device in which one or more traction force threshold values can be predetermined; power supply to the cable pulley motor drive **12** is interrupted automatically when said threshold value(s) is/are reached. In addition, varying traction force measurement signals for determining the height position and/or the thickness **7** and/or the consistency of a floating layer **6** or a sinking layer in the substrate **5** can be analyzed and evaluated in the evaluation device, which are then taken into account in particular when controlling the agitator. This information can optionally also be shown on a display (not shown).

(10) Moreover, in FIG. **1**, a further alternative or optionally additional and hence redundant traction force measuring device **25** is drawn in region A which is encircled by a dot-dash line. The alternative or additional traction force measuring device **25** is explained in more detail with reference to the enlarged illustration in FIG. **2**:

(11) Here, the traction force measuring device **25** is arranged, for example, in a stationary manner in the upper region of the guide rail **9** below the cable pulley **11** and has a deflection device **26** with at least three deflection rollers in the example shown here, namely an upper deflection roller **27**, a lower deflection roller **28** and a central deflection roller **29**. In the example shown here, the deflection rollers **27**, **28** and **29** are thus arranged in a triangular arrangement. Here, by way of example, the traction force measuring device **25** is fastened with a clamping housing **30** to the guide rail **9** so as to be non-displaceable. As shown by way of example here, a bearing block **31** for the upper deflection roller **27** and a bearing block **32** for the lower deflection roller **28** can be arranged on the front wall of the clamping housing **30**, wherein the traction cable **10** is guided vertically at the rear side from above onto the upper deflection roller **27** and extends again vertically downward from the lower deflection roller **28**.

(12) As shown merely by way of example here, the central deflection roller **29** can have the same dimensions as the upper deflection roller **27** and/or the lower deflection roller **28**.

(13) In the specific example shown here, the central deflection roller **29** is arranged in an axially parallel manner offset to the front in the transverse direction (indicated schematically by arrow **33**). The central deflection roller **29** is mounted on a rocker arm, which is designed here as a fork arm **34** merely by way of example, which rocker arm is tied or connected pivotably to the bearing block **31** so that the central deflection roller **29** is held movably in the transverse direction by means of the fork arm **34**.

(14) The traction cable **10** is shown to be guided from the rear side of the upper deflection roller **27** forward via the central deflection roller **29** and from there back again via the rear side of the lower deflection roller **28**, as a result of which a transverse force results in the direction of the clamping housing **30** due to the transverse offset of the central deflection roller **29** when a tensile load is

applied to the traction cable **10**. This transverse force is measured by means of a (commercially available) pressure sensor **35** (not shown in more detail) as a measure of the tension of the traction cable **10**, wherein, on the one hand, the pressure sensor **35** is supported on and fastened to the clamping housing **30** and, on the other hand, the mounting of the central deflection roller **29** in accordance with the fork arm **34** rests with a fork arm part on the pressure-sensitive surface of the pressure sensor **35** or is connected there. As can be seen, the arrangement is designed such that a transverse force acts as perpendicularly as possible on the pressure-sensitive surface of the pressure sensor **35**.

(15) Furthermore, a securing element **36** is formed on the fork arm **34** as a bent sheet metal part, which covers an outer region of the central deflection roller **29** so that a relaxed traction cable **10** cannot fall off the central deflection roller **29**.

(16) A pressure signal generated with the pressure sensor **35** and corresponding to a traction force measurement signal on the traction cable **10** is supplied to the control device **20** with a signal line **37** and is evaluated there, as a result of which control measures are possibly initiated or adapted, as already described above in connection with the first embodiment of a traction force measuring device **22**.

(17) In a further embodiment, a rotational speed sensor **38** is arranged on the cable pulley motor drive **12** or here on the cable pulley **11**, by means of which the current number of cable windings on the cable pulley **11** and thus the currently unwound cable length is measured in conjunction with the current height position of the submersible motor agitator **8**. A corresponding rotational speed signal or height position signal is supplied to the control device **20** with the signal line **39**, which control device can take control measures also taking into account the height position of the submersible motor agitator **8**.

LIST OF REFERENCE SIGNS

(18) **1** Fermenter vessel **2** Outer wall **3** Film wall or ceiling wall **4** Service shaft **5** Substrate **6** Floating layer **7** Thickness **8** Submersible motor agitator **9** Guide rail **10** Traction cable **11** Cable pulley **12** Cable pulley motor drive **13** Electric agitator motor **14** Tubular housing **15** Agitator shaft **16** Propeller **17** Guide carriage **18** Connection point **19** Power line **20** Control device **21** Power line **22** Traction force measuring device **23** Current measuring device **24** Signal line **25** Traction force measuring device **26** Deflection device **27** Upper deflection roller **28** Lower deflection roller **29** Central deflection roller **30** Clamping housing **31** Bearing block **32** Bearing block **33** Arrow **34** Fork arm **35** Pressure sensor **36** Securing element **37** Signal line **38** Rotational speed sensor **39** Signal line

Claims

1. A fermenter vessel of a biogas plant comprising: at least one height-adjustable agitator, wherein the agitator in the fermenter vessel, is guided with a guide element on a guide rail oriented approximately vertically in a vertical axis direction and is held in height-adjustable fashion by means of a traction cable; a traction force measuring device is provided for measuring the traction force on the traction cable in accordance with a cable tension, such that, by means of the traction force measuring device, in the case of a controlled height adjustment of the agitator, varying traction force measurement signals are generated in accordance with varying traction forces and are supplied to an evaluation device.

2. The fermenter vessel according to claim 1, wherein the agitator is held in height-adjustable fashion on a cable pulley by means of the traction cable, the agitator is height-adjustable by winding or unwinding the traction cable with a controllable cable pulley motor drive as a height actuator, and at least one traction force threshold value is predefined in the evaluation device, wherein the cable pulley motor drive shuts down automatically when said threshold value is reached.

3. The fermenter vessel according to claim 2, wherein the cable pulley is arranged in a stationary manner on the fermenter vessel, on an upper guide rail region of the guide rail.
4. The fermenter vessel according to claim 2, wherein the traction force measuring device is part of the controllable cable pulley motor drive, and an actuator energy measuring unit is provided, by means of which an actuator energy consumed by the cable pulley motor drive during a height adjustment is measured and a current traction force measurement signal is respectively derived therefrom, taking into account the actuating direction downward or upward.
5. The fermenter vessel according to claim 2, wherein the controllable cable pulley motor drive is an electric motor drive, and a current measuring device, is provided by means of which current consumption is measured during a height adjustment for generating a current traction force measurement signal and is supplied to the evaluation device.
6. The fermenter vessel according to claim 1, wherein the traction force measuring device is arranged preferably in a stationary manner in the region of the guide rail, wherein the traction force measuring device is positioned below the cable pulley in relation to the vertical axis direction.
7. The fermenter vessel according to claim 1, wherein characterized in that the traction force measuring device has a deflection device with at least one deflection element for the traction cable from its vertical clamping direction, and a sensor element is provided, by means of which the resulting transverse force on the at least one deflection element is measured and supplied to the evaluation device as a traction force measurement signal for the cable tension.
8. The fermenter vessel according to claim 7, wherein the deflection device comprises a plurality of deflection rollers as deflection elements, at least three deflection rollers in a triangular arrangement, wherein, in relation to the vertical axis direction, upper deflection roller and a lower deflection roller are located with contact surfaces in the vertical cable tension direction, and a central deflection roller is arranged, in an axially parallel manner, between the upper deflection roller and the lower deflection roller in a manner offset in the transverse direction and movably guided, and the traction cable is guided opposite the contact surfaces of the upper deflection roller and the lower deflection roller about the central deflection roller, so that, when a load is exerted on the cable, the central deflection roller is pushed in the direction of the vertical cable tension direction with a horizontal transverse force.
9. The fermenter vessel according to claim 8, wherein the traction force measuring device has a pressure sensor as sensor element, which pressure sensor is connected with its pressure-sensitive surface to the mounting of the central deflection roller for measuring its transverse force and generating a traction force measurement signal, wherein it is preferably provided for the pressure sensor to be fastened and/or supported in a stationary manner on the deflection device.
10. The fermenter vessel according to claim 8, wherein the mounting and movable transverse guidance of the central deflection roller is carried out by means of a rocker arm which is fastened pivotably in the direction of the pressure sensor to the deflection device to a bearing block of the upper deflection roller.
11. The fermenter vessel according to claim 10, wherein the rocker arm is designed as a fork arm with two fork parts spaced apart from one another, between which the central deflection roller is arranged with its axis.
12. The fermenter vessel according to claim 7, wherein the sensor element is selected from the group consisting of a pressure sensor in the manner of a weighing cell as a piezoresistive pressure sensor, with strain gauges, a piezoelectric pressure sensor, an inductive pressure sensor, and a capacitive pressure sensor.
13. The fermenter vessel according to claim 2, wherein a rotational speed sensor is arranged on the cable pulley and/or on the cable pulley motor drive, by means of which the current number of cable windings on the cable pulley and thus the currently unwound cable length can be measured in conjunction with the current height position of the agitator, so that a height position signal generated therewith is supplied to the evaluation device for determining the position and/or

thickness of floating and/or sinking layers.

14. The fermenter vessel according to claim 1, wherein, varying traction force measurement signals are supplied to the evaluation device for determining the height position and/or the thickness and/or the consistency of a floating layer and/or sinking layer in the substrate, wherein the information obtained in this way with respect to the height position and/or the thickness and/or the consistency of a floating layer and/or sinking layer in the substrate is supplied to a plant control for the biogas plant and is taken into account and/or shown on a display as a control parameter when controlling the biogas plant when controlling the agitator.

15. The fermenter vessel according to claim 1, wherein the evaluation device is integrated into a plant control for the biogas plant.

16. The fermenter vessel according to claim 1, wherein the agitator is a submersible motor agitator having an agitator motor that is selected from the group consisting of an electric motor agitator, a hydraulic agitator motor, and a pneumatic agitator motor in a tubular housing, from which an agitator shaft with a propeller with at least one agitator blade projects axially on one side, and a guide carriage encompassing the guide rail or engaging therein is arranged as a guide element opposite the propeller, to which guide carriage the tubular housing is fastened and the lower end of the traction cable is connected.

17. A method for operating a fermenter vessel of a biogas plant comprising the steps of providing at least one height-adjustable agitator, guiding the agitator in the fermenter vessel with a guide element on a guide rail that is oriented approximately vertically in a vertical axis direction and is held in height-adjustable fashion by means of a traction cable; providing a traction force measuring device for measuring the traction force on the traction cable in accordance with a cable tension, such that, by means of the traction force measuring device, in the case of a controlled height adjustment of the agitator, varying traction force measurement signals are generated in accordance with varying traction forces and are supplied to an evaluation device.
