

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416776
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Murakami; Taro et al.

Stereo lens apparatus and image pickup apparatus

Abstract

A stereo lens apparatus includes two optical systems arranged in parallel. Each of the two optical systems includes, in order from an object side to an image side, first to third lens units. An optical path is bent at a position between the first and second lens units and at a position between the second and third lens units in each of the two optical systems so that an inter-optical axis distance between two third lens units is narrower than an inter-optical axis distance between two first lens units. Part of one holding mechanism of two holding mechanisms that are configured to respectively hold the two third lens units is located in a concave portion provided on the other holding mechanism, and part of the other holding mechanism is located in a convex portion provided on the one holding mechanism.

Inventors: Murakami; Taro (Tokyo, JP), Ito; Hiroki (Kanagawa, JP), Fukai; Yosuke (Kanagawa, JP), Nitto; Kiyoshi (Saitama, JP), Uehara; Takumi (Kanagawa, JP), Noda; Atsuto (Tokyo, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008818915

Assignee: CANON KABUSHIKI KAISHA (Tokyo, JP)

Appl. No.: 17/934242

Filed: September 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230093930 A1	Mar. 30, 2023

Foreign Application Priority Data

JP	2021-160381	Sep. 30, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G02B7/02 (20210101); G02B7/14 (20210101); G03B35/10 (20210101); H04N13/236 (20180101); H04N23/55 (20230101)

U.S. Cl.:

CPC G02B7/021 (20130101); G02B7/025 (20130101); G02B7/026 (20130101); G02B7/14 (20130101); G03B35/10 (20130101); H04N13/236 (20180501); H04N23/55 (20230101);

Field of Classification Search

CPC: G02B (7/02); G02B (7/021); G02B (7/022); G02B (7/023); G02B (7/025); G02B (7/026); G02B (7/027); G02B (30/34); G02B (23/2415); G02B (7/14); G02B (3/14); G03B (35/10); H04N (13/204); H04N (13/232)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0027792	12/2012	Miyamoto	359/826	G02B 7/023
2015/0181089	12/2014	Mirlay	348/46	H04N 13/204
2020/0132978	12/2019	Winterot	N/A	G02B 26/0816

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H11149004	12/1998	JP	N/A
H11337801	12/1998	JP	N/A
2013238792	12/2012	JP	N/A
2014077305	12/2013	JP	N/A
2014102363	12/2013	JP	N/A
2020-008629	12/2019	JP	N/A
2020154008	12/2019	JP	G02B 23/18
2021051282	12/2020	JP	N/A
2012017684	12/2011	WO	N/A

OTHER PUBLICATIONS

The above foreign patent documents were cited in the Feb. 20, 2024 Japanese Office Action, which is enclosed without an English Translation, that issued in Japanese Patent Application No. 2021-160381. cited by applicant

Primary Examiner: Mebrahtu; Ephrem Z

Attorney, Agent or Firm: Cowan, Liebowitz & Latman, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present disclosure relates to a lens apparatus suitable for capturing a stereoscopic image.

Description of the Related Art

(2) As a stereo lens apparatus that enables acquisition of a stereoscopic image by imaging, a lens apparatus is used that includes two optical systems arranged in parallel so that parallax is provided. Japanese Patent Laid-Open No. ("JP") 2020-008629 discloses a stereo lens apparatus in which two optical systems (fisheye lenses) are arranged in parallel and two reflective members are provided in each optical system so that optical paths are bent. Bending the optical paths narrows a distance between image-side lens units in the two optical systems so that image circles of the two optical systems are formed on a single image sensor, while ensuring a base length between object-side lens units in the two optical systems.

(3) In order that the lens apparatus disclosed in JP 2020-008629 is attached to a general lens-interchangeable type image pickup apparatus, the image side lens units of the two optical systems are made to be accommodated in a mount that is detachably attachable to the image pickup apparatus. Therefore, the distance between the image-side lens units is made to be as narrow as possible. However, if the distance between the image-side lens units is narrowed, it becomes difficult to dispose a holding mechanism that holds each image-side lens unit within the distance.

SUMMARY OF THE INVENTION

(4) The present disclosure provides a stereo lens apparatus and an image pickup apparatus having the same each of which can include holding mechanisms that respectively hold image-side lens units within a distance between image-side lens units while the distance is narrowed.

(5) A stereo lens apparatus according to one aspect of the embodiments of the present disclosure includes two optical systems arranged in parallel. Each of the two optical systems includes, in order from an object side to an image side, a first lens unit, a second lens unit, and a third lens unit. An optical path is bent at a position between the first lens unit and the second lens unit and at a position between the second lens unit and the third lens unit in each of the two optical systems so that an inter-optical axis distance between two third lens units of the two optical systems is narrower than an inter-optical axis distance between two first lens units of the two optical systems. Part of one holding mechanism of two holding mechanisms that are configured to respectively hold the two third lens units is located in a concave portion provided on the other holding mechanism, and part of the other holding mechanism is located in a convex portion provided on the one holding mechanism.

(6) An image pickup apparatus according to one aspect of the embodiments of the present disclosure is an image pickup apparatus to which the stereo lens apparatus is detachably attachable. The image pickup apparatus includes a single image sensor configured to capture two optical images formed by the two optical systems.

(7) A stereo image pickup apparatus according to one aspect of the embodiments of the present disclosure includes the stereo lens apparatus.

(8) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a sectional view of a stereo image pickup lens according to a first embodiment.

(2) FIG. 2 is an exploded perspective view of the image pickup lens according to the first embodiment.

(3) FIG. 3 is another exploded perspective view of the image pickup lens according to the first

embodiment.

(4) FIG. 4 is a front view of the image pickup lens according to the first embodiment.

(5) FIG. 5 is a sectional view along a line AA in FIG. 4.

(6) FIG. 6 is a sectional view along the line AA of an image pickup lens according to a modification example of the first embodiment.

(7) FIG. 7 is a sectional view along a line BB in FIG. 4.

(8) FIG. 8 is a diagram illustrating optical axes of the image pickup lens and image circles on an image sensor according to the first embodiment.

(9) FIG. 9 is a diagram illustrating inclusion of one optical system in an image formed by the other optical system in the image pickup lens according to the first embodiment.

(10) FIG. 10 is a diagram illustrating a camera to which the image pickup lens is attached according to the first embodiment.

(11) FIG. 11 is a diagram illustrating a configuration of a stereo image pickup lens according to a second embodiment.

(12) FIG. 12 is another diagram illustrating a configuration of the image pickup lens according to the second embodiment.

(13) FIG. 13 is an exploded perspective view of the image pickup lens according to the second embodiment.

(14) FIG. 14 is a diagram illustrating a focus operating unit of the image pickup lens according to the second embodiment.

(15) FIG. 15 is a top view of the image pickup lens according to the second embodiment.

(16) FIG. 16 is a side view of the image pickup lens according to the second embodiment.

(17) FIG. 17 is an exploded perspective view of a focus adjusting unit of the image pickup lens according to the second embodiment.

(18) FIG. 18 is a side view of the focus adjusting unit according to the second embodiment.

(19) FIG. 19 is a partial enlarged view of the focus adjusting unit of the image pickup lens according to the second embodiment.

(20) FIG. 20 is a schematic diagram illustrating a load balance of the image pickup lens according to the second embodiment.

(21) FIG. 21 is an exploded perspective view of the focus adjusting unit according to the second embodiment.

(22) FIG. 22 is a sectional view of the focus adjusting unit according to the second embodiment.

(23) FIG. 23 is a perspective view of the focus adjusting unit according to the second embodiment.

(24) FIG. 24 is a schematic diagram of the focus adjusting unit according to the second embodiment.

(25) FIG. 25 is a top view of a stereo image pickup lens according to a third embodiment.

(26) FIG. 26 is a side view of the image pickup lens according to the third embodiment.

(27) FIG. 27 is a rear view of holding mechanisms of third lens units in the image pickup lens according to the third embodiment.

(28) FIG. 28 is an exploded perspective view of the holding mechanism of the third lens unit according to the third embodiment.

(29) FIG. 29 is a sectional view of the holding mechanisms of the third lens units according to the third embodiment.

DESCRIPTION OF THE EMBODIMENTS

(30) Referring now to the accompanying drawings, a description is given of embodiments according to the present disclosure.

First Embodiment

(31) FIG. 1 illustrates a section of a stereo image pickup lens (hereinafter simply referred to as image pickup lens) **200** as a stereo lens apparatus according to a first embodiment of the present disclosure. FIGS. 2 and 3 are exploded views of the image pickup lens **200** viewed from an object

side (front side) and an image side (rear side), respectively. The image pickup lens **200** is an interchangeable lens detachably attachable (interchangeable) to a lens-interchangeable type image pickup apparatus described below. However, the image pickup lens **200** may be provided in a lens-integrated image pickup apparatus and a stereo image pickup apparatus may be configured.

(32) The image pickup lens **200** includes a right-eye optical system **201R** as a first optical system and a left-eye optical system **201L** as a second optical system. The right-eye optical system **201R** and the left-eye optical system **201L** are arranged in parallel in a left-right direction (vertical direction in the drawing of FIG. 1). However, the first optical system and the second optical system may be arranged in parallel in a vertical direction (depth direction in the drawing of FIG. 1). In the following description, R is added to an end of a reference numeral of each part of the right-eye optical system **201R**, and L is added to an end of a reference numeral of each part of the left-eye optical system **201L**.

(33) The right-eye and left-eye optical systems **201R** and **201L** respectively include, in order from the object side to the image side, first lens units **211R** and **211L**, second lens units **221R** and **221L**, and third lens units **231R** and **231L**. Each lens unit includes one or more lenses.

(34) The first lens units **211R** and **211L** have first optical axes OA1R and OA1L, respectively. The first optical axes OA1R and OA1L are separated from each other by an inter-optical axis distance L1 in the left-right direction. The distance L1 is also referred to as a base length. Each of the first lens units **211R** and **211L** includes, on the object side, a front lens surface **211A** having a convex shape, so that each of the right-eye and left-eye optical systems **201R** and **201L** has an angle of view of 180° or more.

(35) The second lens units **221R** and **221L** respectively have second optical axes OA2R and OA2L that extend in the left-right direction and are respectively orthogonal to the first optical axes OA1R and OA1L.

(36) The third lens units **231R** and **231L** respectively have third optical axes OA3R and OA3L extending orthogonally to the second optical axes OA2R and OA2L (parallelly to the first optical axes OA1R and OA1L). Each third lens unit includes a front lens **231a** and a rear lens **231b** in order from the object side to the image side. The third optical axes OA3R and OA3L are separated from each other by a distance (narrow inter-optical axis distance) L2 that is shorter than the base length L1 in the left-right direction. In the following description, a direction in which the first optical axis OA1 (R, L) and the third optical axis OA3 (R, L) extend is referred to as an optical axis direction. A direction orthogonal to the optical axis direction (front-rear direction) is referred to as a radial direction, a direction orthogonal to the optical axis direction and the left-right direction is referred to as a vertical direction, and a direction around the first and third optical axes OA1 (R, L) and OA3 (R, L) is referred to as a circumferential direction.

(37) First prisms **220R** and **220L** are respectively disposed between the first lens unit **211R** and the second lens unit **221R** and between the first lens unit **211L** and the second lens unit **221L**, and the first prisms **220R** and **220L** serve as reflective members that respectively bend optical paths of lights having been transmitted through the first lens units **211R** and **211L** toward the second lens units **221R** and **221L**. Second prisms **230R** and **230L** are respectively disposed between the second lens unit **221R** and the third lens units **231R** and between the second lens unit **221L** and the third lens unit **231L**, and the second prisms **230R** and **230L** serve as reflective members that respectively bend optical paths of lights having been transmitted through the second lens units **221R** and **221L** toward the third lens units **231R** and **231L**.

(38) The right-eye and left-eye optical systems **201R** and **201L** are held respectively by lens holding members **212R** and **212L**, accommodated in an exterior cover member **203**, and screwed and fixed to a lens top base **300**. The lens top base **300** is screwed and fixed to a lens bottom base **301** disposed inside the exterior cover member **203**. A straight guide portion provided on the exterior cover member **203** holds the lens bottom base **301** so that the lens bottom base **301** is movable in the optical axis direction while its rotation is restricted. As a result, the right-eye and

left-eye optical systems **201R** and **201L** can perform focus adjustment by moving in the optical axis direction integrally with the lens top base **300** and the lens bottom base **301** (hereinafter also referred to as lens top/bottom bases **300** and **301**). A lens mount **202** is screwed and fixed to a rear end of the exterior cover member **203**.

(39) A front surface exterior member **204** is fixed to a front end of the exterior cover member **203** by screwing or gluing. The front surface exterior member **204** has two openings **204F** for exposing the front lens surfaces **211A** of the first lens units **211R** and **211L** of the right-eye and left-eye optical systems **201R** and **201L**.

(40) FIG. **4** illustrates the image pickup lens **200** viewed from the object side. FIG. **7** illustrates a section along a line BB of the image pickup lens **200** illustrated in FIG. **4**.

(41) An effective light beam enters each of the right-eye optical system **201R** and the left-eye optical system **201L** from an angle of view of 180° or more. As illustrated in FIG. **4**, an area on an inner side in the radial direction of an effective incident diameter **211C** on the front lens surface **211A** of each of the first lens units **211R** and **211L** is referred to as an effective incident surface **211B**. A light beam from a direction of 180° of the angle of view enters the effective incident surface **211B** from a direction orthogonal to the first optical axis OA1 (R, L). A light beam from a direction of more than 180° of the angle of view travels from the image side of the effective incident surface **211B** toward the effective incident surface **211B**. In order that the light beam from the direction of more than 180° of the angle of view is not blocked, a front surface of the front surface exterior member **204** is located on the image side of the effective incident surfaces **211B** of the first lens units **211R** and **211L** as illustrated in FIG. **7**. Similarly, front surfaces between the openings **204F** and the first lens units **211R** and **211L** of cover members **213** are also located on the image side of the effective incident surfaces **2** outermost **11B**.

(42) Specifically, as illustrated in FIG. **4**, the right side of a center point O between the right-eye optical system **201R** and the left-eye optical system **201L** is referred to as a right-eye area **20R**, and a left side of the center point O is referred to as a left-eye area **20L**. As illustrated in FIG. **7**, in the right-eye area of the front surface exterior member **204**, a right front surface **204A** is formed that does not block an outermost effective light beam (thick dotted line in the drawing) entering the left-eye optical system **201L** from a direction of 180° or more of the angle of view. Specifically, the right front surface **204A** has a shape that becomes closer to the image side as a position on the right front surface **204A** becomes more right side and farther from the first lens unit **211L** of the left-eye optical system **201L**.

(43) Similarly, in the left-eye area **20L** of the front surface exterior member **204**, a left front surface **204B** is formed that does not block an outermost effective light beam entering the right-eye optical system **201R** from a direction of 180° or more of the angle of view. Specifically, the left front surface **204B** has a shape that becomes closer to the image side as a position on the left front surface **204B** becomes more left side and farther from the first lens unit **211R** of the right-eye optical system **201R**.

(44) The right front surface **204A** includes, on portions located in the vicinity of the opening **204F** and on an upper side and a lower side of the center point O, wall portions **204C** that protrude to the front side from the right front surface **204A** and extend in arc shapes along the opening **204F**. Similarly, the left front surface **204B** includes, on portions located in the vicinity of the opening **204F** and on an upper side and a lower side of the center point O, wall portions **204D** that protrude to the front side from the left front surface **204B** and extend in arc shapes along the opening **204F**. The wall portions **204C** do not block the effective light beam entering the right-eye optical system **201R**, but block part of light beams heading the left-eye optical system **201L**. The wall portions **204D** do not block the effective light beam entering the left-eye optical system **201L**, but block part of light beams heading the right-eye optical system **201R**. As a result, as described below, images of the wall portions **204C** are included in an image circle of the left-eye optical system **201L**, and images of the wall portions **204D** are included in the image circle of the right-eye optical system

201R.

(45) FIG. 5 illustrates a section along a line AA of the vicinity of the first lens unit **211L** of the left-eye optical system **201L** in the image pickup lens **200** illustrated in FIG. 4. Here, a description is given of a holding structure of the first lens unit **211L** of the left-eye optical system **201L**, but the same applies to a holding structure of the first lens unit **211R** of the right-eye optical system **201R**.
(46) A lens holding member **212L** holds the first lens unit **211L**, the second lens unit **221L**, the third lens unit **231L**, the first prism **220R**, and the second prism **230R**. The ring-shaped cover member **213** having an opening is attached to an outer circumference of the lens holding member **212L**. A front end inner circumferential portion **213A** surrounding the opening of the cover member **213** covers an outer edge **211D** and its vicinity of the front lens surface **211A** of the first lens unit **211L**. That is, an inner diameter of the opening of the cover member **213** is smaller than a diameter of the outer edge **211D** of the front lens surface **211A**. The outer edge **211D** of the front lens surface **211A** is a boundary with a side surface **211E** of the first lens unit **211L**, and is on an outer side in the radial direction of the effective incident diameter **211C** of the first lens unit **211** represented by a two-dot chain line.

(47) On the rear side of the side surface **211E** of the first lens unit **211L**, a convex portion **211F** is formed that projects outward in the radial direction from the side surface **211E**. The lens holding member **212L** holds the first lens unit **211** in the optical axis direction by sandwiching this convex portion **211F** from the front and rear sides, and holds the first lens unit **211** in the radial direction by coming into contact with the outer circumferential surface of the convex portion **211F**.

(48) As described above, the cover member **213** attached to the outer circumference of the lens holding member **212L** is fitted into the opening **204F** of the left front surface **204B** of the front surface exterior member **204**, and thereby the lens holding member **212L** holding the first lens unit **211L** is held by the front surface exterior member **204** and is further held by the exterior cover member **203** to which the front surface exterior member **204** is fixed.

(49) FIG. 6 illustrates a modification example of FIG. 5. On the first lens unit **211L** illustrated in FIG. 6, the side surface **211E** of the first lens unit **211L** illustrated in FIG. 5 is not formed, and only a convex portion **211F'** is formed. That is, the convex portion **211F'** is directly connected to the outer edge **211D** of the front lens surface **211A**. In FIG. 6, the lens holding member **212L** holds the first lens unit **211** in the optical axis direction by sandwiching the convex portion **211F'** from the front and rear sides, and holds the first lens unit **211** in the radial direction by coming into contact with the outer circumferential surface of the convex portion **211F'**.

(50) In FIGS. 5 and 6, the inner diameter of the opening (front end inner circumferential portion **213A**) of the cover member **213** is ΦA , and the diameter of the outer edge **211D** of the front lens surface **211A** is ΦB . The following equation expresses an overlapping amount X that is an amount of the front end inner circumferential portion **213A** covering a portion of the front lens surface **211A** on the inner side of the outer edge **211D** in the radial direction.

$$X = (\Phi B - \Phi A) / 2$$

External appearance quality is improved by covering the outer edge **211D** of the front lens surface **211A** with the front end inner circumferential portion **213A** of the cover member **213**.

(51) The cover member **213** is attached to the lens holding member **212L** so that the cover member **213** is not displaced in the optical axis direction. Specifically, groove portions **213B** extending in the circumferential direction are formed at a plurality of locations in the circumferential direction (direction around the optical axis) on an inner circumference of the cover member **213**. These groove portions **213B** engage with bayonet claw portions **212A** provided at a plurality of locations in the circumferential direction on the outer circumference of the lens holding member **212L**. During assembly, the cover member **213** is put on the lens holding member **212L** so that the groove portions **213B** and the bayonet claw portions **212A** are located at phases different from each other in the circumferential direction. After that, when the cover member **213** is rotated in the circumferential direction, the bayonet claw portions **212A** enter the groove portions **213B** and

engage with the groove portions **213B** in the optical axis direction. Bayonet claw portions may be provided on the cover member **213**, and groove portions may be provided on the lens holding member **212L**.

(52) On the other hand, the cover member **213** is attached so that the cover member **213** is displaceable by a gap **Y** in the radial direction relatively to the lens holding member **212L**. The gap **Y** is smaller than the overlapping amount **X** of the cover member **213**. Therefore, as illustrated in FIGS. **5** and **6**, even when the lens holding member **212L** is displaced away from the cover member **213** by the amount of the gap **Y**, a state is maintained in which the outer edge **211D** of front lens surface **211A** is covered with the front end inner circumferential portion **213A** of the cover member **213**.

(53) An outer circumferential surface of the cover member **213** attached to the lens holding member **212L** in this manner is fitted into an inner circumferential surface of the opening **204F** of the front surface exterior member **204** so that the cover member **213** is movable in the optical axis direction. Thereby, the cover member **213** and the lens holding member **212L** are held so that they are movable integrally with the front surface exterior member **204** in the optical axis direction. A fitting gap between the outer circumferential surface of the cover member **213** and the inner circumferential surface of the opening **204F** is very small and smaller than the gap **Y** described above.

(54) In this way, the lens holding member **212L** is not directly fitted into the opening **204F** of the front surface exterior member **204**, but the cover member **213** that absorbs a backlash of the gap **Y** in the radial direction of the lens holding member **212L** is fitted into the opening **204F**. As a result, even when a manufacturing error causes a displacement of the position of the lens holding member **212L** in the left-right direction, the position is not forcibly corrected. Therefore, the optical performance of each of the right-eye and left-eye optical systems **201R** and **201L** and the relative error of the right-eye and left-eye optical systems **201R** and **201L** are prevented from being changed when the front surface exterior member **204** is attached.

(55) As illustrated in FIGS. **2** and **3**, a rotation limiting key portion **213C** is formed on the cover member **213**. The rotation limiting key portion **213C** engages with a rotation limiting groove portion **204E** formed on the front surface exterior member **204** so that a rotation is limited of the cover member **213** in the circumferential direction. This prevents the cover member **213** attached to the lens holding member **212L** from rotating and prevents the groove portions **213B** and the bayonet claw portions **212A** from disengaging. The cover member **213** may include a rotation limiting groove portion and the front surface exterior member **204** may include a rotation limiting key.

(56) As illustrated in FIGS. **5** and **6**, between a front inner surface **213D** facing the image side of the cover member **213** and a front end surface **212B** facing the object side of the lens holding member **212**, a ring-shaped first sealing member **214** for drip-proof and dustproof is disposed in a state of being compressed and sandwiched. The first sealing member **214** includes an elastically deformable material such as rubber and sponge. An elastic force of the first sealing member **214** compressed between the front inner surface **213D** and the front end surface **212B** biases the cover member **213** and the lens holding member **212** in opposite directions in the optical axis direction. This can reduce a backlash in the optical axis direction between the cover member **213** and the lens holding member **212**. Further, in a case where the lens holding member **212** is displaced relatively to the cover member **213** by the amount of the gap **Y** described above in the radial direction, the first sealing member **214** is elastically deformed following the displacement. This maintains the drip-proof and dustproof function and the function of biasing the cover member **213** and the lens holding member **212**.

(57) Between a bottom surface of a groove portion **213E** provided on the outer circumference of the cover member **213** and an inner circumference surface of the opening **204F** of the front surface exterior member **204**, a second sealing member **215** for drip-proof and dustproof is disposed in a

state of being sandwiched and compressed in the radial direction.

(58) The image pickup lens **200** having the configuration described above has high external appearance quality, optical performance, and dustproof and drip-proof performance, and can perform imaging for acquiring a stereoscopic image (a right-eye image and a left-eye image as parallax images having parallax) at an angle of view of 180° or more. The stereoscopic image is observed by an observer as a VR image through VR goggles or the like.

(59) FIG. **8** illustrates a positional relation viewed from the optical axis direction between the first to third optical axes OA1R and OA1L to OA3R and OA3L of right-eye and left-eye optical systems **201R** and **201L**, the lens mount **202**, and image circles ICR and ICL on a single image sensor **111** provided in the image pickup apparatus. **2**.

(60) On an image pickup plane of the image sensor **111**, the image circle ICR of the right-eye optical system **201R** (hereinafter referred to as a right image circle) and the image circle ICL of the left-eye optical system **201L** (hereinafter referred to as a left image circle) are formed side by side in the left-right direction. A diameter $\Phi D2$ of each image circle and a distance between the centers of the left and right image circles ICR and ICL are set to values such that the left and right image circles ICR and ICL do not overlap each other. For example, the image pickup plane of the image sensor **111** may be divided into left and right sides at the center, the center of the right image circle ICR may be located at the center of the right side of the image pickup plane, and the center of the left image circle ICL may be located at the center of the left side of the image pickup plane.

(61) Each of the right-eye and left-eye optical systems **201R** and **201L** in this embodiment is configured as a circular fisheye lens that forms a circular image of an object included in the angle of view of 180° or more on the image pickup plane. Circular images are illustrated in the left and right image circles ICR and ICL in FIG. **8**.

(62) For example, a size of the image sensor (image pickup plane) **111** is set to 24 mm long $\times$ 36 mm wide, the diameter $\Phi D2$ of each image circle is set to $\Phi 17$ mm, the distance L2 between the third optical axes OA3R and OA3L is set to 18 mm, and a length of each of the second optical axes OA2R and OA2L is set to 21 mm. In this case, the base length L1 between the first optical axes OA1R and OA1L is 60 mm, which is almost equal to a distance between eyes of an adult. If the diameters of the third lens units **231R** and **231L** and the distance L2 between the third optical axes OA3R and OA3L are set to values such that the third lens units **231R** and **231L** are included inside the lens mount **202**, the base length L1 can be made to be longer than the inner diameter ΦD of the lens mount **202**. That is, a relationship between ΦD , L1, and L2 are expressed by the following inequality.

$$L1 > \Phi D > L2$$

(63) In this embodiment, the angle of view is widened to at least 180° so that a more realistic VR image can be observed. A relationship between a diameter $\Phi D3$ of an image circle of an angle of view of 180° and the diameter $\Phi D2$ of the image circle of the maximum angle of view of more than 180° is expressed by the following inequality.

$$\Phi D2 > \Phi D3$$

(64) FIG. **9** illustrates inclusion of an image of the left-eye area **20L** into the right image circle ICR. The right image circle ICR includes images of the first lens unit **211L** of the left-eye optical system **201L**, the cover member **213**, the wall portions **204D** of the front surface exterior member **204**, and the vicinity thereof each of which is located in the left-eye area **20L**. The images of the cover member **213**, the wall portions **204D**, and the vicinity thereof are included in the image circle ICR (diameter $\Phi D2$) of the maximum angle of view, but are not included in the image circle (diameter $\Phi D3$) of the angle of view of 180° and included on the outer side of this image circle. On the other hand, an image of the first lens unit **211L** is also included in the image circle (diameter $\Phi D3$) of the angle of view of 180° . Thus, the specifications of the image pickup lens **200** cause the inclusion of images of part of the left-eye area **20L** into the right image circle ICR.

(65) However, the images of the cover member **213**, the wall portions **204D** of the front surface

exterior member **204**, and the vicinity thereof are included in the image on an outer side of a vertex of the first lens unit **211L** in the horizontal direction (the left side in FIG. **9**). Therefore, of a captured image that is a circular image formed by the fisheye lens, the portion on the outer side of the vertex of the first lens unit **211L** in the horizontal direction, that is, a small area on the left side of a straight line **Z** illustrated in FIG. **9** is trimmed (cut) in image processing or image editing. This can eliminate an effect on imaging and observation at an angle of view of more than 180°. The same applies to the inclusion of an image of the right-eye area **20R** into the left image circle ICL.

(66) FIG. **10** illustrates a stereo image pickup system **100** configured by attaching the image pickup lens **200** to a digital camera (hereinafter simply referred to as camera) **110** as a lens-interchangeable type image pickup apparatus. The image pickup lens **200** includes a lens controlling unit **209** in addition to the right-eye and left-eye optical systems **201R** and **201L**.

(67) The camera **110** includes the image sensor **111**, an A/D converter **112**, an image processing unit **113**, a display unit **114**, an operation unit **115**, a memory unit **116**, a camera controlling unit **117**, and a camera mount **122**. If the lens mount **202** of the image pickup lens **200** is attached to the camera mount **122** of the camera **110**, the camera controlling unit **117** and the lens controlling unit **209** are electrically connected, and they start communication.

(68) The image sensor **111** is a single photoelectric conversion element, such as a CCD sensor and a CMOS sensor, that generates an analog electric signal by photoelectrically converting (images) a right-eye image (ICR) and a left-eye image (ICL), which are optical images respectively formed by the right-eye and left-eye optical systems **201R** and **201L**. The A/D converter **112** converts the analog electric signal output from the image sensor **111** into a digital signal. The image processing unit **113** generates image data by performing various image processing on the digital signal output from the A/D converter **112**. The display unit **114** includes a display element such as a liquid crystal panel, and displays an image and various information depending on image data.

(69) The operation unit **115** functions as an interface for a user to input various instructions. In a case where the display unit **114** includes a touch sensor, this touch sensor is also included in the operation unit **115**. The memory unit **116** includes RAM, ROM, SSD, etc., and stores image data generated by the image processing unit **113**, a program used by the camera controlling unit **117** as a computer for its operation, and various data.

(70) The camera controlling unit **117** includes a CPU and the like, controls operation of the camera **110**, and controls operation of the image pickup lens **200** through communication with the lens controlling unit **209**.

Second Embodiment

(71) Next, a description is given of a second embodiment of present disclosure. FIG. **11** illustrates a stereo image pickup system **100** including the same image pickup lens **200** as in the first embodiment and a camera **110** to which the image pickup lens **200** is detachably attached. Elements in this embodiment that are the same as elements in the first embodiment are denoted by the same reference numerals as those in the first embodiment.

(72) As described in the first embodiment, the right-eye and left-eye optical systems **201R** and **201L** are attached to the lens top base **300**. More specifically, the left-eye optical system **201L** is fixed to the lens top base **300**, and the right-eye optical system **201R** is attached to the lens top base **300** so that the right-eye optical system **201R** is movable in the optical axis direction. The lens top base **300** is fixed to the lens bottom base **301** and supported by the exterior cover member **203** together with the lens bottom base **301** so that the lens top base **300** and the lens bottom base **301** are movable in the optical axis direction. Therefore, by moving the lens top/bottom bases **300** and **301** in the optical axis direction, the right-eye and left-eye optical systems **201R** and **201L** can be moved together in the same direction. Focus adjustment on the image sensor **111** can be performed by moving the entire right-eye and left-eye optical systems **201R** and **201L** in the optical axis direction.

(73) A description is given of a reason why focus adjustment is performed by moving the entire

right-eye and left-eye optical systems **201R** and **201L**. When the focus is to be adjusted by moving some lenses included in each optical system, if the positions of these moving lenses are erroneously different from each other, the optical characteristics of the right-eye and left-eye optical systems **201R** and **201L** become different from each other. As a result, the focus state differs between the right-eye image and the left-eye image for stereoscopic viewing, which may cause discomfort in stereoscopic viewing. Therefore, by moving the entire right-eye and left-eye optical systems **201R** and **201L**, it is possible to prevent the optical characteristics of the right-eye and left-eye optical systems **201R** and **201L** from being different.

(74) An outer circumference portion of a focus operating unit **400** is exposed outside the exterior cover member **203**, and is rotationally operated in the circumferential direction by the user to move the right-eye and left-eye optical systems **201R** and **201L** (lens top/bottom bases **300**, **301**) in the optical axis direction. A detailed description is given later of the configuration for moving the right-eye and left-eye optical systems **201R** and **201L** in the optical axis direction by the user rotationally operating the focus operating unit **400**.

(75) As described in the first embodiment, the lens mount **202** of the image pickup lens **200** is attached to the camera mount **122** of the camera **110**. Thus, in a case where the mount surface of the lens mount **202** is parallel to the image sensor (imaging surface) **111**, the focus states of the right-eye and left-eye optical systems **201R** and **201L** on the image sensor **111** match each other.

(76) However, as illustrated in FIG. **12**, a manufacturing error in the camera **110** may make the image sensor **111** slightly tilted and not parallel to the mount surface of the lens mount **202**. In this state, the focus states of the right-eye and left-eye optical systems **201R** and **201L** on the image sensor **111** do not match each other. FIG. **12** illustrates the tilt of the image sensor **111** in an exaggerated manner with respect to an actual tilt.

(77) Since the image sensor **111** may be tilted as described above, in this embodiment, the right-eye optical system **201R** is made to be movable in the optical axis direction relatively to the lens top/bottom bases **300** and **301** and the left-eye optical system **201L** that is fixed to the lens top/bottom bases **300** and **301**. A focus adjusting unit **500** can be reached from outside the exterior cover member **203** and is operated by the user to adjust the position of the right-eye optical system **201R** in the optical axis direction. A detailed description is given later of a position adjusting mechanism for adjusting the position of the right-eye optical system **201R** in the optical axis direction by an operation on the focus adjusting unit **500**.

(78) Even in a case where the image sensor **111** is tilted as illustrated in FIG. **12**, operating the focus adjusting unit **500** can adjust the position of the right-eye optical system **201R** in the optical axis direction relative to the left-eye optical system **201L** according to the tilt. Thereby, it is possible to make the focus states of the right-eye and left-eye optical systems **201R** and **201L** on the image sensor **111** match each other. From this state, when the focus of the right-eye and left-eye optical systems **201R** and **201L** are adjusted by a rotational operation on the focus operating unit **400**, in-focus states of the right-eye and left-eye optical systems **201R** and **201L** can be acquired.

(79) FIG. **13** illustrates an exploded view of a configuration for moving the right-eye and left-eye optical systems **201R** and **201L** by rotationally operating the focus operating unit **400**. The drawing also illustrates the focus adjusting unit **500**.

(80) The lens bottom base **301** has cam follower portions **301a** at three locations in the circumferential direction. The cam follower portions **301a** are in contact with, in the optical axis direction, cam portions **302a** provided at three locations in the circumferential direction on a cam member **302**. The lens bottom base **301** is biased by a spring (not illustrated) so that the cam follower portions **301a** are always in contact with the cam portions **302b**. As illustrated in FIG. **14**, each cam portion **302a** has a shape in which a thickness in its optical axis direction (vertical direction in the drawing) varies linearly in the circumferential direction. The exterior cover member **303** holds the cam member **302** rotatably in the circumferential direction.

(81) A focus ring as the focus operating unit **400** is sandwiched in the optical axis direction

between a front cover member **203a** and a rear cover member **203b** each of which is included in the exterior cover member **203**, and is held rotatably in the circumferential direction. Three portions in the circumferential direction on an inner circumference portion of the focus operating unit **400** are engaged with side surfaces of the cam portions **302a** in the circumferential direction. Thus, when the user rotationally operates the focus operating unit **400** in the circumferential direction, the cam member **302** also rotates together.

(82) When the cam member **302** rotates, the thickness of each cam portion **302a** changes in the optical axis direction at the position where the cam portion **302a** is in contact with the cam follower portion **301a**. As a result, the lens bottom base **301** moves in the optical axis direction. That is, the right-eye and left-eye optical systems **201R** and **201L** move together in the optical axis direction.

(83) Next, a description is given of a configuration for attaching the right-eye and left-eye optical systems **201R** and **201L** to the lens top base **300** with reference to FIGS. **13**, **15**, and **16**. FIGS. **15** and **16** are a front view and a side view, respectively, of the right-eye and left-eye optical systems **201R** and **201L**, a base prism bottom **311**, and the lens top base **300**.

(84) The right-eye and left-eye optical systems **201R** and **201L** are positioned so that the lens top base **300** is disposed between them in the left-right direction. A right side surface and a left side surface of the lens top base **300** are connected to base connecting portions **311R** and **311L** provided on the lens holding members **212R** and **212L**, respectively, as illustrated in FIG. **13**. In this embodiment, as described later, the base connecting portions **311R** and **311L** are allowed to slide in the optical axis direction relatively to the lens top base **300**.

(85) The lens top base **300** is disposed between the first optical axes OA1R and OA1L of the right-eye and left-eye optical systems **201R** and **201L**. The second optical axes OA2R and OA2L and the third optical axes OA3R and OA3L pass through concave portions that open rearward in the lens top base **300**. This is because if the lens top base **300** is disposed between the third optical axes OA3R and OA3L, the distance between the third optical axes OA3R and OA3L becomes wider, and the third lens units **231R** and **231L** cannot be accommodated inside the lens mount **202**.

(86) As illustrated in FIGS. **15** and **16**, connecting surfaces **312R** and **312L** where the lens top base **300** and the base connecting portions **311R** and **311L** of the lens holding members **212R** and **212L** are connected are formed as surfaces orthogonal to a line OAC connecting the first optical axes OA1R and OA1L. The connecting surfaces **312R** and **312L** are orthogonal to the second optical axes OA2R and OA2L. The connecting surfaces **312R** and **312L** are respectively surfaces parallel to the first optical axes OA1R and OA1L and the third optical axes OA3R and OA3L and located between the first optical axis OA1R and the third optical axis OA3R and between the first optical axis OA1L and the third optical axis OA3L. This arrangement can improve space efficiency and allows a circuit board **310** to be disposed between the connecting surfaces **312R** and **312L**.

(87) Next, a description is given of a position adjusting mechanism for moving the right-eye optical system **201R** relatively to the lens top base **300** with reference to FIGS. **17**, **18**, and **19**. FIG. **17** is an exploded view of the position adjusting mechanism, and FIG. **18** is a side view of the position adjusting mechanism. FIG. **19** is an enlarged view of part of the position adjusting mechanism.

(88) A base connecting portion **311R** of the lens holding member **212R** that holds the right-eye optical system **201R** is connected to the right side surface of the lens top base **300** by three screws **501a** to **501c** and three compression springs **502a** to **502c** located on outer circumferences of three screws **501a** to **501c** in a state such that the base connecting portion **311R** is always biased against the right side surface of the lens top base **300**. A decentering-rotating member **503** is rotatably attached to the lens top base **300** by a shoulder screw **504**. The decentering-rotating member **503** is positioned inside a hole portion **251** provided on the base connecting portion **311R**. The decentering-rotating member **503** rotates inside the hole portion **251** as the focus adjusting unit **500** is rotationally operated.

(89) As illustrated in FIG. **19**, the decentering-rotating member **503** has an outer shape center OZ2 that is decentered from a rotation center OZ1. Inside the hole portion **251**, D-cut portions **251a** and

251b are provided on both sides in the optical axis direction. The base connecting portion **311R** and the lens top base **300** are biased in directions such that they approach each other in the optical axis direction by a first tension spring **507** hooked to each of them. Hence, an outer circumferential surface of the decentering-rotating member **503** is in contact with the D-cut portions **251a** and **251b** of the hole portion **251**.

(90) In such a configuration, when the decentering-rotating member **503** rotates about the rotation center **OZ1**, the base connecting portion **311R** (that is, the right-eye optical system **201R**) slides in the optical axis direction relatively to the lens top base **300** by the decentering amount of the outer shape center **OZ2** from the rotation center **OZ1**. Thereby, it is possible to adjust the position of the right-eye optical system **201R** in the optical axis direction relative to the lens top base **300**.

(91) Two ball bearings **505a** and **505b** are attached to the lens top base **300** by shoulder screws **506a** and **506b** so that the ball bearings **505a** and **505b** are aligned in the optical axis direction. The ball bearings **505a** and **505b** are respectively located inside guide hole portions **252** and **253** provided on the base connecting portion **311R**, and respectively in contact with straight guide surfaces **252a** and **252b**, and **253a** and **253b** in the guide hole portions **252** and **253**. Thereby, a straight guide portion is configured that guides the right-eye optical system **201R** in the optical axis direction.

(92) As illustrated in FIG. **18**, a second tension spring **508** is hooked to the base connecting portion **311R** and the lens top base **300**. The second tension spring **508** biases the base connecting portion **311R** and the lens top base **300** in a direction such that they approach each other in the optical axis direction, and causes a rotational moment around a connection portion between the decentering-rotating member **503** and the hole portion **251a** in the base connecting portion **311R**. With this configuration, the right-eye optical system **201R** can move in the optical axis direction while being guided by the two ball bearings **505a** and **505b** without rattling in the vertical direction.

(93) Next, a description is given of a balance of loads occurring between the lens top base **300** and the right-eye optical system **201R** with reference to FIG. **20**. Here, m represents a mass of the right-eye optical system **201**, g represents a gravitational acceleration, μ represents a static friction coefficient between the lens top base **300** and the right-eye optical system **201R**, and $k1$ represents a spring constant and $x1$ represents an elongation amount of each of the three compression springs **502a** to **502c**. $k2$ represents a spring constant and $x2$ represents an elongation amount of the first tension spring **507**, and $k3$ represents a spring constant and $x3$ represents an elongation amount of the second tension spring **508**. In this case, load balance conditions expressed by the following inequality (1) and equation (2) is satisfied in state where the right-eye optical system **201R** faces the direction of gravity (downward).

$$\mu N + Mg < k2 \cdot x2 + k3 \cdot x3 \quad (1)$$

$$N = 3(k1 \cdot x1) \quad (2)$$

(94) By satisfying these conditions, the decentering-rotating member **503** and the right-eye optical system **201R** are always in contact with each other without rattling regardless of which direction the image pickup lens **200** faces (regardless of a position or an orientation of the image pickup lens **200**). Thereby, it is possible to prevent a state where the right-eye optical system **201R** does not follow the rotation of the decentering-rotating member **503** and does not move in the optical axis direction.

(95) With the above-described position adjusting mechanism of the right-eye optical system **201R**, the focus adjusting unit **500** can move the right-eye optical system **201R** relatively to the lens top base **300** in the optical axis direction without rattling even in a case where the focus adjusting unit **500** is located at a position away from the optical axis of the right-eye optical system **201R**.

(96) A position adjusting mechanism similar to the above may also be provided for the left-eye optical system **201L**. During assembly of the image pickup lens **200**, rotating the decentering-rotating member can adjust the position of the left-eye optical system **201L** relative to the lens top base **300** in the optical axis direction. The lens holding members **203R** and **203L** (base connecting

portions **311R** and **311L**) are directly connected to the lens top base **300** without any other parts in between, so that occurrence is suppressed of relative tilt and decentering of the right-eye and left-eye optical systems **201R** and **201L** during focus adjustment.

(97) In this embodiment, a description is given of the position adjusting mechanism having the configuration using the decentering-rotating member, but the position adjusting mechanism of other configurations may be used. Also, a description is given of the case where the ball bearing is used for the straight guide portion of the position adjusting mechanism, but a guide bar extending in the optical axis direction, etc. may be used.

(98) Next, a description is given of a configuration of the focus adjusting unit **500** with reference to FIGS. **21** and **22**. FIG. **21** is an exploded view of the focus adjusting unit **500**. FIG. **22** illustrates a connection between the focus adjusting unit **500** and the decentering-rotating member **503** of the position adjusting mechanism described above.

(99) In the focus adjusting unit **500**, an adjusting base **521** has a small diameter portion and a large diameter portion with a through hole formed in the center. The adjusting base **521** is attached to the exterior cover member **203** with two screws **525** in a state in where the small diameter portion is inserted into a hole portion provided on an inner part away from the outer surface of the exterior cover member **203** and a stepped portion between the small diameter portion and the large diameter portion is in contact with the periphery of the hole. An O-ring **529** is disposed between the small diameter portion of the adjusting base **521** and the hole portion of the exterior cover member **203** into which the small diameter portion is inserted.

(100) The adjusting pin **526** is rotatably inserted into the through hole of the adjusting base **521**. A spring **522** is disposed on an outer circumference of a middle portion of the adjusting pin **526** that is inserted into the adjusting base **521**. The spring **522** is compressed between a retaining ring **523** attached to the adjusting pin **526** and an end surface of the small diameter portion of adjusting base **521**. Thereby, the adjusting pin **526** is biased in a direction of insertion into the adjusting base **521**.

(101) The connecting member **524** is engaged with a first guide portion **526a** provided at a tip of the adjusting pin **526**. The first guide portion **526a** has two surfaces parallel to a shaft direction of the adjusting pin **526** on both sides of a shaft of the adjusting pin **526**, and the two surfaces are in contact with a second guide portion **524a** formed as two surfaces parallel to the shaft direction formed inside a groove portion provided on the connecting member **524**. Thereby, the connecting member **524** is held movably in a direction orthogonal to the shaft direction of the adjusting pin **526**.

(102) As illustrated in FIG. **22**, the tip of the connecting member **524** is provided with a third guide portion **524b** formed as a key-shaped protrusion. The third guide portion **524b** is in contact with a fourth guide portion **503a** provided on the decentering-rotating member **503**. Therefore, the user can rotate the adjusting pin **526** with a tool to rotate the decentering-rotating member **503** so as to adjust the position of the right-eye optical system **201R** in the optical axis direction.

(103) In this embodiment, the second guide portion **524a** is formed in the groove portion and the third guide portion **524b** is formed as a protrusion, but the second guide portion **524a** may be formed as a protrusion and the third guide portion **524b** may be formed in a groove portion.

(104) On the connecting member **524**, the second guide portion **524a** and the third guide portion **524b** are formed in directions that are orthogonal to the shaft direction of the adjusting pin **526** and orthogonal to each other. Since the second guide portion **524a** and the third guide portion **524b** are formed in this way, a direction in which the connecting member **524** can move relatively to the adjusting pin **526** and a direction in which the connecting member **524** can move relatively to the decentering-rotating member **503** are orthogonal to each other. As a result, for example, even in a case where a positional relation between the exterior cover member **203** and the right-eye optical system **201R** is changed by operating the focus adjusting unit **500**, the right-eye optical system **201R** can be moved in the optical axis by rotating the adjusting pin **526**.

(105) The decentering-rotating member **503** is pressed against the lens top base **300** by a spring **527**

and a stopper pin **528**, and its rotational position is held by friction with the lens top base **300**. This prevents the position of the right-eye optical system **201R** in the optical axis direction from being easily changed by an external force such as shock.

(106) FIG. **23** illustrates the connecting member **524** and the decentering-rotating member **503**. As described above, the connecting member **524** includes, in its groove portion, the second guide portion **524a** that is in contact with the first guide portion **526a** provided on the adjusting pin **526**. The contact between the first guide portion **526a** and the second guide portion **524a** makes the connecting member **524** movable relatively to the adjusting pin **526** in an X direction in the drawing orthogonal to the shaft direction of the adjusting pin **526**. The third guide portion **524b** of the connecting member **524** is formed as a protrusion extending in a Y direction orthogonal to the X direction. The third guide portion **524b** is in contact with the fourth guide portion **503a** that is provided on the decentering-rotating member **530** and extends in the Y direction. Thereby, the connecting member **524** is movable relatively to the decentering-rotating member **530** in the Y direction and movable relatively to the adjusting pin **526** in the X direction that is orthogonal to the shaft direction and orthogonal to the Y direction.

(107) FIG. **24** illustrates a positional relation between the decentering-rotating member **503** and the connecting member **524** when the focus operating unit **400** and/or the focus adjusting unit **500** are rotationally operated. A thick line circle represents the decentering-rotating member **503**, and a thin line circle represents the connecting member **524**. A thin solid line represents the second guide portion **524a** provided on the connecting member **524**, and a thin broken line represents the third guide portion **524b** provided on the connecting member **524**. A point A represents a rotation center of the decentering-rotating member **503** (OZ1 in FIG. **19**), and a point B represents a rotation center of the adjusting pin **526** engaged with the connecting member **524**. Since the adjusting pin **526** is held at a fixed position by the exterior cover member **203**, the position of the point B does not move. In a state of a neutral position, the position of the point B matches the position of the point A. AX represents the optical axis direction. X and Y represents the same directions as in FIG. **23**.

(108) In a case where the focus operating unit **400** is rotationally operated from the neutral position, the lens top base **300** moves in the AX direction, and the decentering-rotating member **503** attached to the lens top base **300** also moves in the same direction. At this time, relative movement in the X direction between the decentering-rotating member **503** and the connecting member **524** is limited by the contact between the third guide portion **524b** and the fourth guide portion **503a**, and relative movement in the X direction of the connecting member **524** (second guide member **524a**) relative to the adjusting pin **526** (first guide portion **526a**) is allowed. Therefore, when the decentering-rotating member **503** moves in the optical axis direction AX, the connecting member **524** also moves in the AX direction (=X direction) as illustrated in a state (1) and a state (2).

(109) For example, in a state (3) in which the adjusting pin **526** is rotationally operated from the state (1) and the connecting member **524** and the decentering-rotating member **503** are rotated, the X direction is tilted relatively to the AX direction. If the focus operating unit **400** is rotationally operated in this state, the decentering-rotating member **503** moves in the AX direction by moving together with the connecting member **524** in the X direction relatively to the adjusting pin **526** while moving in the Y direction relatively to the connecting member **524**. Therefore, even after the focus operating unit **400** is rotationally operated, the rotation can be transmitted from the adjusting pin **526** to the decentering-rotating member **503** through the connecting member **524**.

(110) As described above, providing, between the adjusting pin **526** and the decentering-rotating member **503**, the connecting member **524** movable in the X and Y directions relatively to the adjusting pin **526** and the decentering-rotating member **503** enables operations on the focus operating unit **400** and the focus adjusting unit **500** independent of each other.

Third Embodiment

(111) Each of FIGS. 25 and 26 illustrates an optical unit in which the lens holding members 212R and 212L hold the right-eye and left-eye optical systems (first lens units 211R and 211L to third lens units 231R and 231L) of the image pickup lens 200 according to a third embodiment of the present disclosure. FIG. 25 is a bottom view of the optical unit as viewed from the rear side (image side), and FIG. 26 illustrates the optical unit as viewed from the upper side. Each of FIGS. 27, 28, and 29 illustrates holding mechanisms of the third lens units 231R and 231L. FIG. 27 illustrates the holding mechanisms as viewed from the rear side, and FIG. 28 is an exploded view of the holding mechanism. The holding mechanisms of the third lens units 231R and 231L only differ in a phase of arrangement around the third optical axis OA3R and OA3L (are rotationally symmetrical about a central axis of the lens mount), and thus FIG. 28 illustrates one of the holding mechanisms. FIG. 29 illustrates a section of the holding mechanism as viewed from the rear side passing through a central axis of a decentering roller, which is described later.

(112) Each of the third lens units 231R and 231L includes the front lens 231a and the rear lens 231b as described in the first embodiment. In each of the third lens units 231R and 231L, the entire outer circumference of the front lens 231a is held by the third unit base 233 by thermal caulking to the third unit base 233. The third unit base 233 includes a wall portion 233d having a shape in which a portion in the circumferential direction of a cylinder as a basic shape is D-cut. The third lens units 231R and 231L are screwed and fixed to the lens holding members 212R and 212L, respectively.

(113) The rear lens 231b is held by a third unit holder 234 while four locations in the circumferential direction on the outer circumference portion of the rear lens 231b are thermally caulked to fastening portions 234a provided at four locations in the circumferential direction on the third unit holder 234. The left and right third unit bases 233 are arranged so that D-cut portions of the wall portions 233d are adjacent to each other. Part of the outer circumferential portions of the left and right third unit holders 234 are adjacent to each other in the D-cut area of the wall portion 233d (an area without the wall portion 233d) of the third unit base 233. In each of the left and right holding mechanisms formed and placed in this manner, a portion at a position where the left and right holding mechanisms are adjacent to each other (hereinafter also referred to as “adjacent portion”) has a smaller thickness in the radial direction (the direction orthogonal to the optical axis of each third lens unit) than the other portion (the portion where the wall portion 233d is provided).

(114) A roller seat, which is described later, is disposed on a portion of the third unit holder 234 where the fastening portion 234a is not provided. Generally, a lens is fastened (caulked) at three points to a member that holds the lens.

(115) However, in this embodiment, the third unit holders 234 are arranged side by side on the left and right as illustrated in FIG. 27. In this case, if fastening portions of the left and right third unit holders 234 are provided on an intersection line of a V plane and an H plane, which is a central axis of the lens mount, and thermal caulking is performed, resin melted out from each fastening portion may form convex portions. Convex amounts vary because of variations in processing, and therefore the convex portions may interfere with each other. For this reason, as illustrated in FIG. 28, column portions 234b projecting rearward are provided on the adjacent portions of the left and right third unit holders 234 so that thermal caulking is not performed on these portions, which prevents the convex portions interfering with each other from being formed.

(116) As illustrated in FIG. 27, the V plane and the H plane divide the entire area when viewed from the rear side into a right-eye upper area 20RU, a left-eye upper area 20LU, a right-eye lower area 20RD, and a left-eye lower area 20LD. At this time, the column portion 234b of the right third unit holder 234 is provided at a phase (position in a direction around the optical axis) near the right-eye lower area 20RD, and the column portion 234b of the left third unit holder 234 is provided at a phase near the left-eye upper area 20LU. Such an arrangement in which the phases of the column portions 234b are different from each other can make a portion on which thermal caulking is not performed so that a convex portion is not formed of each of the left and right third unit holders 234

smaller than the portion in an arrangement in which the column portions **234b** of the left and right third unit holders **234** are located at symmetrical phases in the left-right direction. As a result, it is possible to hinder a holding strength (caulking strength) of the third unit holder **234** holding the rear lens **231b** from being deteriorated.

(117) On the wall portion **233d** of the third unit base **233**, one first hole portion **233a**, two second hole portions **233b**, and two third hole portions **233c** are formed. A first decentering roller **236** is inserted into each of the first hole portion **233a** and the second hole portions **233b**, and a second decentering roller **237** is inserted into each third hole portion **233c**. These five decentering rollers **236** and **237** are rotatably attached to roller seats **234d** provided at five locations in the circumferential direction on the outer circumference portion of the third unit holder **234**. The first and second decentering rollers **236** and **237** and the third unit base **233** having the first to third hole portions **233a** to **233c** form an optical adjusting mechanism that enables optical adjustment of each third lens unit.

(118) The first hole portion **233a** has, on an outer circumferential surface side and an inner peripheral surface side, two-step fitting portions respectively fitting a decentering portion and a concentric portion that are provided as two steps on each first decentering roller **236**. The fitting portion on the outer circumferential surface side fits the decentering portion of the first decentering roller **236** in the optical axis direction (the direction in which the third optical axes **OA3R** and **OA3L** extend), but does not fit the decentering portion in the circumferential direction. The fitting portion on the inner circumferential surface side fits the concentric portion of the first decentering roller **236** over the entire circumference.

(119) The second hole portion **233b** has a fitting portion that fits the decentering portion of the first decentering roller **236**. This fitting portion fits the decentering portion of the first decentering roller **236** in the optical axis direction, but does not fit the decentering portion in the circumferential direction.

(120) The third hole portion **233c** has a fitting portion that fits a decentering portion of the second decentering roller **237**. This fitting portion fits the decentering portion of the second decentering roller **237** in the circumferential direction, but does not fit the decentering portion in the optical axis direction.

(121) By rotating the three first decentering rollers **236** about their central axes, it is possible to adjust a distance between the rear lens **231b** and the front lens **231a** in the optical axis direction. By rotating the second decentering roller **237** about its central axis, it is possible to adjust the decentering of the rear lens **231b** relative to the front lens **231a**.

(122) Three third tension springs **238** are provided that generate biasing force for preventing the rear lens **231b** from being displaced in the optical axis direction and in the circumferential direction (i.e., for holding the rear lens **231** without rattling) by backlashes of fitting between the decentering rollers and the respective hole portions. The third tension spring **238** is hooked to a hook **234c** provided on the third unit holder **234** and to a hook **233e** provided on the third unit base **233**, which are illustrated in FIG. 27, so that the third tension spring **238** is oblique to the optical axis direction. As a result, the third tension springs **238** bias the third unit holder **234** against the third unit base **233** in directions such that the third unit holder **234** and the third unit base **233** approach each other in the circumferential direction and in the optical axis direction.

(123) Of the right holding mechanism, one of the three third tension springs **238** that is provided on the portion adjacent to the left holding mechanism and a hook **233e** of the third unit base **233** to which the one third tension spring **238** is hooked (that is, part of one holding mechanism) are located on a left holding mechanism side of the V plane. Of the left holding mechanism, one of the three third tension springs **238** that is provided on the portion adjacent to the right holding mechanism and a hook **233e** of the third unit base **233** to which the one third tension spring is hooked (that is, part of the other holding mechanism) are located on a right holding mechanism side of the V plane.

(124) More specifically, as illustrated in FIG. 27, in the right holding mechanism, part of a third tension spring **238** most of which is located in the right-eye upper area **20RU** and a hook **233e** to which this third tension spring is hooked protrude to the left-eye upper area **20LU**. In the left holding mechanism, part of a third tension spring **238** most of which is located in the left-eye lower area **20LD** and a hook **233e** to which this third tension spring **238** is hooked protrude to the right-eye lower area **20RD**.

(125) In the third unit base **233** of the left holding mechanism, the portion adjacent to the right holding mechanism is provided with a concave portion **233f** that creates a space where the third tension spring **238** and the hook **233e** of the right holding mechanism are located. Similarly, in the third unit base **233** of the right holding mechanism, the portion adjacent to the left holding mechanism is provided with a concave portion **233f** that creates a space where the third tension spring **238** and the hook **233e** of the left holding mechanism are located. By arranging the third tension springs **238** and the hooks **233e** in the concave portions **233f** in this way, it is possible to prevent the third tension spring **238** and the hook **233e** of the right holding mechanism from interfering with the left holding mechanism and to prevent the third tension the spring **238** and the hook **233e** of the left holding mechanism from interfering with the right holding mechanism.

(126) After the third tension spring **238** is hooked to the hooks **233e** and **234c**, a third unit cap **235** is screwed and fixed to the third unit base **233** as illustrated in FIG. 28 so that the external appearance quality is improved and dust is prevented from entering.

(127) By fixing the third lens units **231R** and **231L** to the lens holding members **212R** and **212L** and further fixing the lens holding members **212R** and **212L** to the lens top base **300**, the left and right holding mechanisms are integrated. In this state, as illustrated in FIGS. 25, 26 and 29, no decentering roller is provided on the side surfaces on the V plane side, which are ends of the portions at positions where the left and right holding mechanisms are adjacent to each other, of the left and right holding mechanisms. The five decentering rollers **236** and **237** are arranged on portions other than the side surface on the V plane side. Thus, in a state where the left and right holding mechanisms are integrated, all decentering rollers **236** and **237** can be reached from outside in the radial direction of each holding mechanism and can be rotated so that each third lens unit can be optically adjusted.

(128) According to this embodiment, the left and right third lens units **231R** and **231L** can be located close to each other and can be accommodated inside the lens mount. In addition, the holding mechanisms that enable optical adjustment of the third lens units **231R** and **231L**, respectively, are realized by arranging them rotationally symmetrically about the center axis of the lens mount and by using the same parts, which reduces the manufacturing cost of the image pickup lens.

(129) The above-described embodiment can provide a stereo lens apparatus including a holding mechanism for holding each third lens unit within a narrowed distance between the third lens units.

(130) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(131) This application claims the benefit of Japanese Patent Application No. 2021-160381, filed on Sep. 30, 2021, which is hereby incorporated by reference herein in its entirety.

Claims

1. A stereo lens apparatus comprising two optical systems arranged in parallel, wherein each of the two optical systems includes, in order from an object side to an image side, a first lens unit, a second lens unit, and a third lens unit, wherein an optical path is bent at a position between the first lens unit and the second lens unit and at a position between the second lens unit and the third lens

unit in each of the two optical systems so that an inter-optical axis distance between two third lens units of the two optical systems is narrower than an inter-optical axis distance between two first lens units of the two optical systems, wherein part of one holding mechanism of two holding mechanisms that are configured to respectively hold the two third lens units is located in a concave portion provided on the other holding mechanism, and part of the other holding mechanism is located in the concave portion provided on the one holding mechanism, wherein each of the two holding mechanisms includes a spring configured to generate a biasing force for holding the third lens unit, and wherein the part of each holding mechanism includes the spring and a hook to which the spring is hooked.

2. The stereo lens apparatus according to claim 1, wherein in each of the two holding mechanisms, a portion at a position where the two holding mechanisms are adjacent to each other has a smaller thickness in a direction orthogonal to an optical axis of the third lens unit than a portion at a position where the two holding mechanisms are not adjacent to each other, and wherein in each of the two holding mechanisms, the part of the holding mechanism and the concave portion are provided on the portion at the position where the two holding mechanisms are adjacent to each other.

3. The stereo lens apparatus according to claim 1, wherein each of the two holding mechanisms includes an adjusting mechanism configured to perform optical adjustment of the third lens unit.

4. The stereo lens apparatus according to claim 3, wherein the adjusting mechanism includes a plurality of decentering rollers for optical adjustment of the third lens unit, and wherein the plurality of decentering rollers are disposed on a portion that is not a portion at a position where the two holding mechanisms are adjacent to each other.

5. The stereo lens apparatus according to claim 1, wherein the stereo lens apparatus includes a mount detachably attachable to an image pickup apparatus, wherein the inter-optical axis distance between the two third lens units is smaller than an inner diameter of the mount, and wherein the inter-optical axis distance between the two first lens units is larger than the inner diameter of the mount.

6. An image pickup apparatus to which a stereo lens apparatus including two optical systems arranged in parallel is detachably attachable, the image pickup apparatus comprising a single image sensor configured to capture two optical images formed by the two optical systems, wherein each of the two optical systems includes, in order from an object side to an image side, a first lens unit, a second lens unit, and a third lens unit, wherein an optical path is bent at a position between the first lens unit and the second lens unit and at a position between the second lens unit and the third lens unit in each of the two optical systems so that an inter-optical axis distance between two third lens units of the two optical systems is narrower than an inter-optical axis distance between two first lens units of the two optical systems, wherein part of one holding mechanism of two holding mechanisms that are configured to respectively hold the two third lens units is located in a concave portion provided on the other holding mechanism, and part of the other holding mechanism is located in the concave portion provided on the one holding mechanism, wherein each of the two holding mechanisms includes a spring configured to generate a biasing force for holding the third lens unit, and wherein the part of each holding mechanism includes the spring and a hook to which the spring is hooked.

7. A stereo image pickup apparatus comprising a stereo lens apparatus including two optical systems arranged in parallel, wherein each of the two optical systems includes, in order from an object side to an image side, a first lens unit, a second lens unit, and a third lens unit, wherein an optical path is bent at a position between the first lens unit and the second lens unit and at a position between the second lens unit and the third lens unit in each of the two optical systems so that an inter-optical axis distance between two third lens units of the two optical systems is narrower than an inter-optical axis distance between two first lens units of the two optical systems, wherein part of one holding mechanism of two holding mechanisms that are configured to

respectively hold the two third lens units is located in a concave portion provided on the other holding mechanism, and part of the other holding mechanism is located in the concave portion provided on the one holding mechanism, wherein each of the two holding mechanisms includes a spring configured to generate a biasing force for holding the third lens unit, and wherein the part of each holding mechanism includes the spring and a hook to which the spring is hooked.
