

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416830
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lim; Eay Jin et al.

Lighting device and vehicle lamp having same

Abstract

The lighting device disclosed at an embodiment of the invention includes a substrate; a first reflective layer disposed on the substrate and having a plurality of reflection patterns; a light source disposed on the substrate; a resin layer disposed on the first reflective layer, and a second reflective layer disposed on the resin layer and having a plurality of holes, wherein an arrangement form of the plurality of holes is the same as that of the plurality of reflection patterns.

Inventors:	Lim; Eay Jin (Seoul, KR), Kim; Seong Jin (Seoul, KR)
Applicant:	LG INNOTEK CO., LTD. (Seoul, KR)
Family ID:	1000008818936
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/690808
Filed (or PCT Filed):	September 16, 2022
PCT No.:	PCT/KR2022/013860
PCT Pub. No.:	WO2023/043253
PCT Pub. Date:	March 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250004325 A1	Jan. 02, 2025

Foreign Application Priority Data

KR	10-2021-0125300	Sep. 17, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: G02F1/13357 (20060101); F21S43/239 (20180101); F21S43/245 (20180101); F21S43/249 (20180101); F21V8/00 (20060101)

U.S. Cl.:

CPC G02F1/133603 (20130101); F21S43/239 (20180101); F21S43/245 (20180101); G02B6/0055 (20130101); G02B6/0061 (20130101); G02F1/133605 (20130101); F21S43/249 (20180101)

Field of Classification Search

CPC: G02F (1/133603); G02F (1/133615); G02F (1/133605); G02F (1/133606); G02B (6/0055); G02B (6/0061); G02B (6/004); G02B (6/0058); G02B (6/006); F21S (43/239); F21S (43/245); F21S (43/249); F21V (7/22); F21V (7/05); F21V (7/0008); F21V (11/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0261286	12/2010	Choi	349/61	G02F 1/133611
2012/0106147	12/2011	Kim	362/235	G02B 6/0051
2012/0327330	12/2011	Takahashi et al.	N/A	N/A
2013/0002938	12/2012	Kim	N/A	N/A
2013/0235577	12/2012	Park	362/235	G02B 6/0021
2020/0218004	12/2019	Yoon et al.	N/A	N/A
2020/0285115	12/2019	Ito	N/A	G02B 6/0043

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
5631776	12/2013	JP	N/A
10-2011-0126839	12/2010	KR	N/A
20120036053	12/2011	KR	N/A
10-2012-0057179	12/2011	KR	N/A
10-2013-0007247	12/2012	KR	N/A
10-2013-0096140	12/2012	KR	N/A
10-2014-0059448	12/2013	KR	N/A
10-2020-0036578	12/2019	KR	N/A
10-2020-0086767	12/2019	KR	N/A
1526740	12/2015	TW	N/A

Primary Examiner: Kryukova; Erin

Attorney, Agent or Firm: KED & ASSOCIATES, LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

(1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2022/013860, filed Sep. 16, 2022, which claims priority to Korean Patent Application No. 10-2021-0125300, filed Sep. 17, 2021, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(2) An embodiment of the invention relates to lighting devices. An embodiment of the invention relates to a light unit or vehicle lamp having a lighting device.

BACKGROUND ART

(3) Light emitting diode (LED) have advantages such as low power consumption, semi-permanent life, fast response speed, safety, and environmental friendliness compared to conventional light sources such as fluorescent lamps and incandescent lamps. The light emitting diode is applied to various display devices, various lighting devices such as indoor or outdoor lights. Recently, as a vehicle light source, a lamp employing a light emitting diode has been proposed. Compared with incandescent lamps, light emitting diodes are advantageous in that power consumption is small. In addition, because the light emitting diode is small in size, it can increase the design freedom of the lamp and is economical due to its semi-permanent lifespan.

Disclosure

Technical Problem

(4) An embodiment of the invention may provide a lighting device for improving non-light images. An embodiment of the invention can provide a lighting device with improved light distribution characteristics by providing a reflection pattern at a lower portion of the resin layer and a hole at an upper portion of the resin layer. An embodiment of the invention may provide a slim lighting device with improved surface uniformity.

Technical Solution

(5) A lighting device according to embodiment of the invention comprises a substrate; a first reflective layer disposed on the substrate and having a plurality of reflection patterns; a light source disposed on the substrate; a resin layer disposed on the first reflective layer; and a second reflective layer disposed on the resin layer and having a plurality of holes, wherein an arrangement form of the plurality of holes may be a same as an arrangement form of the plurality of reflection patterns.

(6) According to an embodiment of the invention, the arrangement form of the plurality of holes includes n column, the arrangement form of the plurality of reflection patterns includes m column, and m and n are integers of one or more and may be the same or different from each other.

(7) According to an embodiment of the invention, the plurality of holes includes a first hole and a second hole in a first column among the n columns, and a first hole and a second hole in a second column among the n columns, an interval between the first hole and the second hole in the first column is equal to or smaller than an interval between the first hole in the first column and the first hole in the second column, and the first column may be disposed closer to the emission surface of the light source than the second column.

(8) According to an embodiment of the invention, the first reflective layer includes a first reflective film, the plurality of reflection patterns is disposed on the first reflective film, and the plurality of reflection patterns may be covered with a lower portion of the resin layer.

(9) According to an embodiment of the invention, the second reflective layer includes a transparent film and a second reflective film disposed on the transparent film, and the plurality of holes may be penetrated through the second reflective film.

(10) According to an embodiment of the invention, the plurality of reflection patterns and the plurality of holes overlap in one region in a direction perpendicular to an upper surface of the substrate, and a size of the hole may be smaller than a size of the reflection pattern in the overlapping region.

(11) A lighting device according to an embodiment of the invention includes a substrate; a first reflective layer disposed on the substrate; a light source disposed on the substrate; a resin layer disposed on the first reflective layer; and a second reflective layer disposed on the resin layer and having a plurality of holes, wherein the plurality of holes includes a region in which a number of holes per unit area of the plurality of holes increases as a distance from the light source increases in an emission direction of the light source.

(12) According to an embodiment of the invention, wherein each of the plurality of holes is a same size, wherein each of the plurality of reflection patterns is a same size, and the plurality of reflection patterns may include a region in which a number of reflection patterns per unit area increases as a distance from the light source increases in the emission direction of the light source.

(13) According to an embodiment of the invention, each of the plurality of holes has the same size, and the plurality of reflection patterns may include a region where a size of the reflection pattern increases as the distance from the light source in the emission direction of the light source increases.

(14) A lighting device according to an embodiment of the invention includes a substrate; a first reflective layer disposed on the substrate; a light source disposed on the substrate; a resin layer disposed on the first reflective layer; and a second reflective layer disposed on the resin layer and having a plurality of holes, wherein the plurality of holes may include a region where a size of the hole increases as a distance from the light source in the emission direction of the light source increases.

(15) According to an embodiment of the invention, the plurality of reflection patterns includes regions where the size of the reflection pattern increases as the distance from the light source in the emission direction of the light source increases, and a total area of the plurality of holes may be smaller than a total area of a reflection region of the second reflective layer.

(16) According to an embodiment of the invention, the light source includes a plurality of LEDs, and the plurality of LEDs may be arranged to emit light in a first direction. A number or size of the plurality of holes disposed adjacent to an emission surface of a first LED in the first direction based on an emission surface of one of the plurality of LEDs may be different from a number or size of the plurality of holes disposed adjacent to the emission surface of the second LED in a second direction opposite to the first direction.

(17) A lighting device according to an embodiment of the invention includes a first reflective layer having a reflection pattern; a second reflective layer having a plurality of holes; a resin layer disposed between the first reflective layer and the second reflective layer; and a light source that provides light to the inside or outside of the resin layer, wherein the reflective layer includes a region in which at least one of a size or interval of the holes changes as a distance from the light source in an emission direction of the light source increases, the second reflective layer includes a reflective film having the plurality of holes on the resin layer, the plurality of holes may penetrate from the upper surface of the reflective film toward the resin layer, and at least one or at least one column of the plurality of holes may overlap the reflection pattern in a vertical direction.

(18) According to an embodiment of the invention, the reflective film is made of a metal material, the size of the hole is 20 times or less than a wavelength emitted from the light source, the plurality of holes has an overlap ratio of 50% or more with the plurality of reflection patterns, and at least one of the plurality of holes may have an overlap ratio with a vertically overlapping reflection patterns in a range of 1% to 100%.

Advantageous Effects

(19) An embodiment of the invention may improve an off-light image and may change an image of lighting according to a viewing angle. Additionally, it may satisfy customer needs by providing a lighting image in the form of a hidden lamp of a vehicle. An embodiment of the invention may provide a thin lighting device with improved light distribution characteristics. Additionally, different images may be provided when the lighting is turned on or not. An embodiment of the

invention may improve the optical reliability of lighting devices by improving surface uniformity, and may be applied to light units, various display devices, or vehicle lamps having the same.

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a plan view of a lighting device according to an embodiment of the invention.
- (2) FIG. 2 is a cross-sectional view along A-A of the lighting device of FIG. 1.
- (3) FIGS. 3 (A) and (B) are plan views of the first and second reflective layers disclosed in FIG. 2.
- (4) FIG. 4 is a perspective view showing an arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 3.
- (5) FIG. 5 is a first modified example of the lighting device of FIG. 2.
- (6) FIG. 6 is a second modified example of the lighting device of FIG. 2.
- (7) FIGS. 7 (A) and (B) show different arrangement form of the reflection pattern of the first reflective layer and the holes of the second reflective layer shown in FIG. 2.
- (8) FIG. 8 is a perspective view showing a different arrangement form of the reflection pattern of the first reflective layer and the holes of the second reflective layer of FIG. 7.
- (9) FIG. 9 is a perspective view showing a different arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 2.
- (10) FIGS. 10 to 12 are examples of side cross-sectional views showing a vertical arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer.
- (11) FIG. 13 is a diagram showing a different arrangement form of a reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 2.
- (12) FIG. 14 is an example of a side cross-sectional view of the lighting device having the first and second reflective layers of FIG. 13.
- (13) FIG. 15 is a detailed configuration diagram of the first reflective layer of FIG. 14.
- (14) FIG. 16 is an example of a side cross-sectional view showing a third modified example of the lighting device of FIG. 1.
- (15) FIG. 17 is an example of a side cross-sectional view showing a fourth modified example of the lighting device of FIG. 1.
- (16) FIG. 18 is a diagram showing an individual light emitting unit as a fifth modified example of the lighting device of FIG. 1.
- (17) FIG. 19 is a diagram showing an individual light emitting unit as a sixth modified example of the lighting device of FIG. 1.
- (18) FIG. 20 is a side cross-sectional view showing another example of the lighting device of FIG. 1.
- (19) FIG. 21 is a side cross-sectional view showing a seventh modified example of the lighting device of FIG. 1.
- (20) FIGS. 22 and 23 are plan views showing the arrangement form of a plurality of LEDs in a lighting device according to an embodiment of the invention.
- (21) FIG. 24 is a plan view showing an example of hole deformation in the second reflective layer according to an embodiment of the invention.
- (22) FIG. 25 is a plan view of a vehicle having a lighting device according to embodiment(s) of the invention.
- (23) FIGS. 26 (A) and (B) are diagrams comparing examples of non-lighting or lighting of a vehicle's tail lamp.
- (24) FIGS. 27 (A) and (B) are diagrams comparing the luminous intensity according to the reflection pattern of lighting devices according to an embodiment of the invention.

BEST MODE

(25) Hereinafter, preferred embodiments of the invention will be described in detail with reference to the accompanying drawings. However, a technical spirit of the invention is not limited to some embodiments to be described, and may be implemented in various other forms, and one or more of the components may be selectively combined and substituted for use within the scope of the technical spirit of the invention. In addition, the terms (including technical and scientific terms) used in the embodiments of the invention, unless specifically defined and described explicitly, may be interpreted in a meaning that may be generally understood by those having ordinary skill in the art to which the invention pertains, and terms that are commonly used such as terms defined in a dictionary should be able to interpret their meanings in consideration of the contextual meaning of the relevant technology. Further, the terms used in the embodiments of the invention are for explaining the embodiments and are not intended to limit the invention. In this specification, the singular forms also may include plural forms unless otherwise specifically stated in a phrase, and in the case in which at least one (or one or more) of A and (and) B, C is stated, it may include one or more of all combinations that may be combined with A, B, and C. In describing the components of the embodiments of the invention, terms such as first, second, A, B, (a), and (b) may be used. Such terms are only for distinguishing the component from other component, and may not be determined by the term by the nature, sequence or procedure etc. of the corresponding constituent element. And when it is described that a component is “connected”, “coupled” or “joined” to another component, the description may include not only being directly connected, coupled or joined to the other component but also being “connected”, “coupled” or “joined” by another component between the component and the other component. In addition, in the case of being described as being formed or disposed “above (on)” or “below (under)” of each component, the description includes not only when two components are in direct contact with each other, but also when one or more other components are formed or disposed between the two components. In addition, when expressed as “above (on)” or “below (under)”, it may refer to a downward direction as well as an upward direction with respect to one element.

(26) FIG. 1 is a plan view of a lighting device according to an embodiment of the invention, FIG. 2 is a cross-sectional view along A-A of the lighting device of FIG. 1, FIG. 3(A)(B) is plan views of the first and second reflective layers disclosed in FIG. 2, FIG. 4 is a perspective view showing an arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 3, FIG. 5 is a first modified example of the lighting device of FIG. 2, FIG. 6 is a second modified example of the lighting device of FIG. 2, FIG. 7(A)(B) shows different arrangement form of the reflection pattern of the first reflective layer and the holes of the second reflective layer shown in FIG. 2, FIG. 8 is a perspective view showing a different arrangement form of the reflection pattern of the first reflective layer and the holes of the second reflective layer of FIG. 7, FIG. 9 is a perspective view showing a different arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 2, FIGS. 10 to 12 are examples of side cross-sectional views showing a vertical arrangement form of the reflection pattern of the first reflective layer and the holes in the second reflective layer, FIG. 13 is a diagram showing a different arrangement form of a reflection pattern of the first reflective layer and the holes in the second reflective layer of FIG. 2, FIG. 14 is an example of a side cross-sectional view of the lighting device having the first and second reflective layers of FIG. 13, FIG. 15 is a detailed configuration diagram of the first reflective layer of FIG. 14, FIG. 16 is an example of a side cross-sectional view showing a third modified example of the lighting device of FIG. 1, and FIG. 17 is an example of a side cross-sectional view showing a fourth modified example of the lighting device of FIG. 1.

(27) Referring to FIGS. 1 to 17, the lighting device **400** according to an embodiment of the invention may include a substrate **110**, a first reflective layer **120** disposed on the substrate **110**, a light source **100** on the substrate **110**, a resin layer **130** disposed on the first reflective layer **120**, and a second reflective layer **150** disposed on the resin layer **130**. The lighting device **400** may

guide the light emitted from the light source **100** and improve the uniformity of the light emitting surface.

(28) The substrate **110** may function as a base member or support member located below the light source **100** and the resin layer **130**. The substrate **110** includes a flexible or rigid substrate (PCB: Printed Circuit Board). The substrate **110** may include, for example, at least one of a resin-based printed circuit board (PCB), a metal core PCB, a flexible PCB, a ceramic PCB, or an FR-4 PCB. The substrate **110** may include, for example, a flexible PCB or a rigid PCB. The upper surface of the substrate **110** has an X-axis-Y axis plane, and a thickness of the substrate **110** may be the height in the Z direction. Here, the X and Y directions may be perpendicular to the Z direction.

(29) The substrate **110** includes a wiring layer (not shown) on the upper portion, and the wiring layer may be electrically connected to the light sources **100**. The light sources **100** include a plurality of LEDs **101** and **102**, and the plurality of LEDs **101** and **102** may be connected in series, parallel, or series-parallel by a wiring layer of the substrate **110**. The light sources **100** may be a group of two or more LEDs connected in series or parallel, or the LED groups may be connected in series or parallel. The thickness of the substrate **110** may be 0.5 mm or less, for example, in the range of 0.3 mm to 0.5 mm. Since the substrate **110** is provided with a thin thickness, the flexible module can be supported without increasing the thickness of the lighting device **400**.

(30) The substrate **110** may have a top view shape of a polygon such as a rectangle or square, may include a bridge or finger shape extending in different directions, or may include a bar shape with a curved surface. The substrate **110** may include a protective layer or a reflective layer on the upper portion. The protective layer or reflective layer may include a member made of a solder resist material, and the solder resist material is a white material and may reflect incident light. As another example, the substrate **110** may include a transparent material. Since the substrate **110** is made of a transparent material, light emitted from the light source **100** may be emitted in the upper and lower directions of the substrate **110**.

(31) The first reflective layer **120** may be disposed on the upper surface of the substrate **110**. The first reflective layer **120** may be disposed between the substrate **110** and the resin layer **130** and may reflect incident light. The first reflective layer **120** may include a single layer or multiple layers. The first reflective layer **120** may include a plurality of reflection patterns **123**. The first reflective layer **120** includes a first reflective film **121** attached to the upper surface of the substrate **110**, and the plurality of reflection patterns **123** may be disposed on the first reflective film **121**.

(32) The first reflective film **121** may include at least one of a reflective material, such as polyester (PET) film, poly methyl methacrylate (PMMA) material, or poly carbonate (PC). The first reflective film **121** may be provided as a film made of a resin material such as silicone or epoxy, and impurities of a reflective material may be added thereto.

(33) The plurality of reflection patterns **123** may be spaced apart from each other. The plurality of reflection patterns **123** may be formed in a dot shape or a hemispherical shape. As an example, the reflection pattern **123** may have a polygonal shape, a circular shape, an elliptical shape, a regular shape, or an irregular shape when viewed in a plan view, and may be formed in two or three dimensions. The plurality of reflection patterns **123** may be formed of metal or non-metallic material. The plurality of reflection patterns **123** may be formed by printing using reflective powder containing at least one of Al, Ag, SiO₂, CaO, Na₂O, TiO₂, and BaO.

(34) The size of the plurality of reflection patterns **123** may be selected from 0.1 mm or more, for example, within the range of 0.1 mm to 0.9 mm. The size of the reflection pattern **123** may be the bottom diameter or the bottom width, and the height of the reflection pattern **123** may be less than or equal to the bottom width. When the size of the reflection pattern **123** is smaller than the above range, reflection efficiency may be reduced, and when the size of the reflection pattern **123** is larger than the above range, light uniformity within the resin layer **130** may be reduced.

(35) The light source **100** may be disposed in plural numbers on the substrate **110**, and the light source **100** includes a plurality of LEDs **101** and **102**, and the plurality of LEDs **101** and **102** may

be arranged in one or more rows or/and one or more columns. The light source **100** may be arranged in n rows or/and m columns (n, m=1 or more). As shown in FIG. 22, a light source having two rows and two or more columns of LEDs **101** and **102** may be arranged, and as shown in FIG. 23, LEDs **101**, **102**, **104**, and **106** arranged in different lines may be arranged, and the substrate and the upper region thereof may include a region in which a part thereof protrudes in any one direction, or any one region may include a concave region. The light source **100** may include a plurality of LEDs **101** and **102**, including a first LED **101** adjacent to one side of the substrate **110** and a second LED **102** adjacent to the other side of the substrate **110**. The light source **100** may emit light in a first direction X or may emit light in different directions on the substrate **110**.

(36) Light emitted from the light source **100** may be emitted through the resin layer **130**. The light source **100** may emit light through at least one side. That is, the light source **100** includes at least one emission surface **11**, and the emission surface **11** may be arranged perpendicular to the upper surface of the substrate **110** and may face at least one side surface of the resin layer **130**. The light source **100** may emit at least one of white, blue, red, green, ultraviolet (UV), or infrared light. The light source **100** may emit at least one of, for example, blue, red, and green. For example, the LEDs **101** and **102** may be a side-type package. As another example, the light source **100** may be implemented as an LED chip.

(37) The light source **100** may be disposed on the substrate **110** and sealed by the resin layer **130**. The plurality of light sources **100** may be in contact with the resin layer **130**. The resin layer **130** may be disposed on the side surfaces and upper surface of the light source **100**. The resin layer **130** seals the light sources **100** and may be in contact with the upper surface of the substrate **110** and/or the first reflective layer **120**. The lower portion of the light source **100** may be disposed on the substrate **110** through a coupling hole in the first reflective layer **120** and may be bonded to the substrate **110** and the bonding member **13**.

(38) The resin layer **130** is disposed on the substrate **110** and seals the light source **100**. The resin layer **130** may be made of a transparent resin material, such as UV (Ultraviolet) resin, silicone, epoxy, or PET (polyethylene terephthalate). The resin layer **130** may be a transparent material layer to which no impurities are added. When the resin layer **130** is free of impurities, light may be transmitted with high linearity. As another example, the resin layer **130** may include a diffusion agent therein.

(39) The resin layer **130** may be thicker than the thickness of the light source **100**. The thickness of the resin layer **130** may be thicker than the thickness of the substrate **110**. The thickness of the resin layer **130** may be at least 5 times thicker than the thickness of the substrate **110**, for example, in the range of 5 to 9 times. By being disposed with the above thickness, the resin layer **130** may seal the light source **100** on the substrate **110**, prevent moisture from penetrating, and support the substrate **110**. The resin layer **130** and the substrate **110** may function as flexible plate. The thickness of the resin layer **130** may be 2.7 mm or less, for example, in the range of 2 mm to 2.7 mm. When the thickness of the resin layer **130** is less than the above range, the diffusion distance of light may increase, and when it is greater than the above range, the overall thickness may increase or the luminous intensity may decrease.

(40) The second reflective layer **150** includes a plurality of holes **155**, and each of the plurality of holes **155** may be a transmission hole having a circular shape and transmits light incident through the resin layer **130**. The second reflective layer **150** may emit surface light from the resin layer **130** as dot light. As shown in FIG. 22, when each of the plurality of holes **155** has a straight shape, it may emit light as straight light, and when each of the plurality of holes **155** has a curved shape, it may emit light as curved light. Accordingly, each of the holes **155** may include a circular shape, an oval shape, a straight shape, a curved shape, a mixture of at least two of these, or a shape of two or more of these connected to each other.

(41) The second reflective layer **150** may include a second reflective film **153** having a plurality of holes **155**. The second reflective layer **150** may include a transparent film **151** and a second

reflective film **153** disposed on the transparent film **151**. The transparent film **151** includes a transparent resin material, and may include, for example, at least one of polyester (PET), poly methyl methacrylate (PMMA), or poly carbonate (PC). The transparent film **151** may be placed on or spaced apart from the upper surface of the resin layer **130**. The transparent film **151** may be adhered to the upper surface of the resin layer **130** with an adhesive material such as silicone or epoxy.

(42) The second reflective film **153** includes a metal film and may include at least one of Al, Ag, and Pt, and may be laminated as an Al layer on the transparent film **151**, for example. At this time, when the Al layer is exposed on the second reflective layer **150**, when the light is not turned on, the Al surface may be exposed, and light may be emitted through the holes **155** when turned on. The holes **155** may have a size that is not visible from the outside when not turned on.

(43) The second reflective film **153** is disposed on the upper surface of the transparent film **151** to reflect light incident through the transparent film **151** and transmit it through the plurality of holes **155**. Each of the plurality of holes **155** may penetrate from the upper surface to the lower surface of the second reflective film **153**. Each of the plurality of holes **155** may not penetrate to the upper or lower surface of the transparent film **151**. That is, the second reflective layer **150** may be formed by punching a plurality of holes **155** on the second reflective film **153** through a laser process and then coating or depositing on one side of the transparent film **151**.

(44) The second reflective film **153** may be disposed on one side or both sides of the transparent film **151**. The second reflective layer **150** including the second reflective film **153** and the transparent film **151** may be attached to the surface of the resin layer **130**. At this time, the second reflective film **153** may be disposed on the outer layer of the transparent film **151**. As another example, the second reflective film **153** may be an inner layer of the transparent film **151**, or may be implemented as an outer layer and an inner layer.

(45) The thickness of the second reflective layer **150** may be 0.6 mm or less, for example, in a range from 0.1 mm to 0.6 mm. when the thickness is smaller than the above range, workability may not be easy or surface uniformity may be reduced, and when the thickness is thicker than the above range, the thickness of the lighting device **400** increases, and ductility characteristics may deteriorate.

(46) The thickness of the transparent film **151** may be 0.3 mm or less, for example, in the range of 0.05 mm to 0.3 mm. When it is thinner than the above range, it is difficult to function as a base layer in process measurement, and when it is thicker than the above range, it is difficult to implement ductility characteristics. The thickness of the second reflective film **153** may be 0.3 mm or less, for example, in the range of 0.05 mm to 0.3 mm. when it is thinner than the above range, reflective characteristics may deteriorate, and when it is thicker than the above range, laser processing may be difficult. The second reflective film **153** may be thinner or the same as the thickness of the transparent film **151**. The thickness of the second reflective film **153** may be the same as the depth of the hole **155**.

(47) Each of the plurality of holes **155** may have the same upper and lower diameters. The plurality of holes **155** may have a diameter or width of 90 μm or less, for example, in the range of 10 μm to 90 μm or 30 μm to 70 μm . The size of the hole **155** may be 20 times or less, for example, 2 to 15 times the wavelength (e.g., red wavelength) emitted from the light source **100**. When the diameter or width of the hole **155** is smaller than the above range, processing is difficult, and when it is larger than the above range, the hidden characteristics of the holes may be difficult. As another example, at least one or two of the plurality of holes **155** may have a lower diameter smaller than the upper diameter, and may be irradiated with a wider light distribution through the inclined surface of the holes **155**.

(48) Each of the plurality of holes **155** may have the same upper surface area and lower surface area. As another example, the upper surface area of each of the holes **155** may be larger than the lower surface area, and in this case, the upper surface area to which the laser is irradiated may be

larger than the lower surface area. The size of the hole **155** may be 90% or less of the size of the reflection pattern **123**, for example, in the range of 10% to 90%. The upper or lower surface area of the hole **155** may be 90% or less of the lower surface area of the reflection pattern **123**, for example, in the range of 10% to 90%. The size of the hole **155** may be the width of each hole **155** or may include the area of the upper or lower surface. When the size of the hole **155** is smaller than the above range, processing is difficult, and when the size of the hole **155** is larger than the above range, the holes may be visible from the outside or surface uniformity may deteriorate.

(49) As shown in FIG. 3, when the plurality of holes **155** are arranged in n rows and m columns (m, n are integers of 2 or more), the holes **155** may include a region in which an interval D1 between adjacent columns (e.g., L1 and L2) is greater than or equal to the interval D2 between the holes **155** in each of the columns L1 and L2. Here, the interval D2 between each hole **155** may be 0.5 mm or more, for example, in the range of 0.5 mm to 2 mm, and the interval D1 between the adjacent columns L1 and L2 may be 0.5 mm or more, for example, in a range of 0.5 mm to 2 mm. The intervals D1 and D2 may be the same or decrease as the distance from the LEDs **101** and **102** increases. Preferably, the plurality of holes **155** include the first hole and the second hole in the first columns L1 among the n columns, and the first hole and the second hole in the second column L2 among the n columns, and the interval D2 between the first hole and the second hole in the first column L1 may be equal to or less than the interval D3 between the first hole and the second hole in the second column L2. The first column L1 may be disposed closer to the emission surface **11** of the light source **100** than the second column L2.

(50) The holes **155** according to the first example may include regions where the holes **155** have the same size or/and regions where the size of the holes **155** gradually increases as the distance from the light source **100** (**101**, **102**) increases. Here, the region where the holes **155** are the same size may include at least two columns, and the regions in which the size of the holes **155** gradually increases may include a region in which the size of the holes **155** continuously increases in the first direction X or discontinuously increases in the first direction X. Additionally, the increasing region may include at least two regions of the same size within each region and different sizes in adjacent regions. Here, the continuously increasing region may gradually increase as the distance from the emission surface **11** of the LEDs **101** and **102** increases, and may be the same in each column, or may increase as the distance from the emission surface **11** of the LEDs **101** and **102** increases.

(51) The holes **155** according to the second example may include regions where the distance between the holes **155** is the same or/and regions where the distance between the holes **155** gradually increases as the distance from the light source **100** (**101**, **102**) increases. Here, the region where the interval between the holes **155** is the same may include at least two columns, and the region in which the interval of the holes **155** gradually increases may include a region in which the interval of the holes **155** increases continuously in one direction (e.g., emission direction) or discontinuously in one direction. Also, the increasing region may have the same or different intervals within each region or each column.

(52) As in the example of FIG. 4, the region where the reflection patterns **123** are arranged may include a first region A1 in which a first reflection pattern R1 having a first size is arranged, a second region A2 in which a second reflection pattern R2 having a second size larger than the first size is arranged, and a third region A3 in which a third reflection pattern R3 having a third size larger than the second size is arranged. The first region A1 has the first reflection patterns R1 arranged in two or more columns based on the emission surfaces **11** of the LEDs **101** and **102**, and the second region A2 is disposed between the first region A1 and the third region A3 and has the second reflection pattern R2 arranged in two or more columns, and the third region A3 is disposed in the farthest region based on the emission surface **11** of the LEDs **101** and **102**, and the third reflection patterns R3 may be arranged in two or more columns. The first to third regions A1, A2, and A3 are regions where the size of the reflection pattern **123** discontinuously increases.

(53) The region in which the holes **155** are arranged is described as first to third regions A1, A2,

and A3 so as to correspond to the regions of the first to third reflection patterns R1, R2, and R3. The region in which the holes 155 are arranged may include a first region A1 in which first holes H1 of a fifth size are arranged, a second region A2 in which second holes H2 of a sixth size larger than the fifth size are arranged, and a third region A3 in which third holes H3 of a seventh size larger than the sixth size are arranged. The first holes H1 are arranged in two or more columns in the first region A1 with respect to the emission surface 11 of the LEDs 101 and 102, and the second holes H2 are arranged in two or more columns in the second region A2 between the first region A1 and the third region A3, and the third hole H3 of the third region A3 is arranged in two or more columns in the farthest region with respect to the emission surface 11 of the LEDs 101 and 102. The first to third regions A1, A2, and A3 are regions in which the sizes of the holes H1, H2, and H3 are discontinuously increased.

(54) As shown in FIGS. 1 and 4, when the sizes of the holes H, H2, and H3 are SA1, SA2, and SA3, the first to third regions A1, A2, and A3 according to the first example may have a relationship of $HA1 < HA2 < HA3$. When the sizes of the reflection patterns R1, R2, and R3 are RA1, RA2, and RA3, the first to third regions A1, A2, and A3 may satisfy a relationship of $RA1 < RA2 < RA3$. The total area of the holes in the second reflective layer 150 may be smaller than the upper surface area of the reflective layer excluding the holes. The total area of the reflection patterns in the first reflective layer 120 may be smaller than the upper surface area of the reflective layer excluding the reflection patterns.

(55) As an example, the lighting device 400 may include a fourth region A4. The fourth region A4 is a region at a predetermined distance in the rear direction from the emission surface 11 of each LED 101 and 102, and may be disposed between the third region A3 and the first region A1 adjacent to the second LED 102, or may be disposed in a rear region from the emission surface 11 of the second LED 102. In the fourth region A4, the size of the fourth reflection pattern R4 may be the same as the size of the first or second reflection patterns R1 and R2 in the first and second regions A1 and A2, or may be smaller than the size of the third reflection pattern R3 in the third region A3. In the fourth region A4, the size of the fourth hole H4 may be the same as the size of the first or second holes H1 and H2 in the first and second regions A1 and A2, or may be smaller than the size of the third hole H3 in the third region A3.

(56) At least two of the n columns of holes 155 (e.g., L1, L2) may be parallel to each other, or may be arranged parallel or inclined to a straight line parallel to each emission surface 11 of the LEDs 101 and 102. The n columns may be arranged in a concentric shape with respect to the LEDs 101 and 102.

(57) As shown in FIGS. 3 and 4, in the embodiment of the invention, the first reflection pattern R1 of the minimum size among the plurality of reflection patterns 123 may be greater or equal to the third hole R3 of the maximum size among the plurality of holes 155. That is, since each of the plurality of holes 155 is processed using a laser, more than 95% of the holes 155 may be provided in a size smaller than the minimum size of the reflection pattern 123.

(58) Among the plurality of holes 155, at least one, at least one column, or two or more may overlap the reflection pattern 123 in a direction Z perpendicular to the substrate 110. The plurality of holes 155 and the plurality of reflection patterns 123 may overlap in a direction perpendicular to the substrate 110 in some regions Z1 and Z2. The overlap ratio of the plurality of holes 155 and the plurality of reflection patterns 123 may overlap by more than 50%, for example, in the range of 60% to 98% or 80% to 98%, in the direction perpendicular to the substrate 110. When the overlap ratio is within the above range, light distribution may be improved, and when it is outside the above range, a region where a hot spot is generated may be created. In the plurality of holes 155, the ratio or number of holes that overlap the reflection pattern 123 in a vertical direction may be greater than the ratio or number of holes that do not overlap the reflection pattern 123. Additionally, the total number of the plurality of holes 155 may be greater than the total number of the plurality of reflection patterns 123.

(59) As an example of the invention, the plurality of reflection patterns **123** may overlap each of the holes **155** in a vertical direction. That is, the plurality of reflection patterns **123** may be disposed in regions **Z1** and **Z2** that face the holes **155** one-to-one. Since the size of each of the holes **155** is smaller than the size of each of the reflection patterns **123**, the vertically overlapping holes **155** may overlap with the center or edge portion of the reflection pattern **123**. For example, as shown in FIG. 4, when looking at the view of the first reflective layer **120** from the second reflective layer **150**, the overlapping holes **155** may be located in a region closer to the LEDs **101** and **102** among regions of the reflection pattern **123**. As another example, the overlapping holes **155** may be located in a region of the reflection pattern **123** that is farther from the LEDs **101** and **102**.

Accordingly, light reflected from the reflection pattern **123** having a curved surface may proceed to opposing holes **155**. That is, the holes **155** may be disposed according to at least one or two or more of a center region, an inner edge of the center, or an outer edge of the center based on the center of the reflection pattern **123** according to a direction in which light is reflected or refracted.

(60) Among the holes **155**, fourth holes **H4** overlapping with the first and second LEDs **101** and **102** may be disposed in the fourth region **A4**. The overlap ratio between the fourth holes **H4** and the fourth reflection pattern **R4** in the fourth region **A4** may be lower than the overlap ratio of the second and third regions **A2** and **A3**. Here, within the entire region, at least one hole **155** may overlap with the reflection pattern **123** below it at an overlap ratio of 1% to 100%. When the overlap ratio is outside the above range, dark portion may occur in some regions or light distribution may not be uniform.

(61) As an example of the invention, the arrangement form of the plurality of reflection patterns **123** may be the same as or partially include the same region as the arrangement form of the holes **155**. That is, the distance between the centers of adjacent reflection patterns **123** based on the emission surfaces **11** of the LEDs **101** and **102** may be equal to or partially include the same region as the distance between the centers of adjacent holes **155**. For example, at least one column of the plurality of reflection patterns **123** may have the same arrangement form as at least one column of the holes **155** and may overlap in the vertical direction. Alternatively, when the arrangement form of the plurality of holes **155** includes n columns and the arrangement form of the plurality of reflection patterns **123** includes m columns, m and n are integers of 1 or more and may be the same or different from each other.

(62) Accordingly, since the plurality of reflection patterns **123** face the holes **155** on a one-to-one basis, light emitted from the LEDs **101** and **102** and light reflected by the reflection pattern **123** may be emitted directly or indirectly through the holes **155**. Accordingly, light uniformity of the second reflective layer **150** may be improved. The lighting device **400** has a distribution of lights emitted through the hole **155** when turned on, and when not turned on, the reflective material (e.g., **Al**), which is the surface color of the second reflective layer **150**, may be exposed or visible. When not turned on, the hole size may be small and may not be visually recognized from the outside, that is, at a distance of 30 cm or more. In this embodiment, the light distribution at the time of lighting is provided as in FIG. 27(A), and the front light distribution is 4.5 cd, which satisfies the front light distribution law of the vehicle.

(63) As shown in FIG. 5, the lighting device **400** may include a fifth region **A5**. The fifth region **A5** is disposed on an upper portion of the first and second LEDs **101** and **102**, and may be a region without the holes **155** and covered with the reflective film **153**. The fifth region **A5** may be a light blocking region. That is, by arranging a light blocking region on the first and second LEDs **101** and **102**, it is possible to block light of relatively high intensity from being emitted in front of the LEDs **101** and **102**. The light blocking region may have an emission side area larger than a rear side area based on the LEDs **101** and **102**. The light blocking region may have a hemispherical shape or a circular shape.

(64) As shown in FIG. 6, the LEDs **101** and **103** disposed on opposite sides of the substrate **110** may have their emission surfaces **11** facing toward the center of the lighting device **400**. The two

LEDs **101** and **103** arranged on opposite sides may be arranged to face each other on the same line, or may be arranged to be offset from each other. Accordingly, the LEDs **101** and **103** may radiate light toward the center region. The configuration of the first and second reflective layers **120** and **150** may selectively apply the examples arranged on the emission side of the light source **100** disclosed above. For example, as the distance from the emission surface **11** of the first and second LEDs **101** and **103** increases, the size of the reflection patterns **123** may gradually increase, and at least one hole **155** of the second reflection layer **150** may face an upper portion of each of the reflection patterns **123**.

(65) Among the plurality of LEDs **101** and **102**, the number or size of the plurality of holes **155** disposed adjacent to the exit surface **11** of the first LED **101** in the first direction X may be the same as or different from the number or size of the plurality of holes **155** disposed adjacent to the emission surface **11** of the second LED **103** in a direction opposite to the first direction X.

(66) FIGS. **7**, **8**, and **9** are examples of modified holes **155** of the second reflective layer **150** in the configuration disclosed above, and the size of the holes **155** may be provided the same in all regions. As shown in FIGS. **7** to **9**, the unit density of the first hole H1 in the first region A1 may be smaller than the unit density of the second hole H2 in the second region A2, the unit density of the second holes H2 in the second region A2 may be smaller than the unit density of the third holes H3 in the third region A3. The first to third holes H1, H2, and H3 may be disposed in a larger number as they move away from each of the LEDs **101** and **102**, or an interval between the holes may become narrower as the regions A1, A2, and A3 are farther away. The fourth region A4 may be arranged in any one of the first and second holes H1 and H2 or arranged at intervals.

(67) As shown in FIG. **8**, in the first region A1 or a part thereof, the first hole H1 and the first reflection pattern R1 may overlap one to one in the vertical direction, and in the second region A2 or a part thereof, one or two second holes H2 may overlap each of the second reflection patterns R2 in a vertical direction, and in the third region A3 or a part thereof, one, two, three or four third holes H3 may overlap each of the third reflection patterns R3 in a vertical direction.

(68) As shown in FIG. **9**, when the sizes of the holes **155** in the second reflective layer **150** are the same in the entire region, and the size of the reflection pattern **123** disposed under the second reflective layer **123** is the same in the entire region and is larger than the size of the hole **155**, 50% or more or 70% or more of the holes **155** may face each of the reflection patterns **123** on a one-to-one basis.

(69) The fourth region A4 shown in FIGS. **4** and **7** to **9** may be removed, in which case the third hole H3 and the third reflection pattern R3 of the third region A3 may extend to the rear side of each of the LEDs **101** and **102**. In addition, in the first, second, and third regions A1, A2, and A3, the first hole H1 may be defined as a first hole group, the second hole H2 may be defined as a second hole group, and the third hole H3 may be defined as a third hole group. Also, in the first, second, and third regions A1, A2, and A3, the first reflection pattern R1 may be defined as a first reflection pattern group, the second reflection pattern R2 may be defined as a second reflection pattern group, and the third reflection pattern R3 may be defined as a third reflection pattern group. In addition, each of the holes H1, H2, H3, and H4 may be defined as a unit hole, and each of the reflection patterns R1, R2, R3, and R4 may be defined as a unit reflection pattern.

(70) FIGS. **10** to **12** illustrate the arrangement form of the reflection pattern and the arrangement form of the holes above the reflection pattern disclosed in an embodiment of the invention.

(71) Referring to FIGS. **10** and **3**, the plurality of first reflection patterns R11 or the first group may have a first width w1, and the plurality of first reflection patterns R11 adjacent to each other on the first column L1 (see FIG. **3**) may be spaced apart at a first interval. The first interval between the plurality of first reflection patterns R11 adjacent to each other along the column of the first reflection patterns R11 may be equal to each other. Here, the first column L1 of the first reflection patterns R11 is shown as a straight line, but may have a curved or diagonal shape.

(72) The second reflection pattern R12 or the second group may be located at a greater distance

from the light source **100** than the first reflection pattern **R11**. The second interval between the plurality of second reflection patterns **R12** adjacent to each other along the column of the second reflection patterns **R12** may be equal to each other. Here, the column of the second reflection pattern **R12** are shown as straight lines, but may have a curved or diagonal shape.

(73) The third reflection pattern **R13** or the third group may be located at a greater distance from the light source **100** than the second reflection pattern **R12**. The third interval between the plurality of third reflection patterns **R13** adjacent to each other along the row of the third reflection patterns **R13** may be equal to each other. Here, the column of the third reflection pattern **R13** are shown as straight lines, but may have a curved or diagonal shape.

(74) The fourth reflection pattern **R14** or the fourth group may be located at a greater distance from the light source **100** than the third reflection pattern **R13**. The fourth interval between the plurality of fourth reflection patterns **R14** adjacent to each other along the column of the fourth reflection patterns **R14** may be equal to each other. Here, the column of the fourth reflection pattern **R14** are shown as straight lines, but may have a curved or diagonal shape.

(75) As shown in FIGS. **10** and **11**, when the widths of each of the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **W1**, **W2**, **W3**, and **W4**, with respect to the light source **100**, a region satisfying at least one condition of the relationship of $W1 < W2$, $W2 < W3$, $W3 < W4$, $W1 < W2 < W3$, or $W1 < W2 < W3 < W4$ may be included. As shown in FIGS. **10** and **12**, when the intervals between the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **P1**, **P2**, and **P3** with respect to the light source **100**, a region satisfying at least one of the conditions of $P1 > P2$, $P2 > P3$, or $P1 > P2 > P3$ may be included. As shown in FIG. **11**, when the widths of each of the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **W1**, **W2**, **W3**, and **W4**, with respect to the light source **100**, a region satisfying at least one of the relationships of $W1 < W2$, $W2 < W3$, $W3 < W4$, $W1 < W2 < W3$, or $W1 < W2 < W3 < W4$ and when the intervals between the adjacent first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **P1**, **P2**, and **P3**, a region satisfying at least one of the conditions of $P1 = P2$, $P2 = P3$, or $P1 = P2 = P3$ may be included.

(76) As shown in FIG. **12**, when the widths of each of the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **W1**, **W2**, **W3**, and **W4**, based on the light source **100**, a region satisfying at least one of the conditions of $W1 = W2$, $W2 = W3$, $W3 = W4$, $W1 = W2 = W3$, or $W1 = W2 = W3 = W4$ may include, and when the intervals between the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14** are **P1**, **P2**, and **P3**, a region satisfying at least one of the conditions of $P1 > P2$, $P2 > P3$, or $P1 > P2 > P3$ may include.

(77) At least a portion of each of the first to fourth holes **H11**, **H12**, **H13**, and **H14** may be arranged to overlap in the vertical direction on an upper portion of each of the first to fourth reflection patterns **R11**, **R12**, **R13**, and **R14**. Accordingly, the first to fourth holes **H11**, **H12**, **H13**, and **H14** have a width smaller than the width **W1**, **W2**, **W3**, and **W4** of the reflection patterns **R11**, **R12**, **R13**, and **R14**, and have the same width (See FIG. **12**) or may face each other with a width (See FIGS. **10** and **11**) that becomes larger as the distance from the light source **100** increases.

(78) As shown in FIGS. **13** to **15**, the first reflective layer **120** may include a polygonal reflection pattern **123** on the first reflective film **121**. The reflection pattern **123** may be spaced apart from the periphery of the emission side of the LEDs **101** and **102**, and may gradually become larger as it moves away from each LED **101** and **102**, or may be provided in the same size. Here, the minimum separation distance **D5** between the reflection pattern **123** and the emission side of the LEDs **101** and **102** is spaced apart in a range of 10% or more, for example, in the range of 10% to 50% or 20% to 40% of the distance **X1** between the LEDs **101** and **102**. The minimum separation distance **D5** may be spaced so that hot spots are suppressed or the light distribution is 90% or more uniform through the second reflective layer **150** due to the reflection pattern **123**.

(79) The first reflective layer **120** may include, for example, a base reflective layer **122**, a light transmitting layer **124** disposed on the base reflective layer **122**, and a pattern layer **126** disposed between the base reflective layer **122** and the light transmitting layer **124**. The base reflective layer

122 includes a material that reflects light, such as a metal or non-metallic material. When it is a metal, a metal layer such as Ag may be disposed, and when it is a non-metallic material, it may include a plastic material. The light transmitting layer **124** is a transparent film and may include at least one of a resin material such as silicone or epoxy, or a transparent plastic material such as polyethylene terephthalate (PET), polyvinyl chloride (PVC), or urethane.

(80) The pattern layer **126** may adhere between the base reflective layer **122** and the light transmitting layer **124** and may include a plurality of reflection patterns **R5** therein. The pattern layer **126** may include a metal oxide, for example, TiO_2 , CaCO_3 , BaSO_4 , Al_2O_3 , or may be printed using an ink containing at least one of silicon and polysilicon (PS). The pattern layer **126** may be formed of, for example, a material in which a metal oxide is added to silicon or epoxy.

(81) The density of the reflection pattern **R5** may gradually increase as the distance from the light source **100** increases. The unit structure of the reflection pattern **R5** may have a polygonal shape, a circular shape, an elliptical shape, a regular shape, or an irregular shape, and may be formed in two or three dimensions. The unit structure of the reflection pattern **R5** may be formed in a densely packed hexagonal shape with an air gap therein. By reflecting light by the pattern layer **126** and the base reflective layer **122**, the number of light sources **100** may be reduced and light uniformity in the entire region may be improved. Since the first reflective layer **120** is disposed on the bottom of the resin layer **130**, the thickness of the resin layer **130** may be reduced.

(82) As shown in FIG. **13**, the size of the plurality of reflection patterns **R5** can become larger as the distance from the LEDs **101** and **102** increases, and the arrangement form of the holes **155** may include a region that increases as the distance from the emission side of the LEDs **101** and **102** increases or/and a region where the density of unit hole increases. As shown in FIG. **14**, the lighting device may include a region where at least one or a plurality of holes **155** overlap in the vertical direction on a plurality of reflection patterns **R5**.

(83) In the lighting device according to the embodiment of FIGS. **13** to **15**, some holes (holes adjacent to the LED) do not overlap with the reflection pattern, and the light distribution when turned on is obtained as shown in FIG. **27(B)**, and the front light distribution is 3.8 cd, which satisfies the vehicle's front light distribution regulations.

(84) FIG. **16** is a modified example of the invention, showing a structure in which a light blocking portion **163** is disposed partially between the resin layer **130** and the second reflective layer **150**. The light blocking portion **163** is disposed higher than the upper surface of the resin layer **130**. The light blocking portion **163** on the LEDs **101** and **102** is 50% or more of the upper surface area of the LEDs **101** and **102**, or is in the range of 50% to 200% of the upper surface area of the LEDs **101** and **102**. The light blocking portion **163** may be a region printed with white material. The light blocking portion **163** is printed in a single layer or multiple layers using a reflective ink containing any one of, for example, TiO_2 , Al_2O_3 , CaCO_3 , BaSO_4 , and Silicon. The light blocking portion **163** reflects light emitted through the emission surface **11** of the LEDs **101** and **102**, thereby reducing the occurrence of hot spots. The light blocking portion **163** may print a light blocking pattern using light blocking ink. The light blocking portion **163** may be formed by printing on the lower surface of the second reflective layer **150**. The light blocking portion **163** is made of a material that does not 100% block incident light, may have a transmittance lower than a reflectance, and may perform the function of blocking and diffusing light. The light blocking portion **163** may have the same thickness or may have different thicknesses depending on the region. For example, the thickness of the light blocking portion **163** may be thickest in the center region and thinner in the edge region than the center region. The thickness of the light blocking portion **163** increases in proportion to the incident light intensity.

(85) The light blocking portion **163** may reduce the problem of the LEDs **101** and **102** being visible from the outside and reduce hot spots on the region of the LEDs **101** and **102**, thereby providing uniform light distribution throughout the entire region. The surrounding region of the light blocking

portion **163** is disposed with an adhesive layer **161**, which is formed of a transparent resin material and may be adhered between the resin layer **130** and the transparent film **151** of the second reflective layer **150**.

(86) FIG. **17** is a modified example of the second reflective layer, in which a second reflective film **153** having a hole **155** on the resin layer **130** and a transparent film **151** may be disposed on the second reflective film **153**. The second reflective film **153** may be adhered to the upper surface of the resin layer **130**. A through hole may not be formed in the transparent film **151** on a region facing the hole **155**. As another example, a through hole (not shown) may be formed in the transparent film **151** on a region facing the hole **155**. Accordingly, diffused light may be emitted through the hole **155** or through hole through the transparent film **151**.

(87) As shown in FIGS. **18** and **19**, the lighting device may be provided as an individual light emitting unit with one column or one LED. These individual light emitting units may be arranged in plural numbers in the row direction, or may be provided as units in which a plurality of LEDs is arranged in the row direction.

(88) As shown in FIG. **18**, the lighting device **400** may be provided in a structure in which the thickness of the resin layer **130** gradually becomes thinner as the distance from the LED **101** increases. That is, the thickness of the resin layer **130** disposed on one side (Adjacent region to an LED) of the substrate **110** may be the thickest, and the thickness of the resin layer **130** disposed on the other side (opposite to one side) of the substrate **110** may be the thinnest. At this time, the size of the reflection pattern **123** may become larger as the distance from the LED **101** increases, or may be provided in the same size. Here, the thinnest thickness of the resin layer **130** is less than 1 times the thickest thickness, for example, in the range of 0.3 to 0.9 times, and when it is in this range, light distribution may be uniformly adjusted in the form of a reflection pattern and an arrangement form of holes.

(89) As shown in FIG. **19**, the lighting device **400** may be provided in a structure in which the thickness of the resin layer **130** gradually becomes thicker as the distance from the LED **101** increases. That is, the thickness of the resin layer **130** disposed on one side (Adjacent region to an LED) of the substrate **110** may be the thinnest, and the thickness of the resin layer **130** disposed on the other side (opposite to one side) of the substrate **110** may be the thickest. At this time, the size of the reflection pattern **123** may become larger as the distance from the LED **101** increases, or may be provided in the same size. Here, the thickest thickness of the resin layer **130** is 3 times or less the thinnest thickness, for example, in the range of 1.1 to 3 times, and when is in this range, light distribution may be uniformly adjusted in the form of a reflection pattern and an arrangement form of holes. As shown in FIGS. **18** and **19**, at least one, at least one column, or two or more of the holes **155** of the second reflective layer **150** may overlap the reflection pattern **123** in the vertical direction. The arrangement form of the reflection pattern **123** and the hole **155** may be selected from the embodiments or modified examples disclosed above.

(90) Referring to FIG. **20**, the light source **105** may be disposed to face one side of the resin layer **130**. The light source **105** is disposed one or more on the substrate **115** and may face one side of the resin layer **130**. Accordingly, since the light source **105** is disposed externally, replacement of the light source **105** may be easy. Additionally, the first reflective layer **120** may be disposed on the support layer **110A** under a lower portion of the resin layer **130**, and the support layer **110A** may be provided as a member without a circuit pattern. The light source **105** may be disposed on one side of the resin layer **130**, or may be disposed on one side and the other side, respectively. In the lighting device **400**, the arrangement form of the reflection pattern **123** of the first reflective layer **120** and the holes **155** of the second reflective layer **150** may be selected from among the embodiments or modified examples disclosed above.

(91) As shown in FIG. **21**, the second reflective layer **150** may include an extension portion **150A** extending to the side of the resin layer **130**. The extension portion **150A** includes a transparent film **151** and a second reflective film **153**, and holes **155** may be disposed in the second reflective film

153. The holes **155** of the extension portion **150A** may not overlap the reflection pattern **123** in the horizontal or vertical direction. Holes **155** may not be formed in the extension portion **150A**.

(92) As shown in FIG. **22**, the plurality of LEDs **101** and **102** may be arranged in the same column or different columns, or may be arranged in the same row or different rows. As shown in FIG. **23**, at least one or more other LEDs **104** and **106** may be disposed outside between adjacent LEDs **101** and **102**.

(93) As shown in FIG. **24**, the lighting device may include line holes **155A** having a long length in the column direction where the above-described reflection patterns are disposed or in the column direction of the LED. The length of the line hole **155A** may be 10% or more of the width (Y-direction length) of the second reflective layer **150**, for example, in a range of 50% to 90%. When the length of the line hole **155A** is greater than the above range, the light distribution outside the line may have a different distribution than the center of the line. Two or more-line holes **155A** may be arranged along each line in the range of 10% to 30% of the width (Y-direction length) of the second reflective layer **150**.

(94) Each of the line holes **155A** may be arranged along the column of the reflection pattern **123** disclosed above. The width (length in the X-direction) of each of the line holes **155A** may become wider as the distance from the LEDs **101** and **102** increases, or may include the same region.

(95) Light distribution at 45 degrees to the left, front, and 45 degrees to the right when turned on and not turned on in the comparative example and the lighting device of the invention will be described. A lighting device will be described as an example in which red light is emitted. As a comparative example, when the light is turned on, red light is emitted in a uniform distribution at 45 degrees to the left, front and 45 degrees to the right, and when the light is not turned on, the left/right drawings may appear the same at 45 degrees to the left, front, and 45 degrees to the right. On the other hand, in the invention, when the light is turned on, the light distribution is uniformly distributed by the holes disclosed above at 45 degrees to the left, front, and 45 degrees to the right, and when the light is not turned on, the holes are not exposed on the external surface images at 45 degrees to the left and right and the external surface at the front, and the image from the front is exposed as another image, such as a metal (Al) image. Accordingly, an image when the light is not turned on may be provided differently according to an angle viewed by the second reflective layer **150**, light distribution when the light is turned on may be improved, and the external image when the light is not turned on may be exposed as a surface material of the reflective layer.

(96) When the lighting device **400** is turned on, hole-shaped light extracted through the second reflective layer **150** may form a light distribution, and when not turned on, the surface (e.g., metal surface) of the second reflective layer **150** may be visually recognized, and the holes may be small in size and may not be substantially visually recognized from the outside. Accordingly, when not turned on, a surface image made of the material of the second reflective layer may be improved.

(97) The lighting device **400** according to an embodiment of the invention may surround a region other than the lighting region with a bracket. The bracket may be placed around the lower portion, side walls, and upper portion of the lighting device **400**. The lighting device **400** may emit light emitted from the lighting module toward a specific direction. The lighting device **400** may be applied to various lamp devices that require lighting, such as vehicle lamps, household lighting devices, and industrial lighting devices. For example, in the case of lighting modules applied to vehicle lamps, it may be applied to head lamps, side lights, side mirror lights, fog lights, tail lamps, turn signal lamps, back up lamps, stop lamps, daytime running lights, vehicle interior lighting, door scarf, rear combination lamp, backup lamp, etc.

(98) FIG. **25** is a plan view of a vehicle to which a vehicle lamp is applied with a lighting device according to an embodiment, and FIG. **26** is a diagram showing an example of a tail light of a vehicle to which a lighting device according to an embodiment is applied.

(99) Referring to FIGS. **25** and **26**, in a moving object or vehicle **900**, the front lamp **850** may include one or more lighting devices, and the operating timing of these lighting devices is

individually controlled to function as a typical headlamp as well as, when the driver opens the vehicle door, additional functions such as welcome lights or celebration effects may be provided. The lamp may be applied to daytime running lights, high beams, low beams, fog lights, or turn signal lights.

(100) In the vehicle **900**, the tail lights **800** may be arranged as a plurality of lamp units **810**, **812**, **814**, and **816** supported by a housing. For example, the lamp units **810**, **812**, **814**, and **816** may include a first lamp unit **810** disposed on one side, a second lamp unit **812** disposed around the outer periphery of the first lamp unit **810**, and third and fourth lamp units **814** and **816** respectively disposed inside the second lamp unit **812**. The tail light **800** may include the lighting device **400** disclosed in the embodiment disposed inside the third and fourth lamp units **814** and **816**, and the lighting device **400** may function as a complex hidden lamp with improved lighting and surface images.

(101) As shown in FIG. **26(A)**, although the holes **155** are shown to be visible when not turned on, the second reflective film of the second reflective layer is exposed and light may be irradiated through the holes **155** as shown in FIG. **26(B)**. The color of the light emitted through the holes **155** of the lighting device **400** is different from the color of the vehicle when not turned on, and the surface image of the second reflective layer of the lighting device **400** is the same as the color of the vehicle or has a metal color (aluminum color). Accordingly, it may be provided as a hidden lamp. As another example, the first to fourth lamp units **810**, **812**, **814**, and **816** may selectively apply the lighting device disclosed in the embodiment, and a red lens cover or a white lens cover may be provided on the outside of the lighting device for the lighting characteristics of the lamp units **810**, **812**, **814**, and **816**. The lighting device disclosed in the embodiment applied to the lamp units **810**, **812**, **814**, and **816** may irradiate surface light at a higher luminous intensity in a specific direction.

(102) The first and second lamp units **810** and **812** may be provided in at least one of a curved shape, a straight shape, an angled shape, an inclined shape, or a flat shape, or a mixed structure thereof. The first and second lamp units **810** and **812** may be arranged one or more in each taillight. The first lamp unit **810** may be provided as a tail light, the second lamp unit **812** may be provided as a brake light, and the third lamp unit **814** may be provided as a reverse light. The fourth lamp unit **816** may be provided as a turn signal lamp. The tail light **800** may provide at least one of a sidelight, a brake light, and a turn signal light using the lighting device disclosed in the embodiment of the invention.

(103) Features, structures, effects, etc. described in the above embodiments are included in at least one embodiment of the invention, and are not necessarily limited to only one embodiment. Furthermore, features, structures, effects, etc. illustrated in each embodiment can be combined or modified for other embodiments by those of ordinary skill in the art to which the embodiments belong. Accordingly, the contents related to such combinations and modifications should be interpreted as being included in the scope of the invention.

(104) In addition, although the embodiments have been mainly described above, this is only an example and does not limit the present invention, and one of ordinary skill in the field to which the present invention belongs will appreciate that various modifications and applications not illustrated above may be possible without departing from the essential characteristics of the present embodiment. For example, each component specifically shown in the embodiment can be implemented by modification. And differences related to such modifications and applications should be construed as being included in the scope of the invention defined in the appended claims.

Claims

1. A lighting device comprising: a substrate; a first reflective layer disposed on the substrate and having a plurality of reflection patterns; a light source disposed on the substrate; a resin layer

disposed on the first reflective layer; and a second reflective layer disposed on the resin layer and having a plurality of holes, wherein an arrangement form of the plurality of holes is a same as an arrangement form of the plurality of reflection patterns, wherein the plurality of reflection patterns and the plurality of holes overlap in one region in a direction perpendicular to an upper surface of the substrate, wherein a size of at least one of the holes is smaller than a size of at least one of the reflection patterns in the overlapping region, and wherein the plurality of holes include a region where a size of the holes increases as a distance from the light source in an emission direction of the light source increases.

2. The lighting device of claim 1, wherein the arrangement form of the plurality of holes includes n columns, wherein the arrangement form of the plurality of reflection patterns includes m columns, wherein m and n are integers of one or more and are a same or different from each other.

3. The lighting device of claim 1, wherein the plurality of holes includes a first hole and a second hole in a first column among n columns, and a first hole and a second hole in a second column among the n columns, wherein an interval between the first hole and the second hole in the first column is equal to or smaller than an interval between the first hole in the first column and the first hole in the second column, wherein the first column is disposed closer to an emission surface of the light source than the second column.

4. The lighting device of claim 1, wherein the first reflective layer includes a first reflective film, wherein the plurality of reflection patterns is disposed on the first reflective film, wherein the plurality of reflection patterns is covered with a lower portion of the resin layer.

5. The lighting device of claim 1, wherein the second reflective layer includes a transparent film and a second reflective film disposed on the transparent film, wherein the plurality of holes is penetrated through the second reflective film, wherein the second reflective film includes a metal film having the plurality of holes.

6. The lighting device of claim 1, wherein the plurality of reflection patterns includes a region where a size of the reflection patterns increases as a distance from the light source in an emission direction of the light source increases, wherein a total area of the plurality of holes is smaller than a total area of a reflective region of the second reflective layer.

7. The lighting device of claim 1, wherein the light source includes a plurality of LEDs, wherein the plurality of LEDs is arranged to emit light in a first direction.

8. The lighting device of claim 1, wherein the light source includes a plurality of LEDs, wherein the plurality of LEDs includes a first LED to emit light in a first direction, and a second LED to light a second direction opposite to the first direction, wherein a number or size of the plurality of holes disposed adjacent to an emission surface of the first LED is different from a number or size of the plurality of holes disposed adjacent to an emission surface of the second LED.

9. The lighting device of claim 1, wherein a thickness of the resin layer is 2.7 mm or less, wherein the lighting device emits red light.

10. The lighting device of claim 1, wherein an overlap ratio between the plurality of holes and the plurality of reflective patterns ranges from 60% to 98% in the direction perpendicular to the upper surface of the substrate.

11. A lighting device comprising: a substrate; a first reflective layer disposed on the substrate and having a plurality of reflection patterns; a light source disposed on the substrate; a resin layer disposed on the first reflective layer; a second reflective layer disposed on the resin layer and having a plurality of holes, wherein the plurality of holes includes a region where a number of holes per unit area increases as a distance from the light source in an emission direction of the light source increases, wherein the plurality of reflection patterns and the plurality of holes overlap in one region in a direction perpendicular to an upper surface of the substrate, and wherein a size of at least one of the holes is smaller than a size of at least one of the reflection patterns in the overlapping region.

12. The lighting device of claim 11, wherein each of the plurality of holes is a same size, wherein

- each of the plurality of reflection patterns is a same size, wherein the plurality of reflection patterns includes a region where a number of reflection patterns per unit area increases as a distance from the light source in an emission direction of the light source increases.
13. The lighting device of claim 11, wherein each of the plurality of holes is a same size, wherein the plurality of reflection patterns includes a region where a size of the reflection patterns increases as a distance from the light source in an emission direction of the light source increases.
14. The lighting device of claim 11, wherein the first reflective layer includes a first reflective film, wherein the plurality of reflective patterns is disposed on the first reflective film, wherein the plurality of reflective patterns is covered with a lower portion of the resin layer.
15. The lighting device of claim 14, wherein the second reflective layer includes a transparent film and a second reflective film disposed on the transparent film, wherein the plurality of holes is penetrated through the second reflective film.
16. The lighting device of claim 15, wherein the second reflective film includes a metal film.
17. A lighting device comprising: a first reflective layer having a plurality of reflection patterns; a second reflective layer having a plurality of holes; a resin layer disposed between the first reflective layer and the second reflective layer; and a light source that provides light to an inside or outside of the resin layer, wherein the second reflective layer includes a region in which at least one of a size or an interval of the holes changes as a distance from the light source in an emission direction of the light source increases, wherein the second reflective layer includes a reflective film having the plurality of holes on the resin layer, wherein the plurality of holes penetrates from an upper surface of the reflective film toward the resin layer, wherein at least one or at least one column of the plurality of holes overlaps at least one of the reflection patterns in a vertical direction, wherein the reflective film is made of metal, wherein the size of at least one of the holes is 20 times or less than a wavelength emitted from the light source, wherein the plurality of holes has an overlap ratio of 50% or more with the plurality of reflection patterns, and wherein at least one of the plurality of holes has an overlap ratio with vertically overlapping at least one of the reflection patterns in a range of 1% to 100%.
18. The lighting device of claim 17, wherein a thickness of the resin layer is 2.7 mm or less, wherein the lighting device emits red light.
-