

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416831
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Long; Chunping et al.

Backlight structure and display device

Abstract

A backlight structure and a display device are provided. The backlight structure includes a barrier wall pattern and light-emitting units. The barrier wall pattern includes openings and a barrier wall surrounding the openings, the openings are configured to define light regions; and the light-emitting units are distributed in the light regions. The backlight structure includes a central region and an edge region, each light region is provided with at least three light-emitting units, centers of M light-emitting units, closest to vertex angles of the light region are sequentially connected to form an M-sided polygon, and a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, and an included angle between each of the first direction and the second direction and each side of the M-sided polygon is greater than 0 degrees.

Inventors:	Long; Chunping (Beijing, CN), Xu; Jian (Beijing, CN), Zhu; Heling (Beijing, CN)
Applicant:	BEIJING BOE TECHNOLOGY DEVELOPMENT CO., LTD. (Beijing, CN); BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)
Family ID:	1000008818817
Assignee:	BEIJING BOE TECHNOLOGY DEVELOPMENT CO., LTD. (Beijing, CN); BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)
Appl. No.:	18/850525
Filed (or PCT Filed):	September 19, 2023
PCT No.:	PCT/CN2023/119785
PCT Pub. No.:	WO2024/061232
PCT Pub. Date:	March 28, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250216717 A1	Jul. 03, 2025

Foreign Application Priority Data

CN202211146615.6Sep. 21, 2022

Publication Classification

Int. Cl.: G02F1/00 (20060101); G02F1/1335 (20060101); G02F1/13357 (20060101)

U.S. Cl.:

CPCG02F1/133603 (20130101); G02F1/133607 (20210101);

Field of Classification Search

USPC:None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9666105	12/2016	Cox et al.	N/A	N/A
2007/0152135	12/2006	Watanabe	250/208.1	G02F 1/133603
2007/0159849	12/2006	Sakai	362/612	G02F 1/133605
2010/0231804	12/2009	Hisakawa	N/A	N/A
2014/0334144	12/2013	Matsuura	362/231	G02F 1/133603
2015/0359067	12/2014	Kurita	315/151	G02F 1/133603
2018/0128458	12/2017	Fukasawa	N/A	F21K 9/64
2019/0146278	12/2018	Son	349/64	G02F 1/133606
2021/0088713	12/2020	Chen	N/A	G02B 6/0068
2021/0233969	12/2020	Sun	N/A	H10K 59/122
2021/0404628	12/2020	Jin	N/A	G02F 1/133607
2022/0066266	12/2021	Ota	N/A	F21V 9/30
2022/0113465	12/2021	Chen et al.	N/A	N/A
2024/0219771	12/2023	Wang	N/A	G02F 1/133606

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106875879	12/2016	CN	N/A
108563068	12/2017	CN	N/A
108572481	12/2017	CN	N/A
108803136	12/2017	CN	N/A
109116631	12/2018	CN	N/A
109166906	12/2018	CN	N/A
106097900	12/2018	CN	N/A
110275349	12/2018	CN	N/A
113972196	12/2021	CN	N/A
114005850	12/2021	CN	N/A
114373854	12/2021	CN	N/A
115047678	12/2021	CN	N/A
100819657	12/2007	KR	N/A
M405521	12/2010	TW	N/A

201231860	12/2011	TW	N/A
1518952	12/2015	TW	N/A
1660018	12/2018	TW	N/A
1696018	12/2019	TW	N/A
1750466	12/2020	TW	N/A
202209710	12/2021	TW	N/A
1771680	12/2021	TW	N/A
2021/051347	12/2020	WO	N/A

OTHER PUBLICATIONS

The First Chinese Office Action; dated Nov. 1, 2022; Appln. No. 202211146615.6. cited by applicant
The First Taiwanese Office Action: Appln. No. 112125237; dated May 30, 2024. cited by applicant
The International Search Report and Written Opinion both mailed Nov. 21, 2023;
PCT/CN2023/119785. cited by applicant
The Extended European Search Report dated Jun. 4, 2025; Appln. No. 23867519.3. cited by applicant

Primary Examiner: Sufleta, II; Gerald J

Background/Summary

(1) The present application is a National Stage of International Application No. PCT/CN2023/119785, filed Sep. 19, 2023, which claims priority to and the benefit of Chinese Patent Application No. 202211146615.6, filed Sep. 21, 2022, the entireties of which are hereby incorporated herein by reference.

TECHNICAL FIELD

(2) Embodiments of the present disclosure relate to a backlight structure and a display device.

BACKGROUND

(3) Display devices used widely at present include thin-film transistor liquid crystal display (TFT-LCD) devices, which have the advantages of long life, high display brightness, high contrast, and wide color gamut.

(4) Mini light-emitting diodes (Mini LEDs) can be used as backlights of the thin film transistor liquid crystal display devices. When a Mini LED used as a backlight is combined with a conventional liquid crystal display panel, by controlling brightness of the Mini LED to enable it to match gray scale presented by the display panel, a liquid crystal display device may have a high contrast ratio comparable to that of an organic light-emitting diode display device.

SUMMARY

(5) Embodiments of the present disclosure provide a backlight structure and a display device.

(6) An embodiment of the present disclosure provides a backlight structure, which includes a substrate and a barrier wall pattern and a plurality of light-emitting units located on the substrate. The barrier wall pattern includes a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings is configured to define a plurality of light regions, and the first direction intersects the second direction; and the plurality of light-emitting units is distributed in the plurality of light regions. The substrate includes a central region and an edge region surrounding the central region, each light region at least in the central region is provided with at least three light-emitting units, centers of M light-emitting units, closest to vertex angles of the light region, among the at least three light-emitting units are sequentially connected to form an M-sided polygon, and a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, and an included angle between the first direction and each side of the M-sided polygon and an included angle between the second direction and each side of the M-sided polygon are both greater than 0 degrees.

- (7) For example, according to an embodiment of the present disclosure, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch of the light region to a side length of the M-sided polygon is 1.7 to 2.3.
- (8) For example, according to an embodiment of the present disclosure, the pitch of the light region is P, each of at least some of the light regions includes N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N, and $L_{\text{sub},i}$, P, and N satisfy: $8.5 \geq P \times (1/L_{\text{sub},1} + 1/L_{\text{sub},2} + \dots + 1/L_{\text{sub},N}) \geq 6.3$.
- (9) For example, according to an embodiment of the present disclosure, a light intensity distribution I of the light-emitting unit satisfies: $I = I_{\text{sub},0} \cos m\alpha$, $I_{\text{sub},0}$ is the light intensity distribution along a direction of a normal perpendicular to a light exit surface of the light-emitting unit, α is an included angle between a light-emitting direction of the light-emitting unit and the normal, $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub},1/2})$, $\alpha_{\text{sub},1/2}$ is an included angle between the light-emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and a light ray emitted by the light-emitting unit has an optical path of h in the normal direction; and each of the at least some of the light regions includes N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N, and $L_{\text{sub},i}$, h, and N satisfy:
 $0.5 \geq \{\cos m \times [(\pi/2) - (h/L_{\text{sub},1})] + \cos m \times [(\pi/2) - (h/L_{\text{sub},2})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub},N})]\} \geq 0.23$.
- (10) For example, according to an embodiment of the present disclosure, a ratio of a light intensity at an edge position of the light region to a light intensity at a center position of the light region is not less than 0.5.
- (11) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions includes at least four light-emitting units, the at least four light-emitting units are arranged to form the M-sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M-sided polygon is 12 to 18 degrees.
- (12) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions is in the shape of a first square, each of the at least some of the light regions includes at least four light-emitting units, the M-sided polygon is a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 12 to 18 degrees.
- (13) For example, according to an embodiment of the present disclosure, at least some of the light regions are in the shape of a rectangle, and two adjacent sides of the rectangle extend along the first direction and the second direction, respectively.
- (14) For example, according to an embodiment of the present disclosure, the light-emitting units disposed in each light region are electrically connected, and the barrier wall includes a shading material.
- (15) For example, according to an embodiment of the present disclosure, the light-emitting unit includes a light-emitting diode chip and an encapsulation structure configured to encapsulate the light-emitting diode chip, and there is a spacing between encapsulation structures of adjacent light-emitting units.
- (16) For example, according to an embodiment of the present disclosure, a maximum size of the light-emitting unit in a direction parallel to the substrate is not greater than 500 μm .
- (17) For example, according to an embodiment of the present disclosure, the at least four light-emitting units include four light-emitting units, and centers of the four light-emitting units are sequentially connected to form the second square.
- (18) For example, according to an embodiment of the present disclosure, the at least four light-emitting units include five light-emitting units, and centers of four light-emitting units, located at outermost edges, of the five light-emitting units are sequentially connected to form the second square.
- (19) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions includes three light-emitting units, centers of the three light-emitting units are sequentially connected to form a triangle, and an included angle between one of the first direction and the second direction and one side of the triangle is less than 5 degrees.
- (20) For example, according to an embodiment of the present disclosure, a thickness of the barrier wall is greater than a height of the light-emitting unit in a direction perpendicular to the substrate.
- (21) For example, according to an embodiment of the present disclosure, the thickness of the barrier

wall is 200 to 400 μm and the height of the light-emitting unit is 50 to 100 μm .

(22) For example, according to an embodiment of the present disclosure, the thickness of the barrier wall is 250 to 270 μm , a width of the barrier wall is 350 to 500 μm , and the height of the light-emitting unit is 80 to 100 μm .

(23) For example, according to an embodiment of the present disclosure, the backlight structure further includes: a flat adhesive, located between the barrier wall and each light-emitting unit, and between two adjacent light-emitting units. A thickness of the flat adhesive is not less than the height of the light-emitting unit and is less than the thickness of the barrier wall, an orthographic projection, on the substrate, of a surface of one side of the flat adhesive close to the substrate is completely located in an orthographic projection, on the substrate, of a surface of one side of the flat adhesive away from the substrate.

(24) For example, according to an embodiment of the present disclosure, a cross section of the flat adhesive intercepted by a plane where a line connecting centers of the two adjacent light-emitting units is located is in the shape of a trapezoid, a length of a first base side of the trapezoid away from the substrate is greater than a length of a second base side of the trapezoid close to the substrate, a distance between endpoints, close to each other, of an orthographic projection of the first base side and an orthographic projection of the second base side on the substrate is 17 to 32 μm , and the plane is perpendicular to the substrate.

(25) For example, according to an embodiment of the present disclosure, the substrate is provided with thermally conductive adhesive on a side away from the light-emitting units, and the thermally conductive adhesive is provided with at least one hole.

(26) For example, according to an embodiment of the present disclosure, the backlight structure further includes: a light diffusion structure, located on a side of the light-emitting unit away from the substrate. The light diffusion structure includes at least one layer of a diffusion film, and the diffusion film has a thickness of 0.05 to 0.2 mm.

(27) For example, according to an embodiment of the present disclosure, the backlight structure further includes: a color conversion structure, located on a side of the light diffusion structure away from the light-emitting units. The color conversion structure includes a color conversion film configured to convert first color light into second color light, the first color light includes blue light, and the second color light includes at least one of red light and green light.

(28) For example, according to an embodiment of the present disclosure, the color conversion structure further includes a prism located on a side of the color conversion film away from the light-emitting units.

(29) For example, according to an embodiment of the present disclosure, the backlight structure further includes: a prism structure located on a side of the color conversion structure away from the light-emitting units. The prism structure includes at least one prism layer, and the prism layer has a thickness of 0.05 to 0.2 mm.

(30) Another embodiment of the present disclosure provides a backlight structure, which includes a substrate and a barrier wall pattern and a plurality of light-emitting units located on the substrate. The barrier wall pattern includes a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings is configured to define a plurality of light regions, and the first direction intersects the second direction; and the plurality of light-emitting units is distributed in the plurality of light regions. At least three light-emitting units are disposed in each of at least some light regions, centers of M light-emitting units of the at least three light-emitting units closest to vertex angles of the light region are sequentially connected to form an M-sided polygon, a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch of the light region to a side length of the M-sided polygon is 1.7 to 2.3; and at least one side of the M-sided polygon is parallel to at least one of the first direction and the second direction.

(31) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions includes N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-

emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N , and $L_{\text{sub},i}$, P , and N satisfy: $8.5 \geq P \times (1/L_{\text{sub},1} + 1/L_{\text{sub},2} + \dots + 1/L_{\text{sub},N}) \geq 6.3$.

(32) For example, according to an embodiment of the present disclosure, a light intensity distribution I of the light-emitting unit satisfies: $I = I_{\text{sub},0} \cos m\alpha$, $I_{\text{sub},0}$ is the light intensity distribution along a direction of a normal perpendicular to a light exit surface of the light-emitting unit, α is an included angle between a light-emitting direction of the light-emitting unit and the normal, $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub},1/2})$, $\alpha_{\text{sub},1/2}$ is an included angle between the light-emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and a light ray emitted by the light-emitting unit has an optical path of h in the normal direction; and each of the at least some of the light regions includes N light-emitting units, where $N \geq M$, a distance from a center of an i -th light-emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N , and $L_{\text{sub},i}$, h , and N satisfy:

$0.5 \geq (\cos m \times [(\pi/2) - (h/L_{\text{sub},1})] + \cos m \times [(\pi/2) - (h/L_{\text{sub},2})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub},N})]) \geq 0.23$.

(33) For example, according to an embodiment of the present disclosure, a ratio of a light intensity at an edge position of the light region to a light intensity at a center position of the light region is not less than 0.5.

(34) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions includes at least four light-emitting units, the at least four light-emitting units are arranged to form the M -sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M -sided polygon is 0 degrees.

(35) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions is in the shape of a first square, each of the at least some of the light regions includes at least four light-emitting units, the M -sided polygon is a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 0 degrees.

(36) For example, according to an embodiment of the present disclosure, the at least four light-emitting units include four light-emitting units, and centers of the four light-emitting units are sequentially connected to form the second square.

(37) For example, according to an embodiment of the present disclosure, each of the at least some of the light regions includes three light-emitting units, centers of the three light-emitting units are sequentially connected to form a triangle, and one side of the triangle extends in either the first direction or the second direction.

(38) For example, according to an embodiment of the present disclosure, the light-emitting units disposed in each light region are electrically connected, and the barrier wall includes a shading material.

(39) For example, according to an embodiment of the present disclosure, the light-emitting unit includes a light-emitting diode chip and an encapsulation structure configured to encapsulate the light-emitting diode chip, and there is a spacing between encapsulation structures of adjacent light-emitting units.

(40) For example, according to an embodiment of the present disclosure, a maximum size of the light-emitting unit in a direction parallel to the substrate is not greater than 500 μm .

(41) For example, according to an embodiment of the present disclosure, at least some of the light regions are in the shape of a rectangle, and two adjacent sides of the rectangle extend along the first direction and the second direction, respectively.

(42) For example, according to an embodiment of the present disclosure, a thickness of the barrier wall is 250 to 270 μm , a width of the barrier wall is 350 to 500 μm , and a height of the light-emitting unit is 80 to 100 μm .

(43) For example, according to an embodiment of the present disclosure, the backlight structure further includes: a flat adhesive, located between the barrier wall and each light-emitting unit, and between two adjacent light-emitting units. A thickness of the flat adhesive is not less than the height of the light-emitting unit and is less than the thickness of the barrier wall, an orthographic projection, on the substrate, of a surface of one side of the flat adhesive close to the substrate is completely located in an orthographic projection, on the substrate, of a surface of one side of the flat adhesive away from the substrate.

(44) For example, according to an embodiment of the present disclosure, a cross section of the flat

adhesive intercepted by a plane where a line connecting centers of the two adjacent light-emitting units is located is in the shape of a trapezoid, a length of a first base side of the trapezoid away from the substrate is greater than a length of a second base side of the trapezoid close to the substrate, a distance between endpoints, close to each other, of an orthographic projection of the first base side and an orthographic projection of the second base side on the substrate is 17 to 32 μm , and the plane is perpendicular to the substrate.

(45) Another embodiment of the present disclosure provides a display device, which includes: a display panel, and a backlight structure as mentioned above. The display panel is located on a light exit side of the backlight structure.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) In order to clearly illustrate the technical solution of the embodiments of the present disclosure, the drawings of the embodiments will be briefly described in the following; it is obvious that the described drawings are only related to some embodiments of the present disclosure and thus are not limitative of the present disclosure.

(2) FIG. 1 is a schematic diagram of a partial planar structure of a backlight structure according to an example of an embodiment of the present disclosure.

(3) FIG. 2A and FIG. 2B are schematic diagrams of light-emitting units in different examples.

(4) FIG. 3A is a schematic diagram of equivalent luminescence of a Lambertian emitter.

(5) FIG. 3B is a schematic diagram of a light-emitting angle and light intensity distribution of a Lambertian emitter.

(6) FIG. 4 is a schematic diagram of a partial cross-sectional structure cut along line AA' shown in FIG. 1 according to an example of an embodiment of the present disclosure.

(7) FIG. 5 is a schematic diagram of light-emitting units in one of light regions shown in FIG. 1.

(8) FIGS. 6 to 9 are schematic diagrams of the distribution of light-emitting units in one light region according to various examples of an embodiment of the present disclosure.

(9) FIG. 10 is a schematic diagram of a partial planar structure of a backlight structure according to another example of an embodiment of the present disclosure.

(10) FIG. 11 is a schematic diagram of a partial cross-sectional structure cut along line BB' shown in FIG. 10 according to an example of an embodiment of the present disclosure.

(11) FIG. 12 is a schematic diagram of light-emitting units in one of light regions shown in FIG. 10.

(12) FIGS. 13A to 13G are schematic diagrams of one light region according to another example of an embodiment of the present disclosure.

(13) FIG. 14 is a relationship diagram of relative light intensity at the edge position of the light region after an M-sided polygon in the light region shown in FIGS. 13A to 13G respectively is rotated at different angles.

(14) FIGS. 15A to 15G are schematic diagrams of one light region according to another example of an embodiment of the present disclosure.

(15) FIG. 16 is a relationship diagram of relative light intensity at the edge position of a light region after an M-sided polygon in the light region shown in FIGS. 15A to 15G respectively is rotated at different angles.

(16) FIGS. 17A to 17G are schematic diagrams of one light region according to another example of an embodiment of the present disclosure.

(17) FIG. 18 is a relationship diagram of relative light intensity at the edge position of a light region after an M-sided polygon in the light region respectively shown in FIGS. 17A to 17G is rotated at different angles.

(18) FIG. 19 is a schematic diagram of the distribution of light-emitting units in one light region in different examples of an embodiment of the present disclosure.

(19) FIG. 20 is a schematic diagram of a partial cross-section cut along line AA' shown in FIG. 1 according to another example of an embodiment of the present disclosure.

(20) FIG. 21 is a schematic diagram of a partial cross-section cut along line BB' shown in FIG. 10 according to another example of an embodiment of the present disclosure.

(21) FIG. 22 is a schematic diagram of a partial cross-sectional structure cut along line BB' shown in FIG. 10 according to another example of an embodiment of the present disclosure.

(22) FIG. 23 is a schematic diagram of a partial cross-section of the backlight structure including the substrate, the barrier wall, and light-emitting units shown in FIG. 11.

(23) FIG. 24 is a schematic diagram of a partial cross-sectional structure of a display device according to another embodiment of the present disclosure.

DETAILED DESCRIPTION

(24) In order to make objects, technical details and advantages of the embodiments of the present disclosure apparent, the technical solutions of the embodiment will be described in a clearly and fully understandable way in connection with the drawings related to the embodiments of the present disclosure. It is obvious that the described embodiments are just a part but not all of the embodiments of the present disclosure. Based on the described embodiments herein, those skilled in the art can obtain other embodiment(s), without any inventive work, which should be within the scope of the present disclosure.

(25) Unless otherwise defined, all the technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art to which the present disclosure belongs. The terms “first,” “second,” etc., which are used in the description and the claims of the present application for disclosure, are not intended to indicate any sequence, amount or importance, but distinguish various components. The terms “comprise,” “comprising,” “include,” “including,” etc., are intended to specify that the elements or the objects stated before these terms encompass the elements or the objects and equivalents thereof listed after these terms, but do not preclude the other elements or objects.

(26) The features “parallel”, “perpendicular” and “same” used in the embodiments of the present disclosure all include features such as “parallel”, “perpendicular” and “same” in the strict sense, and the cases having certain errors, such as “approximately parallel”, “approximately perpendicular”, “approximately the same” or the like, taking into account measurements and errors associated with the measurement of a particular quantity (e.g., limitations of the measurement system), and indicate being within an acceptable range of deviation for a particular value as determined by one of ordinary skill in the art. For example, “approximately” may indicate being within one or more standard deviations, or within 10% or 5% of the stated value. In the case that the quantity of a component is not specifically indicated below in the embodiments of the present disclosure, it means that the component may be one or more, or may be understood as at least one. “At least one” means one or more, and “plurality” means at least two.

(27) The present disclosure provides a backlight structure and a display device. The backlight structure includes a substrate, and a barrier wall pattern and a plurality of light-emitting units that are located on the substrate. The barrier wall pattern includes a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings is configured to define a plurality of light regions; and the plurality of light-emitting units is distributed in the plurality of light regions. The substrate includes a central region and an edge region surrounding the central region, each light region at least in the central region is provided with at least three light-emitting units, centers of M light-emitting units, closest to vertex angles of the light region, among the at least three light-emitting units are sequentially connected to form an M-sided polygon, a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, and an included angle between the first direction and each side of the M-sided polygon and an included angle between the second direction and each side of the M-sided polygon are both greater than 0 degrees.

(28) In the backlight structure provided in the present disclosure, the setting of the included angle between each side of the M-sided polygon and the first direction and the included angle between each side of the M-sided polygon and the second direction is conducive to improving the light emitting uniformity.

(29) The present disclosure further provides another backlight structure. The backlight structure includes a substrate, and a barrier wall pattern and a plurality of light-emitting units that are located on the substrate. The barrier wall pattern includes a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings is configured to define a plurality of light regions; and the plurality of light-emitting units is distributed in the plurality of light regions. At least three light-emitting units are disposed in each of at least some light regions, centers of M light-emitting units of the at least three light-emitting units closest to vertex angles of the light region are sequentially connected to form an M-sided polygon, a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch of the light region to a side length of the M-sided polygon is 1.7 to 2.3; and at least one side of the M-sided polygon is parallel to at least one of the first direction and the second direction.

(30) In the backlight structure provided in the present disclosure, the setting of a relationship between the side length of the M-sided polygon and the pitch of the light region, the setting of a relationship between the center of the M-sided polygon and the center of the light region, and at least one side of the M-sided polygon being parallel to at least one of the first direction and the second direction are conducive to improving the light emitting uniformity.

(31) The following describes, with reference to the accompanying drawings, the backlight structure and the display device provided in embodiments of the present disclosure.

(32) FIG. 1 is a schematic diagram of a partial planar structure of a backlight structure according to an example of an embodiment of the present disclosure. As shown in FIG. 1, the backlight structure includes a substrate **100**, and a barrier wall pattern **200** and a plurality of light-emitting units **310** that are located on the substrate **100**. The barrier wall pattern **200** includes a plurality of openings **210** arrayed along a first direction and a second direction and a barrier wall **220** surrounding the openings **210**, the plurality of openings **210** is configured to define a plurality of light regions **300**, and the first direction intersects the second direction. The plurality of light-emitting units **310** is distributed in the plurality of light regions **300**. At least three light-emitting units **310** are disposed in each of at least some of the light regions **300**, centers of M light-emitting units **310** of the at least three light-emitting units **310** closest to vertex angles of the light region **300** are sequentially connected to form an M-sided polygon, a distance between the center C1 of the M-sided polygon and the center C2 of the light region is less than 10% of the pitch P of the light region **300**, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch P of the light region **300** to a side length P' of the M-sided polygon is 1.7 to 2.3; and at least one side of the M-sided polygon is parallel to at least one of the first direction and the second direction.

(33) According to the present disclosure, the setting of a relationship between the side length of the M-sided polygon and the pitch of the light region, the setting of a relationship between the center of the M-sided polygon and the center of the light region, and at least one side of the M-sided polygon being parallel to at least one of the first direction and the second direction are conducive to improving the light emitting uniformity.

(34) For example, one of the first direction and the second direction is a direction X shown in FIG. 1, and the other of the first direction and the second direction may be a direction Y shown in FIG. 1. This embodiment of the present disclosure is schematically described with the first direction being the direction X and the second direction being the direction Y.

(35) For example, the first direction is perpendicular to the second direction.

(36) For example, an included angle between the first direction and the second direction may be 80 to 110 degrees, or 85 to 100 degrees, or 88 to 92 degrees. This embodiment of the present disclosure is not limited thereto, and the first direction may be interchanged with the second direction.

(37) For example, as shown in FIG. 1, the plurality of openings **210** corresponds to the plurality of light regions **300** one by one, and each of the openings **210** is used to define one light region **300**.

(38) For example, the number of the light-emitting units **310** distributed in different light regions **300** may be the same or different.

(39) For example, this embodiment of the present disclosure schematically shows the same number of

light-emitting units distributed in different light regions, and the light-emitting units in different light regions are arranged in the same shape, thus improving the light emitting uniformity of the backlight structure.

(40) For example, as shown in FIG. 1, the plurality of light regions **300** is evenly distributed, and the plurality of light-emitting units **310** located on the substrate **100** is evenly distributed.

(41) For example, the number of light-emitting units **310** distributed in some of the light regions **300** in a region in the substrate **100** is the same, and the number of light-emitting units **310** distributed in some of the light regions **300** in another region in the substrate **100** is different. The positions of the two regions described above may be set according to the product requirements, for example, one of the regions may be located in a central region of the substrate, and the other region may be an edge region of the substrate; or one of the regions may be located in the edge region of the substrate, and the other region may be located in the central region of the substrate; or both the two regions are located in different edge regions of the substrate.

(42) For example, as shown in FIG. 1, M is not greater than the number of light-emitting units **310** disposed in each light region **300**. For example, the M-sided polygon may be a triangle, a quadrilateral, a hexagon, or the like, and this embodiment of the present disclosure is not limited thereto.

(43) For example, as shown in FIG. 1, at least three light-emitting units **310** are disposed in each light region **300** of all the light regions **300**.

(44) For example, each light region **300** may be provided with three light-emitting units **310**, or four light-emitting units **310**, or five light-emitting units **310**, or six light-emitting units **310**, or the like.

(45) For example, as shown in FIG. 1, the light region **300** may be in the shape of a polygon, such as a triangle, a quadrilateral, a hexagon, or the like.

(46) The center of the light-emitting unit refers to a geometric center of the light-emitting unit, for example, an orthographic projection of the geometric center on the substrate coincides with the center of a two-dimensional plane of an orthographic projection of the light-emitting unit on the substrate. The centers of the M light-emitting units sequentially connected may refer to the centers of the M light-emitting units being connected clockwise or counterclockwise.

(47) For example, as shown in FIG. 1, the pitch P of the light region **300** may be a length of a line connecting centers of adjacent light regions **300** arranged in the first direction, or a length of a line connecting centers of adjacent light regions **300** arranged in the second direction. For example, the ratio of the pitch of the light region **300** in the first direction to the pitch of the light region **300** in the second direction is 0.9 to 1.1, e.g., the pitches of the light regions **300** in the two directions may be equal.

(48) For example, as shown in FIG. 1, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 9.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 9% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 8.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 8% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 7.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 7% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 6.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 6% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 5.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 4.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 4% of the

pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 3.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 3% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 2.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 2% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 1.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 1% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 0.5% of the pitch P of the light region **300**.

(49) For example, as shown in FIG. 1, the center C1 of the M-sided polygon coincides with the center C2 of the light region **300**.

(50) For example, as shown in FIG. 1, the ratio of the lengths of different sides of the M-sided polygon is 0.98 to 1.08.

(51) For example, the ratio of the lengths of different sides of the M-sided polygon is 0.96 to 1.04.

(52) For example, the ratio of the lengths of different sides of the M-sided polygon is 0.95 to 1.05. For example, the ratio of the lengths of different sides of the M-sided polygon is 0.92 to 1.02.

(53) For example, as shown in FIG. 1, all sides of the M-sided polygon are equal in length and are P'.

(54) For example, as shown in FIG. 1, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.7 to 2.3. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.65 to 2.25. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.7 to 2.2. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.75 to 2.15. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.8 to 2.1. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.85 to 2.05. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.9 to 2.

(55) For example, as shown in FIG. 1, the pitch P of the light region **300** is two times the side length P' of the M-sided polygon.

(56) For example, as shown in FIG. 1, at least one side of the M-sided polygon is parallel to at least one of the first direction and the second direction.

(57) For example, the M-sided polygon only includes sides parallel to the first direction, or the M-sided polygon only includes sides parallel to the second direction, or the M-sided polygon includes sides parallel to the first direction as well as sides parallel to the second direction.

(58) FIG. 2A and FIG. 2B are schematic diagrams of light-emitting units in different examples. FIG. 3A is a schematic diagram of the equivalent luminescence of a Lambertian emitter. FIG. 3B is a schematic diagram of a light-emitting angle and light intensity distribution of a Lambertian emitter.

(59) For example, as shown in FIGS. 3A to 3B, if the light intensity of an extended light source is $dI \propto \cos m\alpha$, i.e., its brightness is independent of the direction, this type of emitter is called a cosine emitter, or a Lambertian (J. H. Lambert) emitter, and the above mentioned law of emitting luminous flux in accordance with the law of $\cos \alpha$ is referred to as Lambert's cosine law. dI in the formula is the light intensity of each surface element dS of the extended light surface along a certain direction r , and α is an included angle between the light emitting direction r of the light source and a normal n .

(60) The light intensity distribution satisfies: $I_{\text{sub.}\alpha} = I_{\text{sub.}0} \cos m\alpha$, $I_{\text{sub.}0}$ is the light intensity distribution along a direction of a normal perpendicular to a light source surface, $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub.}1/2})$, i.e., m is determined by $\alpha_{\text{sub.}1/2}$, where $\alpha_{\text{sub.}1/2}$ is defined as an included angle between the light emitting direction and the normal n when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and $\alpha_{\text{sub.}1/2}$ takes a value in a range of 40 to 80 degrees, for the example, $\alpha_{\text{sub.}1/2}$ may take a value in a range of 48 to 75 degrees, or in a range of 46 to 78 degrees, or in a range of 45 to 76 degrees. That is, if the light intensity of a light ray emitted in the

direction of the normal n is set to 1, the light intensity of the emitted light ray having the included angle of $\alpha.\text{sub}.1/2$ with the normal n is $1/2$, while the light ray emitted in a direction at an angle greater than $\alpha.\text{sub}.1/2$ with the normal n has a smaller light intensity. That is, although the Lambertian emitter can theoretically emit an infinite number of light rays, the light rays at different angles with the normal n have different light intensities.

(61) In some examples, as shown in FIG. 2A, the light-emitting unit **310** includes a light-emitting diode chip **323** and an encapsulation structure **324** configured to encapsulate the light-emitting diode chip **323**, and there is a spacing between the encapsulation structures **324** of adjacent light-emitting units **310**.

(62) For example, as shown in FIG. 2A, the light-emitting unit **310** includes the encapsulated light-emitting diode chip. The light-emitting diode chip **323** may be a sub-millimeter light-emitting diode chip (miniLED). A size of an unencapsulated light-emitting diode chip **323** in a direction perpendicular to the substrate **100** may be $70\text{ }\mu\text{m}$ to $180\text{ }\mu\text{m}$, and the maximum size of the unencapsulated light-emitting diode chip **323** in a direction parallel to the direction of the substrate **100** may be not greater than $500\text{ }\mu\text{m}$.

(63) For example, the encapsulated light-emitting diode chip is the light-emitting unit **310**, and the maximum size in the direction parallel to the substrate **100** and the thickness of the encapsulated light-emitting diode chip **323** are greater than the corresponding parameters of the unencapsulated light-emitting diode chip **323**.

(64) For example, as shown in FIG. 2A, a single light-emitting diode chip **323** may be encapsulated as a stand-alone device to form the light-emitting unit **310** before being disposed at a corresponding position on the backlight structure, and is fixedly connected to a pad on the substrate **100**.

(65) Because the unencapsulated light-emitting diode chip can be considered as a Lambertian emitter, after the light-emitting diode chip is encapsulated, a light ray emitted at an angle ranging from $+\alpha.\text{sub}.1/2$ to $-\alpha.\text{sub}.1/2$ can be emitted, whereas a light ray emitted at an angle in a range other than $+\alpha.\text{sub}.1/2$ to $-\alpha.\text{sub}.1/2$ is basically confined to the stand-alone device due to total reflection. At this time, an included angle θ between an utmost-edge light ray of light rays emitted by the light-emitting unit **310** and the substrate **100** may be a complement angle of $\alpha.\text{sub}.1/2$.

(66) For example, as shown in FIG. 2A, the light-emitting unit **310** or the light-emitting diode chip **323** is connected to a pad **321** on the substrate **100** by a solder metal **322**.

(67) For example, the solder metal **322** may include solder tin.

(68) For example, as shown in FIG. 2A, the encapsulation structure **324** may be doped with a color conversion material **325**.

(69) For example, the color conversion material **325** may include a fluorescent powder material or a quantum dot material.

(70) For example, the color conversion material **325** may include a material capable of converting blue light to white light.

(71) For example, the color conversion material **325** may include a material capable of converting blue light to red light and green light. Certainly, this embodiment of the present disclosure is not limited thereto, and the encapsulated structure may be doped with the color conversion material.

(72) For example, as shown in FIG. 2A, the light-emitting diode chip **323** may be encapsulated after being disposed at a corresponding position on the substrate **100**.

(73) For example, a transparent material, such as transparent silicone, can be used to encapsulate each light-emitting diode chip by means of screen printing or dot printing to form the encapsulation structure **324**. According to the different shapes of the encapsulation structure **324**, the light-emitting angle of the light-emitting diode chip **323** can be modulated, thereby changing the light-emitting angle of the light-emitting unit **310**.

(74) For example, as shown in FIG. 2A, a surface of the encapsulation structure **324** away from the substrate **100** may be a curved surface, and the light-emitting angle of the utmost-edge light ray of the light rays emitted by the light-emitting unit **310** is slightly greater than $\alpha.\text{sub}.1/2$ of the light-emitting diode chip **323**. If the value of $\alpha.\text{sub}.1/2$ is in the range of 40 to 65 degrees, the value of the light-emitting angle of the utmost-edge light ray of the light rays emitted by the light-emitting unit **310** may

be in a range of 50 to 70 degrees.

(75) For example, the encapsulation structure **324** may have any desired size in the direction perpendicular to the substrate **100**. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be less than 0.5 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.1 and 0.4 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.2 and 0.4 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be less than 0.3 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.25 and 0.35 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.15 and 0.25 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be about 0.2 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be about 0.3 mm.

(76) For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 2.5 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 2.5 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 0.7 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.8 and 0.9 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 0.5 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 1.0 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 2.0 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be less than 2.0 mm.

(77) For example, a ratio of the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** to its size in the direction perpendicular to the substrate **100** may be greater than 3. For example, the ratio of the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** to its size in the direction perpendicular to the substrate **100** may be between 4 and 6. For example, the ratio of the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** to its size in the direction perpendicular to the substrate **100** may be less than 10.

(78) For example, after being encapsulated as a stand-alone device, a geometric center of the light-emitting diode chip in an orthographic projection of the light-emitting diode chip on the substrate may coincide with a geometric center of an orthographic projection of the stand-alone device on the substrate. Without limitation, however, the geometric center of the orthographic projection of the light-emitting diode chip on the substrate may also be offset with respect to the geometric center of the orthographic projection of the stand-alone device on the substrate; a height of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is a height of the encapsulated light-emitting diode chip.

(79) For example, as shown in FIG. 2A, a size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 200 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 180 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 160 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 150 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 140 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 130 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 120 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 110 μm . For example, the size of the light-emitting

unit **310** in the direction perpendicular to the substrate **100** is not greater than 100 μm . The size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is the height of the light-emitting unit **310**.

(80) In some examples, as shown in FIG. 2A, the height of the light-emitting unit **310** is 50 to 100 μm .

(81) In some examples, as shown in FIG. 2A, the height of the light-emitting unit **310** is 80 to 100 μm .

(82) For example, the height of the light-emitting unit **310** is 55 to 95 μm . For example, the height of the light-emitting unit **310** is 60 to 90 μm . For example, the height of the light-emitting unit **310** is 70 to 85 μm . For example, the height of the light-emitting unit **310** is 75 to 80 μm .

(83) In some examples, as shown in FIGS. 1 to 2A, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 500 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 450 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 400 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 350 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 330 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 300 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 280 μm .

(84) For example, as shown in FIG. 1, a size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 250 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 240 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 230 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 220 μm . For example, the light-emitting unit **310** has a size of 219 μm in both the first direction and the second direction.

(85) The shape of the light-emitting unit described above may refer to the shape of the orthographic projection of the light-emitting unit on the substrate.

(86) For example, the light-emitting unit may be in the shape of a quadrilateral, such as a rectangle, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a length of a diagonal of the quadrilateral.

(87) For example, the light-emitting unit may be in the shape of an oval, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a length of a long axis of the oval.

(88) For example, the light-emitting unit may be in the shape of a circle, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a diameter.

(89) For example, as shown in FIG. 2B, the light-emitting unit **310** may also only include the unencapsulated light-emitting diode chip **323**, and the maximum size of the unencapsulated light-emitting diode chip **323** in the direction parallel to the substrate **100** may be not greater than 500 μm .

(90) For example, the light-emitting unit **310** is the unencapsulated light-emitting diode chip **323**. The light-emitting diode chip **323** is a sub-millimeter inorganic light-emitting diode (miniLED). The unencapsulated light-emitting diode chip **323** may have a thickness of 70 μm to 180 μm , and the maximum size of the unencapsulated light-emitting diode chip **323** in the direction parallel to the substrate **100** is not greater than 500 μm .

(91) For example, the unencapsulated light-emitting diode chip **323** may be equivalent to a Lambertian emitter. Since a light ray emitted by the unencapsulated light-emitting diode chip **323** and having an included angle greater than $\alpha.\text{sub.}1/2$ with the normal n has a small light intensity and is outside the scope of the present disclosure, this embodiment of the present disclosure defines a light ray emitted by the unencapsulated light-emitting diode chip **323** and having the included angle of $\alpha.\text{sub.}1/2$ with the normal n as the utmost-edge light ray of the unencapsulated light-emitting diode chip **323**, i.e., the utmost-edge light ray of the light-emitting unit **310**.

(92) For example, as shown in FIG. 2B, a protective layer **326** is disposed on a side of the plurality of light-emitting units **310** away from the substrate **100**.

(93) For example, in order to prevent the light-emitting diode chip **323** from being scratched or bumped

in subsequent processes, e.g., the process of placing an optical film on the substrate **100** or transportation, a plurality of light-emitting diode chips **323** may be uniformly protected using the protective layer **326**.

(94) For example, the plurality of light-emitting diode chips **323** may share the same protective layer **326**. For example, the protective layer **326** may be made of a transparent material, such as transparent silicone. For example, the protective layer **326** may fill the light regions.

(95) For example, a surface of the protective layer **326** away from the substrate **100** may be a nearly flat surface, thereby improving the yield of the display device.

(96) For example, to reduce the total reflection of light emitted from the light-emitting diode chip **323** within the protective layer **326**, the refractive index of the protective layer **326** may be between the refractive index of the light-emitting diode chip **323** and the refractive index of a material (e.g., air) adjacent to the protective layer **326**.

(97) For example, the refractive index of the protective layer **326** may be between 1.2 and 1.6. For example, the refractive index of the protective layer **326** may be between 1.3 and 1.4. For example, the refractive index of the protective layer **326** is less than 1.4. For example, the refractive index of the protective layer **326** may be less than 1.5. For example, the refractive index of the protective layer **326** may be greater than 1.1. For example, the refractive index of the protective layer **326** may be greater than 1.2. For example, the refractive index of the protective layer **326** may be greater than 1.3. For example, the refractive index of the protective layer **326** may be about 1.35. For example, the protective layer **326** may cover all of the unencapsulated light-emitting diode chips **323** on the substrate **100**, and the protective layer **326** may have a flat or slightly bumpy upper surface. For example, the thickness of the protective layer **326** is slightly greater than the thickness of the unencapsulated light-emitting diode chip **323**.

(98) FIG. **4** is a schematic diagram of a partial cross-sectional structure cut along line AA' shown in FIG. **1** according to an example of an embodiment of the present disclosure.

(99) In some examples, as shown in FIG. **4**, the thickness of the barrier wall **220** is greater than the height of the light-emitting unit **310** in a direction perpendicular to the substrate **100**.

(100) In some examples, as shown in FIG. **4**, the thickness of the barrier wall **220** is 200 to 400 μm and the height of the light-emitting unit **310** is 50 to 100 μm .

(101) The thickness of the barrier wall **220** described above refers to the size of the barrier wall **220** in the direction perpendicular to the substrate **100**.

(102) In some examples, as shown in FIG. **4**, the thickness of the barrier wall **220** is 250 to 270 μm .

(103) For example, the thickness of the barrier wall **220** may be 210 to 390 μm . For example, the thickness of the barrier wall **220** may be 220 to 370 μm . For example, the thickness of the barrier wall **220** may be 230 to 350 μm . For example, the thickness of the barrier wall **220** may be 235 to 320 μm . For example, the thickness of the barrier wall **220** may be 240 to 300 μm . For example, the thickness of the barrier wall **220** may be 245 to 280 μm .

(104) In some examples, as shown in FIG. **4**, the barrier wall **220** has a width of 350 to 500 μm . The width of the barrier wall **220** refers to the size of the barrier wall **220** between two adjacent light regions **300** in the first direction, or the size of the barrier wall **220** between two adjacent light regions **300** in the second direction.

(105) For example, as shown in FIG. **4**, the width of the barrier wall **220** may be 370 to 480 μm . For example, the width of the barrier wall **220** may be 350 to 450 μm . For example, the width of the barrier wall **220** may be 360 to 440 μm . For example, the width of the barrier wall **220** may be 370 to 430 μm . For example, the width of the barrier wall **220** may be 380 to 420 μm . For example, the width of the barrier wall **220** may be 390 to 410 μm . For example, the width of the barrier wall **220** may be 400 μm .

(106) In some examples, as shown in FIG. **1** and FIG. **4**, the barrier wall **220** includes a shading material.

(107) For example, the material of the barrier wall **220** may include black resin.

(108) In some examples, the light-emitting units **310** disposed in each light region **300** are electrically connected as shown in FIG. **1**. For example, a plurality of light-emitting units **310** in each light region **300** is connected in series. For example, the plurality of light-emitting units **310** in each light region **300**

is connected in parallel.

(109) In the backlight structure of the present disclosure, each light region is surrounded by a circle of barrier wall capable of shading, which is conducive to reducing the chance of crosstalk of light rays between different light regions and improves the halo phenomenon.

(110) In some examples, as shown in FIG. 1, at least some of the light regions 300 are in the shape of a rectangle, and two adjacent sides in the rectangle extend in the first direction and the second direction, respectively.

(111) For example, all of the light regions 300 are in the shape of a rectangle.

(112) For example, different light regions 300 have the same shape and are of the same size. Certainly, this embodiment of the present disclosure is not limited thereto. The substrate may be divided into a plurality of regions according to product requirements, the sizes of the light regions in different regions may be different, and the sizes of the light regions in the same region are the same.

(113) FIG. 5 is a schematic diagram of light-emitting units in one of light regions shown in FIG. 1. FIG. 5 schematically illustrates one light region including four light-emitting units, in which an M-sided polygon is a quadrilateral.

(114) For example, as shown in FIG. 5, the light region 300 may be in the shape of a square, and the M-sided polygon formed by a line of centers of the four light-emitting units 310 located in the light region 300 is a square.

(115) For example, using $I_{\alpha} = I_{\text{sub}.0} \cos m\alpha$ as equation 1 and $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub}.1/2})$ as equation 2, the range of $\alpha_{\text{sub}.1/2}$ may be from 45° to 75° , e.g., it may be 60° , and accordingly, $m_{\text{sub}.min} = 0.5$ and $m_{\text{sub}.max} = 2$ can be obtained. For example, a vertical component of an emergent optical path of a light-emitting unit, e.g., an optical path of h in the direction of the normal n shown in FIG. 3A, may be 100 to $350 \mu\text{m}$. For example, h may be 120 to $330 \mu\text{m}$. For example, h may be 150 to $300 \mu\text{m}$. For example, h may be 170 to $280 \mu\text{m}$. For example, h may be 200 to $250 \mu\text{m}$. The h is equal to the height difference between the height of the barrier wall and the height of the light-emitting unit, e.g., h is a vertical height difference from a surface of one side of the light-emitting unit away from the substrate to the highest point of the barrier wall.

(116) For example, as shown in FIG. 5, if the pitch of the light region 300 is P and a distance between the center of a light-emitting unit 314 and the center of a light-emitting unit 313 is $P/2$, for example, $L_{\text{sub}.2}$, $L_{\text{sub}.4}$ and P satisfy $L_{\text{sub}.2} = L_{\text{sub}.4} = [(3 \times P/4)^{\text{sup}.2} + (P/4)^{\text{sup}.2}]^{\text{sup}.1/2} - (10)^{\text{sup}.1/2} \times P/4$; $L_{\text{sub}.1}$ and P satisfy: $L_{\text{sub}.1} = (2)^{\text{sup}.1/2} \times P/4$; and $L_{\text{sub}.3}$ and P satisfy: $L_{\text{sub}.3} = 3 \times (2)^{\text{sup}.1/2} \times P/4$. The $L_{\text{sub}.1}$, $L_{\text{sub}.2}$, $L_{\text{sub}.3}$, and $L_{\text{sub}.4}$ refer to horizontal distances from the center of a corresponding light-emitting unit 310 to a vertex angle of the light region, respectively.

(117) For example, as shown in FIGS. 3A and 5, θ is a complementary angle of α , i.e., $\theta = 90^{\circ} - \alpha$, and $\tan \theta = h/L$, then $\cos m\alpha = \sin m[(\pi/2) - \alpha]$. For example, $\alpha_{\text{sub}.1/2}$ of the light-emitting unit 310, such as the encapsulated light-emitting diode chip may be 60° , then $m \approx 1$.

(118) For example, since the order of magnitude of h is micrometer and the order of magnitude of L is micron, and $L \gg h$, θ is very small; at this time, $\tan \theta \approx \theta = h/L$, α is close to 90° , and $\cos \alpha = \sin \theta \tan \theta = h/L$. Because $m \approx 1$, $\cos m\alpha = \sin (90^{\circ} - m\alpha) \approx \sin [m \times (90^{\circ} - \alpha)] \approx \sin (m \times \theta) \approx m \times \sin \theta \approx m \times h/L$. Therefore, the light intensity $I_{\text{sub}.1} = I_{\text{sub}.0} \cos(m\alpha_{\text{sub}.1}) + I_{\text{sub}.0} \cos(m\alpha_{\text{sub}.2}) + \dots + I_{\text{sub}.0} \cos(m\alpha_{\text{sub}.N}) \approx I_{\text{sub}.0} \times m \times h/L_{\text{sub}.1} + I_{\text{sub}.0} \times m \times h/L_{\text{sub}.2} + \dots$

$+ I_{\text{sub}.0} \times m \times h/L_{\text{sub}.N} = I_{\text{sub}.0} \times m \times h \times (1/L_{\text{sub}.1} + 1/L_{\text{sub}.2} + \dots + 1/L_{\text{sub}.N})$, N takes a value of the

number of the light-emitting units in the light region, and N may be 4 as shown in FIG. 5.

(119) The above relation equation 1: $I_{\text{sub}.1} = I_{\text{sub}.0} \times m \times h \times (1/L_{\text{sub}.1} + 1/L_{\text{sub}.2} + \dots + 1/L_{\text{sub}.N})$ may also be expressed as

$$(120) I_1 = I_0 \times m \times h \times \sum_{i=1}^{i=N} \frac{1}{L_i}.$$

The above relation equation 1 represents a summation relation equation for the corresponding values of N light-emitting units in the light region.

(121) The $L_{\text{sub}.2}$, $L_{\text{sub}.4}$, $L_{\text{sub}.1}$, and $L_{\text{sub}.3}$ may be substituted into the above equations to obtain $I_{\text{sub}.1} \approx I_{\text{sub}.0} \times m \times h / [2 \times (10)^{\text{sup}.1/2} \times P/4 + (2)^{\text{sup}.1/2} \times P/4 + 3 \times (2)^{\text{sup}.1/2} \times P/4] = 6.3 \times I_{\text{sub}.0} \times m \times h / P$.

(122) For example, in an area E2 shown in FIG. 5, the light intensity is

$$I_{\text{sub}.2} \approx 4 \times I_{\text{sub}.0} \times m \times h / [(2)^{\text{sup}.1/2} \times P/4] = 11.3 \times I_{\text{sub}.0} \times m \times h / P.$$

(123) For example, $I_{\text{sub.1}}/I_{\text{sub.2}}=0.56$.

(124) In some examples, as shown in FIG. 5, a ratio of light intensity at the edge position of the light region 300, such as the area E1, to light intensity at the center position of the light region 300, such as an area E2, is not less than 0.5.

(125) For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.9.

(126) In some examples, as shown in FIG. 5, $I_{\text{sub.0}}$, m , and h in the relation equation 1 may be regarded as constants, each light region 300 of at least some of the light regions 300 includes N light-emitting units, where $N \geq M$, a distance from the center of an i -th light-emitting unit 310 to a vertex angle of the light region 300 is $L_{\text{sub.i}}$, i takes a value in a range of 1 to N , and $L_{\text{sub.i}}$, P , and N satisfy: $8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.3$, where $P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$ can be used as an approximate reference value for the unitless relative light intensity at the edge position. The $1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}$ represents the sum of reciprocals of $L_{\text{sub.N}}$ of the N light-emitting units.

(127) For example, $8.3 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.5$. For example, $8.1 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.6$. For example, $8.2 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.7$. For example, $8 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6$. For example, $7.9 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.9$. For example, $7.8 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7$. For example, $7.7 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.8$. For example, $7.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.1$. For example, $7.6 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.2$. For example, $7.4 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.3$.

(128) The vertex angle of the light region described above may refer to the area E1 shown in FIG. 5.

(129) The above relation equation of $8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \leq 6.3$ may also be expressed as

$$(130) 8.5 \geq P \times \sum_{i=1}^N \frac{1}{L_i} \geq 6.3,$$

where

$$(131) Q = P \times \sum_{i=1}^N \frac{1}{L_i}.$$

The above relation equation represents a summation relation equation for the corresponding values of N light-emitting units in the light region.

(132) For example, as shown in FIG. 5, the light region 300 includes four light-emitting units, the distance from the center of the i -th light-emitting unit 310 to the vertex angle of the light region 300 is $L_{\text{sub.i}}$, and i takes a value in a range of 1 to 4, and $L_{\text{sub.i}}$, P , and N satisfy:

$$8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}}) \geq 6.3. \text{ For example,}$$

$$P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}}) = 6.3.$$

(133) For example, as shown in FIG. 1, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.7 to 2.3. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.65 to 2.25. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.7 to 2.2. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.75 to 2.15. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.8 to 2.1. For example, the ratio of the pitch of the

light region **300** to the side length of the quadrilateral is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.9 to 2.

(134) In some examples, as shown in FIGS. **1** and **5**, each of the at least some of the light regions **300** includes at least four light-emitting units **310**, the at least four light-emitting units **310** are arranged to form an M-sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M-sided polygon is 0 degrees.

(135) For example, as shown in FIG. **1**, at least some of the light regions **300** are in the shape of a square.

(136) In some examples, as shown in FIG. **1**, each light region **300** of the at least some of the light regions **300** is in the shape of a first square, each light region **300** of the at least some of the light region **300** includes at least four light-emitting units **310**, and the centers of the four light-emitting units **310**, closest to four vertex angles of the light region **300**, among the at least four light-emitting units **310** are sequentially connected to form a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 0 degrees.

(137) For example, the diagonal of the first square may coincide with the diagonal of the second square.

(138) In some examples, as shown in FIG. **1**, the at least four light-emitting units **310** include four light-emitting units **311**, **312**, **313**, and **314**, and the centers of the four light-emitting units **311**, **312**, **313**, and **314** are sequentially connected to form the second square.

(139) For example, an included angle between each of two sides of the second square and the first direction is 0 degrees, and an included angle between each of two other sides of the second square and the second direction is 0 degrees.

(140) For example, as shown in FIG. **1**, the plurality of light-emitting units **310** in the light region **300** is evenly distributed.

(141) For example, as shown in FIGS. **1** and **5**, the pitch of the light region **300** is 4.46 mm, the pitch of the light-emitting unit **310** is 2.23 mm, and the size of the light-emitting unit **310** may be 0.22 mm×0.22 mm. For example, the number of light regions **300** may be 2,596, for example, the number of light regions **300** arranged in one of the first direction and the second direction may be 44, and the number of light regions **300** arranged in the other one of the first direction and the second direction may be 59. For example, the size of the substrate on which the light regions **300** are disposed may be 263 mm×196 mm.

(142) For example, the total thickness of a light plate formed by the substrate **100**, the light-emitting units **310**, and the barrier wall pattern **200** may be 0.27 mm.

(143) In some examples, as shown in FIGS. **1**, **3A**, and **5**, the light intensity distribution I of the light-emitting units **310** satisfies $I = I_{\text{sub.0}} \cos m\alpha$, $I_{\text{sub.0}}$ is the light intensity distribution in the direction of the normal perpendicular to a light exit surface of the light-emitting unit **310**, α is the included angle between the light emitting direction of the light-emitting unit **310** and the normal, $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub.1/2}})$, $\alpha_{\text{sub.1/2}}$ is the included angle between the light emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and the optical path of a light ray emitted by the light-emitting unit **310** in the normal direction is h ; each of the at least some of the light regions **300** includes N light-emitting units **310**, where $N \geq M$, and the distance between the center of the i -th light-emitting unit **310** and the vertex angle of the light region **300** is $L_{\text{sub.i}}$, i takes a value in a range of 1 to N , and $L_{\text{sub.i}}$, h , and N satisfy: $0.5 \geq \cos m \times [(\pi/2) - (h/L_{\text{sub.1}})] + \cos m \times [(\pi/2) - (h/L_{\text{sub.2}})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub.N}})] \geq 0.23$.

(144) For example, as shown in FIGS. **3A** and **5**, in the case that the light-emitting unit **310** has a small emergent light angle θ , $\tan \theta \approx \theta = h/L$, $\tan \theta \approx \theta = h/L$ as well as $\alpha = (\pi/2) - \theta$ are substituted into the formula $\cos m\alpha$ to obtain $\cos m\alpha = \cos m \times [(\pi/2) - \theta] \approx \cos m \times [(\pi/2) - (h/L)]$. Thus, the light intensity in the area **E1** shown in FIG. **5** is obtained as $I_{\text{sub.1}} = I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.1}})] + I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.2}})] + \dots + I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.N}})]$, N takes a value of the number of the light-emitting units in the light region, and N may be 4 shown in FIG. **5**, then $I_{\text{sub.1}} = I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.1}})] + I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.2}})] + I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.3}})] + I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.4}})]$.

(145) The above relation equation 2: $I_{\text{sub.1}} = I_{\text{sub.0}} \times \cos m \times [(\pi/2) - (h/L_{\text{sub.1}})] + I_{\text{sub.0}} \times \cos m \times [(\pi/2) -$

(h/L.sub.2)]+...+I.sub.0×cos m×[(π/2)−(h/L.sub.N)] may also be expressed as

$$(146) I_1 = I_0 \times S = I_0 \times \text{Math.}_{i=1}^{i=N} \cos m(\frac{\pi}{2} - \frac{h}{L_i}),$$

where,

$$(147) S = \text{Math.}_{i=1}^{i=N} \cos m(\frac{\pi}{2} - \frac{h}{L_i}),$$

where m is approximately equal to 1. The above relation equation 2 represents a summation relation equation for the corresponding values of the N light-emitting units in the light region.

(148) For example, taking the pitch of the light region **300** as 4.46 mm and the pitch of the light-emitting unit **310** as 2.23 mm as an example, then S=0.254002. The pitch of the light-emitting unit **310** may refer to the side length of the M-sided polygon.

(149) For example, $0.48 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.25$.

(150) For example, $0.45 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.27$.

(151) For example, $0.42 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.28$.

(152) For example, $0.4 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.3$.

(153) For example, $0.38 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.32$.

(154) For example, $0.36 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.35$.

(155) FIGS. **6** to **9** are schematic diagrams of the distribution of light-emitting units in one light region according to various examples of an embodiment of the present disclosure.

(156) For example, at least one light region **300** in the example shown in FIG. **6** includes five light-emitting units **311**, **312**, **313**, **314**, and **315**. Centers of the four light-emitting units **311**, **312**, **313**, and **314** are sequentially connected to form a quadrilateral, or the five light-emitting units **311**, **312**, **313**, **314**, and **315** are arranged to form a quadrilateral. An included angle between at least one of the first direction and the second direction and at least one side of the quadrilateral is 0 degrees.

(157) The four light-emitting units **311**, **312**, **313**, and **314** may be the four light-emitting units located outermost, or may be the four light-emitting units closest to vertex angles of the light region.

(158) For example, as shown in FIG. **6**, the light region **300** includes five light-emitting units. A distance from the center of an i-th light-emitting unit **310** to a vertex angle of the light region **300** is L.sub.i, i takes a value in the range of 1 to 5, and L.sub.i, P, and N satisfy:

$$8.5 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6.3.$$

(159) For example, $8.3 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6.5$.

(160) For example, $8.1 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6.6$.

(161) For example, $8.2 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6.7$.

(162) For example, $8 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6$.

(163) For example, $7.9 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.6) \geq 6.9$.

(164) For example, $7.8 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 7$.

(165) For example, $7.7 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 6.8$.

(166) For example, $7.5 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 7.1$.

(167) For example, $7.6 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 7.2$.

(168) For example, $7.4 \geq P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + 1/L.\text{sub}.3 + 1/L.\text{sub}.4 + 1/L.\text{sub}.5) \geq 7.3$.

(169) For example, as shown in FIG. **6**, a ratio of the pitch of the light region **300** to a side length of the quadrilateral is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.9 to 2.

(170) For example, as shown in FIG. 6, the five light-emitting units **311**, **312**, **313**, **314**, and **315** may be evenly distributed. For example, the light-emitting unit **315** may be located at the center of the quadrilateral formed by the four light-emitting units **311**, **312**, **313**, and **314**.

(171) For example, as shown in FIG. 6, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a rectangle.

(172) For example, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a square.

(173) For example, an included angle between each of two sides of the quadrilateral and the first direction is 0 degrees, and an included angle between each of the other two sides of the quadrilateral and the second direction is 0 degrees.

(174) For example, as shown in FIG. 6, the light region **300** is in the shape of the first square, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be the second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 0 degrees. For example, the diagonal of the first square may coincide with the diagonal of the second square.

(175) For example, as shown in FIG. 6, the pitch of the light region **300** is 4.46 mm, the pitch of the light-emitting unit **310** is 2.23 mm, and the size of the light-emitting unit **310** may be 0.22 mm×0.22 mm. For example, the number of light regions **300** may be 2,596, for example, the number of light regions **300** arranged in one of the first direction and the second direction may be 44, and the number of light regions **300** arranged in the other one of the first direction and the second direction may be 59. For example, the size of the substrate on which the light regions **300** are disposed may be 263 mm×196 mm.

(176) For example, parameters such as the size and material of the barrier wall and the size of the light-emitting units in the example shown in FIG. 6 may be the same as the corresponding parameters in the above example and will not be repeated herein.

(177) For example, the at least one light region **300** in the example shown in FIG. 7 includes nine light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, **317**, **318**, and **319**, centers of the four light-emitting units **311**, **312**, **313**, and **314** are sequentially connected to form a quadrilateral, or the nine light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, **317**, **318**, and **319** are arranged to form a quadrilateral, and an included angle between at least one of the first direction and the second direction and at least one side of the quadrilateral is 0 degrees. The four light-emitting units **311**, **312**, **313**, and **314** may be the four light-emitting units located outermost, or may be the four light-emitting units closest to vertex angles of the light region.

(178) For example, as shown in FIG. 7, the light region **300** includes nine light-emitting units, and a distance from the center of an i-th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{sub.i}$, where i takes a value in the range of 1 to 9, and $L_{sub.i}$, P, and N satisfy:

$$8.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.3.$$

(179) For example,

$$8.3 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.5.$$

(180) For example,

$$8.1 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.6.$$

(181) For example,

$$8.2 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.7.$$

(182) For example,

$$8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.$$

(183) For example,

$$7.9 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.9.$$

(184) For example,

$$7.8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 7.$$

(185) For example,

$$7.7 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.8.$$

(186) For example,

$7.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}} + 1/L_{\text{sub.5}} + 1/L_{\text{sub.6}} + 1/L_{\text{sub.7}} + 1/L_{\text{sub.8}} + 1/L_{\text{sub.9}}) \geq 7.1$

(187) For example,

$7.6 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}} + 1/L_{\text{sub.5}} + 1/L_{\text{sub.6}} + 1/L_{\text{sub.7}} + 1/L_{\text{sub.8}} + 1/L_{\text{sub.9}}) \geq 7.2$

(188) For example,

$7.4 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}} + 1/L_{\text{sub.5}} + 1/L_{\text{sub.6}} + 1/L_{\text{sub.7}} + 1/L_{\text{sub.8}} + 1/L_{\text{sub.9}}) \geq 7.3$

(189) For example, as shown in FIG. 7, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.9 to 2.

(190) For example, as shown in FIG. 7, the nine light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, **317**, **318**, and **319** may be evenly distributed. For example, the light-emitting unit **315** may be located at the center of the quadrilateral formed of the four light-emitting units **311**, **312**, **313**, and **314**.

(191) For example, as shown in FIG. 7, the light-emitting unit **318** may be located between the light-emitting unit **311** and the light-emitting unit **312**, the light-emitting unit **319** may be located between the light-emitting unit **311** and the light-emitting unit **314**, the light-emitting unit **317** may be located between the light-emitting unit **313** and the light-emitting unit **314**, and the light-emitting unit **316** may be located between the light-emitting unit **312** and the light-emitting unit **313**.

(192) For example, four sides of the quadrilateral pass through the centers of the light-emitting units **318**, **319**, **317**, and **316**, respectively.

(193) For example, the centers of the light-emitting units **318**, **319**, **317**, and **316** may be the centers of the four sides of the quadrilateral, respectively.

(194) For example, as shown in FIG. 7, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a rectangle.

(195) For example, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a square.

(196) For example, an included angle between two sides of the quadrilateral and the first direction is 0 degrees, and an included angle between the other two sides of the quadrilateral and the second direction is 0 degrees.

(197) For example, as shown in FIG. 7, the light region **300** is in the shape of the first square, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be the second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 0 degrees. For example, the diagonal of the first square may coincide with the diagonal of the second square.

(198) For example, as shown in FIG. 7, the pitch of the light region **300** is 4.46 mm, the pitch of the light-emitting unit **310** is 2.23 mm, and the size of the light-emitting unit **310** may be 0.22 mm×0.22 mm. For example, the number of light regions **300** may be 2,596, for example, the number of light regions **300** arranged in one of the first direction and the second direction may be 44, and the number of light regions **300** arranged in the other one of the first direction and the second direction may be 59. For example, the size of the substrate on which the light regions **300** are disposed may be 263 mm×196 mm.

(199) For example, parameters such as the size and material of the barrier wall and the size of the light-emitting units in the example shown in FIG. 7 may be the same as the corresponding parameters in the above example and will not be repeated herein.

(200) For example, the at least one light region **300** in the example shown in FIG. 8 includes seven light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, and **317**, centers of the six light-emitting units **311**, **312**, **313**, **314**, **316**, and **317** are sequentially connected to form hexagon, or the seven light-emitting units **311**, **312**, **313**, **314**, **315**, **316** and **317** are arranged to form a hexagon, and an included angle between at least one of the first direction and the second direction and at least one side of the hexagon is

0 degrees. The six light-emitting units **311**, **312**, **313**, **314**, **316**, and **317** may be the six light-emitting units located outermost, or may be the six light-emitting units closest to vertex angles of the light region.

(201) For example, as shown in FIG. **8**, the light region **300** includes seven light-emitting units, and a distance from the center of an i-th light-emitting unit **310** to vertex angles of the light region **300** is $L_{sub.i}$, where i takes a value in the range of 1 to 7, and $L_{sub.i}$, P, and N satisfy:

$$8.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.3.$$

(202) For example,

$$8.3 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.5.$$

(203) For example,

$$8.1 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.6.$$

(204) For example,

$$8.2 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.7.$$

(205) For example,

$$8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.$$

(206) For example,

$$7.9 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.9.$$

(207) For example,

$$7.8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 7.$$

(208) For example,

$$7.7 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 6.8.$$

(209) For example,

$$7.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 7.1.$$

(210) For example,

$$7.6 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 7.2.$$

(211) For example,

$$7.4 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7}) \geq 7.3.$$

(212) For example, as shown in FIG. **8**, a ratio of the pitch of the light region **300** to a side length of the hexagon is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the hexagon is 1.9 to 2.

(213) For example, as shown in FIG. **8**, the seven light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, and **317** may be evenly distributed. For example, the light-emitting unit **315** may be located in the center of the hexagon formed by the six light-emitting units **311**, **312**, **313**, **314**, **316**, and **317**.

(214) For example, as shown in FIG. **8**, the hexagon may be a regular hexagon.

(215) For example, as shown in FIG. **8**, an included angle between each of two sides of the hexagon and the first direction or the second direction is 0 degrees.

(216) For example, parameters such as the size and material of the barrier wall and the size of the light-emitting units in the example shown in FIG. **8** may be the same as the corresponding parameters in the above example and will not be repeated herein.

(217) Certainly, this embodiment of the present disclosure is not limited thereto, and the number of the light-emitting units in the light region may also be six, such as by removing the light-emitting unit **315** located in the very center in FIG. **8**. The number of the light-emitting units in the light region may be set according to the needs of the backlight structure and the needs of the display panel.

(218) For example, at least one light region **300** in the example shown in FIG. **9** includes three light-emitting units **311**, **312**, and **313**, centers of the three light-emitting units **311**, **312**, and **313** are connected to form a triangle, and an included angle between at least one of the first direction and the second direction and at least one side of the triangle is 0 degrees. The three light-emitting units **311**,

312, and **313** may be three light-emitting units located outermost.

(219) For example, as shown in FIG. 9, the light region **300** includes three light-emitting units, and a distance from the center of an *i*-th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{sub.i}$, where *i* takes a value in the range of 1 to 3, and $L_{sub.i}$, *P*, and *N* satisfy:

$8.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.3$.

(220) For example, $8.3 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.5$. For example,

$8.1 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.6$. For example,

$8.2 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.7$. For example, $8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6$.

For example, $7.9 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.9$. For example,

$7.8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 7$. For example, $7.7 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 6.8$.

For example, $7.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 7.1$. For example,

$7.6 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 7.2$. For example,

$7.4 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3}) \geq 7.3$.

(221) For example, as shown in FIG. 9, a ratio of the pitch of the light region **300** to a side length of the triangle is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the triangle is 1.9 to 2.

(222) For example, as shown in FIG. 9, the three light-emitting units **311**, **312**, and **313** may be evenly distributed.

(223) For example, as shown in FIG. 9, the triangle may be an equilateral triangle.

(224) For example, as shown in FIG. 9, an included angle between one side of the triangle and the first direction or the second direction is 0 degrees.

(225) Certainly, this embodiment of the present disclosure is not limited thereto, and the triangle may have an included angle of 0 degrees between one side and the first direction and an included angle of 0 degrees between the other side and the second direction.

(226) For example, as shown in FIG. 9, the pitch of the light region **300** is 4.8 mm, the pitch of the light-emitting unit **310** is 2.6 mm, and the size of the light-emitting unit **310** may be 0.219 mm×0.219 mm.

(227) For example, parameters such as the size and material of the barrier wall and the size of the light-emitting units in the example shown in FIG. 9 may be the same as the corresponding parameters in the above example and will not be repeated herein.

(228) FIG. 10 is a schematic diagram of a partial planar structure of a backlight structure according to another example of an embodiment of the present disclosure. As shown in FIG. 10, the backlight structure includes a substrate **100**, and a barrier wall pattern **200** and a plurality of light-emitting units **310** that are located on the substrate **100**. The barrier wall pattern **200** includes a plurality of openings **210** arrayed along a first direction and a second direction and a barrier wall **220** surrounding the openings **210**, the plurality of openings **210** is configured to define a plurality of light regions **300**, and the first direction intersects the second direction. The plurality of light-emitting units **310** is distributed in the plurality of light regions **300**. The substrate **100** includes a central region **101** and an edge region **102** surrounding the central region **101**, each light region **300** at least in the central region **101** is provided with at least three light-emitting units **310**, centers of *M* light-emitting units **310**, closest to vertex angles of the light region **300**, of the at least three light-emitting units **310** are sequentially connected to form an *M*-sided polygon, a distance between the center of the *M*-sided polygon and the center of the light region **300** is less than 10% of the pitch of the light region **300**, and an included angle between the first direction and each side of the *M*-sided polygon and an included angle between the second direction and each side of the *M*-sided polygon are both greater than 0 degrees.

(229) In the backlight structure provided in the present disclosure, the setting of the included angle between each side of the *M*-sided polygon and the first direction and the included angle between each

side of the M-sided polygon and the second direction is conducive to improving the light emitting uniformity.

(230) For example, one of the first direction and the second direction is a direction X shown in FIG. 10, and the other of the first direction and the second direction may be a direction Y shown in FIG. 10. This embodiment of the present disclosure is schematically described with the first direction being the direction X and the second direction being the direction Y.

(231) For example, the first direction is perpendicular to the second direction. For example, an included angle between the first direction and the second direction may be 80 to 110 degrees, or 85 to 100 degrees, or 88 to 92 degrees. This embodiment of the present disclosure is not limited thereto, and the first direction may be interchanged with the second direction.

(232) For example, as shown in FIG. 10, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 0.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 1 degree. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 2 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 3 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 4 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 5.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 6 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 6.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 7 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 8 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 9 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 10 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 10.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 11 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 12 degrees.

(233) For example, as shown in FIG. 10, the included angle between the first direction and one side of the M-sided polygon may be the same as the included angle between the second direction and another side of the M-sided polygon.

(234) Certainly, this embodiment of the present disclosure is not limited thereto, and the included angle between the first direction and one side of the M-sided polygon may be different from the included angle between the second direction and either side of the M-sided polygon.

(235) For example, as shown in FIG. 10, the plurality of openings 210 corresponds to the plurality of light regions 300 one by one, and each of the openings 210 is used to define one light region 300.

(236) For example, the number of the light-emitting units 310 distributed in different light regions 300

may be the same or different.

(237) For example, the number of light-emitting units **310** distributed in some of the light regions **300** in a region on the substrate **100** is the same, and the number of light-emitting units **310** distributed in some of the light regions **300** in another region on the substrate **100** is different. The positions of the two regions described above may be set according to the product requirements, for example, one of the regions may be located in a central region of the substrate, and the other region may be an edge region of the substrate; or one of the regions may be located in the edge region of the substrate, and the other region may be located in the central region of the substrate; or both the two regions are located in different edge regions of the substrate.

(238) For example, as shown in FIG. **10**, a central region **101** of the substrate **100** may include at least one light region **300**.

(239) For example, the central region **101** may include two light regions **300**, four light regions **300**, or more light regions **300**.

(240) For example, an edge region **102** includes at least one circle of light regions **300** located at the edge, the at least one circle of light regions **300** includes two columns of light regions **300** located on either side of the central region **101** in a first direction and two rows of light regions **300** located on either side of the central region **101** in a second direction.

(241) For example, as shown in FIG. **10**, the number of light-emitting units **310** disposed in each of the light regions **300** located in the central region **101** and the edge region **102** respectively are the same. However, without limitation, the number of light regions included in the central region and the edge region respectively and the number of light-emitting units included in each light region may be set according to product requirements.

(242) For example, as shown in FIG. **10**, M is not greater than the number of light-emitting units **310** disposed in each light region **300**. For example, the M-sided polygon may be a triangle, a quadrilateral, a hexagon, or the like. This embodiment of the present disclosure is not limited thereto.

(243) For example, as shown in FIG. **10**, at least three light-emitting units **310** are disposed in each light region **300** of all the light regions **300**.

(244) For example, each light region **300** may be provided with three light-emitting units **310**, or four light-emitting units **310**, or five light-emitting units **310**, or six light-emitting units **310**, or the like.

(245) For example, as shown in FIG. **10**, the light region **300** may be in the shape of a polygon, such as a triangle, a quadrilateral, a hexagon, or the like.

(246) The center of the light-emitting unit refers to a geometric center of the light-emitting unit, for example, an orthographic projection of the geometric center on the substrate coincides with the center of a two-dimensional plane of an orthographic projection of the light-emitting unit on the substrate. Centers of the M light-emitting units sequentially connected may refer to the centers of the M light-emitting units being connected clockwise or counterclockwise.

(247) For example, as shown in FIG. **10**, the pitch P of the light region **300** may be the length of a line connecting centers of adjacent light regions **300** arranged in the first direction, or the length of a line connecting centers of adjacent light regions **300** arranged in the second direction.

(248) For example, a ratio of the pitch of the light region **300** in the first direction to the pitch of the light region **300** in the second direction may be 0.9 to 1.1, e.g., the two pitches may be equal.

(249) For example, as shown in FIG. **10**, a distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 9.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 9% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 8.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 8% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 7.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 7% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon

and the center C2 of the light region **300** is less than 6.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 6% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 5.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 4.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 4% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 3.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 3% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 2.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 2% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 1.5% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 1% of the pitch P of the light region **300**. For example, the distance between the center C1 of the M-sided polygon and the center C2 of the light region **300** is less than 0.5% of the pitch P of the light region **300**.

(250) For example, as shown in FIG. **10**, the center C1 of the M-sided polygon coincides with the center C2 of the light region **300**.

(251) In some examples, as shown in FIG. **10**, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch P of the light region **300** to a side length of the M-sided polygon is 1.7 to 2.3.

(252) For example, as shown in FIG. **10**, the ratio of the lengths of different sides of the M-sided polygon is 0.98 to 1.08. For example, the ratio of the lengths of different sides of the M-sided polygon is 0.96 to 1.04. For example, the ratio of the lengths of different sides of the M-sided polygon is 0.95 to 1.05. For example, the ratio of the lengths of different sides of the M-sided polygon is 0.92 to 1.02.

(253) For example, as shown in FIG. **10**, all sides of the M-sided polygon are equal in length and are P'.

(254) For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.65 to 2.25. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.7 to 2.2. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.75 to 2.15. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.8 to 2.1. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.85 to 2.05. For example, the ratio of the pitch P of the light region **300** to the side length P' of the M-sided polygon is 1.9 to 2.

(255) For example, as shown in FIG. **10**, the pitch P of the light region **300** is two times the side length P' of the M-sided polygon.

(256) For example, the light-emitting units **310** shown in FIG. **10** satisfy the Lambert cosine law of the cosine emitter or the Lambertian emitter shown in FIGS. **3A** to **3B**.

(257) In some examples, each of the light-emitting units **310** shown in FIG. **10** includes a light-emitting diode chip **323** and an encapsulation structure **324** configured to encapsulate the light-emitting diode chip **323**, as shown in FIG. **2**, and there is a spacing between the encapsulation structures **324** of adjacent light-emitting units **310**.

(258) For example, the light-emitting diode chip **323** may be a sub-millimeter light-emitting diode chip (miniLED), a size of an unencapsulated light-emitting diode chip **323** in a direction perpendicular to the substrate **100** may be 70 μm to 180 μm , and the maximum size of the unencapsulated light-emitting diode chip **323** in a direction parallel to the direction of the substrate **100** may be not greater than 500 μm .

(259) For example, the encapsulated light-emitting diode chip is the light-emitting unit **310**, and the

maximum size in the direction parallel to the substrate **100** and the thickness of the encapsulated light-emitting diode chip **323** are greater than the corresponding parameters of the unencapsulated light-emitting diode chip **323**.

(260) For example, as shown in FIG. 2A, a single light-emitting diode chip **323** may be encapsulated as a stand-alone device to form the light-emitting unit **310** before being disposed at a corresponding position on the backlight structure, and is fixedly connected to a pad on the substrate **100**.

(261) Since the unencapsulated light-emitting diode chip can be considered as a Lambertian emitter, after the light-emitting diode chip is encapsulated, a light ray emitted at an angle ranging from $+\alpha.\text{sub.}1/2$ to $-\alpha.\text{sub.}1/2$ can be emitted, whereas a light ray emitted at an angle in a range other than $+\alpha/2$ to $-\alpha/2$ is basically confined to the stand-alone device due to total reflection. At this time, an included angle θ between an utmost-edge light ray of light rays emitted by the light-emitting unit **310** and the substrate **100** may be a complement angle of $\alpha.\text{sub.}1/2$.

(262) For example, as shown in FIG. 2A, the light-emitting unit **310** or the light-emitting diode chip **323** is connected to a pad **321** on the substrate **100** by a solder metal **322**.

(263) For example, the solder metal **322** may include solder tin.

(264) For example, as shown in FIG. 2A, the encapsulation structure **324** may be doped with a color conversion material **325**.

(265) For example, the color conversion material **325** may include a fluorescent powder material or a quantum dot material.

(266) For example, the color conversion material **325** may include a material capable of converting blue light to white light.

(267) For example, the color conversion material **325** may include a material capable of converting blue light to red light and green light. Certainly, the encapsulation structure may not be doped with the color conversion material.

(268) For example, as shown in FIG. 2A, the light-emitting diode chip **323** may be encapsulated after being disposed at a corresponding position on the substrate **100**.

(269) For example, a transparent material, such as transparent silicone, can be used to encapsulate each light-emitting diode chip by means of screen printing or dot printing to form the encapsulation structure **324**. According to the different shapes of the encapsulation structure **324**, the light-emitting angle of the light-emitting diode chip **323** can be modulated, thereby changing the light-emitting angle of the light-emitting unit **310**.

(270) For example, as shown in FIG. 2A, a surface of the encapsulation structure **324** away from the substrate **100** may be a curved surface, and the light-emitting angle of the utmost-edge light ray of the light rays emitted by the light-emitting unit **310** is slightly greater than $\alpha.\text{sub.}1/2$ of the light-emitting diode chip **323**. Assuming that the value of $\alpha.\text{sub.}1/2$ is in the range of 40 to 65 degrees, the value of the light-emitting angle of the utmost-edge light ray of the light rays emitted by the light-emitting unit **310** may be in a range of 50 to 70 degrees.

(271) For example, the encapsulation structure **324** may have any desired size in the direction perpendicular to the substrate **100**. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be less than 0.5 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.1 and 0.4 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.2 and 0.4 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be less than 0.3 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.25 and 0.35 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be between 0.15 and 0.25 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be about 0.2 mm. For example, the size of the encapsulation structure **324** in the direction perpendicular to the substrate **100** may be about 0.3 mm.

(272) For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 2.5 mm. For example, the maximum size of the encapsulation

structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 2.5 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.3 and 0.7 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be between 0.8 and 0.9 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 0.5 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 1.0 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be greater than 2.0 mm. For example, the maximum size of the encapsulation structure **324** in the direction parallel to the substrate **100** may be less than 2.0 mm.

(273) For example, after being encapsulated as a stand-alone device, a geometric center of the light-emitting diode chip in an orthographic projection of the light-emitting diode chip on the substrate may coincide with a geometric center of an orthographic projection of the stand-alone device on the substrate. Without limitation, however, the geometric center of the orthographic projection of the light-emitting diode chip on the substrate may also be offset with respect to the geometric center of the orthographic projection of the stand-alone device on the substrate; a height of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is a height of the encapsulated light-emitting diode chip.

(274) For example, the maximum size of each light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 2 mm.

(275) For example, as shown in FIG. **10**, a size of the light-emitting unit **310** in a direction perpendicular to the substrate **100** is not greater than 200 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 180 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 160 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 150 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 140 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 130 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 120 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 110 μm . For example, the size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** is not greater than 100 μm . The size of the light-emitting unit **310** in the direction perpendicular to the substrate **100** refers to the height of the light-emitting unit **310**.

(276) In some examples, as shown in FIG. **2A**, the height of the light-emitting unit **310** is 50 to 100 μm .

(277) In some examples, as shown in FIG. **2A**, the height of the light-emitting unit **310** is 80 to 100 μm .

(278) For example, the height of the light-emitting unit **310** is 55 to 95 μm . For example, the height of the light-emitting unit **310** is 60 to 90 μm . For example, the height of the light-emitting unit **310** is 70 to 85 μm . For example, the height of the light-emitting unit **310** is 75 to 80 μm .

(279) For example, as shown in FIG. **10**, the light-emitting unit **310** has a maximum size not greater than 3 mm in a direction parallel to the substrate **100**.

(280) In some examples, as shown in FIG. **10**, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 500 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 450 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 400 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 350 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 330 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 300 μm . For example, the maximum size of the light-emitting unit **310** in the direction parallel to the substrate **100** is not greater than 280 μm .

(281) For example, as shown in FIG. **10**, a size of the light-emitting unit **310** in at least one of the first

direction and the second direction is not greater than 250 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 240 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 230 μm . For example, the size of the light-emitting unit **310** in at least one of the first direction and the second direction is not greater than 220 μm . For example, the light-emitting unit **310** has a size of 219 μm in both the first direction and the second direction.

(282) The shape of the light-emitting unit described above may refer to the shape of the orthographic projection of the light-emitting unit on the substrate.

(283) For example, the light-emitting unit may be in the shape of a quadrilateral, such as a rectangle, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a length of a diagonal of the quadrilateral.

(284) For example, the light-emitting unit may be in the shape of an oval, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a length of a long axis of the oval.

(285) For example, the light-emitting unit may be in the shape of a circle, and the maximum size of the light-emitting unit in the direction parallel to the substrate may be a diameter.

(286) Certainly, this embodiment of the present disclosure is not limited thereto, and the light-emitting unit in the example shown in FIG. **10** may further include only the unencapsulated light-emitting diode chip **323**, as shown in FIG. **2B**. The maximum size of the unencapsulated light-emitting diode chip **323** in the direction parallel to the substrate **100** may be not greater than 500 μm .

(287) FIG. **11** is a schematic diagram of a partial cross-sectional structure cut along line BB' shown in FIG. **10** according to an example of an embodiment of the present disclosure.

(288) In some examples, as shown in FIG. **11**, a thickness of the barrier wall **220** is greater than a height of the light-emitting unit **310** in a direction perpendicular to the substrate **100**.

(289) In some examples, as shown in FIG. **11**, the thickness of the barrier wall **220** is 200 to 400 μm and the height of the light-emitting unit **310** is 50 to 100 μm . The thickness of the barrier wall **220** described above refers to the size of the barrier wall **220** in the direction perpendicular to the substrate **100**.

(290) In some examples, as shown in FIG. **11**, the thickness of the barrier wall **220** is 250 to 270 μm .

(291) For example, the thickness of the barrier wall **220** may be 210 to 390 μm . For example, the thickness of the barrier wall **220** may be 220 to 370 μm . For example, the thickness of the barrier wall **220** may be 230 to 350 μm . For example, the thickness of the barrier wall **220** may be 235 to 320 μm . For example, the thickness of the barrier wall **220** may be 240 to 300 μm . For example, the thickness of the barrier wall **220** may be 245 to 280 μm .

(292) In some examples, as shown in FIG. **11**, the barrier wall **220** has a width of 350 to 500 μm . The width of the barrier wall **220** refers to the size, in the first direction, of the barrier wall **220** between two adjacent light regions **300** in the first direction, or the size, in the second direction, of the barrier wall **220** between two adjacent light regions **300** in the second direction.

(293) For example, as shown in FIG. **11**, the barrier wall **220** has a width of 370 to 480 μm . For example, the width of the barrier wall **220** may be 350 to 450 μm . For example, the width of the barrier wall **220** may be 360 to 440 μm . For example, the width of the barrier wall **220** may be 370 to 430 μm . For example, the width of the barrier wall **220** may be 380 to 420 μm . For example, the width of the barrier wall **220** may be 390 to 410 μm . For example, the width of the barrier wall **220** may be 400 μm .

(294) In some examples, as shown in FIG. **11**, the barrier wall **220** includes a shading material. For example, the material of the barrier wall **220** may include black resin.

(295) In some examples, as shown in FIG. **10**, the light-emitting units **310** disposed in each light region **300** are electrically connected. For example, a plurality of light-emitting units **310** in each light region **300** is connected in series. For example, the plurality of light-emitting units **310** in each light region **300** is connected in parallel.

(296) In the backlight structure of the present disclosure, each light region is surrounded by a circle of barrier wall capable of shading, which is conducive to reducing the crosstalk of light rays between different light regions and alleviate the halo phenomenon.

(297) In some examples, as shown in FIG. **10**, at least some of the light regions **300** are in the shape of a

rectangle, and two adjacent sides in the rectangle extend in the first direction and the second direction, respectively.

(298) For example, all of the light regions **300** are in the shape of a rectangle. For example, different light regions **300** have the same shape and are of the same size.

(299) Certainly, this embodiment of the present disclosure is not limited thereto. The substrate may be divided into a plurality of regions according to product requirements, the sizes of the light regions in different regions may be different, and the sizes of the light regions in the same region are the same.

(300) FIG. **12** is a schematic diagram of light-emitting units in one of light regions shown in FIG. **10**. One light region including four light-emitting units is schematically illustrated in the example shown in FIG. **12**, in which an M-sided polygon is a quadrilateral.

(301) For example, as shown in FIG. **12**, the one light region **300** may be in the shape of a square, and the M-sided polygon formed by a line connecting centers of the four light-emitting units **310** located in the light region **300** may be a square.

(302) For example, as shown in FIG. **12**, the light intensity $I_{\text{sub.1}}$ of an area **E1** may be obtained from the relation equation $I_{\text{sub.1}} = I_{\text{sub.0}} \times m \times h \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$ based on the calculation shown in FIG. **5**, where N takes a value of the number of light-emitting units in the light region, and N may be 4 as shown in FIG. **12**.

(303) In some examples, as shown in FIGS. **10** and **12**, $I_{\text{sub.0}}$, m , and h in the relation equation $I_{\text{sub.1}} = I_{\text{sub.0}} \times m \times h \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$ are considered as constants, each light region **300** of at least some light regions **300** includes N light-emitting units **310**, where $N \geq M$, and a distance from the center of an i -th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{\text{sub.i}}$, i takes a value in a range of 1 to N , and $L_{\text{sub.i}}$, P , and N satisfy: $8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.3$, where $P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$ can be used as an approximate reference value for the unitless relative light intensity at the edge position.

(304) For example, $8.3 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.5$. For example $8.1 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.6$. For example, $8.2 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.7$. For example, $8 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6$. For example, $7.9 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.9$. For example, $7.8 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7$. For example, $7.7 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.8$. For example, $7.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.1$. For example, $7.6 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.2$. For example, $7.4 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 7.3$.

(305) The vertex angle of the light region described above may refer to the area **E1** shown in FIG. **12**.

(306) For example, as shown in FIG. **12**, the light region **300** includes four light-emitting units, and a distance from the center of an i -th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{\text{sub.i}}$, where i takes a value in the range of 1 to 4, and $L_{\text{sub.i}}$, P , and N satisfy:

$8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}}) \geq 6.3$.

(307) For example, as shown in FIG. **12**, taking the pitch of the light region **300** as 4.46 mm and a side length of the quadrilateral as 2.23 mm as an example, the value of $L_{\text{sub.1}}$ is 1.123379 μm , the value of $L_{\text{sub.2}}$ is 3.363531 μm , the value of $L_{\text{sub.3}}$ is 4.149638 μm , and the value of $L_{\text{sub.4}}$ is 2.669986 μm . The parameters are substituted into $P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$ to obtain $P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + \dots + 1/L_{\text{sub.N}}) = 8.04$.

(308) For example, as shown in FIGS. **10** and **12**, the four light-emitting units **310** included in the light region **300** form a quadrilateral, and an included angle between one of the first direction and the second direction and at least one side of the quadrilateral is 12 degrees.

(309) For example, as shown in FIG. **12**, the light region **300** is in the shape of a first square, centers of the four light-emitting units **310** included in the light region **300** are sequentially connected to form a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 12 degrees.

(310) According to this embodiment of the present disclosure, the light intensity in the edge region of the light region is increased by rotating the M-sided polygon formed by the light-emitting units in the light region so that neither side of the M-sided polygon is parallel to the first direction and the second direction.

(311) In some examples, as shown in FIG. 12, a ratio of light intensity at the edge position of the light region 300, such as an area E1, to light intensity at the center position of the light region 300 is not less than 0.5.

(312) For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.9.

(313) For example, as shown in FIGS. 10 and 12, a ratio of the pitch of the light region 300 to a side length of the quadrilateral is 1.7 to 2.3. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.65 to 2.25. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.7 to 2.2. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.75 to 2.15. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.8 to 2.1. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.85 to 2.05. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.9 to 2.

(314) In some examples, as shown in FIGS. 10 and 12, at least some of the light regions 300 are in the shape of a rectangle, and two adjacent sides in the rectangle extend in the first direction and the second direction, respectively.

(315) For example, all of the light regions 300 are in the shape of a rectangle.

(316) For example, at least some of the light regions 300 are in the shape of a square.

(317) In some examples, as shown in FIGS. 10, 3A, and 12, the light intensity distribution I of the light-emitting units 310 satisfies $I = I_{\text{sub}.0} \cos m\alpha$, $I_{\text{sub}.0}$ is the light intensity distribution in the direction of the normal perpendicular to a light exit surface of the light-emitting unit 310, α is the included angle between the light emitting direction of the light-emitting unit 310 and the normal, $m = (-\ln 2) / (\ln \cos \alpha_{\text{sub}.1/2})$, $\alpha_{\text{sub}.1/2}$ is the included angle between the light emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and the optical path of the light ray emitted by the light-emitting unit 310 in the normal direction is h ; each light region 300 of the at least some of the light regions 300 includes N light-emitting units 310, where $N \geq M$, and the distance between the center of the i -th light-emitting unit 310 and the vertex angle of the light region 300 is $L_{\text{sub}.i}$, i takes a value in a range of 1 to N , and $L_{\text{sub}.i}$, h , and N satisfy: $0.5 \geq \cos m \times [(\pi/2) - (h/L_{\text{sub}.1})] + \cos m \times [(\pi/2) - (h/L_{\text{sub}.2})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub}.N})] \geq 0.23$.

(318) For example, as shown in FIGS. 10 and 12, in the case that the light-emitting unit 310 has a small emergent light angle θ , $\tan \theta \approx \theta = h/L$, $\tan \theta \approx \theta = h/L$ as well as $\alpha = (\pi/2) - \theta$ are substituted into the formula $\cos m\alpha$ to obtain $\cos m\alpha = \cos m \times [(\pi/2) - \theta] = \cos m \times [(\pi/2) - (h/L)]$. Thus, the light intensity in the area E1 shown in FIG. 12 is obtained as $I_{\text{sub}.1} = I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.1})] + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.2})] + \dots + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.N})]$, where N takes the value of the number of light-emitting units in the light region, and N may be 4 shown in FIG. 12, and then $I_{\text{sub}.1} = I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.1})] + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.2})] + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.3})] + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.N})]$.

(319) The above relation equation 2: $I_{\text{sub}.1} = I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.1})] + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.2})] + \dots + I_{\text{sub}.0} \times \cos m \times [(\pi/2) - (h/L_{\text{sub}.N})]$ may also be expressed as $I_{\text{sub}.1} = I_{\text{sub}.0} \times S$, where m is approximately equal to 1.

(320) For example, taking the pitch of the light region **300** as 4.46 mm and the pitch of the light-emitting units **310** as 2.23 mm as an example, then $S=0.285151$.

(321) For example, $0.48 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.25$.

(322) For example, $0.45 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.27$.

(323) For example, $0.42 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.28$.

(324) For example, $0.4 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.3$.

(325) For example, $0.38 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.32$.

(326) For example, $0.36 \geq \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)] \geq 0.35$.

(327) In another example of the embodiment of the present disclosure, the included angle between each of the sides of the M-sided polygon shown in FIG. **12** and the first direction or the second direction is not changed, for example, the included angle is 12 degrees, and only the pitch of the light region **300** shown in FIG. **12** and the side length of the M-sided polygon formed by the light-emitting units **310** are adjusted, for example, the pitch of the light region **300** is adjusted to be 5.12 mm, the side length of the M-sided polygon is 2.56 μm , and then the value of L.sub.1 is 1.162167 μm , the value of L.sub.2 is 4.156017 μm , the value of L.sub.3 is 5.113352 μm , and the value of L.sub.4 is 3.43394 μm .

(328) For example, the parameters are substituted into $P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + \dots + 1/L.\text{sub}.N)$ to obtain $P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + \dots + 1/L.\text{sub}.N) = 8.13$.

(329) For example, the parameters are substituted into $S = \cos m \times [(\pi/2) - (h/L.\text{sub}.1)] + \cos m \times [(\pi/2) - (h/L.\text{sub}.2)] + \dots + \cos m \times [(\pi/2) - (h/L.\text{sub}.N)]$ to obtain: $S = 0.323765$.

(330) In the backlight structure provided in the embodiment of the present disclosure, by rotating the M-sided polygon formed by the light-emitting units in the light region and adjusting the pitch of the light region and the side length of the M-sided polygon, it is beneficial to further improve the light intensity in the edge region of the light region.

(331) FIGS. **13A** to **13G** are schematic diagrams of one light region according to another example of an embodiment of the present disclosure. FIG. **14** is a relationship diagram of relative light intensity at the edge position of the light region after an M-sided polygon in the light region shown in FIGS. **13A** to **13G** respectively is rotated at different angles.

(332) The relative light intensity shown in FIG. **14** may refer to a value of Q at the edge position of the light region, where $Q = P \times (1/L.\text{sub}.1 + 1/L.\text{sub}.2 + \dots + 1/L.\text{sub}.N)$.

(333) In this embodiment of the present disclosure, the rotation of the M-sided polygon at different angles may refer to rotating the M-sided polygon at a certain angle in a certain region where the center of the M-sided polygon is located, for example, a square is rotated at a certain angle in a certain region where the center of the square is located.

(334) The rotation mentioned above may refer to rotating the M-sided polygon clockwise or rotating the M-sided polygon counterclockwise.

(335) A difference between the light region shown in FIGS. **13A** to **13G** and the light region shown in FIG. **12** is that the included angle between each side of the M-sided polygon and either of the first direction and the second direction is different.

(336) For example, an included angle between a side M1 of an M-sided polygon M01 and the first direction shown in FIG. **13A** may be 5 degrees; an included angle between a side M1 of an M-sided polygon M02 and the first direction shown in FIG. **13B** may be 10 degrees; an included angle between a side M1 of an M-sided polygon M03 and the first direction shown in FIG. **13C** may be 13 degrees; an included angle between a side M1 of an M-sided polygon M04 and the first direction shown in FIG. **13D** may be 15 degrees; an included angle between a side M1 of an M-sided polygon M05 and the first direction shown in FIG. **13E** may be 17 degrees; an included angle between a side M1 of an M-sided polygon M06 and the first direction shown in FIG. **13F** may be 20 degrees; and an included angle

between a side **M1** of an M-sided polygon **M07** and the first direction shown in FIG. **13G** may be 30 degrees.

(337) For example, an included angle between a diagonal **392** of the second square **M01** and a diagonal **391** of the first square shown in FIG. **13A** may be 5 degrees; an included angle between a diagonal **392** of the second square **M02** and the diagonal **391** of the first square shown in FIG. **13B** may be 10 degrees; an included angle between a diagonal **392** of the second square **M03** and the diagonal **391** of the first square shown in FIG. **13C** may be 13 degrees; an included angle between a diagonal **392** of the second square **M04** and the diagonal **391** of the first square shown in FIG. **13D** may be 15 degrees; an included angle between a diagonal **392** of the second square **M05** and the diagonal **391** of the first square shown in FIG. **13E** may be 17 degrees; an included angle between a diagonal **392** of the second square **M06** and the diagonal **391** of the first square shown in FIG. **13F** may be 20 degrees; and an included angle between a diagonal **392** of the second square **M07** and the diagonal **391** of the first square shown in FIG. **13G** may be 30 degrees.

(338) Certainly, this embodiment of the present disclosure is not limited to rotating the M-shaped polygon at the degrees described above, and degrees of rotation of the M-sided polygon may be selected according to the product requirements.

(339) In some examples, as shown in FIGS. **13A** to **13G** and **14**, each light region **300** of the at least some of the light regions **300** includes at least four light-emitting units **310**, the at least four light-emitting units **310** are arranged to form an M-sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M-sided polygon is 12 to 18 degrees.

(340) In some examples, as shown in FIGS. **13A** to **13G**, and FIG. **14**, each light region **300** of the at least some of the light regions **300** is in the shape of the first square, each light region **300** of the at least some of the light region **300** includes at least four light-emitting units **310**, and the centers of the four light-emitting units **310**, closest to four vertex angles of the light region **300**, among the at least four light-emitting units **310** are sequentially connected to form the second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 12 to 18 degrees.

(341) For example, as shown in FIGS. **13A** to **13G**, and FIG. **14**, each light region **300** of the at least some of the light regions **300** includes four light-emitting units **311**, **312**, **313**, and **314**, the four light-emitting units **311**, **312**, **313**, and **314** are arranged to form a quadrilateral, and an included angle between one of the first direction and the second direction and at least one side of the quadrilateral is 12 to 18 degrees.

(342) For example, as shown in FIGS. **13A** to **13G**, the light region **300** is in the shape of a first square, centers of the four light-emitting units **310** included in the light region **300** are sequentially connected to form a second square, and an included angle between a diagonal of the first square and a diagonal of the second square may be 5 degrees, 10 degrees, 13 degrees, 15 degrees, 17 degrees, 20 degrees, or 30 degrees. Certainly, this embodiment of the present disclosure is not limited to the included angle between the diagonal of the first square and the diagonal of the second square being the above-mentioned degrees, and the included angle between the diagonal of the first square and the diagonal of the second square may be selected according to the product requirements.

(343) For example, as shown in FIGS. **13A** to **13G**, a ratio of the pitch of the light region **300** to a side length of the second square is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.9 to 2.

(344) For example, as shown in FIGS. **13A** to **13G**, the light intensity at the edge of the light region **300**, such as a corner area, satisfies $I_{\text{sub.1}} = I_{\text{sub.0}} \times m \times h \times (1/L) + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}$, where a distance from the center of an i-th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{\text{sub.i}}$, the pitch P of the light region **300**, and the number N of light-emitting units **310** satisfies: $8.5 \geq P \times (1/L) + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}} \geq 6.3$.

(345) For example, as shown in FIGS. 13A to 13G, $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}})$, $8.5 \geq Q \geq 6.3$.

(346) For example, as shown in FIGS. 13A to 13G, the size of the light-emitting unit 310 may be $0.219 \text{ mm} \times 0.219 \text{ mm}$.

(347) For example, as shown in FIG. 13A to FIG. 13G and FIG. 14, for example, taking the pitch of the light region 300 as 4.8 mm, the pitch of the light-emitting unit 310 as 2.6 mm, the side length of the M-sided polygon as 2.6 mm as an example, the included angle between the side M1 of the second square and the first direction, i.e., when the included angle between the diagonal of the first square and the diagonal of the second square is 0 degrees, $Q = 6.521148$; when the included angle between the side M1 of the second square and the first direction is 5 degrees, $Q = 6.386526$; when the included angle between the side M1 of the second square and the first direction is 10 degrees, $Q = 6.353103$; when the included angle between the side M1 of the second square and the first direction is 13 degrees, $Q = 6.409105$; when the included angle between the side M1 of the second square and the first direction is 15 degrees, $Q = 6.677322$; when the included angle between the side M1 of the second square and the first direction is 17 degrees, $Q = 6.325694$; when the included angle between the side M1 of the second square and the first direction is 20 degrees, $Q = 6.161672$; and when the included angle between the side M1 of the second square and the first direction is 30 degrees, $Q = 6.117308$. Thus, the relative light intensity at the edge position of the light region becomes first larger and then smaller as the angle increases after the M-sided polygon is rotated at different angles.

(348) For example, as shown in FIG. 14, when the M-sided polygon, e.g., the second square, is rotated at an angle of 12 to 18 degrees, the value of the relative light intensity Q at the edge position of the light region is larger.

(349) In the backlight structure provided in the embodiment of the present disclosure, by adjusting the angle of the M-sided polygon formed by the arrangement of light-emitting units in the light region to a certain range, e.g., 12 to 18 degrees, and by setting the pitch of the light region and the side length of the M-sided polygon, improvement of the light intensity at the edge of the light region is facilitated, thereby improving the light emitting uniformity of the light region.

(350) For example, the included angle between the diagonal of the first square and the diagonal of the second square is 13 to 17 degrees. For example, the included angle between the diagonal of the first square and the diagonal of the second square is 14.5 to 16.5 degrees. For example, the included angle between the diagonal of the first square and the diagonal of the second square is 15 to 16 degrees.

(351) For example, as shown in FIGS. 13A to 13G, the ratio of the light intensity at the edge position of the light region 300, such as a vertex angle area, to the light intensity at the center position of the light region 300 is not less than 0.5.

(352) For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.9.

(353) FIGS. 15A to 15G are schematic diagrams of one light region according to another example of an embodiment of the present disclosure. FIG. 16 is a relationship diagram of relative light intensity at the edge position of the light region after an M-sided polygon in the light region shown in FIGS. 15A to 15G respectively is rotated at different angles.

(354) For example, an included angle between a side **M1** of an M-sided polygon **M11** and a first direction shown in FIG. **15A** may be 5 degrees, an included angle between a side **M1** of an M-sided polygon **M12** and the first direction shown in FIG. **15B** may be 10 degrees, an included angle between a side **M1** of an M-sided polygon **M13** and the first direction shown in FIG. **15C** may be 13 degrees, an included angle between a side **M1** of an M-sided polygon **M14** and the first direction shown in FIG. **15D** may be 15 degrees, an included angle between a side **M1** of an M-sided polygon **M15** and the first direction shown in FIG. **15E** may be 17 degrees, an included angle between a side **M1** of an M-sided polygon **M16** and the first direction shown in FIG. **15F** may be 20 degrees, and an included angle between a side **M1** of an M-sided polygon **M17** and the first direction shown in FIG. **15G** may be 30 degrees.

(355) For example, an included angle between a diagonal **392** of the second square **M11** and a diagonal **391** of the first square shown in FIG. **15A** may be 5 degrees, an included angle between a diagonal **392** of the second square **M12** and the diagonal **391** of the first square shown in FIG. **15B** may be 10 degrees, an included angle between a diagonal **392** of the second square **M13** and the diagonal **391** of the first square shown in FIG. **15C** may be 13 degrees, an included angle between a diagonal **392** of the second square **M14** and the diagonal **391** of the first square shown in FIG. **15D** may be 15 degrees, an included angle between a diagonal **392** of the second square **M15** and the diagonal **391** of the first square shown in FIG. **15E** may be 17 degrees, an included angle between a diagonal **392** of the second square **M16** and the diagonal **391** of the first square shown in FIG. **15F** may be 20 degrees, and an included angle between a diagonal **392** of the second square **M17** and the diagonal **391** of the first square may be 30 degrees.

(356) The relative light intensity shown in FIGS. **15A** to **15G** may refer to a value of Q at the edge position of the light region, where $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$.

(357) In this embodiment of the present disclosure, the rotation of the M-sided polygon at different angles may refer to rotating the M-sided polygon at a certain angle in a certain area where the center of the M-sided polygon is located, for example, a square is rotated at a certain angle in a certain area where the center of the square is located.

(358) The rotation mentioned above may refer to rotating the M-sided polygon clockwise or rotating the M-sided polygon counterclockwise.

(359) A difference between the light region shown in FIGS. **15A** to **15G** and the light region shown in FIGS. **13A** to **13G** includes a difference in the number of light-emitting units included in the light region, for example, the light region **300** shown in FIGS. **15A** to **15G** may include five light-emitting units **310**, e.g., $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}} + 1/L_{\text{sub.5}})$.

(360) In some examples, as shown in FIGS. **15A** to **15G** and **16**, each of the at least some of the light regions **300** includes at least four light-emitting units **310**, the at least four light-emitting units **310** are arranged to form an M-sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M-sided polygon is 12 to 18 degrees.

(361) In some examples, as shown in FIGS. **15A** to **15G**, and FIG. **16**, each light region **300** of the at least some of the light regions **300** is in the shape of a first square, each light region **300** of the at least some of the light region **300** includes at least four light-emitting units **310**, and centers of the four light-emitting units **310**, closest to four vertex angles of the light region **300**, among the at least four light-emitting units **310** are sequentially connected to form a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 12 to 18 degrees.

(362) For example, the quadrilateral formed by arranging the four light-emitting units **310** as shown in FIGS. **13A** to **13G** and the quadrilateral formed by arranging the five light-emitting units **310** as shown in FIGS. **15A** to **15G** may have the same shape and size, but without limitation, at least one of the two parameters, i.e., the shape and size, of the two may be different.

(363) In some examples, as shown in FIGS. **15A** to **15G**, the at least four light-emitting units **310** include five light-emitting units **310**, and centers of four light-emitting units **310**, located at the utmost edge, among the five light-emitting units **310** are sequentially connected to form the second square.

(364) For example, as shown in FIGS. **15A** to **15G**, each light region **300** of the at least some of the light regions **300** includes five light-emitting units **311**, **312**, **313**, **314** and **315**, the five light-emitting

units **311**, **312**, **313**, **314** and **315** are arranged to form a quadrilateral, and an included angle between one of the first direction and the second direction and at least one side of the quadrilateral is 12 to 18 degrees.

(365) For example, as shown in FIGS. **15A** to **15G**, the four light-emitting units **311**, **312**, **313**, and **314** are arranged to form a quadrilateral, and the light-emitting unit **315** is located in the center of the four light-emitting units **311**, **312**, **313**, and **314**.

(366) For example, as shown in FIGS. **15A** to **15G** and **16**, the light region **300** is in the shape of the first square, centers of the four light-emitting units **310** among the five light-emitting units **310** that are located at the utmost edge and included in the light region **300** are sequentially connected to form the second square, and an included angle between a diagonal of the first square and a diagonal of the second square may be 5 degrees, 10 degrees, 13 degrees, 15 degrees, 17 degrees, 20 degrees, or 30 degrees. Certainly, this embodiment of the present disclosure is not limited to the included angle between the diagonal of the first square and the diagonal of the second square being the above-mentioned degrees, and the included angle between the diagonal of the first square and the diagonal of the second square may be selected according to the product requirements.

(367) For example, as shown in FIGS. **15A** to **15G**, a ratio of the pitch of the light region **300** to a side length of the second square is 1.7 to 2.3. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.65 to 2.25. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.7 to 2.2. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the second square is 1.9 to 2.

(368) For example, as shown in FIGS. **15A** to **15G**, the light intensity at the edge of the light region **300**, such as a corner area, satisfies $I_{\text{sub.1}} = I_{\text{sub.0}} \times m \times h \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$, where a distance from the center of an i-th light-emitting unit **310** to a vertex angle of the light region **300** is $L_{\text{sub.i}}$, the pitch P of the light region **300**, and the number N of light-emitting units **310** satisfies: $8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.3$.

(369) For example, as shown in FIGS. **15A** to **15G**,
 $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}} + 1/L_{\text{sub.4}} + 1/L_{\text{sub.5}})$, $8.5 \geq Q \geq 6.3$.

(370) For example, as shown in FIGS. **15A** to **15G**, the size of the light-emitting unit **310** may be 0.219 mm×0.219 mm.

(371) For example, as shown in FIG. **15A** to FIG. **15G** and FIG. **16**, for example, taking the pitch of the light region **300** as 4.8 mm, the pitch of the light-emitting unit **310** as 2.6 mm, the side length of the M-sided polygon as 2.6 mm as an example, the included angle between the side **M1** of the second square and the first direction, i.e., when the included angle between the diagonal of the first square and the diagonal of the second square is 0 degrees, $Q=7.935362$; when the included angle between the side **M1** of the second square and the first direction is 5 degrees, $Q=7.80074$; when the included angle between the side **M1** of the second square and the first direction is 10 degrees, $Q=7.767317$; when the included angle between the side **M1** of the second square and the first direction is 13 degrees, $Q=7.823319$; when the included angle between the side **M1** of the second square and the first direction is 15 degrees, $Q=8.091537$; when the included angle between the side **M1** of the second square and the first direction is 17 degrees, $Q=7.739908$; when the included angle between the side **M1** of the second square and the first direction is 20 degrees, $Q=7.575887$; and when the included angle between the side **M1** of the second square and the first direction is 30 degrees, $Q=7.531522$. Thus, the relative light intensity at the edge position of the light region becomes first larger and then smaller as the angle increases after the M-sided polygon is rotated at different angles.

(372) For example, as shown in FIG. **16**, when the M-sided polygon, e.g., the second square, is rotated at an angle of 12 to 18 degrees, the value of the relative light intensity Q at the edge position of the light region is larger.

(373) In the backlight structure provided in the embodiment of the present disclosure, by adjusting the angle of the M-sided polygon formed by the arrangement of light-emitting units in the light region to a

certain range, e.g., 12 to 18 degrees, and by setting the number of the light-emitting units in the light region, the pitch of the light region and the side length of the M-sided polygon, improvement of the light intensity at the edge of the light region is facilitated, thereby improving the light emitting uniformity of the light region.

(374) For example, as shown in FIGS. 14 and 16, when the number of light-emitting units 310 disposed in the light region 300 is five, the light intensity at the edge position of the light region 300, such as the vertex angle position, is greater than the light intensity at the edge position of the light region 300 when the number of light-emitting units 310 in the light region 300 is four.

(375) For example, the included angle between the diagonal of the first square and the diagonal of the second square is 13 to 17 degrees. For example, the included angle between the diagonal of the first square and the diagonal of the second square is 14.5 to 16.5 degrees. For example, the included angle between the diagonal of the first square and the diagonal of the second square is 15 to 16 degrees.

(376) For example, as shown in FIGS. 15A to 15G, the ratio of the light intensity at the edge position of the light region 300, such as a vertex angle area, to the light intensity at the center position of the light region 300 is not less than 0.5.

(377) For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.9.

(378) For example, the size, material and other parameters of the barrier wall in the example shown in FIGS. 15A to 15G may be the same as the corresponding parameters in the above example and will not be repeated herein.

(379) FIGS. 17A to 17G are schematic diagrams of one light region according to another example of an embodiment of the present disclosure. FIG. 18 is a relationship diagram of relative light intensity at the edge position of a light region after an M-sided polygon in the light region shown in FIGS. 17A to 17G respectively is rotated at different angles.

(380) For example, an included angle between a side M2 of a triangle M21 and a first direction shown in FIG. 17A may be 5 degrees, an included angle between a side M2 of a triangle M22 and the first direction shown in FIG. 17B may be 10 degrees, an included angle between a side M2 of a triangle M23 and the first direction shown in FIG. 17C may be 13 degrees, an included angle between a side M2 of a triangle M24 and the first direction shown in FIG. 17D may be 15 degrees, an included angle between a side M2 of a triangle M25 and the first direction shown in FIG. 17E may be 17 degrees, an included angle between a side M2 of a triangle M26 and the first direction shown in FIG. 17F may be 20 degrees, and an included angle between a side M2 of a triangle M27 and the first direction shown in FIG. 17G may be 30 degrees. Certainly, this embodiment of the present disclosure is not limited to the included angle between one side of the triangle and the first direction being the above mentioned degrees, and the included angle between the side of the triangle and the first direction may be selected according to the product requirements.

(381) The relative light intensity shown in FIGS. 17A to 17G may refer to the value of Q at the edge position of the light region, where $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$.

(382) In this embodiment of the present disclosure, the rotation of the M-sided polygon at different angles may refer to rotating the M-sided polygon at a certain angle in a certain area where the center of

the triangle is located, for example, a triangle is rotated by a certain angle in a certain area where the center of the triangle is located.

(383) The rotation mentioned above may refer to rotating the M-sided polygon clockwise or rotating the M-sided polygon counterclockwise.

(384) A difference between the light region shown in FIG. 17A to FIG. 17G and the light region shown in FIG. 13A to FIG. 13G and FIG. 15A to FIG. 15G is that the M-sided polygons are different in shape, e.g., the M-sided polygon shown in FIG. 17A to FIG. 17G may be a triangle.

(385) In some examples, as shown in FIGS. 17A to 17G, each light region 300 of at least some of the light regions 300 includes three light-emitting units 311, 312, and 313, centers of the three light-emitting units 311, 312, and 313 are sequentially connected to form a triangle, and an included angle between one of the first direction and the second direction and one side M2 of the triangle is less than 5 degrees.

(386) For example, as shown in FIGS. 17A to 17G, a ratio of the pitch of the light region 300 to a side length of the triangle is 1.7 to 2.3. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.65 to 2.25. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.7 to 2.2. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.75 to 2.15. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.8 to 2.1. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.85 to 2.05. For example, the ratio of the pitch of the light region 300 to the side length of the triangle is 1.9 to 2.

(387) For example, as shown in FIGS. 17A to 17G, the light intensity at the edge of the light region 300, such as a corner area, satisfies $I_{\text{sub.1}} = I_{\text{sub.0}} \times m \times h \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}})$, where a distance from the center of an i-th light-emitting unit 310 to a vertex angle of the light region 300 is $L_{\text{sub.i}}$, the pitch P of the light region 300, and the number N of light-emitting units 310 satisfies: $8.5 \geq P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + \dots + 1/L_{\text{sub.N}}) \geq 6.3$.

(388) For example, as shown in FIGS. 17A to 17G, $Q = P \times (1/L_{\text{sub.1}} + 1/L_{\text{sub.2}} + 1/L_{\text{sub.3}})$, $8.5 \geq Q \geq 6.3$.

(389) For example, as shown in FIGS. 17A to 17G, the size of the light-emitting unit 310 may be 0.219 mm×0.219 mm.

(390) For example, as shown in FIGS. 17A to 17G and FIG. 18, taking the pitch of the light region 300 as 4.8 mm, the pitch of the light-emitting unit 310 as 2.6 mm, and the side length of the M-sided polygon as 2.6 mm as an example, when the included angle between the side M2 of the triangle and the first direction is 0 degrees, $Q = 3.926995$; when the included angle between the side M2 of the triangle and the first direction is 5 degrees, $Q = 3.880136$; when the included angle between side M2 of the triangle and the first direction is 10 degrees, $Q = 3.840027$; when the included angle between side M2 of the triangle and the first direction is 13 degrees, $Q = 3.82151$; when the included angle between side M2 of the triangle and the first direction is 15 degrees, $Q = 3.811524$; when the included angle between side M2 of the triangle and the first direction is 17 degrees, $Q = 3.803458$ degrees; when the included angle between side M2 of the triangle and the first direction is 20 degrees, $Q = 3.794941$; and when the included angle between side M2 of the triangle and the first direction is 30 degrees, $Q = 3.797286$. Thus, the relative light intensity at the edge position of the light region is reduced gradually as the angle increases after the M-sided polygon is rotated at different angles.

(391) The included angle between one of the first direction and the second direction and one side M2 of the triangle is set to be small, which is conducive to increasing the light intensity at the edge position of the light region, thereby improving the light emitting uniformity of the light region.

(392) For example, as shown in FIGS. 17A to 17G, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 4.5 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 4 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 3.5 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 3 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 2.5 degrees. For example, the included angle between the first direction or the second direction and the side

M2 of the triangle is less than 2 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 1.5 degrees. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 1 degree. For example, the included angle between the first direction or the second direction and the side M2 of the triangle is less than 0.5 degrees.

(393) For example, as shown in FIGS. 17A to 17G, the ratio of the light intensity at the edge position of the light region 300, such as a vertex angle area, to the light intensity at the center position of the light region 300 is not less than 0.5.

(394) For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region 300 to the light intensity at the center position of the light region 300 is not less than 0.9.

(395) For example, the size, material and other parameters of the barrier wall in the example shown in FIGS. 17A to 17G may be the same as the corresponding parameters in the above example and will not be repeated herein.

(396) FIG. 19 is a schematic diagram of the distribution of light-emitting units in one light region in different examples of an embodiment of the present disclosure.

(397) For example, the at least one light region 300 in the example shown in FIG. 19 includes nine light-emitting units 311, 312, 313, 314, 315, 316, 317, 318, and 319, centers of the four light-emitting units 311, 312, 313, and 314 among them are sequentially connected to form a quadrilateral, or the nine light-emitting units 311, 312, 313, 314, 315, 316, 317, 318, and 319 are arranged to form a quadrilateral, and an included angle between at least one of the first direction and the second direction and at least one side of the quadrilateral is 0 degrees.

(398) The four light-emitting units 311, 312, 313, and 314 may be the four light-emitting units located outermost, or may be the four light-emitting units closest to vertex angles of the light region.

(399) For example, as shown in FIG. 19, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 0.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 1 degree. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 2 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 3 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 4 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 5.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 6 degrees. For example, the included angle between the first direction and each side of the

M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 6.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 7 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 8 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 9 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 10 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 10.5 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 11 degrees. For example, the included angle between the first direction and each side of the M-sided polygon as well as between the second direction and each side of the M-sided polygon is greater than 12 degrees.

(400) For example, as shown in FIG. 19, the included angle between a side M1 of the M-sided polygon and the first direction is 12 to 18 degrees. For example, the included angle between the side M1 of the M-sided polygon and the first direction is 12.5 to 17.5 degrees. For example, the included angle between the side M1 of the M-sided polygon and the first direction is 13 to 17 degrees. For example, the included angle between the side M1 of the M-sided polygon and the first direction is 13.5 to 16.5 degrees. For example, the included angle between the side M1 of the M-sided polygon and the first direction is 14 to 16 degrees. For example, the included angle between the side M1 of the M-sided polygon and the first direction is 14.5 to 15 degrees.

(401) For example, as shown in FIG. 19, the light region 300 includes nine light-emitting units, and a distance from the center of an i-th light-emitting unit 310 to a vertex angle of the light region 300 is $L_{sub.i}$, where i takes a value in the range of 1 to 9, and $L_{sub.i}$, P, and N satisfy:

$$8.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.3.$$

(402) For example,

$$8.3 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.5.$$

(403) For example,

$$8.1 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.6.$$

(404) For example,

$$8.2 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.7.$$

(405) For example,

$$8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.$$

(406) For example,

$$7.9 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.9.$$

(407) For example,

$$7.8 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 7.$$

(408) For example,

$$7.7 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 6.8.$$

(409) For example,

$$7.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 7.1.$$

(410) For example,

$$7.6 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 7.2.$$

(411) For example,

$$7.4 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + 1/L_{sub.3} + 1/L_{sub.4} + 1/L_{sub.5} + 1/L_{sub.6} + 1/L_{sub.7} + 1/L_{sub.8} + 1/L_{sub.9}) \geq 7.3.$$

(412) For example, as shown in FIG. 19, a ratio of the pitch of the light region 300 to a side length of the quadrilateral is 1.7 to 2.3. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.65 to 2.25. For example, the ratio of the pitch of the light region 300 to the side length of the quadrilateral is 1.7 to 2.2. For example, the ratio of the pitch of the light region

300 to the side length of the quadrilateral is 1.75 to 2.15. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.8 to 2.1. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.85 to 2.05. For example, the ratio of the pitch of the light region **300** to the side length of the quadrilateral is 1.9 to 2.

(413) For example, as shown in FIG. **19**, the nine light-emitting units **311**, **312**, **313**, **314**, **315**, **316**, **317**, **318**, and **319** may be evenly distributed.

(414) For example, the light-emitting unit **315** may be located in the center of the quadrilateral formed of the four light-emitting units **311**, **312**, **313**, and **314**.

(415) For example, as shown in FIG. **19**, the light-emitting unit **318** may be located between the light-emitting unit **311** and the light-emitting unit **314**, the light-emitting unit **319** may be located between the light-emitting unit **313** and the light-emitting unit **314**, the light-emitting unit **317** may be located between the light-emitting unit **313** and the light-emitting unit **312**, and the light-emitting unit **316** may be located between the light-emitting unit **312** and the light-emitting unit **311**.

(416) For example, four sides of the quadrilateral pass through the centers of the light-emitting units **318**, **319**, **317**, and **316**, respectively.

(417) For example, the centers of the light-emitting units **318**, **319**, **317**, and **316** may be the centers of the four sides of the quadrilateral, respectively.

(418) For example, as shown in FIG. **19**, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a rectangle.

(419) For example, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be a square.

(420) For example, an included angle between each of two sides of the quadrilateral and the first direction is greater than 0 degrees, and an included angle between each of the other two sides of the quadrilateral and the second direction is greater than 0 degrees.

(421) For example, as shown in FIG. **7**, the light region **300** is in the shape of the first square, the quadrilateral formed by connecting the centers of the four light-emitting units **311**, **312**, **313**, and **314** sequentially may be the second square, and the included angle between a diagonal of the first square and a diagonal of the second square is greater than 0 degrees.

(422) For example, as shown in FIG. **19**, the ratio of the light intensity at the edge position of the light region **300**, such as a vertex angle area, to the light intensity at the center position of the light region **300** is not less than 0.5.

(423) For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.55. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.6. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.65. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.7. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.75. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.8. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.85. For example, the ratio of the light intensity at the edge position of the light region **300** to the light intensity at the center position of the light region **300** is not less than 0.9.

(424) For example, parameters such as the size and material of the barrier wall and the size of the light-emitting units in the example shown in FIG. **19** may be the same as the corresponding parameters in the above example and will not be repeated herein.

(425) This embodiment of the present disclosure is not limited to the shape of the light region being the rectangle as shown in FIGS. **1** to **19**. For example, the shape of the light region may be designed according to the needs of a display panel corresponding to the backlight structure. For example, the light region may be in the shape of a hexagon or octagon or the like.

(426) This embodiment of the present disclosure is not limited to the number of light-emitting units in the light region being three, four, five, seven, or nine as shown in FIGS. **1** to **19**. The number can be set according to the position and size of the light-emitting units, for example, the number of light-emitting units in the light region may be six, eight, ten, eleven, twelve, etc.

(427) In the backlight structure provided in the embodiment of the present disclosure, the number of light-emitting units in the light region, the side length of the M-sided polygon, the pitch of the light region, and the included angle between the side of the M-sided polygon and the first direction or the second direction are set in a coordinated manner, which is conducive to increasing the light intensity at the edge position of the light region, thereby improving the light emitting uniformity of the light region.

(428) FIG. **20** is a schematic diagram of a partial cross-section cut along line AA' shown in FIG. **1** according to another example of an embodiment of the present disclosure. FIG. **21** is a schematic diagram of a partial cross-section cut along line BB' shown in FIG. **10** according to another example of an embodiment of the present disclosure.

(429) In some examples, as shown in FIGS. **20** and **21**, the backlight structure further includes a flat adhesive **400** located between a barrier wall **220** and each light-emitting unit **310**, and between two adjacent light-emitting units **310**. A thickness of the flat adhesive **400** is not less than a height of the light-emitting unit **310** and is less than a thickness of the barrier wall **220**. An orthographic projection, on the substrate **100**, of a surface of one side of the flat adhesive **400** close to the substrate **100** is completely located in an orthographic projection, on the substrate **100**, of a surface of one side of the flat adhesive **400** away from the substrate **100**.

(430) For example, as shown in FIGS. **20** and **21**, the flat adhesive **400** may fill at least a portion of a gap between the barrier wall **220** and the light-emitting unit **310**, and at least a portion of a gap between adjacent light-emitting units **310**.

(431) For example, as shown in FIGS. **20** and **21**, the thickness of the flat adhesive **400** may be greater than or equal to the height of the light-emitting unit **310**.

(432) For example, as shown in FIGS. **20** and **21**, the flat adhesive **400** may be made of white oil. For example, the thickness of the flat adhesive **400** may be 50 μm . For example, the thickness of the flat adhesive **400** may be greater than 90 μm . For example, the thickness of the flat glue **400** may be less than 250 μm . For example, the thickness of the flat glue **400** may be less than 200 μm . For example, the thickness of the flat glue **400** may be less than 180 μm . For example, the thickness of the flat glue **400** may be less than 150 μm . For example, the thickness of the flat glue **400** may be less than 120 μm . For example, the thickness of the flat glue **400** may be less than 100 μm .

(433) In some examples, as shown in FIGS. **20** and **21**, the cross section of the flat adhesive **400** intercepted by a plane (e.g. plane XZ) where a line connecting centers of the two adjacent light-emitting units **310** is located is in the shape of a trapezoid, a length of a first base side **410** of the trapezoid away from the substrate **100** is greater than a length of a second base side **420** of the trapezoid close to the substrate **100**, a distance between endpoints, close to each other, of an orthographic projection of the first base side **410** and an orthographic projection of the second base side **420** on the substrate **100** is 17 to 32 μm , and the plane where the line connecting centers of the two adjacent light-emitting units **310** is located is perpendicular to the substrate **100**.

(434) For example, as shown in FIGS. **20** and **21**, the line connecting centers of the first base side **410** and the second base side **420** is perpendicular to the substrate **100**. For example, a length difference between the first base side **410** and the second base side **420** on one side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 17 to 32 μm .

(435) For example, a difference in thickness of the flat adhesive **400** at different positions may be less than 10% of the maximum thickness of the flat adhesive **400**. For example, the difference in thickness of the flat adhesive **400** at different positions may be less than 8% of the maximum thickness of the flat adhesive **400**.

(436) For example, the thickness of the flat adhesive **400** is 49.79 μm , the length difference between the first base side **410** and the second base side **420** on one side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 28.93 μm , and the length difference between the first base side **410** and the second base side **420** on the other side of the center line, perpendicular to the substrate **100**,

of the trapezoid may be 30.9 μm .

(437) For example, the thickness of the flat adhesive **400** is 47.29 μm , the length difference between the first base side **410** and the second base side **420** on one side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 26.3 μm , and the length difference between the first base side **410** and the second base side **420** on the other side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 29.59 μm .

(438) For example, the thickness of the flat adhesive **400** is 51.28 μm , the length difference between the first base side **410** and the second base side **420** on one side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 18.41 μm , and the length difference between the first base side **410** and the second base side **420** on the other side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 26.96 μm .

(439) For example, the thickness of the flat adhesive **400** is 51.94 μm , the length difference between the first base side **410** and the second base side **420** on one side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 26.3 μm , and the length difference between the first base side **410** and the second base side **420** on the other side of the center line, perpendicular to the substrate **100**, of the trapezoid may be 27.61 μm .

(440) In the backlight structure of the present disclosure, the cross-section of the flat adhesive is set to be a trapezoid, such as an undercut structure, so it is possible to prevent the flat adhesive from eroding the pad electrically connected to the light-emitting unit (e.g., the pad **321** shown in FIG. 2A) when the flat adhesive is subjected to heat extension, and moreover, it is possible to prevent changes in light emitting characteristics due to different refractive indexes caused when light rays emitted by the light-emitting unit exit through the flat adhesive.

(441) FIG. 22 is a schematic diagram of a partial cross-sectional structure cut along line BB' shown in FIG. 10 according to another example of an embodiment of the present disclosure.

(442) In some examples, as shown in FIG. 22, the substrate **100** is provided with a thermally conductive adhesive **500** on one side of the substrate **100** away from the light-emitting units **310**, and the thermally conductive adhesive **500** is provided with at least one hole **501**.

(443) For example, as shown in FIG. 22, the black thermally conductive adhesive having a thickness of less than 1 μm is adhered to the entire side of the substrate **100** away from the light-emitting units **310** to play a role in heat dissipation.

(444) For example, as shown in FIG. 22, the hole **501** may have a diameter of 1.5 mm. For example, the number of holes **501** may be greater than 100, such as 29*18. The holes are provided in the thermally conductive adhesive, which helps to exhaust when the thermally conductive adhesive adheres to the substrate to prevent the thermally conductive adhesive from wrinkling.

(445) For example, the side of the substrate **100** away from the light-emitting unit **310** may also be provided with a grounding conductor, such as a copper conductor. For example, the copper conductor may have a length of 0.45 mm.

(446) For example, the side of the substrate **100** facing the light-emitting units **310** may also be provided with a flat adhesive having a thickness of 0.3 μm . For example, a white dam may be provided at the periphery of each light region, e.g., the white dam may have a width of 0.5 mm and a height of 0.25 mm, in order to play a role in increasing the brightness and improving the halo effect.

(447) FIG. 23 is a schematic diagram of a partial cross-section of the backlight structure including the substrate, the barrier wall, and light-emitting units shown in FIG. 11.

(448) In some examples, as shown in FIG. 23, the backlight structure further includes a light diffusion structure **610** located on a side of the light-emitting unit **310** away from the substrate **100**. The light diffusion structure **610** includes at least one layer of diffusion film. For example, the light diffusion structure **610** includes three layers of diffusion films **611**, **612**, and **613**, each of which has a thickness of 0.05 to 0.2 mm.

(449) For example, the different diffusion films may have the same or different thickness.

(450) For example, as shown in FIG. 23, the thickness of the diffusion film **611** is 0.12 mm, the thickness of the diffusion film **612** is 0.13 mm, and the thickness of the diffusion film **613** is 0.13 mm. For example, the thickness of the diffusion film **611** is 0.085 mm, the thickness of the diffusion film **612**

is 0.19 mm, and the thickness of the diffusion film **613** is 0.14 mm. For example, the three diffusion films **611**, **612**, and **613** may all have a thickness of 0.19 mm. For example, the weight of the diffusion film may be 14.7 g. For example, the weight of the diffusion film **611** is 10.25 g, the weight of the diffusion film **612** is 14.31 g, and the weight of the diffusion film **613** is 20.5 g.

(451) In some embodiments, as shown in FIG. **23**, the backlight structure further includes a color conversion structure **620** located on a side of the light diffusion structure **610** away from the light-emitting unit **310**. The color conversion structure **620** includes a color conversion film **622** configured to convert first color light into second color light, the first color light includes blue light, and the second color light includes at least one of red light and green light. For example, the color conversion film converts the blue light to the red light. For example, the color conversion film converts the blue light to the green light.

(452) In some examples, as shown in FIG. **23**, the color conversion structure **620** further includes a prism **623** located on a side of the color conversion film **622** away from the light-emitting units **310**.

(453) For example, the prism **623** may have a total thickness of 0.2 mm, and the prism **623** includes a plurality of sub-prisms. Each sub-prism may have a length of 39 μm , a width of 39 μm , and a height of 17 μm .

(454) For example, a ratio of the pitch of the sub-prisms to the pitch of the light-emitting units is greater than 100 and less than 150.

(455) For example, as shown in FIG. **23**, the color conversion structure **620** further includes a fluorescent powder composite film **621** located on a side of the color conversion film **622** close to the substrate **100**.

(456) For example, as shown in FIG. **23**, a thickness of the color conversion structure **620** may be 0.2 to 0.4 mm. For example, the thickness of the color conversion structure **620** may be 0.21 mm. For example, the thickness of the color conversion structure **620** may be 0.27 mm. For example, the thickness of the color conversion structure **620** may be 0.308 mm. For example, the weight of the color conversion structure **620** may be 27 g. For example, the weight of the color conversion structure **620** may be 30.78 g.

(457) In some examples, as shown in FIG. **23**, the backlight structure further includes a prism structure **630** located on a side of the color conversion structure **620** away from the light-emitting units **310**. The prism structure **630** includes at least one prism layer, and the prism layer has a thickness of 0.05 to 0.2 mm.

(458) For example, as shown in FIG. **23**, the prism structure **630** includes a prism layer **631** and a prism layer **632**. For example, the thicknesses of the prism layer **631** and the prism layer **632** may be the same or different.

(459) For example, as shown in FIG. **23**, the prism layer **631** may have a thickness of 0.1 mm and the prism layer **632** may have a thickness of 0.11 mm. For example, the thickness of the prism layer **631** may be 0.09 mm and the thickness of the prism layer **632** may be 0.24 mm.

(460) For example, the prism structure **630** may further include only one prism layer. The prism layer may have a thickness of 0.16 mm.

(461) For example, the backlight structure may further include a diffusion plate (not shown in the figure) located on a side of the prism structure **630** away from the substrate **100**.

(462) FIG. **24** is a schematic diagram of a partial cross-sectional structure of a display device according to another embodiment of the present disclosure. As shown in FIG. **24**, the display device includes a display panel **1000** and a backlight structure **2000**, and the display panel **1000** is located on a light exit side of the backlight structure **2000**.

(463) The backlight structure in the display device provided in the present disclosure may be any of the backlight structures provided in the above embodiments, the number of light-emitting units in the light region, the side length of the M-sided polygon, the pitch of the light region, and the included angle between the side of the M-sided polygon and the first direction or the second direction are set in a coordinated manner, which is conducive to increasing the light intensity at the edge position of the light region, thereby improving the light emitting uniformity of the light region.

(464) For example, as shown in FIG. **24**, the backlight structure **2000** further includes a diffusion plate

650 located on one side of the prism structure **630** away from the substrate **100**. For example, the diffusion plate **650** may have a thickness of 0.24 mm. For example, the diffusion plate **650** may have a weight of 15.2 g.

(465) For example, as shown in FIG. 24, the display panel **1000** may be a liquid crystal display panel. The liquid crystal display panel may include an array substrate **1003**, an opposite substrate **1002**, and a liquid crystal layer (not shown) located between the array substrate **1003** and the opposite substrate **1002**.

(466) For example, one side of the array substrate **1003** facing toward the opposite substrate **1002** may include a plurality of gate lines extending in one direction and a plurality of data lines extending in another direction. The plurality of gate lines and the plurality of data lines intersect to define a plurality of pixel units in an array arrangement. The plurality of pixel units may be arranged as a pixel array. Each pixel unit may include a pixel electrode and a thin-film transistor. The gate lines are connected to gates of the thin-film transistors to control on or off of the thin-film transistors. The pixel electrode is connected to one of source and drain electrodes of the thin-film transistor. The data line is connected to the other of the source and drain electrodes of the thin-film transistor. The data lines input voltage signals required for image displaying to the pixel electrode through the thin-film transistor to realize displaying of the array substrate.

(467) For example, the opposite substrate **1002** may be a color film substrate, and a color film layer corresponding to the pixel units and a black matrix covering the structures such as the gate lines and the data lines that are located in a non-display area may be provided on a side of the color film substrate facing toward the array substrate **1003**. For example, a common electrode disposed opposite the pixel electrode may also be provided on the side of the color film substrate facing toward the array substrate **1003**. The common electrode is configured to apply a common voltage to generate an electric field with the pixel electrode to drive the deflection of liquid crystal molecules in the liquid crystal layer. The liquid crystal molecules are deflected to change the transmittance of the liquid crystal layer, thereby realizing displaying of a desired grayscale image.

(468) For example, as shown in FIG. 24, the display panel **1000** may further include a first polarizer **1004** disposed on a side of the array substrate **1003** away from the opposite substrate **1002** and a second polarizer **1001** disposed on a side of the opposite substrate **1002** away from the array substrate **1003**. The first polarizer **1004** includes a light transmission axis extending in a direction DI1 and polarizes backlight incident thereon in the direction DI1. The second polarizer **1001** includes a light transmission axis extending in a direction DI2 and polarizes a light ray incident thereon in the direction DI2. For example, the light transmission axis of the first polarizer **1004** and the light transmission axis of the second polarizer **1001** are perpendicular to each other.

(469) For example, as shown in FIG. 24, the display device further includes a plastic frame **3002**. The plastic frame **3002** is used for supporting the display panel **1000**.

(470) For example, as shown in FIG. 24, the display device further includes a support frame **3001**. The support frame **3001** includes an integrated structure of an outer frame and a back frame. The support frame is used for supporting the plastic frame **3002** and the backlight structure **2000**.

(471) For example, as shown in FIG. 24, the display device further includes a fixing adhesive **640** disposed on a side of the thermally conductive adhesive **500** away from a light plate **123** that includes a substrate, light-emitting units, and a barrier wall pattern, and the other structures. The fixing adhesive **640** is used for fixing the backlight structure **2000** to the support frame **3001**.

(472) For example, as shown in FIG. 24, a thickness of the second polarizer **1001** may be 0.28 mm. For example, a thickness of the opposite substrate **1002** may be 0.25 mm. For example, a thickness of the array substrate **1003** may be 0.25 mm. For example, a thickness of the first polarizer **1004** may be 0.11 mm. For example, the sum of weights of the second polarizer **1001**, the opposite substrate **1002**, the array substrate **1003**, and the first polarizer **1004** may be 159.3 g.

(473) For example, as shown in FIG. 24, the thickness of the second polarizer **1001** may be 0.122 mm. For example, the thickness of the opposite substrate **1002** may be 0.2 mm. For example, the thickness of the array substrate **1003** may be 0.2 mm. For example, the thickness of the first polarizer **1004** may be 0.087 mm. For example, the sum of the weights of the second polarizer **1001**, the opposite substrate

1002, the array substrate **1003**, and the first polarizer **1004** may be 105.47 g.

(474) For example, as shown in FIG. 24, the thickness of the light plate **123** may be 0.27 mm, and a light plate protection adhesive is provided between the light plate **123** and the thermally conductive adhesive **500**. For example, the thickness of the light plate protection adhesive may be 0.31 mm, and the thickness of the thermally conductive adhesive **500** may be 0.09 mm, and the total weight of the light plate, the light plate protection adhesive, and the thermally conductive adhesive may be 76.6 g.

(475) For example, as shown in FIG. 24, the thickness of the light plate **123** may be 0.25 mm, and the side of the light plate **123** away from the light diffusing structure **610** may be provided with only the light plate protection adhesive, and no longer be provided with the thermally conductive adhesive. For example, the thickness of the light plate protection adhesive may be 0.1 mm, and the total weight of the light plate and the light plate protection adhesive may be 41.41 g.

(476) For example, as shown in FIG. 24, the thickness of the fixing adhesive **640** may be 0.03 mm in the case that the thermally conductive adhesive **500** is provided. For example, in the case that the thermally conductive adhesive **500** is not provided, the thickness of the fixing adhesive **640** may be 0.1 mm.

(477) The following statements should be noted:

(478) (1) The accompanying drawings involve only the structure(s) in connection with the embodiment(s) of the present disclosure, and other structure(s) can be referred to common design(s).

(479) (2) In case of no conflict, features in one embodiment or in different embodiments can be combined.

(480) What have been described above are only specific implementations of the present disclosure, the protection scope of the present disclosure is not limited thereto. The protection scope of the present disclosure should be based on the protection scope of the claims.

Claims

1. A backlight structure, comprising: a substrate; a barrier wall pattern, located on the substrate, and comprising a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings being configured to define a plurality of light regions, and the first direction intersecting the second direction; and a plurality of light-emitting units, located on the substrate, and distributed in the plurality of light regions, wherein the substrate comprises a central region and an edge region surrounding the central region, each light region at least in the central region is provided with at least three light-emitting units, centers of M light-emitting units, closest to vertex angles of the light region, among the at least three light-emitting units are sequentially connected to form an M-sided polygon, and a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, and an included angle between the first direction and each side of the M-sided polygon and an included angle between the second direction and each side of the M-sided polygon are both greater than 0 degrees.

2. The backlight structure according to claim 1, wherein a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch of the light region to a side length of the M-sided polygon is 1.7 to 2.3.

3. The backlight structure according to claim 2, wherein the pitch of the light region is P, each of at least some of the light regions comprises N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-emitting unit to a vertex angle of the light region is $L_{sub.i}$, i takes a value in the range from 1 to N, and $L_{sub.i}$, P, and N satisfy: $8.5 \geq P \times (1/L_{sub.1} + 1/L_{sub.2} + \dots + 1/L_{sub.N}) \geq 6.3$.

4. The backlight structure according to claim 2, wherein a light intensity distribution I of the light-emitting unit satisfies: $I = I_{sub.0} \cos m\alpha$, $I_{sub.0}$ is the light intensity distribution along a direction of a normal perpendicular to a light exit surface of the light-emitting unit, α is an included angle between a light-emitting direction of the light-emitting unit and the normal, $m = (-\ln_{sub.2}) / (\ln_{sub.1} / 2)$, $\alpha_{sub.1/2}$ is an included angle between the light-emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and a light ray emitted by the light-emitting unit has an optical path of h in the normal direction; and each of the at

least some of the light regions comprises N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N, and $L_{\text{sub},i}$, h, and N satisfy:

$$0.5 \geq \{\cos m \times [(\pi/2) - (h/L_{\text{sub},1})] + \cos m \times [(\pi/2) - (h/L_{\text{sub},2})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub},N})]\} \geq 0.23.$$

5. The backlight structure according to claim 2, wherein a ratio of a light intensity at an edge position of the light region to a light intensity at a center position of the light region is not less than 0.5.

6. The backlight structure according to claim 2, wherein each of the at least some of the light regions comprises at least four light-emitting units, the at least four light-emitting units are arranged to form the M-sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M-sided polygon is 12 to 18 degrees.

7. The backlight structure according to claim 6, wherein each of the at least some of the light regions is in a shape of a first square, each of the at least some of the light regions comprises at least four light-emitting units, the M-sided polygon is a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 12 to 18 degrees.

8. The backlight structure according to claim 1, wherein at least some of the light regions are in a shape of a rectangle, and two adjacent sides of the rectangle extend along the first direction and the second direction, respectively.

9. The backlight structure according to claim 1, wherein the light-emitting units disposed in each light region are electrically connected, and the barrier wall comprises a shading material.

10. The backlight structure according to claim 1, wherein the light-emitting unit comprises a light-emitting diode chip and an encapsulation structure configured to encapsulate the light-emitting diode chip, and there is a spacing between encapsulation structures of adjacent light-emitting units.

11. The backlight structure according to claim 10, wherein a maximum size of the light-emitting unit in a direction parallel to the substrate is not greater than 500 μm .

12. The backlight structure according to claim 7, wherein the at least four light-emitting units comprise four light-emitting units, and centers of the four light-emitting units are sequentially connected to form the second square.

13. The backlight structure according to claim 7, wherein the at least four light-emitting units comprise five light-emitting units, and centers of four light-emitting units, located at outermost edges, of the five light-emitting units are sequentially connected to form the second square.

14. The backlight structure according to claim 2, wherein each of the at least some of the light regions comprises three light-emitting units, centers of the three light-emitting units are sequentially connected to form a triangle, and an included angle between one of the first direction and the second direction and one side of the triangle is less than 5 degrees.

15. A display device, comprising: a display panel, and a backlight structure according to claim 1, wherein the display panel is located on a light exit side of the backlight structure.

16. A backlight structure, comprising: a substrate; a barrier wall pattern, located on the substrate, and comprising a plurality of openings arrayed along a first direction and a second direction and a barrier wall surrounding the openings, the plurality of openings being configured to define a plurality of light regions, and the first direction intersecting the second direction; and a plurality of light-emitting units, located on the substrate, and distributed in the plurality of light regions, wherein at least three light-emitting units are disposed in each of at least some light regions, centers of M light-emitting units of the at least three light-emitting units closest to vertex angles of the light region are sequentially connected to form an M-sided polygon, a distance between a center of the M-sided polygon and a center of the light region is less than 10% of a pitch of the light region, a ratio of lengths of different sides of the M-sided polygon is 0.9 to 1.1, and a ratio of the pitch of the light region to a side length of the M-sided polygon is 1.7 to 2.3; and at least one side of the M-sided polygon is parallel to at least one of the first direction and the second direction.

17. The backlight structure according to claim 16, wherein each of the at least some of the light regions comprises N light-emitting units, where $N \geq M$, a distance from a center of an i-th light-emitting unit to a vertex angle of the light region is $L_{\text{sub},i}$, i takes a value in the range from 1 to N, and $L_{\text{sub},i}$, P, and N satisfy: $8.5 \geq P \times (1/L_{\text{sub},1} + 1/L_{\text{sub},2} + \dots + 1/L_{\text{sub},N}) \geq 6.3$.

18. The backlight structure according to claim 16, wherein a light intensity distribution I of the light-emitting unit satisfies: $I = I_{\text{sub}0} \cos m\alpha$, $I_{\text{sub}0}$ is the light intensity distribution along a direction of a normal perpendicular to a light exit surface of the light-emitting unit, α is an included angle between a light-emitting direction of the light-emitting unit and the normal, $m = (-\ln I_{\text{sub}2}) / (\ln \cos \alpha_{\text{sub}1/2})$, $\alpha_{\text{sub}1/2}$ is an included angle between the light-emitting direction and the normal when the light intensity is reduced to half of the light intensity corresponding to the normal direction, and a light ray emitted by the light-emitting unit has an optical path of h in the normal direction; and each of the at least some of the light regions comprises N light-emitting units, where $N \geq M$, a distance from a center of an i -th light-emitting unit to a vertex angle of the light region is $L_{\text{sub}i}$, i takes a value in the range from 1 to N , and $L_{\text{sub}i}$, h , and N satisfy:

$$0.5 \geq \{\cos m \times [(\pi/2) - (h/L_{\text{sub}1})] + \cos m \times [(\pi/2) - (h/L_{\text{sub}2})] + \dots + \cos m \times [(\pi/2) - (h/L_{\text{sub}N})]\} \geq 0.23.$$

19. The backlight structure according to claim 16, wherein a ratio of a light intensity at an edge position of the light region to a light intensity at a center position of the light region is not less than 0.5.

20. The backlight structure according to claim 16, wherein each of the at least some of the light regions comprises at least four light-emitting units, the at least four light-emitting units are arranged to form the M -sided polygon, and an included angle between one of the first direction and the second direction and at least one side of the M -sided polygon is 0 degrees; each of the at least some of the light regions is in a shape of a first square, each of the at least some of the light regions comprises at least four light-emitting units, the M -sided polygon is a second square, and an included angle between a diagonal of the first square and a diagonal of the second square is 0 degrees.
