

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418129
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Guo; Rongzhe et al.

Hybrid card-edge connectors and power terminals for high-power applications

Abstract

A power terminal includes first and second conductive sheets. The first conductive sheet includes a first joining portion, first fingers extending from the first joining portion, and a first mounting portion extending from the first joining portion and configured to mount to a substrate. The first fingers have hooked ends connected to the first joining portion by first beams. The second conductive sheet includes a second joining portion, second fingers extending from the second joining portion, and a second mounting portion extending from the second joining portion and configured to mount to the substrate. The two second fingers have curved ends connected to the second joining portion by second beams. The hooked ends and the curved ends include contact surfaces configured to contact a same side of a card. At least one of the first and second mounting portions includes at least two mounting tails.

Inventors: Guo; Rongzhe (Chengdu, CN), Fry; Clarence Randall (Mount Holly Springs, PA), Zou; Chao (Chengdu, CN)

Applicant: FCI USA LLC (Etters, PA)

Family ID: 1000008818862

Assignee: FCI USA LLC (Etters, PA)

Appl. No.: 18/660952

Filed: May 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250015528 A1	Jan. 09, 2025

Foreign Application Priority Data

CN	201811382876.1	Nov. 20, 2018
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18132094 20230407 US 12009613 child-doc US 18660952
continuation parent-doc US 17295001 US 11626681 WO PCT/CN2019/095891 20190712 child-
doc US 18132094

Publication Classification

Int. Cl.: **H01R13/24** (20060101); **H01R12/70** (20110101); **H01R12/72** (20110101); **H01R13/26** (20060101); **H05K1/02** (20060101); **H05K1/11** (20060101); **H05K5/00** (20060101)

U.S. Cl.:

CPC **H01R13/2492** (20130101); **H01R12/7088** (20130101); **H01R12/721** (20130101); **H01R13/26** (20130101); **H05K1/0213** (20130101); **H05K1/117** (20130101); **H05K5/0026** (20130101); H01R12/724 (20130101); H01R12/727 (20130101)

Field of Classification Search

CPC: H01R (13/2492); H01R (13/26); H01R (12/7088); H01R (12/721); H01R (12/724); H01R (12/727); H05K (1/0213); H05K (1/117); H05K (5/00266)

USPC: 439/637

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4040713	12/1976	Konnemann	N/A	N/A
4324451	12/1981	Ammon et al.	N/A	N/A
4734041	12/1987	Bruchmann et al.	N/A	N/A
6394818	12/2001	Smalley, Jr.	439/682	H01R 12/727
6645012	12/2002	Ito et al.	N/A	N/A
6652322	12/2002	Ito et al.	N/A	N/A
6672886	12/2003	Billman	439/82	H01R 12/737
6685512	12/2003	Ooya	N/A	N/A
6997751	12/2005	Miyamoto	439/630	H01R 13/2457
7104812	12/2005	Bogiel et al.	N/A	N/A
7247062	12/2006	Polnyi	N/A	N/A
7637783	12/2008	Sasaoka et al.	N/A	N/A
7985097	12/2010	Gulla	N/A	N/A
8202117	12/2011	Pan	N/A	N/A
8480434	12/2012	Funayama et al.	N/A	N/A
8550855	12/2012	Zhang et al.	N/A	N/A

8672713	12/2013	Tajiri et al.	N/A	N/A
8840406	12/2013	Hirata	N/A	N/A
9054456	12/2014	Orris et al.	N/A	N/A
9070990	12/2014	Flickinger et al.	N/A	N/A
9160105	12/2014	Takaki	N/A	N/A
9160122	12/2014	Sato	N/A	N/A
9190753	12/2014	Takaki	N/A	N/A
9196986	12/2014	Tanaka et al.	N/A	N/A
9225089	12/2014	Sato	N/A	N/A
9236678	12/2015	Joo et al.	N/A	N/A
9287654	12/2015	Takaki	N/A	N/A
9608349	12/2016	Mashiyama et al.	N/A	N/A
9666962	12/2016	Bucher	N/A	N/A
9935385	12/2017	Phillips et al.	N/A	N/A
9941613	12/2017	Zhao	N/A	N/A
9966679	12/2017	Xu et al.	N/A	N/A
10096920	12/2017	Lee	N/A	N/A
10128589	12/2017	Yamaguchi	N/A	N/A
10283910	12/2018	Chen et al.	N/A	N/A
10637175	12/2019	Zou et al.	N/A	N/A
10873146	12/2019	Zou et al.	N/A	N/A
11626681	12/2022	Guo et al.	N/A	N/A
12009613	12/2023	Guo et al.	N/A	N/A
2002/0022381	12/2001	Ito	439/60	H01R 12/721
2002/0098740	12/2001	Ooya	439/630	H01R 12/721
2002/0119704	12/2001	Ito	439/636	H01R 12/721
2006/0189222	12/2005	Bogiel	439/884	H01R 12/724
2007/0004291	12/2006	Bogiel	439/884	H01R 12/724
2009/0170373	12/2008	Pan	N/A	N/A
2012/0115371	12/2011	Chuang et al.	N/A	N/A
2012/0164892	12/2011	Ke	439/676	H01R 27/02
2012/0252275	12/2011	Tajiri et al.	N/A	N/A
2013/0005190	12/2012	Blanchfield et al.	N/A	N/A
2015/0163944	12/2014	Goodwin et al.	N/A	N/A
2016/0043494	12/2015	Mashiyama et al.	N/A	N/A
2017/0054241	12/2016	Sato et al.	N/A	N/A
2017/0373419	12/2016	Lee	N/A	H01R 13/02
2018/0034174	12/2017	Yamaguchi	N/A	N/A
2018/0097320	12/2017	Hashiguchi	N/A	H01R 13/2492
2018/0191093	12/2017	Phillips et al.	N/A	N/A
2018/0212344	12/2017	Li et al.	N/A	N/A

2020/0161791	12/2019	Zou et al.	N/A	N/A
2020/0212616	12/2019	Zou et al.	N/A	N/A
2022/0013942	12/2021	Guo et al.	N/A	N/A
2022/0021142	12/2021	Copper et al.	N/A	N/A
2023/0246373	12/2022	Guo et al.	N/A	N/A
2024/0145959	12/2023	Cheng et al.	N/A	N/A
2024/0178594	12/2023	Zou et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102781176	12/2011	CN	N/A
102804512	12/2011	CN	N/A
103636069	12/2013	CN	N/A
104103931	12/2013	CN	N/A
204668547	12/2014	CN	N/A
105375145	12/2015	CN	N/A
205583210	12/2015	CN	N/A
205846279	12/2015	CN	N/A
106299769	12/2016	CN	N/A
206301977	12/2016	CN	N/A
206727256	12/2016	CN	N/A
207183596	12/2017	CN	N/A
207381578	12/2017	CN	N/A
109326909	12/2018	CN	N/A
208939193	12/2018	CN	N/A
10310899	12/2003	DE	H01R 12/7088
102017103604	12/2016	DE	N/A
102017213140	12/2017	DE	N/A
2016-110966	12/2015	JP	N/A
M422792	12/2011	TW	N/A
M436982	12/2011	TW	N/A
M561346	12/2017	TW	N/A
WO 2017/193684	12/2016	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed Sep. 27, 2019 in connection with International Application No. PCT/CN2019/095891. cited by applicant

Taiwanese Office Action dated Oct. 5, 2022 in connection with Taiwanese Application No. 108142216. cited by applicant

[No Author Listed], New Product: High Density Plus (HD+) Card Edge Power Connectors. TE Connectivity. Nov. 27, 2018. 3 pages. URL:<https://www.te.com/usa-en/about-te/news-center/new-hd-plus-card-edge-connectors.html> [retrieved on May 18, 2021]. cited by applicant

Primary Examiner: Leigh; Peter G

Attorney, Agent or Firm: Wolf, Greenfield & Sacks, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 18/132,094, filed on Apr. 7, 2023, entitled “HYBRID CARD-EDGE CONNECTORS AND POWER TERMINALS FOR HIGH-POWER APPLICATIONS,” which is a continuation of U.S. application Ser. No. 17/295,001, filed on May 18, 2021, entitled “HYBRID CARD-EDGE CONNECTORS AND POWER TERMINALS FOR HIGH-POWER APPLICATIONS,” which is a 35 U.S.C. § 371 National Phase filing of International Application No. PCT/CN2019/095891, filed on Jul. 12, 2019, entitled “HYBRID CARD-EDGE CONNECTORS AND POWER TERMINALS FOR HIGH-POWER APPLICATIONS,” which claims priority to and the benefit of Chinese Patent Application No. 201811382876.1, filed on Nov. 20, 2018. The contents of these applications are incorporated herein by reference in their entireties.

FIELD OF THE DISCLOSURE

(1) The technology disclosed herein relates generally to electrical interconnection systems and more specifically to edge-type electrical connectors and power terminals useable in high-power applications.

BACKGROUND

(2) Electrical connectors are used in many electrical systems. Electronic devices have been provided with assorted types of connectors whose primary purpose is to enable data, commands, power and/or other signals to pass between electronic assemblies. A connector that carries both signals and power is sometimes called a hybrid connector. It is generally easier and more cost effective to manufacture an electrical system as separate electronic assemblies that may be joined with electrical connectors. For example, one type of electronic assembly is a printed circuit board (“PCB”). The terms “card” and “PCB” may be used interchangeably herein.

(3) In some scenarios, a two-piece connector is used to join two assemblies. One connector may be mounted to each of the assemblies. The connectors may be mated, forming connections between the two assemblies.

(4) In some other scenarios, a PCB may be joined directly to another electronic assembly via a one-piece connector, which may be configured as a card edge connector. The PCB may have pads along an edge that is designed to be inserted into an electrical connector attached to another assembly. Contacts within the electrical connector may contact the pads, thus connecting the PCB to the other assembly.

(5) As will be appreciated, the connections provided by the electrical connectors are electrical connections that may communicate electrical signals and/or electrical power (e.g., electrical current and/or voltage).

SUMMARY

(6) The structures of high-power electrical connectors and connector terminals able to carry electrical power and electrical signals are of great importance to electrical systems that may require high-power operation and/or a small size.

(7) According to some aspects of the present technology, a power terminal for use in a connector is provided. The power terminal may comprise a first plurality of first fingers and a second plurality of second fingers. The first plurality may be greater in number than the second plurality. The first plurality of first fingers may comprise first ends spaced apart from each other in a first direction and second ends connected to each other. The second plurality of second fingers may comprise first ends spaced apart from each other in the first direction and second ends connected to each other. The first ends of the second fingers may be spaced apart from the first ends of the first fingers in a second direction, perpendicular to the first direction.

(8) The second ends of the first fingers may be electrically connected to the second ends of the

second fingers at a joint region. The first ends of the first fingers may have first contact points configured to contact a first side of a card, and the first ends of the second fingers may have second contact points configured to contact the first side of the card. The first contact points may be different from the second contact points.

(9) According to some aspects of the present technology, a power terminal assembly for a card edge connector is provided. The terminal assembly may comprise first and second terminals and an insulative housing supporting the first and second terminals. Each of the first and second terminals may comprise a first plurality of first fingers comprising first ends spaced apart from each other in a first direction and second ends connected to each other, and a second plurality of second fingers comprising first ends spaced apart from each other in the first direction and second ends connected to each other. For each of the first and second terminals: the first ends of the second fingers may be spaced apart from the first ends of the first fingers in a second direction, perpendicular to the first direction; the first plurality may be greater in number than the second plurality; and the second ends of the first fingers may be electrically connected to the second ends of the second fingers at a joint region.

(10) For the first terminal, the first ends of the first fingers may have first contact points configured to contact a first side of a card, the first ends of the second fingers may have second contact points configured to contact the first side of the card, and the first contact points may be different from the second contact points. For the second terminal, the first ends of the first fingers may have first contact points configured to contact a second side of the card, the first ends of the second fingers may have second contact points configured to contact the second side of the card, and the first contact points may be different from the second contact points. A portion of each of the first and second terminals may be disposed in the insulative housing such that the first and second contact points of the second terminal may face the first and second contact points of the first terminal across a gap.

(11) According to some aspects of the present technology, a power terminal for a connector is provided. The power terminal may comprise first and second conductive sheets. The first conductive sheet may comprise at least two first fingers comprising first ends spaced apart from each other and second ends connected to each other. The second conductive sheet may comprise a second finger comprising a first end and a second end.

(12) The first ends of the first and second fingers each may have a contact surface thereon. The first end of the second finger may be positioned in a space between the first ends of adjacent ones of the first fingers. The second finger may comprise a first segment comprising the first end of the second finger and having a first average width, and a second segment joined to the first segment and having a second average width greater than the first average width.

(13) According to some aspects of the present technology, a power terminal for a connector is provided. The terminal may comprise a first terminal portion comprising a plurality of metal layers stacked in a layer direction. Each metal layer may comprise fingers arranged in a row direction different from the layer direction. The fingers of the metal layers may form rows of contact surfaces such that a first row of contact surfaces corresponding to a first one of the metal layers may be parallel to a second row of contact surfaces corresponding to a second one of the metal layers.

(14) The fingers of the first one of the metal layers may comprise distal ends curved into hooks having convex surfaces. The first row of contact surfaces may be disposed on the convex surfaces of the hooks of the first one of the metal layers. The fingers of the second one of the metal layers may comprise curved distal ends having convex surfaces. The second row of contact surfaces may be disposed on the convex surfaces of the curved distal ends of the fingers of the second one of the metal layers. The rows of contact surfaces of the metal layers of the first terminal portion may be configured to contact a same mating surface.

(15) Features described herein may be used, separately or together in any combination, in any of the embodiments discussed herein.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) Various aspects and embodiments of the present technology disclosed herein are described below with reference to the accompanying figures. It should be appreciated that the figures are not necessarily drawn to scale. Items appearing in multiple figures may be indicated by the same reference numeral. For the purposes of clarity, not every component may be labeled in every figure.
- (2) FIGS. 1A, 1B, and 1C each show an example of a printed circuit board (PCB) configured to connect with an edge connector.
- (3) FIG. 2A is an illustration of a vertically oriented connection arrangement.
- (4) FIG. 2B is an illustration of a right-angle oriented connection arrangement.
- (5) FIG. 2C is an illustration of a parallel board (straddle-mount) connection arrangement.
- (6) FIG. 3 shows a plan view of a card-receiving face of an edge connector.
- (7) FIG. 4 shows a hybrid card mated with a hybrid connector, according to an embodiment of the present technology.
- (8) FIGS. 5A, 5B, 5C, and 5D each schematically shows an example of a hybrid card in which a signal portion is joined with a power portion to form a single assembly, according to embodiments of the present technology.
- (9) FIG. 5E schematically shows a cross section of a laminated assembly, according to an embodiment of the present technology.
- (10) FIG. 6 shows a hybrid card mated with a hybrid connector, according to an embodiment of the present technology.
- (11) FIGS. 7A, 7B, 7C, 7D, and 7E schematically show examples of elevational views of insertion edges of circuit-board assemblies or hybrid cards having different configurations, according to embodiments of the present technology.
- (12) FIGS. 8A and 8B show hybrid connectors that may be used to connect to a hybrid card, according to embodiments of the present technology.
- (13) FIG. 9 shows a plan view of a connection face of a hybrid connector, according to an embodiment of the present technology.
- (14) FIG. 10 shows a plan view of a connection face of a hybrid connector, according to an embodiment of the present technology.
- (15) FIG. 11 shows a plan view of a connection face of a hybrid connector, according to an embodiment of the present technology.
- (16) FIG. 12 shows a plan view of a connection face of a hybrid connector, according to an embodiment of the present technology.
- (17) FIG. 13A shows a plan view of a power terminal, according to an embodiment of the present technology.
- (18) FIG. 13A' shows a plan view of a power terminal, according to an embodiment of the present technology.
- (19) FIG. 13B shows a cross-sectional view of a power terminal assembly, including two power terminals as in FIG. 13A (or FIG. 13A') within a housing, according to an embodiment of the present technology.
- (20) FIG. 13C shows a cross-sectional view of a power terminal assembly with a mounting portion configured for a right angle connector, according to an embodiment of the present technology.
- (21) FIG. 13D is a perspective view showing a mating portion of a power terminal, according to an embodiment of the present technology.

(22) FIGS. **14A** and **14A'** show a perspective view of a power terminal, according to an embodiment of the present technology.

(23) FIG. **14B** shows an exploded view of the power terminal of FIG. **14A**.

(24) FIG. **14C** shows a perspective view of a power terminal assembly, according to an embodiment of the present technology.

(25) FIGS. **15A**, **15A'**, **15B**, and **15B'** show top and bottom plan views of a power terminal assembly, according to an embodiment of the present technology.

(26) FIGS. **15C**, **15C'**, **15D**, and **15D'** show top and bottom perspective views of the power terminal assembly of FIGS. **15A**, **15A'**, **15B**, and **15B'**.

(27) FIG. **15E** shows a side plan view of the power terminal assembly of FIGS. **15A** and **15B**.

(28) FIG. **16A** shows a bottom plan view of a pair of first fingers of a power terminal, according to an embodiment of the present technology.

(29) FIG. **16B** shows a bottom perspective view of the pair of first fingers of FIG. **16A**.

(30) FIG. **16C** shows a top perspective view of the pair of first fingers of FIG. **16A**.

(31) FIG. **16D** shows a side elevational view of the pair of first fingers of FIG. **16A**.

(32) FIG. **17A** shows a bottom plan view of a second finger, according to an embodiment of the present technology.

(33) FIG. **17B** shows a bottom perspective view of the second finger of FIG. **17A**.

(34) FIG. **17C** shows a side elevational view of the second finger of FIG. **17A**.

DETAILED DESCRIPTION

(35) The inventors have recognized and appreciated designs for interconnection of electronic assemblies to enable compact, less expensive and high functionality electronic systems. Such systems require power to be delivered to or from assemblies in relatively small spaces. These designs include adaptations to card edge connectors, and the cards that mate with them, to support large power flow through small spaces without undesired effects, such as large heat generation and damage to the system that might result from the heat generated.

(36) FIGS. **1A-1C** show examples of PCBs **10A**, **10B**, **10C** configured for insertion into card edge connectors. Electrical contacts, here shown as surface pads, may be placed on one or more edges of a PCB in a variety of different configurations. FIG. **1A** illustrates a portion of a PCB **10A**. As can be seen, the PCB **10A** may have multiple vias, exposed at a surface. The vias may provide connections to conductive structures inside the PCB **10A**. Semiconductor chips and other components may be mounted to the PCB **10A** by attaching their leads to the vias such that signals and power may pass through the conductive structures to or from those components. Within the PCB **10A**, signal traces, patterned on each of multiple layers, may carry the signals. Power may be carried on power planes, which may be interspersed between layers of signal traces. Pads at the edge of the PCB **10A** also may be connected to those conductive structures within the PCB **10A** so that they may be connected to other locations in an electronic system when those pads are inserted into a connector. Certain of the pads, serving as signal terminals, may be connected to traces inside the PCB **10A** whereas others of the pads, serving as power terminals, may be connected to power planes within the PCB **10A**. The components attached to the PCB **10A** may consume power that is delivered to the PCB **10A** through the power terminals. Alternatively, the components attached to the PCB **10A** may condition or otherwise deliver power through the power terminals, where it can then be routed to other components in an electronic system. Regardless of the direction in which power is flowing, onto or off of the PCB **10A**, techniques as described herein may be applied to the PCB and the card edge connector. In many electronic system, however, a large amount of power may flow from a PCB acting as a power supply and then through a card edge connector, such that techniques as described herein may be selectively applied to those components in some embodiments.

(37) FIG. **1B** shows another example of a PCB **10B** configured for insertion in a card edge connector. In this example, the PCB **10B** is shown schematically, without components, vias, or

traces, for simplicity of illustration. In the illustrated example, electrical terminals **12a**, **12b** on the PCB **10B** may be located on a main edge **14A** of the PCB **10B**. In a further example, shown in FIG. **1C**, electrical terminals **12c**, **12d** on a PCB **10C** may be located on edge protrusions **14B**, **14C**, which extend from a main edge **14D** of the PCB **10C**. The edges **14A**, **14B**, **14C** on which electrical terminals are located may be insertion edges, which are edges configured to be inserted into edge connectors.

(38) The electrical terminals **12a**, **12b**, **12c**, **12d** may be configured to carry electrical signals and/or to supply power (e.g., current, voltage). Within an electronic assembly, power may be differentiated from signals based on frequency, voltage, or current. Power is usually low frequency, such as 60 Hz or less, and often DC. Power also is usually higher voltage than a signal, with voltage levels of 5 V, 12 V, or higher. In contrast, signals may be less than 5 V, and often less than 3 V. Likewise, power is usually higher current, often in the range of amps or tens of amps, whereas signals will be on the order of milliamps.

(39) In the example of FIG. **1B**, the electrical terminals **12a** may be configured to carry signals to/from the PCB **10B**, and the electrical terminals **12b** may be configured to supply power. In another example, in the PCB **10C**, the electrical terminals **12c** on the left of the electrical terminals **12d** may be configured to carry power to/from the PCB **10C**, the electrical terminals **12d** may be configured to carry signals, and the electrical terminals **12c** on the right of the electrical terminals **12d** may be configured to carry power. FIGS. **1A-1C** illustrate that PCBs designed for mating with a card edge connector may have any of a number of terminal configurations, and techniques as described herein may be applied with PCBs having any suitable terminal configuration.

(40) Card-edge connectors may be configured to mate with PCBs in any of multiple orientations. For example, FIG. **2A** shows an example of a vertically oriented card-edge connector **20a** configured to receive a PCB **22a** in a slot **24**. A mounting end of the connector **20a** may be configured to be mounted on a substrate **26a**, which may be another printed circuit board, such as a backplane, with the slot **24** positioned to receive the PCB **22a** when it is oriented to extend vertically with respect to the surface of the substrate **26a**.

(41) FIG. **2B** shows an example of a right-angle oriented card-edge connector **20b** configured to receive a PCB **22b** in a slot (not visible in the figure). A mounting end of the connector **20b** may be configured to mount at a right angle on a substrate **26b**. The substrate **26b** may also be a PCB, such as a motherboard in an electronic system, but it should be understood that connectors and card designs may be used with substrates of any suitable type. In this example, the PCB **22b** is parallel to the substrate **26b**.

(42) FIG. **2C** shows an example of a straddle-mount card-edge connector **20c** with a slot in which a PCB **22c** is inserted; a mounting end of the connector **20c** may be configured to mount horizontally on a substrate **26c**. In the illustrated example, contact tails extending from the connector **20c** have a portion aligned with an upper surface of the substrate **26c**. Another portion of the contact tails extending from the connector **20c** are aligned with a lower surface of the substrate **26c**. Such a configuration is sometimes called a straddle mount and may be used for connecting parallel boards. As will be appreciated, card-edge connectors may be configured to attach to a substrate in other orientations. The techniques as described herein may be used with mounting orientations as illustrated in FIGS. **2A-2C**, or in any other suitable mounting orientation.

(43) Each of FIGS. **2A-2C** shows a portion of an electronic system. A full system may have multiple connectors mounted to a substrate, which may provide connections between multiple PCBs inserted into those connectors. Further, the substrate may be connected to other components through cables, bus bars or other than through card edge connectors.

(44) FIG. **3** illustrates a plan view of a card-receiving face of a card-edge connector **30**. The connector **30** may be, for example, the vertically oriented card-edge connector **20a** or the right-angle oriented card-edge connector **20b** or the horizontally oriented card-edge connector **20c**. The connector **30** may comprise a slot **34** configured to receive a card. The slot **34** may comprise a

power section **34A** having power terminals **38a** arranged to contact corresponding power contact-pads of a PCB. For example, the terminals **38a** may be arranged to contact power contact-pads **21a** of the PCB **22a** (or **22b** or **22c**). The slot **34** also may comprise a signal section **34B** having signal terminals **38b** arranged to contact corresponding signal contact-pads of a PCB. For example, the terminals **38b** may be arranged to contact signal contact-pads **21b** of the PCB **22a** (or **22b** or **22c**). (45) As illustrated in the example of FIG. 3, the power terminals **38a** may be wider than the signal terminals **38b**. Such a design enables the power terminals **38a** to carry more current than the signal terminals **38b**, without excessive heating. The larger cross-sectional area of the power terminals **38a** provides a lower contact resistance, a lower bulk resistance, and a lower current density, all of which contribute to less heating within the connector when a relatively large amount of current passes through the power terminals **38a**.

(46) FIGS. 2A-2C illustrate that a PCB, designed for insertion into a card edge connector, may be made with power contact pads that mate with wider power terminals. For example, FIG. 2A shows that the power pads **21a** may be wider than the signal contact pads **21b**. Similar relative dimensions of signal and power pads are also shown for the PCBs **22b** and **22c**.

(47) The inventors have recognized and appreciated designs for power terminals for card edge connectors that can pass larger amounts of power with an acceptable amount of heating. Current flow is often used as an indication of delivered power, because power and current are related, and heating is proportional to current flow. Acceptable heating may be expressed as temperature rise at a rated current. As a specific example, a connector, or a power terminal within the connector, may have a rated current capacity that reflects the amount of current that will increase the temperature from ambient conditions by a set amount, such as 30° C.

(48) Examples of improved power terminals that can pass large amounts of current are given below in connection with FIGS. 13A-17C.

(49) The inventors have recognized and appreciated that for high-power applications, connectors with improved terminal designs may handle more current than can pass through a PCB inserted into that connector without causing an unacceptable level of heating within the PCB. For example, a design may require a PCB to deliver a current of up to 480 amps, with a maximum temperature increase of 30° C. above an ambient temperature. A conventional approach to designing a PCB for higher-current use is to make the PCB have more power planes, which makes the PCB thicker. Increased layer count is usually necessary because the width of the PCB is often set by a need to fit within a specific space. Moreover, widely used PCB manufacturing processes tend to use copper films having a thickness in a predefined range to form power planes within the PCB, such that the thickness of each power plane cannot be arbitrarily increased to increase a current-carrying capacity of the PCB. As a result, increasing layer count is a conventional approach to increasing a current-carrying capacity of a PCB. The increase in layer count of the PCB, however, may not be desirable for some types of electronic systems where, for example, portability and thus a small size or weight is required, or where low cost is desired.

(50) Different approaches to PCB design may expand the utility of improved power terminals and card-edge connectors. A hybrid PCB card (“hybrid card” or “hybrid board” or “hybrid circuit board assembly” herein) may be used for high-power applications.

(51) FIG. 4 shows a hybrid card **40** mated with a hybrid connector **42**, according to some embodiments of the present technology. The hybrid card **40** may be a subassembly acting as a power supply, for example, but may be configured for any suitable functions, as described above. The hybrid connector **42** may be mounted on a substrate **41**. The substrate **41** may be a mother card, a backplane, or another assembly within the electronic system.

(52) A slot **44** of the hybrid connector **42** may be structured to receive the hybrid card **40**. The hybrid card **40** may have a signal portion **40a** and a power portion **40b**. The signal portion **40a** may include signal contact-pads **46** arranged to contact signal terminals of the hybrid connector **42**. Electronic components, such as those that regulate or condition power, if the hybrid card **40** is a

power supply, may be mounted to the signal portion **40a** using conventional printed circuit board manufacturing techniques.

(53) The power portion **40b** may comprise a blade of conductive material. For example, the power portion **40b** may comprise any of the following: a solid piece of elemental metal having high conductivity (e.g., Cu, Al); a solid piece of an alloy of metals (e.g., a Cu alloy); or a solid plate or core clad with a high-conductivity metal (e.g., a Cu plate clad with Au, a steel plate clad with Cu, a resin plate clad with Cu); or a laminate with layers of high conductivity material interspersed with lower conductivity materials.

(54) For instance, the blade may be comprised of any of the following: a solid piece of copper; a core that is clad with a thick layer of copper; a core that is clad with a thick layer of copper and a surface layer of gold; a core that is clad with a thick layer of copper, a layer of silver, and a surface layer of gold; a laminated structure with a thin insulative layer separating two thicker conductive layers; etc. As will be appreciated, the high-conductivity material may be a metal alloy. The core may be made of any material having properties that enable it to be formed into a card-like or blade-like shape and that may be clad with another material without adversely reacting with the other (cladding) material. For example, the core may be made of aluminum.

(55) The power portion **40b** may have an edge suitable for a contact surface, which may be inserted into a portion of a hybrid connector containing power terminals, like the power pads **21a**, illustrated above. The contact surface may result from the use of suitable material to form the blade or from coating or plating a portion of the blade with a coating that resists oxidation, including, for example, a gold plating or a multilayer plating.

(56) The power portion **40b** may be configured as a conductive blade, as pictured in the examples herein. As will be appreciated, the conductive blade **40b** may comprise any high-conductivity material able to conduct electrical current sufficient for applications requiring at least 3000 W of power, and having sufficient rigidity to withstand repeated mating and unmating with a connector. For example, the cladding may be a layer of Cu that has a thickness of at least 0.14 mm, or at least 0.5 mm, or at least 1 mm, or at least 1.5 mm.

(57) The signal portion **40a** and the conductive blade **40b** may be held together as a single assembly. One or more support members may be used to hold the signal portion **40a** and the conductive blade **40b** in a side-by-side configuration. In one example shown in FIG. 5A, at least one edge clip **52** may join together an edge of the signal portion **40a** and an edge of the conductive blade **40b**. The support members may be or may include parts of signal portion **40a** and/or the conductive blade **40b**. In another example, shown in FIG. 5B, an edge of the conductive blade **40b** may be structured with a slot or recess **53** to accommodate therein an edge of the signal portion **40a**. The slot **53** may be profiled with a pattern (dotted lines), and the edge of the signal portion **40a** may be profiled in a complementary pattern, to ensure that the signal portion **40a** and conductive blade **40b** mate together with a desired alignment. Conversely, in another example (not shown in the drawings but analogous to FIG. 5B), an edge of the signal portion **40a** may be structured with a slot or recess to accommodate therein an edge of the conductive blade **40b**.

(58) As mentioned above, FIG. 5A illustrates support members between the signal portion **40a** and the conductive blade **40b**. Support members may be in other locations. For example, one or more support members may form a frame partially or fully around one or more signal portions **40a** and one or more conductive blades **40b** of a hybrid card **40**. As a specific example, a signal portion **40a** may contain control circuitry for a power supply and a plurality of conductive blades **40b** that serve as supply and return lines for one or more circuits supplied with power from the power supply. The power supply may have an enclosure serving as or containing one or more support members, with the signal portion **40a** and the conductive blades **40b** mounted within the enclosure such that their insertion edges are exposed along a same edge of the enclosure. The resulting assembly may be a pluggable power supply and may be inserted into a rack or other electronic system such that the insertion edges of the signal portion **40a** and the conductive blades **40b** may be inserted into a

connector inside the system to make signal and power connections.

(59) In other examples, the signal portion **40a** and the conductive blade **40b** may share a common resin board **54**. The signal portion **40a** may be formed in a part of the resin board **54** and processed as a typical PCB would be processed to form the signal contact-pads **46**. As depicted in FIG. 5C, another part of the resin board **54** may support the conductive blade **40b**. For example, that portion of the resin board **54** may be clad with a layer **55** of high-conductivity material on one or both sides to form the conductive blade **40b**; the cladding layer(s) **55** may be, for example, at least 0.14 mm of Cu or a Cu alloy, or at least 0.5 mm of Cu or a Cu alloy. Alternatively, a conductive blade **40b** may be mounted, such as with screws, adhesives or other fasteners to the surface of resin board **54**. As a further variation, a region **59** of the resin board **54** may be omitted under the conductive blade **40b**, such that the mating edge of the hybrid board, in the power portion **40b** may be formed by the edge of the conductive blade **40b**. The edge of the conductive blade **40b** above the region **59** may be parallel with the body of the conductive blade **40b** over the resin board **54**, or may be bent into alignment with the edge of signal portion **40a**.

(60) As yet another alternative, as shown in FIG. 5D, the conductive blade **40b** may comprise a solid metal plate **58** configured to fit into a cutout or opening **56** of the resin board **54**. The cutout **56** may be a surface trench or may be a hole extending through an entire thickness of the resin board **54**. Optionally, clips **57**, screws adhesives or other fasteners may be used to hold the metal plate **58** in the cutout **56**.

(61) As will be appreciated, the signal portion **40a** and the power portion **40b** may be attached together in other ways. For example, a female-female type edge-socket union may be used to unite the signal and power portions **40a** and **40b**. The examples presented herein are illustrative and are to be considered non-limiting examples.

(62) The conductive blade **40b** in FIGS. 4 and 5A-5D is shown to have a single continuous area on a first side (e.g., a top side, shown in the figures). As will be appreciated, the conductive blade in FIGS. 4 and 5A-5D may also have a second side opposite the first side (e.g., a bottom side, not visible in the figures), which may also have a contact surface along an edge.

(63) In some embodiments, the circuit board assembly may comprise more than one conductive blade. The conductive blades may have contact surfaces on the same or opposite sides of a circuit board assembly. The conductive blades may be held together as an integrated member in which some or all of the conductive blades are separated by insulative layers. Such electrically separated conductive blades may carry power at different voltage levels. When the circuit board assembly includes multiple conductive blades, the blades may have forward edges, adjacent the insertion edge of the circuit board assembly. Some or all of the conductive blades may be set back from the insertion edge of the circuit board assembly, and different ones of the conductive blades may be set back from the insertion edge of the circuit board assembly by different amounts.

(64) FIG. 5E shows an exemplary cross section of a laminated assembly **40b'** of an insulative layer L1 having first and second surfaces L2, L3, a first blade L4 arranged on the first surface L2, and a second blade L5 arranged on the second surface L3. The laminated assembly **40b'** depicted in FIG. 5E may, for example, be used instead of the conductive blade **40b** of FIG. 5D. The first and second surfaces L2, L3 of the insulative layer L1 may be parallel to the surface of a PCB of the signal portion **40a** of FIG. 5D.

(65) The first blade L4 may have a first insertion edge L6 that is set back from an insertion edge L7 of the laminated assembly **40b'** by a first distance D.sub.L4, and the second blade L5 may have a second insertion edge L8 that is set back from the insertion edge L7 of the laminated assembly **40b'** by a second distance D.sub.L5 that may be different from the first distance D.sub.L4. The insertion edges L6, L7, L8 may also be referred to as mating edges herein. The first distance D.sub.L4 may be in a range of 1 mm to 8 mm. The second distance D.sub.L5 may be in a range of 1 mm to 6 mm. As a specific example, the difference in set-back may be on the order of 2 mm to 5 mm. Such a configuration may be used, for example, in a power supply in which one of the blades L4 and L5 is

connected to a supply line of a circuit of the power supply and the other of the blades L4 and L5 is connected to a return line for that circuit. Such a configuration enables advance mating of the supply or return line when the laminated assembly **40b'** is inserted into a slot of a connector, by using the second blade L5 for that portion of the circuit to mate first.

(66) The insulative layer L1 may comprise a rigid plastic layer, which may include an endcap L9 that extends over the first and second insertion edges L6, L8 of the first and second blades L4, L5. Alternatively, the insulative layer L1 may comprise an insulative film. For example, the insulative film may have a thickness of about 0.1 mm and the conductive blades L4, L5 may be copper sheets having a thickness of about 1 mm.

(67) In an example embodiment, the laminated assembly **40b'** may be incorporated in a power bus bar, such that a portion of the laminated assembly **40b'** may extend from a recessed portion of an insulative housing of the power bus bar. The first conductive blade L4 may be a current-in blade that may provide 3000 Watts of power at 48 V, and the second conductive blade L5 may be a current-out blade.

(68) The laminated assembly **40b'** may have a total thickness Y in a range of 1 mm to 6.5 mm. A thickness of each of the first and second conductive blades L4, L5 may be in a range of 0.5 mm to 3.5 mm.

(69) As evident from the discussion above, it is not a requirement that a hybrid card contain a single blade or a unitary blade. FIG. 6 shows another embodiment of a hybrid card **60** mated with a hybrid connector **62**. The hybrid connector **62** may be mounted on a substrate **61**. A slot **64** of the hybrid connector **62** may be structured to receive the hybrid card **60** therein.

(70) The hybrid card **60** may have a signal portion **60a** and a plurality of power portions **60b**, **60c**. The signal portion **60a** may include signal contact-pads **66** arranged to contact signal terminals of the hybrid connector **62**. The power portions **60b**, **60c** may comprise blades of high-conductivity material. For example, a first conductive blade **60b** may serve to carry current from hybrid card **60** to substrate **61**, and the second conductive blade **60c** may provide a return path carrying current from substrate **61** to hybrid card **60**.

(71) The conductive blades **60b**, **60c** and the signal portion **60a** may be joined together to form a single assembly using the techniques discussed above or using other joining techniques known in the art (e.g., insulative clips **65**). For example, each of the conductive blades **60b**, **60c** may be 1.6 mm thick and have a cross-sectional area in a range between 35 mm² and 50 mm², and may be able to carry a current greater than 300 amps in a 50 mm² area, with a maximum temperature increase of 30° C. above an ambient temperature. As will be appreciated, the conductive blades described herein may have a thickness other than 1.6 mm, such as a thickness in a range of from 0.5 mm to 2 mm, or from 1.6 mm to 3 mm, or from 2 mm to 3 mm, or from 3 mm to 4 mm, or from 4 mm to 5 mm.

(72) These blades may be held in parallel using support members that provide electrical insulation between the conductive blades. However, each of the blades **60b**, **60c** may be electrically connected to the signal portion **60a** such that components that respond to control signals can, for example, supply conditioned power through the conductive blades **60b**, **60c**. Such a configuration may be achieved by attaching the conductive blades **60b**, **60c** to a surface of a PCB in which the signal portion **60a** is implemented. In that configuration, conductive structures within the PCB may make connections between the signal portion **60a** and the conductive blades **60b**, **60c**.

(73) Other structures alternatively or additionally may be used to make connections between the conductive blades **60b**, **60c** and the signal portion **60a**. For example, although FIG. 6 illustrates both the conductive blades **60b**, **60c** with straight side edges perpendicular to the edge of the hybrid card **60** inserted into the connector **62**, either or both of the conductive blades **60b**, **60c** may have conductive projections extending to the signal portion **60a**. In some embodiments, connections between the signal portion **60a** and, for example, the conductive blade **60b** may be made on one side of hybrid card **60**, and/or connections between the signal portion **60a** and the conductive blade

60c may be made on the opposite side of the hybrid card 60.

(74) It should be appreciated that, depending on the thickness of the power portion(s) and the signal portion(s) of a hybrid card, as well as the mechanism of attachment of the power portions to the signal portions, the location of contact surfaces on the signal and power portions, relative to the elongated dimension of the slot that receives the edge of the hybrid card, may vary.

(75) FIGS. 7A-7E schematically show examples of elevational views of insertion edges of circuit-board assemblies or hybrid cards having different configurations. These examples are not exhaustive and, as will be appreciated, other configurations may be used for a hybrid card according to other embodiments of the present technology.

(76) In one example, shown in FIG. 7A, a hybrid card 70A may have a uniform insertion edge. In this example, both a signal portion 70a and a conductive blade 70b of the hybrid card 70A may have a same thickness $t_{\text{sub.1}}$ at their insertion edges. External surfaces 72a, 72b, 72c, 72d of the signal portion 70a and the conductive blade 70b may be aligned, and a midplane M.sub.a of the signal portion 70a may be aligned or coplanar with a midplane M.sub.b of the conductive blade 70b. Such a configuration may result, for example, from a configuration as shown in FIGS. 5C and 5D in which the power portion is aligned with the signal portion and both are the same thickness. Such a configuration also may result if a conductive blade with a bend is mounted on the same PCB containing the signal portion, as described above in connection with FIG. 5C. In that configuration, the body of the conductive blade may be offset from the signal portion in a direction perpendicular to the edge (or at another angle), but the edge of the conductive blade may bend into alignment with the edge of the signal portion.

(77) In another example, shown in FIG. 7B, a hybrid card 70B may have a non-uniform insertion edge. In this example, both the signal portion 70a and the conductive blade 70b of the hybrid card 70B may have a same thickness $t_{\text{sub.1}}$ at their insertion edges. However, the midplane M.sub.a of the signal portion 70a may not be aligned with the midplane M.sub.b of the conductive blade 70b for the hybrid card 70B. Such a configuration may result from a configuration as discussed above in connection with FIG. 5C in which a conductive blade is mounted on the same PCB containing the signal portion. The PCB may be implemented without the cutout region 59.

(78) In a further example, shown in FIG. 7C, a hybrid card 70C may have non-uniform insertion edges. In this example, the signal portion 70a may have a thickness $t_{\text{sub.2}}$ at its insertion edge, and the conductive blade 70b may have a different thickness $t_{\text{sub.3}}$ at its insertion edge. Also, the midplane M.sub.a of the signal portion 70a may not be aligned with the midplane M.sub.b of the conductive blade 70b. However, for the hybrid card 70C, an external surface of 72a of the signal portion 70a may be aligned with an external surface 72b of the conductive blade 70b. Such a configuration may result, for example, if the conductive blade and edge of the signal portion have different thicknesses in the examples of FIGS. 5A-5D, or, in the example of FIG. 5C, if the conductive blade is mounted on a top surface of the PCB containing the signal portion.

(79) In another example, shown in FIG. 7D, a hybrid card 70D may have non-uniform insertion edges. In this example, the signal portion 70a may have a thickness t_a at its insertion edge, and the conductive blade 70b may have a different thickness $t_{\text{sub.4}}$ at its insertion edge. However, the midplane M.sub.a of the signal portion 70a may be aligned with the midplane M.sub.b of the conductive blade 70b. For the hybrid card 70D, no external surface of the signal portion 70a is aligned with an external surface of the conductive blade 70b. Such a configuration may result, for example, if the conductive blade and edge of the signal portion have different thicknesses in the examples of FIGS. 5A-5D, or, in the example of FIG. 5C, if conductive blades are mounted on top and bottom surfaces of the PCB containing the signal portion.

(80) In a further example, shown in FIG. 7E, a hybrid card 70E may have non-uniform insertion edges. In this example, the signal portion 70a may have a thickness t_o at its insertion edge, and the conductive blade 70b may have a different thickness $t_{\text{sub.7}}$ at its insertion edge. Also, the midplane M.sub.a of the signal portion 70a may not be aligned with the midplane M.sub.b of the

conductive blade **70b**. For the hybrid card **70E**, no external surface of the signal portion **70a** is aligned with an external surface of the conductive blade **70b**.

(81) FIGS. **8A** and **8B** are illustrations of perspective views of hybrid connectors **80A**, **80B**, which may be used to connect to a hybrid card (e.g., the hybrid card **70A**). The connector **80A** may be a straddle-mount card-edge connector for a parallel board configuration, and the connector of **80B** may be a vertically oriented card-edge connector. Aspects of the connectors **80A** and **80B** may be described collectively below using the reference numeral **80**, as both connectors **80A** and **80B** may have the same mating interface and other components that may be the same.

(82) The connector **80** may comprise an insulative housing **81**, a plurality of first conductive terminals **82**, and a plurality of second conductive terminals **83**. The housing **81** may comprise a slot **84** having a first slot portion **84a** and a second slot portion **84b**. The first conductive terminals **82** may be disposed in the first slot portion **84a**, and the second conductive terminals **83** may be disposed in the second slot portion **84b**. For example, the first conductive terminals **82** may be arranged in rows on opposite sides of the first slot portion **84a**, and the second conductive terminals may be arranged in rows on opposite sides of the second slot portion **84b**.

(83) The first conductive terminals **82** may be signal terminals and may be configured to carry electrical signals. The second conductive terminals **83** may be power terminals and may be configured to carry a relatively large amount of current at a relatively high voltage. For example, each of the second conductive terminals **83** may be configured to carry up to 40 A. In another example, each of the second conductive terminals **83** may be configured to carry up to 50 A at up to 400 V. The first conductive terminals **82** may be electrically isolated from the second conductive terminals **83**. Dimensions of the first conductive terminals **82** may be different from dimensions of the second conductive terminals **83**. Structural configurations of a power terminal according to aspects of the present technology, usable as one of the second conductive terminals **83**, are discussed in more detail below.

(84) The slot **84** may be configured to receive a hybrid card (e.g., **70A**). For example, the first slot portion **84a** may be configured to receive an edge of a circuit board (e.g., **70a**) of the hybrid card inserted therein. The first conductive terminals **82** may be arranged in the first slot portion **84a** to engage with and physically contact signal contact-pads disposed on the circuit board when the hybrid card is in a mated state with the connector **80**. The second slot portion **84b** may be configured to receive an edge of a conductive blade (e.g., **70b**) of the hybrid card inserted therein. The second conductive terminals **83** may be arranged in the second slot portion **84b** to engage with and physically contact one or more conductive blades when the hybrid card is mated with the connector **80**.

(85) FIGS. **9** and **10** show plan views of a connection face of hybrid connectors **90**, **90'**. The connector **90** may comprise an insulative housing **91** having a slot **94**. The slot **94** may comprise first and second slot portions **94a**, **94b**. The first slot portion **94a** may comprise first and second internal surfaces **95a**, **95b**, and the second slot portion **94b** may comprise third and fourth internal surfaces **96a**, **96b**.

(86) First conductive terminals **92** may be arranged in a first array **97a** on the first internal surface **95a** and a second array **97b** on the second internal surface **95b**. The first array **97a** may face the second array **97b** such that a first card-receiving space **98a** may be formed between the first and second arrays **97a**, **97b**.

(87) Similarly, second conductive terminals **93** may be arranged in a third array **99a** on the third internal surface **96a** and a fourth array **99b** on the fourth internal surface **96b**. The third array **99a** may face the fourth array **99b** such that a second card-receiving space **98b** may be formed between the third and fourth arrays **99a**, **99b**.

(88) As shown in FIG. **10**, the first card-receiving space **98a** may comprise a first mid-plane M1 located between the first and second arrays **97a**, **97b** and equidistant from the first array **97a** and the second array **97b**. The second card-receiving space may comprise a second mid-plane M2

located between the third and fourth arrays **99a**, **99b** and equidistant from the third array **99a** and the fourth array **99b**.

(89) The first mid-plane M1 and the second mid-plane M2 may have a predetermined relationship relative to each other. For example, the first mid-plane M1 may be coplanar with the second mid-plane M2; this is depicted schematically in FIGS. **9** and **10**. In another example, the first mid-plane M1 may not be coplanar with the second mid-plane M2; this is depicted schematically in FIGS. **11** and **12**.

(90) As will be appreciated, the first and second mid-planes M1, M2 may be coplanar, or may be parallel, or may be staggered, or may be non-parallel and non-coplanar, etc.

(91) A distance between the first and second internal surfaces **95a**, **95b** of the first slot portion **94a** may be designated a height H1 of the first slot portion **94a**. A distance between the third and fourth internal surfaces **96a**, **96b** of the second slot portion **94b** may be designated a height H2 of the second slot portion **94b**. The height H1 of the first slot portion **94a** may be equal to or different from the height H2 of the second slot portion **94b**. Even though the height H1 of the first slot portion **94a** may be the same as the height H2 of the second slot portion **94b**, a height of the first card-receiving space **98a** may be different from a height of the second card-receiving space **98b** due to a size difference between the first conductive terminals **92** and the second conductive terminals **93**. For example, as depicted schematically in FIG. **11**, a distance between a plane P1 corresponding to contact surfaces of the first array **97a** and a plane P2 corresponding to contact surfaces of the second array **97b** may be different from a distance between a plane P3 corresponding to contact surfaces of the third array **99a** and a plane P4 corresponding to contact surfaces of the fourth array **99b**.

(92) The housing **91** may comprise a first housing portion **91a**, in which the first slot portion **94a** is disposed, and a second housing portion **91b** in which the second slot portion **94b** is disposed. The first and second housing portions **91a**, **91b** may be integrally formed as a single unit or may be connected together to form a single unit, as schematically depicted in FIG. **12**.

(93) Connectors to receive hybrid cards of the various configurations may be constructed, such as are schematically illustrated in FIG. 7A-7E. A connector as illustrated in FIG. **9** may be usable with the topology of FIG. 7A. A connector as illustrated in FIG. **10** may be usable with the topology of FIG. 7D. A connector as illustrated in FIG. **11** may be usable with the topology of FIG. 7C. A connector as illustrated in FIG. **12** may be usable with the topology of FIG. 7B. Other connector configurations may be used with other topologies.

(94) In FIGS. **9-12**, the hybrid connectors in the drawings are shown to have two slot portions to accommodate a hybrid card: one slot portion to accommodate a signal portion of the hybrid card and another slot portion to accommodate a power portion of the hybrid card. In other embodiments, hybrid connectors may have more than two slot portions to accommodate, for example, a hybrid card having more than one signal portion and/or more than one power portion. Though, it should be appreciated that there is not a requirement for a one to one relationship between signal portions and/or power portions of a hybrid card and slot portions in a connector, as more than one power portion, having the same thickness and midplane may fit within the same slot portion. Likewise, more than one signal portion may fit within the same slot portion.

(95) The hybrid cards, as described above, may be used with power terminals that carry a large amount of current. FIG. **13A** depicts a top plan view of a power terminal **1300** that may be used as one of the second conductive terminals **83**, **93**, discussed above. The power terminal **1300** may have multiple groups of fingers, here shown as a first plurality of first fingers **1312** having first ends **1312a** spaced apart from each other and second ends **1312b** connected to each other. The power terminal **1300** also may comprise a second plurality of second fingers **1313** having first ends **1313a** spaced apart from each other and second ends **1313b** (see FIG. **13B**) connected to each other. The first ends **1313a** of the second fingers **1313** may be spaced apart from the first ends **1312a** of the first fingers **1312**. The second ends **1312b** of the first fingers **1312** may be in contact

with the second ends **1313b** of the second fingers **1313** at a joint region **1340**. The first ends **1312a**, **1313a** may be mating ends or mating portions.

(96) The centers of the mating ends of the fingers in two or more of the groups may be offset with respect to each other in a direction perpendicular to a direction of elongation of the fingers. In the example of FIG. **13A**, the centers of the first ends **1312a** are offset with respect to the centers of the first ends **1313a**. Such a configuration may distribute wear of the mating edges of the conductive blades of a hybrid card. Distributing wear reduces the likelihood of a contact failure after repeated use, and may be particularly advantageous in configurations in which the fingers have dimples on their contact surfaces to provide lower contact resistance or a greater ability to wipe away oxide layers as a result of higher contact pressure provided by the dimples.

(97) The first plurality may be greater in number than the second plurality, i.e., a number of the first fingers **1312** may be greater than a number of the second fingers **1313**. For example, there may be three of the first fingers **1312** and two of the second fingers **1313**, as shown in FIG. **13A**.

Optionally, as shown in FIG. **13A'**, a power terminal **1300'** may comprise four of the first fingers **1312** and three of the second fingers **1313**. Having more first fingers enables the first fingers to be narrower than the second fingers. Such a configuration may provide multiple contact fingers that have substantially the same contact force, even though the first fingers are shorter than the second fingers.

(98) FIG. **13D**, however, shows a configuration in which there are two first fingers and two second fingers. FIG. **13D** shows mating portions of two power terminals **1300a''** and **1300b''**, configured for mounting within a connector housing on opposing surfaces of a slot to receive a conductive blade inserted into the slot between them. Outer fingers **1313a''**, **1313b''** are joined to inner fingers **1312a''**, **1312b''** at joints **1340a''**, **1340b''**, respectively. In this example, contact surfaces **1374a''** of the outer fingers align, in a direction perpendicular to an edge of a hybrid card to which the fingers may mate, with contact surfaces **1372a''** of the inner fingers. As will be appreciated, the first plurality and the second plurality may have values different than those of the power terminals **1300**, **1300'**, **1300''** shown in FIGS. **13A**, **13D**, and **13A'**.

(99) The power terminal **1300** also may comprise a mounting end **1320** configured for attachment to a substrate **1365** (see FIG. **13C**). As will be appreciated, mounting ends may be configured to support a desired board configuration. The mounting end **1320** of the power terminal **1300** or **1300'**, for example, may have surface mount solder tails, which may be suitable for a connector as shown in FIG. **2C**. The mounting end **1320** of the power terminals in FIG. **13C**, for example, may have press-fit solder tails, which may be suitable for a connector as shown in FIG. **2B**. The power terminals shown in FIG. **13D** are illustrated without their mounting ends shown; the mounting ends may have any suitable configuration.

(100) The first ends **1312a** of the first fingers **1312** may have first contact points **1312c** that may be configured to contact a first side of a card. For example, the contact points **1312c** may contact a contact surface of a conductive blade or power portion of a hybrid card. The contact points may be on convex surfaces that may be formed in the fingers. Those surfaces may be plated or treated to reduce resistance of a contact. In some embodiments, a contact point may extend across the fingers. In other embodiments, a dimple may be formed in the fingers to provide a smaller contact point.

(101) The first ends **1313a** of the second fingers **1313** may have second contact points **1313c** that may be configured to contact the first side of the card. The first contact points **1312c** may contact the first side of the card at different locations than the second contact points **1313c**.

(102) A length of the first fingers **1312** may be less than a length of the second fingers **1313**. Such a configuration enables both a large number of contact points and a low bulk resistance of the power terminal through the use of multiple sheets of metal to form the power terminal. Two sheets of metal are shown joined at the joint region **1340** in FIG. **13A** and at a joint region **1340a''** and **1340b''** in FIG. **13D**. In the embodiment of FIG. **13C**, terminals on opposite sides of a slot are each stamped from two sheets of metal, which are then joined, resulting in four sheets of metal being

joined.

(103) The joined sheets of metal may have different thicknesses in some embodiments. A thickness T1 of the first fingers **1312** may be less than a thickness T2 of the second fingers **1313**, for example. For example, T1 may be between 0.15 mm to 0.25 mm less than T2.

(104) As shown in FIG. **13B**, at least one of the second fingers **1313** may comprise an elongate straight main body and a hook-shaped first end **1313a** connected to the straight main body. The second contact point **1313c** of each of the at least one of the second fingers **1313** may be on the hook-shaped first end **1313a**. For example, the second contact point **1313c** may protrude from the hook-shaped first end **1313a**.

(105) FIG. **13B** shows a terminal assembly with two power terminals having mating portions as shown in FIG. **13A**, but having mounting portions configured for use in a right-angle connector. In the illustrated embodiment, an assembly **130** of power terminals **1300**, **1301** are held within a base **1347** so that the power terminals **1300**, **1301** are aligned with opposite walls of a slot **1345** when the terminal assembly is inserted into an insulative housing **1350**. The base **1347** may be formed in an insert molding operation or in another suitable way. FIG. **13B** shows a cross section through two opposing power terminals **1300**, **1301** in one terminal assembly **130**. It should be appreciated that a terminal assembly may include more or fewer than two terminals, or that alternative constructions techniques may be used, such as inserting power terminals into a connector housing without forming the terminals into terminal assemblies.

(106) As shown in FIG. **13B**, at least one of the first fingers **1312** may comprise an elongate main body having at least one bend and a first end **1312a** connected to the main body. The first end **1312a** is shown with a curved portion. The first contact point **1312c** of each of the at least one of the first fingers **1312** may be on the curved portion of first end **1312a**. For example, the first contact point **1312c** may protrude from the curved first end **1312a**. In this example, the curved portion forms the distal end of the first finger.

(107) The hook-shaped first end **1313a** of the at least one of the second fingers **1313** may be hooked such that there is an opening **1313e** facing the joint region **1340**. As shown in FIG. **13B**, a concave portion of the hook-shaped first end **1313a** may be structured such that the opening **1313e** faces joint region **1340**. As will be appreciated, although the power terminal **1300** may be described herein to have two layers of fingers stacked on each other, variations of the power terminal **1300** may have three or four or more layers of fingers.

(108) FIG. **13C** is a cross section through opposing power terminals in a right angle connector. The power terminals of FIG. **13C**, therefore, have mounting portions configured differently than in FIG. **13A**, but the mating portion may be the same. As shown in FIG. **13C**, a minimum distance from the straight main body of the second fingers **1313** to a tip **1313d** of the hook-shaped first end **1313a** connected to the straight main body is greater than a minimum distance from the straight main body of the second fingers **1313** to a tip **1312d** of the curve-shaped first end **1312a** of the at least one of the first fingers **1312**. With such a structure, the opening **1313e** facing the joint region **1340** faces the tip **1312d** of the curved-shape first end **1312a** of the at least one of the first fingers **1312**.

(109) As shown in FIG. **13A**, the first fingers **1312** may be disposed in a first row in a row direction R, which is parallel to the elongated direction of the slot **1345** into which an edge of a PCB will be inserted. The second fingers **1313** may be disposed in a second row in a second direction parallel to the row direction R. That is, the first row may be parallel to the second row. A width W1 of at least one of the first fingers in a direction parallel to the row direction is less than a width W2 of at least one of the second fingers in a direction parallel to the row direction.

(110) A connector incorporating the power terminal **1300** may comprise the insulative housing **1350** in which the first fingers **1312** and the second fingers **1313** are disposed. The housing **1350** may comprise at least one opening exposing the first and second contact points **1312c**, **1313c** and a slot **1345** configured to receive an edge of a card **1360** therein. The slot **1345** may have a closed end **1346** configured to limit an insertion distance of the card into the slot **1345**.

(111) Upon insertion of the card **1360** into the slot **1345**, contact points of the power terminal **1300** will wipe over a power pad on a surface of the card **1360**. For the longer, second fingers **1313**, a wipe length is a distance $d1$. The distance $d1$, between the second contact points **1313c** and the closed end **1346** of the slot **1345**, may be in a range between 7.5 mm to 9.5 mm.

(112) The wipe length for the shorter, inner (first) finger **1312** is shown as $d3$. The distance $d3$, between the first contact points **1312c** and the closed end **1346** of the slot **1345**, may be in a range between 4.5 mm to 6.5 mm.

(113) The wipe length $d3$ may be less than the wipe length $d1$ by $d2$. The distance $d2$, between one of the first contact points **1312c** and a nearest one of the second contact points **1313c**, may be in a range between 1.5 mm to 3.5 mm. The inventors have recognized and appreciated that making $d2$ smaller increases the wipe length for the inner finger **1312**, which in turn leads to less contact resistance, as wiping can remove oxide on the contact surfaces that might otherwise increase contact resistance.

(114) As mentioned above, the power terminals **1300**, **1301** may be a first power terminal **1300** and a second power terminal **1301** of a power terminal assembly **130**, as schematically shown in FIG. **13B**. One or more such power terminal assemblies may be inserted in the connector housing **1350** or otherwise held together so as to form a power portion of a connector. The second power terminal **1301** may have a same structure as the first power terminal **1300**, and therefore details of this structure will not be repeated. The first and second power terminals **1300**, **1301** may be arranged such that contact points of the first power terminal **1300** face the contact points of the second power terminal **1301**.

(115) More specifically, for the first power terminal **1300**, the first ends **1312a** of the first fingers **1312** may have first contact points **1312c** that are configured to contact a first side **1360a** of a card **1360**, and the first ends **1313a** of the second fingers **1313** may have second contact points **1313c** configured to contact the first side **1360a** of the card **1360**, with the first contact points **1312c** being different from the second contact points **1313c**. For the second power terminal **1301**, the first ends **1312a** of the first fingers **1312** may have first contact points **1312c** configured to contact a second side **1360b** of the card **1360**, and the first ends **1313a** of the second fingers **1313** may have second contact points **1313c** configured to contact the second side **1360b** of the card **1360**, with the first contact points **1312c** being different from the second contact points **1313c**. A portion of each of the first and second power terminals **1300**, **1301** may be disposed in the housing **1350** such that the first and second contact points **1312c**, **1313c** of the second power terminal **1301** face the first and second contact points **1312c**, **1313c** of the first power terminal **1300** across a gap.

(116) The first contact points **1312c** of the first fingers **1312** of the first power terminal **1300** and the first contact points of the first fingers of the second power terminal **1301** may be separated by a distance $X_{sub.1}$. The second contact points **1313c** of the second fingers **1313** of the first power terminal **1300** and the second contact points of the second fingers of the second power terminal **1301** may be separated by a distance $X_{sub.2}$. $X_{sub.1}$ may be in a range of 0.75 mm to 0.95 mm, and $X_{sub.2}$ may be in a range of 0.80 mm to 1.00 mm. Optionally, $X_{sub.1}$ may be in a range of 0.82 mm to 0.86 mm, and $X_{sub.2}$ may be in a range of 0.88 mm to 0.92 mm.

(117) In the alternative embodiment illustrated in the perspective view of FIG. **13D**, the power terminals **1300a''**, **1300b''** may be inserted into a housing, with or without first being held in a base to form an assembly. As with the other power terminals described above, the power terminals **1300a''**, **1300b''** of FIG. **13D** may be formed of multiple layers. Here two such layers are shown, resulting in power terminals with outer fingers **1313a''**, **1313b''** and inner fingers **1312a''**, **1312b''**. In the illustrated embodiment, there are the same number of inner and outer fingers, and the contact points of the inner and outer fingers are aligned in a direction of insertion of a card to mate with the terminals.

(118) The power terminals **1300a''**, **1300b''** illustrated in FIG. **13D** have longer fingers and shorter fingers. The longer fingers have hooked ends, such that distal tips of the longer fingers curve back

towards distal tips of the shorter fingers. Contact points of the longer fingers are disposed on portions that curl back towards the shorter fingers, such that the wipe distance for both the longer and shorter fingers is similar, which can be desirable. Moreover, such a configuration is resistant to mechanical stubbing because the distal tips of the longer fingers point away from the insertion direction of a card, and the distal tips of the shorter fingers are guarded by the hooked portions of the longer fingers.

(119) FIG. 14A is a perspective view of an alternative embodiment of a power terminal **1400**, and FIG. 14B shows an exploded view of the power terminal **1400** of FIG. 14A. The arrangement of the power terminal **1400** may facilitate inspection of a contact gap between the two rows of fingers, and also may provide a good wipe length compared with other arrangements. FIGS. 15A and 15B show top and bottom plan views of a power terminal assembly **14**, which may have a pair of power terminals facing each other, such as the first and second power terminals **1400**, **1800** discussed below. FIGS. 15C and 15D show top and bottom perspective views of the mating portion of the power terminal assembly **14**. As with FIGS. 14A and 14B, mounting portions of the assembly **14** are not shown, for the sake of simplicity. FIG. 15E shows a side elevational view of a mating portion of the power terminal assembly **14**. Three-dimensional renderings of the line drawings in FIGS. 14A and 15A-15D are shown in FIGS. 14A' and 15A'-15D', to illustrate more clearly curvatures and other features that may not be easily seen in the line drawings.

(120) The power terminal **1400** may be constructed from two or more sheets into which fingers are formed, e.g., by stamping. The sheets may be laid one on top of the other such that contact points on each of the fingers faces the same direction for contacting a power pad on an edge of a card inserted into a connector including the power terminal **1400**. In the illustrated embodiment, the power terminal **1400** may comprise a pair of first fingers **1401**, a second finger **1402**, and a base **1403** to which the first and second fingers **1401**, **1402** are attached. The first fingers **1401** may comprise first ends **1401a** spaced apart from each other and second ends **1401b** connected to each other. The second finger **1402** may comprise a first end **1402a** and a second end **1402b**.

(121) The base **1403** may be configured to hold the second ends **1401b**, **1402b** of the first and second fingers **1401**, **1402**. The base **1403**, for example, may be an insulator molded around portions of the first and second fingers **1401**, **1402** of the terminal **140**. The second ends **1401b**, **1402b** of the first and second fingers **1401**, **1402** may be electrically and/or mechanically connected, such as by welding or soldering, before they are inserted or molded into the base **1403**. Alternatively or additionally, the second ends **1401b**, **1402b** of the first and second fingers **1401**, **1402** may be electrically connected as a result of being held together in the base **1403**. FIG. 14A does not show a mounting portion of the terminal **1400**, but a mounting portion, in a configuration as described above or in any other suitable configuration, may extend from the base **1403**. An opposing power terminal **1800** may be held in the same base **1403**, opposite the power terminal **1400**, to form a power terminal assembly **14** (see FIGS. 14C and 15E), discussed below. Such assemblies may be inserted into a connector housing forming a power portion of a hybrid connector, or power terminals **1400** may be inserted directly into a connector housing, as described above in connection with other embodiments.

(122) As will be appreciated from the discussion above, the base **1403** may be molded around the second ends **1401b**, **1402b** of the first and second fingers **1401**, **1402**, and therefore the base **1403** and the second ends **1401b**, **1402b** are depicted schematically in the figures and may be shaped differently than depicted in the figures.

(123) The first ends **1401a**, **1402a** of the first and second fingers **1401**, **1402** may each have a contact surface **1401c**, **1402c** configured to engage with and physically contact a PCB or a conductive blade (not shown). The first end **1402a** of the second finger **1402** may be positioned in a space between the first ends **1401a** of the first fingers **1401** such that the contact surfaces **1401c**, **1402c** of the first and second fingers **1401**, **1402** may be coplanar and aligned in a row direction R (see FIG. 14C). The second ends **1401b** of the first fingers **1401** may be aligned with the second

end **1402b** of the second finger **1402** in a second direction S different from the row direction R. For example, the second end **1402b** of the second finger **1402** may be stacked on the second ends **1401b** of the first fingers **1401**.

(124) The power terminal **1400** may be a first power terminal **1400** of the power terminal assembly **14**, which may also comprise a second power terminal **1800** in addition to the first power terminal **1400**, as shown in FIGS. **15C-15E**. The second power terminal **1800** may have a same structure as the first power terminal **1400**, and therefore details of this structure will not be repeated (reference numerals designated **18 ##** for the second power terminal **1800** may be used for features analogous to the reference numerals **14 ##** used for the first power terminal **1400**). The first and second power terminals **1400**, **1800** may be attached to the base **1403** such that the first power terminal **1400** faces the second power terminal **1800**. The base **1403** may be an electrically insulative base or an electrically conductive base.

(125) Similar to a connector formed with a power terminal, such as **1300** as described above, the contact surfaces **1401c**, **1402c** of the first power terminal **1400** may be configured to face corresponding contact surfaces **1801c**, **1802c** of the second power terminal **1800** across a gap **1503**. A card-receiving slot **1505** may be formed by external portions of the second fingers **1402**, **1802** of the first and second power terminals **1400**, **1800** that face each other across the gap **1503**, the contact surfaces **1401c**, **1402c**, **1801c**, **1802c** of the first and second power terminals **1400**, **1800** that face each other across the gap **1503**, and a lateral portion **1507** of the base **1403** between the first and second power terminals **1400**, **1800**.

(126) The lateral portion **1507** of the base **1403** may be configured to limit an insertion distance of a PCB or a conductive blade inserted into the card-receiving slot **1505**. The contact surfaces **1401c**, **1402c** of the first power terminal **1400** may be configured to contact a first side of the PCB or conductive blade, and the contact surfaces **1801c**, **1802c** of the second power terminal **1800** may be configured to contact a second side of the PCB or conductive blade.

(127) FIG. **16A** shows a bottom plan view of a first sheet of metal used to form the power terminal **1400**, stamped to form the pair of first fingers **1401**. FIG. **16B** shows a bottom perspective view of the pair of first fingers **1401**. FIG. **16C** shows a top perspective view of the pair of first fingers **1401**. FIG. **16D** shows a side elevational view of the pair of first fingers **1401**. As can be seen in FIGS. **16A-16D**, the first fingers **1401** are stamped to leave a larger gap **1610** between adjacent fingers **1401** in a distal region, and a smaller gap **1612** in a proximal region, closer to the base (not shown). The larger gap **1610** may accommodate a distal segment of the second finger **1402**. The smaller gap **1612** may enable the first fingers **1401** to flex independently of each other.

(128) FIG. **17A** shows a bottom plan view of a second sheet of metal used to form the power terminal **1400**, stamped to form the second finger **1402**. FIG. **17B** shows a bottom perspective view of the second finger **1402**. FIG. **17C** shows a side elevational view of the second finger **1402**.

(129) A total width $D_{sub.A}$ of the first fingers **1401** at the second ends **1401b**, at a region external to the base **1403**, may be within 10% of a width $D_{sub.B}$ at the second end **1402b** of the second finger **1402** at a region external to the base **1403**. The widths $D_{sub.A}$, $D_{sub.B}$ may be dimensions parallel to the row direction R.

(130) A width $D_{sub.C}$ at the first end **1401a** of at least one of the first fingers **1401** may be within 10% of a width $D_{sub.D}$ at the first end **1402a** of the second finger **1402**. The widths $D_{sub.C}$, $D_{sub.D}$ may be dimensions parallel to the row direction R.

(131) The second finger **1402** may have a first, distal segment **1402t** (or **1802t** for terminal **1800**) that fits in the gap **1610** between the first fingers **1401** (or **1801**) of the first sheet. The second finger **1402** may have a second, proximal segment **1402s** (or **1802s** for the second power terminal **1800**). The first segment **1402t** may have a width $D_{sub.D}$. An average width of the second segment **1402s** may be greater than an average width of the first segment **1402t**. This configuration enables a distal end of finger **1402** to fit in gap **1610** between fingers **1401**, while providing a lower resistance for finger **1402** than were second finger **1402** of uniform width. This shape may also

provide a greater wipe length.

(132) The width D.sub.B at the second end **1402b** of the second finger **1402**, at a region external to the base **1403** (not shown in FIGS. 17A-17C), may be greater than the width D.sub.D at the first end **1402a** of the second finger **1402**. The second segment **1402s** of the second finger **1402** may have a width that increases from the width D.sub.D, where the second segment **1402s** is joined to first segment **1402t**, to the width D.sub.B at the base **1403**. The width may increase monotonically over the second segment **1402s**. In the embodiment illustrated, for example, the width tapers linearly. However, the second segment **1402s** need not have the same width as the first segment **1402t** where segments **1402t** and **1402s** join. The second segment **1402s**, for example, may have the width D.sub.B over its entire length or otherwise have a width larger than the width D.sub.B where the first and second segments **1402t**, **1402s** join.

Embodiment 1

(133) According to aspects of a first embodiment of the present technology, a power terminal for use in a connector is provided. The power terminal may comprise a first plurality of first fingers and a second plurality of second fingers. The first plurality may be greater in number than the second plurality. The first plurality of first fingers may comprise first ends spaced apart from each other in a first direction and second ends connected to each other. The second plurality of second fingers may comprise first ends spaced apart from each other in the first direction and second ends connected to each other. The first ends of the second fingers may be spaced apart from the first ends of the first fingers in a second direction, perpendicular to the first direction. The second ends of the first fingers may be electrically connected to the second ends of the second fingers at a joint region. The first ends of the first fingers may have first contact points configured to contact a first side of a card, and the first ends of the second fingers may have second contact points configured to contact the first side of the card. The first contact points may be different from the second contact points.

(134) A terminal according to the first embodiment may have one or more of the following characteristics:

(135) A distance (d2) between one of the first contact points and a nearest one of the second contact points may be in a range between 1.5 mm to 3.5 mm. Alternatively, the distance (d2) may be less than or equal to 3.5 mm.

(136) A length of the first fingers may be less than a length of the second fingers.

(137) A thickness of the first fingers may be less than a thickness of the second fingers. For example, the thickness of the first fingers may be between 0.15 mm to 0.25 mm less than the thickness of the second fingers.

(138) At least one of the second fingers may comprise an elongate straight main body and a hook-shaped first end connected to the straight main body. The second contact point of the at least one of the second fingers may be on the hook-shaped first end.

(139) The hook-shaped first end may comprise a convex surface, and the second contact point of the at least one of the second fingers may be on the convex surface of the hook-shaped first end.

(140) At least one of the first fingers may comprise an elongate main body having at least one bend and a curved first end connected to the main body. The first contact point of the at least one of the first fingers may be on the curved first end.

(141) The curved first end may comprise a convex surface. The first contact point of the at least one of the first fingers may be on the convex surface of the curved first end.

(142) At least one of the second fingers may comprise an elongate straight main body and a hook-shaped first end connected to the straight main body. The hook-shaped first end may have an opening facing the joint region.

(143) A minimum distance from the straight main body of the at least one of the second fingers to a tip of the hook-shaped first end connected to the straight main body of the at least one of the second fingers may be greater than a minimum distance from the straight main body of the at least

one of the second fingers to a tip of the curve-shaped first end of the at least one of the first fingers, such that the opening facing the joint region may face the tip of the curved-shape first end of the at least one of the first fingers.

(144) The first fingers may be disposed in a first row in a row direction, and the second fingers may be disposed in a second row in a second direction parallel to the row direction. A width of at least one of the first fingers in a direction parallel to the row direction may be less than a width of at least one of the second fingers in a direction parallel to the row direction.

(145) A terminal according to the first embodiment may be in combination with an insulative housing in which the first fingers and the second fingers are disposed. The combination may have one or more of the following characteristics:

(146) The insulative housing may comprise at least one opening exposing the first and second contact points, and a slot configured to receive the card therein.

(147) The slot may have a closed end configured to limit an insertion distance of the card into the slot.

(148) A distance between the second contact points and the closed end of the slot may be in a range between 7.5 mm to 9.5 mm.

(149) The distance between the second contact points and the closed end of the slot may be a wipe length of the terminal.

(150) A distance (d3) between the first contact points and the closed end of the slot may be in a range between 4.5 mm to 6.5 mm.

Embodiment 2

(151) According to aspects of a second embodiment of the present technology, a power terminal assembly for a card edge connector is provided. The terminal assembly may comprise first and second terminals and an insulative housing supporting the first and second terminals. Each of the first and second terminals may comprise a first plurality of first fingers comprising first ends spaced apart from each other in a first direction and second ends connected to each other, and a second plurality of second fingers comprising first ends spaced apart from each other in the first direction and second ends connected to each other. For each of the first and second terminals: the first ends of the second fingers may be spaced apart from the first ends of the first fingers in a second direction, perpendicular to the first direction; the first plurality may be greater in number than the second plurality; and the second ends of the first fingers may be electrically connected to the second ends of the second fingers at a joint region.

(152) For the first terminal, the first ends of the first fingers may have first contact points configured to contact a first side of a card, the first ends of the second fingers may have second contact points configured to contact the first side of the card, and the first contact points may be different from the second contact points. For the second terminal, the first ends of the first fingers may have first contact points configured to contact a second side of the card, the first ends of the second fingers may have second contact points configured to contact the second side of the card, and the first contact points may be different from the second contact points. A portion of each of the first and second terminals may be disposed in the insulative housing such that the first and second contact points of the second terminal may face the first and second contact points of the first terminal across a gap.

(153) A terminal assembly according to the second embodiment may have one or more of the following characteristics:

(154) A distance (d2) between one of the first contact points of the first terminal and a nearest one of the second contact points of the first terminal may be less than 3.5 mm. For example, the distance (d2) may be in a range of 2.5 mm to 3.5 mm.

(155) The insulative housing may comprise openings exposing the first and second contact points of the first and second terminals, and a slot configured to receive the card therein, the slot comprising the gap.

(156) The slot may have a closed end configured to limit an insertion distance of the card into the slot.

(157) A distance (d_1) between the second contact points of the first and second terminals and the closed end of the slot may be in a range between 7.5 mm to 9.5 mm.

(158) The distance (d_1) between the second contact points of the first and second terminals and the closed end of the slot may be a wipe length of the terminal.

(159) A distance (d_3) between the first contact points of the first and second terminals and the closed end of the slot may be in a range between 4.5 mm to 6.5 mm.

(160) The first fingers of the first and second terminals may be closer to a closed end of the slot than the second fingers of the first and second terminal.

Embodiment 3

(161) According to aspects of a third embodiment of the present technology, a power terminal for a connector is provided. The power terminal may comprise first and second conductive sheets. The first conductive sheet may comprise at least two first fingers comprising first ends spaced apart from each other and second ends connected to each other. The second conductive sheet may comprise a second finger comprising a first end and a second end.

(162) The first ends of the first and second fingers each may have a contact surface thereon. The first end of the second finger may be positioned in a space between the first ends of adjacent ones of the first fingers. The second finger may comprise a first segment comprising the first end of the second finger and having a first average width, and a second segment joined to the first segment and having a second average width greater than the first average width.

(163) A terminal according to the third embodiment may have one or more of the following characteristics:

(164) A total width of the first fingers at the second ends may be within 10% of a width at the second end of the second finger external to the base. Each of the widths at the second ends of the first and second fingers may be a dimension parallel to the row direction.

(165) A width at the first end of at least one of the first fingers may be within 10% of a width at the first end of the second finger. Each of the widths at the first ends of the at least one first finger and the second finger being a dimension parallel to the row direction.

(166) A width at the second segment may increase from a first end, joined to the first segment, to a second end, opposite the first end.

(167) The width of the second segment may taper linearly to the width at the first end of the second finger.

(168) A terminal assembly may comprise a plurality of terminals according to the third embodiment in combination with an insulative member. The combination may have one or more of the following characteristics:

(169) The plurality of terminals may comprise a first terminal and a second terminal. The insulative member may be attached to the first terminal and the second terminal, such that contact surfaces of the second terminal may face contact surfaces of the first terminal across a gap.

(170) The second terminal may be a duplicate of the first terminal, such that the contact surfaces of the second terminal may directly face the contact surfaces of the first terminal across the gap.

(171) The second terminal may comprise a pair of first fingers and a second finger. The second fingers of the first and second terminals may have intermediate portions that face each other across the gap. A card-receiving slot may be disposed between the intermediate portions of the second fingers that face each other across the gap, and the contact surfaces of the first and second terminals that face each other across the gap.

(172) A portion of the insulative member between the first and second insertions portions may be configured to limit an insertion distance of a card inserted into the card-receiving slot.

(173) The contact surfaces of the first terminal may be configured to contact a first side of the card, and the contact surfaces of the second terminal may be configured to contact a second side of the

card.

Embodiment 4

(174) According to aspects of a fourth embodiment of the present technology, a power terminal for a connector is provided. The terminal may comprise a first terminal portion comprising a plurality of metal layers stacked in a layer direction. Each metal layer may comprise fingers arranged in a row direction different from the layer direction. The fingers of the metal layers may form rows of contact surfaces such that a first row of contact surfaces corresponding to a first one of the metal layers may be parallel to a second row of contact surfaces corresponding to a second one of the metal layers.

(175) The fingers of the first one of the metal layers may comprise distal ends curved into hooks having convex surfaces. The first row of contact surfaces may be disposed on the convex surfaces of the hooks of the first one of the metal layers. The fingers of the second one of the metal layers may comprise curved distal ends having convex surfaces. The second row of contact surfaces may be disposed on the convex surfaces of the curved distal ends of the fingers of the second one of the metal layers. The rows of contact surfaces of the metal layers of the first terminal portion may be configured to contact a same mating surface.

(176) A terminal according to the fourth embodiment may have one or more of the following characteristics:

(177) The fingers of one of the metal layers may have a length that is different from a length of the fingers of another one of the metal layers.

(178) The fingers of one of the metal layers may have a length that is same as a length of the fingers of another one of the metal layers.

(179) A total number of metal layers may be three or four or more.

(180) The terminal may further comprise a second terminal portion comprising a plurality of metal layers stacked in the layer direction. Each metal layer of the second terminal portion may comprise fingers arranged in direction parallel to the row direction. The fingers of the metal layers of the second terminal portion may form rows of contact surfaces such that a first row of contact surfaces corresponding to a first one of the metal layers of the second terminal portion may be parallel to a second row of contact surfaces corresponding to a second one of the metal layers of the second terminal portion. The fingers of the first one of the metal layers of the second terminal portion may comprise distal ends curved into hooks having convex surfaces. The first row of contact surfaces of the second terminal portion may be disposed on the convex surfaces of the hooks of the first one of the metal layers of the second terminal portion. The fingers of the second one of the metal layers of the second terminal portion may comprise curved distal ends having convex surfaces. The second row of contact surfaces of the second terminal portion may be disposed on the convex surfaces of the curved distal ends of the fingers of the second one of the metal layers of the second terminal portion. The rows of contact surfaces of the metal layers of the second terminal portion may be configured to contact an opposite side of the card from the rows of contact surfaces of the metal layers of the first terminal portion.

(181) Each of the fingers of the metal layers may be configured to carry up to 30 amps of current, or to 35 amps of current, or up to 40 amps of current, or up to 45 amps of current, with a maximum temperature increase of 30° C. above an ambient temperature.

CONCLUSION

(182) The foregoing features may be used, separately or together in any combination, in any of the embodiments discussed herein.

(183) Further, although advantages of the present invention are indicated, it should be appreciated that not every embodiment of the invention will include every described advantage. Some embodiments may not implement any features described as advantageous herein. Accordingly, the foregoing description and attached drawings are by way of example only.

(184) Variations on the disclosed embodiment are possible. For example, though power terminals

are described as configured for use in card edge connectors, terminals with mating interfaces as described herein may be used in connectors configured to mate with other types of components. For example, power terminals as described herein may be inserted in a connector housing configured to receive a bus bar or blade-type terminals held in a housing of a mating connector.

(185) Various aspects of the present invention may be used alone, in combination, or in a variety of arrangements not specifically discussed in the embodiments described in the foregoing and is therefore not limited in its application to the details and arrangement of components set forth in the foregoing description or illustrated in the drawings. For example, aspects described in one embodiment may be combined in any manner with aspects described in other embodiments.

(186) Use of ordinal terms such as “first,” “second,” “third,” etc., in the description and the claims to modify an element does not by itself connote any priority, precedence, or order of one element over another, or the temporal order in which acts of a method are performed, but are used merely as labels to distinguish one element or act having a certain name from another element or act having a same name (but for use of the ordinal term) to distinguish the elements or acts.

(187) All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

(188) The indefinite articles “a” and “an,” as used herein in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean “at least one.”

(189) As used herein in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified.

(190) As used herein in the specification and in the claims, the phrase “equal” or “the same” in reference to two values (e.g., distances, widths, etc.) means that two values are the same within manufacturing tolerances. Thus, two values being equal, or the same, may mean that the two values are different from one another by +5%.

(191) The phrase “and/or,” as used herein in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

(192) As used herein in the specification and in the claims, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the claims, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used herein shall only be interpreted as indicating exclusive alternatives (i.e. “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Consisting essentially of,” when used in the

claims, shall have its ordinary meaning as used in the field of patent law.

(193) Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. Use of terms such as “including,” “comprising,” “comprised of,” “having,” “containing,” and “involving,” and variations thereof herein, is meant to encompass the items listed thereafter and equivalents thereof as well as additional items.

(194) The terms “approximately” and “about” if used herein may be construed to mean within $\pm 20\%$ of a target value in some embodiments, within $\pm 10\%$ of a target value in some embodiments, within $\pm 5\%$ of a target value in some embodiments, and within $\pm 2\%$ of a target value in some embodiments. The terms “approximately” and “about” may equal the target value.

(195) The term “substantially” if used herein may be construed to mean within 95% of a target value in some embodiments, within 98% of a target value in some embodiments, within 99% of a target value in some embodiments, and within 99.5% of a target value in some embodiments. In some embodiments, the term “substantially” may equal 100% of the target value.

Claims

1. A power terminal for a connector, the power terminal comprising: a first conductive sheet comprising at least two first fingers comprising first ends spaced apart from each other and second ends connected to each other; and a second conductive sheet comprising at least one second finger comprising a first end and a second end, wherein: the first ends of the first and second fingers each have a contact surface thereon, the first end of the at least one second finger is positioned between the first ends of adjacent ones of the first fingers, the contact surfaces of the first ends of the first and second fingers are coplanar and are aligned in a row direction, the first end of a second finger of the at least one second finger has a smaller width than that of the second end of the second finger, and the second finger is tapered in a region between the first end and the second end.
2. The power terminal of claim 1, wherein the second end of the at least one second finger is stacked on the second ends of the at least two first fingers.
3. The power terminal of claim 1, further comprising: an insulative member supporting the second ends of the at least two first fingers and the second end of the at least one second finger.
4. The power terminal of claim 3, wherein the second ends of the at least two first fingers and the second end of the at least one second finger are inserted into the insulative member.
5. The power terminal of claim 3, wherein the insulative member is molded around the second ends of the at least two first fingers and the second end of the at least one second finger.
6. The power terminal of claim 1, wherein the first conductive sheet is welded to the second conductive sheet.
7. The power terminal of claim 1, wherein: the first conductive sheet comprises more fingers than the second conductive sheet; and the second conductive sheet comprises at least one finger with a larger average width than the fingers of the first conductive sheet.
8. The power terminal of claim 1, wherein the at least one second finger comprises: a first segment comprising the first end of the at least one second finger and having a first average width, and a second segment joined to the first segment and having a second average width greater than the first average width.
9. A power terminal for a connector, the power terminal comprising: a first conductive sheet comprising at least two first fingers comprising first ends spaced apart from each other and second ends connected to each other; and a second conductive sheet comprising at least one second finger comprising a first end and a second end, wherein: the first ends of the first and second fingers each have a contact surface thereon, the first end of the at least one second finger is positioned between the first ends of adjacent ones of the first fingers, the contact surfaces of the first ends of the first and second fingers are coplanar and are aligned in a row direction, and a gap between the first fingers at a distal region, near the first ends of the first fingers, is larger than a gap between the first

fingers at a proximal region, near the second ends of the first fingers.

10. A power terminal assembly for a connector, the power terminal assembly comprising: a first power terminal, comprising: a first conductive sheet comprising at least two first fingers comprising first ends spaced apart from each other and second ends connected to each other; and a second conductive sheet comprising at least one second finger comprising a first end and a second end, wherein: the first ends of the first and second fingers each have a contact surface thereon, and the first end of the at least one second finger is positioned between the first ends of adjacent ones of the first fingers; a second power terminal, comprising: a third conductive sheet comprising at least two third fingers comprising first ends spaced apart from each other and second ends connected to each other; and a fourth conductive sheet comprising at least one fourth finger comprising a first end and a second end, wherein: the first ends of the third and fourth fingers each have a contact surface thereon, and the first end of the at least one fourth finger is positioned between the first ends of adjacent ones of the third fingers; and an insulative member supporting the first and second power terminals, wherein the first and second power terminals are positioned such that the contact surfaces of the first and second fingers of the first power terminal face the contact surfaces of the third and fourth fingers of the second power terminal across a gap.

11. The power terminal assembly of claim 10, wherein the contact surfaces of the first ends of the first and second fingers of the first power terminal are coplanar.

12. The power terminal assembly of claim 10, wherein the contact surfaces of the first ends of the first and second fingers of the first power terminal are aligned in a row direction.

13. The power terminal assembly of claim 10, wherein the insulative member supporting the first and second power terminals supports the second ends of the first, second, third and fourth fingers.

14. The power terminal assembly of claim 10, wherein at least a portion of the first and second conductive sheets of the first power terminal and at least a portion of the second and third conductive sheets of the second power terminal are inserted into the insulative member.

15. The power terminal assembly of claim 10, wherein the insulative member is molded around at least a portion of the first and second conductive sheets of the first power terminal and at least a portion of the second and third conductive sheets of the second power terminal.

16. The power terminal assembly of claim 10, wherein the first conductive sheet is welded to the second conductive sheet and the third conductive sheet is welded to the fourth conductive sheet.

17. The power terminal assembly of claim 10, wherein: the first conductive sheet comprises more fingers than the second conductive sheet; and the second conductive sheet comprises at least one finger with a larger average width than the fingers of the first conductive sheet.

18. The power terminal assembly of claim 10, wherein the at least one second finger of the first power terminal comprises: a first segment comprising the first end of the at least one second finger and having a first average width, and a second segment joined to the first segment and having a second average width greater than the first average width.

19. The power terminal assembly of claim 10, wherein a gap between the first fingers of the first power terminal at a distal region, near the first ends of the first fingers, is larger than a gap between the first fingers at a proximal region, near the second ends of the first fingers.

20. The power terminal assembly of claim 10, wherein the contact surfaces of the first and second fingers of the first power terminal are configured to contact a first side of a card inserted into the gap and the third and fourth fingers of the second power terminal are configured to contact a second side of the card.
