

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418151
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Cutsforth; Robert S. et al.

System and method for monitoring the status of one or more components of an electrical machine

Abstract

A system for monitoring the wear state of a carbon brush of a brush holder assembly in which the length of the carbon brush is diminished from an initial length as an end of the carbon brush wears away during use. The system includes a wear state monitor, including a sensor, coupled to the carbon brush. The wear state monitor is configured to rotate as the length of the carbon brush diminishes. The sensor is configured to measure an angular displacement of the wear state monitor as the wear state monitor rotates. The measured angular displacement of the wear state monitor correlates to an amount of diminution in the length of the carbon brush.

Inventors: Cutsforth; Robert S. (Bellingham, WA), Cutsforth; Dustin L. (Leawood, KS), Bruey; Douglas Christopher (Seattle, WA), Schaaf; Michael Lee (Seattle, WA), Harrison; David William Drury (Seattle, WA)

Applicant: CUTSFORTH, INC. (Minneapolis, MN)

Family ID: 1000008818854

Assignee: CUTSFORTH, INC. (Minneapolis, MN)

Appl. No.: 18/660394

Filed: May 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240291217 A1	Aug. 29, 2024

Related U.S. Application Data

continuation parent-doc US 17529521 20211118 US 12003067 child-doc US 18660394
continuation parent-doc US 16592269 20191003 US 11211757 20211228 child-doc US 17529521

Publication Classification

Int. Cl.: **H02K11/20** (20160101); **G01B21/22** (20060101); **H01R39/26** (20060101); **H01R39/38** (20060101); **H01R39/58** (20060101); **H02K13/00** (20060101)

U.S. Cl.:

CPC **H01R39/58** (20130101); **G01B21/22** (20130101); **H01R39/26** (20130101); **H01R39/38** (20130101); **H02K11/20** (20160101);

Field of Classification Search

CPC: H02K (11/20); H02K (11/13); H01R (39/58); H01R (39/26); H01R (39/38)

USPC: 310/68B; 310/242

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1307028	12/1918	Sweet	N/A	N/A
2935632	12/1959	Schmitz	N/A	N/A
3523288	12/1969	Thompson	N/A	N/A
3534206	12/1969	Carey	N/A	N/A
3634710	12/1971	Woda	N/A	N/A
3641379	12/1971	Vick	N/A	N/A
4024525	12/1976	Baumgartner et al.	N/A	N/A
4058804	12/1976	Sawada et al.	N/A	N/A
4121207	12/1977	Jones	N/A	N/A
4172988	12/1978	Lowther	N/A	N/A
4272695	12/1980	Buchwald et al.	N/A	N/A
4316186	12/1981	Purdy et al.	N/A	N/A
4329611	12/1981	Ohmstedt et al.	N/A	N/A
4329683	12/1981	Kimberlin	N/A	N/A
4333095	12/1981	Silva	N/A	N/A
4334072	12/1981	Becker et al.	N/A	N/A
4344009	12/1981	Reynolds	N/A	N/A
4344072	12/1981	Harper	N/A	N/A
4348608	12/1981	Michael	N/A	N/A
4355254	12/1981	Oki et al.	N/A	N/A
4359685	12/1981	Eguchi et al.	N/A	N/A
4390870	12/1982	Michael	N/A	N/A
4400638	12/1982	Albrecht et al.	N/A	N/A
4420705	12/1982	Kimberlin	N/A	N/A
4488078	12/1983	Orton	N/A	N/A
4513495	12/1984	Kimberlin	N/A	N/A
4528556	12/1984	Maddox	N/A	N/A

4528557	12/1984	Braun	N/A	N/A
4536670	12/1984	Mayer	N/A	N/A
4542374	12/1984	Kollmannsberger et al.	N/A	N/A
4577151	12/1985	Tanisaka et al.	N/A	N/A
4636778	12/1986	Corkran et al.	N/A	N/A
4646001	12/1986	Baldwin et al.	N/A	N/A
4652783	12/1986	Cheesmore et al.	N/A	N/A
4723084	12/1987	Reynolds	N/A	N/A
4739208	12/1987	Kimberlin	N/A	N/A
4743787	12/1987	Bunner et al.	N/A	N/A
4761594	12/1987	Rodi et al.	N/A	N/A
4831302	12/1988	Dietrich et al.	N/A	N/A
4831602	12/1988	Kroenert et al.	N/A	N/A
4918348	12/1989	Fitzsimmons et al.	N/A	N/A
4950933	12/1989	Pipkin et al.	N/A	N/A
4977345	12/1989	Toperzer	N/A	N/A
5157372	12/1991	Langford	N/A	N/A
5185967	12/1992	Cutsforth	N/A	N/A
5229817	12/1992	Lange et al.	N/A	N/A
5256925	12/1992	Cutsforth	N/A	N/A
5327184	12/1993	Nomura et al.	N/A	N/A
5387831	12/1994	Yang	N/A	N/A
5397952	12/1994	Decker et al.	N/A	N/A
5463264	12/1994	Koenitzer	N/A	N/A
5488261	12/1995	Swoboda et al.	N/A	N/A
5509625	12/1995	Oullette et al.	N/A	N/A
5621262	12/1996	Han	N/A	N/A
5643264	12/1996	Sherman et al.	N/A	N/A
5731650	12/1997	Scheucher	N/A	N/A
5739619	12/1997	Thornley	N/A	N/A
5753992	12/1997	Avitable et al.	N/A	N/A
5753995	12/1997	Ogino	N/A	N/A
5870026	12/1998	Challenger	N/A	N/A
6034531	12/1999	Senglat et al.	N/A	N/A
6067159	12/1999	Discenzo et al.	N/A	N/A
6111643	12/1999	Discenzo et al.	N/A	N/A
6255955	12/2000	Blaettner	N/A	N/A
6359690	12/2001	Discenzo et al.	N/A	N/A
6495940	12/2001	Kliman et al.	N/A	N/A
6552467	12/2002	Suriano et al.	N/A	N/A
6580511	12/2002	Discenzo	N/A	N/A
6598597	12/2002	Marocco et al.	N/A	N/A
6652360	12/2002	Cutsforth	N/A	N/A
6731042	12/2003	Bank et al.	N/A	N/A
6933650	12/2004	Wang	N/A	N/A
6960922	12/2004	Klaar	N/A	N/A
6966754	12/2004	Wobben	N/A	N/A
6972681	12/2004	Matsuoka et al.	N/A	N/A
7005964	12/2005	Edmonson et al.	N/A	N/A

7010959	12/2005	Dingfelder et al.	N/A	N/A
7034430	12/2005	Custforth et al.	N/A	N/A
7045929	12/2005	Yu	N/A	N/A
7049532	12/2005	Kanazawa et al.	N/A	N/A
7122935	12/2005	Custforth et al.	N/A	N/A
7141906	12/2005	Custforth et al.	N/A	N/A
7169022	12/2006	Cutsforth	N/A	N/A
7218028	12/2006	Annis et al.	N/A	N/A
7248142	12/2006	Beck et al.	N/A	N/A
7277004	12/2006	Beck et al.	N/A	N/A
7358640	12/2007	Itou et al.	N/A	N/A
7365470	12/2007	Eger et al.	N/A	N/A
7417354	12/2007	Cutsforth et al.	N/A	N/A
7485882	12/2008	Zombo et al.	N/A	N/A
7545072	12/2008	Cutsforth	N/A	N/A
7551288	12/2008	Discenzo	N/A	N/A
7564160	12/2008	Cutsforth et al.	N/A	N/A
7705744	12/2009	Cutsforth	N/A	N/A
7768174	12/2009	Cutsforth et al.	N/A	N/A
7816834	12/2009	Cutsforth	N/A	N/A
7880362	12/2010	Cutsforth et al.	N/A	N/A
7880363	12/2010	Cutsforth et al.	N/A	N/A
7916038	12/2010	Cutsforth	N/A	N/A
7960892	12/2010	Cutsforth	N/A	N/A
7969059	12/2010	Cacal et al.	N/A	N/A
7990018	12/2010	Cutsforth et al.	N/A	N/A
7994683	12/2010	Cutsforth et al.	N/A	N/A
8047083	12/2010	Puzio et al.	N/A	N/A
8054190	12/2010	Hobelsberger	N/A	N/A
8084704	12/2010	Mark et al.	N/A	N/A
8120503	12/2011	Mark et al.	N/A	N/A
8134472	12/2011	Cutsforth	N/A	N/A
8159396	12/2011	Folden et al.	N/A	N/A
8165552	12/2011	Rofougaran et al.	N/A	N/A
8179014	12/2011	Cutsforth et al.	N/A	N/A
8493707	12/2012	Cutsforth	N/A	N/A
8546993	12/2012	Cutsforth et al.	N/A	N/A
8618943	12/2012	Cutsforth et al.	N/A	N/A
8714860	12/2013	Cutsforth	N/A	N/A
8825800	12/2013	Cutsforth	N/A	N/A
8922092	12/2013	Cutsforth	N/A	N/A
9099827	12/2014	Cutsforth	N/A	N/A
9178327	12/2014	Cutsforth	N/A	N/A
9209667	12/2014	Cutsforth	N/A	N/A
9252643	12/2015	Cutsforth	N/A	N/A
9287674	12/2015	Cutsforth et al.	N/A	N/A
9287675	12/2015	Cutsforth et al.	N/A	N/A
9287676	12/2015	Cutsforth et al.	N/A	N/A
9293879	12/2015	Cutsforth et al.	N/A	N/A
9293880	12/2015	Cutsforth et al.	N/A	N/A

9293881	12/2015	Cutsforth et al.	N/A	N/A
9331555	12/2015	Fish et al.	N/A	N/A
9350130	12/2015	Cutsforth et al.	N/A	N/A
9560729	12/2016	Cutsforth et al.	N/A	N/A
9590375	12/2016	Cutsforth et al.	N/A	N/A
9590376	12/2016	Cutsforth	N/A	N/A
9640930	12/2016	Cutsforth	N/A	N/A
9762016	12/2016	Fish et al.	N/A	N/A
9793670	12/2016	Steinbach et al.	N/A	N/A
9874492	12/2017	Cutsforth	N/A	N/A
9917408	12/2017	Cutsforth	N/A	N/A
10181772	12/2018	Cutsforth	N/A	N/A
10199790	12/2018	Cutsforth et al.	N/A	N/A
10249999	12/2018	Cutsforth	N/A	N/A
10316888	12/2018	Cutsforth	N/A	N/A
10348047	12/2018	Cutsforth et al.	N/A	N/A
RE47563	12/2018	Cutsforth	N/A	N/A
10371726	12/2018	Jahnke et al.	N/A	N/A
2001/0043022	12/2000	Narushima et al.	N/A	N/A
2003/0011388	12/2002	Klaar	N/A	N/A
2005/0116475	12/2004	Hibi et al.	N/A	N/A
2006/0021775	12/2005	Duesselberg et al.	N/A	N/A
2006/0119211	12/2005	Annis	310/239	H01R 39/381
2007/0273165	12/2006	Beck et al.	N/A	N/A
2008/0101895	12/2007	Holcomb et al.	N/A	N/A
2008/0264735	12/2007	Matsushita et al.	N/A	N/A
2008/0291273	12/2007	Cutsforth et al.	N/A	N/A
2009/0096315	12/2008	Mantle	N/A	N/A
2009/0153089	12/2008	Hobelsberger	N/A	N/A
2009/0267782	12/2008	Mark et al.	N/A	N/A
2011/0210837	12/2010	Jin	N/A	N/A
2012/0169176	12/2011	Toledo et al.	N/A	N/A
2012/0206010	12/2011	Kuban et al.	N/A	N/A
2012/0228988	12/2011	Cutsforth	N/A	N/A
2012/0248929	12/2011	Fish et al.	N/A	N/A
2013/0218514	12/2012	Schieke et al.	N/A	N/A
2014/0009142	12/2013	Cauwenberghs	N/A	N/A
2014/0052611	12/2013	Cutsforth	N/A	N/A
2014/0077960	12/2013	Cutsforth	N/A	N/A
2014/0125206	12/2013	Fish et al.	N/A	N/A
2014/0265675	12/2013	Cutsforth	N/A	N/A
2015/0357780	12/2014	Steinbach et al.	N/A	N/A
2016/0111838	12/2015	Cutsforth	310/68B	H01R 39/381
2017/0098983	12/2016	Cutsforth et al.	N/A	N/A
2018/0106701	12/2017	Cutsforth	N/A	N/A
2018/0351439	12/2017	Jahnke et al.	N/A	N/A
2019/0173250	12/2018	Cutsforth	N/A	N/A
2019/0207353	12/2018	Cutsforth et al.	N/A	N/A

2019/0302155	12/2018	Jahnke et al.	N/A	N/A
--------------	---------	---------------	-----	-----

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2008256639	12/2013	AU	N/A
2016271337	12/2017	AU	N/A
2688007	12/2007	CA	N/A
2688053	12/2007	CA	N/A
2912493	12/2007	CA	N/A
2918013	12/2007	CA	N/A
2688007	12/2015	CA	N/A
2918013	12/2017	CA	N/A
1395343	12/2002	CN	N/A
1442683	12/2002	CN	N/A
101369706	12/2008	CN	N/A
101701791	12/2009	CN	N/A
105247746	12/2015	CN	N/A
3417711	12/1984	DE	N/A
19758235	12/1998	DE	H01R 39/58
19755232	12/1998	DE	N/A
20003874	12/1999	DE	N/A
202006003418	12/2005	DE	N/A
102005062073	12/2006	DE	N/A
102012102726	12/2011	DE	N/A
0099158	12/1983	EP	N/A
0920092	12/1998	EP	N/A
1090702	12/2000	EP	N/A
1271716	12/2002	EP	N/A
1090702	12/2003	EP	N/A
1439042	12/2003	EP	N/A
1441422	12/2003	EP	N/A
1801938	12/2006	EP	N/A
2584679	12/2011	EP	N/A
2151024	12/2012	EP	N/A
2642642	12/2012	EP	N/A
3319238	12/2017	EP	N/A
2613546	12/1987	FR	N/A
2172445	12/1985	GB	N/A
2489577	12/2011	GB	N/A
55152415	12/1979	JP	N/A
56101360	12/1980	JP	N/A
57138846	12/1981	JP	N/A
60039337	12/1984	JP	N/A
62037039	12/1986	JP	N/A
S6336156	12/1987	JP	N/A
01321845	12/1988	JP	N/A
05074537	12/1992	JP	N/A
580163	12/1992	JP	N/A
H614501	12/1993	JP	N/A

08054226	12/1995	JP	N/A
2009268301	12/2008	JP	N/A
2010124518	12/2009	JP	N/A
2013090425	12/2012	JP	N/A
2013174279	12/2012	JP	N/A
2016512679	12/2015	JP	N/A
1179464	12/1984	SU	N/A
0051511	12/1999	WO	N/A
0219698	12/2001	WO	N/A
03052902	12/2002	WO	N/A
2008148058	12/2007	WO	N/A
2008148060	12/2007	WO	N/A
2008148060	12/2008	WO	N/A
2012119832	12/2011	WO	N/A
2012123402	12/2011	WO	N/A
2014150190	12/2013	WO	N/A

OTHER PUBLICATIONS

Wurfel et al. "Monitoring and diagnostics of the rotor slip ring system of three phase current induction generators" University of Technology Chemnitz, D-09126 Chemnitz, Germany. cited by applicant

Japanese Laid-Open Utility Model Publication No. 2-110975, Sep. 5, 1990, 15 pages. cited by applicant

International Search Report and Written Opinion for PCT/US2019/054542, dated Jan. 14, 2020. cited by applicant

International Search Report and Written Opinion dated May 13, 2020 for International Application No. PCT/US2019/054549. cited by applicant

Invitation to Pay Additional Fees dated Jan. 27, 2020 for International Application No. PCT/US2019/054549. cited by applicant

Primary Examiner: Gonzalez Quinones; Jose A

Attorney, Agent or Firm: Seager, Tufte & Wickhem LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/529,521, filed on Nov. 18, 2021, which is a continuation of U.S. patent application Ser. No. 16/592,269, filed on Oct. 3, 2019, now U.S. Pat. No. 11,211,757 which claims the benefit of priority under 35 U.S.C. § 119 to U.S. Provisional Application Ser. No. 62/741,152, filed on Oct. 4, 2018, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The disclosure generally relates to monitoring systems for monitoring brushes and brush holder assemblies that may be used in electrical devices and/or slip ring assemblies. More specifically, the disclosure relates to monitoring apparatus, assemblies, systems and methods of monitoring the wear of a brush in a brush holder assembly and/or the condition of a slip ring of an electrical device using a sensor.

BACKGROUND

(2) A purpose of a brush in an electrical device is to pass electrical current from a stationary contact to a moving contact surface, or vice versa. Brushes and brush holders may be used in electrical devices such as electrical generators, electrical motors, and/or slip ring assemblies, or sliding connection applications, for example, slip ring assemblies on a rotating machine such as a rotating crane or a linear sliding connection on a monorail. Brushes in many electrical devices are blocks or other structures made of conductive material, such as graphite, carbon graphite, electrographite, metal graphite, or the like, that are adapted for contact with a conductive surface or surfaces to pass electrical current. Electrically conductive leads or shunts extend from the brush to provide an electrical pathway to and/or from the brush from another conductive member.

(3) In some designs, a brush box type brush holder, or other type of brush holder, may be used to support a brush in contact with a moving contact surface of an electrical device during operation. The brush and brush box may be designed such that the brush can slide within the brush box to provide for continuing contact between the brush and the moving contact surface contacted by the brush. During operation an anomalous and/or threshold condition may occur, which may be indicative that one or more components of the electrical device may need to be replaced, one or more components of the electrical device may require inspection or attention, and/or maintenance may need to be performed. For example, an anomalous and/or threshold condition may indicate that one or more of a brush, brush holder, spring, shunt, commutator, collector ring, and/or other component may need to be replaced, one or more of a brush, brush holder, spring, shunt, commutator, collector ring, and/or other component may need to be inspected, and/or maintenance may need to be performed. It would be advantageous to monitor one or more components of an electrical device in order to observe the occurrence of an anomalous and/or threshold condition. Furthermore, it would be advantageous to alert an operator and/or technician of the occurrence of an anomalous and/or threshold condition and/or schedule technician intervention.

SUMMARY

(4) The disclosure is directed to monitoring apparatus, assemblies, systems and methods of monitoring the wear of a brush in a brush holder assembly and/or the condition of a slip ring of an electrical device using a sensor.

(5) An example system for monitoring the wear state of a carbon brush includes a brush holder assembly including a carbon brush having a first end, a second end opposite the first end, and a length measured from the first end to the second end. The length is diminished from an initial length as the first end of the carbon brush wears away during use. The brush holder assembly also includes a wear state monitor coupled to the carbon brush. The wear state monitor includes a sensor. The wear state monitor is configured to rotate as the length of the carbon brush diminishes. The sensor is configured to measure an angular displacement of the wear state monitor as the wear state monitor rotates. The measured angular displacement of the wear state monitor correlates to an amount of diminution in the length of the carbon brush.

(6) In addition or alternatively, the brush holder assembly includes a spring having a first end and a second end, with the first end coupled to the wear state monitor. The spring is configured to provide a force urging the carbon brush into contact with a rotating conductive surface of an electrical machine.

(7) In addition or alternatively, the wear state monitor includes a circumferential groove extending around a circumferential outer surface of the wear state monitor, and wherein the spring is disposed within the groove.

(8) In addition or alternatively, a coiled portion of the spring is configured to wrap around a circumferential outer surface of the wear state monitor as the wear state monitor rotates.

(9) In addition or alternatively, the brush holder assembly includes a spring having a coiled portion and an elongate portion extending from the coiled portion, wherein the wear state monitor is positioned within the coiled portion.

- (10) In addition or alternatively, the wear state monitor includes a circumferential groove extending around a circumferential outer surface of the wear state monitor, and wherein the coiled portion of the spring is disposed within the groove.
- (11) In addition or alternatively, the brush holder assembly includes a spacer positioned between the coiled portion of the spring and the second end of the carbon brush.
- (12) In addition or alternatively, the spacer includes a magnet, and the sensor is a Hall effect sensor sensing a magnetic field of the magnet.
- (13) In addition or alternatively, the spacer defines a concave cradle, wherein the coiled portion of the spring rests in the cradle.
- (14) In addition or alternatively, the wear state monitor rotates about an axis of rotation, wherein the axis of rotation is a fixed distance from the second end of the carbon brush as the wear state monitor rotates.
- (15) In addition or alternatively, the sensor is a rotary magnetic encoder.
- (16) In addition or alternatively, the sensor is configured to transmit a wireless signal to a site monitor, and wherein the wireless signal is configured to provide information relating to diminution in length of the carbon brush.
- (17) Another example system for monitoring the wear state of a carbon brush includes a brush holder coupled to a handle. The brush holder includes an opening, and a carbon brush is disposed within the opening of the brush holder. The system also includes a spring applying a force against the carbon brush to translate the carbon brush within the opening as a first end of the carbon brush wears away during use. The system further includes a wear state monitor positioned within a coiled portion of the spring, the wear state monitor configured to rotate as the first end of the carbon brush wears away.
- (18) In addition or alternatively, the system further includes a sensor disposed within a housing of the wear state monitor, wherein the sensor is configured to measure an angular displacement of the wear state monitor as the wear state monitor rotates.
- (19) In addition or alternatively, the measured angular displacement of the wear state monitor correlates to an amount the carbon brush has worn away.
- (20) In addition or alternatively, the wear state monitor rotates about an axis of rotation, wherein the axis of rotation is a fixed distance from an upper surface of the carbon brush as the wear state monitor rotates.
- (21) In addition or alternatively, the spring includes an elongate portion extending from the coiled portion of the spring along a side surface of the carbon brush.
- (22) In addition or alternatively, an end of the elongate portion of the spring is removably coupled to the brush holder.
- (23) In addition or alternatively, the wear state monitor includes a circumferential groove extending around a circumferential outer surface of the wear state monitor, and wherein the coiled portion of the spring is disposed within the groove.
- (24) In addition or alternatively, a portion of the spring is configured to wind up around a circumferential outer surface of the wear state monitor as the wear state monitor rotates.
- (25) In addition or alternatively, the wear state monitor is configured to rotate through an arc angle as the carbon brush wears away, and wherein the arc angle correlates to the amount the carbon brush wears away.
- (26) Another embodiment is a method for monitoring the wear state of a carbon brush. The method includes determining an angular displacement of a wear state monitor positioned adjacent to the carbon brush with a sensor as the wear state monitor rotates as a length of the carbon brush diminishes during use, and determining a wear state of the carbon brush based on the angular displacement of the wear state monitor.
- (27) In addition or alternatively, the method further includes comparing the wear state of the carbon brush to a threshold value.

(28) In addition or alternatively, the method further includes communicating an indication of the wear state of the carbon brush to a user.

(29) The above summary of some embodiments, aspects, and/or examples is not intended to describe each embodiment or every implementation of the present disclosure. The figures and the detailed description which follows more particularly exemplify these embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The aspects of the disclosure may be more completely understood in consideration of the following detailed description of various embodiments in connection with the accompanying drawings, in which:

(2) FIG. 1 shows an illustrative view of an exemplary brush monitoring system positioned adjacent a component of an electrical machine;

(3) FIG. 2 shows an example wear state monitor and spring positioned adjacent a spacer on a brush;

(4) FIG. 3 shows an exploded view of the brush holder assembly components shown in FIG. 2;

(5) FIG. 4 shows an end view of the wear state monitor and spring shown in FIG. 4;

(6) FIG. 5 shows a side view of the wear state monitor and spring shown in FIG. 4;

(7) FIG. 6 shows an exploded view of the wear state monitor shown in FIG. 4;

(8) FIGS. 7 and 8 show side views of an illustrative brush holder assembly at a first wear state and a second wear state.

(9) While the aspects of the disclosure are amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit aspects of the disclosure to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DETAILED DESCRIPTION

(10) For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

(11) All numeric values are herein assumed to be modified by the term “about”, whether or not explicitly indicated. The term “about” generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (i.e., having the same function or result). In many instances, the term “about” may be indicative as including numbers that are rounded to the nearest significant figure.

(12) The recitation of numerical ranges by endpoints includes all numbers within that range (e.g., 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

(13) Although some suitable dimensions, ranges and/or values pertaining to various components, features and/or specifications are disclosed, one of skill in the art, incited by the present disclosure, would understand desired dimensions, ranges and/or values may deviate from those expressly disclosed.

(14) As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

(15) The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The detailed description and the drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the disclosure. The illustrative embodiments depicted are intended only as

exemplary. Selected features of any illustrative embodiment may be incorporated into an additional embodiment unless clearly stated to the contrary.

(16) FIG. 1 illustrates an exemplary brush monitoring system **100** that may include a brush holder assembly **110**, a site monitor **120** and/or a remote monitoring site **140** including a remote monitoring device **150**, **160**. In some cases, the brush holder assembly **110** may substantially resemble a brush holder assembly as described in U.S. Pat. No. 7,034,430, entitled “BRUSH HOLDER APPARATUS, BRUSH ASSEMBLY, AND METHOD”, which is herein incorporated by reference in its entirety. However, the illustrative brush monitoring system **100** may be amenable to any of various brush holder assembly configurations. Thus, the intention is that the illustrative brush monitoring system **100** may be used in conjunction with any desired brush holder assembly configurations of an electrical device, such as an industrial electrical generator. For example, the illustrative brush monitoring system **100** may be used with brush holder assemblies, brush holders and/or brushes disclosed in U.S. Pat. Nos. 6,731,042; 5,753,992; 5,621,262; 5,463,264; 5,397,952; and 5,256,925; each of which is incorporated herein by reference.

(17) FIG. 1 illustrates a brush **24** including a first end surface **34** and a second end surface **35** and a length extending therebetween. The second end surface **35** may be in electrical contact with a conductive surface **12** of a rotating component **15** of an electrical machine (e.g., a collector ring, a slip ring, or a commutator) and conduct electrical current therefrom. Further, FIG. 1 illustrates that, in some examples, one or more sides of the brush **24** may be surrounded by a brush holder **22** (e.g., a brush box), whereby the brush holder **22** may include a plurality of guiding surfaces for guiding linear or longitudinal movement of the brush **24** toward the conductive surface **12** of the rotating component **15**. In other words, the brush **24** may translate linearly within an aperture defined by the plurality of guiding surfaces of the brush holder **22** as the brush **24** wears. In some embodiments it is contemplated that the brush holder **22** may not take on the form of a box, but may include one or a plurality of guiding surfaces, such as channels, posts or columns, abutting and/or encompassing one or more sides of the brush **24** and/or extending into or through the brush **24**, or a portion thereof, for guiding linear or longitudinal movement of the brush **24**.

(18) FIG. 1 further illustrates that the brush holder **22** may be secured to a mounting beam **26** configured and adapted to be mounted to another structure, such as a mounting block **70**. The brush holder assembly **110** may be configured to place the brush **24** in contact with the conductive surface **12**, such as the surface of the rotating component **15** of the electrical machine. The brush **24** may extend from the lower edge of the brush holder **22** such that the second end surface **35** of the brush **24** engages the conductive surface **12**. The mounting beam **26** may include an over-center engagement mechanism, a slotted or channeled engagement mechanism for sliding engagement, or other mechanism for easily engaging and disengaging the brush **24** from a conductive surface **12**. In other embodiments, the brush holder assembly **110** may include a brush holder **22** rigidly mounted to another structure holding the brush holder **22** stationary, or mounted to another structure in any desired arrangement. For example, in some embodiments the brush holder **22** may be bolted or welded to a stationary structure. Some such brush holders are disclosed in U.S. Pat. Nos. 6,731,042; 5,753,992; 5,621,262; 5,463,264; 5,397,952; and 5,256,925; which are incorporated herein by reference.

(19) As shown in FIG. 1, the mounting beam **26** may include an upper beam member **27** and a lower beam member **28** hingedly or pivotally coupled to one another. When the upper beam member **27** and the lower beam member **28** are aligned with one another (e.g., the longitudinal axis of the upper beam member **27** is parallel with the longitudinal axis of the lower beam member **28**), the brush holder **22** may be considered to be in an engaged, or locked, position such that the brush **24** may be contiguous with or in contact with the conductive surface **12**. When the upper beam member **27** is tilted from the lower beam member **28** (e.g., the longitudinal axis of the upper beam member **27** is oblique to the longitudinal axis of the lower beam member **28**), the brush holder **22** may be considered to be in a disengaged, or unlocked, position such that the brush **24** may be non-

contiguous with, spaced from, or otherwise not in direct electrical contact with the conductive surface **12**. The mounting beam **26** may be removably coupled to the mounting block **70** during operation. In some embodiments, the mounting beam **26** may slidably engage with, interlock with, or otherwise be removably coupled to the mounting block **70**. The mounting block **70** may be coupled to, secured to, or otherwise extend from another structure which maintains the mounting block **70** stationary with respect to (i.e., a fixed distance from) the conductive surface **12**, for example.

(20) In some embodiments, a handle **21** may be attached to the brush holder **22** to facilitate engagement and disengagement of the brush **24** from the conductive surface **12**. For example, the handle **21** may be attached to the upper beam member **27** such that movement of the handle **21** actuates (e.g., pivots, slides, releases) the upper beam member **27** relative to the lower beam member **28**. The handle **21** may be a removable handle or the handle **21** may be permanently attached to the upper beam member **27** or another portion of the brush holder **22**.

(21) FIG. **1** further illustrates that the brush holder assembly **110** may include a wear state monitor **50** and a spacer **30**. The spacer **30** may be attached to the first end surface **34** of the brush **24**. Additionally, FIG. **1** illustrates that the wear state monitor **50** may be coupled to a spring **29**. In some examples, a portion of the spring **29** may be coiled around a portion of the wear state monitor **50**, with an elongate portion of the spring extending from the coiled portion. Further detailed discussion of the wear state monitor **50**, the spacer **30** and the spring **29** follows below.

(22) In some examples the wear state monitor **50** may include one or more sensors which collect and/or measure a variety of parameters corresponding to the “wear state” of the brush **24**. For example, the wear state monitor **50** may include one or more sensors which measure and/or communicate the extent to which the brush **24** wears away while in contact with the conductive surface **12** of the rotating component **15**. In some examples, the sensor(s) may also measure the vibration and/or temperature of the brush holder assembly **110** (including individual components thereof) and/or the brush **24**, and/or electrical current passing through the brush **24**, for instance.

(23) In some cases, the wear state monitor **50** may be positioned adjacent to a surface of a component of the brush holder assembly **110**, different than the spring **29**. For example, the wear state monitor **50** may be positioned on or adjacent to the brush holder **22**, the lower beam member **28**, the upper beam member **27** and/or on or adjacent to the handle **21** of the brush holder assembly **110**. In some cases, the wear state monitor **50** may be permanently and/or removably incorporated into a portion of the handle **21** or other component of the brush holder assembly **110**. In some examples, the wear state monitor **50** may be free from the spring **29**.

(24) As described above, in some examples the wear state monitor **50** may be mounted adjacent a surface of the spring **29** or otherwise within the spring **29**, such as within a coiled portion of the spring **29**. The spring **29** may include a constant force spring, which provides tension to the brush **24**, the wear state monitor **50** or both the brush **24** and the wear state monitor **50** to bias the brush **24** toward and in contact with the conductive surface **12** of the rotating component **15**. In other words, the spring **29** may include a coiled portion designed to provide a force to engage the brush **24** with a rotating component of an electrical machine, such as a slip ring, a commutator, and the like.

(25) In some examples, the spring **29** may be attached to a portion of the brush holder **22** and/or the mounting beam **26** of the brush holder assembly **110**. In some instances, a first end **32** of the spring **29** may be removably coupled to the brush holder and/or the mounting beam **26** with an elongate portion of the spring **29** extending along a side surface of the brush **24**, between the brush **24** and the mounting beam **26**. Thus, in some embodiments, an elongate portion of the spring **29** may extend along one side surface of the brush **24** between the brush **24** and the mounting beam **26** of the brush holder assembly **110** up to the coiled portion of the spring **29** positioned above the upper surface **34** of the brush **24**. The opposite, second end **33** of the spring **29** may be located at the interior of the coiled portion of the spring **29**.

(26) In some cases, the wear state monitor **50** may also include one or more indicators **55** (e.g., one or more light emitting diodes (LEDs), a speaker, or a combination of LEDs and/or speakers) for communicating wear state information to a user. In some instances, the wear state monitor **50** may be capable of communicating information about the wear state of the brush **24** and/or the rotating component **15** to a user via the indicators **55**. In some cases, the wear state monitor **50** may be capable of receiving messages from an external device, such as the site monitor **120** and/or a programming device located at the same site or at a remote location (e.g., a computer **150**, a tablet **160**, a smart phone, etc.). The messages may include commands, such as commands to send wear state information about the brush **24** and/or the rotating component **15**, or commands for modifying information used by the wear state monitor **50**. For example, a user may desire to modify one or more thresholds used to determine the wear state information of the brush **24** and/or the rotating component **15**, and/or to reprogram the wear state monitor **50** by downloading instructions, tables and/or the like.

(27) As described above, in some examples the wear state monitor **50** may measure and/or collect information regarding the wear state of the brush **24**. In particular, the wear state monitor **50** may be designed to measure and collect information regarding the extent to which the second end surface **35** of the brush **24** contacting the conductive surface **12** has worn away (i.e., the amount of diminution in length of the brush **24** at some time from its initial length when installed in the brush holder assembly **110**). It can be appreciated that as the second end surface of the brush **24** maintains contact with the rotating component **15**, the second end surface **35** of the brush **24** may wear away, thereby shortening the overall length of the brush **24**.

(28) As described above, the spring **29** may apply a force to the brush **24** which is directed linearly along the aperture defined by the brush holder **22**. Further, as the brush **24** decreases in length within the brush holder **22**, the wear state monitor **50** may rotate within the coil of the spring **29** while the axis of rotation of the wear state monitor **50** translates linearly with linear translation of the brush **24** toward the conductive surface **12** of the rotating component **15**. Additionally, a sensor may be positioned within the wear state monitor **50** and may measure and collect data representing the extent (e.g., total angular distance and/or total arc length) of rotation of the wear state monitor **50** from its initial position when the brush **24** was installed in the brush holder assembly **110**, or any other duration desired. It can be appreciated that the amount of rotation measured by the sensor (positioned within the wear state monitor **50**) may be equivalent, proportional, or otherwise representative of the linear or longitudinal movement of the brush **24** as it translates (e.g., shortens) within the brush holder **22**, and thus equivalent, proportional, or otherwise representative of the amount of diminution of the brush **24** from its initial length.

(29) In some cases, the sensor may associate the rotation of the wear state monitor **50** with a wear state of the brush **24** and/or a wear state of the conductive surface **12** and/or the rotating component **15**. The value (e.g., amount of rotation of the wear state monitor **50**) measured by the sensor may correspond to the position of the first end of the brush **24** relative to the conductive surface **12** of the rotating component **15**. In some cases, the value measured by the sensor may correspond to a value obtained over any desired time interval or duration of wear of the brush **24**. It can be appreciated that the value (e.g., amount of rotation of the wear state monitor **50** from its initial position) may be compared to one or more predetermined threshold values to determine a wear state of the brush **24** and/or other diagnostic information about the machine.

(30) For example, in some cases the wear state monitor **50** (including the sensor positioned therein) may be configured to monitor a vibration of the brush **24**. Vibration of the brush **24** may be due to one or more imperfections, wear or other deformation of the rotating component **15** of the electrical machine. For example, a slip ring may deform or may wear unevenly to cause one or more portions of the slip ring to be out of round. As the brush **24** encounters these defects at one or more positions during a revolution of the rotating component **15**, the defects may cause the brush **24** to vibrate at a rate corresponding to the rotation speed and/or the number of defects at the conductive surface **12**

of the rotating component **15** (e.g., a slip ring, a commutator, etc.). In some examples, the transient angular displacement of the wear state monitor **50** may correspond and/or correlate to a threshold change in vibration or other deformation of the rotating component **15** of the electrical machine. As used herein, “transient angular displacement” means momentary change in the rotational orientation of the wear state monitor **50** in an oscillating fashion. Therefore, in some examples, information corresponding to the transient angular displacement (which may correspond to a threshold change in vibration) of the wear state monitor **50** may be collected and transmitted to the site monitor **120** to determine if the brush **24** is experiencing excessive vibration.

(31) Similarly, it can be appreciated that the sensor positioned within the wear state monitor **50** (or a separate temperature sensor) may measure and collect information associated with a temperature of the brush **24**, other components of the electrical machine and/or the ambient air temperature surrounding the brush holder assembly **110**. Further, the collected temperature values may be monitored and/or compared to one or more predetermined temperature thresholds, whereby the temperature thresholds may trigger the sensor to send a signal to the site monitor **120** indicative of the need for inspection and/or maintenance to be performed on one or more components of the electrical machine. For example, in some instances, the temperature threshold may be set to trigger a signal when the measured temperature exceeds a threshold temperature, such as a threshold temperature of 125 degrees Celsius. In other words, when the temperature sensor measures a temperature (e.g., ambient air temperature, temperature of a component of the electrical machine, etc.) greater than 125 degrees Celsius, it may send a signal to the site monitor **120** alerting personnel of the need for inspection and/or maintenance to be performed on one or more components of the electrical machine. In other instances, the threshold temperature may be set in a range of 100 degrees Celsius to 140 degrees Celsius, in a range of 110 degrees Celsius to 130 degrees Celsius, or in a range of 120 degrees Celsius to 130 degrees Celsius, for example.

(32) In some cases, the site monitor **120** may be positioned near the electrical machine to monitor the wear state of one or more brush holder assemblies **110** and/or the wear state of the slip ring or other rotating component of the electrical machine. The site monitor **120** may be capable of monitoring the wear states of the brush **24** of the brush holder assembly **110**. In some cases, the site monitor **120** may be capable of monitoring the movement of the brushes **24** of two or more brush holder assemblies **110** associated with one or more electrical machines. For example, the site monitor **120** may be communicatively coupled to one or more, or a plurality of wear state monitors **50** associated with a particular electrical machine, such as the wear state monitor **50** of the brush holder assembly **110** via a communication link **115** (e.g., a wireless link). The site monitor **120** may be configured to receive processed data and/or raw data providing information about the wear state of the brush **24** and/or the rotating component **15**. For example, the site monitor **120** may receive information about a value received from the sensor corresponding to the amount of rotation of the wear state monitor **50** from its initial position at some temporal occasion after the brush **24** has been installed on the electrical machine. However, in other examples, the site monitor **120** may receive information about a value obtained by the sensor and a comparison between the value and one or more predetermined thresholds. In some cases, the communication link **115** may include a radio frequency (RF) communication link, an audio-based communication link (e.g., an ultrasonic communication link), and/or an optical communication link (e.g., an infrared (IR) communication link, a visible light communication link, etc.). In some cases, the site monitor **120** may be configured to predict or determine an estimated projection of a condition of the brush **24** into the future.

(33) In some examples, the wear state monitor **50** may be configured to communicate the wear state information about the brush **24** to the site monitor **120** using a predetermined schedule (e.g., once per hour or hourly, once per day or daily, once per week or weekly, twice per week, etc.). In some examples, the wear state monitor **50** may provide the wear state information about the brush **24** and/or the rotating component **15** of the electrical machine to the site monitor **120** in response to

a command received from the site monitor **120** and/or the remote monitoring device **150, 160**. Additionally, the site monitor **120** may be programmed to receive wear state information about the brush **24** at predetermined intervals. In some cases, the predetermined intervals may be fixed at a particular value (e.g., once per hour or hourly, once per day or daily, once per week or weekly, twice per week, etc.) and in other cases, the intervals may change after a particular wear state has been reached. For example, the site monitor **120** may be configured to receive wear state information from the wear state monitor **50** at a first time interval, such as once per day, until one or more brushes **24** and/or the rotating component **15** reach a wear state approaching the replacement wear state. At that point, the wear state monitor **50** may sample the wear state information from the brush **24** at a second shorter time interval, such as hourly. Thus, the wear state information from the wear state monitor **50** may be communicated to the site monitor **120** at first frequency until the brush **24** reaches a first wear state, and thereafter, the wear state information may be communicated to the site monitor **120** at a second frequency greater than the first frequency.

(34) The site monitor **120** may output an indication of the condition and/or projected condition of the brush **24**. In some cases, the indication may be configured to alert operator, technician and/or other personnel that the brush **24** and/or the rotating component **15** are sufficiently worn and/or needs to be replaced, the brush **24** and/or the rotating component **15** are damaged, failure has occurred or is imminent, or other maintenance or inspection may need to be performed. In some embodiments, the indication may be used for scheduling maintenance or inspection, sending personnel to perform maintenance or inspection, ordering and/or scheduling distribution/delivery of a replacement brush or other part, routing maintenance personnel and/or product delivery to a specified location, or arranging for other notification and/or scheduling tasks be performed.

(35) The brush monitoring system **100** may also be used to identify and/or notify other key maintenance, failure of the brush holder assembly **110** and/or other anomalous conditions. For example, incidents of excess heating, arcing or excess vibration, which may indicate a need to perform maintenance and/or disrupt operation of the electrical equipment, may be identified and/or assessed by one or more components of the brush monitoring system **100**. The wear state monitor **50**, the site monitor **120** and/or the remote monitoring device **150, 160** may carry out an appropriate response to respond to an identified anomalous condition in an attempt to rectify the anomalous condition. In some cases, an operator may carry out an appropriate response to respond to an anomalous condition identified with the brush monitoring system **100** in an attempt to rectify the anomalous condition.

(36) In some cases, the site monitor **120** may be communicatively coupled by a wireless link **125** and/or wired link **127** to a network **130**. The site monitor **120** may be capable of communicating information about the wear state of one or more brushes **24** to a remote monitoring device **150, 160** at a remote monitoring site **140** via the network **130** and one or more wired **137** and/or wireless **135** communication links. The wired link **127, 137** and/or wireless link **125, 135** communication links may be configured to operate using one or more standardized communication protocols (e.g., Ethernet, Ethernet/IP, BACnet, Modbus, LonWorks, etc.), or proprietary communication protocols. Examples of a remote monitoring system are described in U.S. Pat. No. 7,705,744, entitled "MONITORING SYSTEMS AND METHODS FOR MONITORING THE CONDITION OF ONE OR MORE COMPONENTS OF AN ELECTRICAL DEVICE", U.S. Pat. No. 8,618,943, entitled "BRUSH HOLDER ASSEMBLY MONITORING APPARATUS, ASSEMBLY, SYSTEM AND METHOD", and U.S. Pat. No. 9,252,643, entitled "SYSTEM AND METHOD FOR MONITORING THE STATUS OF ONE OR MORE COMPONENTS OF AN ELECTRICAL MACHINE", which are herein incorporated by reference in their entirety. The remote monitoring site **140** may include one or more remote monitors, such as a personal computer **160**, a workstation, a laptop, a tablet **150**, a smart phone or the like, for collecting data and/or analyzing data received from one or more user sites.

(37) The remote monitoring devices and/or site monitor **120** may be integrated into a maintenance program for a brush holder assembly **110**, such that the site monitor **120** may be configured to monitor at least a condition of one or more components of the brush holder assembly **110**. To do so, the remote monitors and/or the site monitor **120** may be configured to identify each brush holder assembly **110** on a particular machine or at a particular site and/or store an installation date and any servicing dates for each brush holder assembly **110** and/or components thereof, such as the installation date of a brush **24** in the brush holder assembly **110**. In some examples, the wear state monitor **50** (or other sensor of the brush holder assembly **110**) may output a signal to the site monitor **120** indicating that a brush **24** or other component of the electrical machine has been removed and/or replaced, and/or an indication that a new brush **24** has been installed. Component replacement information may be collected and monitored by the wear state monitor **50**, one or more sensors of the brush assembly **110** and/or the site monitor **120**.

(38) In some cases, one or more parameters received from the wear state monitor **50** associated with a brush holder assembly **110** may be monitored over time to determine trending information about a brush **24** and/or a rotating component **15** of the electrical machine. For example, the site monitor **120** and/or the remote monitors may determine trend information, that may include an average lifetime for a brush **24** installed in a particular brush holder assembly **110** and/or for a particular installation position on an electrical machine. The site monitor **120** and/or the remote monitors may be configured to store information about the position of a brush **24** when the brush **24** and/or brush holder assembly **110** is first installed on an electrical machine. By monitoring the final position and/or replacement date of a brush **24** along with the initial position and/or installation date each time a brush **24** is replaced and a new brush **24** is installed in the brush holder assembly **110**, information may be gathered about a wear state of the rotating component **15**. For example, a slip ring, or other rotating component of the electrical machine, may have an initial outer diameter measurement. Over time, with wear including normal wear and/or due to environmental conditions (e.g., humidity, temperature, contaminants including abrasives, etc.) a wear state associated with the thickness and/or outer diameter of the rotating component **15** may be measured and/or predicted. In some cases, preventative measures to improve the lifetime of the brush **24** and/or the rotating component **15** may be obtained by analysis of the information received from the one or more wear state monitors **50**. For example, a user may be advised to adjust one or more environmental conditions for a space near the electrical machine, such as a temperature, a humidity level and/or a contaminant level.

(39) FIG. 2 illustrates the wear state monitor **50**, spring **29** and spacer **30** shown in FIG. 1, positioned above an upper surface of a carbon brush **24**. FIG. 3 illustrates an exploded perspective view of the wear state monitor **50**, spring **29** and spacer **30** as described above in FIG. 2. For clarity, FIG. 3 illustrates the wear state monitor **50**, spring **29** and spacer **30** after having been rotated 180 degrees as compared with their orientation depicted in FIG. 1 and FIG. 2.

(40) As illustrated in FIG. 2 in some examples the wear state monitor **50** and spring **29** may be nested within the spacer **30**, such as within a concave cradle of the spacer **30**. The spacer **30** may be positioned between the coiled portion of the spring **29** and the upper or first end surface **34** of the carbon brush **24**. In some instances, the spacer **30** may be attached to the first end surface **34** of the brush **24** such that the spacer **30** moves with the brush **24**. For example, as shown in FIG. 3, the spacer **30** may include one or more projections, such as pin members **38**, designed to engage bores extending into the brush **24** from the first end surface **34** (shown in FIG. 1) of the brush **24**. For example, each of the pin members **38** may be designed to extend into a corresponding bore located within the first end surface **34** of the brush **24**. It can be appreciated that engagement of the pin members **38** within their respective bore functions to secure the spacer **30** to the brush **24**. In other instances, the spacer **30** may include a different engagement feature configured to mate with a complementary engagement feature in the first end surface **34** of the brush. For example, the spacer **30** may include one or more rails configured to extend into corresponding channels formed in the

first end surface **34** of the brush **24**.

(41) The wear state monitor **50** may include a first end region **40**, a second end region **42** and a medial region **43** (see FIG. **4**) extending therebetween. The medial region **43** may be generally cylindrical, or other such shape designed to facilitate integration into a brush holder assembly **110** or other mounting location within the brush holder assembly **110**. In some instances, the medial region **43** may have a cylindrical circumferential surface. Each of the first end region **40** and the second end region **42** may extend radially outward from the circumferential surface of the medial region **43**, thereby creating a groove or recessed area (further illustrated in FIG. **4**) in which the coiled portion of the spring **29** may be positioned between the first end region **40** and the second end region **42**.

(42) As discussed above, the medial portion **43** of the wear state monitor **50** may be designed to be captured within the coiled portion of the spring **29**. In other words, a portion of the spring **29** (i.e., the coiled portion) may be coiled (e.g., wrapped) around the medial region **43** of the wear state monitor **50**. As shown in FIG. **2**, the first end region **40** and the second end region **42** may provide a shoulder on opposing sides of the coiled portion of the spring **29** to ensure that the spring **29** does not slip out of the groove defined between the first end region **40** and the second end region **42**. It can be appreciated that the first end region **40** and/or the second end region **42** may be removable, or otherwise configurable, to allow the wear state monitor **50** to be mounted within a coiled portion of different sized springs. For example, the removable and/or configurable first end region **40** and/or second end region **42**, may allow the wear state monitor **50** to be mounted within a coiled portion of a spring having a first width and a first coil diameter and/or a spring having a second different width and/or a second different coil diameter.

(43) As discussed above, a sensor may be positioned within the wear state monitor **50** and may measure and collect data representing a current rotational position of the wear state monitor **50** which can be used to determine the extent (e.g., total angular distance and/or total arc length) of rotation of the wear state monitor **50** from its initial position whereby the amount of rotation measured by the sensor (positioned within the wear state monitor **50**) may be equivalent, proportional, or otherwise representative of the linear or longitudinal movement of the brush **24** (shown in FIG. **1**) as it translates (e.g., shortens) within the brush holder **22** (shown in FIG. **1**). In particular, the sensor positioned within the wear state monitor **50** may be designed to detect the absolute angular position of the sensor relative to a permanent magnet positioned adjacent the sensor. For example, FIG. **2** illustrates a magnet **14** attached to the spacer **30**, or otherwise incorporated with the spacer **30**. While FIG. **2** illustrates the magnet **14** approximately aligned with the central axis of the wear state monitor **50**, it is contemplated that the magnet **14** may be positioned along other portions of the wear state monitor **50** and/or along other elements of the brush holder assembly **110**. FIG. **3** illustrates that, in some examples, the medial region **43** of the wear state monitor **50** may include an engagement feature such as a tab, shoulder or an opening, (not shown in FIG. **2**) which may be used to facilitate a connection with or engagement with the second end **33** of the spring **29** located on the interior of the coiled portion of the spring **29**. For example, FIG. **3** illustrates a boss (e.g., protrusion) **16** extending away from the outer surface of the medial region **43**. The boss **14** may have a shape configured to mate with a corresponding opening **18** of the spring **29** proximate the second end **33** of the spring **29**. The opening **18** may have a shape corresponding to a cross-sectional shape of the boss **16**. For example, the boss **16** may have a circular cross-sectional shape designed to mate with a circular shape of the opening **18**. However, while FIG. **3** illustrates the boss **16** and the opening **18** having a circular shape, other shapes are contemplated. For example, the boss **16** and the opening **18** may include square, ovular, rectangular, star, triangular, or any other geometric shape. It can be appreciated that engagement of the boss **16** with the opening **18** may rotationally fix the wear state monitor **50** with the coiled portion of the spring **29** such that rotational movement (e.g., coiling) of the coiled portion of the spring **29** correspondingly rotates the wear state monitor **50** an equal amount.

(44) In other embodiments, the outer surface of the medial region **43** may include a shoulder or raised edge configured to engage the second end **33** of the spring **29** when the coiled portion of the spring **29** is coiled around the medial region **43**. In some instances, the second end **33** of the spring **29** may be trapped underneath the layers of the coiled spring **29** wound thereover, which may apply a radially inward compressive force on the second end **33** of the spring **29** to maintain the second end **33** of the spring **29** against the surface of the medial region **43**, ensuring the second end **33** of the spring **29** remains rigidly fixed to the wear state monitor **50**.

(45) FIG. **3** further illustrates that the first end of the spring **32** may be folded back on itself to form a tab, wherein the tab is designed to be removably coupled to the brush holder and/or the mounting beam **26** (shown in FIG. **1**). In other words, the tab **19** may be designed to engaged (e.g., be inserted into) a portion of the brush holder and/or the mounting beam **26**.

(46) As illustrated in FIG. **3**, the spacer **30** may include one or more arcuate surfaces **36** defining a concave cradle designed to mate with the circumferential profile of the wear state monitor **50**. In other words, the spacer **30** may include one or more concave surfaces **36** having a radius of curvature that substantially matches the radius of curvature of the outer surface of the wear state monitor **50**. Thus, a portion of the wear state monitor **50** may be positioned in the concave cradle of the spacer **30**. The spacer **30** may be positioned between the coiled portion of the spring **29** and the upper surface of the brush **24** to space the coiled portion of the spring **29** away from the brush **24**.

(47) Additionally, FIG. **3** illustrates that the spacer **30** may include a projection **34** designed to engage the second end region **42** of the wear state monitor **50**. It can be appreciated that the second end region **42** may include a recess (not shown) which is designed to mate with the projection **34** and permit rotational movement of the wear state monitor **50** about a rotational axis aligned with the central axis of the projection **34**. The engagement of the projection **34** within the recess of the second end portion may provide additional securement between the wear state monitor **50** and the spacer **30** while permitting rotational movement therebetween. Thus, it can be appreciated the projection **34** may cooperate with the arcuate surfaces **36** of the concave cradle to permit the wear state monitor **50** to rotate (as described above) when engaged with the spacer **30**.

(48) FIG. **4** illustrates an end view of the wear state monitor **50** including the first end region **40**, the second end region **42** and the medial region **43** extending therebetween. As discussed above, FIG. **4** illustrates the outer peripheral surfaces of both the first end region **40** and the second end region **42** extending radially outward beyond the cylindrical circumferential surface of the medial region **43**. As described above, the inner surfaces of each of the first end region **40**, the second end region **42** and the circumferential surface of medial region **43** may define a groove in which the spring **29** may be positioned, with the inner surfaces of the first and second end regions **40**, **42** forming shoulders.

(49) FIG. **5** shows a side view of the wear state monitor **50** and the spring **29** described above. FIG. **5** illustrates that spring **29** may include an elongate portion extending away from the wear state monitor **50** whereby the first end **32** of the spring **29** extends past the outer circumferential surface of the wear state monitor **50**. As noted above, the first end **32** of the spring **29** (including tab **19** described above) may be removably coupled to the brush holder and/or the mounting beam **26** with the elongate portion of the spring **29** extending along a side surface of the brush **24**, between the brush **24** and the mounting beam **26**. Additionally, FIG. **5** illustrates spring **29** wrapping around the medial region **43** of the wear state monitor **50**. For example, the dashed line represents the spring **29** wrapping around the medial region **43** of the wear state monitor **50**, whereby the second end **33** of the spring **29** is coupled to or otherwise in contact with the wear state monitor **50**, such as via the boss **16** and opening **18** connection, as described above with respect to FIG. **3**.

(50) FIG. **6** illustrates an exploded view of the wear state monitor **50** described above. As illustrated in FIG. **6**, the wear state monitor **50** may include an exterior housing **52**. The exterior housing **52** may include an inner cavity **54**. The cavity **54** may be configured to contain one or more internal components of the wear state monitor **50**. The wear state monitor **50** may also

include a housing lid **60** configured to mate with the exterior housing **52**. In other words, the lid **60** may be designed to be rigidly attached to the exterior housing **52**. In other instances, the exterior housing **52** may be adhesively bonded or snap fit to the lid **60** to secure the exterior housing **52** and the lid **60** together. Further, the lid **60** may include an aperture **71** extending through the entire wall thickness of the lid **60**.

(51) Additionally, the wear state monitor **50** may include a button **59**. In some instances, the button **59** may be a Viton button. The button **59** may be utilized to pair the wear state monitor **50** to another device via a Bluetooth connection, for example. Further, it can be appreciated that a portion of the button **59** may be designed to project through the aperture **71** of the lid **60**, thereby making the button **59** accessible to depress and pair the wear state monitor **50** to another device via a Bluetooth connection. When the exterior housing **52** is engaged with the lid **60** and the button **59**, the cavity **54** created by the combination of the exterior housing **52**, the lid **60** and the button **59** may be sealed to the outside environment.

(52) In other instances, the housing **52** may include a first housing section and a second housing section separable from one another to expose an interior cavity of the wear state monitor **50** housing the internal components of the wear state monitor **50**. In some instances, the first housing section and the second housing section may be hingedly connected (e.g., connected in a “clam shell” configuration), or otherwise movable relative to one another. In such cases, when the wear state monitor **50** is located within the coiled portion of the spring **29** (e.g., a helical spring), the force provided by the spring **29** may facilitate a compression connection or snap fit connection for engaging the first housing section with the second housing section of the wear state monitor **50**. In other instances, the first housing section may be adhesively bonded or snap fit to the second housing section to secure the first and second housing sections together.

(53) FIG. **6** further illustrates that the wear state monitor **50** may further include a power source **53** (e.g., one or more batteries, capacitors, or both) and a sensor **56** (it is noted that the sensor **56** may correspond to the sensor described above with respect to FIG. **1**). The power source **53** may be rechargeable and/or replaceable.

(54) In some instances, the sensor **56** may be referred to as an angular sensor **56** and/or a magnetic encoder **56**. As discussed above, the sensor **56** may produce a signal corresponding to the rotation (e.g., the absolute angular position) of the wear state monitor **50** relative to the stationary magnet **14** described above with respect to FIG. **2**. For example, the sensor **56** may be able to sense a change in the magnetic field created by the magnet **14**, thus determining a rotational orientation of the wear state monitor **50**. The signals provided by the sensor **56** corresponding to the rotational orientation of the wear state monitor **50** may be compared to determine an angular displacement of the wear state monitor **50** between two temporal occasions, such as between an angular position of the wear state monitor **50** when the brush **24** is installed in the brush holder assembly **110** and some later time when the brush **24** has worn. These signals (corresponding to the angular displacement and/or rotational orientation of the wear state monitor **50**) may be communicated to the site monitor **120** via a variety of communication methods. In some instances, the sensor **56** may additionally include an accelerometer configured to sense dynamic vibration of the brush **24** in the brush holder **22**. For example, the sensor **56**, in addition to sensing angular displacement and/or rotational orientation of the wear state monitor **50**, may sense transient angular displacement of the wear state monitor **50** corresponding to dynamic vibration of the brush **24**.

(55) Additionally, in some cases, the power source **53** and/or sensor **56** may be located within the cavity **54** of the wear state monitor **50**, such that the power source **53** and/or the sensor **56** may be integrated with the wear state monitor **50**. Further, it can be appreciated that when the exterior housing **52** is engaged with the lid **60** and the second button member **59**, both the power source **53** and the sensor **56** may be sealed within the cavity **54** formed by the combination of the exterior housing **52**, the lid **60** and the second button member **59**.

(56) Additionally, FIG. **6** illustrates that the wear state monitor **50** may include a first foam

insulation member **61a** and a second foam insulation member **61b**. In some instances, each of the first foam insulation member **61a** and the second foam insulation member **61b** may be formed from silicone. Other materials may be utilized to form the first foam insulation member **61a** and/or the second foam insulation member **61b**. Further, the first foam insulation member **61a** and the second foam insulation member **61b** may be utilized to insulate the power supply **53** when positioned within the cavity **54**. In other words, when positioned inside the cavity **54**, the power supply **53** may be disposed between the first foam insulation member **61a** and the second foam insulation member **61b**.

(57) The power source **53** of the wear state monitor **50** may be used to supply power to one or more components of the wear state monitor **50**, such as the sensor **56**, to facilitate the measurement and generation of a value representative of the angular displacement or rotation of the wear state monitor **50** (which is proportional to the diminution in length of the brush **24** during use, as described above). In other words, as the wear state monitor **50** rotates in response to the diminution in length of the brush **24** as the brush **24** wears, the sensor **56** may sense, measure and collect the information (e.g., data) of the amount of rotation or angular displacement of the wear state monitor **50**, which is proportional to or otherwise correlates to the amount of diminution in length of the brush **24**. The wear state monitor **50** rotates about an axis of rotation passing through the center of the wear state monitor **50**. The axis of rotation is a fixed distance from the second end **34** of the carbon brush **24** as the wear state monitor **50** rotates, and thus the axis of rotation translates with the brush **24** as the brush **24** wears and diminishes in length.

(58) For example, in some instances, the sensor **56** may obtain values corresponding to a first position of the brush **24**, at a first temporal occasion T.sub.0, such as an initial position of the brush **24** when the brush **24** has been placed on the electrical device and having approximately no wear. In other words, the sensor **56** may be used to sense the angular position of the wear state monitor **50** at the initial temporal occasion T.sub.0. The sensor **56** may obtain values corresponding to a position of the brush **24** at a later temporal occasion T.sub.1 after the brush has been worn a first amount. In other words, the sensor **56** may be used to sense the angular position of the wear state monitor **50** at the temporal occasion T.sub.1. The sensor **56** may obtain additional values corresponding to a further position of the brush **24** at later temporal occasions T.sub.2, T.sub.3, T.sub.4, etc. after the brush has been worn an additional amount. In other words, the sensor **56** may be used to sense the angular position of the wear state monitor **50** at the further temporal occasions T.sub.2, T.sub.3, T.sub.4, etc. The angular displacement of the wear state monitor **50** between each temporal occasion may be used to determine the diminution in length of the brush **24**, and thus the current wear state of the brush **24** and/or project when the brush **24** will diminish in length to a threshold amount at a future time. In some instances, the threshold amount may correspond to a brush length approximating when the brush **24** has a predetermined amount of wear (e.g., approaching the replacement threshold, maximum allowable wear, etc.).

(59) Additionally, in some cases, the sensor **56** may be configured to sense a first threshold value corresponding to a first wear state of the brush **24** and a second threshold value different from the first threshold value corresponding to a second wear state of the brush **24**. For example, the first threshold value may include the total rotation amount or angular displacement of the wear state monitor **50** indicative of a wear state where the brush **24** should be replaced within a predetermined time period (e.g., within a week). The second threshold value may correspond to a total rotation amount or angular displacement of the wear state monitor **50** indicative of a wear state requiring the brush **24** to be replaced as soon as possible.

(60) FIGS. 7 and 8 illustrate side views of the brush holder assembly **110** shown in FIG. 1, at different temporal occasions representing different identifiable wear states of the brush **24**. For simplicity purposes, the spacer **30** (shown in FIG. 1) has been removed from FIGS. 7 and 8. Additionally, FIGS. 7 and 8 illustrate the brush holder assembly **110** including the brush holder **22** secured to the mounting beam **26**, whereby the mounting beam **26** is configured to be removably

mounted to the mounting block **70**. Further, FIGS. **7** and **8** show the mounting beam **26** including the upper beam member **27** and the lower beam member **28** pivotally coupled to one another in the engaged position, as described above with respect to FIG. **1**. FIG. **7** and FIG. **8** further illustrate the brush holder assembly **110** including a handle **21** and the conductive wires **62** attached to both the brush **24** and extending therefrom.

(61) As discussed above and illustrated in FIGS. **7** and **8**, an end region of the spring **29** may be coiled around a portion (e.g., the medial region) of the wear state monitor **50** while the elongate portion of the spring **29** extends along a side surface of the brush **24** with the first end **32** of the spring **29** coupled to the mounting beam **26**. Further, while not visible in FIGS. **7** and **8**, a sensor and/or power supply may be positioned within an interior space (e.g., a cavity) within the wear state monitor **50** (as described above).

(62) FIG. **7** illustrates a first configuration (e.g., an initial wear state) of the brush **24** at an initial temporal occasion $T_{sub.0}$, such as when the brush **24** of the brush holder assembly **110** is first installed on an electrical machine. FIG. **7** illustrates the brush **24** positioned within the brush holder **22** (as described above with respect to FIG. **1**), with the lower surface of the brush **24** engaged with the conductive surface **12** of the rotating component **15**. Additionally, FIG. **7** shows that the first end surface **34** of the brush **24** is positioned a distance $X_{sub.1}$ from the end of the brush holder **22** nearest the handle **21** at an initial position at the initial temporal occasion $T_{sub.0}$. It can be appreciated that when the brush holder assembly **110** is in an engaged position, the spring **29** may apply a force to the first end surface **34** of the brush **24** to engage the brush **24** with the conductive surface **12** of the rotating component **15**.

(63) For illustrative purposes, FIG. **7** includes a “rotation marker” **64** placed on the wear state monitor **50**. For simplicity, the rotation marker **64** has been placed on the wear state monitor **50** at approximately the “twelve o'clock” position, but could be placed at any desired location. The rotation marker **64** need not be a visual marker, although it is possible to include a visual marker. The rotation marker **64** may be representative of a positional signal provided by the sensor **56** of a rotational orientation of the wear state monitor **50**.

(64) FIG. **8** illustrates a second configuration (e.g., a second wear state) of the brush **24** at a later temporal occasion $T_{sub.1}$, such as after the brush **24** has engaged the conductive surface **12** of the rotating component **15** over a period of time and diminished in length. As described above, the spring **29** may continue to exert a force on the first end surface **34** of the brush **24** as the brush **24** wears away against the conductive surface **12** of the rotating component **15**. For example, FIG. **8** illustrates the first end surface **34** of the brush **24** positioned a distance $X_{sub.2}$ from end of the brush holder **22** nearest the handle. It can be appreciated that the difference between distance “ $X_{sub.2}$ ” and distance “ $X_{sub.1}$ ” shown in FIG. **7**, represents the amount of diminution in length of the brush **24** (i.e., how much the brush **24** has shortened in length).

(65) Additionally, as described above, as the brush **24** translates within the brush holder **22**, the wear state monitor **50** may rotate in proportion to the length of shortening of the brush **24**. The rotation or angular displacement θ of the wear state monitor **50** between the initial rotational position of the wear state monitor **50** at $T_{sub.0}$ and the rotational position of the wear state monitor **50** at $T_{sub.1}$ is illustrated in FIG. **8**. Additionally, FIG. **8** shows the rotation position marker **64** in a second position, further representing the rotation or angular displacement of the wear state monitor **50**. It is noted that the rotational axis of the wear state monitor **50** remains at a fixed distance from the upper surface of the brush **24** throughout the wear of the brush **24**.

(66) As described above, as the wear state monitor **50** rotates in response to the shortening of the brush **24** (e.g., the wearing of the second end surface **35** of the brush **24**), the sensor **56** may measure and collect information relating to the rotation or angular displacement of the wear state monitor **50**. Further, this information relating to the rotation or angular displacement of the wear state monitor **50** may be analyzed to determine an amount of diminution in length of the brush **24**, a current wear state of the brush **24**, a wear rate of the brush **24**, and/or predict a future wear state of

the brush **24** at a future time. Such information and/or data regarding the state of the brush **24** may be communicated to the site monitoring device **120** and/or a remote monitoring device **140**. The remote monitoring device **140** may be located at the same and/or at a different geographical location from the geographical location of the electrical machine and the site monitoring device **120**.

(67) In some cases, the wear state monitor **50**, the site monitor **120** and/or the remote monitoring device **140** may include a processor capable of processing instructions for predicting a life expectancy of the brush **24** and/or the rotating component **15** of the electrical machine. In some cases, the processor may be capable of processing instructions for identifying the wear state of the carbon brush and/or identifying the wear state of the rotating electrical component (e.g., a slip ring, a commutator, etc.) of the electrical device.

(68) Those skilled in the art will recognize that aspects of the present disclosure may be manifested in a variety of forms other than the specific embodiments described and contemplated herein. Accordingly, departure in form and detail may be made without departing from the scope and spirit of the present disclosure as described in the appended claims.

Claims

1. A system for monitoring the wear state of a carbon brush, comprising: a carbon brush having an upper surface, a lower surface opposite the upper surface, and a length measured from the upper surface to the lower surface, wherein the length is diminished from an initial length as the lower surface of the carbon brush wears away during use; a spring having a coiled portion and an elongate portion extending from the coiled portion, wherein the spring is configured to provide a force urging the lower surface of the carbon brush into contact with a rotating conductive surface of an electrical machine; a spacer coupled to the upper surface of the carbon brush, the spacer positioned between the coiled portion of the spring and the upper surface of the carbon brush; and a wear state monitor including a sensor, wherein the sensor is configured to measure an amount of diminution in the length of the carbon brush from its initial length as the lower surface of the carbon brush wears away during use; wherein the wear state monitor is configured to detect an angular position of the sensor to a magnet.
2. The system of claim 1, wherein the spacer includes an engagement feature configured to mate with a complementary engagement feature in the upper surface of the carbon brush.
3. The system of claim 1, wherein the spacer includes a pin configured to extend into a bore located within the upper surface of the carbon brush.
4. The system of claim 1, wherein the sensor measures an angular displacement of the coiled portion of the spring.
5. The system of claim 1, wherein the sensor is positioned within the coiled portion of the spring.
6. The system of claim 1, wherein the sensor is configured to sense a change in a magnetic field created by the magnet.
7. The system of claim 1, wherein the wear state monitor is positioned in the coiled portion of the spring.
8. The system of claim 1, wherein the spacer defines a concave cradle, wherein the coiled portion of the spring rests in the cradle.
9. The system of claim 1, wherein the sensor is configured to transmit a wireless signal to a site monitor, and wherein the wireless signal is configured to provide information relating to diminution in length of the carbon brush.
10. A system for monitoring the wear state of a carbon brush, comprising: a carbon brush having an upper surface, a lower surface opposite the upper surface, and a length measured from the upper surface to the lower surface, wherein the length is diminished from an initial length as the lower surface of the carbon brush wears away during use; a spring having a coiled portion and an

elongate portion extending from the coiled portion, wherein the spring is configured to provide a force urging the lower surface of the carbon brush into contact with a rotating conductive surface of an electrical machine; a spacer coupled to the upper surface of the carbon brush, the spacer positioned between the coiled portion of the spring and the upper surface of the carbon brush; and a wear state monitor including a sensor, wherein the sensor is configured to measure an amount of diminution in the length of the carbon brush from its initial length as the lower surface of the carbon brush wears away during use; wherein the sensor includes an accelerometer configured to sense dynamic vibration of the carbon brush.

11. The system of claim 1, wherein the wear state monitor is configured to rotate through an arc angle as the carbon brush wears away, and wherein the arc angle correlates to the amount the carbon brush wears away.

12. The system of claim 1, wherein the wear state monitor rotates about an axis of rotation, wherein the axis of rotation is a fixed distance from an upper surface of the carbon brush as the wear state monitor rotates.

13. A system for monitoring the wear state of a carbon brush, comprising: a carbon brush having an upper surface, a lower surface opposite the upper surface, and a length measured from the upper surface to the lower surface, wherein the length is diminished from an initial length as the lower surface of the carbon brush wears away during use; a spring having a coiled portion and an elongate portion extending from the coiled portion, wherein the spring is configured to provide a force urging the lower surface of the carbon brush into contact with a rotating conductive surface of an electrical machine; a spacer coupled to the upper surface of the carbon brush, the spacer positioned between the coiled portion of the spring and the upper surface of the carbon brush; and a wear state monitor including a sensor, wherein the sensor is configured to measure an amount of diminution in the length of the carbon brush from its initial length as the lower surface of the carbon brush wears away during use; wherein the spacer defines a concave cradle, wherein the coiled portion of the spring rests in the cradle; wherein the spacer includes a pin configured to extend into a bore located within the upper surface of the carbon brush; wherein the wear state monitor is configured to detect an angular position of the sensor to a magnet.

14. The system of claim 13, wherein the sensor measures an angular displacement of the coiled portion of the spring.

15. The system of claim 13, wherein the sensor is configured to sense a change in a magnetic field created by the magnet.

16. The system of claim 13, wherein the sensor is configured to transmit a wireless signal to a site monitor, and wherein the wireless signal is configured to provide information relating to diminution in length of the carbon brush.

17. A method for monitoring the wear state of a carbon brush, the method comprising: detecting an angular position of a sensor to a magnet by sensing a change in a magnetic field created by the magnet with the sensor; determining an angular displacement of a coiled portion of a spring of a brush holder assembly based on the change in the magnetic field sensed by the sensor as a length of a carbon brush of the brush holder assembly diminishes during use, wherein the spring is configured to provide a force urging the carbon brush into contact with a rotating conductive surface of an electrical machine; and determining a wear state of the carbon brush based on the angular displacement of the coiled portion of the spring.

18. The method of claim 17, further comprising a spacer positioned between the coiled portion of the spring and the carbon brush.

19. The method of claim 18, wherein the spacer defines a concave cradle, wherein the coiled portion of the spring rests in the cradle.
