

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12419122
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kang; Dong Hoon

Image sensor package

Abstract

An image sensor package includes: a solder resist layer wrapping a redistribution layer and a connection pad; a mold layer on the solder resist layer and including an inner wall and an opposing outer wall, the inner wall defining a sensor array region; a logic chip on the solder resist layer and in the sensor array region, and contacting the mold layer; an image sensor chip on the logic chip and in the sensor array region, and contacting the mold layer; a transparent substrate spaced apart from the image sensor chip in a first direction; and an adhesive layer disposed between the transparent substrate and the mold layer. The mold layer includes a third face and a fourth face opposite to each other and connecting the inner wall and the outer wall. The fourth face of the mold layer does not overlap the image sensor chip in the first direction.

Inventors:	Kang; Dong Hoon (Hwaseong-si, KR)
Applicant:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Family ID:	1000008818821
Assignee:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Appl. No.:	18/651840
Filed:	May 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240282790 A1	Aug. 22, 2024

Foreign Application Priority Data

KR	10-2020-0149951	Nov. 11, 2020
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: H10F39/00 (20250101); H10F39/18 (20250101)

U.S. Cl.:

CPC H10F39/804 (20250101); H10F39/011 (20250101); H10F39/182 (20250101); H10F39/8053 (20250101); H10F39/8063 (20250101); H10F39/811 (20250101);

Field of Classification Search

CPC: H10F (39/804); H10F (39/182); H10F (39/8063); H10F (39/011); H10F (39/8053); H10F (39/811)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9653504	12/2016	Lin et al.	N/A	N/A
9899442	12/2017	Katkar	N/A	N/A
10418395	12/2018	Chiu	N/A	N/A
10418396	12/2018	Wu	N/A	N/A
10615212	12/2019	Jung et al.	N/A	N/A
12002827	12/2023	Kang	N/A	H10F 39/8053
2005/0236684	12/2004	Chen et al.	N/A	N/A
2006/0006486	12/2005	Seo et al.	N/A	N/A
2006/0086899	12/2005	Chao et al.	N/A	N/A
2016/0172402	12/2015	Katkar	N/A	N/A
2019/0363121	12/2018	Chiu	N/A	N/A
2020/0098808	12/2019	Wu et al.	N/A	N/A
2022/0149095	12/2021	Kang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H09-181096	12/1996	JP	N/A
H10-65037	12/1997	JP	N/A
10-1020876	12/2010	KR	N/A
10-1522758	12/2014	KR	N/A
10-2017-0093903	12/2016	KR	N/A
10-2019-0143584	12/2018	KR	N/A

OTHER PUBLICATIONS

Office Action dated Mar. 31, 2025 issued in corresponding Korean Patent Application No. 10-2020-0149951. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 17/398,503, filed on Aug. 10, 2021, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2020-0149951, filed on Nov. 11, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entirety.

TECHNICAL FIELD

(1) Embodiments of the present inventive concept relate to an image sensor package, and more specifically, to a transparent substrate disposed on a mold layer and an adhesive layer.

DISCUSSION OF RELATED ART

(2) An image sensor is a semiconductor device that converts optical information into an electric signal. Examples of image sensors include a charge coupled device (CCD) image sensor and a complementary metal-oxide semiconductor (CMOS) image sensor.

(3) An image sensor may be configured in a package. An image sensor package may be configured as a structure which protects the image sensor and allows light to enter a photo receiving surface or a sensing area of the image sensor.

SUMMARY

(4) According to an embodiment of the inventive concept, an image sensor package includes: an image sensor chip that includes first and second faces that are opposite to each other, the image sensor chip including side walls that connect the first and second faces; a mold layer disposed on the side walls of the image sensor chip and that includes third and fourth faces that are opposite to each other; a transparent substrate disposed on the second face of the image sensor chip and spaced apart from the image sensor chip in a first direction, the transparent substrate including a first portion that overlaps the image sensor chip in the first direction and a second portion that does not overlap the image sensor chip in the first direction; and an adhesive layer disposed between the mold layer and the second portion of the transparent substrate, wherein the side walls of the image sensor chip overlap the mold layer in a second direction intersecting the first direction and the fourth face of the mold layer does not overlap the image sensor chip in the first direction.

(5) According to an embodiment of the present inventive concept, an image sensor package includes: a solder resist layer that wraps around a redistribution layer and a connection pad; a mold layer disposed on the solder resist layer and including an inner wall and an outer wall opposite to the inner wall, the inner wall of the mold layer defining a sensor array region; an image sensor chip disposed on the solder resist layer and in the sensor array region, and contacting the mold layer; a transparent substrate spaced apart from the image sensor chip in a first direction; and an adhesive layer disposed between the transparent substrate and the mold layer, wherein the mold layer includes a third face and a fourth face that are opposite to each other and that connect the inner wall of the mold layer and the outer wall of the mold layer, and the fourth face of the mold layer does not overlap the image sensor chip in the first direction.

(6) According to an embodiment of the present inventive concept, an image sensor package includes: an image sensor chip that includes a first face on which a redistribution layer is formed and a second face that is opposite to the first face and on which a photoelectric conversion layer is formed, the image sensor chip including side walls that connect the first and second faces; a solder resist layer disposed on the first face of the image sensor chip and that wraps around the

redistribution layer and a connection pad on the redistribution layer; a mold layer disposed on the side walls of the image sensor chip and that includes a third face placed on a same plane as the first face of the image sensor chip and a fourth face opposite to the third face; a transparent substrate disposed on the second face of the image sensor chip and that is spaced apart from the image sensor chip in a first direction, the transparent substrate including a first portion that overlaps the image sensor chip in the first direction and a second portion that does not overlap the image sensor chip in the first direction; an adhesive layer placed between the second portion of the transparent substrate and the fourth face of the mold layer; and a solder bump disposed on the connection pad and electrically connected to the redistribution layer and the connection pad, wherein the image sensor chip includes a first substrate layer including a through electrode and a second substrate layer placed on the first substrate layer and including the photoelectric conversion layer, wherein the through electrode penetrates the first substrate layer and electrically connects the redistribution layer and the photoelectric conversion layer, wherein the side walls of the image sensor chip overlap the mold layer in a second direction intersecting the first direction, and wherein the fourth face of the mold layer does not overlap the first substrate layer in the first direction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other features of the inventive concept will become more apparent by describing in detail embodiments thereof with reference to the accompanying drawings, in which:
- (2) FIG. 1 is a plan view of an image sensor package according to an embodiment of the present inventive concept;
- (3) FIG. 2 is a cross-sectional view taken along a line A-A of FIG. 1;
- (4) FIG. 3 is an enlarged view of a region P of FIG. 2;
- (5) FIG. 4 is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept;
- (6) FIG. 5 is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept;
- (7) FIG. 6 is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept;
- (8) FIG. 7 is a cross-sectional view of a sensor package according to an embodiment of the present inventive concept; and
- (9) FIGS. 8 to 19 are intermediate stage diagrams illustrating a method for fabricating an image sensor package according to embodiments of the present inventive concept.
- (10) It should be noted that these figures are intended to illustrate the general characteristics of methods, structure, and/or materials used in certain embodiments and to supplement the written description provided below. The drawings are not, however, to scale and may not precisely reflect the precise structural or performance characteristics of any given embodiment, and should not be interpreted as defining or limiting the range of values or properties encompassed by embodiments. For example, the relative thickness and positioning of modules, layers, regions, and/or structural elements may be reduced or exaggerated for clarity. The use of similar reference numbers in the various drawings is intended to indicate the presence of a similar or identical element or feature.

DETAILED DESCRIPTION

- (11) Embodiments of the present inventive concept will be described more fully hereinafter with reference to the accompanying drawings. Like reference numerals may refer to like elements throughout the accompanying drawings.
- (12) It will be understood that when a component, such as a film, a region, a layer, or an element, is referred to as being “on”, “connected to”, “coupled to”, or “adjacent to” another component, it can

be directly on, connected, coupled to, or adjacent to the other component, or intervening components may be present. It will also be understood that when a component is referred to as being “between” two components, it can be the only component between the two components, or one or more intervening components may also be present. It will also be understood that when a component is referred to as “covering” another component, it can be the only component covering the other component, or one or more intervening components may also be covering the component. Other words to use to describe the relationship between elements should be interpreted in a like fashion.

(13) It will be understood that, although the terms “first”, “second”, etc. may be used herein to describe various elements, components, regions, layers, and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or section from another element, component, region, layer, or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of embodiments.

(14) Spatially relative terms, such as “beneath”, “below”, “lower”, “above”, “upper”, and the like may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the package in use or operation in addition to the orientation depicted in the figures. For example, if the package in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The package may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

(15) As used herein, the singular forms “a”, “an”, and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

(16) Embodiments of the present inventive concept are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments of the present inventive concept should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing, as would be understood by a person having ordinary skill in the art.

(17) FIG. 1 is a plan view of an image sensor package according to an embodiment of the present inventive concept.

(18) Referring to FIG. 1, an image sensor package according to an embodiment of the present inventive concept may include a mold layer **200** including an inner wall **200is** and an outer wall **200os** opposite to the inner wall **200is**.

(19) The inner wall **200is** of the mold layer **200** may define a sensor array region SAR. An image sensor chip (e.g., **100** of FIG. 2) may be disposed inside the sensor array region SAR. The mold layer **200** may be formed along the periphery of the sensor array region SAR.

(20) Although not shown in FIG. 1, an adhesive layer (e.g., **300** of FIG. 2) may be formed on the mold layer **200**. A transparent substrate (e.g., **400** of FIG. 2) that covers the adhesive layer and the sensor array region SAR may be formed on the adhesive layer and the sensor array region SAR.

(21) The sensor array region SAR may include a region corresponding to an active pixel sensor array. For example, a plurality of unit pixels disposed two-dimensionally (for example, in the form of a matrix) may be formed in the sensor array region SAR.

(22) Although it is not shown, the sensor array region SAR may include a photo receiving region and a photo shielding region. Active pixels that receive light and generate an active signal may be arranged in the photo receiving region. Optical black pixels that shield light and generate an optical

black signal may be arranged in the photo shielding region. Although the photo shielding region may be formed, for example, along the periphery of the photo receiving region, the present inventive concept is not limited as such.

(23) FIG. 2 is a cross-sectional view taken along a line A-A of FIG. 1. FIG. 3 is an enlarged view of a region P of FIG. 2.

(24) Referring to FIGS. 2 and 3, an image sensor package according to an embodiment of the present inventive concept may include an image sensor chip **100**, a solder resist layer **120**, a mold layer **200**, an adhesive layer **300**, and a transparent substrate **400**.

(25) The image sensor chip **100** may include a first face **100A** and a second face **100B** that are opposite to each other. The first face **100A** and the second face **100B** may be parallel to each other. The first face **100A** and the second face **100B** may not intersect each other.

(26) The first face **100A** may be a lower face of the image sensor chip **100** in a first direction **D1**. The second face **100B** may be an upper face of the image sensor chip **100** in the first direction **D1**. The first direction **D1** may be, for example, perpendicular to the first face **100A** and the second face **100B**.

(27) The image sensor chip **100** may include a side wall **100S** that connects the first face **100A** and the second face **100B**. The side wall **100S** of the image sensor chip **100** may be aligned with the first direction **D1**. That is, the side wall **100S** of the image sensor chip **100** may have a linear shape.

(28) A redistribution layer **115** and a solder resist layer **120** may be disposed on the first face **100A** of the image sensor chip **100**. The solder resist layer **120** and the redistribution layer **115** may be in contact with the first face **100A** of the image sensor chip **100**.

(29) The image sensor package according to some embodiments may include a connection pad **110** that is in contact with the redistribution layer **115**. The image sensor package according to some embodiments may include a solder bump **105** connected to the connection pad **110**. The solder bump **105** may electrically connect the connection pad **110** and the redistribution layer **115**.

(30) The solder resist layer **120** may wrap around the redistribution layer **115** and the connection pad **110**. The solder resist layer **120** may not wrap around the solder bump **105**. That is, the solder bump **105** may protrude from the lower face of the solder resist layer **120** in the first direction **D1**.

(31) The solder bump **105** may include a substance included in a solder material. For example, the solder bump **105** may include, but is not limited to, at least one of lead (Pb), tin (Sn), indium (In), bismuth (Bi), antimony (Sb), silver (Ag), and alloys thereof.

(32) The solder resist layer **120** may be made of, for example, a passivation substance, such as polyimide. Alternatively, the solder resist layer **120** may be made of, but is not limited to, for example, BCB (benzocyclobutenes), polybenzoxazole, polyimide, epoxy, silicon oxide, silicon nitride, or a combination thereof.

(33) The redistribution layer **115** may include a conductive substance. The redistribution layer **115** may include, but is not limited to, for example, at least one of copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), and alloys thereof.

(34) The image sensor chip **100** may be disposed on the solder resist layer **120**. The image sensor chip **100** may include a first substrate layer **130**, a first through electrode **135**, a second substrate layer **140**, a color filter **150**, and a microlens **160**.

(35) The first substrate layer **130** may be disposed on the solder resist layer **120**. The pixel gate layer **143** may be disposed inside the first substrate layer **130**.

(36) The first substrate layer **130** may include, for example, at least one of silicon oxide, silicon nitride, silicon oxynitride, and a low dielectric constant (low-k) substance having a lower dielectric constant than silicon oxide. The low dielectric constant substance may include, but is not limited to, for example, at least one of FOX (Flowable Oxide), TOSZ (Torene SilaZene), USG (Undoped Silica Glass), BSG (Borosilica Glass), PSG (PhosphoSilica Glass), BPSG (BoroPhosphoSilica Glass), PETEOS (Plasma Enhanced Tetra Ethyl Ortho Silicate), FSG (Fluoride Silicate Glass), CDO (Carbon Doped silicon Oxide), Xerogel, Aerogel, Amorphous Fluorinated Carbon, OSG

(Organo Silicate Glass), Parylene, BCB (bis-benzocyclobutenes), SiLK, polyimide, porous polymeric material, or a combination thereof.

(37) A connection wiring **137** may be disposed inside the first substrate layer **130**. The connection wiring **137** may be electrically connected to a storage node region **142**, a photoelectric conversion layer PD, and a pixel gate layer **143**.

(38) The connection wiring **137** may include a wiring barrier layer and a wiring filling layer. The wiring barrier layer may include, for example, at least one of tantalum (Ta), tantalum nitride (TaN), titanium (Ti), titanium nitride (TiN), ruthenium (Ru), cobalt (Co), nickel (Ni), nickel boron (NiB), tungsten (W), tungsten nitride (WN), zirconium (Zr), zirconium nitride (ZrN), vanadium (V), vanadium nitride (VN), niobium (Nb), niobium nitride (NbN), platinum (Pt), iridium (Ir), and rhodium (Rh).

(39) The wiring filling layer may include, for example, at least one of aluminum (Al), copper (Cu), tungsten (W), cobalt (Co), ruthenium (Ru), and molybdenum (Mo).

(40) The first through electrode **135** may be formed inside the first substrate layer **130**. The first through electrode **135** may penetrate the first substrate layer **130** and electrically connect the connection wiring **137** with the redistribution layer **115**. The redistribution layer **115** and the photoelectric conversion layer PD may be electrically connected accordingly.

(41) The second substrate layer **140** may be disposed on the first substrate layer **130**. The second substrate layer **140** may be, for example, bulk silicon or SOI (silicon-on-insulator). Alternatively, the second substrate layer **140** may be a silicon substrate or may include other substances, but are not limited to, for example, silicon germanium, SGOI (silicon germanium on insulator), indium antimonide, lead tellurium compounds, indium arsenic, indium phosphorus, gallium arsenide, or gallium antimonide.

(42) The storage node region **142** may be formed inside the second substrate layer **140**. The storage node region **142** may be disposed apart from the photoelectric conversion layer PD. The storage node region **142** may include impurities of conductivity type different from the second substrate layer **140**. The storage node region **142** may be a region corresponding to a floating diffusion region.

(43) The photoelectric conversion layer PD may be disposed inside the second substrate layer **140**. The photoelectric conversion layer PD may generate a light charge in proportion to an amount of light incident from the outside. The photoelectric conversion layer PD may receive light and convert an optical signal into an electric signal. The photoelectric conversion layer PD may be formed by doping impurities in the second substrate layer **140**.

(44) For example, there may be a concentration difference in impurities between an upper part and a lower part of the photoelectric conversion layer PD so that the photoelectric conversion layer PD may have a potential gradient. For example, the photoelectric conversion layer PD may be formed in a stacked form of a plurality of impurity regions.

(45) A pixel separation region **144** may be disposed to surround the photoelectric conversion layer PD. Although the pixel separation region **144** is shown to extend from the lower face to the upper face of the second substrate layer **140**, this is only for convenience of explanation, and embodiments are not limited thereto. The pixel separation region **144** may prevent the light charges generated in a specific pixel by incident light from moving to the adjacent pixel region by a random drift. Further, the pixel separation region **144** may refract incident light that is obliquely incident on the photoelectric conversion layer PD.

(46) A first flattening film **145** may be disposed on the second substrate layer **140**. The first flattening film **145** may include an insulating substance. Further, the first flattening film **145** may include, for example, a silicon oxide film. Unlike the shown configuration, in some embodiments of the present inventive concept, the first flattening film **145** may be omitted.

(47) A color filter **150** may be disposed on the first flattening film **145**. The color filter **150** may be disposed on the photoelectric conversion layer PD. The color filter **150** may allow light of a

specific wavelength to pass and reach the lower photoelectric conversion layer PD. The color filter **150** may be implemented, for example, as a color filter array including at least one of a red (R) filter, a green (G) filter, and a blue (B) filter. The color filter **150** may be made up of, for example, a substance obtained by mixing a resin with a pigment including a metal or a metal oxide.

(48) A second flattening film **155** may be disposed on the color filter **150**. The second flattening film **155** may include an insulating substance, for example, a silicon oxide.

(49) The microlens **160** may change the path of light incident on a region other than the photoelectric conversion layer PD and concentrate the light into the photoelectric conversion layer PD. The microlens **160** may include, but is not limited to, organic substances such as light transmissive resin.

(50) The mold layer **200** may be disposed on the side wall **100S** of the image sensor chip **100**, on the solder resist layer **120**. The mold layer **200** may include an inner wall **200is** that is in contact with the side wall **100S** of the image sensor chip **100**, and an outer wall **200os** opposite to the inner wall **200is**.

(51) The side wall **100S** of the image sensor chip **100** may overlap the mold layer **200** in the second direction **D2**. The second direction **D2** may intersect the first direction **D1**. For example, the second direction **D2** may be perpendicular to the first direction **D1**.

(52) The mold layer **200** may include a third face **200A** and a fourth face **200B** that are opposite to each other. The third face **200A** in the first direction **D1** may be, for example, a lower face of the mold layer **200** in the first direction **D1**. The fourth face **200B** may be, for example, an upper face of the mold layer **200** in the first direction **D1**.

(53) The inner wall **200is** of the mold layer **200** may connect the third face **200A** of the mold layer **200** and the fourth face **200B** of the mold layer **200**. Similarly, the outer wall **200os** of the mold layer **200** may connect the third face **200A** of the mold layer **200** and the fourth face **200B** of the mold layer **200**. The inner wall **200is** and the outer wall **200os** of the mold layer **200** may be aligned with the first direction **D1** and perpendicular to the second direction **D2**.

(54) The third face **200A** of the mold layer **200** may be in contact with the solder resist layer **120**. The third face **200A** of the mold layer **200** may be disposed on a same plane as the first face **100A** of the image sensor chip **100**.

(55) The fourth face **200B** of the mold layer **200** may be disposed on a plane different from the second face **100B** of the image sensor chip **100**. Specifically, the second face **100B** of the image sensor chip **100** may be lower than the fourth face **200B** of the mold layer **200**.

(56) A height **H1** from the second face **100B** of the image sensor chip **100** to the fourth face **200B** of the mold layer **200** may be 50 μm or more and 200 μm or less. The height **H1** from the second face **100B** of the image sensor chip **100** to the fourth face **200B** of the mold layer **200** may be 100 μm .

(57) A level difference between the image sensor chip **100** and the mold layer **200** may reduce a flare. Further, the level difference between the image sensor chip **100** and the mold layer **200** may reduce a ghost risk.

(58) The mold layer **200** may include, for example, an insulating substance. For example, the mold layer **200** may include a thermosetting resin such as an epoxy resin, a thermoplastic resin such as polyimide, or resins obtained by mixing resins with an inorganic filler or by impregnating resins in core materials such as glass fiber (Glass Cloth, Glass Fabric) together with an inorganic filler (e.g., prepreg, ABF (Ajinomoto Build-up Film), FR-4, and BT (Bismaleimide Triazine)) and the like. Alternatively, the mold layer **200** may also include a photoimageable dielectric (PID).

(59) The transparent substrate **400** may be disposed on the second face **100B** of the image sensor chip **100** and spaced apart from the image sensor chip **100** in the first direction **D1**.

(60) The transparent substrate **400** may include a first portion **400_1** that may overlap the image sensor chip **100** in the first direction **D1**, and a second portion **400_2** that may not overlap the image sensor chip **100** in the first direction **D1**. The second portion **400_2** of the transparent

substrate **400** may overlap the mold layer **200** in the first direction **D1**.

(61) The transparent substrate **400** may include a fifth face **400A** facing the second face **100B** of the image sensor chip **100**, and a sixth face **400B** opposite to the fifth face **400A**. In the first direction **D1**, the fifth face **400A** of the transparent substrate **400** may be, for example, a lower face of the transparent substrate **400**. In the first direction **D1**, the sixth face **400B** of the transparent substrate **400** may be, for example, an upper face of the transparent substrate **400**.

(62) In some embodiments, the transparent substrate **400** may be a glass substrate. In another embodiment, the transparent substrate **400** may also be a plastic substrate.

(63) The adhesive layer **300** may be disposed on the mold layer **200**. The adhesive layer **300** may be disposed between the mold layer **200** and the transparent substrate **400**. Specifically, the adhesive layer **300** may be disposed between the mold layer **200** and the second portion **400_2** of the transparent substrate **400**.

(64) The adhesive layer **300** may be in contact with the fourth face **200B** of the mold layer **200**. Also, the adhesive layer **300** may be in contact with the second portion **400_2** of the transparent substrate **400**.

(65) The adhesive layer **300** may include an inner wall **300is**, and an outer wall **300os** opposite to the inner wall **300is**. The inner wall **300is** of the adhesive layer **300** may be disposed on the same plane as the inner wall **200is** of the mold layer **200**. Similarly, the outer wall **300os** of the adhesive layer may be disposed on the same plane as the outer wall **200os** of the mold layer **200**.

(66) The adhesive layer **300** may include, for example, a curable polymer. The adhesive layer **300** may include, for example, an epoxy-based polymer.

(67) An image sensor package according to an embodiment of the present inventive concept may include a cavity **CV**. The cavity **CV** may be defined by the fifth face **400A** of the transparent substrate **400**, the second face **100B** of the image sensor chip **100**, the inner wall **200is** of the mold layer **200**, and the inner wall **300is** of the adhesive layer **300**. The cavity **CV** may be filled with air. The microlens **160** may be disposed inside the cavity **CV**.

(68) FIG. **4** is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept. For convenience, differences from components described with reference to FIGS. **1** to **3** will be mainly described.

(69) Referring to FIG. **4**, an image sensor package according to an embodiment of the present inventive concept may further include a first semiconductor chip **500**.

(70) The first semiconductor chip **500** may be disposed on the first face **100A** of the image sensor chip **100** and spaced apart from the first face **100A** of the image sensor chip **100** in the first direction **D1**. The solder resist layer **120** and the solder bump **105** may be disposed between the first semiconductor chip **500** and the image sensor chip **100**.

(71) The first semiconductor chip **500** may include a chip pad **505**. The solder bump **105** may be disposed on the chip pad **505**. The first semiconductor chip **500** may be electrically connected to the image sensor chip **100** through the solder bump **105**.

(72) The first semiconductor chip **500** may include, for example, a PCB substrate. Further, the first semiconductor chip **500** may include, for example, a memory element, a digital signal process integrated circuit, an application specific integrated circuit, and a driver.

(73) FIG. **5** is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept. For convenience, differences from the components described with reference to FIGS. **1** to **3** will be mainly described.

(74) Referring to FIG. **5**, an image sensor package according to an embodiment of the present inventive concept may further include a second semiconductor chip **600**.

(75) The second semiconductor chip **600** may be a logic chip that converts light detected from an image sensor chip **100** into an electric signal.

(76) The second semiconductor chip **600** may be disposed on the solder resist layer **120**. The second semiconductor chip **600** may include a semiconductor substrate layer **610**, a first wiring

insulation layer **620**, and a second wiring insulation layer **630**.

(77) The semiconductor substrate layer **610** may be disposed on the solder resist layer **120**. The semiconductor substrate layer **610** may include a second through electrode **615**. The second through electrode **615** may penetrate the semiconductor substrate layer **610** and be electrically connected to the redistribution layer **115** and the connection pad **110**. The second semiconductor chip **600** and the photoelectric conversion layer (e.g., PD of FIG. 3) may be electrically connected accordingly.

(78) The semiconductor substrate layer **610** may be, for example, bulk silicon or SOI (silicon-on-insulator). Alternatively, the semiconductor substrate layer **610** may be a silicon substrate, or may include, but is not limited to, for example, other substances such as silicon germanium, SGOI (silicon germanium on insulator), indium antimonide, lead tellurium compounds, indium arsenic, indium phosphorus, gallium arsenide, or gallium antimonide.

(79) The first wiring insulation layer **620** may be disposed on the semiconductor substrate layer **610**. A first wiring layer **625** may be formed in the first wiring insulation layer **620**. The first wiring insulation layer **620** may wrap around the first wiring layer **625**. A first joining pad **627** may be electrically connected to the first wiring layer **625**.

(80) A second wiring insulation layer **630** may be disposed on the first wiring insulation layer **620**. The second wiring insulation layer **630** may be disposed between the first substrate layer **130** and the first wiring insulation layer **620**. A second wiring layer **635** may be formed inside the second wiring insulation layer **630**. A second joining pad **637** may be formed inside the second wiring insulation layer **630**. The second joining pad **637** may be electrically connected to the second wiring layer **635**.

(81) The first joining pad **627** and the second joining pad **637** may be directly connected to each other. That is, the first joining pad **627** and the second joining pad **637** may be directly bonded.

(82) Each of the first joining pad **627** and the second joining pad **637** may include a pad barrier layer and a pad filling layer. The pad barrier layer may include, for example, at least one of tantalum (Ta), tantalum nitride (TaN), titanium (Ti), titanium nitride (TiN), ruthenium (Ru), cobalt (Co), nickel (Ni), nickel boron (NiB), tungsten (W), tungsten nitride (WN), zirconium (Zr), zirconium nitride (ZrN), vanadium (V), vanadium nitride (VN), niobium (Nb), niobium nitride (NbN), platinum (Pt), iridium (Ir), and rhodium (Rh). The pad filling layer may include, for example, copper (Cu).

(83) FIG. 6 is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept. For convenience, differences from the components described with reference to FIGS. 1 to 5 will be mainly described.

(84) Referring to FIG. 6, an image sensor package according to an embodiment of the present inventive concept may include the first semiconductor chip **500** and the second semiconductor chip **600**.

(85) FIG. 7 is a cross-sectional view of an image sensor package according to an embodiment of the present inventive concept. For convenience, differences from the components described with reference to FIGS. 1 to 6 will be mainly described.

(86) Referring to FIG. 7, an image sensor package according to an embodiment of the present inventive concept may include a housing **700**.

(87) The housing **700** may wrap around the image sensor chip **100**. The housing **700** may protect the image sensor chip **100**. The housing **700** may be connected to the first semiconductor chip **500**.

(88) The housing **700** may include first to fourth lenses **710**, **720**, **730**, and **740**. The first to fourth lenses **710**, **720**, **730**, and **740** may be connected to the housing **700**. Light may be transmitted to the image sensor chip **100** through the first to fourth lenses **710**, **720**, **730**, and **740**.

(89) Although four lenses are shown, the present inventive concept is not limited thereto. Also, although the second to fourth lenses **720**, **730**, and **740** are shown to include a curved surface, the present inventive concept is not limited thereto, and the second to fourth lenses may, of course,

include a planar surface.

(90) Although not shown, an underfill layer may be included between the first semiconductor chip **500** and the image sensor chip **100**. The underfill layer may wrap around the solder bumps **105**.

(91) FIGS. **8** to **19** are intermediate stage diagrams illustrating a method for fabricating an image sensor package according to embodiments of the present inventive concept.

(92) Referring to FIG. **8**, an image sensor chip **100** that includes a first substrate layer **130** including a plurality of first through electrodes **135** and a second substrate layer **140** disposed on the first substrate layer **130** may be provided.

(93) The image sensor chip **100** may include a first face **100A** and a second face **100B** that are opposite to each other. The first face **100A** may be a lower face of the image sensor chip **100**. The second face **100B** may be an upper face of the image sensor chip **100**.

(94) The image sensor chip **100** may include a color filter **150** and a microlens **160** that are disposed on the second face **100B**. A region in which the color filter **150** and the microlens **160** are disposed may be a sensor array region (for example, SAR of FIG. **1**).

(95) Referring to FIG. **9**, a sacrificial layer **800** may be formed on the second face **100B** of the image sensor chip **100**.

(96) The lower face of the sacrificial layer **800** may be bonded to the second face **100B** of the image sensor chip **100**. The sacrificial layer **800** may cover the color filter **150** and the microlens **160**. The sacrificial layer **800** may be, for example, a tape substrate.

(97) Referring to FIG. **10**, a silicon carrier **900** may be provided.

(98) The silicon carrier **900** may be formed on the sacrificial layer **800**. The silicon carrier **900** may be bonded to the sacrificial layer **800**. Specifically, the silicon carrier **900** may be bonded to the upper face of the sacrificial layer **800**. The silicon carrier **900** may be, for example, a silicon substrate.

(99) Referring to FIG. **11**, a trench TR may be formed by etching a part of the image sensor chip **100** and a part of the sacrificial layer **800**.

(100) The trench TR may expose the silicon carrier **900**.

(101) Subsequently, referring to FIG. **12**, a pre mold layer **200p** that fills the trench TR and covers the first face **100A** of the image sensor chip **100** may be formed.

(102) The pre mold layer **200p** may include, for example, an insulating substance. For example, the pre mold layer **200p** may include a thermosetting resin such as an epoxy resin, a thermoplastic resin such as polyimide, or resins obtained by mixing resins with an inorganic filler or by impregnating resins in core materials such as glass fiber (Glass Cloth, Glass Fabric) together with an inorganic filler (e.g., prepreg, ABF (Ajinomoto Build-up Film), FR-4, and BT (Bismaleimide Triazine)) and the like. Alternatively, the pre mold layer **200p** may also include a photoimageable dielectric (PID).

(103) Subsequently, referring to FIG. **13**, the pre mold layer **200p** may be ground.

(104) The pre mold layer **200p** may be ground to form the mold layer **200**. The mold layer **200** may include a third face **200A** and a fourth face **200B** that are opposite to each other. The third face **200A** may be a lower face of the mold layer **200**. The fourth face **200B** may be an upper face of the mold layer **200**. The fourth face **200B** of the mold layer **200** may be disposed on the same plane as the upper face of the sacrificial layer **800**.

(105) The pre mold layer **200p** may be ground to expose the first face **100A** of the image sensor chip **100**. The third face **200A** of the mold layer **200** and the first face **100A** of the image sensor chip **100** may be disposed on the same plane.

(106) Referring to FIG. **14**, a solder resist layer **120**, a redistribution layer **115**, a connection pad **110**, and a solder bump **105** may be formed on the first face **100A** of the image sensor chip **100**.

(107) First, the redistribution layer **115** may be formed on a part of the first face **100A** of the image sensor chip **100**.

(108) The redistribution layer **115** may include a conductive substance. The redistribution layer **115**

may include, but is not limited to, for example, at least one of copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), and alloys thereof.

(109) Subsequently, the solder resist layer **120** may be formed. After the solder resist layer **120** is formed, the connection pad **110** may be formed. The solder resist layer **120** may wrap around the redistribution layer **115** and the connection pad **110**.

(110) Subsequently, the solder bump **105** may be formed on the connection pad **110**. The solder bump **105** may electrically connect the connection pad **110** and the redistribution layer **115** to the first through electrode **135**.

(111) Referring to FIG. **15**, the silicon carrier **900** may be removed.

(112) The silicon carrier **900** may be removed to expose the fourth face **200B** of the mold layer **200**. Also, the silicon carrier **900** may be removed to expose the sacrificial layer **800**.

(113) Referring to FIG. **16**, the mold layer **200** may be etched. The mold layer **200** may be sawed.

(114) The mold layer **200** may be cut to form a plurality of image sensor chips **100**. Each image sensor chip **100** may be an image sensor chip included in an image sensor package according to embodiments of the present inventive concept.

(115) Referring to FIG. **17**, the sacrificial layer **800** may be removed.

(116) The sacrificial layer **800** may be removed to expose the second face **200B** of the image sensor chip **100**. Also, the microlens **160** may be exposed.

(117) The fourth face **200B** of the mold layer **200** and the second face **100B** of the image sensor chip **100** may be spaced apart from each other in the first direction **D1**. That is, the second face **100B** of the image sensor chip **100** may be lower than the fourth face **200B** of the mold layer **200**.

(118) A height **H1** between the fourth face **200B** of the mold layer **200** and the second face **200B** of the image sensor chip **100** may be 50 μm or more and 200 μm or less. The height **H1** from the second face **100B** of the image sensor chip **100** to the fourth face **200B** of the mold layer **200** may be 100 μm .

(119) A flare phenomenon may be reduced due to a level difference between the mold layer **200** and the image sensor chip **100**. Further, a ghost risk may be reduced due to the level difference between the image sensor chip **100** and the mold layer **200**.

(120) Referring to FIG. **18**, an adhesive layer **300** may be formed on the mold layer **200**.

(121) The adhesive layer **300** may bond a transparent substrate **400** to be described later. A width of the adhesive layer **300** in the second direction **D2** may be the same as a width of the mold layer **200** in the second direction **D2**.

(122) The adhesive layer **300** may have a height **300H** in the first direction **D1**. The height **300H** of the adhesive layer **300** in the first direction **D1** may be at least 20 μm or more. The height **300H** of the adhesive layer **300** in the first direction **D1** may be 20 μm or more and 50 μm or less.

(123) Referring to FIG. **19**, the transparent substrate **400** may be attached. The transparent substrate **400** may be brought into contact with and bonded to the adhesive layer **300**.

(124) The transparent substrate **400** may include a second portion (e.g., **4002** of FIG. **2**) that is bonded to the adhesive layer **300**, and a first portion (e.g., **4001** of FIG. **2**) that is not bonded to the adhesive layer **300**.

(125) Although not shown, the first portion of the transparent substrate **400**, the image sensor chip **100**, the mold layer **200**, and the adhesive layer **300** may define a cavity (e.g., **CV** of FIG. **2**).

(126) In concluding the detailed description, those skilled in the art will appreciate that many variations and modifications may be made to embodiments without substantially departing from the principles of the present inventive concept. Therefore, disclosed embodiments of the of the present inventive concept are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. An image sensor package comprising: a solder resist layer that wraps around a redistribution layer and a connection pad; a mold layer disposed on the solder resist layer and including an inner wall and an outer wall opposite to the inner wall, the inner wall of the mold layer defining a sensor array region; a logic chip on the solder resist layer and in the sensor array region, and contacting the mold layer; an image sensor chip on the logic chip and in the sensor array region, and contacting the mold layer; a transparent substrate spaced apart from the image sensor chip in a first direction; and an adhesive layer disposed between the transparent substrate and the mold layer, wherein the mold layer includes a third face and a fourth face that are opposite to each other and that connect the inner wall of the mold layer and the outer wall of the mold layer, and the fourth face of the mold layer does not overlap the image sensor chip in the first direction.
2. The image sensor package of claim 1, wherein the image sensor chip includes a first face and a second face that are opposite to each other, wherein the transparent substrate includes a fifth face facing the second face of the image sensor chip and a sixth face that is opposite to the fifth face, and the image sensor package further comprises a cavity defined by the fifth face of the transparent substrate, the second face of the image sensor chip, the inner wall of the mold layer, and the inner wall of the adhesive layer.
3. The image sensor package of claim 2, wherein the cavity is filled with air.
4. The image sensor package of claim 1, wherein the image sensor chip includes a first face and a second face that are opposite to each other, and the first face of the image sensor chip is disposed on a same plane as the third face of the mold layer.
5. The image sensor package of claim 4, wherein the second face of the image sensor chip is lower than the fourth face of the mold layer.
6. The image sensor package of claim 1, wherein the logic chip includes a semiconductor substrate layer, a first wiring insulation layer surrounding a first joining pad, and a second wiring insulation layer surrounding a second joining pad, wherein the semiconductor substrate layer, the first wiring insulation layer and the second wiring insulation layer are sequentially arranged in the first direction on the solder resist layer.
7. The image sensor package of claim 6, wherein the first joining pad and the second joining pad are directly bonded.
8. The image sensor package of claim 1, wherein the image sensor chip includes a first face and a second face that are opposite to each other, and wherein a height in the first direction between the second face of the image sensor chip and the fourth face of the mold layer is 50 μm or more and 200 μm or less.
9. The image sensor package of claim 1, wherein the image sensor chip includes: a first substrate layer including a through electrode; and a second substrate layer disposed on the first substrate layer and including a photoelectric conversion layer, wherein the through electrode penetrates the first substrate layer and is electrically connected to the photoelectric conversion layer.
10. The image sensor package of claim 1, wherein at least a part of the solder resist layer overlaps the mold layer in the first direction.
11. An image sensor package comprising: a first semiconductor chip; an image sensor chip on the first semiconductor chip including: first and second faces that are opposite to each other; and side walls connecting the first and second faces; a mold layer disposed on the side walls of the image sensor chip and including third and fourth faces that are opposite to each other; a transparent substrate disposed on the second face of the image sensor chip and spaced apart from the image sensor chip in a first direction, the transparent substrate including a first portion that overlaps the image sensor chip in the first direction and a second portion that does not overlap the image sensor chip in the first direction; an adhesive layer disposed between the mold layer and the second portion of the transparent substrate; and a housing on the first semiconductor chip and surrounding the image sensor chip, the mold layer, the adhesive layer and the transparent substrate, wherein the

side walls of the image sensor chip overlap the mold layer in a second direction intersecting the first direction, and the fourth face of the mold layer does not overlap the image sensor chip in the first direction.

12. The image sensor package of claim 11, wherein the housing includes a plurality of lenses.

13. The image sensor package of claim 11, wherein the first semiconductor chip is a PCB substrate.

14. The image sensor package of claim 11, further comprising: a logic chip disposed between the first semiconductor chip and the image sensor chip.

15. The image sensor package of claim 11, wherein the image sensor chip includes: a first substrate layer including a through electrode; and a second substrate layer disposed on the first substrate layer and including a photoelectric conversion layer, wherein the through electrode penetrates the first substrate layer and is electrically connected to the photoelectric conversion layer.

16. The image sensor package of claim 13, further comprising: a solder resist layer between the first semiconductor chip and the image sensor chip, and wraps around a redistribution layer and a connection pad, wherein the redistribution layer and the connection pad are electrically connected to the through electrode.

17. The image sensor package of claim 14, further comprising: a solder bump between the first semiconductor chip and the solder resist layer and electrically connecting the first semiconductor chip and the image sensor chip.

18. The image sensor package of claim 14, wherein at least a part of the solder resist layer overlaps the mold layer in the first direction.

19. The image sensor package of claim 11, wherein the transparent substrate includes a fifth face facing the second face of the image sensor chip and a sixth face that is opposite to the fifth face, and the image sensor package further comprises a cavity defined by the fifth face of the transparent substrate, the second face of the image sensor chip, the inner wall of the mold layer, and the inner wall of the adhesive layer.

20. The image sensor package of claim 11, wherein the second face of the image sensor chip is lower than the fourth face of the mold layer.
