

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250270048
Kind Code	A1
Publication Date	August 28, 2025
Inventor(s)	LEE; Haesoo

AUTOMATIC LOGISTICS SORTING APPARATUS INCLUDING LNB SORTERS

Abstract

The present invention provides an automatic logistics sorting apparatus including LNB sorters. The automatic logistics sorting apparatus includes: a transfer conveyor configured such that a plurality of LNB sorters spaced apart from each other by a predetermined distance are installed in the form of an endless track in order to transfer the products in one direction; LNB sorters configured to sort and discharge the products in a direction orthogonal to the moving direction of the transfer conveyor; a wireless communicator installed in each of the LNB sorters in order to enable wireless communication with a server so that the products can be sorted in a direction orthogonal to the transfer conveyor; and a power connection unit installed to supply power to the wireless communicator and the roller motor that are installed on the LNB sorter.

Inventors:	LEE; Haesoo (Seoul, KR)
Applicant:	HOGUNL&S Co., Ltd. (Hwaseong-si, KR)
Family ID:	1000008480489
Appl. No.:	19/055392
Filed:	February 17, 2025

Foreign Application Priority Data

KR	10-2024-0027428	Feb. 26, 2024
----	-----------------	---------------

Publication Classification

Int. Cl.: B65G17/00 (20060101); B07C3/08 (20060101); B65G47/50 (20060101)

U.S. Cl.:

CPC B65G17/005 (20130101); B07C3/08 (20130101); B65G47/503 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of Korean Patent Application No. 10-2024-0027428 filed on Feb. 26, 2024, which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

[0002] The present invention relates to automatic logistics sorting apparatus including linear narrow belt (LNB) sorters, and more specifically, to automatic logistics sorting apparatus including LNB in sorters, which a conveyor configured to transfer products is formed of sorters having a narrow width and products are sorted by the LNB sorters that are self-driven while transferring the products in a desired direction.

2. Description of the Related Art

[0003] The term “logistics” is another term for physical distribution, and is a general term for the functions or activities that effectively move products and goods from producers to consumers. In other words, logistics refers to various activities such as packaging, unloading, transportation, storage, and information.

[0004] Usually, transporting products and goods involves several processes such as packaging, storage, collection/loading, transportation, unloading/delivery, and storage. Regardless of the means of transportation used, the movement of products and goods is impossible without going through these processes. The overall procedure of this movement is physical distribution (logistics).

[0005] In recent years, mass production, mass sales, and mass consumption have become the trends of the times and the need to streamline the flow of materials between them has grown, so that the importance of logistics is gradually increasing.

[0006] A logistics warehouse is a storage warehouse for the temporary or long-term storage of all products used in daily life such as various types of foodstuffs, beverages, clothing, home appliances, miscellaneous products, and industrial products, which are mass-produced at factories or production sites.

[0007] Due to the rapid development of the logistics industry, these logistics warehouses are designed and constructed to go beyond simple logistics management and to create new businesses such as inventory management as well as efficient inventory placement and efficient receipt and delivery.

[0008] Since the rapid receipt and delivery of cargo is essential for such logistics warehouses, most of the logistics warehouses are equipped with mechanized or automated cargo loading and unloading means. Representative examples of the mechanized or automated cargo loading and unloading means include automated equipment such as stacker cranes, shuttles, and lifts.

[0009] In addition, there are also used sorter systems capable of automatically sorting various types of cargoes according to specific sorting criteria set by users.

[0010] The sorters have the transfer speed, width of the transfer conveyor belt, and transfer method that vary according to the volume of the cargo being transferred in order to optimize the transfer function. Accordingly, when cargo is received in individual sorters, the cargo is sorted by volume to be suitable for each sorter and then received.

[0011] However, the conventional previous volume sorting work for sorting cargo by sorter is done by manpower. Accordingly, there arise problems in that reliability is low due to the limitations of manual work and uniform sorting is difficult due to different criteria of individual workers.

[0012] There are further problems in that the work speed is slow, the amount of cargo received by each sorter varies depending on the skill level of the worker, and there is a concern that industrial accidents may occur for workers due to long-term repeated work.

[0013] Meanwhile, the applicant of the present application disclosed an “Automatic Logistics Sorting Apparatus” as described in Korean Patent No. 10-2607958. The “Automatic Logistics Sorting Apparatus” sorts products through the rotation of bevel gears installed on a cross-transfer conveyor while moving the cross-transfer conveyor by a sprocket driven by a motor.

[0014] The automatic logistics sorting apparatus including a bevel gear structure generates noise as it drives the bevel gears together with the conveyor, which causes the problem of not creating a pleasant working environment.

[0015] In addition, the automatic logistics sorting apparatus is formed of a chain and sprocket structure, so that there is the inconvenience of having to adjust the tension of a chain during use and also there is a problem in that the work time increases due to the tension adjustment.

Related Art Literature

[0016] Patent Document 1: Korean Patent No. 10-2607958 [0017] Patent Document 2: Korean Patent No. 10-2170705 [0018] Patent Document 3: Korean Patent No. 10-1832142

SUMMARY

[0019] The present invention has been conceived to overcome the above-described problems, and an object of the present is to provide an automatic logistics sorting invention apparatus including LNB sorters, in which a transfer conveyer configured to transfer products is formed of a plurality of LNB sorters and the transfer conveyor may be rotated in the form of an endless track by electromagnets installed in the respective sorters.

[0020] Another object of the present invention is to provide an automatic logistics sorting apparatus including LNB sorters, in which wireless communicators configured to enable the wirelessly communication of the LNB sorters with a server are installed and the operations of the sorters may be controlled by means of wireless communication.

[0021] Still another object of the present invention is to provide an automatic logistics sorting apparatus including LNB sorters, in which the noise generated from the automatic logistics sorting apparatus and the LNB sorters may be reduced by driving a transfer conveyor by electromagnets installed in the LNB sorters and electromagnets installed in the transfer conveyor.

[0022] In order to accomplish the above objects, the present invention provides an automatic logistics sorting apparatus sorters, the automatic logistics sorting including LNB apparatus sorting a plurality of products while transferring the plurality of products, the automatic logistics sorting apparatus including: a transfer conveyor configured such that a plurality of LNB sorters spaced apart from each other by a predetermined distance are installed in the form of an endless track in order to transfer the products in one direction; LNB sorters configured to sort and discharge the products in a direction orthogonal to the moving direction of the transfer conveyor; a wireless communicator installed in each of the LNB sorters in order to enable wireless communication with a server so that the products can be sorted in a direction orthogonal to the transfer conveyor; and a power connection unit installed to supply power to the wireless communicator and the roller motor that are installed on the LNB sorter; wherein, when the LNB sorters reach a sorting location for the products, the products are sorted by driving the LNB sorters in response to signals received from the wireless communicators.

[0023] The transfer conveyor may include a power supply rail installed in an endless track form on horizontal frames in order to supply power to the LNB sorters, and transfer electromagnets installed on the horizontal frames at regular intervals so that the LNB sorters can move.

[0024] Serial numbers may be assigned to the LNB sorters, respectively, the transfer conveyor may

be equipped with a sorter number recognizer configured to recognize the starting number of the serial numbers assigned to the respective LNB sorters, and the transfer conveyor may further be equipped with a sorter counter configured to count the number of LNB sorters that has passed therethrough.

[0025] Each of the LNB sorters may include: a pair of side plates formed on both sides of a horizontal plate, respectively, in the lengthwise direction; roller motor covers installed on the pair of side plates, respectively, so that a roller motor can be installed on one side of the side plates; driven roller covers installed on the pair of side plates, respectively, so that a driven roller can be installed on an opposite side of the side plates; the roller motor installed between the roller motor covers; the driven roller installed between the driven roller covers; a belt rotatably installed around the roller motor and the driven roller in the form of an endless track; a cover body installed on the side plates; a wireless communicator installed on the top surface of the cover body to enable wireless communication with the server; and a power connection unit installed to come into contact with a power supply rail installed on the transfer conveyor so that it can supply power to the roller motor and the wireless communicator.

[0026] The power connection unit may include: a plurality of fixed brackets installed on the cover body; fixed links installed on first sides of the fixed brackets; a pair of connection links rotatably coupled to each of the fixed links; a spring installed between the pair of connection links spaced apart from each other so that the connection links are flexibly installed; a movable link coupled to the connection links; and power connection terminals installed to be movable by the LNB sorter while in contact with the power supply rail.

[0027] As described above, in the automatic logistics sorting apparatus including LNB sorters according to the present invention, effects are achieved in that the LNB sorters may be controlled by the wireless communicators configured to enable wireless communication with the server, the logistics sorting apparatus may be constructed in a simpler form by controlling the LNB sorters through wireless communication, and the overall structure of the automatic logistics sorting apparatus may be constructed in a simpler form.

[0028] In addition, in the automatic logistics sorting apparatus including LNB sorters according to the present invention, effects are achieved in that noise is not generated by moving the LNB sorters via the electromagnets compared to a chain or sprocket structure, a working environment for logistics transfer may be kept quieter and more comfortable, the inconvenience caused by adjusting the tension of a chain may be eliminated and also a long work time caused by the adjustment of tension may be reduced, and the automatic logistics sorting apparatus may be continuously used without worrying about breakdowns.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] The above and other objects, features, and advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0030] FIG. 1 is a front view showing an automatic logistics sorting apparatus including LNB sorters according to an embodiment of the present invention;

[0031] FIG. 2 is a plan view showing the automatic logistics sorting apparatus including LNB sorters according to the present embodiment;

[0032] FIG. 3 is a side view showing the automatic logistics sorting apparatus including LNB sorters according to the present embodiment;

[0033] FIG. 4 is a three-dimensional view showing an LNB sorter according to one embodiment of the present invention;

[0034] FIG. 5 is a three-dimensional exploded view showing the LNB sorter according to the present embodiment;

[0035] FIG. 6 is a three-dimensional bottom view showing the LNB sorter according to the present embodiment;

[0036] FIG. 7 is an exploded three-dimensional view showing the LNB sorter according to the present embodiment.

[0037] FIG. 8 is a three-dimensional view showing a power connection unit installed in an LNB sorter according to one embodiment of the present invention;

[0038] FIG. 9 is a three-dimensional exploded view showing the power connection unit installed in the LNB sorter according to the present embodiment; and

[0039] FIG. 10 is a three-dimensional partial view showing the power connection unit installed in the LNB sorter according to the present embodiment.

DETAILED DESCRIPTION

[0040] Embodiments of the present invention will be described in detail below with reference to the accompanying drawings so that those of ordinary skill in the art to which the present invention pertains can easily implement the present invention.

[0041] However, the description of the present invention is only an example for structural and functional illustration, and thus, the scope of the present invention should not be construed as being limited to the embodiments described in the detailed description.

[0042] For example, the embodiments may be modified in various manner and take various forms, and thus, the scope of the present invention should be understood to include equivalents that can realize the technical spirit of the present invention.

[0043] In addition, the objects or effects presented in the present specification do not require that a specific embodiment must include all of them or include only them, so that the scope of the present invention should not be understood as being limited thereto.

[0044] In the present specification, the embodiments are provided to make the disclosure of the present invention complete and to fully inform the scope of the invention to those of ordinary skill in the art to which the present invention pertains. Furthermore, the present invention is defined only by the scope of the claims.

[0045] Accordingly, in some embodiments, well-known components, well-known operations, and well-known techniques are not specifically described in order to avoid ambiguity in the interpretation of the present invention.

[0046] Meanwhile, the meanings of the terms described in the present specifications are not limited to the dictionary meanings and should be understood as follows:

[0047] All the terms used herein, unless otherwise defined, have the same meanings as commonly understood by those of ordinary skill in the art to which the present invention pertains.

[0048] The terms defined in commonly used dictionaries should be interpreted as being consistent with meanings in the context of the relevant technology, and cannot be interpreted as having ideal or excessively formal meanings unless explicitly defined in the present specification.

[0049] An automatic logistics sorting apparatus including LNB sorters according to one embodiment of the present invention will be described in detail below with reference to the accompanying drawings.

[0050] According to one embodiment of the present invention, there is provided an automatic logistics sorting apparatus including LNB sorters, the automatic logistics sorting apparatus sorting a plurality of products while transferring the plurality of products, the automatic logistics sorting apparatus including: a transfer conveyor **110** configured such that a plurality of LNB sorters **130** spaced apart from each other by a predetermined distance are installed in the form of an endless track in order to transfer the products in one direction; LNB sorters **130** configured to sort and discharge the products in a direction orthogonal to the moving direction of the transfer conveyor **110**; a wireless communicator **150** installed in each of the LNB sorters **130** in order to enable

wireless communication with a server so that the products can be sorted in a direction orthogonal to the transfer conveyor **110**; and a power connection unit **160** installed to supply power to the wireless communicator **150** and the roller motor **137** that are installed on the LNB sorter **130**; wherein, when the LNB sorters **130** reach a sorting location for the products, the products are sorted by driving the LNB sorters **130** in response to signals received from the wireless communicators **150**.

[0051] FIG. **1** is a front view showing an automatic logistics sorting apparatus including LNB sorters according to an embodiment of the present invention, FIG. **2** is a plan view showing the automatic logistics sorting apparatus including LNB sorters according to the present embodiment, and FIG. **3** is a side view showing the automatic logistics sorting apparatus including LNB sorters according to the present embodiment.

[0052] As shown in FIGS. **1** to **3**, the transfer conveyor **110** of the automatic logistics sorting apparatus according to the embodiment of the present invention is configured such that a plurality of liner narrow belt (LNB) sorters **130** spaced at regular intervals are installed along an endless track to be rotatable.

[0053] In the above transfer conveyor **110**, vertical frames **111** are installed on left and right sides, respectively, horizontal frames **112** are installed on the upper and lower sides of the vertical frame **111**, respectively, and covers **113** are installed on both sides, respectively.

[0054] The transfer conveyor **110** includes a power supply rail **114** installed on the horizontal frames **112** in the form of an endless track so that power can be supplied to the LNB sorters **130** and transfer electromagnets **115** installed on the horizontal frames **112** at regular intervals so that the LNB sorters **130** can be moved.

[0055] In the transport conveyor **110**, the power supply rail **114** forming an endless track is installed such that power can be supplied to the LNB sorters **130**, and the transfer electromagnets **115** are installed on the horizontal frames **112** so that the LNB sorters **130** can be moved.

[0056] The transfer electromagnets **115** are installed at regular distance along the endless track.

[0057] N poles and S poles are formed in the transfer electromagnets **115** by applied power. When the N poles are formed as those of sorter electromagnets **144** installed in the LNB sorters **130**, the LNB sorters **130** are moved by the repulsive force attributable to the same polarity formed in the sorter electromagnets **144** and the transfer electromagnets **115**.

[0058] In addition, the transfer conveyor **110** is equipped with a sorter number recognizer **116** configured to recognize the first one of the LNB sorters **130** that are assigned respective serial numbers, and a sorter counter **117** configured to count the number of LNB sorters **130** that pass therethrough.

[0059] That is, the above-described transfer conveyor **110** is equipped with a first LNB sorter **130** indicative of a starting location among the number of LNB sorters **130** that move along an endless track, and the sorter number recognizer **116** configured to recognize the starting location of approximately 100 or more LNB sorters **130** in order to transfer products.

[0060] The sorter number recognizer **116** recognizes the first LNB sorter **130**.

[0061] This is intended to enable the sorting of items, placed on the plurality of LNB sorters **130**, to designated locations.

[0062] In addition, the sorter counter **117** configured to measure the number of LNB sorters **130** passing therethrough is installed on the transfer conveyor **110**. The sorter counter **117** recognizes how many LNB sorters **130** have passed therethrough.

[0063] That is, the transfer conveyor **110** sorts and discharges products at designated locations during the transfer of the products. The transfer conveyor **110** enables the moving location of the LNB sorter **130** having passed through the sorter number recognizer **116** to be identified, so that products can be sorted at the designated locations.

[0064] FIG. **4** is a three-dimensional view showing an LNB sorter according to one embodiment of the present invention, FIG. **5** is a three-dimensional exploded view showing the LNB sorter

according to the present embodiment, FIG. 6 is a three-dimensional bottom view showing the LNB sorter according to the present embodiment, and FIG. 7 is a three-dimensional exploded view showing the LNB sorter according to the present embodiment.

[0065] As shown in FIG. 4 and FIG. 7, the LNB sorters **130** constituting the transfer conveyor **110** are each formed in a narrow shape. This is intended to enable the transfer of products regardless of their size, and may allow products to be classified while allowing products with a small size (or width) to be transferred by one LNB sorter **130** and also allowing products with a large size (or width) to be transferred by two or more sorters **130**.

[0066] Each of the LNB sorters **130** may include: a pair of side plates **132** formed on both sides of a horizontal plate **131**, respectively, in the lengthwise direction; roller motor covers **135** installed on the pair of side plates **132**, respectively, so that a roller motor **137** can be installed on one side of the side plates **132**; driven roller covers **136** installed on the pair of side plates **132**, respectively, so that a driven roller **138** can be installed on the opposite side of the side plates **132**; the roller motor **137** installed between the roller motor covers **135**; the driven roller **138** installed between the driven roller covers **136**; a belt **139** rotatably installed around the roller motor **137** and the driven roller **138** in the form of an endless track; a cover body **141** installed on the side plates **132**; a wireless communicator **150** installed on the top surface of the cover body **141** to enable wireless communication with the server; and a power connection unit **160** installed to come into contact with a power supply rail **114** installed on the transfer conveyor **110** so that it can supply power to the roller motor **137** and the wireless communicator **150**.

[0067] The LNB sorters **130** are configured to transfer products and classify and discharge the products to desired locations while moving along an endless track, and are formed to have the same width as the transfer conveyor **110**.

[0068] In the LNB sorter **130**, the horizontal plate **131** is integrated with the side plates **132** on both sides of the horizontal plate **131** in the lengthwise direction.

[0069] In addition, fastening holes **133** are formed on both sides of the side plates **132** so that the covers **135** and **136** can be installed on the side plates **132**.

[0070] The pair of roller motor covers **135** are installed on one side of the LNB sorter **130** so that the roller motor **137** can be installed therebetween, and the pair of driven roller covers **136** are installed on the other side, so that a driven roller **138** can be installed.

[0071] The roller motor **137** is rotatably installed between the pair of roller motor covers **135**, and the driven roller **138** is rotatably installed between the pair of driven roller covers **136**.

[0072] A motor (not shown) is embedded inside the roller motor **137**, and a roller is driven by power supplied to the embedded motor. A conventional motor is used as the roller motor **137** (also called a “roller conveyor electric motor”), and a detailed description thereof will be omitted.

[0073] The belt **139** capable of moving products is rotatably installed on the outer surfaces of the roller motor **137** and the driven roller **138** in the form of an endless track.

[0074] In addition, connection brackets **140** configured to connect adjacent LNB sorters **130** so that they can move continuously along an endless track are provided on both sides of the LNB sorter **130**.

[0075] It is obvious that a plurality of idle rollers (not shown) may be rotatably installed on the connection brackets **140**.

[0076] The cover body **141** is installed on the tops of the side plates **132** (see FIGS. 6 and 7), and a serial number plate **142** is installed on one side of the cover body **141** so that a serial number attached to the LNB sorter **130** can be recognized.

[0077] The serial number plate **142a** shown in FIG. 6 is installed on the first one **130** of the plurality of sorters **130**, and the serial number plate **142b** shown in FIG. 7 is installed in the same manner on each of all LNB sorters **130** except for the first LNB sorter **130**.

[0078] That is, the serial number plate **142a** installed on the first LNB sorter **130** is composed of two plates, and each of the remaining serial number plates **142b** is composed of a single plate.

[0079] This is intended not only to make the recognition of the first sorter **130** easier, but also to facilitate the initialization work according to the transfer of products, that is, to facilitate initialization by matching the first LNB sorter **130** with the sorter number recognizer **116**.

[0080] In addition, that enables the transfer conveyor **110** to be more easily initialized or reset during the transfer and sorting of products.

[0081] In addition, the power supply unit **143** capable of supplying power to the roller motor **137** and the wireless communicator **150** is installed on the cover body **141**, and the sorter electromagnet **144** corresponding to the transfer electromagnet **115** that is not a chain or sprocket structure is installed on the LNB sorter **130**.

[0082] N or S poles are formed in such the sorter electromagnets **144** by applied power, and the transfer conveyor **110** is moved by the repulsive force attributable to the polarity that is the same as that of the transfer electromagnets **115**.

[0083] In addition, a roller motor controller **145** configured to control the operation of the roller motor **137** is installed on the cover body **141**, and the roller motor controller **145** controls the operation of the roller motor **137** according to control signals received from the wireless communicator **150**.

[0084] When the LNB sorter **130** reaches a sorting (discharging) location for products, the roller motor controller **145** rotates the belt **139** by the rotation of the roller motor **137** and the driven roller **138** by applying power to the roller motor **137**.

[0085] In this case, the belt **139** may move and discharge products in the desired direction of the LNB sorter **130** by the forward and reverse rotation of the roller motor **137**.

[0086] In addition, a heat sink **146** configured to release heat generated from the power supply unit **143** and the like is installed on the cover body **141**, and prevents an erroneous function attributable to heat generation by cooling the heat generated from the LNB sorter **130**.

[0087] The wireless communicator **150** configured to perform wireless communication with a server (not shown) is installed on the cover body **141**. This wireless communicator **150** may be based on a Wi-Fi or a local area network, and the wireless communicator **150** receives a control signal transmitted from the server and transmits it to the roller motor controller **145**.

[0088] Accordingly, the roller motor controller **145** drives the roller motor **137** so that a product placed on the belt **139** can be transferred to a desired location and then sorted into a desired discharge location.

[0089] The power connection unit **160** may include: a plurality of fixed brackets **161** installed on the cover body **141**; fixed links **162** installed on first sides of the fixed brackets **161**; a pair of connection links **163** rotatably coupled to each of the fixed links **162**; a spring **164** installed between the pair of connection links **163** spaced apart from each other so that the connection links **163** are flexibly installed; a movable link **165** coupled to the connection links **163**; and power connection terminals **166** installed to be movable by the LNB sorter **130** while in contact with the power supply rail **114**.

[0090] The power connection unit **160** includes the plurality of fixed brackets **161**, and the fixed links **162** are formed on the first sides of the fixed brackets **161** so that first sides of the connection links **163** can be rotatably connected to the fixed links **162**.

[0091] The above connection links **163** are formed to having a predetermined length and are provided in pairs so that they can be brought into elastic contact with the power supply rail **114** by the elasticity of the spring **164**.

[0092] The movable link **165** is coupled to the opposite sides of the connection links **163**, and the power connection terminal **166** is coupled to the movable link **165**.

[0093] The power connection terminal **166** comes into elastic contact with the power supply rail **114** formed as an endless track, is equipped with an insulator **167** to prevent electrical contact with another adjacent power connection terminal **166**, and is provided with a fixing bar **168** to couple the power connection terminal **166** to the movable link **165**.

[0094] On the horizontal frames **112** of the automatic logistics sorting apparatus including LNB sorters, the power supply rail **114** is installed in the form of an endless track, and also the transfer electromagnets **115** whose polarity is changed by an authorized power source is installed. The power connection unit **160** configured to move along the power supply rail **114** in the form of an endless track is installed in the LNB sorters **130** forming the transfer conveyor **110**.

[0095] The power connection unit **160** stably supplies power to the wireless communicator **150**, the roller motor **137**, and the like while moving in contact with the power supply rail **114** configured in the form of an endless track.

[0096] In addition, the sorter electromagnets **144** corresponding to the transfer electromagnets **115** are installed on the LNB sorters **130**, and the LNB sorters **130** are moved by the repulsive force of the electromagnets **144** formed to have the polarity that is the same as the transfer electromagnets **115**.

[0097] The roller motors **137** configured to drive the belt **139** are installed on the LNB sorters **130**, and the roller motors **137** are driven by the roller motor controllers **145**.

[0098] Meanwhile, the sorter number recognizer **116** configured to recognize the first one **130** of the LNB sorters **130** is installed on the transfer conveyor **110**, the sorter number recognizer **116** recognizes the first LNB sorter **130**, and the sorter counter **117** measures the movement distance of the first LNB sorter **130** by counts the number of movements of the first LNB sorter **130**.

[0099] The products to be sorted are placed on the LNB sorters **130**, the LNB sorters **130** are moved by the repulsive force of the electromagnets **115** and **144**, and the roller motors **137** are driven by the roller motor controllers **145** through the wireless communicators **150** installed on the LNB sorters **130**.

[0100] That is, when the LNB sorter **130** on which a product is stacked reaches the location where the product is to be sorted, the wireless communicator **150** transmits a control signal to the roller motor controller **145** in response to a control signal transmitted from the server (not shown), and the roller motor **137** is driven in response to a control signal from the roller motor controller **145**.

[0101] Therefore, the roller motors **137** of the LNB sorters **130** are driven, and the belt **139** is rotated, thereby discharging products to desired locations.

[0102] Although the present invention contrived by the present inventor has been specifically described according to the above embodiments, the present invention is not limited to the above embodiments, and it is obvious that various modifications may be made without departing from the technical spirit of the present invention.

Claims

1. An automatic logistics sorting apparatus including LNB sorters, the automatic logistics sorting apparatus sorting a plurality of products while transferring the plurality of products, the automatic logistics sorting apparatus comprising: a transfer conveyor configured such that a plurality of LNB sorters spaced apart from each other by a predetermined distance are installed in an endless track form in order to transfer the products in one direction; LNB sorters configured to sort and discharge the products in a direction orthogonal to a moving direction of the transfer conveyor; a wireless communicator installed in each of the LNB sorters in order to enable wireless communication with a server so that the products can be sorted in a direction orthogonal to the transfer conveyor; and a power connection unit installed to supply power to the wireless communicator and the roller motor that are installed on the LNB sorter; wherein the transfer conveyor comprises a power supply rail installed in an endless track form on horizontal frames in order to supply power to the LNB sorters, and transfer electromagnets installed on the horizontal frames at regular intervals so that the LNB sorters can move; wherein sorter electromagnets formed to have a predetermined length, corresponding to the transfer electromagnets formed to have a predetermined length, are installed in the LNB sorters, and the sorter electromagnets are installed in a same lengthwise direction as the

transfer electromagnets, and the LNB sorters are moved in one direction by a repulsive force attributable to an identical polarity of the transfer electromagnets and the sorter electromagnets; and wherein, when the LNB sorters reach a sorting location for the products, the products are sorted by driving the LNB sorters in response to signals received from the wireless communicators.

2. The automatic logistics sorting apparatus of claim 1, serial numbers are assigned to the LNB sorters, wherein respectively, the transfer conveyor is equipped with a sorter number recognizer configured to recognize a starting number of the serial numbers assigned to the respective LNB sorters, and the transfer conveyor is further equipped with a sorter counter configured to count a number of LNB sorters that has passed therethrough.

3. The automatic logistics sorting apparatus of claim 1, wherein each of the LNB sorters comprises: a pair of side plates formed on both sides of a horizontal plate, respectively, in a lengthwise direction; roller motor covers installed on the pair of side plates, respectively, so that a roller motor can be installed on one side of the side plates; driven roller covers installed on the pair of side plates, respectively, so that a driven roller can be installed on an opposite side of the side plates; the roller motor installed between the roller motor covers; the driven roller installed between the driven roller covers; a belt rotatably installed around the roller motor and the driven roller in an endless track form; a cover body installed on the side plates; a wireless communicator installed on a top surface of the cover body to enable wireless communication with the server; and a power connection unit installed to come into contact with a power supply rail installed on the transfer conveyor so that it can supply power to the roller motor and the wireless communicator.

4. The automatic logistics sorting apparatus of claim 1, wherein the power connection unit comprises: a plurality of fixed brackets installed on the cover body; fixed links installed on first sides of the fixed brackets; a pair of connection links rotatably coupled to each of the fixed links; a spring installed between the pair of connection links spaced apart from each other so that the connection links are flexibly installed; a movable link coupled to the connection links; and power connection terminals installed to be movable by the LNB sorter while in contact with the power supply rail.
