

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250274472

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

BOLTURK; Eda et al.

Systems and Methods for Use in Assessments in Connection with Cyber Attacks

Abstract

Systems and methods are provided for assessing cyber attack preparedness associated with organizations. One example computer-implemented method includes accessing data indicative of multiple controls of an organization, where the organization includes an information network, which includes the controls and where the controls are associated with securing one or more information assets. The data is indicative of the controls including multiple indicators. The method also includes aggregating one or more ratings for at least one of the indicators to a criteria, aggregating the aggregate rating for the criteria to a category, and aggregating the aggregate rating for the category to one of the controls as a control maturity score for said one of the controls. The method then includes displaying the control maturity score for said one of the controls to a first user associated with the organization.

Inventors: BOLTURK; Eda (Istanbul, TR), YNIV; Eran (Holon, IL), GABBER; Keren (Tel Aviv, IL)

Applicant: MASTERCARD INTERNATIONAL INCORPORATED (PURCHASE, NY)

Family ID: 1000008473985

Appl. No.: 18/586964

Filed: February 26, 2024

Publication Classification

Int. Cl.: H04L9/40 (20220101); G06Q10/0635 (20230101)

U.S. Cl.:

CPC H04L63/1433 (20130101); G06Q10/0635 (20130101);

Background/Summary

FIELD

[0001] The present disclosure generally relates to systems and methods for effecting assessments in connection with attack preparedness (e.g., for preparedness against cyber attacks, etc.).

BACKGROUND

[0002] This section provides background information related to the present disclosure, which is not necessarily prior art.

[0003] Networks are known to be accessed for a variety of different reasons. Often, access to the networks is consistent with the purposes of the networks, for example, to access services, to retrieve information, to post information, etc. Occasionally, attempts to access the networks are consistent with nefarious purposes, such as, for example, cyber attacks. Cyber attacks may include unauthorized attempts to access computers, etc. Example cyber attacks include malware attacks, phishing attacks, password attacks, man-in-the-middle attacks, etc. Networks often include various hardware and software components, which aim to eliminate, or at least limit, these cyber attacks and the potential for success of such cyber attacks.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0004] The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations and are not intended to limit the scope of the present disclosure.

[0005] FIG. 1 is a block diagram of an example system of the present disclosure suitable for use in assessing cyber attack preparedness associated with organizations;

[0006] FIG. 2 illustrates an example interface, which may be displayed in the system of FIG. 1;

[0007] FIG. 3 is a block diagram of an example computing device, that may be used in the system of FIG. 1;

[0008] FIG. 4 is an example method for assessing cyber attack preparedness associated with organizations, which may be implemented in the system of FIG. 1; and

[0009] FIG. 5 illustrates an example identification of a financial impact defined by a curve indicative of a relationship between the financial impact and risk associated with asset(s).

[0010] Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

[0011] The description and specific examples included herein are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

[0012] Systems provided by organizations are often protected from cyber attacks through various forms of hardware and software, i.e., referred to herein as controls, which are designed to prevent the attacks, limit the impact of the attacks, or prevent one or more aims of the attacks (e.g., to disrupt, destroy or control computer systems or to alter, delete, manipulate or steal data, etc.). Often, decision-makers associated with the various forms of controls weigh cost of implementation against not only efficacy of the controls, but also the potential risk associated with the cyber attacks. Unfortunately, especially for larger organizations, sizes of the systems in terms of number of users, applications, services, locations, cloud services, third-party vendors, and hybrid environments, etc., make it difficult (if not impossible) to provide accurate assessments of not only the preparedness of the networks with respect to, but also potential financial impact of, cyber attacks. That is, organizations need to understand their cyber preparedness postures and potential

impact (e.g., based on confidentiality, integrity, availability of impact to assets, etc.) caused by possible cyber attacks, or cyber events. In addition, decision makers want to understand the potential financial loss in dollar (or other suitable currencies) amounts of such cyber attacks.

[0013] Beyond the above, it is difficult to catch bad actors in the fast-changing conditions, i.e., in the ever-changing environment, that is the cyber security. Not only is the technology changing, in the organizations' networks, but also cyber attack actors continuously evolve raising new risks and vulnerabilities. As such, an up-to-date algorithm with correct coefficients and real time data is needed to accurately assess the real cyber posture or cyber risk of organizations.

[0014] Uniquely, the systems and methods herein provide for modeling preparedness (e.g., of organizations, etc.) for cyber attacks, and potentially, the financial losses associated with the cyber attacks. The modeling relies on identifying a threat landscape, cyber maturity status, and information assets.

[0015] FIG. 1 illustrates an example system **100**, in which one or more aspects of the present disclosure may be implemented. Although the system **100** is presented in one arrangement, other embodiments may include systems arranged otherwise within the scope of the present disclosure.

[0016] The system **100** includes an organization **102**, which is configured to perform one or more services for users or customers of the organization **102**. The organization **102** illustrated in FIG. 1 may refer to any organization, such as, for example, a corporation, a government, a non-governmental organization, an international organization, a charity, a not-for-profit, a partnership, a cooperative, a university, or a combination of the same (e.g., private, public, government, etc.). The service(s) of the organization **102** may be technology-based, or otherwise, but the organization **102** does include an information technology (IT) ecosystem, which supports the offering of the service(s). In connection therewith, for purposes of illustration, the organization **102** includes a network infrastructure **103** and various assets **104a-d** (generally referred to herein as assets **104**) and technologies **106a-b** (generally referred to herein as technologies **106**).

[0017] In this example embodiment, the assets **104** generally include business assets, or information assets, or also physical assets, etc. The assets **104** are of various types, such as, for example, organization confidential business information; customer financial information; brand reputation and trust; intellectual property (IP); customer personal identifying information (PII); supply-chain information; agreements and contracts; personnel information; customer-facing services; core business systems/processes; customer protected health information (PHI); physical equipment; and organization confidential financial information.

[0018] While only four assets **104** are illustrated in FIG. 1, it should be appreciated that any suitable number of assets, consistent with the description herein, may be part of the organization **102** in other embodiments. Also, it should be appreciated that other types of information assets, or other assets may be included in the organization **102** in other system embodiments.

[0019] That said, as it relates to the specific assets **104** above, the organization confidential business information refers to information and data whose disclosure may harm the business, including, for example, business plans, secret information on mergers and acquisitions, new product plans, etc. Customer financial information refers to monetary assets held in cash or a form suitable to be liquidated, such as, for example, stocks and savings accounts, bank accounts and credit card information. Brand reputation and trust refers to the organization **102** being reliable, credible, trustworthy and responsible for employees, customers, shareholders and financial markets. Intellectual property is a category of property that includes intangible creations of the human intellect, and primarily encompasses copyrights, patents, trademarks, trade secrets, and product designs.

[0020] Customer PII includes any information or set of information relating to a person that identifies such person or could be used to identify such person, including without limitation, a person's name, address, ID number, telephone number, email address or call data records, user-ids and passwords. Supply-chain information includes information related to suppliers, contractors, or

vendors, which is confidentially maintained by the organization **102**. Agreements and contracts include documentation of relationships between the organization **102** and any other organization/individual stipulating expectations and covenants between the two or more parties. The agreements may include service agreements, service definitions, contracts, SCRs, NDAs, etc. [0021] The personnel information includes information about employees that is to be maintained confidential between the employees and the organization **102**, as the employer. The specific information may include, without limitation, CVs, salary letters, references, personal sensitive information, disciplinary information, pension information, starter-mover-joiner processes, etc. Customer-facing services include the services provided to clients by the organization **102**. The services generally are tied to the generation of revenue, or generating of value to the organization **102**, when operational, or services which the organization **102** is obliged to provide to its client by law. The services may include, without limitation, online payments, online purchases, government services, support services, etc.

[0022] Core business systems may include software programs or suites of related programs, which are “mission critical” to the organization **102**, so that the organization **102** functions continuously in order for a business or segment of a business to be successful. If the program(s) experiences even brief downtime, the negative consequences to the organization **102** are likely to be financial. In addition to lost productivity, failure of this type of program to function may also damage the business' reputation. Example programs may include, without limitation, customer-relationship management (CRM), enterprise resource planning (ERP), payment systems, etc.

[0023] Customer protected health information includes any information about health status, provision of health care, or payment for health care that is created or collected by a covered entity or business associate of the covered entity, and can be linked to a specific individual. Physical equipment includes hardware and physical equipment belonging to the organization **102** or its employees or used as part of the organization's business processes. The equipment may include, without limitation, laptops, devices, ATM machines, USB drives, etc. Organizational confidential financial information refers to digitized information about or related to the organization **102** that can be considered as the equivalent to money. This information can be resident on storage devices or in transmission over electronic channels, and may include, specifically, wired money transfers, credit card transactions, etc. Organization public information includes information about the organization **102** that is publicly available.

[0024] In addition to the assets **104**, the technologies **106** of the organization **102** may include, without limitation, application development; data processing and storage; network, servers and systems; web services; employee internet access; control systems; mobile devices; workstations; and email services. The technologies **106**, generally, are configured to provide an approach or access to the specific assets **104** of the organization. The technologies **106** may be an approach to one asset, or multiple assets, as shown in FIG. 1. Further, the technologies **106** are associated with priorities of the organization **102**, where the access to such technologies **106** is prioritized, for example, based on customer demand, importance of the technology/assets, etc. The priority of the technologies **106** may be defined, for example, by an information technology (IT) manager **116** (broadly, a user), alone or with consultation with or direction from one or more others in the organization **102**. In addition to priority, the technologies **106** are also each associated with an access level, which indicates a level of exposure of the technologies **106**, and then also, in turn, the assets **104** approached through the technologies **106**. Generally, the higher the access level, the higher the risk. Further, it should also be appreciated that while only two technologies **106** are illustrated in FIG. 1 (e.g., technology **106a**, technology **106b**, etc.), any suitable number of technologies, consistent with the description herein, may be part of the organization **102** in other embodiments.

[0025] Also, it should be appreciated that other types of technologies **106** may be included in the organization **102** in other system embodiments.

[0026] That said, as it relates to the above, the application development includes technologies **106** that contain internally developed applications/websites or custom applications/websites purchased by the organization **102**. Data processing and storage includes technologies **106** that store and/or process sensitive data such as PII, PHI, IP, etc. Networks include network infrastructure **103** (e.g., routers, switches, cloud-based or similar, etc.). Servers and systems include the organization's server infrastructure, which includes, potentially, both physical and virtual resources, including a complete set of hardware and software. Web services include technologies **106** that are exposed to the Internet, providing online services (e.g., marketing or an e-commerce website, online government services, etc.). Employee Internet access includes technologies **106** that provide employees internet access. Industrial control systems include technologies that may include lines, climate control systems (HVAC), Uninterrupted Power Supply (UPS) systems/emergency power backup generators, fire extinguisher systems, etc. Mobile devices include technologies **106** that provide mobile connectivity for mobile devices, such as, laptops, smartphones, tablets, etc., while workstations include technologies **106** that are dedicated terminals or workstations for employee productivity (e.g., as related to email, enterprise applications, offices, etc.), etc. And, finally, email services include technologies **106** that provide e-mail services to employees of the organization **102**.

[0027] As shown in FIG. 1, the assets **104** and technologies **106** are organized into environments **108**, where the environments **108** may be specific to services or functions of the organization **102**. In this embodiment, the assets **104** and technologies **106** are organized into two environments, **108a-b**. As should be appreciated from FIG. 1, the environments **108** may include the same or different assets **104** and/or technologies **106**. For example, as shown, the environment **108a** includes assets **104a-b** and technology **106b**, while the environment **108b** includes assets **104b-d** and technology **106a**. While the assets **104** and technologies **106** are separate and not shared between environments **108**, it should be appreciated that the assets **104** and/or technologies **106** may be shared between environments in other embodiments. What's more, it should also be appreciated that the assets **104** and technologies **106** included in the organization **102** may be organized into different environments **108** in still other embodiments.

[0028] The specific assets **104** and technologies **106** included in the environment **108** often depend on the specific type and/or function of the environment **108**. Example environments **108** may include, business units (e.g., marketing, human resources, sales, etc.), order fulfillment, customer billing, and credit card processing, etc. It should be appreciated that the order fulfillment may utilize various assets **104** (e.g., customer PII, customer-facing services, supply chain information, agreements, etc.), while customer billing may rely on some of the same assets **104**, but also different assets **104** (e.g., customer financial information, etc.).

[0029] Further, it should be understood that the specific environment(s) **108** included in the organization **102** are generally specific to the one or more services offered by the organization **102** to its customers, etc.

[0030] With continued reference to FIG. 1, the organization **102** further includes controls **110**, which are imposed on the assets **104**. It should be appreciated that the organization **102** includes an information network, which includes both hardware and software, in which the assets **104** and technologies **106** are implemented. That is, for example, Customer PII may be stored in a server located at a facility of the organization, where the server is part of the information network. Likewise, network infrastructure **103** is included as part of the information network, where not only the routers and switches reside, but also the specific anti-virus and anti-malware tools are employed. The information network may be understood to include the hardware and/or software hosting, supporting, and/or underlying, etc., the technologies **106**, as approaches to the assets **104**.

[0031] The information network then includes the controls **110**, which may include policies, systems/hardware, software, configurations, training, and analysis of the organization's network, etc. Policies, for example, may include a removable media policy (e.g., removable media barred,

etc.), software updates, email policies, patch management, password rules, asset management (e.g., remote wipe, etc.), encryption requirements, etc., which may be imposed through human action and/or automatically, via the assets **104**. Systems may include, without limitation, network intrusion detection and/or prevention systems, etc. Software may include, without limitation, asset management software, password management, anomaly detection, etc. Configurations may include, without limitation, application controls/whitelisting/blacklisting, email security settings, accessibility (e.g., eliminating access to specific webpages, etc.), user asset security, authentication, encryption, etc. Training may include, without limitation, training related to phishing, password sharing, email assessment (e.g., links, checking sender email addresses, etc.), physical asset security, dual authentication, threat awareness, policies, etc. And, further, analysis of the organization's network may include, without limitation, brand reputation and protection, network traffic anomaly detection, threat intelligence analysis, etc.

[0032] The controls **110**, in this embodiment, are categorized as preventive, infrastructure, and detective, which may be used in one or more of the assessments described below. It should be appreciated that other categories of controls may be included in other embodiments.

[0033] The system **100** also includes an internal data structure **112** and an external data structure **114**. The internal data structure **112** is included as part of the organization **102**, while the external data structure **114** is external or separate from the organization **102**. The data structures **112**, **114** include data specific to the assessment of the organization **102**, as further described below. Any data described with reference to the internal data structure **112** may also, or alternatively, be included in the external data structure **114**, and vice versa.

[0034] Example data included in the data structure **112** may include, without limitation, configuration files associated with the assets **104**, the technologies **106**, and/or the controls **110** (and the network infrastructure **103**) of the organization **102**, revenues of the organization **102** (e.g., annual, monthly, etc.), industries of the organization **102**, location and facility information for the organization **102**, employee information (e.g., number of employees, organization charts, work locations of employees, salary of employees, etc.), etc. Similarly, example data included in the data structure **114**, for example, includes reporting data related to cyber attacks. The reporting data may indicate, for example, cyber attack events and associated timing, targets, methodologies, actors and objectives, and also analytics related to the same. The analytics may include the frequency and/or activity level of cyber attack events, in general or by methodology, actor, etc. The reporting data may be collected and stored in the data structure **114**, for example, from monitoring thousands of clear, deep and dark web CTI sources, etc.

[0035] In addition to the above, the organization **102** also includes the IT manager **116** (broadly, user), who is employed directly or through contract with the organization **102**. In this example, the IT manager **116** is knowledgeable about the assets **104** and technologies **106** of the organization **102**, and situated to participate, as needed, in the assessment described herein, and also to review and present findings to decision makers associated with resource allocation at the organization **102** (e.g., as it relates to remedial, prevention, or IT initiatives associated with the assets **104**, the technologies **106**, or more broadly, the organization **102**; etc.).

[0036] In this example embodiment, the system **100** includes an assessment platform **118**, which is configured to assess the organization **102** as it relates to cyber attacks and to predict the financial loss associated with the cyber attack(s).

[0037] In particular, the platform **118** may be a standalone computing device, or integrated, in whole or in part, with one or more assets **104** or technologies **106** of the organization **102**. The platform **118** is configured to generate a control maturity assessment, assess the threat activity level, and determine a probability of success of attack by methodology, etc.

[0038] It should be appreciated that the platform **118** is configured to respond to one or more requests for assessment of the organization **102**, which may be submitted by a user (e.g., an IT manager, etc.) associated with the organization **102**. The user **116**, often, aims to assess the

preparedness of the organization **102** as it relates to cyber attacks, i.e., cyber risk assessment. The request may be manually provided from the user **116**, or automated at one or more regular or irregular intervals.

[0039] Initially, in response to a request, in this example embodiment, the platform **118** is configured to perform a control maturity assessment for the controls **110** of the organization **102**. In connection with the assessment, the platform **118** is configured to collect data relevant to the specific controls **110**. The data may be collected automatically (e.g., by collecting configuration files, etc.), or through the IT manager **116**. For example, the platform **118** may be configured to collect configuration files for the assets **104**, from the data structure **112**, which defines the topology, setup, etc., of the technologies **106** in place at the organization **102** and the settings thereof. The platform **118** may be configured to also capture policies, restrictions, rules, etc., and also to pursue validation of the specific policies, restrictions, rules, etc., related to the assets **104**, etc.

[0040] As it relates to the IT manager **116**, the platform **118** may be configured to submit questions to be answered. Example questions related to the assets **104** are illustrated in Table 1. The example questions are merely example in nature, and the questions posed to the IT manager **116** generally include various details about the assets **104** and technologies **106**, sufficient to assess the same.

TABLE-US-00001 TABLE 1 To what extent are the asset management policy and procedures implemented in the organization to ensure proper inventory, maintenance, and protection of assets? To what extent is employees' internet browsing secure against web-related threats? To what extent does the organization follow a change management process to prevent unintentional adverse impacts on a system as a result of a change? To what extent is data at rest encrypted to prevent unauthorized information disclosure? To what extent are the privacy protection policy, procedures, and controls implemented to ensure that personal information is collected, processed, and stored according to privacy laws and regulations? Does the organization use a centrally managed signature-based anti-malware technology to continuously monitor and defend each workstation and server? Is the signature-based anti-malware tools' rule set and policy reviewed and updated regularly to prevent new threats? Does the endpoint anti-malware prevent all known malware?

[0041] Each of the questions illustrated in Table 1 may be posed to the IT manager **116**, whereby the IT manager **116** provides a response in text, or selects from multiple answers displayed with the questions. In other examples, the IT manager **116** uploads files, etc., in response to questions from the platform **118**. More generally, it should be understood that various forms of questions and/or answers may be employed to sufficiently inform the platform **118**. It should be further appreciated that the automated collection of information related to the organization **102**, and questioning the IT manager **116**, may be combined for certain assets **104**, technologies **106** or controls **110**.

[0042] The data captured, collected and/or received includes various details about the organization **102**, the assets **104**, the technologies **106**, the controls **110**, etc. Further, it should be understood that the data captured, collected and/or received may be classified into two categories, generally, technical data from the automated collection (e.g., of configuration files, etc.) and question data from the interrogation of the IT manager **116** (e.g., from the question in TABLE 1).

[0043] In connection with the above, it should be further appreciated that assets **104** may be assigned priorities (e.g., low, medium, high, very high, etc.), where certain ones of the assets **104** may be designated as priorities over other assets **104**. The basis for the priority may be a business need, a core business function, current initiatives, etc. The priority of the assets **104** is generally indicated by the IT manager **116**, based on input from the organization **102** (e.g., employees, managers, leaders, etc.).

[0044] In this example embodiment, based on the data captured, collected and/or received, the platform **118** is configured to generate a control maturity score for each of the controls **110** implemented in the organization **102**.

[0045] In particular, the platform **118** is configured to extract indicators from the configuration files

(e.g., through an API service, etc.) (technical indicators) and/or the responses from the IT manager **116** (question indicators). The indicators are representative of the maturity of the technologies **106** and/or the assets **104**, for example, relative to one or more industry standards. In connection therewith, the standards may include, for example, NIST CSF 1.1, NIST 800:53, ISO 27002:2022, PCI-DSS 4.0, CIS Controls 7-8, HIPAA, or other suitable standards, etc.

[0046] The indicators may include a rating of the maturity of the controls **110**, for example, between 0 and 100 (or on another suitable scale). The platform **118** is configured, then, to map the indicators to the specific controls **110**. That is, the platform **118** is configured to employ a hierarchy, which is used, then, to combine the indicators, through mapping, into scores for the controls **110**. Specifically, in this exemplary embodiment, the indicators may be mapped to the controls **110**, by mapping the ratings/scores to specific criteria, which are in turn mapped to sub-categories. The sub-categories are then mapped to categories, by aggregating each of the aggregate ratings/scores of the sub-categories for each category. And after, the categories are mapped to controls, by aggregating each the aggregate scores/ratings of the categories to for each control. The controls **110** may then be separated or mapped into control types (e.g., preventives, detection, infrastructure, etc.).

[0047] It should be appreciated that mapping in this context includes the aggregation of the different levels of the hierarchy (e.g., ratings/scores of 10, 60, 50, 80 aggregated to 50, as an average, etc.). That is, when multiple criteria are mapped into a single sub-category, the ratings for the criteria are aggregated, such as, for example, by average, weighted average, sum, weighted sum, etc. Conversely, when only one criteria is mapped to a single sub-category, no aggregation is required. It should be appreciated that the aggregation is applied as criteria are mapped to sub-categories, sub-categories are mapped to categories, the categories are mapped to controls, etc. The aggregation of the rating may be the same, or different, at the different levels of the hierarchy. In this exemplary embodiment, the aggregation includes averaging the ratings at the layer below.

[0048] That said, as used herein, indicators define various different details about the operation, settings, configurations, etc., of the organization **102**, and specific controls applied thereto. The indicators may include details related to, without limitation, virus scan tool (e.g., “virus scan detects unwanted adware?” etc.), antivirus, firewalls, encryption, penetration testing, access controls, password policies, and any other details of the organization **102** that may affect, impact or relate to access to the assets **104** of the organization **102**, etc.

[0049] Based on the hierarchy, the indicators are mapped to criteria. Accordingly, to one specific example, an indicator of “antivirus can block 70% of malware” maps to the criteria of “malware prevention capabilities.” Generally, an indicator will map to at least one criteria, but may map to multiple criteria (i.e., under different sub-categories, etc.). Based on the defined hierarchy for the organization **102**, the criteria of “malware prevention capabilities” and, for example, a criteria for “end-point anti-malware detects unwanted programs” (and, potentially, other criteria) are then mapped into a sub-category for “malicious code is detected.” The sub-category for “malicious code is detected” then maps to a category of “security continuous monitoring.” This category then maps to a technical one of the controls **110** for the organization **102**.

[0050] In another specific example, the indicator of “endpoint malware prevent all known malware” maps to the criteria of the same name, which maps, along with the above criteria for “malware prevention capabilities,” to the sub-category of “network firewall-actual effectiveness indicators.” The sub-category is mapped up to a category of the same name, which is in turn mapped, along with categories for “network firewall-design effectiveness” and “network firewall-operating effectiveness” (as an average), into a “network firewall” control. The “network firewall” control is then mapped or assigned, potentially, to the prevention type of control.

[0051] In yet another specific example, as it relates to network access for the organization **102**, the exemplary control **110** includes applications secure configurations, which is related to DNS local parent mismatch as an indicator. The DNS local parent mismatch is assessed based on the criteria

of DNS configuration. That assessment is included in or mapped to the application secure operating effectiveness configurations-operating effectiveness sub-category, and the application secure operating effectiveness configurations-operating effectiveness sub-category is mapped to the application secure operating effectiveness configurations-operating effectiveness category. Then, the application secure operating effectiveness configurations-operating effectiveness category is mapped to the applications secure configurations.

[0052] Further, from the above examples, it should be clear that the hierarchy is generally based on the specifics of the organization **102**, as it relates to technical indicators and question indicators, and linking of the same through mapping to controls **110**. As such, examples of the hierarchy herein are specific to one organization **102**, and may be different in other systems embodiments. It should therefore be appreciated that various other indicators, criteria, sub-categories, categories, controls, etc., may be included in the organization **102**, or hierarchy thereof, which are assessed and mapped in a similar manner to the various controls **110** consistent with the description above.

[0053] Consistent with the above, the platform **118** is configured to then average, or otherwise aggregate, the ratings from the categories of each of the controls **110** into the maturity scores for each of the controls **110**, as shown, for example, shown in Table 2. In addition, the platform **118** is configured to then average or otherwise aggregate the scores/ratings from the controls **110** into maturity scores for each of the controls types, i.e., preventive, infrastructure, detective, in this example.

[0054] In one specific numeric example consistent with the above, a patch management control of the controls **110** is a practice associated with the timely application of firmware and software updates to improve functionality, close security vulnerabilities, and optimize performance. The patch management control is subject to technical validation by the platform **118** (i.e., technical indicators), and also questions submitted by the platform **118** to the IT manager **116** (i.e., question indicators). Based on the collected data, and the response from the IT manager **116**, for example, the network firewall-Design effectiveness sub-category score may be calculated as 58%. The network firewall-Design effectiveness sub-category is mapped from two criteria: CQ Question criterion-1 (Is there a signature-based anti-malware tool?) and CQ Question criterion-2 (Does the endpoint anti-malware prevent all known malware?) That is, for example, to calculate the network firewall-Design effectiveness sub-category, the scores of CQ Question criterion-1 (rating of 50) and CQ Question criterion-2 (rating of 66) at the criteria level of the hierarchy are aggregated with a simple average method. The maturity score of the network firewall-Design effectiveness sub-category is expressed as $(50+66)/2=58$.

[0055] Table 2 illustrates a number of different controls **110** and the types of the controls **110** into which each control is organized, the maturity control score and then also a weight associated with the particular type of control. The weights may be employed, as herein, to adjust the impact of the different groups of controls, or potentially, even in some instances, the individual types of controls on the control maturity assessment.

TABLE-US-00002

TABLE 2	Control	Control	Control	Control	Name	Group	Score	Weight
Intrusion Prevention/	Preventive	60	0.65	Detection System	Removable Media Control	Preventive	36	0.65
User Endpoint Secure	Configurations	Preventive	35	0.65	E-mail Security	Preventive	0	0.65
Data-in-Transit Encryption	Preventive	0	0.65	Application Control and Whitelisting	Infrastructure	60	0.2	
Asset Management	Infrastructure	50	0.2	Awareness and Training	Infrastructure	27	0.2	
Brand Reputation and Protection	Detective	20	0.1	Network Traffic Anomalies Detection	Detective	0	0.1	
Threat Intelligence Analysis	Detective	8	0.1					

[0056] After calculating the control maturity scores for the controls **110** and types of controls, as necessary or desired, the platform **118** is configured to assess a threat activity level, which is generally an indicator of how active different types of threat actors and/or attack methods are.

[0057] For example, certain threat actors may be prone to specific types of attack methods, while other actors may be prone to the most effective, or most recently developed attack methods, etc., as

appreciated from data included in the external data structure **114**. The data may include identification of attack methods relevant for certain assets, for example, based on profiles of attackers which may be identified as prone to be interested in the assets. Such attackers' profiles may be obtained or identified according to available global data and reports included in the external data structure **114**. Each attacker profile may describe the attacker behavior including typical attack method, objectives, skill level of the attacker, attacker intensity, common target assets, etc.

[0058] In connection therewith, the platform **118** is configured to continuously monitor various clear, deep and dark web CTI sources, which may be extracted, received or retrieved from the data structure **112**, and further to determine matches, for example, based on a single language or a multilingual dictionary, between threat actors and attack methods. The data sources may include, for example, a strategic level cyber threat trends analysis component. The matches, generally, are determined based on cyber events that include the actor and also the method, whereby each event includes one instance. In this example, the actors are generally referenced by type, while in other embodiments, the threat actors may be specific actors (e.g., an individual or a collaborative group, etc.). The platform **118** is configured to aggregate the matches, statistically, to identify threat activity level trends, propensities, etc., for each combination of threat actor and attack method and to assign a score in relation to the top activity data points from the aggregation. The threat activity level is a value between 0 and 100 and calculated as based on historical occurrences, which may be, potentially, specific to the particular industry of the organization **102**, the location(s) of the organization **102**, etc.

[0059] Example threat activity scores for specific matches between threat actors and attack methods are illustrated in Table 3, below. As shown, the combination of Blackhat hacker/fraudster as the actor and malware attack as the method includes a threat activity score of 97.

TABLE-US-00003

Attacker	Attack Method	Activity Level
Blackhat hacker/fraudster	Malware attacked	97
Blackhat hacker/fraudster	Ransomware Attack	96
Organized Cyber Criminal	Ransomware Attack	93
Organized Cyber Criminal	Malware attacked	92
Blackhat hacker/fraudster	Email social Engineering	92

[0060] Next, in this example embodiment, the platform **118** is configured to calculate probability of success (POS) scores, for the organization **102**. The probability of success scores are calculated based on a stop factor associated with the organization **102**. The initial probability of success is based on a lack of the controls **110** in the organization **102**, whereby the probability of success is determined to be 100%, i.e., a clear indicator of success without any control to defend against the cyber attack. It should be appreciated that the initial probability of success may be otherwise, where there are considerations beyond the maturity of the controls **110** in assessing the risk associated with one or more particular cyber attacks.

[0061] From there, in this example embodiment, the platform **118** is configured to calculate the stop factor associated with the organization **102** based on the preventive, detective and infrastructure groups of controls of the organization **102**, i.e., the controls **110**. The platform **118** is configured to aggregate the control scores, per group or category, from the control maturity assessment (e.g., as shown in Table 2, etc.). As such, in the example above, for the infrastructure category, the platform **118** is configured to aggregate (e.g., average, etc.), the control score for application control and whitelisting, asset management, and awareness and training (i.e., average 60, 50, and 27= $\sim$ 45). The platform **118** is configured, in this example, to aggregate the control scores for the other categories in the same manner. For example, the aggregate control score for preventive is $\sim$ 26 (i.e., average of 60, 36, 35, 0, and 0), and the aggregate control score for detective is $\sim$ 9 (i.e., average of 20, 0, and 8).

[0062] It should be appreciated that in other embodiments, the control scores may be aggregated differently, by category, or not, etc.

[0063] Next, in this example embodiment, the platform **118** is configured to combine the aggregate control scores from the different categories of controls **110**, in general or based on the weights

associated therewith, with the example above, the combined aggregate scores is ~27 (i.e., $26 \times 0.65 + 45 \times 0.2 + 9 \times 0.1 = 26.8$). The combined aggregate score for the organization **102** is the stop factor. The platform **118** is configured to then calculate the probability of success as the probability of a specific attack, which is based on the maturity analysis above and the threat landscape, less the stop factor of the controls **110** in place at the organization **102**. For example, for a malware attack having an initial 100% chance of success, the platform **118** is configured to calculate the probability of success as 100 minus 27, or 73%.

[0064] With continued reference to FIG. **1**, the platform **118** is configured to then calculate risk level (or preparedness level) of the organization **102** for each threat actor and/or each attack method considered by the threat actors, while considering malicious intent (e.g., confidentiality, availability or integrity (CIA) objectives of the actor, etc.) against the assets **104**.

[0065] In connection therewith, the platform **118** is configured to determine various attack scenarios (e.g., hundreds, thousands, etc.), which are aggregated to a specific asset **104**. The scenarios are based on the type of threat actor, attack method, accessibility of the actor, skill level of the actor, actor intensity or objectives, and probability of success for the specific attack method. Table 4 illustrates various attack scenarios, which are specific to the organization **102**.

TABLE-US-00004

TABLE 4	Risk Scenario	Attacker	Method	Objective	Asset	Priority
#1	Disgruntled	Denial of Availability	Brand Med IT Employee	Service Reputation & Attack Trust		
#2	Hackivist	Injection Confidentiality	Brand Med attack	Reputation & Trust		
#3	Disgruntled	Injection Availability	Brand Med IT Employee	attack Reputation & Trust		

[0066] The scenarios included in the listing above, and others, are defined through possibilities from the threat landscape of the organization **102** (or relevant industry), as compiled through research in the threat landscape. The platform **118** is configured to determine the various attack scenarios based on assets, and asset priorities. In particular, the assets **104** and associated priorities, threat actors, attack methods and aims, along with confidentiality, integrity and availability, are matched based on the threat landscape and end users. The probable attack scenarios are taken into consideration, by the platform **118**, in creating risk scenarios. It should be appreciated that the platform **118** is not configured to account for all permutations, in this example embodiment, as each threat actor is not potentially relevant on each asset and attack method.

[0067] The platform **118** is further configured to calculate the preparedness (or risk) associated with each of the assets **104a-d**, shown in FIG. **1**, separately. The platform **118** is configured to rely on the risk level, for each of the threat actors and each threat method, as it relates to the specific asset **104**. In doing so, the platform **118** is configured to aggregate the preparedness for the attack scenarios of the assets **104**, as a median or an average, based on the maturity scores of the controls **110**, the threat landscape, and the threat access, which are combined to define the risk levels of each risk scenario (and which are in turn aggregated to the specific assets **104**).

[0068] Table 5 illustrates the combination of the risk scores for the attackers and the risk scores for the attack methods into the risk score specific to the particular assets **104** of the organization **102**, along with the priority of the assets **104** discussed above.

TABLE-US-00005

TABLE 5	Business Asset	Priority	Risk Score	Customer protected health information	Very High	3.57	Personnel Information	Very High	3.57	Customer Financial Information	Very High	3.57	Organization Confidential business Information	Very High	3.72	Core Business Systems/Processes	High	3.3	Organization Confidential Financial Information	High	2.24
---------	----------------	----------	------------	---------------------------------------	-----------	------	-----------------------	-----------	------	--------------------------------	-----------	------	--	-----------	------	---------------------------------	------	-----	---	------	------

[0069] The platform **118** is configured to then aggregate the asset scores, for the assets **104**, in the environment **108**, for example, into an average of the preparedness or risk scores for the specific environment **108**. That is, the environments **108a-b** are considered, and the specific assets **104** included in those environments **108** are aggregated (e.g., as an average, a weighted average, a mean, a sum, a maximum, etc.) into a preparedness or risk score for the specific environment **108**. Similarly, the platform **118** is configured to determine the preparedness or risk score of the organization **102**, which includes the preparedness or risk scores for the environments **108** included

in the organization **102**. The preparedness or risk score for the organization **102** may similarly be an aggregate (e.g., an average, a weighted average, a mean, a sum, a maximum, etc.) of the underlying scores. In one example, the organization preparedness or risk score is the highest preparedness score from the environments **108**, i.e., the worst score in this example.

[0070] Based on the above, the preparedness scores for the assets **104**, environments **108**, and the organization **102**, as related to specific actors and attack methods, are provided by the platform **118** to, for example, the IT manager **116**.

[0071] FIG. **2** illustrates an example interface **200** that may be displayed to the IT manager **116**, or others, via the system **100**. The interface **200** includes the preparedness or risk score of the organization **102** (e.g., “Risk score”, etc.), along with the specific risk scores for the assets **104** and the environments **108**. The risk scores, as determined above, are also included for specific controls **110**, such as, for example, awareness and training, network access control, etc. In this way, the IT manager **116** is permitted to assess the general risk associated with the organization **102**, and to work through the environments **108** of the specific assets **104**, as necessary or desired.

[0072] As shown, the risk scores are represented in a variety of different manners. The risk scores for the assets **104**, the environments **108**, and the organization **102** are illustrated as meters, with the dials indicative of the specific scores. Each of the meters includes a narrative indicator of a risk range (e.g., Medium, etc.) depending on the risk value relative to specific ranges. Also, the risk associated with the threat agents (or attackers) and attack methods, as well as the controls, are bars, which change color and length to indicate the associated risk scores. Each of the bars is associated with a narrative indicator of a risk range (e.g., Medium, Low, High, etc.) depending on the risk value relative to specific ranges.

[0073] With reference again to FIG. **1**, based on the associated risk scores, the platform **118** is configured to identify one or more of the controls **110**, which may be changed or adjusted to impact the preparedness score of the assets **104**, the environments **108**, and/or the organization **102**. For example, where a specific control includes a High risk score (e.g., the awareness and training control in FIG. **2**, etc.), the platform **118** may be configured to identify the basis for the risk score and to simulate, in this manner, various control changes (e.g., dozens, hundreds, or thousands, etc.). The platform **118** is configured to organize the control changes based on the impact on the preparedness score of the assets **104**, the environments **108**, or the organization **102**.

[0074] It should be appreciated that the various control changes may be presented in connection with the example interface **200**, for example, or otherwise to inform the IT manager **116**.

[0075] With continued reference to FIG. **1**, the platform **118** is further configured to determine a financial impact of potential loss due to a successful cyber event.

[0076] In connection therewith, the platform **118** is configured to collect various organizational data related to the organization **102**, including, without limitation, annual revenue, industry, geopolitical location, number of employees, average salary of the organization **102**, etc., for example, from the data structure **112**, etc. The data may be specific to locations (e.g., organizational facilities, etc.), environments **108**, assets **104**, etc.

[0077] In addition, the platform **118** is configured to then access one or more cost of data breach reports, from the external data structure **114**. The reports may define cost in terms of locations, attack methods, etc.

[0078] Next, the platform **118** is configured to calculate a maximum financial impact for the organization **102** based on the one or more of the cost of data breach reports, annual revenue of the organization **102**, geopolitical locations, and industry(ies) of the organization **102**, etc. In particular, the platform **118** is configured to determine a business value, based on annual revenue of the organization **102**, or portion thereof, and then, to determine, based on a formulation, the maximum financial impact value as a function of the business value. Next, the platform **118** is configured to account for the industry and geopolitical locations of the organization **102** to find maximum financial impact calculations. That is, the industry and geopolitical locations are used to find the

specific impact thereto from one or more data breach reports (e.g., IBM Data Breach Report, etc.). For example, where a base value is calculated based on an annual revenue of \$10 M, to be \$9.5 M, the maximum impact may be calculated (based on a suitable representation of historical and/or empirical data) to be \$3.4 M. Then, using the base value, and the selected industry and the location effect values related to the organization **102** and included in the data breach report, the maximum impact value is reduced to \$1.8 M. The maximum input value, therefore, in this example, is dependent on annual revenue and the industry(ies) and location(s) of the organization **102**.

[0079] The platform **118** is also configured to calculate a minimum financial impact of the organization **102**. In particular, the platform **118** is configured to calculate the minimum financial impact, based on the maximum financial impact and the formula where the maximum financial impact is divided by a constant, which are based on historical data and/or empirical input. The constant may be included in a suitable range, for example, above zero, from thirty to seventy, from fifty to sixty, or other suitable range of constants, or at specific values such as, for example, 30, 70, 150, etc., based on the above indicated data. It should be appreciated that the constant may be changed or altered based on the historical data distributions associated, potentially, with historical breaches, data breach reports, etc. In one example, where the maximum financial impact is \$100B (USD) and the constant is identified as 60, the platform **118** is configured to calculate the minimum financial impact as \$100B/60, or \$1.67B. The platform **118** is configured to then divide or split the maximum and minimum financial impact among the different assets **104** of the organization **102**, consistent with the priorities of the assets **104** and associated confidentiality, integrity, and availability parameters. That is, the platform **118** is configured to evaluate each of the assets **104** in connection with confidentiality, integrity and availability (CIA) parameters (e.g., as defined in TABLE 4, etc.). Each parameter is given in a percentage for each asset **104**. Each asset **104**, then, is associated with a distribution for confidentiality, integrity and availability. The platform **118** is configured to split the maximum and minimum impact values with these distributions to each asset **104** (e.g., PII, PHI, IP, etc.) with its priorities to find lowest, medium and highest financial impact values.

[0080] Specifically, in order to split the minimum and maximum values, the platform **118** is configured to calculate, for each asset **104**, the financial value under confidentiality, integrity and availability (CIA) parameters for low, medium and high financial impact values, based on assigned importance levels and the priorities of each business asset **104** are used. As shown in Table 6, for example, to find minimum score (low) for each business asset, minimum financial value from above is combined with associated percentage of each parameter, priorities of each business asset, and some constants like user coefficients with mathematical calculations and normalizations to split total maximum score. Maximum score (high) for each business asset, maximum financial value above is combined with associated percentage of each parameter, priorities of each business asset, and some constants like user coefficients with mathematical calculations and normalizations to split total maximum score. Medium financial impact score is found by lowest and highest score with a formulation. Medium financial impact score is between highest and lowest score. An example of the results are seen in Table 6, where the result are specific to the agreements and contracts business asset **104**.

TABLE-US-00006 TABLE 6 Confidentiality Integrity Availability Business Assets Low Med. High Low Med. High Agreements and Contracts

	\$3.1	\$4.5	\$11.1	\$1.45	\$5.2	\$8.2	\$2	\$5.1	\$7
--	-------	-------	--------	--------	-------	-------	-----	-------	-----

[0081] Then, the platform **118** is configured to calculate, for each asset **104**, the financial value under confidentiality, integrity and availability (CIA) for low, medium and high financial impact values. The platform **118** is configured to combine and aggregate cyber risk scores and financial impact values with lowest, highest and expected (medium) for each business asset.

[0082] In connection therewith, FIG. 5 illustrates an example financial impact curve, which defines a relationship between financial impact and risk to a specific asset, such as, for example, PII

information asset **104**. In this example, the low, medium and high values for the confidentiality parameter (similar to what is in Table 6 above) are 4.1, 9.0 and 13.3, respectively. The values are aligned with a risk level of low to high, or 0 to 5, in this example embodiment, and a curve indicative of risk values versus financial impact values. An example curve is illustrated at reference **502**, and the intersection point for an asset specific cyber risk score of 4 (on the X-axis scale from 0-5) (e.g., at 80%, etc.) is provided as an inception point **504** at a total financial impact of the specific assets as \$30 M.

[0083] The platform **118** is configured to then calculate cyber risk scores and financial impact for the environments **108**, and the organization **102**, separately. In particular, the platform **118** is configured to average the asset scores for the assets **104** included within the environment **108**. So, for example, with reference to FIG. 1, the cyber risk scores for the assets **104a-b** are averaged to provide the cyber risk score for the environment **108a**. The cyber risk scores for the environments **108** may further be averaged to provide the cyber risk score for the organization **102**. Alternatively, in this example embodiment, the platform **118** is configured to compare the cyber risk scores for the different environments **108** and to select the highest, biggest cyber risk score as the cyber risk score for the organization **102**. It should be appreciated, however, that the cyber risk scores may be aggregated up to the environments **108** and then to the organization **102** in any suitable manner, depending, potentially, for example, on decisions to be made, particular assets/environments, industries, locations, specific cyber attacks, etc.

[0084] Based on the above, the platform **118** is configured to generate at least one interface, which includes one or more of the scores for the organization **102**, the environments **108**, and/or the assets **104**. In this way, the specific risks associated with cyber attacks are presented as specific dollar values, i.e., financial impact, as compared to numeric scores untied to specific financial impact.

[0085] FIG. 3 illustrates an example computing device **300** that can be used in the system **100** of FIG. 1. The computing device **300** may include, for example, one or more servers, workstations, personal computers, laptops, tablets, smartphones, etc. In addition, the computing device **300** may include a single computing device, or it may include multiple computing devices located in close proximity or distributed over a geographic region, so long as the computing devices are specifically configured to function as described herein. In the example embodiment of FIG. 1, the data structures **112**, **114** and the platform **118** each may be included in (and/or may include) and/or may each be implemented in a computing device, consistent with and/or similar to the computing device **300**, coupled to (and in communication with) one or more networks. It should be further appreciated that the assets **104**, technologies **106** and the controls **110** are integrated into and may be considered computing devices, etc., whereby each is again consistent with the computing device **300**. However, the system **100** should not be considered to be limited to the computing device **300**, as described below, as different computing devices and/or arrangements of computing devices may be used in other embodiments. In addition, different components and/or arrangements of components may be used in other computing devices.

[0086] Referring to FIG. 3, the example computing device **300** includes a processor **302** and a memory **304** coupled to (and in communication with) the processor **302**. The processor **302** may include one or more processing units (e.g., in a multi-core configuration, etc.). For example, the processor **302** may include, without limitation, a central processing unit (CPU), a microcontroller, a reduced instruction set computer (RISC) processor, an application specific integrated circuit (ASIC), a programmable logic device (PLD), a gate array, and/or any other circuit or processor capable of the functions described herein.

[0087] The memory **304**, as described herein, is one or more devices that permit data, instructions, etc., to be stored therein and retrieved therefrom. The memory **304** may include one or more computer-readable storage media, such as, without limitation, dynamic random access memory (DRAM), static random access memory (SRAM), read only memory (ROM), erasable programmable read only memory (EPROM), solid state devices, flash drives, CD-ROMs, thumb

drives, floppy disks, tapes, hard disks, and/or any other type of volatile or nonvolatile physical or tangible computer-readable media. The memory **304** may be configured to store, without limitation, risk scores, questionnaires, configuration files, annual revenue, reports, and/or other types of data (and/or data structures) suitable for use as described herein. Furthermore, in various embodiments, computer-executable instructions may be stored in the memory **304** for execution by the processor **302** to cause the processor **302** to perform one or more of the operations described herein (e.g., one or more of the operations described herein), such that the memory **304** is a physical, tangible, and non-transitory computer readable storage media. Such instructions often improve the efficiencies and/or performance of the processor **302** and/or other computer system components configured to perform one or more of the various operations herein, whereby the instructions effectively transform the computing device **300** into a special purpose device configured to perform the unique and specific operations described herein. It should be appreciated that the memory **304** may include a variety of different memories, each implemented in one or more of the operations or processes described herein.

[0088] In the example embodiment, the computing device **300** also includes a presentation unit **306** that is coupled to (and is in communication with) the processor **302** (however, it should be appreciated that the computing device **300** could include output devices other than the presentation unit **306**, etc.). The presentation unit **306** outputs data (e.g., preparedness scores, threat levels, as shown in interface **200**, etc.), visually or audibly, for example, to a user of the computing device **300**, etc. And, various interfaces (e.g., as defined by one or more websites, applications, etc.) may be displayed at computing device **300**, and in particular at presentation unit **306**, to display certain information to the user of the device. The presentation unit **306** may include, without limitation, a liquid crystal display (LCD), a light-emitting diode (LED) display, an organic LED (OLED) display, an “electronic ink” display, speakers, etc. In some embodiments, presentation unit **306** may include multiple devices.

[0089] In addition, the computing device **300** includes an input device **308** that receives inputs from the user (i.e., user inputs) of the computing device **300** such as, for example, questionnaire/survey response related to controls for different assets, as further described herein. The input device **308** may include a single input device or multiple input devices. The input device **308** is coupled to (and is in communication with) the processor **302** and may include, for example, one or more of a keyboard, a pointing device, a mouse, a camera, a touch sensitive panel (e.g., a touch pad or a touch screen, etc.), another computing device, and/or an audio input device. In various example embodiments, a touch screen, such as that included in a tablet, a smartphone, or similar device, may behave as both the presentation unit **306** and an input device **308**.

[0090] Further, the illustrated computing device **300** also includes a network interface **310** coupled to (and in communication with) the processor **302** and the memory **304**. The network interface **310** may include, without limitation, a wired network adapter, a wireless network adapter, or other device capable of communicating to one or more different ones of the networks herein and/or with other devices described herein. In some example embodiments, the computing device **300** may include at least one processor (e.g., the processor **302**, etc.), at least one memory (e.g., the memory **304**, etc.), and/or one or more network interfaces (e.g., network interface **310**, etc.) included in, or incorporated into or with the at least one processor.

[0091] FIG. **4** illustrates an example method **400** for assigning a preparedness or risk score to an organization, and its assets and/or environments. The example method **400** is described as implemented in the platform **118** of the system **100**, and with additional reference to the computing device **300**. The methods herein should not be understood to be limited to the example system **100** or the example computing device **300**, and likewise, the systems and the computing devices herein should not be understood to be limited to the example method **400**.

[0092] Initially, in response to one or more intervals, or a threat review or audit, the method **400** is initiated. That is, the user **116** may provide a request to the platform **118**, where the request

indicated the scope of the assessment, for example, the organization **102** or a subset thereof.

[0093] In response, at **402**, the platform **118** accesses data required for the assessment of the organization **102** (or subset thereof). The data, as explained above, may include configuration files for the assets **104** and technologies **106** of the organization **102**, revenues of the organization **102** (e.g., annual, monthly, etc.), industries of the organization **102**, locations/facilities of the organization **102**, employee information (e.g., number of employees, organization charts, work locations of employees, salary of employees, etc.), etc. The data may further include reporting data related to cyber attacks, where the reporting data includes cyber attack events and associated timing, targets, methodologies, actors and objectives, and also analytics related to the same.

[0094] It should be appreciated that the data may further include a framework of indicators, criteria, sub-categories, categories and controls, where the data is related to any part of all of the same.

[0095] In addition, at **404**, the platform **118** solicits data through one or more questionnaires to the user **116**. The questionnaires may be specific to assets **104**, technologies **106** and/or the applicable controls **110**. Different examples of questions included therein are provided above, including, for example; "To what extent is employees' internet browsing secure against web-related threats?" In response, the user **116** proceeds through the one or more questionnaires (i.e., each have one or more questions related to specific criteria, indicators, or even control, etc.) and responds with appropriate, responsive data specific to the organization **102**. The platform **118**, in turn, receives the data.

[0096] It should be appreciated that the data is accessed through steps **402** and **404** above, at the outset, but the data may also be accessed later in the method **400**, as necessary or desired. For example, revenue data may be accessed, by the platform **118**, in connection with step **418**, for example. What's more, between the manual entry of data by the user **116** through the questionnaire, and the access of data, the platform **118** is enabled with the data necessary for the computations and calculations described herein.

[0097] As shown in FIG. **4**, the platform **118** proceeds to calculate the control maturity score, at **406**. In particular, as explained above, the platform **118** initially determines the quantitative scores for each indicator. The scores are determined, in this example, on a range from 0 to 100. The scores are determined from both the accessed data (e.g., which is machine accessed, etc.) and also the manually entered data from the user **116**, as explained above.

[0098] Next, the platform **118** calculates the average scores for the indicators that map to a specific criteria for assessing the organization **102** (e.g., DNS configuration, etc.). The average scores for each of the criteria are then averaged according to the sub-categories to which the criteria are mapped. Next, the scores for the sub-categories are averaged, based on the category to which each sub-category is mapped. The scores provide category specific maturity levels. The category scores are then averaged, again, consistent with a mapping of the categories to specific ones of the controls **110**.

[0099] The scores for the controls **110** may be further combined based on control type: preventive, infrastructure, and detective in this example embodiment. It should be appreciated that the controls **110** may be organized by type, or otherwise, in other embodiments.

[0100] Through the above sequence, as defined by the indicators to control hierarchy explained above, the platform **118** calculates the control maturity score (for the different controls **110**) based on the accessed data.

[0101] At **408**, the platform **118** determines the threat activity level/scores for attacker(s) (or actor(s) and attack method(s). Specifically, as explained above, certain threat actors may be prone to specific types of attack methods, while other actors may be prone to the most effective, or most recently developed attack methods, etc., as appreciated from data. The platform **118** continuously or otherwise monitors the data and further determines matches, for example, based on a single language or a multilingual dictionary, between threat actors and attack methods. The matches,

generally, are determined based on cyber events that include the actor and also the method, whereby each event includes one instance. The platform **118** aggregates the matches, statistically, to identify threat activity level trends, propensities, etc., for each combination of threat actor and attack method and to assign a score in relation to the top activity data points from the aggregation. [0102] In this example embodiment, consistent with the above, the threat activity level is a value between 0 and 100 and calculated as based on historical occurrences, which may be, potentially, specific to the particular industry of the organization **102**, the location(s) of the organization **102**, etc.

[0103] At **410**, the platform **118** determines the POS for the attack methods, based, at least in part, on the control maturity score. The POS or probability of success scores are calculated based on a stop factor associated with the organization **102**, as explained above, where the POS is calculated based on multiple correlations between threat actors and attached methods, and the controls **110** implemented in the organization **102**, considering actual effectiveness level.

[0104] At **412**, the platform **118** assigns a risk level (or preparedness level) to the organization **102** for each threat actor and/or each attack method considered by the threat actors, while considering malicious intent (e.g., confidentiality, availability or integrity (CIA) objectives of the actor, etc.) against the assets **104**.

[0105] At **414**, the platform **118** determines a risk score for the assets **104** of the organization **102** for different scenarios, based on the risk level, for each of the threat actors and each threat method, as it relates to the specific asset **104**. In doing so, the platform **118** is configured to aggregate the preparedness of the attack scenarios of the assets **104**, as a median above average.

[0106] The platform **118** is configured to then aggregate the asset scores, for the assets **104**, in the environment **108**, for example, into an average of the preparedness or risk scores for the specific environment **108**. That is, the environments **108a-b** are considered, and the specific assets **104** included in those environments **108** are aggregated (e.g., as an average, a weighted average, a mean, a sum, a maximum, etc.) into a preparedness or risk score for the specific environment **108**. Similarly, the platform **118** is configured to determine the preparedness or risk score of the organization **102**, which includes the preparedness or risk scores for the environments **108** included in the organization **102**. The preparedness or risk score for the organization **102** may similarly be an aggregate (e.g., an average, a weighted average, a mean, a sum, a maximum, etc.) of the underlying scores. In one example, the organization preparedness or risk score is the highest preparedness score from the environments **108**, i.e., the worst score in this example.

[0107] Based on the above, the preparedness scores for the assets **104**, environments **108**, and the organization **102**, as related to specific actors and attack methods, are provided by the platform **118** to, for example, for presentation or display to the IT manager **116** (e.g., at step **424**, etc.).

[0108] At **416**, the platform **118** is configured to determine control remediation based on the assets **104** priorities. That is, the risk score(s) for the organization **102**, the environments **108**, the technologies **106** and the assets **104**, may be decompiled, based on the hierarchy of the organization **102** to determine which indicators (or categories or sub-categories, etc.) impact the risk scores. In doing so, the platform **118** is able to assess the ratings/score of the indicator, criteria, sub-category, category, etc., to identify one or more controls or details thereof to be modified, in a manner intended to remediate the risk score/rating associated therewith. The platform **118** may simulate various changes to the indicators, which, in turn, are factored into recalculation consistent with steps **406-414**, whereby an improvement for one or more remediations may be determined for presentation or display to the IT manager **116** (e.g., at step **424**, etc.).

[0109] With continued reference to FIG. **4**, the platform **118** also collects various data associated with financial impact of a cyber attack on the organization **102**. The data includes organization data, such as, without limitation, annual revenue, industry, geopolitical location, number of employees, average salary (e.g. from the data structure **112**, etc.) and also data breach reports (e.g., from the external data structure **114**, etc.).

[0110] Next, at **418**, the platform **118** calculates a maximum financial impact for the organization **102** based on the one or more of the cost of data breach reports, annual revenue of the organization **102**, geopolitical locations, and industry(ies) of the organization **102**, etc. The platform **118** also calculates, at **418**, a minimum financial impact of the organization **102**, based on the maximum financial impact and the formula where the maximum financial impact is divided by a constant. At **420**, the platform splits the financial impact (e.g., maximum and minimum, separately, etc.) among the different assets **104** of the organization **102**, consistent with the priorities of the assets **104** and associated confidentiality, integrity, and availability. As shown in FIG. 4, the financial impact, both high (maximum) and low (minimum) are split to the different categories of assets **104**. Next, as shown in FIG. 4, at **422**, the platform **118** calculates, for each asset **104**, the financial value under confidentiality, integrity and availability categories for low, medium and high financial impact values, based on the cyber risk scores for the specific assets **104**.

[0111] Based on the above, the platform **118** generates and displays, at **424**, one or more interfaces, which includes one or more of the scores for the organization **102**, the environments **108**, and/or the assets **104**. In this way, the specific risks associated with cyber attacks are presented as specific dollar values, i.e., financial impact, as compared to numeric scores untied to specific financial impact. An example interface, as explained above, is illustrated in FIG. 2.

[0112] In view of the above, the systems and methods herein provide for modeling preparedness (e.g., of organizations, etc.) for cyber attacks, and potentially, the financial losses associated with the cyber attacks. The modeling relies on identifying a threat landscape, cyber maturity status, and information assets. In this manner, the systems and methods provide for an objectives measure of the preparedness or risk of an organization, where control maturity risk is comprehensive if its assessment, and then financial impact is calculated as a mechanism to educate decision makers associated with remediation of the organization **102** (e.g., in efforts to further secure the information assets **104**, etc.).

[0113] In this way, the systems and methods herein may provide quantitative evaluations about maturity of controls with enhanced objectivity as based on clear standards, ratings, scores, etc., and further, may provide up-to-date control maturity information based on the automation and/or data accessed (e.g., technical indicators, question indicators, etc.).

[0114] Again and as previously described, it should be appreciated that the functions described herein, in some embodiments, may be described in computer executable instructions stored on a computer readable media, and executable by one or more processors. The computer readable media is a non-transitory computer readable storage medium. By way of example, and not limitation, such computer-readable media can include RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of instructions or data structures and that can be accessed by a computer. Combinations of the above should also be included within the scope of computer-readable media.

[0115] It should also be appreciated that one or more aspects of the present disclosure transform a general-purpose computing device into a special-purpose computing device when configured to perform the functions, methods, and/or processes described herein.

[0116] As will be appreciated based on the foregoing specification, the above-described embodiments of the disclosure may be implemented using computer programming or engineering techniques including computer software, firmware, hardware or any combination or subset thereof, wherein the technical effect may be achieved by performing at least one of the claimed operations.

[0117] Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different

forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

[0118] The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

[0119] When an element or layer is referred to as being “on,” “engaged to,” “connected to,” “coupled to,” “associated with,” or “included with” another element or layer, it may be directly on, engaged, connected or coupled to, or associated with the other element or layer, or intervening elements or layers may be present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0120] Although the terms first, second, third, etc. may be used herein to describe various features, these features should not be limited by these terms. These terms may be only used to distinguish one feature from another. Terms such as “first,” “second,” and other numerical terms when used herein do not imply a sequence or order unless clearly indicated by the context. Thus, a first feature discussed herein could be termed a second feature without departing from the teachings of the example embodiments.

[0121] The foregoing description of example embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

Claims

1. A computer-implemented method for use in assessing cyber attack preparedness associated with an organization, the method comprising: accessing data associated with an organization, the data including multiple indicators of an information network and financial data related to the organization, the organization including multiple information assets; determining, based on the multiple indicators, a maturity score for the organization; calculating, by a computing device, a probability of success (POS) of each of multiple attack methods on the organization; calculating, by the computing device, a cyber risk score for each of the information assets, based on the POS of each of the multiple attack methods and multiple risk scenarios, each risk scenario including an actor and one of the multiple attack methods; calculating, by the computing device, based on the financial data and location(s) of the organization, a maximum financial impact for a cyber attack on the organization; calculating, by the computing device, a minimum financial impact for the cyber attack on the organization; splitting, by the computing device, the maximum and minimum financial impacts among the multiple assets, according to confidentiality, integrity, and availability parameters; and calculating, by the computing device, a potential financial impact for each information asset with aggregating maximum and minimum potential financial ranges and cyber risk scores.

2. The computer-implemented method of claim 1, wherein calculating the POS of each of the multiple attack methods includes: calculating a stop factor based on controls associated with preventive, detective and infrastructure control types; and subtracting the stop factor from a chance of success of each of multiple attack methods.
3. The computer-implemented method of claim 2, wherein calculating the POS of each of the multiple attack methods includes calculating the chance of success, based on activity levels of actors and attack methods in a threat landscape.
4. The computer-implemented method of claim 1, wherein the risk scenarios include combinations of actors and ones of the multiple attack methods.
5. The computer-implemented method of claim 1, wherein calculating the maximum financial impact for the cyber attack on the organization includes: calculating the maximum financial impact for the cyber attack on the organization based on a cost of data breach data and industry and geopolitical indicators.
6. The computer-implemented method of claim 1, further comprising calculating, by the computing device, a financial impact for an environment of the organization and a financial impact for the organization, separately.
7. The computer-implemented method of claim 1, wherein the financial data includes annual revenue, industry, geopolitical location, number of employees, and average salary of the organization.
8. A system for use in assessing cyber attack preparedness associated with an organization, the system comprising at least one computing device configured to: access data associated with an organization, the data including multiple indicators of an information network and financial data related to the organization, the organization including multiple information assets; determine, based on the multiple indicators, a maturity score for the organization; calculate a probability of success (POS) of each of multiple attack methods on the organization; calculate a cyber risk score for each of the information assets, based on the POS of each of the multiple attack methods and multiple risk scenarios, each risk scenario including an actor and one of the multiple attack methods; calculate, based on the financial data and location(s) of the organization, a maximum financial impact for a cyber attack on the organization; calculate a minimum financial impact for the cyber attack on the organization; split the maximum and minimum financial impacts among the multiple assets, according to confidentiality, integrity, and availability parameters; and calculate a potential financial impact for each information asset with aggregating maximum and minimum potential financial ranges and cyber risk scores.
9. The system of claim 8, wherein the at least one computing device is configured, in order to calculate the POS of each of the multiple attack methods, to: calculate a stop factor based on controls associated with preventive, detective and infrastructure control types; and subtract the stop factor from a chance of success of each of multiple attack methods.
10. The system of claim 9, wherein the at least one computing device is configured, in order to calculate the POS of each of the multiple attack methods, to calculate the chance of success, based on activity levels of actors and attack methods in a threat landscape.
11. The system of claim 8, wherein the risk scenarios include combinations of actors and ones of the multiple attack methods.
12. The system of claim 8, wherein the at least one computing device is configured, in order to calculate the maximum financial impact for the cyber attack on the organization, to: calculate the maximum financial impact for the cyber attack on the organization based on a cost of data breach data and industry and geopolitical indicators.
13. The system of claim 8, wherein the at least one computing device is further configured to calculate a financial impact for an environment of the organization and a financial impact for the organization, separately.
14. The system of claim 8, wherein the financial data includes annual revenue, industry,

geopolitical location, number of employees, and average salary of the organization.

15. A non-transitory computer-readable storage medium comprising executable instructions for use in assessing cyber attack preparedness associated with an organization, which when executed by at least one processor, cause the at least one processor to: access data associated with an organization, the data including multiple indicators of an information network and financial data related to the organization, the organization including multiple information assets; determine, based on the multiple indicators, a maturity score for the organization; calculate a probability of success (POS) of each of multiple attack methods on the organization; calculate a cyber risk score for each of the information assets, based on the POS of each of the multiple attack methods and multiple risk scenarios, each risk scenario including an actor and one of the multiple attack methods; calculate, based on the financial data and location(s) of the organization, a maximum financial impact for a cyber attack on the organization; calculate a minimum financial impact for the cyber attack on the organization; split the maximum and minimum financial impacts among the multiple assets, according to confidentiality, integrity, and availability parameters; and calculate a potential financial impact for each information asset with aggregating maximum and minimum potential financial ranges and cyber risk scores.

16. The non-transitory computer-readable storage medium of claim 15, wherein the executable instructions, when executed by the at least one processor to calculate the POS of each of the multiple attack methods, cause the at least one processor to: calculate a stop factor based on controls associated with preventive, detective and infrastructure control types; and subtract the stop factor from a chance of success of each of multiple attack methods.

17. The non-transitory computer-readable storage medium of claim 16, wherein the executable instructions, when executed by the at least one processor to calculate the POS of each of the multiple attack methods, cause the at least one processor to calculate the chance of success, based on activity levels of actors and attack methods in a threat landscape.

18. The non-transitory computer-readable storage medium of claim 15, wherein the risk scenarios include combinations of actors and ones of the multiple attack methods.

19. The non-transitory computer-readable storage medium of claim 16, wherein the executable instructions, when executed by the at least one processor to calculate the maximum financial impact for the cyber attack on the organization, cause the at least one processor to: calculate the maximum financial impact for the cyber attack on the organization based on a cost of data breach data and industry and geopolitical indicators.

20. The non-transitory computer-readable storage medium of claim 15, wherein the executable instructions, when executed by the at least one processor, cause the at least one processor to calculate a financial impact for an environment of the organization and a financial impact for the organization, separately.
