

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12384288
B2
August 12, 2025
Vachon; Marc et al.

Strap anchor for securing an accessory to a vehicle using a strap and method therefor

Abstract

A strap anchor for securing an accessory to a vehicle with a strap includes: a mounting portion including anchor base configured to engage an upper surface of an accessory receiving base connected to the vehicle and an anchor lock connected to the anchor base, the anchor lock being configured to be inserted through an aperture defined by the accessory receiving base; and a pivoting portion that is pivotably connected to the mounting portion about a pivot axis, the pivoting portion including a strap-receiving part configured for engaging the strap therewith. The strap anchor is configured to be removably fixed to the accessory receiving base by inserting the anchor lock through the aperture and turning the mounting portion such that the anchor lock is prevented from being extracted through the aperture. A method for securing an accessory to a vehicle using a strap anchor is also disclosed.

Inventors: Vachon; Marc (St-Denis-de-Brompton, CA), Bitsch; Magali (Saint-Francois-Xavier-de-Brompton, CA), Robillard; Pierre-Luc (Sherbrooke, CA), Baldachino; Simon (Bromont, CA), Guendoul; Nabil (Granby, CA), Bourassa; Michel (Sherbrooke, CA)

Applicant: BOMBARDIER RECREATIONAL PRODUCTS INC. (Valcourt, CA)

Family ID: 91192310

Assignee: BOMBARDIER RECREATIONAL PRODUCTS INC. (Valcourt, CA)

Appl. No.: 18/072381

Filed: November 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240174164 A1	May. 30, 2024

Publication Classification

Int. Cl.: B60P7/00 (20060101); B60P7/08 (20060101)

U.S. Cl.:

CPC B60P7/0807 (20130101); B60P7/0823 (20130101);

Field of Classification Search

CPC: B60P (7/0823); B60P (7/0807)

USPC: 410/113; 410/101

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8777531	12/2013	Massicotte et al.	N/A	N/A
8875830	12/2013	Massicotte	180/89.1	B60R 9/06
9505335	12/2015	Massicotte et al.	N/A	N/A
9511704	12/2015	Massicotte et al.	N/A	N/A
9751592	12/2016	Labbe et al.	N/A	N/A
10227110	12/2018	Valence et al.	N/A	N/A
10391949	12/2018	Labbe et al.	N/A	N/A
10730576	12/2019	Labbe et al.	N/A	N/A
10744953	12/2019	Labbe et al.	N/A	N/A
10850806	12/2019	Labbe et al.	N/A	N/A
10941801	12/2020	Roy et al.	N/A	N/A
11235829	12/2021	Robillard et al.	N/A	N/A
2005/0180835	12/2004	Schneider	410/100	B60P 7/0823
2011/0064535	12/2010	Tardif	410/101	B60P 7/0807
2014/0026373	12/2013	Seader	24/193	A44B 11/12
2020/0339040	12/2019	Labbe et al.	N/A	N/A
2020/0406730	12/2019	Fournier et al.	N/A	N/A
2021/0039749	12/2020	Labbe et al.	N/A	N/A

OTHER PUBLICATIONS

<https://www.rockymountainatvmc.com/parts/tusk-cargo-anchor-p>, retrieved from Rocky Mountain ATV-MC.com's website on May 5, 2023. cited by applicant

Primary Examiner: Douglas; Steven O

Attorney, Agent or Firm: BCF LLP

Background/Summary

TECHNICAL FIELD

(1) The present technology relates to anchors for securing accessories to a vehicle.

BACKGROUND

(2) In many recreational vehicles, it is generally desirable to have an area for mounting accessories such as storage containers (e.g., coolers), bags, and fuel caddies to provide more cargo-carrying capacity. For example, some personal watercrafts (PWCs), all-terrain vehicles (ATVs), side-by-side vehicles (SSVs) and snowmobiles are designed to provide anchoring points at which anchors connected to the accessory can be fixed.

(3) While this provides a quick and convenient way to secure an accessory to the vehicle, such anchors are typically only compatible with accessories that have a rigid base to support the anchors. Indeed, these anchors are often unsuitable for an accessory having a flexible exterior material without a rigid base fixed thereto. To address this, some anchors have been designed to accommodate the use of a strap and are mountable at the anchor mounting points of the vehicle. The strap is tied to the anchor and to the accessory to thereby secure the accessory to the vehicle. However, these “strap” anchors are often difficult to mount, notably requiring tools to install and uninstall, which can prevent a user from removing the anchors, thereby hindering the versatility of the anchor mounting points provided on the vehicle.

(4) In view of the foregoing, there is a need for a strap anchor that addresses at least in part some of these defects.

SUMMARY

(5) It is an object of the present technology to ameliorate at least some of the inconveniences present in the prior art.

(6) According to one aspect of the present technology, there is provided a strap anchor for securing an accessory to a vehicle with a strap, the strap anchor comprising: a mounting portion comprising: an anchor base configured to engage an upper surface of an accessory receiving base connected to the vehicle, the anchor base being generally elongated; and an anchor lock connected to the anchor base, the anchor lock having a generally hexagonal shape that is elongated, the anchor lock being configured to be inserted through an aperture defined by the accessory receiving base; and a pivoting portion that is pivotably connected to the mounting portion about a pivot axis, the pivoting portion comprising a strap-receiving part configured for engaging the strap therewith, the strap anchor being configured to be removably fixed to the accessory receiving base by inserting the anchor lock through the aperture and then turning the mounting portion relative to the accessory receiving base such that the anchor lock is prevented from being extracted through the aperture.

(7) In some embodiments, the anchor lock has at least one upper tapered surface configured to engage a lower surface of the accessory receiving base during turning of the mounting portion relative to the accessory receiving base.

(8) In some embodiments, the strap anchor is configured to be fixed to the accessory receiving base by turning the mounting portion by a quarter turn about a turning axis extending, in use, through the aperture.

(9) In some embodiments, the anchor base comprises at least one locking tab protruding downwardly from a lower base surface of the anchor base to engage an inner surface of the accessory retaining base defining the aperture.

(10) In some embodiments, without the strap engaged with the strap-receiving part, the pivoting portion is free to pivot relative to the mounting portion a full rotation about the pivot axis.

(11) In some embodiments, the anchor base comprises a first protruding body and a second protruding body spaced from each other; and part of the pivoting portion is disposed between the first protruding body and the second protruding body.

(12) In some embodiments, the pivoting portion is pivotable relative to the mounting portion about the pivot axis extending between the first and second protruding bodies; each of the first and

second protruding bodies comprises an inner body surface facing the pivot axis; the inner surfaces of the first and second protruding bodies are curved and spaced from a curved outer surface of the part of the pivoting portion.

(13) In some embodiments, each of the first and second protruding bodies has an upper body surface; and an upper surface of the part of the pivoting portion is generally aligned with the upper body surfaces of the first and second protruding bodies.

(14) In some embodiments, the strap-receiving part is configured to adjust a position of an end of the strap relative to the strap-receiving part.

(15) In some embodiments, the strap-receiving part is a ladder lock buckle.

(16) In some embodiments, the ladder lock buckle comprises a first bar and a second bar extending generally parallel to each other.

(17) In some embodiments, the pivoting portion is connected to the mounting portion by a fastener.

(18) In some embodiments, the mounting portion defines an opening; the pivoting portion comprises a stem extending within the opening of the mounting portion, the stem extending along the pivot axis; and the fastener retains the stem within the opening to prevent the pivoting portion from being disengaged from the mounting portion.

(19) In some embodiments, the fastener comprises a fastener head, the fastener head being disposed at a lower end of the pivoting portion.

(20) In some embodiments, the mounting portion further comprises an outer stem extending between the anchor base and the anchor lock.

(21) In some embodiments, the anchor lock comprises two cams extending from the outer stem in opposite directions from each other.

(22) In some embodiments, the anchor base is elongated in a first direction; and the anchor lock is elongated in a second direction that is generally perpendicular to the first direction.

(23) In some embodiments, an anchor assembly for securing an accessory to a vehicle comprises: the strap anchor; and a strap engaged with the strap-receiving part, the strap being configured to be tied to the accessory in order to secure the accessory to the vehicle.

(24) According to another aspect of the present technology, there is provided a vehicle comprising: an accessory receiving base defining at least one aperture having a generally elongated hexagonal shape; and at least one strap anchor removably fixed to the accessory receiving base, the anchor lock of the at least one strap anchor being disposed beneath a lower surface of the accessory receiving base and being oriented to prevent extraction of the anchor lock through the at least one aperture.

(25) According to another aspect of the present technology, there is provided a method for securing an accessory to a vehicle using a strap anchor, the strap anchor comprising a mounting portion and a pivoting portion that is pivotable relative to the mounting portion, the method comprising: inserting an anchor lock of the mounting portion of the strap anchor through an aperture of an accessory receiving base connected to the vehicle until an anchor base of the mounting portion engages an upper surface of the accessory receiving base; turning the strap anchor to orient the anchor lock such that the anchor lock is prevented from being extracted through the aperture; and tying a strap engaged with a strap-receiving part of the pivoting portion to the accessory.

(26) In some embodiments, the method also comprises adjusting a position of an end of the strap relative to the strap-receiving part in order to adjust a force exerted by the strap on the accessory.

(27) In some embodiments, the strap is tied to the accessory prior to turning the strap anchor.

(28) For purposes of this application, the terms related to spatial orientation such as forwardly, rearward, left and right, are as they would normally be understood by an operator of a vehicle sitting thereon in a normal driving position.

(29) Embodiments of the present technology each have at least one of the above-mentioned objects and/or aspects, but do not necessarily have all of them. It should be understood that some aspects of the present technology that have resulted from attempting to attain the above-mentioned objects

may not satisfy these objects and/or may satisfy other objects not specifically recited herein.
(30) Additional and/or alternative features, aspects, and advantages of embodiments of the present technology will become apparent from the following description, the accompanying drawings, and the appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a better understanding of the present technology, as well as other aspects and further features thereof, reference is made to the following description which is to be used in conjunction with the accompanying drawings, where:
- (2) FIG. 1 is a perspective view, taken from a top, front, right side, of a personal watercraft equipped with strap anchors in accordance with an embodiment of the present technology for securing an accessory to the watercraft;
- (3) FIG. 2 is a right side elevation view of the watercraft of FIG. 1;
- (4) FIG. 3 is a perspective view, taken from a top, rear, right side, of the watercraft of FIG. 1;
- (5) FIG. 4 is a perspective view, taken from a top, rear, right side, of the watercraft of FIG. 1, shown without the accessory and the strap anchors;
- (6) FIG. 5 is a perspective view, taken from a top, rear, right side, of an accessory receiving base of the watercraft of FIG. 1;
- (7) FIG. 6 is a bottom plan view of the accessory receiving base of FIG. 5;
- (8) FIG. 7 is a perspective view, taken from a top, rear, left side, of one of the strap anchors of the watercraft of FIG. 1;
- (9) FIG. 8 is a perspective view, taken from a bottom, rear, left side, of the strap anchor of FIG. 7;
- (10) FIG. 9 is a left side elevation view of the strap anchor of FIG. 7;
- (11) FIG. 10 is a top plan view of the strap anchor of FIG. 7;
- (12) FIG. 11 is a bottom plan view of the strap anchor of FIG. 7;
- (13) FIG. 12 is a cross-sectional view of the strap anchor of FIG. 7 taken along line 12-12 in FIG. 10;
- (14) FIG. 13 is a cross-sectional view of the strap anchor of FIG. 7 taken along line 13-13 in FIG. 10, showing a strap engaged with the strap anchor; and
- (15) FIG. 14 is the cross-sectional view of FIG. 13 showing the strap engaged with the strap anchor in an alternative manner.

DETAILED DESCRIPTION

- (16) FIGS. 1 to 3 show a vehicle provided with a plurality of strap anchors 100 in accordance with an embodiment of the present technology. In this embodiment, the vehicle is a personal watercraft (PWC) 10. It is contemplated that the vehicle may be any other suitable type of vehicle in other embodiments such as an off-road vehicle (e.g., an all-terrain vehicle (ATV), a snowmobile, etc.) or a road vehicle. As will be described in detail further below, the strap anchors 100 facilitate securing an accessory 50 (such as a waterproof bag, as shown in FIGS. 1 to 3) to the PWC 10.
- (17) The PWC 10 will now be generally described with reference to FIGS. 1 to 3. The PWC 10 has a hull 12 and a deck 14 supported by the hull 12. The hull 12 buoyantly supports the PWC 10 in the water. The deck 14 is designed to accommodate one or multiple riders. The hull 12 and the deck 14 are joined together at a seam that joins the parts in a sealing relationship. A bumper 19 generally covers the seam 16, which helps to prevent damage to the outer surface of the PWC 10 when the PWC 10 is docked, for example.
- (18) The hull 12 has a bow 16 and a stern 17 opposite the bow 16, as well as a laterally centered keel 21. The hull 12 also has strakes 43 and chines 45 on each lateral side thereof. A strake 43 is a protruding portion of the hull 12. The chines 45 are the vertices formed where two surfaces of the

hull 12 meet.

(19) The deck **14** has a centrally positioned straddle-type seat **24** positioned on top of a pedestal **29** to accommodate multiple riders in a straddling position. The seat **24** includes a front seat portion **40** and a rear, raised seat portion **42**. The seat **24** is preferably made as a cushioned or padded unit, or as interfitting units. The front and rear seat portions **40**, **42** are removably attached to the pedestal **29**. The seat portions **32**, **34** can be individually tilted or removed completely. Seat portion **40** covers a motor access opening defined by a top portion of the pedestal **29** to provide access to a motor **25** (shown schematically in FIG. 2).

(20) The PWC **10** has a pair of generally upwardly extending walls located on either side of the PWC **10** known as gunwales or gunnels **27**. The gunnels **27** help to prevent the entry of water in footrests **26** of the PWC **10**, provide lateral support for the riders' feet, and also provide buoyancy when turning the PWC **10**, since the personal PWC **10** rolls slightly when turning. Towards the rear of the PWC **10**, the gunnels **27** extend inwardly to act as heel rests. A passenger riding the PWC **10** facing towards the rear, to spot a water-skier for example, may place his or her heels on the heel rests, thereby providing a more stable riding position. Heel rests could also be formed separately from the gunnels **27**.

(21) Located on both sides of the PWC **10**, between the pedestal **29** and the gunnels **27**, are the left and right footrests **26** which are disposed on opposite sides of a longitudinal centerplane of the PWC **10** that bisects a width thereof. The footrests **26** are designed to accommodate the riders' feet in various riding positions. The footrests **26** are covered by carpeting made of a rubber-type material, for example, to provide additional comfort and traction for the feet of the riders.

(22) A reboarding platform **44** is provided at the rear of the PWC **10** on the deck **14** to allow the rider or a passenger to easily reboard the PWC **10** from the water. Nonslip mats or some other suitable covering may cover the reboarding platform **40**. A retractable ladder (not shown) may be affixed to a transom of the stern **17** to facilitate boarding the PWC **10** from the water onto the reboarding platform **44**. In this embodiment, a plurality of anchor fixtures **80** are provided on the reboarding platform **44**. The anchor fixtures **80** are configured to receive an anchor and/or a tongue fastener for securing accessories thereto. Such anchor fixtures and their functionality are described in detail in U.S. Pat. No. 10,227,110, issued Mar. 12, 2019, the entirety of which is incorporated by reference herein.

(23) As seen in FIG. 1, the PWC **10** is provided with a hood **46** located forwardly of the seat **24** and a helm assembly **20**. A hinge (not shown) is attached between a forward portion of the hood **46** and the deck **14** to allow the hood **46** to move to an open position to provide access to a front storage bin. A latch (not shown) located at a rearward portion of the hood **46** locks the hood **46** into a closed position. When in the closed position, the hood **46** prevents water from entering the front storage bin **24**.

(24) As best seen in FIG. 2, the helm assembly **20** is positioned forwardly of the seat **24**. The helm assembly **20** has a central helm portion, that is padded, and a pair of steering handles **28**, also referred to as a handlebar. One of the steering handles **28** is provided with a throttle operator **23**, which allows the rider to control the motor **25**, and therefore the speed of the PWC **10**. The throttle operator **23** is a finger-actuated throttle lever. However, it is contemplated that the throttle operator **23** could take other forms, such as a thumb-actuated throttle lever or a twist grip. The throttle operator **23** is movable between an idle position and multiple actuated positions. In this embodiment, the throttle operator **23** is biased towards the idle position, such that, should the driver of the PWC **10** let go of the throttle operator **23**, it will move to the idle position. The other of the steering handles **65** is provided with a reverse gate operator (not shown) used by the driver to actuate a reverse gate (not shown) of the PWC **10**. The reverse gate operator is a finger-actuated lever. However, it is contemplated that the reverse gate operator could be a thumb-actuated lever or a twist grip.

(25) The helm assembly **20** is provided with a key receiving post (not shown) located near a center

of the central helm portion. The key receiving post is adapted to receive a key required to start the PWC **10**. It should be noted that the key receiving post may be placed in any suitable location on the PWC **10**.

(26) As shown in FIG. **3**, a display area or cluster **30** is located forwardly of the helm assembly **20**. The display cluster **30** can be of any conventional display type, including a liquid crystal display (LCD), dials or LED (light emitting diodes). The central helm portion has various buttons, which could alternatively be in the form of levers or switches, that allow the driver to modify the display data or mode (speed, engine rpm, time, etc.) on the display cluster **30** or to change a condition of the PWC **10**, such as trim (the pitch of the PWC **10**). In this embodiment, the PWC **10** also has a navigation device **31** (e.g., a GPS device) to the right of the display cluster **30**.

(27) With reference to FIG. **2**, the motor **25** is supported by the hull **12** and is enclosed within a motor compartment defined between the hull **12** and the deck **14**. The motor **25** is configured for driving a jet propulsion system **70** (also commonly referred to as a “jet pump drive”) which propels the PWC **10**. The motor compartment accommodates the motor **25**, as well as a muffler, gas tank, electrical system (battery, electronic control unit, etc.), air box, storage bins, and other elements required or desirable in the PWC **10**. In this embodiment, the motor **25** is an internal combustion engine **25** and will thus be referred to as the engine **25**. However, it is contemplated that, in alternative embodiments, the motor **25** may be any other suitable type of motor such as an electric motor. As will be understood, in such an embodiment, certain components of the PWC **10** would be added to (e.g., a battery pack) or omitted from (e.g., no muffler and gas tank, etc.).

(28) As mentioned above, the PWC **10** is propelled by the jet propulsion system **70** which pressurizes water to create thrust. To that end, the jet propulsion system **50** has a duct (not shown) in which water is pressurized and which is defined by various components of the jet propulsion system **70**, including an intake ramp (not shown), an impeller housing (not shown), and a steering nozzle **71** of the jet propulsion system **70**. A driveshaft is connected between the engine **25** and an impeller (not shown) of the jet propulsion system **70**. A bellow assembly (not shown) is mounted to the driveshaft and provides a seal between the duct and the hull **12** such as to prevent entry of water into the hull **12**.

(29) The PWC **10** is also provided with a reverse gate (not shown) which is movable between a stowed position where it does not interfere with the jet of water being expelled rearwardly along the duct by the jet propulsion system **70** and a plurality of positions where it redirects the jet of water being expelled rearwardly along the duct by the jet propulsion system **70**. Notably, the reverse gate can be actuated into a neutral position in which the thrust generated by the jet propulsion system **70** does not have a horizontal component such that the PWC **10** will not be accelerated or decelerated by the thrust and will stay in position if it was not moving prior to moving the reverse gate in the neutral position. The reverse gate can also be actuated into a reverse position as it redirects the jet of water towards the front of the PWC **10**, thus causing the PWC **10** to move in a reverse direction. A reverse gate actuator (not shown), in the form of an electric motor, is operatively connected to the reverse gate to move the reverse gate. The reverse gate actuator could alternatively be any one of a mechanical, a hydraulic, or another type of electric actuator.

(30) The PWC **10** also has other features and characteristics that are commonly known in the art and will therefore not be described herein.

(31) As shown in FIGS. **1** to **3**, the PWC **10** has an accessory receiving base **60** that is configured for securing the accessory **50** thereto and for removably connecting the strap anchors **100** thereto. In this embodiment, the accessory receiving base **60** is fastened to the deck **14**. With particular reference to FIGS. **5** and **6**, the accessory receiving base **60** has a rear end **62**, a front end **64** and left and right ends **66**, **68**. In this example, the accessory receiving base **60** is disposed behind the seat **24**. The accessory receiving base **60** has an upper surface **72** (FIG. **5**) on an upper side thereof and a lower surface **75** (FIG. **6**) on a lower side thereof opposite the upper side. The accessory receiving base **60** defines a plurality of apertures **74** configured to receive respective ones of the

strap anchors **100** as will be described in greater detail below. As can be seen, each aperture **74** extends from the upper surface **72** to the lower surface **75**. In this example, each aperture **74** has a generally elongated hexagonal shape. That is, each aperture **74** is defined by a respective inner surface **79** of the accessory receiving base **60**, each inner surface **79** having six sides and being elongated along a given direction. The shape of each aperture **74** is also symmetrical.

(32) In this embodiment, the apertures **74** of the accessory receiving base **60** are aligned in respective rows. Notably, at least two of the apertures **74** are aligned with each other in a lateral direction of the PWC **10**. In other embodiments, the apertures **74** may not be aligned with each other in the lateral direction of the PWC **10**.

(33) As shown in FIG. 5, in this embodiment, the accessory receiving base **60** also has two of the retractable anchor fixtures **80** that are configured to receive an anchor and/or a tongue fastener for securing accessories thereto. The anchor fixtures **80** may be omitted in other embodiments.

(34) In this embodiment, the accessory receiving base **60** has two attaching mounts **90** that are operable by a user to secure the accessory receiving base **60** to the deck **14**. As shown in FIGS. 5 and 6, each attaching mount **90** includes a handle **92** (FIG. 5) disposed on the upper side of the accessory receiving base **60** and a locking member **93** (FIG. 6) disposed on the lower side of the accessory receiving base **60**. The handle **92** is connected to the locking member **93** and is pivotable together with the locking member **93**. In this example, in order to secure the accessory receiving base **60** to the deck **14**, the locking member **93** of each attaching mount **90** is inserted through a corresponding aperture (not shown) defined by the deck **14** (similar to the apertures **74**) and the handle **92** is pivoted to cause the locking member **93** to pivot and be disposed in an orientation that prevents the locking member **93** from being extracted through the aperture.

(35) It is contemplated that the accessory receiving base **60** could be secured to the deck **14** differently in other embodiments (e.g., via bolts).

(36) While in this embodiment the accessory receiving base **60** is a distinct component that is connected to the deck **14**, it is contemplated that in other embodiments, the accessory receiving base **60** could be integrated as part of the deck **14**. For instance, the deck **14** could itself define one or more apertures **74**. Furthermore, in examples of other vehicles, the apertures **74** could be defined by a frame or a body of the vehicle.

(37) The strap anchors **100** will now be described in greater detail with reference to FIGS. 7 to 12. In this embodiment, each strap anchor **100** is identical and therefore a single one of the strap anchors **100** will be described herein. It is to be understood that the same description applies to the other strap anchors **100**.

(38) The strap anchor **100** has a mounting portion **102** and a pivoting portion **104** that is pivotably connected to the mounting portion **102**. In particular, the pivoting portion **104** is pivotable relative to the mounting portion **102** about a pivot axis PA (FIG. 9). The pivoting portion **104** has a strap-receiving part **138** that is configured for engaging a corresponding strap **55** therewith (FIG. 3). Notably, the strap **55** is tied to the accessory **50** in order to secure the accessory **50** to the PWC **10**. The mounting portion **102** includes an anchor base **106**, an anchor lock **108** and an outer stem **110** extending between the anchor base **106** and the anchor lock **108**. In this embodiment, the anchor base **106**, the anchor lock **108** and the outer stem **110** are a single-piece component (i.e., they are formed together and are made of a common continuous material). It is contemplated that, in other embodiments, one or more of the anchor base **106**, the anchor lock **108** and the outer stem **110** could be a distinct piece fastened or otherwise attached to the others.

(39) As shown in FIGS. 8 and 11, the anchor base **106** has a lower surface **119** which, in use, engages the upper surface **72** of the accessory receiving base **60**. As can be seen, in this example, the anchor base **106** has a generally elongated hexagonal shape and is generally elongated in a direction D1 (FIG. 11). Notably, the anchor base **106** extends from a proximal end **115** to a distal end **117** along the direction D1. It is contemplated that, in other embodiments, the anchor base **106** may have a shape different from a hexagonal shape. In this embodiment, the anchor base **106** has

two protruding bodies **114** spaced from each other and extending upwardly from the lower surface **119**. Each of the protruding bodies **114** defines a respective one of the proximal end **115** and the distal end **117**.

(40) As best shown in FIG. **8**, in this embodiment, the anchor base **106** has two locking tabs **130** protruding downwardly from the lower surface **119** of the anchor base **106**. The locking tabs **130** are configured to engage the inner surface **79** of the accessory receiving base **60** defining a corresponding one of the apertures **74**, namely the extremities of the elongated shape of the inner surface **79**, in order to help retain the strap anchor **100** in position when mounted to the accessory receiving base **60**.

(41) The anchor lock **108** is configured to be inserted through the corresponding aperture **74** defined by the accessory receiving base **60**. The anchor lock **108** is disposed at a lower end of the cylindrical outer stem **110**. In this embodiment, the anchor lock **108** has two cams **112** extending from the outer stem **110** in opposite directions from each other. As best shown in FIG. **11**, the anchor lock **108** has a generally hexagonal shape that is elongated in a direction **D2**. As can be seen, the direction **D2** is perpendicular to the direction **D1** along which the anchor base **106** is elongated. Thus, the anchor lock **108** is disposed perpendicularly to the anchor base **106**. This can be helpful to easily and securely mount the strap anchor **100** to the accessory receiving base **60**. It is contemplated that, in other embodiments, the direction **D2** may be generally perpendicular to the direction **D1** (e.g., within 30° of being perpendicular) or may be parallel. On its lower side, the anchor lock **108** defines a recess **123** through which an opening **111** (FIGS. **12**, **13**) defined by the outer stem **110** is accessible. As will be described in greater detail below, a fastener **170** (FIG. **12**) is insertable into the opening of the outer stem **110** through the recess **123** to connect the pivoting portion **104** to the mounting portion **102**. As shown in FIGS. **7** and **9**, in this embodiment, the cams **112** of the anchor lock **108** have upper tapered surfaces **120** (one of which is shown in FIGS. **7** and **9**) which may enhance engagement with the lower surface **75** of the accessory receiving base **60** to securely mount the strap anchor **100** to the accessory receiving base **60**. The upper tapered surfaces **120** may be omitted in other embodiments.

(42) As best shown in FIGS. **7** and **10**, the pivoting portion **104** has an upper base section **132** that is disposed on the anchor base **106**. The upper base section **132** supports a strap-receiving part **138** that is configured to receive the strap **55**. As can be seen, the upper base section **132** and the strap-receiving part **138** are disposed between the two protruding bodies **114**. In this embodiment, respective inner surfaces **135** of the two protruding bodies **114**, facing the upper base section **132** and thus the pivot axis **PA**, are curved to surround a curved outer surface of the upper base section **132** and of two side supports **134** of the strap-receiving part **138**. The inner surfaces **135** are spaced from the curved outer surface of the upper base section **132** and the side supports **134**. In this embodiment, the strap-receiving part **138** is a buckle, sometimes referred to as a ladder lock buckle although other adjustable buckles are contemplated, that includes the two side supports **134** extending upwardly from the upper base section **132** and two bars **140**, **142** that extend between the side supports **134**. The two bars **140**, **142** extend parallel to each other and allow the strap **55** to be wrapped thereabout, as shown schematically in FIG. **13**, in order to engage the strap **55** with the strap anchor **100**. In this example, the strap **55** is made of a fabric webbing (e.g., nylon webbing) and has a width of approximately 1 inch. Other configurations and sizes of the strap **55** are contemplated in other embodiments. As will be appreciated, in this embodiment, the strap-receiving part **138** is fixed to the strap anchor **100** and is also configured to adjust a position of an end of the strap **55** relative to the strap-receiving part **138**. Notably, the end of the strap **55** can be pulled to tighten the strap **55**, thereby adjusting a force exerted by the strap **55** on the accessory **50**. The strap **55** may also be engaged with the strap anchor **100** differently. For instance, as shown in FIG. **14**, the strap **55** could be engaged with the strap anchor **100** by looping the strap **55** underneath both bars **140**, **142** of the strap-receiving part **138**. In such an implementation, the strap **55** is engaged with the strap anchor **100** but the strap **55** is not tightened via its engagement with

the strap-receiving part **138**. Rather, as can be seen, in this case, one end of the strap **55** is affixed to the accessory **50** while another end of the strap **55** engages a buckle **77** (shown schematically in FIG. **14**) such as a ladder lock buckle (or any other suitable adjusting device such as a hook and loop fastener for example) to allow tightening of the strap **55**. The buckle **77** may also be fixed to the accessory **50** via another strap (not shown) that wraps about the accessory **50**.

(43) As shown in FIG. **12**, in this embodiment, the strap-receiving part **138** has an upper surface **149** that is generally aligned with respective upper surfaces **147** of the two protruding bodies **114**. As such, the strap-receiving part **138** does not protrude significantly from the surround protruding bodies **114**. This may allow the anchor **100** to be relative compact. In other embodiments, the upper surface **149** of the strap-receiving part **138** may be disposed significantly higher or lower than the upper surfaces **147** of the protruding bodies **114**. This may minimize the risk of interference between the strap **55** and the mounting portion **102**.

(44) It is contemplated that the strap-receiving part **138** could be configured differently in other embodiments. For instance, in some embodiments, the strap-receiving part **138** could be a hook and loop type fastener, a snap button fastener, or any other suitably type of fastener for connecting a strap. It is understood that the strap **55** could be modified to have a matching fastener to be secured to the strap-receiving part **138** accordingly.

(45) As shown in FIGS. **12** and **13**, a stem **150** of the pivoting portion **104** extends downward from the upper base section **132** and within the opening **111** of the outer stem **110**. The stem **150** may thus be referred as an inner stem **150**. The inner stem **150** extends along the pivot axis PA. The inner stem **150** has a lower end **156** and defines an inner cavity **154**. The fastener **170** (FIG. **12**) retains the inner stem **150** within the opening **111** to prevent the pivoting portion **104** from being disengaged from the mounting portion **102**. In particular, a threaded shank **174** of the fastener **170** extends into the inner cavity **154** of the inner stem **150** while a head **172** of the fastener **170** is disposed at the lower end **156** and is prevented from entering the inner cavity **154** as its size is greater than the diameter of the inner cavity **154**. In this embodiment, the fastener **170** is a self-tapping screw. Other types of fasteners are contemplated in other embodiments.

(46) As will be appreciated, the pivoting portion **104** has a significant rotational range of motion about the pivot axis PA. In particular, without the strap **55** engaged with the strap-receiving part **138** (i.e., without being limited by being tied to the accessory **50**), the pivoting portion **104** is free to pivot relative to the mounting portion **102** about the pivot axis PA by any given angle (i.e., 360° freedom of rotation about the pivot axis PA). This may be helpful to enable the strap **55** to extend in any desired direction relative to the mounting portion **102**.

(47) In order to removably fix the strap anchor **100** to the accessory receiving base **60**, the anchor lock **108** is inserted through the corresponding aperture **74** until the anchor base **106** engage the upper surface **72** of the accessory receiving base **60**. The mounting portion **102** is then turned relative to the accessory receiving base **60** about a turning axis TA (FIGS. **9**, **12**) that, in this embodiment, is coaxial with the pivot axis PA. As will be appreciated, the turning axis TA extends through the aperture **74** as the strap anchor **100** is being mounted to the accessory receiving base **60**. In this embodiment, the mounting portion **102** is turned by a quarter turn (i.e., 90°) about the turning axis TA. The angle may vary in other embodiments (e.g., the mounting portion **104** may be turned by any other angle that is not close to 180°). In use, with the strap **55** engaged with the strap-receiving part **138**, the pivoting portion **104** is configured to pivot relative to the mounting portion **102** which may allow the strap **55** to freely move to an orientation that is most suitable for the accessory **50** being secured to the PWC **10**.

(48) In this embodiment, while turning the mounting portion **102** about the turning axis TA, the upper tapered surfaces **120** of the anchor lock **108** engage the lower surface **75** (see FIG. **13**) of the accessory receiving base **60**, forming a ramp that progressively exerts a force between the upper tapered surfaces **120** and the lower surface **75** to securely affix the strap anchor **100** to the accessory receiving base **60**.

(49) Once the mounting portion **102** has been turned relative to the accessory receiving base **60**, as shown in FIG. **13**, the anchor lock **108** is disposed beneath the lower surface **75** of the accessory receiving base **60** and is oriented such that the anchor lock **108** is prevented from being extracted through the aperture **74**. In this embodiment, the strap **55** is tied to the accessory **50** prior to turning the strap anchor **100** about the turning axis TA. Nevertheless, it is contemplated that, in other embodiments, the strap **55** may be tied to the accessory **50** after turning the strap anchor **100** (i.e., after mounting the strap anchor **100** to the accessory receiving base **60**). As shown in FIGS. **1** to **3**, in this embodiment, each strap **55** is engaged with a corresponding strap anchor **100** is tied to one of a rear end **52** and a front end **54** of the accessory **50**. It is contemplated that the straps **55** may be secured to the accessory **50** differently in other embodiments. For instance, in some cases, the strap **55** could fasten the accessory **50** to the PWC **10** by overlying the accessory **50** and being engaged with two strap anchors **100** on opposite sides of the accessory **50**.

(50) Modifications and improvements to the above-described embodiments of the present technology may become apparent to those skilled in the art. The foregoing description is intended to be exemplary rather than limiting. The scope of the present technology is therefore intended to be limited solely by the scope of the appended claims.

Claims

1. A strap anchor for securing an accessory to a vehicle with a strap, the strap anchor comprising: a mounting portion comprising: an anchor base configured to engage an upper surface of an accessory receiving base connected to the vehicle, the anchor base being generally elongated; and an anchor lock connected to the anchor base, the anchor lock having a generally hexagonal shape that is elongated, the anchor lock being configured to be inserted through an aperture defined by the accessory receiving base; and a pivoting portion that is pivotably connected to the mounting portion about a pivot axis, the pivoting portion comprising a strap-receiving part configured for engaging the strap therewith, the strap anchor being configured to be removably fixed to the accessory receiving base by inserting the anchor lock through the aperture and then turning the mounting portion relative to the accessory receiving base such that the anchor lock is prevented from being extracted through the aperture.
2. The strap anchor of claim 1, wherein the anchor lock has at least one upper tapered surface configured to engage a lower surface of the accessory receiving base during turning of the mounting portion relative to the accessory receiving base.
3. The strap anchor of claim 1, wherein the strap anchor is configured to be fixed to the accessory receiving base by turning the mounting portion by a quarter turn about a turning axis extending, in use, through the aperture.
4. The strap anchor of claim 1, wherein the anchor base comprises at least one locking tab protruding downwardly from a lower base surface of the anchor base to engage an inner surface of the accessory retaining base defining the aperture.
5. The strap anchor of claim 1, wherein, without the strap engaged with the strap-receiving part, the pivoting portion is free to pivot relative to the mounting portion a full rotation about the pivot axis.
6. The strap anchor of claim 1, wherein: the anchor base comprises a first protruding body and a second protruding body spaced from each other; and part of the pivoting portion is disposed between the first protruding body and the second protruding body.
7. The strap anchor of claim 6, wherein: the pivoting portion is pivotable relative to the mounting portion about the pivot axis extending between the first and second protruding bodies; each of the first and second protruding bodies comprises an inner body surface facing the pivot axis; and the inner surfaces of the first and second protruding bodies are curved and spaced from a curved outer surface of the part of the pivoting portion.
8. The strap anchor of claim 6, wherein: each of the first and second protruding bodies has an upper

- body surface; and an upper surface of the part of the pivoting portion is generally aligned with the upper body surfaces of the first and second protruding bodies.
9. The strap anchor of claim 1, wherein the strap-receiving part is configured to adjust a position of an end of the strap relative to the strap-receiving part.
10. The strap anchor of claim 9, wherein the strap-receiving part is a ladder lock buckle.
11. The strap anchor of claim 10, wherein the ladder lock buckle comprises a first bar and a second bar extending generally parallel to each other.
12. The strap anchor of claim 1, wherein the pivoting portion is connected to the mounting portion by a fastener.
13. The strap anchor of claim 12, wherein: the mounting portion defines an opening; the pivoting portion comprises a stem extending within the opening of the mounting portion, the stem extending along the pivot axis; and the fastener retains the stem within the opening to prevent the pivoting portion from being disengaged from the mounting portion.
14. The strap anchor of claim 12, wherein the fastener comprises a fastener head, the fastener head being disposed at a lower end of the pivoting portion.
15. The strap anchor of claim 1, wherein the mounting portion further comprises an outer stem extending between the anchor base and the anchor lock.
16. The strap anchor of claim 15, wherein the anchor lock comprises two cams extending from the outer stem in opposite directions from each other.
17. The strap anchor of claim 1, wherein: the anchor base is elongated in a first direction; and the anchor lock is elongated in a second direction that is generally perpendicular to the first direction.
18. An anchor assembly for securing an accessory to a vehicle, comprising: the strap anchor of claim 1; and a strap engaged with the strap-receiving part, the strap being configured to be tied to the accessory in order to secure the accessory to the vehicle.
19. A vehicle comprising: an accessory receiving base defining at least one aperture having a generally elongated hexagonal shape; and at least one strap anchor according to claim 1 removably fixed to the accessory receiving base, the anchor lock of the at least one strap anchor being disposed beneath a lower surface of the accessory receiving base and being oriented to prevent extraction of the anchor lock through the at least one aperture.
20. A method for securing an accessory to a vehicle using a strap anchor, the strap anchor comprising a mounting portion and a pivoting portion that is pivotable relative to the mounting portion, the method comprising: inserting an anchor lock of the mounting portion of the strap anchor through an aperture of an accessory receiving base connected to the vehicle until an anchor base of the mounting portion engages an upper surface of the accessory receiving base; turning the strap anchor to orient the anchor lock such that the anchor lock is prevented from being extracted through the aperture; and tying a strap engaged with a strap-receiving part of the pivoting portion to the accessory.
21. The method of claim 20, further comprising adjusting a position of an end of the strap relative to the strap-receiving part in order to adjust a force exerted by the strap on the accessory.
22. The method of claim 20, wherein the strap is tied to the accessory prior to turning the strap anchor.
-