

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386435
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lorenz; Philip J.

Multi-input interface computer device and methods for using the same

Abstract

A multi-input interface device includes one or more units. The one or more units include one or more sensor units positioned within a portion of the one or more units and configured to detect a first relative movement of the one or more units. The multi-input interface device includes one or more auxiliary units. The one or more auxiliary units include one or more auxiliary sensor units positioned within a portion of the one or more auxiliary units and configured to detect a second relative movement of the one or more auxiliary units. The one or more units and the one or more auxiliary units are formed as separate units. The one or more units and the one or more auxiliary units are configured to be operated by a user.

Inventors:	Lorenz; Philip J. (Cedar Rapids, IA)
Applicant:	CODEK FOUNDRIES, INC. (Cedar Rapids, IA)
Family ID:	91248367
Assignee:	CODEK FOUNDRIES, INC. (Cedar Rapids, IA)
Appl. No.:	18/212579
Filed:	June 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240427432 A1	Dec. 26, 2024

Publication Classification

Int. Cl.:	G06F3/0354 (20130101)
U.S. Cl.:	

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4835528	12/1988	Flinchbaugh	N/A	N/A
6590563	12/2002	Oross	345/157	G06F 3/039
8054292	12/2010	Forde	345/163	G06F 3/03543
2006/0250353	12/2005	Yasutake	345/156	G06F 3/0383
2010/0097309	12/2009	Nishida et al.	N/A	N/A
2010/0315335	12/2009	Villar et al.	N/A	N/A
2011/0254769	12/2010	Delattre	N/A	N/A
2019/0302788	12/2018	Yabushita	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2524721	12/2011	EP	N/A

OTHER PUBLICATIONS

International Application No. PCT/US2024/026386, International Search Report and Written Opinion, mailed Jul. 26, 2024. cited by applicant

Primary Examiner: Lee; Nicholas J

Attorney, Agent or Firm: MARSHALL, GERSTEIN & BORUN LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure is related generally to an interface device for computer systems and other electronic devices.

BACKGROUND

(2) Most computers, e.g., laptop and desktops, receive input from a user via input devices such as a mouse and keyboard. Typically, a mouse allows a user to move the mouse along a surface, and the movement is translated into relative actions on the computer, e.g., move a cursor and select widgets on a graphical user interface (GUI) on a display screen. The mouse typically includes a trackball or optical sensor (located at a bottom side of the mouse) for translating the movement of the mouse into signals used by the computer. The mouse, however, is limited to a single movement input. That is, the user can make one type of movement, (e.g., move the mouse vertically, horizontally, diagonally, etc.) which is translated to movement on the display screen.

(3) The systems and methods disclosed herein provide solutions to these problems and can provide solutions to the ineffectiveness, insecurities, difficulties, inefficiencies, encumbrances and/or other

drawbacks of conventional techniques.

SUMMARY

(4) The present aspects can relate to, inter alia, a multi-input interface device operates an input device that enables a user to interface with a computer system or other electronic device in multiple ways, simultaneously, to expand input and increase efficiency of the user interactions.

(5) In one aspect, a multi-input interface device includes one or more units. The one or more units include one or more sensor units positioned within a portion of the one or more units and configured to detect a first relative movement of the one or more units. The multi-input interface device includes one or more auxiliary units. The one or more auxiliary units include one or more auxiliary sensor units positioned within a portion of the one or more auxiliary units and configured to detect a second relative movement of the one or more auxiliary units. The one or more units and the one or more auxiliary units are formed as separate units. The one or more units and the one or more auxiliary units are configured to be operated by a user.

(6) In another aspect, a method for detecting input includes determining an operating mode of a multi-input interface device comprising at least one base unit and at least one auxiliary unit. The operating mode defines input received from the at least one base unit and the at least one auxiliary unit, and the at least one base unit and the at least one auxiliary unit are separate units. The method also includes determining a first input received at the at least one base unit caused by a first interaction of a user with the base unit. Further, the method includes translating the first input into a first operation to be performed by an electronic device. Additionally, the method includes determining a second input received at the at least one auxiliary unit caused by a second interaction of the user with the auxiliary unit. The method includes translating the second input into a second operation to be performed by the electronic device.

(7) In another aspect, a tangible, non-transitory computer-readable medium stores instructions that, when executed by one or more processors of a computing device, cause the computing device to determine an operating mode of a multi-input interface device comprising at least one base unit and at least one auxiliary unit. The operating mode defines input received from the at least one base unit and the at least one auxiliary unit. The at least one base unit and the at least one auxiliary unit are separate units. The instructions, when executed by one or more processors of a computing device, cause the computing device to determine a base unit input received at the at least one base unit caused by a base unit interaction of a user with the at least one base unit; translate the base unit input into a first operation to be performed by an electronic device; determine an auxiliary unit input received at the at least one auxiliary unit caused by an auxiliary unit interaction of the user with the at least one auxiliary unit; and translate the auxiliary unit input into a second operation to be performed by the electronic device.

(8) Advantages will become more apparent to those of ordinary skill in the art from the following description of the preferred aspects, which have been shown and described by way of illustration. As will be realized, the present aspects can be capable of other and different aspects, and their details are capable of modification in various respects. Accordingly, the drawings and description are to be regarded as illustrative in nature and not as restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 depicts a top, perspective view of a multi-input interface device according to aspects of the present disclosure.

(2) FIG. 2 depicts a bottom, flat view of the multi-input interface device of FIG. 1 according to aspects of the present disclosure.

(3) FIG. 3 depicts a side, flat view of the multi-input interface device of FIG. 1 according to aspects

of the present disclosure.

(4) FIG. 4 depicts a top, perspective view of another multi-input interface device according to aspects of the present disclosure.

(5) FIG. 5 depicts a top, perspective view of the multi-input interface device of FIG. 4 according to aspects of the present disclosure.

(6) FIG. 6 depicts a block diagram of an environment including a multi-input interface device according to aspects of the present disclosure.

(7) FIG. 7 depicts a flow diagram of a process of operating a multi-input interface device according to aspects of the present disclosure.

(8) FIG. 8 depicts a top, perspective view of a multi-input interface device during operations according to aspects of the present disclosure.

(9) FIG. 9A-9F depict simplified views of a multi-input interface device operating with a computer device according to aspects of the present disclosure.

(10) The figures depict preferred embodiments for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the systems and methods illustrated herein can be employed without departing from the principles described herein.

DETAILED DESCRIPTION

(11) Overall, a multi-input interface device operates an input device that enables a user to interface with a computer system or other electronic device in multiple ways, simultaneously, to expand input and increase efficiency of the user interactions. The interface device can be designed to be used by a human user, for example the hand (left or right) of the human user. The interface device mechanically includes one or more separate units: a base unit and one or more auxiliary units. The base unit and the auxiliary unit are designed to be operated by a user. For example, the base unit and the auxiliary unit can be used by different portions of the hand of the user. In this example, the base unit can be configured as a palm unit, and the one or more auxiliary units can be configured as one or more finger units. The base unit can be constructed to accommodate a size and shape of a human palm. Each of the one or more finger units can be constructed to fit and rest one, two, three or four (or more) fingers of the human hand.

(12) The base unit (e.g., palm unit) includes at least one sensor, e.g., optical sensor, for detecting two-dimensional (2D) or three-dimensional (3D) movement along a surface, e.g., tabletop, and rotation of the base unit. The one or more auxiliary units (e.g., finger pad units) at least one sensor, e.g., optical sensor, for detecting 2D or 3D movement along a surface, e.g., tabletop, and rotation of the auxiliary unit. The multiple sensor data is then evaluated through software algorithms to allow for complex operations on the computer systems or electronic devices. For example, the interface device can allow coarse (e.g., movement of the base unit) and fine manipulation (e.g., auxiliary unit) of information on a display of a computer system (e.g., cursor, targeting sight, CAD manipulation, etc.) The interface device can also allow machine control or interface to vehicles (e.g., drone, robot, etc.) or other intentionally human controlled object.

(13) The base unit (e.g., palm unit) and the one or more auxiliary units (e.g., finger pads), each, include one or more input devices (e.g., buttons, scroll wheels, etc.) for additional input to the computer system or other electronic device. The configuration and operation of the one or more input devices can be configured to provide customizable input and control to the user.

(14) Reference will now be made in detail to the various embodiments and aspects of the present disclosure illustrated in the accompanying drawings. Wherever possible, the same or like reference numbers will be used throughout the drawings to refer to the same or like features. It should be noted that the drawings are in simplified form and are not drawn to precise scale. Certain terminology is used in the following description for convenience only and is not limiting.

Directional terms such as “top,” “bottom,” “left,” “right,” “above,” “below” and “diagonal,” “vertical”, “horizontal”, and derivatives thereof relate to a cartesian (x, y, z) coordinate system as

illustrated in FIGS. 1-5. The term “distal” means away from the center of a body. The term “proximal” means closer towards the center of a body and/or away from the “distal” end. The words “inwardly” and “outwardly” refer to directions toward and away from, respectively, the geometric center of the identified element and designated parts thereof. Such directional terms used in conjunction with the following description of the drawings should not be construed to limit the scope of the present disclosure in any manner not explicitly set forth.

(15) FIG. 1 depicts a top, perspective view of an example of an interface device **100** for multi-input control, in accordance with various aspects of the present disclosure. FIG. 2 depicts a bottom, flat view the interface device **100** of FIG. 1, in accordance with various aspects of the present disclosure. FIG. 3 depicts a side, flat view of the interface device **100** of FIG. 1, in accordance with various aspects of the present disclosure. While FIGS. 1, 2, and 3 illustrate various components that can be included in the interface device **100**, additional components can be added and components, which are illustrated, can be removed.

(16) As illustrated in FIG. 1, the interface device **100** includes a base unit **102** and one or more auxiliary units **104**. As illustrated, in one example, the interface device **100** can include one base unit **102** and one base unit **104**. The interface device **100** can also include multiple base units **102** and multiple auxiliary units **104**. For example, the interface device **100** can include one base unit **102** and two (2), three (3), etc. auxiliary units **104**. While the interface device **100** is describe below with a base unit **102** and **104**, the design, construction, and operations described herein are intended to include multiple base units **102** and/or multiple auxiliary units **104**.

(17) The base unit **102** and the auxiliary unit **104** are configured to receive input from a user. The input received by the base unit **102** and the auxiliary unit **104** can be received to control operations of one or more electronic devices. For example, the one or more electronic devices can include computer devices and systems (e.g., laptop computers, desktop computers, tablets, smart phones, server computers, thin clients, virtual reality headsets, and the like.) Likewise, the one or more electronic devices can include remotely-operated vehicles (e.g., robotic systems, drones, remotely controlled automobiles, remotely controlled aircraft, and the like).

(18) The base unit **102** and the auxiliary unit **104** can operate as independent units to provide independent input and/or control the one or more electronic devices. The base unit **102** and the auxiliary unit **104** can be moved, independently, on a supporting surface to provide independent input to the one or more electronic devices. For example, 2D or 3D movement of the base unit **102** relative to the supporting surface can be translated to first operations on the one or more electronic devices, and 2D or 3D movement of the auxiliary unit **104** relative to the supporting surface can be translated to second operations on the one or more electronic devices. The movement of the base unit **102** and the auxiliary unit **104** can be simultaneous or the movement of the base unit **102** and the auxiliary unit **104** can be sequential. For instance, movement of the base unit **102** can be translated to course movement of a cursor on a display screen of a computer system, and movement of the auxiliary unit **104** can be translated to fine manipulation the cursor on a display screen of a computer system.

(19) The movement of the base unit **102** and the auxiliary unit **104** can be simultaneous or the movement of the base unit **102** and the auxiliary unit **104** can be sequential. In an embodiment, the simultaneous movement of the base unit **102** and the auxiliary unit **104** can translate to one type of operation on the one or more electronic devices, and the sequential movement of the base unit **102** and the auxiliary unit **104** can translate to another type of operation on the one or more electronic devices.

(20) In embodiments, the base unit **102** is designed to be operated by a user. The base unit **102** includes a base housing **106** having a top surface **108** defined by a front **110**, rear **112**, right side **114**, and left side **116**. The base housing **106** can be constructed on any suitable material such as polymeric material (e.g., plastic) and/or composite material. In an example, the top surface **108** of the base unit **102** is sculpted to accommodate a first portion of a human hand and configured to be

controlled by the first portion of the human hand. For example, the top surface **108** of the base housing **106** can be sculpted to accommodate a palm and/or thumb of the human hand. For example, as illustrated in FIG. **1** and further in FIG. **3**, the top surface **108** of the base housing **106** can include a first sculpted portion **118** and a second sculpted portion **119**. The first sculpted portion **118** of the housing can form a rounded, convex protrusion in the top surface **108** of the base housing **106** that is sculpted to accommodate a palm of the human hand. The second sculpted portion **119** can form a concave trench form along the left side **116** of the base housing **106** that is sculpted to accommodate a thumb of the human hand. While the base unit **102** is described herein as being operated by a human hand, the base unit **102** can be operated by any part of a user.

Additionally, while the base unit **102** is described herein as being operated by human, the base unit **102** can be operated by any type of entity that can provide input to the base unit **102**, e.g., robot.

(21) FIGS. **1** and **3** illustrate the base housing **106** having the second sculpted portion **119** formed on the left side **116** of the base housing **106** thereby accommodating a right hand of a human user. The second sculpted portion **119** can be switched to the right side **114** of the base housing **106** thereby accommodating a left hand of a human user.

(22) The base unit **102** includes one or more input devices, for example, input devices **120**. The input devices **120** can be any type of input device that can be actuated by the user of the interface device **100** and/or receive input from the user to provide additional input to the base unit **102**. The input devices **120** can detect the actuation by the user using any type of method, for example, mechanical sensing of actuation, electrical sensing of actuation, thermal sensing of actuation, capacitive sensing of actuation, and combination thereof. For example, the input devices **120** can include one or more of a button, a scroll wheel, a toggle, a switch, a joystick, a digital pad, an audio input device (e.g., speaker and/or microphone), a touch pad, and the like. When one or more of the input devices **120** are actuated, a signal is generated that represents the actuation of the input devices **120**.

(23) The base unit **102** includes a base sensor unit **122** housed within the base housing **106**. The base sensor unit **122** is positioned within the base housing **106**. In an embodiment, the base unit **102** can include one base sensor unit **122**. In another embodiment, the base unit **102** can include multiple base sensor units **122**. In one example, the base sensor unit **122** is positioned within the base housing **106** so that a portion (e.g., window) of the base sensor unit **122** is open on the bottom surface **150** of the base unit **102**. The base sensor unit **122** operates to detect the movement of the base unit **102** relative to a reference surface. For example, the base sensor unit **122** can operate to detect the movement of the base unit **102** relative to a support structure, e.g., tabletop or desktop. As illustrated in FIG. **2**, the base sensor unit **122** can include one or more base sensors **126**. The base sensors **126** are configured to detect and measure translational movement of the base unit **102** in any of the x, y, z plane. The base sensors **126** are configured to detect and measure rotational movement of the base unit **102** about an axis, for example, an axis perpendicular to the bottom surface **150** of the base unit **102**. For example, the one or more base sensors **126** can include optical sensors, mechanical sensors, gyroscopic sensors, electro-magnetic induction sensors, accelerometers, thermal sensors, pressure sensors, capacitive sensors, and the like that measure movement (e.g., type of movement, direction of movement, velocity of movement, duration of movement, etc.) of the base unit **102**.

(24) In an embodiment, the base sensor unit **122** and sensors **126** can include an infrared (IR) sensor unit. The IR sensor unit operates based on the principle of reflection or interruption of IR radiation. The base sensor unit **122** can include a radiation emitter, for example, an IR light emitting diode (LED) that emits IR radiation in the range of 850 to 950 nanometers. The sensors **126** can include has a sensor that detects IR radiation, for example, a photodiode or other optical sensor. When the base unit **102** is moved on a reference surface, the emitted IR radiation contacts the reference surface, and the IR radiation is either reflected off the reference surface or interrupted if there is a gap or change in the reference surface. The sensor **126** detects the reflected or

interrupted IR radiation. The base sensor unit **122** includes hardware and/or software to process the information received from the sensor **126**. The hardware and/or software can calculate movement data (e.g., type of movement, direction of movement, velocity of movement, duration of movement, etc.) representing movement of the base unit **102** based on changes in the reflected or interrupted IR radiation. While the above describes the base sensor unit **122** as an IR sensor, this is one example of a sensor. The base unit sensor **122** can include any type and number of sensors that measure input to the base unit **102**.

(25) The base unit **102** includes a base communication unit **124**. The base communication unit **124** includes hardware and software to communicate with one or more electronic devices and transmit the input received at the base unit **102** to one or more electronic devices. For example, the base communication unit **124** can transmit the movement data and signals generated by the actuation of the input devices **120** to one or more electronic devices. The base unit **102** can also communicate with the auxiliary unit **104** using the base communication unit **124**. In an embodiment, the base communication unit **124** can include a hardwire electrical connection, e.g., universal serial bus (USB) cable, to transmit signals and data. In an embodiment, the base communication unit **124** can include a wireless communication unit for wirelessly transmitting the signals and data using wireless protocols such as BLUETOOTH, WiFi, or any other radio frequency protocol.

(26) The base unit **102** also includes a base power source housing **152** positioned within the base housing **106**. The base power source housing **152** can be a compartment that contains one or more power sources for the base unit **102**. Examples of power sources can include batteries, capacitors, and the like. In an embodiment, the base unit **102** can receive power via the base communication unit **124**, whether wired or wireless. The base unit **102** can also include one or more anti-friction pads **154** positioned on the bottom surface **150** of the base housing **106**. The anti-friction pads **154** can be constructed on any material (e.g., felt) that reduces the friction between bottom surface **150** of the base housing **106** and the reference surface. In an embodiment, the base unit **102** can receive power from an external source, whether wired or wireless.

(27) The auxiliary unit **104** includes an auxiliary housing **130** having a top surface **132** defined by a front **134**, a rear **135**, a right side **136**, and a left side **137**. The base housing **106** can be constructed on any suitable material such as polymeric material (e.g., plastic) and/or composite material. In one example, the top surface **132** of the auxiliary housing **130** is configured to be controlled by a second portion of the human hand. For example, the top surface **132** of the auxiliary housing **130** can be controlled by one or more fingers of the human hand. While the auxiliary unit **104** is described herein as being operated by a human hand, the auxiliary unit **104** can be operated by any part of a user. Additionally, while the auxiliary unit **104** is described herein as being operated by human, the auxiliary unit **104** can be operated by any type of entity that can provide input to the auxiliary unit **104**, e.g., robot.

(28) The auxiliary unit **104** can include one or more input devices, for example, a first input device **140**, a second input device **141**, a third input device **142**, and a fourth input device **143**. The first input device **140**, the second input device **141**, the third input device **142**, and the fourth input device **143** can be any types of input devices that can be actuated by the user of the interface device **100** and/or receive input from a user. The first input device **140**, the second input device **141**, the third input device **142**, and the fourth input device **143** can detect the actuation by the user using any type of method, for example, mechanical sensing of actuation, electrical sensing of actuation, thermal sensing of actuation, capacitive sensing of actuation, and combination thereof. For example, the input devices **120** can include one or more of a button, a scroll wheel, a toggle, a switch, a joystick, a digital pad, an audio input device (e.g., speaker and/or microphone), touch pad, and the like. When one or more of the input devices **120** are actuated, a signal is generated that represents the actuation of the input devices **120**.

(29) In one example, one or more portions of the auxiliary housing **130** can be sculpted to accommodate the second portions of the human hand, e.g., human fingers. In an embodiment, the

first input device **140**, the second input device **141**, and/or the third input device **142** can be sculpted to accommodate the second portions of the human hand, e.g., human fingers. For example, the first input device **140**, the second input device **141**, and/or the third input device **142** can be constructed having a concave indentation relative to the top surface **132** of the auxiliary housing **130**. The concave indentation can be open on the rear **135** of the auxiliary housing **130**, which is adjacent to the front **110** of the base housing **106**. While FIG. **1** illustrates the auxiliary unit **104** as having three input devices that are sculpted, the auxiliary unit **104** can include additional input devices or fewer input devices. Additionally, one or more of the first input device **140**, the second input device **141**, and/or the third input device **142** can be replaced with a sculpted portion in the top surface **132** of the to accommodate a finger of the human hand, e.g., a concave indentation relative to the top surface **132**. While FIG. **1** illustrates one auxiliary unit **104**, the interface device **100** can include multiple auxiliary units **104**. For example, the interface device **100** can include two (2) auxiliary units **104**, three (3) of the auxiliary unit **104**, etc. that can be controlled by one or more fingers of a hand of a user.

(30) The auxiliary unit **104** includes an auxiliary sensor unit **144** housed within the auxiliary housing **130**. The auxiliary sensor unit **144** is positioned within the auxiliary housing **130**. In an embodiment, the auxiliary unit **104** can include one auxiliary sensor unit **144**. In another embodiment, the auxiliary unit **104** can include multiple auxiliary sensor unit **144**. In one example, the auxiliary sensor unit **144** can be positioned within the auxiliary housing **130** so that a portion (e.g., window) of the auxiliary sensor unit **144** is open on a bottom surface **170** of the auxiliary unit **104**. The auxiliary sensor unit **144** operates to detect the movement of the auxiliary unit **104** relative to a reference surface. For example, the auxiliary sensor unit **144** can operate to detect the movement of the auxiliary unit **104** relative to a support structure, e.g., tabletop or desktop. As illustrated in FIG. **2**, the auxiliary sensor unit **144** can include one or more auxiliary sensors **148**. The auxiliary sensors **148** are configured detect and measure translational movement of the auxiliary unit **104** in any of the x, y, z plane. The auxiliary sensors **148** are configured to detect and measure rotational movement of the auxiliary unit **104** about an axis, for example, an axis perpendicular to the bottom surface **170** of the auxiliary unit **104**. For example, the one or more auxiliary sensors **148** can include optical sensors, mechanical sensors, gyroscopic sensors, electromagnetic induction sensors, accelerometers, thermal sensors, pressure sensors, capacitive sensors, and the like that measure movement (e.g., type of movement, direction of movement, velocity of movement, duration of movement, etc.) of the auxiliary unit **104**. In an embodiment, the auxiliary sensor unit **144** and sensors **148** can include an IR sensor unit as described above. While the above describes the one or more auxiliary sensors **148** as an IR sensor, this is one example of a sensor. The auxiliary unit **104** can include any type and number of sensors that measure input to the auxiliary unit **104**.

(31) The auxiliary unit **104** includes an auxiliary communication unit **146**. The auxiliary communication unit **146** includes hardware and software to communicate with one or more electronic devices and transmit the input received at the auxiliary unit **104** to one or more electronic devices. For example, the auxiliary communication unit **146** can transmit the movement data and signals generated by the actuation of the input devices of the auxiliary unit **104** to one or more electronic devices. The auxiliary unit **104** can also communicate with the base unit **102** using the auxiliary communication unit **146**. In an embodiment, the auxiliary communication unit **146** can include a hardwire electrical connection, e.g., USB cable, to transmits signals and data. In an embodiment, the auxiliary communication unit **146** can include a wireless communication unit for wireless transmitting the signals and data using wireless protocols such as BLUETOOTH, WiFi, or any other radio frequency protocol.

(32) The auxiliary unit **104** also includes an auxiliary power source housing **172** positioned within the auxiliary housing **130**. The auxiliary power source housing **172** can be a compartment that contains one or more power sources for the auxiliary unit **104**. Examples of power sources can

include batteries, capacitors, and the like. In an embodiment, the auxiliary unit **104** can receive power via the auxiliary communication unit **146**, whether wired or wireless. The auxiliary unit **104** can also include one or more anti-friction pads **174** positioned on the bottom surface **170** of the auxiliary housing **130**. The anti-friction pads **174** can be constructed on any material (e.g., felt) that reduces the friction between bottom surface **170** of the auxiliary housing **130** and the reference surface. In an embodiment, the base unit **102** can receive power from an external source, whether wired or wireless.

(33) In embodiments and examples described herein, the interface device **100**, e.g., the base unit **102** and auxiliary unit **104** can be constructed to any dimensions and specifications as required by the intended user of the interface device. For example, the base unit **102** and auxiliary unit **104** can be constructed to dimensions and specifications that enable the base unit **102** and auxiliary unit **104** to be used and operated by a hand of a user, e.g., human hand. In other examples, the base unit **102** and auxiliary unit **104** can be constructed to dimensions and specifications that enable the base unit **102** and auxiliary unit **104** to be used and operated by other parts of a user, e.g., elbow, head, foot, etc.

(34) FIG. 4 depicts a top, perspective view of another example of the interface device **100** for multi-input control, in accordance with various aspects of the present disclosure. FIG. 3 depicts a bottom, flat view of the interface device **100** of FIG. 4, in accordance with various aspects of the present disclosure. While FIGS. 4 and 5 illustrate various components that can be included in the interface device **100**, additional components can be added and components, which are illustrated, can be removed.

(35) As illustrated in FIG. 4, the interface device **100** includes a connector bar **300**. The connector bar **300** couples the base unit **102** to the auxiliary unit **104**. The connector bar **300** can be constructed of any type of material such as metal, metal alloy, a polymeric material (e.g., plastic) or composite material. In an embodiment, the connector bar **300** can be constructed having a rectangular bar shape. While the connector bar **300** is described as having a “bar” shape, the connector bar **300** can be constructed as having any type of other shape, for example, a rod shape. Additionally, while FIG. 4 illustrates the interface device **100** as having a single connector bar **300**, the interface device **100** can include multiple connector bars **300** that couple the base unit **102** to the auxiliary unit **104**.

(36) In an embodiment, the connector bar **300** enables the base unit **102** to the auxiliary unit **104** to operate as a single unit. That is, the connector bar **300** provides a rigid connection between the base unit **102** to the auxiliary unit **104** so that, if the base unit **102** is moved, the auxiliary unit **104** correspondingly moves and vice versa. When coupled by the connector bar **300**, the interface device **100** can operate in an absolute mode. The absolute mode allows the interface device **100** to operate as a single unit, similar to a computer mouse, with the additional input devices, the first input device **140**, the second input device **141**, the third input device **142**, and the fourth input device **143**, of the auxiliary unit **104**. In the absolute mode, the interface device **100** can determine the movement data using the base sensor unit **122** and/or the auxiliary sensor unit **144**.

(37) In an embodiment, the connector bar **300** enables the base unit **102** to the auxiliary unit **104** to operate in combination to provide additional input. That is, the connector bar **300** provides a semi-rigid and/or elastic connection between the base unit **102** to the auxiliary unit **104** so that the base unit **102** to the auxiliary unit **104** can be independently within limits based on the rigidity and/or elasticity of the connector bar **300**. Additionally, the resistance and elasticity provided by the connector bar **300** can operate as additional input to the interface unit **100**. For example, the connector bar **300** can be constructed of a semi-rigid, elastic material, e.g., spring material, that provides resistance when the base unit **102** to the auxiliary unit **104** are moved relative to one another. The semi-rigid, elastic material of the connector bar **300** can also provide a return force, e.g., when a force is applied to the base unit **102** to the auxiliary unit **104** and then removed, the base unit **102** and the auxiliary unit **104** can return to an initial position based on the elasticity of the connector bar **300**.

(38) When coupled by the connector bar **300** having semi-rigid and/or elastic properties, the interface device **100** can operate in a return-to-center mode. The return-to-center mode allows the resistance and elasticity provided by the connector bar **300** to operate as additional input to the interface unit **100**. For example, when a force is applied to the base unit **102** to the auxiliary unit **104** and then removed, the base unit **102** and the auxiliary unit **104** can return to an initial position based on the elasticity of the connector bar **300**. The return to the initial position of the base unit **102** and the auxiliary unit **104** relative to one another can correspond to an input to an electronic device. For example, this return can cause a cursor on a display device to return to a center of the display device.

(39) When coupled by the connector bar **300** having semi-rigid and/or elastic properties, the interface device **100** can operate in a resistive mode. The resistive mode allows the resistance and elasticity provided by the connector bar **300** to operate as additional input to the interface unit **100**. For example, the base unit **102** and/or the auxiliary unit **104** can include one or more sensors that measure the force applied to the connector bar **300**, the deformation of the connector bar **300**, and the like. These measurements can be translated into input on an electronic device.

(40) As illustrated in FIG. 5, the connector bar **300** can be coupled to the auxiliary unit **104** by an auxiliary connector **302**. The auxiliary connector **302** can allow the connector bar **300** to be attached and removed from the auxiliary unit **104**. The connector bar **300** can be coupled to the base unit **102** by a base connector **304**. The base connector **304** can allow the connector bar **300** to be attached and removed from the base unit **102**. The auxiliary connector **302** and/or base connector **304** can include one or more sensors that detect when the connector bar is coupled to the auxiliary connector **302** and the base connector **304**. For example, the one or more sensors can include a mechanical, electrical, and/or electro-mechanical switch or latch that actuates when the connector bar is coupled to the auxiliary connector **302** and/or base connector **304**. The one or more sensors can provide a signal that is used to place the interface device **100** in different modes, e.g., absolute mode, return-to-center mode, and/or resistance mode.

(41) In an embodiment, the base unit **102** can include a bar storage **306** formed in the base housing **106**. The bar storage **306** can receive and store the connector bar **300** when not in use to connect the base unit **102** and the auxiliary unit **104**. For example, the bar storage **306** can be constructed as a cavity within the base housing **106**. In another example, the bar storage **306** can be constructed as a trench that holds the connector bar **300** flush with or recessed from the bottom surface **150** of the base housing **106**.

(42) FIG. 6 depicts an example of a computing environment **600** in which the interface device **100** can be used, in accordance with various aspects of the present disclosure. While FIG. 6 illustrates various components, systems, and entities that can be included in the computing environment **600**, additionally components, systems, and entities can be added and components, systems, and entities, which are illustrated, can be removed.

(43) As illustrated in FIG. 6, the computing environment **600** can include a computer system **602** that communicates with the interface device **100**. The computer system **602** can represent one or more computer devices and/or electronic devices that are communicating with and receiving input from the interface device **100**. The computer system **602** can include a processor **610**, a communication interface **612**, and a memory **614**. The processor **610** can include any suitable number of processors and/or processor types. The processor **610** can include one or more suitable processors (e.g., central processing units (CPUs) and/or graphics processing units (GPUs)). The processor **610** can be connected to the memory **614** via a computer bus (not depicted) responsible for transmitting electronic data, data packets, or otherwise electronic signals to and from the processor **610** and memory **614** in order to implement or perform the machine-readable instructions, methods, processes, elements or limitations, as illustrated, depicted, or described for the various flowcharts, illustrations, diagrams, figures, and/or other disclosure herein. The processor **610** can interface with the memory **614** via a computer bus to execute an operating

system (OS) **640** and/or computing instructions contained therein, and/or to access other services/aspects. For example, the processor **610** can interface with the memory **614** via the computer bus to create, read, update, delete, or otherwise access or interact with the data stored in the memory **614** and/or a storage devices (internal and/or external), such as a database.

(44) The memory **614** can include one or more forms of volatile and/or non-volatile, fixed and/or removable memory, such as read-only memory (ROM), electronic programmable read-only memory (EPROM), random access memory (RAM), erasable electronic programmable read-only memory (EEPROM), and/or other hard drives, flash memory, MicroSD cards, and others. The memory **614** can store an interface module **620**, as described below. The memory **614** can store the OS **640** (e.g., Microsoft Windows, Linux, UNIX, MacOS, etc.) capable of facilitating the functionalities, apps, methods, or other software as discussed herein. The memory **614** can also include one or more software programs **642** that can be executed on the computer system **602**.

(45) In general, a software program, computer program, computer based product, application, or code (e.g., the model(s), such as artificial intelligence (AI) and/or machine learning (ML) models, or other computing instructions described herein) can be stored on a computer usable storage medium, or tangible, non-transitory computer-readable medium (e.g., standard random access memory (RAM), an optical disc, a universal serial bus (USB) drive, or the like) having such computer-readable program code or computer instructions embodied therein, wherein the computer-readable program code or computer instructions can be installed on or otherwise adapted to be executed by the processor **610** (e.g., working in connection with the respective operating system in memory **614**) to facilitate, implement, or perform the machine readable instructions, methods, processes, elements or limitations, as illustrated, depicted, or described for the various flowcharts, illustrations, diagrams, figures, and/or other disclosure herein. In this regard, the program code can be implemented in any desired program language, and can be implemented as machine code, assembly code, byte code, interpretable source code or the like (e.g., via Golang, Python, C, C++, C#, Objective-C, Java, Scala, ActionScript, JavaScript, HTML, CSS, XML, etc.).

(46) A database, which can communicate with the computer system **602**, can be a relational database, such as Oracle, DB2, MySQL, a NoSQL based database, such as MongoDB, or another suitable database. The database can be local to the computer system **602**. The database can be remote from the computer system **602** and communicate, for example, via a network **606**.

(47) The network **606** can be a single communication network or can include multiple communication networks of one or more types (e.g., one or more wired and/or wireless local area networks (LANs), and/or one or more wired and/or wireless wide area networks (WANs) such as the internet). For example, the network **606** can include a wireless cellular service (e.g., 4G, 5G, 6G, etc.). In one aspect, the network **606** can include a cellular base station, such as cell tower(s), communicating to the computer system **602** via wired/wireless communications based on any one or more of various mobile phone standards, including NMT, GSM, CDMA, UMTS, LTE, 5G, 6G, or the like. Additionally or alternatively, the network **606** can comprise one or more routers, wireless switches, or other such wireless connection points communicating to the components of the computer system **602** via wireless communications based on any one or more of various wireless standards, including by non-limiting example, IEEE 802.11a/b/g/n/ac/ax/be (WIFI), Bluetooth, and/or the like. In some embodiments, the computer system **602** can connect to the network **606** via the communications interface **612**.

(48) As described herein and in an aspect, the functionality of the computer system **602** can be embodied in one or more servers. The one or more servers can perform the functionalities as part of a cloud network or can otherwise communicate with other hardware or software components within one or more cloud computing environments to send, retrieve, or otherwise analyze data or information described herein. For example, in certain aspects of the present techniques, the computer system **602** can comprise an on-premise computing environment, a multi-cloud computing environment, a public cloud computing environment, a private cloud computing

environment, and/or a hybrid cloud computing environment. For example, an entity (e.g., a business) providing a chatbot to enable remediation provider and/or insurance provider notification can host one or more services in a public cloud computing environment (e.g., Alibaba Cloud, Amazon Web Services (AWS), Google Cloud, IBM Cloud, Microsoft Azure, etc.). The public cloud computing environment can be a traditional off-premise cloud (i.e., not physically hosted at a location owned/controlled by the business). Alternatively, or in addition, aspects of the public cloud can be hosted on-premise at a location owned/controlled by a structure owner or lessee. The public cloud can be partitioned using visualization and multi-tenancy techniques and can include one or more infrastructure-as-a-service (IaaS) and/or platform-as-a-service (PaaS) services.

(49) The computer environment **600** can also include a remote device **650**. The remote device **650** can be any type of electronic device that can communicate with the interface device **100** and receive input from the interface device **100**. For example, the remote device **650** can include remotely-operated vehicles (e.g., robotic systems, drones, remotely controlled automobiles, remotely controlled aircraft, and the like.)

(50) In some embodiments, the interface device **100** can communicate with the computer system **602** and/or the remote device **650** via the network **606**. For example, the interface device **100** can communicate with the network **606** via a connection **630**. The computer system **602** can communicate with the network **606** via a connection **634**. The remote device **650** can communicate with the network **606** via a connection **638**. In some embodiments, the interface device **100** can directly communicate with the computer system **602** via a direct connection **632**. In some embodiments, the interface device **100** can directly communicate with the remote device via a direct connection **636**.

(51) To translate the input received from the interface device **100**, the interface device **100**, the computer system **602**, and/or the remote device can include an interface module **620**. The interface module **620** can include a set of computer-executable implementing the communication with the interface device **100** and the translation of input. The interface module **620** can include the necessary logic, commands, and algorithms to translate the input received at the interface device **100** into operations. In some embodiments, the memory **614** can store a copy of the interface module **620**. In some embodiments, the interface device **100** can store a copy of the interface module **620**. In some embodiments, the remote device **650** can store a copy of the interface module **620**.

(52) The interface module **620** can include a translation table and/or library that translates the input data received from the interface device **100**, e.g., movement data of the base unit **102** and/or auxiliary unit **104**, rotational data of the base unit **102** and/or auxiliary unit **104**, input data for the input devices of the base unit **102** and/or auxiliary unit **104**, into an operation to be performed by the computer system **602** and/or the remote device **650**. The interface module **620** can store one or more translation tables and/or libraries, where each translation table and/or library correspond to a software program **642** or a remote device **650**. The interface module **620** can include logic, commands, and algorithms that allow a user to configure how the input is translated into custom operations performed by the computer system **602** and/or the remote device **650**.

(53) Tables 1 illustrates a simplified version of a translation table for controlling and interfacing with objects displayed on a display of the computer system **602**, when the interface device is operating in independent mode. Tables 2 illustrates a simplified version of a translation table for controlling and interfacing with objects displayed on a display of the computer system **602**, when the interface device is operating in absolute mode. Tables 1 and 2 illustrates a simplified versions in plain text for illustration proposes and can include additional input and operations. One skilled in the art will realize that the translation table and/or library can be implemented in computer languages and/or instructions that are readable by the computer system **602** and/or the remote device **650**. Additionally, any of the operations listed in Tables 1 and 2 can be predefined or customized by a user of the interface device **100**.

(54) TABLE-US-00001 TABLE 1 Input Data Operation Example Operation Translational Movement Operation Course Movement of a of Base Unit 102 A Display Cursor Translational Movement Operation Fine Movement of a of Auxiliary Unit 104 B Display Cursor Selection of input Operation Selection of a displayed device 120 C object Actuation of input device Operation Selection of a displayed 120 + Translational D object and movement Movement of Base Unit of the displayed object 102 Actuation of input device Operation Selection of a displayed 120 + Rotational E object and rotation of the Movement of Base Unit displayed object 102 Actuation of input device Operation Generation of a selection 142 + Translational F box and increase/ Movement of Auxiliary decrease of the Unit 104 selection box Actuation of input device Operation Generation of a selection 140 + Rotational G circle and increase/decrease Movement of Auxiliary of the selection circle Unit 104 Actuation of input device Operation Temporally place interface 120 + Actuation of input H device in absolute mode device 142 + Translational and Course Movement of a Movement of Base Unit Display Cursor 102 and/or Auxiliary Unit 104

(55) TABLE-US-00002 TABLE 2 Input Data Operation Example Operation Translational Movement of Operation AA Course Movement of a Base Unit 102 and Auxiliary Display Cursor Unit 104 Selection of input Operation BB Selection of a displayed device 120 object Actuation of input device Operation CC Selection of a displayed 120 + Translational object and movement Movement of Base Unit 102 of the displayed object and Auxiliary Unit 104 Actuation of input device Operation DD Selection of a displayed 120 + Rotational Movement object and rotation of the of Base Unit 102 and displayed object Auxiliary Unit 104 Actuation of input device Operation EE Utilize input data from 142 + Translational Auxiliary Unit 104 and Movement of Auxiliary Fine Movement of a Unit 104 Display Cursor Actuation of input device Operation FF Sticky Selection of a 120 + Actuation of input displayed object and device 142 + Translational movement of the Movement of Base Unit 102 displayed object. and/or Auxiliary Unit 104

(56) In some embodiments, the interface module **620**, the OS **640**, and/or the software programs **642** can include one or more natural language processing (NLP) modules for communicating with the computer system **602**. For example, the interface device **100** can include a microphone for receiving audio input. The NLP modules comprising a set of computer-executable instructions implementing NLP, natural language understanding (NLU) and/or natural language generator (NLG) functionality. The NLP modules can be responsible for transforming the user input (e.g., unstructured conversational input such as speech or text) to an interpretable format. The NLP modules can include an NLU to understand the intended meaning of utterances and/or prompts, among other things. The NLP modules can include an NLG, which can provide text summarization, machine translation, and/or dialog where structured data is transformed into natural conversational language (i.e., unstructured) for output to the user.

(57) In some embodiments, the interface module **620**, the OS **640**, and/or the software programs **642** can include and/or communicate with voice bots or chatbots for communicating with the computer system **602**. For example, the interface device **100** can include a microphone for receiving audio input. Voice bots or chatbots discussed herein can be configured to utilize AI and/or ML techniques. For instance, the voice bot or chatbot can be a ChatGPT chatbot. The voice bots or chatbots can generate human-like responses to text inputs and engage in conversations with users of the computer system **602**. The voice bot or chatbot can employ supervised or unsupervised machine learning techniques, which can be followed or used in conjunction with reinforced or reinforcement learning techniques. The voice bot or chatbot can employ the techniques utilized for ChatGPT. The voice bot or chatbot can deliver various types of output for user consumption in certain embodiments, such as verbal or audible output, a dialogue output, text or textual output (such as presented on a computer or mobile device screen or display), visual or graphical output, and/or other types of outputs. The voice bot or chat bot can be programmed to simulate human conversation, interact with users, understand their needs, and recommend an appropriate line of action with minimal and/or no human intervention, among other things. This can include providing

the best response of any query that it receives and/or asking follow-up questions.

(58) Aspects described herein can include automated machine learning to determine data risk levels, identify relevant data risk factors, and evaluate the data security factors. Although the methods described elsewhere herein may not directly mention machine learning techniques, such methods can be read to include such machine learning for any determination or processing of data that can be accomplished using such techniques. In some embodiments, such machine-learning techniques can be implemented automatically upon occurrence of certain events or upon certain conditions being met. Use of machine learning techniques, as described herein, can begin with training a machine learning program, or such techniques can begin with a previously trained machine learning program.

(59) Additionally or alternatively, the machine learning programs can be trained by inputting sample data sets or certain data into the programs, such as data security factors discussed herein. The machine learning programs can utilize deep learning algorithms that are primarily focused on pattern recognition and can be trained after processing multiple examples. The machine learning programs can include Bayesian program learning (BPL), voice recognition and synthesis, image or object recognition, optical character recognition, and/or natural language processing, either individually or in combination. The machine learning programs can also include natural language processing, semantic analysis, automatic reasoning, and/or machine learning.

(60) In supervised machine learning, a processing element can be provided with example inputs and their associated outputs, and can seek to discover a general rule that maps inputs to outputs, so that when subsequent novel inputs are provided the processing element can, based upon the discovered rule, accurately predict the correct or a preferred output. In unsupervised machine learning, the processing element can be required to find its own structure in unlabeled example inputs. These techniques can be followed by reinforced or reinforcement learning techniques.

(61) It will be understood that the above disclosure is one example and does not necessarily describe every possible embodiment. As such, it will be further understood that alternate embodiments can include fewer, alternate, and/or additional steps or elements.

(62) While FIG. 6 shows only one computer system **602**, it is understood the computer system **602** can be composed of multiple computer system and devices that are in remote communication, for example, via the network **606**.

(63) FIG. 7 is a flow diagram of an exemplary method **700** for operating a multi-input interface device. The method **700** can be implemented by hardware and/or software contained within a multi-input interface device, e.g., the interface device **100**. The method **700** can be implemented by one or more processors of a computing system such as the computer system **602**, which is communicating with a multi-input interface device, e.g., the interface device **100**. Alternatively or additionally, the method **700** can be implemented by one or more processors of a distributed system, which is communicating with a multi-input interface device, e.g., the interface device **100**. The method implemented by one or more remote electronic devices, e.g., remote device **650**, which is communicating with a multi-input interface device, e.g., the interface device **100**.

(64) At block **702**, a connection is initiated with an interface device. The interface device **100** can be coupled to an electronic device such as the computer system **602** or the remote device **650**. For example, the interface device **100** can be directly connected to the computer system **602** by the connection **632**, or the interface device **100** can be directly connected to the remote device by the connection **636**. In another example, the interface device **100** can communicate with the computer system **602** via the network **606**, or the interface device **100** can communicate with the remote device **650** via the network **606**.

(65) At block **704**, the operating mode of the interface device is determined. For example, the interface device **100** operate in two modes: an independent mode and an absolute mode. In independent mode, the base unit **102** and the auxiliary unit **104** can be operated to provide independent inputs to the computer system **602** and/or the remote device **650**. In the absolute mode,

the base unit **102** and the auxiliary unit **104** can operate as a single unit to provide inputs to the computer system **602** and/or the remote device **650**.

(66) If the interface device is operating in independent mode, at block **706**, movement data for a base unit is determined. The movement data can include 2D and/or 3D movement of the base unit relative to a surface. For example, as illustrated in FIG. **8**, the base unit **102** can experience translational movement **802**, i.e., movement in the x, y, z directions, based on a user control of the base unit **102** using a portion of a hand (e.g., palm and thumb.) The movement data can be detected by the base sensor unit **122** and transmitted to the computer system **602** and/or the remote device **650**.

(67) At block **708**, rotational data for the base unit is determined. For example, as illustrated in FIG. **8**, the base unit **102** can also experience rotational movement **804**, i.e., rotational about an axis extending in the z-direction, based on the user control of the base unit **102** using the same portion of the hand (e.g., palm and thumb.) The rotational data can be detected by the base sensor unit **122** and transmitted to the computer system **602** and/or the remote device **650**.

(68) At block **710**, movement data for the auxiliary unit is determined. In the independent mode, the user can also provide independent input using the auxiliary unit **104** using a different portion of the hand (e.g., one or more fingers of the hand.) For example, as illustrated in FIG. **8**, the auxiliary unit **104** can experience translational movement **806**, i.e., movement in the x, y, z directions, based on a user control of the auxiliary unit **104** using the different portion of the hand (e.g., one or more fingers of the hand.) The movement data can be detected by the auxiliary sensor unit **144** and transmitted to the computer system **602** and/or the remote device **650**.

(69) At block **712**, rotational data for the auxiliary unit is determined. For example, as illustrated in FIG. **8**, the auxiliary unit **104** can also experience rotational movement **808**, i.e., rotation about an axis extending in the z-direction, based on the user control of the auxiliary unit **104** using the different portion of the hand (e.g., one or more fingers of the hand.) The rotational data can be detected by the auxiliary sensor unit **144** and transmitted to the computer system **602** and/or the remote device **650**.

(70) At block **714**, additional input data is determined for the base unit and/or auxiliary unit. For example, the user can provide additional input by actuating one or more of the input devices of the base unit **102** and/or the auxiliary unit **104** (e.g., the input devices **120**, the first input device **140**, the second input device **141**, the third input device **142**, and the fourth input device **143**.) The determination of input data in blocks **708**, **710**, **712**, and **714** can occur simultaneously or sequentially, in any order, depending on the input by the user. For example, a user can move the base unit **102** and auxiliary unit **104**, simultaneous. As such, the detection of the movement can be determined simultaneously. In another example, a user can move the base unit **102** while actuating an input device of the auxiliary unit **104**.

(71) At block **715**, the movement data, the rotational data, and/or additional input data is translated into operations. For example, the movement data, the rotational data, and/or additional input data of the base unit **102** and the auxiliary unit **104** can be translated by the interface module **620** into operations to be performed by the computer system **602** and/or the remote device **650**. Once the operation is determined, the computer system **602** and/or the remote device **650** can perform the operations.

(72) For example, as illustrated in FIGS. **9A-9E**, the user can be using the interface device **100** to control the movement of a robot **904** having an arm **906** and vision system **908** that is displayed on a display **902**. In this example, the movement and operation of the robot **904** can be controlled by input provided to the interface device **100**. In an embodiment, the robot **904** can be a virtual robot that is generated by one or more software programs executing on the computer system **102**. In an embodiment, the robot **904** can be a virtual representation of a real-world robot operating as remote device **650**.

(73) As illustrated in FIG. **9A**, a user can perform base unit translational movement **910** on the base

unit **102** in the x-direction and y-direction, and the movement data can be captured by the base unit **102**. The movement data can then be translated into movement operations of the robot **904**, e.g., robot forward movement **912**, robot back movement **914**, robot left movement **916**, and robot right movement **918**.

(74) As illustrated in FIG. **9B**, a user can perform base unit rotation **920** on the base unit **102**, and the rotational data can be captured by the base unit **102**. The rotational data can then be translated into movement operations of the robot **904**, e.g., robot clockwise rotational **922** and robot counter-clockwise rotational **924**.

(75) As illustrated in FIG. **9C**, the movement and/or rotational of the base unit **102** can also be translated into a different operation based on the actuation of an input device of the base unit **102**. For example, a user can actuate the input device **120** (e.g., button) of the base unit **102** while performing the base unit rotation **920** on the base unit **102**, and the rotational data can be captured by the base unit **102**. Because the input device **120** has been actuated during the base unit rotation **920**, the interface module **620** can translate the base unit rotation **920** into a different operation for the robot **904**, e.g., clockwise rotational **926** of the vision system **908** or counter-clockwise rotational **928** of the vision system **908**.

(76) As illustrated in FIG. **9D**, the independent movement of the auxiliary unit **104** can correspond to different operations of the robot **904**, e.g., movement of the robot arm. For example, a user can perform auxiliary unit translational movement **930** on the auxiliary unit **104** in the x-direction and y-direction, and the movement data can be captured by the auxiliary unit **104**. The movement data can then be translated into movement operations of the robot **906**, e.g., robot arm forward movement **932**, robot arm back movement **934**, robot arm left movement **936**, and robot arm right movement **938**.

(77) As illustrated in FIG. **9E**, the independent rotational of the auxiliary unit **104** can correspond to different operations of the robot **904**, e.g., rotational of the robot arm. For example, a user can perform auxiliary unit rotation **940** on the auxiliary unit **104**, and the rotational data can be captured by the auxiliary unit **104**. The rotational data can then be translated into rotational operations of the robot arm **906**, e.g., robot arm clockwise rotational **942** and robot arm counter-clockwise rotational **944**.

(78) As illustrated in FIG. **9F**, the rotational and/or movement of the auxiliary unit **104** can also be translated into a different operation based on the actuation of an input device of the auxiliary unit **104**. For example, a user can actuate the input device (e.g., button) of the auxiliary unit **104** while performing the auxiliary unit rotation **940** on the auxiliary unit **104**, and the rotational data can be captured by the auxiliary unit **104**. Because the input device has been actuated during the auxiliary unit rotation **940**, the interface module **620** can translate the auxiliary unit rotation **940** into a different operation for the robot **904**, e.g., clockwise rotational **946** of the vision system **908** or counter-clockwise rotational **948** of the vision system **908**.

(79) Returning to FIG. **7**, at block **716**, it is determined if the operating mode has changed. If the operating mode has not changed, the method **700** returns to block **706** and further input is monitored while the interface device is in independent mode. If the mode has changed, the method can return to block **704** to determine the new operating mode.

(80) At block **720**, if the interface device is operating the absolute mode, movement data for the base unit and/or the auxiliary unit is determined. For example, in absolute mode, the interface device **100** operates as a single unit. In an embodiment, the movement data can be captured by the base unit **102** or captured by the auxiliary unit **104**. In an embodiment, the movement data can be captured by both the base unit **102** and the auxiliary unit **104**, the movement data can be combined to represent movement data of the interface device as a single unit.

(81) For example, the base unit **102** and the auxiliary unit **104**, as a single unit, can experience translational movement, i.e., movement in the x, y, z directions, based on a user control of the base unit **102** and the auxiliary unit **104** (coupled together) using the hand. The movement data can be

detected by the base sensor unit **122** and/or the auxiliary sensor unit **144** and transmitted to the computer system **602** and/or the remote device **650**.

(82) At block **722**, rotational data for the base unit and/or the auxiliary unit is determined. For example, the base unit **102** and the auxiliary unit **104**, as a single unit, can experience rotational movement, i.e., movement about an axis, based on a user control of the base unit **102** and the auxiliary unit **104** (coupled together) using the hand. The movement data can be detected by the base sensor unit **122** and/or the auxiliary sensor unit **144** and transmitted to the computer system **602** and/or the remote device **650**.

(83) At block **724**, additional input data is determined for the base unit and/or auxiliary unit. For example, the user can provide additional input by actuating one or more of the input devices of the base unit **102** and/or the auxiliary unit **104** (e.g., the input devices **120**, the first input device **140**, the second input device **141**, the third input device **142**, and the fourth input device **143**.) The determination of input data in blocks **720**, **722**, and **724** can occur simultaneously or sequentially, in any order, depending on the input by the user. For example, a user can move the base unit **102** and auxiliary unit **104**, as a single unit, while actuating an input device of the auxiliary unit **104** and/or the base unit **102**. In another example, the user can first move the base unit **102** and auxiliary unit **104**, as a single unit, and then actuate an input device of the auxiliary unit **104** and/or the base unit **102**.

(84) At block **725**, the movement data, the rotational data, and/or additional input data is translated into operations. For example, the movement data, the rotational data, and/or additional input data of the base unit **102** and auxiliary unit **104**, as a single unit, can be translated by the interface module **620** into operations to be performed by the computer system **602** and/or the remote device **650**. Once the operation is determined, the computer system **602** and/or the remote device **650** can perform the operations.

(85) At block **726**, it is determined if the operating mode has changed. If the operating mode has not changed, the method **700** returns to block **720** and further input is monitored while the interface device is in absolute mode. If the mode has changed, the method can return to block **704** to determine the new operating mode.

(86) The method **700** above is described as detecting two (2) modes of an interface device, e.g., interface device **100**. The method **700** can also be modified to detect any number of modes, additional or fewer. Additionally, while the method **700** indicates that an interface device, e.g., interface device **100**, operates in a single mode, the interface device, e.g., interface device **100** can operate in multiple modes simultaneously, which are determined in the method. For example, as described herein, the method **700** at block **704** can determine one or more modes from multiple modes, e.g., independent mode, absolute mode, return-to-center mode, resistance mode, etc. In any modes determined, the method **700** can determine translation movement, rotational movement, and/or additional input to the interface device **100** and translate the input to operation on an electronic device.

(87) Aspects of the present disclosure can include the following examples of embodiments.

(88) Embodiment 1 includes a multi-input interface device. The multi-input device includes one or more units comprising one or more sensor units positioned within a portion of the one or more units and configured to detect a first relative movement of the one or more units; and one or more auxiliary units comprising one or more auxiliary sensor units positioned within a portion of the one or more auxiliary units and configured to detect a second relative movement of the one or more auxiliary units. The one or more units and the one or more auxiliary units are formed as separate units, and the one or more units and the one or more auxiliary units are configured to be operated by a user.

(89) Embodiment 2 includes the multi-input interface device of embodiment 1, wherein each of the one or more units comprise a base housing configured to house the one or more sensor units, wherein the base housing is structured to allow control by a first portion of the user; and each of the

one or more auxiliary units comprise an auxiliary housing configured to house the one or more auxiliary sensor units, wherein the auxiliary housing is structured to allow control by a second portion of the user.

(90) Embodiment 3 includes the multi-input interface device of embodiment 2, wherein the first portion of the user is different from the second portion of the user.

(91) Embodiment 4 includes the multi-input interface device of embodiment 2, wherein the one or more units comprise one or more input devices; and the one or more auxiliary units comprise one or more auxiliary input devices forming a portion of a top surface of the auxiliary housing.

(92) Embodiment 5 includes the multi-input interface device of embodiment 1, wherein the one or more sensor units are configured to detect one or more of translation movement of the one or more units and rotational movement of the one or more units; and the one or more auxiliary sensor units are configured to detect one or more of translation movement of the one or more auxiliary units and rotational movement of the one or more auxiliary units.

(93) Embodiment 6 includes the multi-input interface device of embodiment 1, further comprising a connector bar configured to be coupled to the one or more units and the one or more auxiliary units.

(94) Embodiment 7 includes the multi-input interface device of embodiment 6, wherein the connector bar is formed of a rigid material and causes the one or more units and the one or more auxiliary units to operate a single unit.

(95) Embodiment 8 includes the multi-input interface device of embodiment 6, wherein the connector bar is formed of a semi-rigid, elastic material that limits movement of the one or more units and the one or more auxiliary units relative to one another.

(96) Embodiment 9 includes the multi-input interface device of embodiment 8, further comprising one or more connector bar sensor units configured to measure physical properties of the connector bar during the movement of the one or more units and the one or more auxiliary units relative to one another.

(97) Embodiment 10 includes a method for detecting input. The method includes determining an operating mode of a multi-input interface device comprising at least one base unit and at least one auxiliary unit, wherein the operating mode defines input received from the at least one base unit and the at least one auxiliary unit, and the at least one base unit and the at least one auxiliary unit are separate units. The method includes determining a first input received at the at least one base unit caused by a first interaction of a user with the at least one base unit; translating the first input into a first operation to be performed by an electronic device; determining a second input received at the at least one auxiliary unit caused by a second interaction of the user with the at least one auxiliary unit; and translating the second input into a second operation to be performed by the electronic device.

(98) Embodiment 11 includes the method of embodiment 10, the method further comprising: determining a new operating mode of the multi-input interface device; determining a third input received at least one of the at least one base unit or the at least one auxiliary unit; and translating the third input into a third operation to be performed by the electronic device based at least partially on the new operating mode.

(99) Embodiment 12 includes the method of embodiment 11, wherein the new operating mode defines the at least one base unit and the at least one auxiliary unit operating as a single unit.

(100) Embodiment 13 includes the method of embodiment 10, wherein the first interaction comprises one or more of translational movement of the at least one base unit, rotation of the at least one base unit about a first axis, and actuation of an input device of the at least one base unit; and the second interaction comprises one or more of translational movement of the at least one auxiliary unit, rotation of the at least one auxiliary unit about a second axis, and actuation of an input device of the at least one auxiliary unit.

(101) Embodiment 14 includes the method of embodiment 10, wherein the electronic device

comprises a computer system; and the first operation and the second operation cause a change in objects displayed on a display of the computer system.

(102) Embodiment 15 includes the method of embodiment 14, wherein the first operation is movement of a cursor at a first rate, and the second operation is movement of the cursor at a second rate.

(103) Embodiment 16 includes the method of embodiment 10, wherein the electronic device comprises one or more of a real-world vehicles, a virtual vehicle, and a simulated vehicle; and the first operation and the second operation cause control actions in the one or more of the real-world vehicle, the virtual vehicle, and the simulated vehicle.

(104) Embodiment 17 includes a tangible, non-transitory computer-readable medium storing instructions that, when executed by one or more processors of a computing device, cause the computing device to determine an operating mode of a multi-input interface device comprising at least one base unit and at least one auxiliary unit, wherein the operating mode defines input received from the at least one base unit and the at least one auxiliary unit, and determine a base unit input received at the at least one base unit caused by a base unit interaction of a user with the at least one base unit. The instructions, when executed by one or more processors of a computing device, cause the computing device to: translate the base unit input into a first operation to be performed by an electronic device; determine an auxiliary unit input received at the at least one auxiliary unit caused by an auxiliary unit interaction of the user with the at least one auxiliary unit; and translate the auxiliary unit input into a second operation to be performed by the electronic device.

(105) Embodiment 18 includes the tangible, non-transitory computer-readable medium of embodiment 17, wherein the instructions, when executed by the one or more processors, cause the computer device to determine a new operating mode of the multi-input interface device, the new operating mode defining the at least one base unit and the at least one auxiliary unit operating as a single unit; determine a new input received at least one of the at least one base unit or the at least one auxiliary unit; and translate the new input into a new operation to be performed by the electronic device.

(106) Embodiment 19 includes the tangible, non-transitory computer-readable medium of embodiment 17, wherein: the base unit interaction comprises one or more of translational movement of the at least one base unit, rotation of the at least one base unit about a first axis, and actuation of an input device of the at least one base unit; and the auxiliary unit interaction comprises one or more of translational movement of the at least one auxiliary unit in the plane, rotation of the at least one auxiliary unit about a second axis, and actuation of an input device of the at least one auxiliary unit.

(107) Embodiment 20 includes the tangible, non-transitory computer-readable medium of embodiment 17, wherein the first operation and the second operation cause a change in objects displayed on a display of the computer device.

(108) The following considerations also apply to the foregoing discussion. Throughout this specification, plural instances can implement operations or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations can be performed concurrently, and nothing requires that the operations be performed in the order illustrated. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

(109) “About” as used herein when referring to a measurable value such as an amount, a temporal duration, a measurement, and the like, is meant to encompass variations of $\pm 20\%$, $\pm 10\%$, $\pm 5\%$, $\pm 1\%$, or $\pm 0.1\%$ from the specified value, as such variations are appropriate or government by manufacturing tolerances.

(110) Unless specifically stated otherwise, discussions herein using words such as “processing,” “computing,” “calculating,” “determining,” “presenting,” “displaying,” or the like can refer to

actions or processes of a machine (e.g., a computer) that manipulates or transforms data represented as physical (e.g., electronic, magnetic, or optical) quantities within one or more memories (e.g., volatile memory, non-volatile memory, or a combination thereof), registers, or other machine components that receive, store, transmit, or display information.

(111) As used herein any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

(112) As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to only those elements but can include other elements not expressly listed or inherent to such process, method, article, or apparatus. Further, unless expressly stated to the contrary, “or” refers to an inclusive or and not to an exclusive or.

(113) In addition, use of “a” or “an” is employed to describe elements and components of the embodiments herein. This is done merely for convenience and to give a general sense of the invention. This description should be read to include one or at least one and the singular also can include the plural unless it is obvious that it is meant otherwise.

(114) Upon reading this disclosure, those of skill in the art will appreciate still additional alternative structural and functional designs for providing feedback to owners of properties, through the principles disclosed herein. Therefore, while particular embodiments and applications have been illustrated and described, it is to be understood that the disclosed embodiments are not limited to the precise construction and components disclosed herein. Various modifications, changes, and variations, which will be apparent to those skilled in the art, can be made in the arrangement, operation and details of the method and apparatus disclosed herein without departing from the spirit and scope defined in the appended claims.

(115) The patent claims at the end of this patent application are not intended to be construed under 35 U.S.C. § 112(f) unless traditional means-plus-function language is expressly recited, such as “means for” or “step for” language being explicitly recited in the claim(s). The systems and methods described herein are directed to an improvement to computer functionality and improve the functioning of conventional computers.

Claims

1. A multi-input interface device, comprising: a unit comprising: a sensor unit positioned within a portion of the unit and configured to detect a first relative movement of the unit; and a single auxiliary unit comprising: an auxiliary sensor unit positioned within a portion of the single auxiliary unit and configured to detect a second relative movement of the single auxiliary unit, wherein: the unit and the single auxiliary unit are formed as separate units, and the unit and the single auxiliary unit are configured to be operated by a user, the unit comprises a base housing configured to house the sensor unit, wherein the base housing is structured to allow control by a first portion of the user, the single auxiliary unit comprises an auxiliary housing configured to house the auxiliary sensor unit, wherein the auxiliary housing is structured to allow control by a second portion of the user, and at least two auxiliary input devices formed in the auxiliary housing, wherein each of the at least two auxiliary input devices is configured for mechanical actuation by the second portion of the user.
2. The multi-input interface device of claim 1, wherein the first portion of the user is different from the second portion of the user.
3. The multi-input interface device of claim 1, wherein: the unit comprises an input device; and the at least two auxiliary input devices of the single auxiliary unit form a portion of a top surface of the

auxiliary housing.

4. The multi-input interface device of claim 1, wherein: the sensor unit is configured to detect one or more of translation movement of the unit and rotational movement of the unit; and the auxiliary sensor unit is configured to detect one or more of translation movement of the single auxiliary unit and rotational movement of the single auxiliary unit.

5. The multi-input interface device of claim 1, further comprising: a connector bar configured to be coupled to the unit and the single auxiliary unit.

6. The multi-input interface device of claim 5, wherein the connector bar is formed of a rigid material and causes the unit and the single auxiliary unit to operate as a single unit.

7. The multi-input interface device of claim 5, wherein the connector bar is formed of a semi-rigid, elastic material that limits movement of the unit and the single auxiliary unit relative to one another.

8. The multi-input interface device of claim 7, further comprising: a connector bar sensor unit configured to measure physical properties of the connector bar during the movement of the unit and the single auxiliary unit relative to one another.

9. A method for detecting input, the method comprising: determining an operating mode of a multi-input interface device comprising a base unit and a single auxiliary unit, wherein: the operating mode defines input received from the base unit and the single auxiliary unit, the base unit and the single auxiliary unit are separate units, and at least two auxiliary input devices are formed in an auxiliary housing of the single auxiliary unit, wherein each of the at least two auxiliary input devices is configured for mechanical actuation by a user; determining a first input received at the base unit caused by a first interaction of the user with the base unit; translating the first input into a first operation to be performed by an electronic device; determining a second input received at the single auxiliary unit caused by a second interaction of the user with the single auxiliary unit; and translating the second input into a second operation to be performed by the electronic device.

10. The method of claim 9, the method further comprising: determining a new operating mode of the multi-input interface device; determining a third input received at at least one of the base unit or the single auxiliary unit; and translating the third input into a third operation to be performed by the electronic device based at least partially on the new operating mode.

11. The method of claim 10, wherein the new operating mode defines the base unit and the single auxiliary unit operating as a single unit.

12. The method of claim 9, wherein: the first interaction comprises one or more of translational movement of the base unit, rotation of the base unit about a first axis, and actuation of an input device of the base unit; and the second interaction comprises one or more of translational movement of the single auxiliary unit, rotation of the single auxiliary unit about a second axis, and actuation of one of the at least two auxiliary input devices.

13. The method of claim 9, wherein: the electronic device comprises a computer system; and the first operation and the second operation cause a change in objects displayed on a display of the computer system.

14. The method of claim 13, wherein the first operation is movement of a cursor at a first rate, and the second operation is movement of the cursor at a second rate.

15. The method of claim 9, wherein: the electronic device comprises one or more of a real-world vehicle, a virtual vehicle, and a simulated vehicle; and the first operation and the second operation cause control actions in the one or more of the real-world vehicle, the virtual vehicle, and the simulated vehicle.

16. A tangible, non-transitory computer-readable medium storing instructions that, when executed by one or more processors of a computing device, cause the computing device to: determine an operating mode of a multi-input interface device comprising a base unit and a single auxiliary unit, wherein: the operating mode defines input received from the base unit and the single auxiliary unit, the base unit and the single auxiliary unit are separate units, and at least two auxiliary input

devices are formed in an auxiliary housing of the single auxiliary unit, wherein each of the at least two auxiliary input devices is configured for mechanical actuation by a user; determine a base unit input received at the base unit caused by a base unit interaction of the user with the base unit; translate the base unit input into a first operation to be performed by an electronic device; determine an auxiliary unit input received at the single auxiliary unit caused by an auxiliary unit interaction of the user with the single auxiliary unit; and translate the auxiliary unit input into a second operation to be performed by the electronic device.

17. The tangible, non-transitory computer-readable medium of claim 16, wherein the instructions, when executed by the one or more processors, cause the computer device to: determine a new operating mode of the multi-input interface device, the new operating mode defining the base unit and the single auxiliary unit operating as a single unit; determine a new input received at at least one of the base unit or the single auxiliary unit; and translate the new input into a new operation to be performed by the electronic device.

18. The tangible, non-transitory computer-readable medium of claim 16, wherein: the base unit interaction comprises one or more of translational movement of the base unit, rotation of the base unit about a first axis, and actuation of an input device of the base unit; and the auxiliary unit interaction comprises one or more of translational movement of the single auxiliary unit in the plane, rotation of the single auxiliary unit about a second axis, and actuation of one of the at least two auxiliary input devices.

19. The tangible, non-transitory computer-readable medium of claim 16, wherein the first operation and the second operation cause a change in objects displayed on a display of the computer device.
