

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278997

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

GUPTA; Vaibhav et al.

A CONTROL PANEL FOR FIRE ALARM SYSTEMS AND A METHOD FOR UPDATING THE CONFIGURATION INFORMATION

Abstract

A control panel for a fire alarm system and a method for updating configuration information of a control panel are disclosed. The control panel includes a communication module for short-range communication with a portable electronic device and a processing circuit for updating configuration information using data packets received from the portable electronic device. The processing circuit receives the data packets via short-range communication with the portable electronic device. The control panel comprises a data transfer region, wherein the communication module is configured to establish short-range communication with the portable electronic device when the portable electronic device is proximal to the data transfer region.

Inventors: GUPTA; Vaibhav (Bareilly, IN), TIWARI; Sumit (Hadapsar, IN), DESHPANDE; Praveen (Atul Nagar, IN), TIWARI; Shishir (Dhanori, IN)

Applicant: Johnson Controls Tyco IP Holdings LLP (Boca Raton, FL)

Family ID: 80050580

Appl. No.: 18/268119

Filed (or PCT Filed): December 26, 2021

PCT No.: PCT/IN2021/051206

Foreign Application Priority Data

IN 202011056504

Dec. 26, 2020

Publication Classification

Int. Cl.: G08B29/16 (20060101); **G08B17/00** (20060101); **G08B25/10** (20060101); **G08B29/22** (20060101)

U.S. Cl.:

CPC G08B29/16 (20130101); **G08B25/10** (20130101); **G08B29/22** (20130101); G08B17/00 (20130101)

Background/Summary

FIELD

[0001] The present disclosure relates to the field of control panels for fire alarm systems.

BACKGROUND

[0002] This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present disclosure and are described below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be noted that these statements are to be read in this light, and not as admissions of prior art.

[0003] Fire alarm systems are often installed within commercial, residential, or governmental buildings. Examples of these buildings include hospitals, warehouses, schools, shopping malls, government buildings, and casinos, to list a few examples. The fire alarm systems typically include control panel(s), initiating device(s), and annunciator(s). Signals from initiating devices are monitored by the control panel, such as a fire alarm control panel (“FACP”). The FACP, upon sensing an alarm condition, sends commands to one or more annunciators to alert occupants in one section of the building, in multiple sections of the building, or in all sections of the building. Annunciators can output a visual notification, an audible notification, or both.

[0004] Typically, to read and/or update configuration of the control panel, a technician is required to establish a wired connection between a laptop and the control panel for reading and/or updating configuration. The process additionally requires the technician to access the control panel for establishing the connection.

[0005] Moreover, the technician is required to carry his/her laptop, cables, and connectors to site. The entire process, therefore, becomes time consuming and tedious which is not desired.

[0006] There is, therefore, felt a need to provide a control panel for a fire alarm system that eliminates the requirement of establishing wired connection for communicating with portable electronic devices thereby overcoming the above-mentioned drawbacks.

OBJECTS

[0007] Some of the objects of the present disclosure, which at least one embodiment herein satisfies, are as follows:

[0008] An object of the present disclosure is to provide a control panel for a fire alarm system.

[0009] Another object of the present disclosure is to provide a control panel that eliminates the requirement of establishing wired connection with a portable electronic device.

[0010] Still another object of the present disclosure is to provide a control panel that can be wirelessly connected to a portable electronic device.

[0011] Yet another object of the present disclosure is to provide a control panel that is provided with Near Field Communication (NFC) capabilities.

[0012] Still another object of the present disclosure is to provide a control panel that is cost effective.

[0013] Yet another object of the present disclosure is to provide a control panel that can be read

and/or updated wirelessly by portable electronic devices.

[0014] Other objects and advantages of the present disclosure will be more apparent from the following description, which is not intended to limit the scope of the present disclosure.

SUMMARY

[0015] The present disclosure describes a control panel for a fire alarm system. In one aspect of the present disclosure, the control panel comprises a communication module and a data transfer region. The communication module facilitates short-range communication with a portable electronic device. The communication module is configured to establish short-range communication with the portable electronic device when the portable electronic device is proximal to the data transfer region. The communication module includes a near field communication (NFC) unit.

[0016] In some embodiments, the data transfer region is an opening provided on a housing of the control panel. In some other embodiments, the data transfer region is defined via markings on a housing of the control panel.

[0017] The control panel further comprises a processing circuit configured to store configuration information pertaining to the fire alarm system, to receive one or more data packets from the portable electronic device via short-range wireless communication, and to update at least a part of the configuration information using the one or more data packets.

[0018] The processing circuit is configured to authenticate a user of the portable electronic device prior to receiving the one or more data packets. In some embodiments, the processing circuit receives one or more user credentials of the user via a user interface of the control panel for authentication.

[0019] The processing circuit is configured to validate the one or more data packets received from the portable electronic device prior to updating the configuration information. The processing circuit falls back to historical configuration information upon detecting failure in updating the configuration information.

[0020] In another aspect of the present disclosure, a method is described. The method comprises establishing a short-range wireless communication with a portable electronic device, receiving one or more data packets from the portable electronic device, and updating at least a part of configuration information using the one or more data packets.

[0021] The method further comprises a step of authenticating a user of the portable electronic device prior to establishing the short-range wireless communication. A near field communication (NFC) unit is activated upon authenticating a user of the portable electronic device. The short-range wireless communication between the portable electronic device and a communication module is established when the portable electronic device is proximal to a data transfer region of a control panel.

[0022] In some embodiments, the method further comprises validating the one or more data packets received from the portable electronic device prior to updating the configuration information.

Description

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWING

[0023] Various objects, aspects, features, and advantages of the disclosure will become more apparent and better understood by referring to the detailed description taken in conjunction with the accompanying drawing, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.

[0024] A control panel for a fire alarm system, of the present disclosure, will now be described with the help of the accompanying drawing, in which:

[0025] FIG. 1 is a drawing of a building equipped with a building management system (BMS), according to some embodiments.

[0026] FIG. 2 is a block diagram of a BMS that serves the building of FIG. 1, according to some embodiments.

[0027] FIG. 3 is a block diagram of a BMS controller which can be used in the BMS of FIG. 2, according to some embodiments.

[0028] FIG. 4 is another block diagram of the BMS that serves the building of FIG. 1, according to some embodiments.

[0029] FIG. 5 is a block diagram of a fire alarm system, according to some embodiments of the present disclosure.

[0030] FIG. 6 is a schematic view of a housing of a control panel, according to some embodiments.

[0031] FIG. 7 is a schematic view of a door of the housing of FIG. 6, according to some embodiments.

[0032] FIG. 8 is another schematic view of the housing, according to some embodiments.

[0033] FIG. 9 is block diagram of the control panel of the fire alarm system of FIG. 5 in communication with portable electronic device(s), according to some embodiments.

[0034] FIG. 10 is a block diagram of a memory of a processing circuit of the control panel shown in FIG. 9.

[0035] FIGS. 11-14 are schematic views of a user interface of the control panel of FIG. 9.

[0036] FIG. 15 is a flowchart depicting steps of a method of the present disclosure, according to some embodiments.

DETAILED DESCRIPTION

[0037] One or more specific embodiments will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be noted that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be noted that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0038] When introducing elements of various embodiments of the present disclosure, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be noted that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features.

[0039] Before turning to the Figures, it should be understood that the disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology is for the purpose of description only and should not be regarded as limiting.

Building and Building Management System

[0040] Referring now to FIG. 1, a perspective view of a building 10 is shown, according to an exemplary embodiment. A BMS serves building 10. The BMS for building 10 may include any number or type of devices that serve building 10. For example, each floor may include one or more security devices, video surveillance cameras, fire detectors, smoke detectors, lighting systems, HVAC systems, or other building systems or devices. In modern BMSs, BMS devices can exist on different networks within the building (e.g., one or more wireless networks, one or more wired networks, etc.) and yet serve the same building space or control loop. For example, BMS devices

may be connected to different communications networks or field controllers even if the devices serve the same area (e.g., floor, conference room, building zone, tenant area, etc.) or purpose (e.g., security, ventilation, cooling, heating, etc.).

[0041] BMS devices may collectively or individually be referred to as building equipment.

Building equipment may include any number or type of BMS devices within or around building **10**. For example, building equipment may include controllers, chillers, rooftop units, fire and security systems, elevator systems, thermostats, lighting, serviceable equipment (e.g., vending machines), and/or any other type of equipment that can be used to control, automate, or otherwise contribute to an environment, state, or condition of building **10**. The terms “BMS devices,” “BMS device” and “building equipment” are used interchangeably throughout this disclosure.

[0042] Referring now to FIG. 2, a block diagram of a BMS **11** for building **10** is shown, according to an exemplary embodiment. BMS **11** is shown to include a plurality of BMS subsystems **20-26**. Each BMS subsystem **20-26** is connected to a plurality of BMS devices and makes data points for varying connected devices available to upstream BMS controller **12**. Additionally, BMS subsystems **20-26** may encompass other lower-level subsystems. For example, an HVAC system may be broken down further as “HVAC system A,” “HVAC system B,” etc. In some buildings, multiple HVAC systems or subsystems may exist in parallel and may not be a part of the same HVAC system **20**.

[0043] As shown in FIG. 2, BMS **11** may include a HVAC system **20**. HVAC system **20** may control HVAC operations building **10**. HVAC system **20** is shown to include a lower-level HVAC system **42** (named “HVAC system A”). HVAC system **42** may control HVAC operations for a specific floor or zone of building **10**. HVAC system **42** may be connected to air handling units (AHUs) **32, 34** (named “AHU A” and “AHU B,” respectively, in BMS **11**). AHU **32** may serve variable air volume (VAV) boxes **38, 40** (named “VAV_3” and “VAV_4” in BMS **11**). Likewise, AHU **34** may serve VAV boxes **36** and **110** (named “VAV_2” and “VAV_1”). HVAC system **42** may also include chiller **30** (named “Chiller A” in BMS **11**). Chiller **30** may provide chilled fluid to AHU **32** and/or to AHU **34**. HVAC system **42** may receive data (i.e., BMS inputs such as temperature sensor readings, damper positions, temperature setpoints, etc.) from AHUs **32, 34**. HVAC system **42** may provide such BMS inputs to HVAC system **20** and on to middleware **14** and BMS controller **12**. Similarly, other BMS subsystems may receive inputs from other building devices or objects and provide the received inputs to BMS controller **12** (e.g., via middleware **14**).

[0044] Middleware **14** may include services that allow interoperable communication to, from, or between disparate BMS subsystems **20-26** of BMS **11** (e.g., HVAC systems from different manufacturers, HVAC systems that communicate according to different protocols, security/fire systems, IT resources, door access systems, etc.). Middleware **14** may be, for example, an EnNet server sold by Johnson Controls, Inc. While middleware **14** is shown as separate from BMS controller **12**, middleware **14** and BMS controller **12** may be integrated in some embodiments. For example, middleware **14** may be a part of BMS controller **12**.

[0045] Still referring to FIG. 2, window control system **22** may receive shade control information from one or more shade controls, ambient light level information from one or more light sensors, and/or other BMS inputs (e.g., sensor information, setpoint information, current state information, etc.) from downstream devices. Window control system **22** may include window controllers **107, 108** (e.g., named “local window controller A” and “local window controller B,” respectively, in BMS **11**). Window controllers **107, 108** control the operation of subsets of window control system **22**. For example, window controller **108** may control window blind or shade operations for a given room, floor, or building in the BMS.

[0046] Lighting system **24** may receive lighting related information from a plurality of downstream light controls (e.g., from room lighting **104**). Door access system **26** may receive lock control, motion, state, or other door related information from a plurality of downstream door controls. Door access system **26** is shown to include door access pad **106** (named “Door Access Pad 3F”), which

may grant or deny access to a building space (e.g., a floor, a conference room, an office, etc.) based on whether valid user credentials are scanned or entered (e.g., via a keypad, via a badge-scanning pad, etc.).

[0047] BMS subsystems **20-26** may be connected to BMS controller **12** via middleware **14** and may be configured to provide BMS controller **12** with BMS inputs from various BMS subsystems **20-26** and their varying downstream devices. BMS controller **12** may be configured to make differences in building subsystems transparent at the human-machine interface or client interface level (e.g., for connected or hosted user interface (UI) clients **16**, remote applications **18**, etc.). BMS controller **12** may be configured to describe or model different building devices and building subsystems using common or unified objects (e.g., software objects stored in memory) to help provide the transparency. Software equipment objects may allow developers to write applications capable of monitoring and/or controlling various types of building equipment regardless of equipment-specific variations (e.g., equipment model, equipment manufacturer, equipment version, etc.). Software building objects may allow developers to write applications capable of monitoring and/or controlling building zones on a zone-by-zone level regardless of the building subsystem makeup.

[0048] Referring now to FIG. 3, a block diagram illustrating a portion of BMS **11** in greater detail is shown, according to an exemplary embodiment. Particularly, FIG. 3 illustrates a portion of BMS **11** that services a conference room **102** of building **10** (named “B1_F3_CR5”). Conference room **102** may be affected by many different building devices connected to many different BMS subsystems. For example, conference room **102** includes or is otherwise affected by VAV box **110**, window controller **108** (e.g., a blind controller), a system of lights **104** (named “Room Lighting **17**”), and a door access pad **106**.

[0049] Each of the building devices shown at the top of FIG. 3 may include local control circuitry configured to provide signals to their supervisory controllers or more generally to the BMS subsystems **20-26**. The local control circuitry of the building devices shown at the top of FIG. 3 may also be configured to receive and respond to control signals, commands, setpoints, or other data from their supervisory controllers. For example, the local control circuitry of VAV box **110** may include circuitry that affects an actuator in response to control signals received from a field controller that is a part of HVAC system **20**. Window controller **108** may include circuitry that affects windows or blinds in response to control signals received from a field controller that is part of window control system (WCS) **22**. Room lighting **104** may include circuitry that affects the lighting in response to control signals received from a field controller that is part of lighting system **24**. Access pad **106** may include circuitry that affects door access (e.g., locking or unlocking the door) in response to control signals received from a field controller that is part of door access system **26**.

[0050] Still referring to FIG. 3, BMS controller **12** is shown to include a BMS interface **132** in communication with middleware **14**. In some embodiments, BMS interface **132** is a communications interface. For example, BMS interface **132** may include wired or wireless interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with various systems, devices, or networks. BMS interface **132** can include an Ethernet card and port for sending and receiving data via an Ethernet-based communications network. In another example, BMS interface **132** includes a Wi-Fi transceiver for communicating via a wireless communications network. BMS interface **132** may be configured to communicate via local area networks or wide area networks (e.g., the Internet, a building WAN, etc.).

[0051] In some embodiments, BMS interface **132** and/or middleware **14** includes an application gateway configured to receive input from applications running on client devices. For example, BMS interface **132** and/or middleware **14** may include one or more wireless transceivers (e.g., a Wi-Fi transceiver, a Bluetooth transceiver, an NFC transceiver, a cellular transceiver, etc.) for

communicating with client devices. BMS interface **132** may be configured to receive building management inputs from middleware **14** or directly from one or more BMS subsystems **20-26**. BMS interface **132** and/or middleware **14** can include any number of software buffers, queues, listeners, filters, translators, or other communications-supporting services.

[0052] Still referring to FIG. 3, BMS controller **12** is shown to include a processing circuit **134** including a processor **136** and memory **138**. Processor **136** may be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **136** is configured to execute computer code or instructions stored in memory **138** or received from other computer readable media (e.g., CDRom, network storage, a remote server, etc.).

[0053] Memory **138** may include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. Memory **138** may include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. Memory **138** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. Memory **138** may be communicably connected to processor **136** via processing circuit **134** and may include computer code for executing (e.g., by processor **136**) one or more processes described herein. When processor **136** executes instructions stored in memory **138** for completing the various activities described herein, processor **136** generally configures BMS controller **12** (and more particularly processing circuit **134**) to complete such activities.

[0054] Still referring to FIG. 3, memory **138** is shown to include building objects **142**. In some embodiments, BMS controller **12** uses building objects **142** to group otherwise ungrouped or unassociated devices so that the group may be addressed or handled by applications together and in a consistent manner (e.g., a single user interface for controlling all of the BMS devices that affect a particular building zone or room). Building objects can apply to spaces of any granularity. For example, a building object can represent an entire building, a floor of a building, or individual rooms on each floor. In some embodiments, BMS controller **12** creates and/or stores a building object in memory **138** for each zone or room of building **10**. Building objects **142** can be accessed by UI clients **16** and remote applications **18** to provide a comprehensive user interface for controlling and/or viewing information for a particular building zone. Building objects **142** may be created by building object creation module **152** and associated with equipment objects by object relationship module **158**, described in greater detail below.

[0055] Still referring to FIG. 3, memory **138** is shown to include equipment definitions **140**. Equipment definitions **140** stores the equipment definitions for various types of building equipment. Each equipment definition may apply to building equipment of a different type. For example, equipment definitions **140** may include different equipment definitions for variable air volume modular assemblies (VMAs), fan coil units, air handling units (AHUs), lighting fixtures, water pumps, and/or other types of building equipment.

[0056] Equipment definitions **140** define the types of data points that are generally associated with various types of building equipment. For example, an equipment definition for VMA may specify data point types such as room temperature, damper position, supply air flow, and/or other types data measured or used by the VMA. Equipment definitions **140** allow for the abstraction (e.g., generalization, normalization, broadening, etc.) of equipment data from a specific BMS device so that the equipment data can be applied to a room or space.

[0057] Each of equipment definitions **140** may include one or more point definitions. Each point definition may define a data point of a particular type and may include search criteria for

automatically discovering and/or identifying data points that satisfy the point definition. An equipment definition can be applied to multiple pieces of building equipment of the same general type (e.g., multiple different VMA controllers). When an equipment definition is applied to a BMS device, the search criteria specified by the point definitions can be used to automatically identify data points provided by the BMS device that satisfy each point definition.

[0058] In some embodiments, equipment definitions **140** define data point types as generalized types of data without regard to the model, manufacturer, vendor, or other differences between building equipment of the same general type. The generalized data points defined by equipment definitions **140** allows each equipment definition to be referenced by or applied to multiple different variants of the same type of building equipment.

[0059] In some embodiments, equipment definitions **140** facilitate the presentation of data points in a consistent and user-friendly manner. For example, each equipment definition may define one or more data points that are displayed via a user interface. The displayed data points may be a subset of the data points defined by the equipment definition.

[0060] In some embodiments, equipment definitions **140** specify a system type (e.g., HVAC, lighting, security, fire, etc.), a system sub-type (e.g., terminal units, air handlers, central plants), and/or data category (e.g., critical, diagnostic, operational) associated with the building equipment defined by each equipment definition. Specifying such attributes of building equipment at the equipment definition level allows the attributes to be applied to the building equipment along with the equipment definition when the building equipment is initially defined. Building equipment can be filtered by various attributes provided in the equipment definition to facilitate the reporting and management of equipment data from multiple building systems.

[0061] Equipment definitions **140** can be automatically created by abstracting the data points provided by archetypal controllers (e.g., typical or representative controllers) for various types of building equipment. In some embodiments, equipment definitions **140** are created by equipment definition module **154**, described in greater detail below.

[0062] Still referring to FIG. 3, memory **138** is shown to include equipment objects **144**.

Equipment objects **144** may be software objects that define a mapping between a data point type (e.g., supply air temperature, room temperature, damper position) and an actual data point (e.g., a measured or calculated value for the corresponding data point type) for various pieces of building equipment. Equipment objects **144** may facilitate the presentation of equipment-specific data points in an intuitive and user-friendly manner by associating each data point with an attribute identifying the corresponding data point type. The mapping provided by equipment objects **144** may be used to associate a particular data value measured or calculated by BMS **11** with an attribute that can be displayed via a user interface.

[0063] Equipment objects **144** can be created (e.g., by equipment object creation module **156**) by referencing equipment definitions **140**. For example, an equipment object can be created by applying an equipment definition to the data points provided by a BMS device. The search criteria included in an equipment definition can be used to identify data points of the building equipment that satisfy the point definitions. A data point that satisfies a point definition can be mapped to an attribute of the equipment object corresponding to the point definition.

[0064] Each equipment object may include one or more attributes defined by the point definitions of the equipment definition used to create the equipment object. For example, an equipment definition which defines the attributes “Occupied Command,” “Room Temperature,” and “Damper Position” may result in an equipment object being created with the same attributes. The search criteria provided by the equipment definition are used to identify and map data points associated with a particular BMS device to the attributes of the equipment object. The creation of equipment objects is described in greater detail below with reference to equipment object creation module **156**.

[0065] Equipment objects **144** may be related with each other and/or with building objects **142**.

Causal relationships can be established between equipment objects to link equipment objects to each other. For example, a causal relationship can be established between a VMA and an AHU which provides airflow to the VMA. Causal relationships can also be established between equipment objects **144** and building objects **142**. For example, equipment objects **144** can be associated with building objects **142** representing particular rooms or zones to indicate that the equipment object serves that room or zone. Relationships between objects are described in greater detail below with reference to object relationship module **158**.

[0066] Still referring to FIG. 3, memory **138** is shown to include client services **146** and application services **148**. Client services **146** may be configured to facilitate interaction and/or communication between BMS controller **12** and various internal or external clients or applications. For example, client services **146** may include web services or application programming interfaces available for communication by UI clients **16** and remote applications **18** (e.g., applications running on a mobile device, energy monitoring applications, applications allowing a user to monitor the performance of the BMS, automated fault detection and diagnostics systems, etc.). Application services **148** may facilitate direct or indirect communications between remote applications **18**, local applications **150**, and BMS controller **12**. For example, application services **148** may allow BMS controller **12** to communicate (e.g., over a communications network) with remote applications **18** running on mobile devices and/or with other BMS controllers.

[0067] In some embodiments, application services **148** facilitate an applications gateway for conducting electronic data communications with UI clients **16** and/or remote applications **18**. For example, application services **148** may be configured to receive communications from mobile devices and/or BMS devices. Client services **146** may provide client devices with a user interface that consumes data points and/or display data defined by equipment definitions **140** and mapped by equipment objects **144**.

[0068] Still referring to FIG. 3, memory **138** is shown to include a building object creation module **152**. Building object creation module **152** may be configured to create the building objects stored in building objects **142**. Building object creation module **152** may create a software building object for various spaces within building **10**. Building object creation module **152** can create a building object for a space of any size or granularity. For example, building object creation module **152** can create a building object representing an entire building, a floor of a building, or individual rooms on each floor. In some embodiments, building object creation module **152** creates and/or stores a building object in memory **138** for each zone or room of building **10**.

[0069] The building objects created by building object creation module **152** can be accessed by UI clients **16** and remote applications **18** to provide a comprehensive user interface for controlling and/or viewing information for a particular building zone. Building objects **142** can group otherwise ungrouped or unassociated devices so that the group may be addressed or handled by applications together and in a consistent manner (e.g., a single user interface for controlling all of the BMS devices that affect a particular building zone or room). In some embodiments, building object creation module **152** uses the systems and methods described in U.S. patent application Ser. No. 12/887,390, filed Sep. 21, 2010, for creating software defined building objects.

[0070] In some embodiments, building object creation module **152** provides a user interface for guiding a user through a process of creating building objects. For example, building object creation module **152** may provide a user interface to client devices (e.g., via client services **146**) that allows a new space to be defined. In some embodiments, building object creation module **152** defines spaces hierarchically. For example, the user interface for creating building objects may prompt a user to create a space for a building, for floors within the building, and/or for rooms or zones within each floor.

[0071] In some embodiments, building object creation module **152** creates building objects automatically or semi-automatically. For example, building object creation module **152** may automatically define and create building objects using data imported from another data source (e.g.,

user view folders, a table, a spreadsheet, etc.). In some embodiments, building object creation module **152** references an existing hierarchy for BMS **11** to define the spaces within building **10**. For example, BMS **11** may provide a listing of controllers for building **10** (e.g., as part of a network of data points) that have the physical location (e.g., room name) of the controller in the name of the controller itself. Building object creation module **152** may extract room names from the names of BMS controllers defined in the network of data points and create building objects for each extracted room. Building objects may be stored in building objects **142**.

[0072] Still referring to FIG. **3**, memory **138** is shown to include an equipment definition module **154**. Equipment definition module **154** may be configured to create equipment definitions for various types of building equipment and to store the equipment definitions in equipment definitions **140**. In some embodiments, equipment definition module **154** creates equipment definitions by abstracting the data points provided by archetypal controllers (e.g., typical or representative controllers) for various types of building equipment. For example, equipment definition module **154** may receive a user selection of an archetypal controller via a user interface. The archetypal controller may be specified as a user input or selected automatically by equipment definition module **154**. In some embodiments, equipment definition module **154** selects an archetypal controller for building equipment associated with a terminal unit such as a VMA.

[0073] Equipment definition module **154** may identify one or more data points associated with the archetypal controller. Identifying one or more data points associated with the archetypal controller may include accessing a network of data points provided by BMS **11**. The network of data points may be a hierarchical representation of data points that are measured, calculated, or otherwise obtained by various BMS devices. BMS devices may be represented in the network of data points as nodes of the hierarchical representation with associated data points depending from each BMS device. Equipment definition module **154** may find the node corresponding to the archetypal controller in the network of data points and identify one or more data points which depend from the archetypal controller node.

[0074] Equipment definition module **154** may generate a point definition for each identified data point of the archetypal controller. Each point definition may include an abstraction of the corresponding data point that is applicable to multiple different controllers for the same type of building equipment. For example, an archetypal controller for a particular VMA (i.e., “VMA-20”) may be associated an equipment-specific data point such as “VMA-20.DPR-POS” (i.e., the damper position of VMA-20) and/or “VMA-20.SUP-FLOW” (i.e., the supply air flow rate through VMA-20). Equipment definition module **154** abstract the equipment-specific data points to generate abstracted data point types that are generally applicable to other equipment of the same type. For example, equipment definition module **154** may abstract the equipment-specific data point “VMA-20.DPR-POS” to generate the abstracted data point type “DPR-POS” and may abstract the equipment-specific data point “VMA-20.SUP-FLOW” to generate the abstracted data point type “SUP-FLOW.” Advantageously, the abstracted data point types generated by equipment definition module **154** can be applied to multiple different variants of the same type of building equipment (e.g., VMAs from different manufacturers, VMAs having different models or output data formats, etc.).

[0075] In some embodiments, equipment definition module **154** generates a user-friendly label for each point definition. The user-friendly label may be a plain text description of the variable defined by the point definition. For example, equipment definition module **154** may generate the label “Supply Air Flow” for the point definition corresponding to the abstracted data point type “SUP-FLOW” to indicate that the data point represents a supply air flow rate through the VMA. The labels generated by equipment definition module **154** may be displayed in conjunction with data values from BMS devices as part of a user-friendly interface.

[0076] In some embodiments, equipment definition module **154** generates search criteria for each point definition. The search criteria may include one or more parameters for identifying another

data point (e.g., a data point associated with another controller of BMS **11** for the same type of building equipment) that represents the same variable as the point definition. Search criteria may include, for example, an instance number of the data point, a network address of the data point, and/or a network point type of the data point.

[0077] In some embodiments, search criteria include a text string abstracted from a data point associated with the archetypal controller. For example, equipment definition module **154** may generate the abstracted text string “SUP-FLOW” from the equipment-specific data point “VMA-20.SUP-FLOW.” Advantageously, the abstracted text string matches other equipment-specific data points corresponding to the supply air flow rates of other BMS devices (e.g., “VMA-18.SUP-FLOW,” “SUP-FLOW.VMA-01,” etc.). Equipment definition module **154** may store a name, label, and/or search criteria for each point definition in memory **138**.

[0078] Equipment definition module **154** may use the generated point definitions to create an equipment definition for a particular type of building equipment (e.g., the same type of building equipment associated with the archetypal controller). The equipment definition may include one or more of the generated point definitions. Each point definition defines a potential attribute of BMS devices of the particular type and provides search criteria for identifying the attribute among other data points provided by such BMS devices.

[0079] In some embodiments, the equipment definition created by equipment definition module **154** includes an indication of display data for BMS devices that reference the equipment definition. Display data may define one or more data points of the BMS device that will be displayed via a user interface. In some embodiments, display data are user defined. For example, equipment definition module **154** may prompt a user to select one or more of the point definitions included in the equipment definition to be represented in the display data. Display data may include the user-friendly label (e.g., “Damper Position”) and/or short name (e.g., “DPR-POS”) associated with the selected point definitions.

[0080] In some embodiments, equipment definition module **154** provides a visualization of the equipment definition via a user interface. The visualization of the equipment definition may include a point definition portion which displays the generated point definitions, a user input portion configured to receive a user selection of one or more of the point definitions displayed in the point definition portion, and/or a display data portion which includes an indication of an abstracted data point corresponding to each of the point definitions selected via the user input portion. The visualization of the equipment definition can be used to add, remove, or change point definitions and/or display data associated with the equipment definitions.

[0081] Equipment definition module **154** may generate an equipment definition for each different type of building equipment in BMS **11** (e.g., VMAs, chillers, AHUs, etc.). Equipment definition module **154** may store the equipment definitions in a data storage device (e.g., memory **138**, equipment definitions **140**, an external or remote data storage device, etc.).

[0082] Still referring to FIG. **3**, memory **138** is shown to include an equipment object creation module **156**. Equipment object creation module **156** may be configured to create equipment objects for various BMS devices. In some embodiments, equipment object creation module **156** creates an equipment object by applying an equipment definition to the data points provided by a BMS device. For example, equipment object creation module **156** may receive an equipment definition created by equipment definition module **154**. Receiving an equipment definition may include loading or retrieving the equipment definition from a data storage device.

[0083] In some embodiments, equipment object creation module **156** determines which of a plurality of equipment definitions to retrieve based on the type of BMS device used to create the equipment object. For example, if the BMS device is a VMA, equipment object creation module **156** may retrieve the equipment definition for VMAs; whereas if the BMS device is a chiller, equipment object creation module **156** may retrieve the equipment definition for chillers. The type of BMS device to which an equipment definition applies may be stored as an attribute of the

equipment definition. Equipment object creation module **156** may identify the type of BMS device being used to create the equipment object and retrieve the corresponding equipment definition from the data storage device.

[0084] In other embodiments, equipment object creation module **156** receives an equipment definition prior to selecting a BMS device. Equipment object creation module **156** may identify a BMS device of BMS **11** to which the equipment definition applies. For example, equipment object creation module **156** may identify a BMS device that is of the same type of building equipment as the archetypal BMS device used to generate the equipment definition. In various embodiments, the BMS device used to generate the equipment object may be selected automatically (e.g., by equipment object creation module **156**), manually (e.g., by a user) or semi-automatically (e.g., by a user in response to an automated prompt from equipment object creation module **156**).

[0085] In some embodiments, equipment object creation module **156** creates an equipment discovery table based on the equipment definition. For example, equipment object creation module **156** may create an equipment discovery table having attributes (e.g., columns) corresponding to the variables defined by the equipment definition (e.g., a damper position attribute, a supply air flow rate attribute, etc.). Each column of the equipment discovery table may correspond to a point definition of the equipment definition. The equipment discovery table may have columns that are categorically defined (e.g., representing defined variables) but not yet mapped to any particular data points.

[0086] Equipment object creation module **156** may use the equipment definition to automatically identify one or more data points of the selected BMS device to map to the columns of the equipment discovery table. Equipment object creation module **156** may search for data points of the BMS device that satisfy one or more of the point definitions included in the equipment definition. In some embodiments, equipment object creation module **156** extracts a search criterion from each point definition of the equipment definition. Equipment object creation module **156** may access a data point network of the building automation system to identify one or more data points associated with the selected BMS device. Equipment object creation module **156** may use the extracted search criterion to determine which of the identified data points satisfy one or more of the point definitions.

[0087] In some embodiments, equipment object creation module **156** automatically maps (e.g., links, associates, relates, etc.) the identified data points of selected BMS device to the equipment discovery table. A data point of the selected BMS device may be mapped to a column of the equipment discovery table in response to a determination by equipment object creation module **156** that the data point satisfies the point definition (e.g., the search criteria) used to generate the column. For example, if a data point of the selected BMS device has the name “VMA-18.SUP-FLOW” and a search criterion is the text string “SUP-FLOW,” equipment object creation module **156** may determine that the search criterion is met. Accordingly, equipment object creation module **156** may map the data point of the selected BMS device to the corresponding column of the equipment discovery table.

[0088] Advantageously, equipment object creation module **156** may create multiple equipment objects and map data points to attributes of the created equipment objects in an automated fashion (e.g., without human intervention, with minimal human intervention, etc.). The search criteria provided by the equipment definition facilitates the automatic discovery and identification of data points for a plurality of equipment object attributes. Equipment object creation module **156** may label each attribute of the created equipment objects with a device-independent label derived from the equipment definition used to create the equipment object. The equipment objects created by equipment object creation module **156** can be viewed (e.g., via a user interface) and/or interpreted by data consumers in a consistent and intuitive manner regardless of device-specific differences between BMS devices of the same general type. The equipment objects created by equipment object creation module **156** may be stored in equipment objects **144**.

[0089] Still referring to FIG. 3, memory 138 is shown to include an object relationship module 158. Object relationship module 158 may be configured to establish relationships between equipment objects 144. In some embodiments, object relationship module 158 establishes causal relationships between equipment objects 144 based on the ability of one BMS device to affect another BMS device. For example, object relationship module 158 may establish a causal relationship between a terminal unit (e.g., a VMA) and an upstream unit (e.g., an AHU, a chiller, etc.) which affects an input provided to the terminal unit (e.g., air flow rate, air temperature, etc.).

[0090] Object relationship module 158 may establish relationships between equipment objects 144 and building objects 142 (e.g., spaces). For example, object relationship module 158 may associate equipment objects 144 with building objects 142 representing particular rooms or zones to indicate that the equipment object serves that room or zone. In some embodiments, object relationship module 158 provides a user interface through which a user can define relationships between equipment objects 144 and building objects 142. For example, a user can assign relationships in a “drag and drop” fashion by dragging and dropping a building object and/or an equipment object into a “serving” cell of an equipment object provided via the user interface to indicate that the BMS device represented by the equipment object serves a particular space or BMS device.

[0091] Still referring to FIG. 3, memory 138 is shown to include a building control services module 160. Building control services module 160 may be configured to automatically control BMS 11 and the various subsystems thereof. Building control services module 160 may utilize closed loop control, feedback control, PI control, model predictive control, or any other type of automated building control methodology to control the environment (e.g., a variable state or condition) within building 10.

[0092] Building control services module 160 may receive inputs from sensory devices (e.g., temperature sensors, pressure sensors, flow rate sensors, humidity sensors, electric current sensors, cameras, wireless sensors, microphones, etc.), user input devices (e.g., computer terminals, client devices, user devices, etc.) or other data input devices via BMS interface 132. Building control services module 160 may apply the various inputs to a building energy use model and/or a control algorithm to determine an output for one or more building control devices (e.g., dampers, air handling units, chillers, boilers, fans, pumps, etc.) in order to affect a variable state or condition within building 10 (e.g., zone temperature, humidity, air flow rate, etc.).

[0093] In some embodiments, building control services module 160 is configured to control the environment of building 10 on a zone-individualized level. For example, building control services module 160 may control the environment of two or more different building zones using different setpoints, different constraints, different control methodology, and/or different control parameters. Building control services module 160 may operate BMS 11 to maintain building conditions (e.g., temperature, humidity, air quality, etc.) within a setpoint range, to optimize energy performance (e.g., to minimize energy consumption, to minimize energy cost, etc.), and/or to satisfy any constraint or combination of constraints as may be desirable for various implementations.

[0094] In some embodiments, building control services module 160 uses the location of various BMS devices to translate an input received from a building system into an output or control signal for the building system. Building control services module 160 may receive location information for BMS devices and automatically set or recommend control parameters for the BMS devices based on the locations of the BMS devices. For example, building control services module 160 may automatically set a flow rate setpoint for a VAV box based on the size of the building zone in which the VAV box is located.

[0095] Building control services module 160 may determine which of a plurality of sensors to use in conjunction with a feedback control loop based on the locations of the sensors within building 10. For example, building control services module 160 may use a signal from a temperature sensor located in a building zone as a feedback signal for controlling the temperature of the building zone in which the temperature sensor is located.

[0096] In some embodiments, building control services module **160** automatically generates control algorithms for a controller or a building zone based on the location of the zone in the building **10**. For example, building control services module **160** may be configured to predict a change in demand resulting from sunlight entering through windows based on the orientation of the building and the locations of the building zones (e.g., east-facing, west-facing, perimeter zones, interior zones, etc.).

[0097] Building control services module **160** may use zone location information and interactions between adjacent building zones (rather than considering each zone as an isolated system) to more efficiently control the temperature and/or airflow within building **10**. For control loops that are conducted at a larger scale (i.e., floor level) building control services module **160** may use the location of each building zone and/or BMS device to coordinate control functionality between building zones. For example, building control services module **160** may consider heat exchange and/or air exchange between adjacent building zones as a factor in determining an output control signal for the building zones.

[0098] In some embodiments, building control services module **160** is configured to optimize the energy efficiency of building **10** using the locations of various BMS devices and the control parameters associated therewith. Building control services module **160** may be configured to achieve control setpoints using building equipment with a relatively lower energy cost (e.g., by causing airflow between connected building zones) in order to reduce the loading on building equipment with a relatively higher energy cost (e.g., chillers and roof top units). For example, building control services module **160** may be configured to move warmer air from higher elevation zones to lower elevation zones by establishing pressure gradients between connected building zones.

[0099] Referring now to FIG. **4**, another block diagram illustrating a portion of BMS **11** in greater detail is shown, according to some embodiments. BMS **11** can be implemented in building **10** to automatically monitor and control various building functions. BMS **11** is shown to include BMS controller **12** and a plurality of building subsystems **428**. Building subsystems **428** are shown to include a building electrical subsystem **434**, an information communication technology (ICT) subsystem **436**, a security subsystem **438**, a HVAC subsystem **440**, a lighting subsystem **442**, a lift/escalators subsystem **432**, and a fire safety subsystem **430**. In various embodiments, building subsystems **428** can include fewer, additional, or alternative subsystems. For example, building subsystems **428** may also or alternatively include a refrigeration subsystem, an advertising or signage subsystem, a cooking subsystem, a vending subsystem, a printer or copy service subsystem, or any other type of building subsystem that uses controllable equipment and/or sensors to monitor or control building **10**.

[0100] Each of building subsystems **428** can include any number of devices, controllers, and connections for completing its individual functions and control activities. HVAC subsystem **440** can include many of the same components as HVAC system **20**, as described with reference to FIGS. **2-3**. For example, HVAC subsystem **440** can include a chiller, a boiler, any number of air handling units, economizers, field controllers, supervisory controllers, actuators, temperature sensors, and other devices for controlling the temperature, humidity, airflow, or other variable conditions within building **10**. Lighting subsystem **442** can include any number of light fixtures, ballasts, lighting sensors, dimmers, or other devices configured to controllably adjust the amount of light provided to a building space. Security subsystem **438** can include occupancy sensors, video surveillance cameras, digital video recorders, video processing servers, intrusion detection devices, access control devices and servers, or other security-related devices.

[0101] Still referring to FIG. **4**, BMS controller **12** is shown to include a communications interface **407** and a BMS interface **132**. Interface **407** may facilitate communications between BMS controller **12** and external applications (e.g., monitoring and reporting applications **422**, enterprise control applications **426**, remote systems and applications **444**, applications residing on client

devices **448**, etc.) for allowing user control, monitoring, and adjustment to BMS controller **12** and/or subsystems **428**. Interface **407** may also facilitate communications between BMS controller **12** and client devices **448**. BMS interface **132** may facilitate communications between BMS controller **12** and building subsystems **428** (e.g., HVAC, lighting security, lifts, power distribution, business, etc.).

[0102] Interfaces **407**, **132** can be or include wired or wireless communications interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with building subsystems **428** or other external systems or devices. In various embodiments, communications via interfaces **407**, **132** can be direct (e.g., local wired or wireless communications) or via a communications network **446** (e.g., a WAN, the Internet, a cellular network, etc.). For example, interfaces **407**, **132** can include an Ethernet card and port for sending and receiving data via an Ethernet-based communications link or network. In another example, interfaces **407**, **132** can include a Wi-Fi transceiver for communicating via a wireless communications network. In another example, one or both of interfaces **407**, **132** can include cellular or mobile phone communications transceivers. In one embodiment, communications interface **407** is a power line communications interface and BMS interface **132** is an Ethernet interface. In other embodiments, both communications interface **407** and BMS interface **132** are Ethernet interfaces or are the same Ethernet interface.

[0103] Still referring to FIG. **4**, BMS controller **12** is shown to include a processing circuit **134** including a processor **136** and memory **138**. Processing circuit **134** can be communicably connected to BMS interface **132** and/or communications interface **407** such that processing circuit **134** and the various components thereof can send and receive data via interfaces **407**, **132**. Processor **136** can be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable electronic processing components.

[0104] Memory **138** (e.g., memory, memory unit, storage device, etc.) can include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage, etc.) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present application. Memory **138** can be or include volatile memory or non-volatile memory. Memory **138** can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present application. According to some embodiments, memory **138** is communicably connected to processor **136** via processing circuit **134** and includes computer code for executing (e.g., by processing circuit **134** and/or processor **136**) one or more processes described herein.

[0105] In some embodiments, BMS controller **12** is implemented within a single computer (e.g., one server, one housing, etc.). In various other embodiments BMS controller **12** can be distributed across multiple servers or computers (e.g., that can exist in distributed locations). Further, while FIG. **4** shows applications **422** and **426** as existing outside of BMS controller **12**, in some embodiments, applications **422** and **426** can be hosted within BMS controller **12** (e.g., within memory **138**).

[0106] Still referring to FIG. **4**, memory **138** is shown to include an enterprise integration layer **410**, an automated measurement and validation (AM&V) layer **412**, a demand response (DR) layer **414**, a fault detection and diagnostics (FDD) layer **416**, an integrated control layer **418**, and a building subsystem integration later **420**. Layers **410-420** can be configured to receive inputs from building subsystems **428** and other data sources, determine optimal control actions for building subsystems **428** based on the inputs, generate control signals based on the optimal control actions, and provide the generated control signals to building subsystems **428**. The following paragraphs describe some of the general functions performed by each of layers **410-420** in BMS **11**.

[0107] Enterprise integration layer **410** can be configured to serve clients or local applications with

information and services to support a variety of enterprise-level applications. For example, enterprise control applications **426** can be configured to provide subsystem-spanning control to a user interface such as a graphical user interface (GUI) or to any number of enterprise-level business applications (e.g., accounting systems, user identification systems, etc.). Enterprise control applications **426** may also or alternatively be configured to provide configuration GUIs for configuring BMS controller **12**. In yet other embodiments, enterprise control applications **426** can work with layers **410-420** to optimize building performance (e.g., efficiency, energy use, comfort, or safety) based on inputs received at interface **407** and/or BMS interface **132**.

[0108] Building subsystem integration layer **420** can be configured to manage communications between BMS controller **12** and building subsystems **428**. For example, building subsystem integration layer **420** may receive sensor data and input signals from building subsystems **428** and provide output data and control signals to building subsystems **428**. Building subsystem integration layer **420** may also be configured to manage communications between building subsystems **428**. Building subsystem integration layer **420** translate communications (e.g., sensor data, input signals, output signals, etc.) across a plurality of multi-vendor/multi-protocol systems.

[0109] Demand response layer **414** can be configured to optimize resource usage (e.g., electricity use, natural gas use, water use, etc.) and/or the monetary cost of such resource usage in response to satisfy the demand of building **10**. The optimization can be based on time-of-use prices, curtailment signals, energy availability, or other data received from utility providers, distributed energy generation systems **424**, from energy storage **427**, or from other sources. Demand response layer **414** may receive inputs from other layers of BMS controller **12** (e.g., building subsystem integration layer **420**, integrated control layer **418**, etc.). The inputs received from other layers can include environmental or sensor inputs such as temperature, carbon dioxide levels, relative humidity levels, air quality sensor outputs, occupancy sensor outputs, room schedules, and the like. The inputs may also include inputs such as electrical use (e.g., expressed in kWh), thermal load measurements, pricing information, projected pricing, smoothed pricing, curtailment signals from utilities, and the like.

[0110] According to some embodiments, demand response layer **414** includes control logic for responding to the data and signals it receives. These responses can include communicating with the control algorithms in integrated control layer **418**, changing control strategies, changing setpoints, or activating/deactivating building equipment or subsystems in a controlled manner. Demand response layer **414** may also include control logic configured to determine when to utilize stored energy. For example, demand response layer **414** may determine to begin using energy from energy storage **427** just prior to the beginning of a peak use hour.

[0111] In some embodiments, demand response layer **414** includes a control module configured to actively initiate control actions (e.g., automatically changing setpoints) which minimize energy costs based on one or more inputs representative of or based on demand (e.g., price, a curtailment signal, a demand level, etc.). In some embodiments, demand response layer **414** uses equipment models to determine an optimal set of control actions. The equipment models can include, for example, thermodynamic models describing the inputs, outputs, and/or functions performed by various sets of building equipment. Equipment models may represent collections of building equipment (e.g., subplants, chiller arrays, etc.) or individual devices (e.g., individual chillers, heaters, pumps, etc.).

[0112] Demand response layer **414** may further include or draw upon one or more demand response policy definitions (e.g., databases, XML files, etc.). The policy definitions can be edited or adjusted by a user (e.g., via a user interface) so that the control actions initiated in response to demand inputs can be tailored for the user's application, desired comfort level, particular building equipment, or based on other concerns. For example, the demand response policy definitions can specify which equipment can be turned on or off in response to particular demand inputs, how long a system or piece of equipment should be turned off, what setpoints can be changed, what the

allowable set point adjustment range is, how long to hold a high demand setpoint before returning to a normally scheduled setpoint, how close to approach capacity limits, which equipment modes to utilize, the energy transfer rates (e.g., the maximum rate, an alarm rate, other rate boundary information, etc.) into and out of energy storage devices (e.g., thermal storage tanks, battery banks, etc.), and when to dispatch on-site generation of energy (e.g., via fuel cells, a motor generator set, etc.).

[0113] Integrated control layer **418** can be configured to use the data input or output of building subsystem integration layer **420** and/or demand response layer **414** to make control decisions. Due to the subsystem integration provided by building subsystem integration layer **420**, integrated control layer **418** can integrate control activities of the subsystems **428** such that the subsystems **428** behave as a single integrated supersystem. In some embodiments, integrated control layer **418** includes control logic that uses inputs and outputs from a plurality of building subsystems to provide greater comfort and energy savings relative to the comfort and energy savings that separate subsystems could provide alone. For example, integrated control layer **418** can be configured to use an input from a first subsystem to make an energy-saving control decision for a second subsystem. Results of these decisions can be communicated back to building subsystem integration layer **420**.

[0114] Integrated control layer **418** is shown to be logically below demand response layer **414**. Integrated control layer **418** can be configured to enhance the effectiveness of demand response layer **414** by enabling building subsystems **428** and their respective control loops to be controlled in coordination with demand response layer **414**. This configuration may advantageously reduce disruptive demand response behavior relative to conventional systems. For example, integrated control layer **418** can be configured to assure that a demand response-driven upward adjustment to the setpoint for chilled water temperature (or another component that directly or indirectly affects temperature) does not result in an increase in fan energy (or other energy used to cool a space) that would result in greater total building energy use than was saved at the chiller.

[0115] Integrated control layer **418** can be configured to provide feedback to demand response layer **414** so that demand response layer **414** checks that constraints (e.g., temperature, lighting levels, etc.) are properly maintained even while demanded load shedding is in progress. The constraints may also include setpoint or sensed boundaries relating to safety, equipment operating limits and performance, comfort, fire codes, electrical codes, energy codes, and the like. Integrated control layer **418** is also logically below fault detection and diagnostics layer **416** and automated measurement and validation layer **412**. Integrated control layer **418** can be configured to provide calculated inputs (e.g., aggregations) to these higher levels based on outputs from more than one building subsystem.

[0116] Automated measurement and validation (AM&V) layer **412** can be configured to verify that control strategies commanded by integrated control layer **418** or demand response layer **414** are working properly (e.g., using data aggregated by AM&V layer **412**, integrated control layer **418**, building subsystem integration layer **420**, FDD layer **416**, or otherwise). The calculations made by AM&V layer **412** can be based on building system energy models and/or equipment models for individual BMS devices or subsystems. For example, AM&V layer **412** may compare a model-predicted output with an actual output from building subsystems **428** to determine an accuracy of the model.

[0117] Fault detection and diagnostics (FDD) layer **416** can be configured to provide on-going fault detection for building subsystems **428**, building subsystem devices (i.e., building equipment), and control algorithms used by demand response layer **414** and integrated control layer **418**. FDD layer **416** may receive data inputs from integrated control layer **418**, directly from one or more building subsystems or devices, or from another data source. FDD layer **416** may automatically diagnose and respond to detected faults. The responses to detected or diagnosed faults can include providing an alert message to a user, a maintenance scheduling system, or a control algorithm configured to attempt to repair the fault or to work-around the fault.

[0118] FDD layer **416** can be configured to output a specific identification of the faulty component or cause of the fault (e.g., loose damper linkage) using detailed subsystem inputs available at building subsystem integration layer **420**. In other exemplary embodiments, FDD layer **416** is configured to provide “fault” events to integrated control layer **418** which executes control strategies and policies in response to the received fault events. According to some embodiments, FDD layer **416** (or a policy executed by an integrated control engine or business rules engine) may shut-down systems or direct control activities around faulty devices or systems to reduce energy waste, extend equipment life, or assure proper control response.

[0119] FDD layer **416** can be configured to store or access a variety of different system data stores (or data points for live data). FDD layer **416** may use some content of the data stores to identify faults at the equipment level (e.g., specific chiller, specific AHU, specific terminal unit, etc.) and other content to identify faults at component or subsystem levels. For example, building subsystems **428** may generate temporal (i.e., time-series) data indicating the performance of BMS **11** and the various components thereof. The data generated by building subsystems **428** can include measured or calculated values that exhibit statistical characteristics and provide information about how the corresponding system or process (e.g., a temperature control process, a flow control process, etc.) is performing in terms of error from its setpoint. These processes can be examined by FDD layer **416** to expose when the system begins to degrade in performance and alert a user to repair the fault before it becomes more severe.

A Control Panel For a Fire Alarm System

[0120] A control panel for a fire alarm system of the present disclosure is now described with reference to accompanying figures. The control panel is configured to control operation of the fire alarm system. In some embodiments, the control panel receives input signals from one or more input devices of the fire alarm system. The input devices are configured to sense various fire related parameters, such as, but not limited to, smoke, rise in temperature etc. The input devices sense the fire related parameters and transmit the input signals corresponding to the sensed fire related parameters to the control panel. The control panel processes the input signals to determine occurrence of fire event. If the fire event is detected, the control panel generates output signals and transmit to output devices of the fire alarm system. The control panel typically generates audio alarms. In some embodiments, the control panel is configured to actuate the fire suppression devices of the fire alarm system such as sprinklers.

[0121] Referring now to FIG. 5, a block diagram of a fire alarm system **500** is depicted. The fire alarm system **500** includes a plurality of fire alarm devices and a control panel **510**. The control panel **510** is enabled to control operation of the plurality of fire alarm devices of the fire alarm system. The fire alarm devices include one or more input devices **520** and one or more output devices **530**. Typically, the input devices **520** and/or output devices **530** are positioned throughout building **10** of FIG. 1. The input devices **520** can be any device that causes an environmental event signal to be sent to control panel **510**. More specifically, the input devices **520** are configured to sense various parameters such as temperature, pressure, presence of certain gases, smoke that can be used to detect an event of fire. For example, the input device **520** can be a smoke detector that detects smoke which is an indication of occurrence of fire nearby the smoke detector. In another example, the input device **520** can be a temperature sensor that detects temperature of surroundings. The temperature values sensed by the temperature sensor can be used to detect an occurrence of fire if rise in temperature beyond a certain limit is observed in sensed temperature values.

[0122] In an embodiment, input devices **520** are initiating devices that can include, but not limited to, smoke detectors, heat detectors, flame detectors, pull stations, gas detectors such as carbon monoxide detectors, natural gas detectors, and the like.

[0123] In some embodiments, output devices **530** are notification appliances that can be selected from, but not limited to, strobes, speakers, buzzers, visual indicators, displays or any combination

thereof. The notification appliances, i.e., the output devices **530** can be enabled to broadcast live or pre-recorded voice and/or video messages. In one embodiment, either or both input devices **520** and output devices **530** are IoT enabled devices. In some embodiments, the output devices **530** can include fire suppression devices such as sprinklers.

[0124] In an embodiment, the signals from input devices **520** are received and monitored by the control panel **510**. Specifically, the control panel **510** is a system controller or a fire alarm control panel, i.e., FACP. The control panel **510** upon sensing an alarm condition sends commands to one or more output devices **530** to alert occupants of the building **10**. In an exemplary embodiment, the control panel **510** may only activate output devices associated with one or more zones of the building **10**.

[0125] The control panel **510** is provided with a power supply. As shown in FIG. 5, the control panel **510** is connected to a primary power supply **540** and a secondary power supply **550**. The primary power supply **540** can be mains supply and the secondary power supply **550** can be an auxiliary power supply utilized for powering control panel **510** in absence or interruption of primary power supply **540**.

[0126] Referring to FIG. 6, a schematic view of the control panel **510** is shown. The control panel **510** comprises a housing **560** for accommodating various components of the control panel. The housing **560** can have any suitable shape. As shown in FIG. 6, the housing **560** is box shaped. In some embodiments, the housing **560** comprises a housing body **565** having a space for housing components and a door **570** attached to the housing body **565**. The door **570** can be provided with a safety lock which can be unlocked by an authorized person. The lock can be a mechanical lock or a digital lock requiring authentication from a user for opening the door **570**. The authentication can be performed using passwords and/or biometric authentication. In the biometric authentication, a user is required to verify his one or more biometric details in order to open the door **570** to gain access to interior of the housing **560**. In some embodiments, the door **570** can be hinged to the housing body **565**. In some other embodiments, the door **570** can be temporarily detached from the housing body **565** and can be reattached to the housing body **565**.

[0127] The housing **560** can be made of any suitable material. In some embodiments, the housing **560** is made of metallic material. In some other embodiments, the housing **560** is made of plastic or any other non-metallic material. In some other embodiments, the housing body **565** and the door **570** can be made of different materials. For example, the housing body **565** can be made of metallic material, whereas the door **570** can be made of non-metallic material or vice-versa. The housing **560** is provided with apertures or slots to provide a passage to electrical wires connected between components within the housing **560** and devices of the fire alarm system **500** outside the housing **560**. The apertures or slots are provided with proper insulation to prevent ingress of dust and moisture in the housing.

[0128] The control panel **510** has a data transfer region **580**. When a portable electronic device is placed proximal to or in physical contact with the data transfer region **580**, data can be transferred between the portable electronic device and the control panel **510** via short-range wireless communication. Preferably, the data transfer region **580** is provided on a portion of the housing **560** which facilitates radio frequency data transfer therethrough without data losses. For example, the data transfer region **580** is provided on non-metallic portion of the housing **560**.

[0129] In some embodiments, the data transfer region **580** is provided on the door **570**. In some embodiments, the data transfer region **580** is provided on sides of the housing body **565**. The data transfer region **580** is clearly defined for quick identification. The data transfer region **580** can be in various forms. In some embodiments, as shown in FIG. 6, the data transfer region **580** is in form of an opening provided on the door **570** of the housing **560**. The opening can be provided with a transparent glazing to enable a user to view components within the housing **560** without opening the door **570**. Typically, the opening is provided when the door **570** is of metallic material. However, the opening can be provided even when the door **570** is made of non-metallic material. In

some other embodiments, the door **570** can be of metallic material provided with the data transfer region **580** made of non-metallic material.

[0130] In some embodiments, as shown in FIG. 7, the data transfer region **580** is defined on the door **570** of the housing **560** using markings **610**. Preferably, the door **570** is made of non-metallic material. In some other embodiments, the data transfer region **580** can be provided at other locations, such as housing body **565**. The markings **610** can be in the form of dashed or continuous lines, patterns, labels, color codes etc. In some embodiments, the data transfer region **580** is suitably labeled using alphabets and/or symbols.

[0131] In some other embodiments, as shown in FIG. 8, the housing **560** includes a cover **575** provided between the door **570** and the housing body **565**. The data transfer region **580** is provided on the cover **575**. Preferably, the cover **575** is made of a non-metallic material to facilitate radio frequency data transfer therethrough. In some embodiments, the cover **575** is made of transparent material. In some embodiments, the cover **575** is provided when the door **570** is made of metallic material. The data transfer region **580** is defined on the cover **575** using markings **610**. The cover **575** can have length and height same as that of the door **570**. In other embodiments, the cover **575** can have smaller dimensions than the door **570**.

[0132] Referring to FIG. 9, a block diagram of the control panel **510** is shown in accordance with some embodiments of the present disclosure. The control panel **510** includes a processing circuit **620**, a communication interface **630**, a communication module **640**, a user interface **650** and the power bank **660**. In some embodiments, the processing circuit **620**, the communication interface **630**, the communication module **640**, and the user interface **650** are housed within the housing **560**. In some other embodiments, the communication interface **630**, the communication module **640**, and/or the user interface **650** can be mounted on outer surfaces of the housing **560**. For example, the communication module **640** can be mounted on an outer surface of one of the sides or the door **570** of the housing **560** for facilitating easy access to the communication module **640**.

[0133] Although FIG. 9 depicts power bank **660** as part of the control panel **510**, it is understood that the power bank **660** can reside within the housing **560** (shown in FIG. 6) of the control panel **510** or can be remotely placed within the premises of building **10**.

[0134] In some embodiments, the control panel **510** includes a printed circuit board (PCB) **670** (shown in FIG. 6) for mounting the processing circuit **620**, the communication interface **630**, the communication module **640**, and the user interface **650**. The PCB **670** facilitates mounting of aforementioned components of the control panel **510** as well as provides reliable electrical connections between aforementioned components in a controlled manner.

[0135] The communication interface **630** enables connection of the control panel **510** with the devices such as the input devices **520** and the output devices **530** of the fire alarm system **500**. The communication interface **630** can be or include wired or wireless communications interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for establishing data communications with input devices **520**, output devices **530**, or other external systems or devices. In various embodiments, communications via communication interface **630** can be direct (e.g., local wired or wireless communications) or via a communications network (e.g., a WAN, the Internet, a cellular network, etc.). For example, the communication interface **630** can include an Ethernet card and port for sending and receiving data via an Ethernet-based communications link or network. In another example, communication interface **630** can include a Wi-Fi transceiver for communicating via a wireless communications network. In another example, the communication interface **630** can include cellular or mobile phone communications transceivers.

[0136] The communication module **640** is configured to establish a wireless connection with a portable electronic device **680**. Preferably, the communication module **640** is enabled to facilitate short-range wireless communication with the portable electronic device **680**. In an embodiment, the portable electronic device **680** can be selected from the group consisting of, but is not limited to, a smartphone, a tablet, a mobile phone, a personal digital assistant (PDA), a mobile computing

device, a personal information manager (PIM) with a wireless interface, an ultra-mobile PC, a tablet computer (such as an iPad®), or the like. The smartphone is a mobile phone that provides more advanced computing ability and connectivity than a contemporary basic feature phone. The smartphone includes the functionality of a handheld computer integrated within a mobile telephone. Specifically, the portable electronic device **680** can be any electronic device with communication and processing capabilities.

[0137] The communication module **640** is provided with Near Field Communication (NFC) unit **690**. In some embodiments, the communication module **640** can be provided with both NFC unit and radio frequency identification (RFID) communication unit. The control panel **510** can selectively and/or simultaneously utilize NFC unit **690** and RFID. In some other embodiments, the communication module **640** can include a Bluetooth unit, an infrared communication unit or any other suitable short-range wireless communication unit in addition to the NFC unit **690**.

[0138] In one implementation of the present disclosure, the NFC unit **690** employs a transceiver integrated circuit that is an integrated analog front end and data-framing device for a 13.56-MHz RFID/Near Field Communication system.

[0139] In some embodiments, the communication module **640** is arranged such that it is proximal to the data transfer region **580**. In some embodiments, the communication module **640** is placed behind the data transfer region **580** with respect to a user. More specifically, the data transfer region **580** overlaps the communication module **640**. In some embodiments, the cover **575** is provided on the communication module **640**, wherein the data transfer region **580** is defined on the cover **575**. In some other embodiments, the data transfer region is defined on the communication module **640** itself. The communication module **640** is configured to establish short-range communication with the portable electronic device **680** when the portable electronic device **680** is proximal to the data transfer region **580**. In some embodiments, the portable electronic device **680** is placed in physical contact with the data transfer region **580** to enable short-range wireless communication between the communication module **640** and the portable electronic device **680**.

[0140] The power bank **660** can be electrically coupled to the secondary power supply **550** for supplying power. In one embodiment, the power bank **660** may include one or more batteries. In one other embodiment, the power bank **660** may also be provided with one or more supercapacitors. In still another embodiment, the power bank **660** may comprise both the one or more supercapacitors and the one or more batteries.

[0141] Referring to FIG. 11-14, the user interface **650** of the control panel **510** is shown. The user interface **650** is provided to receive user inputs and to display data related to the control panel **510**. The user input pertains to one or more of operating commands, selection of one or more operating modes, user credentials, and the like. In some embodiments, the user interface **650** is provided in the housing **560**, wherein access means are provided on the housing **560** to access the user interface **650**. In some embodiments, the access means can be an opening **590** or any other suitable means. The user interface **650** can be accessed by opening the door **570** or through the opening **590**. The user interface **650** comprises a display **700**, user input means **710**, and indicators **720**. The user input means **710** are provided to receive inputs from a user. In some embodiments, the user input means **710** can be an alphanumeric keypad. In some embodiments, the display **700** is a touchscreen display which can show data as well as receive inputs from the user. In some other embodiments, the display **700** can be one of, but not limited to, a Liquid Crystal Display (LCD), a seven-segment display, a backlit LCD display, and a Light Emitting Diode (LED) display. The indicators **720** are provided to indicate occurrences of various events related to the fire alarm system **500**. For an example, the indicators **720** can indicate occurrence of fire, supply status of power supply, establishment of short-range wireless communication between the portable electronic device **680** and the control panel, or data transfer between the portable electronic device **680** and the control panel etc. The indicators **720** can be provided with labels **730** and an indication lamp **740**. The indication lamp **740** tuned ON to indicate occurrence of an event. The details of that event can be

provided on the label **730**. The processing circuit **620** is provided to store configuration information pertaining to the fire alarm system **500**, to receive one or more data packets from the portable electronic device **680** via short-range wireless communication, and to update at least a part of the configuration information using the one or more data packets.

[0142] In some embodiments, the user interface **650** is configured to display data related to capabilities of the control panel **510**. For example, the user interface **650** can display options related to functionalities of the control panel **510** such as universal serial bus (USB), system default, device aping, near field communication (NFC) etc. The user interface **650** is configured to display progress of operations carried out by the control panel **510**. For example, the user interface **650** can display progress of ongoing NFC transfer. Further, the user interface **650** is configured to display various process related data such as failure in operating certain features of the control panel **510** or failure in establishing NFC communication, interruption in NFC communication, and the like.

[0143] Referring to FIG. **9-14**, the control panel **510** is described in detail. The processing circuit **620** of the control panel **510** is configured to store configuration information pertaining to the fire alarm system **500**. In an embodiment, the configuration information is related at least one of input devices, output devices, and the control panel. Typically, the configuration information is data related to identification, operation, and control of the devices and/or the control panel **510** of the fire alarm system **500** such as, but not limited to, name, type, location, operating conditions, labels, zones, operating parameters etc. of the devices and/or the control panel **510**.

[0144] The configuration information can be initially loaded in the processing circuit **620** while the control panel **510** is being commissioned. However, during operating life of the fire alarm system, the configuration information needs to be updated based on customization, modifications, or enhancements being made to the fire alarm system **500**. In some embodiments, the enhancements can be due to addition of one or more input devices or output devices. In some other embodiments, the modification can be due to replacement of one or more previously deployed input device or output device.

[0145] Referring to FIGS. **9-10**, the processing circuit **620** is configured to communicate with the portable electronic device **680** using short-range wireless communication technique, such as NFC, to receive and/or transmit one or more data packets. In an embodiment, the data packets being received from the portable electronic device **680** can pertain to data patch essential for updating at least a portion of the configuration information. In one embodiment, the data packets being transmitted from the control panel **510** to the portable electronic device **680** may pertain to current software version, current configuration information, or system logs, alert logs, etc. related to the control panel **510** or other devices of the fire alarm system **500**.

[0146] Still referring to FIGS. **9** and **10**, the processing circuit **620** includes a memory **750**, a processor **760**, and a repository **770**. The processing circuit **620** is communicatively coupled with the communication interface **630** and the communication module **640** such that the processing circuit **620** and various components thereof can send and receive data and/or signals. Processor **760** can be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable electronic processing components.

[0147] Memory **750** (e.g., memory, memory unit, storage device, etc.) can include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage, etc.) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present application. Memory **750** can be or include volatile memory or non-volatile memory. Memory **750** can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present application. According to some embodiments, memory **750** is communicably connected to processor **760** via processing circuit **620** and includes computer code

for executing (e.g., by processing circuit **620** and/or processor **760**) one or more processes described herein.

[0148] Referring to FIG. **9**, the repository **770** is communicatively connected to the processor **760**. The repository **770** can include one or more devices (e.g., ROM, Flash memory, hard disk storage, etc.) configured for storing historical data associated with one or more input devices **520**, configuration information pertaining to the fire alarm system **500** including its devices and control panel **510**, status reports of one or more input devices **520** and/or output devices **530**, access history, and historical data pertaining to generation of alert signals by one or more input devices **520**, among others. In an embodiment, the repository **770** can be or include non-volatile memory and/or volatile memory. Repository **770** can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present application. Although, the repository **770** is shown as part of the processing circuit **620** it is to be understood that the repository **770** can be a separate unit. In an embodiment, the repository **770** can correspond to a remote data storage or remote database.

[0149] The configuration information stored in the repository **770** includes information related to device details and their operations. For example, the configuration information can include, name, type, location, operating conditions, labels, zones, operating parameters, operating codes, firmware etc. of the devices and/or the control panel **510** of the fire alarm system **500**. However, the term 'configuration information' used in the present disclosure is not limited to aforementioned attributes and can include any type of data related to identification, operation, and control of the devices and/or the control panel **510** of the fire alarm system **500**. The configuration information is required to be updated when a new device is to be incorporated in the fire alarm system **500** or attributes or data related to existing device of the fire alarm system **500** are to be altered. In such cases, a part of the configuration information related to new or existing device is updated.

[0150] To update at least a part of the configuration information, the processing circuit **620** establishes short-range wireless communication with the portable electronic device **680** via the communication module **640**. The portable electronic device **680** transmits one or more data packets having updated configuration information or one or more data patches. The processing circuit **620** receives the one or more data packets and updates at least a part of the prestored configuration information using received data packets from the portable electronic device **680**. In some embodiments, the processing circuit **620** updates configuration information using one or more data packets. In some other embodiments, the processing circuit **620** replaces the existing configuration information with latest configuration information received via one or more data packets. In some embodiments, the processing circuit **620** modifies only a part of configuration information using the received one or more data packets.

[0151] Referring to FIGS. **10**, the memory **750** is shown to include an authenticator **780** that is configured to authenticate a user of the portable electronic device **680**. In some embodiments, the authenticator **780** may prompt the user to provide user credentials in form of user input via the user interface **650** of the control panel **510** prior to accessing one or more functionalities of the control panel **510**. In some other embodiments, the authenticator **780** may prompt the user to provide user credentials via the user interface **650** prior establishing short-range wireless communication between the control panel **510** and the portable electronic device **680**. The user credentials can include, but not limited to, passwords, biometric details, pattern, etc. The authenticator **780** is configured to validate the user credentials with prestored user credentials. The authenticator **780** generates an authentication signal indicating successful authentication, i.e., when received credentials are in confirmation with the prestored user credentials. Subsequently, the user is allowed to access to one or more functionalities of the control panel **510**. In an alternative event, the authenticator **780** is configured to generate a flag signal when validation of user credential is unsuccessful. The processing circuit **620** denies access to the user and displays an error message on

the user interface **650**. Additionally, the processing circuit **620** may generate notification via one or more indicators **720** provided on the user interface **650** regarding successful authentication or failed authentication.

[0152] The memory **750** further includes a communication activator **790** provided to activate the communication module **640**. The communication activator **790** activates the communication module **640** based on successful authentication, on receiving command from the user for activating the communication module **640** via the user interface **650**, or both. In some embodiments, the communication activator **790** is in communication with the authenticator **780** and activates the communication module **640** upon receiving the authentication signal generated by the authenticator **780**. In case the communication activator **790** receives the flag signal from the authenticator **780** which signifies that the authentication was failed, the communication activator **790** denies activation of the communication module **640** and can prompt a message about the same on the user interface **650**.

[0153] In some embodiments, wherein the authenticator **780** authenticates the user prior to accessing one or more functionalities of the control panel **510**, the communication activator **790** is configured to activate communication module **640** upon receiving a command from the user for initiating communication module **640** via the user interface **650**. In this case, the communication activator **790** may not require the authentication signal as the user cannot access the control panel **510** for providing the command for initiating communication module **640** without successful authentication. In some embodiments, the processing circuit **620** may prompt a user to authenticate prior to selecting the command for initiating communication module **640** or after selecting the command for initiating communication module **640**.

[0154] In some embodiments, the communication activator **790** activates the communication module **640** for a predetermined time period until the portable electronic device **680** is connected/paired to the communication module **640** via short-range wireless communication. The predetermined time period can be stored in the repository **770**. To establish the communication, the portable electronic device **680** needs to have an active short-range communication facility and should be in proximity with the communication module **640**, more specifically with the data transfer region **580**. Once the portable electronic device **680** is in communication with the communication module **640** via short-range communication, data packets are transferred between the portable electronic device **680** and the control panel **510**. The data packets can be transmitted in batches or all at once as per user preference.

[0155] In case any device (for example, the portable electronic device **680**) is not connected or not in communication with the communication module **640** for the predetermined time period, the communication activator **790** deactivates the communication module **640**. The communication activator **790** can include a timer or a counter to determine time elapsed post activation of the communication module **640**.

[0156] In some embodiments, the communication activator **790** is configured to display status of data transfer on the user interface **650**. For example, the communication activator **790** can display a message 'NFC Transfer: IN PROGRESS' (as shown in FIG. **14**) and showing progress of data transfer in filled blocks on the user interface **650**.

[0157] Still further, the memory **750** is shown to include a data validator **800** that is configured to receive data packets from the portable electronic device **680** through the communication module **640**. The data validator **800** is responsible for validating the one or more data packets received from the portable electronic device **680** prior to utilizing the data packets to update the configuration information. The data validator **800** validates the data packets based on predetermined rules or test logic. In one example, the data validator **800** may include a debugger that scans the data packets to one or more errors in the received data packets. In one other example, the data validator **800** can check if the received data packets are related to the fire alarm system **500** or whether the received data packets are corrupted, tampered, partially received, etc. Once the data

packets are validated, the data validator **800** tags those data packets as valid and additionally generates a data validation signal. If the data validator **800** determines that one or more data packets of the received data packets are invalid, the data validator **800** may tag such data packets as invalid and may additionally generate a data invalid signal. In some embodiments, the data validator **800** can generate data validation or data invalidation signals corresponding to each of the received data packets separately. In some embodiments, the data validator **800** stores received data packets with timestamp in the repository **770**.

[0158] Still referring to FIG. **10**, the memory **750** is shown to include a data updater **810**. The data updater **810** is configured to cooperate with the data validator **800** to receive validation and/or invalidation signals. The data updater **810** is configured to update at least a part of the configuration information based on tagging provided by the data validator **800**. That is, the data updater **810** updates the configuration data utilizing only those data packet(s) that are tagged as valid and further configured to discard the data packet(s) that are tagged as invalid. In some embodiments, the data updater **810** may check for tagging of the data packets subsequent to reception of the validation signal and/or invalid signal. That is, in case the validation signals are generated for particular data packets, the data updater **810** updates the configuration information using only those data packets for which validation signals are provided by the data validator **800**. In some embodiments, updating the configuration information includes, but not limited to, updating full or partial panel configuration, upgrading panel firmware etc.

[0159] In some embodiments, the data updater **810** is configured to reboot the control panel **510** to update the configuration information. Once the updating of configuration information is completed, the data updater **810** is configured to display a message (for example, 'updating task complete') indicating completion of the configuration information updating on the user interface **650**. The data updater **810** is further configured to detect errors or failure while updating the configuration information. The data updater **810** is configured to display a message (for example, 'error in updating') on the user interface **650** indicating failure or errors in updating configuration information. The data updater **810** is configured to fall back or roll back to historical configuration information upon detecting failure in updating the configuration information. In an embodiment, the historical configuration information relates to a last known configuration information that was being utilized by the control panel **510** prior updating. The historical configuration information is stored in the repository **770**.

[0160] In some embodiments, the processing circuit **620** is configured to provide indications based on signals generated by other components of the processing unit **620**. In some embodiments, the processing circuit **620** provide the indicators **720** on the user interface **650**. For example, the processing circuit **620** can provide visual indication by turning ON an indication lamp **740** when data packets are being transferred between the portable electronic device **680** and the control panel **510**. In some embodiments, the processing circuit **620** can generate audio alarms corresponding to the indications.

[0161] In an aspect of the present disclosure, a user gains access of the control panel **510** by authenticating himself. In some embodiments, as shown in FIG. **11**, the user interface **650** displays and provides multiple options to the user. The multiple options include, but are not limited to, auto, device, output, gateway, USB, system, default, device mapping, and NFC. Here, NFC denotes short-range communication. The user can select desired option using the user input means **710**. For transfer of one or more data packets, the user needs to select option 'NFC'. In some embodiments, the authenticator **780** authenticates the user before the communication module **640** is activated, i.e., the user interface **650** may prompt the user to provide credential to activate short-range wires communication post selection of option 'NFC'. The provided credentials are then verified by the authenticator **780**. In some embodiments, the authenticator **780** authenticates the user before displaying aforementioned options on the user interface **650**. After successful authentication, the communication activator **790** activates the communication module **640** and displays a message

‘Waiting for NFC Transmission to start; Hold your mobile near NFC Reader’ (as shown in FIG. 12) on the display of user interface. The user needs to place the portable electronic device **680** with an active short-range communication facility (for example, NFC) proximal to the communication module **640** or the data transfer region **580** in order to initiate data transmission. In some embodiments, the user is required to keep the portable electronic device **680** in physical contact with the data transfer region **580**. Once the short-range communication between the portable electronic device **680** and the communication module **640** is established, the communication activator **790** displays a message ‘NFC Transfer: IN PROGRESS’ (as shown in FIG. 13) with filled blocks showing the progress of data transfer. In some embodiments, after establishing communication, the processing circuit **620** receives confirmation from the user about receiving data packets via the short-range communication. The processing circuit **620** may display a message ‘Load NFC Data’ (as shown in FIG. 14). Once the user confirms the data transfer by selecting this option, the data validator **800** initiates receiving data packets from the portable electronic device **680** via the communication module **640**. It is to be noted that aforementioned operative configuration is elaborated for explanation purposes and can be altered as per user's requirement. The processing circuit **620** is also configured to display various other messages for example, completion of data transfer, updating the configuration, rebooting system, failure in updating activity etc., on detection of corresponding events.

[0162] In an embodiment, the portable electronic device **680** includes a processor, a memory, a display, and a wireless I/O. The processor works in combination with wireless I/O in order to communicate with the control panel **510**. The portable electronic device **680** is provided with a near-field communication module to facilitate communication with communication module **640** of the control panel **510**. In one embodiment, the near-field communication module can be detachably attached to the portable electronic device **680** to enable communication with control panel **510**. The portable electronic device **680** may be configured, via software resident in the memory, to access one or more aspects of the control panel **510**. For example, the portable electronic device **680** may access one or more data residing in the repository **770** of the control panel **510**. In some embodiments, the portable electronic device **680** can transmit a request to the control panel **510**, wherein the processing circuit **620** of the control panel **510** is configured to process the request and provide data corresponding to the request to the portable electronic device **680** via the communication module **640**. For example, a user can put a request through the portable electronic device **680** regarding extracting diagnostics logs from the repository **770** of the control panel **510**. The processing circuit **620** receives the request, processes it, extracts diagnostics logs data and transmits the diagnostics logs data to the portable electronic device **680** via the communication module **640**.

[0163] In one non-limiting embodiment, the display of the portable electronic device **680** may be used to duplicate the user interface **650** of the control panel **510**. The display of the portable electronic device **680** can be configured to accept user commands. For example, a user may enter commands via display of the portable electronic device **680**. The display of portable electronic device **680** can be a touchscreen.

[0164] The memory, of the portable electronic device **680**, may include software configuration tools in order for the portable electronic device **680** to configure the control panel **510**. The software configuration tools resident in the portable electronic device **680** may be the same as the software configuration tools resident at the control panel **510**. Alternatively, the software configuration tools resident in the portable electronic device **680** may be different from the software configuration tools resident at the control panel **510**, such as including a different user interface.

[0165] Further, the portable electronic device **680** is communicatively connected with a server (not shown in figures). In an embodiment, the server can be one or more of a cloud server, a remote server, an on-premises server, a personal computer, and the like. The portable electronic device **680**

is configured to receive data packets regarding updates of configuration information or a portion of updated configuration information pertaining to the control panel **510** from server. The updated configuration information can be fed to the control panel **510** by the portable electronic device **680** utilizing communication module **640**. In one embodiment, the updated configuration information can be pre-stored within the memory of the portable electronic device **680**. The portable electronic device **680** can be provided with a software based application to download data packets and transmit to the control panel **510**. The application can be downloaded from the server. The application can be configured to authenticate the portable electronic device **680**. The authentication can be performed using a list of allowed portable devices with their specific IDs, passwords, specific IDs provided by manufacturer of the control panel **510**, etc.

[0166] Present disclosure envisages a method for updating configuration information of the control panel. The method includes steps of establishing a short-range wireless communication with a portable electronic device; receiving one or more data packets from the portable electronic device; and updating at least a part of configuration information using the one or more data packets.

[0167] Referring now to FIG. **15**, a method **900** for updating configuration information of the control panel **510** is described in more details. Steps of the method **900** can be executed using the processing circuit **620**. The method **900** includes a step **920** of establishing a short-range wireless communication with the portable electronic device **680**. The control panel **510** includes the communication module **640** provided with the NFC unit **690** that can establish short-range wireless communication with the portable electronic device **680**. In some embodiments, the portable electronic device **680** is required to be proximal or in physical contact with the data transfer region **580** to establish the short-range communication with the NFC unit **690**.

[0168] In some embodiments, the method **900** includes a step **910** of authenticating a user of the portable electronic device **680** prior to establishing the short-range wireless communication via the authenticator **780** of the processing circuit **620**. The processing circuit **620** includes the authenticator **780** that authenticates a user prior to establishing short-range wireless communication. The authenticator **780** can authenticate the user based on user credentials received from the user such as passwords, patterns, biometric details etc.

[0169] In some embodiments, the user is authenticated by the authenticator **780** before accessing one or more functionalities of the control panel **510**. In some other embodiments, the user is authenticated by the authenticator **780** before activating the communication module **640**.

[0170] The short-range wireless communication between the portable electronic device **680** and the control panel **510** is established using a near field communication (NFC) unit of the communication module **640** (step **920**). In some embodiments, the processing circuit **620** activates NFC unit **690** after authenticating a user of the portable electronic device **680**. The short-range wireless communication between the portable electronic device **680** and the communication module **640** is established when the portable electronic device **680** is proximal to the data transfer region **580**.

[0171] The method **900** further comprises a step **930** of receiving one or more data packets from the portable electronic device **680**. The processing circuit **620** receives the data packets from the portable electronic device **680** through the communication module **640** and validates the data packets. The processing circuit **620** can validate individual data packets and provide tags to them

[0172] In some embodiments, the method **900** comprises a step **940** of validating the one or more data packets received from the portable electronic device **680**. The processing circuit **620** validates the data packets and tags them as valid or invalid. The tags can be provided to each data packet individually or to batches of data packets or to all data packets received.

[0173] The method **900** further comprises a step **950** of updating at least a part of configuration information using the one or more data packets. The configuration information is typically stored in the repository **770**. The processing circuit **620** utilizes valid data packets to update the configuration information. The configuration information can be updated partially or completely

based on valid data packets. For example, the processing circuit **620** may receive data packets corresponding to a new device, validates the data packet, and add/update information in the data packet in the configuration information. In another example, the processing circuit **620** may receive data packets corresponding to an existing device whose configuration information is preloaded in the repository **770**, validates the data packet, and update a part of the configuration information corresponding to the existing device with valid data packets.

[0174] The present disclosure utilizes short-range communication as one of the preferred ways of communication over Wi-Fi, Bluetooth, and other known wireless technologies due to following advantages: [0175] Short-range communication such as NFC consumes least amount of power. For example, a typical NFC unit consumes less than 100 mW power, whereas power consumption of Bluetooth is around 250 mW and that of Wi-Fi is around 2 to 3 W; [0176] Data Transfer rate of NFC is superior; [0177] Minimal interference since the devices connected using NFC are required to be in proximity to each other; and [0178] NFC is an encrypted method of transferring data over wireless means making it one of the safest means of wireless transmission because of protocols like ISO/IEC 15693, ISO/IEC 18000-3, ISO/IEC 14443 A and B, and FeliCa.

Technical Advancements

[0179] The present disclosure described herein above has several technical advantages including, but not limited to, the realization of a control panel for fire alarm systems that: [0180] is cost effective; [0181] is user friendly; [0182] eliminates set up time required for establishing communication link; and [0183] eliminates need of wired connection with portable electronic devices.

Configuration of Exemplary Embodiments

[0184] The construction and arrangement of the apparatus, systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements can be reversed or otherwise varied, and the nature or number of discrete elements or positions can be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps can be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions can be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

[0185] The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure can be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general-purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or

group of functions.

[0186] Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also, two or more steps can be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

Claims

1. A control panel for a fire alarm system, the control panel comprising: a communication module for short-range communication with a portable electronic device; and a data transfer region, wherein the communication module is configured to establish short-range communication with the portable electronic device when the portable electronic device is proximal to the data transfer region.
2. The control panel of claim 1, wherein the communication module includes a near field communication (NFC) unit.
3. The control panel of claim 1, wherein the data transfer region is an opening provided on a housing of the control panel.
4. The control panel of claim 1, wherein the data transfer region is defined via markings on a housing of the control panel.
5. The control panel of claim 1, wherein the data transfer region overlaps the communication module.
6. The control panel of claim 1 further comprising a processing circuit configured to store configuration information pertaining to the fire alarm system, to receive one or more data packets from the portable electronic device via short-range wireless communication, and to update at least a part of the configuration information using the one or more data packets.
7. A control panel for a fire alarm system, the control panel comprising: a communication module to establish a short-range wireless communication with a portable electronic device; and a processing circuit configured to: store configuration information pertaining to the fire alarm system; receive one or more data packets from the portable electronic device via the short-range wireless communication; and update at least a part of the configuration information using the one or more data packets.
8. The control panel of claim 7, wherein the processing circuit is configured to authenticate a user of the portable electronic device prior to receiving the one or more data packets.
9. The control panel of claim 8, wherein the processing circuit is configured to receive one or more user credentials of the user via a user interface of the control panel.
10. The control panel of claim 7, wherein the communication module includes a near field communication (NFC) unit to establish short-range wireless communication.
11. The control panel of claim 7, wherein the processing circuit is configured to fall back to historical configuration information upon detecting failure in updating the configuration information.
12. The control panel of claim 7, wherein the processing circuit is configured to validate the one or more data packets received from the portable electronic device prior to updating the configuration information.
13. The control panel of claim 7 further comprising a data transfer region, wherein communication between the communication module and the portable electronic device is established when the portable electronic device is proximal to the data transfer region.
14. The control panel of claim 13, wherein the data transfer region overlaps the communication

module.

15. A method comprising: establishing a short-range wireless communication with a portable electronic device; receiving one or more data packets from the portable electronic device; and updating at least a part of configuration information using the one or more data packets.

16. The method of claim 15 further comprising a step of authenticating a user of the portable electronic device prior to establishing the short-range wireless communication.

17. The method of claim 15 further comprising validating the one or more data packets received from the portable electronic device prior updating the configuration information.

18. The method of claim 15, wherein the short-range wireless communication is established using a near field communication (NFC) unit.

19. The method of claim 18 further comprising activating near field communication (NFC) unit upon authenticating a user of the portable electronic device.

20. The method of claim 15, wherein the short-range wireless communication between the portable electronic device and a communication module is established when the portable electronic device is proximal to a data transfer region of a control panel.
