

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409409
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Hiyama; Tsutomu

Condensation device, flux recovery device, soldering device, water vapor removing method, flux recovery method and solder processing method

Abstract

Provided is a condensation device capable of removing water vapor from a larger amount of gas without making a size larger than in related art. A condensation device **700** according to the present invention includes an outer cooling unit **720** including one or two or more inner tubes **722**, an outer tube **724** located outside the one or two or more inner tubes **722**, and a first flow path **726** through which a first cooling medium passes between the one or two or more inner tubes **722** and the outer tube **724**.

Inventors:	Hiyama; Tsutomu (Tokyo, JP)
Applicant:	SENJU METAL INDUSTRY CO., LTD. (Tokyo, JP)
Family ID:	72668398
Assignee:	SENJU METAL INDUSTRY CO., LTD. (Tokyo, JP)
Appl. No.:	17/600567
Filed (or PCT Filed):	March 06, 2020
PCT No.:	PCT/JP2020/009608
PCT Pub. No.:	WO2020/203033
PCT Pub. Date:	October 08, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220126236 A1	Apr. 28, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: **B23K1/00** (20060101); **B01D5/00** (20060101); **B01D53/00** (20060101); **B01D53/26** (20060101); **B23K3/08** (20060101); **F28D7/00** (20060101); **F28D7/12** (20060101); **F28D7/16** (20060101); **F28F1/24** (20060101); F28F9/02 (20060101); H05K3/34 (20060101)

U.S. Cl.:

CPC **B01D53/265** (20130101); **B01D5/0003** (20130101); **B01D5/0012** (20130101); **B01D5/0039** (20130101); **B01D53/002** (20130101); **B23K3/082** (20130101); **F28D7/0083** (20130101); **F28D7/12** (20130101); **F28D7/16** (20130101); **F28F1/24** (20130101); B01D2221/14 (20130101); B01D2257/80 (20130101); F28F9/0258 (20130101); H05K3/3494 (20130101)

Field of Classification Search

CPC: B01D (53/265); B23K (1/008); F28D (7/106); F28D (2021/0038); F28F (1/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4638852	12/1986	Basseen	165/47	B01D 53/265
6385978	12/2001	Elliott	62/93	B01D 53/265
6994833	12/2005	Nishimura et al.	N/A	N/A
2016/0279726	12/2015	Hiyama	N/A	B23K 3/0653

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104673331	12/2015	CN	N/A
3300929	12/1983	DE	N/A
19653613	12/1997	DE	N/A
3064304	12/2015	EP	N/A
260066	12/1925	GB	N/A
S56-010904	12/1980	JP	N/A
2004-327893	12/2003	JP	N/A
2006-284004	12/2005	JP	N/A
2011-060856	12/2010	JP	N/A
5761467	12/2014	JP	N/A
WO-2015-064143	12/2014	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for corresponding EP Application 20783006.8, dated Nov. 7, 2022 (9 pages). cited by applicant
Office Action issued in JP-2019-072420 dated Oct. 25, 2019 (with English Translation) (10 pages). cited by applicant

Office Action issued in JP-2019-072420 dated Feb. 6, 2020 (with English Translation) (8 pages).

cited by applicant

Office Action issued in JP-2019-072420 dated Apr. 6, 2020 (with English Translation) (10 pages).

cited by applicant

Office Action issued in JP-2019-072420 dated Aug. 20, 2020 (with English Translation) (14 pages).

cited by applicant

International Search Report (in English and Japanese) of the International Searching Authority

issued in PCT/JP2020/009608, mailed Apr. 14, 2020; ISA/JP. cited by applicant

Primary Examiner: Ruppert; Eric S

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase Application under 35 U.S.C. 371 of International Application No. PCT/JP2020/009608 filed on Mar. 6, 2020, which claims the benefit of priority from Japanese Patent Application No. 2019-072420 filed Apr. 5, 2019. The entire disclosures of all of the above applications are incorporated herein by reference.

TECHNICAL FIELD

(2) The present invention relates to a condensation device, a flux recovery device, a soldering device, a water vapor removing method, a flux recovery method and a solder processing method.

BACKGROUND ART

(3) In a case of soldering an electronic component to a circuit board, a soldering device such as a reflow furnace or a jet soldering device is used. When the soldering is performed, flux is applied to a soldering location of the circuit board. The flux is applied to remove an oxide film of a metal surface to be soldered, and to prevent the metal surface from being re-oxidized during heat treatment in a soldering process. The flux is obtained mainly by dissolving a solid component such as rosin, thixotropic agent, or activator in solvent. In a case of applying the flux to the circuit board, for example, in a case of using the reflow furnace, solder paste obtained by mixing and pasting flux and solder powder is used, and in a case of using the jet soldering device, flux is applied directly to the board with a fluxer.

(4) When the flux is applied as the solder paste or with the fluxer, especially the solvent in a flux component vaporizes to form flux fume in a preheating unit before the soldering. In a main heating unit where the soldering is performed, especially a solid component such as rosin in the flux component vaporizes to form the flux fume that floats in the device. When these flux fumes come in contact with a part having a comparatively low temperature in the device, for example, a chain conveyor that conveys the circuit board, the fumes are cooled and condensed, and when temperature further drops, a sticky solid is formed. This solid adheres and is deposited onto each part in the soldering device, and the device might cause a defect. For example, in a case where a large amount of solid adheres on the chain conveyor, the circuit board does not leave the conveyor and is caught up in a sprocket of the conveyor, and the circuit board is damaged. Further, when the solid adheres on the circuit board being conveyed, the circuit board is stained. Therefore, a flux recovery device is used to separate and remove the flux component from a gaseous mixture of atmosphere in the soldering device or inert atmosphere of nitrogen or the like and the flux component.

(5) Here, an example of the flux recovery device is described in Patent Literature 1. The flux

recovery device described in PTL1 includes a first water spray unit that sprays water to the gaseous mixture, and a separation unit that separates the flux component from the gaseous mixture. Also, the separation unit comprises an introduction part that introduces the gaseous mixture into an upper part, a flux component separating tubular body including an upper opening and a lower conical portion, and a lid engaged in the opening in the tubular body. Furthermore, the lid includes a disc-shaped main body, and a cylindrical portion for exhaust having a predetermined length is provided to penetrate the main body.

(6) According to this flux recovery device, when the gaseous mixture is taken into the introduction part from a tangential direction of the tubular body, the gaseous mixture is mixed with water to form a swirling flow. Then, the flux contained in the gaseous mixture is cooled with water supplied into the separation unit. Consequently, most of the flux starts to be liquefied and solidified, and the flux is coated with the sprayed water. That is, flux is mixed with water, and removed as water containing flux from the gaseous mixture. Afterward, gas from which flux is removed is sucked out from the cylindrical portion. Consequently, this flux recovery device can separate the flux from the gaseous mixture.

(7) Furthermore, water is for use in separating flux, and hence gas from which flux is removed contains a lot of water vapor. When water vapor generated in a separation process flows into a solder processing unit, the water vapor condenses and becomes waterdrops in a low temperature part of the solder processing unit. When the waterdrops adhere on an interior of the furnace, rusting is caused. Also, when the waterdrops adhere on the circuit board, the circuit board absorbs moisture. The circuit board that absorbs moisture is heated during solder processing, and thereby the moisture absorbed evaporates. This evaporation of water might cause a phenomenon where solder in a soldered region scatters. When the solder scattering occurs, a soldering defect that the scattered solder causes an electrical short circuit across terminals, that is, so-called solder bridge is caused. Further, the circuit board that absorbs moisture might be a factor that causes deterioration of the soldered region due to changes over years, or migration. The water vapor that enters the furnace might cause defects related to reliability of the circuit board. Furthermore, water to be reused might decrease. To solve this problem, this flux recovery device further includes condensation means for removing water vapor from the gas from which flux is removed. In PTL 1, as the condensation means, water-cooled coil type condensation means and air-cooled multi-tube type condensation means are disclosed.

(8) The water-cooled coil type condensation means is a box body, and comprises a coiled pipe having satisfactory thermal conductivity inside the box body. Then, in the water-cooled coil type condensation means, liquid such as water flows into the coiled pipe, to cool a surface of the pipe. Consequently, when the gas containing water vapor passes through an interior of the box body of this condensation means, the gas is cooled and condensed by the coiled pipe inside the box body. Then, through the condensation, water vapor is removed from the gas containing water vapor.

(9) Also, the air-cooled multi-tube type condensation means is a box body, and includes a pipe group including one or more pipes inside the box body. Then, cold air flows through interiors of the pipes in the group, to cool surfaces of the pipes in the group. Consequently, when the gas containing water vapor passes through the interior of the box body of this condensation means, the gas is cooled and condensed by the pipe group inside the box body. Then, through the condensation, water vapor is removed from the gas containing water vapor.

(10) Therefore, in the flux recovery device described in PTL 1, dry gas can be generated from the gas containing water vapor by use of the water-cooled coil type condensation means or the air-cooled multi-tube type condensation means. Consequently, this flux recovery device can collect flux from the gaseous mixture containing the flux component that is generated in the solder processing unit, and supply the dry gas to the solder processing unit again.

CITATION LIST

Patent Literature

SUMMARY OF INVENTION

Technical Problem

(12) As described above, a flux recovery device described in PTL 1 comprises condensation means, to remove water vapor from gas containing water vapor, the gas being generated during recovery of flux. An amount of the gas containing water vapor that can be treated with the condensation means is related with an amount of the gaseous mixture that can be treated with the flux recovery device, and is therefore important.

(13) However, in two condensation means described above, the gas containing water vapor is cooled mainly by a coiled pipe or a pipe group inside a box body. Consequently, to increase the amount of the gas containing water vapor that can be treated per unit time by the condensation means, a length of the coiled pipe is required to be increased, or a number of pipes constituting the pipe group is required to be increased. In this case, there is concern that the condensation means itself increases in size and that the flux recovery device or a soldering device including this condensation means also increases in size.

(14) Therefore, in view of the above-described problems, an object of the present invention is to provide a condensation device, a flux recovery device, a soldering device, a water vapor removing method, a flux recovery method and a solder processing method that are capable of removing water vapor from a larger amount of gas without making a size larger than in related art.

Solution to Problem

(15) (Aspect 1)

(16) A condensation device according to Aspect 1 comprises an outer cooling unit including one or two or more inner tubes, an outer tube located outside the one or two or more inner tubes, and a first flow path through which a first cooling medium passes between the one or two or more inner tubes and the outer tube.

(17) In the condensation device according to Aspect 1, in a case where gas containing water vapor is distributed inside the inner tube of the outer cooling unit, the gas containing water vapor comes in contact with the inner tube of the outer cooling unit. Consequently, the gas containing water vapor is cooled by the inner tube of the outer cooling unit. Therefore, this condensation device can condense water vapor, and remove water vapor from the gas containing water vapor. Particularly in a case where the condensation device according to Aspect 1 comprises plural inner tubes, the device can cool the gas containing water vapor more quickly, and remove water vapor from a large amount of gas without making a size larger than in related art.

(18) (Aspect 2)

(19) In a condensation device according to Aspect 2, the condensation device according to Aspect 1 further comprises a heat absorption member that is located inside at least one inner tube in the one or two or more inner tubes, and that comes in contact with the outer cooling unit.

(20) In the condensation device according to Aspect 2, the gas containing water vapor is cooled by the outer cooling unit and the heat absorption member. Consequently, in the condensation device according to Aspect 2, a surface area of a part that cools the gas containing water vapor increases as compared with condensation means of PTL 1. Therefore, this condensation device can remove water vapor from a larger amount of gas without making a size larger than in the related art, due to increase in contact area with the gas.

(21) (Aspect 3)

(22) In a condensation device according to Aspect 3, the condensation device according to Aspect 1 or Aspect 2 further comprises an inner cooling unit located inside the one or two or more inner tubes and including a second flow path through which a second cooling medium passes.

(23) In the condensation device according to Aspect 3, the gas containing water vapor is cooled by the inner tube of the outer cooling unit and the inner cooling unit. Consequently, in the condensation device according to Aspect 3, the surface area of the part that cools the gas containing

water vapor increases as compared with the condensation means of PTL 1. Therefore, this condensation device can remove water vapor from a larger amount of gas without making a size larger than in the related art, due to the increase in contact area with the gas.

(24) (Aspect 4)

(25) In a condensation device according to Aspect 4, the condensation device according to Aspect 3 further comprises a heat absorption member that is located inside the one or two or more inner tubes and outside the inner cooling unit, and that comes in contact with the inner cooling unit.

(26) In the condensation device according to Aspect 4, the gas containing water vapor is cooled by the inner tube of the outer cooling unit, the inner cooling unit and the heat absorption member. That is, in this condensation device, the surface area of the part that cools the gas containing water vapor increases more than in the condensation device according to Aspect 3. Therefore, this condensation device can cool the gas containing water vapor more quickly due to the increase in contact area with the gas.

(27) (Aspect 5)

(28) According to a condensation device of Aspect 5, in the condensation device according to Aspect 4, the heat absorption member includes a plurality of fins.

(29) In the condensation device according to Aspect 5, with the plurality of fins, a contact area of a fin that comes in contact with the gas containing water vapor can increase more than with one fin. That is, this condensation device can cool the gas containing water vapor more quickly due to the increase in contact area.

(30) (Aspect 6)

(31) According to a condensation device of Aspect 6, in the condensation device according to Aspect 4 or Aspect 5, the inner cooling unit has a straight tube shape, the inner tube of the outer cooling unit extends in an axial direction of the straight tube shape of the inner cooling unit, and the heat absorption member includes a first fin having a thin plate shape extending in a direction intersecting the axis.

(32) In flowing gas, gas flowing through the vicinity of the inner tube of the outer cooling unit, the inner cooling unit and the heat absorption member is cooled more than gas flowing through a position away from the inner tube of the outer cooling unit, the inner cooling unit and the heat absorption member. Consequently, in a case where the gas containing water vapor does not provide convection in an interior of the inner tube of the outer cooling unit, a difference in temperature might be made in gas to be discharged depending on a position through which the gas containing water vapor flows. In this case, there is concern that gas that is not cooled and still contains a lot of water vapor passes through the condensation device.

(33) However, according to the condensation device of Aspect 6, the first fin is disposed extending in a direction intersecting the axis. That is, the first fin is oriented to block the flow of the gas containing water vapor. Consequently, when the gas containing water vapor collides with the first fin, the convection of gas occurs in the interior of the inner tube of the outer cooling unit. In consequence, this condensation device can uniformly cool the gas containing water vapor. That is, this condensation device can inhibit the gas still containing a lot of water vapor from being passed through the condensation device.

(34) (Aspect 7)

(35) According to a condensation device of Aspect 7, in the condensation device according to Aspect 6, the first fin has a shape in which a bow-shaped cutout is formed in a thin disc shape, the heat absorption member further comprises a second fin having the same shape as in the first fin, disposed adjacent to the first fin via a space, and located on a downstream side of the first fin, and an extending direction of a chord forming the bow shape of the cutout in the first fin is different from an extending direction of a chord forming a bow shape of a cutout in the second fin.

(36) In a case where two fins having the same shape are arranged in parallel via a space and gas is blown from a direction facing a plate surface of each fin, wind is hard to flow between the two fins,

and gas between the two fins might stay. Consequently, in the case where the two fins are arranged in parallel in the condensation device, gas stays between the two fins, this gas is only cooled, gas at another position is hard to cool. However, according to the condensation device of Aspect 7, the bow-shaped cutouts are formed in the first fin and the second fin, respectively, and the extending direction of the chord forming the bow shape of the first fin is different from the extending direction of the chord forming the bow shape of the second fin. Therefore, in a case where gas passing through a portion of the first fin in which the cutout is formed flows straight forward, at least part of this gas collides with the second fin. This causes the convection of gas between the first fin and the second fin. That is, the gas between the first fin and the second fin is inhibited from staying. Therefore, this condensation device can make uniform a temperature of gas in the vicinity of the first fin and the second fin.

(37) (Aspect 8)

(38) A flux recovery device according to Aspect 8 is a flux recovery device that recovers flux from a gaseous mixture containing a flux component, and comprises a separation unit that separates flux from the gaseous mixture by use of water, and discharges gas containing water vapor and water containing flux, and the condensation device according to any one of Aspects 1 to 7 that removes water vapor from the gas discharged from the separation unit.

(39) Since the flux recovery device according to Aspect 8 comprises the condensation device according to any one of Aspects 1 to 7, this condensation device can remove water vapor from a larger amount of gas without making a size larger than in the related art in the same manner as in Aspect 1. Consequently, this flux recovery device can remove water vapor from a larger amount of gas without making a size larger than in the related art, due to increase in amount of gas to be treated by the condensation device.

(40) (Aspect 9)

(41) In a flux recovery device according to Aspect 9, the flux recovery device according to Aspect 8 further comprises a purification device to which the water containing flux that is discharged from the separation unit is supplied, and that separates flux from the water containing flux, and recovers flux, and a piping that supplies water separated from flux and purified in the purification device from the purification device to the condensation device, and at least one of the first cooling medium and the second cooling medium is water supplied from the purification device.

(42) The flux recovery device according to Aspect 9 uses water purified in the purification device as at least one of the first cooling medium and the second cooling medium. Consequently, the flux recovery device does not have to comprise another facility to supply a cooling medium for use in the first cooling medium and the second cooling medium, in addition to the purification device.

(43) (Aspect 10)

(44) In a flux recovery device according to Aspect 10, the flux recovery device according to Aspect 9 further comprises a pump that supplies the water purified in the purification device to the separation unit, a chiller unit that cools the water purified in the purification device, and a blower that blows, from the condensation device, the gas from which water vapor is removed in the condensation device.

(45) The flux recovery device according to Aspect 10 can use the water purified in the purification device as water for use by the separation unit in separating flux from a gaseous mixture. Also, the chiller unit can cool water for use in separating flux, and water for use in the first cooling medium and the second cooling medium.

(46) (Aspect 11)

(47) In a flux recovery device according to Aspect 11, the flux recovery device according to any one of Aspects 8 to 10 comprises a plurality of the condensation devices connected to one another.

(48) Since the flux recovery device according to Aspect 11 comprises the plurality of condensation devices connected to one another, water vapor can be removed from a larger amount of gas as compared with a case where the flux recovery device comprises one condensation device.

(49) (Aspect 12)

(50) A soldering device according to Aspect 12 comprises, a solder processing unit, and the flux recovery device according to any one of Aspects 8 to 11 that recovers flux from a gaseous mixture containing flux generated in the solder processing unit.

(51) Since the soldering device according to Aspect 12 comprises the flux recovery device according to any one of Aspects 8 to 11, the flux recovery device provided in the soldering device can remove water vapor from a larger amount of gas without making a size larger than in the related art, in the same manner as in Aspect 8. Consequently, this soldering device can remove water vapor from a larger amount of gas without making the size larger than in the related art.

(52) (Aspect 13)

(53) A water vapor removing method according to Aspect 13 comprises the steps of allowing a first cooling medium to pass through a first flow path between one or two or more inner tubes and an outer tube in an outer cooling unit including the one or two or more inner tubes and the outer tube located outside the one or two or more inner tubes, and allowing, in interiors of the one or two or more inner tubes, condensation of water vapor contained in gas flowing through the interiors of the one or two or more inner tubes, to remove water vapor contained in the gas.

(54) According to the water vapor removing method according to Aspect 13, the gas containing water vapor comes in contact with the inner tube of the outer cooling unit, so that the inner tube of the outer cooling unit can cool the gas containing water vapor. Therefore, this water vapor removing method is capable of condensing water vapor, and removing water vapor from the gas containing water vapor. In particular, in a case where the outer cooling unit according to Aspect 13 comprises plural inner tubes, the gas containing water vapor can be cooled more quickly, and the water vapor can be removed from a larger amount of gas without making a size larger than in the related art.

(55) (Aspect 14)

(56) In a water vapor removing method according to Aspect 14, the method according to Aspect 13 further comprises the steps of allowing a second cooling medium to pass through a second flow path included in an inner cooling unit located inside the one or two or more inner tubes, and cooling, by a heat absorption member, gas flowing through an interior of the inner tube, the heat absorption member being located inside the one or two or more inner tubes of the outer cooling unit and outside the inner cooling unit, the heat absorption member coming in contact with at least one of the outer cooling unit and the inner cooling unit.

(57) According to the water vapor removing method according to Aspect 14, each of the inner tube of the outer cooling unit, the inner cooling unit and the heat absorption member can cool the gas containing water vapor. That is, in this water vapor removing method, a surface area of a portion that cools the gas containing water vapor increases more than in the water vapor removing method according to Aspect 13. Therefore, this condensation device can cool the gas containing water vapor more quickly, due to the increase in contact area.

(58) (Aspect 15)

(59) A flux recovery method according to Aspect 15 comprises the steps of separating flux from a gaseous mixture containing flux by use of water, and generating gas containing water vapor and water containing flux, separating flux from the water containing flux, and recovering flux, and removing water vapor from the generated gas containing water vapor by the water vapor removing method according to Aspect 13 or Aspect 14.

(60) The flux recovery method according to Aspect 15 further comprises the steps of removing water vapor by the water vapor removing method according to Aspect 13. Consequently, water vapor can be removed from a larger amount of gas without making a size of a device for use in the flux recovery method according to Aspect 15 larger than in the related art.

(61) (Aspect 16)

(62) A solder processing method according to Aspect 16 comprises the steps of performing solder

processing in a solder processing unit, recovering flux from a gaseous mixture containing flux that is generated by the solder processing, by the flux recovery method according to Aspect 15, and supplying, to the solder processing unit, gas from which water vapor is removed, the gas being generated by the flux recovery method.

(63) The solder processing method according to Aspect 16 further comprises the steps of recovering flux by the flux recovery method according to Aspect 15. Consequently, water vapor can be removed from a larger amount of gas without making a size of a device for use in the solder processing method according to Aspect 16 larger than in the related art.

Advantageous Effects of Invention

(64) According to the present invention, water vapor can be removed from a larger amount of gas without making a size larger than in related art.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a structure diagram of a soldering device comprising a condensation device according to a first embodiment of the present invention.

(2) FIG. 2 is a front view showing a configuration of the condensation device shown in FIG. 1.

(3) FIG. 3 is a plan view of the condensation device shown in FIG. 2.

(4) FIG. 4 is a cross-sectional view of the condensation device taken along the A-O-B line shown in FIG. 3.

(5) FIG. 5 is a cross-sectional view of the condensation device taken along the C-C line shown in FIG. 2.

(6) FIG. 6 is a cross-sectional view of the condensation device taken along the D-D line shown in FIG. 2.

(7) FIG. 7 is a structure diagram of a condensation device according to a second embodiment of the present invention.

(8) FIG. 8 is a cross-sectional view of the condensation device taken along the E-E line shown in FIG. 7.

DESCRIPTION OF EMBODIMENTS

(9) Hereinafter, description will be made as to embodiments of the present invention with reference to the drawings. In the drawings described below, the same or corresponding constituent component is denoted with the same reference sign and description thereof will not be repeated.

First Embodiment

(10) (Entire Configuration)

(11) FIG. 1 is a structure diagram of a soldering device comprising a condensation device according to a first embodiment of the present invention. With reference to FIG. 1, a soldering device **100** comprises a solder processing unit **120** and a flux recovery device **200**. The soldering device **100** is a device that solders an electronic component to a circuit board as an example.

(12) Hereinafter, respective constituent components of the soldering device **100** will be described separately.

(13) The solder processing unit **120** performs a process related to soldering, such as a process of soldering an electronic component to a circuit board, or a process of preheating the circuit board, as an example. In the solder processing unit **120**, the circuit board to which flux is applied is used to smoothly perform the soldering. Consequently, through the soldering process or the preheating of the circuit board, flux vaporizes, and floats in an interior of the solder processing unit **120**. That is, the interior of the solder processing unit **120** is filled with a gaseous mixture containing a flux component. Note that in the present description, the gaseous mixture is gas in which gaseous flux generated during solder processing is mixed with gas that exists from beginning in the solder

processing unit **120**.

(14) The flux recovery device **200** is a device that recovers flux from the gaseous mixture containing the flux component. The flux recovery device **200** is connected to the solder processing unit **120**. Then, the flux recovery device **200** can recover flux from the gaseous mixture in the interior of the solder processing unit **120**, and supply, to the solder processing unit **120**, gas from which flux is recovered. The flux recovery device **200** comprises, as an example, a separation unit **400**, a purification device **600**, a pump **220**, a water supply tank **280**, a chiller unit **300**, three condensation devices **700a**, **700b**, and **700c**, a blower **340** and a piping **360**. Note that in FIG. **1**, to simplify the drawing, the piping through which liquid is distributed is shown as a dotted line, and the piping through which gas is distributed is shown as a dashed line.

(15) The separation unit **400** fluid-communicates with the solder processing unit **120**, and can suction the gaseous mixture from the solder processing unit **120**. Also, the separation unit **400** has a function of separating flux from the suctioned gaseous mixture by a known method. More specifically, the separation unit **400** mixes water with the gaseous mixture. Consequently, flux contained in the gaseous mixture is cooled by water. The cooled flux is liquefied or solidified. Thus, flux contained in the gaseous mixture is separated, and flux is removed from the gaseous mixture. Also, liquefied or solidified flux is coated with water used in the separation of flux, and discharged from the separation unit **400**.

(16) The condensation device **700a**, the condensation device **700b** and the condensation device **700c** have the same configuration as an example. The condensation device **700a** fluid-communicates with the separation unit **400**, the condensation device **700b** fluid-communicates with the condensation device **700a**, and the condensation device **700c** fluid-communicates with the condensation device **700b**. That is, three condensation devices **700a**, **700b** and **700c** are connected to one another. When the gas from which flux is removed in the separation unit **400** is supplied to the condensation device **700a**, the gas from which flux is removed passes through the three condensation devices **700a**, **700b**, and **700c** in order, and is discharged from the condensation device **700c**. The condensation device **700c** fluid-communicates with the blower **340**, and the gas discharged from the condensation device **700c** is supplied to the blower **340**.

(17) The separation unit **400** separates flux from the gaseous mixture by use of water as described above. Consequently, the gas from which flux is removed in the separation unit **400** contains a lot of water vapor. The condensation devices **700a**, **700b** and **700c** have a function of removing water vapor from the gas containing water vapor. Also, the three condensation devices **700a**, **700b** and **700c** are arranged to extend in a gravity direction as an example. That is, an axis L of an inner cooling unit **740** described later extends in the gravity direction (see FIG. **4**). Note that detailed configurations of the condensation devices **700a**, **700b** and **700c** will be described later.

(18) The blower **340** has a function of suctioning, from the condensation device **700c**, the gas from which water vapor is removed, and blowing, to the solder processing unit **120**, the gas from which water vapor is removed.

(19) The purification device **600** fluid-communicates with the separation unit **400**. Consequently, the water containing flux that is discharged from the separation unit **400** is supplied to the purification device **600**. Also, the purification device **600** includes a purification tank **620** and an ozone generator **640** as an example. The purification device **600** stores the supplied water containing flux in the purification tank **620**. Further, the ozone generator **640** supplies bubbles of ozone to the purification tank **620**. Consequently, the purification device **600** decomposes flux by use of ozone. Afterward, the purification device **600** passes the water containing decomposition of flux through a filter. Thus, the decomposition is adsorbed on the filter, and hence the purification device **600** can separate flux from the water containing flux, to purify water.

(20) Further, the purification device **600** fluid-communicates with the separation unit **400** via the pump **220**. Consequently, the pump **220** can supply, to the separation unit **400**, water purified in the purification device **600**.

(21) The piping **360** connects the purification device **600** to the three condensation devices **700a**, **700b**, and **700c**. Consequently, the piping **360** can supply the water purified by separating flux in the purification device **600** from the purification device **600** to the condensation devices **700a**, **700b**, and **700c**.

(22) The chiller unit **300** is attached to the purification device **600**. The chiller unit **300** can cool the water purified in the purification device **600**, and return the water to the purification device **600** again. Consequently, a temperature of the water purified and stored in the purification device **600** is about 5 degrees centigrade as an example.

(23) Water that comes short while being circulated is supplied from the water supply tank **280** to the purification tank **620**.

(24) (Condensation Device)

(25) Next, description will be made as to more detailed configuration of the condensation devices **700a**, **700b**, and **700c** with reference to FIG. 2 to FIG. 6. Since the condensation devices **700a**, **700b** and **700c** have the same configuration, the condensation devices **700a**, **700b** and **700c** are represented and described as a condensation device **700**. FIG. 2 is a front view showing a configuration of the condensation device **700** shown in FIG. 1. FIG. 3 is a plan view of the condensation device **700** shown in FIG. 2. FIG. 4 is a cross-sectional view of the condensation device **700** taken along the A-O-B line shown in FIG. 3. FIG. 5 is a cross-sectional view of the condensation device **700** taken along the C-C line shown in FIG. 2. Further, FIG. 6 is a cross-sectional view of the condensation device **700** taken along the D-D line shown in FIG. 2.

(26) With reference to FIG. 2, the condensation device **700** includes an outer cooling unit **720**, the inner cooling unit **740**, a heat absorption member **760**, a gas inlet **702** and a gas outlet **704**. The condensation device **700** has a tubular shape as an example, as seen from FIG. 2 and FIG. 3.

(27) With reference to FIG. 4, the outer cooling unit **720** includes an inner tube **722**, an outer tube **724** located outside the inner tube **722**, a first flow path **726** through which a first cooling medium passes between the inner tube **722** and the outer tube **724**, a first cooling medium inlet **728**, and a first cooling medium outlet **730**. As an example, the first cooling medium inlet **728** is located below the first cooling medium outlet **730** in the gravity direction. In addition, water supplied from the purification device **600** is supplied from the first cooling medium inlet **728** to the first flow path **726**, and discharged from the first cooling medium outlet **730**. Afterward, the discharged water is returned to the purification device **600**. Therefore, water supplied from the purification device **600** is for use as the first cooling medium. Also, the inner tube **722** of the outer cooling unit **720** extends in an extending direction of the axis L as an example.

(28) The inner cooling unit **740** is located inside the inner tube **722** of the outer cooling unit **720**, and includes a second flow path **742** through which a second cooling medium passes, a second cooling medium inlet **744**, and a second cooling medium outlet **746**. Also, the inner cooling unit **740** has, as an example, a straight tube shape around the axis L as a central axis. Further, as an example, the second cooling medium inlet **744** is located below the second cooling medium outlet **746** in the gravity direction. In addition, water supplied from the purification device **600** is supplied from the second cooling medium inlet **744** to the second flow path **742**, and discharged from the second cooling medium outlet **746**. Afterward, the discharged water is returned to the purification device **600**. Therefore, the water supplied from the purification device **600** is used as the second cooling medium.

(29) The heat absorption member **760** is located inside the inner tube **722** of the outer cooling unit **720** and outside the inner cooling unit **740**, and comes in contact with the inner cooling unit **740**. The heat absorption member **760** includes a first fin **762** and a second fin **768** as an example. The first fin **762** has a thin plate shape extending in a direction intersecting the axis L of the inner cooling unit **740**. Also, the first fin **762** has a shape in which two bow-shaped cutouts **766** symmetrical around a center are formed in a thin disc shape **764** (see FIG. 5). An outer shape of the thin disc shape **764** of the first fin **762** has a value larger than a value obtained by multiplying a

value of the inner tube **722** of the outer cooling unit **720** by 0.9 as an example. In addition, two chords **767a** and **767b** forming a bow shape of each cutout **766** of the first fin **762** extend in the same direction, because two cutouts **766** are formed symmetrically around the center. On the other hand, the second fin **768** is disposed adjacent to the first fin **762** via a space, and located on a downstream side of the first fin **762** (see FIG. 4). Further, the second fin **768** has the same shape as in the first fin **762** (see FIG. 6). That is, the second fin **768** has a shape in which two bow-shaped cutouts **772** symmetrical around a center are formed in a thin disc shape **770**.

(30) Further, in the condensation device **700**, as an example, an extending direction of a chord **767** of the first fin **762** is different from an extending direction of a chord **774** forming a bow shape of each cutout **772** of the second fin **768** (see FIG. 2, FIG. 5 and FIG. 6). In more detail, the extending direction of the chord **767** is different from the extending direction of the chord **774** by 90 degrees.

(31) Further, the heat absorption member **760** includes a plurality of fins **780** as an example (see FIG. 4). Each of the first fin **762** and the second fin **768** is an example of the fins **780**. In addition, the first fin **762** is located on a most upstream side among the fins **780**. Furthermore, all the fins **780** included in the heat absorption member **760** have the same shape as an example. That is, each fin **780** has a shape in which two bow-shaped cutouts symmetrical around the center are formed in the thin disc shape. Further, an extending direction of a chord forming the cutout of the fin **780** at an odd-numbered position counted from an upstream side is equal to the extending direction of the chord **767** of the first fin **762**. That is, all the fins **780** at odd-numbered positions counted from the upstream side face in the same direction. On the other hand, an extending direction of a chord forming a cutout of the fin **780** at an even-numbered position counted from the upstream side is equal to the extending direction of the chord **774** of the second fin **768**. That is, all the fins **780** at even-numbered positions counted from the upstream side face in the same direction. In addition, the fin **780** is made of aluminum, copper, iron, another metal with a high thermal conductivity, or the like as an example. Also, in the present description, in a case where gas flowing through a first point flows through a second point after flowing through the first point, the first point is defined on an upstream side of the second point, and the second point is defined on a downstream side of the first point.

(32) Through the gas inlet **702**, the gas containing water vapor is introduced into the inner tube **722** of the outer cooling unit **720**.

(33) Through the gas outlet **704**, the gas from which water vapor is removed is discharged from the inner tube **722** of the outer cooling unit **720**. The gas inlet **702** is located above the gas outlet **704** in the gravity direction as an example, and the gas inlet **702** may be located below the gas outlet **704** in the gravity direction.

(34) <Operation>

(35) Next, description will be made as to an operation of the soldering device **100**.

(36) First, the soldering device **100** performs the solder processing in the solder processing unit **120** (see FIG. 1). In this case, since the circuit board to which flux is applied is used, flux vaporizes, and the interior of the solder processing unit **120** is filled with the gaseous mixture containing the flux component.

(37) Next, the separation unit **400** suctions the gaseous mixture from the solder processing unit **120**. Then, the separation unit **400** separates flux from the gaseous mixture containing flux by use of water, and generates the gas containing water vapor and the water containing flux. Afterward, the water containing flux is conveyed from the separation unit **400** to the purification device **600**, and the purification device **600** separates flux, and recovers flux. On the other hand, the gas containing water vapor is conveyed to the condensation device **700a**, and enters an interior of the inner tube **722** of the outer cooling unit **720** through the gas inlet **702** (see FIG. 4).

(38) At this time, in the condensation device **700a**, water that is the first cooling medium passes through the first flow path **726** of the outer cooling unit **720**, and water that is the second cooling medium passes through the second flow path **742** of the inner cooling unit **740**. Consequently,

surface temperatures of the outer cooling unit **720** and inner cooling unit **740** drop down to temperatures at which water can condense from the gas containing water vapor. Also, the heat absorption member **760** comes in contact with the inner cooling unit **740**, and hence a surface temperature of the heat absorption member **760** also drops down to a temperature at which water can condense from the gas containing water vapor. Thus, the outer cooling unit **720**, the inner cooling unit **740** and the heat absorption member **760** can cool the gas flowing through the interior of the inner tube **722** of the outer cooling unit **720**. Then, in the interior of the inner tube **722**, the water vapor contained in the gas condenses. Consequently, the water vapor contained in the gas is removed.

(39) Afterward, the gas from which water vapor is removed in the condensation device **700a** passes through the condensation device **700b** and the condensation device **700c**. At this time, the gas from which water vapor is removed in the condensation device **700a** further has the water vapor removed by the condensation device **700b** and the condensation device **700c** in the same manner as when passing through the condensation device **700a**. Then, the gas from which water vapor is removed after passing through the condensation device **700c** is suctioned into the blower **340**. Afterward, the blower **340** blows the gas from which water vapor is removed to the solder processing unit **120**.

Operations and Effects

(40) Next, description will be made below as to operations and effects of the condensation device **700**, the soldering device **100** and the flux recovery device **200** according to the present embodiment.

(41) (First Effect)

(42) In the condensation device **700**, as described above, the gas flowing through the interior of the inner tube **722** of the outer cooling unit **720** can be cooled by the outer cooling unit **720**, the inner cooling unit **740**, and the heat absorption member **760**. Consequently, in the condensation device **700**, a surface area of a portion that cools the gas containing water vapor increases as compared with a condensation device described in PTL 1. Therefore, in a case where the condensation device **700** removes water vapor from gas with the same flow rate as in the condensation device described in PTL 1, a size of the device can be made smaller than that of the condensation device described in PTL 1. Also, in a case where the condensation device **700** has the same size as in the condensation device described in PTL 1, water vapor can be removed from a larger amount of gas.

(43) (Second Effect)

(44) In the condensation device **700**, the heat absorption member **760** includes the plurality of fins **780**. Consequently, the condensation device **700** can increase a contact area of the heat absorption member **760** more than with one fin **780**. Therefore, the condensation device **700** can cool the gas containing water vapor more quickly due to the increase in contact area.

(45) (Third Effect)

(46) The gas flowing in the vicinity of the inner tube **722** of the outer cooling unit **720**, the inner cooling unit **740** and the heat absorption member **760** is cooled more than gas flowing through a position away from the inner tube **722** of the outer cooling unit **720**, the inner cooling unit **740** and the heat absorption member **760**. Consequently, if it is considered that convection of the gas containing water vapor does not occur in the interior of the inner tube **722** of the outer cooling unit **720**, a difference in temperature of gas to be discharged might be made depending on a position through which the gas containing water vapor flows. In this case, there is concern that gas that is not cooled and still contains a lot of water vapor passes through the condensation device **700**.

(47) However, in the condensation device **700**, the first fin **762** is disposed to extend in the direction intersecting the axis L of the inner cooling unit **740**. That is, the first fin **762** is oriented to block the flow of the gas containing water vapor. Consequently, when the gas containing water vapor collides with the first fin **762**, the convection of gas occurs in the interior of the inner tube **722** of the outer cooling unit **720**. In consequence, the condensation device **700** can uniformly cool

the gas containing water vapor. That is, the condensation device **700** can inhibit the gas still containing a lot of water vapor from being passed through the condensation device **700**.

(48) (Fourth Effect)

(49) In the condensation device **700**, it is assumed that the first fin **762** and the second fin **768** are arranged so that the extending direction of the chord **767** of the first fin **762** is equal to the extending direction of the chord **774** of the second fin **768**. In this case, when gas passing through a portion of the first fin **762** in which the cutout **766** is formed flows straight forward, the gas passes through a portion of the second fin **768** in which the cutout **772** is formed. Consequently, wind is hard to flow between the first fin **762** and the second fin **768**, and gas between the first fin **762** and the second fin **768** might stay. Thus, gas stays between the first fin **762** and the second fin **768**, this gas is only cooled, gas at another position might be hard to cool.

(50) However, according to the condensation device **700**, the extending direction of the chord **767** of the first fin **762** is different from the extending direction of the chord **774** of the second fin **768** (see FIG. 2, FIG. 5 and FIG. 6). Therefore, in a case where gas passing through a portion of the first fin **762** in which the cutout **766** is formed flows straight forward, this gas collides with the second fin **768**. This causes the convection of gas between the first fin **762** and the second fin **768**. That is, the gas between the first fin **762** and the second fin **768** is inhibited from staying. Therefore, the condensation device **700** can make uniform a temperature of gas in the vicinity of the first fin **762** and the second fin **768**.

(51) <Modifications>

(52) Next, description will be made below as to modifications of the condensation device **700** and the flux recovery device **200** according to the present embodiment.

(53) (First Modification)

(54) In the condensation device **700**, the heat absorption member **760** is in contact with the inner cooling unit **740**. However, the heat absorption member **760** may be in contact with at least one of the outer cooling unit **720** and the inner cooling unit **740**. This is because the heat absorption member **760** can cool gas passing through the inner tube **722** of the outer cooling unit **720**, as long as the heat absorption member **760** can be cooled by the outer cooling unit **720** or the inner cooling unit **740**.

(55) (Second Modification)

(56) Also, in the condensation device **700**, the inner cooling unit **740** has the straight tube shape. However, the inner cooling unit **740** may have a shape such as a spherical shape or a cube shape. This is because the inner cooling unit **740** can cool the gas passing through the inner tube **722** of the outer cooling unit **720**, and the heat absorption member **760**, even if the inner cooling unit **740** has any shape.

(57) (Third Modification)

(58) Further, in the condensation device **700**, the heat absorption member **760** includes a plurality of fins **780**, but the heat absorption member **760** may include only one fin **780**. Alternatively, the heat absorption member **760** may include the fin **780** in which one or three or more bow-shaped cutouts are formed in a thin disc shape, or may comprise the fin **780** having any other shape. This is because the heat absorption member **760** can cool passing gas, as long as the included fins **780** can come in contact with the gas passing through the inner tube **722** of the outer cooling unit **720** regardless of the shape or number of the fins.

(59) (Fourth Modification)

(60) Water supplied from the purification device **600** is used as the first cooling medium and the second cooling medium. However, in the condensation device **700**, any low-temperature liquid may be used as the first cooling medium or the second cooling medium, as long as the gas passing through the inner tube **722** of the outer cooling unit **720** is cooled and condensation can occur in the interior of the inner tube **722**.

Second Embodiment

(61) (Condensation Device)

(62) FIG. 7 is a structure diagram of a condensation device according to a second embodiment of the present invention. FIG. 8 is a cross-sectional view of the condensation device taken along the E-E line shown in FIG. 7.

(63) With reference to FIG. 7, a condensation device **800** includes an outer cooling unit **820**, a gas inlet **802**, a gas outlet **804**, a distributary chamber **806** and a confluence chamber **808**. The condensation device **800** has a tubular shape as an example as seen from FIG. 7 and FIG. 8. In addition, the condensation device **700** according to the first embodiment is replaced with the condensation device **800** according to the present embodiment as an example for use in the flux recovery device **200** and the soldering device **100**.

(64) With reference to FIG. 7, the outer cooling unit **820** includes a plurality of inner tubes **822**, an outer tube **824** located outside the inner tubes **822**, a first flow path **826** through which a first cooling medium passes between the inner tube **822** and the outer tube **824**, a first cooling medium inlet **828**, and a first cooling medium outlet **830**. As an example, the first cooling medium inlet **828** is located below the first cooling medium outlet **830** in a gravity direction. In addition, water supplied from a purification device **600** is supplied from the first cooling medium inlet **828** to the first flow path **826**, and discharged from the first cooling medium outlet **830**. Afterward, the discharged water is returned to the purification device **600**. Therefore, the water supplied from the purification device **600** is for use as the first cooling medium.

(65) The gas inlet **802** fluid-communicates with respective inner tube inlets **810** via the distributary chamber **806**. Consequently, the gas containing water vapor that is supplied to the gas inlet **802** is branched in the distributary chamber **806**, and supplied to the respective inner tubes **822** via the respective inner tube inlets **810**.

(66) The gas outlet **804** fluid-communicates with respective inner tube outlets **812** via the confluence chamber **808**. Consequently, gases from which water vapor is removed and that are discharged from respective gas outlets **804** join in the confluence chamber **808**, and are discharged from the gas outlet **804**.

Operations and Effects

(67) Next, description will be made below as to operations and effects of the condensation device **800** according to the present embodiment.

(68) (First Effect)

(69) The condensation device **800** can cool gas flowing through interiors of a plurality of inner tubes **822** by the outer cooling unit **820**. In particular, the condensation device **800** includes the plurality of inner tubes **822**, and hence can cool gas containing water vapor more quickly than in a case where the device includes one inner tube **822**.

(70) <Modifications>

(71) Next, description will be made below as to modifications of the condensation device **800** according to the present embodiment.

(72) (First Modification)

(73) The condensation device **800** comprises the plurality of inner tubes **822**. However, the condensation device **800** may comprise one inner tube **822** in place of the plurality of inner tubes **822**. This is because, also in this case, the condensation device **800** can cool the gas flowing through an interior of one inner tube **822** by the one inner tube **822** of the outer cooling unit **820**. That is, when the condensation device **800** comprises one or two or more inner tubes **822**, water vapor can be removed from gas.

(74) (Second Modification)

(75) The condensation device **800** may comprise an inner cooling unit located inside at least one of a plurality of inner tubes **822** as in the condensation device **700** of the first embodiment. This is because, in this case, the condensation device **800** can cool the gas flowing through an interior of the inner tube **822** by the outer cooling unit **820** and the inner cooling unit.

(76) (Third Modification)

(77) The condensation device **800** may comprise, inside at least one of the plurality of inner tubes **822**, a heat absorption member that comes in contact with the inner tube **822**. This is because, in this case, the condensation device **800** can cool the gas flowing through an interior of the inner tube **822** by the outer cooling unit **820** and the heat absorption member.

(78) The embodiments of the present invention and the respective modifications according to the embodiments have been described above, and needless to say, the respective examples have been described above to facilitate understanding of the present invention, and do not intend to restrict the present invention. The present invention can be appropriately changed and modified without departing from the scope, and the present invention includes equivalents to the invention. Also, in a range in which at least some of the above-described problems can be solved or a range in which at least some of effects are exhibited, any arbitrary combination or omission of the respective constituent components described in claims and description is possible.

REFERENCE SIGNS LIST

(79) **100**: soldering device **120**: solder processing unit **200**: flux recovery device **220**: pump **280**: water supply tank **300**: chiller unit **340**: blower **360**: piping **400**: separation unit **600**: purification device **620**: purification tank **640**: ozone generator **700**, **700a**, **700b**, **700c** and **800**: condensation device **702** and **802**: gas inlet **704** and **804**: gas outlet **806**: distributary chamber **808**: confluence chamber **720** and **820**: outer cooling unit **722** and **822**: inner tube **724** and **824**: outer tube **726** and **826**: first flow path **740**: inner cooling unit **742**: second flow path **760**: heat absorption member **762**: first fin **768**: second fin **780**: fin

Claims

1. A flux recovery device that recovers flux from a gaseous mixture containing a flux component, the flux recovery device comprising: a condensation device comprising: an outer cooling unit including two or more inner tubes, an outer tube located outside the two or more inner tubes, and a first flow path through which a first cooling medium passes between the two or more inner tubes and the outer tube, wherein the two or more inner tubes have a shape of a cylinder a purification device to which the water containing flux is supplied, and that separates flux from the water containing flux, and recovers flux a piping that supplies water separated from flux and purified in the purification device from the purification device to the condensation device and a separation unit that separates flux from the gaseous mixture by use of water, and discharges gas containing water vapor and water containing flux, wherein the outer cooling unit includes a first cooling medium inlet, and a first cooling medium outlet, wherein the first cooling medium is configured to be supplied from the first cooling medium inlet to the first flow path, and discharged from the first cooling medium outlet, and wherein the first cooling medium outlet is in fluid communication with the purification device without passing through the separation unit.
2. The flux recovery device according to claim 1, wherein the outer tube has a shape of a cylinder.
3. The flux recovery device according to claim 1, wherein the first cooling medium inlet is located below the first cooling medium outlet in a gravity direction.
4. The flux recovery device according to claim 1, wherein the condensation device further comprises: a heat absorption member that is located inside at least one inner tube in the two or more inner tubes, and that comes in contact with the outer cooling unit.
5. The flux recovery device according to claim 1, wherein the condensation device further comprises: an inner cooling unit located inside the two or more inner tubes and including a second flow path through which a second cooling medium passes.
6. The flux recovery device according to claim 5, wherein the condensation device further comprises: a heat absorption member that is located inside the two or more inner tubes and outside the inner cooling unit, and that comes in contact with the inner cooling unit.

7. The flux recovery device according to claim 6, wherein the heat absorption member includes a plurality of fins.
8. The flux recovery device according to claim 6, wherein the inner cooling unit has a straight tube shape, the inner tube of the outer cooling unit extends in an axial direction of the straight tube shape of the inner cooling unit, and the heat absorption member includes a first fin having a thin plate shape extending in a direction intersecting the axis.
9. The flux recovery device according to claim 8, wherein the first fin has a shape in which a bow-shaped cutout is formed in a thin disc shape, the heat absorption member further comprises a second fin having the same shape as in the first fin, disposed adjacent to the first fin via a space, and located on a downstream side of the first fin, and an extending direction of a chord forming the bow shape of the cutout in the first fin is different from an extending direction of a chord forming a bow shape of a cutout in the second fin.
10. The flux recovery device according to claim 1, wherein the purification device is configured to be supplied with the water containing flux that is discharged from the separation unit.
11. The flux recovery device according to claim 10, wherein the condensation device further includes an inner cooling unit located inside the two or more inner tubes and including a second flow path through which a second cooling medium passes, and wherein at least one of the first cooling medium and the second cooling medium is water supplied from the purification device.
12. The flux recovery device according to claim 10, further comprising: a pump that supplies the water purified in the purification device to the separation unit, a chiller unit that cools the water purified in the purification device, and a blower that blows, from the condensation device, the gas from which water vapor is removed in the condensation device.
13. The flux recovery device according to claim 1, comprising: a plurality of the condensation devices connected to one another.
14. A soldering device comprising: a solder processing unit, and the flux recovery device according to claim 1 that recovers flux from a gaseous mixture containing flux generated in the solder processing unit.
15. A water vapor removing method comprising the steps of: allowing a first cooling medium to pass through a first flow path between two or more inner tubes and an outer tube in an outer cooling unit including the two or more inner tubes and the outer tube located outside the two or more inner tubes, allowing, in interiors of the two or more inner tubes, condensation of water vapor contained in gas flowing through the interiors of the two or more inner tubes, to remove water vapor contained in the gas, and allowing the water that separated from flux and purified in a purification device to be supplied from the purification device to the condensation device as the first cooling medium, wherein the two or more inner tubes have a shape of a cylinder, wherein the outer cooling unit includes a first cooling medium inlet, and a first cooling medium outlet, wherein the first cooling medium is configured to be supplied from the first cooling medium inlet to the first flow path, and discharged from the first cooling medium outlet, wherein the first cooling medium outlet is in fluid communication with the purification device without passing through a separation unit, and wherein the separation unit is configured to separate flux from the gaseous mixture by use of water, and discharges gas containing water vapor and water containing flux.
16. The water vapor removing method according to claim 15, wherein the outer tube has a shape of a cylinder.
17. The water vapor removing method according to claim 15, wherein the first cooling medium inlet is located below the first cooling medium outlet in a gravity direction, the method further comprising the steps of: supplying the first cooling medium from the first cooling medium inlet to the first flow path, and discharging the first cooling medium from the first cooling medium outlet.
18. The water vapor removing method according to claim 15, further comprising the steps of: allowing a second cooling medium to pass through a second flow path included in an inner cooling unit located inside the two or more inner tubes, and cooling, by a heat absorption member, gas

flowing through an interior of the inner tube, the heat absorption member being located inside the two or more inner tubes of the outer cooling unit and outside the inner cooling unit, the heat absorption member coming in contact with at least one of the outer cooling unit and the inner cooling unit.

19. A flux recovery method comprising the steps of: separating flux from a gaseous mixture containing flux by use of water, and generating gas containing water vapor and water containing flux, separating flux from the water containing flux, and recovering flux, and removing water vapor from the generated gas containing water vapor by the water vapor removing method according to claim 15.

20. A solder processing method comprising the steps of: performing solder processing in a solder processing unit, recovering flux from a gaseous mixture containing flux that is generated by the solder processing, by the flux recovery method according to claim 19, and supplying, to the solder processing unit, the gas from which water vapor is removed, the gas being generated by the flux recovery method.

21. A flux recovery device that recovers flux from a gaseous mixture containing a flux component, the flux recovery device comprising: a condensation device comprising: an outer cooling unit including one or two or more inner tubes, an outer tube located outside the one or two or more inner tubes, and a first flow path through which a first cooling medium passes between the one or two or more inner tubes and the outer tube, and an inner cooling unit located inside the one or two or more inner tubes and including a second flow path through which a second cooling medium passes a purification device to which the water containing flux is supplied, and that separates flux from the water containing flux, and recovers flux, and a piping that supplies water separated from flux and purified in the purification device from the purification device to the condensation device, and a separation unit that separates flux from the gaseous mixture by use of water, and discharges gas containing water vapor and water containing flux, wherein the outer cooling unit includes a first cooling medium inlet, and a first cooling medium outlet, wherein the first cooling medium is configured to be supplied from the first cooling medium inlet to the first flow path, and discharges from the first cooling medium outlet, and wherein the first cooling medium outlet is in fluid communication with the purification device without passing through the separation unit.

22. A water vapor removing method comprising the steps of: allowing a first cooling medium to pass through a first flow path between one or two or more inner tubes and an outer tube in an outer cooling unit including the one or two or more inner tubes and the outer tube located outside the one or two or more inner tubes, allowing, in interiors of the one or two or more inner tubes, condensation of water vapor contained in gas flowing through the interiors of the one or two or more inner tubes, to remove water vapor contained in the gas, allowing a second cooling medium to pass through a second flow path included in an inner cooling unit located inside the one or two or more inner tubes, and allowing the water that separated from flux and purified in a purification device to be supplied from the purification device to the condensation device as the first cooling medium wherein the outer cooling unit includes a first cooling medium inlet, and a first cooling medium outlet, wherein the first cooling medium is configured to be supplied from the first cooling medium inlet to the first flow path, and discharged from the first cooling medium outlet, wherein the first cooling medium outlet is in fluid communication with the purification device without passing through a separation unit, and wherein the separation unit is configured to separate flux from the gaseous mixture by use of water, and discharges gas containing water vapor and water containing flux.
