

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409754
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Rocholl; Joshua D. et al.

Battery storage system for electrified vehicle

Abstract

An electrified vehicle includes a chassis, a cab coupled to the chassis, a body assembly coupled to the chassis, and an energy storage system. The body assembly is positioned behind the cab with a space defined therebetween. The energy storage system is positioned within the space between the cab and the body assembly. The energy storage system includes a housing and a plurality of battery cells disposed within the housing. The housing is coupled directly to the chassis and extends upward from the chassis such that a portion of the housing is positioned above at least a portion of a roof of the cab.

Inventors: Rocholl; Joshua D. (Rochester, MN), Wentz; Derek A. (Austin, WI), Kellander; John T. (Oronoco, MN), Clifton; Cody D. (Mapleton, MN), Hoover; Vincent (Byron, MN), Klein; Zachary L (Rochester, MN), Weckwerth; Clinton T. (Pine Island, MN), Wachter; Skylar A. (Dodge Center, MN), Smith; Chad (Omro, WI), Dekarske; Neil (Oshkosh, WI)

Applicant: Oshkosh Corporation (Oshkosh, WI)

Family ID: 73017191

Assignee: Oshkosh Corporation (Oshkosh, WI)

Appl. No.: 18/370288

Filed: September 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240001798 A1	Jan. 04, 2024

Related U.S. Application Data

continuation parent-doc US 17972714 20221025 US 11794604 child-doc US 18370288
continuation parent-doc US 17362390 20210629 PENDING child-doc US 17972714

Publication Classification

Int. Cl.: **B60L50/64** (20190101); **B60K1/04** (20190101); **B60L50/60** (20190101); **B60L53/80** (20190101); **B65F3/00** (20060101)

U.S. Cl.:

CPC **B60L53/80** (20190201); **B60L50/64** (20190201); **B60L50/66** (20190201); **B65F3/00** (20130101); B60K2001/0416 (20130101); B60K2001/045 (20130101); B60K2001/0461 (20130101)

Field of Classification Search

CPC: B60L (53/80); B60L (50/64); B60L (50/66); B60L (1/04); B60L (2001/0466); B60L (2001/0461); B60L (2001/0411)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3089813	12/1962	Ellsworth	N/A	N/A
3817415	12/1973	Lewis	N/A	N/A
4248323	12/1980	Gaffney	N/A	N/A
5171121	12/1991	Smith et al.	N/A	N/A
5697741	12/1996	Harris et al.	N/A	N/A
5779300	12/1997	McNeilus et al.	N/A	N/A
5829946	12/1997	McNeilus et al.	N/A	N/A
5919027	12/1998	Christenson	N/A	N/A
5931628	12/1998	Christenson	N/A	N/A
5934858	12/1998	Christenson	N/A	N/A
5934867	12/1998	Christenson	N/A	N/A
5938394	12/1998	Christenson	N/A	N/A
5951235	12/1998	Young et al.	N/A	N/A
5967731	12/1998	Brandt	N/A	N/A
5984609	12/1998	Bartlett	N/A	N/A
6033176	12/1999	Bartlett	N/A	N/A
6062803	12/1999	Christenson	N/A	N/A
6089813	12/1999	McNeilus et al.	N/A	N/A
6120235	12/1999	Humphries et al.	N/A	N/A
6123500	12/1999	McNeilus et al.	N/A	N/A
6210094	12/2000	McNeilus et al.	N/A	N/A
6213706	12/2000	Christenson	N/A	N/A
6224318	12/2000	McNeilus et al.	N/A	N/A
6247713	12/2000	Konop	N/A	N/A
6290450	12/2000	Humphries et al.	N/A	N/A

6315515	12/2000	Young et al.	N/A	N/A
6336783	12/2001	Young et al.	N/A	N/A
6350098	12/2001	Christenson et al.	N/A	N/A
6447239	12/2001	Young et al.	N/A	N/A
6474928	12/2001	Christenson	N/A	N/A
6478317	12/2001	Konop	N/A	N/A
6485079	12/2001	Brown et al.	N/A	N/A
6527495	12/2002	Humphries et al.	N/A	N/A
6565305	12/2002	Schrafel	N/A	N/A
6666491	12/2002	Schrafel	N/A	N/A
6918721	12/2004	Venton-Walters et al.	N/A	N/A
6997506	12/2005	Hecker	N/A	N/A
7055880	12/2005	Archer	N/A	N/A
7070382	12/2005	Pruteanu et al.	N/A	N/A
7073847	12/2005	Morrow et al.	N/A	N/A
7111858	12/2005	Manser et al.	N/A	N/A
7118314	12/2005	Zhou et al.	N/A	N/A
7140461	12/2005	Morrow	N/A	N/A
7198130	12/2006	Schimke	N/A	N/A
7226080	12/2006	Humphries	N/A	N/A
7264305	12/2006	Kuriakose	N/A	N/A
7270346	12/2006	Rowe et al.	N/A	N/A
7284943	12/2006	Pruteanu et al.	N/A	N/A
7302320	12/2006	Nasr et al.	N/A	N/A
7357203	12/2007	Morrow et al.	N/A	N/A
7370904	12/2007	Wood et al.	N/A	N/A
7379797	12/2007	Nasr et al.	N/A	N/A
7419021	12/2007	Morrow et al.	N/A	N/A
7448460	12/2007	Morrow et al.	N/A	N/A
7517005	12/2008	Kuriakose	N/A	N/A
7520354	12/2008	Morrow et al.	N/A	N/A
7521814	12/2008	Nasr	N/A	N/A
7556468	12/2008	Grata	N/A	N/A
7559735	12/2008	Pruteanu et al.	N/A	N/A
7621580	12/2008	Randjelovic et al.	N/A	N/A
7823948	12/2009	Redman et al.	N/A	N/A
7848857	12/2009	Nasr et al.	N/A	N/A
7878750	12/2010	Zhou et al.	N/A	N/A
7931103	12/2010	Morrow et al.	N/A	N/A
7937194	12/2010	Nasr et al.	N/A	N/A
7954882	12/2010	Brummel et al.	N/A	N/A
8000850	12/2010	Nasr et al.	N/A	N/A
8152216	12/2011	Howell et al.	N/A	N/A
8182194	12/2011	Pruteanu et al.	N/A	N/A
8337352	12/2011	Morrow et al.	N/A	N/A
8360706	12/2012	Addleman et al.	N/A	N/A
8376439	12/2012	Kuriakose et al.	N/A	N/A
8397853	12/2012	Stefani et al.	N/A	N/A
8540475	12/2012	Kuriakose et al.	N/A	N/A
8561735	12/2012	Morrow et al.	N/A	N/A

8616319	12/2012	Yokoyama et al.	N/A	N/A
8789635	12/2013	Franzen et al.	N/A	N/A
8794886	12/2013	Nett et al.	N/A	N/A
8807613	12/2013	Howell et al.	N/A	N/A
8864613	12/2013	Morrow et al.	N/A	N/A
8936124	12/2014	Auer et al.	N/A	N/A
8967699	12/2014	Richmond et al.	N/A	N/A
9061712	12/2014	Patberg et al.	N/A	N/A
9114804	12/2014	Shukla et al.	N/A	N/A
9114930	12/2014	Simmons	N/A	N/A
9132736	12/2014	Oshkosh	N/A	N/A
9174686	12/2014	Oshkosh	N/A	N/A
9216856	12/2014	Howell et al.	N/A	N/A
9328986	12/2015	Pennau et al.	N/A	N/A
9366507	12/2015	Richmond et al.	N/A	N/A
9376102	12/2015	Shukla et al.	N/A	N/A
9387985	12/2015	Gillmore et al.	N/A	N/A
9428042	12/2015	Morrow et al.	N/A	N/A
9452750	12/2015	Shukla et al.	N/A	N/A
9493093	12/2015	Stingle et al.	N/A	N/A
9494170	12/2015	Hou	N/A	N/A
9533569	12/2016	Mckinney	N/A	N/A
9579969	12/2016	Crist et al.	N/A	N/A
9598235	12/2016	Vasilescu et al.	N/A	N/A
9630483	12/2016	Yamada et al.	N/A	N/A
9694671	12/2016	Wildgrube et al.	N/A	N/A
9694776	12/2016	Nelson et al.	N/A	N/A
9707869	12/2016	Messina et al.	N/A	N/A
9731594	12/2016	Wildgrube	N/A	N/A
9738186	12/2016	Krueger et al.	N/A	N/A
9821789	12/2016	Shukla et al.	N/A	N/A
9880581	12/2017	Kuriakose et al.	N/A	N/A
9956860	12/2017	Tsuji	N/A	N/A
9981803	12/2017	Davis et al.	N/A	N/A
10021467	12/2017	Dunbar	N/A	N/A
10029556	12/2017	Morrow et al.	N/A	N/A
10035648	12/2017	Haddick et al.	N/A	N/A
10099622	12/2017	Handschke et al.	N/A	N/A
10106032	12/2017	Crist et al.	N/A	N/A
10166883	12/2018	Brendecke et al.	N/A	N/A
10196205	12/2018	Betz et al.	N/A	N/A
10315643	12/2018	Shukla et al.	N/A	N/A
10351340	12/2018	Haddick et al.	N/A	N/A
10392000	12/2018	Shukla et al.	N/A	N/A
10414067	12/2018	Datema et al.	N/A	N/A
10414266	12/2018	Wiegand et al.	N/A	N/A
10421345	12/2018	Kerspe et al.	N/A	N/A
10434949	12/2018	Handschke et al.	N/A	N/A
10456610	12/2018	Betz et al.	N/A	N/A
10457134	12/2018	Morrow et al.	N/A	N/A

10457533	12/2018	Puszkiewicz et al.	N/A	N/A
D869332	12/2018	Gander et al.	N/A	N/A
10493837	12/2018	Angelo et al.	N/A	N/A
10500975	12/2018	Healy	N/A	N/A
10513392	12/2018	Haddick et al.	N/A	N/A
10545010	12/2019	Leeman et al.	N/A	N/A
10556622	12/2019	Calliari et al.	N/A	N/A
10558234	12/2019	Kuriakose et al.	N/A	N/A
10589788	12/2019	Milton et al.	N/A	N/A
10611416	12/2019	Groteleuschen et al.	N/A	N/A
10618405	12/2019	Crist et al.	N/A	N/A
10688856	12/2019	Kasai et al.	N/A	N/A
10781090	12/2019	Puszkiewicz et al.	N/A	N/A
10800605	12/2019	Rocholl et al.	N/A	N/A
10843379	12/2019	Rocholl et al.	N/A	N/A
10843549	12/2019	Morrow et al.	N/A	N/A
10858184	12/2019	Betz et al.	N/A	N/A
10858231	12/2019	Holmes et al.	N/A	N/A
10859167	12/2019	Jax et al.	N/A	N/A
10899538	12/2020	Nelson et al.	N/A	N/A
10901409	12/2020	Datema et al.	N/A	N/A
10913346	12/2020	Wiegand et al.	N/A	N/A
10940610	12/2020	Clifton et al.	N/A	N/A
10994929	12/2020	Haddick et al.	N/A	N/A
10997802	12/2020	Koga et al.	N/A	N/A
11001135	12/2020	Yakes et al.	N/A	N/A
11001440	12/2020	Rocholl et al.	N/A	N/A
11007863	12/2020	Yakes et al.	N/A	N/A
11020621	12/2020	Betz et al.	N/A	N/A
11021078	12/2020	Rocholl et al.	N/A	N/A
11040610	12/2020	Sloan et al.	N/A	N/A
11042745	12/2020	Wildgrube et al.	N/A	N/A
11042750	12/2020	Wildgrube et al.	N/A	N/A
11046329	12/2020	Clifton et al.	N/A	N/A
11052899	12/2020	Shukla et al.	N/A	N/A
11059436	12/2020	Wildgrube et al.	N/A	N/A
11110977	12/2020	Smith et al.	N/A	N/A
2002/0025245	12/2001	Humphries et al.	N/A	N/A
2002/0159870	12/2001	Pruteanu et al.	N/A	N/A
2003/0047956	12/2002	Schrafel	N/A	N/A
2003/0230412	12/2002	Archer	N/A	N/A
2003/0231944	12/2002	Weller et al.	N/A	N/A
2004/0071537	12/2003	Pruteanu et al.	N/A	N/A
2004/0156706	12/2003	Weller et al.	N/A	N/A
2004/0165977	12/2003	Hecker	N/A	N/A
2004/0228699	12/2003	Venton-Walters et al.	N/A	N/A
2006/0039771	12/2005	Zhou	N/A	N/A
2006/0045700	12/2005	Siebers et al.	N/A	N/A
2006/0055206	12/2005	Morrow et al.	N/A	N/A
2006/0087152	12/2005	Kuriakose	N/A	N/A

2007/0138817	12/2006	Calliari et al.	N/A	N/A
2007/0154294	12/2006	Shim et al.	N/A	N/A
2007/0222253	12/2006	Wood et al.	N/A	N/A
2007/0296248	12/2006	Kuriakose	N/A	N/A
2008/0012280	12/2007	Humphries	N/A	N/A
2008/0036232	12/2007	Randjelovic et al.	N/A	N/A
2008/0038106	12/2007	Spain	N/A	N/A
2008/0129068	12/2007	Brummel et al.	N/A	N/A
2008/0150350	12/2007	Morrow et al.	N/A	N/A
2008/0237285	12/2007	Calliari	N/A	N/A
2008/0284188	12/2007	Redman et al.	N/A	N/A
2009/0194347	12/2008	Morrow et al.	N/A	N/A
2010/0052357	12/2009	Howell et al.	N/A	N/A
2010/0166531	12/2009	Bauer et al.	N/A	N/A
2010/0320012	12/2009	Stappen et al.	N/A	N/A
2011/0233952	12/2010	Kuriakose et al.	N/A	N/A
2012/0111654	12/2011	Origuchi	N/A	N/A
2012/0282077	12/2011	Alberts et al.	N/A	N/A
2013/0037337	12/2012	Auer et al.	N/A	N/A
2013/0199863	12/2012	Robbins	N/A	N/A
2013/0327583	12/2012	Nitawaki et al.	N/A	N/A
2014/0367954	12/2013	Mckinney	N/A	N/A
2015/0043231	12/2014	Clark	N/A	N/A
2015/0059598	12/2014	Philipp et al.	N/A	N/A
2015/0151651	12/2014	Stingle et al.	N/A	N/A
2015/0353150	12/2014	Ursich	280/755	B62D 37/04
2016/0185243	12/2015	Zhou et al.	N/A	N/A
2016/0276638	12/2015	Sham	N/A	N/A
2016/0375805	12/2015	Krueger et al.	N/A	N/A
2017/0158070	12/2016	Salasoo	N/A	N/A
2017/0341860	12/2016	Dodds et al.	N/A	N/A
2017/0361491	12/2016	Datema et al.	N/A	N/A
2018/0056769	12/2017	Kerspe et al.	N/A	N/A
2018/0250847	12/2017	Wurtz et al.	N/A	N/A
2018/0265289	12/2017	Davis et al.	N/A	N/A
2019/0039407	12/2018	Smith	N/A	N/A
2019/0077254	12/2018	Stanley	N/A	N/A
2019/0081298	12/2018	Matecki et al.	N/A	N/A
2019/0091890	12/2018	Rocholl et al.	N/A	N/A
2019/0121353	12/2018	Datema et al.	N/A	N/A
2019/0185077	12/2018	Smith et al.	N/A	N/A
2019/0193934	12/2018	Rocholl et al.	N/A	N/A
2019/0202312	12/2018	Aufdencamp	N/A	N/A
2019/0291559	12/2018	Trenne et al.	N/A	N/A
2019/0291560	12/2018	Lampsa et al.	N/A	N/A
2019/0291711	12/2018	Shukla et al.	N/A	N/A
2019/0292975	12/2018	Hou et al.	N/A	N/A
2019/0322321	12/2018	Schwartz et al.	N/A	N/A
2019/0325220	12/2018	Wildgrube et al.	N/A	N/A
2019/0344475	12/2018	Datema et al.	N/A	N/A

2019/0360600	12/2018	Jax et al.	N/A	N/A
2020/0078986	12/2019	Clifton et al.	N/A	N/A
2020/0083573	12/2019	Caliskan et al.	N/A	N/A
2020/0096953	12/2019	Stalker et al.	N/A	N/A
2020/0139804	12/2019	Holmes et al.	N/A	N/A
2020/0148073	12/2019	Sasu	N/A	N/A
2020/0158474	12/2019	Leeman et al.	N/A	N/A
2020/0164760	12/2019	Sohmshetty et al.	N/A	N/A
2020/0230841	12/2019	Datema et al.	N/A	N/A
2020/0230842	12/2019	Datema et al.	N/A	N/A
2020/0231035	12/2019	Crist et al.	N/A	N/A
2020/0247486	12/2019	Groteleuschen et al.	N/A	N/A
2020/0262328	12/2019	Nelson et al.	N/A	N/A
2020/0262366	12/2019	Wildgrube et al.	N/A	N/A
2020/0265656	12/2019	Koga et al.	N/A	N/A
2020/0316816	12/2019	Messina et al.	N/A	N/A
2020/0317083	12/2019	Messina et al.	N/A	N/A
2020/0321573	12/2019	Confer	N/A	N/A
2020/0335840	12/2019	Sloan et al.	N/A	N/A
2020/0346547	12/2019	Rocholl et al.	N/A	N/A
2020/0346556	12/2019	Rocholl et al.	N/A	N/A
2020/0346557	12/2019	Rocholl et al.	N/A	N/A
2020/0346657	12/2019	Clifton et al.	N/A	N/A
2020/0346854	12/2019	Rocholl et al.	N/A	N/A
2020/0346855	12/2019	Rocholl et al.	N/A	N/A
2020/0346856	12/2019	Rocholl et al.	N/A	N/A
2020/0346857	12/2019	Rocholl et al.	N/A	N/A
2020/0346858	12/2019	Buege et al.	N/A	N/A
2020/0346859	12/2019	Buege et al.	N/A	N/A
2020/0346860	12/2019	Buege et al.	N/A	N/A
2020/0346861	12/2019	Rocholl et al.	N/A	N/A
2020/0346862	12/2019	Rocholl et al.	N/A	N/A
2020/0347659	12/2019	Rocholl et al.	N/A	N/A
2020/0347661	12/2019	Rocholl et al.	N/A	N/A
2020/0347857	12/2019	Clifton et al.	N/A	N/A
2020/0348681	12/2019	Clifton et al.	N/A	N/A
2020/0348764	12/2019	Clifton et al.	N/A	N/A
2020/0358150	12/2019	Fields et al.	N/A	N/A
2020/0369334	12/2019	Lee	N/A	N/A
2020/0376977	12/2019	Lee et al.	N/A	N/A
2020/0398628	12/2019	Schardt et al.	N/A	N/A
2020/0398670	12/2019	Rocholl et al.	N/A	N/A
2020/0398695	12/2019	Rocholl et al.	N/A	N/A
2020/0398697	12/2019	Rocholl et al.	N/A	N/A
2020/0398772	12/2019	Wildgrube et al.	N/A	N/A
2020/0399057	12/2019	Rocholl et al.	N/A	N/A
2020/0399058	12/2019	Rocholl et al.	N/A	N/A
2020/0402325	12/2019	Koga et al.	N/A	N/A
2021/0002112	12/2020	Puszkiewicz et al.	N/A	N/A
2021/0031611	12/2020	Yakes et al.	N/A	N/A

2021/0031612	12/2020	Yakes et al.	N/A	N/A
2021/0031649	12/2020	Messina et al.	N/A	N/A
2021/0039719	12/2020	Datema et al.	N/A	N/A
2021/0054942	12/2020	Jax et al.	N/A	N/A
2021/0069934	12/2020	Rocholl et al.	N/A	N/A
2021/0086991	12/2020	Betz et al.	N/A	N/A
2021/0122229	12/2020	Wiegand et al.	N/A	N/A
2021/0124347	12/2020	Datema et al.	N/A	N/A
2021/0139237	12/2020	Nelson et al.	N/A	N/A
2021/0143663	12/2020	Bolton	N/A	N/A
2021/0155224	12/2020	Mckibben et al.	N/A	N/A
2021/0162630	12/2020	Clifton et al.	N/A	N/A
2021/0188069	12/2020	Friedman	N/A	N/A
2021/0188076	12/2020	Morrow et al.	N/A	N/A
2021/0214156	12/2020	Haddick et al.	N/A	N/A
2021/0218101	12/2020	Menon et al.	N/A	N/A
2021/0221216	12/2020	Yakes et al.	N/A	N/A
2021/0225095	12/2020	Koga et al.	N/A	N/A
2021/0229755	12/2020	Schwartz et al.	N/A	N/A
2021/0229908	12/2020	Rocholl et al.	N/A	N/A
2021/0339648	12/2020	Koga et al.	N/A	N/A
2021/0362579	12/2020	Kumagai	N/A	N/A
2022/0111716	12/2021	Mckibben et al.	N/A	N/A
2022/0169252	12/2021	Yhr	N/A	N/A
2022/0194489	12/2021	Roche et al.	N/A	N/A
2022/0348113	12/2021	Delrieu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201530302	12/2009	CN	N/A
105644639	12/2015	CN	N/A
106515413	12/2016	CN	N/A
107264253	12/2016	CN	B60K 1/02
106275084	12/2017	CN	N/A
107825950	12/2017	CN	N/A
109203960	12/2018	CN	N/A
10 2012 007 875	12/2012	DE	N/A
20 2016 006 076	12/2015	DE	N/A
10 2017 009 176	12/2020	DE	N/A
3043600	12/2017	FR	N/A
2 492 148	12/2011	GB	N/A
WO-2014/161557	12/2013	WO	N/A
WO-2017064582	12/2016	WO	B60K 1/00
WO-2017/162787	12/2016	WO	N/A
WO-2020/090171	12/2019	WO	N/A

OTHER PUBLICATIONS

Translation of CN-107264253-A (Year: 2017). cited by examiner
Translation of WO-2017064582-A1 (Year: 2017). cited by examiner
US 2002/0347659 (withdrawn). cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/972,714, filed Oct. 25, 2022, which is a continuation of U.S. patent application Ser. No. 17/362,390, filed Jun. 29, 2021, which is a continuation of U.S. patent application Ser. No. 17/007,622, filed Aug. 31, 2020, which is a continuation of U.S. patent application Ser. No. 16/851,149, filed Apr. 17, 2020, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/842,934, filed May 3, 2019, all of which are incorporated herein by reference in their entireties.

BACKGROUND

(1) Refuse vehicles collect a wide variety of waste, trash, and other material from residences and businesses. Operators of the refuse vehicles transport the material from various waste receptacles within a municipality to a storage or processing facility (e.g., a landfill, an incineration facility, a recycling facility, etc.).

SUMMARY

(2) One embodiment relates to a refuse vehicle including a chassis, a body assembly coupled to the chassis, the body assembly defining a refuse compartment, and an electric energy system, the electric energy system including one or more battery cells and control hardware, the electric energy system detachably coupled to the body and configured to be accessed by a door in the body, and wherein the one or more battery cells of the electric energy system are replaceable.

(3) In some embodiments, the refuse vehicle is fully powered by the electric energy system. In some embodiments, the refuse vehicle does not include a combustion engine. In some embodiments, the one or more battery cells are detachably coupled to a first portion of the body and wherein the control hardware is detachably coupled to a second portion of the body distinct from the first portion. In some embodiments, at least a portion of the electric energy system is coupled to a tailgate of the refuse vehicle, and wherein the tailgate is detachably coupled to the body of the refuse vehicle. In some embodiments, at least a portion of the electric energy system is coupled to at least one wheel of the refuse vehicle. In some embodiments, the refuse vehicle includes a cab and wherein at least a portion of the electric energy system is positioned between the cab and the body.

(4) Another embodiment relates to an electrical energy system for powering a refuse vehicle, the electrical energy system including one or more battery cells configured to store electrical potential energy, control hardware configured to manage charging the one or more battery cells and distributing the stored electrical potential energy, and an attachment assembly configured to detachably couple the electrical energy system to the refuse vehicle, and wherein the electrical energy system is configured to provide power to the refuse vehicle.

(5) In some embodiments, the electrical energy system is configured to provide an entire power needed to operate the refuse vehicle. In some embodiments, the attachment assembly is configured to detachably couple the electrical energy system to a tailgate of the refuse vehicle. In some embodiments, the attachment assembly is configured to detachably couple the electrical energy system above a cab portion of the refuse vehicle. In some embodiments, the attachment assembly is configured to detachably couple a first component of the electrical energy system to a first portion of the refuse vehicle and wherein the attachment assembly is configured to detachably couple a second component of the electrical energy system to a second portion of the refuse vehicle that is

distinct from the first portion of the refuse vehicle. In some embodiments, the first portion includes a wheel of the refuse vehicle and wherein the second portion includes a body of the electric refuse vehicle. In some embodiments, the attachment assembly is configured to facilitate removal of the one or more battery cells from the refuse vehicle for charging.

(6) Another embodiment relates to an electric refuse vehicle including a chassis, a body assembly coupled to the chassis, the body assembly defining a refuse compartment, a prime mover, wherein the prime mover is an electric motor, and an electrical energy system including one or more battery cells detachably coupled to the body and configured to completely power the prime mover.

(7) In some embodiments, a first number of the one or more battery cells are detachably coupled to a first portion of the body and wherein a second number of the one or more battery cells are detachably coupled to a second portion of the body that is distinct from the first portion of the body. In some embodiments, at least one of the one or more battery cells are detachably coupled to a tailgate of the electric refuse vehicle. In some embodiments, the one or more battery cells are hot-swappable. In some embodiments, at least one of the one or more battery cells are positioned between the chassis and the body and are accessible by a door in the body. In some embodiments, the one or more battery cells are positioned between the body and a cab of the electric refuse vehicle.

(8) In some embodiments, the body assembly is detachably coupled to the chassis. In some embodiments, the electric refuse vehicle is a rear loading refuse vehicle and wherein a center of mass of the electrical energy system is forward of a rear axle of the electric refuse vehicle. In some embodiments, the electric refuse vehicle is a side loading refuse vehicle and wherein a center of mass of the electrical energy system is rearward of a rear axle of the electric refuse vehicle. In some embodiments, the electric refuse vehicle is a front loading refuse vehicle and wherein a center of mass of the electrical energy system is rearward of a rear axle of the electric refuse vehicle.

(9) This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a refuse vehicle, according to an exemplary embodiment.

(2) FIG. 2 is a side view of a refuse container of the refuse vehicle of FIG. 1 having a top energy storage and/or generation system, according to an exemplary embodiment.

(3) FIG. 3 is the refuse container of FIG. 1 having a bottom energy storage and/or generation system, according to an exemplary embodiment.

(4) FIG. 4 is the refuse vehicle of FIG. 1 having a centralized energy storage and/or generation system, according to an exemplary embodiment.

(5) FIG. 5 is the refuse vehicle of FIG. 1 having a tailgate energy storage and/or generation system, according to an exemplary embodiment.

(6) FIG. 6 is the refuse vehicle of FIG. 1 having a frame energy storage and/or generation system, according to an exemplary embodiment.

(7) FIGS. 7A-8B are the refuse vehicle of FIG. 1 having a distributed energy storage and/or generation system, according to several exemplary embodiments.

(8) FIGS. 9A-9B are the refuse vehicle of FIG. 1 having a top energy storage and/or generation system, according to several exemplary embodiments.

DETAILED DESCRIPTION

(9) Before turning to the figures, which illustrate certain exemplary embodiments in detail, it

should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

(10) According to an exemplary embodiment, an energy storage and/or generation system for a refuse vehicle is disclosed herein. The energy storage and/or generation system of the present disclosure provides many advantages over conventional systems. The energy storage and/or generation system may be positioned to evenly distribute the weight of batteries across the frame of the refuse vehicle and/or minimize component stress of one or more load bearing members (e.g., an axle) of the refuse vehicle. The energy storage and/or generation system may be positioned to be easily accessible and/or removable from the refuse vehicle. Ease of access and removability reduce the labor involved in servicing an energy storage and/or generation system, making routine inspection and servicing more feasible and thereby increasing the life of the energy storage and/or generation system. Furthermore, removability allows the energy storage and/or generation system to be “hot-swapped” when it is depleted of charge for a fresh battery, thereby enabling greater uptime for a refuse vehicle. In addition, a removable energy storage and/or generation system may be safely charged at greater speeds than an energy storage and/or generation system confined to a refuse vehicle, thereby allowing for a smaller number of energy storage and/or generation systems to be used to support a fleet of refuse vehicles. Finally, the energy storage and/or generation system may be modular, allowing individual components of the energy storage and/or generation system to be easily replaced for one another. Modularity not only reduces maintenance costs but also allows for future upgrades to the energy storage and/or generation system. For example, the batteries of the energy storage and/or generation system may be easily upgraded to future chemistries not yet available.

(11) Overall Vehicle

(12) As shown in FIG. 1, a vehicle, shown as refuse vehicle **10** (e.g., a garbage truck, a waste collection truck, a sanitation truck, a recycling truck, etc.), is configured as a front-loading refuse truck. In other embodiments, the refuse vehicle **10** is configured as a side-loading refuse truck or a rear-loading refuse truck. In still other embodiments, the vehicle is another type of vehicle (e.g., a skid-loader, a telehandler, a plow truck, a boom lift, etc.). As shown in FIG. 1, the refuse vehicle **10** includes a chassis, shown as frame **12**; a body assembly, shown as body **14**, coupled to the frame **12** (e.g., at a rear end thereof, etc.); and a cab, shown as cab **16**, coupled to the frame **12** (e.g., at a front end thereof, etc.). The cab **16** may include various components to facilitate operation of the refuse vehicle **10** by an operator (e.g., a seat, a steering wheel, actuator controls, a user interface, switches, buttons, dials, etc.).

(13) As shown in FIG. 1, the refuse vehicle **10** includes a prime mover, shown as electric motor **18**, and an energy system, shown as energy storage and/or generation system **20**. In other embodiments, the prime mover is or includes an internal combustion engine. According to the exemplary embodiment shown in FIG. 1, the electric motor **18** is coupled to the frame **12** at a position beneath the cab **16**. The electric motor **18** is configured to provide power to a plurality of tractive elements, shown as wheels **22** (e.g., via a drive shaft, axles, etc.). In other embodiments, the electric motor **18** is otherwise positioned and/or the refuse vehicle **10** includes a plurality of electric motors to facilitate independently driving one or more of the wheels **22**. In still other embodiments, the electric motor **18** or a secondary electric motor is coupled to and configured to drive a hydraulic system that powers hydraulic actuators. According to the exemplary embodiment shown in FIG. 1, the energy storage and/or generation system **20** is coupled to the frame **12** beneath the body **14**. In other embodiments, the energy storage and/or generation system **20** is otherwise positioned (e.g., within a tailgate of the refuse vehicle **10**, beneath the cab **16**, along the top of the body **14**, within the body **14**, etc.).

(14) According to an exemplary embodiment, the energy storage and/or generation system **20** is

configured to (a) receive, generate, and/or store power and (b) provide electric power to (i) the electric motor **18** to drive the wheels **22**, (ii) electric actuators of the refuse vehicle **10** to facilitate operation thereof (e.g., lift actuators, tailgate actuators, packer actuators, grabber actuators, etc.), and/or (iii) other electrically operated accessories of the refuse vehicle **10** (e.g., displays, lights, etc.). The energy storage and/or generation system **20** may include one or more rechargeable batteries (e.g., lithium-ion batteries, nickel-metal hydride batteries, lithium-ion polymer batteries, lead-acid batteries, nickel-cadmium batteries, etc.), capacitors, solar cells, generators, power buses, etc. In one embodiment, the refuse vehicle **10** is a completely electric refuse vehicle. In other embodiments, the refuse vehicle **10** includes an internal combustion generator that utilizes one or more fuels (e.g., gasoline, diesel, propane, natural gas, hydrogen, etc.) to generate electricity to charge the energy storage and/or generation system **20**, power the electric motor **18**, power the electric actuators, and/or power the other electrically operated accessories (e.g., a hybrid refuse vehicle, etc.). For example, the refuse vehicle **10** may have an internal combustion engine augmented by the electric motor **18** to cooperatively provide power to the wheels **22**. The energy storage and/or generation system **20** may thereby be charged via an on-board generator (e.g., an internal combustion generator, a solar panel system, etc.), from an external power source (e.g., overhead power lines, mains power source through a charging input, etc.), and/or via a power regenerative braking system, and provide power to the electrically operated systems of the refuse vehicle **10**. In some embodiments, the energy storage and/or generation system **20** includes a heat management system (e.g., liquid cooling, heat exchanger, air cooling, etc.).

(15) According to an exemplary embodiment, the refuse vehicle **10** is configured to transport refuse from various waste receptacles within a municipality to a storage and/or processing facility (e.g., a landfill, an incineration facility, a recycling facility, etc.). As shown in FIG. **1**, the body **14** includes a plurality of panels, shown as panels **32**, a tailgate **34**, and a cover **36**. The panels **32**, the tailgate **34**, and the cover **36** define a collection chamber (e.g., hopper, etc.), shown as refuse compartment **30**. Loose refuse may be placed into the refuse compartment **30** where it may thereafter be compacted (e.g., by a packer system, etc.). The refuse compartment **30** may provide temporary storage for refuse during transport to a waste disposal site and/or a recycling facility. In some embodiments, at least a portion of the body **14** and the refuse compartment **30** extend above or in front of the cab **16**. According to the embodiment shown in FIG. **1**, the body **14** and the refuse compartment **30** are positioned behind the cab **16**. In some embodiments, the refuse compartment **30** includes a hopper volume and a storage volume. Refuse may be initially loaded into the hopper volume and thereafter compacted into the storage volume. According to an exemplary embodiment, the hopper volume is positioned between the storage volume and the cab **16** (e.g., refuse is loaded into a position of the refuse compartment **30** behind the cab **16** and stored in a position further toward the rear of the refuse compartment **30**, a front-loading refuse vehicle, a side-loading refuse vehicle, etc.). In other embodiments, the storage volume is positioned between the hopper volume and the cab **16** (e.g., a rear-loading refuse vehicle, etc.).

(16) As shown in FIG. **1**, the refuse vehicle **10** includes a lift mechanism/system (e.g., a front-loading lift assembly, etc.), shown as lift assembly **40**, coupled to the front end of the body **14**. In other embodiments, the lift assembly **40** extends rearward of the body **14** (e.g., a rear-loading refuse vehicle, etc.). In still other embodiments, the lift assembly **40** extends from a side of the body **14** (e.g., a side-loading refuse vehicle, etc.). As shown in FIG. **1**, the lift assembly **40** is configured to engage a container (e.g., a residential trash receptacle, a commercial trash receptacle, a container having a robotic grabber arm, etc.), shown as refuse container **60**. The lift assembly **40** may include various actuators (e.g., electric actuators, hydraulic actuators, pneumatic actuators, etc.) to facilitate engaging the refuse container **60**, lifting the refuse container **60**, and tipping refuse out of the refuse container **60** into the hopper volume of the refuse compartment **30** through an opening in the cover **36** or through the tailgate **34**. The lift assembly **40** may thereafter return the empty refuse container **60** to the ground. According to an exemplary embodiment, a door, shown as

top door **38**, is movably coupled along the cover **36** to seal the opening thereby preventing refuse from escaping the refuse compartment **30** (e.g., due to wind, bumps in the road, etc.).

(17) Energy Storage and/or Generation System

(18) As shown in FIG. 2, the energy storage and/or generation system **20** is coupled to the rearward top portion of the body **14**. In other embodiments, the energy storage and/or generation system **20** is coupled to the forward top portion of the body **14**. In some embodiments, the energy storage and/or generation system **20** is removable/detachable from the body **14**. Locating the energy storage and/or generation system **20** on top of the body **14** facilitates easy access to the energy storage and/or generation system **20**. For example, a user may readily inspect and service the energy storage and/or generation system **20** because it is located on an external surface of the refuse vehicle **10**.

(19) The energy storage and/or generation system **20** may include one or more attachment mechanisms (e.g., pins, linkages, latches, etc.) to couple the energy storage and/or generation system **20** to the body **14**. In some embodiments, the energy storage and/or generation system **20** is a pod or battery compartment, configured to receive and electrically couple one or more batteries. For example, the energy storage and/or generation system **20** may allow a battery cell to be inserted from one end thereby coupling the battery cell to the energy storage and/or generation system **20** and providing power to the refuse vehicle **10**. In some embodiments, the energy storage and/or generation system **20** is modular and facilitates easy replacement of one or more battery cells. For example, a second fully charged battery cell may replace a first depleted battery cell by uncoupling the first battery cell from the energy storage and/or generation system and replacing it with the second battery cell. In some embodiments, the entire energy storage and/or generation system **20** is replaced with a different one of energy storage and/or generation system **20**. Replacing one or more battery cells of the energy storage and/or generation system reduces the downtime associated with charging a typical battery system. In some embodiments, the energy storage and/or generation system **20** is “hot-swappable” and is able to replace one or more battery cells without cutting power to the refuse vehicle **10**.

(20) The energy storage and/or generation system **20** may include an electric connection (e.g., a pantograph, a current collector, a high-voltage line, etc.) to allow the energy storage and/or generation system **20** to connect to external power sources (e.g., an overhead power line, the grid, a charging station, etc.). For example, the energy storage and/or generation system **20** may include a charging port to allow one or more battery cells to be charged while the energy storage and/or generation system **20** is coupled to the refuse vehicle **10** (e.g., by a 220V charger). In some embodiments, the energy storage and/or generation system **20** includes an electrical bypass to power the refuse vehicle **10** from a charging source while the battery is being charged. In some embodiments, the energy storage and/or generation system **20** connects to one or more power sources of refuse vehicle **10** (e.g., an internal combustion generator, a battery, etc.) to charge the energy storage and/or generation system **20**. For example, the energy storage and/or generation system **20** may include a connection to an onboard diesel generator configured to provide power to the energy storage and/or generation system **20** for charging.

(21) As shown in FIG. 3, the energy storage and/or generation system **20** is coupled to the rearward bottom portion of the body **14**. In other embodiments, the energy storage and/or generation system **20** is coupled to the forward bottom portion of the body **14**. As described above, the energy storage and/or generation system **20** may be removable/replaceable. For example, the refuse vehicle **10** may include a door on the side of the body **14** to allow removal and replacement of the energy storage and/or generation system **20**. In some embodiments, the energy storage and/or generation system **20** is located on a track such that the energy storage and/or generation system **20** can slide out from the body **14** similar to a drawer. In some embodiments, the energy storage and/or generation system **20** is modular. For example, the energy storage and/or generation system **20** may include one or more sub-batteries to reduce the bulkiness of the energy storage and/or generation

system **20** and permit easy removal and/or replacement. Modularity further enables more precise inspection and service of battery cells and allows individual battery cells to be replaced without the need to replace an entire larger array. Furthermore, modularity enables battery cells to be easily upgraded.

(22) As described above, the energy storage and/or generation system **20** may include a charging port to allow the energy storage and/or generation system **20** to receive external power for charging. For example, the refuse vehicle **10** may include a 220V charging port on a side of the body **14** to charge the energy storage and/or generation system **20**.

(23) As shown in FIG. **4**, the energy storage and/or generation system **20** is coupled between the cab **16** and the body **14**. In some embodiments, the energy storage and/or generation system **20** is coupled to the frame **12**. Locating the energy storage and/or generation system **20** between the cab **16** and the body **14** reduces a rear weight of the refuse vehicle **10**, thereby reducing component stress of weight bearing members (e.g., a rear axle). Furthermore, centrally locating the energy storage and/or generation system **20** protects the energy storage and/or generation system **20** from damage in the event of a collision. Furthermore, centrally locating the energy storage and/or generation system **20** allows easy modification/retrofitting of existing refuse vehicles to include the energy storage and/or generation system **20**. The energy storage and/or generation system **20** may be easily accessed and/or removed from the refuse vehicle **10**. For example, the energy storage and/or generation system **20** may include forklift pockets so that a forklift may easily remove the energy storage and/or generation system **20** from the refuse vehicle **10**. In some embodiments, the system **20** includes one or more eyelet connectors to receive a lifting hook or similar hoisting attachment. The energy storage and/or generation system **20** may be configured to connect to an external rail system to quickly replace the energy storage and/or generation system **20** by sliding it orthogonally off the refuse vehicle **10**.

(24) In some embodiments, the energy storage and/or generation system **20** is configured to dynamically change position on the refuse vehicle **10** based on loading of the refuse vehicle **10**. For example, the energy storage and/or generation system **20** may translate horizontally along the frame **12** toward the cab **16** or toward the body **14** to change a weight distribution of the vehicle. In some embodiments, the energy storage and/or generation system **20** includes one or more controllers to measure the weight distribution of the refuse vehicle **10** and adjust a position of the energy storage and/or generation system **20** accordingly.

(25) As shown in FIG. **5**, the energy storage and/or generation system **20** is coupled to the tailgate **34** of the refuse vehicle **10**. In some embodiments, the energy storage and/or generation system **20** is positioned vertically along a rearward side of the refuse compartment **30**. In some embodiments, the energy storage and/or generation system **20** is positioned substantially near the base of the tailgate **34** or as part of the tailgate **34**. The energy storage and/or generation system **20** may be configured to be accessible via the tailgate **34**. For example, a user could open the tailgate **34** to reveal the energy storage and/or generation system **20**. In some embodiments, the tailgate **34** includes one or more rotating elements (e.g., hinges, mechanical bearings) to facilitate rotation around a rearward corner of the refuse compartment **30**. For example, the tailgate **34** could include one or more hinging mechanisms on a side to allow a user to open the tailgate **34** like a door and gain access to the energy storage and/or generation system **20** located along the frame **12** of the refuse vehicle **10**. In some embodiments, the tailgate **34** is a double door. Swinging the tailgate **34** open like a door requires less energy than lifting the tailgate **34**.

(26) In some embodiments, the tailgate **34** is fully integrated with the energy storage and/or generation system **20** and is configured to be removable/replaceable. For example, a first tailgate **34** having a first energy storage and/or generation system **20** could be replaced by a second tailgate **34** having a second energy storage and/or generation system **20** when the first energy storage and/or generation system **20** is depleted of energy. Removing and replacing the tailgate **34** may limit loss of vehicle operation due to charging time because the tailgate **34** including the depleted

energy storage and/or generation system **20** may be charged separately of the refuse vehicle **10**. Furthermore, swappable energy storage and/or generation systems enable a smaller fleet of refuse vehicles to service the same area because the reduced downtime associated with battery charging enables the refuse vehicles to operate for longer periods of time. In some embodiments, a number of racks index one or more battery cells of the energy storage and/or generation system **20**.

(27) As shown in FIG. **6**, the energy storage and/or generation system **20** is coupled between the body **14** and the frame **12**. As described above, in some embodiments, the energy storage and/or generation system **20** may be configured to translate horizontally along the frame **12** of the refuse vehicle **10**. For example, the energy storage and/or generation system **20** could move between a forward portion and a rearward portion of the body **14** of the refuse vehicle **10** such that the refuse vehicle **10** is evenly loaded. As described above, in some embodiments, the energy storage and/or generation system **20** is removable and/or replaceable. The energy storage and/or generation system **20** may be accessed via a door on a side of the body **14** or via the tailgate **34**. Similarly, the energy storage and/or generation system **20** may be removed and/or replaced by another energy storage and/or generation system. Alternatively, one or more individual battery cells of the energy storage and/or generation system **20** could be replaced. In some embodiments, the energy storage and/or generation system **20** can be accessed by removing the refuse compartment **30**. For example, a refuse vehicle with a removable refuse compartment (e.g., a container truck) may remove the refuse compartment to reveal the energy storage and/or generation system **20**. In some embodiments, the energy storage and/or generation system **20** is coupled to the refuse compartment **30** itself and can be removed with the refuse compartment **30**. For example, a refuse vehicle could swap a first full refuse compartment with a first depleted energy storage and/or generation system for a second empty refuse compartment with a second charged energy storage and/or generation system.

(28) Referring now to FIGS. **7A-8B**, several illustrations of an exemplary placement of the energy storage and/or generation system **20** is shown, according to several exemplary embodiments. In various embodiments, the energy storage and/or generation system **20** is coupled to a rearward top portion of the refuse vehicle **10** (e.g., above the refuse compartment etc.). Additionally or alternatively, the energy storage and/or generation system **20** is coupled to a rearward portion of the refuse vehicle **10**. For example, the energy storage and/or generation system **20** may be coupled to the tailgate **34** and/or a rearward portion of the refuse compartment **30** (e.g., as shown in FIGS. **7A-7C**). As another example, the energy storage and/or generation system **20** may be coupled to a vertical rear surface of the refuse compartment **30**. In some embodiments, the energy storage and/or generation system **20** or components thereof are coupled to the wheel **22**. For example, an energy storage cell of the energy storage and/or generation system **20** may be coupled to a hub of the wheels **22** and a power converter of the energy storage and/or generation system **20** may be coupled to a top rearward portion of the refuse container **30**. In some embodiments, the energy storage and/or generation system **20** is coupled to a front and rear wheelset of the refuse vehicle **10** (e.g., as shown in FIGS. **7A-7C**). In various embodiments, placement of the energy storage and/or generation system **20** as shown in FIGS. **7A-7C** facilitates shifting weight rearward on the refuse vehicle **10**, thereby reducing strain on forward load bearing components (e.g., a front axle, etc.). In some embodiments, the placement of the energy storage and/or generation system **20** shown in FIGS. **7A-7C** is preferred for a rear-loading refuse vehicle **10**. In various embodiments, the energy storage and/or generation system **20** includes a different number and/or arrangement of components than shown explicitly in the FIGURES. For example, the energy storage and/or generation system **20** may include a first component coupled to an exterior hub surface of the front wheels **22** electrically coupled to a second component integrated with the tailgate **34**. In some embodiments, the placement of the energy storage and/or generation system **20** shown in FIGS. **8A-8B** is preferred for a front-loading refuse vehicle **10** and/or a side-loading refuse vehicle **10**. In various embodiments, the energy storage and/or generation system **20**, or components thereof, are

detachable from the refuse vehicle **10** as described in detail above.

(29) Referring now to FIGS. **9A-9B**, several illustrations of another exemplary placement of the energy storage and/or generation system **20** is shown, according to several exemplary embodiments. In various embodiments, the energy storage and/or generation system **20** is coupled to a top portion of the refuse vehicle **10**. For example, the energy storage and/or generation system **20** may be coupled to a top portion of refuse compartment **30** and/or above the cab **16** (e.g., as shown in FIGS. **9A-9B**). In some embodiments, the energy storage and/or generation system **20** is coupled to a canopy (or other structural element) located above the cab **16**. Additionally or alternatively, the energy storage and/or generation system **20**, or components thereof, may be coupled to the wheels **22**. For example, a first component of the energy storage and/or generation system **20** (e.g., a battery cell, etc.) may be coupled to an exterior hub region of the wheels **22** and a second component of the energy storage and/or generation system **20** (e.g., a power converter, etc.) may be coupled to a structural element (e.g., a portion of frame **12**, etc.) above the cab **16**. In some embodiments, the placement of the energy storage and/or generation system **20** shown in FIGS. **9A-9B** is preferred for a rear-loading refuse vehicle **10**. In various embodiments, the placement of the energy storage and/or generation system **20** as shown in FIGS. **9A-9B** facilitates moving weight (e.g., battery weight, etc.) forward on the refuse vehicle **10** (e.g., toward the cab **16** and away from the tailgate **34**, etc.), thereby reducing stress on rear load-bearing components (e.g., a rear axle, etc.).

(30) As utilized herein, the terms “approximately,” “about,” “substantially”, and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

(31) It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

(32) The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using a separate intervening member and any additional intermediate members coupled with one another, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

(33) References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

(34) The hardware and data processing components used to implement the various processes, operations, illustrative logics, logical blocks, modules and circuits described in connection with the

embodiments disclosed herein may be implemented or performed with a general purpose single- or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, or, any conventional processor, controller, microcontroller, or state machine. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, particular processes and methods may be performed by circuitry that is specific to a given function. The memory (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory may be or include volatile memory or non-volatile memory, and may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. According to an exemplary embodiment, the memory is communicably connected to the processor via a processing circuit and includes computer code for executing (e.g., by the processing circuit or the processor) the one or more processes described herein.

(35) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(36) Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

(37) It is important to note that the construction and arrangement of the refuse vehicle **10** and the systems and components thereof as shown in the various exemplary embodiments is illustrative only. Additionally, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. Although only one example of an element from one embodiment that can be incorporated or utilized in another embodiment has been described above, it should be appreciated that other elements of the various embodiments may be incorporated or utilized with any of the other embodiments disclosed herein.

Claims

1. An electrified vehicle comprising: a chassis; a cab coupled to the chassis; a body assembly coupled to the chassis, the body assembly positioned behind the cab with a space defined therebetween; and an energy storage system positioned within the space between the cab and the body assembly, the energy storage system including: a housing coupled directly to the chassis and extending upward from the chassis such that a portion of the housing is positioned above at least a portion of a roof of the cab; and a plurality of battery cells disposed within the housing.
2. The electrified vehicle of claim 1, wherein the energy storage system includes power control hardware disposed within the housing.
3. The electrified vehicle of claim 1, wherein the plurality of battery cells are removable from the housing.
4. The electrified vehicle of claim 1, wherein the energy storage system is positioned to distribute weight forward of a rear axle of the electrified vehicle to reduce loading on the rear axle.
5. The electrified vehicle of claim 1, further comprising a generator configured to facilitate charging the energy storage system.
6. The electrified vehicle of claim 1, further comprising an electric motor, wherein the energy storage system is configured to provide electric power to the electric motor.
7. The electrified vehicle of claim 6, wherein the electric motor is configured to drive at least one of a front axle or a rear axle of the electrified vehicle.
8. The electrified vehicle of claim 7, further comprising: the front axle coupled to the chassis; and the rear axle coupled to the chassis.
9. The electrified vehicle of claim 6, wherein the electric motor is configured to drive a fluid system of the electrified vehicle.
10. The electrified vehicle of claim 6, wherein the electric motor is configured to selectively drive (a) an axle of the electrified vehicle and (b) a fluid system of the electrified vehicle.
11. The electrified vehicle of claim 1, wherein the plurality of battery cells are a first plurality of battery cells, further comprising a second plurality of battery cells positioned outside of the space between the cab and the body assembly.
12. The electrified vehicle of claim 1, wherein the electrified vehicle is a truck.
13. An electrified vehicle comprising: a chassis; a cab coupled to the chassis; a body coupled to the chassis; and an energy storage system positioned between the cab and the body, the energy storage system including: a housing coupled directly to and extending upward from the chassis, the housing extending above at least a portion of a roof of the cab; a plurality of battery cells disposed within the housing; and power control hardware disposed within the housing.
14. The electrified vehicle of claim 13, wherein the electrified vehicle is a truck.
15. The electrified vehicle of claim 13, wherein the plurality of battery cells are a first plurality of battery cells, further comprising a second plurality of battery cells positioned outside of the housing.
16. The electrified vehicle of claim 13, further comprising a generator configured to facilitate charging the energy storage system.
17. The electrified vehicle of claim 13, further comprising: at least one of an axle or a fluid system; and an electric motor electrically coupled to the energy storage system, wherein the electric motor is configured to drive the at least one of the axle or the fluid system.
18. The electrified vehicle of claim 17, wherein the electrified vehicle includes the axle and the fluid system, and wherein the electric motor is configured to drive the axle and the fluid system.
19. An electrified vehicle comprising: a chassis; a front axle coupled to the chassis; a rear axle coupled to the chassis; an electric motor configured to drive at least one of the front axle or the rear axle; a cab coupled to the chassis; a body coupled to the chassis, the body positioned behind the

cab with a space defined therebetween; and an energy storage system including a housing coupled to the chassis within the space between the cab and the body, wherein a portion of the housing is positioned above at least a portion of a roof of the cab.
