

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12409826
B2
September 09, 2025
Couppee; Ulrich et al.

Trailer brake control module

Abstract

A trailer brake control module (300a; 300b; 300c) for a towing vehicle (502) facilitating braking of a towed vehicle or trailer (504) includes a pressure supply port (P11), a trailer control pressure port (P22), a primary control port (P42) for receiving either directly and/or indirectly a control brake pressure for operating the trailer brake control module (300a; 300b; 300c). The primary control port (P42) receives the control brake pressure from a pneumatically operated pressure medium, a pneumatic control pressure line (308.1) provides alternative control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the pneumatic control pressure line (308.1) receives the alternative control brake pressure from an electronically operated pressure medium, and a relay valve (310) is activated using either the control brake pressure received at the primary control port (P42), or the alternative control brake pressure from the pneumatic control pressure line (308.1).

Inventors:	Couppee; Ulrich (Coppentrügge, DE), Drelich; Lukasz (Czestochowa, PL), Otremba; Robert (Ronnenberg, DE), Riediger-Janisch; Karl-Heinz (Hannover, DE), Swiatek; Pawel (Wroclaw, PL), Toma; Leszek (Wroclaw, PL)
Applicant:	ZF CV Systems Europe BV (Brussels, BE)
Family ID:	73037934
Assignee:	ZF CV Systems Europe BV (Brussels, BE)
Appl. No.:	18/032575
Filed (or PCT Filed):	October 21, 2020
PCT No.:	PCT/EP2020/079556
PCT Pub. No.:	WO2022/083855
PCT Pub. Date:	April 28, 2022

Prior Publication Data

Document Identifier

US 20230398973 A1

Publication Date

Dec. 14, 2023

Publication Classification

Int. Cl.: **B60T15/20** (20060101); **B60T13/26** (20060101); **B60T13/68** (20060101)

U.S. Cl.:

CPC **B60T15/203** (20130101); **B60T13/263** (20130101); **B60T13/683** (20130101);

Field of Classification Search

CPC: B60T (8/266); B60T (8/362); B60T (8/1708); B60T (13/683); B60T (13/66); B60T (13/265); B60T (13/263); B60T (15/027); B60T (15/18); B60T (15/181); B60T (15/203); B60T (17/22); B60T (2230/06)

USPC: 303/7

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4264108	12/1980	Bordoni	N/A	N/A
4768840	12/1987	Sullivan	303/9.62	B60T 17/22
4804234	12/1988	Gee	303/9.62	B62D 53/0807
4818035	12/1988	McNinch, Jr.	303/9.69	B60T 8/74
2008/0030068	12/2007	Bensch	303/17	B60T 13/588
2015/0239441	12/2014	Klostermann	303/7	B60T 11/108
2018/0304871	12/2017	Eckert	N/A	B60T 8/17554
2020/0047730	12/2019	Van Thiel	N/A	B60T 15/027
2020/0094805	12/2019	Riley et al.	N/A	N/A
2020/0139953	12/2019	Dombek et al.	N/A	N/A
2020/0223414	12/2019	Brütt	N/A	B60T 13/263

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110431054	12/2018	CN	N/A
110446634	12/2018	CN	N/A
110446637	12/2018	CN	N/A
102018123750	12/2019	DE	N/A

OTHER PUBLICATIONS

European Patent Office, Rijswijk, Netherlands, International Search Report of International Application No. PCT/EP2020/079556, Mailed Jul. 15, 2021, 3 pages. cited by applicant
English Translation of Chinese Office Action issued by the Chinese Patent Office (CPO) on Jun. 20, 2025 (Notification of First Office Action and Search Report), 9 pages. cited by applicant

Primary Examiner: Siconolfi; Robert A.

Assistant Examiner: Aung; San M

Attorney, Agent or Firm: Dickinson Wright PLLC

Background/Summary

FIELD

(1) The present disclosure relates to trailer brake control modules or trailer control valves. In particular, the present disclosure relates to a trailer control valve utilized in a modular brake control system of a towing vehicle. The trailer control valve can be operated using pressurized air.

(2) Throughout the text explaining the present disclosure, the terms—towing vehicle, towed vehicle, or trailer are repeatedly used in a variety of contexts. For the sake of understanding, it is noted that the term “towing vehicle” can refer to e.g., a truck, tractor, or any other vehicle which includes a primary propulsion system e.g., an engine for moving the vehicle. The term “towed vehicle” can refer to a trailer, a semi-trailer, or any extension of the towing vehicle with at least a pair of wheels included in it.

BACKGROUND

(3) The existing conventional braking systems include a variety of techniques to manage the difference in deceleration rates between a towing vehicle and a trailer. This is necessary, for instance, to prevent over-braking and/or under-braking of the trailer in comparison to the towing vehicle.

(4) However, the role of trailer control valves in achieving a balance in the deceleration rates between the towing vehicle and the trailer is seldom provided the attention it deserves.

(5) One such conventional trailer control valve with means to balance the deceleration rates with a pneumatic valve such as a predominance valve attached to the side of the trailer control valve is explained in the patent publication U.S. Pat. No. 4,264,108A.

(6) Furthermore, conventional trailer control valves helping to meet the requirements of Regulation No. 13 of Economic Commission for Europe of the United Nations (UN/ECE), in particular stipulations under S. No. 5.2.1.28 are already known.

(7) There is however still a need to further improve and/or to provide effective alternatives to the existing trailer control valves.

SUMMARY

(8) In accordance with an embodiment, a trailer brake control module for a towing vehicle facilitating braking of a towed vehicle or trailer is disclosed. The trailer brake control module comprises a pressure supply port, a trailer control pressure port, a primary control port for receiving either directly or indirectly a control brake pressure for operating the trailer brake control module, wherein the primary control port receives the control brake pressure from a pneumatically operated pressure medium. The trailer brake control module further comprises a pneumatic control pressure line providing alternative control brake pressure for operating the trailer brake control module, wherein the pneumatic control pressure line receives the alternative control brake pressure from an electronically operated pressure medium, and a relay valve is activated using either the control brake pressure received at the primary control port, or the alternative control brake pressure from the pneumatic control pressure line, wherein on activating the relay valve, the pneumatic pressure received at the pressure supply port is connected to the trailer control pressure port, wherein the trailer brake control module is additionally provided with a braking rate (z) rebalancing unit so that the difference of the braking rate between said towing vehicle and said trailer is maintained within a permissible threshold range.

(9) The presence of the braking rate rebalancing unit within the trailer brake control module enables the rebalancing of the difference in the individual braking rate enabled at the towing and towed vehicles. This rebalancing is necessary to prevent accidental effects during the application of brakes in the towing and towed vehicles such as jack-knifing.

(10) In accordance with a preferred embodiment, the braking rate (z) rebalancing unit can be or is an electronic unit or a mechanical unit (predominance valve) or an electro-mechanical valve unit explained in one or more aspects of the present disclosure as “electronically operated sub-unit (W, **304, 306**)” in a trailer brake module (**300a**) or “mechanically operated sub-unit (PRV)” in a trailer brake module (**300b** or **300c**).

(11) Furthermore, in accordance with an embodiment of the present disclosure, the trailer brake control module consists of the following ports: the primary control port, a parking brake control port, the pressure supply port, the trailer control pressure port, a trailer supply pressure port, and a pressure relief port at the housing of the trailer brake module. This should be read in comparison with what is known in prior art e.g., as displayed in FIG. 2 where an additional port **P41** is provided. Thus, conventional trailer brake control modules include one more port **P41** which entails one more chamber for receiving the pressurized air from **P41** and an additional control piston therein. Such components are rendered unnecessary with the trailer brake module consisting of the ports mentioned above thereby having a positive effect on the costs of the device.

(12) In accordance with an embodiment of the present disclosure, the trailer brake control module further comprises a double check or select-high valve for supplying one of the control brake

pressure and the alternative control brake pressure depending on the magnitude of each of the brake pressures, wherein the brake pressure which has the higher magnitude is supplied to the relay valve. For instance, the presence of the double check valve directly contributes to the number of control pressure ports necessary for the trailer brake control module. As can be realized, the double check valve enables connecting the relay valve with the pressure of higher magnitude from either the control brake pressure received at the primary control port, or the alternative control brake pressure from the pneumatic control pressure line. Thus, the need for having an additional redundant pneumatic control port, should the connection to the primary control port fail, is eliminated.

(13) In accordance with the present embodiment, said brake rate rebalancing unit includes a mechanically operated sub-unit which is either coaxially positioned in relation to a central axis (Y-Y') of the trailer brake control module or is positioned perpendicular to said central axis (Y-Y'), wherein said mechanically operated sub-unit is at least vertically above the relay valve and/or at the same horizontal level or above the horizontal level of the trailer control pressure port taking the central axis (Y-Y') as reference.

(14) The mechanically operated sub-unit provides a trailer brake control module which is hybrid in nature, in which said brake control module can work under an electronic control (e.g., via operating the solenoid valves), but on the other hand cannot or need not block out the pneumatic driver control using e.g., the mechanically operated sub-unit.

(15) In an embodiment, the trailer brake control module further comprises a pneumatically controlled metering valve connecting the pressure supply port and a trailer supply pressure port, wherein said metering valve operates in first and second positions, wherein in the first position, the metering valve connects the pressure supply port and the trailer supply pressure port through a throttled flow orifice, and wherein in the second position, the metering valve connects the pressure supply port and the trailer supply pressure port in an invariable and open manner such that the whole of the pneumatic pressure received at the pressure supply port is transmitted to the trailer supply pressure port. In combination with the above embodiment, preferably wherein the pneumatically controlled metering valve is held in the second position with the help of at least partly pre-existing pressure in the trailer supply pressure port and/or a spring.

(16) In accordance with yet another embodiment, the trailer brake control module, of any one of the above embodiments, further comprises a first electronically controlled solenoid valve whose inlet is connected to the pressure supply port and outlet is selectively connected to the relay valve, wherein said outlet supplies the alternative control brake pressure. For instance, the electronically controlled solenoid valve enables electronically implemented dynamic braking functions such as EBS (Electronic Brake System), ASR (Anti-Slip Regulation), ESP (Electronic Stability Program) and others while operating the trailer brake control module.

(17) In accordance with one more of the above embodiments, the outlet of the first electronically controlled solenoid valve carrying the alternative control brake pressure is connected to a first inlet of the double check or select-high valve, wherein the double check or select-high valve enables the selective connection of the outlet with the relay valve when the pressure supplied at the outlet is of higher magnitude than the pressure at the primary control port.

(18) In accordance with any one of the above embodiments, the magnitude of the pressure received at the primary control port is proportional to the driver's brake demand.

(19) The trailer brake control module, in accordance with any one of the above embodiments, provides that the pressure at the trailer brake control port is measured using a Pulse Width Modulation (PWM) based pressure sensor. The technical purpose and/or advantage of using the PWM based pressure sensor is to provide for "functional safety" according to ISO standard 26262.

(20) In accordance with one or more embodiments, the trailer brake control module further comprises a first pneumatic control chamber to which the primary control port is connected. Furthermore, in the same or different embodiment, the trailer brake control module further

comprises a first control piston separating the first pneumatic control chamber and an additional volume (AV), and wherein the first control piston integrally comprises a fluid flow path indirectly connecting the trailer control pressure port and the additional volume (AV).

(21) Furthermore, a pneumatic brake system comprising the trailer brake control module of any one of the above-mentioned embodiments is provided. The system further comprises an electronic control unit connected to the trailer brake control module to perform brake functions with or without driver brake demand. In the same or different embodiment, the pneumatic brake system is disclosed, wherein the electronic control unit controls the trailer brake control module such that braking rate (z) rebalancing unit achieves the maintenance of the difference of the braking rate between said towing vehicle and said towed vehicle within said permissible threshold range.

(22) Finally, a commercial vehicle or an autonomous vehicle comprising the pneumatic brake system of the above embodiment is disclosed.

(23) For a more complete understanding of the present disclosure, the present disclosure will now be described in detail with reference to the accompanying drawing. The detailed description will illustrate and describe what is considered as a preferred embodiment of the present disclosure. It should of course be understood that various modifications and changes in form or detail could readily be made without departing from the spirit of the present disclosure. It is intended that the present disclosure may not be limited to the exact form and detail shown and described herein, nor to anything less than the whole of the present disclosure disclosed herein and as claimed hereinafter. Further the features described in the description, the drawing and the claims disclosing the present disclosure may be essential for the present disclosure considered alone or in combination. In particular, any reference signs in the claims shall not be construed as limiting the scope of the present disclosure. The wording “comprising” does not exclude other elements or steps. The wording “a” or “an” does not exclude a plurality. The wording, “a number of” items, comprises also the number one, i.e. a single item, and further numbers like two, three, four and so forth.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows an exemplary characteristic curve displaying a comparison of deliver pressure at port P22 of an exemplary trailer control valve and a control pressure received at primary control port P42 of the exemplary trailer control valve;
- (2) FIG. 2 shows a schematic diagram of a conventional trailer control valve;
- (3) FIG. 3a shows a schematic diagram of a trailer control valve in accordance with an embodiment of the present disclosure;
- (4) FIG. 3b shows a schematic diagram of a trailer control valve in accordance with another embodiment of the present disclosure;
- (5) FIG. 4a shows an external view of a trailer control valve in accordance with an embodiment of the present disclosure;
- (6) FIG. 4b shows a cross-sectional view (taken at section B-B) of a trailer control valve (shown in FIG. 4a) in accordance with an embodiment of the present disclosure;
- (7) FIG. 4c shows a cross-sectional view (taken at section A-A) of a trailer control valve (shown in FIG. 4a) in accordance with an embodiment of the present disclosure;
- (8) FIG. 5 shows a cross-sectional view of a trailer control valve in accordance with yet another embodiment of the present disclosure; and
- (9) FIG. 6 schematically shows a commercial vehicle, or an autonomous vehicle equipped with a trailer control valve in accordance with an embodiment of the present disclosure.
- (10) For identical or equivalent items or items of identical or equivalent function(s) same reference

marks or signs are used. The corresponding features are generally referred to the description.

DETAILED DESCRIPTION

(11) FIG. 1 shows an exemplary characteristic curve displaying a comparison of deliver pressure at port labeled “P22” of Y-Axis (the port is not shown in FIG. 1, but see e.g., FIG. 2 or FIGS. 3a and 3b for understanding) of an exemplary trailer control valve (not shown in FIG. 1, but see e.g., FIG. 2 or FIGS. 3a and 3b) and a control pressure received at primary control port P42 (the port is not shown in FIG. 1, but see e.g., FIG. 2 or FIGS. 3a and 3b) of the exemplary trailer control valve (not shown in FIG. 1, but see e.g., FIG. 2 or FIGS. 3a and 3b).

(12) For the sake of explanation, it is denoted that the pressure at P22 leads to a coupling head (see e.g., 312.2 in FIG. 3a) provided at the end of P22. The coupling head is connected to the pneumatic line which represents the control pressure that is required to operate a trailer brake system. Alternative term for coupling heads is ‘glad hand’, which is predominantly used in brake terminologies.

(13) The exemplary characteristic curve shown in FIG. 1 at a region 102 represents an increasingly disproportionate magnitude (or a slightly higher magnitude) of pressure recorded at port “P22” after approximately 0.5 bar (see X-axis of the curve) is achieved at port P42 (primary control port). As can be noticed, between e.g., 0.5 to 0.7 bar of pressure recorded at port P42, there is considerably surge in pressure at port P22.

(14) This “surge” later changes or is relatively reduced at region “101” marked in graph shown in FIG. 1 after a point of deflection “103”, which is also marked in the graph. In any case, the point of deflection 103 in FIG. 1 can represent opening of a predominance valve within a trailer brake control module i.e., based on the settings in the predominance valve, the curve at region 101 can move left or right in comparison to the curve at 103, but nevertheless would maintain a slope of 45 degrees. One such example of the predominance valve is cited in the background section is e.g., known from U.S. Pat. No. 4,264,108A. If the volume in the predominance valve is filled, the curve shown after region 102 i.e., in region 101 in FIG. 1 progresses almost proportionally. For instance, in simple terms, a 3 bar control input at e.g., port P42 can lead to a 2.7 or 3.6 bar output at port P22. This change in the output is referred to as a “predominance” setting, which can be adjusted to be in a predetermined range today from e.g., -1 bar to +0.3 bar. Typically, this type of change in predominance set is carried out after assembly of a trailer control valve or trailer brake module by a testing department before the product reaches a customer.

(15) In any case, the predominance valve in simple terms extends the volume of a chamber of the trailer control valve connected to port P22 using e.g., a spring-based check valve system.

(16) One of the reasons for providing this predominance valve in the pneumatic brake circuit is to enable achieving a balance in the braking rate between the towing vehicle and the towed vehicle.

(17) The braking rate (z) of a vehicle is generally defined as: $z = \text{braking rate of vehicle} = J/g$, wherein ‘J’ refers to the deceleration of the corresponding vehicle (towed or towing) in ‘m/s.sup.2’ and ‘g’ refers to the acceleration due to gravity=9.81 m/s.sup.2.

(18) However, an unmanaged difference in the braking rate between the towed vehicle and the towing vehicle can cause instability while braking the vehicle. In extreme cases, this may also result in effects such as jack-knifing.

(19) For the sake of understanding, it is mentioned herewith that the desired braking rate of a vehicle and/or a trailer is dependent on a variety of factors such as size and its load carrying capacity, rolling resistance. Thus, a value or a range of values cannot be explicitly mentioned as these are customized based on the type of the vehicle, its characteristics, and also the characteristics of trailer attached to it. Furthermore, these values and/or ranges may be influenced by the class of the vehicles generally characterized by the weight, laden or unladen. In any case, what is required for an understanding, it is vital to have the difference in the braking rate between the towed and towing vehicle within a desired range. There are however variety of means to achieve this.

(20) FIG. 2 shows a schematic diagram of a conventional trailer control valve 200.

(21) Conventional trailer control valve **200** shown in FIG. 2 includes ports P3, P11, P12, P22 P41, P42, P43, a first control valve **204**, a conventional relay valve **202** and a conventional predominance valve CPRV. A brief explanation of conventional trailer control valve **200** is provided herewith.

(22) In FIG. 2, a supply pressure inlet P11 is shown which is typically connected to a pressurized fluid source (not shown in FIG. 2) such as a fluid reservoir. Supply pressure inlet P11 is connected to a trailer supply pressure outlet P12 which leads the output pressure to trailer brakes. Between supply pressure inlet P11 and trailer supply pressure outlet P12, a pneumatically controlled metering valve **204** is provided. Pneumatically controlled metering valve **204** operates for instance in two positions. In the first position as shown in FIG. 2 in the current state, pneumatically controlled metering valve **204** connects supply pressure inlet P11 directly to trailer supply pressure outlet P12 without any metering i.e., with no pressure reduction. However, in the second position, pneumatically controlled metering valve **204** may act as e.g., a throttled flow orifice wherein the supply pressure received at P11 is reduced before transmitting to trailer supply pressure outlet P12. For instance, metering valve **204** has two positions, one is fully open (full flow), and the second one is closed, smaller flow with an unspecified volume or flow rate.

(23) Furthermore, conventional trailer valve **200** includes relay valve **202** which needs to be activated by control pressure to enable a connection between the pressure provided from supply inlet P11 to a trailer control pressure outlet P22. In order to activate and/or deactivate relay valve **202** control pressure can be derived from each of the following ports: primary brake signal port P41, a primary control port P42, and a parking brake control port P43. In non-activated position, relay valve **202** enables connection between P11 and pressure relief port P3. The relay valve **202**, for instance, can be brought to the deactivated position when parking brake control port P43 is pressurized. At the deactivated state of relay valve **202**, and when the parking brake is desired to be activated, one or more brake actuators at the wheel end of the vehicle are extended merely because of the force of one or more springs provided within the actuators. This is, however, part of a common general knowledge of the skilled person in the field of brake systems.

(24) Finally, conventional predominance valve CPRV is provided in association with trailer control pressure outlet P22 to enable the predominance characteristics such as the as shown in region **101** of FIG. 1. This is merely shown for illustration of an additional volume connected to P22, but in practice the predominance valve may include a spring-based valve to let the pressure from port P22 into an extended volume it includes (see e.g., US patent publication 4264108 cited also above).

(25) FIG. 3a shows a schematic diagram of a trailer control valve or a trailer brake control module **300a** in accordance with an embodiment of the present disclosure.

(26) In accordance with the present embodiment, trailer brake control module **300a** is provided on a towing vehicle (not shown in FIG. 3a) in order to facilitate braking of a towed vehicle or trailer. The trailer brake control module **300a** comprises a pressure supply port or a supply pressure inlet P11, a trailer control pressure port or outlet P22, a primary control port P42 for receiving either directly and/or indirectly a control brake pressure for operating the trailer brake control module **300a**. In accordance with the present embodiment, the primary control port P42 receives the control brake pressure from a pneumatically operated pressure medium (not shown). In accordance with an exemplary embodiment, this pneumatically operated pressure medium can be a Brake Signal Transmitter (BST) or a Foot Brake Valve (FBV) or simply a valve that is directly connected to a brake pedal present at the driver's cabin. In principle, the pressure received at port P42 reflects largely the driver's actual brake demand.

(27) In the same embodiment, trailer brake control module **300a** includes a pneumatic control pressure line **308.1** providing alternative control brake pressure for operating trailer brake control module **300a**, wherein the pneumatic control pressure line **308.1** receives the alternative control brake pressure from an electronically operated pressure medium. Furthermore, a relay valve **310** (which is part of trailer brake control module **300a**) is activated using either the control brake

pressure received at primary control port P42, or the alternative control brake pressure from pneumatic control pressure line 308.1, wherein on activating relay valve 310, the pneumatic pressure, or at least part of that received at pressure supply port P11, is connected to trailer control pressure port P22. In the same embodiment, the trailer brake control module 300a; 300b is additionally provided with braking rate 'z' rebalancing unit so that the difference of the braking rate between said towing vehicle and said trailer is maintained within a permissible threshold range, wherein in accordance with the present embodiment said brake rate rebalancing unit is enabled using an electronically operated sub-unit (W, 304, 306), and more particularly, said brake rate rebalancing unit is provided within a housing (406) of the trailer brake module (300b).

(28) For instance, brake control module 300a in this embodiment includes said electronically operated sub-unit. Said sub-unit may include a connection plug W shown in FIG. 3a, a first solenoid valve 304, a second solenoid valve 306, and a pressure sensor 'X' (e.g., PWM based pressure sensor). In the same instance, at least connection plug W may be connected to a centralized electronic brake module (not shown in FIG. 3a) or an electronic control unit, which provides the requisite commands to operate or activate or deactivate e.g., first and second solenoid valves 304, 306 so as to enable maintenance of the braking rate difference between said towing vehicle and said trailer within the permissible threshold range. For instance, in a setup where electronic control is used in all normal operating conditions such as EBS, the predominance is electronically realized. One of the means of realizing this electronically is by the so-called CFC (coupling force control) function.

(29) It may be understandable here that said electronic control unit or the centralized electronic brake module may receive variety of inputs from sensors within the towing vehicle and the towed vehicle or trailer to determine what is the optimum braking performance that is required at any given time. In particular, the optimum braking performance is arrived at, such that the centralized electronic brake module or the electronic control unit within the trailer brake control module 300a can operate first and second solenoid valves 304 and 306 and effectively control e.g., operating frequency or cycles of said valves 304 and 306. By this way the maintenance of e.g., the braking rate difference between said towing vehicle and said trailer within the permissible threshold range is possible to be performed dynamically. It should be here understood that the term "dynamically" may refer to the varying values at different driving conditions experienced by the towed and towing vehicles. In accordance with this embodiment, should however the electronically operated sub-unit not function for any technical or electronic failure, there is no possibility of achieving the predominance.

(30) Thus, in accordance with this embodiment explained above, the braking rate (z) rebalancing unit is the same as said electronically operated sub-unit. The electronically operated sub-unit is part of trailer brake control module 300a.

(31) In accordance with the same or different embodiment discussed in association with FIG. 3a, it is also noticeable that there is no further pneumatic brake "control" port other than a primary control port P42 and a parking brake control port P43 within trailer brake control module 300a for receiving either directly and/or indirectly a control brake pressure for operating trailer brake control module 300a. Details of the pressurized air flow direction can be deciphered from the arrow marks indicated in FIG. 3a exiting and entering relay valve 310. Furthermore, the parking brake or hand brake signal that is provided to engage the parking brake of the trailer or the towed vehicle is supplied through port P43.

(32) One of the technical advantages envisaged in trailer brake control module 300a vis-à-vis conventional trailer control valve or module 200 shown in FIG. 2. In particular, the need for port P41 in module 300 is eliminated in comparison to trailer control valve or module 200 taking the overall construction of trailer brake control module 300a into account. Thus, the feature "the trailer brake control module 300a consists of the following ports: the primary control port (P42), a parking brake control port (P43), the pressure supply port (P11), the trailer control pressure port

(P22), a trailer supply pressure port (P21), and a pressure relief port (P3) within a housing (406) of the trailer brake module)" is directed to denote absence of any additional control port. A skilled person would notice that, this implies that a redundant pneumatic brake control port that can transmit the control brake pressure reflecting the driver's brake demand is made unnecessary. It also further implies a control piston and a control chamber within a trailer control valve is spared due to the absence of an additional port P41 which would activate relay valve 202 or 310. This particular technical advantage is applicable to all the trailer control brake modules explained in accordance with the present disclosure.

(33) Furthermore, as can be seen in FIG. 3a, trailer brake control module 300a is additionally provided with a double check or select-high valve 308 for supplying one of the control brake pressure and the alternative control brake pressure depending on the magnitude of each of the brake pressures, wherein the brake pressure which has the higher magnitude is supplied to relay valve 310. As mentioned above, double check valve 308 receives the control brake pressure from port P42 as marked in FIG. 3a. Optionally, a second filter F2 is provided at the line connecting primary control port P42 and double check valve 308. Furthermore, double check valve 308 receives the alternative control brake pressure via solenoid valve 304 (depending on its respective position) and a first connection 308.1 to connect at least part of the pressure received from port P11.

(34) In accordance with the present embodiment, double check valve 308 is configured to function as the select-high valve i.e., it moves a spool within the body of double check valve 308 to the side of the port which has a lesser pressure magnitude thereby connecting the pressure port with higher pressure magnitude to the outlet. From FIG. 3a, a skilled person would derive that if pressure from first connection 308.1 is of higher magnitude compared to the magnitude of pressure received from primary control port P42, the connection between first connection 308.1 and output port 308.2 is established. The situation is opposite if pressure is of higher magnitude is at port P42. This allows for saving costs in overall construction of trailer brake control module 300a as it potentially replaces an electronically controlled solenoid valve in its place along with detecting pressure sensors at each of the connections from port P42 and connection 308.1 and, thus, saves cost for a manufacturer of trailer brake modules. For a tier I manufacturer as the applicant/patentee, this results in reduction of costs depending on the scale and at the same time potentially saves time during the assembly.

(35) In the present embodiment, trailer brake control module 300a further comprises a trailer supply pressure port P21, wherein pressure supply port P11 and trailer supply pressure port P21 are connected via a pneumatically controlled metering valve 302. The technical purpose of using metering valve 302 in accordance with the present embodiment is for instance to ensure at least a minimum pressure supply to trailer brakes via port P21. As can be seen in FIG. 3a, inlet port 302.2 of metering valve 302 is connected to pressure supply port P11 and in both the positions of metering valve 302 some amount of pressurized fluid is transmitted to trailer supply pressure port P21 via outlet port 302.1. The position of metering valve 302 is controlled by using pressure at least partly from output port 308.2.

(36) In other words, pneumatically controlled metering valve 302 operates in two positions, namely first and second positions, wherein in the first position, metering valve 302 connects pressure supply port P11 and the trailer supply pressure port P21 through a throttled flow orifice, and wherein in the second position, metering valve 302 connects pressure supply port P11 and trailer supply pressure port P21 in an invariable and open manner such that the whole of the pneumatic pressure received at pressure supply port P11 is transmitted to trailer supply pressure port P21. In the embodiment disclosed in FIG. 3a, metering valve 302 includes a spring 302.3 which holds a piston or a spool in a predetermined position and the pressure from output port 308.2 determines the position of metering valve 302. Further, pneumatically controlled metering valve 302 is held in the second position with the help of at least partly because of the pre-existing pressure in trailer supply pressure port P21 and spring 302.3.

(37) On a different note, but part of the embodiment, trailer brake control module **300a** includes first electronically controlled solenoid valve **304** whose inlet **304.1** is connected to pressure supply port **P11** and outlet **304.2** is connected selectively to relay valve **310**, wherein outlet **304.2** supplies the alternative control brake pressure. This has a direct effect on the quantity and/or rate of the pressurized fluid that can be supplied to double check valve **308**. Furthermore, in accordance with an embodiment, the connection line which connects port **P11** and inlet **304.1** includes a first filter **F1** as can be derived from FIG. **3a** in order to remove any moisture and/or impurities in the pressurized fluid. Overall functioning of trailer brake control module **300a** is provided herewith.

(38) As shown in FIG. **3a**, with reference 'W', it denotes that electronic signals can be received via electric connection ports at "W". These electronic signals operate first and second solenoid valves **304** and **306**. Similar to first electronically controlled solenoid valve **304**, second electronically controlled solenoid valve **306** includes an inlet **306.1** and an outlet **306.2**, wherein based on the position of second electronically controlled solenoid valve **306** a connection from outlet **306.2** to pressure relief port **P3** is either established or prevented. They can be activated at varying frequency cycles such that a precise control over the pressure supplied to pneumatic control pressure line **308.1**. It should be noted that the activation of said first and second solenoid valves **304** and **306** can either be driver initiated or automatically performed by the electronic control unit (not shown in FIG. **3a**) based on the braking requirements of the trailer including the dynamically changing braking rates and emergency braking conditions at any given time. For instance, the emergency braking conditions take into account of external and/or environmental factors such as surface and/or road conditions.

(39) Thus, based on the activation states of solenoid valves **304** and **306**, the supply pressure that is received at port **P11** is sent to pneumatic control pressure line **308.1**. This brake pressure is referred in the present application as "alternative" control brake pressure. Simultaneously, a control brake pressure is also received at primary control port **P42** via a second pneumatic control pressure line **308.3**. Both the control brake pressure and said alternative control brake pressure converge at double check valve **308**, wherein whichever pressure line among **308.1** and **308.3** carries pressure with higher magnitude is fused with output port **308.2**. The pressure from output port **308.2** is partly sent to relay valve **310** and partly sent to metering valve **302**. When the pressure at output port **308.2** is above a certain threshold, a spring-based resistance (not shown) within relay valve **310** is overcome. This results in establishing a fluid connection between ports **P11**, **P21** and **P22** so that all said ports are supplied with pressure from a pressurized fluid source such as a reservoir (not shown in FIG. **3a**). This reservoir is connected to port **P11**.

(40) The pressure exiting port **P21** is connected to a first coupling head **312.1**, which in turn is connected to a supply pressure line for trailer brakes. Typically coupling head **312.1** is red colored. On the other hand, the pressure exiting port **P22** is connected to a second coupling head **312.2**, which in turn leads to a control pressure line for controlling or operating the trailer brakes.

(41) Furthermore, in accordance with a particularly preferred embodiment of the present disclosure, pressure at line connected to port **P22** is measured almost constantly using sensor 'X' referenced in FIG. **3a**. This sensor 'X' of this particularly preferred embodiment is a PWM-based-pressure sensor or Pulse-Width-Modulation-based-pressure sensor. The usage of PWM-based-pressure sensor enables "functional safety" according to ISO standard 26262 of trailer control module **300a**. Over the duration of usage of trailer control module **300a** in a commercial vehicle, the usage of PWM based pressure sensor directly affects the average life cycle of batteries used in the commercial vehicle.

(42) FIG. **3b** shows a schematic diagram of trailer control valve or trailer control module **300b** in accordance with another embodiment of the present disclosure.

(43) The elements that are explained in reference to FIG. **3a** are same in relation to FIG. **3b** except that trailer control module **300b** additionally includes a mechanically operated sub-unit '314' to establish the predominance or to maintain the brake rate difference between the towing vehicle and

the trailer within a predetermined threshold in addition to or alternative to the electronically operated sub-unit (W, **304**, **306**). The elements that are same in FIG. **3b** and FIG. **3a** are marked with same reference signs. For the sake of simplicity, the explanation provided in relation to the elements with the same reference signs in FIG. **3b** is not repeated.

(44) It is nevertheless noted that the disclosure provided in FIG. **3a** is provided to illustrate that in accordance with an exemplary embodiment on how the braking rate (z) rebalancing unit operates, particularly when it is implemented or enabled using the electronically operated sub-unit (W, **304**, **306**). As mentioned in the same embodiment, the electronically operated sub-unit e.g., 'W' may receive controls from a central electronic unit (such as **508** in FIG. **5**) or trailer control module **300a** or **300b** may have an electronic control unit be mounted to a housing of said module.

(45) In any case, the present embodiment discloses the brake rate rebalancing unit is enabled either optionally or additionally using a mechanically operated sub-unit **314** (which can alternatively be referred to as predominance valve) that is coaxially positioned in relation to the relay valve **310**. As symbolically represented in FIG. **3b**, mechanically operated sub-unit **314** is present in the path that connects outlet **310.1** of relay valve **310** and trailer control pressure port **P22**. This has space-saving effect taking the overall construction of trailer brake control module **300b** into account. Further details on this are provided in the explanation in relation to FIG. **4b**.

(46) It is however noted that mechanically operated sub-unit '314' that is symbolically shown in FIG. **3b** to be in the path of port **P22** as merely to represent an additional volume along the path. This additional volume may be selectively opened and/or closed using the pressure that reaches port **P22**, the details of which will be explained in reference to FIG. **4b**. In accordance with one exemplary application, this selective opening of mechanically operated sub-unit **314** causes the variation in pressure characteristics between port **P42** and **P22**, as displayed in FIG. **1** of the present application with reference sign "102". The initial spike in pressure at port **P22** is due to the closed status or non-opening of the predominance or additional volume of the mechanically operated sub-unit '314'. Once the predominance or additional volume is opened for access to pressure at port **P22**, there is a slight reduction in the pressure magnitude (or a change in the slope of the curve) at port **P22** which is shown in the graph of FIG. **1** beyond region **102**.

(47) As can be understood, this equalization of pressure magnitude at e.g., port **P22** needs to be taken into account every time trailer brake control module **300b** is operated and/or activated, wherein the predominance volume is selectively opened.

(48) To the contrary, in trailer brake control module **300a** disclosed in relation to FIG. **3a**, this phenomenon of providing pressure normalization after initial inequality of pressures at ports **P22** and **P42** as disclosed in region **102** of FIG. **1** is established via electronic control algorithms or control methods which are implemented via an electronic control unit **508** of FIG. **5**.

(49) One of the unique advantages of trailer brake control module **300b** is that it combines the possibility of purely electronically controlling pressure characteristics at ports **P22** and **P42** to follow the trend of pressure magnitudes at the respective ports as displayed in e.g., FIG. **1** with an additional or optional mechanically operated sub-unit '314' within trailer control module **300b**. As can be noted, in case of failure in electrical or electronic connection systems, which can happen in the electric connection ports at CW of trailer control module **300a** or **300b**, a mechanically operated sub-unit to selectively open predominance volume or to bring the pressure characteristics at ports **P22** and **P42** within desired range can still be achieved pneumatically. Furthermore, this mechanically operated sub-unit **314**, and its threshold pressure to selectively open an additional volume (AV) or a predominance volume for pressure normalization at ports **P22** and **P42**, can be calibrated to the overall brake system requirement before delivery to vehicle manufacturers.

(50) If necessary, the entire mechanically operated sub-unit **314** within trailer brake control module **300b** can be disabled for purely electronic controlling to achieve the necessary pressure characteristics at ports **P22** and **P42**, and vice-versa.

(51) FIG. **4a** shows an external view of a trailer control valve or trailer brake control module **300a**

or **300b** in accordance with an embodiment of the present disclosure. As shown in FIG. **4a**, trailer brake control module **300a** or **300b** consists of the following ports: the primary control port (**P42**), a parking brake control port (**P43**), the pressure supply port (**P11**), the trailer control pressure port (**P22**), a trailer supply pressure port (**P21**), and a pressure relief port (**P3**) at housing **406** of trailer brake module **300a** or **300b**.

(52) The external view illustrates the spatial arrangement of ports **P11**, **P21**, **P22**, **P42**, **P43**, and **P3** in accordance with an exemplary embodiment. 'W' in FIG. **4a** shows the electronic connection point where wirings and other related components are enclosed. Furthermore, solenoid valves **304** and **306** of FIGS. **3a** and **3b** are connected to the wirings provided within the section labeled as "W" in trailer brake control module **300a** or **300b** as shown in FIG. **4a**.

(53) Furthermore, the cross-sectional view displayed in FIG. **4b** is from the plane A-A' whereas the cross-sectional view in FIG. **4c** is from the plane B-B'.

(54) FIG. **4b** shows a cross-sectional view of a trailer control valve **300b** in accordance with an embodiment of the present disclosure.

(55) In accordance with the present embodiment or in conjunction with the embodiment associated with FIG. **3b**, trailer brake control module **300b** further comprises a first pneumatic control chamber **402**, to which primary control port **P42** or pneumatic control pressure line **308.1** is connected. As the pressurized air enters from port **P42** or from pneumatic control pressure line **308.1** into chamber **402**, a first piston **404** moves linearly down along axis Y-Y' as shown in FIG. **4b**. The downward direction in relation to axis Y-Y' is shown as CD' in FIG. **4b**.

(56) After the downward movement of piston **404** due to pressurization of pneumatic control chamber **402** to in FIG. **4b**, an extension **404.1** impinges on a top surface of a relay piston **414**. Relay piston **414** is configured to move in a fluid tight manner along axis Y-Y' within a housing **406** and is supported by relay spring **416**. As relay piston **414** moves downwards, valve seat **310.1** of relay valve **310** is dislodged, thereby enabling a pressure connection between chamber marked as **P11** and port **P22**. The direction of flow of air in case activating relay valve **310** is shown via arrow marks 'F' in FIG. **4b**.

(57) With regards to a predominance volume or additional volume (denoted as "AV" in FIG. **4b**) within trailer brake control module **300b**, as can be seen, it is provided coaxially with respect to relay valve **310** along axis Y-Y', but at the same time vertically above relay valve **310**. Said predominance volume or additional volume AV is part of mechanically operated sub-unit **314** or predominance valve (PRV). For the sake of illustration, the functioning of mechanically operated sub-unit (**314**) is explained herewith.

(58) On activating relay valve **310** by relay piston **414**, the pressurized air enters chamber associated with **P22** from **P11** via the direction of flow shown as 'F'. The pressurized air enters predominance volume chamber **408**. The connection between **P22** and chamber **408** is not shown in the cross-section displayed in the present figure. In any case, as the pressurized air enters chamber **408** of the mechanically operated sub-unit **314** (or the predominance valve PRV), or at least a part of mechanically operated sub-unit **314**, a predominance valve piston **408.1** moves in downward direction along axis Y-Y'. After certain amount downward movement of piston **408.1**, a plate valve **410** positioned concentrically with piston **408.1** hits an adjustment screw **412**. On still further downward movement, adjustment screw **412** displaces or lifts plate valve **410** against a spring **408.2** located within chamber **408**. It is noted that plate valve **410** is not exactly circular in shape. The shape of plate valve **410** is only good enough to close a central bore **412.1** of adjustment screw **412**. However, plate valve **410** is not in interference fit or flush with an inner diameter "D1" of piston **408.1** and there exists a gap between a lateral outer surface and inner diameter D1 of piston **408.1**. Thus, on dislodging or lifting plate valve **410** by adjustment screw **412** on piston **408.1**'s downward movement, the pressurized air from chamber **408** enters the additional volume or predominance volume AV. This volume is responsible for commensurate pressure reduction at port **P22** and causes the change in pressure characteristics as shown in region **102** of FIG. **1**. As already

explained above, the change in the pressure characteristics between ports P42 and P22 causes proportional change in the braking rate of the trailer or the towed vehicle for which the brake needs to be applied using trailer brake control module **300b**. By this way, mechanically operated sub-unit (**314**) maintains the difference of the braking rate between the towing vehicle and the trailer within a permissible threshold range.

(59) It follows from the above, in accordance with an embodiment of the present disclosure, mechanically operated sub-unit **314** is operated such that an initial pressure increase at trailer control pressure port P22 (shown at region **102** of FIG. **1**) is accommodated by providing an additional volume AV within the trailer brake control module **300b**. Moreover, it is reiterated that additional volume AV of predominance valve PRV is coaxially arranged, but vertically above relay valve **310** within trailer brake control module **300b**. The wording “vertically above” can be understood in the present context with the help of disclosure in FIG. **4b** along with arrow mark “U” denoting upward direction or what it means to be above in relation to relay valve **310**. One exemplary technical advantage here is that, trailer brake control module **300b** provides predominance valve PRV in addition to or alternative to the electronically controlled sub-unit of trailer brake control module **300a** to enable maintaining the braking rate difference between the trailer and the towing vehicle. Thus, predominance valve PRV of trailer brake control module **300b** is configured to operate independently from the electronically controlled sub-unit of trailer brake control module **300a** while at the same time not disabling or disturbing the capability of the electronically controlled sub-unit to perform e.g., coupling force control (CFC) i.e., to keep the braking rate difference between the trailer and the towing vehicle within a threshold range.

(60) Furthermore, in trailer brake control module **300b** of the present embodiment, first control piston **404** separates first pneumatic control chamber **402** and additional volume (AV i.e., part of predominance valve PRV), and moreover first control piston **404** integrally comprises a fluid flow path **404.2** indirectly connecting trailer control pressure port P22 and additional volume (AV) through the above-explained mechanism.

(61) FIG. **4c** shows a cross-sectional view of trailer control valve or trailer brake control module **300a** or **300b** in accordance with an embodiment of the present disclosure.

(62) The cross-sectional view of trailer brake control module **300a** or **300b** displays the section of module as cut at plane B-B' of FIG. **4a**.

(63) The primary purpose of FIG. **4c** is to show the spatial arrangement of ports P42, P11 and P21 along with the flow path ‘F’ of the pressurized fluid from port p11 towards P21. Furthermore, the structure and working of metering valve **302** as shown and explained also in conjunction with FIGS. **3a** and **3b** is explained with the assistance of cross-sectional view of valve **302**.

(64) As also shown in FIGS. **3a** and **3b**, valve **302** lies in the direct fluid path between ports P11 and P21. Valve **302** includes a linear piston **422** that can linearly reciprocate within a cylindrical chamber **426**. Piston **422** is held a predetermined position using spring **302.3**. Piston **422** is configured to operate in two positions as also explained before i.e., first and second positions. In the first position, metering valve **302** connects pressure supply port P11 and trailer supply pressure port P21 through a throttled flow orifice **428**, and wherein in the second position, metering valve **302** connects pressure supply port P11 and trailer supply pressure port P21 in an invariable and open manner such that the whole of the pneumatic pressure received through pressure supply port P11 is transmitted to trailer supply pressure port P21. In FIG. **4c**, the displayed position is in the second position as shown in FIGS. **3a** and **3b** as well. The pressurized fluid or air from P11 is directly sent without any metering to P21.

(65) However, when a control pressure via output port **308.2** (not shown in FIG. **4c**, but refer to FIGS. **3a** and **3b**) enters a metering chamber **424** present above piston **422**, the downward movement of piston **422** brings the first position of valve **302** and causes narrowing down of orifice **428**. Hence, a reduced amount of pressurized air is sent to port P21 from port P11 in the first position as compared to the second position of valve **302**.

(66) Furthermore, a silencer **420** is provided at bottom portion of housing **406** that is configured to reduce the noise generated during the operation of trailer brake control module **300a** or **300b**. Silencer **420** is positioned at pressure relief port **P3** of trailer brake control module **300a** or **300b**.

(67) FIG. 5 shows a cross-sectional view of a trailer brake control module **300c** in accordance with another embodiment of the present disclosure.

(68) In particular, FIG. 5 shows an arrangement of predominance valve PRV or mechanically operated sub-unit **314**, which is positioned perpendicular to axis Y-Y' of trailer brake control module **300c**. Furthermore, it is also realizable that predominance valve PRV is located vertically above a relay valve **516** of trailer brake module **300c**. In order to show what is meant by “vertically above”—an arrow mark with reference “U” is shown in FIG. 5. The general function of trailer brake control module **300b** is explained herewith. First pneumatic control chamber **402** receives control pressure from port **P42** (not shown in FIG. 5, but can be found in schematic representation of FIG. 3a). This control pressure in first pneumatic control chamber **402** pushes a first relay piston **514** in downwards direction “D”. First relay piston **514** as shown in FIG. 5, includes a stopper **520** inserted in a groove **522**. Due to this downward movement of first relay piston **514**, a second relay piston **524**, which is functionally coupled to first relay piston **514** via stopper **520** also moves in the downward direction “D”.

(69) Furthermore, second relay piston **524** includes an axial extension **526** which impinges on a top surface **526** of a valve seat **530** to move said valve seat **530** in downwards direction against a resisting force of a spring **530** within relay valve **516**, thereby removing a closed contact at a contact zone **528** between valve seat **530** and a lateral extension **532** of a supply pressure receiving chamber **518**. Due to this downward movement of valve seat **530**, supply pressure receiving chamber **518**, connected to port **P11** (not shown in FIG. 5, but refer to the schematic illustration in FIG. 3a or 3b), now establishes a fluid connection with a control port pressure chamber **V22**. As shown in FIG. 5, control port pressure chamber **V22** is connected to port **P22** on one side shown purely for illustrative reasons and is connected to predominance valve PRV on the other side.

(70) The pressurized air received at chamber **V22** reaches an inlet **534** of predominance valve PRV, which is normally closed by a valve cap **510**. If the pressure of the air reaching inlet **534** is higher than a threshold pressure that can overcome the resisting force of a spring **512** of predominance valve PRV, valve cap **510** is lifted and a fluid connection is established between chamber **V22** and additional volume “AV” as shown in FIG. 5 with arrow mark “F”— a symbolic representation of fluid flow direction. In particular “F” in FIG. 5 shows how the pressurized air starting from supply pressure receiving chamber **518** to **V22** to inlet **534** to additional volume AV while at the same time reaching trailer control pressure port **P22**.

(71) Apart from the other details, valve **300c** includes all the elements displayed in valve **300a** in FIG. 3a and complies with the schematic layout displayed in FIG. 3b.

(72) FIG. 6 schematically shows a commercial vehicle **600**, or an autonomous vehicle **600** equipped with a trailer control valve or trailer brake control module **300a** or **300b** or **300c** in accordance with an embodiment of the present disclosure.

(73) More particularly, vehicle **600** includes a pneumatic brake system **606**, which in turn comprises trailer brake control module **300a** or **300b** or **300c** of any one of the above-mentioned embodiments, and an electronic control unit **608** connected to trailer brake control module **300a** or **300b** or **300c** to perform brake functions with or without driver brake demand.

(74) In accordance with an embodiment, the electronic control unit **608** controls the electronically operated sub-unit (W, **304**, **306**) of trailer brake control module **300a** such that braking rate (z) rebalancing unit achieves the maintenance of the difference of the braking rate between towing vehicle **602** and towed vehicle **604** within said permissible threshold range. This is achieved by obtaining the requisite pressure characteristics as illustrated above at ports **P22** and **P42** e.g., by electronically implemented operating technique through first and second solenoid valves **304** and **306**.

LIST OF REFERENCE SIGNS (PART OF THE DESCRIPTION)

(75) **101**—a second region representing a proportional progression of the magnitude of pressure at port **P22** in relation to port **P42** **102**—a region or an area representing a minor delay in the beginning of recording any pressure at port “**P22**” when the pressure recorded at primary control port “**P42**” is already at approximately 0.5 bar **200**—conventional trailer control valve **202**—relay valve of conventional trailer control valve **200** **204**—pneumatically controlled metering valve PRV—a predominance valve, CPRV—conventional predominance valve **P3**—pressure relief port **P11**—supply pressure inlet **P12**—trailer supply pressure outlet **P22**—trailer control pressure outlet **P41**—primary brake signal port **P42**—primary control port **P43**—parking brake control port **300a**—trailer brake control module of one embodiment **300b**—trailer brake control module of another embodiment **300c**—trailer brake control module of a yet another embodiment **302**—pneumatically controlled metering valve **302.1**—outlet port of pneumatically controlled metering valve **302** **302.2**—inlet port of pneumatically controlled metering valve **302** **302.3**—spring of pneumatically controlled metering valve **302** **304**—first electronically controlled solenoid valve **304.1**—inlet of first electronically controlled solenoid valve **304.2**—outlet of first electronically controlled solenoid valve **306**—second electronically controlled solenoid valve **306.1**—inlet of second electronically controlled solenoid valve **306.2**—outlet of second electronically controlled solenoid valve **F1**—first filter **F2**—second filter **308**—double check valve **308.1**—first connection of double check valve **308** **308.2**—output port of double check valve **308** **308.3**—second pneumatic control pressure line **310**—relay valve **310.1**—outlet of relay valve **310** **312.1**—first coupling head **312.2**—second coupling head **314**—mechanically operated sub-unit **W**—part of electronically operated sub-unit mainly representing electronic connection pins **X**—pressure sensor, in particular PWM-based pressure sensor **402**—first pneumatic control chamber **404**—first control piston **404.1**—extension of first control piston **404.2**—fluid flow path laid out within first control piston **404** **406**—housing **408**—predominance volume chamber **408.1**—predominance valve piston **408.2**—spring within predominance volume chamber **408** **AV**—additional volume **410**—plate valve **412**—adjustment screw **412.1**—central bore of adjustment screw **412** **414**—relay piston **416**—relay spring **420**—silencer **422**—linear piston of valve **302** **424**—metering chamber **426**—cylindrical chamber **428**—flow orifice **600**—commercial or autonomous vehicle **602**—towing vehicle **604**—towed vehicle **606**—pneumatic brake system **608**—electronic control unit or ECU **V22**—a chamber within TCV connected to port **P22** **510**—valve cap of predominance valve PRV **512**—spring of predominance valve PRV **514**—first relay piston of trailer brake control module **300c** **516**—relay valve of trailer brake control module **300c** **518**—supply pressure receiving chamber of trailer brake control module **300c** **520**—stopper coupled to first relay piston **514** **522**—groove to receive stopper **520** at first relay piston **514** **524**—second relay piston **526**—axial extension **528**—a contact zone **528** showing between valve seat **530** and lateral extension **532** **530**—valve seat **532**—lateral extension

Claims

1. A trailer brake control module (**300a**; **300b**; **300c**) for a towing vehicle (**502**) facilitating braking of a towed vehicle or trailer (**504**), comprising: a pressure supply port (**P11**); a trailer control pressure port (**P22**); a primary control port (**P42**) for receiving either directly or indirectly a control brake pressure for operating the trailer brake control module (**300a**; **300b**; **300c**), wherein the primary control port (**P42**) receives the control brake pressure from a pneumatically operated supply of pressure medium; a pneumatic control pressure line (**308.1**) providing alternative control brake pressure for operating the trailer brake control module (**300a**; **300b**; **300c**), wherein the pneumatic control pressure line (**308.1**) receives the alternative control brake pressure from an electronically operated supply of pressure medium; and a relay valve (**310**; **516**) that is activated using either: the control brake pressure received at the primary control port (**P42**), or the alternative

control brake pressure from the pneumatic control pressure line (308.1), wherein on activating the relay valve (310), the pneumatic pressure received at the pressure supply port (P11) is connected to the trailer control pressure port (P22), wherein the trailer brake control module (300a; 300b; 300c) is additionally provided with a braking rate rebalancing unit that maintains the difference of the braking rate between said towing vehicle and said trailer within a permissible threshold range; wherein the trailer brake control module (300a; 300b; 300c) further comprises a double check or select-high valve (308) for supplying one of the control brake pressure and the alternative control brake pressure depending on the magnitude of each of the brake pressures, wherein the brake pressure which has the higher magnitude is supplied to the relay valve (310).

2. The trailer brake control module (300a; 300b; 300c) of claim 1, wherein the trailer brake control module (300a; 300b; 300c) includes the following ports, which are the only ports provided at a housing of the trailer brake control module: the primary control port (P42), a parking brake control port (P43), the pressure supply port (P11), the trailer control pressure port (P22), a trailer supply pressure port (P21), and a pressure relief port (P3).

3. The trailer brake control module (300a; 300b; 300c) of claim 1, wherein the trailer brake control module (300a; 300b; 300c) further comprises a pneumatically controlled metering valve (302) connecting the pressure supply port (P11) and a trailer supply pressure port (P21), wherein said metering valve (302) operates in first and second positions, wherein in the first position, the metering valve (302) connects the pressure supply port (P11) and the trailer supply pressure port (P21) through a throttled flow orifice, and wherein in the second position, the metering valve (302) connects the pressure supply port (P11) and the trailer supply pressure port (P21) in an invariable and open manner such that the whole of the pneumatic pressure received at the pressure supply port (P11) is transmitted to the trailer supply pressure port (P21).

4. The trailer brake control module (300a; 300b; 300c) of claim 3, wherein the pneumatically controlled metering valve (302) is held in the second position by at least partly pre-existing pressure in the trailer supply pressure port (P21) and a spring (302.3).

5. The trailer brake control module (300a; 300b; 300c) of claim 1, further comprising a first electronically controlled solenoid valve (304) having an inlet (304.1) that is connected to the pressure supply port (P11) and an outlet (304.2) that is selectively connected to the relay valve (310), wherein said outlet (304.2) supplies the alternative control brake pressure.

6. The trailer brake control module (300a; 300b; 300c) of claim 5, wherein the outlet (304.2) carrying the alternative control brake pressure is connected to a first inlet (308.1) of the double check or select-high valve (308), wherein the double check or select-high valve (308) enables the selective connection of the outlet (304.2) with the relay valve (310), when the pressure supplied at the outlet (304.2) is of higher magnitude than the pressure at the primary control port (P42).

7. The trailer brake control module (300a; 300b; 300c) of claim 1, wherein the magnitude of the pressure received at the primary control port (P42) is proportional to the driver's brake demand.

8. The trailer brake control module (300a; 300b; 300c) of claim 1, wherein the trailer brake control module is installed in a pneumatic brake system (606) having an electronic control unit (608) connected to the trailer brake control module (300a; 300b; 300c) to perform brake functions with or without driver brake demand.

9. The trailer brake control module (300a; 300b; 300c) of claim 8, wherein the electronic control unit (608) controls the trailer brake control module (300a; 300b; 300c) such that the braking rate rebalancing unit achieves the maintenance of the difference of the braking rate between said towing vehicle (602) and said towed vehicle (604) within said permissible threshold range.

10. The trailer brake control module (300a; 300b; 300c) of claim 9, wherein the trailer brake control module and pneumatic brake system (606) are installed in a commercial vehicle or an autonomous vehicle (600).

11. A trailer brake control module (300a; 300b; 300c) for a towing vehicle (502) facilitating braking of a towed vehicle or trailer (504), comprising: a pressure supply port (P11); a trailer

control pressure port (P22); a primary control port (P42) for receiving either directly or indirectly a control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the primary control port (P42) receives the control brake pressure from a pneumatically operated supply of pressure medium; a pneumatic control pressure line (308.1) providing alternative control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the pneumatic control pressure line (308.1) receives the alternative control brake pressure from an electronically operated supply of pressure medium; and a relay valve (310; 516) that is activated using either: the control brake pressure received at the primary control port (P42), or the alternative control brake pressure from the pneumatic control pressure line (308.1), wherein on activating the relay valve (310), the pneumatic pressure received at the pressure supply port (P11) is connected to the trailer control pressure port (P22), wherein the trailer brake control module (300a; 300b; 300c) is additionally provided with a braking rate rebalancing unit that maintains the difference of the braking rate between said towing vehicle and said trailer within a permissible threshold range; wherein the braking rate rebalancing unit includes a mechanically operated sub-unit (314 or PRV) that is either coaxially positioned in relation to a central axis (Y-Y') of the trailer brake control module (300a; 300b; 300c) or is positioned perpendicular to said central axis (Y-Y'), wherein said mechanically operated sub-unit (314 or PRV) is at least vertically above the relay valve (310; 516).

12. The trailer brake control module (300a; 300b; 300c) of claim 11, wherein the mechanically operated sub-unit (PRV) is operated such that an initial pressure increase at trailer control pressure port (P22) is accommodated by an additional volume (AV) within the trailer brake control module (300b), wherein the additional volume (AV) is coaxially arranged with and vertically above the relay valve (310) within the trailer brake control module (300b).

13. The trailer brake control module (300a; 300b; 300c) of claim 11, wherein the mechanically operated sub-unit (PRV) operates independently from an electronically controlled sub-unit without disabling the electronically controlled sub-unit.

14. The trailer brake control module (300a; 300b; 300c) of claim 11, wherein the mechanically operated sub-unit is perpendicular to the axis (Y-Y'), wherein the relay valve includes a first relay piston (514) that shifts downward in response to control pressure received in a first pneumatic control chamber from primary control port (P42), wherein the first relay piston is functionally coupled to a second relay piston (524), wherein the second relay piston moves a valve seat (530) and connects a supply pressure receiving chamber (518), connected to the pressure supply port (P11), to a control port pressure chamber (V22) and the trailer control pressure port (P22).

15. The trailer brake control module (300a; 300b; 300c) of claim 11, wherein the mechanically operated sub-unit (PRV) is in addition to an electronically operated sub-unit (W, 304, 306) comprising first and second solenoid valves (304, 306) operable to selectively connect the pressure supply port (P11) to the pneumatic control pressure line (308.1).

16. The trailer brake control module (300a; 300b; 300c) of claim 11, wherein the mechanically operated sub-unit (PRV) is a predominance valve.

17. A trailer brake control module (300a; 300b; 300c) for a towing vehicle (502) facilitating braking of a towed vehicle or trailer (504), comprising: a pressure supply port (P11); a trailer control pressure port (P22); a primary control port (P42) for receiving either directly or indirectly a control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the primary control port (P42) receives the control brake pressure from a pneumatically operated supply of pressure medium; a pneumatic control pressure line (308.1) providing alternative control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the pneumatic control pressure line (308.1) receives the alternative control brake pressure from an electronically operated supply of pressure medium; and a relay valve (310; 516) that is activated using either: the control brake pressure received at the primary control port (P42), or the alternative control brake pressure from the pneumatic control pressure line (308.1), wherein on activating the relay valve (310), the pneumatic pressure received at the pressure supply port (P11) is connected to

the trailer control pressure port (P22), wherein the trailer brake control module (300a; 300b; 300c) is additionally provided with a braking rate rebalancing unit that maintains the difference of the braking rate between said towing vehicle and said trailer within a permissible threshold range; wherein the pressure at the trailer brake control port (P22) is measured using a Pulse Width Modulation (PWM) based pressure sensor.

18. The trailer brake control module (300a; 300b; 300c) of claim 17, wherein the trailer brake control module (300a; 300b; 300c) further comprises a double check or select-high valve (308) for supplying one of the control brake pressure and the alternative control brake pressure depending on the magnitude of each of the brake pressures, wherein the brake pressure which has the higher magnitude is supplied to the relay valve (310).

19. A trailer brake control module (300a; 300b; 300c) for a towing vehicle (502) facilitating braking of a towed vehicle or trailer (504), comprising: a pressure supply port (P11); a trailer control pressure port (P22); a primary control port (P42) for receiving either directly or indirectly a control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the primary control port (P42) receives the control brake pressure from a pneumatically operated supply of pressure medium; a pneumatic control pressure line (308.1) providing alternative control brake pressure for operating the trailer brake control module (300a; 300b; 300c), wherein the pneumatic control pressure line (308.1) receives the alternative control brake pressure from an electronically operated supply of pressure medium; and a relay valve (310; 516) that is activated using either: the control brake pressure received at the primary control port (P42), or the alternative control brake pressure from the pneumatic control pressure line (308.1), wherein on activating the relay valve (310), the pneumatic pressure received at the pressure supply port (P11) is connected to the trailer control pressure port (P22), wherein the trailer brake control module (300a; 300b; 300c) is additionally provided with a braking rate rebalancing unit that maintains the difference of the braking rate between said towing vehicle and said trailer within a permissible threshold range; wherein trailer brake control module (300a; 300b; 300c) further comprises a first pneumatic control chamber (402) to which the primary control port (P42) is connected.

20. The trailer brake control module (300b; 300c) of claim 19, wherein the trailer brake control module (300b; 300c) further comprises a first control piston (404) separating the first pneumatic control chamber (402) and an additional volume (AV), and wherein the first control piston (404) integrally comprises a fluid flow path (404.2) indirectly connecting the trailer control pressure port (P22) and the additional volume (AV).
