

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411384
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yang; Shu-Han et al.

Electronic device

Abstract

The electronic device includes a first substrate, a second substrate, a first support member, a planarization layer, and an alignment layer. The second substrate is opposite to the first substrate. The first support member is disposed in the peripheral region and located between the first substrate and the second substrate. The planarization layer is disposed on the first substrate and has a first portion and an opening. The first portion is disposed between the opening, and the first support member and the first portion are overlapped in a normal direction of the first substrate. The alignment layer is disposed on the planarization layer. The alignment layer on the first portion has a first thickness. The alignment layer in the opening has a second thickness. The first thickness is greater than or equal to zero and less than the second thickness.

Inventors: Yang; Shu-Han (Miaoli County, TW), Huang; Hui-Min (Miaoli County, TW), Yeh; Chia-Min (Miaoli County, TW)

Applicant: Innolux Corporation (Miaoli County, TW)

Family ID: 72943928

Assignee: Innolux Corporation (Miaoli County, TW)

Appl. No.: 18/474221

Filed: September 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240012294 A1	Jan. 11, 2024

Foreign Application Priority Data

CN	201911013323.3	Oct. 23, 2019
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17727840 20220425 US 11803085 child-doc US 18474221
continuation parent-doc US 17033693 20200926 US 11347113 20220531 child-doc US 17727840

Publication Classification

Int. Cl.: G02F1/1339 (20060101); G02F1/1333 (20060101); G02F1/1341 (20060101)

U.S. Cl.:

CPC G02F1/13394 (20130101); G02F1/133345 (20130101); G02F1/1341 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0064697	12/2019	Ra	N/A	G02F 1/136286
2021/0018775	12/2020	Shin	N/A	G02F 1/1339

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106033163	12/2015	CN	N/A
201617707	12/2015	TW	N/A
2019198376	12/2018	WO	N/A

OTHER PUBLICATIONS

“Office Action of China Counterpart Application”, issued on Jan. 20, 2024, p. 1-p. 9. cited by applicant

Primary Examiner: Kim; Richard H

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This is a continuation application of and claims the priority benefit of a prior application Ser. No. 17/727,840, filed on Apr. 25, 2022. The prior application Ser. No. 17/727,840 is a continuation application of and claims the priority benefit of a prior application Ser. No. 17/033,693, filed on Sep. 26, 2020, which claims the priority benefit of China application serial no. 201911013323.3, filed on Oct. 23, 2019. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(1) The disclosure relates to an electronic device, and particularly relates to an electronic device with openings disposed in a peripheral region.

Description of Related Art

(2) Electronic products have become indispensable necessities in modern society. Along with rapid development of the electronic products, consumers have high expectations for qualities, functions or prices of the products.

(3) Therefore, the electronic products need to be improved, such as improving reliability of electronic devices, but there are still some problems to be solved.

SUMMARY

(4) The disclosure is directed to an electronic device having better reliability or display quality.

(5) According to an embodiment of the disclosure, the electronic device has a peripheral region, and includes a first substrate, a second substrate, a first support member, a planarization layer, and an alignment layer. The second substrate is opposite to the first substrate. The first support member is disposed in the peripheral region and located between the first substrate and the second substrate. The planarization layer is disposed on the first substrate and has a first portion and an opening. The first portion is disposed between the opening, and the first support member and the first portion are overlapped in a normal direction of the first substrate. The alignment layer is disposed on the planarization layer. The alignment layer on the first portion has a first thickness. The alignment layer in the opening has a second thickness. The first thickness is greater than or equal to zero and less than the second thickness.

(6) Based on the above description, based on the planarization layer having the openings and configuration of the first portions between the openings, structural reliability, reliability, performance or display quality of the electronic device may be improved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1 is a schematic top view of an electronic device according to an embodiment of the disclosure.

(3) FIG. 2 is a schematic cross-sectional view of the electronic device of FIG. 1 viewing along a section line A-A' and a section line B-B'.

(4) FIG. 3 is a schematic top view of an electronic device according to another embodiment of the disclosure.

(5) FIG. 4 is a schematic cross-sectional view of the electronic device of FIG. 3 viewing along a section line A-A' and a section line C-C'.

DESCRIPTION OF THE EMBODIMENTS

(6) The disclosure may be understood with reference to the following detailed description and the accompanying drawings. It should be noted that, for ease of understanding by readers and concise drawings, a plurality of accompanying drawings in the disclosure merely show a part of an electronic device or a display device, and specific elements in the accompanying drawings are not drawn to scale. In addition, the quantity and size of the elements in the drawings are merely exemplary, and are not intended to limit the scope of the disclosure. For example, relative sizes, thicknesses, and positions of films, regions, and/or structures may be reduced or enlarged for

clarity.

(7) The term “approximately”, “equal to”, “the same as”, “substantially” or “roughly” referred to herein generally represents falling within 10% of a given value or a range, or represents falling within 5%, 3%, 2%, 1%, or 0.5% of a given value or a range. In addition, phrases “a given range is a first value to a second value” and “a given range falls within a range of a first value to a second value” mean that the given range includes the first value, the second value, and other values between the first value and the second value.

(8) In the disclosure, a situation that one structure (or a layer, a component, a substrate) is located on another structure (a layer, a component, a substrate) may refer to that the two structures are located adjacent to each other and in direct connection, or refer to that the two structures are adjacent to each other but in indirect connection, and the indirect connection refers to that there is at least one intermediate structure (or an intermediate layer, an intermediate component, an intermediate substrate, an intermediate interval) between the two structures, where a lower surface of one structure is adjacent to or directly connected to an upper surface of the intermediate structure, and an upper surface of the other structure is adjacent to or directly connected to a lower surface of the intermediate structure, and the intermediate structure may be composed of a single-layer or multi-layer physical structure or non-physical structure, which is not limited by the disclosure. In the disclosure, when a structure is placed “on” another structure, it may mean that the structure is “directly” on the other structure, or that the structure is “indirectly” on the other structure, i.e., there is at least one structure clamped between the structure and the other structure.

(9) The electrical connections or couplings mentioned in the disclosure may all refer to direct connections or indirect connections, and in the case of the direct connection, terminals of two circuit components are directly connected or connected through a conductive line, and in the case of the indirect connection, a switch, a diode, a capacitor, an inductor, a resistor or other proper components or a combination of the above components may be configured between the terminals of the two circuit components, but the disclosure is not limited thereto.

(10) In the following embodiments, same or similar reference numerals are used to indicate same or similar elements, and details may be omitted in the description. In addition, the features in the embodiments may be used in any combination without departing from the spirit of the invention or conflicting with each other, and simple equivalent changes and modifications made to the specification or the claims shall still fall within the scope of the disclosure. Besides, the terms “first”, “second” and the like mentioned in the specification or the claims are used only to name discrete elements or to distinguish different embodiments or ranges, but are not intended to define the upper or lower limit of the number of elements or the manufacturing or arrangement order of the elements.

(11) In the disclosure, a scanning electron microscope (SEM), a thin-film thickness profile measuring instrument (α -step), an elliptical thickness gauge or other suitable methods may be used to measure a thickness of each layer. In detail, in some embodiments, the SEM may be used to obtain a cross-sectional image of a structure, and measure a thickness of each layer in the image. The above thickness may be the maximum thickness in a normal direction in any cross-sectional image, in other words, the thickness may be the maximum thickness in a local area of the electronic device. Moreover, a method of using the SEM to perform thickness measurement includes using the SEM to measure thickness after disassembling and splitting the electronic device to obtain a single substrate. In the present disclosure, the thickness may be measured by using an optical microscope (OM), a SEM, or other suitable methods.

(12) A display device of the disclosure may be applied to various electronic devices. The electronic device may include a display device, an antenna device, a sensing device, or a splicing device, but the disclosure is not limited thereto. The electronic device may be a bendable or flexible electronic device. The electronic device may include, for example, liquid crystal or light-emitting diodes; the light-emitting diodes may include, for example, organic light-emitting diodes (OLEDs), mini

LEDs, micro LEDs or quantum dot (QD) LEDs (for example, QLED, QDLED), fluorescence, phosphor, or other suitable materials and the materials may be arbitrarily arranged and combined, but the disclosure is not limited thereto. The antenna device may be, for example, a liquid crystal antenna, but the disclosure is not limited thereto. The splicing device may be, for example, a display splicing device or an antenna splicing device, but the disclosure is not limited thereto. It should be noted that the electronic device may be any arrangement and combination of the above, but the disclosure is not limited thereto. Hereinafter, the display device will be used as the electronic device or the splicing device to explain the content of the disclosure, but the disclosure is not limited thereto.

(13) In the disclosure, the various embodiments described below may be mixed and matched without departing from the spirit and scope of the disclosure. For example, some features of one embodiment may be combined with some features of another embodiment to become another embodiment.

(14) Reference will now be made in detail to the exemplary embodiments of the disclosure, examples of which are illustrated in the drawings. Wherever possible, the same component symbols are used in the drawings and description to denote the same or similar parts.

(15) FIG. 1 is a schematic top view of an electronic device according to an embodiment of the disclosure. For the sake of clarity and convenience in the drawing, several components are omitted in FIG. 1. FIG. 2 is a schematic cross-sectional view of the electronic device of FIG. 1 viewing along a section line A-A' and a section line B-B'. For the sake of clarity and convenience in the drawing, several components are omitted in FIG. 2. Referring to FIG. 1 and FIG. 2, the electronic device 10 includes a first substrate 100, a second substrate 200, a support member (including a first support member PS1), a planarization layer 130, and an alignment layer 150. In the embodiment, the second substrate 200 is disposed opposite to the first substrate 100, and the first support PS1 is disposed between the first substrate 100 and the second substrate 200. The planarization layer 130 is disposed on the first substrate 100 and has a first portion 131 and an opening 133. The first portion 131 of the planarization layer 130 is located between the opening 133 in a normal direction N, and the first support member PS1 and the first portion 131 are overlapped in the normal direction N of the first substrate 100. The alignment layer 150 is disposed on the planarization layer 130. In the embodiment, the electronic device 10 may include a plurality of conductive layers (including a first conductive layer M1 and a second conductive layer M2 (indicated in FIG. 4)), an insulating layer 140, a package element 160, a light-shielding layer BM, an overcoat layer 220 (OC) or display medium layer DM (indicated in FIG. 4). The insulating layer 140 is disposed on the planarization layer 130. The package element 160 is disposed on the insulating layer 140 to surround the support members. The light-shielding layer BM is disposed on the second substrate 200, and the overcoat layer 220 is disposed on the light-shielding layer BM, so that the light-shielding layer BM is located between the overcoat layer 220 and the second substrate 200. The first support member PS1 may be disposed on the overcoat layer 220. In addition, the light-shielding layer BM is disposed between the second substrate 200 and the first support member PS1. In the embodiment, the opening 133 of the planarization layer 130 may form an accommodating space, so that an area of the planarization layer 130 contacting the package element 160 is increased. In addition, the alignment layer 150 may be formed in the accommodating space of the opening 133 to increase a contact area of the alignment layer 150 and the planarization layer 130. In this way, adhesion between the package element 160 and the planarization layer 130 and/or the alignment layer 150 and the planarization layer 130 may be enhanced to increase the reliability of the electronic device 10. Moreover, the accommodating space formed by the opening 133 may buffer a lateral stress of the insulating layer 140 pressed and/or pushed by the support member, so that a risk that the insulating layer 140 is crushed by the support member is reduced, and a situation that moisture passes through the cracked insulating layer 140 to influence the planarization layer 130 or the conductive layer is mitigated, so as to

improve the reliability and/or performance of the electronic device **10**.

(16) In the embodiment, the electronic device **10** includes the first substrate **100**, the second substrate **200** disposed opposite to the first substrate **100**, and a plurality of the support members disposed between the first substrate **100** and the second substrate **200**. The first substrate **100** or the second substrate **200** may be a transparent substrate, such as a transparent plastic substrate or a glass substrate. For example, a material of the first substrate **100** or the second substrate **200** may include glass, quartz, sapphire, ceramic, polycarbonate (PC), polyimide (PI), polyethylene terephthalate (PET), glass fiber, ceramic, other suitable substrate materials, or a combination of the above materials, but the embodiment is not limited thereto. A material of the support member includes a photoresist material or other suitable materials. The material of the support member may also include an inorganic material, an organic material, other suitable materials, or a combination of the above materials, but the embodiment is not limited thereto. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials. The above-mentioned organic material is, for example (but not limited to): a polymer material such as polyimide resin, epoxy resin, or acrylic resin, etc.

(17) As shown in FIG. 1 and FIG. 2, the electronic device **10** of the embodiment includes a peripheral region **12**. The peripheral region **12** may be defined as a region disposed at an edge of the electronic device **10** and surrounding a working region (shown in FIG. 3 and FIG. 4), but the embodiment is not limited thereto. In the embodiment, the support members include a plurality of first support members PS1 disposed on the first substrate **100** and/or the second substrate **200**, and the first support members PS1 are disposed in the peripheral region **12**, but the embodiment is not limited thereto. In some embodiments, the support members may also be disposed in the working region. In the embodiment, the support members may be arranged in the peripheral region **12** in an array or other suitable manner, but the embodiment is not limited thereto.

(18) In the embodiment, the first conductive layer M1 may be disposed on the first substrate **100**, and forms a plurality of traces, a plurality of electrodes, or a plurality of pads through a patterning process. For example, as shown in FIG. 1 and FIG. 2, on the first substrate **100**, the first conductive layer M1 may at least form scan lines, gate lines (not shown), or gates G in the peripheral region **12**, but the embodiment is not limited thereto. In some embodiments, the first conductive layer M1 may be disposed on the first substrate **100** and may be patterned on any position of the first substrate **100** according to an actual requirement. In the embodiment, a material of the first conductive layer M1 includes a metal material, such as aluminum, molybdenum, copper, nickel, titanium, silver, other suitable metals, an alloy of the above metals, or a combination of the above metals, but the embodiment is not limited thereto. In the embodiment, the patterning process of the first conductive layer M1 includes photolithography, chemical vapor deposition (CVD), physical vapor deposition (PVD), and atomic layer deposition (ALD) or screen printing, but the embodiment is not limited thereto.

(19) A gate insulating layer **110** is disposed on the first substrate **100** and partially overlaps the first conductive layer M1. A material of the gate insulating layer **110** includes an inorganic material, an organic material, other suitable materials, or a combination of the above materials, but the embodiment is not limited thereto. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials. The above-mentioned organic material is, for example (but not limited to): a polymer material such as polyimide resin, epoxy resin, and acrylic resin, etc.

(20) In the embodiment, a plurality of active devices T may be disposed on the first substrate **100**. The active device T includes a gate G, a semiconductor layer CH, a source S, and a drain D. As shown in FIGS. 1 and 2, the semiconductor layer CH is disposed on the gate insulating layer **110**, and the source S and the drain D are electrically connected to the semiconductor layer CH. A dielectric layer **120** is disposed on the gate insulating layer **110** and partially overlaps the

semiconductor layer CH, the source S, and the drain D, but the embodiment is not limited thereto. The active device T includes a thin film transistor (TFT), such as a top gate TFT, a bottom gate TFT, or other suitable TFTs, but the embodiment is not limited thereto. In the embodiment, the gate G belongs to the first conductive layer M1, and the source S and the drain D belong to the second conductive layer M2. A material of the second conductive layer M2 may include molybdenum, aluminum, copper, nickel, titanium, silver, other suitable metals, an alloy of the above metals, or a combination of the above metals, but the embodiment is not limited thereto. The semiconductor layer CH may include amorphous silicon, low-temperature polysilicon (LTPS), or metal oxide, but the embodiment is not limited thereto. In some embodiments, different active devices T may include different materials of the semiconductor layer CH, but the embodiment is not limited thereto.

(21) In the embodiment, the second conductive layer M2 may be disposed on the gate insulating layer 110, and may form a plurality of signal traces or a plurality of pads through a patterning process. The signal traces are, for example, data lines (not shown), common electrode lines (not shown), power lines (not shown), ground wires (not shown) or other suitable lines, but the embodiment is not limited thereto. In the embodiment, a plurality of the active devices T may be electrically connected to the first conductive layer M1 and the second conductive layer M2 in the gate insulating layer 110 and the dielectric layer 120 to be used as an active device array or a gate on array (GOA), but the embodiment is not limited thereto.

(22) The dielectric layer 120 is disposed on the gate insulating layer 110 and partially overlaps the second conductive layer M2. A material of the dielectric layer 120 includes an inorganic material, an organic material, other suitable materials, or a combination of the above materials, but the embodiment is not limited thereto. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials. The above-mentioned organic material is, for example (but not limited to): a polymer material such as polyimide resin, epoxy resin, or acrylic resin, etc.

(23) The planarization layer 130 is disposed on the dielectric layer 120. In the embodiment, the planarization layer 130 is disposed on the dielectric layer 120 over the entire surface, and is partially located in the peripheral region 12 and has a distance (not indicated) from an outer edge of the electronic device 10. Namely, the planarization layer 130 is not aligned with an edge of the first substrate 100. According to another aspect, the planarization layer 130 has a distance from the edge of the first substrate 100. The planarization layer 130 is overlapped with the first conductive layer M1, the second conductive layer M2, and/or a plurality of the active devices T in the normal direction N of the first substrate 100. A material of the planarization layer 130 includes an organic material, but the embodiment is not limited thereto. For example, the material of the planarization layer 130 includes perfluoroalkoxy polymer resin (PFA), polymer film on array (PFA), fluoroelastomers, etc., but the embodiment is not limited thereto. In some embodiments, the material of the planarization layer 130 may also include an inorganic material, other suitable materials, or a combination of the aforementioned materials, but the embodiment is not limited thereto.

(24) In the embodiment, a thickness of the planarization layer 130 is, for example, in a range from 0.1 μm to 5 μm ($0.1\ \mu\text{m} \leq \text{thickness} \leq 5\ \mu\text{m}$), or in a range from 1.5 μm to 2.5 μm ($1.5\ \mu\text{m} \leq \text{thickness} \leq 2.5\ \mu\text{m}$), but the disclosure is not limited thereto. In the embodiment, the thickness of the planarization layer 130 may be defined as the maximum thickness of the planarization layer 130 in the normal direction N of the first substrate 100 after splitting. According to the above arrangement, the planarization layer 130 may have a sufficient thickness, so that the opening 133 of the peripheral region 12 may also have a sufficient thickness, and the subsequent alignment layer 150 may flow into the opening 133 during the manufacturing process, in this way, the thickness of the alignment layer 151 on the planarization layer 130 is reduced, and the thickness of the alignment layer 153 in the opening 133 is increased. The increase of the thickness of the alignment

layer **153** may increase anchoring energy of alignment thereof. In addition, the thickness reduction of the alignment layer **151** on the first portion **131** may reduce fragments probably generated in the subsequent processes, so as to improve the reliability or performance of the electronic device **10**, or improve the display quality of the electronic device **10**.

(25) The insulating layer **140** is disposed on the planarization layer **130**. In the embodiment, the insulating layer **140** is disposed on the first substrate **100** over the entire surface and partially overlaps the planarization layer **130**, and is partially located in the peripheral region **12**. A material of the insulating layer **140** includes an inorganic material. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials. In some embodiments, the material of the insulating layer **140** further includes an organic material, other suitable materials or a combination of the above materials, but the embodiment is not limited thereto. The above-mentioned organic material is, for example (but not limited to): a polymer material such as polyimide resin, epoxy resin, or acrylic resin, etc. In the embodiment, the insulating layer **140** is an inorganic material, and the planarization layer **130** is an organic material, but the embodiment is not limited thereto.

(26) In the embodiment, a thickness of the insulating layer **140** is, for example, in a range from $0.1\ \mu\text{m}$ to $0.8\ \mu\text{m}$ ($0.1\ \mu\text{m} \leq \text{thickness} \leq 0.8\ \mu\text{m}$), or in a range from $0.25\ \mu\text{m}$ to $0.75\ \mu\text{m}$ ($0.25\ \mu\text{m} \leq \text{thickness} \leq 0.75\ \mu\text{m}$), but the disclosure is not limited thereto. In the embodiment, the thickness of the insulating layer **140** may be defined as the maximum thickness of the insulating layer **140** in the normal direction N of the first substrate **100** after splitting. It should be noted that the thickness of the planarization layer **130** divided by the thickness of the insulating layer **140** is greater than or equal to 1.5 and less than or equal to

(27) $25(1.5 < \frac{\text{the thickness of the planarization layer}}{\text{the thickness of the insulating layer}} \leq 25)$.

According to the above configuration, the insulating layer **140** may protect the planarization layer **130** from being influenced by moisture, or the planarization layer **130** may have a sufficient thickness so that the surface of the planarization layer **130** contacting the insulating layer **140** may be planarized to enhance the structural reliability of the electronic device **10**.

(28) The alignment layer **150** is disposed on the insulating layer **140** on the planarization layer **130**. In the embodiment, the alignment layer **150** is disposed on the first substrate **100**, and a part of the alignment layer **150** is located in the peripheral region **12**. The alignment layer **150** may be overlapped with a part of the planarization layer **130** or the insulating layer **140** in the normal direction N of the first substrate **100**. According to another aspect, the insulating layer **140** is disposed between the planarization layer **130** and the alignment layer **150**, but the embodiment is not limited thereto. A material of the alignment layer **150** includes an organic material, such as polyimide, but the disclosure is not limited thereto. In some embodiments, the material of the alignment layer **150** may also include an inorganic material. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials.

(29) In the embodiment, a thickness of the alignment layer **150** is, for example, in a range from $300\ \text{\AA}$ to $1500\ \text{\AA}$ ($300\ \text{\AA} \leq \text{thickness} \leq 1500\ \text{\AA}$), or in a range from $500\ \text{\AA}$ to $1200\ \text{\AA}$ ($500\ \text{\AA} \leq \text{thickness} \leq 1200\ \text{\AA}$), but the disclosure is not limited thereto. In the embodiment, the thickness of the alignment layer **150** may be defined as the maximum thickness of the alignment layer **150** in the normal direction N of the first substrate **100** after splitting.

(30) The light-shielding layer BM is disposed on the second substrate **200**. In the embodiment, the light-shielding layer BM may be partially located in the peripheral region **12**. The light-shielding layer BM is, for example, a black matrix, but the disclosure is not limited thereto. The light-shielding layer BM may be patterned to form a plurality of patterned openings (not shown) corresponding to a plurality of pixel regions (not shown). For example, the light-shielding layer BM may be correspondingly overlapped with a patterned trace (not shown) of the first conductive layer M1 or a patterned signal trace (not shown) of the second conductive layer M2 in the normal

direction N of the first substrate **100**, but the disclosure is not limited thereto.

(31) The overcoat layer **220** is disposed on the light-shielding layer BM. In the embodiment, the overcoat layer **220** may be disposed on the light-shielding layer BM, and partially located in the peripheral region **12**. The overcoat layer **220** is, for example, a transparent overcoat layer, but the disclosure is not limited thereto.

(32) It should be noted that the light shielding layer BM of the embodiment has a groove OP in the peripheral region **12**, and the groove OP may surround the electronic device **10** in the peripheral region **12**. The groove OP is not overlapped with the planarization layer **130** in the normal direction of the first substrate **100**. In other words, the groove OP of the light-shielding layer BM is located in a region of the light-shielding layer BM that is not overlapped with the planarization layer **130**. In the embodiment, there is a distance K between the groove OP and an outer edge **11** of the electronic device **10**, and the distance K may be, for example, in a range from 10 μm to 150 μm ($10\ \mu\text{m} \leq \text{distance K} \leq 150\ \mu\text{m}$), or in a range from 50 μm to 100 μm ($50\ \mu\text{m} \leq \text{distance K} \leq 100\ \mu\text{m}$). The above-mentioned distance K may be defined as the shortest distance between the outer edge **11** of the electronic device **10** and an outer edge **211** of the groove OP in a local area in a direction perpendicular to the normal direction N of the first substrate **100**. A width W of the groove OP may be in a range from 10 μm to 100 μm ($10\ \mu\text{m} \leq \text{width W} \leq 100\ \mu\text{m}$), or in a range from 15 μm to 25 μm ($15\ \mu\text{m} \leq \text{width W} \leq 25\ \mu\text{m}$). The width W of the groove OP may be defined as the maximum width of the groove OP in the local area in the direction perpendicular to the normal direction N of the first substrate **100**.

(33) According to the above configuration, the overcoat layer **220** may be filled into the groove OP to increase a contact area or adhesion strength between the overcoat layer **220** and the light-shielding layer BM, so as to improve the reliability or performance of the electronic device **10** or improve the display quality of the electronic device **10**.

(34) A plurality of supporting members are disposed on one of the first substrate **100** and the second substrate **200**. In the embodiment, the support members include a plurality of the first support members PS1 disposed in the peripheral region **12**. The first support members PS1 are disposed on the overcoat layer **220** on the second substrate **200** and press against the planarization layer **130** on the first substrate **100**. To be specific, the first support members PS1 press against the surface of the insulating layer **140** on the planarization layer **130**, but the disclosure is not limited thereto. In some embodiments, the first support members PS1 may not contact the insulating layer **140**. In some embodiments, the first support members PS1 may also be in contact with the alignment layer **151**. Due to the arrangement of the opening **133**, the thickness of the alignment layer **151** on the first portion **131** of the planarization layer **130** may be reduced to reduce the contact of the first support PS1 with the alignment layer **151**, so as to reduce fragments of the alignment layer **151** caused by squeezing during the contact, which may improve the reliability or performance of the electronic device **10** or improve the display quality of the electronic device **10**.

(35) In the embodiment, the electronic device **10** further includes an another alignment layer **250**. The another alignment layer **250** may be disposed on the overcoat layer **220** and surround the first support members PS1. Namely, the another alignment layer **250** may be in direct contact with the first support members PS1, and in the normal direction N1 of the first substrate **100**, the another alignment layer **250** is not located between the first support members PS1 and the overcoat layer **220**, namely, the another alignment layer **250** is not overlapped with the first support member PS1, but the embodiment is not limited to thereto. In some embodiments, the another alignment layer **250** may directly contact side walls of the first support members PS1. In some embodiments, the another alignment layer **250** may directly contact top surfaces of the first support members PS1. In some other embodiments, the another alignment layer **250** may not contact the first support members PS1. A material of the another alignment layer **250** and the material of the alignment layer **150** may be the same or different, which includes an organic material, such as polyimide, but the disclosure is not limited thereto. In some embodiments, the material of the another alignment

layer **250** may also include an inorganic material. The above-mentioned inorganic material is, for example (but not limited to): silicon oxide, silicon nitride, silicon oxynitride, or a stacked layer of at least two of the above materials.

(36) The package element **160** is disposed in the peripheral region **12** and located between the first substrate **100** and the second substrate **200**. In the embodiment, the package element **160** is, for example, a sealant, which is circumferentially disposed near the outer edge of the electronic device **10** and overlapped with a part of the peripheral region **12**. For example, the package element **160** may be overlapped with a part of the traces of the first conductive layer **M1**, a part of the signal traces of the second conductive layer **M2**, and the active devices **T** in the normal direction **N** of the first substrate **100**. A material of the package element **160** includes epoxy resin, polymethylmethacrylate (PMMA), light curing adhesive, thermal curing adhesive, light thermal curing adhesive, other suitable materials, or a combination of the above materials, but the disclosure is not limited to thereto.

(37) The electronic device **10** of the embodiment applies a technique of configuring the first support members **PS1** in the package element **160**. According to the above configuration, the package element **160** may directly contact the alignment layer **150** and the another alignment layer **250**, and the package element **160** surrounds the first support members **PS1** in the peripheral region **12**. In addition, the electronic device **10** of the embodiment further includes the planarization layer **130** disposed in the peripheral region **12**, and the planarization layer **130** is partially overlapped with the package element **160** in the normal direction **N** of the first substrate **100**. Since the planarization layer **130** may overlap the first conductive layer **M1**, the second conductive layer **M2**, and/or the active devices **T** in the peripheral region **12**, thickness consistency of a display medium layer (shown in FIG. 4) may be maintained, so that the overall thickness of the electronic device **10** is consistent or similar, which improves the structural reliability or performance. In addition, the planarization layer **130** may also protect the traces and/or the active devices **T** in the peripheral region **12** to improve the display quality of the electronic device **10**.

(38) It should be noted that the planarization layer **130** has the first portion **131** and the opening **133**. As shown in FIG. 1 and FIG. 2, the planarization layer **130** may be patterned to form a plurality of openings **133** and **133A** to surround a plurality of the corresponding first portions **131**. Namely, the first portion **131** may be disposed between the opening **133** and/or the opening **133A** to form, for example, an island shape. According to FIG. 1, it is known that the first portion **131** may be circular in the normal direction **N** of the first substrate **100** (for example, in a top view direction), and the opening **133** and the opening **133A** surround the first portion **131** and have an arc-shaped edge, for example, a circular arc shape in the normal direction **N** of the first substrate **100**, but the embodiment is not limited thereto. In some embodiments, the first portion **131**, the opening **133**, and/or the opening **133A** may also be ellipses, rectangles, triangles, irregular shapes, or other suitable shapes in a top view, but the embodiment is not limited thereto. In the embodiment, a distance **W1** of the opening **133** and the opening **133A** may be in a range from 5 μm to 50 μm , respectively ($5\ \mu\text{m} \leq \text{distance } W1 \leq 50\ \mu\text{m}$). A width **W3** of the first portion **131** is in a range from 15 μm to 50 μm ($15\ \mu\text{m} \leq \text{width } W3 \leq 50\ \mu\text{m}$), or in a range from 25 μm to 30 μm ($25\ \mu\text{m} \leq \text{width } W3 \leq 30\ \mu\text{m}$). The distance **W1** of the opening **133** and the opening **133A** may be defined as the minimum distance between an opening side wall of the opening **133** and the opening **133A** and the first portion **131** in a direction perpendicular to the normal direction **N** of the first substrate **100**. The width **W3** of the first portion **131** may be defined as the maximum width of the first portion **131** in the direction perpendicular to the normal direction **N** of the first substrate **100**.

(39) In the embodiment, the opening **133** and the opening **133A** are, for example, grooves formed on the planarization layer **130** in the normal direction **N** of the first substrate **100**. The opening **133** may penetrate through the planarization layer **130** in the normal direction **N** of the first substrate **100**, but the embodiment is not limited thereto. The insulating layer **140** may overlap the planarization layer **130** and may be filled into the opening **133** and the opening **133A**, and/or

overlap the top surface of the first portion **131** in the normal direction N and/or a side wall of the first portion **131** in the opening **133** and the opening **133A**. The side wall of the first portion **131** is not parallel to the normal direction N, but has a tilt angle. Or from another point of view, the tilt angle is between the side wall of the first portion **131** and the first substrate **100**. When viewing from one side, the formed first portion **131** is substantially trapezoidal in shape, which may increase a surface area of the first portion **131**, and the tilt angle facilitates the alignment layer flowing into the opening **133** and the opening **133A** in the subsequent process of fabricating the alignment layer, so that the thickness of the alignment layer **151** on the first portion **131** is reduced, and the thickness of the alignment layer **153** in the opening **133** and the opening **133A** is increased, but the embodiment is not limited thereto. In this way, the planarization layer **130** may increase the surface in contact with the insulating layer **140** through the opening **133** and the opening **133A**, thereby increasing the adhesion or reliability between the planarization layer **130** and the insulating layer **140**.

(40) Moreover, the alignment layer **150** formed on the insulating layer **140** may be partially overlapped with the first portion **131**, the opening **133**, and the planarization layer **130** other than the first portion **131** and the opening **133** in the normal direction N of the first substrate **100**. For example, in the process of forming the alignment layer **150**, the alignment layer **150** adjacent to the outer edge of the opening **133** may slide into the opening **133** along the surface of the insulating layer **140** and is formed in an accommodating space of the opening **133**. In this way, the alignment layer **150** may include the alignment layer **151** overlapped with a part of the first portion **131** (for example, on the first portion **131**) in the normal direction N of the first substrate **100** and the alignment layer **153** located in the opening **133**. According to the above configuration, the surface area of the alignment layer **150** may be increased. In this way, the area where the package element **160** directly contacts the alignment layer **150** (including the alignment layer **151** on the first portion **131** and the alignment layer **153** in the opening **133**) may be increased. Therefore, the adhesion or reliability of the package element **160** and the alignment layer **150** may be increased.

(41) In the embodiment, the alignment layer **151** on the first portion **131** has a first thickness H1, and the alignment layer **153** in the opening **133** has a second thickness H2. The first thickness H1 is greater than or equal to zero, and the first thickness H1 is less than the second thickness H2. For example, the first thickness H1 is greater than or equal to 0 Å and less than or equal to 500 Å, but the disclosure is not limited thereto. The second thickness is greater than 0 Å and less than or equal to 5000 Å. In some embodiments, the second thickness H2 may also be greater than or equal to 500 Å and less than or equal to 1200 Å, but the disclosure is not limited thereto. In the embodiment, the first thickness H1 may be defined as the minimum thickness of the alignment layer **151** substantially located on a central area of the first portion **131** in the normal direction N of the first substrate **100**. The above minimum thickness may be defined as the minimum thickness in any cross-sectional image of the structure obtained by the SEM. The second thickness H2 may be defined as the maximum thickness of the alignment layer **152** in the opening **133** in the normal direction N of the first substrate **100**.

(42) Moreover, the first support member PS1 is overlapped with the first portion **131** in the normal direction N of the first substrate **100**, namely, the first support member PS1 presses against the first portion **131**. In the embodiment, a width W2 of the first support member PS1 is smaller than the width W3 of the first portion **131**. In the embodiment, the width W2 may be defined as the maximum width of the first support member PS1 in the direction perpendicular to the normal direction N of the first substrate **100**. The width W3 may be defined as the maximum width of the first portion **131** in the direction perpendicular to the normal direction N of the first substrate **100**. The width W2 of the first support member PS1 is in a range from 5 μm to 40 μm ($5\text{ }\mu\text{m}\leq\text{width W2}\leq 40\text{ }\mu\text{m}$), or in a range from 9.5 μm to 15 μm ($9.5\text{ }\mu\text{m}\leq\text{width W2}\leq 15\text{ }\mu\text{m}$), but the embodiment is not limited thereto.

(43) In some embodiment, the alignment layer **150** in the peripheral region **12** is not aligned with

an outer edge of the first substrate **100**, and the another alignment layer **250** is not aligned with an outer edge of the second substrate **200**, so that a part of inorganic material layers may be exposed, for example (but not limited to), the insulating layer **140**, the dielectric layer **120**, the gate insulating layer **110**, the first substrate **100** or the second substrate **200**. In this way, the package element **160** may directly contact the inorganic material layers, which may increase the structural reliability or display quality of the electronic device **10**.

(44) In the embodiment, as shown in FIG. 2, the first portion **131** located between the opening **133** may be overlapped with the first conductive layer **M1** in the normal direction **N** of the first substrate **100**. The first support member **PS1** pressing against the first portion **131** may be overlapped with the first conductive layer **M1** in the normal direction **N** of the first substrate **100**, but the embodiment is not limited thereto. In some embodiments, the planarization layer **130** that is not overlapped with the first support member **PS1** may also be overlapped with the first conductive layer **M1**, the second conductive layer **M2**, or the active device **T** in the normal direction **N** of the first substrate **100**, but the embodiment is not limited thereto. In the embodiment, the insulating layer **140** is disposed between the first support members **PS1** and the planarization layer **130**. In this way, when the first support member **PS1** directly contacts and squeezes the insulating layer **140**, the accommodating space formed by the opening **133** of the planarization layer **130** may buffer a lateral stress of the insulating layer **140** pressed and/or pushed by the first support member **PS1**. To be specific, compared to the planarization layer **130**, the harder insulating layer **140** may move laterally through the opening **133** on the softer planarization layer **130** to buffer the influence of stress on the insulating layer **140**. Therefore, the risk that the insulating layer **140** is crushed by the first support member **PS1** may be reduced. In addition, a phenomenon that moisture passes through the cracked insulating layer **140** and the planarization layer **130** absorbs the moisture to swell may be mitigated, or the influence of moisture on the conductive layer overlapped by the insulating layer **140** may be reduced, so as to improve the reliability and/or performance or display quality of the electronic device **10**.

(45) In the embodiment, the package element **160** may also be filled into the opening **133**. In this way, the contact area between the package element **160** and the insulating layer **140** or between the package element **160** and the planarization layer **130** may be increased. In this way, the adhesion between the package element **160** and the insulating layer **140** or the planarization layer **130** may be increased to enhance the reliability of the electronic device **10**.

(46) In some embodiments, a plurality of the openings **133** may be disposed corresponding to or not corresponding to the support members according to user requirements. In addition, since the sizes of the support members may be set according to user requirements, the sizes of the openings **133** must also be designed corresponding to the sizes of the corresponding support members. In other words, the distances **W1** of the openings **133** may be the same or different, and the sizes of the distances **W1** of the openings **133** at different positions may be the same or different, which is not limited by the embodiment. For example, the distance **W1** of the opening **133** near the outer edge **11** of the electronic device **10** shown in FIG. 2 may be greater than or equal to the distance **W1** of the opening **133A** away from the outer edge **11**, but the embodiment is not limited thereto. For example, the distance **W1** of the opening **133** near the outer edge **11** may be 10 μm , and the distance **W1** of the opening **133A** away from the outer edge **11** may be 6 μm , but the embodiment is not limited thereto. In this way, the widths of the openings may be adjusted according to a design requirement of the support members or requirement on different positions of the support members, so as to increase the adhesion between the support members and the insulating layer **140**. It should be noted that, for clarity and convenience's sake, FIG. 2 schematically illustrates the distances **W1** of different openings **133** and opening **133A** and the distances **W1** of different support members to be consistent, but those skilled in the art should understand that as long as the distances **W1** of the openings **133** may overlap the conductive layer and make the alignment layer **150** to be filled into the opening **133** and the opening **133A**, the distances **W1** may be mixed and used in collaboration

without departing from the spirit and scope of the disclosure.

(47) In the embodiment, a part of the package element **160** may be overlapped with the insulating layer **140** and/or the dielectric layer **120** in the normal direction N of the first substrate **100**, but is not overlapped with the planarization layer **130**. Namely, an outer edge of the package element **160** may be located between the outer edge of the first substrate **100** and the outer edge of the planarization layer **130** in the normal direction N of the first substrate **100**, but the embodiment is not limited thereto. In some embodiments, the outer edge of the package element **160** may also be aligned with the outer edge of the planarization layer **130**. In some embodiments, the outer edge of the package element **160** may also be aligned with the outer edge of the first substrate **100**. In addition, the groove OP of the light-shielding layer BM may not be overlapped with the package element **160** in the normal direction N, but the embodiment is not limited thereto.

(48) In brief, in the electronic device **10** of an embodiment of the disclosure, since the planarization layer **130** may be disposed in the peripheral region **12**, and the planarization layer **130** has a plurality of the openings **133** and the first portions **131** between the openings **133**, the contact area of the planarization layer **130** may be increased, and the alignment layer **150** on the planarization layer **130** may flow into a plurality of the openings **133** during the manufacturing process, so as to reduce the thickness of the alignment layer **151** on the planarization layer **130**, and increase the adhesion between the package element **160** and the planarization layer **130** to improve the structural reliability of the electronic device **10**. Moreover, the alignment layer **150** may flow into the opening **133** to reduce the thickness of the alignment layer **151** on the planarization layer **130**, and reduce fragments that may be generated by the alignment layer **151**. In this way, the reliability or performance of the electronic device **10** may be improved. In addition, the first thickness H1 of the alignment layer **151** located on the first portion **131** is smaller than the second thickness H2 of the alignment layer **153** in the opening **133**, by which the adhesion between the alignment layer **150** and the insulating layer **140** is increased, or the first support member PS1 may contact the insulating layer **140** to increase the adhesion between the first support member PS1 and the insulating layer **140**. Moreover, the adhesion between the package element **160** and the alignment layer **150** may also be enhanced. In addition, the opening **133** may also buffer the lateral stress of the insulating layer **140** pressed and/or pushed by the first support member PS1, so that the risk that the insulating layer **140** is squeezed and crushed by the first support member PS1 may be reduced, and the phenomenon that moisture passes through the cracked insulating layer **140** and the planarization layer **130** absorbs the moisture to swell may be mitigated, so as to improve the reliability, performance and display quality of the electronic device **10**. Moreover, the planarization layer **130** is overlapped with the first conductive layer M1, the second conductive layer M2, or the active devices T in the normal direction N of the first substrate **100**, and protects the above components to reduce a direct impact of external environment on performance of the electronic components, so as to improve the performance or display quality of the electronic device **10**.

(49) FIG. 3 is a schematic top view of an electronic device according to another embodiment of the disclosure. For clarity and convenience's sake, FIG. 3 omits illustration of some components. FIG. 4 is a schematic cross-sectional view of the electronic device of FIG. 3 viewing along a section line A-A' and a section line C-C'. For clarity and convenience's sake, FIG. 4 omits illustration of some components. The electronic device **10A** of the embodiment is substantially similar to the electronic device **10** of FIG. 1, so that the same and similar components in the two embodiments will not be repeated. A main difference between the electronic device **10A** of the embodiment and the electronic device **10** is that the electronic device **10A** further has a working region **14**.

(50) In detail, the working region **14** may be defined as a region of the electronic device **10A** having a signal adjusting function, such as an optical signal or an electromagnetic wave signal, but the embodiment is not limited thereto. In the embodiment, the working region **14** may be disposed adjacent to the peripheral region **12** and surrounded by the peripheral region **12**, but the embodiment is not limited thereto. The working region **14** may include a plurality of working

electrodes (not shown) (which may be, for example, pixel electrodes and common electrodes) and an active device array (not shown). Referring to FIG. 3 and FIG. 4, in the working region 14, the active device T is disposed on the first substrate 100, and the planarization layer 130 is disposed on the dielectric layer 120, and is partially overlapped with the first conductive layer M1, the second conductive layer M2, and the active device T in the normal direction N of the first substrate 100. In the embodiment, a display medium layer DM may be disposed between the first substrate 100 and the second substrate 200. A material of the display medium layer DM includes a liquid crystal material, an electrowetting display material, an electrophoretic display material, etc., but the embodiment is not limited thereto. The active device T is electrically connected to the pixel electrode and is used to provide a driving electric field to drive the display medium layer DM to achieve a desired signal adjusting effect.

(51) In the embodiment, the planarization layer 130 of the electronic device 10A further has a plurality of openings 134 disposed in the working region 14. The openings 134 in the working region 14 are substantially similar to the openings 133 in the peripheral region 12, so that detail thereof is not repeated. A width W4 of the opening 134 in the working region 14 and the distance W1 of the opening 133 in the peripheral region 12 may be the same or different, which is not limited by the embodiment. For example, the distance W1 of the opening 133 in the peripheral region 12 may be greater than or equal to the width W4 of the opening 134 in the working region 14, or the width W4 of the opening 134 in the working region 14 may be greater than or equal to the distance W1 of the opening 133 in the peripheral region 12, but the embodiment is not limited thereto.

(52) In the embodiment, the alignment layer 150 further includes an alignment layer 152 disposed on the first portion 132 and an alignment layer 154 disposed in the opening 134. As shown in FIG. 4, a part of the alignment layer 150 on the first portion 132 may slide into the opening 134 to become the alignment layer 154 formed in the accommodating space of the opening 134.

(53) As shown in FIG. 3 and FIG. 4, the electronic device 10A further includes a second support member PS2 disposed in the working region 14, and the second support member PS2 is disposed between the first substrate 100 and the second substrate 200. For example, the second support PS2 may be disposed on the first portion 132 between the opening 134 in the working region 14. The second support member PS2 is substantially similar to the first support member PS1, so that detail thereof is not repeated. The second support member PS2 is overlapped with the first portion 132 in the normal direction N of the first substrate 100, namely, the second support member PS2 presses against the first portion 132. In addition, with respect to the first support member PS1, the second support member PS2 may be overlapped with the second conductive layer M2 in the normal direction N of the first substrate 100. In some embodiments, the second support member PS2 may be overlapped with the first conductive layer M1 and the second conductive layer M2 in the normal direction N of the first substrate 100, but the embodiment is not limited thereto. In some embodiments, the second support member PS2 presses against the surface of the insulating layer 140 on the planarization layer 130, but the embodiment is not limited thereto. In some other embodiments, the second support member PS2 may also be in contact with the alignment layer 152. Due to the configuration of the opening 134, the thickness of the alignment layer 152 on the first portion 132 of the planarization layer 130 may be reduced to reduce the contact between the second support member PS2 and the alignment layer 152, so as to reduce fragments of the alignment layer 152 probably caused by squeezing during the contact. In this way, the reliability or performance of the electronic device 10 is enhanced, or the display quality of the electronic device 10 is enhanced.

(54) In the embodiment, a width of the second support member PS2 is smaller than a width of the first portion 132. The width of the second support member PS2 is in a range from 15 μm to 50 μm ($15\ \mu\text{m} \leq \text{width} \leq 50\ \mu\text{m}$), or in a range from 20 μm to 30 μm ($20\ \mu\text{m} \leq \text{width} \leq 30\ \mu\text{m}$). The width of the second support member PS2 may be defined as the maximum width of the second support

member PS2 in the direction perpendicular to the normal direction N of the first substrate 100. Moreover, the width of the first support member PS1 and the width of the second support member PS2 may be the same or different. In some embodiments, the width of the first support member PS1 may be greater than or equal to the width of the second support member PS2. In some other embodiments, the width of the second support member PS2 may be greater than or equal to the width of the first support member PS1, but the disclosure is not limited thereto.

(55) It should be noted that a height H3 of the first support member PS1 in the embodiment is the same as a height H4 of the second support member PS2. For example, the height H3 of the first support member PS1 is in a range from 1 μm to 6 μm ($1\ \mu\text{m} \leq \text{height H3} \leq 6\ \mu\text{m}$), or in a range from 2 μm to 4 μm ($2\ \mu\text{m} \leq \text{height H3} \leq 4\ \mu\text{m}$). The height H4 of the second support member PS2 is in a range from 1 μm to 6 μm ($1\ \mu\text{m} \leq \text{height H4} \leq 6\ \mu\text{m}$), or in a range from 2 μm to 4 μm ($2\ \mu\text{m} \leq \text{height H4} \leq 4\ \mu\text{m}$). The height H3 of the first support member PS1 may be defined as the maximum height of the first support member PS1 on the first portion 131 in the normal direction N of the first substrate 100. The height H4 of the second support member PS2 may be defined as the maximum height of the second support member PS2 on the first portion 132 in the normal direction N of the first substrate 100. According to the above configuration, the thickness maintained by the second support member PS2 in the working region 14 may be substantially the same or similar to the thickness maintained by the first support member PS1 in the peripheral region 12. In this way, the overall thickness of the electronic device 10A may be substantially uniform or similar, so as to improve structural reliability or performance, or enhance the display quality of the electronic device 10A.

(56) In summary, in the electronic device of an embodiment of the disclosure, since the planarization layer may be disposed in the peripheral region and/or the working region, and the planarization layer has a plurality of openings and the first portions between the openings, the contact area of the planarization layer may be increased, and the alignment layer on the planarization layer may flow into a plurality of the openings during the manufacturing process, so as to reduce the thickness of the alignment layer on the planarization layer, and reduce the fragments probably generated by the alignment layer, or make the first support member and/or the second support member to contact the insulating layer to respectively increase the adhesion between the first support member and/or the second support member and the insulating layer, so as to improve the adhesion between the package element and the planarization layer, which may improve the reliability or performance of the electronic device, or improve the overall structural reliability of the electronic device. Moreover, the opening may also buffer the lateral stress of the insulating layer that is pressed and/or pushed by the support member (including the first support member or the second support member), so that the risk that the insulating layer is squeezed and crushed by the support member may be reduced, and the phenomenon that moisture passes through the cracked insulating layer and the planarization layer absorbs the moisture to swell may be mitigated, so as to improve the reliability, performance and display quality of the electronic device. The planarization layer is overlapped with the first conductive layer, the second conductive layer, or the active device in the normal direction of the first substrate, and protects the electronic components in the electronic device to reduce a direct impact of external environment on performance of the electronic components, so as to improve the performance or display quality of the electronic device.

(57) Moreover, the ratio of the thickness of the planarization layer to the thickness of the insulating layer may enhance the effect that the insulating layer protects the planarization layer from being influenced by moisture. The sufficient thickness of the planarization layer may increase flatness of the surface of the planarization layer in contact with the insulating layer to improve the structural reliability of the electronic device. The light-shielding layer may be provided with a groove on a region that is not overlapped with the planarization layer. The overcoat layer may be filled into the groove to increase an adhesive strength, which may improve the reliability, performance, or display

quality of the electronic device.

(58) It should be noted that the above embodiments are only used to illustrate the technical solution of the disclosure, rather than limit it; although the disclosure has been described in detail with reference to the foregoing embodiments, those of ordinary skill in the art should understand that: the technical solutions described in the aforementioned embodiments may still be modified, or some or all of the technical features may be equivalently replaced; and these modifications or replacements do not deviate the essence of the corresponding technical solutions from the scope of the technical solutions of the embodiments of the disclosure. It should be understood that anyone with ordinary knowledge in the technical field may make changes, substitutions, and decorations without departing from the spirit and scope of the disclosure, and the protection scope of the disclosure also includes a combination of each patent application scope and embodiments.

Claims

1. An electronic device comprising: a first substrate; an active device disposed on the first substrate and comprising a gate and a semiconductor layer; a first conductive element disposed on the first substrate, wherein the first conductive element is a same layer of the gate of the active device; a first support member disposed on the first substrate, wherein the first support member overlaps the first conductive element; a second conductive element disposed on the first substrate; a second support member overlapping the second conductive element; and a package element disposed on the first substrate, wherein in a cross-sectional view of the electronic device, at least a portion of the first support member and at least a portion of the second support member are laterally surrounded by the package element and at least a portion of the package element is disposed between the first support member and the second support member, and wherein in a top view of the electronic device, the first conductive element and the second conductive element extend in a same direction, and the semiconductor layer is between the first conductive element and the second conductive element.
 2. The electronic device as claimed in claim 1, wherein the first conductive element is adjacent to the gate and spaced apart from the gate by a gap.
 3. The electronic device as claimed in claim 1, wherein in the top view, the gate is located between the first conductive element and the second conductive element and the second conductive element is the same layer of the gate of the active device.
 4. The electronic device as claimed in claim 1, wherein the semiconductor includes metal oxide.
 5. The electronic device as claimed in claim 1, wherein a width of the second support member is the same as a width of the first support member.
 6. The electronic device as claimed in claim 1, wherein in the top view of the electronic device, the package element overlaps the semiconductor layer, the first conductive element and the second conductive element.
-