

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413116
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chen; Jinhua et al.

Motor rotor, motor, and vehicle

Abstract

A motor rotor includes a wound rotor comprising a rotating shaft, a rotor core, and a plurality of rotor coils. The rotor core is fixedly sleeved on the rotating shaft, a plurality of winding holes surrounding the rotating shaft are provided at intervals on the rotor core, each winding hole penetrates through two ends that are of the rotor core and that are disposed in an axial direction, each rotor coil is wound on hole walls of two adjacent winding holes, and two adjacent rotor coils share one winding hole. A gap is formed between two adjacent rotor coils, a first shaft hole is formed on the rotating shaft, the gap is configured as a first heat dissipation channel connected to the first shaft hole, and the first heat dissipation channel is used for inflow of coolant in the rotating shaft.

Inventors: Chen; Jinhua (Dongguan, CN), Wu; Chaoqiang (Shenzhen, CN), Zhou; Zhao (Dongguan, CN), Huang; Jianxin (Shenzhen, CN), Wang; Shaohua (Shenzhen, CN)

Applicant: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 72719214

Assignee: HUAWEI DIGITAL POWER TECHNOLOGIES CO., LTD. (Shenzhen, CN)

Appl. No.: 17/990113

Filed: November 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230077647 A1	Mar. 16, 2023

Foreign Application Priority Data

CN	202010418983.6	May. 18, 2020
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/072624 20210119 PENDING child-doc US 17990113

Publication Classification

Int. Cl.: H02K9/14 (20060101); H02K1/12 (20060101); H02K1/26 (20060101)

U.S. Cl.:

CPC H02K9/14 (20130101); H02K1/12 (20130101); H02K1/26 (20130101);

Field of Classification Search

CPC: H02K (1/12); H02K (1/24); H02K (1/26); H02K (1/32); H02K (1/325); H02K (11/0094); H02K (19/12); H02K (3/24); H02K (9/14); H02K (9/19)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5189325	12/1992	Jarczynski	N/A	N/A
2003/0030333	12/2002	Johnsen	310/54	H02K 1/32
2016/0043613	12/2015	Patel	310/52	H02K 9/22
2016/0149451	12/2015	Teter	310/54	H02K 3/24
2016/0164374	12/2015	Yang et al.	N/A	N/A
2018/0375403	12/2017	Garmon et al.	N/A	N/A
2020/0036248	12/2019	Krais et al.	N/A	N/A
2020/0112217	12/2019	Pal	N/A	N/A
2023/0077647	12/2022	Chen	180/65.6	H02K 1/12
2024/0079934	12/2023	Ledieu	N/A	H02K 1/32

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1057551	12/1991	CN	N/A
105680596	12/2015	CN	N/A
110535261	12/2018	CN	N/A
209982270	12/2019	CN	N/A
111162633	12/2019	CN	N/A
111769673	12/2019	CN	N/A
111769674	12/2019	CN	N/A
102016215428	12/2017	DE	N/A
3934066	12/2021	EP	N/A

Primary Examiner: Desai; Naishadh N

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of International Patent Application No. PCT/CN2021/072624 filed on Jan. 19, 2021, which claims priority to Chinese Patent Application No. 202010418983.6 filed on May 18, 2020. The disclosures of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) This disclosure relates to the field of drive device technologies, and in particular, to a motor rotor, a motor, and a vehicle.

BACKGROUND

(2) An excitation motor does not need to use magnetic steel, and excitation of a rotor of the excitation motor is adjustable. Therefore, the excitation motor has features such as low costs, no demagnetization risk, and high drive efficiency. The motor may be used as a drive device in the field of main drive and auxiliary drive systems of vehicles, prilling systems of factories, or the like.

(3) In a related technology, an excitation motor includes a stator and a rotor, where the stator is movably sleeved on a periphery of the rotor, and the rotor is connected to a load. During operation, the rotor rotates relative to the stator under the action of a rotating magnetic field generated by the stator, thereby driving the load to move. To ensure that the rotor of the excitation motor can stably operate, effective heat dissipation needs to be performed on the rotor. In the conventional technology, a gap between an inner wall of a stator and an outer wall of a rotor is used as a cooling air duct, and a heat dissipation fan facing the cooling air duct is disposed at one end of the rotor. During heat dissipation, air blown by the heat dissipation fan enters the cooling air duct, and directly contacts a core of the rotor, to indirectly cool the stator and a winding on the core of the rotor through the core.

(4) However, a conventional motor uses air cooling heat dissipation, and heat dissipation cannot be effectively performed on a core and a winding of a rotor of the motor. Consequently, a useful life of the motor is affected.

SUMMARY

(5) Embodiments of this disclosure provide a motor rotor, a motor, and a vehicle, to resolve a problem that heat dissipation cannot be effectively performed on a conventional motor rotor because the conventional motor rotor uses air cooling heat dissipation.

(6) An embodiment of this disclosure provides a motor rotor, including a wound rotor.

(7) The wound rotor includes a rotating shaft, a rotor core, and a plurality of rotor coils, where the rotor core is fixedly sleeved on the rotating shaft, a plurality of winding holes surrounding the rotating shaft are provided at intervals on the rotor core, each winding hole penetrates through two ends that are of the rotor core and that are disposed in an axial direction, each rotor coil is wound on hole walls of two adjacent winding holes, and two adjacent rotor coils share one winding hole.

(8) A gap is formed between two adjacent rotor coils, a first shaft hole is formed on the rotating shaft, and the gap is configured as a first heat dissipation channel connected to the first shaft hole.

(9) In the motor rotor in this embodiment of this disclosure, the gap between two adjacent rotor coils is used as the first heat dissipation channel connected to the first shaft hole of the rotating shaft. In this way, coolant introduced into the rotating shaft from an outside enters the first heat dissipation channel from the first shaft hole under the action of centrifugal force, and directly dissipates heat from the rotor coil of the wound rotor. Compared with air cooling heat dissipation in the conventional technology, heat dissipation efficiency of the rotor coil is effectively improved. In addition, because the coolant is in direct contact with the rotor coil that generates a large amount of heat, a heat dissipation effect on the rotor coil is further improved, a useful life of the motor rotor is prolonged, and stable operation of the motor rotor is ensured. In addition, compared with a

conventional motor, an additional heat dissipation fan does not need to be disposed in a heat dissipation structure of the motor rotor in this embodiment of this disclosure, and the winding hole in the rotor core is directly used as the first heat dissipation channel, so that a heat dissipation effect on the motor rotor is improved, a size of the motor rotor is reduced, and a structure of the motor rotor is simplified, thereby improving assembly efficiency of the motor rotor.

(10) Optionally, a plurality of first shaft holes are provided at intervals on the rotating shaft in a circumferential direction, and a quantity of first shaft holes is equal to or less than a quantity of first heat dissipation channels.

(11) The plurality of first shaft holes are provided on the rotating shaft, to improve efficiency of the coolant in the rotating shaft entering the first heat dissipation channels.

(12) Optionally, the wound rotor further includes a first end plate and a second end plate that are respectively disposed at the two ends that are of the rotor core and that are in the axial direction.

(13) A first radial channel configured to connect the first shaft hole and the first heat dissipation channel is formed between the rotor core and the first end plate, a first outlet channel connected to an outside of the rotor core is formed between the second end plate and the rotor core, and the first heat dissipation channel is connected to the first outlet channel. In this way, the coolant flowing out from the first shaft hole of the rotating shaft can flow in from one end that is of the first heat dissipation channel and that is in the axial direction through the first radial channel, and then flow out from the first heat dissipation channel through the first outlet channel at the other end of the first heat dissipation channel. In other words, the coolant flowing out from the rotating shaft flows in from one end of the rotor core and flows out from the other end of the rotor core. This lengthens a flow path of the coolant in the first heat dissipation channel, increases a contact area between the coolant and the rotor coil, and improves heat dissipation efficiency of the rotor coil and the rotor core. In addition, after exchanging heat with the rotor coil, the coolant can be timely discharged to the outside of the rotor core, to further ensure that heated coolant does not affect an operating temperature of the wound rotor. In addition, a manufacturing process of the first radial channel and the first outlet channel is simplified by disposing the first end plate and the second end plate.

Therefore, it is ensured that the coolant flowing out from the first shaft hole can effectively enter one end of the first heat dissipation channel and smoothly flow out from the other end of the first heat dissipation channel to the outside of the rotor core, and manufacturing efficiency of the wound rotor in this embodiment of this disclosure is improved.

(14) Optionally, the wound rotor further includes a first reinforcement assembly.

(15) The first reinforcement assembly is disposed between the first end plate and the rotor core, and the first radial channel is disposed between the first reinforcement assembly and the first end plate.

(16) The first reinforcement assembly is disposed between the first end plate and one end of the rotor core, to enhance structural strength of the wound rotor in a rotation process, and ensure structural stability in a high-speed operation process of the wound rotor formed through assembly of components such as the rotating shaft and the rotor core.

(17) Optionally, the first reinforcement assembly includes a first potting adhesive.

(18) A plurality of first radial holes surrounding the rotating shaft are provided at intervals on the first potting adhesive, the first radial hole separately extends to the first heat dissipation channel and the first end plate in the axial direction, and the first radial channel includes at least a part that is of the first radial hole and that extends in a radial direction.

(19) The first potting adhesive is disposed to enhance connection strength between the rotor core and the first end plate, and improve the structural strength of the wound rotor. In addition, the first radial hole connected to the first heat dissipation channel is formed on the first potting adhesive, so that the coolant flowing out from the first shaft hole can also effectively enter the first heat dissipation channel.

(20) Optionally, a quantity of first radial holes is equal to the quantity of first shaft holes, and each first radial hole penetrates to a corresponding first shaft hole in the radial direction. In this way, the

coolant flowing out from each first shaft hole can enter each first heat dissipation channel through a corresponding first radial hole, thereby improving flow efficiency of the coolant from the first shaft hole of the rotating shaft to each first heat dissipation channel.

(21) Optionally, the first reinforcement assembly further includes a first lantern ring fixedly sleeved on the rotating shaft, and the first potting adhesive is disposed on a periphery of the first lantern ring.

(22) The first radial channel further includes a plurality of drainage grooves that surround the rotating shaft and that are disposed at intervals on the first lantern ring, the drainage grooves are disposed corresponding to the first shaft holes, a first end of each drainage groove extends to a corresponding first shaft hole, and a second end of the drainage groove is connected to the first radial hole.

(23) The first lantern ring is disposed at one end of the rotor core, to limit the rotor core in the axial direction, and ensure stability of the rotor core on the rotating shaft in a high-speed rotation process. In addition, the drainage groove connected to the first shaft hole is disposed on the first lantern ring, so that the coolant flowing out from the first shaft hole enters the first radial hole of the first potting adhesive through each drainage groove, and is finally drained into the first heat dissipation channel through the first radial hole. This improves flow efficiency of the coolant from the rotating shaft to each first heat dissipation channel, and reduces a loss of the coolant on a path from the first shaft hole to the first heat dissipation channel.

(24) Optionally, the quantity of first shaft holes is less than a quantity of first radial holes, and one drainage groove is connected between two adjacent first radial holes, to simplify a structure of the rotating shaft and the first lantern ring, thereby improving the manufacturing efficiency of the wound rotor.

(25) Optionally, a gap is formed between the first lantern ring and a part that is of the first potting adhesive and that faces each drainage groove, and two ends of each gap respectively extend to the first radial holes on two adjacent sides of the drainage groove. In this way, the coolant drained out from each drainage groove can smoothly enter the first radial holes on the two sides through the gap. Therefore, structure disposition of the wound rotor is simplified, a loss amount of the coolant on the first radial channel is reduced, and it is ensured that the coolant is quickly drained from each first shaft hole to each first heat dissipation channel.

(26) Optionally, the first reinforcement assembly further includes a first end framework sleeved on the first lantern ring, and the first end framework is located between the first potting adhesive and the rotor core.

(27) A first avoidance port is formed at a position that is of the first end framework and that corresponds to the winding hole, and each rotor coil passes through the first avoidance port and is wound on one side that is of the first end framework and that is away from the rotor core.

(28) The first end framework is disposed to further enhance structural strength of one end of the rotor core, and enhance stability of the rotor core in the axial direction of the rotating shaft. In addition, a part that is of each rotor coil and that passes through one end of the winding hole is wound on one end that is of the first end framework and that is away from the rotor core, so that when the first end framework is an electrical-insulating material, an insulation function is implemented between the rotor coil and an end part of the rotor core.

(29) Optionally, a first limiting part extends, in a direction away from the rotor core, from one end that is of the first end framework and that is away from the rotating shaft, and a part that is of each rotor coil and that passes through the first end framework is located between the first limiting part and the rotating shaft, to limit movement of the rotor coil in a direction perpendicular to the rotating shaft, thereby improving stability of the rotor coil in the radial direction.

(30) Optionally, the wound rotor further includes a second reinforcement assembly.

(31) The second reinforcement assembly is disposed between the second end plate and the rotor core, and the first outlet channel is disposed between the second reinforcement assembly and the

second end plate.

(32) The second reinforcement assembly is disposed between the second end plate and the rotor core, to further enhance the structural strength of the wound rotor in the rotation process, and ensure the structural stability in the high-speed operation process of the wound rotor formed through assembly of components such as the rotating shaft and the rotor core.

(33) Optionally, the second reinforcement assembly includes a second potting adhesive, a plurality of second radial holes surrounding the rotating shaft are provided at intervals on the second potting adhesive, two ends that are of the second radial hole and that are in the axial direction respectively extend to the first heat dissipation channel and the second end plate, and at least a part that is of the second radial hole and that extends in the radial direction is configured as the first outlet channel.

(34) The second potting adhesive is disposed to enhance connection strength between the rotor core and the second end plate, and improve the structural strength of the wound rotor. In addition, the second radial hole connected to the first heat dissipation channel is formed on the second potting adhesive, so that the coolant flowing out from the first heat dissipation channel can be smoothly discharged to the outside of the rotor core through the second radial hole. In addition, the second radial hole configured to drain out the coolant is formed on the second potting adhesive, so that structure disposition of the first outlet channel is more convenient and simpler.

(35) Optionally, a plurality of second heat dissipation channels surrounding the rotating shaft are disposed at intervals on the rotor core, the second heat dissipation channel is located between the rotating shaft and the first heat dissipation channel, the second heat dissipation channel penetrates through the two ends that are of the rotor core and that are disposed in the axial direction, a second shaft hole connected to the second heat dissipation channel is formed on the rotating shaft, and the second heat dissipation channel is used for inflow of the coolant in the rotating shaft.

(36) In this embodiment of this disclosure, the plurality of second heat dissipation channels are disposed in the rotor core in the axial direction, and the second shaft hole connected to the second heat dissipation channel is provided on the rotating shaft. In this way, after the coolant flowing out from the second shaft hole enters the second heat dissipation channel, heat dissipation is directly performed on the rotor core, thereby further improving heat dissipation efficiency of the wound rotor and ensuring the stable operation of the motor rotor.

(37) Optionally, the second reinforcement assembly further includes a second lantern ring fixedly sleeved on the rotating shaft, and the second lantern ring is disposed between the rotating shaft and the second potting adhesive.

(38) A first annular groove is formed between the second lantern ring and the rotating shaft, and the second shaft hole and one end that is of the second heat dissipation channel and that faces the second lantern ring are located in the first annular groove.

(39) The second lantern ring is disposed at the other end of the rotor core, to further limit the rotor core in the axial direction of the rotating shaft, and ensure the stability of the rotor core on the rotating shaft in the high-speed rotation process. In addition, two ends of the second heat dissipation channel respectively penetrate to the two ends of the rotor core, to lengthen a flow path of the coolant in the rotor core, thereby improving heat dissipation efficiency of the coolant on the rotor core. In addition, the first annular groove is disposed between the second lantern ring and the rotating shaft, and each second shaft hole and one end of each second heat dissipation channel are accommodated in the first annular groove. In this way, the coolant flowing out from the second shaft hole first enters the first annular groove, and the coolant smoothly enters the second heat dissipation channel in a buffer process of the first annular groove, thereby avoiding a loss of the coolant in a process of flowing into the second heat dissipation channel.

(40) Optionally, a second outlet channel connected to the outside of the rotor core is formed between the first potting adhesive and the first end plate.

(41) A perforative hole is formed on the first lantern ring in an extension direction of the rotating shaft, and two ends of the perforative hole are respectively connected to the second heat dissipation

channel and the second outlet channel. In this way, the coolant flowing out from the second heat dissipation channel enters the second outlet channel through the perforative hole of the first lantern ring, and is finally drained out to the outside of the rotor core. In addition, the second outlet channel connected to the outside is formed between the first potting adhesive and the first end plate, to ensure that the coolant flowing out from the second heat dissipation channel can smoothly flow to the outside of the rotor core, so that disposition of the second outlet channel is more convenient and faster, thereby improving the manufacturing efficiency of the wound rotor.

(42) Optionally, a quantity of perforative holes is less than a quantity of second heat dissipation channels. A second annular groove surrounding the rotating shaft is disposed on one side that is of the first lantern ring and that faces the second heat dissipation channel, and the perforative hole is located in the second annular groove.

(43) Because the quantity of perforative holes is set to be less than the quantity of second heat dissipation channels, a manufacturing process of the first lantern ring is simplified. In addition, flow efficiency of the coolant from the second heat dissipation channel to the second outlet channel is reduced, so that the coolant flowing out from the perforative hole can gradually dissipate heat from the first end plate, that is, contact duration between the coolant and the first end plate is prolonged, and a heat dissipation effect of the coolant flowing out from the second heat dissipation channel on the first end plate is improved. In addition, the second annular groove is disposed on the side that is of the first lantern ring and that faces the second heat dissipation channel, to ensure that the coolant flowing out from each second heat dissipation channel can smoothly enter the perforative hole in a buffer process of the second annular groove, thereby reducing a loss of the coolant in a process of flowing into the perforative hole from the second heat dissipation channel.

(44) Optionally, the second outlet channel and the first radial channel are disposed in a staggered manner. In this way, a flow path of the first heat dissipation channel and a flow path of the second heat dissipation channel are independent of each other, that is, after exchanging heat with the rotor core, the coolant can be directly discharged to the outside of the rotor core after entering the second outlet channel without entering the first heat dissipation channel through the first radial channel, thereby preventing heated coolant from affecting the heat dissipation effect on the rotor coil. In addition, at least a part of the coolant entering the first radial channel from the first shaft hole is prevented from flowing out from the second outlet channel to the outside of the rotor core before entering the first heat dissipation channel, and normal heat dissipation of the coolant to the wound rotor is prevented from being affected.

(45) Optionally, the wound rotor further includes a second end framework sleeved on the second lantern ring, and the second end framework is located between the second potting adhesive and the rotor core.

(46) A second avoidance port is formed at a position that is of the second end framework and that corresponds to the winding hole, and each rotor coil passes through the second avoidance port and is wound on one side that is of the second end framework and that is away from the rotor core.

(47) The second end framework is disposed to further enhance structural strength of the other end of the rotor core, and enhance the stability of the rotor core in the axial direction of the rotating shaft. In addition, a part that is of each rotor coil and that passes through one end of the winding hole is wound on one end that is of the second end framework and that is away from the rotor core, so that when the second end framework is an electrical-insulating material, an insulation function is implemented between the rotor coil and an end part of the rotor core.

(48) Optionally, the rotor core includes a core body and a plurality of groove wedges.

(49) A plurality of winding grooves surrounding the rotating shaft are formed on an outer wall of the core body, each winding groove penetrates through two ends that are of the core body and that are disposed in the axial direction, each groove wedge is clamped at a groove opening that is of a corresponding winding groove and that is away from the rotating shaft, and a groove wall of the winding groove and the groove wedge jointly enclose to form the winding hole.

(50) According to the disposition manner of the rotor core, the rotor coil can be directly wound on groove walls of two adjacent winding grooves by using groove openings of the core body, thereby improving assembly efficiency between the rotor coil and the core body. In addition, each groove wedge is clamped at the groove opening of the winding groove, to prevent the rotor coil from being released from the winding groove.

(51) Optionally, a first radial channel is formed between the two ends that are of the rotor core and that are disposed in the axial direction, and two ends of the first radial channel respectively penetrate to the first shaft hole and the first heat dissipation channel in the radial direction of the rotor core.

(52) Optionally, the wound rotor further includes a rotor jacket.

(53) The rotor jacket includes a first annular jacket and a second annular jacket, where one of the first annular jacket and the second annular jacket is sleeved on a periphery that is of the first reinforcement assembly and that is away from the rotating shaft, and the other of the first annular jacket and the second annular jacket is sleeved on a periphery that is of the second reinforcement assembly and that is away from the rotating shaft.

(54) In this embodiment of this disclosure, the rotor jacket is sleeved on the periphery of the first reinforcement assembly and the periphery of the second reinforcement assembly, to further enhance structural strength of the end parts of the wound rotor, thereby ensuring the structural stability of the motor rotor in the high-speed operation process.

(55) Optionally, the motor rotor further includes an excitation module.

(56) The excitation module includes an excitation transformer rotor fixedly sleeved on the rotating shaft and a rectifier board electrically connected to the excitation transformer rotor. The rectifier board is fastened to the first end plate, and a lead of the rotor coil is electrically connected to the rectifier board.

(57) The excitation module further includes a third potting adhesive. The excitation transformer rotor is connected to the first end plate by using the third potting adhesive. In this way, connection strength between the excitation transformer rotor and the first end plate is enhanced, thereby improving connection strength between the excitation module and the wound rotor, and ensuring structural stability of the entire motor in a moving process. In addition, the rectifier board is fastened to the first end plate, so that the coolant in a heat dissipation groove of the first end plate can further dissipate heat from the rectifier board, thereby ensuring stable operation of the rectifier board.

(58) Optionally, the rectifier board is disposed on one side that is of the first end plate and that is away from the rotor core, the excitation transformer rotor is disposed on one side that is of the rectifier board and that is away from the rotor core, and the rectifier board is located in the third potting adhesive. In this way, components of the excitation module are packaged into an integral structure by using the third potting adhesive. This enhances structural strength of the excitation module, and makes assembly between the excitation module and both of the rotating shaft and the wound rotor more convenient and faster. In addition, the rectifier board is disposed on the side that is of the first end plate and that is away from the rotor core, to provide a proper disposition space for disposing the heat dissipation groove, and facilitate electrical connection between the rectifier board and the excitation transformer rotor.

(59) Optionally, the rotor coil is detachably connected to the rectifier board. In this way, a detachable connection between the wound rotor and the excitation module is implemented, so that the excitation module is detached and replaced as a separate module.

(60) Optionally, the excitation module further includes an excitation module rotor jacket sleeved on the rotating shaft, the excitation transformer rotor is sleeved on the excitation module rotor jacket, and one end of the third potting adhesive is connected to the excitation module rotor jacket.

(61) The excitation module rotor jacket is disposed to enhance connection strength between the excitation transformer rotor and the rotating shaft, and ensure stability of the excitation transformer

rotor in the high-speed rotation process of the rotating shaft. In addition, one end of the third potting adhesive is connected to the excitation module rotor jacket, to further ensure that the components of the excitation module are packaged into an integral structure by using the third potting adhesive, so that connection strength between the components of the entire excitation module is enhanced, and the integrally modularized excitation module is quickly assembled on the rotating shaft and is fixedly connected to the wound rotor.

(62) Optionally, a third heat dissipation channel connected to the first shaft hole is formed on the first end plate or the excitation module rotor jacket in the axial direction of the rotating shaft. In this way, the coolant flowing out from the first shaft hole can further enter the third heat dissipation channel, to effectively dissipate heat from the excitation module.

(63) Optionally, a notch is formed on a sidewall of the first end plate or the second end plate, and the notch is disposed away from the rotating shaft.

(64) The notch is disposed on a sidewall that is of the first end plate and that is away from the rotating shaft, to adjust a center of gravity of the wound rotor, and ensure that the center of gravity of the wound rotor is located on an axis of the rotating shaft, so that a dynamic balance of the wound rotor is implemented, and it is ensured that each component of the wound rotor can stably synchronously move around the axis of the rotating shaft.

(65) Optionally, an annular boss is formed at one end that is of the first end plate and that is away from the rotating shaft, the notch is disposed on the annular boss, and the rectifier board is disposed between the rotating shaft and the annular boss.

(66) The annular boss is disposed on the first end plate to meet a requirement for a notch of a different depth. In addition, the annular boss also plays a role of limiting and protecting the rectifier board disposed on the first end plate in the radial direction.

(67) An embodiment of this disclosure further provides a motor, including a stator and the foregoing motor rotor, where the stator is movably sleeved on a periphery of the motor rotor.

(68) In the motor in this embodiment of this disclosure, the motor rotor is disposed in the stator. Compared with air cooling heat dissipation in the conventional technology, heat dissipation efficiency of the motor rotor is effectively improved, a useful life of the motor is prolonged, and stable operation of the motor rotor is ensured. In addition, compared with a conventional motor, an additional heat dissipation fan does not need to be disposed in a heat dissipation structure of the motor in this embodiment of this disclosure, and the winding hole in the rotor core is directly used as the first heat dissipation channel, so that a heat dissipation effect on the motor is improved, a size of the motor is reduced, and a structure of the motor is simplified, thereby improving assembly efficiency of the motor.

(69) An embodiment of this disclosure further provides a vehicle, including at least wheels, a transmission component, and the foregoing motor, where the rotating shaft of the motor is connected to the wheels by using the transmission component.

(70) In the vehicle provided in this embodiment of this disclosure, the motor is used to drive the wheels to rotate. A heat dissipation effect of the motor is good, so that the motor can stably drive the wheels to rotate without affecting normal drive of the wheels due to overheating of the motor, thereby effectively improving drive efficiency of the vehicle, and reducing drive and heat dissipation energy consumption of the vehicle.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram of an overall structure of a motor rotor according to an embodiment of this disclosure;

(2) FIG. 2 is a schematic diagram of a partial structure of FIG. 1;

- (3) FIG. 3 is an exploded view of FIG. 2;
- (4) FIG. 4 is a sectional view of FIG. 1 in a direction A-A;
- (5) FIG. 5 is a schematic diagram of a structure of a rotating shaft in FIG. 1;
- (6) FIG. 6 is a schematic diagram of a structure of a core body in FIG. 1;
- (7) FIG. 7 is an assembly diagram of a core body and a rotor coil in FIG. 1;
- (8) FIG. 8 is a sectional view of FIG. 2 in a radial direction;
- (9) FIG. 9 is another sectional view of FIG. 2 in a radial direction;
- (10) FIG. 10 is a schematic diagram of a structure of a wound rotor in FIG. 2 in a first perspective;
- (11) FIG. 11 is a schematic diagram of a structure of a wound rotor in FIG. 2 in a second perspective;
- (12) FIG. 12 is an assembly diagram of a rotating shaft and a second lantern ring in FIG. 1;
- (13) FIG. 13 is a schematic diagram of a structure of a first lantern ring in FIG. 10;
- (14) FIG. 14 is an assembly diagram of a first end plate and an excitation module in FIG. 2;
- (15) FIG. 15 is a schematic diagram of a partial structure of FIG. 11;
- (16) FIG. 16 is an assembly diagram of an excitation module rotor jacket and a wound rotor in FIG. 1;
- (17) FIG. 17 is a schematic diagram of a partial structure of FIG. 16; and
- (18) FIG. 18 is a schematic diagram of a partial structure of a motor according to an embodiment of this disclosure.

DESCRIPTION OF REFERENCE NUMERALS

- (19) **100**—motor rotor; **200**—stator; **10**—wound rotor; **20**—excitation module; **11**—rotating shaft; **12**—rotor core; **13**—rotor coil; **14**—first end plate; **15**—second end plate; **16**—first reinforcement assembly; **17**—second reinforcement assembly; **18**—rotor jacket; **19**—fourth potting adhesive; **21**—excitation module rotor; **22**—excitation module stator; **111**—first shaft hole; **112**—second shaft hole; **113**—inlet; **114**—boss; **121**—core body; **122**—groove wedge; **123**—first heat dissipation channel; **124**—first radial channel; **125**—first outlet channel; **126**—second heat dissipation channel; **127**—second outlet channel; **128**—winding hole; **131**—lead; **132**—terminal; **141**—heat dissipation groove; **142**—mounting hole; **143**—annular boss; **161**—first potting adhesive; **162**—first lantern ring; **163**—first end framework; **171**—second potting adhesive; **172**—second lantern ring; **173**—second end framework; **211**—excitation transformer rotor; **212**—rectifier board; **213**—third potting adhesive; **214**—third lantern ring; **215**—excitation module rotor jacket; **1211**—winding groove; **1611**—first radial hole; **1621**—drainage groove; **1622**—perforative hole; **1623**—second annular groove; **1631**—first annular connection part; **1632**—first insulation part; **1633**—first limiting part; **1711**—second radial hole; **1721**—first annular groove; **1731**—second annular connection part; **1732**—second insulation part; **1733**—second limiting part; **2111**—transformer rotor core; **2112**—transformer rotor coil; and **2121**—bolt hole.

DESCRIPTION OF EMBODIMENTS

(20) Terms used in embodiments of this disclosure are only used to explain embodiments of this disclosure, but are not intended to limit this disclosure.

(21) In the conventional technology, a motor includes a stator and a rotor, where the stator is movably sleeved on a periphery of the rotor, and the rotor is connected to loads such as a wheel. During operation, the stator generates a rotating magnetic field in an air gap between the stator and the rotor. When a direct current flows into an excitation winding of the rotor, a stationary magnetic field with constant polarity is generated. Under the action of an armature reaction, the rotor generates a torque relative to the stator, thereby driving a load to move.

(22) It can be learned from an operation process of the motor that the rotor of the motor needs to rotate at a high speed to drive the load to move. Therefore, compared with the stator, a large amount of heat is generated in the operation process. When a temperature of the rotor is excessively high, insulation performance of an insulating material on the rotor is affected, or even a condition that the motor is burnt occurs.

(23) To effectively dissipate heat from the motor, in the conventional technology, the air gap between an inner wall of the stator and an outer wall of the rotor is used as a cooling air duct, and a heat dissipation fan facing the cooling air duct is disposed at one end of the rotor. During heat dissipation, air blown by the heat dissipation fan enters the cooling air duct, and directly contacts a core of the rotor, to indirectly cool the stator and a winding on the core of the rotor through the core, so that the temperature of the rotor and a temperature of the stator of the motor are reduced.

(24) However, the motor uses air cooling heat dissipation, and heat dissipation cannot be effectively performed on the rotor of the motor. Consequently, a useful life of the motor is shortened.

(25) To resolve the foregoing problem, embodiments of this disclosure provide a motor rotor, a motor, and a vehicle. A gap between two adjacent rotor coils is used as a first heat dissipation channel connected to a first shaft hole of a rotating shaft. In this way, coolant introduced into the rotating shaft from an outside enters the first heat dissipation channel from the first shaft hole under the action of centrifugal force, and directly dissipates heat from the rotor coil of a wound rotor. Compared with the air cooling heat dissipation in the conventional technology, heat dissipation efficiency of the rotor coil is effectively improved. In addition, because the coolant is in direct contact with the rotor coil that generates a large amount of heat, a heat dissipation effect on the rotor coil is further improved, a useful life of the motor rotor is prolonged, and stable operation of the motor rotor is ensured.

(26) The following describes in detail the motor rotor in embodiments of this disclosure with reference to accompanying drawings.

(27) FIG. 1 is a schematic diagram of an overall structure of a motor rotor according to an embodiment of this disclosure. FIG. 2 is a schematic diagram of a partial structure of FIG. 1. FIG. 3 is an exploded diagram of FIG. 2. FIG. 4 is a sectional view of FIG. 1 in a direction A-A. FIG. 5 is a schematic diagram of a structure of a rotating shaft in FIG. 1. FIG. 6 is a schematic diagram of a structure of a core body in FIG. 1. FIG. 7 is an assembly diagram of a core body and a rotor coil in FIG. 1. FIG. 8 is a sectional view of FIG. 2 in a radial direction. Refer to FIG. 1. An embodiment of this disclosure provides a motor rotor **100**, including a wound rotor **10**. The wound rotor **10** is used as a main part of the motor rotor **100**, to generate a stationary magnetic field with constant polarity, so that a stator **200** of a motor rotates under the action of a rotating magnetic field to drive a load to move.

(28) In an actual application, a direct current excitation power may be transmitted to the wound rotor **10** by using a rotating contactor, for example, a carbon brush or a slip ring, or an excitation power may be transmitted to the wound rotor **10** by using a power electronic transformer (for example, an excitation module rotor **21** of an excitation module **20** in FIG. 1), so that the wound rotor **10** generates a magnetic field.

(29) Refer to FIG. 2. The wound rotor **10** in this embodiment of this disclosure includes a rotating shaft **11**, a rotor core **12**, and a plurality of rotor coils **13** (as shown in FIG. 3). The rotor core **12** is fixedly sleeved on the rotating shaft **11**. For example, the rotor core **12** may be fastened to the rotating shaft **11** by using a key groove, to limit the rotor core **12** in a circumferential direction of the rotating shaft **11**, to ensure that the rotating shaft **11** rotates synchronously with the rotor core **12**. Certainly, to simplify an assembly process of the motor rotor **100**, the rotor core **12** may be alternatively integrally formed on the rotating shaft **11**, to enhance connection strength between the rotor core **12** and the rotating shaft **11**, thereby improving mechanical strength of the motor rotor **100**.

(30) Refer to FIG. 4. In this embodiment of this disclosure, a plurality of winding holes **128** surrounding the rotating shaft **11** are provided at intervals on the rotor core **12**, each winding hole **128** penetrates through two ends that are of the rotor core **12** and that are disposed in an axial direction, each rotor coil **13** is wound on hole walls of two adjacent winding holes **128** (as shown in FIG. 7), and two adjacent rotor coils **13** share one winding hole **128**.

(31) In an example in which three winding holes **128** are sequentially provided at intervals around the axial direction of the rotating shaft **11**, one rotor coil **13** is wound on a hole wall of a first winding hole **128** and a hole wall of a second winding hole **128**, and another rotor coil **13** adjacent to the rotor coil **13** is wound on the hole wall of the second winding hole **128** and a hole wall of a third winding hole **128**. In this case, a part of each of the two adjacent rotor coils **13** is disposed in the second winding hole **128**. The second winding hole **128** is located between the first winding hole **128** and the third winding hole **128**.

(32) Refer to FIG. 3. To ensure effective insulation between the rotor coil **13** and the rotor core **12**, an insulation layer **19** is filled on the hole wall of the winding hole **128**, and the rotor coil **13** is disposed on one side that is of the insulation layer **19** and that is away from the hole wall. It may be understood that the insulation layer **19** may be directly made of an existing insulating material. Details are not described herein again.

(33) It may be understood that, in this embodiment of this disclosure, there are at least three winding holes **128**, to ensure that at least two rotor coils **13** are disposed on the rotor core **12**. For example, a quantity of winding holes **128** may be three, six, or eight. In this embodiment of this disclosure, an example in which there are eight winding holes **128** provided at intervals and eight rotor coils **13** is merely used for description.

(34) A cross-sectional shape of the winding hole **128** may be a triangular shape, a quadrilateral shape, or a pentagonal shape.

(35) Refer to FIG. 2 to FIG. 4. In an actual application, the rotor core **12** may include a core body **121** and a plurality of groove wedges **122**. Refer to FIG. 6. A plurality of winding grooves **1211** surrounding the rotating shaft **11** are formed on an outer wall of the core body **121**, each winding groove **1211** penetrates through two ends that are of the core body **121** and that are disposed in the axial direction, each groove wedge **122** is clamped at a groove opening that is of a corresponding winding groove **1211** and that is away from the rotating shaft **11**, and a groove wall of the winding groove **1211** and the groove wedge **122** jointly enclose to form the winding hole **128**.

(36) According to the disposition manner of the rotor core **12**, the rotor coil **13** can be directly wound on groove walls of two adjacent winding grooves **1211** by using groove openings of the core body **121**, thereby improving assembly efficiency between the rotor coil **13** and the core body **121**. In addition, each groove wedge **122** is clamped at the groove opening of the winding groove **1211**, to prevent the rotor coil **13** from being released from the winding groove **1211**.

(37) In some examples, the rotor core **12** is an integral part formed integrally, and the winding hole **128** is formed in the rotor core **12** in a manner of stamping or injection molding.

(38) Still refer to FIG. 7. A gap is formed between two adjacent rotor coils **13**, for example, there is a gap, in the axial direction, between parts that are of two adjacent rotor coils **13** and that are in a shared winding hole **128**. Refer to FIG. 4 and FIG. 7. A first shaft hole **111** is formed on the rotating shaft **11**, the gap between two adjacent rotor coils **13** is configured as a first heat dissipation channel **123** connected to the first shaft hole **111**, and the first heat dissipation channel **123** is used for inflow of coolant in the rotating shaft **11**. Refer to FIG. 4. It may be understood that the first heat dissipation channel **123** is formed by a part of an inner cavity of the winding hole **128**.

(39) For ease of description, an axial direction of each component described below may be the axial direction of the rotating shaft **11**.

(40) Because two ends of the winding hole **128** on the rotor core **12** penetrate to, in the axial direction, two end faces that are of the rotor core **12** and that are disposed in the axial direction, the gap (that is, the first heat dissipation channel **123**) between two adjacent rotor coils **13** located in a same winding hole **128** also penetrates to the two ends of the rotor core **12** in the axial direction.

(41) The rotating shaft **11** in this embodiment of this disclosure is a hollow structure, and the first shaft hole **111** on the rotating shaft **11** penetrates through a sidewall of the rotating shaft **11**, to ensure that two ends of the first shaft hole **111** are respectively connected to an inner cavity of the rotating shaft **11** and the first heat dissipation channel **123**.

(42) Refer to FIG. 2. In some examples, an inlet **113** connected to the inner cavity of the rotating shaft **11** may be formed at any end of the rotating shaft **11**. For example, the inlet **113** may be disposed at a right end of the rotating shaft **11**, and the inlet **113** is connected to an external coolant delivery pipe. In this way, the coolant can be delivered from the inlet **113** of the rotating shaft **11** to the inner cavity of the rotating shaft **11** through the coolant pipe. The coolant may be coolant oil.

(43) During disposition, a projection of the first shaft hole **111** of the rotating shaft **11** on the rotor core **12** may be located in an area between the two ends that are of the rotor core **12** and that are in the axial direction. To implement a connection between the first shaft hole **111** and the first heat dissipation channel **123**, a through hole whose two ends are respectively connected to the first shaft hole **111** and the first heat dissipation channel **123** may be provided on the rotor core **12**. In this way, the coolant located in the rotating shaft **11** flows from the first shaft hole **111** into the through hole, and flows into the first heat dissipation channel **123** through the through hole, to exchange heat with the rotor coil **13**. Therefore, direct heat dissipation of the rotor coil **13** is implemented, and heat dissipation of the rotor core **12** can be indirectly performed by using the rotor coil **13**.

(44) It may be understood that, in a high-speed rotation process of the motor rotor **100**, the coolant in the rotating shaft **11** may be sprayed at a high speed from the first shaft hole **111** under the action of centrifugal force, and quickly enter the first heat dissipation channel **123**. Therefore, flow efficiency of the coolant is improved, and heat dissipation efficiency of the wound rotor **10** is improved.

(45) Refer to FIG. 4 and FIG. 8. In the motor rotor **100** in this embodiment of this disclosure, the gap between two adjacent rotor coils **13** is used as the first heat dissipation channel **123** connected to the first shaft hole **111** of the rotating shaft **11**. In this way, the coolant introduced into the rotating shaft **11** from the outside enters the first heat dissipation channel **123** from the first shaft hole **111** under the action of the centrifugal force, and directly dissipates heat from the rotor coil **13** of the wound rotor **10**. Compared with air cooling heat dissipation in the conventional technology, heat dissipation efficiency of the rotor coil **13** is effectively improved. In addition, because the coolant is in direct contact with the rotor coil **13** that generates a large amount of heat, a heat dissipation effect on the rotor coil **13** is further improved, a useful life of the motor rotor **100** is prolonged, and stable operation of the motor rotor **100** is ensured. In addition, an excitation load capability of the motor rotor **100** is improved, and a torque density and a power density of the motor are improved.

(46) In addition, compared with a conventional motor, an additional heat dissipation fan does not need to be disposed in a heat dissipation structure of the motor rotor **100** in this embodiment of this disclosure, and the winding hole **128** formed in the rotor core **12** through stamping is directly used as the first heat dissipation channel **123**, so that a heat dissipation effect on the motor rotor **100** is improved, a size of the motor rotor **100** is reduced, and a structure of the motor rotor **100** is simplified, thereby improving assembly efficiency of the motor rotor **100**.

(47) Refer to FIG. 5. In this embodiment of this disclosure, a plurality of first shaft holes **111** may be provided at intervals on the rotating shaft **11** in a circumferential direction, and a quantity of first shaft holes **111** is equal to or less than a quantity of first heat dissipation channels **123**. For example, when the quantity of first heat dissipation channels **123** is eight, eight first shaft holes **111** may be provided at intervals on the rotating shaft **11** in the circumferential direction. In this way, each first heat dissipation channel **123** corresponds to one first shaft hole **111**, so that the coolant in the rotating shaft **11** flows into a corresponding first heat dissipation channel **123** after being sprayed from each first shaft hole **111** under the action of the centrifugal force. Certainly, when the quantity of first heat dissipation channels **123** is eight, the quantity of first shaft holes **111** may be a proper value, for example, four, five, six, or seven. Further, a disposition quantity of first shaft holes **111** may be adjusted based on an actual size of the rotating shaft **11** and the like.

(48) In this embodiment of this disclosure, the plurality of first shaft holes **111** are provided on the rotating shaft **11**, so that the coolant in the rotating shaft **11** can simultaneously enter the first heat

dissipation channels **123** through the plurality of first shaft holes **111**, thereby improving flow efficiency of the coolant in the rotating shaft **11** into the first heat dissipation channels **123**, and further improving heat dissipation efficiency of the motor rotor **100** in this embodiment of this disclosure.

(49) Refer to FIG. 2 and FIG. 8. The wound rotor **10** in this embodiment of this disclosure may further include a first end plate **14** and a second end plate **15** that are respectively disposed at the two ends that are of the rotor core **12** and that are in the axial direction.

(50) Refer to FIG. 8. That the first end plate **14** is assembled at a right end face that is of the rotor core **12** and that is disposed in the axial direction, and the second end plate **15** is assembled at a left end face that is of the rotor core **12** and that is disposed in the axial direction is used as an example. A first radial channel **124** configured to connect the first shaft hole **111** and the first heat dissipation channel **123** is formed between the rotor core **12** and the first end plate **14**. For example, a groove (which is not shown in the figure) may be formed on a surface on one side that is of the first end plate **14** and that faces the rotor core **12**, one end of the groove extends to the first shaft hole **111**, and the other end of the groove extends to one end that is of the first heat dissipation channel **123** and that is close to the first end plate **14**. In this way, when the first end plate **14** is fastened to one end of the rotor core **12**, a groove wall of the groove on the first end plate **14** and an end face of the rotor core **12** jointly enclose to form the first radial channel **124**, so that the coolant flowing out from the first shaft hole **111** flows from the end that is of the first heat dissipation channel **123** and that is close to the first end plate **14**, that is, a right port of the first heat dissipation channel **123**, into the first heat dissipation channel **123**.

(51) In addition, a first outlet channel **125** connected to the outside of the rotor core **12** is formed between the second end plate **15** and the rotor core **12**, and the first heat dissipation channel **123** is connected to the first outlet channel **125**. For example, a gap is formed between the second end plate **15** and the left end face of the rotor core **12**. The gap may be used as the first outlet channel **125**, one end of the gap extends to one end that is of the first heat dissipation channel **123** and that is close to a second end face, that is, a left port of the first heat dissipation channel **123**, and the other end of the gap extends to an outer wall of the rotor core **12**. In this way, the coolant flowing out from the left port of the first heat dissipation channel **123** can flow to the outside of the rotor core **12** through the gap, thereby ensuring that heated coolant does not affect an operating temperature of the wound rotor **10**.

(52) In addition, according to the foregoing disposition manner, the coolant flowing out from the first shaft hole **111** of the rotating shaft **11** can arrive, through the first radial channel **124**, one end of the first heat dissipation channel **123**, for example, the right port, enter the first heat dissipation channel **123** from one end of the first heat dissipation channel **123**, dissipate heat from the rotor coil **13** and the rotor core **12**, then enter the first outlet channel **125** from the other end of the first heat dissipation channel **123**, that is, the left port, and be discharged to the outside of the rotor core **12** through the first outlet channel **125**. In other words, the coolant flowing out from the rotating shaft **11** flows in from one end of the rotor core **12**, and is discharged from the other end of the rotor core **12**. This lengthens a flow path of the coolant in the first heat dissipation channel **123**, increases a contact area between the coolant and the rotor coil **13**, and improves a heat dissipation effect on the rotor coil **13** and the rotor core **12**.

(53) A manufacturing process of the first radial channel **124** and the first outlet channel **125** is also simplified by disposing the first end plate **14** and the second end plate **15**. Therefore, it is ensured that the coolant flowing out from the first shaft hole **111** can effectively enter one end of the first heat dissipation channel **123** and smoothly flow out from the other end of the first heat dissipation channel **123** to the outside of the rotor core **12**, and manufacturing efficiency of the wound rotor **10** in this embodiment of this disclosure is improved.

(54) Refer to FIG. 3 and FIG. 8. In the foregoing example, the first end plate **14** is located on the right end face of the rotor core **12**, and the second end plate **15** is located on the left end face of the

rotor core **12**. In another example, the first end plate **14** may be alternatively located on the left end face of the rotor core **12**, and the second end plate **15** may be located on the right end face of the rotor core **12**. It may be understood that, when the inlet **113** of the rotating shaft **11** is located on the right end of the rotating shaft **11**, the first end plate **14** may be located at one end that is of the rotating shaft **11** and that is close to the inlet **113**, or may be located at one end that is of the rotating shaft **11** and that is away from the inlet **113**. Specific positions of disposing the first end plate **14** and the second end plate **15** are not limited in this embodiment of this disclosure. For ease of description, the following describes the structure of the motor rotor **100** with an example in which the inlet **113** of the rotating shaft **11** is located at the right end of the rotating shaft **11**, and the first end plate **14** is located on the right end face of the rotor core **12**.

(55) In this embodiment of this disclosure, during assembly, the first end plate **14** may be directly fastened to the right end face of the rotor core **12**, to seal the right port of the first heat dissipation channel **123** and form the first radial channel **124**. For example, the first end plate **14** may be integrally formed on the right end face of the rotor core **12** through injection molding, and the first radial channel **124** is integrally formed between the first end plate **14** and the right end face of the rotor core **12**. In this way, a structure of the wound rotor **10** can be simplified, assembly efficiency of the wound rotor **10** can be improved, and connection strength between the first end plate **14** and the rotor core **12** can be enhanced. Certainly, in some examples, the first end plate **14** may be alternatively fastened to the right end face of the rotor core **12** in a detachable manner, for example, through threaded connection or clamping, to detach and replace the first end plate **14**.

(56) FIG. **9** is another sectional view of FIG. **2** in a radial direction. Refer to FIG. **9**. The wound rotor **10** in this embodiment of this disclosure may further include a first reinforcement assembly **16**. The first reinforcement assembly **16** is disposed between the first end plate **14** and the rotor core **12**. For example, one end of the first reinforcement assembly **16** is connected to the right end face of the rotor core **12**, and the other end of the first reinforcement assembly **16** is connected to the first end plate **14**. In other words, the first end plate **14** is fastened to the right end face of the rotor core **12** by using the first reinforcement assembly **16**, and the first radial channel **124** is disposed between the first reinforcement assembly **16** and the first end plate **14**.

(57) In this embodiment of this disclosure, the first reinforcement assembly **16** is disposed between the first end plate **14** and one end of the rotor core **12**, to enhance structural strength of the wound rotor **10** in a rotation process, and ensure structural stability in a high-speed operation process of the wound rotor **10** formed through assembly of components such as the rotating shaft **11** and the rotor core **12**.

(58) FIG. **10** is a schematic diagram of a structure of the wound rotor in FIG. **2** in a first perspective. Refer to FIG. **3**, FIG. **9**, and FIG. **10**. The first reinforcement assembly **16** may include a first potting adhesive **161**, for example, the first potting adhesive **161** is filled in a gap between the first end plate **14** and the right end face of the rotor core **12**, to enhance mechanical structural strength of the entire wound rotor **10**.

(59) The first potting adhesive **161** may be a liquid polyurethane compound. The first potting adhesive **161** is solidified into a thermosetting polymer insulating material at a normal temperature or after being heated, to implement an insulation function between both of the rotor core **12** and the rotor coil **13** disposed on the rotor core **12** and the first end plate **14**.

(60) Still refer to FIG. **8** to FIG. **10**. A plurality of first radial holes **1611** surrounding the rotating shaft **11** are provided at intervals on the first potting adhesive **161**, the first radial hole **1611** separately extends to the first heat dissipation channel **123** and the first end plate **14** in the axial direction, and the first radial channel **124** includes at least a part that is of the first radial hole **1611** and that extends in the radial direction. The first radial holes **1611** are provided in a one-to-one correspondence with the first heat dissipation channels **123**. The coolant flowing out from the first shaft hole **111** may be first drained to one end that is of the first radial hole **1611** and that is away from the first heat dissipation channel **123** through the part that is of each of the plurality of first

radial holes **1611** and that extends in the radial direction, and then flow into a corresponding first heat dissipation channel **123** in an axial extension direction of the first radial hole **1611**.

(61) In this embodiment of this disclosure, the first radial hole **1611** connected to the first heat dissipation channel **123** is formed on the first potting adhesive **161**, so that the coolant flowing out from the first shaft hole **111** can effectively enter the first heat dissipation channel **123**. One end that is of the first radial hole **1611** and that extends in the radial direction may extend to one end that is of the first heat dissipation channel **123** and that is away from the rotating shaft **11**, to increase a flow rate of the coolant entering the first heat dissipation channel **123** from the first radial hole **1611**, thereby improving flow efficiency of the coolant in the wound rotor **10**, and further improving the heat dissipation efficiency of the wound rotor **10**.

(62) During disposition, a quantity of first radial holes **1611** may be equal to the quantity of first shaft holes **111**. One end that is of each first radial hole **1611** and that is in the radial direction penetrates to a corresponding first shaft hole **111**. For example, eight first shaft holes **111** and eight first radial holes **1611** are provided, and each first shaft hole **111** is connected to one first radial hole **1611**. In this way, the coolant flowing out from each first shaft hole **111** can enter each first heat dissipation channel **123** through a corresponding first radial hole **1611**, thereby improving flow efficiency of the coolant from the first shaft hole **111** of the rotating shaft **11** to each first heat dissipation channel **123**.

(63) Refer to FIG. **10**. In some examples, the quantity of first shaft holes **111** may alternatively be less than the quantity of first radial holes **1611**. For example, when there are eight first radial holes **1611**, the quantity of first shaft holes **111** may be a proper value, for example, four, five, or six. Each first shaft hole **111** may be connected to one or more first radial holes **1611** by using a drainage groove **1621** or the like, provided that it is ensured that the coolant flowing out from each first shaft hole **111** can smoothly flow into each first heat dissipation channel **123**.

(64) Still refer to FIG. **10**. The first reinforcement assembly **16** in this embodiment of this disclosure may further include a first lantern ring **162** fixedly sleeved on the rotating shaft **11**, where the first lantern ring **162** is fastened on a right end of the rotor core **12**, and the first potting adhesive **161** is disposed on a periphery of the first lantern ring **162**.

(65) The first lantern ring **162** is disposed to limit the rotor core **12** in the axial direction, thereby ensuring stability of the rotor core **12** on the rotating shaft **11** in the high-speed rotation process.

(66) Refer to FIG. **8** to FIG. **10**. The first radial channel **124** in this embodiment of this disclosure may further include a plurality of drainage grooves **1621** that surround the rotating shaft **11** and that are disposed at intervals on the first lantern ring **162**. For example, one side that is of the first lantern ring **162** and that is away from the rotor core **12** is recessed to form the plurality of drainage grooves **1621**, each drainage groove **1621** is disposed corresponding to the first shaft hole **111**, a first end of each drainage groove **1621** extends to a corresponding first shaft hole **111**, and a second end of the drainage groove **1621** is connected to the first radial hole **1611**. In this way, the coolant flowing out from the first shaft hole **111** can enter the first radial hole **1611** of the first potting adhesive **161** through each drainage groove **1621**, and can be finally drained into the first heat dissipation channel **123** through the first radial hole **1611**. This improves the flow efficiency of the coolant from the rotating shaft **11** to each first heat dissipation channel **123**, and reduces a loss of the coolant on a path from the first shaft hole **111** to the first heat dissipation channel **123**.

(67) When the quantity of first shaft holes **111** is less than the quantity of first radial holes **1611**, one drainage groove **1621** may be connected between two adjacent first radial holes **1611**. In this way, the coolant flowing out from the drainage groove **1621** can separately flow into the first radial holes **1611** on both sides, and then flow into the first heat dissipation channel **123**. According to this disposition, a structure of the rotating shaft **11** and the first lantern ring **162** is simplified, thereby improving manufacturing efficiency of the wound rotor **10**.

(68) A gap may be formed between the first lantern ring **162** and a part that is of the first potting adhesive **161** and that faces each drainage groove **1621**, and two ends of each gap respectively

extend to the first radial holes **1611** on two adjacent sides of the drainage groove **1621**. In this way, the coolant drained out from each drainage groove **1621** can smoothly enter the first radial holes **1611** on the two sides through the gap. Therefore, structure disposition of the wound rotor **10** is simplified, a loss amount of the coolant on the first radial channel **124** is reduced, and it is ensured that the coolant is quickly drained from each first shaft hole **111** to each first heat dissipation channel **123**.

(69) It may be understood that the gap between the first potting adhesive **161** and the first lantern ring **162** may be a through hole that is provided in a stamping manner or the like, or certainly, may be a gap reserved when the first potting adhesive **161** is filled. A manner of disposing the gap is not limited in this embodiment of this disclosure.

(70) Refer to FIG. **9**. The wound rotor **10** in this embodiment of this disclosure may further include a second reinforcement assembly **17**. The second reinforcement assembly **17** is disposed between the second end plate **15** and the rotor core **12**. For example, the second reinforcement assembly **17** is disposed on the left end face of the rotor core **12**, and the first outlet channel **125** is disposed between the second reinforcement assembly **17** and the second end plate **15**.

(71) In this embodiment of this disclosure, the second reinforcement assembly **17** is disposed between the second end plate **15** and the rotor core **12**, to further enhance the structural strength of the wound rotor **10** in the rotation process, and ensure the structural stability in the high-speed operation process of the wound rotor **10** formed through assembly of components such as the rotating shaft **11** and the rotor core **12**.

(72) FIG. **11** is a schematic diagram of a structure of the wound rotor in FIG. **2** in a second perspective. Refer to FIG. **3**, FIG. **9**, and FIG. **11**. Optionally, the second reinforcement assembly **17** may include a second potting adhesive **171**. For example, the second potting adhesive **171** is filled between the second end plate **15** and the left end face of the rotor core **12**, to enhance connection strength between the rotor core **12** and the second end plate **15**, and improve the structural strength of the wound rotor **10**.

(73) Refer to FIG. **8** and FIG. **11**. A plurality of second radial holes **1711** surrounding the rotating shaft **11** are provided at intervals on the second potting adhesive **171**, two ends that are of the second radial hole **1711** and that are in the axial direction respectively extend to the first heat dissipation channel **123** and the second end plate **15**, and at least a part that is of the second radial hole **1711** and that extends in the radial direction is configured as the first outlet channel **125**.

(74) One end that is of the second radial hole **1711** and that extends in the radial direction may extend to an outer edge that is of the second potting adhesive **171** and that is away from the rotating shaft **11**, and the other end that is of the second radial hole **1711** and that extends in the radial direction may extend to be flush with one end that is of the first heat dissipation channel **123** and that is close to the rotating shaft **11**, or may extend to an extension direction inside the first heat dissipation channel **123**, provided that it is ensured that the coolant flowing out from a left end of the first heat dissipation channel **123** can be discharged to the outside of the rotor core **12** from the second radial hole **1711**.

(75) In this embodiment of this disclosure, the second radial hole **1711** connected to the first heat dissipation channel **123** is formed on the second potting adhesive **171**, so that the coolant flowing out from the first heat dissipation channel **123** can be smoothly discharged to the outside of the rotor core **12** through the second radial hole **1711**.

(76) In addition, the second radial hole **1711** configured to drain out the coolant is formed on the second potting adhesive **171**, so that structure disposition of the first outlet channel **125** is more convenient and simpler.

(77) In this embodiment of this disclosure, a material of the second potting adhesive **171** and a material of the first potting adhesive **161** are the same, and each may be a liquid polyurethane compound.

(78) To enable the coolant discharged from a second outlet channel **127** to dissipate heat on an

outer surface of the rotor core **12**, a drainage groove (which is not shown in the figure) may be formed on a part that is of the outer surface of the rotor core **12** and that corresponds to the winding hole **128**. That is, a projection of the drainage groove inside the rotor core **12** is located in the winding hole **128**. Two ends of the drainage groove respectively extend to two ends that are of the winding hole **128** and that are disposed in the axial direction. In this way, at least a part of the coolant flowing out from the first heat dissipation channel **123** enters the drainage groove through the first outlet channel **125**. Through drainage of the drainage groove, the coolant discharged from an inside of the rotor core **12** can stably flow on the outer surface of the rotor core **12**, thereby dissipating heat from the rotor core **12**.

(79) In an actual application, the stator **200** of the motor is sleeved on a periphery of the rotor core **12**, and the coolant flowing in the drainage groove of the rotor core **12** can further dissipate heat from the stator **200**. Therefore, the heat dissipation effect on the motor rotor **100** and the motor in this embodiment of this disclosure is further improved, and the excitation load capability of the rotor is improved.

(80) Refer to FIG. 4, FIG. 6, and FIG. 8. A plurality of second heat dissipation channels **126** surrounding the rotating shaft **11** are disposed at intervals on the rotor core **12**. The second heat dissipation channel **126** is located between the rotating shaft **11** and the first heat dissipation channel **123**, and the second heat dissipation channel **126** penetrates through the two ends that are of the rotor core **12** and that are disposed in the axial direction. For example, the second heat dissipation channel **126** extends to the left end face and the right end face of the rotor core **12** in the axial direction, and a second shaft hole **112** connected to the second heat dissipation channel **126** is formed on the rotating shaft **11**. In this way, in the high-speed rotation process of the rotating shaft **11**, the coolant located in the rotating shaft **11** can flow out from a plurality of second shaft holes **112** and enter the second heat dissipation channels **126**, to directly dissipate heat from the rotor core **12**, thereby further improving the heat dissipation efficiency of the wound rotor **10**, and ensuring the stable operation of the motor rotor **100**.

(81) A projection of the second shaft hole **112** of the rotating shaft **11** on the rotor core **12** may be located in the area between the two ends that are of the rotor core **12** and that are in the axial direction. To implement a connection between the second shaft hole **112** and the second heat dissipation channel **126**, a through hole whose two ends are respectively connected to the second shaft hole **112** and the second heat dissipation channel **126** may be provided on the rotor core **12**. In this way, the coolant located in the rotating shaft **11** flows from the second shaft hole **112** into the through hole, and flows into the second heat dissipation channel **126** through the through hole, to exchange heat with the rotor coil **13**. Therefore, direct heat dissipation of the rotor coil **13** is implemented, and heat dissipation of the rotor core **12** can be indirectly performed by using the rotor coil **13**.

(82) In some examples, the projection of the second shaft hole **112** on the rotor core **12** may be alternatively located between the rotor core **12** and the second potting adhesive **171**. For example, the projection of the second shaft hole **112** on the rotor core **12** is located on a left port of a second channel, and the through hole is provided between the left end face of the rotor core **12** and the second potting adhesive **171**. In this way, the coolant in the rotating shaft **11** can flow into the through hole from the second shaft hole **112**, and then flow into the second heat dissipation channel **126** from a left port of the second heat dissipation channel **126**, to directly exchange heat with the rotor core **12**.

(83) During disposition, a quantity of second shaft holes **112** may be equal to or less than a quantity of second heat dissipation channels **126**. For example, when the quantity of second heat dissipation channels **126** is eight, eight second shaft holes **112** may be provided at intervals on the rotating shaft **11** in the circumferential direction. In this way, each second heat dissipation channel **126** corresponds to one second shaft hole **112**, so that the coolant in the rotating shaft **11** flows into a corresponding second heat dissipation channel **126** after being sprayed from each second shaft hole

112 under the action of the centrifugal force. Certainly, when the quantity of second heat dissipation channels **126** is eight, the quantity of second shaft holes **112** may be a proper value, for example, four, five, six, or seven. Further, a disposition quantity of second shaft holes **112** may be adjusted based on an actual size of the rotating shaft **11** and the like.

(84) FIG. **12** is an assembly diagram of the rotating shaft and a second lantern ring in FIG. **1**. Refer to FIG. **3** and FIG. **12**. The second reinforcement assembly **17** in this embodiment of this disclosure further includes a second lantern ring **172** fixedly sleeved on the rotating shaft **11**. The second lantern ring **172** is located on the left end face (as shown in FIG. **9**) of the rotor core **12**, and is disposed between the rotating shaft **11** and the second potting adhesive **171**, to further limit the rotor core **12** in the axial direction of the rotating shaft **11**, thereby ensuring the stability of the rotor core **12** on the rotating shaft **11** in the high-speed rotation process.

(85) The second lantern ring **172** may be fixedly sleeved on the rotating shaft **11** by using a key groove, to ensure that the second lantern ring **172** rotates synchronously with the rotating shaft **11**.

(86) Refer to FIG. **12**. To ensure that the coolant flowing out from the second shaft hole **112** can smoothly enter the second heat dissipation channel **126**, a first annular groove **1721** may be formed between the second lantern ring **172** and the rotating shaft **11**, and the second shaft hole **112** and one end that is of the second heat dissipation channel **126** and that faces the second lantern ring **172** are located in the first annular groove **1721**. In this way, the coolant flowing out from the second shaft hole **112** first enters the first annular groove **1721**, and the coolant smoothly enters the second heat dissipation channel **126** in a buffer process of the first annular groove **1721**, thereby avoiding a loss of the coolant in a process of flowing into the second heat dissipation channel **126**.

(87) The first annular groove **1721** may be formed in the following two manners: Refer to FIG. **5** and FIG. **12**. In a first feasible implementation, a boss **114** may be formed on a periphery of the rotating shaft **11**. The boss **114** is located on one side that is of the second shaft hole **112** and that is away from the rotor core **12**, a part of the second lantern ring **172** is fastened to the boss **114**, the other part of the second lantern ring **172** extends over the second shaft hole **112**, and the part that is of the second lantern ring **172** and that is above the second shaft hole **112**, an outer wall of the rotating shaft **11**, and a sidewall of the boss **114** jointly enclose to form the first annular groove **1721**.

(88) In a second feasible implementation, the first annular groove **1721** may be directly disposed on an inner side that is of the second lantern ring **172** and that faces the rotating shaft **11**, and both the second shaft hole **112** and the left port of the second heat dissipation channel **126** are accommodated in the first annular groove **1721**, to ensure that the coolant flowing out from the second shaft hole **112** can be distributed into each second heat dissipation channel **126**.

(89) Refer to FIG. **8**. In this embodiment of this disclosure, a second outlet channel **127** connected to the outside of the rotor core **12** may be formed between the first potting adhesive **161** and the first end plate **14**.

(90) FIG. **13** is a schematic diagram of a structure of the first lantern ring in FIG. **10**. Refer to FIG. **9**, FIG. **10**, and FIG. **13**. In this embodiment of this disclosure, when being assembled, the first lantern ring **162** is disposed on the right end face of the rotor core **12** and is located at a right port of the second heat dissipation channel **126**. In this embodiment of this disclosure, a perforative hole **1622** is formed on the first lantern ring **162** in an extension direction of the rotating shaft **11**, and two ends of the perforative hole **1622** are respectively connected to the second heat dissipation channel **126** and the second outlet channel **127**. In this way, the coolant flowing out from the right port of the second heat dissipation channel **126** enters the second outlet channel **127** through the perforative hole **1622** of the first lantern ring **162**, and is finally drained to the outside of the rotor core **12**.

(91) In addition, the second outlet channel **127** connected to the outside is formed between the first potting adhesive **161** and the first end plate **14**, to ensure that the coolant flowing out from the second heat dissipation channel **126** can smoothly flow to the outside of the rotor core **12**, so that

disposition of the second outlet channel **127** is more convenient and faster, thereby improving the manufacturing efficiency of the wound rotor **10**. In addition, the coolant flows in from the left port of the second heat dissipation channel **126**, and flows out from the right port of the second heat dissipation channel **126**, to further lengthen the flow path of the coolant in the rotor core **12**, thereby improving the heat dissipation efficiency of the coolant to the rotor core **12**.

(92) Certainly, when the first lantern ring **162** is located between the right port of the second heat dissipation channel **126** and the rotating shaft **11**, and the first potting adhesive **161** is disposed at the right port of the second heat dissipation channel **126**, the perforative hole **1622** may be directly provided on the first potting adhesive **161**, to ensure that the coolant flowing out from the second heat dissipation channel **126** enters the second outlet channel **127** between the first potting adhesive **161** and the first end plate **14**, and then is discharged to the outside of the rotor core **12**.

(93) Refer to FIG. **6** and FIG. **10**. A quantity of perforative holes **1622** on the first lantern ring **162** may be less than the quantity of second heat dissipation channels **126**. For example, when the quantity of second heat dissipation channels **126** is eight, the quantity of perforative holes **1622** may be a proper value, for example, four, five, or six. In this way, a manufacturing process of the first lantern ring **162** is simplified, and flow efficiency of the coolant entering the second outlet channel **127** from the second heat dissipation channel **126** is reduced, so that the coolant flowing out from the perforative hole **1622** can gradually dissipate heat from the first end plate **14**. That is, contact duration between the coolant and the first end plate **14** is prolonged, so that a heat dissipation effect, on the first end plate **14**, of the coolant flowing out from the second heat dissipation channel **126** is improved.

(94) Still refer to FIG. **13**. Optionally, a second annular groove **1623** surrounding the rotating shaft **11** is disposed on one side that is of the first lantern ring **162** and that faces the second heat dissipation channel **126**, and the perforative hole **1622** on the first lantern ring **162** is located in the second annular groove **1623**. In this way, the coolant flowing out from each second heat dissipation channel **126** can smoothly enter the perforative hole **1622** in a buffer process of the second annular groove **1623**, thereby reducing a loss of the coolant in a flow process of flowing into the perforative hole **1622** from the second heat dissipation channel **126**.

(95) In this embodiment of this disclosure, the second outlet channel **127** and the first radial channel **124** are disposed in a staggered manner. For example, refer to FIG. **10**. The perforative hole **1622** connected to the second outlet channel **127** and the drainage groove **1621** on the first lantern ring **162** are disposed in a staggered manner. In this way, a flow path of the first heat dissipation channel **123** and a flow path of the second heat dissipation channel **126** are independent of each other. That is, after exchanging heat with the rotor core **12**, the coolant can be directly discharged to the outside of the rotor core **12** after entering the second outlet channel **127** without entering the first heat dissipation channel **123** through the first radial channel **124**, so that heated coolant is prevented from affecting the heat dissipation effect on the rotor coil **13**. In addition, at least a part of the coolant entering the first radial channel **124** from the first shaft hole **111** is prevented from flowing out from the second outlet channel **127** to the outside of the rotor core **12** before entering the first heat dissipation channel **123**, so that normal heat dissipation of the wound rotor **10** is prevented from being affected.

(96) FIG. **14** is an assembly diagram of the first end plate and the excitation module in FIG. **2**. Refer to FIG. **8** and FIG. **14**. In this embodiment of this disclosure, during disposition, the second outlet channel **127** may include a heat dissipation groove **141** formed on one side that is of the first end plate **14** and that faces the first potting adhesive **161**. In this way, the coolant flowing out from the perforative hole **1622** enters the heat dissipation groove **141**, and is drained to the outside of the rotor core **12** through the heat dissipation groove **141**, so that a structure of the second outlet channel **127** is simplified, disposition of the second outlet channel **127** is more convenient and faster, and a contact area between the coolant and the first end plate **14** is increased. Therefore, the coolant flowing out from the second heat dissipation channel **126** to the second outlet channel **127**

can effectively dissipate heat from the first end plate **14**.

(97) During disposition, the heat dissipation groove **141** may have a plurality of bent parts in a radial direction of the first end plate **14**, to lengthen a length of the heat dissipation groove **141**, thereby increasing the contact area between the coolant and the first end plate **14**, and improving a heat dissipation effect on the first end plate **14**.

(98) FIG. **15** is a schematic diagram of a partial structure of FIG. **11**. Refer to FIG. **3**, FIG. **9**, and FIG. **15**. The wound rotor **10** in this embodiment of this disclosure may further include a second end framework **173** sleeved on the second lantern ring **172**, and the second end framework **173** is located between the second potting adhesive **171** and the rotor core **12**. For example, the second end framework **173** is fastened to one end that is of the rotor core **12** and that faces the second potting adhesive **171**, that is, fastened to the left end face of the rotor core **12**.

(99) An avoidance port **1734** is formed at a position that is of the second end framework **173** and that corresponds to the winding hole **128**. Each rotor coil **13** passes through the avoidance port **1734**, and is wound on one side that is of the second end framework **173** and that is away from the rotor core **12**. In this way, when being an electrical-insulating material, the second end framework **173** can play a role of insulation between the rotor coil **13** and an end part of the rotor core **12**.

(100) It may be understood that a size of each avoidance port **1734** is the same as a size of the winding hole **128**, so that when two adjacent rotor coils **13** pass through the avoidance port **1734**, a gap can be reserved between the two adjacent rotor coils **13** for the coolant to flow. In some examples, a top part of the avoidance port **1734** may penetrate through an outer edge of the second end framework **173**, to facilitate disposition of the avoidance port **1734**.

(101) For ease of disposition, the second end framework **173** may include a second annular connection part **1731** sleeved on the second lantern ring **172**, and a plurality of second insulation parts **1732** extend at intervals from the second annular connection part **1731** in a direction away from the second lantern ring **172**. The second insulation part **1732** and the second annular connection part **1731** further enhance stability of the rotor core **12** in the axial direction. The second insulation parts **1732** are spaced to form the avoidance port **1734**, and each rotor coil **13** is wound on one side that is of the second insulation part **1732** and that is away from the rotor core **12**, to enter an adjacent winding hole **128** from a left end of a winding hole **128**.

(102) The second annular connection part **1731** may be fixedly sleeved on the second lantern ring **172** by using a key groove, or may be integrated with the second lantern ring **172** as an integral part, to ensure that both the second end framework **173** and the second lantern ring **172** rotate synchronously with the rotating shaft **11**.

(103) During disposition, a part of the second potting adhesive **171** is filled in a gap of the second end framework **173**. For example, when the second end framework **173** includes the second annular connection part **1731** and the second insulation part **1732**, the part of the second potting adhesive **171** is filled between two ends that are of two adjacent second insulation parts **1732** and that are away from the rotating shaft **11**, to enhance structural strength of the second end framework **173**.

(104) In this embodiment of this disclosure, the second end framework **173** is disposed on one end that is of the rotor core **12** and that is close to the second potting adhesive **171**, that is, the left end face of the rotor core **12**, to further enhance structural strength of the other end of the rotor core **12**, and enhance the stability of the rotor core **12** in the axial direction of the rotating shaft **11**.

(105) Refer to FIG. **15**. A second limiting part **1733** may extend, in a direction away from the rotor core **12**, from one end that is of the second end framework **173** and that is away from the rotating shaft **11**. For example, the second limiting part **1733** is disposed at one end that is of each second insulation part **1732** of the second end framework **173** and that is away from the second annular connection part **1731**, and the second limiting part **1733** extends to one side away from the rotor core **12** in the axial direction. A part that is of each rotor coil **13** and that passes through the second end framework **173** is located between the second limiting part **1733** and the rotating shaft **11**, to limit movement of the rotor coil **13** in a direction perpendicular to the rotating shaft **11**, thereby

improving stability of the rotor coil **13** in the radial direction.

(106) During disposition, each part of the second end framework **173** may be an integral part formed integrally, so that the structural strength of the wound rotor **10** is enhanced, and an assembly process of the wound rotor **10** is simplified. Certainly, in another possible example, in the second end framework **173**, the second limiting part **1733** and the second insulation part **1732** or the second insulation part **1732** and the second annular connection part **1731** can be connected in a clamping manner, a bonding manner, or the like. A disposition manner of the second end framework **173** is not limited herein.

(107) Refer to FIG. **3** and FIG. **9**. The first reinforcement assembly **16** in this embodiment of this disclosure may further include a first end framework **163** sleeved on the first lantern ring **162**, and the first end framework **163** is located between the first potting adhesive **161** and the rotor core **12**. For example, the first end framework **163** is fastened to one end that is of the rotor core **12** and that faces the first potting adhesive **161**, that is, fastened to the right end face of the rotor core **12**.

(108) A structure of the first end framework **163** in this embodiment of this disclosure may be disposed the same as a structure of the second end framework **173**. For example, an avoidance port (which is not shown in the figure) is formed at a position that is of the first end framework **163** and that corresponds to the winding hole **128**. Each rotor coil **13** passes through the avoidance port, and is wound on one side that is of the first end framework **163** and that is away from the rotor core **12**. In this way, when being an insulating material, the first end framework **163** can play a role of insulation between the rotor coil **13** and an end part of the rotor core **12**.

(109) It may be understood that a size of each avoidance port is the same as the size of the winding hole **128**, so that when two adjacent rotor coils **13** pass through the avoidance port, a gap can be reserved between the two adjacent rotor coils **13** for the coolant to flow. In some examples, a top part of the avoidance port may penetrate through an outer edge of the first end framework **163**, to facilitate disposition of the avoidance port.

(110) Refer to FIG. **9**. Similar to the structure of the second end framework **173**, the first end framework **163** may include a first annular connection part **1631** sleeved on the first lantern ring **162**, and a plurality of first insulation parts **1632** extend at intervals from the first annular connection part **1631** in a direction away from the first lantern ring **162**. The first insulation parts **1632** and the first annular connection part **1631** further enhance the stability of the rotor core **12** in the axial direction. The first insulation parts **1632** are spaced to form the avoidance port, and each rotor coil **13** is wound on one side that is of the first insulation part **1632** and that is away from the rotor core **12**, to enter an adjacent winding hole **128** from a right end of a winding hole **128**.

(111) The first annular connection part **1631** may be fixedly sleeved on the first lantern ring **162** by using a key groove, or may be integrated with the first lantern ring **162** as an integral part, to ensure that both the first end framework **163** and the first lantern ring **162** rotate synchronously with the rotating shaft **11**.

(112) During disposition, a part of the first potting adhesive **161** is filled in a gap of the first end framework **163**. For example, when the first end framework **163** includes the first annular connection part **1631** and the first insulation part **1632**, the part of the first potting adhesive **161** is filled between two ends that are of two adjacent first insulation parts **1632** and that are away from the rotating shaft **11**, to enhance structural strength of the first end framework **163**.

(113) In this embodiment of this disclosure, the first end framework **163** is disposed on one end that is of the rotor core **12** and that is close to the first potting adhesive **161**, that is, the right end face of the rotor core **12**, to further enhance structural strength of one end of the rotor core **12**, and enhance the stability of the rotor core **12** in the axial direction of the rotating shaft **11**.

(114) Refer to FIG. **8**. A first limiting part **1633** may extend, in a direction away from the rotor core **12**, from one end that is of the first end framework **163** and that is away from the rotating shaft **11**. For example, the first limiting part **1633** is disposed at one end that is of each first insulation part **1632** of the first end framework **163** and that is away from the first annular connection part **1631**,

and the first limiting part **1633** extends to one side away from the rotor core **12** in the axial direction. A part that is of each rotor coil **13** and that passes through the first end framework **163** is located between the first limiting part **1633** and the rotating shaft **11**, to limit the movement of the rotor coil **13** in the direction perpendicular to the rotating shaft **11**, thereby improving the stability of the rotor coil **13** in the radial direction.

(115) For a disposition manner of the first end framework **163**, directly refer to the content of the second end framework **173**. Details are not described herein again.

(116) Refer to FIG. 2 and FIG. 3. In an optional example, the wound rotor **10** in this embodiment of this disclosure further includes a rotor jacket **18**. The rotor jacket **18** may include a first annular jacket **181** and a second annular jacket **182**. One of the first annular jacket **181** and the second annular jacket **182** is sleeved on a periphery that is of the first reinforcement assembly **16** and that is away from the rotating shaft **11**, and the other of the first annular jacket **181** and the second annular jacket **182** is sleeved on a periphery that is of the second reinforcement assembly **17** and that is away from the rotating shaft **11**, to further enhance the structural strength of the wound rotor **10** in this embodiment of this disclosure, and ensure structural stability of the wound rotor **10** in the high-speed rotation process.

(117) For example, the first annular jacket **181** is sleeved on the first end framework **163** and a periphery that is of the first potting adhesive **161** and that is away from the rotating shaft **11**, and the second annular jacket **182** is sleeved on the second end framework **173** and a periphery that is of the second potting adhesive **171** and that is away from the rotating shaft **11**, to enhance structural strength of peripheries of the two reinforcement assemblies, namely, the first reinforcement assembly **16** and the second reinforcement assembly **17**.

(118) FIG. 16 is an assembly diagram of an excitation module rotor jacket and the wound rotor in FIG. 1. Refer to FIG. 1, FIG. 2, FIG. 15, and FIG. 16. The motor rotor **100** in this embodiment of this disclosure may further include an excitation module **20**. The excitation module **20** includes an excitation module rotor **21** and an excitation module stator **22**. The excitation module rotor **21** is fastened to the rotating shaft **11**. Refer to FIG. 9. Further, the excitation module rotor **21** includes an excitation transformer rotor **211** fixedly sleeved on the rotating shaft **11** and a rectifier board **212** electrically connected to the excitation transformer rotor **211**. The rectifier board **212** is fastened to the first end plate **14**, and the rotor coil **13** is electrically connected to the rectifier board **212**. The rectifier board **212** may be a flexible circuit board integrated with a rectifier diode.

(119) In an actual application, the excitation module stator **22** includes a wireless power transmit end (which is not shown in the figure). The wireless power transmit end may be disposed on a housing of the motor, and the excitation transformer rotor **211** of the excitation module **20** is a wireless power receive end. During operation, the wireless power transmit end transmits an alternating current of a power to the excitation transformer rotor **211** of the excitation module **20**, the excitation transformer rotor **211** adjusts a voltage corresponding to the power to a voltage required by the motor rotor **100**, and then the rectifier board **212** adjusts the alternating current into a direct current, and transmits the direct current to the rotor coil **13** of the motor rotor **100**, to enable the rotor coil **13** to generate a magnetic field.

(120) The wireless power transmit end and the excitation transformer rotor **211** may be disposed in the axial direction of the rotating shaft **11**. For example, the wireless power transmit end of the excitation module stator **22** is located on one side that is of the excitation transformer rotor **211** and that is away from the rectifier board **212**. In some examples, the wireless power transmit end and the excitation transformer rotor **211** may be alternatively disposed in the radial direction of the rotating shaft **11**. For example, the wireless power transmit end is located on one side that is of the excitation transformer rotor **211** and that is away from the rotating shaft **11**. It may be understood that there is a gap between the wireless power transmit end and the excitation transformer rotor **211**, so that it is ensured that the excitation transformer rotor **211** does not affect structural stability of the wireless power transmit end in the high-speed rotation process with the rotating shaft **11**.

(121) In addition, the gap between the wireless power transmit end and the excitation transformer rotor **211** may be further used for heat dissipation.

(122) Refer to FIG. **16**. It should be noted that, in this embodiment of this disclosure, a terminal of the rotor coil **13** is disposed close to the first end plate **14**, and the rectifier board **212** is fastened to the first end plate **14**. In another example, the terminal of the rotor coil **13** may be alternatively disposed close to the second end plate **15**, and the rectifier board **212** is fastened to the first end plate **14**.

(123) Still refer to FIG. **2** and FIG. **15**. The excitation module **20** further includes a third potting adhesive **213**. The excitation transformer rotor **211** is connected to the first end plate **14** by using the third potting adhesive **213**. In this way, connection strength between the excitation transformer rotor **211** and the first end plate **14** is enhanced, thereby improving connection strength between the excitation module **20** and the wound rotor **10**, and ensuring structural stability of the entire motor in a moving process.

(124) In addition, the rectifier board **212** is fastened to the first end plate **14**, so that the coolant in the heat dissipation groove **141** of the first end plate **14** can further dissipate heat from the rectifier board **212**, thereby ensuring stable operation of the rectifier board **212**.

(125) In an actual application, the excitation transformer rotor **211** includes a transformer rotor core **2111** sleeved on the rotating shaft **11** and a transformer rotor coil **2112** wound on the transformer rotor core **2111**. A wireless power transmit end on the stator **200** further provides an alternating current to the transformer rotor coil **2112**. The third potting adhesive **213** is filled in a gap between the transformer rotor core **2111** and the first end plate **14**, to enhance structural strength of the excitation module **20**.

(126) During disposition, the excitation transformer rotor **211** may be assembled on one side that is of the first end plate **14** and that is away from the rotor core **12**, to reserve the second outlet channel **127** and a heat dissipation space on one side that is of the first end plate **14** and that faces the rotor core **12**.

(127) Refer to FIG. **9** and FIG. **16**. The rectifier board **212** may be fastened to one side that is of the first end plate **14** and that is away from the rotor core **12**, and the excitation transformer rotor **211** is disposed on one side that is of the rectifier board **212** and that is away from the first end plate **14**, that is, the rectifier board **212** is located between the first end plate **14** and the excitation transformer rotor **211**, and is located in the third potting adhesive **213**. In this way, components of the excitation module **20** are packaged into an integral structure by using the third potting adhesive **213**, so that the structural strength of the excitation module **20** is enhanced, and assembly between the excitation module **20** and both of the rotating shaft **11** and the wound rotor **10** is more convenient and faster.

(128) In addition, the rectifier board **212** is disposed on the side that is of the first end plate **14** and that is away from the rotor core **12**, to provide a proper disposition space for disposing the heat dissipation groove **141**, and facilitate electrical connection between the rectifier board **212** and the excitation transformer rotor **211**.

(129) FIG. **17** is a schematic diagram of a partial structure of FIG. **16**. Refer to FIG. **17**. When the rectifier board **212** is further electrically connected to the rotor coil **13**, the rectifier board **212** may be connected to the rotor coil **13** in a detachable manner.

(130) For example, a connector may be disposed on one end of the rotor coil **13**, and a pin (for example, a copper column) is disposed on one side of the rectifier board **212**. The pin on the rectifier board **212** is inserted into the connector, so that the rectifier board **212** is electrically connected to the rotor coil **13**. When the rectifier board **212** is disposed on one side that is of the first end plate **14** and that is away from the rotor core **12**, the pin disposed on the rectifier board **212** may pass through the first end plate **14**, and be in electrical contact with the connector on the rotor coil **13**.

(131) In some examples, a lead **131** may be further disposed at one end of the rotor coil **13**, and a

terminal **132** is disposed at one end of the lead **131**. In addition, a bolt hole may be provided on the rectifier board **212**, and the terminal **132** may be fastened to the rectifier board **212** by using a bolt that is disposed in the bolt hole **2121**, to enhance electrical connection stability between the terminal **132** and the rectifier board **212**. It may be understood that when the rectifier board **212** is located on the side that is of the first end plate **14** and that is away from the rotor core **12**, a mounting hole **142** may be provided on the first end plate **14**. The lead **131** and the terminal **132** first pass through the mounting hole **142**, and are electrically connected to the rectifier board **212** by using the bolt.

(132) The rectifier board **212** is connected to the rotor coil **13** in a bolt or pin manner. In this way, the excitation module **20** may be used as a separate component, so that disassembly and replacement between the excitation module **20** and the wound rotor **10** are more convenient and faster.

(133) In another example, the lead **131** of the rotor coil **13** may be alternatively directly welded on the rectifier board **212**, to simplify a connection structure between the rotor coil **13** and the rectifier board **212**, thereby improving assembly efficiency of the entire motor.

(134) In some other examples, the rectifier board **212** may be alternatively fastened to the side that is of the first end plate **14** and that faces the rotor core **12**, and the lead **131** of the rotor coil **13** may be directly fastened to the rectifier board **212** by using the bolt or the like. The lead **131** on the excitation transformer rotor **211** located on the side that is of the first end plate **14** and that is away from the rotor core **12** may pass through the mounting hole **142** on the first end plate **14**, and be electrically connected to the rectifier board **212**.

(135) Refer to FIG. **14**. In an actual application, for a reason, for example, an assembling error of each component of the motor rotor, a case in which the motor rotor **100** moves away from an axis of the rotating shaft **11** in the high-speed rotation process is prone to occur, which affects stability and drive efficiency of the entire motor. Based on this, in this embodiment of this disclosure, a notch (which is not shown in the figure) may be formed on any side of the first end plate **14** or the second end plate **15**, and the notch is disposed at a position that is of the first end plate **14** or the second end plate **15** and that is away from the rotating shaft **11**. A center of gravity of the wound rotor **10** is adjusted by using the notch, to implement a dynamic balance of the entire motor rotor **100**, and ensure that the motor rotor **100** can stably move around the axis of the rotating shaft **11**.

(136) For example, when the rotor core **12**, the first reinforcement assembly **16**, and the like that are sleeved on the rotating shaft **11** are tilted downward to the rotating shaft **11** in the high-speed rotation process, the notch may be disposed on the first end plate **14** or the second end plate **15** below the rotating shaft, to shift the center of gravity of the wound rotor **10** upward, and ensure that the rotor core **12**, the first reinforcement assembly **16**, and the like stably rotate around the axis of the rotating shaft **11**.

(137) Refer to FIG. **17**. To meet a requirement for a notch of a different depth, in this embodiment of this disclosure, an annular boss **143** may be formed on a part of a sidewall that is of the first end plate **14** and that is away from the rotating shaft **11**. For example, the annular boss **143** may be disposed on the side that is of the first end plate **14** and that is away from the rotor core **12**, and the annular boss **143** is disposed at a part of an outer edge that is of the first end plate **14** and that is away from the rotating shaft **11** in the circumferential direction. According to this disposition, a thickness of the part of the outer edge that is of the first end plate **14** and that is away from the rotating shaft **11** can be increased. In this way, the notch is disposed on the annular boss **143**, so that a depth range of the notch can be increased, and a center of gravity adjustment range of the motor rotor **100** can be improved. A thickness of the annular boss may be adjusted based on an actual requirement. This is not limited herein.

(138) It may be understood that the annular boss (which is not shown in the figure) may be alternatively formed on a part of a sidewall that is of the second end plate **15** and that is away from the rotating shaft **11**, and the notch configured to perform center of gravity adjustment is disposed

on the annular boss, to increase the depth range of the notch, and improve the center of gravity adjustment range of the motor rotor **100**.

(139) When the annular boss **143** on the first end plate **14** may be disposed on one side that is of the first end plate **14** and that has the rectifier board **212**, and the rectifier board **212** is located between the rotating shaft **11** and the annular boss **143**, the annular boss **143** can limit the rectifier board **212** in the radial direction, to enhance structural stability of the rectifier board **212** on the first end plate **14**, protect the rectifier board **212**, and avoid scraping damage caused by an external component to the rectifier board **212**.

(140) Refer to FIG. **15** and FIG. **16**. The excitation module **20** may further include an excitation module rotor jacket **215** sleeved on the rotating shaft **11**, and the excitation transformer rotor **211** is sleeved on the excitation module rotor jacket **215**. For example, the transformer rotor core **2111** is sleeved on the excitation module rotor jacket **215**, to enhance connection strength between the excitation transformer rotor **211** and the rotating shaft **11**, thereby ensuring stability of the excitation transformer rotor **211** in the high-speed rotation process of the rotating shaft **11**.

(141) In this embodiment of this disclosure, one end of the third potting adhesive **213** is connected to the excitation module rotor jacket **215**, to further ensure that the components of the excitation module **20** form the integral structure after being packaged by using the third potting adhesive **213**, so that connection strength between the components of the entire excitation module **20** is enhanced, and the integrally modularized excitation module **20** is quickly assembled on the rotating shaft **11** and is fixedly connected to the wound rotor **10**.

(142) To implement effective heat dissipation for the excitation module **20**, a third heat dissipation channel (which is not shown in the figure) that is connected to the first shaft hole **111** may be formed on the first end plate **14** or the excitation module rotor jacket **215** in the axial direction of the rotating shaft **11**. In this way, the coolant flowing out from the first shaft hole **111** can further enter the third heat dissipation channel, to effectively dissipate heat from the excitation module **20**.

(143) For example, a heat dissipation through hole is provided on the first end plate **14** and an inner side that is of the excitation module rotor jacket **215** and that is close to the rotating shaft **11**. The heat dissipation through hole is used as the third heat dissipation channel, one end of the heat dissipation through hole penetrates to the drainage groove **1621** on the first lantern ring **162**, and the other end of the heat dissipation through hole penetrates to one end that is of the excitation module rotor jacket **215** and that is away from the first end plate **14**. In this way, a part of the coolant flowing out from the first shaft hole **111** enters the third heat dissipation channel through the drainage groove **1621**, exchanges heat with the first end plate **14** and the excitation module rotor jacket **215**, and flows out from the end that is of the excitation module rotor jacket **215** and that is away from the first end plate **14** into a gap between the motor rotor **100** and the stator **200**.

(144) Further, a third outlet channel (which is not shown in the figure) may be further formed between one side that is of the first end plate **14** and that faces the excitation transformer rotor **211** and the third potting adhesive **213**. One end of the third outlet channel is connected to the third heat dissipation channel on the first end plate **14**, and the other end of the third outlet channel is connected to an outer edge that is of the first end plate **14** and that is away from the rotating shaft **11**. In this way, the coolant in the third heat dissipation channel can further enter the third outlet channel, to effectively dissipate heat from the side that is of the first end plate **14** and that faces the excitation transformer rotor **211**, the rectifier board **212**, and the third potting adhesive **213**.

(145) In addition, refer to FIG. **2** and FIG. **9**. To improve stability of the excitation transformer rotor **211** in the axial direction, a third lantern ring **214** may be disposed on one side that is of the excitation transformer rotor **211** and that is away from the first end plate **14**, and the third lantern ring **214** is fixedly sleeved on the rotating shaft **11** to block the excitation transformer rotor **211**, thereby further ensuring stability of the excitation module **20** on the rotating shaft **11**.

(146) It should be noted that all of the first potting adhesive **161**, the second potting adhesive **171**, the third potting adhesive **213**, and a fourth potting adhesive **19** in this embodiment of this

disclosure may be replaced with a plastic packaging adhesive, provided that the structural strength of the entire motor rotor **100** can be ensured. For example, refer to FIG. **9** and FIG. **10**. The plastic packaging adhesive is filled in a gap between the first end plate **14** and the rotor core **12**, to enhance connection strength between the rotor core **12** and the first end plate **14**, thereby improving mechanical strength of the entire wound rotor **10**.

(147) FIG. **18** is a schematic diagram of a partial structure of a motor according to an embodiment of this disclosure. Refer to FIG. **18**. An embodiment of this disclosure further provides a motor. The motor includes a stator **200** and the foregoing motor rotor **100**, where the stator **200** is movably sleeved on the periphery of the motor rotor **100**. In an actual application, both the stator **200** and the motor rotor **100** are located in a housing of the motor, where the stator **200** is fastened to an inner wall of the housing, and the motor rotor **100** is movably connected to the inner wall of the housing by using a bearing.

(148) During operation, the excitation module rotor **21** of the excitation module **20** provides a direct current to the rotor coil **13** of the motor rotor **100**, so that the wound rotor **10** generates a stationary magnetic field with constant polarity, and then rotates under the action of a rotating magnetic field of the stator **200**, to drive a load, for example, a wheel, to rotate.

(149) Coolant flowing out from the first outlet channel **125** and the second outlet channel **127** of the motor rotor **100** may flow in a gap between the stator **200** and the motor rotor **100**, thereby implementing heat dissipation on the stator **200**.

(150) In the motor in this embodiment of this disclosure, the motor rotor **100** is disposed in the stator **200**. Compared with air cooling heat dissipation in the conventional technology, heat dissipation efficiency of the motor rotor **100** is effectively improved, a useful life of the motor is prolonged, and stable operation of the motor is ensured. In addition, compared with a conventional motor, an additional heat dissipation fan does not need to be disposed in a heat dissipation structure of the motor in this embodiment of this disclosure, and the winding hole **128** in the rotor core **12** is directly used as the first heat dissipation channel **123**, so that a heat dissipation effect on the motor is improved, a size of the motor is reduced, and a structure of the motor is simplified, thereby improving assembly efficiency of the motor.

(151) An embodiment of this disclosure further provides a vehicle, including at least wheels, a transmission component, and the foregoing motor. The rotating shaft **11** of the motor is connected to the wheels by using the transmission component.

(152) The vehicle provided in this embodiment may be an electric vehicle (EV), a pure electric vehicle/battery electric vehicle (PEV/BEV), a hybrid electric vehicle (HEV), a range extended electric vehicle (REEV), a plug-in hybrid electric vehicle (PHEV), a new energy vehicle (New Energy Vehicle), or the like.

(153) The rotating shaft **11** of the motor is connected to the wheels by using the transmission component. In this way, the rotating shaft **11** of the motor rotates to output power, and the transmission component transmits the power to the wheels, so that the wheels rotate. In this embodiment, it should be noted that a quantity of motors included in the vehicle may be one or two. When the quantity of motors is one, the motor is connected to two front wheels or two rear wheels by using the transmission component. When the motor is connected to the two front wheels by using the transmission component, the front wheels are driving wheels, and the rear wheels are driven wheels. Correspondingly, when the motor is connected to the two rear wheels by using the transmission component, the rear wheels are driving wheels, and the front wheels are driven wheels. When the quantity of motors is two, one of the motors is connected to the two front wheels by using the transmission component, and the other motor is connected to the two rear wheels by using another transmission component.

(154) In the vehicle provided in this embodiment of this disclosure, the motor is used to drive the wheels to rotate. A heat dissipation effect of the motor is good, so that the motor can stably drive the wheels to rotate without affecting normal drive of the wheels due to overheating of the motor,

thereby effectively improving drive efficiency of the vehicle, and reducing drive and heat dissipation energy consumption of the vehicle.

(155) In the descriptions of embodiments of this disclosure, it should be noted that, unless otherwise clearly specified and limited, terms “assemble”, “connected”, and “connection” should be understood in a broad sense. For example, the terms may be used for a fixed connection, an indirect connection through an intermediate medium, an internal connection between two elements, or an interaction relationship between two elements. Persons of ordinary skill in the art may understand specific meanings of the terms in embodiments of this disclosure based on specific cases.

(156) In the specification, claims, and accompanying drawings of embodiments of this disclosure, the terms “first”, “second”, “third”, “fourth”, and so on (if existent) are intended to distinguish between similar objects but do not necessarily indicate a specific order or sequence.

Claims

1. A motor rotor, comprising: a wound rotor comprising: a rotating shaft; a first shaft hole formed on the rotating shaft; a rotor core fixedly sleeved on the rotating shaft; a plurality of rotor coils; winding holes surrounding the rotating shaft and provided at intervals on the rotor core, wherein each winding hole penetrates through two ends that are of the rotor core and that are disposed in an axial direction, wherein each rotor coil is wound on hole walls of two adjacent winding holes, and wherein two adjacent rotor coils share one winding hole; a first heat dissipation channel coupled to the first shaft hole, wherein the first heat dissipation channel comprises a gap formed between two adjacent rotor coils; a plurality of first heat dissipation channels, wherein the first heat dissipation channel is one of the plurality of first heat dissipation channels; a plurality of first shaft holes provided at intervals on the rotating shaft in a circumferential direction, wherein a quantity of the plurality of first shaft holes is equal to or less than a quantity of the plurality of first heat dissipation channels; a first end plate and a second end plate that are respectively disposed at the two ends that are of the rotor core and that are in the axial direction; a first radial channel formed between the rotor core and the first end plate and configured to couple the first shaft hole and the first heat dissipation channel; a first outlet channel formed between the second end plate and the rotor core and coupled to an outside of the rotor core, and wherein the first heat dissipation channel is coupled to the first outlet channel; and a first reinforcement assembly disposed between the first end plate and the rotor core, and wherein the first radial channel is disposed between the first reinforcement assembly and the first end plate.

2. The motor rotor of claim 1, wherein the first reinforcement assembly comprises: a first potting adhesive; and first radial holes surrounding the rotating shaft and provided at intervals on the first potting adhesive, wherein a first radial hole of the plurality of the first radial holes separately extends to the first heat dissipation channel and the first end plate in the axial direction, and wherein the first radial channel comprises at least a part that is of the first radial hole and that extends in a radial direction.

3. The motor rotor of claim 2, wherein a quantity of the first radial holes is equal to the quantity of the plurality of first shaft holes, and wherein each of the first radial holes penetrates to a corresponding first shaft hole in the radial direction.

4. The motor rotor of claim 2, wherein the first reinforcement assembly further comprises a first lantern ring fixedly sleeved on the rotating shaft, wherein the first potting adhesive is disposed on a periphery of the first lantern ring, wherein the first radial channel further comprises drainage grooves that surround the rotating shaft and that are disposed at intervals on the first lantern ring, wherein the drainage grooves are disposed corresponding to the plurality of first shaft holes, wherein a first end of each drainage groove extends to a corresponding first shaft hole, and wherein a second end of the drainage groove is coupled to the first radial hole.

5. The motor rotor of claim 4, wherein the quantity of the plurality of first shaft holes is less than of the quantity of the first radial holes, and wherein one drainage groove is coupled between two adjacent first radial holes.
6. The motor rotor of claim 5, further comprising a gap formed between the first lantern ring and a part that is of the first potting adhesive and that faces each of the drainage grooves, wherein two ends of each gap respectively extend to the first radial holes on two adjacent sides of the drainage groove.
7. The motor rotor of claim 4, wherein the first reinforcement assembly further comprises a first end framework sleeved on the first lantern ring and located between the first potting adhesive and the rotor core, wherein a first avoidance port is formed at a position that is of the first end framework and that corresponds to the winding hole, and wherein each rotor coil passes through the first avoidance port and is wound on one side that is of the first end framework and that is away from the rotor core.
8. The motor rotor of claim 7, wherein a first limiting part extends, in a direction away from the rotor core, from one end that is of the first end framework and that is away from the rotating shaft, and wherein a part that is of each rotor coil and that passes through the first end framework is located between the first limiting part and the rotating shaft.
9. The motor rotor of claim 4, wherein the wound rotor further comprises a second reinforcement assembly disposed between the second end plate and the rotor core, and wherein the first outlet channel is disposed between the second reinforcement assembly and the second end plate.
10. The motor rotor of claim 9, wherein the second reinforcement assembly comprises a second potting adhesive, wherein second radial holes surrounding the rotating shaft are provided at intervals on the second potting adhesive, wherein two ends that are of the second radial hole and that are in the axial direction respectively extend to the first heat dissipation channel and the second end plate, and wherein at least a part that is of the second radial hole and that extends in the radial direction is configured as the first outlet channel.
11. The motor rotor of claim 10, further comprising a plurality of second heat dissipation channels surrounding the rotating shaft and that are disposed at intervals on the rotor core, wherein a second heat dissipation channel of the plurality of second heat dissipation channels is located between the rotating shaft and the first heat dissipation channel, wherein the second heat dissipation channel penetrates through the two ends that are of the rotor core and that are disposed in the axial direction, wherein a second shaft hole coupled to the second heat dissipation channel is formed on the rotating shaft, and wherein the second heat dissipation channel is used for inflow of coolant proximate to the rotating shaft.
12. The motor rotor of claim 11, wherein the second reinforcement assembly further comprises a second lantern ring fixedly sleeved on the rotating shaft and disposed between the rotating shaft and the second potting adhesive, wherein a first annular groove is formed between the second lantern ring and the rotating shaft, and wherein the second shaft hole and one end that is of the second heat dissipation channel and that faces the second lantern ring are located in the first annular groove.
13. The motor rotor of claim 12, further comprising: a second outlet channel coupled to the outside of the rotor core and formed between the first potting adhesive and the first end plate; and a perforative hole formed on the first lantern ring in an extension direction of the rotating shaft, wherein two ends of the perforative hole are respectively coupled to the second heat dissipation channel and the second outlet channel.
14. A motor comprising: a stator; and a motor rotor comprising a wound rotor, wherein the wound rotor comprises: a rotating shaft; a rotor core fixedly sleeved on the rotating shaft; a plurality of rotor coils; a plurality of winding holes surrounding the rotating shaft and provided at intervals on the rotor core, wherein each winding hole penetrates through two ends that are of the rotor core and that are disposed in an axial direction, wherein each rotor coil is wound on hole walls of two

adjacent winding holes, and wherein two adjacent rotor coils share one winding hole; a first shaft hole formed on the rotating shaft; a first heat dissipation channel coupled to the first shaft hole, wherein the first heat dissipation channel comprises a gap formed between two adjacent rotor coils; a plurality of first heat dissipation channels, wherein the first heat dissipation channel is one of the plurality of first heat dissipation channels; a plurality of first shaft holes provided at intervals on the rotating shaft in a circumferential direction, wherein a quantity of the plurality of first shaft holes is equal to or less than a quantity of the plurality of first heat dissipation channels; a first end plate and a second end plate that are respectively disposed at the two ends that are of the rotor core and that are in the axial direction; a first radial channel formed between the rotor core and the first end plate and configured to couple the first shaft hole and the first heat dissipation channel; a first outlet channel formed between the second end plate and the rotor core and coupled to an outside of the rotor core, and wherein the first heat dissipation channel is coupled to the first outlet channel; and a first reinforcement assembly disposed between the first end plate and the rotor core, and wherein the first radial channel is disposed between the first reinforcement assembly and the first end plate, wherein the stator is sleeved on a periphery of the motor rotor, and wherein the motor rotor is movable relative to the stator.

15. A vehicle comprising: at least two wheels; a transmission component; and a motor comprising: a stator; and a motor rotor comprising a wound rotor, wherein the wound rotor comprises: a rotating shaft; a rotor core fixedly sleeved on the rotating shaft; a plurality of rotor coils; a plurality of winding holes surrounding the rotating shaft and provided at intervals on the rotor core, wherein each winding hole penetrates through two ends that are of the rotor core and that are disposed in an axial direction, wherein each rotor coil is wound on hole walls of two adjacent winding holes, and wherein two adjacent rotor coils share one winding hole; a first shaft hole formed on the rotating shaft; and a first heat dissipation channel coupled to the first shaft hole, wherein the first heat dissipation channel comprises a gap formed between two adjacent rotor coils, wherein the stator is movably-sleeved on a periphery of the motor rotor, wherein the motor rotor is movable relative to the stator, and wherein the rotating shaft is coupled to the wheels using the transmission component.

16. The vehicle of claim 15, wherein the wound rotor further comprises: a plurality of first heat dissipation channels, wherein the first heat dissipation channel is one of the plurality of first heat dissipation channels; and a plurality of first shaft holes provided at intervals on the rotating shaft in a circumferential direction, wherein a quantity of the plurality of first shaft holes is equal to or less than a quantity of the plurality of first heat dissipation channels.

17. The vehicle of claim 16, wherein the wound rotor further comprises: a first end plate and a second end plate that are respectively disposed at the two ends that are of the rotor core and that are in the axial direction; a first radial channel formed between the rotor core and the first end plate and configured to couple the first shaft hole and the first heat dissipation channel; and a first outlet channel formed between the second end plate and the rotor core and coupled to an outside of the rotor core, and wherein the first heat dissipation channel is coupled to the first outlet channel.

18. The vehicle of claim 17, wherein the wound rotor further comprises a first reinforcement assembly disposed between the first end plate and the rotor core, and wherein the first radial channel is disposed between the first reinforcement assembly and the first end plate.

19. The vehicle of claim 18, wherein the first reinforcement assembly comprises: a first potting adhesive; and first radial holes surrounding the rotating shaft and provided at intervals on the first potting adhesive, wherein a first radial hole of the plurality of the first radial holes separately extends to the first heat dissipation channel and the first end plate in the axial direction, and wherein the first radial channel comprises at least a part that is of the first radial hole and that extends in a radial direction.

20. The vehicle of claim 19, wherein a quantity of the first radial holes is equal to the quantity of

the plurality of first shaft holes, and wherein each of the first radial holes penetrates to a corresponding first shaft hole in the radial direction.
