

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281683

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Zaniboni; Andrea

OXYGENATOR WITH INTEGRATED PRESSURE SENSOR

Abstract

An oxygenation device for use in connection with extracorporeal blood circulation, the device including a stacked oxygenator housing defining a blood inlet, a blood outlet and a blood flow path between the blood inlet and the blood outlet. The device further includes a plurality of stacked hollow fibers disposed inside the housing and along the blood flow path, the hollow fibers fluidly coupled to a gas inlet port and a gas outlet port. The blood inlet port has a blood inlet lumen fluidly coupled to the blood inlet and includes an inlet housing in fluid communication with the blood inlet lumen, the inlet housing adapted to house an inlet pressure sensor. The blood outlet port has a blood outlet lumen fluidly coupled to the blood outlet and includes an outlet housing in fluid communication with the blood outlet lumen, the outlet housing adapted to house an outlet pressure sensor.

Inventors: Zaniboni; Andrea (Mirandola, IT)

Applicant: CHINABRIDGE (SHENZHEN) MEDICAL TECHNOLOGY CO., LTD.
(Shenzhen, CN)

Family ID: 1000007738363

Appl. No.: 18/601894

Filed: March 11, 2024

Publication Classification

Int. Cl.: A61M1/16 (20060101); A61M1/14 (20060101)

U.S. Cl.:

CPC A61M1/1698 (20130101); A61M1/153 (20220501); A61M1/1625 (20140204);
A61M1/1629 (20140204); A61M2205/18 (20130101); A61M2205/3331 (20130101);
A61M2205/3592 (20130101); A61M2205/583 (20130101); A61M2230/30 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] This disclosure relates to the field of devices for extracorporeal circulation of blood. More specifically, the disclosure relates to some important components of the extracorporeal circuit, such as the sensors, in particular pressure sensors used to measure the blood pressures at various points of the circuit.

BACKGROUND

[0002] Blood extracorporeal circuits may include dual portions of an oxygenator and heat exchanger to exchange oxygen and carbon dioxide between blood and a gas mixture and exchange heat between blood and a heating or cooling fluid through the walls of semipermeable hollow fiber membranes. Such circuits also include other elements like a pump for providing a certain blood flow through the circuit and sensors measuring quantities, among others, like blood pressures, flow rate, temperatures, oxygen saturations and oxygen and carbon dioxide partial pressures. Blood contacts the outside surfaces of the hollow fibers, while the gas mixture and the heating/cooling fluid (e.g., a water solution) are circulated inside the hollow fiber lumens. In the devices using this technology, the hollow fibers may be organized in different ways. They may be in a single or multifilament form which is woven (to form a so-called “wound” oxygenator type) around a core or may be structured in mats wound around a core or stacked in parallel mat layers on top of one another without a core (to form a so-called “stacked” oxygenator type). Various examples of this technology are well known in the technical field. As far as the blood pump it may be of roller, or centrifugal types. In the latter case, the pump rotor may be levitated and kept floating by means of a magnetic field, which results in low friction operation and hence reduced hemolysis rate, particularly necessary in long term perfusion procedures like in ECMO (ExtraCorporeal Membrane Xxygenation), lasting several days, if not a few weeks, of continuous extracorporeal heart/lung support of the patient. In ECMO, very often the extracorporeal circuit needs to be moved with the patient from one hospital department to another and thus it's important that it be as much simplified, compact and lightweight as possible.

[0003] Often measuring sensors are used to keep the process under control, which results in adding to the complexity of the system, particularly when the sensors are reusable and cannot come into direct contact with blood. In the case of reusable pressure sensors, it is necessary to interpose blood catchers, mounted along specific tubing lines derived from the main flow circuit and placed at the pressure measuring points to create small air separation volumes between blood and sensors to prevent blood from touching the sensors. Such a complication is overcome with disposable pressure sensors which are discarded with the entire extracorporeal circuit at the end of the perfusion procedure and are included in expressly made connectors inserted along the main tubing lines to and from the patient, each of them with the sensor area in direct contact with blood by means of a small hole drilled through the tube wall. With them, the complexity is decreased as there are no more derived measuring lines and blood catchers are no more needed. In any case, the pressure sensor connectors are somewhat bulky elements added to the system, requiring a certain space along the tubing in correspondence to the appropriate measuring locations. This may pose circuit layout problems when such a space is not sufficient and may oblige the operator to dispose the sensors away from the oxygenator blood ports, which would result in measuring at locations not ideal for optimally controlling performance of the extracorporeal circuit. Also, electrical connections between the sensors and the remote monitoring unit may present a complexity problem.

SUMMARY

[0004] Embodiments of the present invention include an oxygenation hollow fiber membrane

organized in stacked hollow fiber mat layers with a structure expressly conceived to provide higher-gas exchange efficiency and better oxygenation effect with pressure sensors integrated into the blood inlet and outlet ports.

[0005] The invention here proposed provides increased simplification and compactness to the extracorporeal circuit, obtained by integrating the disposable pressure sensors into the inlet and outlet ports of a stacked oxygenator device. In this way, oxygenator and pressure sensors become one integrated assembly, thus reducing the number of circuit assembling operations and increasing user friendliness during set up and initial prime of the system. In a stacked oxygenator, the pressures are measured in positions that are relatively close, respectively, to the blood inlet and the blood outlet of the gas transfer compartment of the oxygenator. By monitoring these blood inlet and blood outlet pressures, it is possible to receive an early indication of oxygenator malfunction. For instance, a blood pressure drop (given by $\Delta P = P_{in} - P_{out}$, where P_{in} is the pressure measured at the oxygenator blood inlet port and P_{out} is the pressure measured at the oxygenator blood outlet port) increase may be indicative of coagulation starting inside the oxygenator and thus may trigger a series of corrective actions from the operator.

[0006] In other words, such integration provides the oxygenator “true” inlet/outlet pressure and pressure drop values that would not be otherwise obtainable if the two sensors, as is usually the case with would oxygenators, cannot be integrated close to the inlet and outlet blood ports, and thus were connected along the tubing, each of them placed at a certain distance apart from the oxygenator. In such situations, the measured values would in fact be inclusive also of the pressure drops associated with the paths between the sensors and the oxygenator ports. Another advantage of this integration is that it allows rationalized and simplified electrical connections of the pressure sensors to the remote control and monitoring unit which displays and monitors the pressure values. The connection may be realized in various ways, e.g., by two cables (each connected to the electrical socket of each integrated sensor), or by only one cable connected to a single socket wired to both integrated sensors and conveniently placed on the oxygenator housing, or without cables by exploiting a wireless (e.g., Wi-Fi or Bluetooth) connection between oxygenator and remote control and monitoring unit. In the case of connection to the remote control and monitoring unit by one or two cables, the pressure sensor socket(s) may be oriented in any directions with respect to the oxygenator. In the case of wireless connection, a battery-operated transmitter conveniently placed on the oxygenator housing, and wired to both integrated sensors, communicates the measured pressure values by telemetry to the remote control and monitoring unit, thus further increasing the compactness of the system.

[0007] Example 1 is an oxygenation device for use in connection with extracorporeal blood circulation, the device including an oxygenator housing including a blood inlet end cap defining a blood inlet opening, a blood outlet end cap defining a blood outlet and a blood flow path between the blood inlet and the blood outlet; a plurality of stacked, mat layers of hollow fibers disposed inside the housing and along the blood flow path, the hollow fibers fluidly coupled to a gas inlet port and a gas outlet port; a blood inlet port having a blood inlet lumen defining an inlet sensing hole and fluidly coupled to the blood inlet opening of the blood inlet end cap, the blood inlet port including an inlet pressure sensor housing in fluid communication with the blood inlet lumen through the inlet sensing hole, the inlet pressure sensor housing adapted to house an inlet pressure sensor, wherein the inlet sensing hole is disposed less than 3 cm from the blood inlet opening on the blood inlet end cap; and a blood outlet port having a blood outlet lumen fluidly defining an outlet sensing hole and fluidly coupled to the blood outlet opening of the blood outlet end cap, the blood outlet port including an outlet pressure sensor housing in fluid communication with the blood outlet lumen through the outlet sensing hole, the outlet pressure sensor housing adapted to house an outlet pressure sensor; wherein during operation of the oxygenation device, each of the inlet pressure sensor and the outlet pressure sensor are configured to measure an inlet blood pressure and an outlet blood pressure, respectively.

[0008] Example 2 is the device of Example 1, wherein the oxygenator housing defines an oxygenator module and a heat exchanger module, and further wherein the plurality of hollow fibers includes oxygenator fibers associated with the oxygenator module and heat exchanger fibers associated with the heat exchanger module.

[0009] Example 3 is the device of Example 2, wherein the housing further comprises a separation grid or a collection grid positioned between the heat exchanger module and the oxygenator module.

[0010] Example 4 is the device of Example 1 further comprising a remote monitoring unit communicatively coupled to each of the inlet and outlet pressure sensors.

[0011] Example 5 is the device of Example 4 further comprising communication circuitry coupled to each of the inlet and outlet pressure sensors and adapted to communicate with the remote monitoring unit.

[0012] Example 6 is the device of Example 5, wherein the communication circuitry is adapted to communicate with the remote monitoring unit by wireless telemetry.

[0013] Example 7 is the device of Example 1 further comprising electrical terminals mechanically connected to each of the inlet and outlet ports and adapted for coupling at least one of the inlet and outlet pressure sensors with an electrical connector.

[0014] Example 8 is the device of Example 7, wherein the electrical connector is configured to communicatively couple both of the pressure sensors with a remote monitoring unit.

[0015] Example 9 is the device of Example 7 further comprising a second electrical connector and wherein the first electrical connector is adapted to couple the inlet pressure sensor to the remote monitoring unit and the second electrical connector is adapted to couple the outlet pressure sensor to the remote monitoring unit.

[0016] Example 10 is the device of Example 1, wherein the housing is configured such that a gas mixture may enter through the gas inlet port, pass through the plurality of hollow fibers and exit through the gas outlet port.

[0017] Example 11 is the device of Example 1, wherein the housing further defines a fluid inlet port and a fluid outlet port and is configured such that a H/C fluid may pass through the plurality of hollow fibers.

[0018] Example 12 is the device of Example 6, wherein the remote monitoring unit includes a display adapted to display the inlet blood pressure, the outlet blood pressure and a pressure drop based on a difference between the inlet and outlet blood pressures.

[0019] Example 13 is the device of Example 14, wherein the heat exchanger module includes an H/C fluid inlet chamber and an H/C fluid outlet chamber, and the oxygenator module includes a gas inlet port and a gas outlet port.

[0020] Example 14 is an oxygenation system for use in connection with extracorporeal blood circulation, the system comprising: an oxygenator housing including a blood inlet end cap defining a blood inlet opening, a blood outlet end cap defining a blood outlet and a blood flow path between the blood inlet and the blood outlet, the oxygenator housing defining a heat exchanger module and an oxygenator module adjacent the heat exchanger module; a plurality of stacked, mat layers of hollow fibers disposed inside the housing and along the blood flow path, the hollow fibers fluidly coupled to the oxygenator module; a blood inlet port having a blood inlet lumen defining an inlet sensing hole and fluidly coupled to the blood inlet opening of the blood inlet end cap, the blood inlet port including an inlet pressure sensor housing in fluid communication with the blood inlet lumen through the inlet sensing hole, the inlet pressure sensor housing adapted to house an inlet pressure sensor, wherein the inlet sensing hole is disposed less than 3 cm from the blood inlet opening on the blood inlet end cap; a blood outlet port having a blood outlet lumen fluidly defining an outlet sensing hole and fluidly coupled to the blood outlet opening of the blood outlet end cap, the blood outlet port including an outlet pressure sensor housing in fluid communication with the blood outlet lumen through the outlet sensing hole, the outlet pressure sensor housing adapted to house an outlet pressure sensor; and a remote monitoring unit communicatively coupled to the inlet

pressure sensor and outlet pressure sensor, wherein during operation of the oxygenation system, the inlet pressure sensor is configured to generate an inlet blood pressure signal and the outlet pressure sensor is configured to generate an outlet blood pressure signal, and wherein the monitoring unit is configured to receive the inlet blood pressure signal and outlet blood pressure signal and display corresponding blood pressure measurements.

[0021] Example 15 is the system of Example 14, wherein the heat exchanger module includes an H/C fluid inlet chamber and an H/C fluid outlet chamber, and the oxygenator module includes a gas inlet port and a gas outlet port.

[0022] Example 16 is the system of Example 15, wherein the H/C fluid may pass from the H/C fluid inlet chamber through the plurality of hollow fibers and exit to the H/C outlet chamber.

[0023] Example 17 is the system of Example 15, wherein a gas mixture may pass from the gas inlet port through the plurality of fibers and exit through the gas outlet port.

[0024] Example 18 is the system of Example 14, wherein the remote monitoring unit is adapted to communicate with the remote monitoring unit by wireless telemetry.

[0025] Example 19 is the system of Example 14, wherein the remote monitoring unit is adapted to communicate with the remote monitoring unit via electrical connectors mechanically coupled between the inlet and outlet pressure sensors and the remote monitoring unit.

[0026] Example 20 is the system of Example 14, wherein the remote monitoring unit includes a display and an alarm.

[0027] While multiple embodiments are disclosed, still other embodiments of the present invention will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments of the invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] FIG. 1 is a schematic view of a patient undergoing extracorporeal blood circulation.

[0029] FIG. 2 is a schematic front view of an exemplary stacked oxygenator device, which does not include pressure sensors.

[0030] FIG. 3 is a lateral isometric view from the left of the oxygenator device of FIG. 2.

[0031] FIG. 4 is a lateral cross-section of the oxygenator device taken along line A-A of FIG. 2.

[0032] FIG. 5 is an exploded view of the oxygenator device of FIG. 2.

[0033] FIG. 6 is an exploded view of a disposable pressure sensor adapted to be integrated into the blood inlet/outlet ports of FIGS. 2 to 5 oxygenator.

[0034] FIG. 7 is a lateral cross-section of FIGS. 2 to 5 oxygenator with pressure sensors of FIG. 6 integrated into the blood inlet/outlet ports, taken along the line A-A of FIG. 2.

[0035] FIG. 8 is a perspective view of the oxygenator shown in FIG. 7.

[0036] FIG. 9 is a lateral cross-section of a second embodiment of the oxygenator of FIGS. 2 to 5 with pressure sensors of FIG. 6 integrated into the blood inlet/outlet ports, taken along line B-B of FIG. 2.

[0037] FIG. 10 is a perspective view of the oxygenator of FIG. 9.

[0038] FIG. 11 is a perspective view of the oxygenator of FIG. 10, showing a third embodiment of the invention.

[0039] While the invention is amenable to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the invention to the embodiments described. On the contrary, the invention is intended to cover all modifications, equivalents, and alternatives falling within the scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

[0040] The following detailed description is exemplary in nature and is not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the following description provides some practical illustrations for implementing exemplary embodiments of the present invention. Examples of constructions, materials, and/or dimensions are provided for selected elements. Those skilled in the art will recognize that many of the noted examples have a variety of suitable alternatives.

[0041] As the terms are used herein with respect to measurements (e.g., dimensions, characteristics, attributes, components, etc.), and ranges thereof, of tangible things (e.g., products, inventory, etc.) and/or intangible things (e.g., data, electronic representations of currency, accounts, information, portions of things (e.g., percentages, fractions), calculations, data models, dynamic system models, algorithms, parameters, etc.), “about” and “approximately” may be used, interchangeably, to refer to a measurement that includes the stated measurement and that also includes any measurements that are reasonably close to the stated measurement, but that may differ by a reasonably small amount such as will be understood, and readily ascertained, by individuals having ordinary skill in the relevant arts to be attributable to measurement error; differences in measurement and/or manufacturing equipment calibration; human error in reading and/or setting measurements; adjustments made to optimize performance and/or structural parameters in view of other measurements (e.g., measurements associated with other things); particular implementation scenarios; imprecise adjustment and/or manipulation of things, settings, and/or measurements by a person, a computing device, and/or a machine; system tolerances; control loops; machine-learning; foreseeable variations (e.g., statistically insignificant variations, chaotic variations, system and/or model instabilities, etc.); preferences; and/or the like.

[0042] Although illustrative methods may be represented by one or more drawings (e.g., flow diagrams, communication flows, etc.), the drawings should not be interpreted as implying any requirement of, or specific order among or between, various steps disclosed herein. However, certain some embodiments may require certain steps and/or certain orders between certain steps, as may be explicitly described herein and/or as may be understood from the nature of the steps themselves (e.g., the performance of some steps may depend on the outcome of a previous step). Additionally, a “set,” “subset,” or “group” of items (e.g., inputs, algorithms, data values, etc.) may include one or more items, and, similarly, a subset or subgroup of items may include one or more items. A “plurality” means more than one.

[0043] As used herein, the term “based on” is not meant to be restrictive, but rather indicates that a determination, identification, prediction, calculation, and/or the like, is performed by using, at least, the term following “based on” as an input. For example, predicting an outcome based on a particular piece of information may additionally, or alternatively, base the same determination on another piece of information.

[0044] FIG. 1 is a schematic view of an extracorporeal blood circulation system **10** (also referred to herein as an extracorporeal circuit **10**) for supporting a patient **1** requiring extracorporeal blood circulation. In various embodiments, the patient **1** is connected through a first tubing **12** (also called a venous line) to the extracorporeal blood circuit **10** including a pump **15** to cause blood to be transferred from the patient **1**, through the first tubing **12** and **16**, to a mass transfer device **20**, commonly referred to as an oxygenator device **20** (or oxygenator **20**). Note that the oxygenator **20** may include one or both of an oxygenator module and a heat exchanger module.

[0045] The system **10** further includes a second tubing **14** (also called an arterial line) that extends from the oxygenator **20** to the patient **1** for transferring blood that has been circulated within the pump **15** and oxygenator **20** back to the patient **1**. The extracorporeal circuit **10** includes a plurality of sensors which measure parameters like blood pressures, flow rate, temperatures, hematocrit, oxygen saturation and oxygen and carbon dioxide partial pressures of blood, that must be kept under control during the perfusion process. In general, and not exclusively, such sensors may be

located pre- and/or post-oxygenator, depending on whether the quantities must be measured on the venous or the arterial side. In FIG. 1, a group of venous side sensors **17** and a group of arterial side sensors **18** are schematically shown. They may be in direct contact with blood or may measure the quantities from the tubing outside and are electrically connected to a separate and remote control and monitoring unit **21** under operator (e.g., a perfusionist) control by means of an appropriate control system. In various embodiments, oxygen (O₂) and carbon dioxide (CO₂) are exchanged between blood and a gas mixture within the oxygenator device **20**, as will be described further herein. The oxygenator device **20**, in certain embodiments, is also configured for exchanging temperature (hot or cool temperatures) between the blood and heating/cooling (H/C) fluid within the oxygenator device **20**. In some embodiments, the H/C fluid is water or a water solution.

[0046] FIG. 2 is a front view of an exemplary stacked oxygenator device **20** having an oxygenator module (not shown) and a heat exchanger module (not shown). The oxygenator device **20** has an upper portion **26** and a lower portion **28**. In various embodiments, the oxygenator **20** includes a gas inlet port **30** configured for receiving a gas mixture, a gas outlet port **32** configured for exporting a gas mixture, a H/C fluid inlet port **34** for receiving H/C fluid, an H/C fluid outlet port **36** for exporting H/C fluid, a blood inlet port **38** for receiving blood from the patient **1** through the tubing **16**, and a blood outlet port (not shown) for exporting blood from the oxygenator device **20** back to the patient **1** through the tubing **14**. The oxygenator device **20** further includes a venous sampling port **44** and a first purging port **42a**, as will be described further with reference to FIG. 3. In some embodiments, the oxygenator device **20** additionally includes a bracket attachment **46** to allow for attachment and rotation of the oxygenator device **20** from the top. Alternatively, the bracket attachment **46** may also be coupled to the bottom so as to allow attachment and rotation of the oxygenator from the bottom.

[0047] FIG. 3 is a side view, from the left of FIG. 2, of the oxygenator device **20**. As illustrated, the oxygenator device **20** includes a front portion **52** and a rear portion **54**. The front portion **52** includes a blood inlet end cap **56** coupled to a blood inlet port **38** configured for receiving blood from tubing **16** and the rear portion **54** includes a blood outlet end cap **58** coupled to a blood outlet port **40** for providing an exit for the blood to return to the patient **1** through the tubing **14**. Additionally, as illustrated in FIG. 3, the oxygenator device **20** includes the gas inlet port **30** on the side surface of the oxygenator device **20**. The oxygenator device **20** additionally includes a plurality of purging ports **42** including at least the first purging port **42a** and a second purging port **42b**. Purging ports **42a**, **42b** may allow for removal of air during an initial priming phase of the oxygenator device **20** prior to use with the patient. During operation, i.e., when blood and gas flow through the device **20**, the purging ports **42a**, **42b** may be reopened for removing entrapped air from blood. Additionally, the purging ports **42a**, **42b** may be opening after operation of the device **20**, i.e., when blood is no longer flowing through the device **20**, to ensure proper emptying of any blood from the device **20** and returning it to the patient. The oxygenator device **20** may also include a pedestal **59** positioned on a bottom surface of the device **20** for supporting and stabilizing the device **20**, if the bracket attachment **46**, as shown in FIG. 2, is located at the top of the oxygenator. [0048] As previously described with reference to FIG. 2, the oxygenator device **20** includes a front portion **52** and a rear portion **54**. In these embodiments and as illustrated in FIG. 3, the front portion **52** encompasses at least a portion of the heat exchanger module **24** and the rear portion **54** encompasses at least a portion of the oxygenator module **22**.

[0049] FIG. 4 illustrates a lateral cross-section of the oxygenator device **20** taken along line A-A of FIG. 2. In the illustrative embodiment of FIG. 4, the oxygenator device **20** includes the oxygenator module **22** and the heat exchanger module **24** positioned adjacent the oxygenator module **22**. Both modules **22**, **24** are provided with hollow fiber mat layers vertically stacked one adjacent to the other. As shown, the inlet end cap **56** includes an inlet opening **37** coupled to the inlet blood port **38** and the outlet end cap **58** includes an outlet opening **39** coupled to the outlet blood port **40**.

[0050] The heat exchanger module **24** is bordered on a right side, towards the front portion **52** of the oxygenator device **20**, by a blood inlet distribution grid **60**. The blood inlet distribution grid **60** receives the inputted blood from the blood inlet port **38** connected to the inlet opening **37** of the inlet end cap **56** and distributes it within the blood inlet distribution grid **60** before flowing the blood into the heat exchanger module **24**. Heat exchanger module **24** is bordered on the left side, towards the rear portion **54**, by a separation grid **62** which provides a physical separation between the oxygenator module **22** and the heat exchanger module **24** and distributes blood flowing past the heat exchanger module **24** towards the oxygenator module **22**. The heat exchanger module **24** is thus on the opposing side of separation grid **62** relative to the oxygenator module **22** which is positioned further towards the rear portion **54** of the oxygenator device **20**. The heat exchanger module **24** is positioned vertically below an H/C fluid inlet chamber **66** and positioned vertically above the pedestal **59** and an H/C fluid outlet chamber **70**. The oxygenator module **22** is also bordered on the left side, towards rear portion **54** of the oxygenator device **20**, by a blood outlet collection grid **64** which is configured for collecting the blood flowing from the oxygenator module **22** and directing it through the outlet opening **39** of the outlet end cap **58** to the blood outlet port **40**. As illustrated, vertically positioned above the oxygenator module **22** is a gas inlet chamber **68** and the bracket attachment **46**. Vertically positioned below the oxygenator module **22** is the gas outlet chamber **72**.

[0051] Each of the oxygenator module **22** and the heat exchanger module **24** generally include two portions, or two halves. As will be further described below, the oxygenator module **22** has a portion configured for communication with the gas inlet chamber **68** and a portion configured for communication with the gas outlet chamber **72**. Similarly, the heat exchanger module **24** has a portion configured for communication with the H/C fluid inlet chamber **66** and a portion configured for communication with the H/C fluid outlet chamber **70**. As illustrated, the front portion **52** of the oxygenator device **20** includes the blood inlet port **38** and the rear portion **54** of the oxygenator device **20** includes the blood outlet port **40**. As a result of this configuration, when the blood is driven to pass through both the heat exchanger module **24** and the oxygenator module **22** it flows along a blood flow path from the blood inlet port **38** to the blood outlet port **40**, the blood is able to come into contact (by interposition of the appropriate hollow fiber membranes in the heat exchanger module **24** and the oxygenator module **22**), with the fluid mixtures and the gas for sufficient heat and gas exchange.

[0052] FIG. 5 is an exploded view of the oxygenator device **20** illustrating the component assembly within the oxygenator device **20**. As shown, the oxygenator device **20** includes a blood path comprising the blood inlet end cap **56** (with the blood inlet port **38**), the purging port **42a**, the potted body **80**, and the blood outlet end cap **58** (with the blood outlet port **40**) and the purging port **42b**. In various embodiments, the inlet port **38** is a separate component from the inlet end cap **56** and may be coupled or assembled with it by resin casting, such that the internal lumen of the inlet opening **37** is continuous with the internal lumen of the inlet port **38**. Similarly, in various embodiment, the blood outlet port **40** is a separate component from the outlet end cap **58** and may be coupled or assembled with it by resin casting, such that the internal lumen of the outlet opening **39** is continuous with the internal lumen of the outlet port **40**. The potted body **80** includes, embedded all together in one (potted) piece, the blood inlet distribution grid **60**, the heat exchanger module **24**, the separation grid **62**, the oxygenator module **22**, and the blood outlet collection grid **64**. Access for H/C fluid and gas to the inner lumens of the hollow fibers of the heat exchanger **24** and oxygenator **22** is made possible through the hollow fiber open ends on the potted body outer surface.

[0053] In certain embodiments, the blood inlet end cap **56** is provided with a plurality of peripheral cavities **74** that mechanically fit into the corresponding peripheral notches **61** on the blood inlet distribution grid **60** of the potted body **80**. Air tightness between blood inlet end cap **56** and blood inlet distribution grid **60** may be obtained by resin casting along the two circular contact surfaces of

the blood inlet end cap **56** and the blood inlet distribution grid **60**. Similarly, in various embodiments, on the opposite end of the potted body **80**, the blood outlet end cap **58** includes a plurality of peripheral cavities **76** that mechanically fit into the corresponding peripheral notches **65** on the outlet collection grid **64** of the potted body **80**. Air tightness between blood outlet end cap **58** and outlet collection grid **64** is obtained by resin casting along the circular contact surfaces of the blood outlet end cap **58** and outlet collection grid **64**. In this way, the entire blood compartment, including blood inlet end cap **56**, blood outlet end cap **58**, potted body **80** and blood inlet/outlet ports **38** and **40** are joined in one airtight piece.

[0054] During operation, blood enters the oxygenator device **20** through the blood inlet port **38** in a direction orthogonal to the stacked hollow fiber mat layers and continues into the device through the blood inlet opening **37** of the blood inlet end cap **56**, then crosses blood inlet distribution grid **60**, the stacked hollow fiber mat layers forming the heat exchanger module **24**, the separation grid **62**, the stacked hollow fiber mat layers forming the oxygenator **22**, the outlet collection grid **64**, and exits the device in a direction orthogonal to the stacked hollow fiber layers by flowing through the outlet opening **39** of the blood outlet end cap **58** and through the blood outlet port **40**. As shown in FIGS. **3** to **5**, the blood inlet and blood outlet paths (e.g., the ports **38** and **40**) to reach the inside of the oxygenator **20** are quite short. In certain embodiments, the blood inlet distribution grid **60**, the separation grid **62**, and the outlet collection grid **64** are circular plastic parts with relatively large bores (from 1 to 8 mm) throughout their surfaces and are configured for keeping the elements of the heat exchanger module **24** and the oxygenator module **22** in place and assuring an even distribution of blood flowing across them. The remaining parts of the device **20** comprise external housings enclosing the H/C fluid compartment and the gas compartment, i.e., the H/C fluid collector **82** (including the H/C fluid inlet port **34** and the H/C fluid outlet port **36**) and the gas collector **78** (including the gas inlet port **30** and the gas outlet port **32**, as shown in FIG. **2**, and including the bracket attachment **46** and the pedestal **59**).

[0055] As shown in FIG. **5**, the H/C fluid collector **82** is positioned externally over the potted body **80** portion corresponding to the heat exchanger module **24** and assembled to the blood inlet end cap **56** by means of resin casting to air tighten the circular right side of the H/C fluid compartment. The left circular edge of the H/C fluid collector **82** is positioned externally in correspondence of the separation grid **62** and is air tightened to the potting body **80** by resin casting. In this way, the entire H/C fluid compartment is air tightened. The H/C fluid compartment is divided into two halves including an H/C fluid inlet chamber **66** and an H/C fluid outlet chamber **70** (shown in FIG. **4**) by means of two sealing gaskets **56a**, **56b** which are inserted along two alignment features, illustratively two diametrically opposed and longitudinal grooves located on the outer surface of the potted body **80**. The H/C fluid flows inside the H/C fluid compartment to (and from) the heat exchanger module **24** through the gap between the inner surface of the H/C fluid collector **82** and the outer surface of the potted body **80**, thus forming the H/C fluid inlet chamber **66** and the H/C fluid outlet chamber **70** (shown in FIG. **4**).

[0056] Similarly, as shown, the gas collector **78** is positioned externally in correspondence with the outer surface of the potted body **80** relative to the oxygenator module **22** and assembled with the blood outlet end cap **58** by means of resin casting in order to air tighten the left circular side of the gas compartment of the device **20**. The right circular edge of the gas collector **78** is positioned externally next to the H/C fluid collector **82** in correspondence of the separation grid **62** and is air tightened to the potting body **80** by resin casting. In this way, the gas compartment is entirely air tightened. Also, the gas compartment is divided in two halves: a gas inlet chamber **68** and a gas outlet chamber **72** (shown in FIG. **4**) by means of two sealing gaskets **59a**, **59b** which are inserted along two alignment features, illustratively two diametrically opposed and longitudinal grooves located on the outer surface of the potted body **80**. The gas flows to (and from) the oxygenator module **22** through the gas compartment given by the gap between the inner surface of gas collector **78** and outer surface of the potted body **80**, forming the gas inlet chamber **68** and the gas

outlet chamber **72**.

[0057] In some embodiments, the body **80** of the oxygenator device **20** is obtained by stacking circular layers of hollow fiber mats, made, for the oxygenator, of polypropylene, or polymethylpentene and, for the heat exchanger, of polyethylene, or polyurethane, potting it with polyurethane resin and afterwards slicing its outer surface to cut open the fibers lumens so as to allow water and gas circulation inside the fiber lumens. The woven fibers of each layer are alternatively angled vs an alignment direction by an angle α and an angle β disposed on opposite sides of the alignment direction. Angles α and β may be equal, or not, and are each comprised in the range 0 to 25 degrees. To give them a certain structural consistency, the layers are individually and circularly hot sealed on their external circumference. During such an operation, two orienting elements, whose function is to ease the correct stacking of the layers during the subsequent assembly of the body **80** prior to potting, are also hot sealed along the outer circumference of each layer.

[0058] FIG. **6** shows an exploded view of the blood inlet port **38** (or outlet port **40**) adapted to accommodate pressure sensor integration. In various embodiment, the blood port **38** or **40** is separate from the blood end cap (either **56** or **58** shown in FIG. **5**) and assembled to it by resin casting. Note that while further details are provided below with respect to the blood inlet port **38**, the same details also apply in certain embodiments to the blood outlet port **40**.

[0059] The blood inlet port **38** is fluidly coupled to the blood inlet opening of the blood inlet end cap **56** via an inlet port **38a**. As shown, the inlet port **38a** includes a blood inlet lumen **99**. The inlet port **38a** includes an inlet sensing hole **103** in fluid communication with the blood inlet lumen **99**. The inlet port **38** also include an inlet pressure sensor housing **100**. The inlet pressure sensor housing **100** is adapted to accept and support a pressure sensor **101**, such as inlet pressure sensor **101**, which is introduced with the circular sensing element **102** facing, through the inlet sensing hole **103**, the blood flow and being in direct contact with it. The pressure sensor **101** is in fluid communication with the blood inlet lumen **99** through the inlet sensing hole **103**. The pressure sensor **101** can be any type of commercially available devices, like, for instance, Amphenol Nova Sensors NPC **100** or **120** series. In addition to the sensing element **102**, the pressure sensor **101** further includes circuitry for converting the pressure sensed by the sensing element **102** to an appropriate electrical signal.

[0060] While FIG. **6** is shown with respect to an inlet blood port **38**, it could be similarly illustrated with respect to the outlet blood port **40**. For instance, the blood outlet port **40** is fluidly coupled to the blood outlet opening of the blood outlet end cap **58** via an outlet port, which is configured similarly to inlet port **38a**. The blood outlet port includes a blood outlet lumen, configured similarly to lumen **99**. The outlet port includes an outlet sensing hole, which is configured similarly to inlet sensing hole **103**, in fluid communication with the blood inlet lumen. The outlet port **40** also includes an outlet pressure sensor housing, configured similarly to inlet pressure sensor housing **100**. The outlet pressure sensor housing is adapted to accept and support a pressure sensor **101**, such as an outlet pressure sensor, which is introduced with the circular sensing element **102** facing, through the outlet sensing hole, the blood flow and being in direct contact with it. The outlet pressure sensor is in fluid communication with the blood outlet lumen through the outlet sensing hole.

[0061] As shown, the inlet blood port **38a** is configured such that the sensing hole **103** is positioned very proximate to the blood inlet opening **37** on the blood inlet end cap **56**. This proximity is enabled by the structure of the stacked oxygenator where the inlet blood port can be positioned close to the blood entrance into the gas exchange compartment of the oxygenator. In various embodiments, the sensing hole **103** is located at a distance of less than 3 cm from the inlet opening **37**. In other embodiments, the sensing hole **103** is located at a distance of less than 2 cm from the inlet opening **37**. In some embodiments, the sensing hole **103** is located 1.5 cm from the inlet opening **37**. This minimal distance between the sensing hole **103** and the inlet opening **37**,

substantially reduces the pressure drop or loss associated with the flow through the inlet blood port between the inlet opening the pressure sensor. This, in turn, allows the pressure sensor to measure a more accurate reading of the pressure at the inlet (or outlet) to the end caps, thereby allowing for a more accurate determination of the pressure drop across the device.

[0062] In certain embodiments, the pressure sensor **101**, including the sensing element **102**, is assembled and sealed to the blood port by resin casting to prevent blood leaks and is electrically connected by means of wires (not shown) to the board **104**, which includes terminals for electrically coupling to a cable or wireless transmission system. The board **104** is assembled to the covers **106** and **107** using the four screws **105**. The outside cover **106**, which houses the board **104** and screws **105** is glued and sealed to the blood port where the pressure sensor **101** has already been encased. The pins of the electrical connector **108** can be introduced into corresponding openings in the covers **106** and **107** and can contact the electrical terminals of the board **104** to which the wires to the pressure sensor **101** are connected. While the electrical connector **108** is shown in a particular orientation in FIG. 6, in other embodiments, the electrical connector **108** may be oriented in any direction with respect to the blood ports **38a**, **40a**.

[0063] FIG. 7 is a cross-section, along the line A-A in FIG. 2, of a first embodiment of this application showing a stacked oxygenator of the type described in FIGS. 2 to 5 with the pressure sensors integrated in the blood inlet and outlet ports and connected by means of two separate cables to the remote control and monitoring unit **21**. While the connectors and cables are shown in a particular orientation in FIG. 7, these components may be oriented in any other direction. One of the two cables, the inlet pressure cable **110** is shown in FIG. 7. An end of the cable **110** is inserted into the connector **108a** of the integrated inlet port pressure sensor. Also, the oxygenator is shown with the bracket attachment **46** located at the bottom (as opposed to the top position shown in FIGS. 2 to 5). In FIG. 7 the pressure sensing hole **103** (for the blood inlet port **38a**) is visible. For the blood outlet port **40a**, the integrated pressure sensor is not visible.

[0064] FIG. 8 is a perspective view of the oxygenator shown in FIG. 7. The two electrical cables **110** (for the inlet pressure sensor) and **111** (for the outlet pressure sensor) are disconnected from the two pressure sensors **108a** and **108b**, respectively integrated into the inlet port **38a** and outlet port **40a**. They transfer the pressure signals to the remote control and monitoring unit **21**.

[0065] FIGS. 9 and 10 are respectively a cross-sectional view along line B-B in FIG. 2, and a perspective view of a second embodiment of this application showing the oxygenator described in FIGS. 2 to 5 with the pressure sensors integrated in the blood inlet and outlet ports and connected by means of a single cable to the remote monitoring unit. Such an embodiment provides further simplification and compactness to the whole oxygenator device compared to the one presented in FIGS. 7 and 8. The two blood ports **38a** and **40a** integrate the two pressure sensors **108a** and **108b** now oriented to present the sensing holes **103** in the lower half of the two port internal lumens. The sensor wires travel following either a hidden dotted path inside the channel **112** (and corresponding **113** on the outlet port) and **120** (and correspondingly on the outlet side of the oxygenator, not visible in FIG. 10) or a visible printed circuit board (e.g., a Kapton PCB) following the same path to reach the unique female connector pad **125** conveniently placed in a central position on one side of the oxygenator housing. Pad **125** has a terminal connector **127**, which may be oriented in any direction including and in addition to the orientation shown in FIGS. 9 and 10, where the cable can be attached to bring the pressure signals to the remote control and monitoring unit **21**.

[0066] FIG. 11 shows a perspective view of the oxygenator of FIGS. 9 and 10 with a third embodiment including a wireless (e.g., radio-frequency, Bluetooth or Wi-Fi) connection between the sensors and the remote control and monitoring unit. In this case, the pad **125** besides the wiring to the integrated pressure sensors (as already described for FIGS. 9 and 10), includes the battery power supply and the telemetry transmitting circuitry **126** to make it possible the wireless connection to the remote control and monitoring unit **21**. This embodiment provides further simplification to the sensor/oxygenator integration.

[0067] Once the pressure signals from the sensors reach the remote control and monitoring unit they may be displayed in mmHg (which is the most commonly used unit in cardiac surgery or ECMO applications), shown on a screen in numerical, or graphical form and compared with limits set by the operator, or fixed by the system. If such limits are exceeded, audible and visual alarms may be switched on to attract the operator attention who may decide to start corrective actions. Inlet/outlet pressure values may also be shown as difference between them (i.e., as a pressure drop, DeltaP). The pressure drop value may be monitored by activating an alarm, in case it exceeds a set value. It may also be factored into an appropriate functionality of the remote control and monitoring unit to automatically act on the pump speed (i.e., revolutions per minute) so as to maintain the blood flow rate at a constant set value.

[0068] Various modifications and additions can be made to the exemplary embodiments discussed without departing from the scope of the present invention. For example, while the embodiments described above refer to particular features, the scope of this invention also includes embodiments having different combinations of features and embodiments that do not include all of the described features. Accordingly, the scope of the present invention is intended to embrace all such alternatives, modifications, and variations as fall within the scope of the claims, together with all equivalents thereof.

Claims

1. An oxygenation device for use in connection with extracorporeal blood circulation, the device comprising: an oxygenator housing including a blood inlet end cap defining a blood inlet opening, a blood outlet end cap defining a blood outlet and a blood flow path between the blood inlet and the blood outlet; a plurality of stacked, mat layers of hollow fibers disposed inside the housing and along the blood flow path, the hollow fibers fluidly coupled to a gas inlet port and a gas outlet port; a blood inlet port having a blood inlet lumen defining an inlet sensing hole and fluidly coupled to the blood inlet opening of the blood inlet end cap, the blood inlet port including an inlet pressure sensor housing in fluid communication with the blood inlet lumen through the inlet sensing hole, the inlet pressure sensor housing adapted to house an inlet pressure sensor, wherein the inlet sensing hole is disposed less than 3 cm from the blood inlet opening on the blood inlet end cap; and a blood outlet port having a blood outlet lumen fluidly defining an outlet sensing hole and fluidly coupled to the blood outlet opening of the blood outlet end cap, the blood outlet port including an outlet pressure sensor housing in fluid communication with the blood outlet lumen through the outlet sensing hole, the outlet pressure sensor housing adapted to house an outlet pressure sensor; wherein during operation of the oxygenation device, each of the inlet pressure sensor and the outlet pressure sensor are configured to measure an inlet blood pressure and an outlet blood pressure, respectively.
2. The device of claim 1, wherein the oxygenator housing defines an oxygenator module and a heat exchanger module, and further wherein the plurality of hollow fibers includes oxygenator fibers associated with the oxygenator module and heat exchanger fibers associated with the heat exchanger module.
3. The device of claim 2, wherein the housing further comprises a separation grid or a collection grid positioned between the heat exchanger module and the oxygenator module.
4. The device of claim 1 further comprising a remote monitoring unit communicatively coupled to each of the inlet and outlet pressure sensors.
5. The device of claim 4 further comprising communication circuitry coupled to each of the inlet and outlet pressure sensors and adapted to communicate with the remote monitoring unit.
6. The device of claim 5, wherein the communication circuitry is adapted to communicate with the remote monitoring unit by wireless telemetry.
7. The device of claim 1 further comprising electrical terminals mechanically connected to each of

the inlet and outlet ports and adapted for coupling at least one of the inlet and outlet pressure sensors with an electrical connector.

8. The device of claim 7, wherein the electrical connector is configured to communicatively couple both of the pressure sensors with a remote monitoring unit.

9. The device of claim 7 further comprising a second electrical connector and wherein the first electrical connector is adapted to couple the inlet pressure sensor to the remote monitoring unit and the second electrical connector is adapted to couple the outlet pressure sensor to the remote monitoring unit.

10. The device of claim 1, wherein the housing is configured such that a gas mixture may enter through the gas inlet port, pass through the plurality of hollow fibers and exit through the gas outlet port.

11. The device of claim 1, wherein the housing further defines a fluid inlet port and a fluid outlet port and is configured such that a H/C fluid may pass through the plurality of hollow fibers.

12. The device of claim 6, wherein the remote monitoring unit includes a display adapted to display the inlet blood pressure, the outlet blood pressure and a pressure drop based on a difference between the inlet and outlet blood pressures.

13. The device of claim 6, wherein the remote monitoring unit includes an alarm configured to alert a user upon any of the inlet blood pressure, the outlet blood pressure and a difference between the inlet and outlet blood pressure achieving a certain set value.

14. An oxygenation system for use in connection with extracorporeal blood circulation, the system comprising: an oxygenator housing including a blood inlet end cap defining a blood inlet opening, a blood outlet end cap defining a blood outlet and a blood flow path between the blood inlet and the blood outlet, the oxygenator housing defining a heat exchanger module and an oxygenator module adjacent the heat exchanger module; a plurality of stacked, mat layers of hollow fibers disposed inside the housing and along the blood flow path, the hollow fibers fluidly coupled to the oxygenator module; a blood inlet port having a blood inlet lumen defining an inlet sensing hole and fluidly coupled to the blood inlet opening of the blood inlet end cap, the blood inlet port including an inlet pressure sensor housing in fluid communication with the blood inlet lumen through the inlet sensing hole, the inlet pressure sensor housing adapted to house an inlet pressure sensor, wherein the inlet sensing hole is disposed less than 3 cm from the blood inlet opening on the blood inlet end cap; a blood outlet port having a blood outlet lumen fluidly defining an outlet sensing hole and fluidly coupled to the blood outlet opening of the blood outlet end cap, the blood outlet port including an outlet pressure sensor housing in fluid communication with the blood outlet lumen through the outlet sensing hole, the outlet pressure sensor housing adapted to house an outlet pressure sensor; and a remote monitoring unit communicatively coupled to the inlet pressure sensor and outlet pressure sensor, wherein during operation of the oxygenation system, the inlet pressure sensor is configured to generate an inlet blood pressure signal and the outlet pressure sensor is configured to generate an outlet blood pressure signal, and wherein the monitoring unit is configured to receive the inlet blood pressure signal and outlet blood pressure signal and display corresponding blood pressure measurements.

15. The system of claim 14, wherein the heat exchanger module includes an H/C fluid inlet chamber and an H/C fluid outlet chamber, and the oxygenator module includes a gas inlet port and a gas outlet port.

16. The system of claim 15, wherein the H/C fluid may pass from the H/C fluid inlet chamber through the plurality of hollow fibers and exit to the H/C outlet chamber.

17. The system of claim 15, wherein a gas mixture may pass from the gas inlet port through the plurality of fibers and exit through the gas outlet port.

18. The system of claim 14, wherein the remote monitoring unit is adapted to communicate with the remote monitoring unit by wireless telemetry.

19. The system of claim 14, wherein the remote monitoring unit is adapted to communicate with

the remote monitoring unit via electrical connectors mechanically coupled between the inlet and outlet pressure sensors and the remote monitoring unit.

20. The system of claim 14, wherein the remote monitoring unit includes a display and an alarm.
