

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282439

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

MONINGER; BENJAMIN D. et al.

ELECTRIC VEHICLE FRAME FOR MOUNTING HIGH-CAPACITY BATTERY

Abstract

A vehicle frame for a vehicle is provided for mounting a high-capacity battery. The vehicle frame includes a lower mount structure coupled to a lower portion of the vehicle frame. The vehicle frame further includes an upper mount structure coupled to an upper portion of the vehicle frame. The lower mount structure and the upper mount structure are configured to receive a battery unit in a space formed between the lower mount structure and the upper mount structure, such that the battery unit is slidably disposed in an inclined position in the space.

Inventors: MONINGER; BENJAMIN D. (MARYSVILLE, OH), RITCHIE; SETH A. (MARYSVILLE, OH), KLUCHAR; MICHAEL JOSEPH (PLAIN CITY, OH)

Applicant: Honda Motor Co., Ltd. (Tokyo, JP)

Family ID: 96948498

Appl. No.: 18/596411

Filed: March 05, 2024

Publication Classification

Int. Cl.: B62J43/28 (20200101); B62J1/08 (20060101); B62J43/16 (20200101); B62K5/01 (20130101)

U.S. Cl.:

CPC B62J43/28 (20200201); B62J1/08 (20130101); B62J43/16 (20200201); B62K5/01 (20130101);

Background/Summary

BACKGROUND

[0001] A development of safe battery mounting techniques is required when integrating electric vehicle (EV) technology into powersports like all-terrain vehicles (ATVs). Because of their size, batteries need to be positioned differently than gasoline fuel and take up more space. This necessitates a mounting solution that integrates multiple vehicle functions that can hold a large battery. The structure also needs to be strong enough to endure the rigors of off-road driving.

[0002] Limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of described systems with few aspects of the present disclosure, as set forth in the remainder of the present application and with reference to the drawings.

SUMMARY

[0003] According to an embodiment of the disclosure, a vehicle frame for a vehicle may be provided to mount a high-capacity battery. The vehicle frame may include a lower mount structure that may be coupled to a lower portion of the vehicle frame. The vehicle frame may further include an upper mount structure that may be coupled to an upper portion of the vehicle frame. Further, the lower mount structure and the upper mount structure may be configured to receive a battery unit in a space that may be formed between the lower mount structure and the upper mount structure such that the battery unit may be slidably disposed in an inclined position in the space.

[0004] According to another embodiment of the disclosure, a battery mounting structure for a vehicle may be provided to mount a high-capacity battery. The battery mounting structure may include a lower mount structure that may be coupled to a lower portion of the vehicle frame. The battery mounting structure may further include an upper mount structure that may be coupled to an upper portion of the vehicle frame. Further, the lower mount structure and the upper mount structure may be configured to receive a battery unit in a space that may be formed between the lower mount structure and the upper mount structure such that the battery unit may be slidably disposed in an inclined position in the space.

[0005] According to another embodiment of the disclosure, a method of assembling a vehicle frame for a vehicle may be provided to mount a high-capacity battery. The method may include coupling a lower mount structure to a lower portion of a vehicle frame and coupling an upper mount structure to an upper portion of the vehicle frame. Further, the lower mount structure and the upper mount structure may be configured to receive a battery unit in a space that may be formed between the lower mount structure and the upper mount structure such that the battery unit may be slidably disposed in an inclined position in the space.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is a diagram that illustrates an exemplary vehicle frame for a vehicle, in accordance with an embodiment of the disclosure.

[0007] FIG. 2A is a diagram that illustrates a lower mount structure associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure.

[0008] FIG. 2B is a diagram that illustrates an upper mount structure associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure.

[0009] FIG. 3 is a diagram that illustrates a shock absorber associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure.

[0010] FIGS. 4A and 4B are scenario diagrams that collectively illustrate configuration of an upper mount structure in a stowed and an un-stowed configuration to control access to a battery unit associated with a vehicle, in accordance with an embodiment of the disclosure.

[0011] FIG. 5 is a flowchart that illustrates an exemplary method of assembling a vehicle frame for

a vehicle, in accordance with an embodiment of the disclosure.

[0012] The foregoing summary, as well as the following detailed description of the present disclosure, is better understood when read in conjunction with the appended drawings. To illustrating the present disclosure, exemplary constructions of the preferred embodiment are shown in the drawings. However, the present disclosure is not limited to the specific methods and structures disclosed herein. The description of a method step or a structure referenced by a numeral in a drawing is applicable to the description of that method step or structure shown by that same numeral in any subsequent drawing herein.

DETAILED DESCRIPTION

[0013] Various embodiments of the present disclosure may be found in a vehicle frame for a vehicle. The disclosed vehicle frame may include a lower mount structure that may be coupled to a lower portion of the vehicle frame. The vehicle frame may further include an upper mount structure that may be coupled to an upper portion of the vehicle frame. Further, the lower mount structure and the upper mount structure may be configured to receive a battery unit in a space that may be formed between the lower mount structure and the upper mount structure, such that the battery unit is slidably disposed in an inclined position in the space. The lower mount structure may be configured to support a bottom portion of the battery unit and the upper mount structure may be configured to secure a top portion of the battery unit. The lower mount structure may be coupled to the lower portion of the vehicle frame in the inclined position with respect to a horizontal plane. The inclination of the lower mount structure with respect to the horizontal plane may allow the battery unit to be securely placed in the inclined position.

[0014] The installation of a larger battery pack in off-road electric vehicles, such as electric all-terrain vehicles (ATVs) can cause a number of issues. For example, increased vehicle weight due to a larger battery pack can reduce efficiency, resulting in slower acceleration and poorer handling. Second, the location of the battery pack can affect the vehicle's center of gravity, which can impact drivability. Third, due to the risk of fire and explosion, the battery pack should not be deformed in any way. Finally, larger batteries necessitate more substantial structures/systems, and other components such as brakes, suspension, thermal management, and so on must be designed and reinforced to handle these issues, which add mass and cost to the vehicle.

[0015] To overcome some of the abovementioned issues, the proposed vehicle frame includes a two-part mount structure that is securely placed inside the vehicle frame in an inclined position. The space formed in the two-part mount structure is provided to slidably receive a battery unit (e.g., a larger battery pack that is suitable for electric vehicles), without requiring a disassembly of the vehicle frame or the two-part mount structure. The inclination helps to distribute the weight of the battery unit and eases removal or replacement of the battery unit from the vehicle frame. The structure includes rubber pads at the base portion to absorb the shocks and/or jerks experienced by the vehicle frame and protect the battery unit from any damage caused by the shocks and/or the jerks. A pivot point in the two-part mount structure facilitates access to the battery unit, which is otherwise secured in the space between the two-part mount structure.

[0016] Reference will now be made in detail to specific aspects or features, examples of which are illustrated in the accompanying drawings. Wherever possible, corresponding, or similar reference numbers will be used throughout the drawings to refer to the same or corresponding parts.

[0017] FIG. 1 is a diagram that illustrates an exemplary vehicle frame for a vehicle, in accordance with an embodiment of the disclosure. With reference to the FIG. 1, there is shown a diagram that includes an environment **100**. The environment **100** may include a vehicle frame **102** which includes a lower portion **102A** and an upper portion **102B**. The environment **100** may further include a lower mount structure **104** associated with the lower portion **102A** of the vehicle frame **102**, and an upper mount structure **106** associated with the upper portion **102B** of the vehicle frame **102**. The vehicle frame **102** may further include a battery unit **108** accommodated between the lower mount structure **104** and the upper mount structure **106**.

[0018] The vehicle may be an electric vehicle (EV) or a hybrid vehicle that uses one or more electric motors for propulsion. The vehicle can be powered by a collector system, with electricity from extravehicular sources, or the vehicle can be powered autonomously by a battery, which can be charged by solar panels, or by converting fuel to electricity using fuel cells or a generator. Examples of the vehicle may include, but are not limited to, a three-wheeled vehicle, a four-wheeled vehicle, a hybrid vehicle, or an off-road vehicle (such as an all-terrain vehicle). It should be noted here that the vehicle frame **102** shown in FIG. **1** is associated with an all-terrain vehicle, which uses a battery for propulsion merely as an example. The examples of the all-terrain vehicle may include, but is not limited to, a quad bike or a quad. The vehicle frame **102** may be also applicable to other types of battery electric vehicles, as defined by American National Standard Institute (ANSI). The description of such types of the vehicle has been omitted from the disclosure for the sake of brevity. The vehicle may include a battery mounting structure that may further include the vehicle frame **102**.

[0019] The vehicle frame **102** of the vehicle may be a main support structure of the vehicle which may be configured to bear stresses induced on the vehicle. The vehicle frame **102** may be a load-bearing framework that may structurally support a plurality of vehicle systems, such as, but not limited to, a transmission system, a brake system, a suspension system, or a steering system. For example, the vehicle frame **102** for a quad bike may include components, such as, but not limited, a fuel tank, seat(s), handlebars, two wheels, or a suspension system. The present disclosure may be applicable to the vehicle frame **102** of other types of the all-terrain vehicles (for example, a quad having four wheels). The description of such types of vehicle frame **102** has been omitted from the disclosure for the sake of brevity. The vehicle frame **102** may include a lower portion **102A**, and an upper portion **102B**. By way of example, and not limitation, the lower portion **102A** may be in proximity of a ground surface and the upper portion **102B** may be away from the ground surface.

[0020] The lower mount structure **104** is shown to have a substantially rectangular shape in FIG. **1**. Alternatively, the lower mount structure **104** may be formed to have another shape (for example, a substantially square shape, a substantially circular shape, a substantially semi-circular shape, and the like), without a departure from the scope of the present disclosure. A perspective view of the lower mount structure **104** is shown, for example in FIG. **2A**. The lower mount structure **104** may be coupled to the lower portion **102A** of the vehicle frame **102** and may be configured to receive a bottom portion of the battery unit **108**. In an embodiment, the lower mount structure **104** may be made from high strength and shock absorbent materials (for example, a Polypropylene, a Polyurethane, a Polycarbonate, a Polyamide-imide, and the like) to bear stresses induced on the vehicle frame **102**.

[0021] The upper mount structure **106** is shown to have a substantially tubular structure in FIG. **1**. Alternatively, the lower mount structure **104** may be formed with other cross sections (for example, a substantially square shape, a substantially circular shape, a substantially semi-circular shape, and the like). The upper mount structure **106** may be coupled to the upper portion **102B** of the vehicle frame **102** and may be configured to secure a top portion of the battery unit **108**. In an embodiment, the upper mount structure **106** may be made from high strength and shock absorbent materials (for example, a Polypropylene, a Polyurethane, a Polycarbonate, a Polyamideimide, and the like) to bear stresses induced on the vehicle frame **102**.

[0022] The battery unit **108** may be a rechargeable battery, that is, a source of electric power for one or more electric circuits or loads (not shown) associated with the vehicle. For example, the battery unit **108** may be a source of electrical power for an electronic control unit, a sensor system associated with the vehicle, or an electric motor of the vehicle. In some embodiments, the battery unit **108** may correspond to a battery pack, which may have a plurality of clusters of batteries, surrounded by a suitable coolant and a charge controller (not shown in FIG. **1**). Examples of the battery unit **108** may include, but are not limited to, a lead acid battery, a nickel cadmium battery, a nickel-metal hydride battery, a lithium-ion battery, and other rechargeable batteries.

[0023] The battery mounting structure may include the vehicle frame **102**. The vehicle frame **102** may further include the lower mount structure **104** and the upper mount structure **106**. The lower mount structure **104** may be coupled with the lower portion **102A** of the vehicle frame **102**. The upper mount structure **106** may be coupled with the upper portion **102B** of the vehicle frame **102**. By way of example, but not limitation, the lower portion **102A** of the vehicle frame **102** may be in proximity of the ground surface and the upper portion **102B** of the vehicle frame **102** may be away from the ground surface.

[0024] The lower mount structure **104** and the upper mount structure **106** may be attached to the vehicle frame **102**, using at least one of a bolted joint, a welded joint, or a pivot joint. By way of example, and not limitation, the bolted joint may include a long bolt and a nut. The long bolt may be inserted into a pre-drilled hole provided on the vehicle frame **102**, the lower mount structure **104**, and the upper mount structure **106**. Thereafter, the nut may be tightened onto bolt mating threads provided on the long bolt. The attachment of the lower mount structure **104** and the upper mount structure **106** with the vehicle frame **102** using the bolted joint may ease disassembly of at least one of the lower mount structure **104** or the upper mount structure **106** from the vehicle frame **102**. The welded joint may join the at least one of the lower mount structure **104** or the upper mount structure **106** with the vehicle frame **102**, using a suitable welding process. The attachment of the lower mount structure **104** and the upper mount structure **106** with the vehicle frame **102** using the welded joint may permanently joint at least one of the lower mount structure **104** or the upper mount structure **106** with the vehicle frame **102**. The pivot joint may pivotally couple at least one of the lower mount structure **104** or the upper mount structure **106** with the vehicle frame **102**. The attachment of the lower mount structure **104** and the upper mount structure **106** with the vehicle frame **102** using the pivot joint may ease disassembly of the at least one of the lower mount structure **104** or the upper mount structure **106** from the vehicle frame **102**. Further details related to the pivot joint are provided, for example, in FIGS. 4A and 4B.

[0025] The lower mount structure **104** may receive the bottom portion of the battery unit **108** and the upper mount structure **106** may secure the top portion of the battery unit **108**. The lower mount structure **104** may be coupled to the lower portion **102A** of the vehicle frame **102** in an inclined position with respect to a horizontal plane, which may be configured to secure the battery unit **108** in the inclined position. By way of example, and not limitation, the inclined position of the battery unit **108** may include an inclination angle that may be between a range of about 35 degrees and 45 degrees. A space may be formed between the upper mount structure **106** and the lower mount structure **104**. The space formed by the lower mount structure **104** and the upper mount structure **106** may be large enough to receive the battery unit **108** of a high capacity in the inclined position. The battery unit **108** with high capacity may power the vehicle for longer duration and may be effective for long routes or off-road driving.

[0026] FIG. 2A is a diagram that illustrates a lower mount structure associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure. FIG. 2A is explained in conjunction with elements from FIG. 1. With reference to the FIG. 2A, there is shown a diagram **200A** of the lower mount structure **104**. The lower mount structure **104** may include a four-sided enclosure **202** having a base portion **202A** and four sides **202B**. The lower mount structure **104** may further include a plurality of rubber pads **204**, and a plurality of pores **206**.

[0027] The four-sided enclosure **202** may be configured to receive a bottom portion of the battery unit **108**. The four-sided enclosure **202** may have a substantially rectangular shape or another shape (for example, a substantially square shape, a substantially circular shape, a substantially semi-circular shape, and the like).

[0028] The four-sided enclosure **202** may further include the base portion **202A** and four sides **202B**. The base portion **202A** may be configured to receive the bottom portion of the battery unit **108**. The base portion **202A** may be configured to cover entire surface of the bottom portion and the four sides **202B** may be configured to partially cover the battery unit **108**. By way of example,

and not limitation, the partial covering of the battery unit **108** by the four sides **202B** may be preferred as it may help to reduce cost of manufacturing and weight of the lower mount structure **104**.

[0029] The plurality of rubber pads **204** may be disposed on at least one of the base portion **202A** or on the four sides **202B** of the lower mount structure **104**. The rubber pads **204** may include a steel base bonded to a rubber section. The steel base associated with the rubber pads **204** may be attached to one of the base portion **202A** or on the four sides **202B** of the lower mount structure **104**. The rubber section may be in a direct contact with the bottom portion of the battery unit **108** and may be configured to absorb shock and jerk experienced by the lower mount structure **104** to protect the battery unit **108** from any physical damage. The shock or jerk experienced by the lower mount structure **104** may be due to a vibration in the vehicle frame **102**, a sudden braking, uneven road conditions, or malfunctioning of vehicle components.

[0030] The base portion **202A** of the lower mount structure **104** may include the plurality of pores **206**. The plurality of pores **206** may be configured to allow liquid to drain out of the vehicle frame **102**. By way of example, and not limitation, the lower mount structure **104** may collect liquid (for example, water) due to rain or off-road conditions. For instance, the lower mount structure **104** may collect fluid (for example, muddy water) due to operation of the vehicle on off-road tracks. Therefore, draining out of the liquid from the lower mount structure **104** from the plurality of pores **206** may prevent the vehicle frame **102** and the vehicle components from any water-related damage (such as a short circuit or rust).

[0031] FIG. 2B is a diagram that illustrates an upper mount structure associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure. FIG. 2B is explained in conjunction with elements from FIG. 1 and FIG. 2A. With reference to the FIG. 2B, there is shown a diagram **200B** of the upper mount structure **106**. The upper mount structure **106** may include a battery fixing member **208** having a rubber padding **210**. The upper mount structure **106** may further include a seat mount **212**, a pair of brackets **214**, and a plurality of slots **216**.

[0032] The upper mount structure **106** may include the battery fixing member **208**. The battery fixing member **208** may be configured to secure a top portion of the battery unit **108**. The battery fixing member **208** may have a substantially tubular structure or another shape (for example, a substantially square shape, a substantially circular shape, a substantially semi-circular shape, and the like). The shape and dimensions of the battery fixing member **208** may correspond to that of the battery unit **108**. The battery fixing member **208** may be made from high strength and shock absorbent materials (for example, a Polypropylene, a Polyurethane, a Polycarbonate, a Polyamideimide, and the like) to firmly secure the battery unit **108**. In an embodiment, the battery fixing member **208** may be provided with a plurality of pre-drilled holes to secure the top portion of the battery unit **108** using suitable fasteners such as, a screw, or a nut and bolt.

[0033] The battery fixing member **208** may further include the rubber padding **210**. The rubber padding **210** may include a metallic base bonded to a rubber section. The metallic base associated with the rubber padding **210** may be attached to the battery fixing member **208**. The rubber section may be in a direct contact with the top portion of the battery unit **108** and may be configured to absorb shock and jerk experienced by the upper mount structure **106**. The shock or jerk may be caused by at least one of a vibration in the vehicle frame **102**, a sudden braking, uneven road conditions, or malfunctioning of vehicle components. The shock or jerk may be absorbed by the rubber section of the rubber padding **210** to protect the top portion of the battery unit **108** from any physical wear and tear.

[0034] The upper mount structure **106** may further include the seat mount **212**. The seat mount **212** may be configured to mount a seat associated with the vehicle. In an example embodiment, the seat mount **212** may be a U-shaped transverse section. The inclined position of the battery unit **108** may have an inclination angle that may be based on a position of the seat mount **212**. In case the position of the seat mount **212** is substantially parallel to a horizontal plane, the inclined position of

the battery unit **108** may be substantially parallel to the horizontal plane. For example, if the position of the seat mount **212** is about 30 degrees with respect to the horizontal plane, then the inclined position of the battery unit **108** may be about 30 degrees with respect to the horizontal plane.

[0035] The upper mount structure **106** may further include at least a pair of brackets **214**. The pair of brackets **214** may be configured to mount a tank cover associated with the vehicle. By way of example, and not limitation, the tank cover may be mounted using fasteners, such as a screw, or a nut and bolt. The pair of brackets **214** may have a substantially rectangular shape or may be formed with various other shapes (for example, a substantially square shape, a substantially rectangular shape, and the like).

[0036] The upper mount structure **106** may further include the plurality of slots **216** that may be configured to guide a plurality of electric wires that may connect the battery unit **108** to one or more functional components associated with the vehicle. The plurality of slots **216** may have a substantially rectangular shape or may be formed to have various other shapes (for example, a substantially square shape, a substantially rectangular shape, and the like). The choice of the shape for each slot may be based on a shape of the upper mount structure **106** or other vehicle design requirements.

[0037] FIG. **3** is a diagram that illustrates a shock absorber associated with a battery mounting structure for a vehicle, in accordance with an embodiment of the disclosure. FIG. **3** is explained in conjunction with elements from FIG. **1**, FIG. **2A**, and FIG. **2B**. With reference to FIG. **3** there is shown an exemplary scenario **300** that includes a shock absorber **302** that may be mounted between the lower portion **102A** of the vehicle frame **102** and the base portion **202A** of the lower mount structure **104**.

[0038] The shock absorber **302** may be configured to absorb shock and jerk experienced by the lower portion **102A** of the vehicle frame **102**. Examples of the shock absorber **302** may include, but are not limited to, a spiral spring, a leaf spring, or a coil spring. In certain situations, the lower portion **102A** of the vehicle frame **102** may be experience shocks and jerk, which may compress or rebound a spring associated with the shock absorber **302**. The shocks and jerk experienced by the lower portion **102A** of the vehicle frame **102** may be due to a vibration in the vehicle frame **102**, a sudden braking, a road condition, or a malfunctioning of vehicle components.

[0039] In an exemplary embodiment, the shock absorber **302** may include an air suspension, which may include alteration of stiffness of a spring by adjusting an effective volume of the spring associated with the shock absorber **302**. The adjustment of the effective volume of the spring may be achieved via a solenoid valve to connect the spring to an extra volume (for example, an accumulator). Further, the extra volumes may allow a spring rate to be altered based on the shock and jerk, which may be subjected due to at least one of a vibration in the vehicle frame **102**, a sudden braking, a road condition, or a malfunctioning of vehicle components. To stiffen the spring while the vehicle is cruising at a higher speed on longer routes or over off-road tracks, the solenoid may disconnect the extra volume. In case a softer spring rate is required based on the shock and jerk, the solenoid may connect the extra volume. The shock absorber **302** may absorb the shock and jerk experienced by the lower portion **102A** of the vehicle frame **102** and may limit transmission of the shock and jerk to the base portion **202A** of the lower mount structure **104**. Therefore, the base portion **202A** of the lower mount structure **104** may be protected from physical damages. It should be noted that the exemplary scenario **300** of FIG. **3**, is for exemplary purposes and should not be construed to limit the scope of the disclosure.

[0040] FIGS. **4A** and **4B** are scenario diagrams that collectively illustrate configuration of an upper mount structure in a stowed and an un-stowed configuration to control access to a battery unit associated with a vehicle, in accordance with an embodiment of the disclosure. FIGS. **4A** and **4B** are explained in conjunction with elements from FIG. **1**, FIG. **2A**, FIG. **2B**, and FIG. **3**. With reference to FIG. **4A**, there is shown a scenario diagram **400A** that includes a stowed configuration

that may include a pivot point **402**. With reference to FIG. **4B**, there is shown another scenario diagram **400B** that includes an un-stowed configuration that may include the pivot point **402**. [0041] The upper mount structure **106** may be pivotally coupled to the upper portion **102B** of the vehicle frame **102** using the pivot point **402**. The pivot point **402** may be configured to provide a rotational movement to the upper mount structure **106** about an axis, which may be substantially parallel to a lateral axis of the upper mount structure **106**. The pivot point **402** may allow a rotational movement of the upper mount structure **106** about a single point, and therefore may have one degree of freedom. The rotational movement about the pivot point **402** may be required to control access to the battery unit **108**. In an embodiment, the movement of the pivot point **402** may be automatically controlled via an electronic control unit (ECU) associated with the vehicle. In another embodiment, the movement of the pivot point **402** may be manually controlled by the user by application of resistive force to provide required rotational movement to the pivot point **402** to place the upper mount structure **106** in the stowed or the un-stowed configuration.

[0042] In FIG. **4A**, the stowed configuration of the upper mount structure **106** along the upper portion **102B** of the vehicle frame **102** is shown. The stowed configuration of the upper mount structure **106** may help to secure the battery unit **108** in the space formed between the upper mount structure **106** and the lower mount structure **104**.

[0043] In FIG. **4B**, the un-stowed configuration of the upper mount structure **106** from the upper portion **102B** of the vehicle frame **102** is shown. The pivot point **402** may be configured to move the upper mount structure **106** in the un-stowed configuration. The upper mount structure **106** may be coupled with the seat associated with the vehicle. A movement of the seat coupled to the upper mount structure **106** may cause the upper mount structure **106** to move, leaving a gap in the vehicle frame **102** to slidably remove the battery unit **108** from the space formed between the upper mount structure **106** and the lower mount structure **104**. The un-stowed configuration of the upper mount structure **106** may allow the user to access the battery unit **108**. By way of example, and not limitation, if the user requires to replace or repair the battery unit **108**, then the user may move the seat coupled to the upper mount structure **106** along the direction of rotation (for example, a clockwise direction). The pivot point **402** may be configured to move the upper portion **102B** along the direction of rotation with respect to a vertical plane. Further, in the un-stowed configuration, the battery unit **108** may be slidably removed by the user in a direction “A” as shown in FIG. **4B**. After the battery unit **108** is repaired or replaced, the user may move the seat coupled to the upper mount structure **106** along a direction opposite to the direction of rotation (for example, a counterclockwise direction) to place the upper mount structure **106** in the stowed configuration.

[0044] It should be noted that the scenario diagrams **400A** and **400B** of FIGS. **4A** and **4B** are for exemplary purposes and should not be construed to limit the scope of the disclosure.

[0045] FIG. **5** is a flowchart that illustrates an exemplary method of assembling a vehicle frame for a vehicle, in accordance with an embodiment of the disclosure. FIG. **5** is explained in conjunction with elements from FIG. **1**, FIG. **2A**, FIG. **2B**, FIG. **3**, FIG. **4A** and FIG. **4B**. With reference to FIG. **6**, there is shown a flowchart **500**, which may depict method of assembling the vehicle frame **102** for the vehicle. The method illustrated in the flowchart **500** may start at **502** and proceed to **504**.

[0046] At **504**, the lower mount structure **104** may be coupled to the lower portion **102A** of the vehicle frame **102**. In one or more embodiments, the lower mount structure **104** may be coupled to the lower portion **102A** using at least one of a bolted joint, a welded joint, or a pivot joint, as further described, in detail, for example, in FIG. **1**.

[0047] At **506**, the upper mount structure **106** may be coupled to the upper portion **102B** of the vehicle frame **102**. In one or more embodiments, the upper mount structure **106** may be coupled to the upper portion **102B** using at least one of a bolted joint, a welded joint, or a pivot joint, as further described, in detail, for example, in FIG. **1**. Further, the lower mount structure **104** and the upper mount structure **106** may be configured to receive the battery unit **108** in the space formed between the lower mount structure **104** and the upper mount structure **106** such that the battery unit

108 may be slidably disposed in the inclined position in the space, as further described, in detail, for example, in FIG. 1, FIG. 2A, FIG. 2B, FIG. 3, FIG. 4A and FIG. 4B. Control may pass to end. [0048] Although the flowchart **500** is illustrated as discrete operations, such as **502**, and **504**, the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the particular implementation without detracting from the essence of the disclosed embodiments.

[0049] For the purposes of the present disclosure, expressions such as “including”, “comprising”, “incorporating”, “consisting of”, “have”, “is” used to describe, and claim the present disclosure are intended to be construed in a non-exclusive manner, namely allowing for items, components or elements not explicitly described also, to be present. Reference to the singular is also to be construed to relate to the plural. Further, all joinder references (e.g., attached, affixed, coupled, connected, and the like) are only used to aid the reader's understanding of the present disclosure, and may not create limitations, particularly as to the position, orientation, or use of the systems and/or methods disclosed herein. Therefore, joinder references, if any, are to be construed broadly. Moreover, such joinder references do not necessarily infer that two elements are directly connected to each other.

[0050] The foregoing description of embodiments and examples has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the forms described. Numerous modifications are possible considering the above teachings. Some of those modifications have been discussed and others will be understood by those skilled in the art. The embodiments were chosen and described for illustration of various embodiments. The scope is, of course, not limited to the examples or embodiments set forth herein but can be employed in any number of applications and equivalent devices by those of ordinary skill in the art. Rather it is hereby intended the scope be defined by the claims appended hereto. Additionally, the features of various implementing embodiments may be combined to form further embodiments.

Claims

1. A vehicle frame for a vehicle, comprising: a lower mount structure coupled to a lower portion of the vehicle frame; and an upper mount structure coupled to an upper portion of the vehicle frame, wherein the lower mount structure and the upper mount structure are configured to receive a battery unit in a space formed between the lower mount structure and the upper mount structure such that the battery unit is slidably disposed in an inclined position in the space.
2. The vehicle frame according to claim 1, wherein the lower mount structure is having a four-sided enclosure and the upper mount structure is having a battery fixing member, wherein the four-sided enclosure is configured to receive a bottom portion of the battery unit and the battery fixing member is configured to secure a top portion of the battery unit.
3. The vehicle frame according to claim 2, wherein the battery fixing member associated with the upper mount structure comprises a rubber padding to absorb shock and jerk experienced by the upper mount structure.
4. The vehicle frame according to claim 1, wherein the lower mount structure comprises a plurality of rubber pads.
5. The vehicle frame according to claim 4, wherein the plurality of rubber pads is disposed on at least one of: a base portion or on four sides of the lower mount structure.
6. The vehicle frame according to claim 1, wherein the inclined position of the battery unit includes an inclination angle that is between a range of about 35 degrees and 45 degrees with respect to a horizontal plane.
7. The vehicle frame according to claim 1, wherein the lower mount structure and the upper mount structure are attached to the vehicle frame using at least one of a bolted joint, a welded joint, or a

pivot joint.

- 8.** The vehicle frame according to claim 1, wherein the upper mount structure comprises a seat mount configured to mount a seat associated with the vehicle.
 - 9.** The vehicle frame according to claim 8, wherein the seat mount is a U-shaped transverse section.
 - 10.** The vehicle frame according to claim 8, wherein the inclined position of the battery unit includes an inclination angle that is based on a position of the seat mount.
 - 11.** The vehicle frame according to claim 1, wherein the upper mount structure comprises at least a pair of brackets configured to mount a tank cover associated with the vehicle.
 - 12.** The vehicle frame according to claim 1, wherein the upper mount structure comprises a plurality of slots configured to guide a plurality of electric wires that connect the battery unit to one or more functional components associated with the vehicle.
 - 13.** The vehicle frame according to claim 1, wherein the lower mount structure comprises a shock absorber mounted between the lower portion of the vehicle frame and a base portion of the lower mount structure.
 - 14.** The vehicle frame according to claim 1, wherein the lower mount structure comprises a plurality of pores on a base portion of the lower mount structure, and wherein the plurality of pores is configured to allow liquid to drain out of the vehicle frame.
 - 15.** The vehicle frame according to claim 1, wherein the upper mount structure is pivotally coupled to the upper portion of the vehicle frame, and wherein a movement of a seat coupled to the upper mount structure causes the upper mount structure to move, leaving a gap in the vehicle frame to slidably remove the battery unit from the space.
 - 16.** A battery mounting structure for a vehicle, comprising: a lower mount structure coupled to a lower portion of a vehicle frame; and an upper mount structure coupled to an upper portion of the vehicle frame, wherein the lower mount structure and the upper mount structure are configured to receive a battery unit in a space formed between the lower mount structure and the upper mount structure such that the battery unit is slidably disposed in an inclined position in the space.
 - 17.** The battery mounting structure according to claim 16, wherein the lower mount structure is having a four-sided enclosure and the upper mount structure is having a battery fixing member, wherein the four-sided enclosure is configured to receive a bottom portion of the battery unit and the battery fixing member is configured to secure a top portion of the battery unit.
 - 18.** The battery mounting structure according to claim 16, wherein the upper mount structure is having a battery fixing member that comprises a rubber padding to absorb shock and jerk experienced by the upper mount structure.
 - 19.** The battery mounting structure according to claim 16, wherein the lower mount structure comprises a plurality of rubber pads.
 - 20.** A method of assembling a battery mounting structure, comprising: coupling a lower mount structure to a lower portion of a vehicle frame; and coupling an upper mount structure to an upper portion of the vehicle frame, wherein the lower mount structure and the upper mount structure are configured to receive a battery unit in a space formed between the lower mount structure and the upper mount structure such that the battery unit is slidably disposed in an inclined position in the space.
-