

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282612

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

CHEN; Ying-Chung

PACKAGE STRUCTURE

Abstract

A package structure is provided. The package structure includes a substrate structure, a chip, an encapsulant, and an adhesive element. The substrate structure defines a cavity. The chip is disposed in the cavity. The encapsulant encapsulates the chip. The adhesive element is disposed over a top surface of the substrate structure, wherein the substrate structure includes a barring structure between the encapsulant and the adhesive element and configured to reduce a contact between the encapsulant and the adhesive element.

Inventors: CHEN; Ying-Chung (Taoyuan, TW)

Applicant: Advanced Semiconductor Engineering, Inc. (Kaohsiung, TW)

Family ID: 96948709

Assignee: Advanced Semiconductor Engineering, Inc. (Kaohsiung, TW)

Appl. No.: 18/600579

Filed: March 08, 2024

Publication Classification

Int. Cl.: B81B7/00 (20060101); B81C1/00 (20060101); H01L23/00 (20060101)

U.S. Cl.:

CPC B81B7/0077 (20130101); B81C1/00269 (20130101); B81B2207/012 (20130101); B81B2207/096 (20130101); H01L24/05 (20130101); H01L24/06 (20130101); H01L24/32 (20130101); H01L24/48 (20130101); H01L24/49 (20130101); H01L24/73 (20130101); H01L2224/05553 (20130101); H01L2224/05554 (20130101); H01L2224/0603 (20130101); H01L2224/06051 (20130101); H01L2224/32145 (20130101); H01L2224/32225 (20130101); H01L2224/48091 (20130101); H01L2224/48145 (20130101); H01L2224/48227 (20130101); H01L2224/49175

Background/Summary

BACKGROUND

1. Technical Field

[0001] The present disclosure relates generally to a package structure.

2. Description of the Related Art

[0002] Along with the increasing technical advance of package technology, package sizes are decreased, and various structures are developed. For example, MEMS packages are provided with advantages of high strength, high performance, and low cost; thus the development of MEMS packages has become increasingly important in package technology.

[0003] Open cavity mold packages or open cavity pre-mold packages are widely used for IC packaging and IC assemblies. However, formation of the mold structure requires delicate mold tools and thus the manufacturing complexity as well as the cost may increase, package sizes may increase, and device density may decrease.

SUMMARY

[0004] In one or more arrangements, a package structure includes a substrate structure, a chip, an encapsulant, and an adhesive element. The substrate structure defines a cavity. The chip is disposed in the cavity. The encapsulant encapsulates the chip. The adhesive element is disposed over a top surface of the substrate structure, wherein the substrate structure includes a barring structure between the encapsulant and the adhesive element and configured to reduce a contact between the encapsulant and the adhesive element.

[0005] In one or more arrangements, a package structure includes a substrate structure, a sensing device, and a gel. The substrate structure includes a lower substrate, a middle substrate, and an upper substrate laminated to each other and collectively defining a cavity. The sensing device is disposed in the cavity. The gel covers the sensing device and is spaced apart from an upper surface of the substrate structure.

[0006] In one or more arrangements, a package structure includes a substrate, a sidewall, a chip, an encapsulant, and a cap. The sidewall is disposed over the substrate, and the sidewall and the substrate collectively define a cavity. The chip is disposed in the cavity. The encapsulant is disposed in the cavity and encapsulates the chip. The cap is disposed over the sidewall, wherein an outer lateral surface of the sidewall is substantially aligned with a lateral surface of the substrate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Aspects of the present disclosure are better understood from the following detailed description when read with the accompanying drawings. It is noted that various features may not be drawn to scale, and the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

[0008] FIG. 1A is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0009] FIG. 1B is a top view of a package structure in accordance with some arrangements of the present disclosure.

[0010] FIG. 1C is a top view of a package structure in accordance with some arrangements of the present disclosure.

[0011] FIG. 1D is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0012] FIG. 1E is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0013] FIG. 1F is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0014] FIG. 1G is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0015] FIG. 1H is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0016] FIG. 2A is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0017] FIG. 2B is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0018] FIG. 2C is a cross-section of a package structure in accordance with some arrangements of the present disclosure.

[0019] FIG. 3A, FIG. 3B, FIG. 3C, FIG. 3D, FIG. 3E, FIG. 3F, FIG. 3G, and FIG. 3H illustrate various stages of an exemplary method for manufacturing a package structure in accordance with some arrangements of the present disclosure.

[0020] FIG. 4A and FIG. 4B illustrate various stages of an exemplary method for manufacturing a package structure in accordance with some arrangements of the present disclosure.

[0021] FIG. 5A, FIG. 5B, and FIG. 5C illustrate various stages of an exemplary method for manufacturing a package structure in accordance with some arrangements of the present disclosure.

[0022] FIG. 6A and FIG. 6B illustrate various stages of an exemplary method for manufacturing a package structure in accordance with some arrangements of the present disclosure.

[0023] FIG. 7A and FIG. 7B illustrate various stages of an exemplary method for manufacturing a package structure in accordance with some arrangements of the present disclosure.

[0024] Common reference numerals are used throughout the drawings and the detailed description to indicate the same or similar elements.

DETAILED DESCRIPTION

[0025] FIG. 1A is a cross-section of a package structure **1** in accordance with some arrangements of the present disclosure. FIG. 1B is a top view of a package structure **1** in accordance with some arrangements of the present disclosure. In some arrangements, FIG. 1A is a cross-section along a line **1A-1A'** in FIG. 1A. The package structure **1** may include a substrate structure **10**, chips **20** and **40**, an encapsulant **30**, conductive wires **51**, **52**, and **53**, a lid **60**, and an adhesive element **70**.

[0026] The substrate structure **10** may include a plurality of substrates laminated to each other. In some arrangements, the substrate structure **10** includes substrates **100**, **200**, and **300**, adhesive elements **400** and **500**, and an alignment mark **600**. In some arrangements, the substrate **100** is adhered to the substrate **200** through the adhesive element **400**, and the substrate **200** is adhered to the substrate **300** through the adhesive element **500**. In some arrangements, the substrate structure defines a cavity **10C**.

[0027] In some arrangements, each of the substrates **100**, **200**, and **300** may independently include, for example, a printed circuit board, such as a paper-based substrate layer, a composite substrate layer, or a polymer-impregnated glass-fiber-based substrate layer. Each of the substrates **100**, **200**, and **300** may independently include an interconnection structure, which may include such as a plurality of conductive traces and/or a plurality of conductive vias. The interconnection structure may include a redistribution layer (RDL) and/or a grounding element. In some arrangements, each of the substrates **100**, **200**, and **300** may independently include an organic substrate or a leadframe. In some arrangements, each of the substrates **100**, **200**, and **300** may independently include a two-layer substrate which includes a core layer and a conductive material and/or structure disposed on

an upper surface and a bottom surface of the substrate. Each of the substrates **100**, **200**, and **300** may independently include one or more electronic components. The electronic component may be a chip or a die including a semiconductor substrate, one or more integrated circuit devices and one or more overlying interconnection structures therein. The integrated circuit devices may include active devices such as transistors and/or passive devices such resistors, capacitors, inductors, or a combination thereof. Each of the substrates **100**, **200**, and **300** may independently include one or more conductive elements, surfaces, contacts, or pads.

[0028] In some arrangements, the substrate **100** includes a core layer **110**, conductive layers **120** and **130** on opposite surfaces of the core layer **110**, dielectric layers **140** and **150** on the conductive layers **120** and **130**, respectively, and a conductive structure **160** electrically connecting the conductive layer **120** to the conductive layer **130**. In some arrangements, the dielectric layer **140** defines an opening **140T** exposing at least a portion of a conductive pad **120A** of the conductive layer **120**. In some arrangements, the dielectric layer **150** defines an opening **150T** exposing at least a portion of the conductive layer **130**. The substrate **100** may be referred to as a lower substrate configured to support the chips **20** and **40**.

[0029] In some arrangements, the substrate **200** is disposed on the substrate **100**. In some arrangements, the substrate **200** is laminated to the substrate **100**. In some arrangements, the substrate **200** is disposed between the substrate **100** and the substrate **300**. In some arrangements, the substrate **200** has or defines a through hole **200T** (also referred to as “an opening” or “a cavity”) exposing a portion of a top surface (e.g., a surface **101**) of the substrate **100**. In some arrangements, the substrates **100** and **200** collectively may be referred to or construct a multi-layered substrate. In some arrangements, the substrates **100** and **200** collectively define a cavity (e.g., the through hole **200T**). In some arrangements, an outer lateral surface (e.g., a surface **200b**) of the substrate **200** is substantially aligned with a lateral surface (e.g., a surface **100b**) of the substrate **100**. The substrate **200** may be referred to as a middle substrate or a sidewall of the substrate structure **10**.

[0030] In some arrangements, the substrate **300** is connected to the substrates **100** and **200**. In some arrangements, the substrate **300** is laminated to the substrate **200**. In some arrangements, the substrate **300** has or defines a through hole **300T** (also referred to as “an opening” or “a cavity”) connected to the through hole **200T**. In some arrangements, the through hole **300T** is over and vertically overlapping the chip **20**. In some arrangements, the through hole **300T** defines an opening of the cavity **10C** and vertically overlapping the chip **20**, for example, in a direction substantially perpendicular to a surface **10a** of the substrate structure **10**. In some arrangements, the through hole **300T** connects the cavity **10C** to outside the cavity **10C**. In some arrangements, the substrates **100**, **200**, and **300** are laminated to each other and collectively define the cavity **10C** of the substrate structure **10**. In some arrangements, the through holes **200T** and **300T** collectively define the cavity **10C** of the substrate structure **10**. In some arrangements, a width **W2** of the through hole **300T** is less than a width **W1** of the through hole **200T** in a cross-sectional view. In some arrangements, a lateral sidewall (e.g., a surface **300b**) of the substrate **300** is substantially aligned with lateral sidewalls of the substrates **100** and **200**. In some arrangements, a lateral sidewall (e.g., a surface **300a**) of the substrate **300** is protruded out of the substrate **200** and overhanging over the through hole **200T**. The substrate **300** may be referred to as an upper substrate, a cap substrate, a cap, or a roof element. In some arrangements, a bottom surface (e.g., a surface **302**) of the substrate **300** (or the roof element) defines an inner top surface of the cavity **10C**.

[0031] In some arrangements, the adhesive element **400** adheres the substrate **100** (or the lower substrate) to the substrate **200** (or the middle substrate) and is exposed to the cavity **10C**. In some arrangements, the adhesive element **400** includes portions **400A** and **400B** on opposite sides of the chip **20** in a cross-sectional view perspective. In some arrangements, the portion **400A** of the adhesive element **40** has a surface **400a** exposed to and protruded toward the cavity **10C**. In some arrangements, the portion **400A** of the adhesive element **40** has a surface **400b** opposite to the

surface **400a** and substantially aligned with an outer lateral surface (e.g., the surface **200b**) of the substrate **200**. In some arrangements, the surface **400b** is substantially aligned with an outer lateral surface (e.g., the surface **100b**) of the substrate **100**. In some arrangements, the surface **400b** is substantially aligned with an outer lateral surface (e.g., the surface **300b**) of the substrate **300**. In some arrangements, the portion **400A** covers a portion of the inner sidewall (e.g., a surface **200a**) of the cavity **10C**. In some arrangements, the portion **400B** of the adhesive element **40** has a surface **400a'** exposed to and protruded toward the cavity **10C**. In some arrangements, the portion **400B** of the adhesive element **40** has a surface **400b'** opposite to the surface **400a'** and substantially aligned with an outer lateral surface (e.g., the surface **200b**) of the substrate **200**. In some arrangements, the surface **400b'** is substantially aligned with an outer lateral surface (e.g., a surface **300b**) of the substrate **300**. In some arrangements, the portions **400A** and **400B** are protruded toward or into the cavity **10C** by different lengths. In some arrangements, the surfaces **400a** and **400a'** of the adhesive element **400** are protruded out of or beyond the inner lateral surface (e.g., the surfaces **200a** and **200a'**) of the substrate **200** (or the sidewall). The protrusions of the adhesive element **400** may be resulted from the thermal-compression operation in which the substrate **200** is pressed toward the substrate **100** and the adhesive element **400** disposed there-between is softened upon heating and then deformed under the pressure. In some arrangements, the adhesive element **400** may be or include an epoxy-based material, e.g., an epoxy-based resin. In some arrangements, the adhesive element **400** includes fillers **400f**. The adhesive element **400** may be referred to as an adhesive resin, a lower adhesive element, or a lower adhesive resin.

[0032] In some arrangements, the adhesive element **500** adheres the substrate **300** (or the upper substrate) to the substrate **200** (or the middle substrate) and is exposed to the cavity **10C**. In some arrangements, a width of the adhesive element **500** is less than a width of the bottom surface of the substrate **300** (or the cap) in a cross-sectional view perspective. In some arrangements, the substrate **300** (or the cap substrate) is adhered to the multi-layered substrate (e.g., the combination of the substrates **100** and **200**) through the adhesive element **500**. In some arrangements, the adhesive element **500** includes portions **500A** and **500B** on opposite sides of the chip **20** in a cross-sectional view perspective. In some arrangements, a width of the adhesive element **500** is greater than a minimum width of the substrate **200** (or the sidewall) in a cross-sectional view perspective. In some arrangements, the portion **500A** of the adhesive element **50** has a surface **500a** exposed to and protruded toward the cavity **10C**. In some arrangements, the portion **500A** of the adhesive element **50** has a surface **500b** opposite to the surface **500a** and substantially aligned with an outer lateral surface (e.g., the surface **200b**) of the substrate **200**. In some arrangements, the surface **500b** is substantially aligned with an outer lateral surface (e.g., a surface **300b**) of the substrate **300**. In some arrangements, the portion **500B** of the adhesive element **50** has a surface **500a'** exposed to and protruded toward the cavity **10C**. In some arrangements, the portion **500B** of the adhesive element **50** has a surface **500b'** opposite to the surface **500a'** and substantially aligned with an outer lateral surface (e.g., the surface **200b**) of the substrate **200**. In some arrangements, the surface **500b'** is substantially aligned with an outer lateral surface (e.g., a surface **300b**) of the substrate **300**. In some arrangements, the portion **500B** covers a portion of the inner sidewall (e.g., the surface **200a'**) of the cavity **10C**. In some arrangements, the surfaces **500a** and **500a'** of the adhesive element **500** are protruded out of or beyond the inner lateral surface (e.g., the surfaces **200a** and **200a'**) of the substrate **200** (or the sidewall). The protrusions of the adhesive element **500** may be resulted from the thermal-compression operation in which the substrate **300** is pressed toward the substrate **200** and the adhesive element **500** disposed there-between is softened upon heating and then deformed under the pressure. In some arrangements, the adhesive element **500** may be or include an epoxy-based material, e.g., an epoxy-based resin. In some arrangements, the adhesive element **500** includes fillers (not shown). The adhesive element **500** may be referred to as an adhesive resin, an upper adhesive element, or an upper adhesive resin. In some arrangements, the substrate **300** is adhered to the multi-layered substrate (e.g., the combination of the substrates **100** and **200**) through

the adhesive element **500**.

[0033] In some arrangements, the alignment mark **600** is disposed or formed on an upper surface or a top surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, the alignment mark **600** is or includes a conductive pad or a conductive pattern.

[0034] In some arrangements, the chip **20** is disposed in the cavity **10C**. In some arrangements, the width **W2** of the through hole **300T** of the substrate **300** is greater than a width **W4** of the chip **20**. In some arrangements, the chip includes a conductive pad **210**. In some arrangements, the chip **20** may be or include a sensor element or a sensing device. In some arrangements, the chip **20** may be or include a microelectromechanical system (MEMS) device. The MEMS device may include micro-sized electromechanical components, for example, switches, mirrors, capacitors, accelerometers, sensors, capacitive sensors, or actuators etc. In some arrangements, the chip **20** includes a MEMS sensor, which includes a membrane separating a sealed cavity from the atmosphere. The MEMS sensor is configured to detect a pressure difference by determining a change in capacitance or resistance due to deformation of the membrane.

[0035] In some arrangements, the chip **40** is disposed in the cavity **10C**. In some arrangements, the width **W2** of the through hole **300T** of the substrate **300** is greater than a width **W5** of the chip **40**. In some arrangements, the chip **40** is adhered to the substrate **100** through an adhesive layer **82**, and the chip **20** is adhered to the chip **40** through an adhesive layer **81**. The adhesive layers **81** and **82** may be or include die-attach films (DAFs). In some arrangements, the chip **40** includes conductive pads **410**, **420**, and **430**. In some arrangements, the conductive pad **210** of the chip **20** is electrically connected to the conductive pad **410** of the chip **40** through the conductive wire **51**. In some arrangements, the conductive pad **420** of the chip **40** is electrically connected to a conductive pad **120A** of the conductive layer **120** of the substrate **100** through the conductive wire **52**. In some arrangements, the conductive pad **430** of the chip **40** is electrically connected to a conductive pad **120B** of the conductive layer **120** of the substrate **100** through the conductive wire **53**. The chip **40** may be or include a control integrated circuit (IC) or a processor IC, e.g., an ASIC die.

[0036] In some arrangements, the encapsulant **30** encapsulates the chips **20** and **40**. The encapsulant **30** may be referred to as a gel. In some arrangements, the encapsulant **30** (or the gel) covers the chip **20** and is spaced apart from the upper surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, the encapsulant **30** is physically spaced apart from the bottom surface (e.g., the surface **302**) of the substrate **300** (or the roof element). In some arrangements, the encapsulant **30** is free from contacting an inner sidewall (e.g., a surface **300a**) of the through hole **300T**. In some arrangements, the encapsulant **30** is physically spaced apart from an inner sidewall (e.g., a surface **300a**) of the through hole **300T**. In some arrangements, the substrate **300** (or the cap) is disposed over the substrate **200** (or the sidewall) and configured to block a vertical extending path of the encapsulant **30** (or the gel) in the manufacturing process. In some arrangements, a top surface (e.g., the surface **31**) of the encapsulant **30** is lower than a top surface (e.g., a surface **201**) of the substrate **200** with respect to the surface **101** of the substrate **100**. In some arrangements, the top surface (e.g., the surface **31**) includes a concave curved surface. In some arrangements, the cavity **10C** includes a portion (e.g., at least a portion of the through hole **200T**) filled with the encapsulant **30** and one or more portions (e.g., an upper part of the through hole **200T** and the through hole **300T**) free of the encapsulant **30**. In some arrangements, the width **W1** of the portion of the through hole **200T** filled with the encapsulant **30** is substantially the same as a width **W1'** of the upper part of the through hole **200T** free of the encapsulant **30**. In some arrangements, the width **W2** of the through hole **300T** is less than the width **W1'** of the upper part of the through hole **200T**. In some arrangements, the adhesive element **400** and the encapsulant **30** include different materials. In some arrangements, the adhesive element **500** and the encapsulant **30** include different materials. In some arrangements, the encapsulant **30** includes a silicone-based gel. In some arrangements, the encapsulant **30** is free of fillers. In some arrangements, the encapsulant **30** formed of a silicone-based gel is relatively soft to protect the surface (or the membrane) of the

chip **20** (or the MEMS sensor) while still allowing the membrane to deform upon pressure changes. [0037] In some arrangements, the lid **60** is attached to the upper surface (e.g., the surface **10a**) of the substrate structure **10** through the adhesive element **70**. In some arrangements, the lid **60** is free from contacting the encapsulant **30**. In some arrangements, the lid **60** is physically spaced apart from the encapsulant **30**. In some arrangements, the lid **60** includes a material different from the material of the substrate **300**. In some arrangements, the lid **60** has or defines a through hole **60T** (also referred to as “an opening” or “a channel”) over the through hole **300T**. In some arrangements, a width **W3** of the through hole **60T** less than the width **W2** of the through hole **300T**, and the width **W2** of the through hole **300T** is less than a width (e.g., the width **W1**) of the cavity **10C**. In some arrangements, the width **W4** of the chip **20** is greater than the width **W3** of the through hole **60T**. In some arrangements, the width **W5** of the chip **40** is greater than the width **W3** of the through hole **60T**. In some arrangements, the lid **60** includes a chimney structure defining the through hole **60T** (or the channel) connected to the cavity **10C**, and the width **W3** of the through hole **60T** (or the channel) is less than a thickness **W3'** (or “a width”) of a wall of the chimney structure. In some arrangements, an inner sidewall of the chimney structure vertically overlaps the encapsulant **30**. In some arrangements, an inner sidewall (e.g., a lateral surface **60a**) of the chimney structure vertically overlaps the encapsulant **30**. In some arrangements, the inner sidewall (e.g., the lateral surface **60a**) of the chimney structure is free from vertically overlapping the barring structure (e.g., the roof element of the substrate **300**). In some arrangements, an outer sidewall (e.g., a lateral surface **60b**) of the chimney structure vertically overlaps the encapsulant **30**. In some arrangements, the outer sidewall (e.g., the lateral surface **60b**) of the chimney structure is free from vertically overlapping the barring structure (e.g., the roof element of the substrate **300**). In some arrangements, the lid **60** includes a metal lid. According to some arrangements of the present disclosure, with the chimney structure having wall with a relatively large thickness **W3'** compared to the width **W3** of the through hole **60T** of the lid **60**, when a pipe used for measuring pressure is placed on the chimney structure of the lid **60**, the relatively thick wall of the chimney structure can provide sufficient support and structure strength for the pressure measurement.

[0038] In some arrangements, the adhesive element **70** is disposed over the upper surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, the substrate structure **10** includes a barring structure (e.g., the substrate **300**) between the encapsulant **30** and the adhesive element **70** and configured to reduce the contact between the encapsulant **30** and the adhesive element **70**. In some arrangements, the adhesive element **70** is between and contacts the substrate **300** (or the roof element) and the lid **60**. In some arrangements, a top surface (e.g., a surface **201**) of the chip **20** is at an elevation lower than an elevation of the adhesive element **70** with respect to the upper surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, an elevation of the adhesive element **70** is higher than an elevation of a top surface (e.g., the surface **201**) of the chip **20** with respect to a bottom surface (e.g., a surface **202**) opposite to the top surface of the chip **20**. In some arrangements, an elevation of an upper surface (e.g., a surface **701**) of the adhesive element **70** that is attached to the lid **60** is higher than an elevation of an upper surface (e.g., the surface **201**) of the chip **20** with respect to a lower surface (e.g., a surface **202**) opposite to the upper surface of the chip **20**. In some arrangements, the adhesive element **70** overlaps the encapsulant **30** in a direction substantially perpendicular to the surface **10a** of the substrate structure **10**. In some arrangements, an elevation of a bottom surface (e.g., a surface **702**) of the adhesive element **70** is higher than an elevation of a top surface (e.g., the surface **31**) of the encapsulant **30** (or the gel) with respect to an upper surface (e.g., the surface **101**) of the substrate **100**. In some arrangements, a width of the adhesive element **70** is less than a width of the top surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, a width of the adhesive element **70** is less than a width of a bottom surface of the lid **60**. In some arrangements, a gap is between the adhesive element **70** and the encapsulant **30** in a direction substantially perpendicular to an upper surface (e.g., the surface **10a**) of the substrate **300**. In some

arrangements, the encapsulant **30** is physically spaced apart from the adhesive element **70**. In some arrangements, the encapsulant **30** is physically spaced apart from the adhesive element **70** by the substrate **300** (or the roof element). In some arrangements, the adhesive element **70** is not horizontally overlapped with the encapsulant **30**. In some arrangements, the adhesive element **70** vertically overlaps the encapsulant **30**. In some arrangements, a hardness of the adhesive element **70** is greater than a hardness of the encapsulant **30**. In some arrangements, a modulus of the adhesive element **70** is greater than a modulus of the encapsulant **30**. In some arrangements, the adhesive elements **400**, **500**, and **70** include at least an epoxy-based resin, and the encapsulant **30** includes a silicone-based material. In some arrangements, the adhesive element **70** includes fillers (not shown). In some arrangements, the epoxy-based resin of the adhesive elements **400**, **500**, and **70** can provide a relatively strong adhesion between the substrates or between the substrate and the lid **60**.

[0039] In some cases where a MEMS sensor is disposed in a cavity formed by a molding compound, for example, an epoxy-based molded structure, after a silicone-based gel is filled in the cavity to cover the membrane of the MEMS sensor, a metal lid is then attached to the top surface of the molded structure. However, the silicone-based gel may overflow to cover some regions of the top surface of the molded structure on which adhesive elements are supposed to be disposed to adhere the metal lid to the molded structure. As a result, the metal lid may fail to attach to the molded structure due to that the silicone-based gel occupies the attaching areas instead of the adhesive element, or the molded structure has to be made with a relatively large top surface in order to provide tolerance area for the overflow of the silicon-based gel, which may lead to an increase of the package size.

[0040] In contrast, according to some arrangements of the present disclosure, the chip **20** is disposed in the cavity **10C** defined by substrates laminated to each other instead of a molded structure, and the top surface of the laminated substrates is spaced apart from the encapsulant **30** that covers the chip **20**. Therefore, the adhesive element **70** used for attaching the lid **60** to the laminated substrates can be disposed on the top surface without reserving spare spaces for overflow tolerance or overflow control, thus the area (e.g., the area in x-y directions) of the package structure can be reduced, and the package size can be reduced as well.

[0041] Moreover, in some cases where molded structures are formed by disposing molding materials on a substrate strip, the interfaces between the molding materials and the substrate strip may cause warpage of the strip structure. In order to reduce the warpage from the interfaces, tolerance spaces are required between the molded structures to form separated mold areas for respective molded structures, and thus the strip density is reduced. In contrast, according to some arrangements of the present disclosure, the cavity is defined by laminated substrates instead of a molded structure, delicate mold tools used for manufacturing molded structures can be omitted, thus the manufacturing process can be simplified, and the cost can be reduced. In addition, molding materials are not used, thus the tolerance spaces for reducing warpage of the substrate strip can be omitted. Therefore, the strip density can be increased significantly, for example, by about 150%. Furthermore, the process for forming alignment marks for aligning the lid **60** to the substrate structure **10** can be integrated in the process for forming the substrate, and thus the placement of the lid **60** can be accomplished with a reduced alignment shift while the overall process remains simplified.

[0042] In addition, according to some arrangements of the present disclosure, the adhesive element **70** connects the lid **60** to the top surface of the laminated substrates and is spaced apart from the encapsulant **30** that covers the chip **20**. Therefore, the lid **60** can be attached to the top surface of the substrate structure **10** without being adversely affected by the poor adhesion between the heterogeneous materials of the adhesive element **70** and the encapsulant **30**. Therefore, the stability and the reliability of the package structure can be improved while the package size is reduced. Moreover, the substrate structure **10** includes a roof element, thus the adhesive element **70** can be

spaced apart from the encapsulant **30** by the roof element, and the roof element can also provide an enlarge area for disposing the adhesive element **70** and the alignment mark **600**.

[0043] Furthermore, in some cases wherein a silicone-based gel is used to cover the membrane of a MEMS sensor on a substrate, and an epoxy-based adhesive is used to adhere a metal lid to the substrate to accommodate the MEMS chip in the space provided by the metal lid. However, the silicone-based gel may contact the epoxy-based adhesive, and the relatively poor adhesion between the silicone-based gel and the epoxy-based adhesive may reduce the stability of the package structure. In contrast, according to some arrangements of the present disclosure, the encapsulant **30** is spaced apart from the adhesive element **70**, such that the aforesaid issue can be solved, and thus the stability and reliability of the package structure can be increased.

[0044] FIG. **1C** is a top view of a package structure **1C** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1C** has a structure similar to the structure illustrated in FIG. **1B**, with differences therebetween as follows.

[0045] In some arrangements, the substrate structure **10** includes a pair of alignment marks **600** at corners of the upper surface of the substrate structure **10**. In some arrangements, the conductive pads **420** and **430** are on opposite sides of the chip **20**. In some arrangements, the conductive wires **52** and **53** are on opposite sides of the chip **20**. In some arrangements, the conductive pads **120A** and **120B** are on opposite sides of the chip **20**.

[0046] FIG. **1D** is a cross-section of a package structure **1D** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1D** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0047] In some arrangements, the encapsulant **30** (or the gel) contacts the adhesive element **500**. In some arrangements, the encapsulant **30** contacts the bottom surface (e.g., the surface **302**) of the substrate **300**. In some arrangements, at least a portion of a top surface (e.g., the surface **31**) of the encapsulant **30** is higher than the top surface (e.g., a surface **201**) of the substrate **200** with respect to the surface **101** of the substrate **100**.

[0048] In some arrangements, the cavity **10C** includes a portion (e.g., at least a portion of the through hole **200T**) filled with the encapsulant **30** and one or more portions (e.g., an upper part of the through hole **200T** and the through hole **300T**) free of the encapsulant **30**. In some arrangements, the width **W1** of the portion of the through hole **200T** filled with the encapsulant **30** is greater than a width **W1'** of the upper part of the through hole **200T** free of the encapsulant **30**. In some arrangements, the width **W2** of the through hole **300T** is less than the width **W1'** of the upper part of the through hole **200T**. In some arrangements, the encapsulant **30** in the upper part of the through hole **200T** contacts the surface **302** of the substrate **300**. In some arrangements, a width (i.e., the width **W1'**) of the surface **31** of the encapsulant **30** free from contacting the surface **302** is less than the width **W1** of the through hole **200T**.

[0049] In some arrangements, the adhesive element **70** includes a portion **710** adjacent to the alignment mark **600** and a portion **720** distal from the alignment mark **600** and separated from the portion **710**, and a width of the portion **720** is greater than a width of the portion **710**. According to some arrangements of the present disclosure, the portion **710** adjacent to the alignment mark **600** has a relatively small width can provide an increased tolerance area for preventing the adhesive element **70** from covering the alignment mark **600**. Therefore, the alignment mark **600** can be exposed by the adhesive element **70** and the lid **60**, such that the alignment accuracy of the lid **60** with the substrate structure **10** can be retested by detecting the relative position of the alignment mark **600** and the lid **60** to confirm whether the package structure **1D** is manufactured as expected.

[0050] In some arrangements, an elevation of a top surface (e.g., the surface **701**) of the adhesive element **70** (e.g., the portion **720**) is higher than an elevation of a bottom surface (e.g., a surface **602**) of the lid **60** with respect to the surface **10a** of the substrate structure **10**. In some arrangements, a portion (e.g., the portion **720**) of the adhesive element **70** extends over an outer lateral surface (e.g., the lateral surface **60b**) of the lid **60**. In some arrangements, the adhesive

element **70** is free from contacting an inner lateral surface (e.g., the lateral surface **60a**) of the lid **60**. In some arrangements, the width or the volume of the portion **710** is less than that of the portion **720** for reserving the tolerance area for the alignment mark **600**. Therefore, after the lid **60** is attached to the substrate structure **10**, the portion **720** may be pressed to extend and protrude out of the space between the lid **60** and the surface **10a** of the substrate structure **10**, and thus the portion **720** may further extend over an outer lateral surface (e.g., the lateral surface **60b**) of the lid **60**. According to some arrangements of the present disclosure, with the portion **720** further covering and contacting at least a portion of the outer lateral surface (e.g., the lateral surface **60b**) of the lid **60**, the attachment between the lid **60** and the substrate structure **10** can be increased, and thus the structural strength and reliability of the package structure **1D** can be increased.

[0051] FIG. **1E** is a cross-section of a package structure **1E** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1E** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0052] In some arrangements, the top surface (e.g., the surface **31**) of the encapsulant **30** includes a curved surface. The surface **31** includes a plurality of concave portions and a plurality of convex portions. In some arrangements, a portion of the encapsulant **30** contacts the surface **302** of the substrate **300**.

[0053] In some arrangements, the portions **710** and **720** extend over the lateral surfaces **60b** of the lid **60** by different lengths. In some arrangements, an elevation of the top surface of the portion **710** is lower than an elevation of the top surface of the portion **720** with respect to the surface **10a**.

[0054] FIG. **1F** is a cross-section of a package structure **1F** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1F** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0055] In some arrangements, an outer lateral surface **70a** of the adhesive element **70** is substantially aligned with the lateral surface **60b** of the lid **60** and the surface **300b** of the substrate **300**.

[0056] FIG. **1G** is a cross-section of a package structure **1G** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1G** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0057] In some arrangements, the substrate structure **10** includes the substrates **100** and **200**. In some arrangements, the substrate **200** includes a molding layer or a bulk substrate having the through hole **200T** tapering toward the substrate **100**. In some arrangements, the surface **200a** of the substrate **200** is inclined so as to serve as a barring structure between the encapsulant **30** and the adhesive element **70** and configured to reduce the contact between the encapsulant **30** and the adhesive element **70**.

[0058] FIG. **1H** is a cross-section of a package structure **1H** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **1H** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0059] In some arrangements, the substrate structure **10** includes the substrates **100** and **200**. In some arrangements, the substrate **200** includes a molding layer or a bulk substrate. In some arrangements, the substrate **200** is relatively tall, such that an upper portion of the substrate **200** may serve as barring structure between the encapsulant **30** and the adhesive element **70** and configured to reduce the contact between the encapsulant **30** and the adhesive element **70**.

[0060] FIG. **2A** is a cross-section of a package structure **2A** in accordance with some arrangements of the present disclosure. In some arrangements, the package structure **2A** has a structure similar to the structure illustrated in FIG. **1A**, with differences therebetween as follows.

[0061] In some arrangements, the package structure **2A** does not include an alignment mark **600**, the adhesive element **70**, and the lid **60** over the upper surface (e.g., the surface **10a**) of the substrate structure **10**. In some arrangements, the top surface (e.g., the surface **31**) of the encapsulant **30** includes a convex curved surface.

[0062] FIG. 2B is a cross-section of a package structure 2B in accordance with some arrangements of the present disclosure. In some arrangements, the package structure 2B has a structure similar to the structure illustrated in FIG. 1D, with differences therebetween as follows.

[0063] In some arrangements, the package structure 2B does not include an alignment mark 600, the adhesive element 70, and the lid 60 over the upper surface (e.g., the surface 10a) of the substrate structure 10. In some arrangements, the top surface (e.g., the surface 31) of the encapsulant 30 includes a concave curved surface. In some arrangements, a center line of the concave curved surface is misaligned with a center line of the through hole 200T.

[0064] FIG. 2C is a cross-section of a package structure 2C in accordance with some arrangements of the present disclosure. In some arrangements, the package structure 2C has a structure similar to the structure illustrated in FIG. 2A, with differences therebetween as follows.

[0065] In some arrangements, the width W2 of the through hole 300T of the substrate 300 is less than the width W4 of the chip 20 and the width W5 of the chip 40. In some arrangements, the top surface (e.g., the surface 31) of the encapsulant 30 includes a convex curved surface. In some arrangements, a center line of the convex curved surface is misaligned with a center line of the through hole 200T.

[0066] FIG. 3A, FIG. 3B, FIG. 3C, FIG. 3D, FIG. 3E, FIG. 3F, FIG. 3G, and FIG. 3H illustrate various stages of an exemplary method for manufacturing a package structure 2A in accordance with some arrangements of the present disclosure.

[0067] Referring to FIG. 3A, substrates 1000, 2000' and 3000' may be provided, and adhesive elements 4000' and 5000' may be formed on opposite surfaces of the substrate 2000'. In some arrangements, referring to FIG. 2A, the substrate 1000 includes a core layer 110, conductive layers 120 and 130, dielectric layers 140 and 150, and a conductive structure 160. In some arrangements, copper foils may be removed from surfaces of the substrates 2000' and 3000' prior to forming the adhesive elements 4000' and 5000' on the surfaces of the substrate 2000'. The copper foils may be removed by etching. The adhesive elements 4000' and 5000' may be formed on the surfaces of the substrate 2000' by lamination.

[0068] Referring to FIG. 3B and FIG. 3C, FIG. 3C is a top view of the structure illustrated in FIG. 3B, a removal operation may be performed on the substrate 2000' to form a substrate 2000 including through holes 200T, and a removal operation may be performed on the substrate 3000' to form a substrate 3000 including through holes 300T. In some arrangements, portions of the adhesive elements 4000' and 5000' may be removed to form adhesive elements 4000 and 5000 having through holes aligned with the through holes 200T.

[0069] Referring to FIG. 3D, the substrates 2000 and 3000 may be stacked over the substrate 1000.

[0070] Referring to FIG. 3E, a thermoforming operation may be performed to adhere the substrates 1000, 2000, and 3000 through the adhesive elements 4000 and 5000. In some arrangements, the adhesive elements 4000 and 5000 may soften and deform to form adhesive elements 4000A and 5000A that connect the substrates 1000, 2000, and 3000 to each other. In some arrangements, portions of the adhesive elements 4000A and 5000A may be softened and protruded into the cavity 10C defined by the through holes 200T and 300T.

[0071] Referring to FIG. 3F, chips 20 and 40 may be disposed in the cavities 10C. In some arrangements, the chip 40 is adhered to the substrate 1000, and the chip 20 is adhered to the chip 40. In some arrangements, conductive wires 51 may be provided to electrically connect the chips 20 to the chips 40. In some arrangements, conductive wires 52 may be provided to electrically connect the chips 40 to the substrate 1000.

[0072] Referring to FIG. 3G, encapsulants 30 may be filled in the cavities 10C to encapsulate the chips 20 and 40.

[0073] Referring to FIG. 3H, a singulation operation may be performed to form the package structures 2A. In some arrangements, the singulation operation may be performed on the substrates 1000, 2000, 3000, and the adhesive elements 4000A and 5000A. As such, the package structure 2A

illustrated in FIG. 2A may be formed.

[0074] FIG. 4A and FIG. 4B illustrate various stages of an exemplary method for manufacturing a package structure **1** in accordance with some arrangements of the present disclosure.

[0075] Referring to FIG. 4A, operations similar to those illustrated in FIGS. 3A-3G may be performed to form a structure illustrated in FIG. 3G, alignment marks **600** may be formed on an upper surface of the substrate **1000**, and lids **60** may be attached to the upper surface of the substrate **1000** through adhesive elements **70**.

[0076] Referring to FIG. 4B, a singulation operation may be performed to form the package structures **1**. In some arrangements, the singulation operation may be performed on the substrates **1000**, **2000**, **3000**, and the adhesive elements **4000A** and **5000A**. As such, the package structure **1** illustrated in FIGS. 1A-1B may be formed.

[0077] FIG. 5A, FIG. 5B, and FIG. 5C illustrate various stages of an exemplary method for manufacturing a package structure **2A** in accordance with some arrangements of the present disclosure.

[0078] Referring to FIG. 5A, operations similar to those illustrated in FIGS. 3A-3C may be performed to provide a substrate **1000** and a substrate **2000** having through holes **200T** with adhesive elements **4000** and **5000** on surfaces of the substrate **2000**, and a thermoforming operation may be performed to adhere the substrate **2000** to the substrate **1000** through the adhesive element **4000**. In some arrangements, the adhesive element **4000** may soften and deform to form an adhesive element **4000A** that connects the substrates **1000** and **2000** to each other. In some arrangements, portions of the adhesive element **4000A** may be softened and protruded into the through holes **200T**.

[0079] Referring to FIG. 5B, chips **20** and **40** may be disposed in the through holes **200T**. In some arrangements, the chip **40** is adhered to the substrate **1000**, and the chip **20** is adhered to the chip **40**. In some arrangements, conductive wires **51** may be provided to electrically connect the chips **20** to the chips **40**. In some arrangements, conductive wires **52** may be provided to electrically connect the chips **40** to the substrate **1000**.

[0080] Referring to FIG. 5C, operations similar to those illustrated in FIGS. 3A-3C may be performed to provide a substrate **3000** having through holes **300T**, a thermoforming operation may be performed to adhere the substrate **3000** to the substrate **2000** through the adhesive element **5000**. In some arrangements, the adhesive element **5000** may soften and deform to form an adhesive element **5000A** that connects the substrates **2000** and **3000** to each other. In some arrangements, portions of the adhesive element **5000A** may be softened and protruded into cavities **10C** defined by the through holes **200T** and **300T**.

[0081] Next, operations similar to those illustrated in FIGS. 3G-3H may be performed to fill encapsulants **30** in the cavities **10C** and singulate the strip-form structure to form the package structures **2A**.

[0082] FIG. 6A and FIG. 6B illustrate various stages of an exemplary method for manufacturing a package structure **2A** in accordance with some arrangements of the present disclosure.

[0083] Referring to FIG. 6A, a substrate **1000** may be provided.

[0084] Referring to FIG. 6B, chips **20** and **40** may be disposed on the substrate **1000**. In some arrangements, the chip **40** is adhered to the substrate **1000**, and the chip **20** is adhered to the chip **40**. In some arrangements, conductive wires **51** may be provided to electrically connect the chips **20** to the chips **40**. In some arrangements, conductive wires **52** may be provided to electrically connect the chips **40** to the substrate **1000**.

[0085] Next, operations similar to those illustrated in FIGS. 3A-3E may be performed to laminate the substrates **2000** and **3000** to the substrate **1000**. Next, operations similar to those illustrated in FIGS. 3G-3H may be performed to fill encapsulants **30** in the cavities **10C** and singulate the strip-form structure to form the package structures **2A**.

[0086] FIG. 7A and FIG. 7B illustrate various stages of an exemplary method for manufacturing a

package structure **1F** in accordance with some arrangements of the present disclosure.

[0087] Referring to FIG. 7A, operations similar to those illustrated in FIGS. 3A-3G may be performed to form a structure illustrated in FIG. 3G, and a lid layer **60A** may be attached to the upper surface of the substrate **1000** through adhesive elements **70A**.

[0088] Referring to FIG. 7B, a singulation operation may be performed to form the package structures **1F**. In some arrangements, the singulation operation may be performed on the lid layer **60A**, the substrates **1000**, **2000**, **3000**, and the adhesive elements **70A**, **4000A**, and **5000A**. As such, the package structure **1A** illustrated in FIG. 1F may be formed.

[0089] Spatial descriptions, such as “above,” “below,” “up,” “left,” “right,” “down,” “top,” “bottom,” “vertical,” “horizontal,” “side,” “higher,” “lower,” “upper,” “over,” “under,” and so forth, are indicated with respect to the orientation shown in the figures unless otherwise specified. It should be understood that the spatial descriptions used herein are for purposes of illustration only, and that practical implementations of the structures described herein can be spatially arranged in any orientation or manner, provided that the merits of embodiments of this disclosure are not deviated from by such an arrangement.

[0090] As used herein, the terms “approximately,” “substantially,” “substantial” and “about” are used to describe and account for small variations. When used in conjunction with an event or circumstance, the terms can refer to instances in which the event or circumstance occurs precisely as well as instances in which the event or circumstance occurs to a close approximation. For example, when used in conjunction with a numerical value, the terms can refer to a range of variation less than or equal to $\pm 10\%$ of that numerical value, such as less than or equal to $\pm 5\%$, less than or equal to $\pm 4\%$, less than or equal to $\pm 3\%$, less than or equal to $\pm 2\%$, less than or equal to $\pm 1\%$, less than or equal to $\pm 0.5\%$, less than or equal to $\pm 0.1\%$, or less than or equal to $\pm 0.05\%$. For example, a first numerical value can be deemed to be “substantially” the same or equal to a second numerical value if the first numerical value is within a range of variation of less than or equal to $\pm 10\%$ of the second numerical value, such as less than or equal to $\pm 5\%$, less than or equal to $\pm 4\%$, less than or equal to $\pm 3\%$, less than or equal to $\pm 2\%$, less than or equal to $\pm 1\%$, less than or equal to $\pm 0.5\%$, less than or equal to $\pm 0.1\%$, or less than or equal to $\pm 0.05\%$. For example, “substantially” perpendicular can refer to a range of angular variation relative to 90° that is less than or equal to $\pm 10^\circ$, such as less than or equal to $\pm 5^\circ$, less than or equal to $\pm 4^\circ$, less than or equal to $\pm 3^\circ$, less than or equal to $\pm 2^\circ$, less than or equal to $\pm 1^\circ$, less than or equal to $\pm 0.5^\circ$, less than or equal to $\pm 0.1^\circ$, or less than or equal to $\pm 0.05^\circ$.

[0091] Two surfaces can be deemed to be coplanar or substantially coplanar if a displacement between the two surfaces is no greater than $5\text{ }\mu\text{m}$, no greater than $2\text{ }\mu\text{m}$, no greater than $1\text{ }\mu\text{m}$, or no greater than $0.5\text{ }\mu\text{m}$. A surface can be deemed to be substantially flat if a displacement between a highest point and a lowest point of the surface is no greater than $5\text{ }\mu\text{m}$, no greater than $2\text{ }\mu\text{m}$, no greater than $1\text{ }\mu\text{m}$, or no greater than $0.5\text{ }\mu\text{m}$.

[0092] As used herein, the singular terms “a,” “an,” and “the” may include plural referents unless the context clearly dictates otherwise.

[0093] As used herein, the terms “conductive,” “electrically conductive” and “electrical conductivity” refer to an ability to transport an electric current. Electrically conductive materials typically indicate those materials that exhibit little or no opposition to the flow of an electric current. One measure of electrical conductivity is Siemens per meter (S/m). Typically, an electrically conductive material is one having a conductivity greater than approximately 10^4 S/m , such as at least 10^5 S/m or at least 10^6 S/m . The electrical conductivity of a material can sometimes vary with temperature. Unless otherwise specified, the electrical conductivity of a material is measured at room temperature.

[0094] Additionally, amounts, ratios, and other numerical values are sometimes presented herein in a range format. It is to be understood that such range format is used for convenience and brevity and should be understood flexibly to include numerical values explicitly specified as limits of a

range, but also to include all individual numerical values or sub-ranges encompassed within that range as if each numerical value and sub-range is explicitly specified.

[0095] While the present disclosure has been described and illustrated with reference to specific embodiments thereof, these descriptions and illustrations are not limiting. It should be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the true spirit and scope of the present disclosure as defined by the appended claims. The illustrations may not be necessarily drawn to scale. There may be distinctions between the artistic renditions in the present disclosure and the actual apparatus due to manufacturing processes and tolerances. There may be other embodiments of the present disclosure which are not specifically illustrated. The specification and drawings are to be regarded as illustrative rather than restrictive. Modifications may be made to adapt a particular situation, material, composition of matter, method, or process to the objective, spirit and scope of the present disclosure. All such modifications are intended to be within the scope of the claims appended hereto. While the methods disclosed herein have been described with reference to particular operations performed in a particular order, it will be understood that these operations may be combined, sub-divided, or re-ordered to form an equivalent method without departing from the teachings of the present disclosure. Accordingly, unless specifically indicated herein, the order and grouping of the operations are not limitations of the present disclosure.

Claims

1. A package structure, comprising: a substrate structure defining a cavity; a chip disposed in the cavity; an encapsulant encapsulating the chip; and an adhesive element disposed over a top surface of the substrate structure, wherein the substrate structure comprises a barring structure between the encapsulant and the adhesive element and configured to reduce a contact between the encapsulant and the adhesive element.
2. The package structure as claimed in claim 1, wherein the barring structure comprises a roof element, the roof element defines a through hole connecting the cavity to outside the cavity and overlapping the chip in a direction substantially perpendicular to the top surface of the substrate structure.
3. The package structure as claimed in claim 2, wherein a bottom surface of the roof element defines an inner top surface of the cavity.
4. The package structure as claimed in claim 2, wherein the encapsulant is physically spaced apart from the adhesive element by the roof element.
5. The package structure as claimed in claim 2, wherein the encapsulant is free from contacting an inner sidewall of the through hole.
6. The package structure as claimed in claim 1, further comprising a lid attached to the top surface of the substrate structure through the adhesive element, wherein an elevation of the adhesive element is higher than an elevation of a top surface of the chip with respect to a bottom surface opposite to the top surface of the chip.
7. The package structure as claimed in claim 6, wherein the encapsulant does not contact the lid.
8. A package structure, comprising: a substrate structure comprising a lower substrate, a middle substrate, and an upper substrate laminated to each other and collectively defining a cavity; a sensing device disposed in the cavity; and a gel covering the sensing device and spaced apart from an upper surface of the substrate structure.
9. The package structure as claimed in claim 8, wherein the lower substrate supports the sensing device, and the upper substrate defines an opening over and overlapping the sensing device in a direction substantially perpendicular to the upper surface of the substrate structure.
10. The package structure as claimed in claim 9, wherein the middle substrate has a through hole, and the opening and the through hole collectively define the cavity of the substrate structure.

- 11.** The package structure as claimed in claim 10, wherein a width of the opening is less than a width of the through hole in a cross-sectional view.
- 12.** The package structure as claimed in claim 8, further comprising a lid attached to a top surface of the upper substrate through an adhesive element, and the adhesive element overlaps the gel in a direction substantially perpendicular to the upper surface of the substrate structure.
- 13.** The package structure as claimed in claim 12, wherein an elevation of a top surface of the adhesive element is higher than an elevation of a bottom surface of the lid with respect to the upper surface of the substrate structure.
- 14.** The package structure as claimed in claim 12, wherein an elevation of a bottom surface of the adhesive element is higher than an elevation of a top surface of the gel with respect to an upper surface of the lower substrate.
- 15.** The package structure as claimed in claim 12, wherein the lid has an opening having a first width and attached to the upper substrate through the adhesive element, and the upper substrate has an opening having a second width greater than the first width.
- 16.** The package structure as claimed in claim 12, wherein the substrate structure further comprises an alignment mark on the upper surface of the substrate structure, and wherein in a cross-sectional view perspective, the adhesive element comprises a first portion adjacent to the alignment mark and a second portion distal from the alignment mark and separated from the first portion, and a width of the second portion is greater than a width of the first portion.
- 17.** A package structure, comprising: a substrate; a sidewall disposed over the substrate, the sidewall and the substrate collectively defining a cavity; a chip disposed in the cavity; an encapsulant disposed in the cavity and encapsulating the chip; and a cap disposed over the sidewall, wherein an outer lateral surface of the sidewall is substantially aligned with a lateral surface of the substrate.
- 18.** The package structure as claimed in claim 17, further comprising an adhesive adhering the sidewall to the substrate, wherein an outer lateral surface of the adhesive is substantially aligned with the outer lateral surface of the sidewall and the lateral surface of the substrate.
- 19.** The package structure as claimed in claim 17, wherein an outer lateral surface of the cap is substantially aligned with the outer lateral surface of the sidewall.
- 20.** The package structure as claimed in claim 19, further comprising an adhesive adhering the cap to the sidewall, wherein an outer lateral surface of the adhesive is substantially aligned with the outer lateral surface of the cap and the outer lateral surface of the sidewall.
-