

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284350

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

AL-HAWAS; Razan Osama et al.

SMART STYLUS FOR HAND REHABILITATION THERAPY

Abstract

A smart stylus for use in hand therapy includes an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap. The stylus end is connected to a first end of the central body and a second end of the central body is connected to a first end of the C-shaped handle. The central body is configured to taper in width and depth from the second end of the central body to the first end of the central body and the handle end cap is connected to a second end of the C-shaped handle. The length of the central body may be adjusted by sliding mechanisms. A pressure sensor measures the amount of force of the stylus tip on a therapeutic tablet. The therapeutic tablet presents therapy exercises and communicates therapy results to a physical therapist of the patient.

Inventors: AL-HAWAS; Razan Osama (Dammam, SA), EL-WAKEEL; Hala (Dammam, SA), KATTAN; Noran (Dammam, SA), ALSHEHRI; Lama (Dammam, SA), ALAMRI; Lojain (Dammam, SA)

Applicant: Imam Abdulrahman Bin Faisal University (Dammam, SA)

Family ID: 1000007738017

Assignee: Imam Abdulrahman Bin Faisal University (Dammam, SA)

Appl. No.: 18/598029

Filed: March 07, 2024

Publication Classification

Int. Cl.: G06F3/0354 (20130101); G06F3/041 (20060101); G06F3/044 (20060101); G16H20/30 (20180101); G16H40/67 (20180101)

U.S. Cl.:

Background/Summary

BACKGROUND

Technical Field

[0001] The present disclosure is directed towards physical rehabilitation techniques, and more particularly, directed towards a smart stylus, a system incorporating the smart stylus, and method for hand therapy in stroke patients.

Description of Related Art

[0002] The “background” description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent it is described in this background section, as well as aspects of the description which may not otherwise qualify as prior art at the time of filing, are neither expressly or impliedly admitted as prior art against the present invention.

[0003] Cases of strokes and subsequent paralysis are currently on the rise. In general, stroke is a medical condition including two major types, namely, ischemic stroke and hemorrhagic stroke. Ischemic stroke occurs when blood supply to a part of human brain is blocked or reduced. This prevents brain tissue from getting oxygen and nutrients resulting in death of brain cells within minutes. Hemorrhagic stroke occurs when a blood vessel in the brain ruptures or bursts, subsequently bleeding in the brain. A major complication of stroke is loss of muscle movement or paralysis. Paralysis is uncertain and depends on the type and intensity of stroke, adversely affecting one or more muscle in human body.

[0004] Traditionally there are several solutions to treat complications associated with stroke such as paralysis. In accordance with general consensus, the most effective way to treat stroke paralysis is to activate neuroplasticity. Neuroplasticity refers to a mechanism that the brain uses to heal by reorganizing nerve cells and forming new neural pathways. These new neural pathways allow healthy, undamaged portions of the brain to take over control from areas that were affected by the stroke. Therefore, by engaging neuroplasticity, the brain may grow new neural pathways to the paralysed muscles to help recover from paralysis. Neuroplasticity may be activated through high repetition of rehab exercises. This high repetition results in reinforced, new neural pathways. Subsequently, strengthening the newly formed neural pathways may result in stronger and more efficient connection between the brain and affected muscles. Rehab exercises include, but are not limited to, passive exercises, mental practice, electrical stimulation, acupuncture, and mirror therapy. Passive exercise refers to moving the paralysed muscles on behalf of a stroke patient by supplemental apparatuses and systems. Similarly, in electrical stimulation, supplemental apparatuses are used to stimulate the paralysed muscles using mild electrical stimulus. However, the aforementioned techniques have limitations in helping the stroke patient recover fully. Different age groups of patients respond differently to the above stated rehab exercises. With continuous increment of young stroke patients, some of the traditional methods are rendered useless due to their orthodox approach and dated protocols, which do not resonate with the younger generation of stroke patients. Hence, there arises a need for a modern and advanced method, system and apparatus to provide the necessary support to a stroke patient, including all age groups.

[0005] U.S. Pat. No. 4,596,335A describes a marking implement holder. The marking implement holder includes a guide arm and a support arm. The guide arm has a free end adapted to engage a marking surface and act as a guide when the holder is grasped and moved along the marking

surface. The support arm extends from the guide arm and is spaced from the free end thereof. However, the marking implement holder is not adapted for therapy or for use with a tablet, nor does it have adjustable length or spaces for weights.

[0006] US20120019488A1 describes a stylus for use with a system having a touchscreen display coupled to a processor. The touchscreen display is configured to determine positional information of an object positioned within a display area of the touchscreen display. Further, the stylus includes a tip portion and housing, and is configured to transmit pressure and orientation information of the housing to the processor. However, the stylus is not adapted for therapy nor does have adjustable length or spaces for weights. Further, the tablet associated with the aforementioned publication is not programmed with therapy lessons to aid in rehabilitation.

[0007] CN2230236Y describes a utility model that relates to a corrector for exercising the finger shape of a pencil holder for training directional holding, which is composed of a holding body, wherein a positioning hole for the pencil holder is arranged on the holding body. One side of the holding body is a pencil-holding curved surface which emulates a forefinger and the other side is a pencil-holding curved surface which emulates a thumb. The lower part of the front end of the holding body is provided with a convex middle finger holding point. The corrector is sheathed on the proper position of a hard pencil and is naturally held in a space formed by the thumb, the forefinger and the middle finger and three fingers to directly touch a pencil rod, therefore, the utility model has the advantages of natural and comfortable pencil-holding finger shape, writing flexibility, high speed, small force, and unbroken nib and is beneficial for children who first learn writing to master correct pencil-holding posture. However, there is no mention that the device is adapted for therapy nor does it have adjustable length, a curved shape, communications circuitry, a pressure sensor, spaces for weights. Further, there is no communication with a tablet programmed with therapy games or lessons.

[0008] US20090251442A1 describes an electronic stylus pen with weight adjusting mechanism. The electronic stylus pen includes a pen body, a stepped portion arranged in the central portion of the pen body, a pen tip arranged at a tip end of the pen body, and a small-diameter portion arranged in an area between the stepped portion and the pen tip of the pen body. The diameter of the small-diameter portion is smaller than that of the pen body. Weight adjusting members are mounted at arbitrary positions of the small-diameter portion. However, there is no mention that the device is adapted for therapy nor does it have adjustable length, a curved shape, communications circuitry, a pressure sensor, spaces for weights or the curved configuration of the lessons smart pen of the present disclosure. Further, there is no communication with a tablet programmed with therapy games or lessons.

[0009] Each of the aforementioned prior arts suffer from one or more drawbacks hindering their adoption. Therefore, a need arises for better and more advanced techniques for the rehabilitation of paralyzed muscles. Accordingly, it is one object of the present disclosure to provide a smart stylus, and a smart stylus therapeutic system including the smart stylus and a therapeutic tablet for rehabilitation of paralysed hand muscles due to stroke.

SUMMARY

[0010] In an exemplary embodiment, a smart stylus for use in hand therapy is described. The smart stylus includes an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap. The stylus end is connected to a first end of the central body, and a second end of the central body is connected to a first end of the C-shaped handle. The central body is configured to taper in width and depth from the second end of the central body to the first end of the central body and the handle end cap is connected to a second end of the C-shaped handle. Furthermore, the smart stylus includes a first sliding mechanism located between the central body and the first end of the C-shaped handle. Moreover, the smart stylus includes a second sliding mechanism located between the second end of the C-shaped handle and the handle end cap, and a length of the elongate body depends on an adjustment of the first sliding mechanism and the second sliding

mechanism.

[0011] In another exemplary embodiment, a smart stylus therapeutic system for use in hand therapy is described. The smart stylus therapeutic system includes an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap. The stylus end is connected to a first end of the central body, a second end of the central body is connected to a first end of the C-shaped handle, and the handle end cap is connected to a second end of the C-shaped handle. The smart stylus therapeutic system further includes a rechargeable battery located within the handle end cap, a microcontroller located within the central body, and operatively connected to the rechargeable battery, and a near field communications unit located within the central body and operatively connected with the microcontroller. Further, the smart stylus therapeutic system includes a therapeutic tablet including a touch screen. The therapeutic tablet includes a memory having program instructions including a hand therapy treatment plan and one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit and display the hand therapy treatment plan and hand therapy exercises upon the touch screen. The hand therapy exercises are configured to direct a patient to write upon the touch screen with the stylus end while gripping the C-shaped handle. The hand therapy exercise may include, but not limited to, tracing exercises, therapeutic objectives, or a combination thereof. Moreover, the smart stylus therapeutic system includes a case configured to hold the elongate body and the therapeutic tablet, and a charging port located on the case and configured to mate with the handle end cap. In addition, the smart stylus therapeutic system includes a rechargeable battery located with the central body and an electromagnetic coil located within the handle end cap and connected to the rechargeable battery. The electromagnetic coil is configured to generate a charging current when the handle end cap is placed adjacent to the charging port.

[0012] In yet another exemplary embodiment, a method of using the smart stylus in hand therapy is described. The method includes forming an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap. The stylus end is connected to a first end of the central body, a second end of the central body is connected to a first end of the C-shaped handle, and the handle end cap is connected to a second end of the C-shaped handle. Further, the method includes installing a rechargeable battery within the handle end cap, inserting a microcontroller within the central body, and operatively connecting the microcontroller to the rechargeable battery. Furthermore, the method includes forming a case to hold the elongate body and the therapeutic tablet and forming a charging port in the case. The charging port is configured to mate with the handle end cap. Moreover, the method includes installing an electromagnetic coil within the handle end cap and connecting the electromagnetic coil to the rechargeable battery. The electromagnetic coil is configured to generate a charging current when the handle end cap is placed adjacent to the charging port. In addition, the method includes installing a near field communications unit within the central body and operatively connecting the near field communications unit with the microcontroller. The method further includes linking a therapeutic tablet including a touch screen to the microcontroller. The therapeutic tablet includes a memory including program instructions including a hand therapy treatment plan and one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit and display the hand therapy treatment plan and hand therapy exercises upon the touch screen. The hand therapy exercises are configured to direct a patient to write upon the touch screen with the stylus end while gripping the C-shaped handle.

[0013] The foregoing general description of the illustrative embodiments and the following detailed description thereof are merely exemplary aspects of the teachings of this disclosure and are not restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] A more complete appreciation of this disclosure and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

[0015] FIG. 1 is a schematic perspective view of a smart stylus for use in hand therapy, according to certain embodiments.

[0016] FIG. 2 is a schematic side view of the smart stylus of FIG. 1 showing an extended configuration thereof, according to certain embodiments.

[0017] FIG. 3A is a schematic rear perspective view of the smart stylus of FIG. 1, according to certain embodiments.

[0018] FIG. 3B is a schematic top view of the smart stylus of FIG. 1, according to certain embodiments.

[0019] FIG. 4A depicts use of the smart stylus, according to certain embodiments.

[0020] FIG. 4B is a schematic enlarged view of a portion of the smart stylus showing a first flexible grip, according to certain embodiments.

[0021] FIG. 4C is a schematic perspective of the smart stylus showing a second flexible grip, according to certain embodiments.

[0022] FIG. 5A is a schematic perspective view of the smart stylus showing weight receiving compartments, according to certain embodiments.

[0023] FIG. 5B is a schematic diagram of a plurality of weights associated with the smart stylus, according to certain embodiments.

[0024] FIG. 5C depicts a schematic illustration of a method of removing the plurality of weights, according to certain embodiments.

[0025] FIG. 5D depicts a schematic illustration of the method of FIG. 5C showing removal of one weight from the plurality of weights, according to certain embodiments.

[0026] FIG. 6A is a schematic perspective view of the smart stylus depicting one or more internal electrical components thereof, according to certain embodiments.

[0027] FIG. 6B is a schematic diagram of an electromagnetic coil located in the smart stylus, according to certain embodiments.

[0028] FIG. 6C is a schematic diagram of a pressure sensor located in the smart stylus, according to certain embodiments.

[0029] FIG. 7A is a schematic diagram of a smart stylus therapeutic system for use in hand therapy, according to certain embodiments.

[0030] FIG. 7B is a schematic illustration of a program instruction displayed on a touch screen of the smart stylus therapeutic system, according to certain embodiments.

[0031] FIG. 7C is a schematic illustration of another program instruction displayed on the touch screen of the smart stylus therapeutic system, according to certain embodiments.

[0032] FIG. 7D is a schematic illustration of yet another program instruction displayed on the touch screen of the smart stylus therapeutic system, according to certain embodiments.

[0033] FIG. 8A is a schematic diagram of the smart stylus therapeutic system with the smart stylus detached from a therapeutic tablet, according to certain embodiments.

[0034] FIG. 8B is a schematic illustration of a battery charge status as displayed on the touch screen of the therapeutic tablet, according to certain embodiments.

[0035] FIG. 8C is a schematic diagram of the smart stylus depicting a pair of proximity sensors, according to certain embodiments.

[0036] FIG. 9 is a schematic block diagram of a patient assessment computing environment, according to certain embodiments.

[0037] FIG. 10 is an exemplary flowchart of a method of using the smart stylus in the hand therapy,

according to certain embodiments.

[0038] FIG. **11** is an illustration of a non-limiting example of details of computing hardware used in a computing system, according to certain embodiments.

[0039] FIG. **12** is an exemplary schematic diagram of a data processing system used within the computing system, according to certain embodiments.

[0040] FIG. **13** is an exemplary schematic diagram of a processor used with the computing system, according to certain embodiments.

[0041] FIG. **14** is an illustration of a non-limiting example of distributed components which may share processing with a controller, according to certain embodiments.

DETAILED DESCRIPTION

[0042] In the drawings, like reference numerals designate identical or corresponding parts throughout the several views. Further, as used herein, the words “a,” “an” and the like generally carry a meaning of “one or more”, unless stated otherwise.

[0043] Furthermore, the terms “approximately,” “approximate,” “about” and similar terms generally refer to ranges that include the identified value within a margin of 20%, 10%, or preferably 5%, and any values therebetween.

[0044] Aspects of this disclosure are directed to a system and a method for rehabilitation therapy of stroke affected limbs, in particular, paralyzed hands. The present disclosure includes a smart stylus, a smart stylus therapeutic system including the smart stylus and a therapeutic tablet, and a method describing the implementation of the smart stylus and the smart stylus therapeutic system. The system described in the present disclosure tracks the progress of a particular patient using the smart stylus in conjunction with the therapeutic system in order to personalize a plurality of parameters for a tailored experience and accelerated recovery of the particular patient. Further, the system described herein allows for remote goal setting and progress tracking of the particular patient. In addition, the system is capable of remote monitoring and tele-rehabilitation by one or more physicians.

[0045] Referring to FIG. **1**, a schematic perspective view of a smart stylus **100** for use in hand therapy is illustrated. In particular, the smart stylus **100** is a near field communications (NFC) and Wi-Fi enabled device, with ergonomic design elements to support a patient in rehabilitation exercises and therapy through full recovery. The smart stylus **100** includes an elongate body **102** having a stylus end **104**, a central body **106**, a C-shaped handle **108**, and a handle end cap **110**. The central body **106** and the handle end cap **110** are slidably coupled to the C-shaped handle **108** to define the elongate body **102**. The stylus end **104** is connected to a first end **106A** of the central body **106**. The first end **106A** of the central body **106** is configured to detachably couple with the stylus end **104**. As such, the stylus end **104** may be detached from the central body **106** and replaced as needed due to wear and tear after regular use of the smart stylus **100**. Further, a second end **106B** of the central body **106** is connected to a first end **108A** of the C-shaped handle **108**. The second end **106B** of the central body **106** is configured to slidably couple with the first end **108A** of the C-shaped handle **108**, such that the central body **106** may extend away from the C-shaped handle **108** by a distance defined by a coupling mechanism provided between the central body **106** and the C-shaped handle **108**. In some aspects, the central body **106** and the C-shaped handle **108** are made of elastomeric thermoplastic. In general, elastomeric thermoplastics are a class of copolymers or a physical mix of polymers that include materials with both thermoplastic (thermoset) and elastomeric (elastic) properties. As such, elastomeric thermoplastics possess an ability to stretch to moderate elongations and return to their near original shape to create a sustainable and reliable material. In addition, the C-shaped handle **108** provides a curved shape to the smart stylus **100**, where the curved shape may enhance a functionality and performance of the smart stylus **100**. A curvature of the curved shape provided by the C-shaped handle **108** is strategically designed to optimize a grip and control of the patient during occupational therapy exercises. Further, the curvature of the C-shaped handle provides an ergonomic grip to the patient,

thereby reducing hand fatigue and discomfort, and also, improving usability, comfort, and continued usage of the smart stylus **100**, during a therapy session. The curvature of the C-shaped handle **108** mimics a natural shape of a hand of the patient.

[0046] In some aspects, the central body **106** is configured to taper in width and depth from the second end **106B** of the central body **106** to the first end **106A** of the central body **106**. The central body **106** is shaped in order to have a slimmer first end **106A** as compared to the second end **106B**. The central body **106** has a rounded edge rectangular cross-section having a width and a thickness that progressively decreases from the second end **106B** to the first end **106A** to couple with the stylus end **104**. Further, the handle end cap **110** is connected to a second end **108B** of the C-shaped handle **108**. In particular, the handle end cap **110** is configured to detachably, and slidably, couple with the second end **108B** of the C-shaped handle **108**, as such, the handle end cap **110** may extend away from the C-shaped handle **108** by a distance defined by a coupling mechanism provided between the handle end cap **110** and the C-shaped handle **108**.

[0047] Referring to FIG. 2, a schematic side view of the smart stylus **100** showing an extended configuration is illustrated. The extended configuration of the smart stylus **100** may be defined as an extended position at which both the central body **106** and the handle end cap **110** extend away from the C-shaped handle to increase an overall length of the smart stylus **100** as needed to adjust to different hand lengths. The extended configuration of the smart stylus **100** is defined by a first sliding mechanism **202** located between the central body **106** and the C-shaped handle **108** and a second sliding mechanism **204** located between the handle end cap **110** and the C-shaped handle **108**. In particular, the first sliding mechanism **202** is located between the central body **106** and the first end **108A** of the C-shaped handle **108**. The first sliding mechanism **202** is slidably coupled with the central body **106** and the first end **108A** of the C-shaped handle **108** in such a way that the central body **106** may move away from the C-shaped handle by a first distance 'D1'. As such, the overall length of the smart stylus **100** defined by the stylus end **104** and the C-shaped handle **108** at a normal position, otherwise known as a non-extended position, may increase by the first distance 'D1'. In one example, the first sliding mechanism **202** may include an extended portion **202A** attached to the first end **108A** of the C-shaped handle **108**. The extended portion **202A** may be configured to slidably receive within the second end **106B** of the central body **106**, as such, the central body **106** may slide over the extended portion **202A** for the first distance 'D1'. Further, a stopping mechanism may be defined in the second end **106B** of the central body **106** and the extended portion **202A** to prevent movement of the central body **106** beyond the first distance 'D1' or to avoid detachment of the central body **106** from the extended portion **202A**. Moreover, the first sliding mechanism **202** may include a locking mechanism to lock a position of the central body **106** at one or more places with the extended portion **202A** such that the overall length of the smart stylus **100** may be fixed at different lengths per the hand size of the patient. In one example, a spring biased button may be coupled to the extended portion **202A**, and multiple holes may be defined in the central body **106**. Each of the holes may be configured to receive the spring biased button therethrough and defined at equal distance to define varying overall length for the smart stylus **100** based on the number of holes. During a locking position, the spring biased button may be engaged with one of the multiple holes at normal position thereof and to cause sliding of the central body **106** over the extended portion **202A**, a force may be applied on the spring biased button to disengage from the hole. Upon releasing the force, the spring biased button is set in a preferred position by engaging with one of the multiple holes.

[0048] The smart stylus **100** further includes the second sliding mechanism **204** located between the second end **108B** of the C-shaped handle **108** and the handle end cap **110**. In particular, the second sliding mechanism **204** is slidably coupled with the handle end cap **110** and the second end **108B** of the C-shaped handle **108** in such a way that the handle end cap **110** may move away from the C-shaped handle **108** by a second distance 'D2'. As such, an overall length of a handle portion of the smart stylus **100** defined by the handle end cap **110** and the C-shaped handle **108** at a normal

position, otherwise known as a non-extended position, may increase by the second distance 'D2'. In one example, the second sliding mechanism **204** may include an extended portion **204A** attached to the second end **108B** of the C-shaped handle **108**. The extended portion **204A** may be configured to slidably receive within the handle end cap **110**, as such, the handle end cap **110** may slide over the extended portion **204A** for the second distance 'D2'. As described with reference to the first sliding mechanism **202**, the second sliding mechanism **204** may include an identical stopping mechanism and locking mechanism. As such, a length of the elongate body **102** depends on an adjustment of the first sliding mechanism **202** and the second sliding mechanism **204**. In particular, the first sliding mechanism **202** in collaboration with the second sliding mechanism **204** provides extension abilities to the smart stylus **100**. In some aspects, the above mentioned extension abilities of the smart stylus **100** adjusts the smart stylus to a comfortable length for use by the patient.

[0049] Referring to FIG. 3A, a schematic rear perspective view of the smart stylus **100** is illustrated. As can be seen from FIG. 3A, an outer region **302** of the C-shaped handle **108** includes a first groove **304** which extends from the first end **108A** of the C-shaped handle **108** to the second end **108B** of the C-shaped handle **108**. The outer region **302** of the C-shaped handle **108**, included in the smart stylus **100**, is configured to define the first groove **304** in order to allow a thumb or any one of the figures of the patient to rest inside the first groove **304** for better grip and comfort of the patient. In some aspects, the first groove **304** has a width in a range of 80% to 90% of a width of the C-shaped handle **108**, and a depth in a range of 0.25 centimeters (cm) to 1.0 cm. In other aspects, the dimensional specifications such as the width and the depth of the first groove **304** may vary based on various factors including, but not limited to, an overall size of the C-shaped handle **108**, material used for making the C-shaped handle **108**, and use of the smart stylus **100** for patients such as adult patients or young patients.

[0050] Referring to FIG. 3B, a schematic top perspective view of the smart stylus **100** is illustrated. As can be seen from FIG. 3B, an outer region **306** of the central body **106** from the second end **106B** of the central body **106** to about halfway between the first end **106A** of the central body **106** and the second end **106B** of the central body **106** includes a second groove **308** which matches the first groove **304** of the C-shaped handle **108** in depth and width. The second groove **308** is similar in dimensional specifications and constructional design to the first groove **304** to align with the first groove **304** when the central body **106** is slidably coupled to the C-shaped handle **108** using the first sliding mechanism **202**. In some aspects, the first groove **304** and the second groove **308** are defined in the outer regions **302** and **306** of the C-shaped handle **108** and the central body **106**, respectively, of the smart stylus **100** for improved grip and ergonomics of the smart stylus **100**. Further, the first groove **304** and the second groove **308** may be defined as indents, to accommodate the thumb and one or more fingers of the patient, in the C-shaped handle **108** and the central body **106**. In some aspects, a rough surface texture may be defined in the first and second grooves **304**, **308** to further improve the gripping capabilities of the smart stylus **100**. As shown in FIG. 3A, in some aspects of the present disclosure, a third groove **310** may be defined in the handle end cap **110** to match the first groove **304** in depth and width. The third groove **310** is similar in dimensional specifications and constructional design to the first groove **304** to align with the first groove **304** when the handle end cap **110** is slidably coupled to the C-shaped handle **108** using the second sliding mechanism **204**. The third groove **310** is defined in the handle end cap **110** for improved grip by accommodate the thumb or one or more fingers of the patient.

[0051] Referring to FIG. 4A, a schematic perspective view of the smart stylus **100** depicting hand holding thereof is illustrated. In some aspects, the smart stylus **100** is a flexible device which allows the patient to control an amount of pressure applied thereon based on an ability of the patient. Referring to FIG. 4B, a schematic diagram of an enlarged view of the central body **106** of the smart stylus **100** showing a first flexible grip **402** is illustrated, according to certain aspects. In particular, the smart stylus **100** includes the first flexible grip **402** located on the central body **106** halfway between the first end **106A** of the central body **106** and the second end **106B** of the central

body **106**. In some aspects, the first flexible grip **402** includes raised lines **402A** extending across the central body **106** perpendicular to a central axis 'C1' of the central body **106**. In one example, the raised lines **402A** may extend along the thickness of the central body **106**. In another example, the raised lines **402A** may extend along the width of the central body **106**. In particular, the first flexible grip **402** having the raised lines **402A** is employed to provide an anti-slip grip to the patient when holding the smart stylus **100**. In addition, the first flexible grip **402** may provide flexibility and pressure moderation abilities, while performing a task with the stylus end **104** of the smart stylus **100**. Referring to FIG. 4C, a schematic diagram of the smart stylus **100** showing a second flexible grip **404** is illustrated, according to certain aspects. In particular, the smart stylus **100** includes the second flexible grip **404** located on the handle end cap **110**, wherein the second flexible grip **404** includes raised lines **404A** extending across the handle end cap **110** perpendicular to a central axis 'C2' of the handle end cap **110**. In one example, the raised lines **404A** may extend along a thickness of the handle end cap **110**. In another example, the raised lines **402A** may extend along a width of the handle end cap **110**. In yet another example, the raised lines **404A** may be defined at an end of the handle end cap **110** along the thickness or the width thereof. The first flexible grip **402** and the second flexible grip **404** may assist the patient in improving grip strength as well as cognitive control of the pressure applied on the smart stylus **100** while performing a task. [0052] Referring to FIG. 5A, a schematic perspective view of the smart stylus **100** is illustrated. In one aspect of the present disclosure, the smart stylus **100** includes at least one upper weight receiving compartment **502**. The upper weight receiving compartment **502** is defined at the first end **108A** of the C-shaped handle **108**. In another aspect of the present disclosure, the smart stylus **100** includes at least two upper weight receiving compartments **502**. The at least two weight receiving compartments **502** further include a first upper weight receiving compartment and a second upper weight receiving compartment. As such, each upper weight receiving compartment **502** is located on either side of the C-shaped handle **108** near the first end **108A** of the C-shaped handle **108**. In one aspect of the present disclosure, the smart stylus **100** includes at least one lower weight receiving compartment **504**. The lower weight receiving compartment **504** is defined at the second end **108B** of the C-shaped handle **108**. In another aspect of the present disclosure, the smart stylus **100** includes at least two lower weight receiving compartments **504**. The lower weight receiving compartments **504** further include a first weight receiving compartment and a second weight receiving compartment. As such, each lower weight receiving compartment **504** is located on either side of the C-shaped handle **108** near the second end **108B** of the C-shaped handle **108**. [0053] Referring to FIG. 5B, a schematic diagram of a plurality of weights **510** is illustrated, according to certain aspects. In particular, each weight of the plurality of weights **510** is sized to fit within a respective weight receiving compartment. The respective weight receiving compartment refers to the upper and lower weight receiving compartments **502**, **504**. The upper weight receiving compartments **502** are configured to be hollow and structurally reinforced portion to securely house one or more of the plurality of weights **510**. Similarly, the lower weight receiving compartments **504** are configured to be hollow and structurally reinforced portions to securely house one or more of the plurality of weights **510**. In an example, the plurality of weights **510** includes, but are not limited to, one or more first weights weighing 10 grams, one or more second weights weighing 15 grams, and one or more third weights weighing 20 grams. In some aspects, as shown in FIG. 5A, the plurality of weights **510** includes an oblong weight **510A** and a cylindrical weight **510B**. The oblong weight **510A** may have a cuboid shape and be configured to fit within the respective weight receiving compartments. Similarly, the cylindrical weight **510B** may have a cylinder shape and be configured to fit within the respective weight receiving compartments. In particular, each side of the C-shaped handle **108** includes a weight receiving compartment sized to receive the oblong weight **510A** and a weight receiving compartment sized to receive the cylindrical weight **510B**. Each weight receiving compartment may include retention features to hold a respective weight within the weight receiving compartment. In a non-limiting example, the retention features may

include indentations in the sides of the weight receiving compartment configured to grip the weight. In another non-limiting example, the weights may have corresponding features, such as raised bands which are configured to fit within the indentations. In another non-limiting example, the weight receiving compartment may have a door as shown connected to **502** in FIG. 5A to cover the weight receiving compartment **502**. Weight receiving compartment **504** may also have a door, as shown in FIG. 5A.

[0054] Referring to FIG. 5C and FIG. 5D, schematic illustrations of a method of removing one or more of the plurality of weights **510** from weight receiving slots defined in a case is depicted. In some aspects, the plurality of weights **510** may be removed manually, and installed manually in the upper and lower weight receiving compartments **502**, **504** of the smart stylus **100**. The plurality of weights **510** are included in order to keep the patient from hitting a therapeutic plateau during rehabilitation phase. More particularly, a therapeutic plateau refers to a stagnancy in a course of recovery of the patient. In some cases, when certain parameters such as, but are not limited to, weight of a therapeutic instrument, and a style of a therapeutic program are not varied sufficiently, the patient may reach at the therapeutic plateau, hindering the patient from further rehabilitation. When subjected to dissimilar therapeutic techniques, the brain of the patient may halt formation of new neural pathways, which are essential for continued rehabilitation. In an example, the plurality of weights **510** are placed within the weight receiving compartments in such a way that a top end of the weight **510** projects above a top surface of the case so that the patient can easily remove the plurality of weights **510** from the case. In another example, an indent or a raised portion may be defined at the top end of the plurality of weights **510** to comfortably hold the plurality of weights **510** while removing the plurality of weights **510** from the weight receiving slots.

[0055] Referring to FIG. 6A, a schematic perspective view of the smart stylus **100** showing one or more internal components is illustrated, according to certain aspects. The smart stylus **100** includes a rechargeable battery **602** located within the handle end cap **110**. In an example, the rechargeable battery **602** may be equipped with wireless charging technology and supports normal functioning of the smart stylus **100**. In some aspects, the rechargeable battery **602** may be a lithium-ion battery, a lithium-polymer battery, a nickel-cadmium battery, and the like. The handle end cap **110** is configured to have sufficient space in order to accommodate the rechargeable battery **602**. Further, referring to FIG. 6B, a schematic illustration of an electromagnetic coil **604** is depicted, according to certain aspects. In particular, the smart stylus **100** includes the electromagnetic coil **604** for wireless charging of the rechargeable battery **602**. The electromagnetic coil **604** may be made of copper (Cu), or any other suitable ferrite material. Furthermore, referring to FIG. 6C, a schematic illustration of a pressure sensor **610** is depicted, according to certain aspects. In particular, the rechargeable battery **602** is electrically coupled with the pressure sensor **610** located within the elongate body **102**. The pressure sensor **610** is further connected to the stylus end **104**. The pressure sensor **610** is configured to generate an electric signal indicative of an amount of pressure applied on the stylus end **104** by the patient when the smart stylus **100** is in use. Further, the pressure sensor **610** is configured to communicate with the rechargeable battery **602** to receive operating power therefrom. Though FIG. 6C illustrates a specific construction of the pressure sensor **610**, any other known pressure sensor adaptable to the smart stylus **100** may be implemented for the purpose of detecting the amount of pressure applied on the smart stylus **100** by the patient. Moreover, as can be seen in FIG. 6A, the smart stylus **100** includes a microcontroller **612** located within the central body **106**. In some aspects, the microcontroller **612** is operatively connected to the rechargeable battery **602** and the pressure sensor **610**. The microcontroller **612** is configured to communicate with the pressure sensor **610** to receive the electric signal indicative of the amount of pressure applied on the smart stylus **100**. Upon receiving the electric signal, the microcontroller **612** may be configured to determine a pressure value and the pressure value may be further stored in a memory of the microcontroller **612** for further reference or use. The microcontroller **612** is configured to communicate with the rechargeable battery **602** to control charging of the rechargeable battery **602**.

In some aspects, the smart stylus **100** includes a near field communications unit **614** located within the central body **106** and operatively connected with the microcontroller **612**. In some aspects, an additional rechargeable battery may be located with the central body **106** to power the pressure sensor **610**, the microcontroller **612**, and the near field communications unit **614**. The additional rechargeable battery may be charged using the wireless charging technology. The electrical connection among the rechargeable battery **602**, the pressure sensor **610**, the microcontroller **612**, and the near field communications unit **614** are shown schematically in FIG. **6A** by broken lines. In general, near field communication (NFC) is a set of communication protocols that provides communication between two electronic devices over a distance of 4 centimeters or less. NFC offers a low-speed connection through a simple setup that may be used for the bootstrapping of capable wireless connections. Similar to other proximity card technologies, NFC is based on inductive coupling between two electromagnetic coils present on a NFC-enabled device such as a tablet. NFC communicating in one or both directions uses a frequency of 13.56 MHz in the globally available unlicensed radio frequency ISM band, compliant with the ISO/IEC 18000-3 air interface standard at data rates ranging from 106 to 848 kbit/s. In some aspects of the present disclosure, the near field communications unit **614** may be included in order to send a set of data from the smart stylus **100** to a plurality of devices present in a vicinity of the smart stylus **100**. In some aspects of the present disclosure, the near field communications unit **614** may be included in order to receive another set of data from the plurality of devices present in the vicinity of the smart stylus **100**. Further, the microcontroller **612** is configured to be operatively and electrically coupled with the rechargeable battery **602**, the pressure sensor **610**, and the near field communications unit **614**. In a non-limiting example, the near field communications unit **614** may use a Bluetooth protocol.

[0056] Referring to FIG. **7A**, a smart stylus therapeutic system **700** for use in hand therapy is illustrated, according to certain aspects. The smart stylus therapeutic system **700** is alternatively referred to as 'the system **700**' for brevity in explanation. The system **700** refers to the smart stylus **100** in conjunction with a therapeutic tablet **702** for use in the hand therapy, such as, hand rehabilitation and movement restoration after a stroke. In some aspects, the system **700** includes the smart stylus **100** including the elongate body **102** having the stylus end **104**. Further, the smart stylus **100** includes the central body **106**, the C-shaped handle **108**, and the handle end cap **110**. As such, the stylus end **104** is connected to the first end **106A** of the central body **106**, the second end **106B** of the central body **106** is connected to the first end **108A** of the C-shaped handle **108**. Furthermore, the handle end cap **110** is connected to the second end **108B** of the C-shaped handle **108**. The system **700** further includes the rechargeable battery **602** located within the handle end cap **110**. In addition, the system **700** includes the microcontroller **612** located within the central body **106** and the microcontroller **612** is operatively connected to the rechargeable battery **602**. The system **700** further includes the near field communications unit **614** located within the central body **106** and operatively connected with the microcontroller **612**.

[0057] The system **700** includes a case **710**. The case **710** is configured to hold the elongate body **102**, in particular the smart stylus **100**, and the therapeutic tablet **702**. In some aspects, the case **710** includes a charging port **712** configured to mate with the handle end cap **110** of the smart stylus **100**. In addition, the system **700** includes the electromagnetic coil **604** located within the handle end cap **110** and connected to the rechargeable battery **602**. As such, the electromagnetic coil **604** is configured to generate a charging current when the handle end cap **110** is placed adjacent to the charging port **712**. In particular, the charging port **712** is a wireless charging station, providing the smart stylus **100** of the system **700** with wireless charging capabilities, and the electromagnetic coil **604** present in the handle end cap **110** is configured to receive the charging current from the charging port **712**. In an aspect, the charging port **712** is defined as an engraved slot in the case **710** having a size and shape identical to the shape and size of the handle end cap **110** such that the handle end cap **110** may be received within the charging port **712** for charging the smart stylus **100**. In some aspects, a voltage, and an ampere of the charging current may be predetermined based on

safety and performance parameters. In some aspects, the charging port **712** may have a temperature sensors in order to detect heat generated during the charging of the smart stylus **100** and protect the system **700** from overheating during the charging process.

[0058] In some aspects, the system **700** includes the therapeutic tablet **702** equipped with a touch screen **714**. The therapeutic tablet **702** includes a memory **716** for storing program instructions including a hand therapy treatment plan. Further, the therapeutic tablet **702** includes one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit **614**.

[0059] The smart stylus **100** of the system **700** includes the at least two upper weight receiving compartments **502**, and each upper weight receiving compartment of the at least two upper weight receiving compartments **502** is located on either side of the C-shaped handle **108** near the first end **108A** thereof. In addition, the smart stylus **100** of the system **700** includes the at least two lower weight receiving compartments **504**, and each lower weight receiving compartment of the at least two lower weight receiving compartments **504** is located on either side of the C-shaped handle **108** near the second end **108B**. Further, the system **700** includes the plurality of weights **510**, each weight of the plurality of weights **510** is sized to fit within the respective weight receiving compartments. In some aspects, the plurality of weights **510** is stored in weight receiving slots **718** defined in the case **710**. The case **710** is configured to define the weight receiving slots **718** on top left corner of the case **710**. The weight receiving slots **718** are crafted with precision in order to suit the dimensional specifications and constructional details of the plurality of weights **510**.

[0060] Referring to FIG. 7B, a schematic illustration of a program instruction on the touch screen **714** of the therapeutic tablet **702** is illustrated, according to certain aspects. The touch screen **714** prompts a set of instructions asking the patient to register and create an account. The account may be used to track the progress of the patient over time. Further, referring to FIG. 7C, a schematic illustration of another program instruction displayed on the touch screen **714** is illustrated, according to certain aspects. The program instructions as executed by the one or more processors displays a selection of tasks for the patient or physical therapist to select and proceed accordingly.

[0061] Referring to FIG. 7D, a schematic illustration of the touch screen **714** displaying the hand therapy treatment plan is illustrated. In particular, the program instructions as included in the therapeutic tablet **702**, when executed by the one or more processors, display the hand therapy treatment plan and hand therapy exercises upon the touch screen **714**. The hand therapy exercises are configured to direct the patient to write upon the touch screen **714** with the stylus end **104** while gripping the C-shaped handle **108**. In some aspects, the patient may grip the smart stylus **100** of the system **700** with the first and the second flexible grips **402**, **404**.

[0062] Referring to FIG. 8A and FIG. 8B, schematic illustrations of the system **700** and the therapeutic tablet **702** are illustrated, according to certain aspects. As can be seen from FIG. 8A, the smart stylus, weights, charger and therapeutic tablet are held in a single unit. As can be seen from FIG. 8B, the therapeutic tablet **702** is configured to receive a battery charge status by the near field communications from the microcontroller **612** and display the battery charge status on the touch screen **714**. The touch screen **714** of the therapeutic tablet **702** displays the battery charge status of the rechargeable battery **602** present in the handle end cap **110** of the smart stylus **100**, in order to keep the patient updated of the battery charge status for the smart stylus **100**. In some aspects, the therapeutic tablet **702** and the touch screen **714** may show an alert if the battery charge status is low and alert the patient to charge the smart stylus **100** as required. Further, the smart stylus **100** of the system **700** includes the pressure sensor **610** located within the elongate body **102** and connected to the stylus end **104**. In particular, the pressure sensor **610** is connected to the microcontroller **612**, as such, the pressure sensor **610** is configured to generate electrical signals in response to the amount of pressure sensed by the pressure sensor **610** when the stylus end **104** contacts the touch screen **714**. In general, pressure sensors are devices that translate a magnitude of a physical pressure that is being exerted on the pressure sensor **610** into an output signal that may be used to establish a

quantitative value for the pressure. In some aspects, the pressure sensor **610** may be including, but not limited to, potentiometric pressure sensors, inductive pressure sensors, capacitive pressure sensors, piezoelectric pressure sensors, strain gauge pressure sensors, variable reluctance pressure sensors, or a combination thereof.

[0063] The microcontroller **612** is configured to transmit the electrical signals related to the amount of pressure by near field communications to the therapeutic tablet **702**. In other words, a magnitude of the pressure sensed by the pressure sensor **610** is determined and transmitted to the therapeutic tablet **702** by the near field communications unit **614**. The therapeutic tablet **702** makes it easy for the patient to read and understand pressure readings, as recorded by the pressure sensor **610**. In addition, the therapeutic tablet **702** is configured to receive the electrical signals related to the amount of pressure of the stylus end **104** against the touch screen **714** and select a weight from the plurality of weights **510** in accordance with the hand therapy treatment plan. The system **700** has the ability to determine appropriate weight amount, via the hand therapy treatment plan, for a particular patient depending on where the patient is in terms of progress pertaining to the hand therapy treatment plan. In some aspects, a dynamic approach of weight selection keeps the patient from hitting therapeutic plateau during the hand therapy. In some aspects, the hand therapy exercises include grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve the motor skills, coordination, and cognitive functions. In some aspects, the hand therapy exercises may be remotely updated via a software application and additional exercises may be added to the existing hand therapy exercises in order to better suit the patient and therapeutic requirements.

[0064] Referring to FIG. **8C**, a schematic diagram of the smart stylus **100** having one or more proximity sensors **802** is illustrated, according to certain aspects. The one or more proximity sensors **802** may further include a first proximity sensor **802A** and a second proximity sensor **802B**. In particular, the first proximity sensor **802A** is configured to be placed near a center of the central body **106** of the smart stylus **100**. The second proximity sensor **802B** is configured to be placed near a distal end of the handle end cap **110**. The first proximity sensor **802A** and the second proximity sensor **802B** are configured to measure a distance between the center of the central body **106** and the distal end of the handle end cap **110**. Further, the one or more proximity sensors **802** are electrically and operatively coupled with the rechargeable battery **602**. In some aspects, sensor data collected by the one or more proximity sensors **802** is communicated to the microcontroller **612**, and subsequently relayed on to the therapeutic tablet **702**. In particular, shrinking of the distance between the proximity sensors of the smart stylus **100** due to the pressure applied by the patient may be determined by the first and second proximity sensors **802A**, **802B**. The distance readings between the central body **106** and the distal end of the handle end cap **110** may provide additional information required by the one or more physicians in order to develop a better rehabilitation therapy plan for the patient. In some aspects, the therapeutic tablet **702** may be connected with the microcontroller **612** via a Wi-Fi connection, an LTE connection, a mobile application platform, a website platform, or a combination thereof.

[0065] Referring to FIG. **9**, a schematic block diagram of a patient assessment computing environment **900** is illustrated, according to certain aspects. In particular, the system **700** includes a patient assessment unit **902** located within the therapeutic tablet **702**. The patient assessment unit **902** is configured to monitor a progress of the patient against a baseline assessment and generate a progress report. Further, the system **700** includes a wireless communication unit **904** located within the therapeutic tablet **702**. The wireless communication unit **904** is configured to wirelessly transmit the progress report to a remote medical system **906** configured to monitor the progress of the patient. The progress of the patient is tracked throughout the hand therapy process, and a progress report is generated based on the baseline assessment of the patient. The baseline assessment refers to the assessment of the motor skills, hand-eye coordination, and cognitive skills of the patient conducted before the enrollment of the patient into the hand therapy. In respect to the

baseline assessment, the progress report is tracked and sent to the remote medical system **906**, where one or more healthcare professionals further examine the progress report of the patient. The remote medical system **906** is an integral part of the system **700** in order to make the hand therapy dynamic, adaptive and effective in developing new neural pathways in the brain of the patient. [0066] Referring to FIG. **10**, a flowchart depicting a method **1000** of using the smart stylus **100** in hand therapy is illustrated, according to certain aspects. The order in which the method **1000** is described is not intended to be construed as a limitation, and any number of the described method steps may be combined in any order to implement the method **1000**. Additionally, individual steps may be removed from or added to the method **1000** as needed in the therapy without departing from the spirit and scope of the present disclosure.

[0067] At step **1002**, the method **1000** includes forming the elongate body **102** having the stylus end **104**, the central body **106**, the C-shaped handle **108**, and the handle end cap **110**. Further, the stylus end **104** is connected to the first end **106A** of the central body **106** and the second end **106B** of the central body **106** is connected to the first end **108A** of the of the C-shaped handle **108**. Furthermore, the handle end cap **110** is connected to the second end **108B** of the C-shaped handle **108**. In an aspect, the central body **106**, the C-shaped handle **108**, the handle end cap **110**, and the stylus end **104** are manufactured as individual elements using various known manufacturing process. Further, the first end **106A** of the central body **106** is detachably coupled to the stylus end **104** and the second end **106B** of the central body **106** is slidably coupled to the first end **108A** of the C-shaped handle **108** using the first sliding mechanism **202**. The second end **108B** of the C-shaped handle **108** is slidably attached to the handle end cap **110** using the second sliding mechanism **204**. As such, the central body **106**, the stylus end **104**, the C-shaped handle **108**, and the handle end cap **110** are detachably coupled to form the elongate body **102** of the smart stylus **100**.

[0068] At step **1004**, the method **1000** includes installing the rechargeable battery **602** within the handle end cap **110**, into the smart stylus **100**. In one aspect, a receiving portion may be defined in the handle end cap **110** to insert the rechargeable battery **602**. As such, after forming the elongate body **102**, a user may manually place the rechargeable battery **602** within the handle end cap **110** and may remove or replace the rechargeable battery **602** as needed. In another aspect, the rechargeable battery **602** may be installed in the handle end cap **110** during the manufacturing of the smart stylus **100** such that the rechargeable battery **602** become an integral component of the smart stylus **100** and may not be replaceable or removable by the user during the life time of the smart stylus **100**.

[0069] At step **1006**, the method **1000** includes inserting the microcontroller **612** within the central body **106** of the smart stylus **100**, as such, the microcontroller **612** receives operating current from the rechargeable battery **602**. As explained with reference to the rechargeable battery **602** at the step **1004**, the microcontroller **612** may be either installed with the central body **106** during the manufacturing thereof to become an integral portion thereof or the microcontroller **612** may be installed by the user upon forming the elongate body **102** of the smart stylus **100**.

[0070] At step **1008**, the method **1000** includes operatively connecting the microcontroller **612** to the rechargeable battery **602**. As such, the rechargeable battery **602** supplies a required power input to the microcontroller **612**. At step **1010**, the method **1000** includes forming the case **710** to hold the elongate body **102** of the smart stylus **100** and the therapeutic tablet **702**. In particular, the case **710** may be formed using an elastomeric thermoplastic, a polymeric plastic, a metal alloy mixed with a plastic, and the like. The case **710** is defined as a rectangular body to accommodate the smart stylus **100** towards a left end of the case **710** and the touch screen **714** towards the right end of the case. The weight receiving slots **718** are defined at the top left corner of the case **710** for the patient to comfortably and conveniently access the plurality of the weights **510**.

[0071] At step **1012**, the method **1000** includes forming the charging port **712** in the case **710**. As such, the charging port **712** is configured to mate with the handle end cap **110** of the smart stylus

100. Further, at step **1014**, the method **1000** includes installing the electromagnetic coil **604** within the handle end cap **110** and connecting the electromagnetic coil **604** to the rechargeable battery **602**. In some aspects, the electromagnetic coil **604** is configured to generate the charging current when the handle end cap **110** is placed adjacent to the charging port **712**. The electromagnetic coil **604** is configured to receive the charging current transmitted by the charging port **712** present on the case **710**. In some aspects, charging may be wireless charging. At step **1016**, the method **1000** includes installing the near field communications unit **614** within the central body **106** and operatively connecting the near field communications unit **614** with the microcontroller **612**. The near field communications unit **614** receives instructions from the microcontroller **612** electronically, on a command given by the patient to the microcontroller **612**.

[0072] At step **1018**, the method **1000** includes linking the therapeutic tablet **702** including the touch screen **714** to the microcontroller **612**. Furthermore, the therapeutic tablet **702** includes the memory **716**, including program instruction including the hand therapy treatment plan and the one or more processors for executing the program instructions to receive near field communications from the near field communications unit **614**. Moreover, the therapeutic tablet **702** displays the hand therapy treatment plan and hand therapy exercises upon the touch screen **714**. The hand therapy exercises are configured to direct the patient to write upon the touch screen **714** with the stylus end **104** while gripping the C-shaped handle **108**, and also, while gripping the first and the second flexible grips **402**, **404**. The hand therapy treatment plan is embedded into the program instruction stored in the memory **716** of the therapeutic tablet **702**. The program instructions are executed by the processor when the patient prompts the system **700** for the hand therapy exercises. When executed, the patient performs the said hand therapy exercises by gripping the smart stylus **100**, on the touch screen **714** of the therapeutic tablet **702**.

[0073] The method **1000** further includes connecting the pressure sensor **610** to the stylus end **104** and connecting the pressure sensor **610** to the microcontroller **612**. In addition, the method **1000** includes generating, by the pressure sensor **610**, electrical signals in response to an amount of pressure sensed by the pressure sensor **610** when the stylus end **104** contacts the touch screen **714**. In other words, when the patient uses the smart stylus **100** on the touch screen **714** of the therapeutic tablet **702**, the pressure exerted by the patient on the stylus end **104** is sensed by the pressure sensor **610** and is subsequently relayed on to the microcontroller **612**. Furthermore, the method **1000** includes transmitting, by the near field communications unit **614**, the electrical signals related to the amount of pressure by near field communication to the therapeutic tablet **702**. In some aspects, the method **1000** includes displaying, on the touch screen **714**, the hand therapy exercises including grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve motor skills, coordination, and cognitive functions of the patient.

[0074] The method **1000** further includes monitoring the progress of the patient by the patient assessment unit **902** located within the therapeutic tablet **702**, and comparing, by the patient assessment unit **902**, the progress of the patient against the baseline assessment. As described above, the baseline assessment is conducted before the enrollment of the patient in the hand therapy and further assessments are made using the patient assessment unit **902**, as the patient progresses in the hand therapy treatment plan. Furthermore, the method **1000** includes generating, by the patient assessment unit **902**, the progress report and transmitting, by a wireless communication unit **904** located within the therapeutic tablet **702**, the progress report to the remote medical system **906** configured to monitor the progress of the patient.

[0075] The first embodiment of the present disclosure is illustrated with respect to FIG. **1** through FIG. **6C**. The first embodiment describes the smart stylus **100** for use in hand therapy, including an elongate body **102** having the stylus end **104**, the central body **106**, the C-shaped handle **108**, and the handle end cap **110**, wherein the stylus end **104** is connected to the first end **106A** of the central body **106**, the second end **106B** of the central body **106** is connected to the first end **108A** of the C-shaped handle **108**, wherein the central body **106** is configured to taper in width and depth from the

second end **106B** of the central body **106** to the first end **106A** of the central body **106**, wherein the handle end cap **110** is connected to the second end **108B** of the C-shaped handle **108**. The first sliding mechanism **202** is located between the central body **106** and the first end **108A** of the C-shaped handle **108**, and the second sliding mechanism **204** is located between the second end **108B** of the C-shaped handle **108** and the handle end cap **110**, wherein the length of the elongate body **102** depends on an adjustment of the first sliding mechanism **202** and the second sliding mechanism **204**.

[0076] In an aspect of the smart stylus **100**, the outer region **302** of the C-shaped handle **108** includes the first groove **304** which extends from the first end **108A** of the C-shaped handle **108** to the second end **108B** of the C-shaped handle **108**, wherein the first groove **304** has the width in a range of 80% to 90% of the width of the C-shaped handle **108** and the depth in the range of 0.25 to 1.0 cm.

[0077] In an aspect of the smart stylus **100**, the outer region **306** of the central body **106** from the first end **106A** of the central body **106** to about halfway between the first end **106A** of the central body **106** and the second end **106B** of the central body **106** includes the second groove **308** which matches the first groove **304** of the C-shaped handle **108** in depth and width.

[0078] In an aspect, the smart stylus **100** further including the first flexible grip **402** located on the central body **106** halfway between the first end **106A** of the central body **106** and the second end **106B** of the central body **106**, wherein the first flexible grip **402** includes raised lines **402A** extending across the central body **106** perpendicular to the central axis 'C1' of the central body **106**, and the second flexible grip **404** located on the handle end cap **110**, wherein the second flexible grip **404** includes raised lines **404A** extending across the handle end cap **110** perpendicular to the central axis 'C2' of the handle end cap **110**.

[0079] In an aspect, the smart stylus **100** further including the at least two upper weight receiving compartments **502**, wherein each upper weight receiving compartment is located on either side of the C-shaped handle **108** near the first end **108A**, and the at least two lower weight receiving compartments **504**, wherein each lower weight receiving compartment is located on either side of the C-shaped handle **108** near the second end **108B**, and the plurality of weights **510**, wherein each weight is sized to fit within a respective weight receiving compartment.

[0080] In an aspect of the smart stylus **100**, the plurality of weights **510** includes the oblong weight **510A** and the cylindrical weight **510B**, wherein each side of the C-shaped handle **108** includes a weight receiving compartment sized to receive the oblong weight **510A** and a weight receiving compartment sized to receive the cylindrical weight **510B**.

[0081] In an aspect of the smart stylus **100**, the elongate body **102** and the C-shaped handle **108** are made of the elastomeric thermoplastic.

[0082] In an aspect, the smart stylus **100** further including the rechargeable battery **602** located within the handle end cap **110**.

[0083] In an aspect, the smart stylus **100** further including the pressure sensor **610** located within the elongate body **102** and connected to the stylus end **104**.

[0084] In an aspect, the smart stylus **100** further including the microcontroller **612** located within the central body **106**, wherein the microcontroller **612** is operatively connected to the rechargeable battery **602** and the pressure sensor **610**, and the near field communications unit **614** located within the central body **106** and operatively connected with the microcontroller **612**.

[0085] The second embodiment of the present disclosure is illustrated with respect to FIG. 7A through FIG. 9. The second embodiment describes the smart stylus therapeutic system **700** for use in hand therapy, including an elongate body **102** having the stylus end **104**, the central body **106**, the C-shaped handle **108**, and the handle end cap **110**, wherein the stylus end **104** is connected to the first end **106A** of the central body **106**, the second end **106B** of the central body **106** is connected to the first end **108A** of the C-shaped handle **108**, and the handle end cap **110** is connected to the second end **108B** of the C-shaped handle **108**, the rechargeable battery **602** located

within the handle end cap **110**, the microcontroller **612** located within the central body **106**, wherein the microcontroller **612** is operatively connected to the rechargeable battery **602**, the near field communications unit **614** located within the central body **106** and operatively connected with the microcontroller **612**, the therapeutic tablet **702** including the touch screen **714**, wherein the therapeutic tablet **702** includes the memory **716** including program instructions including the hand therapy treatment plan and the one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit **614** and display the hand therapy treatment plan and the hand therapy exercises upon the touch screen **714**, wherein the hand therapy exercises are configured to direct the patient to write upon the touch screen **714** with the stylus end **104** while gripping the C-shaped handle **108**, the case **710** configured to hold the elongate body **102** and the therapeutic tablet **702**, the charging port **712** located on the case **710**, wherein the charging port **712** is configured to mate with the handle end cap **110**, the rechargeable battery located with the central body **106**, the electromagnetic coil **604** located within the handle end cap **110** and connected to the rechargeable battery **602**, wherein the electromagnetic coil **604** is configured to generate the charging current when the handle end cap **110** is placed adjacent to the charging port **712**.

[0086] In an aspect of the smart stylus therapeutic system **700**, the therapeutic tablet **702** is configured to receive the battery charge status by near field communications from the microcontroller **612** and display the battery charge status on the touch screen **714**.

[0087] In an aspect, the smart stylus therapeutic system **700** further including the pressure sensor **610** located within the elongate body **102** and connected to the stylus end **104**, wherein the pressure sensor **610** is connected to the microcontroller **612**, wherein the pressure sensor **610** is configured to generate electrical signals in response to an amount of pressure sensed by the pressure sensor **610** when the stylus end **104** contacts the touch screen **714**, and wherein the microcontroller **612** is configured to transmit the electrical signals related to the amount of pressure by near field communications to the therapeutic tablet **702**.

[0088] In an aspect, the smart stylus therapeutic system **700** further including the at least two upper weight receiving compartments **502**, wherein each upper weight receiving compartment is located on either side of the C-shaped handle **108** near the first end **108A**, and the at least two lower weight receiving compartments **504**, wherein each lower weight receiving compartment is located on either side of the C-shaped handle **108** near the second end **108B**, and the plurality of weights **510**, wherein each weight is sized to fit within the respective weight receiving compartment, wherein the plurality of weights are stored in the weight receiving slots **718** in the case **710**, and wherein the therapeutic tablet **702** is configured to receive the electrical signals related to the amount of pressure of the stylus end **104** against the touch screen **714** and select the weight from the plurality of weights **510** in accordance with the hand therapy treatment plan. In an aspect of the smart stylus therapeutic system **700**, the hand therapy exercises include grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve motor skills, coordination, and cognitive functions.

[0089] In an aspect, the smart stylus therapeutic system **700** further including the patient assessment unit **902** located within the therapeutic tablet **702**, wherein the patient assessment unit **902** is configured to monitor the progress of the patient against the baseline assessment and generate the progress report, and the wireless communication unit **904** located within the therapeutic tablet **702**, wherein the wireless communication unit **904** is configured to wirelessly transmit the progress report to the remote medical system **906** configured to monitor the progress of the patient.

[0090] The third embodiment of the present disclosure is illustrated with respect to FIG. **10**. The third embodiment describes the method **1000** of using the smart stylus **100** in the hand therapy, including forming the elongate body **102** having the stylus end **104**, the central body **106**, the C-shaped handle **108**, and the handle end cap **110**, wherein the stylus end **104** is connected to the first

end **106A** of the central body **106**, the second end **106B** of the central body **106** is connected to the first end **108A** of the C-shaped handle **108**, and the handle end cap **110** is connected to the second end **108B** of the C-shaped handle **108**, installing the rechargeable battery **602** within the handle end cap **110**, inserting the microcontroller **612** within the central body **106**, operatively connecting the microcontroller **612** to the rechargeable battery **602**, forming the case **710** configured to hold the elongate body **102** and the therapeutic tablet **702**, forming the charging port **712** in the case **710**, wherein the charging port **712** is configured to mate with the handle end cap **110**, installing the electromagnetic coil **604** within the handle end cap **110** and connecting the electromagnetic coil **604** to the rechargeable battery **602**, wherein the electromagnetic coil **604** is configured to generate the charging current when the handle end cap **110** is placed adjacent to the charging port **712**, installing the near field communications unit **614** within the central body **106** and operatively connecting the near field communications unit **614** with the microcontroller **612**, and linking the therapeutic tablet **702** including the touch screen **714** to the microcontroller **612**, wherein the therapeutic tablet **702** includes the memory **716** including program instructions including the hand therapy treatment plan and the one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit **614** and display the hand therapy treatment plan and the hand therapy exercises upon the touch screen **714**, wherein the hand therapy exercises are configured to direct the patient to write upon the touch screen **714** with the stylus end **104** while gripping the C-shaped handle **108**.

[0091] In an aspect, the method **1000** further including connecting the pressure sensor **610** to the stylus end **104** and connecting the pressure sensor **610** to the microcontroller **612**, generating, by the pressure sensor **610**, electrical signals in response to the amount of pressure sensed by the pressure sensor **610** when the stylus end **104** contacts the touch screen **714**, and transmitting, by the near field communications unit **614**, the electrical signals related to the amount of pressure by near field communication to the therapeutic tablet **702**.

[0092] In an aspect, the method **1000** further including displaying, on the touch screen **714**, the hand therapy exercises including grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve motor skills, coordination, and cognitive functions of the patient.

[0093] In an aspect, the method **1000** further including monitoring the progress of the patient by the patient assessment unit **902** located within the therapeutic tablet **702**, comparing, by the patient assessment unit **902**, the progress of the patient against the baseline assessment, generating, by the patient assessment unit **902**, the progress report, and transmitting, by the wireless communication unit **904** located within the therapeutic tablet **702**, the progress report to the remote medical system **906** configured to monitor the progress of the patient.

[0094] Next, further details of the hardware description of the computing environment according to exemplary aspects is described with reference to FIG. **11**. In FIG. **11**, a controller **1100** is described, representative of the system **700** of FIG. **7A** in which the controller is a computing device which includes a CPU **1101** which performs the processes described above/below. The process data and instructions may be stored in memory **1102**. These processes and instructions may also be stored on a storage medium disk **1104** such as a hard drive (HDD) or portable storage medium or may be stored remotely.

[0095] Further, the claims are not limited by the form of the computer-readable media on which the instructions of the inventive process are stored. For example, the instructions may be stored on CDs, DVDs, in FLASH memory, RAM, ROM, PROM, EPROM, EEPROM, hard disk or any other information processing device with which the computing device communicates, such as a server or computer.

[0096] Further, the claims may be provided as a utility application, background daemon, or component of an operating system, or combination thereof, executing in conjunction with CPU **1101**, **1103** and an operating system such as Microsoft Windows 7, Microsoft Windows 10,

Microsoft Windows 11, UNIX, Solaris, LINUX, Apple MAC-OS and other systems known to those skilled in the art.

[0097] The hardware elements in order to achieve the computing device may be realized by various circuitry elements, known to those skilled in the art. For example, CPU **1101** or CPU **1103** may be a Xenon or Core processor from Intel of America or an Opteron processor from AMD of America, or may be other processor types that would be recognized by one of ordinary skill in the art. Alternatively, the CPU **1101**, **1103** may be implemented on an FPGA, ASIC, PLD or using discrete logic circuits, as one of ordinary skill in the art would recognize. Further, CPU **1101**, **1103** may be implemented as multiple processors cooperatively working in parallel to perform the instructions of the inventive processes described above.

[0098] The computing device in FIG. **11** also includes a network controller **1106**, such as an Intel Ethernet PRO network interface card from Intel Corporation of America, for interfacing with network **1160**. As can be appreciated, the network **1160** can be a public network, such as the Internet, or a private network such as an LAN or WAN network, or any combination thereof and can also include PSTN or ISDN sub-networks. The network **1160** can also be wired, such as an Ethernet network, or can be wireless such as a cellular network including EDGE, 3G, 4G and 5G wireless cellular systems. The wireless network can also be Wi-Fi, Bluetooth, or any other wireless form of communication that is known.

[0099] The computing device further includes a display controller **1108**, such as a NVIDIA GeForce GTX or Quadro graphics adaptor from NVIDIA Corporation of America for interfacing with display **1110**, such as a Hewlett Packard HPL2445w LCD monitor. A general purpose I/O interface **1112** interfaces with a keyboard and/or mouse **1114** as well as a touch screen panel **1116** on or separate from display **1110**. General purpose I/O interface also connects to a variety of peripherals **1118** including printers and scanners, such as an Office-Jet or Desk-Jet from Hewlett Packard.

[0100] A sound controller **1120** is also provided in the computing device such as Sound Blaster X-Fi Titanium from Creative, to interface with speakers/microphone **1122** thereby providing sounds and/or music.

[0101] The general purpose storage controller **1124** connects the storage medium disk **1104** with communication bus **1126**, which may be an ISA, EISA, VESA, PCI, or similar, for interconnecting all of the components of the computing device. A description of the general features and functionality of the display **1110**, keyboard and/or mouse **1114**, as well as the display controller **1108**, storage controller **1124**, network controller **1106**, sound controller **1120**, and general purpose I/O interface **1112** is omitted herein for brevity as these features are known.

[0102] The exemplary circuit elements described in the context of the present disclosure may be replaced with other elements and structured differently than the examples provided herein. Moreover, circuitry configured to perform features described herein may be implemented in multiple circuit units (e.g., chips), or the features may be combined in circuitry on a single chipset, as shown on FIG. **12**.

[0103] FIG. **12** shows a schematic diagram of a data processing system, according to certain aspects, for performing the functions of the exemplary aspects. The data processing system is an example of a computer in which code or instructions implementing the processes of the illustrative aspects may be located.

[0104] In FIG. **12**, data processing system **1200** employs a hub architecture including a north bridge and memory controller hub (NB/MCH) **1225** and a south bridge and input/output (I/O) controller hub (SB/ICH) **1220**. The central processing unit (CPU) **1230** is connected to NB/MCH **1225**. The NB/MCH **1225** also connects to the memory **1245** via a memory bus and connects to the graphics processor **1250** via an accelerated graphics port (AGP). The NB/MCH **1225** also connects to the SB/ICH **1220** via an internal bus (e.g., a unified media interface or a direct media interface). The CPU Processing unit **1230** may contain one or more processors and even may be implemented

using one or more heterogeneous processor systems.

[0105] For example, FIG. 13 shows one implementation of CPU 1230. In one implementation, the instruction register 1338 retrieves instructions from the fast memory 1340. At least part of these instructions are fetched from the instruction register 1338 by the control logic 1336 and interpreted according to the instruction set architecture of the CPU 1230. Part of the instructions can also be directed to the register 1332. In one implementation the instructions are decoded according to a hardwired method, and in another implementation the instructions are decoded according to a microprogram that translates instructions into sets of CPU configuration signals that are applied sequentially over multiple clock pulses. After fetching and decoding the instructions, the instructions are executed using the arithmetic logic unit (ALU) 1334 that loads values from the register 1332 and performs logical and mathematical operations on the loaded values according to the instructions. The results from these operations can be feedback into the register and/or stored in the fast memory 1340. According to certain implementations, the instruction set architecture of the CPU 1230 can use a reduced instruction set architecture, a complex instruction set architecture, a vector processor architecture, a very large instruction word architecture. Furthermore, the CPU 1230 can be based on the Von Neuman model or the Harvard model. The CPU 1230 can be a digital signal processor, an FPGA, an ASIC, a PLA, a PLD, or a CPLD. Further, the CPU 1230 can be an x86 processor by Intel or by AMD; an ARM processor, a Power architecture processor by, e.g., IBM; a SPARC architecture processor by Sun Microsystems or by Oracle; or other known CPU architecture.

[0106] Referring again to FIG. 12, the data processing system 1200 can include that the SB/ICH 1220 is coupled through a system bus to an I/O Bus, a read only memory (ROM) 1256, universal serial bus (USB) port 1264, a flash binary input/output system (BIOS) 1268, and a graphics controller 1258. PCI/PCIe devices can also be coupled to SB/ICH 1288 through a PCI bus 1262.

[0107] The PCI devices may include, for example, Ethernet adapters, add-in cards, and PC cards for notebook computers. The Hard disk drive 1260 and CD-ROM 1266 can use, for example, an integrated drive electronics (IDE) or serial advanced technology attachment (SATA) interface. In one implementation the I/O bus can include a super I/O (SIO) device.

[0108] Further, the hard disk drive (HDD) 1260 and optical drive 1266 can also be coupled to the SB/ICH 1220 through a system bus. In one implementation, a keyboard 1270, a mouse 1272, a parallel port 1278, and a serial port 1276 can be connected to the system bus through the I/O bus. Other peripherals and devices that can be connected to the SB/ICH 1220 using a mass storage controller such as SATA or PATA, an Ethernet port, an ISA bus, a LPC bridge, SM-bus, a DMA controller, and an Audio Codec.

[0109] Moreover, the present disclosure is not limited to the specific circuit elements described herein, nor is the present disclosure limited to the specific sizing and classification of these elements. For example, the skilled artisan will appreciate that the circuitry described herein may be adapted based on changes on battery sizing and chemistry or based on the requirements of the intended back-up load to be powered.

[0110] The functions and features described herein may also be executed by various distributed components of a system. For example, one or more processors may execute these system functions, wherein the processors are distributed across multiple components communicating in a network. The distributed components may include one or more client and server machines, which may share processing, as shown by FIG. 14, in addition to various human interface and communication devices (e.g., display monitors, smart phones, tablets, personal digital assistants (PDAs)). The network may be a private network, such as a LAN or WAN, or may be a public network, such as the Internet. Input to the system may be received via direct user input and received remotely either in real-time or as a batch process. Additionally, some implementations may be performed on modules or hardware not identical to those described. Accordingly, other implementations are within the scope that may be claimed.

[0111] The above-described hardware description is a non-limiting example of corresponding structure for performing the functionality described herein.

[0112] According to the present disclosure, the smart stylus **100**, the smart stylus therapeutic system **700**, and the method **1000** provide an efficient, adaptive, and dynamic way of treating paralysis and loss of motor skills caused by stroke, or any other similar illness. The smart stylus **100**, the smart stylus therapeutic system **700**, and the method **1000** are designed for ease of operation and adaptation in a plurality of environments. As such, the smart stylus **100** and the smart stylus therapeutic system **700** provide advanced prospects of adaptation in a plurality of medical rehabilitation centers, physiological rehabilitation centers, and neurological rehabilitation centers. Furthermore, the smart stylus **100** provides a gamified experience to the patient in order to enhance rehabilitation therapy time of the patient. The system **700** may provide visual cues, prompts, and engaging activities that may motivate the patient during a particular, tailored therapy session. Therefore, the system **700** may result in better overall patient rehabilitation. The smart stylus therapeutic system **700** may eliminate the stigma associated with stroke rehabilitation therapy as previously recorded in a younger generation of stroke patients. In some aspects, the smart stylus therapeutic system **700** may be capable of receiving over the air (OTA) updates for remote upgradation of the system **700**.

[0113] Numerous modifications and variations of the present disclosure are possible in light of the above teachings. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described herein.

Claims

1. A smart stylus for use in hand therapy, comprising: an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap, wherein the stylus end is connected to a first end of the central body, a second end of the central body is connected to a first end of the C-shaped handle, wherein the central body is configured to taper in width and depth from the second end of the central body to the first end of the central body, wherein the handle end cap is connected to a second end of the C-shaped handle; a first sliding mechanism located between the central body and the first end of the C-shaped handle; and a second sliding mechanism located between the second end of the C-shaped handle and the handle end cap, wherein a length of the elongate body depends on an adjustment of the first sliding mechanism and the second sliding mechanism.
2. The smart stylus of claim 1, wherein an outer region of the C-shaped handle includes a first groove which extends from the first end of the C-shaped handle to the second end of the C-shaped handle, wherein the first groove has a width in a range of 80% to 90% of a width of the C-shaped handle and a depth in a range of 0.25 to 1.0 cm.
3. The smart stylus of claim 2, wherein an outer region of the central body from the second end of the central body to about halfway between the first end of the central body and the second end of the central body includes a second groove which matches the first groove of the C-shaped handle in depth and width.
4. The smart stylus of claim 1, further comprising: a first flexible grip located on the central body halfway between the first end of the central body and the second end of the central body, wherein the first flexible grip includes raised lines extending across the central body perpendicular to a central axis of the central body; and a second flexible grip located on the handle end cap, wherein the second flexible grip includes raised lines extending across the handle end cap perpendicular to a central axis of the handle end cap.
5. The smart stylus of claim 1, further comprising: at least two upper weight receiving compartments, wherein each upper weight receiving compartment is located on either side of the C-shaped handle near the first end; at least two lower weight receiving compartments, wherein each lower weight receiving compartment is located on either side of the C-shaped handle near the

second end; and a plurality of weights, wherein each weight is sized to fit within a respective weight receiving compartment.

6. The smart stylus of claim 5, wherein the plurality of weights includes an oblong weight and a cylindrical weight, wherein each side of the C-shaped handle includes a weight receiving compartment sized to receive the oblong weight and a weight receiving compartment sized to receive the cylindrical weight.

7. The smart stylus of claim 1, wherein the elongate body and the C-shaped handle are made of elastomeric thermoplastic.

8. The smart stylus of claim 1, further comprising: a rechargeable battery located within the handle end cap.

9. The smart stylus of claim 8, further comprising: a pressure sensor located within the elongate body and connected to the stylus end.

10. The smart stylus of claim 9, further comprising: a microcontroller located within the central body, wherein the microcontroller is operatively connected to the rechargeable battery and the pressure sensor; and a near field communications unit located within the central body and operatively connected with the microcontroller.

11. A smart stylus therapeutic system for use in hand therapy, comprising: an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap, wherein the stylus end is connected to a first end of the central body, a second end of the central body is connected to a first end of the C-shaped handle, and the handle end cap is connected to a second end of the C-shaped handle; a rechargeable battery located within the handle end cap; a microcontroller located within the central body, wherein the microcontroller is operatively connected to the rechargeable battery; a near field communications unit located within the central body and operatively connected with the microcontroller; a therapeutic tablet including a touch screen, wherein the therapeutic tablet includes a memory including program instructions including a hand therapy treatment plan and one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit and display the hand therapy treatment plan and hand therapy exercises upon the touch screen, wherein the hand therapy exercises are configured to direct a patient to write upon the touch screen with the stylus end while gripping the C-shaped handle; a case configured to hold the elongate body and the therapeutic tablet; a charging port located on the case, wherein the charging port is configured to mate with the handle end cap, wherein the rechargeable battery is located within the central body; and an electromagnetic coil located within the handle end cap and connected to the rechargeable battery, wherein the electromagnetic coil is configured to generate a charging current when the handle end cap is placed adjacent to the charging port.

12. The smart stylus therapeutic system of claim 11, wherein the therapeutic tablet is configured to receive a battery charge status by near field communications from the microcontroller and display the battery charge status on the touch screen.

13. The smart stylus therapeutic system of claim 11, further comprising: a pressure sensor located within the elongate body and connected to the stylus end, wherein the pressure sensor is connected to the microcontroller, wherein the pressure sensor is configured generate electrical signals in response to an amount of pressure sensed by the pressure sensor when the stylus end contacts the touch screen, and wherein the microcontroller is configured to transmit the electrical signals related to the amount of pressure by near field communications to the therapeutic tablet.

14. The smart stylus therapeutic system of claim 13, further comprising: at least two upper weight receiving compartments, wherein each upper weight receiving compartment is located on either side of the C-shaped handle near the first end; and at least two lower weight receiving compartments, wherein each lower weight receiving compartment is located on either side of the C-shaped handle near the second end; and a plurality of weights, wherein each weight is sized to fit within a respective weight receiving compartment, wherein the plurality of weights is stored in

weight receiving slots in the case, and wherein the therapeutic tablet is configured to receive the electrical signals related to the amount of pressure of the stylus end against the touch screen and select a weight from the plurality of weights in accordance with the hand therapy treatment plan.

15. The smart stylus therapeutic system of claim 11, wherein the hand therapy exercises include grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve motor skills, coordination, and cognitive functions.

16. The smart stylus therapeutic system of claim 15, further comprising: a patient assessment unit located within the therapeutic tablet, wherein the patient assessment unit is configured to monitor a progress of the patient against a baseline assessment and generate a progress report; and a wireless communication unit located within the therapeutic tablet, wherein the wireless communication unit is configured to wirelessly transmit the progress report to a remote medical system configured to monitor the progress of the patient.

17. A method of using a smart stylus in hand therapy, comprising: forming an elongate body having a stylus end, a central body, a C-shaped handle, and a handle end cap, wherein the stylus end is connected to a first end of the central body, a second end of the central body is connected to a first end of the C-shaped handle, and the handle end cap is connected to a second end of the C-shaped handle; installing a rechargeable battery within the handle end cap; inserting a microcontroller within the central body; operatively connecting the microcontroller to the rechargeable battery; forming a case to hold the elongate body and the therapeutic tablet; forming a charging port in the case, wherein the charging port is configured to mate with the handle end cap; installing an electromagnetic coil within the handle end cap and connecting the electromagnetic coil to the rechargeable battery, wherein the electromagnetic coil is configured to generate a charging current when the handle end cap is placed adjacent to the charging port; installing a near field communications unit within the central body and operatively connecting the near field communications unit with the microcontroller; and linking the therapeutic tablet including a touch screen to the microcontroller, wherein the therapeutic tablet includes a memory including program instructions including a hand therapy treatment plan and one or more processors configured to execute the program instructions to receive near field communications from the near field communications unit and display the hand therapy treatment plan and hand therapy exercises upon the touch screen, wherein the hand therapy exercises are configured to direct a patient to write upon the touch screen with the stylus end while gripping the C-shaped handle.

18. The method of claim 17, further comprising: connecting a pressure sensor to the stylus end and connecting the pressure sensor to the microcontroller; generating, by the pressure sensor, electrical signals in response to an amount of pressure sensed by the pressure sensor when the stylus end contacts the touch screen, and transmitting, by the near field communications unit, the electrical signals related to the amount of pressure by near field communication to the therapeutic tablet.

19. The method of claim 18, further comprising: displaying, on the touch screen, the hand therapy exercises including grip strength exercises, hand-eye coordination exercises, and interactive games configured to improve motor skills, coordination, and cognitive functions of the patient.

20. The method of claim 19, further comprising: monitoring a progress of the patient by a patient assessment unit located within the therapeutic tablet; comparing, by the patient assessment unit, the progress of the patient against a baseline assessment; generating, by the patient assessment unit, a progress report; and transmitting, by a wireless communication unit located within the therapeutic tablet, the progress report to a remote medical system configured to monitor the progress of the patient.
