

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12415309
B2
September 16, 2025
Lee; Eric et al.

Overlay applicator machines and methods of providing the same

Abstract

A machine including an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The machine also can include an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators, each respective one of the overlay applicators comprising a respective overlay configured to be applied to a respective surface of each of the electronic devices. The machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices. The adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to adjust a respective position of each of the electronic devices held in the adjustable cradle with respect to the alignment base. Other embodiments are described.

Inventors: Lee; Eric (Cypress, CA), Cheung; Stanley (Winnetka, CA), Lane; Steven (Orange, CA), Otani; Kazuyoshi Raijin (Los Angeles, CA), Kleeman; David A. (Marina Del Rey, CA), Wadsworth; John F. (Burbank, CA), Poon; Aaron Ka Hoo (Arcadia, CA)

Applicant: Belkin International, Inc. (El Segundo, CA)

Family ID: 1000008818987

Assignee: BELKIN INTERNATIONAL, INC. (El Segundo, CA)

Appl. No.: 18/738956

Filed: June 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240326319 A1	Oct. 03, 2024

Related U.S. Application Data

continuation parent-doc US 17180481 20210219 US 12005628 child-doc US 18738956
us-provisional-application US 62978812 20200219

Publication Classification

Int. Cl.: **B29C63/02** (20060101); **B29C63/00** (20060101); **H04B1/3888** (20150101); B29L31/34 (20060101)

U.S. Cl.:

CPC **B29C63/0004** (20130101); **B29C63/02** (20130101); **H04B1/3888** (20130101); B29C2063/0008 (20130101); B29L2031/3437 (20130101)

Field of Classification Search

CPC: B29C (63/0004); B29C (63/02); B29C (2063/0008); H04B (1/3888); B29L (2031/3437)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4082873	12/1977	Williams	N/A	N/A
4285559	12/1980	Koch	N/A	N/A
D305648	12/1989	Edington	N/A	N/A
4895231	12/1989	Yamaguchi et al.	N/A	N/A
5069732	12/1990	Levine	N/A	N/A
5609938	12/1996	Shields	N/A	N/A
5680709	12/1996	Stone	N/A	N/A
5805251	12/1997	Ozawa	N/A	N/A
6406758	12/2001	Bottari et al.	N/A	N/A
7084859	12/2005	Pryor	N/A	N/A
D578164	12/2007	Ingle	N/A	N/A
D598024	12/2008	Scott et al.	N/A	N/A
D601959	12/2008	Lee et al.	N/A	N/A
D601960	12/2008	Dai	N/A	N/A
7697827	12/2009	Konicek	N/A	N/A
D627826	12/2009	Halimi	N/A	N/A
7957524	12/2010	Chipping	N/A	N/A
7966861	12/2010	Yee et al.	N/A	N/A
D641210	12/2010	Hamilton	N/A	N/A
8044942	12/2010	Leonhard et al.	N/A	N/A
8047365	12/2010	Lin et al.	N/A	N/A
D651214	12/2010	Yoo et al.	N/A	N/A
D651791	12/2011	Cataldo et al.	N/A	N/A
D658164	12/2011	Chan	N/A	N/A
D665809	12/2011	Wang et al.	N/A	N/A
8369072	12/2012	Alonzo et al.	N/A	N/A
8388243	12/2012	Smith	N/A	N/A
8393377	12/2012	Patel et al.	N/A	N/A
D679753	12/2012	Sato et al.	N/A	N/A
D680166	12/2012	Sato et al.	N/A	N/A
8517367	12/2012	Napier	N/A	N/A
D690704	12/2012	Padilla et al.	N/A	N/A
8564538	12/2012	Wadsworth	N/A	N/A
D694240	12/2012	Cho	N/A	N/A

8640759	12/2013	Chen	N/A	N/A
8675353	12/2013	Alonzo et al.	N/A	N/A
D707217	12/2013	Toulotte	N/A	N/A
D710843	12/2013	Akana et al.	N/A	N/A
D713397	12/2013	Du et al.	N/A	N/A
D714053	12/2013	Yoo	N/A	N/A
8821659	12/2013	Ng et al.	N/A	N/A
D715301	12/2013	Ashcraft et al.	N/A	N/A
D715784	12/2013	Lin et al.	N/A	N/A
D720353	12/2013	Nakamura	N/A	N/A
8905107	12/2013	Patel et al.	N/A	N/A
D721359	12/2014	Kim	N/A	N/A
8931770	12/2014	Kaminski	N/A	N/A
9001502	12/2014	Cowan	N/A	N/A
9010396	12/2014	Patel et al.	N/A	N/A
D729235	12/2014	Nagao et al.	N/A	N/A
9033019	12/2014	Patel et al.	N/A	N/A
D734311	12/2014	Takamoto et al.	N/A	N/A
9089085	12/2014	Patel et al.	N/A	N/A
9159260	12/2014	Oh et al.	N/A	N/A
D743402	12/2014	Ehara et al.	N/A	N/A
D746265	12/2014	Colby et al.	N/A	N/A
D747320	12/2015	Snyder et al.	N/A	N/A
D751556	12/2015	Conley et al.	N/A	N/A
D751557	12/2015	Lane	N/A	N/A
D759640	12/2015	Wadsworth	N/A	N/A
D767550	12/2015	Beaupre et al.	N/A	N/A
D769857	12/2015	Shin et al.	N/A	N/A
D772199	12/2015	Igarashi	N/A	N/A
9481159	12/2015	Wang	N/A	N/A
D773927	12/2015	Cernokus et al.	N/A	N/A
D776123	12/2016	Akana et al.	N/A	N/A
D777714	12/2016	Akana et al.	N/A	N/A
D778869	12/2016	Kim et al.	N/A	N/A
D781861	12/2016	Lane et al.	N/A	N/A
D783024	12/2016	Conley et al.	N/A	N/A
9662860	12/2016	Wadsworth	N/A	N/A
9688016	12/2016	Rostami	N/A	N/A
9701062	12/2016	Wadsworth et al.	N/A	N/A
9701096	12/2016	Beaupre	N/A	N/A
9757934	12/2016	Wadsworth	N/A	N/A
D800126	12/2016	Wadsworth et al.	N/A	N/A
D800127	12/2016	Beaupre et al.	N/A	N/A
D800128	12/2016	Beaupre et al.	N/A	N/A
D800129	12/2016	Wadsworth et al.	N/A	N/A
D800130	12/2016	Beaupre et al.	N/A	N/A
D800131	12/2016	Wadsworth et al.	N/A	N/A
D800714	12/2016	Lee et al.	N/A	N/A
D802594	12/2016	Beaupre et al.	N/A	N/A
D811404	12/2017	Wadsworth	N/A	N/A
D811405	12/2017	Wadsworth et al.	N/A	N/A
D811406	12/2017	MacDonald et al.	N/A	N/A
D811407	12/2017	Wadsworth et al.	N/A	N/A

D811408	12/2017	Wadsworth et al.	N/A	N/A
9902111	12/2017	Wadsworth et al.	N/A	N/A
D812061	12/2017	MacDonald et al.	N/A	N/A
D812062	12/2017	MacDonald et al.	N/A	N/A
D812063	12/2017	Lane et al.	N/A	N/A
9918418	12/2017	Chou	N/A	N/A
9931823	12/2017	Patel et al.	N/A	N/A
10021818	12/2017	Patel et al.	N/A	N/A
10065365	12/2017	Lane	N/A	N/A
10076894	12/2017	Lin et al.	N/A	N/A
10091341	12/2017	Cha et al.	N/A	N/A
D833439	12/2017	MacDonald et al.	N/A	N/A
D835108	12/2017	MacDonald et al.	N/A	N/A
10155370	12/2017	Wadsworth	N/A	N/A
10399315	12/2018	Patel et al.	N/A	N/A
10675817	12/2019	MacDonald et al.	N/A	N/A
10782746	12/2019	Kleeman et al.	N/A	N/A
12005628	12/2023	Lee et al.	N/A	N/A
2002/0054030	12/2001	Murphy	N/A	N/A
2004/0109096	12/2003	Anderson et al.	N/A	N/A
2004/0246386	12/2003	Thomas et al.	N/A	N/A
2005/0030296	12/2004	Stohrer et al.	N/A	N/A
2005/0164148	12/2004	Sinclair	N/A	N/A
2007/0013662	12/2006	Fauth	N/A	N/A
2007/0021068	12/2006	Dewhurst	N/A	N/A
2007/0058990	12/2006	Weaver et al.	N/A	N/A
2007/0115621	12/2006	Guillen	N/A	N/A
2007/0229962	12/2006	Mason, Jr.	N/A	N/A
2007/0247793	12/2006	Carnevali	N/A	N/A
2007/0293282	12/2006	Lewis et al.	N/A	N/A
2009/0015509	12/2008	Gottwald et al.	N/A	N/A
2009/0133219	12/2008	Lowry et al.	N/A	N/A
2009/0186181	12/2008	Mase	N/A	N/A
2009/0245565	12/2008	Mittleman et al.	N/A	N/A
2009/0314400	12/2008	Liu	N/A	N/A
2010/0053926	12/2009	Shi et al.	N/A	N/A
2010/0079972	12/2009	Chen et al.	N/A	N/A
2010/0097757	12/2009	Wang	N/A	N/A
2010/0309152	12/2009	Kusuda et al.	N/A	N/A
2011/0188179	12/2010	Myers et al.	N/A	N/A
2011/0206887	12/2010	Kim	N/A	N/A
2011/0267793	12/2010	Cohen et al.	N/A	N/A
2011/0279383	12/2010	Wilson et al.	N/A	N/A
2011/0309608	12/2010	Flynn et al.	N/A	N/A
2012/0043015	12/2011	Feller	N/A	N/A
2012/0063077	12/2011	Tomobe et al.	N/A	N/A
2012/0076967	12/2011	Muramatsu	N/A	N/A
2012/0087072	12/2011	McGuire et al.	N/A	N/A
2012/0110868	12/2011	Abbondanzio	N/A	N/A
2012/0183712	12/2011	Leonhard et al.	N/A	N/A
2012/0211168	12/2011	Patel et al.	N/A	N/A
2012/0211170	12/2011	Patel et al.	N/A	N/A
2012/0261930	12/2011	Bethea	N/A	N/A

2012/0268394	12/2011	Hsu et al.	N/A	N/A
2012/0276318	12/2011	Franke	N/A	N/A
2013/0020005	12/2012	Koblick et al.	N/A	N/A
2013/0020020	12/2012	Liu	N/A	N/A
2013/0040088	12/2012	Hirayama et al.	N/A	N/A
2013/0048203	12/2012	Yau et al.	N/A	N/A
2013/0113348	12/2012	Holben et al.	N/A	N/A
2013/0156999	12/2012	Braesch et al.	N/A	N/A
2013/0184845	12/2012	Hales	N/A	N/A
2013/0237296	12/2012	Chen	N/A	N/A
2013/0264235	12/2012	Lin	N/A	N/A
2014/0047708	12/2013	Chae	N/A	N/A
2014/0055927	12/2013	Wang et al.	N/A	N/A
2014/0124146	12/2013	Patel et al.	N/A	N/A
2014/0130971	12/2013	Wu et al.	N/A	N/A
2014/0250964	12/2013	Dai et al.	N/A	N/A
2014/0332417	12/2013	Wicks et al.	N/A	N/A
2014/0338829	12/2013	Peng et al.	N/A	N/A
2015/0000831	12/2014	Wang	N/A	N/A
2015/0041069	12/2014	Wadsworth et al.	N/A	N/A
2015/0047773	12/2014	Wadsworth et al.	N/A	N/A
2015/0107767	12/2014	Wadsworth et al.	N/A	N/A
2015/0121691	12/2014	Wang	N/A	N/A
2015/0136314	12/2014	Napier	N/A	N/A
2015/0227226	12/2014	Wierenga et al.	N/A	N/A
2015/0246514	12/2014	LaColla et al.	N/A	N/A
2015/0314523	12/2014	Mason et al.	N/A	N/A
2015/0362736	12/2014	Kowasie	N/A	N/A
2016/0009024	12/2015	Mason	N/A	N/A
2016/0176101	12/2015	Fan	N/A	N/A
2016/0253039	12/2015	Heo et al.	N/A	N/A
2016/0288470	12/2015	Wadsworth	N/A	N/A
2017/0001364	12/2016	MacDonald et al.	N/A	N/A
2017/0094039	12/2016	Lu	N/A	N/A
2017/0253014	12/2016	Kleeman et al.	N/A	N/A
2018/0324987	12/2017	Patel et al.	N/A	N/A
2019/0381775	12/2018	Patel et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201456516	12/2009	CN	N/A
201538078	12/2009	CN	N/A
102632674	12/2011	CN	N/A
202395823	12/2011	CN	N/A
202463101	12/2011	CN	N/A
302141011	12/2011	CN	N/A
202540892	12/2011	CN	N/A
202609123	12/2011	CN	N/A
202623469	12/2011	CN	N/A
302239597	12/2011	CN	N/A
202657286	12/2012	CN	N/A
202686811	12/2012	CN	N/A
202896928	12/2012	CN	N/A

202923909	12/2012	CN	N/A
202953197	12/2012	CN	N/A
103129767	12/2012	CN	N/A
202967060	12/2012	CN	N/A
202987565	12/2012	CN	N/A
302452344	12/2012	CN	N/A
203032965	12/2012	CN	N/A
203077741	12/2012	CN	N/A
203094507	12/2012	CN	N/A
103273716	12/2012	CN	N/A
203255376	12/2012	CN	N/A
302740093	12/2013	CN	N/A
302795168	12/2013	CN	N/A
203652157	12/2013	CN	N/A
203681932	12/2013	CN	N/A
203902881	12/2013	CN	N/A
104150008	12/2013	CN	N/A
203997012	12/2013	CN	N/A
203997014	12/2013	CN	N/A
104118600	12/2014	CN	N/A
205087201	12/2015	CN	N/A
105500879	12/2015	CN	N/A
105766077	12/2015	CN	N/A
105829070	12/2015	CN	N/A
106476262	12/2016	CN	N/A
304152067	12/2016	CN	N/A
206826987	12/2017	CN	N/A
107719745	12/2017	CN	N/A
207000900	12/2017	CN	N/A
304514721	12/2017	CN	N/A
207060487	12/2017	CN	N/A
207089749	12/2017	CN	N/A
107985667	12/2017	CN	N/A
207658144	12/2017	CN	N/A
108454081	12/2017	CN	N/A
207889127	12/2017	CN	N/A
207889128	12/2017	CN	N/A
207889129	12/2017	CN	N/A
108724691	12/2017	CN	N/A
108748969	12/2017	CN	N/A
108819207	12/2017	CN	N/A
208035358	12/2017	CN	N/A
109080122	12/2017	CN	N/A
208263434	12/2017	CN	N/A
208291553	12/2017	CN	N/A
208438723	12/2018	CN	N/A
208438727	12/2018	CN	N/A
109333989	12/2018	CN	N/A
208452294	12/2018	CN	N/A
208646031	12/2018	CN	N/A
109591280	12/2018	CN	N/A
208697960	12/2018	CN	N/A
208714487	12/2018	CN	N/A

305133996	12/2018	CN	N/A
109822880	12/2018	CN	N/A
209080265	12/2018	CN	N/A
209096015	12/2018	CN	N/A
110126248	12/2018	CN	N/A
209290791	12/2018	CN	N/A
110202780	12/2018	CN	N/A
209506199	12/2018	CN	N/A
209506202	12/2018	CN	N/A
209521263	12/2018	CN	N/A
305395645	12/2018	CN	N/A
209599846	12/2018	CN	N/A
209617594	12/2018	CN	N/A
209699847	12/2018	CN	N/A
209832653	12/2018	CN	N/A
110641003	12/2019	CN	N/A
202013102944	12/2012	DE	N/A
102013021563	12/2014	DE	N/A
2489495	12/2013	EP	N/A
0024866540001	12/2013	EP	N/A
0024866540002	12/2013	EP	N/A
0024866540003	12/2013	EP	N/A
0024866540004	12/2013	EP	N/A
0024866540005	12/2013	EP	N/A
0024866540006	12/2013	EP	N/A
0024866540007	12/2013	EP	N/A
0024866540008	12/2013	EP	N/A
0024866960001	12/2013	EP	N/A
0024866960002	12/2013	EP	N/A
0024866960003	12/2013	EP	N/A
0024866960004	12/2013	EP	N/A
0024866960005	12/2013	EP	N/A
0024866960006	12/2013	EP	N/A
0024866960007	12/2013	EP	N/A
0024866960008	12/2013	EP	N/A
0024866960009	12/2013	EP	N/A
0024866960010	12/2013	EP	N/A
0024866960011	12/2013	EP	N/A
0024866960012	12/2013	EP	N/A
0024866960013	12/2013	EP	N/A
0024866960014	12/2013	EP	N/A
0024866960015	12/2013	EP	N/A
0024866960016	12/2013	EP	N/A
0024867120001	12/2013	EP	N/A
0024867120002	12/2013	EP	N/A
0024867120003	12/2013	EP	N/A
0024867120004	12/2013	EP	N/A
0024867120005	12/2013	EP	N/A
0024867120006	12/2013	EP	N/A
0024867120007	12/2013	EP	N/A
0024867120008	12/2013	EP	N/A
0024867120009	12/2013	EP	N/A
0024867120010	12/2013	EP	N/A

0024867120011	12/2013	EP	N/A
0024867120012	12/2013	EP	N/A
0024867120013	12/2013	EP	N/A
0024867120014	12/2013	EP	N/A
0024867120015	12/2013	EP	N/A
0024867120016	12/2013	EP	N/A
3046262	12/2015	EP	N/A
10199422	12/1997	JP	N/A
2002049327	12/2001	JP	N/A
2002057764	12/2001	JP	N/A
2003066419	12/2002	JP	N/A
2006145918	12/2005	JP	N/A
2006155452	12/2005	JP	N/A
3124275	12/2005	JP	N/A
3180690	12/2011	JP	N/A
3182856	12/2012	JP	N/A
2016049742	12/2015	JP	N/A
3221751	12/2018	JP	N/A
200454225	12/2010	KR	N/A
20110008023	12/2010	KR	N/A
101080018	12/2010	KR	N/A
101103436	12/2011	KR	N/A
101135144	12/2011	KR	N/A
101176316	12/2011	KR	N/A
1020130007791	12/2012	KR	N/A
101250080	12/2012	KR	N/A
1020130043720	12/2012	KR	N/A
300704457	12/2012	KR	N/A
300704458	12/2012	KR	N/A
300704459	12/2012	KR	N/A
300704460	12/2012	KR	N/A
1020130092713	12/2012	KR	N/A
1020130092804	12/2012	KR	N/A
300720375	12/2012	KR	N/A
300720376	12/2012	KR	N/A
101408663	12/2013	KR	N/A
1020140070046	12/2013	KR	N/A
1020140076245	12/2013	KR	N/A
101441640	12/2013	KR	N/A
101468710	12/2013	KR	N/A
200475420	12/2013	KR	N/A
200475419	12/2013	KR	N/A
1020140136596	12/2013	KR	N/A
1020140142904	12/2013	KR	N/A
1020140143262	12/2013	KR	N/A
1020150006910	12/2014	KR	N/A
200476916	12/2014	KR	N/A
1020150039292	12/2014	KR	N/A
2020150001663	12/2014	KR	N/A
300804459	12/2014	KR	N/A
1020160022665	12/2015	KR	N/A
1020160022755	12/2015	KR	N/A
1020160061078	12/2015	KR	N/A

1020160088067	12/2015	KR	N/A
1020160091491	12/2015	KR	N/A
20160144625	12/2015	KR	N/A
2020170000128	12/2016	KR	N/A
102002105	12/2018	KR	N/A
M443629	12/2011	TW	N/A
M431133	12/2011	TW	N/A
M449696	12/2012	TW	N/A
M452053	12/2012	TW	N/A
1401223	12/2012	TW	N/A
M547122	12/2016	TW	N/A
201910109	12/2018	TW	N/A
2003093879	12/2002	WO	N/A
2004005141	12/2003	WO	N/A
2005058705	12/2004	WO	N/A
2011065796	12/2010	WO	N/A
2011163151	12/2010	WO	N/A
2012074802	12/2011	WO	N/A
2012141505	12/2011	WO	N/A
2013009149	12/2012	WO	N/A
2013109788	12/2012	WO	N/A
2014021486	12/2013	WO	N/A
2014045468	12/2013	WO	N/A
2015035679	12/2014	WO	N/A
2015038883	12/2014	WO	N/A
2018053333	12/2017	WO	N/A
2018177590	12/2017	WO	N/A
2019140932	12/2018	WO	N/A

OTHER PUBLICATIONS

English machine translation of Seo; WO-2014021486-A1; Feb. 6, 2014; B29C63/02; 68 pages. (Year: 2014). cited by examiner

English machine translation of WO-2014021486-A1, Seo, 15 pages, Feb. 6, 2014. 2014. cited by applicant

Translation of KR-10-1135144, retrieved from the Internet on Jun. 9, 2017. 2017. cited by applicant

International Search Report and Written Opinion for PCT/US2014/050420 dated Nov. 19, 2014. Nov. 19, 2014. cited by applicant

International Search Report and Written Opinion for PCT/US2014/060300 dated Jan. 27, 2015. Jan. 27, 2015. cited by applicant

International Search Report and Written Opinion for PCT/US2014/071767 dated Apr. 24, 2015. Apr. 24, 2015. cited by applicant

AMZER—Kristal Screen Protectors <http://www.amzer.com/kristal/>, Mar. 21, 2014. Mar. 2014. cited by applicant

MyScreenPROTECTOR—<https://www.myscreenprotector.com/?lng=3&view=cms&txt=about-my-screen-protector>, Mar. 21, 2014. Mar. 2014. cited by applicant

PureGear—PureTek Roll-On Kit—<http://www.pure-gear.com/shop-by-category/screen/puretek-roll-on-kit-antibacterial-antiglare-anti-fingerprint.html>, Mar. 21, 2014. Mar. 2014. cited by applicant

Tylt Alin Perfect Alignment Screen Protection—<http://www.tylt.com/alin/>, Mar. 21, 2014. Mar. 2014. cited by applicant

Zagg Introduces invisibleShield On Demand and invisible Shield Glass at CES 2, <http://investors.zagg.com/releasedetail.cfm?ReleaseID=817526>, Mar. 21, 2014. Mar. 2014. cited by applicant

International Search Report and Written Opinion for PCT/US 09/61553, dated Dec. 17, 2009. Dec. 17, 2009. cited by applicant

Protrusion on “F” key of computer keyboard; 1 page; picture taken Oct. 20, 2008. Oct. 20, 2008. cited by

applicant

Protrusion on “5” key of telephone; 1 page; picture taken Oct. 20, 2008. Oct. 20, 2008. cited by applicant
Systech Displays, Inc.; Home page; <http://www.systechdisplays.com/>; Oct. 21, 2008. Oct. 21, 2008. cited by applicant

Belkin Ez Frame Iris Anti-glare Film, posted at ebay.com, posting date Jul. 26, 2017, Copyright (C) 1995-2017 eBay Inc., [online], [site visited Mar. 20, 2017]. Available from Internet, <URL: <http://www.ebay.com/itm/BelkinEzFrameIrisAntiglareFilmwithEasyInstallFrameforIphone55S/171728155795>> Jul. 26, 2016. cited by applicant

Belkin InvisiGlass Ultra Screen Protection for iPhone 7, posted at apple.com, posting date not given, Copyright (C) 2017 Apple Inc., [online], [site visited Mar. 20, 2017]. Available from Internet, <URL: <http://www.apple.com/shop/product/HKF2ZM/B/belkininvisiglassultrascreenprotectionforiphone7>> 2017. cited by applicant

Belkin ScreenForce Transparent Screen Protector, posted at belkin.com, (C) 2017 Belkin International, Inc., [online], [site visited Mar. 20, 2017]. Available from Internet, <URL: <http://www.belkin.com/us/F8W526-3/p/P-F8W526-3/>> 2017. cited by applicant

International Search Report and Written Opinion for PCT/US2017/051882, dated Nov. 29, 2017. 2017. cited by applicant

Machine Translation of DE102013021563, published Jun. 18, 2015. Jun. 18, 2015. cited by applicant

International Search Report and Written Opinion for PCT/US2021/018889, dated Jun. 8, 2021. 2021. cited by applicant

Machine Translation of KR101103436B1 Jul. 3, 2022. cited by applicant

Primary Examiner: Gray; Linda L

Attorney, Agent or Firm: BRYAN CAVE LEIGHTON PAISNER LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/180,481, filed Feb. 19, 2021, which claims the benefit of U.S. Provisional Application No. 62/978,812, filed Feb. 19, 2020. U.S. patent application Ser. No. 17/180,481 and U.S. Provisional Application No. 62/978,812 are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) This disclosure relates generally to overlays and relates more particularly to overlay applicator machines and methods of providing the same.

BACKGROUND

(2) Electronic devices, such as smartphones, tablet computing devices, media players, etc., have gained widespread popularity. These devices generally have screens, and many of these devices have touchscreens, such as capacitive touchscreens. To protect these screens, many manufacturers now produce clear film overlays, which can be applied to the screens to keep the screens clear and protect against damage, such as accidental scratching. Many of these films include a self-wetting adhesive to adhere to the screens of the electronic devices. Oftentimes, application of an overlay to the screen of a device results in misalignment of the overlay on the device, air bubbles between the overlay and the screen of the device, and/or dirt (such as dust, fingerprints, oil, and/or other particulates) between the overlay and the screen of the device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To facilitate further description of the embodiments, the following drawings are provided in which:

(2) FIG. 1 illustrates an exploded isometric view of an overlay applicator, according to an embodiment;

(3) FIG. 2 illustrates an isometric view of a system for using the overlay applicator of FIG. 1 to apply an overlay to a device with a frame, according to another embodiment;

(4) FIG. 3 illustrates an isometric view of a system for using the overlay applicator of FIG. 1 to apply an overlay to a device with a cradle, according to another embodiment;

(5) FIG. 4 illustrates an exploded isometric view of an overlay applicator, according to another embodiment;

(6) FIG. 5 illustrates a side view of the overlay applicator of FIG. 4;

(7) FIG. 6 illustrates an isometric view of an overlay applicator, according to another embodiment;

(8) FIG. 7 illustrates an exploded isometric view of an overlay applicator, according to another embodiment;

(9) FIG. 8 illustrates an isometric view of a machine for using an overlay applicator to apply an overlay to a device, according to another embodiment;

(10) FIG. 9 illustrates a top view of the machine of FIG. 8;

(11) FIG. 10 illustrates an isometric view of the machine of FIG. 8, with a handle assembly not extended, and showing an outline of the overlay applicator of FIG. 1;

(12) FIG. 11 illustrates an isometric view of the machine of FIG. 8, with the handle assembly partially extended;

(13) FIG. 12 illustrates a top view of the machine of FIG. 8, with the handle assembly partially extended;

(14) FIG. 13 illustrates an isometric view of the machine of FIG. 8, with the handle assembly fully extended;

(15) FIG. 14 illustrates a top view of the machine of FIG. 8, with the handle assembly fully extended;

(16) FIG. 15 illustrates an exploded isometric view of an overlay applicator, according to another embodiment;

(17) FIG. 16 illustrates an isometric view of an machine in a first configuration, according to another embodiment;

(18) FIG. 17 illustrates a top view of the machine of FIG. 16 in a second configuration;

(19) FIG. 18 illustrates a side view of the machine of FIG. 16 in a second configuration;

(20) FIG. 19 illustrates a side view of the machine of FIG. 16 in a third configuration;

(21) FIG. 20 illustrates an isometric view of a machine for using an overlay applicator to apply an overlay to a device, showing an overlay cover extended, according to another embodiment;

(22) FIG. 21 illustrates an isometric view of the machine of FIG. 20 with the overlay cover engaged and the roller pressing against a tongue of the overlay cover;

(23) FIG. 22 illustrates an isometric view of the machine of FIG. 20 with the overlay cover engaged and the roller disengaged from the overlay cover;

(24) FIG. 23 illustrates a flow chart for a method of providing an overlay applicator, according to another embodiment;

(25) FIG. 24 illustrates a flow chart for a method of providing a machine, according to another embodiment;

(26) FIG. 25 illustrates a flow chart for a method of providing a machine, according to another embodiment;

(27) FIG. 26 illustrates a flow chart for a method of using an overlay applicator to apply an overlay to a screen of an electronic device, according to another embodiment;

(28) FIG. 27 illustrates a perspective view of components of an overlay applicator, according to the embodiment of FIG. 30;

(29) FIG. 28 illustrates a perspective view of components of the overlay applicator of FIG. 30;

(30) FIG. 29 illustrates a perspective view of components of the overlay applicator of FIG. 30;

(31) FIG. 30 illustrates a perspective view of an overlay applicator, according to an embodiment;

(32) FIG. 31 illustrates a perspective view of a cradle, according to an embodiment;

(33) FIG. 32 illustrates a top view of the cradle of FIG. 31 being used with an overlay applicator;

(34) FIG. 33 illustrates a side view of the cradle of FIG. 31 being used with an overlay applicator;

(35) FIG. 34 illustrates a partial cross-sectional view of the cradle of FIG. 31 being use with an overlay applicator;

(36) FIG. 35 illustrates a perspective view of a machine and an overlay applicator, according to an embodiment;

(37) FIG. 36 illustrates a perspective view of the machine of FIG. 36 with a slider being used to apply pressure to an overlay;

(38) FIG. 37 illustrates a system for using an overlay applicator to apply an overlay to a device, according to an embodiment;

(39) FIG. 38 illustrates a top side view of a cradle, according to the embodiment of FIG. 37;

(40) FIG. 39 illustrates a top side view of a cradle frame, according to the embodiment of FIG. 37;

(41) FIG. 40 illustrates a bottom side view of the cradle frame of FIG. 39;

(42) FIG. 41 illustrates a left side view of a machine in an open configuration, according to the embodiment of FIG. 37;

(43) FIG. 42 illustrates the system of FIG. 37 with the device placed in the cradle;

(44) FIG. 43 illustrates the system of FIG. 37 with the cradle placed in the machine;

(45) FIG. 44 illustrates the system of FIG. 37 with the machine in a closed configuration;

(46) FIG. 45 illustrates the system of FIG. 37 with the machine in an open configuration;

(47) FIG. 46 illustrates a perspective view of a machine in a closed configuration, according to another embodiment;

(48) FIG. 47 illustrates a perspective view of the machine of FIG. 46 in an open configuration;

(49) FIG. 48 illustrates a perspective view of the machine of FIG. 46 in an open configuration with a device in the cradle and an overlay applicator above the device on the cradle;

(50) FIG. 49 illustrates a perspective view of the machine of FIG. 46 in a closed configuration with the pull tab of the overlay applicator being pulled;

(51) FIG. 50 illustrates a perspective view of the machine of FIG. 46 in an open configuration with portions of the overlay applicator remaining on the device;

(52) FIG. 51 illustrates a flow chart for a method of providing an overlay applicator, according to another embodiment;

(53) FIG. 52 illustrates a flow chart for a method of providing a cradle, according to another embodiment;

(54) FIG. 53 illustrates a flow chart for a method of providing a machine, according to another embodiment;

(55) FIG. 54 illustrates a flow chart for a method of providing a machine, according to another embodiment;

(56) FIG. 55 illustrates an exploded view of a dust sticker assembly, according to another embodiment;

(57) FIG. 56 illustrates a bottom perspective view the dust sticker assembly of FIG. 55 and a device;

(58) FIG. 57 illustrates a perspective view of the machine of FIG. 35, the dust sticker assembly of FIG. 55, and the device of FIG. 56;

(59) FIG. 58 illustrates a perspective view of a portion of the machine of FIG. 35 and the dust sticker assembly of FIG. 55;

(60) FIG. 59 illustrates a perspective view of a portion of the machine of FIG. 35 and the dust sticker assembly of FIG. 55, with an end portion of a release liner being peeled away from a dust removal sticker of the dust sticker assembly of FIG. 55;

(61) FIG. 60 illustrates a perspective view of the machine of FIG. 35, the dust sticker assembly of FIG. 55, and an overlay applicator;

(62) FIG. 61 illustrates a side elevational view of a portion of the dust sticker assembly of FIG. 55 as attached to the device of FIG. 56 and the overlay applicator of FIG. 60;

(63) FIG. 62 illustrates a perspective view of a wiper, according to another embodiment;

(64) FIG. 63 illustrates a perspective view of a wiper, according to another embodiment;

(65) FIG. 64 illustrates a top side view of a set of cradles, according to another embodiment;

(66) FIG. 65 illustrates a perspective view of the overlay applicator of FIG. 35 being utilized with one of the cradles of the set of cradles of FIG. 64, the cradle holding a device;

(67) FIG. 66 illustrates a perspective view of the overlay applicator of FIG. 35 being utilized with the cradle of FIG. 65, which is holding the device of FIG. 65;

(68) FIG. 67 illustrates a perspective view of the set of cradles of FIG. 64 in a stacked configuration;

(69) FIG. **68** illustrates a side view of the set of cradles of FIG. **64** in a stacked configuration;

(70) FIG. **69** illustrates a perspective view of a machine, according to another embodiment;

(71) FIG. **70** illustrates a perspective view of a clamshell frame of the machine of FIG. **69**;

(72) FIG. **71** illustrates a perspective view of the machine of FIG. **69** in an open configuration while holding a device;

(73) FIG. **72** illustrates a perspective view of the machine of FIG. **69** in a closed configuration while holding the device of FIG. **71**;

(74) FIG. **73** illustrates a perspective view of the machine of FIG. **69** in an open configuration with the overlay applicator of FIG. **30** placed on a cradle of the machine;

(75) FIG. **74** illustrates a perspective view of the machine of FIG. **69** in a closed configuration holding the overlay applicator of FIG. **30** and the device of FIG. **71**, with a pull tab of the overlay applicator being pulled

(76) FIG. **75** illustrates a flow chart for a method of providing a machine, according to another embodiment;

(77) FIG. **76** illustrates a flow chart for a method of providing a cradle, according to another embodiment;

(78) FIG. **77** illustrates a flow chart for a method of providing a set of cradles, according to another embodiment;

(79) FIG. **78** illustrates a flow chart for a method of providing an overlay applicator, according to another embodiment;

(80) FIG. **79** illustrates a flow chart for a method of providing a system, according to another embodiment;

(81) FIG. **80** illustrates a top, front, right side perspective view of an overlay applicator tray, according to another embodiment;

(82) FIG. **81** illustrates a front side elevational view of the overlay applicator tray of FIG. **80**;

(83) FIG. **82** illustrates an enlarged front side elevational view of a portion of the overlay applicator tray of FIG. **80**, as identified in FIG. **81**;

(84) FIG. **83** illustrates a top view of the overlay applicator tray of FIG. **80**, with an electronic device being held in a device slot of FIG. **80**, and with an overlay applicator of FIG. **80** resting on the electronic device;

(85) FIG. **84** illustrates a top view of the overlay applicator tray of FIG. **80**, with the electronic device of FIG. **83** being held in the device slot of FIG. **80**, and with the overlay applicator of FIG. **80** being folded upwards;

(86) FIG. **85** illustrates a top view of an overlay applicator tray kit with an overlay applicator tray book in an open configuration, according to another embodiment;

(87) FIG. **86** illustrates a top, front view of the overlay applicator tray book of FIG. **85** in a closed configuration;

(88) FIG. **87** illustrates a bottom, front view of a package used to enclose the overlay applicator tray kit of FIG. **85**, according to another embodiment;

(89) FIG. **88** illustrates a top, front, right side perspective view of an overlay applicator tray, according to another embodiment;

(90) FIG. **89** illustrates a front side elevational view of the overlay applicator tray of FIG. **88**;

(91) FIG. **90** illustrates an enlarged front side elevational view of a portion of the overlay applicator tray of FIG. **88**, as identified in FIG. **89**;

(92) FIG. **91** illustrates a top view of an overlay applicator tray with an overlay applicator in a lowered position, according to another embodiment;

(93) FIG. **92** illustrates a top, right side view of the overlay applicator tray of FIG. **91** with the overlay applicator of FIG. **91** in a raised position;

(94) FIG. **93** illustrates a flow chart for a method, according to another embodiment;

(95) FIG. **94** illustrates a flow chart for a method, according to another embodiment;

(96) FIG. **95** illustrates an enlarged front side elevational view of a portion of an overlay applicator of the overlay applicator tray of FIG. **80**, as identified in FIG. **82**;

(97) FIG. **96** illustrates an enlarged top, right side view of a portion of the overlay applicator of FIG. **91**,

as identified in FIG. 92;

(98) FIG. 97 illustrates a perspective view of an exemplary overlay attached to an electronic device, according to another embodiment;

(99) FIG. 98 illustrates a cross-sectional view of the electronic device of FIG. 98 along cross-section line 98-98 in FIG. 97, and the bottom edge of the touchscreen of FIG. 97 and the overlay of FIG. 97;

(100) FIG. 99 illustrates an enlarged cross-sectional view of a portion of the electronic device of FIG. 97 along cross-section line 98-98 in FIG. 97, and a portion of the bottom edge of the touchscreen of FIG. 97 and the overlay of FIG. 97, as identified in FIG. 98;

(101) FIG. 100 illustrates an enlarged cross-sectional view of an electronic device, and the bottom edge of a touchscreen of the electronic device, and an overlay, according to another embodiment;

(102) FIG. 101 illustrates a cross-sectional view of the electronic device of FIG. 97 along cross-section line 98-98 in FIG. 97, and a portion of the bottom edge of the touchscreen of FIG. 97, as identified in FIG. 98, and an overlay, according to another embodiment;

(103) FIG. 102 illustrates a cross-sectional view of the electronic device of FIG. 97 along cross-section line 98-98 in FIG. 97, and a portion of the bottom edge of the touchscreen of FIG. 97, as identified in FIG. 98, and an overlay, according to another embodiment;

(104) FIG. 103 illustrates a perspective view of an adhesive carrier, according to another embodiment;

(105) FIG. 104 illustrates a perspective view of an overlay and an adhesive component, according to another embodiment; and

(106) FIG. 105 illustrates a flow chart for an embodiment of a method, according to another embodiment.

(107) FIG. 106 illustrates a perspective view of a machine in a closed configuration, according to another embodiment;

(108) FIG. 107 illustrates a perspective view of the machine of FIG. 106 in an opened configuration;

(109) FIG. 108 illustrates a perspective view of the base and the adjustable cradle of the machine of FIG. 106;

(110) FIG. 109 illustrates a perspective view of a portion of the adjustable cradle of the machine of FIG. 106, showing internal components of a portion of the adjustable cradle;

(111) FIG. 110 illustrates a perspective view of the base of the machine of FIG. 106, in which an electronic device is being inserted into the adjustable cradle;

(112) FIG. 111 illustrates a plan view of various components of the machine of FIG. 106, including an alignment base, a pin holder plate, a top holder, a top holder plate, a spur gear, and a rotor spring;

(113) FIG. 112 illustrates a plan view of the base of the machine of FIG. 106, in which the electronic device of FIG. 110 is seated within the adjustable cradle;

(114) FIG. 113 illustrates a plan view of a portion of the machine of FIG. 106 in an opened configuration with the electronic device of FIG. 110 seated within the adjustable cradle, with a screen or other surface of the electronic device facing outwards (in a z-direction) and an overlay applicator attached to an alignment base of the machine so as to be positioned over the screen or other surface of electronic device;

(115) FIG. 114 illustrates a plan view of the machine of FIG. 106 in a closed configuration, after the electronic device of FIG. 110 and the overlay applicator of FIG. 113 have been installed inside the machine;

(116) FIG. 115 illustrate a cross-sectional elevational view of the machine of FIG. 106 as the lid of the machine is being closed, but ajar, before the lid has been latched into the base of the machine;

(117) FIG. 116 illustrates a cross-sectional elevational view of a portion of the machine of FIG. 106 in a closed configuration with the electronic device of FIG. 110 seated within the adjustable cradle of the machine;

(118) FIG. 117 illustrates a plan view of a machine in an opened configuration, according to another embodiment;

(119) FIG. 118 illustrates a perspective view of the machine of FIG. 117 in an opened configuration;

(120) FIG. 119 illustrates a perspective view of a portion of the base of the machine of FIG. 117;

(121) FIG. 120 illustrates a plan view of the base of FIG. 117, showing various external and internal components of the base, with a side holder of FIG. 117 in a partially opened position;

(122) FIG. 121 illustrates a plan view of the base of FIG. 117, showing various external and internal components of the base, with the side holder of FIG. 117 in a closed position;

(123) FIG. 122 illustrates a perspective view of a portion of the base of FIG. 117, showing various external and internal components of the base, with the side holder of FIG. 117 in a closed position;

(124) FIG. 123 illustrates a plan view of a portion of the base of FIG. 117, showing various external and internal components of the base, with a top holder of FIG. 117 in a seated position holding an electronic device of FIG. 117;

(125) FIG. 124 illustrates a plan view of a portion of the base of FIG. 117, showing various external and internal components of the base, with the top holder of FIG. 117 in a closed position;

(126) FIG. 125 illustrates a perspective view of a machine in a closed configuration with an overlay applicator installed, according to another embodiment;

(127) FIG. 126 illustrates a perspective view of a base of the machine of FIG. 125 with the overlay applicator of FIG. 125 installed and without an electronic device installed;

(128) FIG. 127 illustrates a perspective view of the base of FIG. 125 with the overlay applicator of FIG. 125 and an electronic device installed;

(129) FIG. 128 illustrates a plan view of the base of FIG. 125 with a left side holder, a right side holder, a left top corner holder, and a right top corner holder in an opened position;

(130) FIG. 129 illustrates a plan view of the base of FIG. 125 with the left side holder, the right side holder, the left top corner holder, and the right top corner holder in a closed (released) position;

(131) FIG. 130 illustrates a plan view of a portion of the base of FIG. 125 below a base support surface to view an under surface on the opposite side of the base support surface;

(132) FIG. 131 illustrates a plan view of a portion of the base of FIG. 125 with an alignment plate installed;

(133) FIG. 132 illustrates a plan view of a portion of the base of FIG. 125 with the alignment plate removed;

(134) FIG. 133 illustrates a perspective view of a machine in an opened configuration, according to another embodiment;

(135) FIG. 134 illustrates a perspective view of the machine of FIG. 133 in a closed configuration;

(136) FIG. 135 illustrates a plan view of the base of FIG. 133 with a right top corner holder in a closed position;

(137) FIG. 136 illustrates a plan view of the base of FIG. 133 with the right top corner holder in an opened position;

(138) FIG. 137 illustrates a cross-sectional elevational view of the machine of FIG. 133 in a closed configuration;

(139) FIG. 138 illustrates an enlarged cross-sectional view of a portion of the machine of FIG. 133, as identified in FIG. 137, in the closed configuration;

(140) FIG. 139 illustrates a flow chart for an embodiment of a method of providing a machine, according to another embodiment;

(141) FIG. 140 illustrates a flow chart for an embodiment of a method of providing a machine, according to another embodiment;

(142) FIG. 141 illustrates a flow chart for an embodiment of a method of providing a machine, according to another embodiment; and

(143) FIG. 142 illustrates a flow chart for an embodiment of a method of providing a machine, according to another embodiment.

(144) For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different figures denote the same elements.

(145) The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms

“include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.

(146) The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

(147) The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements mechanically and/or otherwise. Two or more electrical elements may be electrically coupled together, but not be mechanically or otherwise coupled together. Coupling may be for any length of time, e.g., permanent or semi-permanent or only for an instant. “Electrical coupling” and the like should be broadly understood and include electrical coupling of all types. The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable. “Mechanical coupling” and the like should be broadly understood and include mechanical coupling of all types.

(148) The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable.

(149) As defined herein, two or more elements are “integral” if they are comprised of the same piece of material. As defined herein, two or more elements are “non-integral” if each is comprised of a different piece of material.

(150) As defined herein, “approximately” can, in some embodiments, mean within plus or minus ten percent of the stated value. In other embodiments, “approximately” can mean within plus or minus five percent of the stated value. In further embodiments, “approximately” can mean within plus or minus three percent of the stated value. In yet other embodiments, “approximately” can mean within plus or minus one percent of the stated value.

DESCRIPTION OF EXAMPLES OF EMBODIMENTS

(151) Various embodiments include an overlay applicator. The overlay applicator can include an overlay. The overlay can include a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to a screen of an electronic device. The overlay applicator also can include an adhesive release liner. The adhesive release liner can include a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants. The overlay applicator further can include a protective film removably attached to the top side of the overlay. The overlay applicator also can include an alignment tab. The alignment tab can include an alignment mechanism. The overlay applicator further can include a pull tab. The pull can include a wiper. The pull tab, including the wiper, and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner and can be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. The pull tab, including the wiper, and the adhesive release liner can be configured such that, when the pull tab is pulled, the wiper can be configured to wipe across and clean the screen of the electronic device.

(152) A number of embodiments can include a method of providing an overlay applicator. The method can include providing an overlay. The overlay can include a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to a screen of an electronic device. The method also can include providing an adhesive release liner. The adhesive release liner can include a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants. The method further can include providing a protective film removably attached to the top side of the overlay. The method also can include providing an alignment tab. The alignment tab can include an alignment mechanism. The method further can include providing a pull tab. The pull tab can include a wiper. The pull tab, including the wiper, and the adhesive release liner can be

configured such that the pull tab can be folded across the bottom side of the adhesive release liner and can be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. The pull tab, including the wiper, and the adhesive release liner can be configured such that, when the pull tab is pulled, the wiper can be configured to wipe across and clean the screen of the electronic device.

(153) Some embodiments include a machine. The machine can include a base. The machine also can include a carriage. The carriage can include a first cradle configured to securely hold a first electronic device. The carriage also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The machine further can include a handle assembly. The handle assembly can include a handle and a pulling mechanism configured to engage with a pull tab of the overlay applicator. The machine can be configured such that the handle assembly can be pulled in a first direction relative to the base from a first handle position to a second handle position. The machine can be configured such that when the handle assembly is moved from the first handle position to the second handle position, the carriage can move in a second direction relative to the base from a first carriage position to a second carriage position. The second direction can be opposite the first direction. The machine can be configured such that when (a) the alignment base is engaged with the alignment mechanism of the overlay applicator, (b) the pulling mechanism is engaged with the pull tab of the overlay applicator, (c) the first cradle is holding the first electronic device, and (d) the handle assembly is pulled in the first direction relative to the base from the first handle position to the second handle position, an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator starting at a leading edge of the overlay and continuing to a trailing edge of the overlay to expose an adhesive agent of the overlay to a screen of the first electronic device.

(154) Many embodiments include a method of providing a machine. The method can include providing a base. The method also can include providing a carriage. The carriage can include a first cradle configured to securely hold a first electronic device. The carriage also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The method further can include providing a handle assembly. The handle assembly can include a handle and a pulling mechanism configured to engage with a pull tab of the overlay applicator. The machine can be configured such that the handle assembly can be pulled in a first direction relative to the base from a first handle position to a second handle position. The machine can be configured such that when the handle assembly is moved from the first handle position to the second handle position, the carriage can move in a second direction relative to the base from a first carriage position to a second carriage position. The second direction can be opposite the first direction. The machine can be configured such that when (a) the alignment base is engaged with the alignment mechanism of the overlay applicator, (b) the pulling mechanism is engaged with the pull tab of the overlay applicator, (c) the first cradle is holding the first electronic device, and (d) the handle assembly is pulled in the first direction relative to the base from the first handle position to the second handle position, an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator starting at a leading edge of the overlay and continuing to a trailing edge of the overlay to expose an adhesive agent of the overlay of the overlay applicator to a screen of the first electronic device.

(155) Several embodiments include a machine. The machine can include a base. The machine also can include a cradle configured to securely hold a first electronic device. The machine further can include an alignment piece hingedly attached to the base. The alignment piece can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The machine also can include a pulling piece hingedly attached to the base. The pulling piece can include a pulling mechanism configured to engage with a pull tab of the overlay applicator. The machine can be configured such that the pulling piece can be rotated relative to the base in a first direction from a first pulling piece position to a second pulling piece position. The first pulling piece position can be proximate to the cradle. The machine can be configured such that the alignment piece can be rotated relative to the base in the first direction from a first alignment piece position to a second alignment piece position. The second alignment piece position can be proximate to the cradle. The machine can be configured such that when (a) the alignment base is engaged with the alignment mechanism of the overlay applicator, (b) the pulling mechanism is engaged with the pull tab of the overlay applicator, (c) the cradle is holding the first

electronic device, and (d) the pulling piece is rotated relative to the base in the first direction from the first pulling piece position to the second pulling piece position, the alignment piece can be rotated relative to the base in the first direction from the first alignment piece position to the second alignment piece position, and an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator to expose an adhesive agent of an overlay to a screen of the first electronic device. (156) Further embodiments include a method of providing a machine. The method can include providing a base. The method also can include providing a cradle configured to securely hold a first electronic device. The method further can include providing an alignment piece hingedly attached to the base. The alignment piece can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The method also can include providing a pulling piece hingedly attached to the base. The pulling piece can include a pulling mechanism configured to engage with a pull tab of the overlay applicator. The machine can be configured such that the pulling piece can be rotated relative to the base in a first direction from a first pulling piece position to a second pulling piece position. The first pulling piece position can be proximate to the cradle. The machine can be configured such that the alignment piece can be rotated relative to the base in the first direction from a first alignment piece position to a second alignment piece position. The second alignment piece position can be proximate to the cradle. The machine can be configured such that when (a) the alignment base is engaged with the alignment mechanism of the overlay applicator, (b) the pulling mechanism is engaged with the pull tab of the overlay applicator, (c) the cradle is holding the first electronic device, and (d) the pulling piece is rotated relative to the base in the first direction from the first pulling piece position to the second pulling piece position, the alignment piece can be rotated relative to the base in the first direction from the first alignment piece position to the second alignment piece position to pull the pull tab of the overlay applicator, and an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator to expose an adhesive agent of an overlay to a screen of the first electronic device. (157) Yet further embodiments include a method of using an overlay applicator to apply an overlay to a screen of an electronic device. The method can include attaching the overlay applicator to a first apparatus securely holding the electronic device. The overlay applicator can include an overlay. The overlay can include a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to the screen of the electronic device. The overlay applicator also can include an adhesive release liner. The adhesive release liner can include a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants. The overlay applicator further can include protective film removably attached to the top side of the overlay. The overlay applicator also can include an alignment tab. The alignment tab can include an alignment mechanism configured to engage with an alignment base of the first apparatus. The overlay applicator further can include a pull tab. The pull can include a wiper. The method also can include pulling the pull tab across the bottom side of the adhesive release liner to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent to the screen of the electronic device.

(158) Still further embodiments include a method of providing an overlay applicator. The method can include providing an adhesive release liner including a top side and a bottom side. The method also can include providing a pull tab including a top side and a bottom side. The method further can include attaching a wiper to the top side of the pull tab. The method additionally can include providing an overlay layer including a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to a screen of an electronic device. The method further can include attaching the bottom side of the overlay layer to the top side of the adhesive release liner. The method additionally can include providing a protective film layer including a top side and a bottom side. The method further can include attaching the bottom side of the protective film layer to the top side of the overlay layer. The method additionally can include cutting the protective film layer and the overlay layer to create an interface slit between an alignment tab and a device portion, and to create a tail slit between a tail portion and the device portion. The method further can include attaching a sticker to the top side of the protective film. The sticker can span the interface slit between the device portion and the alignment tab. The device portion of the overlay layer can be configured to adhere to a screen of an electronic device. The device

portion can have dimensions approximately the same as dimensions of the screen of the electronic device.

(159) Additional embodiments include a cradle. The cradle can include a base. The cradle also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The cradle further can include one or more frame pieces configured to securely hold an electronic device in a device slot in a fixed position with respect to the alignment base. The base, the alignment base, and the one or more frame pieces can be configured to hold the overlay applicator between the base and a screen of the electronic device when the screen of the electronic device is facing toward the base; and facilitate applying an overlay of the overlay applicator to the screen of the electronic device.

(160) Further embodiments include a method of providing a cradle. The method can include providing a base. The method also can include providing an alignment base configured to engage with an alignment mechanism of an overlay applicator. The method further can include providing one or more frame pieces configured to securely hold an electronic device in a device slot in a fixed position with respect to the alignment base. The base, the alignment base, and the one or more frame pieces can be configured to hold the overlay applicator between the base and a screen of the electronic device when the screen of the electronic device is facing toward the base; and facilitate applying an overlay of the overlay applicator to the screen of the electronic device.

(161) Still further embodiments include a machine. The machine can include a base. The base can include a first end and a second end. The base also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include a first alignment tab and a second alignment tab. The first alignment tab can include a first portion of the alignment mechanism. The second alignment tab can include a second portion of the alignment mechanism. The alignment base can include a first side proximate the first end of the base. The first side can be configured to engage with the first portion of the alignment mechanism of the overlay applicator. The alignment base also can include a second side proximate the second end of the base. The second side can be configured to engage with the second portion of the alignment mechanism of the overlay applicator. The base further can include a pull slot. The machine further can include a cradle located between the first side of the alignment base and the second side of the alignment base. The cradle can be configured to securely hold an electronic device. The machine additionally can include a slider configured to move between the first and second ends of the base. The slider can include a bar. The bar can be configured to press an overlay of the overlay applicator toward a screen of the electronic device when the slider is moved between the first and second ends of the base.

(162) Yet further embodiments can include a method of providing a machine. The method can include providing a base. The base can include a first end and a second end. The base also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include a first alignment tab and a second alignment tab. The first alignment tab can include a first portion of the alignment mechanism. The second alignment tab can include a second portion of the alignment mechanism. The alignment base can include a first side proximate the first end of the base. The first side can be configured to engage with the first portion of the alignment mechanism of the overlay applicator. The alignment base also can include a second side proximate the second end of the base. The second side can be configured to engage with the second portion of the alignment mechanism of the overlay applicator. The base further can include a pull slot. The method further can include providing a cradle located between the first side of the alignment base and the second side of the alignment base. The cradle can be configured to securely hold an electronic device. The method additionally can include providing a slider configured to move between the first and second ends of the base. The slider can include a bar. The bar can be configured to press an overlay of the overlay applicator toward a screen of the electronic device when the slider is moved between the first and second ends of the base.

(163) Additional embodiments can include a machine. The machine can include a base. The machine also can include a cradle configured to securely hold an electronic device. The cradle can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The machine further can include an arm. The arm can include an expandable bladder and a pumping mechanism configured to inflate the expandable bladder. The arm can be configured to be hingedly

rotated between an open configuration and a closed configuration. The machine can be configured such that when the arm is in the closed configuration and the expandable bladder is inflated, the expandable bladder can press an overlay of the overlay applicator toward a screen of the electronic device to adhere an adhesive side of the overlay to the screen of the electronic device.

(164) Further embodiments can include a method of providing a machine. The method can include providing a base. The method also can include providing a cradle configured to securely hold an electronic device. The cradle can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The method further can include providing an arm. The arm can include an expandable bladder and a pumping mechanism configured to inflate the expandable bladder. The arm can be configured to be hingedly rotated between an open configuration and a closed configuration. The machine can be configured such that when the arm is in the closed configuration and the expandable bladder is inflated, the expandable bladder can press an overlay of the overlay applicator toward a screen of the electronic device to adhere an adhesive side of the overlay to the screen of the electronic device.

(165) Additional embodiments can include a machine. The machine can include a support base. The machine also can include a first cradle configured to hold a first electronic device. The machine further can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The machine also can include a lid hingedly attached to the support base. The machine can be configured such that the lid can be rotated with respect to the support base between an open configuration and a closed configuration. The machine can be configured in the closed configuration to facilitate applying the overlay of the overlay applicator to the screen of the first electronic device.

(166) Further embodiments can include a method of providing a machine. The method can include providing a support base. The method also can include providing a first cradle configured to hold a first electronic device. The method further can include providing an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The method also can include providing a lid hingedly attached to the support base. The machine can be configured such that the lid can be rotated with respect to the support base between an open configuration and a closed configuration. The machine can be configured in the closed configuration to facilitate applying the overlay of the overlay applicator to the screen of the first electronic device.

(167) Still further embodiments can include a cradle. The cradle can include a device slot configured to securely hold an electronic device. The cradle also can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include a first alignment tab and a second alignment tab. The first alignment tab can include a first portion of the alignment mechanism. The second alignment tab can include a second portion of the alignment mechanism. The alignment base can include a first side configured to engage with the first portion of the alignment mechanism of the overlay applicator. The alignment base also can include a second side configured to engage with the second portion of the alignment mechanism of the overlay applicator. The cradle further can include a pull slot disposed between the device slot and the second side of the alignment base.

(168) Yet further embodiments can include a method of providing a cradle. The method can include providing a device slot configured to securely hold an electronic device. The method also can include providing an alignment base configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can include a first alignment tab and a second alignment tab. The first alignment tab can include a first portion of the alignment mechanism. The second alignment tab can include a second portion of the alignment mechanism. The alignment base can include a first side configured to engage with the first portion of the alignment mechanism of the overlay applicator. The alignment base also can include a second side configured to engage with the second portion of the alignment mechanism of the overlay applicator. The method further can include providing a pull slot disposed between the device slot and the second side of the alignment base.

(169) Additional embodiments can include a set of cradles. The set of cradles can include a first cradle. The first cradle can include a first device slot including first dimensions and configured to securely hold

a first electronic device. The first cradle also can include a first alignment base configured to engage with an alignment mechanism of a first overlay applicator. The first overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The set of cradles also can include a second cradle. The second cradle can include a second device slot including second dimensions and configured to securely hold a second electronic device. The second cradle also can include a second alignment base configured to engage with an alignment mechanism of a second overlay applicator. The second overlay applicator can include an overlay configured to be applied to a screen of the second electronic device. The first dimensions of the first device slot of the first cradle can be different from the second dimensions of the second device slot of the second cradle. The first cradle and the second cradle can be configured to be stacked in a first coterminous configuration.

(170) Further embodiments can include a method of providing a set of cradles. The method can include providing a first cradle. The first cradle can include a first device slot including first dimensions and configured to securely hold a first electronic device. The first cradle also can include a first alignment base configured to engage with an alignment mechanism of a first overlay applicator. The first overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The method also can include providing a second cradle. The second cradle can include a second device slot including second dimensions and configured to securely hold a second electronic device. The second cradle also can include a second alignment base configured to engage with an alignment mechanism of a second overlay applicator. The second overlay applicator can include an overlay configured to be applied to a screen of the second electronic device. The first dimensions of the first device slot of the first cradle can be different from the second dimensions of the second device slot of the second cradle. The first cradle and the second cradle can be configured to be stacked in a first coterminous configuration.

(171) Still further embodiments can include an overlay applicator. The overlay applicator can include an overlay including a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to a screen of an electronic device. The overlay applicator also can include an adhesive release liner including a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants. The overlay applicator further can include an alignment tab including an alignment mechanism. The overlay applicator also can include a pull tab. The overlay applicator further can include a wiper. The wiper can include a surface and a first slot extending at least partially through the surface of the wiper. The wiper can be attached to the pull tab. The pull tab, the wiper, and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner and can be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. The pull tab, the wiper, and the adhesive release liner can be configured such that, when the pull tab is pulled, the wiper can wipe across and clean the screen of the electronic device.

(172) Yet further embodiments can include a method of providing an overlay applicator. The method can include providing an overlay comprising a top side and a bottom side. The bottom side can include an adhesive agent configured to adhere to a screen of an electronic device. The method also can include providing an adhesive release liner comprising a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants. The method further can include providing an alignment tab including an alignment mechanism. The method also can include providing a pull tab. The method further can include providing a wiper. The wiper can include a surface and a first slot extending at least partially through the surface of the wiper. The method also can include attaching the wiper to the pull tab. The pull tab, the wiper, and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner and can be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. The pull tab, the wiper, and the adhesive release liner can be configured such that, when the pull tab is pulled, the wiper can wipe across and clean the screen of the electronic device.

(173) Additional embodiments can include a system. The system can include an overlay applicator. The overlay applicator can include an overlay including a top side and a bottom side. The bottom side can include a first adhesive agent configured to adhere to a screen of an electronic device. The overlay

applicator also can include an adhesive release liner including a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the first adhesive agent at the bottom side of the overlay from contaminants. The overlay applicator further can include a protective film removably attached to the top side of the overlay. The overlay applicator also can include an alignment tab including an alignment mechanism. The overlay applicator also can include a pull tab. The system also can include a sticker assembly. The sticker assembly can include a sticker including a top side and a bottom side and an end portion. The bottom side can include a second adhesive agent configured to removably adhere to the screen of the electronic device. The sticker assembly also can include a release liner removably attached to the bottom side of the sticker. The release liner can include a device portion and an end portion. The end portion of the release liner can be removably attached to the end portion of the sticker. The sticker assembly can be configured such that, when the device portion of the release liner is removed to expose the second adhesive agent, the second adhesive agent of the bottom side of the sticker can be adhered to the screen of the electronic device, and the end portion of the sticker can be folded back over the top side of the sticker to expose the end portion of the release liner. The pull tab and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner. The sticker assembly can be configured such that, when the end portion of the sticker is folded back over the top side of the sticker and the end portion of the release liner is removed from the sticker to expose the second adhesive agent, the end portion of the sticker can be adhered to the pull tab while the pull tab is folded across the bottom side of the adhesive release liner. The overlay applicator and sticker assembly can be configured such that, when the end portion of the sticker is adhered to the pull tab, the pull tab can be pulled to remove the sticker from the screen of the electronic device and to remove the adhesive release liner from the bottom side of the overlay to expose the first adhesive agent to the screen of the device. The sticker can be configured to remove dust from the screen of the electronic device when the sticker is removed from the screen of the electronic device.

(174) Further embodiments include a method. The method can include providing an overlay applicator. The overlay applicator can include an overlay including a top side and a bottom side. The bottom side can include a first adhesive agent configured to adhere to a screen of an electronic device. The overlay applicator also can include an adhesive release liner including a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. The adhesive release liner can be configured to protect the first adhesive agent at the bottom side of the overlay from contaminants. The overlay applicator further can include a protective film removably attached to the top side of the overlay. The overlay applicator also can include an alignment tab including an alignment mechanism. The overlay applicator also can include a pull tab. The method also can include providing a sticker assembly. The sticker assembly can include a sticker including a top side and a bottom side and an end portion. The bottom side can include a second adhesive agent configured to removably adhere to the screen of the electronic device. The sticker assembly also can include a release liner removably attached to the bottom side of the sticker. The release liner can include a device portion and an end portion. The end portion of the release liner can be removably attached to the end portion of the sticker. The sticker assembly can be configured such that, when the device portion of the release liner is removed to expose the second adhesive agent, the second adhesive agent of the bottom side of the sticker can be adhered to the screen of the electronic device, and the end portion of the sticker can be folded back over the top side of the sticker to expose the end portion of the release liner. The pull tab and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner. The sticker assembly can be configured such that, when the end portion of the sticker is folded back over the top side of the sticker and the end portion of the release liner is removed from the sticker to expose the second adhesive agent, the end portion of the sticker can be adhered to the pull tab while the pull tab is folded across the bottom side of the adhesive release liner. The overlay applicator and sticker assembly can be configured such that, when the end portion of the sticker is adhered to the pull tab, the pull tab can be pulled to remove the sticker from the screen of the electronic device and to remove the adhesive release liner from the bottom side of the overlay to expose the first adhesive agent to the screen of the device. The sticker can be configured to remove dust from the screen of the electronic device when the sticker is removed from the screen of the electronic device.

(175) Additional embodiments include an overlay applicator tray. The overlay applicator tray can include a cradle including a device slot. The device slot can be configured to securely hold an electronic device in the device slot. The overlay applicator tray also can include an overlay applicator. The overlay applicator can include an overlay layer. The overlay layer can include a first side and a second side. The second side can be configured to be adhered to a screen of the electronic device. The overlay applicator also can include a release liner. The release liner can be configured to be removed from the second side of the overlay layer to permit the second side of the overlay layer to be adhered to the screen of the electronic device. The overlay applicator tray additionally can include an alignment piece coupling the cradle to the overlay applicator such that the overlay layer is aligned with the screen of the electronic device when the electronic device is securely held in the device slot as the overlay applicator is applied to the screen of the electronic device.

(176) A number of embodiments can include an overlay applicator tray. The overlay applicator tray can include a cradle including a device slot. The device slot can be configured to securely hold an electronic device in the cradle. The overlay applicator tray also can include an overlay applicator. The overlay applicator can include an overlay layer and an adhesive release liner. The overlay layer can include a top side and a bottom side. The bottom side can be configured to be adhered to a screen of the electronic device. The adhesive release liner can be removable from and/or removably attached to the bottom side of the overlay layer. The overlay applicator tray additionally can include an alignment piece coupling the cradle to the overlay applicator. The alignment piece can align the overlay layer of the overlay applicator with the screen as the overlay layer is applied to the screen when the electronic device is securely held in the device slot. In some embodiments, the alignment of the overlay layer with the screen by the alignment piece is automatic or self-aligned.

(177) Embodiments also can include an overlay applicator tray. The overlay applicator tray can include a cradle including a device slot. The device slot can be configured to hold an electronic device in the cradle. The overlay applicator tray also can include an overlay applicator. The overlay applicator can include an overlay layer and an adhesive release liner. The overlay layer can include a first side and a second side. In some embodiments, the first side is a bottom side, and the second side is a top side, and in other embodiments, the first side is a top side, and the second side is a bottom side. The first side can be configured to be adhered to a screen of the electronic device. The adhesive release liner can be removable from and/or removably attached to the first side of the overlay layer. The overlay applicator tray additionally can include an alignment piece coupling the cradle to the overlay applicator. The alignment piece can align the overlay layer of the overlay applicator with the screen as the overlay layer is applied to the screen when the electronic device is held in the device slot. In some embodiments, the device slot can hold the electronic device in the cradle in a secure manner, and in the same or different embodiments, the alignment of the overlay layer with the screen by the alignment piece is automatic or self-aligned.

(178) Further embodiments can include a method. The method can include inserting an electronic device into a device slot of a cradle of an overlay applicator tray. The device slot can be configured to securely hold the electronic device in the cradle. The overlay applicator tray can include an overlay applicator and an alignment piece coupling the cradle to the overlay applicator. The method also can include rotating the overlay applicator with respect to the cradle to apply an overlay layer of the overlay applicator to a screen of the electronic device. The overlay layer can include a top side and a bottom side. The bottom side can be configured to be adhered to the screen. The alignment piece can align the overlay layer with the screen and maintain the coupling of the cradle to the overlay applicator as the overlay layer is applied to the screen. In some embodiments, the alignment of the overlay layer with the screen by the alignment piece is automatic or self-aligned.

(179) Further embodiments can include a method. The method can include inserting an electronic device into a device slot of a cradle of an overlay applicator tray. The device slot can be configured to hold the electronic device in the cradle. The overlay applicator tray can include an overlay applicator and an alignment piece coupling the cradle to the overlay applicator. The method also can include rotating the overlay applicator with respect to the cradle to apply an overlay layer of the overlay applicator to a screen of the electronic device. The overlay layer can include a first side and a second side. In some embodiments, the first side is a bottom side, and the second side is a top side, and in other embodiments, the first side is a top side, and the second side is a bottom side. The first side can be configured to be

adhered to the screen. The alignment piece can align the overlay layer with the screen and maintain the coupling of the cradle to the overlay applicator as the overlay layer is applied to the screen. In some embodiments, the device slot can hold the electronic device in the cradle in a secure manner, and in the same or different embodiments, the alignment of the overlay layer with the screen by the alignment piece is automatic or self-aligned.

(180) Additional embodiments can include an apparatus. The apparatus can include an overlay including a top side and a bottom side. The apparatus also can include an adhesive component including a top side and a bottom side. The top side of the adhesive component can be adhered to the bottom side of the overlay. The adhesive component can be configured to adhere the bottom side of the overlay to a screen of an electronic device in a single-use application of the overlay by adhering the bottom side of the adhesive component to the screen of the electronic device. The apparatus can be configured such that, when the overlay is removed from being adhered to the screen of the electronic device after the single-use application of the overlay, at least a portion of the adhesive component is detached from at least a portion of the overlay.

(181) Further embodiments can include a method. The method can include providing an overlay. The overlay can include a top side and a bottom side. The method also can include providing an adhesive component. The adhesive component can include a top side and a bottom side. The top side of the adhesive component can be adhered to the bottom side of the overlay. The adhesive component can be configured to adhere the bottom side of the overlay to a screen of an electronic device in a single-use application of the overlay by adhering the bottom side of the adhesive component to the screen of the electronic device. The overlay and the adhesive component can be configured such that, when the overlay is removed from being adhered to the screen of the electronic device after the single-use application of the overlay, at least a portion of the adhesive component can be detached from at least a portion of the overlay.

(182) Additional embodiments include a machine. The machine can include a base including a first cradle. The first cradle can include a device slot being configured to securely hold a first electronic device. The machine also can include an alignment piece hingedly attached to the base at a hinge. The alignment piece can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The machine additionally can include a pulling piece movably attached to the base. The pulling piece can be configured to remove an adhesive release liner of the overlay applicator to expose an adhesive agent of an overlay of the overlay applicator when the alignment piece is rotated relative to the base around the hinge from a first alignment piece position to a second alignment piece position.

(183) Additional embodiments include a method of providing a machine. The method can include providing a machine including a base including a first cradle. The first cradle can include a device slot being configured to securely hold a first electronic device. The method also can include providing an alignment piece hingedly attached to the base at a hinge. The alignment piece can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The method additionally can include providing a pulling piece movably attached to the base. The pulling piece can be configured to remove an adhesive release liner of the overlay applicator to expose an adhesive agent of an overlay of the overlay applicator when the alignment piece is rotated relative to the base around the hinge from a first alignment piece position to a second alignment piece position.

(184) Various embodiments of an overlay applicator can be configured to facilitate application of an overlay on the screen of a device. In some embodiments, the overlay applicator can be configured to facilitate removing dust from the screen of the device immediately before application. In certain embodiments, the overlay applicator can facilitate keeping dust and fingerprints from coming into contact with adhesive on the overlay. In various embodiments, the overlay applicator can be configured to facilitate alignment of the overlay with the screen of the device during application.

(185) A number of embodiments include a machine. The machine can include an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The machine also can include an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators. Each respective one of the overlay applicators can include a respective overlay configured to be applied to a respective surface of each of the electronic devices.

The machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices.

(186) Various embodiments include a method of providing a machine. The method can include providing an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The method also can include providing an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators. Each respective one of the overlay applicators can include a respective overlay configured to be applied to a respective surface of each of the electronic devices. The machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices.

(187) A number of embodiments include a machine. The machine can include an alignment base. The machine also can include an adjustable cradle including one or more adjustable side holders configured to center an electronic device held in the adjustable cradle with respect to the alignment base.

(188) Various embodiments include a method of providing a machine. The method can include providing an alignment base. The method also can include providing an adjustable cradle including one or more adjustable side holders configured to center an electronic device held in the adjustable cradle with respect to the alignment base.

(189) A number of embodiments include a machine. The machine can include an alignment base. The machine also can include an adjustable cradle including a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a first side of an electronic device upon insertion of the electronic device into the adjustable cradle and (b) hold the electronic device against a second side wall of the adjustable cradle opposite the first side wall when the electronic devices is held within the adjustable cradle.

(190) Various embodiments include a method of providing a machine. The method can include providing an alignment base. The method also can include providing an adjustable cradle including a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a first side of an electronic device upon insertion of the electronic device into the adjustable cradle and (b) hold the electronic device against a second side wall of the adjustable cradle opposite the first side wall when the electronic devices is held within the adjustable cradle.

(191) A number of embodiments include a machine. The machine can include an alignment base. The machine can include an adjustable cradle including springs configured to adjust an inward position of the adjustable cradle for a thickness of an electronic device held in the adjustable cradle.

(192) Various embodiments include a method of providing a machine. The method can include providing an alignment base. The method also can include providing an adjustable cradle including springs configured to adjust an inward position of the adjustable cradle for a thickness of an electronic device held in the adjustable cradle.

(193) A number of embodiments include a machine. The machine can include an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The machine also can include an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators, each respective one of the overlay applicators comprising a respective overlay configured to be applied to a respective surface of each of the electronic devices. The machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices. The adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to adjust a respective position of each of the electronic devices held in the adjustable cradle with respect to the alignment base.

(194) Various embodiments include a method of providing a machine. The method can include providing an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The method also can include providing an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators, each respective one of the overlay applicators comprising a respective overlay configured to be applied to a respective surface of each of the electronic devices. The machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices. The adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder.

The second adjustable holder and the third adjustable holder can be configured to adjust a respective position of each of the electronic devices held in the adjustable cradle with respect to the alignment base.

(195) Turning to the drawings, FIG. 1 illustrates an exploded view showing various elements of an overlay applicator **100**. Overlay applicator **100** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. In a number of embodiments, overlay applicator **100** can include an alignment tab **110**, a protective film **120**, an overlay **130**, an adhesive release liner **140**, and/or a pull tab **150**. Overlay **130** can be a protective film for protecting the screen of an electronic device, such as a mobile phone, a tablet computer, or a smart phone, such as an iPhone, developed and sold by Apple, Inc., of Cupertino, California, among other devices. Overlay **130** can be made of polyethylene terephthalate (PET) or another suitable material. Overlay **130** can have dimensions such that it partially or fully covers the screen of the electronic device. In some embodiments, overlay **130** can have one or more holes, slots, or apertures. For example, overlay **130** can include a speaker slot **133**, which can allow sound from a speaker on the device to pass through overlay **130**. Overlay **130** can include a button slot **134**, which can allow a user to push a button on the face of the device without touching, stretching, or otherwise affecting overlay **130**. Overlay **130** can include a top side **131** and a bottom side **132**. In some embodiments, top side **131** can include a hard coating. In certain embodiments, top side **131** can include an optical coating. In many embodiments, bottom side **132** can include an adhesive agent to adhere overlay **130** to the screen of the device.

(196) In a number of embodiments, protective film **120** can be attached to top side **131** of overlay **130**. In many embodiments, protective film **120** can have dimensions substantially similar to the dimensions of overlay **130**. Protective film **120** can have a first side **129** and a second side **128**. Protective film **120** can provide protection for the hard coating or optical coating on overlay **130** during installation of overlay **130** on the device. In some embodiments, protective film **120** can be a thick flexible film and can have a thickness of approximately 0.1 to approximately 0.4 millimeters (mm), for example. In many embodiments, protective film **120** does not stretch or distort, which can advantageously facilitate alignment of overlay **130** on the device. In a number of embodiments, protective film **120** can be made of a suitable plastic or paper, or another suitable material. Protective film **120** can be configured such that it can be peeled away from top side **131** of overlay **130**. In certain embodiments, protective film **120** can include one or more holes, slots, or apertures. For example, protective film **120** can include a speaker slot **123** and a button slot **124**, which can be aligned with speaker slot **133** and button slot **134** when protective film **120** is attached to overlay **130**.

(197) In some embodiments, protective film **120** can include an adhesive region **121**, which can be adhered to alignment tab **110** at an adhesive region **112**. In many embodiments, protective film **120** can be removably attached to top side **131** of overlay **130**. In certain embodiments, adhesive region **121** of protective film **120** can be adhered to adhesive region **112** of alignment tab **110** using an adhesive agent. In some embodiments, protective film **120** can be attached to alignment tab **110** using a suitable fastening mechanism, such as one or more rivets or hook and loop tape, as examples. When alignment tab **110** is attached to protective film **120**, alignment tab **110** can extend beyond protective film **120**, in some embodiments, such that a portion of alignment tab **110** is not adhered to or touching protective film **120**. In some embodiments, alignment tab **110** can include an alignment mechanism **115** at the portion of alignment tab **110** that is not adhered to or touching protective film **120**. Alignment mechanism **115** can facilitate aligning alignment tab **110**, protective film **120**, and overlay **130** with various features of the device during application of overlay **130**. Alignment mechanism **115** can be one or more holes, slots, or other suitable alignment aid features. In some embodiments, alignment tab **110** does not stretch or distort, which can help facilitate accurate alignment of overlay **130** on the device. Alignment tab **110** can be made of plastic or cardboard, and can be thicker than protective film **120**. In certain embodiments, protective film **120** and at least a portion of alignment tab **110** can be integral, or in other words, made of the same piece of material. In such embodiments, protective film **120** can be made of a thicker material, such as alignment tab **110**, so as to provide sufficient structural support for alignment mechanism **115**.

(198) In a number of embodiments, adhesive release liner **140** can be attached to bottom side **132** of overlay **130**. In many embodiments, adhesive release liner **140** can have dimensions substantially similar to the dimensions of overlay **130**. Adhesive release liner **140** can have a first side **149** and a second side

148. By being attached to bottom side **132** of overlay **130**, adhesive release liner **140** can keep the adhesive agent on bottom side **132** covered and protected until the overlay **130** is ready to be adhered to the screen of the device. In many embodiments, a top side of adhesive release liner **140** can be removably attached to bottom side **132** of overlay **130**, and/or can be configured to protect the adhesive agent on bottom side **132** of overlay **130** from contaminants. In some embodiments, adhesive release liner **140** can be a thin flexible film and can have a thickness of approximately 0.1 mm to approximately 0.25 mm. In certain embodiments, adhesive release liner **140** can be made of a material that can stretch and/or distort. In certain other embodiments, adhesive release liner **140** can be made of a material that does not stretch or distort. In a number of embodiments, adhesive release liner **140** can be made of a suitable thin plastic film or paper, or another suitable material. Adhesive release liner **140** can be configured such that it can be peeled away from bottom side **132** of overlay **130**. In certain embodiments, adhesive release liner **140** can include one of more holes, slots, or apertures. For example, adhesive release liner **140** can include a speaker slot **143** and a button slot **144**, which can be aligned with speaker slot **133** and button slot **134** when adhesive release liner **140** is attached to overlay **130**.

(199) In some embodiments, pull tab **150** can facilitate removal of adhesive release liner **140**. Pull tab **150** can include a first side **159** and a second side **158**. In some embodiments, adhesive release liner **140** can include an adhesive region **142** at second side **148**, which can be adhered to pull tab **150** at an adhesive region **151** at first side **159**. In certain embodiments, adhesive region **142** of adhesive release liner **140** can be adhered to adhesive region **151** of pull tab **150** using an adhesive agent. In other embodiments, adhesive release liner **140** can be attached to pull tab **150** using another suitable fastening mechanism, such as rivets or hook and loop tape. When pull tab **150** is attached to adhesive release liner **140**, alignment tab **110** can extend beyond adhesive release liner **140**, such that a portion of pull tab **150** is not adhered to or touching adhesive release liner **140**. In a number of embodiments, pull tab **150** can have a dimension such that a distance from first side **159** to second side **158** of pull tab **150** is longer than a dimension from first side **149** to second side **148** of adhesive release liner **140**. In many embodiments, when pull tab **150** is attached to adhesive release liner **140**, pull tab **150** can be folded back near first side **159** and can extend across the length of and beyond first side **149** of adhesive release liner **140**. In a number of embodiments, pull tab **150** can be folded across the bottom side of adhesive release liner **140** and pulled to remove adhesive release liner **140** from bottom side **132** of overlay **130** to expose the adhesive agent. Pull tab **150** can be made of a flexible plastic or paper, or another suitable material. In certain embodiments, adhesive release liner **140** and pull tab **150** can be integral. In such embodiments, adhesive release liner **140** can be made of a thicker material, pull tab **150**, so as to provide sufficient structural support for pulling on adhesive release liner **140**.

(200) In some embodiments, pull tab **150** can include a pulling aid **156**. Pulling aid **156** can facilitate pulling pull tab **150**, and can be or include one or more holes, slots, grooves, ridges, channels, etc. For example, pulling aid **156** can be two holes in which a user can place two fingers to assist in pulling pull tab **150** or in which an applicator machine can insert tabs to engage with pull tab **150**. Pulling aid **156** can also assist a user in differentiating the ends of pull tab **150** and in knowing which end to pull when installing overlay **130** on the device.

(201) In many embodiments, overlay applicator **100** and/or pull tab **150** can include a wiper **157**. Wiper **157** can remove dust from the screen of the device and can facilitate application of overlay **130** to the screen of the device without dust between overlay **130** and the screen. In a number of embodiments, wiper **157** can be adhered to a top side of pull tab **150**. Wiper **157** can be made of microfiber cloth, soft silicone, an extruded rubber profile wiper blade, and/or other suitable materials. In various embodiments, wiper **157** can be a solid block, a row of fins, or of another suitable form for cleaning the screen of the device. In many embodiments, wiper **157** can be configured such that when pull tab **150** is pulled, wiper **157** can wipe across and clean the screen of the device, as described below in further detail. In a number of embodiments, the wiper can be configured to wipe across a length of the screen of the device. In some embodiments, the length of the screen of the device can be greater than a width of the screen of the device.

(202) In many embodiments, overlay applicator **100** can be manufactured such that protective film **120**, overlay **130**, and adhesive release liner **140** are each attached and are coterminous with each other. For example, protective film **120**, overlay **130**, and adhesive release liner **140** can be attached and then cut,

such that the sides and other features of protective film **120**, overlay **130**, and adhesive release liner **140** are aligned. Alignment tab **110** can then be adhered to protective film **120**, and pull tab **150** can be adhered to adhesive release liner **140**. In certain embodiments, as described above, protective film **120** and at least a portion of alignment tab **110** can be integral. For example, adhesive release liner **140** can be adhered to overlay **130** and overlay can be adhered to protective film **120**, and overlay **130** and adhesive release liner **140** can be cut to size without cutting protective film **120**.

(203) Turning ahead in the drawings, FIG. 2 illustrates a system **200** for using overlay applicator **100** to apply overlay **130** to a device. System **200** is merely exemplary and embodiments of the system are not limited to embodiments presented herein. The system can be employed in many different embodiments or examples not specifically depicted or described herein. System **200** can include overlay applicator **100**, a frame **210**, and a device **220** (e.g., a smart phone). Frame **210** can include a hole **211** in which device **220** can be placed with the screen of device **220** facing upwards or away from frame **210**. In some embodiments, hole **211** is conformal with device **220**. In other embodiments, hole **211** can have dimensions large enough that it can fit around a several different electronic devices. Frame **210** can have a height substantially similar to the height of device **220**. In many embodiments, frame **210** can include an alignment base **212**, which can engage with alignment mechanism **115**. In some embodiments, alignment base **212** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **115**. Alignment base **212** and alignment mechanism **115** can be configured and positioned such that when alignment mechanism **115** is engaged with alignment base **212**, overlay **130** can be positioned directly above the screen of the device, and aligned such that overlay **130** will be adhered in an accurate position on the screen when adhesive release liner **140** is removed.

(204) In some embodiments, overlay applicator **100** can be used to apply overlay **130** to device **220** in frame **210**. Pull tab **150** can be folded such that second side **158** of pull tab **150** is pulled under adhesive release liner **140** from second side **148** to first side **149**, as shown in FIG. 2. Overlay applicator **100** can be placed on frame **210** such that alignment mechanism **115** engages with alignment base **212**. Frame **210** can be placed over device **220** with the screen of device **220** facing up. In many embodiments, by placing frame **210** over device **220**, wiper **157** can come in contact with the screen of device **220**. While holding frame **210**, a user can pull on pull tab **150**, e.g., by using pulling aid **156**, such that wiper **157** is pulled across the screen of device **220**, which can remove dust or other particles from the screen of device **220**. In a number of embodiments, as pull tab **150** is pulled, adhesive release liner **140** is removed from bottom side **132** (FIG. 1) of overlay **130**, and overlay **130** adheres to the screen of device **220** in an accurately aligned position. After overlay **130** is adhered to the screen of device **220**, the user can smooth overlay **130** on device **220** to remove any bubbles between overlay **130** and the screen of device **220**. Protective film **120** can be removed from overlay **130**. In some embodiments, protective film can be removed by lifting and/or pulling alignment tab **110**. In many embodiments, protective film **120** is removed after smoothing out any bubbles, so that protective film **120** can prevent damage to overlay **130** from forceful pushing or rubbing involved in smoothing the bubbles. For example, optical coated overlays can be damaged by objects, such as credit cards, being used to smooth out bubbles. Device **220** can be removed from frame **210** with overlay **130** installed.

(205) Turning ahead in the drawings, FIG. 3 illustrates a system **300** for using overlay applicator **100** to apply overlay **130** to a device. System **300** is merely exemplary and embodiments of the system are not limited to embodiments presented herein. The system can be employed in many different embodiments or examples not specifically depicted or described herein. System **300** can include overlay applicator **100**, a cradle **310**, and a device **320** (e.g., a smart phone). Cradle **310** can include a slot **311** in which device **320** can be placed with screen facing upwards or away from cradle **310**. In some embodiments, slot **311** is conformal with device **320**. In other embodiments, slot **311** can have dimensions large enough that several different electronic devices can fit within it. Slot **311** can have sides and a bottom, and cradle **310** can have a height greater than the height of device **320**. In many embodiments, cradle **310** can include an alignment base **312**, which can engage with alignment mechanism **115**. In some embodiments, alignment base **312** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **115**. Alignment base **312** and alignment mechanism **115** can be configured and positioned such that when alignment mechanism **115** is engaged with alignment base **312**, overlay **130** can be positioned directly above the screen of the device, and aligned such that overlay **130** will be adhered in an accurate position

on the screen when adhesive release liner **140** is removed.

(206) In some embodiments, overlay applicator **100** can be used to apply overlay **130** to device **320** in cradle **310**. Pull tab **150** can be folded such that second side **158** of pull tab **150** is pulled under adhesive release liner **140** from second side **148** to first side **149**, as shown in FIG. 3. Device **320** can be placed in cradle **310**, with the screen of device **320** facing up. Overlay applicator **100** can be placed on cradle **310** such that alignment mechanism **115** engages with alignment base **312**. In many embodiments, by placing overlay applicator **110** on cradle **210**, wiper **157** can come in contact with the screen of device **320**. While holding cradle **310**, a user can pull on pull tab **150**, e.g., by using pulling aid **156**, such that wiper **157** is pulled across the screen of device **320**, which can remove dust or other particles from the screen of device **320**. In a number of embodiments, as pull tab **150** is pulled, adhesive release liner **140** is removed from bottom side **132** (FIG. 1) of overlay **130**, and overlay **130** adheres to the screen of device **320** in an accurately aligned position. After overlay **130** is adhered to the screen of device **320**, the user can smooth overlay **130** on device **320** to remove any bubbles between overlay **130** and the screen of device **320**. Protective film **120** can be removed from overlay **130**. In some embodiments, protective film **120** can be removed by lifting and/or pulling alignment tab **110**. In many embodiments, protective film **120** is removed after smoothing out any bubbles, so that protective film **120** can prevent damage to overlay **130** from forceful pushing or rubbing involved in smoothing the bubbles, as explained above. Device **320** can be removed from cradle **310** with overlay **130** installed.

(207) In yet other embodiments, overlay applicator **100** can be used with a machine, such as the machine shown in FIGS. 8-14 and 16-20, and described below, which can semi-automatically align overlay applicator **100** with a device and engage with pull tab **150** and/or alignment tab **110** to install overlay **130** on the device.

(208) Advantageously, overlay applicator **100** can be used to install overlay **130** without dust or particles between overlay **130** and the screen of the device. Frame **210** (FIG. 2) or frame **310** (FIG. 3) can be used with overlay applicator **100** to accurately position overlay **130** relative to features of the device.

Advantageously, by wiping the screen of the device immediately before applying overlay **130**, overlay applicator **100** can clean any dust or particles on the screen. Beneficially, by removing adhesive release liner **140** immediately before applying overlay **130** minimizes exposure of the adhesive agent on bottom side **132**, which can prevent dust or other particles from coming in contact with the adhesive agent. As another advantage, by using pull tab **150** to remove adhesive release liner **140** and/or by holding overlay **130** in position by using alignment tab **110**, a user does not need to hold the sides of overlay **130**, which can prevent the user from inadvertent contact with the adhesive agent on bottom side **132** of overlay **130**.

(209) Turning ahead in the drawings, FIG. 4 illustrates an isometric view of an overlay applicator **400**. FIG. 5 illustrates a side view of overlay applicator **400**. Overlay applicator **400** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **400** can be similar to overlay applicator **100** (FIG. 1), and various components and/or constructions of overlay applicator **400** can be substantially identical or similar to various components of overlay applicator **100** (FIG. 1). Overlay applicator **400** can include a protective film **420**, an overlay **430**, an adhesive release liner **440**, and/or a pull tab **450**. Protective film **420** can be similar to protective film **120** (FIG. 1), overlay **430** can be similar to overlay **130** (FIG. 1), adhesive release liner **440** can be similar to adhesive release liner **140** (FIG. 1), and/or pull tab **450** can be similar to pull tab **150** (FIG. 1).

(210) In some embodiments, overlay applicator can include a speaker slot **423** and/or a button slot **424**. Speaker slot **423** and/or button slot **424** can extend through protective film **420**, overlay **430**, and adhesive release liner **440**. In a number of embodiments, overlay applicator **400** can include a device portion **470** and an alignment tab **410**. Alignment tab **410** can be similar to alignment tab **110** (FIG. 1). In some embodiments, device portion **470** and alignment tab **410** can be made of the layers used for protective film **420**, overlay **430**, and adhesive release liner **440**. Alignment tab **410** can include alignment mechanism **415**. Alignment mechanism **415** can be one or more holes, slots, or other suitable alignment aid features, which can facilitate aligning alignment tab **410**, protective film **420**, overlay **430**, and adhesive release liner **440** with various features of the device during application of overlay **430**.

(211) In many embodiments, construction of overlay applicator **400** can include adhering and/or

attaching layers of material for protective film **420**, overlay **430**, and adhesive release liner **440**. After attaching the layers, protective film **420**, overlay **430**, and adhesive release liner **440** can be cut to predetermined dimensions of device portion **470** and alignment tab **410**. In some embodiments, the cutting of device portion **470** and alignment tab **410** to size can include cutting speaker slot **423**, button slot **424**, and/or alignment mechanism **415**. As a result of the cut, device portion **470** and alignment tab **410** can be adjoined and integral on all three layers of protective film **420**, overlay **430**, and adhesive release liner **440**, and can extend from first side **429** to second side **428**. Construction of overlay applicator **400** also can include a die cut between alignment tab **410** and device portion **470** to create an interface slit **460**. The die cut can be a kiss cut through adhesive release liner **440** and overlay **430**, but not protective film **420**. In a number of embodiments, alignment tab **410** can include a top layer that is integral with the protective film, a middle layer attached to the top layer, and/or a bottom layer attached to the middle layer. In some embodiments, overlay applicator **400** can include a cut between the middle layer of alignment tab **410** and overlay **530**, and a cut between the bottom layer of alignment tab **410** and adhesive release liner **440**. As a result of the kiss cut, the dimensions of device portion **470** at overlay **430** and adhesive release liner **440** can be equal to the dimensions of the screen of the device. The process of cutting the layers (protective film **420**, overlay **430**, and adhesive release liner **440**) to size, cutting alignment mechanism **415**, and other feature slots (e.g., speaker slot **423** and button slot **424**), and kiss cutting to create interface slit **460** can advantageously provide a simpler method of constructing overlay applicator **400**, and/or can provide overlay applicator **400** with a very accurate alignment of alignment mechanism **415** with respect to overlay **430** and its features.

(212) In a number of embodiments, after kiss cutting alignment tab **410** and device portion **470** to size, pull tab **450** can be attached to adhesive release liner **440**. Pull tab **450** can be substantially similar or identical to pull tab **150** (FIG. 1), and various components or constructions of pull tab **450** can be the same as various components of pull tab **150** (FIG. 1). Pull tab **450** can facilitate removal of adhesive release liner **440**. Construction of overlay applicator **400** can include adhering pull tab **450** to adhesive release liner **440**. Pull tab can include a first side **459** and a second side **458**. Pull tab **450** can include an adhesive region **451** at or near first side **459**. Adhesive release liner **440** can include an adhesive region **442** at device portion **470** next to interface slit **460**. Adhesive region **451** can be adhered to adhesive region **442** to attach pull tab **450** to adhesive release liner **440**. Pull tab **450** can include a wiper **457**, which can remove dust from the screen of the device, and can be similar to wiper **157** (FIG. 1). Pull tab **450** can include a pulling aid **156** at or near second side **458**, which can assist a user and/or an applicator machine in engaging with and pulling pull tab **450**, as describe above in connection with pull tab **150** (FIG. 1). After pull tab **450** is attached to adhesive release liner **440**, a user and/or machine can pull on pull tab **450** to peel back and remove adhesive release liner **440** starting at interface slit **460** and peeling back to first side **429**.

(213) Turning ahead in the drawings, FIG. 6 illustrates an isometric view of an overlay applicator **600**. Overlay applicator **600** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **600** can be similar to overlay applicator **100** (FIG. 1) and/or overlay applicator **400** (FIGS. 4-5), and various components and/or constructions of overlay applicator **600** can be substantially identical or similar to various components of overlay applicator **100** (FIG. 1) and/or overlay applicator **400** (FIGS. 4-5). Overlay applicator **600** can include a protective film **620**, an overlay **630**, an adhesive release liner **640**, and/or a pull tab **650**. Protective film **620** can be similar to protective film **120** (FIG. 1) and/or protective film **420** (FIGS. 4-5), overlay **630** can be similar to overlay **130** (FIG. 1) and/or overlay **430** (FIGS. 4-5), adhesive release liner **640** can be similar to adhesive release liner **140** (FIG. 1) and/or adhesive release liner **440** (FIGS. 4-5), and/or pull tab **650** can be similar to pull tab **150** (FIG. 1) and/or pull tab **450** (FIGS. 4-5).

(214) In a number of embodiments, overlay applicator **600** can include a device portion **670** and an alignment tab **610**. Alignment tab **610** can be similar to alignment tab **110** (FIG. 1) and/or alignment tab **410** (FIG. 4). Device portion **670** can be similar to device portion **470** (FIGS. 4-5). In some embodiments, device portion **670** and alignment tab **610** can be made of the layers used for protective film **620**, overlay **630**, and adhesive release liner **640**. Alignment tab **610** can include an alignment mechanism **615**, which can be similar to alignment mechanism **115** (FIG. 1) and/or alignment mechanism

415 (FIGS. 4-5), and which can facilitate aligning alignment tab **610**, protective film **620**, overlay **630**, and adhesive release liner **640** with various features of the device during application of overlay **630**. Pull tab **650** can be integral with release liner **640** and can be a single layer of material, such as plastic, paper, or another suitable liner film. Pull tab **450** can facilitate removal of adhesive release liner **440**.

(215) In many embodiments, construction of overlay applicator **600** can include adhering and/or attaching layers of material for protective film **620**, overlay **630**, and adhesive release liner **640**. After attaching the layers, protective film **620** and overlay **630** can be kiss cut to predetermined dimensions of device portion **670** and alignment tab **610**, without cutting adhesive release liner **640** and/or pull tab **650**. Excess material from the layers for protective film **620** and overlay **630** can be removed. In some embodiments, the kiss cutting of device portion **670** and alignment tab **610** to size at the layers of protective film **620** and overlay **630** can include cutting a speaker slot **623**, a button slot **624**, and/or alignment mechanism **615**. The kiss cutting can also include cutting an interface slit **660** between alignment tab **610** and device portion **670** through the layers of protective film **620** and overlay **630**, but not adhesive release liner **640**. As a result of the kiss cut, the dimensions of device portion **670** at overlay **630** and protective film **620** can be equal to the dimensions of the screen of the device. In many embodiments, alignment tab **610** can include a top layer and a bottom layer attached to the top layer, and overlay applicator **600** can include a cut between the top layer of alignment tab **610** and protective film **620**, and a cut between the bottom layer of the alignment tab and overlay **630**.

(216) In a number of embodiments, after kiss cutting alignment tab **610** and device portion **670** to size at the layers of protective film **620** and overlay **630**, and cutting interface slit **660**, construction of overlay applicator **600** can include adhering a joining sticker **680** on the top the layer of protective film **620** to span interface slit **660** and join device portion **670** of protective film **620** with the top layer of alignment tab **610**. Joining sticker **680** can help maintain alignment between alignment tab **610** and device portion **670**. In many embodiments, joining sticker **680** does not stretch or distort, which can advantageously facilitate alignment of alignment mechanism **615** with overlay **630**, such that overlay **630** can be accurately positioned on the screen of the device.

(217) In a number of embodiments, after kiss cutting alignment tab **610** and device portion **670** to size, a wiper **657** can be attached to pull tab **650**. Wiper **657** can remove dust from the screen of the device, and can be similar to wiper **157** (FIG. 1) and/or wiper **457** (FIGS. 4-5). In certain embodiments, after joining sticker **680** has been attached between alignment tab **610** and device portion **670**, pull tab **650** can be folded back, such that a second side **658** is folded beneath release liner **640** to a first side **659**. Pull tab **650** and release liner **640** can be peeled back off of a portion of alignment tab **610**, such that alignment mechanism **615** is uncovered by release liner **640**, allowing alignment mechanism to engage with an alignment base, such as alignment base **212** (FIG. 2) or alignment base **312** (FIG. 3). The process of kiss cutting the layers at protective film **620** and overlay **630** can advantageously provide a simpler method of constructing overlay applicator **600**, and/or can provide overlay applicator **600** with a very accurate alignment of alignment mechanism **615** with respect to overlay **630** and its features.

(218) Turning ahead in the drawings, FIG. 7 illustrates an exploded isometric view of an overlay applicator **700**. Overlay applicator **700** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **700** can be similar to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), and/or overlay applicator **600** (FIG. 6), and various components and/or constructions of overlay applicator **700** can be substantially identical or similar to various components of overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), and/or overlay applicator **600** (FIG. 6). Overlay applicator **700** can include a protective film **720**, an overlay **730**, an adhesive release liner **740**, and/or a pull tab **750**. Protective film **720** can be similar to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), and/or protective film **620** (FIG. 6); overlay **730** can be similar to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), and/or overlay **630** (FIG. 6); adhesive release liner **740** can be similar to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), and/or adhesive release liner **640** (FIG. 6); and/or pull tab **750** can be similar to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), and/or pull tab **650** (FIG. 6).

(219) In many embodiments, protective film **720** can include an alignment frame **710** extending around each side of overlay **730**. Alignment frame **710** can be similar to alignment tab **110** (FIGS. 1-3),

alignment tab **410** (FIGS. 4-5), and/or alignment tab **610** (FIG. 6). In many embodiments, alignment frame **710** can be integral with protective film **720**. Alignment frame **710** can include an alignment mechanism **715**. In some embodiments, alignment mechanism **715** can include multiple holes surrounding overlay **730**. For example, as shown in FIG. 7, alignment mechanism **715** can include six holes spaced relatively evenly around alignment frame **710**, surrounding overlay **730**. In other embodiments, alignment mechanism **715** can include more or fewer holes than six. Alignment mechanism **715** can engage with an alignment base (e.g., similar to alignment base **212** (FIG. 2), and/or alignment base **312** (FIG. 3)). For example, overlay **700** can be used on a cradle, similar to cradle **310**, which has alignment base pins configured to engage with alignment mechanism **715**. Alignment frame **710** can provide alignment at multiple points around the overlay and the device, which can advantageously provide accurate alignment and help reduce distortion.

(220) In some embodiments, construction of overlay applicator **700** can include adhering and/or attaching layers of material for protective film **720** and overlay **730**. After attaching the layers of material for protective film **720** and overlay **730**, constructing overlay applicator **700** can include cutting the layers for protective film **720** and overlay **730** to the appropriate dimensions of protective film **720**. Such cutting can include cutting a button hole **724** and/or a speaker hole **723**. Construction of overlay applicator **700** also can include kiss cutting through the layer of material for overlay **730** to cut overlay **730** to its appropriate dimension, i.e., to the size of the screen of the device. In many embodiments, the kiss cut through the layer of material for overlay **730** does not extend into protective film **720**.

(221) In a number of embodiments, after kiss cutting overlay **730**, overlay **700** can be constructed by adhering adhesive release liner **740** and pull tab **750** to overlay **730**. Pull tab **750** can be integral with release liner **740** and can be a single layer of material, such as plastic, paper, or another suitable liner film. Pull tab **750** can facilitate removal of adhesive release liner **740**. Pull tab **750** can include a pulling aid **756**, which can be a tab that allows a user and/or machine to pull on pull tab **750** and peel back adhesive release liner **740** from overlay **730**. Pull tab **750** also can include a wiper **757**. Wiper **757** can remove dust from the screen of the device, and can be similar to wiper **157** (FIG. 1), wiper **457** (FIGS. 4-5), and/or wiper **657** (FIG. 6).

(222) Turning ahead in the drawings, FIG. 8 illustrates an isometric view of a machine **800** for using an overlay applicator to apply an overlay to a device. FIG. 9 illustrates a top view of machine **800**. FIG. 10 illustrates an isometric view of machine **800**, with a handle assembly not extended, and showing an outline of overlay applicator **100**. FIG. 11 illustrates an isometric view of machine **800** with the handle assembly partially extended. FIG. 12 illustrates a top view of machine **800** with the handle assembly partially extended. FIG. 13 illustrates an isometric view of machine **800** with the handle assembly fully extended. FIG. 14 illustrates a top view of machine **800** with the handle assembly fully extended. Machine **800** is merely exemplary and embodiments of the machine are not limited to embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. Machine **800** can be used with overlay applicator **100** to apply overlay **130** (not shown) to the device. Machine **800** also can be used with other overlay applicators (e.g., overlay applicator **400** (FIGS. 4-5), or overlay applicator **600** (FIG. 6)). In many embodiments, machine **800** can include a base **810**, a carriage **830**, and a handle assembly **850**. In some embodiments, base **810** can extend from a first side **819** to a second side **818**. Base **810** can include a gear **911** (FIGS. 9 and 12-14), a carriage rail **913** (FIGS. 9 and 11-14), and a handle rail **915** (FIGS. 9 and 12-14). Carriage rail **913** and handle rail **915** can extend partially or fully across base **810** in the direction from first side **819** to second side **818**.

(223) In certain embodiments, handle assembly **850** can include a handle sliding mechanism **851**, which can engage with handle rail **915** to attach handle assembly **850** to base **810** and to allow handle assembly **850** to slide back and forth along base **810** along the direction of handle rail **915**. In several embodiments, handle assembly **850** can include a handle extender **852** and a handle base **854**. In some embodiments, handle extender **852** can extend parallel to handle rail **915** and handle base **854** can be substantially perpendicular to handle extender **852**. Handle extender **852** can include handle gear teeth **853**, which can engage with gear **911** of base **810**. Handle base **854** can include a handle **855**, which a user can use to pull handle assembly **850** and extend handle assembly **850** with respect to base **810**. In several embodiments, handle base **854** can include a pulling mechanism **856**. In certain embodiments, pulling

mechanism **856** can be one or more knobs or pins, which can engage with pulling aid **156** of pull tab **150** on overlay applicator **100**, as shown in FIG. 9.

(224) In some embodiments, carriage **830** can include a carriage sliding mechanism (not shown), which can engage with carriage rail **913** to attach carriage **830** to base **810** and to allow carriage **830** to slide back and forth along base **810** along the direction of carriage rail **913**. In many embodiments, carriage **830** can include carriage gear teeth **1139** (FIGS. 11-14), which can engage with gear **911** of base **810**. In a number of embodiments, carriage **830** can include one or more carriage slots **831** and/or a cradle **832**. In some embodiments, cradle **832** can include one or more cradle tabs **833** that can engage in carriage slots **831** to hold cradle **832** in position. In some embodiments, carriage **830** can be used with multiple different sizes of cradles, which can be used for different devices. Carriage slots **831** and cradle tabs **833** can advantageously allow carriage **830** to removably hold cradle **832**, which can allow machine **800** to be used to apply overlays to multiple different types of devices. For example, carriage **830** can be configured to hold one or more additional cradles that are different than cradle **832**. The one or more additional cradles can be configured to securely hold one or more devices having one or more different dimensions than the device that fits in cradle **832**. In some embodiments, cradle **832** can be integral with carriage **830**. Cradle **832** can include a recess **834** in which a device can be placed with screen facing upwards or away from cradle **832**. Recess **834** can have sides and a bottom, and cradle **832** can have a height greater than the height of the device. In many embodiments, recess **834** is conformal with the device.

(225) In some embodiments, cradle **832** can include an alignment base **835**, which can engage with alignment mechanism **115**, as shown in FIG. 10. In the same or other embodiments, carriage **830** can include alignment base **835**. In some embodiments, alignment base **835** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **115**. Alignment base can be configured to engage with alignment mechanism **115**. Alignment base **835** and alignment mechanism **115** can be configured and positioned such that when alignment mechanism **115** is engaged with alignment base **835**, overlay **130** (FIG. 1) can be positioned directly above the screen of the device, and aligned such that overlay **130** (FIG. 1) will be adhered in an accurate position on the screen when adhesive release liner **140** (FIG. 1) is removed.

(226) In many embodiments, cradle **832** can include an overlay cover **836**. In some embodiments, overlay cover **836** can partially cover overlay applicator **100** and can hold overlay applicator **100** to cradle **832**. As shown in FIGS. 8-9, overlay cover **836** can cover alignment mechanism **115** and hold overlay applicator **100** to alignment base **835** when alignment mechanism **115** is engaged with alignment base **835**. In various embodiments, overlay cover **836** can be removably attached to carriage **830** and/or cradle **832**. In other embodiments, overlay cover **836** can be hingedly attached to carriage **830** and/or cradle **832**. In some embodiments, overlay cover **836** can snap onto cradle **832** and/or alignment base **835**. In other embodiments, overlay cover **836** can be attached to cradle **832** through a spring hinge, which can allow overlay cover **836** to be removably placed over overlay applicator **100** and to hold overlay applicator **100** close to cradle **832**, and/or to retain alignment mechanism **115** on alignment base **835**. In some embodiments, overlay cover **836** can have a trapezoidal shape or curved shape, so as to allow one or more rollers (described below) to roll over overlay cover **836**.

(227) In many embodiments, the device can be placed in cradle **832**, with the screen of the device facing up. Overlay applicator **100** can be placed on cradle **832**, as described above, and as shown in FIG. 9, such that alignment mechanism **115** engages with alignment base **835**. Overlay cover **836** can be placed over overlay applicator **100**.

(228) In many embodiments, when handle assembly **850** is not extended, as shown in FIGS. 8-10, carriage **830** can be located at a first side **819** of base **810**. As a user pulls handle assembly **855** and extends handle assembly **855** with respect to base **810**, as shown in FIGS. 11-14, handle gear teeth **853** move toward first side **819**, which can result in gear **911** rotating clockwise, and can further result in carriage gear teeth **1139** and carriage **830** moving toward second side **818**. As handle assembly **850** moves away from carriage **830**, pulling mechanism **856** can pull on pull tab **150**, which can pull wiper **157** across the screen of the device and remove dust or other particles from the screen of the device, and which can peel away adhesive release liner **140** (FIG. 1) to expose the adhesive agent on bottom side **132** (FIG. 1) to the screen of the device. In many embodiments, handle assembly **850** can be pulled in a

direction from second side **818** to first side **819**. For example, handle assembly **850** can be pulled from a first handle position, such as shown in FIGS. **8-10**, to a second handle position, such as shown in FIGS. **13-14**. In several embodiments, when handle assembly **850** is moved from the first handle position, such as shown in FIGS. **8-10**, to the second handle position, such as shown in FIGS. **13-14**, carriage **830** can move in a second direction from first side **819** to second side **818**, which is opposite from the first direction of movement by handle assembly **850**. For example, carriage **830** can move from a first carriage position, such as shown in FIGS. **8-10**, to a second carriage position, such as shown in FIGS. **13-14**. In a number of embodiments, machine **800** can be configured such that when alignment base **835** is engaged with alignment mechanism **115**, pulling mechanism **856** is engaged with pull tab **150**, cradle **832** is holding the device, and handle assembly **850** is pulled in the first direction from the first handle position to the second handle position, adhesive release liner **140** (FIG. **1**) of overlay applicator **100** can be removed from overlay **130** (FIG. **1**) starting at a leading edge of overlay **130** (FIG. **1**) (e.g., proximate to alignment mechanism **115**) and continuing to a trailing edge of overlay **130** (FIG. **1**) to expose the adhesive agent of overlay **130** (FIG. **1**) to the screen of the device.

(229) In a number of embodiments, base **810** can include a roller assembly **820**. In some embodiments, roller assembly **820** can include roller assembly supports **823**, a first roller assembly **821**, and/or a second roller assembly **822**. Roller assembly supports **823** can be attached to base **810** and extend upward or away from base **810** to provide support for first roller assembly **821** and/or second roller assembly **822**. Roller assembly supports **823** can be configured such that carriage **830** can slide back and forth between roller assembly supports **823** and under first roller assembly **821** and/or second roller assembly **822**. First roller assembly **821** can be attached to roller assembly supports **823** at axle **824**. First roller assembly **821** can include a first roller axle **925** (FIGS. **9** and **12**), which can have a first roller surface (not shown) with a width at least equal to the width of the device. In some embodiments, axle **824** can be spring-loaded to provide downward pressure for first roller axle **925** as it rolls over overlay applicator **100**.

(230) Second roller assembly **822** can be attached to first roller assembly **821** at axle **826**. Second roller assembly **822** can include a second roller axle **827**, which can have a second roller surface **828**. The width of second roller surface **828** can be less than the width of the device. In some embodiments, axle **826** can be spring-loaded to provide downward pressure for second roller axle **827** as it rolls over overlay applicator **100**. The width of second roller surface **828** can be less than the width of the first roller surface (not shown). In many embodiments, roller assembly **820** can include one or more rollers, such as first roller axle **925** and/or second roller axle **827**. In some embodiments, the width of the second roller surface **828** can be half the width of the device, and second roller surface **828** can be centered over the device as carriage **830** moves through roller assembly **820** from first side **819** to second side **818**. As carriage **830** moves from first side **819** to second side **818**, and as release liner **140** (FIG. **1**) is removed, second roller surface **828** can roll along the middle of the top surface of protective film **120** (FIG. **1**) to adhere overlay **130** (FIG. **1**) to the screen of the device. Second roller surface **828** can roll along over the top surface of protective film **120** before first roller surface (not shown) rolls over the top surface of protective film **120** (FIG. **1**) when carriage **830** moves from a first carriage position, such as shown in FIGS. **8-10**, to a second carriage position, such as shown in FIGS. **13-14**. In some embodiments, when carriage **830** moves from the first carriage position to the second carriage position, the first roller surface (not shown) and second roller surface **828** can roll over and press downward on overlay applicator **100** to adhere the exposed adhesive agent of overlay **130** (FIG. **1**) to the screen of the device. In various embodiments, when carriage **830** moves from the first carriage position to the second carriage position, one or more of the rollers, such as the first roller surface (not shown) and/or second roller surface **828** can roll fully over a length of the screen of the device. By rolling over protective film **120** (FIG. **1**) with second roller surface **828** before rolling over protective film **120** (FIG. **1**) (having the wider first roller surface (not shown)), roller assembly **820** can advantageously apply overlay **130** (FIG. **1**) to the screen of the device with fewer air bubbles, as air bubbles in the middle can be initially pushed outward by second roller surface **828**.

(231) In many embodiments, as a user pulls handle **855** and pull tab **150** is pulled, adhesive release liner **140** (FIG. **1**) is peeled back from bottom side **132** (FIG. **1**) of overlay **130** (FIG. **1**) at the same rate as cradle **832** rolls through roller assembly **820**, which can advantageously adhere overlay **130** (FIG. **1**) to the screen of the device very shortly after it is exposed from the peeling of adhesive release liner **140**

(FIG. 1), which can keep dust from adhering to overlay **130** (FIG. 1). In many embodiments, carriage **830** can move away from handle **855** at twice the rate that carriage **830** moves through roller assembly **820**, which can advantageously allow pull tab **150** and adhesive release liner **140** (FIG. 1) to be fully peeled from off of overlay **130** (FIG. 1).

(232) After overlay **130** (FIG. 1) is adhered to the screen of the device, the user can smooth overlay **130** (FIG. 1) on the device to remove bubbles, if there are any, between overlay **130** (FIG. 1) and the screen of the device. Protective film **120** (FIG. 1) can be removed from overlay **130** (FIG. 1). In some embodiments, protective film **120** (FIG. 1) can be removed by lifting and/or pulling alignment tab **110**. In many embodiments, protective film **120** (FIG. 1) is removed after smoothing out any bubbles, so that protective film **120** (FIG. 1) can prevent damage to overlay **130** (FIG. 1) from forceful pushing or rubbing involved in smoothing the bubbles, as explained above. The device can be removed from cradle **832** with overlay **130** (FIG. 1) installed.

(233) In some embodiments, overlay cover **836** can have a dimension such that it can fully cover protective cover **120** (FIG. 1). Overlay cover **836** can hold overlay applicator **100** close and/or securely to alignment base **835** and/or the device, such that, as handle **855** is extended, as pulling mechanism **856** pulls pulling aid **156**, and as wiper **157** is pulled across the device, wiper **157** is held close to the device to remove any dust or other particles from the device. In some embodiments, overlay cover **836** can be a slightly flexible material that is rigid enough to hold overlay applicator **100** close to the device, but is flexible enough to allow second roller surface **828** and/or first roller surface (not shown) to provide local downward pressure through overlay cover **836** to adhere overlay **130** (FIG. 1) to the device and facilitate removing any air bubbles. For example, overlay cover **836** can be a clear plastic material having a thickness of approximately 1 mm to approximately 2 mm. Clear plastic can advantageously allow the user to see through overlay cover **836** to ensure alignment and proper operation of machine **800**.

(234) In other embodiments, machine **800** does not include roller assembly **820**, overlay cover **836** can have a dimension such that it can fully cover protective cover **120** (FIG. 1). Overlay cover **836** can be rigid, and can be hinged to cradle **832** and/or carriage **830**. Overlay cover **836** can include a snap or other attachment mechanism on the side opposite the hinge, which can hold overlay cover **836** at a predetermined distance from the device screen and facilitate wiping of the device screen by wiper **157**. In another embodiment, the hinge connecting overlay cover **836** to cradle **832** and/or carriage **830** can be spring-loaded to hold overlay cover **836** close to overlay applicator **100**.

(235) Turning ahead in the drawings, FIG. 15 illustrates an exploded isometric view of an overlay applicator **1500**. Overlay applicator **1500** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **1500** can be similar to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), and/or overlay applicator **700** (FIG. 7), and various components and/or constructions of overlay applicator **1500** can be substantially identical or similar to various components of overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), and/or overlay applicator **700** (FIG. 7). Overlay applicator **1500** can include a protective film **1520**, an overlay **1530**, an adhesive release liner **1540**, and/or a pull tab **1550**. Protective film **1520** can be similar to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), and/or protective film **720** (FIG. 7); overlay **1530** can be similar to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), and/or overlay **730** (FIG. 7); adhesive release liner **1540** can be similar to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), and/or adhesive release liner **740** (FIG. 7); and/or pull tab **1550** can be similar to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), and/or pull tab **750** (FIG. 7). In some embodiments, protective film **1520**, overlay **1530**, and adhesive release liner **1540** can be attached to each other, and pull tab **1550** can be adhered to adhesive release liner **1540**, similarly as shown above in FIG. 1, described above.

(236) In many embodiments, protective film **1520** can include an alignment flaps **1510** extending at each corner of overlay **1530**. Alignment flaps **1510** can be similar to alignment tab **110** (FIGS. 1-3), alignment tab **410** (FIGS. 4-5), alignment tab **610** (FIG. 6), and/or alignment frame **710** (FIG. 7). In a number of embodiments, alignment flaps **1510** can be integral with protective film **1520**. Alignment flaps **1510** can

include an alignment mechanism **1515**. In some embodiments, alignment mechanism **1515** can include multiple holes surrounding overlay **1530**. For example, as shown in FIG. **15**, alignment mechanism **1515** can include a hole at each of alignment flaps **1510**, at each corner surrounding overlay **1530**. Alignment flaps **1510** can provide alignment at multiple points around overlay **1530**, which can advantageously provide accurate alignment and help reduce distortion. In some embodiments, pull tab **1550** can include pulling aid **1556**, which can be similar to pulling aid **156** (FIG. **1**) and/or pulling aid **456** (FIGS. **4-5**). (237) Turning ahead in the drawings, FIG. **16** illustrates an isometric view of a machine **1600** in a first configuration. FIG. **17** illustrates a top view of machine **1600** in a second configuration. FIG. **18** illustrates a side view of machine **1600** in a second configuration. FIG. **19** illustrates a side view of machine **1600** in a third configuration. Machine **1600** is merely exemplary and embodiments of the machine are not limited to embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiment, machine **1600** can include a base **1610**, a cradle **1620**, a first frame **1630**, and/or a second frame **1640**. In some embodiments first frame **1630** can be an alignment piece hingedly attached to base **1610**. In a number of embodiments, second frame **1640** can be a pulling piece hingedly attached to base **1610**. Cradle **1620** can include a slot **1621** in which a device **1650** (e.g., a smart phone) can be placed with the screen facing upwards or away from cradle **1620**. Cradle **1620** can also include recesses **1622** surrounding slot **1621** to allow a user to remove the device from cradle **1620**. In some embodiments, slot **1621** is conformal with device **1650**. In some embodiments, cradle **1620** can be integral with base **1610**. In other embodiments, cradle **1620** can be removable from base **1610**. For example, base **1610** can be configured to hold one or more additional cradles that are different than cradle **1620**. The one or more additional cradles can be configured to securely hold one or more devices having one or more different dimensions than the device that fits in cradle **1620**.

(238) In several embodiments, first frame **1630** can be attached to base **1610** at first hinge **1631**, and can rotate around first hinge **1631**. For example, first frame **1630** can be rotated relative to base **1610** in a first direction from a first position, such as shown in FIGS. **16-18**, to a second position proximate to cradle **1620**, such as shown in FIG. **19**. In many embodiments, second frame **1640** can be attached to base **1610** at second hinge **1641**, and can rotate around second hinge **1641**. For example, second frame **1640** can be rotated relative to base **1610** in the first direction from a first position proximate to cradle **1620**, such as shown in FIGS. **17-18**, to a second position, such as shown in FIG. **16**. First frame **1630** can include an alignment base **1632**, which can engage with alignment mechanism **1515** to secure overlay applicator **1500** to first frame **1630**. In certain embodiments, when machine **1600** is in a first configuration with cradle **1620** uncovered, as shown in FIG. **16**, device **1650** can be placed in slot **1621**, and overlay applicator **1500** can be attached to first frame **1630**, with overlay applicator **1500** oriented with protective film **1520** facing first frame **1630** and adhesive release liner **1540** facing upward or away from first frame **1630**. In some embodiments, first frame **1630** can include an aperture or window **1633**, and/or second frame **1640** can include an aperture or window **1643**. Aperture or window **1633** and/or aperture or window **1643** can allow a user to reach through and/or see through first frame **1630** and second frame **1640**.

(239) When machine **1600** is in a second position with second frame **1640** covering cradle **1620**, as shown in FIGS. **17-18**, pull tab **1550** can be attached to second frame **1640** at the same time as overlay applicator **1500** is attached to first frame **1630**. Second frame **1640** can include a pulling mechanism **1741**, which can engage with pulling aid **1556** of pull tab **1550**. Pulling mechanism **1741** can be a protrusion or other suitable attachment mechanism. In a number of embodiments, machine **1600** can be configured such that when alignment base **1632** is engaged with alignment mechanism (such as alignment flaps **1510**), pulling mechanism **1741** is engaged with pull tab **1550**, cradle **1620** is holding the device, and second frame **1640** is rotated relative to base **1610** in the first direction from the first position proximate, such as shown in FIGS. **17-18**, to the second position, such as shown in FIG. **16**, first frame **1630** can be rotated relative to base **1610** in the first direction from the first position, such as shown in FIGS. **16-18**, to the second position, such as shown in FIG. **19**, and adhesive release liner **1540** can be removed from overlay **1530** (FIG. **15**) to expose the adhesive agent of overlay **1530** (FIG. **15**) to the screen of the device.

(240) To illustrate, for example, after pull tab **1550** is attached to second frame **1640**, a user can lift

second frame **1640**, which can pull on pull tab **1550** and begin to peel adhesive release liner **1540** from overlay **1530** (FIG. 15). Raising second frame **1640** from base **1610** and pulling on pull tab **1550**, can result in first frame **1630** being raised from base **1610**, around first hinge **1631**, as shown in FIG. 19. Continuing to rotate second frame **1640** around second hinge **1641** can result in adhesive release liner **1540** being peeling away from overlay **1530** (FIG. 15), exposing the adhesive agent on the bottom of overlay **1530** (FIG. 15). In many embodiments, second frame **1640** can be raised and rotated sufficiently around second hinge **1641** while pulling on pull tab **1550** and removing adhesive release liner **1540** to allow first frame **1630** to be further rotated around first hinge **1631** and lowered toward device **1650**. When second frame **1640** has rotated fully around second hinge **1641**, adhesive release liner **1540** can be completely removed from overlay **1530** (FIG. 15), and first frame can be lowered completely onto device **1650**. After overlay **1530** (FIG. 15) is adhered to the screen of device **1650**, the user can reach through aperture **1633** to smooth overlay **1530** (FIG. 15) on device **1650** to remove any bubbles between overlay **1530** (FIG. 15) and the screen of device **1650**. First frame **1630** can be lifted and removed from protective film **1520**. Protective film **1520** can be removed from overlay **1530** (FIG. 15). In some embodiments, protective film **1520** can be removed by lifting and/or pulling alignment flaps **1510**. In many embodiments, protective film **1520** is removed after smoothing out any bubbles, so that protective film **1520** can prevent damage to overlay **1530** (FIG. 15) from forceful pushing or rubbing involved in smoothing the bubbles, as explained above. Device **1650** can be removed from cradle **1620** with overlay **1530** (FIG. 15) installed. In many embodiments, machine **1600** can be lightweight and easily portable, for example, such that it can be carried around by a sales associate.

(241) Turning ahead in the drawings, FIG. 20 illustrates an isometric view of a machine **2000** for using an overlay applicator to apply an overlay to a device, showing the overlay cover extended. FIG. 21 illustrates an isometric view of machine **2000** with the overlay cover engaged and the roller pressing against the tongue of the overlay cover. FIG. 22 illustrates an isometric view of machine **2000** with the overlay cover engaged and the roller disengaged from the overlay cover. Machine **2000** is merely exemplary and embodiments of the machine are not limited to embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. Machine **2000** can be used with an overlay applicator, such as overlay applicator **100** (FIG. 1), to apply an overlay, such as overlay **130** (FIG. 1), to the device. Machine **2000** also can be used with other overlay applicators (e.g., overlay applicator **400** (FIGS. 4-5), and/or overlay applicator **600** (FIG. 6). Machine **2000** can be similar to machine **800** (FIGS. 8-14) and various components or constructions of machine **2000** can be substantially identical or similar to various components of machine **800** (FIGS. 8-14), but can include variations in the roller assembly and the overlay cover. The operation of machine **2000** can be similar to the operation of machine **800** (FIGS. 8-14).

(242) In many embodiments, machine **2000** can include a base **2010**, a carriage **2030**, and a handle assembly **2050**, and can operate in a substantially similar manner to the operation of base **810**, carriage **830** and handle assembly **850**, respectively, of machine **800** (FIGS. 8-14). Base **2010** can extend from a first side **2019** to a second side **2018**. Carriage **2030** can be configured to hold a cradle **2032**, which can be substantially similar to cradle **832** (FIGS. 8-14). Carriage **2030** can be used with various different cradles, which can be configured for different devices. Cradle **2032** can include an alignment base **2035**, which can engage with alignment mechanism **115** (FIG. 1).

(243) Carriage **2030** can include an overlay cover **2036**, which can cover overlay applicator **100** (FIG. 1) and can hold overlay applicator **100** (FIG. 1) to cradle **2032**. In many embodiments, the device can be placed in cradle **2032**, with the screen of the device facing up, as shown in FIGS. 20-22. Overlay applicator **100** (FIG. 1) can be placed on cradle **2032**, such that alignment mechanism **115** (FIG. 1) engages with alignment base **2035**. Overlay cover **2036** can be placed over overlay applicator **100**. Overlay cover **2036** can be attached to carriage **2030** at an end of carriage **2030** closer to first end **2019**, and/or can be attached with a hinge **2037**. In other embodiments, overlay cover **2036** can be attached instead to cradle **2032**. In many embodiments, hinge **2037** can be a spring-loaded hinge, which can bias overlay cover to cover overlay applicator **100** (FIG. 1). In other embodiments, overlay cover **2036** can include a snap or other attachment mechanism on the side opposite hinge **2037**. Overlay cover **2036** can hold overlay applicator **100** (FIG. 1) within a predetermined distance from the device screen and can provide sufficient pressure to wiper **157** (FIG. 1) as it is pulled in order to clean the screen of the device.

(244) Overlay cover **2036** can include a frame **2071** extending around a cover sheet **2072**. Frame **2071** and/or cover sheet **2072** can be substantially rectangular. In many embodiments, cover sheet **2072** can be a piece of flexible or semi-flexible plastic. Cover sheet **2072** can be configured to press wiper **157** (FIG. 1) downward toward the screen of the device as wiper **157** (FIG. 1) moves across the screen of the device. In a number of embodiments, cover sheet **2072** can be configured to secure overlay **130** (FIG. 1) proximate to the screen of the device. Cover sheet **2072** can be approximately 1.5 mm. In a number of embodiments, cover sheet **2072** can include a tongue **2073**, which can be formed by two slits **2074** through the thickness of cover sheet **2072**. In some embodiments, cover sheet **2072** can be attached to frame **2071** around the entire perimeter of frame **2071** except at a tongue interface **2075** in which tongue **2073** contacts frame **2071**. Tongue **2073** can be centered between the sides of cover sheet **2072** and/or can extend through cover sheet **2072** from the side of opposite hinge **2037** partially toward of hinge **2037**. Tongue **2073** can be configured to cover overlay applicator **100** (FIG. 1) proximate to the leading edge of overlay **130** (FIG. 3), near alignment mechanism **115** (FIG. 1). Tongue **2073** can include a central pad **2076**. Central pad **2076** can be made of foam or an elastomeric material.

(245) Base **2010** can include a roller assembly **2020**. Roller assembly **2020** can be similar to roller assembly **820** (FIGS. 8-14). Roller assembly **2020** can include roller assembly supports **2023** and/or a roller cross support **2021**. Roller assembly supports **2023** can be attached to base **2010** and extend upward or away from base **2010** to provide support for roller cross support **2021**. Roller assembly supports **2023** can be configured such that carriage **2030** can slide back and forth between roller assembly supports **2023** and under roller cross support **2021**. Roller cross support **2021** can be attached to roller assembly supports **2023** at axle **2024**. Roller cross support **2021** can include a roller **2025**, which can have a central roller surface **2026** with a width less than or equal to the width of tongue **2073** and can roll across the center between the two sides of overlay cover **2036**. Roller **2025** can include one or more side rollers surfaces **2027**, which can roll along the sides of frame **2071**. In some embodiments, axle **2024** can be spring-loaded to provide downward pressure for roller **2025** as central roller surface **2026** rolls over overlay cover **2036**.

(246) In some embodiments, as handle assembly **2050** is extended and carriage **2030** moves from first side **2019** to second side **2018**, central roller surface **2026** can roll along the central top side of overlay cover **2036**. In many embodiments, as handle assembly **2050** is extended and pull tab **150** is pulled, wiper **157** (FIG. 1) is pulled away from the leading edge of overlay cover **2036** opposite hinge **2037**, such that wiper **157** (FIG. 1) can be beyond the region near tongue interface **2075** when central roller surface **2026** first contacts tongue **2073** at tongue interface **2075**. In many embodiments, as central roller surface **2026** rolls over tongue **2073**, as shown in FIG. 21, it can provide sufficient pressure to depress tongue **2073** to adhere the exposed adhesive of overlay **130** (FIG. 1) to the surface of the device and push out air bubbles. Central pad **2076** can distribute the pressure to and provide a controlled pressure at the leading edge of overlay **130** (FIG. 1) near tongue interface **2075**. By providing a solid adherence between overlay **130** (FIG. 1) and the screen of the device in the middle, the adhesive of overlay **130** (FIG. 1) can wet out to adhere toward the edges of overlay **130** (FIG. 1).

(247) In many embodiments, one or both sides of frame **2071** can include a cam **2077**. In some embodiments, cam **2077** can be configured to raise roller **2025**, such as by side rollers **2027** rolling over the ramp and raised portions of cam **2077**, so as to prevent central roller surface **2026** from pressing down on overlay cover **2036**. In many embodiments, after central roller surface **2026** rolls over the length of tongue **2073**, cam **2077** can raise roller **2025**, which can disengage roller surface **2026** from overlay cover **2036** and allow machine **2000** to more easily pull away adhesive release liner **140** (FIG. 1) under the portion of overlay cover **2036** near hinge **2037**, as shown in FIG. 22. Cam **2077** can be located proximate to the trailing edge of overlay **130** opposite from alignment mechanism **115** (FIG. 1).

(248) Turning ahead in the drawings, FIG. 23 illustrates a flow chart for an embodiment of a method **2300** of providing an overlay applicator. Method **2300** is merely exemplary and is not limited to the embodiments presented herein. Method **2300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **2300** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or

the activities in method **2300** can be combined or skipped. In some embodiments, the overlay applicator can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), and/or overlay applicator **1500** (FIG. 15).

(249) Referring to FIG. 23, method **2300** can include a block **2301** of providing an overlay. In many embodiments, the overlay can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15). In a number of embodiments, the overlay can have a top side and a bottom side. The top side of the overlay can be similar or identical to top side **131** (FIG. 1) of overlay **130** (FIG. 1). The bottom side of the overlay can be similar or identical to bottom side **132** (FIG. 1) of overlay **130** (FIG. 1). In various embodiments, the bottom side can include an adhesive agent configured to adhere to a screen of an electronic device.

(250) In some embodiments, method **2300** can include a block **2302** of providing an adhesive release liner. The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7); and/or adhesive release liner **1540** (FIG. 15). In a number of embodiments, the adhesive release liner can have a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. In some embodiments, the adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants.

(251) In a number of embodiments, method **2300** can include a block **2303** of providing a protective film. In some embodiments, the protective film can be similar or identical to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), protective film **720** (FIG. 7), and/or protective film **1520** (FIG. 15). In many embodiments, the protective film can be removably attached to the top side of the overlay.

(252) In many embodiments, method **2300** can include a block **2304** of providing an alignment tab. In some embodiments, the alignment tab can be similar or identical to alignment tab **110** (FIG. 1), alignment tab **410** (FIGS. 4-5), alignment tab **610** (FIG. 6), alignment frame **710** (FIG. 7), and/or alignment flaps **1510** (FIG. 15). In many embodiments, the alignment tab can include an alignment mechanism. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. 1), alignment mechanism **415** (FIG. 4), alignment mechanism **615** (FIG. 6), alignment mechanism **715** (FIG. 7), and/or alignment mechanism **1515** (FIG. 15). In various embodiments, the alignment mechanism of the alignment tab can be configured to engage with an alignment base, such as alignment base **212** (FIG. 2), alignment base **312** (FIG. 3), alignment base **835** (FIGS. 8-9, 13-14), alignment base **1632** (FIGS. 16-19), and/or alignment base **2035** (FIG. 20), to align the overlay with the screen of the electronic device.

(253) In a number of embodiments, the alignment tab can include a top layer that is integral with the protective film, a middle layer attached to the top layer; and a bottom layer attached to the middle layer. In some embodiments, method **2300** of providing the overlay applicator can include providing a cut between the middle layer of the alignment tab and the overlay, and between the bottom layer of the alignment tab and the adhesive release liner.

(254) In various embodiments, the alignment tab can include a top layer and a bottom layer attached to the top layer. In some embodiments, method **2300** of providing the overlay applicator can include providing a cut between the top layer of the alignment tab and the protective film, and between the bottom layer of the alignment tab and the overlay. In certain embodiments, method **2300** of providing the overlay applicator can include providing a sticker attached to and spanning the cut between the protective film and the top layer of the alignment tab.

(255) In some embodiments, the alignment tab can include an alignment frame extending around each side of the overlay. In several embodiments, the alignment frame can be integral with the protective film. In a number of embodiments, the alignment frame can include the alignment mechanism. In various embodiments, the alignment mechanism can include at least six holes.

(256) In a number of embodiments, the alignment tab can include alignment flaps extending at each corner of the overlay. In certain embodiments, the alignment flaps can be integral with the protective film. In various embodiments, the alignment flaps can include alignment mechanism.

(257) In several embodiments, method **2300** can include a block **2305** of providing a pull tab. In some embodiments, the pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), pull tab **750** (FIG. 7), and/or pull tab **1550** (FIG. 15). In many embodiments, the

pull tab can include a wiper. The wiper can be similar or identical to wiper **157** (FIG. **1**), wiper **457** (FIG. **4**), wiper **657** (FIG. **6**), and/or wiper **757** (FIG. **7**). In certain embodiments, the pull tab can be integral with the adhesive release liner. In many embodiments, the pull tab, including the wiper, and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner and be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. In several embodiments, the pull tab, including the wiper, and the adhesive release liner can be configured such that when the pull tab is pulled, the wiper can be configured to wipe across and clean the screen of the electronic device. In several embodiments the pull tab, including the wiper, and the adhesive release liner can be configured such that when the pull tab is pulled, the wiper can be configured to wipe across a length of the screen of the electronic device that is greater than a width of the screen of the electronic device.

(258) Proceeding to the next drawing, FIG. **24** illustrates a flow chart for an embodiment of a method **2400** of providing a machine. Method **2400** is merely exemplary and is not limited to the embodiments presented herein. Method **2400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **2400** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **2400** can be combined or skipped. In some embodiments, the machine can be similar or identical to machine **800** (FIGS. **8-14**) and/or machine **2000** (FIGS. **20-22**).

(259) Referring to FIG. **24**, method **2400** can include a block **2401** of providing a base. In many embodiments, the base can be similar or identical to base **810** (FIGS. **8-14**) and/or base **2010** (FIGS. **20-22**). In various embodiments, the base can include a roller assembly. The roller assembly can be similar or identical to roller assembly **820** (FIGS. **8-14**) and or roller assembly **2020** (FIGS. **20-22**). The roller assembly can include one or more rollers, such as the first roller surface or second roller surface **828** (FIGS. **8, 11, 13**), central roller surface **2026** (FIGS. **20-22**), and/or side roller surfaces **2027** (FIGS. **20-22**).

(260) In some embodiments, method **2400** can include a block **2402** of providing a carriage. The carriage can be similar or identical to carriage **830** (FIGS. **8-14**) and/or carriage **2030** (FIGS. **20-22**). In a number of embodiments, the carriage can include a first cradle. The first cradle can be similar or identical to cradle **832** (FIGS. **8-9, 12-14**) and/or cradle **2032** (FIG. **20**). The first cradle can be configured to securely hold a first electronic device. In many embodiments, the carriage can include an alignment base. The alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), and/or alignment base **2035** (FIG. **20**). The alignment base can be configured to engage with an alignment mechanism, such as alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), and/or alignment mechanism **1515** (FIG. **15**), of an overlay applicator, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), and/or overlay applicator **1500** (FIG. **15**).

(261) In a number of embodiments, method **2400** can include a block **2403** of providing a handle assembly. The handle assembly can be similar or identical to handle assembly **850** (FIGS. **8-14**) and/or handle assembly **2050** (FIGS. **20-22**). In some embodiments, the handle assembly can include a handle. The handle can be similar or identical to handle **855** (FIGS. **8-9, 11-14**). In several embodiments, the handle assembly can include a pulling mechanism. The pulling mechanism can be similar or identical to pulling mechanism **856** (FIGS. **8-9, 11-14**) and/or pulling mechanism **1741** (FIGS. **17, 19**). In a number of embodiments, the pulling mechanism can be configured to engage with a pull tab, such as pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIG. **7**), and/or pull tab **1550** (FIG. **15**), of the overlay applicator.

(262) In many embodiments, the machine can be configured such that the handle assembly can be pulled in a first direction relative to the base from a first handle position to a second handle position. In many embodiments, the machine can be configured such that when the handle assembly is moved from the first handle position to the second handle position, the carriage can move in a second direction relative to the base from a first carriage position to a second carriage position. The second direction can be opposite the

first direction. In several embodiments, the machine can be configured such that when the alignment base is engaged with the alignment mechanism of the overlay applicator, the pulling mechanism is engaged with the pull tab of the overlay applicator, the first cradle is holding the first electronic device, and the handle assembly is pulled in the first direction relative to the base from the first handle position to the second handle position, an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator starting at a leading edge of the overlay and continuing to a trailing edge of the overlay to expose an adhesive agent of the overlay of the overlay applicator to a screen of the first electronic device.

(263) In some embodiments, the machine can be configured such that when the carriage moves from the first carriage position to the second carriage position, the one or more rollers can be configured to roll over and press downward on the overlay applicator to adhere the exposed adhesive agent of the overlay to the screen of the first electronic device. In a number of embodiments, method **2400** can include providing an overlay cover. The overlay cover can be similar or identical to overlay cover **836** (FIGS. **8-9, 12-14**) and/or overlay cover **2036** (FIGS. **20-22**). In various embodiments, the overlay cover can be configured to secure the overlay applicator to the alignment base when the alignment mechanism of the overlay applicator is engaged with the alignment base.

(264) Proceeding to the next drawing, FIG. **25** illustrates a flow chart for an embodiment of a method **2500** of providing a machine. Method **2500** is merely exemplary and is not limited to the embodiments presented herein. Method **2500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **2500** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **2500** can be combined or skipped. In some embodiments, the machine can be similar or identical to machine **1600** (FIGS. **16-19**).

(265) Referring to FIG. **25**, method **2500** can include a block **2501** of providing a base. In many embodiments, the base can be similar or identical to base **1610** (FIGS. **16-19**).

(266) In some embodiments, method **2500** can include a block **2502** of providing a cradle. The cradle can be similar or identical to cradle **1620** (FIG. **16**). The cradle can be configured to securely hold a first electronic device.

(267) In a number of embodiments, method **2500** can include a block **2503** of providing an alignment piece. The alignment piece can be similar or identical to first frame **1630** (FIGS. **16-19**). In many embodiments, the alignment piece can be hingedly attached to the base. In several embodiments, the alignment piece can include an alignment base. The alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), and/or alignment base **2035** (FIG. **20**). The alignment base can be configured to engage with an alignment mechanism, such as alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), and/or alignment mechanism **1515** (FIG. **15**), of an overlay applicator, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), and/or overlay applicator **1500** (FIG. **15**). In a number of embodiments, method **2500** can include a block **2504** of providing a pulling piece. The pulling piece can be similar or identical to second frame **1640** (FIGS. **16-19**). In many embodiments, the pulling piece can be hingedly attached to the base. In several embodiments, the pulling piece can include a pulling mechanism. The pulling mechanism can be similar or identical to pulling mechanism **856** (FIGS. **8-9, 11-14**) and/or pulling mechanism **1741** (FIGS. **17, 19**). In a number of embodiments, the pulling mechanism can be configured to engage with a pull tab, such as pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIG. **7**), and/or pull tab **1550** (FIG. **15**), of the overlay applicator.

(268) In some embodiments, the machine can be configured such that the pulling piece can be rotated relative to the base in a first direction from a first pulling piece position to a second pulling piece position. The first pulling piece position can be proximate to the cradle. In many embodiments, the machine can be configured such that the alignment piece can be rotated relative to the base in the first direction from a first alignment piece position to a second alignment piece position. The second

alignment piece position can be proximate to the cradle. In many embodiments, the machine can be configured such that when the alignment base is engaged with the alignment mechanism of the overlay applicator, the pulling mechanism is engaged with the pull tab of the overlay applicator, the cradle is holding the first electronic device, and the pulling piece is rotated relative to the base in the first direction from the first pulling piece position to the second pulling piece position, the alignment piece can be rotated relative to the base in the first direction from the first alignment piece position to the second alignment piece position to pull the pull tab of the overlay applicator, and an adhesive release liner of the overlay applicator can be removed from an overlay of the overlay applicator to expose an adhesive agent of an overlay to a screen of the first electronic device.

(269) Proceeding to the next drawing, FIG. **26** illustrates a flow chart for an embodiment of a method **2600** of using an overlay applicator to apply an overlay to a screen of an electronic device. Method **2600** is merely exemplary and is not limited to the embodiments presented herein. Method **2600** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2600** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **2600** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **2600** can be combined or skipped. In some embodiments, the overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), and/or overlay applicator **1500** (FIG. **15**). In many embodiments, the overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**).

(270) Referring to FIG. **26**, method **2600** can include a block **2601** of attaching the overlay applicator to a first apparatus. In some embodiments, the first apparatus can be a frame. The frame can be similar or identical to frame **210** (FIG. **2**). In many embodiments, the first apparatus can be a cradle. The cradle can be similar or identical to cradle **310** (FIG. **3**), cradle **832** (FIGS. **8-9**, **12-14**) and/or cradle **2032** (FIG. **20**). In several embodiments, the first apparatus can be a machine. The machine can be similar or identical to machine **800** (FIGS. **8-14**), machine **1600** (FIGS. **16-19**), and/or machine **2000** (FIGS. **20-22**). In many embodiments, the first apparatus can securely hold the electronic device.

(271) In many embodiments, the overlay applicator can include an overlay. In many embodiments, the overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**). In a number of embodiments, the overlay can have a top side and a bottom side. The top side of the overlay can be similar or identical to top side **131** (FIG. **1**) of overlay **130** (FIG. **1**). The bottom side of the overlay can be similar or identical to bottom side **132** (FIG. **1**) of overlay **130** (FIG. **1**). In various embodiments, the bottom side can include an adhesive agent configured to adhere to the screen of the electronic device.

(272) In a number of embodiments, the overlay applicator can include an adhesive release liner. The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**); and/or adhesive release liner **1540** (FIG. **15**). In a number of embodiments, the adhesive release liner can have a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. In some embodiments, the adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants.

(273) In several embodiments, the overlay applicator can include a protective film. In some embodiments, the protective film can be similar or identical to protective film **120** (FIG. **1**), protective film **420** (FIGS. **4-5**), protective film **620** (FIG. **6**), protective film **720** (FIG. **7**), and/or protective film **1520** (FIG. **15**). In many embodiments, the protective film can be removably attached to the top side of the overlay.

(274) In various embodiments, the overlay applicator can include an alignment tab. In some embodiments, the alignment tab can be similar or identical to alignment tab **110** (FIG. **1**), alignment tab **410** (FIGS. **4-5**), alignment tab **610** (FIG. **6**), alignment frame **710** (FIG. **7**), and/or alignment flaps **1510** (FIG. **15**). In many embodiments, the alignment tab can include an alignment mechanism. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415**

(FIG. 4), alignment mechanism **615** (FIG. 6), alignment mechanism **715** (FIG. 7), and/or alignment mechanism **1515** (FIG. 15). In various embodiments, the alignment mechanism of the alignment tab can be configured to engage with an alignment base, such as alignment base **212** (FIG. 2), alignment base **312** (FIG. 3), alignment base **835** (FIGS. 8-9, 13-14), alignment base **1632** (FIGS. 16-19), and/or alignment base **2035** (FIG. 20), of the first apparatus.

(275) In several embodiments, the overlay applicator can include a pull tab. In some embodiments, the pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), pull tab **750** (FIG. 7), and/or pull tab **1550** (FIG. 15). In many embodiments, the pull tab can include a wiper. The wiper can be similar or identical to wiper **157** (FIG. 1), wiper **457** (FIG. 4), wiper **657** (FIG. 6), and/or wiper **757** (FIG. 7).

(276) In some embodiments, method **2600** can include a block **2602** of pulling the pull tab across the bottom side of the adhesive release liner to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent to the screen of the electronic device.

(277) Turning ahead in the drawings, FIGS. 27-30 illustrate a perspective view of components of an overlay applicator **3000**, which is shown in its entirety in FIG. 30, and illustrate a method of constructing overlay applicator **3000**. Overlay applicator **3000** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **3000** can be similar to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), and/or overlay applicator **1500** (FIG. 15), and various components and/or constructions of overlay applicator **3000** can be substantially identical or similar to various components of overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), and/or overlay applicator **1500** (FIG. 15).

(278) As shown in FIG. 27, overlay applicator **3000** (FIG. 30) can be constructed to include an adhesive release liner **2740** and a pull tab **2750**. In some embodiments, pull tab **2750** can be integral with release liner **2740** and can be a single layer of material, such as plastic, paper, or another suitable liner film. Pull tab **2750** can facilitate removal of adhesive release liner **2740**. Pull tab **2750** can be at a second side **2758** of the material and adhesive release liner **2740** can be at a first side **2759**. Pull tab **2750** can include a pulling aid **2756**, which can be similar to pulling aid **156** (FIG. 1), pulling aid **456** (FIGS. 4-5), and/or pulling aid **1556** (FIG. 15). Release liner **2740** also can include a speaker slot **2723**, a button slot **2724**, and/or one or more other slots for a front side camera, a camera flash, a status indicator, etc. Pull tab **2750** and adhesive release liner **2740** can be cut as one piece of material, and pulling aid **2756**, speaker slot **2723**, button slot **2724**, etc., can be cut out from pull tab **2750** and adhesive release liner **2740**.

(279) In a number of embodiments, after cutting pull tab **2750** and adhesive release liner **2740**, such as shown in FIG. 27, a wiper **2857** can be added to pull tab **2750**, as shown in FIG. 28. Wiper **2857** can remove dust from the screen of the device, and can be similar to wiper **157** (FIG. 1), wiper **457** (FIGS. 4-5), wiper **657** (FIG. 6), and/or wiper **757** (FIG. 7).

(280) In various embodiments, after adhering or otherwise attaching wiper **2857** to pull tab **2750**, construction of overlay applicator **3000** (FIG. 30) can include adhering and/or attaching layers of material for overlay **2930** and protective film **2920**, as shown in FIG. 29. Protective film **2920** can be similar to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), protective film **720** (FIG. 7) and/or protective film **1520** (FIG. 15). Overlay **2930** can be similar to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15). In a number of embodiments, overlay applicator **3000** (FIG. 30) can include an alignment tab **2910**, a device portion **2970** and/or a tail portion **2990**. Alignment tab **2910** can be similar to alignment tab **110** (FIG. 1), alignment tab **410** (FIG. 4), and/or alignment tab **610** (FIG. 6). Device portion **2970** can be similar to device portion **470** (FIGS. 4-5) and/or device portion **670** (FIG. 6). In some embodiments, device portion **2970** and alignment tab **2910** can be made of the layers used for protective film **2920**, overlay **2930**, and adhesive release liner **2740**. Alignment tab **2910** can include an alignment mechanism **2915**, which can be similar to alignment mechanism **115** (FIG. 1), alignment mechanism **415** (FIGS. 4-5), and/or alignment mechanism **615** (FIG. 6), and which can facilitate aligning alignment tab **2910**, protective film **2920**, overlay **2930**, and adhesive release liner **2740** with various

features of the device during application of overlay **2930**.

(281) After attaching the layers, protective film **2920** and overlay **2930** can be kiss cut to predetermined dimensions of alignment tab **2910**, device portion **2970**, and/or tail portion **2990**, without cutting adhesive release liner **2740** and/or pull tab **2750**. In some embodiments, excess material from the layers for protective film **2920** and overlay **2930** can be removed. In various embodiments, the kiss cutting of device portion **2970**, alignment tab **2910**, and tail portion **2990** to size at the layers of protective film **2920** and overlay **2930** can include cutting speaker slot **2723**, button slot **2724**, and other slots, as described above, and/or cutting alignment mechanism **2915**. The kiss cutting can also include cutting an interface slit **2960** between alignment tab **2910** and device portion **2970**, and/or cutting a tail slit **2991** between device portion **2970** and tail portion **2990**, such that the kiss cutting is through the layers of protective film **2920** and overlay **2930**, but not through adhesive release liner **2740**. As a result of the kiss cut, the dimensions of device portion **2970** at overlay **2930** and protective film **2920** can be approximately equal or similar to the dimensions of the screen of the device.

(282) As shown in FIG. **30**, in a number of embodiments, after kiss cutting alignment tab **2910**, device portion **2970**, and tail portion **2990** to size at the layers of protective film **2920** and overlay **2930**, and cutting interface slit **2960** and tail slit **2991**, construction of overlay applicator **3000** can include adhering a joining sticker **3080** on top of the layer of protective film **2920** to span interface slit **2960** and join device portion **2970** of protective film **2920** with the top layer of alignment tab **2910**, as shown in FIG. **30**. Joining sticker **3080** can help maintain alignment between alignment tab **2910** and device portion **2970**, which can advantageously maintain alignment during application of overlay **2930**. In many embodiments, joining sticker **3080** does not stretch or distort, which can advantageously facilitate alignment of alignment mechanism **2915** with overlay **2930**, such that overlay **2930** can be accurately positioned on the screen of the device.

(283) In certain embodiments, after joining sticker **3080** has been attached between alignment tab **2910** and device portion **2970**, pull tab **2750** can be folded back, such that second side **2758** is folded beneath adhesive release liner **2740** to first side **2759**. Pull tab **2750** and adhesive release liner **2740** can be peeled back off of at least a portion of alignment tab **2910**, such that alignment mechanism **2915** is uncovered by adhesive release liner **2740**, allowing alignment mechanism to engage with an alignment base, such as alignment base **212** (FIG. **2**) or alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**) and/or alignment base **3112** (FIG. **31**, described below). The process of kiss cutting the layers at protective film **2920** and overlay **2930** can advantageously provide a simpler method of constructing overlay applicator **3000**, and/or can provide overlay applicator **3000** with a very accurate alignment of alignment mechanism **2915** with respect to overlay **2930** and its features.

(284) Turning ahead in the drawings, FIG. **31** illustrates a perspective view of a cradle **3100** that can be used with an overlay applicator, such as overlay applicator **3000** (FIG. **30**), to apply an overlay, such as overlay **2930** (FIGS. **29-30**), to a device. FIG. **32** illustrates a top view of cradle **3100** being used with overlay applicator **3000**. FIG. **33** illustrates a side view of cradle **3100** being used with overlay applicator **3000**. FIG. **34** illustrates a partial cross-sectional view of cradle **3100** being used with overlay applicator **3000** and a device. Cradle **3100** is merely exemplary and embodiments of the cradle are not limited to embodiments presented herein. The cradle can be employed in many different embodiments or examples not specifically depicted or described herein. In many embodiments, cradle **3100** can include an alignment base **3112**, which can engage with alignment mechanism **2915**, as shown in FIG. **32**. In some embodiments, alignment base **3112** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **2915**. Alignment base **3112** and alignment mechanism **2915** can be configured and positioned such that when alignment mechanism **2915** is engaged with alignment base **3112**, overlay **2930** (FIGS. **29-30**) can be positioned directly above the screen of the device held by cradle **3100**, and aligned such that overlay **2930** (FIGS. **29-30**) will be adhered in an accurate position on the screen when adhesive release liner **2740** is removed, as described below.

(285) In many embodiments, cradle **3100** can include a bottom frame **3110**, side frames **3120**, corner frames **3130**, and/or an end frame **3140**. Side frames **3120**, corner frames **3130**, and/or end frame **3140** can provide a device slot **3111** for a device by partially or fully providing support along the sides and/or ends of the device, and can be positioned so as to provide a snug fit for the device to prevent movement

of the device to other portions of cradle **3100**.

(286) In certain embodiments, corner frames **3130** can provide a corner support for the device, and can be attached to bottom frame **3110**. In many embodiments, each corner frame **3130** can include a corner end **3132** that can be configured to extend around an end of the device, and can provide a corner slot **3131** between corner end **3132** and bottom frame **3110**. Corner slots **3131** can allow overlay applicator **3000** to extend under and be secured by corner end **3132**, as shown in FIGS. 32-33.

(287) In a number of embodiments, end frame **3140** can provide corner supports for the device, and can be attached to bottom frame **3110** at end frame attachments **3143**. In some embodiments, end frame **3140** can include an end bar **3142**, which can provide an end slot **3141** between end bar **3142** and bottom frame **3110**. End slot **3141** can allow overlay applicator **3000** to extend under and be secured by end bar **3142**, as shown in FIGS. 32-33. In a number of embodiments, end frame attachments **3143** can provide side supports for overlay applicator **3000**, which can help to keep overlay applicator **3000** within end slot **3141** and properly aligned with respect to the device held by cradle **3100**.

(288) In some embodiments, cradle **3100** can include a central support **3150**, which can be positioned between the sides of cradle **3100** and can extend from one end to the other end of the device when the device is held by cradle **3100** in device slot **3111**. Central support **3150** can be made of foam or an elastomeric material. Central support **3150** can provide support for overlay applicator **3000** and press overlay **2930** (FIGS. 29-30) against the screen of the device as adhesive release liner **2740** (FIGS. 27-30) is peeled away from overlay **2930** (FIGS. 29-30), as described below.

(289) As shown in FIGS. 32-33, overlay applicator **3000** can be placed on cradle **3100** such that alignment base **3112** can engage with alignment mechanism **2915**. Overlay applicator **3000** can extend through corner slots **3131** and end slot **3141**. Overlay applicator **3000** can be positioned on cradle **3100** such that protective film **2920** is placed against central support **3150**, and adhesive release liner **2740** (FIGS. 27-30) and pull tab **2750** are above protective film **2920**. Pull tab **2750** can be folded back across adhesive release liner **2740** (FIGS. 27-30), such that alignment tab **2910** is partially or fully uncovered and wiper **2857** is face up. When overlay applicator **3000** is placed on cradle **3100**, central support **3150** (FIG. 31) can support overlay applicator **3000** above bottom frame **3110** of cradle **3100**. Joining sticker **3080** can be positioned near the region of corner slots **3131**. Device portion **2970** can be positioned between corner frames **3130** and end frame **3140**, and tail portion **2990** can extend through, be supported within, and/or be positioned within end slot **3141**. In a number of embodiments, pull tab **2750** can extend past the end of tail portion **2990**, which can allow a user to pull on pull tab **2750** to remove adhesive release liner **2740** (FIGS. 27-30).

(290) As shown in the cross-section cut-out in FIG. 34, after overlay applicator **3000** is placed on cradle **3100**, a device, such as device **3401**, can be placed on overlay applicator **3000** within slot **3111** of cradle **3100**, with the screen of device **3401** facing downward against pull tab **2750**. Device **3401** can be cradled within slot **3111**. As shown in FIG. 34, central support **3150** can support overlay applicator **3000** above bottom frame **3110** of cradle **3100**. Side frames **3120** can each include a beveled edge **3421**, which can support device **3401** above bottom frame **3110**. The inner width between each of side frames **3120** be wider than overlay applicator **3000**, as shown in FIG. 34, but can be narrower than the width of device **3401**.

(291) After device **3401** is secured within slot **3111** above overlay applicator **3000**, as shown in FIG. 34, pull tab **2750** can be pulled to pull wiper **2857** (FIG. 28-30) across the screen of device **3401** and to remove adhesive release liner **2740** (FIGS. 27-30). Central support **3150** can provide pressure against protective film **2920** (FIGS. 29-30) to press wiper **2857** against the screen of device **3401** as it is wiped across the screen of device **3401**. As adhesive release liner **2740** (FIGS. 27-30) is pulled, it can be folded across itself, can move along the screen of device **3401**, and can expose the adhesive on overlay **2930** (FIGS. 29-30) to the screen of device **3401**. Central support **3150** can be depressed slightly as the fold in adhesive release liner **2740** (FIGS. 27-30) moves from one end to the other end of device **3401**, and can rebound to provide pressure against protective film **2920** (FIGS. 29-30) to press the overlay **2930** (FIGS. 29-30) against the screen of device **3401** as it is exposed. Central support **3150** can advantageously allow the center of overlay **2930** (FIGS. 29-30) to be adhered and can facilitate removing any air bubbles at the center of overlay **2930** (FIGS. 29-30). Beginning the adhesion of overlay **2930** (FIGS. 29-30) to device **3401** at the center can advantageously allow the remainder of overlay **2930** (FIGS. 29-30) to be

accurately adhered to the screen of device **3401** without wrinkles and/or with minimal or no bubbles. (292) Turning ahead in the drawings, FIG. **35** illustrates a perspective view of a machine **3500** that can be used with an overlay applicator **3550** to apply an overlay to a device. FIG. **36** illustrates a perspective view of machine **3500** with the slider being used to apply pressure to the overlay. Machine **3500** is merely exemplary and embodiments of the machine are not limited to embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator **3550** is merely exemplary and embodiments of the overlay applicator are not limited to embodiments presented herein. The overlay applicator can be employed in many different embodiment or examples not specifically depicted or described herein. Overlay applicator **3550** can be similar to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), and/or overlay applicator **3000** (FIG. **30**), and various components and/or constructions of overlay applicator **3550** can be substantially identical or similar to various components of overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), and/or overlay applicator **3000** (FIG. **30**).

(293) In some embodiments, overlay applicator **3550** can include an adhesive release liner (not shown), a pull tab **3555**, an overlay (not shown), and/or a protective film **3552**. In some embodiments, pull tab **3555** can be integral with the adhesive release liner and can be a single layer of material, such as plastic, paper, or another suitable liner film. Pull tab **3555** can facilitate removal of the adhesive release liner from the overlay. In a number of embodiments, overlay applicator **3550** can include alignment tabs **3556**.

Alignment tabs **3556** can be located at each end of overlay applicator **3550** and/or can be located at each end of a device portion **3560** of overlay applicator **3550**. Device portion **3560** can be similar to device portion **470** (FIGS. **4-5**), device portion **670** (FIG. **6**), and/or device portion **2970** (FIGS. **29-30**). In some embodiments, device portion **3560** and alignment tabs **3556** can be made of the layers used for protective film **3552**, the overlay, and/or the adhesive release liner. Each of alignment tabs **3556** can include an alignment mechanism **3557**, which can be similar to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIGS. **4-5**), alignment mechanism **615** (FIG. **6**), and/or alignment mechanism **2915** (FIGS. **29-30**), and which can facilitate aligning alignment tab **3556**, protective film **3552**, the overlay, and the adhesive release liner with various features of the device during application of the overlay.

(294) Protective film **3552** and the overlay can be kiss cut to predetermined dimensions of alignment tabs **3556** and device portion **3560**, without cutting the adhesive release liner and/or pull tab **3555**. In some embodiments, excess material from the layers for protective film **3552** and the overlay can be removed. In some embodiments, the kiss cutting of device portion **3560** and alignment tabs **3556** to size at the layers of protective film **3552** and the overlay can include cutting speaker slots, button slots, and/or other slots, as described above, and/or cutting alignment mechanism **3557**. The kiss cutting can also include cutting interface slits **3558** between alignment tabs **3556** and device portion **3560**, such that the cutting is through the layers of protective film **3552** and the overlay, but not the adhesive release liner. As a result of the kiss cut, the dimensions of device portion **3560** at the overlay and protective film **3552** can be approximately equal or similar to the dimensions of the screen of the device.

(295) In a number of embodiments, after the kiss cutting, construction of overlay applicator **3550** can include adhering joining stickers **3559** on the top the layer of protective film **3552** to span interface slits **3558** and join device portion **3560** of protective film **3552** with the top layer of alignment tabs **3556**, as shown in FIG. **35**. Joining stickers **3559** can help maintain alignment between alignment tabs **3556** and device portion **3560**, which can advantageously maintain alignment during application of the overlay. In many embodiments, joining stickers **3559** does not stretch or distort, which can advantageously facilitate alignment of alignment mechanisms **3557** with the overlay, such that the overlay can be accurately positioned on the screen of the device. In certain embodiments, after joining stickers **3559** have been attached between alignment tabs **3556** and device portion **3560**, pull tab **3555** can be folded back beneath the adhesive release liner, as described above in other embodiments.

(296) In many embodiments, machine **3500** can include a base **3510**, a cradle **3520**, and a slider **3530**. Base **3510** can extend from a first end **3511** to a second end **3512**. In some embodiments, base **3510** can be used with multiple different cradles, which can be used for different devices. Cradle **3520** can include a recess **3521** in which a device can be placed with screen facing upwards or away from recess **3521**.

Recess **3521** can have sides and a bottom, and cradle **3520** can have a thickness greater than the thickness of the device. In many embodiments, recess **3521** is conformal with the device.

(297) In some embodiments, base **3510** can include an alignment base **3514**. In many embodiments, alignment base **3514** can be one or more protrusions that can secure overlay applicator to base **3510**, such as by engaging with alignment mechanisms **3557**. In some embodiments, such as shown in FIGS. **35-36**, alignment base **3514** can be located on base **3510** beyond the each end of cradle **3520**. In other embodiments, alignment base **3514** can be located on cradle **3520**, such as at each end of cradle **3520**. In a number of embodiments, the lines of support between each side of alignment base **3514** can be in line with and within overlay applicator **3550**. Alignment base **3514** and alignment mechanism **3557** can be configured and positioned such that when alignment mechanism **3557** is engaged with alignment base **3514**, the overlay can be positioned directly above the screen of the device. In a number of embodiments, alignment base **3514** can be configured to secure overlay applicator **3550** slightly above the screen of the device.

(298) In a number of embodiments, base **3510** can include a pull slot **3515**. In many embodiments, pull slot **3515** is below one side of alignment base **3514**. In many embodiments, pull tab **3555** can be inserted through pull slot **3515**, which can allow pull tab **3555** to be pulled while overlay applicator **3550** is secured on alignment base **3514**.

(299) In some embodiments, overlay applicator **3550** can include a wiper (not shown), which can be similar to wiper **157** (FIG. **1**), wiper **457** (FIGS. **4-5**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), and/or wiper **2857** (FIG. **28**). The wiper can remove dust from the screen of the device. In other embodiments, after inserting the device in cradle **3520**, a cloth (not shown), such as a microfiber cloth or another suitable cleaning cloth, which can have dimensions similar to pull tab **3555**, can be draped across the screen of the device between the screen of the device and overlay applicator **3550**. One end of the cloth can be inserted through pull slot **3515**. In some embodiments, pull tab **3555** and the cloth can be inserted together through pull slot **3515**, and as pull tab **3555** and the cloth are pulled, the cloth can remove dust from the screen of the device.

(300) In many embodiments, pull tab **3555** can be pulled through pull slot **3515**, and, in certain embodiments, along with a wiper, cloth, or sticker to clean the screen of the device, and the adhesive release liner can be removed to expose the adhesive on the overlay. In a number of embodiments, after the adhesive release liner is removed and the adhesive of the overlay is exposed, the overlay can be secured slightly above the screen of the device, such that adhesion between the overlay and the screen of the device does not occur. In other embodiments, the overlay can be secured at the screen of the device, such that adhesion can begin to occur upon removal of the adhesive release liner.

(301) In some embodiments, base can include a track **3513** on each side, which can allow slider **3530** to move between first end **3511** to second end **3512**. In many embodiments, slider **3530** can include slider side supports **3531**. In a number of embodiments, slider side supports **3531** can include pins (not shown) that can engage in tracks **3513** and allow slider side supports **3531** to slide along tracks **3513**. Slider side supports **3531** can be connected and/or held within tracks **3513** by a slider cross support **3532**. In some embodiments, slider **3530** can include a handle **3533**, which can be used to move slider **3530** back and forth between first end **3511** and second end **3512**. Slider **3530** can include a pressure bar support **3534** on each side of a pressure bar **3535**. Pressure bar supports **3534** can be spring loaded or elastically attached to slider cross support **3532** and/or slider side supports **3531** such that pressure bar **3535** can provide downward pressure. In various embodiments, base **3510** can include cams **3516** in the regions near alignment base **3514**, which can raise pressure bar **3535** such that slider **3530** can move back and forth from first side **3511** to second side **3512** without interference from alignment base **3514**.

(302) In many embodiments, after pull tab **3555** is pulled and the adhesive release liner is partially or fully removed from the overlay, slider **3530** can be moved from first side **3511** partially or fully toward second side **3512** such that pressure bar **3535** provides downward pressure on protective film **3552** to adhere the overlay to the screen of the device, as shown in FIG. **36**. Pressure bar **3535** can provide sufficient pressure to prevent and/or remove any air bubbles. In a number of embodiments, pressure bar **3535** can be a roller. In other embodiments, pressure bar **3535** can be a fixed bar that slides along the top of overlay applicator **3550**. Machine **3500** can thus advantageously be used to accurately align the overlay on the screen of the device without dust or air bubbles.

(303) Turning ahead in the drawings, FIG. 37 illustrates a system 3700 for using an overlay applicator, such as overlay applicator 700 (FIG. 7), to apply an overlay, such as overlay 730 (FIG. 7), to a device. System 3700 is merely exemplary and embodiments of the system are not limited to embodiments presented herein. The system can be employed in many different embodiments or examples not specifically depicted or described herein. System 3700 can include overlay applicator 700, a cradle 3710, a device 3720 (e.g., a smart phone), a cradle frame 3730, and a machine 3740. Cradle 3710 can be similar to cradle 310 (FIG. 3), and various components and/or constructions of cradle 3710 can be substantially identical or similar to various components of cradle 300 (FIG. 3).

(304) Turning ahead in the drawings, FIG. 38 illustrates a top side view of cradle 3710. Cradle 3710 is merely exemplary and embodiments of the cradle are not limited to embodiments presented herein. The cradle can be employed in many different embodiments or examples not specifically depicted or described herein. Cradle 3710 can include a slot 3811 in which device 3720 (FIG. 37) can be placed with the screen of device 3720 (FIG. 37) facing upwards or away from slot 3811. In some embodiments, slot 3811 is conformal with device 3720 (FIG. 37). Slot 3811 can have sides 3812 and a bottom 3813. Cradle 3710 can have a thickness greater than the thickness of device 3720 (FIG. 37). In many embodiments, cradle 3710 can include an alignment base 3814, which can engage with alignment mechanism 715 (FIG. 7). In some embodiments, alignment base 3814 can be one or more protrusions that can fit inside the one or more slots of alignment mechanism 715 (FIG. 7). For example, as shown in FIG. 7, alignment mechanism 715 (FIG. 7) can include six holes spaced relatively evenly around alignment frame 710 (FIG. 7). Alignment base 3814 can include six protrusions configured to engage with the six holes of alignment mechanism 715 (FIG. 7). In some embodiments, the protrusions of alignment base 3814 can be spring loaded. Alignment base 3814 and alignment mechanism 715 (FIG. 7) can be configured and positioned such that when alignment mechanism 715 (FIG. 7) is engaged with alignment base 3814, overlay 730 (FIG. 7) can be positioned directly above the screen of device 3720 (FIG. 37) in slot 3811, and aligned such that overlay 730 (FIG. 7) will be adhered in an accurate position on the screen when adhesive release liner 740 (FIG. 7) is removed. In certain embodiments, cradle 3710 can include a bottom aperture 3815, which can facilitate removal of device 3720 (FIG. 37) from cradle 3710.

(305) Turning ahead in the drawings, FIG. 39 illustrates a top side view of cradle frame 3730. FIG. 40 illustrates a bottom side view of cradle frame 3730. Cradle frame 3730 is merely exemplary and embodiments of the cradle frame are not limited to embodiments presented herein. The cradle frame can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, cradle frame 3730 can include side frames 3910, which can include alignment holes 3911 that can engage with alignment base 3814 (FIG. 38). Cradle frame 3730 can include a bottom plate 3912, which can be bent at a crease 3913 midway between the two sides and extending partially or fully from one end to the other end of cradle frame 3730. Bottom plate 3912 can be made of a flexible or semi-flexible plastic. In various embodiments, the bend in bottom plate 3912 at crease 3913 can be maintained by end caps 3914, which can be centered at each end of cradle frame 3730. End caps 3914 can be made of a rigid material, such as a rigid metal or polycarbonate (PC). In many embodiments, cradle frame 3730 can include end frames 3915 extending at each end of cradle frame 3730 between side frames 3910. In certain embodiments, end frame 3915 can be less thick than side frames 3710, which can allow flexibility for bottom plate 3912 to be depressed and semi-flexibly bent downward, such as in the region of crease 3913. In a number of embodiments, cradle frame 3730 can include a recess 3916 between side frames 3910 and end frames 3915, and bounded at the bottom by bottom plate 3912. Recess 3916 can have dimensions substantially similar to overlay 730 (FIG. 7) and/or the screen of device 3720 (FIG. 37).

(306) Turning ahead in the drawings, FIG. 41 illustrates a left side view of machine 3740 with the arm in a raised configuration. Machine 3740 is merely exemplary and embodiments of the machine are not limited to embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In many embodiments, machine 3740 can include a base 4110, a cradle support 4120, a stand 4130, a hinge assembly 3740, and an arm 4150. In many embodiments, base 4110 can provide a sturdy support base for machine 3740. In certain embodiments, base 4110 can include feet 4111 made from an elastomeric material for non-slip, cushioned, and/or balanced support. In some embodiments, cradle support 4120 can be a recess in base 4110, as shown in FIG. 41. Cradle support 4120 can be configured to hold a cradle, such as cradle 3710

(FIGS. 37-38). Cradle support **4120** can be used with various different cradles, which can be configured for different devices.

(307) In many embodiments, stand **4130** can provide support for arm **4150**. In certain embodiments, stand **4130** can extend upright from base **4110**, and, in some embodiments, can be substantially perpendicular to base **4110**. Stand **4130** can be connected to arm **4150** at hinge assembly **4140**. In many embodiments, hinge assembly **4140** can include a hinge axis **4141**. In some embodiments, hinge assembly **4140** can include a hinge track **4142** to allow arm **4150** to move along a predetermined arc. In a number of embodiments, hinge assembly **4140** can include a hinge clamp **4143**, which can allow arm **4150** to be secured at desired and/or predetermined positions. For example, arm **4150** can be raised to a raised configuration, as shown in FIG. 41, or lowered to a lowered position, as shown in FIG. 44, described below. When arm **4150** is raised, cradle **3710** (FIGS. 37-38) can be inserted or removed from cradle support **4120**. When arm **4150** is lowered, overlay applicator **700** (FIGS. 7, 37) can be used apply overlay **730** (FIG. 7), as described below. In some embodiments, stand **4130** can include a positioning piece **4131**, which can prevent arm **4150** from lowering below a predetermined position.

(308) In certain embodiments, arm **4150** can include a handle **4154**, which can be used to assist in raising and/or lowering arm **4150** when hinge assembly **4140** is unclamped. In some embodiments, arm **4150** can include an expandable bladder **4151**, such as an air bladder. In many embodiments, expandable bladder **4151** can be connected to a pumping mechanism **4152**, which can fill expandable bladder **4151** with air, as shown in FIG. 44, described below. In certain embodiments, expandable bladder **4151** and/or pumping mechanism **4152** can be a part of a portable (e.g., battery powered) blood pressure monitor and cuff, which can include a microprocessor and a start/stop button **4153** to initiate or terminate the inflation and/or deflation of expandable bladder **4151** with air.

(309) Turning ahead in the drawings, FIGS. 42-45 illustrate using system **3700** with machine **3740**, cradle **3710**, overlay applicator **700**, and cradle frame **3730** to apply overlay **730** (FIG. 7) to device **3720**. FIG. 42 illustrates machine **3740**, cradle frame **3730**, device **3720** located in cradle **3710**, and overlay applicator **700** located on cradle **3710** above device **3720**. In many embodiments, device **3720** can be placed in slot **3811** in cradle **3710** with the screen facing upwards or away from slot **3811**, as shown in FIG. 42. After placing device **3720** in cradle **3710**, overlay applicator **700** can be placed on cradle **3710** above device **3720** (FIG. 37), with protective film **720** facing up and above overlay **730** (FIG. 7), adhesive release liner **740** (FIG. 7), and pull tab **750**. In many embodiments, pull tab **750** and wiper **757** can be facing downward, and resting upon or proximate to the screen of device **3720** (FIG. 37). In some embodiments, overlay applicator **700** can be secured to cradle **3710** by alignment base **3814** engaging with alignment mechanism **715**.

(310) FIG. 43 illustrates cradle **3710** located in cradle support **4120** of machine **3740**, with cradle frame **3730** upon cradle **3710**. Cradle frame **3730** can be placed upon cradle **3710** above overlay applicator **700** and device **3720** (FIG. 37). In some embodiments, bottom plate **3912** (FIGS. 39-40) can protrude slightly downward toward overlay applicator **700**. In various embodiments, alignment holes **3911** (FIGS. 39-40) can engage with alignment base **3814** (FIG. 38) to secure cradle frame **3730** to cradle **3710**. Cradle **3710**, along with device **3720** (FIG. 37), overlay applicator **700**, and cradle frame **3730**, as assembled as described above, can be placed in cradle support **4120** of machine **3740**. In many embodiments, arm **4150** of machine **3740** can be in a raised position to facilitate insertion of cradle **3710** in cradle support **4120**.

(311) FIG. 44 illustrates machine **3740** with arm **4150** in a lowered position and expandable bladder **4151** filled, and with pull tab **750** and adhesive release liner **740** removed. In many embodiments, arm **3850** can be lowered to a lowered position, as shown in FIG. 44. In many embodiments, hinge clamp **4143** can be disengaged to allow arm **4150** to rotate along hinge track **4142** around hinge axis **4141** to the lowered position, and then reengaged at the lowered position. In several embodiments, handle **4154** can be used to assist lowering arm **4150**. In various embodiments when arm **4150** is in a lowered position, expandable bladder **4151** can rest upon cradle frame **3730**, and, in some embodiments, can rest within recess **3916** (FIG. 39).

(312) In some embodiments, pull tab **750** can be pulled to remove adhesive release liner **740** from the adhesive side of overlay **730** (FIG. 7). In many embodiments, as pull tab **750** is pulled, wiper **757** can wipe across the screen of device **3720** (FIG. 37) to remove any dust. In some embodiments, bottom plate

3912 (FIG. 39) of cradle frame **3730** can be positioned so as to provide enough pressure on wiper **757** such that wiper **757** can stay in contact with the screen of device **3720 (FIG. 37)** and effectively clean off any dust. In many embodiments, after pull tab **750** has been pulled out and adhesive release liner **740** has been removed from covering overlay **730 (FIG. 7)**, overlay **730 (FIG. 7)** can be secured such that it remains above and does not adhere to the screen of device **3720 (FIG. 37)**.

(313) In many embodiments, pumping mechanism **4152** can be activated to fill expandable bladder **4151**. In many embodiments, start/stop button **4153** can be activated to fill expandable bladder **4151** with air. As shown in **FIG. 44**, expandable bladder **4151** can expand as it fills with air. In some embodiments, the expansion of expandable bladder **4151** can provide downward force on bottom plate **3912 (FIG. 39)**. Crease **3913 (FIG. 39)** can push down on overlay applicator **700 (FIG. 7)** such that overlay **730 (FIG. 7)** can begin to adhere to the screen of device **3720 (FIG. 37)** along the center line between the sides of device **3720 (FIG. 37)**. As expandable bladder **4151** continues to inflate, other regions of bottom plate **3912 (FIG. 39)** can press down on overlay **730 (FIG. 7)**, extending outward from the center. Beginning the adhesion of overlay **730 (FIG. 7)** to device **3720 (FIG. 37)** at the center of device **3720 (FIG. 37)** can advantageously allow the remainder of overlay **730 (FIG. 7)** to be accurately adhered to the screen of device **3720 (FIG. 37)** without wrinkles and/or with minimal or no bubbles.

(314) **FIG. 45** illustrates machine **3740** with arm **4150** in a raised position, with cradle **3710** removed from cradle support **4120**, with cradle frame **3730** removed off of cradle **3710**, and with pull tab **750** and adhesive release liner **740** removed. In many embodiments, pumping mechanism **4152** can be deactivated to stop the inflation of expandable bladder **4151** and/or to begin the deflation of expandable bladder **4151**. In many embodiments, start/stop button **4153** can be deactivated to deflate expandable bladder **4151**. In other embodiments, pumping mechanism **4152** can be pre-programmed to stop the inflation of expandable bladder **4151** and to begin the deflation of expandable bladder **4151** after expandable bladder reaches a predetermined level of inflation.

(315) In several embodiments, arm **4150** can be raised to a raised position. In many embodiments, hinge clamp **4143** can be disengaged to allow arm **4150** to rotate along hinge track **4142** around hinge axis **4141** to the raised position, and then reengaged at the raised position. In many embodiments, handle **4154** can help facilitate moving arm **4150**. Arm **4150** of machine **3740** can be in a raised position to facilitate removal of cradle **3710** from cradle support **3720** of machine **3740**.

(316) In a number of embodiments, cradle **3710** can be removed, along with device **3720**, overlay applicator **700 (FIG. 7)**, and cradle frame **3730** from cradle support **4120** of machine **3740**. In several embodiments, cradle frame **3730** can next be removed from cradle **3710** to uncover protective film **720** and alignment frame **710**, which in many embodiments can be integral with protective film **720**, as described above. In some embodiments, device **3720**, along with the protective film **720**, alignment frame **710**, and overlay **730**, can be removed from cradle **3710**. In many embodiments, removal of device **3720** can be accomplished by manually reaching through bottom aperture **3815 (FIG. 38)** of cradle **3710** to push upward or away from bottom aperture **3815** on device **3720**. In a number of embodiments, alignment frame **710** and protective film **720** can be peeled away from overlay **730**, which is adhered to device **3720**. After alignment frame **710** and protective film **720** have been peeled away from overlay **730**, application of overlay **730** to the screen of device **3720** can be complete.

(317) Turning ahead in the drawings, **FIG. 46** illustrates a perspective view of a machine **4600** in a closed configuration. **FIG. 47** illustrates a perspective view of machine **4600** in an open configuration. Machine **4600** can be used with an overlay applicator to apply an overlay to a device. Machine **4600** is merely exemplary and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **4600** can include a base **4610**, a cradle support **4620**, a cradle **4630**, a hinge assembly **4640**, an arm **4650**.

(318) In many embodiments, base **4610** can provide a sturdy support base for machine **4600**. In some embodiments, cradle support **4620** can be a recess in base **4610**. In a number of embodiments, base **4610** can include an indented region **4611**, which can extend partially along a side of base **4610** and/or cradle support **4620**, and which can facilitate removal of cradle **4630** from cradle support **4620**. Cradle support **4620** can be configured to hold a cradle, such as cradle **4630**. In various embodiments, cradle support **4620** can be used interchangeably with various different cradles, such as cradles configured for various

different devices.

(319) Cradle **4630** can be similar to cradle **3710** (FIGS. **37-38**), and various components and/or constructions of cradle **4630** can be substantially identical or similar to various components of cradle **3710** (FIGS. **37-38**). Cradle **4630** can be configured to be used with an overlay applicator, such as overlay applicator **700** (FIG. **7**). As shown in FIG. **47**, cradle **4630** can include a slot **4731** in which a device can be placed with the screen of the device facing upwards or away from slot **4731**. In some embodiments, slot **4731** can be conformal with the device. Cradle **4630** can have a thickness greater than the thickness of the device. In many embodiments, cradle **4630** can include an alignment base **4734**, which can engage with an alignment mechanism, such as alignment mechanism **715** (FIG. **7**), of an overlay applicator, such as overlay applicator **700** (FIG. **7**). In some embodiments, alignment base **4734** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **715** (FIG. **7**). For example, as shown in FIG. **7**, alignment mechanism **715** (FIG. **7**) can include six holes spaced relatively evenly around alignment frame **710** (FIG. **7**). Alignment base **4734** can include six protrusions configured to engage with the six holes of alignment mechanism **715** (FIG. **7**). In some embodiments, the protrusions of alignment base **4734** can be spring loaded. Alignment base **4734** and alignment mechanism **715** (FIG. **7**) can be configured and positioned such that when alignment mechanism **715** (FIG. **7**) is engaged with alignment base **4734**, overlay **730** (FIG. **7**) can be positioned directly above the screen of the device in slot **4731**, and aligned such that overlay **730** (FIG. **7**) will be adhered in an correct position on the screen when adhesive release liner **740** (FIG. **7**) is removed. In certain embodiments, cradle **4630** can include a bottom aperture **4735**, which can facilitate removal of the device from cradle **4630**.

(320) In many embodiments, base **4610** can be connected to arm **4650** at hinge assembly **4640**. In many embodiments, hinge assembly **4640** can allow arm **4650** to rotate relative to base **4610**. In some embodiments, hinge assembly **4640** can lock in two positions, which can allow arm to be held at a raised position and at a lowered position. Hinge assembly **4640** can include a hinge axle **4641**, which can connect a hinge central member **4642** to side supports **4643** through a hinge axis of rotation. In several embodiments, hinge side supports **4643** can include notches **4644**, and hinge central member **4642** can include a locking rod **4645**, which can engage in notches **4644** to lock hinge assembly **4640** such that arm **4650** can be held at a raised position and/or at a lowered position. In many embodiments, locking rod **4645** can have a spring-loaded bias to remain in notches **4644**. Arm **4650** can be raised to a raised configuration, as shown in FIG. **47**, or lowered to a lowered position, as shown in FIG. **46**. When arm **4650** is raised, cradle **4630** can be inserted or removed from cradle support **4620**. When arm **4650** is lowered, overlay applicator **700** (FIG. **7**) can be used apply overlay **730** (FIG. **7**), as described below.

(321) In certain embodiments, arm **4650** can include a handle **4654**, which can be used to assist in raising and/or lowering arm **4650** with respect to base **4610** about hinge assembly **4640**. In some embodiments, arm **4650** can include an expandable bladder **4651**, such as an air bladder. In many embodiments, expandable bladder **4651** can be connected to a pumping mechanism **4652**, which can fill expandable bladder **4651** with air. Pumping mechanism **4652** can be similar or identical to pumping mechanism **4152** (FIG. **41**), and/or expandable bladder **4651** can be similar or identical to expandable bladder **4151** (FIG. **41**). In certain embodiments, expandable bladder **4651** and/or pumping mechanism **4652** can be a part of a portable (e.g., battery powered) blood pressure monitor and cuff, which can include a microprocessor and a start/stop button **4653** to initiate or terminate the inflation and/or deflation of expandable bladder **4651** with air.

(322) Turning ahead in the drawings, FIGS. **48-50** illustrate using machine **4600** to apply overlay **730** (FIG. **7**) to the screen of a device. FIG. **48** illustrates a perspective view of a machine **4600** in an open configuration, with a device in cradle **4630**, and an overlay applicator **700** above the device on cradle **4630**. As shown in FIG. **48**, a device **4800** can be placed in slot **4731** (FIG. **47**) of cradle **4630** with the screen of device **4800** facing upwards or away from cradle **4630**. In some embodiments, cradle **4630** can be placed in cradle support **4620** (FIGS. **46-47**) prior to inserting device **4800** in cradle **4630**. In other embodiments, cradle **4630** can be placed in cradle support **4620** (FIGS. **46-47**) after inserting device **4800** in cradle **4630**. In many embodiments, arm **4650** of machine **4600** can be in a raised position to facilitate insertion of cradle **4630** in cradle support **4620** (FIGS. **46-47**) and/or insertion of device **4800** in cradle **4630**.

(323) In a number of embodiments, overlay applicator **700** can be placed on cradle **4630** above device **4800**, with protective film **720** facing up and above overlay **730** (FIG. 7), adhesive release liner **740** (FIG. 7), and pull tab **750**. In many embodiments, pull tab **750** and wiper **757** (FIG. 7) can be facing downward, and resting upon or proximate to the screen of device **4800**. In some embodiments, overlay applicator **700** can be secured to cradle **4630** by alignment base **4734** engaging with alignment mechanism **715**.

(324) FIG. **49** illustrates a perspective view of a machine **4600** in a closed configuration, with pull tab **750** of overlay applicator **700** being pulled. In several embodiments, arm **4650** can next be lowered to a lowered position, as shown in FIG. **49**. In many embodiments, hinge central member **4642** can rotate with respect to hinge side supports **4643**, and locking rod **4645** (FIGS. **46-47**) can disengage with one or more of notches **4644** (FIGS. **46-47**) and reengage with a different one or more of notches **4644** (FIGS. **46-47**). In various embodiments when arm **4650** is in a lowered position, expandable bladder **4651** can rest upon overlay applicator **700**.

(325) In several embodiments, pull tab **750** can be pulled to remove adhesive release liner **740** (FIG. 7) from the adhesive side of overlay **730** (FIG. 7). In many embodiments, as pull tab **750** is pulled, wiper **757** (FIG. 7) can wipe across the screen of device **4800** (FIG. **48**) to remove any dust from the screen of device **4800** (FIG. **48**). In many embodiments, after pull tab **750** has been pulled out and adhesive release liner **740** (FIG. 7) has been removed from covering overlay **730** (FIG. 7), overlay **730** (FIG. 7) can be secured such that it remains above and does not adhere to the screen of device **4800** (FIG. **48**). In some embodiments, pulling on pull tab **750** to remove adhesive release liner **740** (FIG. 7) from the adhesive side of overlay **730** (FIG. 7) can occur before lowering arm **4650** to a lowered position.

(326) In some embodiments, pumping mechanism **4652** can next be activated to fill expandable bladder **4651**. In many embodiments, start/stop button **4653** can be activated to fill expandable bladder **4651** with air. Expandable bladder **4651** can expand as it fills with air. In some embodiments, the expansion of expandable bladder **4651** can provide downward force on protective film **720** (FIG. 7) such that overlay **730** (FIG. 7) can begin to adhere to the screen of device **4800** (FIG. **48**). Adhering overlay **730** (FIG. 7) to device **4800** (FIG. **48**) by applying pressure with expandable bladder **4651** can advantageously allow the overlay **730** (FIG. 7) to be accurately adhered to the screen of device **4800** (FIG. **48**) without wrinkles and/or with minimal or no bubbles. In certain embodiments, expandable bladder **4651** can be configured to begin inflation at the center of expandable bladder **4651** and continue inflating out to the perimeter regions of expandable bladder **4651**, which can adhere overlay **730** (FIG. 7) beginning at the center of the screen of device **4800** (FIG. **48**), and continue the adhesion out to the perimeter regions of the screen of device **4800** (FIG. **48**), which can advantageously cause overlay **730** (FIG. 7) to be adhered to the screen of device **4800** (FIG. **48**) with minimal or no air bubbles.

(327) In many embodiments, pumping mechanism **4652** can be deactivated to stop the inflation of expandable bladder **4651** and/or to begin the deflation of expandable bladder **4651**. In many embodiments, start/stop button **4653** can be pressed to deactivate pumping mechanism **4652** to deflate expandable bladder **4651**. In other embodiments, pumping mechanism **4652** can be pre-programmed to stop the inflation of expandable bladder **4651** and to begin the deflation of expandable bladder **4651** after expandable bladder reaches a predetermined level of inflation.

(328) FIG. **50** illustrates a perspective view of a machine **4600** in an open configuration, with portions of overlay applicator **700** remaining on device **4800**. In a number of embodiments, arm **4650** can be raised to a raised position, as shown in FIG. **50**. In many embodiments, hinge central member **4642** can rotate with respect to hinge side supports **4643**, and locking rod **4645** (FIGS. **46-47**) can disengage with one or more of notches **4644** (FIGS. **46-47**) and reengage with a different one or more of notches **4644** (FIGS. **46-47**). In many embodiments, handle **4654** can help facilitate lifting and/or moving arm **4650**. Arm **4650** of machine **4600** can be in a raised position to facilitate removal of cradle **4630** from cradle support **4620**, and/or removal of device **4800** from cradle **4630**.

(329) In several embodiments, cradle **4630**, along with device **4800** and overlay applicator **700**, can next be removed from cradle support **4620** of machine **4600**. In a number of embodiments, device **4800**, along with the protective film **720**, alignment frame **710**, and overlay **730**, can be removed from cradle **4630**. In many embodiments, removal of device **4800** can be accomplished by manually reaching through bottom aperture **4735** (FIG. **47**) of cradle **4630** to push upward (or away from bottom aperture **4735**) on device

4800. In several embodiments, alignment frame **710** and protective film **720**, which can be integral, can be peeled away from overlay **730**, which is adhered to device **4800**. After alignment frame **710** and protective film **720** have been peeled away from overlay **730**, application of overlay **730** to the screen of device **4800** can be complete.

(330) Turning ahead in the drawings, FIG. **51** illustrates a flow chart for an embodiment of a method **5100** of providing an overlay applicator. Method **5100** is merely exemplary and is not limited to the embodiments presented herein. Method **5100** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **5100** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **5100** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **5100** can be combined or skipped. In some embodiments, the overlay applicator can be similar or identical to overlay applicator **3000** (FIG. **30**).

(331) Referring to FIG. **51**, method **5100** can include a block **5101** of providing an adhesive release liner. In many embodiments, the adhesive release liner layer can be similar or identical to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**); adhesive release liner **1540** (FIG. **15**), and/or adhesive release liner **2740** (FIGS. **27-30**). In a number of embodiments, the adhesive release liner can include a top side and a bottom side.

(332) In some embodiments, method **5100** can include a block **5102** of providing a pull tab. In various embodiments, the pull tab can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIG. **7**), pull tab **1550** (FIG. **15**), and/or pull tab **2750** (FIGS. **27-30**). In some embodiments, the pull tab can include a top side and a bottom side. In various embodiments, the adhesive release liner can be integral with the pull tab. In a number of embodiments, method **5100** can include adhering the adhesive release liner to the pull tab.

(333) In a number of embodiments, method **5100** can include a block **5103** of attaching a wiper to the top side of the pull tab. In several embodiments, the wiper can be similar or identical to wiper **157** (FIG. **1**), wiper **457** (FIG. **4**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), and/or wiper **2857** (FIGS. **28-30**).

(334) In various embodiments, method **5100** can include a block **5104** of providing an overlay layer. The overlay layer can be similar or identical to the layer of material for overlay **2930** (FIGS. **29-30**). In a number of embodiments, the overlay layer can include a top side and a bottom side. In some embodiments, the bottom side can include an adhesive agent configured to adhere to the top side of the adhesive release liner.

(335) In many embodiments, method **5100** can include a block **5105** of attaching the bottom side of the overlay layer to the top side of the adhesive release liner.

(336) In some embodiments, method **5100** can include a block of **5106** of providing a protective film layer. In a number of embodiments, the protective film layer can be similar or identical to the layer of material for protective film layer **2920** (FIGS. **29-30**). In various embodiments, the protective film layer can include a top side and a bottom side.

(337) In several embodiments, method **5100** can include a block **5107** of attaching the bottom side of the protective film layer to the top side of the overlay layer.

(338) In various embodiments, method **5100** can include a block **5108** of cutting the protective film layer and the overlay layer to create an interface slit between an alignment tab and a device portion, and to create a tail slit between a tail portion and the device portion. In some embodiments, the interface slit can be similar or identical to interface slit **2960** (FIGS. **29-30**). In a number of embodiments, the tail slit can be similar or identical to tail slit **2991** (FIGS. **29-30**). In some embodiments, the alignment tab can be similar or identical to alignment tab **110** (FIG. **1**), alignment tab **410** (FIGS. **4-5**), alignment tab **610** (FIG. **6**), and/or alignment tab **2910** (FIGS. **29-30**). In many embodiments, the device portion can be similar or identical to device portion **470** (FIGS. **4-5**), device portion **670** (FIG. **6**), device portion **2970** (FIGS. **29-30**), and/or device portion **3560** (FIG. **35**). In some embodiments, the tail portion can be similar or identical to tail portion **2990** (FIGS. **29-30**). In several embodiments, the alignment tab can be configured to engage with an alignment base to align the overlay with the screen of the device.

(339) In many embodiments, method **5100** can include a block **5109** of attaching a sticker to the top side of the protective film. In several embodiments, the sticker can be similar or identical to joining sticker

680 (FIG. 6), joining sticker **3080** (FIG. 30), and/or joining stickers **3559** (FIG. 35). In some embodiments, the sticker can span the interface slit between the device portion and the alignment tab. In a number of embodiments, the sticker can include a non-stretching material.

(340) Proceeding to the next drawing, FIG. 52 illustrates a flow chart for an embodiment of a method **5200** of providing a cradle. Method **5200** is merely exemplary and is not limited to the embodiments presented herein. Method **5200** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **5200** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **5200** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **5200** can be combined or skipped. In some embodiments, the cradle can be similar or identical to cradle **3100** (FIGS. 31-34).

(341) Referring to FIG. 52, method **5200** can include a block **5201** of providing a base. In a number of embodiments, the base can be similar or identical to bottom frame **3110** (FIG. 31).

(342) In many embodiments, method **5200** can include a block **5202** of providing an alignment base. In several embodiments, the alignment base can be similar or identical to alignment base, such as alignment base **212** (FIG. 2) or alignment base **312** (FIG. 3), alignment base **835** (FIGS. 8-9, 13-14), alignment base **1632** (FIGS. 16-19), alignment base **2035** (FIG. 20) and/or alignment base **3112** (FIG. 31). In various embodiments, the alignment base can be configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), and/or overlay applicator **3000** (FIG. 30). In a number of embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. 1), alignment mechanism **415** (FIGS. 4-5), alignment mechanism **615** (FIG. 6), and/or alignment mechanism **2915** (FIGS. 29-30).

(343) In some embodiments, method **5200** can include a block **5203** of providing one or more frame pieces. In several embodiments, the one or more frame pieces can include two corner frames located at a first end of the base proximate to the alignment base. The corner frames can be similar or identical to corner frames **3130** (FIG. 31). In many embodiments, the one or more frame pieces can include an end frame located at a second end of the base opposite the first end. The end frame can be similar or identical to end frame **3140** (FIG. 31). In several embodiments, the one or more frame pieces can include two side frames located at each side of the base between the first end and the second end. The side frames can be similar or identical to side frames **3120** (FIG. 31).

(344) In some embodiments, the frame pieces can be configured to securely hold an electronic device in a device slot in a fixed position with respect to the alignment base. The device slot can be similar or identical to device slot **3111** (FIG. 31). In various embodiments, the base, the alignment base, and the one or more frame pieces can be configured to hold the overlay applicator between the base and a screen of the electronic device when the screen of the electronic device is facing toward the base. In a number of embodiments, the base, the alignment base, and the one or more frame pieces can be configured to facilitate applying an overlay of the overlay applicator to the screen of the electronic device. The overlay can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), overlay **1530** (FIG. 15), and/or overlay **2930** (FIGS. 29-30). In many embodiments, the one or more frame pieces can be configured to align the overlay applicator as the overlay of the overlay applicator is applied to the screen of the electronic device.

(345) In several embodiments, the one or more frame pieces can include a pull tab slot configured to allow a pull tab of the overlay applicator to extend beyond the device slot. The pull tab slot can be similar or identical to end slot **3141** (FIG. 31). The pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), and/or pull tab **2750** (FIGS. 27-30). For example, the pull tab can extend beyond the device slot as shown in FIGS. 32-33.

(346) In a number of embodiments, the base can include a support piece extending in a first direction. The support piece can be similar or identical to central support **3150** (FIG. 31). In some embodiments, the support piece can be configured to press an adhesive side of the overlay of the overlay applicator toward the screen of the electronic device when the screen of the electronic device is facing toward the support piece and the pull tab of the overlay applicator is pulled in the first direction to remove an

adhesive release liner of the overlay applicator and expose the adhesive side of the overlay to the screen of the electronic device. In a number of embodiments, the support piece can include an elastomeric material. In various embodiments, the support piece can be configured to press the adhesive side of the overlay against the screen of the electronic device when the adhesive release liner of the overlay applicator is removed to expose the adhesive side of the overlay. In various embodiments, the support piece can be configured to press a wiper of the pull tab toward the screen of the electronic device as the wiper moves across the screen of the electronic device in the first direction. The wiper can be similar or identical to wiper **157** (FIG. **1**), wiper **457** (FIG. **4**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), and/or wiper **2857** (FIGS. **28-30**).

(347) Proceeding to the next drawing, FIG. **53** illustrates a flow chart for an embodiment of a method **5300** of providing a machine. Method **5300** is merely exemplary and is not limited to the embodiments presented herein. Method **5300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **5300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **5300** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **5300** can be combined or skipped. In some embodiments, the machine can be similar or identical to machine **3500** (FIGS. **35-36**).

(348) Referring to FIG. **53**, method **5300** can include a block **5301** of providing a base. In a number of embodiments, the base can be similar or identical to base **3510** (FIGS. **35-36**). In several embodiments, the base can include a first end. The first end can be similar or identical to first end **3511** (FIGS. **35-36**). In many embodiments, the base can include a second end. The second end can be similar or identical to second end **3512** (FIGS. **35-36**). In some embodiments, the base can include an alignment base. The alignment base can be similar or identical to alignment base **3514** (FIGS. **35-36**). In many embodiments, the alignment base can be configured to engage with an alignment mechanism of an overlay applicator. The alignment mechanism can be similar or identical to alignment mechanism **3557** (FIGS. **35-36**). The overlay applicator can be similar or identical to overlay applicator **3550** (FIGS. **35-36**).

(349) In a number of embodiments, the overlay applicator can include a first alignment tab and a second alignment tab. The first and second alignment tabs can be similar or identical to alignment tabs **3556** (FIGS. **35-36**). In several embodiments, the first alignment tab can include a first portion of the alignment mechanism, and the second alignment tab including a second portion of the alignment mechanism. In many embodiments, the alignment base can include a first side proximate the first end of the base. In a number of embodiments, the first side can be configured to engage with the first portion of the alignment mechanism of the overlay applicator. In many embodiments, a second side proximate the second end of the base, the second side can be configured to engage with the second portion of the alignment mechanism of the overlay applicator.

(350) In a number of embodiments, the base can include a pull slot. The pull slot can be similar or identical to pull slot **3515** (FIGS. **35-36**). In some embodiments, the pull slot can be located between the cradle and the second side of the alignment base.

(351) In many embodiments, method **5300** can include a block **5302** of providing a cradle. The cradle can be similar or identical to cradle **3520** (FIGS. **35-36**). In several embodiments, the cradle can be located between the first side of the alignment base and the second side of the alignment base. In some embodiments, the cradle can be configured to securely hold an electronic device. In various embodiments, the cradle can be integral with the base. In many embodiments, the cradle can be removably coupled to the base.

(352) In some embodiments, method **5300** can include a block **5303** of providing a slider configured to move between the first and second ends of the base. The slider can be similar or identical to slider **3530** (FIGS. **35-36**). In a number of embodiments, the slider can include a bar. The bar can be similar or identical to pressure bar **3535** (FIGS. **35-36**). In many embodiments, the bar can be configured to press an overlay of the overlay applicator toward a screen of the electronic device when the slider is moved between the first and second ends of the base. The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**). In several embodiments, the bar can be spring-loaded to press

downward toward the base. In a number of embodiments, the base can include one or more tracks configured to engage with the slider and allow the slider to move between the first and second ends of the base. The tracks can be similar or identical to track **3513** (FIGS. **35-36**).

(353) In several embodiments, the base can include one or more first cams at the first end of the base and one or more second cams at the second end of the base. In first and second cams can be similar or identical to cams **3516**. In many embodiments, the one or more first cams can be configured to prevent the bar from contacting the first side of the alignment base when the slider is moved between the first and second ends of the base. the one or more second cams can be configured to prevent the bar from contacting the second side of the alignment base when the slider is moved between the first end and second ends of the base.

(354) In many embodiments, the machine can be configured such that when the alignment base is engaged with the alignment mechanism of the overlay applicator and the cradle is holding the electronic device, a pull tab of the overlay applicator can be pulled through the pull slot to remove an adhesive release liner of the overlay applicator and expose an adhesive side of the overlay to the screen of the electronic device. The pull tab be similar or identical to pull tab **3555** (FIG. **35**). In various embodiments, the machine can be further configured such that when the adhesive release liner of the overlay applicator is removed to expose the adhesive side of the overlay to the screen of the electronic device and the slider is moved between the first and second ends of the base, the bar can be configured to press the adhesive side of the overlay against the screen of the electronic device.

(355) Proceeding to the next drawing, FIG. **54** illustrates a flow chart for an embodiment of a method **5400** of providing a machine. Method **5400** is merely exemplary and is not limited to the embodiments presented herein. Method **5400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **5400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **5400** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **5400** can be combined or skipped. In some embodiments, the machine can be similar or identical to machine **3700** (FIGS. **37, 41-45**) and/or machine **4600** (FIGS. **46-50**).

(356) Referring to FIG. **54**, method **5400** can include a block **5401** of providing a base. In a number of embodiments, the base can be similar or identical to base **4110** (FIG. **41**) and/or base **4610** (FIG. **46**).

(357) In many embodiments, method **5400** can include a block **5402** of providing a cradle configured to securely hold an electronic device. The cradle can be similar or identical to cradle **3710** (FIGS. **37-38**) and/or cradle **4630** (FIGS. **46-50**). The electronic device can be similar or identical to device **3720** (FIG. **37**) and/or device **4800** (FIG. **48**). in several embodiments, the cradle can include an alignment base configured to engage with an alignment mechanism of an overlay applicator. The alignment base can be similar or identical to alignment base **3814** (FIG. **38**) and/or alignment base **4734** (FIG. **47**). The alignment mechanism can be similar or identical to alignment mechanism **715** (FIGS. **7, 48**). In several embodiments, the alignment base can include six protrusions configured to engage with an alignment frame of the overlay applicator. In some embodiments, the cradle can be integral with the base. In many embodiments, the base can include a cradle support configured to removably hold the cradle. The cradle support can be similar or identical to cradle support **4120** (FIG. **41**) and/or cradle support **4620** (FIG. **46**).

(358) In some embodiments, method **5400** can include a block **5403** of providing an arm. The arm can be similar or identical to arm **4150** (FIG. **41**) and/or arm **4650** (FIG. **46**). In several embodiments, the arm can include an expandable bladder. The expandable bladder can be similar or identical to expandable bladder **4151** (FIG. **41**) and/or expandable bladder **4651** (FIG. **46**). In a number of embodiments, the arm can include a pumping mechanism configured to inflate the expandable bladder. The pumping mechanism can be similar or identical to pumping mechanism **4152** (FIG. **41**) and/or pumping mechanism **4652** (FIG. **46**). In some embodiments, the arm can include a handle. The handle can be similar or identical to handle **4154** (FIG. **41**) and/or handle **4654** (FIG. **46**). In various embodiments, the arm can be configured to be hingedly rotated between an open configuration and a closed configuration. The open configuration can be similar or identical to the configuration shown in FIGS. **41-43** and **45** for machine **4100**, and/or the configuration shown in FIGS. **47-48** and **50** for machine **4600**. The closed

configuration can be similar or identical to the configuration shown in FIG. 44 for machine 4100 and/or the configuration shown in FIGS. 46 and 49 for machine 4600. In some embodiments, the pumping mechanism can include a button configured to control inflation of the expandable bladder. The button can be similar or identical to start/stop button 4153 (FIGS. 41, 44-45) and/or start/stop button 4653 (FIGS. 46, 49). In various embodiments, the arm can be hingedly attached to the base, such as in shown in FIGS. 46-50 for machine 4600. In a number of embodiments, method 5400 can include the providing a stand attached to the base and hingedly attached to the arm. The stand can be similar or identical to stand 4130 (FIG. 41).

(359) In various embodiments, the machine can be configured such that when the arm is in the closed configuration and the expandable bladder is inflated, the expandable bladder can press an overlay of the overlay applicator toward a screen of the electronic device to adhere an adhesive side of the overlay to the screen of the electronic device. The overlay can be similar or identical to overlay 730 (FIGS. 7, 45, 50). In some embodiments, the machine can be further configured such that when (a) the arm is in the closed configuration, (b) a pull tab of the overlay applicator is pulled to remove an adhesive release liner and expose the adhesive side of the overlay to the screen of the electronic device, and (c) the expandable bladder is inflated, the expandable bladder can be configured to press the adhesive side of the overlay against the screen of the electronic device. The pull tab can be similar or identical to pull tab 750 (FIGS. 7, 42, 44-45, 48-49).

(360) In some embodiments, method 5400 can include providing a cradle frame configured to engage with the cradle and secure the overlay applicator to the cradle. The cradle frame can be similar or identical to cradle frame 3730 (FIGS. 37, 39-40). In a number of embodiments, the cradle frame can include a bottom plate. The bottom plate can be similar or identical to bottom plate 3912 (FIGS. 39-40). In many embodiments, the bottom plate can include a crease configured to press downward on the overlay applicator to adhere the adhesive side of the overlay to the screen of the electronic device. The crease can be similar or identical to crease 3913 (FIGS. 39-40). In several embodiments, the cradle frame can include a recess. The recess can be similar or identical to recess 3916 (FIG. 39). In various embodiments, the expandable bladder can be configured to be positioned within the recess of the cradle frame when the arm is in the closed configuration. In several embodiments, the cradle frame can include alignment holes configured to engage with alignment base. The alignment holes can be similar or identical to alignment holes 3911 (FIGS. 39-40).

(361) Turning ahead in the drawings, FIG. 55 illustrates an exploded view of a dust sticker assembly 5500. Dust sticker assembly 5500 is merely exemplary and embodiments of the dust sticker assembly are not limited to embodiments presented herein. The dust sticker assembly can be employed in many different embodiments or examples not specifically depicted or described herein. In many embodiments, dust sticker assembly 5500 can include a dust removal sticker 5510 and/or a release liner 5520. In many embodiments, a bottom side of dust removal sticker 5510 can include an adhesive. In many embodiments, release liner 5520 can be attached to the bottom side of dust removal sticker 5510 and/or can cover the adhesive on the bottom side of dust removal sticker 5510. In a number of embodiments, release liner 5520 can include a device portion 5521 and an end portion 5522. Device portion 5521 and end portion 5522 can be separated at a fold line 5523. In many embodiments, fold line 5523 can be formed by a cut through release liner 5520 to form device portion 5521 and end portion 5522.

(362) Turning ahead in the drawings, FIG. 56 illustrates a bottom perspective view of dust sticker assembly 5500 and a device 5600. In a number of embodiments, dust removal sticker 5510 can be applied to device 5600 by peeling off device portion 5521 from the bottom of dust removal sticker 5510 and adhering dust removal sticker 5510 to cover the screen of device 5600. In a number of embodiments, after dust removal sticker 5510 is adhered to the screen of device 5600, end portion 5522 can extend beyond an end of the screen of device 5600.

(363) Turning ahead in the drawings, FIG. 57 illustrates a perspective view of machine 3500 (as shown in FIGS. 35-36 and described above) and dust sticker assembly 5500, which can be used together to remove dust from the screen of device 5600 (FIG. 56). Device 5600 (FIG. 56) can be placed in recess 3521 of cradle 3520. In many embodiments, dust removal sticker 5510 can be adhered to the screen of device 5600 (FIG. 56) before placing device 5600 (FIG. 56) in cradle 3520. In other embodiments, dust removal sticker 5510 can be adhered to the screen of device 5600 (FIG. 56) after placing device 5600 (FIG. 56) in

cradle 3520.

(364) Turning ahead in the drawings, FIG. 58 illustrates a perspective view of a portion of machine 3500 and dust sticker assembly 5500. FIG. 59 illustrates a perspective view of a portion of machine 3500 and dust sticker assembly 5500, with end portion of release liner 5520 being peeled away from dust removal sticker 5510. In a number of embodiments, end portion 5522 and a portion of dust removal sticker 5510 attached to end portion 5522 can be folded back at fold line 5523, as shown in FIG. 58, such that end portion 5522 of release liner 5520 (FIG. 55) can be exposed. With end portion 5522 folded back, end portion 5522 of release liner 5520 (FIG. 55) can be peeled away from dust removal sticker 5510, as shown in FIG. 59, to expose an adhesive end region 5922 of dust removal sticker 5510.

(365) Turning ahead in the drawings, FIG. 60 illustrates a perspective view of machine 3500, dust sticker assembly 5500, and an overlay applicator 6050. Overlay applicator 6050 can be similar to overlay applicator 100 (FIG. 1), overlay applicator 400 (FIGS. 4-5), overlay applicator 600 (FIG. 6), overlay applicator 700 (FIG. 7), overlay applicator 1500 (FIG. 15), overlay applicator 3000 (FIG. 30) and/or overlay applicator 3550 (FIG. 35), and various components and/or constructions of overlay applicator 6050 can be substantially identical or similar to various components of overlay applicator 100 (FIG. 1), overlay applicator 400 (FIGS. 4-5), overlay applicator 600 (FIG. 6), overlay applicator 700 (FIG. 7), overlay applicator 1500 (FIG. 15), overlay applicator 3000 (FIG. 30), and/or overlay applicator 3550 (FIG. 35). In some embodiments, overlay applicator 6050 can include an adhesive release liner (not shown), a pull tab 6055, an overlay (not shown), a protective film 6052, and/or alignment tabs 6056.

(366) In some embodiments, alignment tabs 6056 can be similar to alignment tabs 3556 (FIG. 35), and can include an alignment mechanism 6057, which can engage with alignment base 3514 to position overlay applicator 6050 so that the overlay is positioned directly above the screen of device 5600 (FIG. 56). In many embodiments, when overlay applicator 6050 is lowered onto alignment base 3514, adhesive end region 5922 can be attached to pull tab 6055, as shown in FIG. 61, described below. In some embodiments, pull tab 6055 can be integral with the adhesive release liner and can be a single layer of material, such as plastic, paper, or another suitable liner film. In many embodiments, pull tab 6055 can be inserted through pull slot 3515, which can allow pull tab 6055 to be pulled while overlay applicator 6050 is secured to machine 3500 on alignment base 3514. As pull tab 6055 is pulled, such as through pull slot 3515, adhesive end region 5922 can be pulled along with pull tab 6055, which can peel off dust removal sticker 5510 from the screen of device 5600 (FIG. 56). As dust removal sticker 5510 is peeled off the screen of device 5600 (FIG. 56), dust, dirt, and/or finger smudges can be removed from the screen of device 5600 (FIG. 56). As dust removal sticker 5510 is peeled off the screen of device 5600 (FIG. 56), the bottom, adhesive side of dust removal sticker 5510 can be folded over to face and/or attach to pull tab 6055 and/or the adhesive release liner.

(367) Turning ahead in the drawings, FIG. 61 illustrates a side elevational view of a portion of dust sticker assembly 5500 as attached to device 5600 and overlay applicator 6050. Dust removal sticker 5510 can be adhered to the screen of device 5600, and adhesive end region 5922 can be folded back at fold line 5523 and exposed such that it can be adhered to pull tab 6055, which is folded back along an adhesive release liner 6153 of overlay applicator 6050. In many embodiments, adhesive end region 5922 can be adhered to pull tab 6055 after end portion 5522 (FIG. 55) of release liner 5520 (FIG. 55) is removed from adhesive end region 5922 of dust removal sticker 5510.

(368) Turning ahead in the drawings, FIG. 62 illustrates a perspective view of a wiper 6200. Wiper 6200 is merely exemplary and embodiments of the wiper are not limited to embodiments presented herein. The wiper can be employed in many different embodiments or examples not specifically depicted or described herein. Wiper 6200 can be similar to wiper 157 (FIG. 1), wiper 457 (FIGS. 4-5), wiper 657 (FIG. 6), wiper 757 (FIG. 7), and/or wiper 2857 (FIG. 28), and various components and/or constructions of wiper 6200 can be substantially identical or similar to various components of wiper 157 (FIG. 1), wiper 457 (FIGS. 4-5), wiper 657 (FIG. 6), wiper 757 (FIG. 7), and/or wiper 2857 (FIG. 28). In many embodiments, wiper 6200 can be used with an overlay applicator, such as overlay applicator 100 (FIG. 1), overlay applicator 400 (FIGS. 4-5), overlay applicator 600 (FIG. 6), overlay applicator 700 (FIG. 7), and/or overlay applicator 3000 (FIG. 30) to remove dust, dirt, smudges, etc., from the screen of a device prior to adhering an overlay to the screen of the device. In many embodiments, wiper 6200 can be attached to a pull tab, such as pull tab 150 (FIG. 1), pull tab 450 (FIGS. 4-5), pull tab 650 (FIG. 6), pull

tab **FIG. 7**), and/or pull tab **2750** (FIGS. **27-30**).

(369) In a number of embodiments, wiper **6200** can include a wiper support **6210** and a wiper surface **6220** at a top side of wiper support **6210**. In various embodiments, an opposite bottom side of wiper support **6210** can be configured to attach to the pull tab. In many embodiments, wiper support **6210** can be made of foam or an elastomeric material. Wiper support **6210** can have sufficient thickness to ensure a close contact and/or pressure between wiper surface **6220** and the screen of the device when wiper surface **6220** is pulled across the screen of the device. In many embodiments, wiper surface **6220** can be made of a fabric (e.g., a microfiber cloth), soft silicone, an extruded rubber, or another suitable material. In a number of embodiments, wiper surface **6220** can include a slot **6230**. In some embodiments, slot **6230** can extend partially or fully through the thickness of wiper surface **6220**. In some embodiments, slot **6230** can be debossed in wiper surface **6220**. In certain embodiments, wiper surface **6220** can be as long as, or slightly longer than, the width of the screen of the device. In some embodiments, slot **6230** can be as long as the width of the screen of the device, and wiper surface **6220** can extend an additional approximately 2 mm on each side of slot **6220**. In a number of embodiments, wiper surface **6220** can have a width of approximately 10 mm, slot **6230** can have a width of approximately 2 mm, and wiper surface **6220** can extend 4 mm on each side of slot **6230**.

(370) In many embodiments, as wiper **6200** is pulled across the screen of the device, the leading edge and/or the material of wiper surface **6220** can intercept dust particles. Slot **6230** can intercept dust particles that are not intercepted by the leading edge or the material of wiper surface **6220**, such as a rounded dirt particle that rolls across wiper surface **6220**. In a number of embodiments, including slot **6230** in wiper surface **6220** can advantageously decrease the surface area of wiper surface **6220**, which can advantageously increase the pressure of the remaining surface of wiper surface **6220** on the screen of the device during wiping and forestall dust and/or dirt particles from rolling past the leading edge of wiper surface **6220** or slot **6230**.

(371) Other embodiments of wipers, such as wiper **6200**, can have additional slots. For example, FIG. **63** illustrates a perspective view of a wiper **6300**. Wiper **6300** is merely exemplary and embodiments of the wiper are not limited to embodiments presented herein. The wiper can be employed in many different embodiments or examples not specifically depicted or described herein. Wiper **6300** can be similar to wiper **157** (FIG. **1**), wiper **457** (FIGS. **4-5**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), wiper **2857** (FIG. **28**), and/or wiper **6200** (FIG. **62**), and various components and/or constructions of wiper **6200** can be substantially identical or similar to various components of wiper **157** (FIG. **1**), wiper **457** (FIGS. **4-5**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), wiper **2857** (FIG. **28**), and/or wiper **6200** (FIG. **62**). In many embodiments, wiper **6300** can include wiper support **6210** and a wiper surface **6320** at the top side of wiper support **6210**. The bottom side of wiper support **6210** can be configured to attach to a pull tab, as described above.

(372) In a number of embodiments, wiper surface **6320** can include a slot **6330** and slot **6340**. In some embodiments, slots **6330** and **6340** can extend partially across the length of wiper surface **6320**. In a number of embodiments, slot **6330** can extend across one half of the length of wiper surface **6320** and slot **6340** can extend across the other half of the length of wiper surface **6320**. In certain embodiments, slots **6330** and **6340** can each extend into an overlap region **6350**. In some embodiments, overlap region **6350** can extend approximately 4 mm. Overlap region **6350** can advantageously provide sufficient overlap in the wiping paths of slots **6330** and **6340** as slots **6330** and **6340** wipe across the screen of the device to ensure rolling dust particles roll in either slot **6330** or slot **6340**. In other embodiments, slots **6330** and **6340** can each extend across the length of wiper surface **6320** and/or the width of the screen of the device, such that rolling dust particles could be intercepted by two slots. In yet additional embodiments, slots **6330** and **6250** can be positioned in another suitable configuration and/or wiper **6300** can include additional slots.

(373) Turning ahead in the drawings, FIG. **64** illustrates a top side view of a set of cradles **6400**. Set of cradles **6400** can include a cradle **6410** for a first device, a cradle **6420** for a second device, and cradle **6430** for a third device. Cradles **6410**, **6420**, and **6430** are merely exemplary and embodiments of the cradles are not limited to embodiments presented herein. The cradles can be employed in many different embodiments or examples not specifically depicted or described herein. Cradles **6410**, **6420**, and/or **6430** can be similar to cradle **310** (FIG. **3**), cradle **832** (FIG. **8**), cradle **1620** (FIG. **16**), cradle **2032** (FIG. **20**),

cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38) and/or cradle **4630** (FIGS. 46-50), and various components and/or constructions of cradles **6410**, **6420**, and/or **6430** can be substantially identical or similar to various components of cradle **310** (FIG. 3), cradle **832** (FIG. 8), cradle **1620** (FIG. 16), cradle **2032** (FIG. 20), cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38) and/or cradle **4630** (FIGS. 46-50). Cradles **6410**, **6420**, and/or **6430** can be used with an overlay applicator, e.g., overlay applicator **3550** (FIG. 35), to apply an overlay to the screen of the device.

(374) Cradle **6410** can include a device slot **6411** in which a first device can be placed with the screen of the first device facing upwards or away from device slot **6411**. In some embodiments, device slot **6411** is conformal with the first device. Device slot **6411** can have sides **6412** and a bottom **6413**. Cradle **6410** can have a thickness greater than the thickness of device slot **6411** and/or the first device. Similarly, cradle **6420** can include a device slot **6421**, which can include sides **6422** and a bottom **6423**, and/or cradle **6430** can include a device slot **6431**, which can include sides **6432** and a bottom **6433**. Device slot **6421** can be configured to hold a second device with the screen of the second device facing upwards or away from device slot **6421**, and/or device slot **6431** can be configured to hold a third device with the screen of the third device facing upwards or away from device slot **6431**. Device slot **6421** can be conformal with the second device, and/or device slot **6431** can be conformal with the third device. Cradle **6420** can have a thickness greater than the thickness of device slot **6421** and/or the second device, and cradle **6430** can have a thickness greater than the thickness of device slot **6431** and/or the third device.

(375) In many embodiments, cradle **6410** can include an alignment base **6414**, which can engage with an alignment mechanism of the overlay applicator, such as alignment mechanism **3557** (FIG. 35) on overlay applicator **3550** (FIG. 35). In some embodiments, alignment base **6414** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **3557** (FIG. 35). For example, as shown in FIG. 35, alignment mechanism **3557** can include two holes on each of alignment tabs **3556** at each end of overlay applicator **3550**. Alignment base **6414** can include two protrusions at each end of cradle **6410** configured to engage with the two holes at each end of alignment mechanism **3557** (FIG. 35). Alignment base **6414** and alignment mechanism **3557** (FIG. 35) can be configured and positioned such that when alignment mechanism **3557** (FIG. 35) is engaged with alignment base **6414**, the overlay can be positioned directly above the screen of the first device in device slot **6411**, and aligned such that the overlay will be adhered in an accurate position on the screen when the adhesive release liner is removed. In certain embodiments, cradle **6410** can include one or more bottom apertures **6415**, which can facilitate removal of the first device from cradle **6410**.

(376) In various embodiments, cradle **6410** can include a pull slot **6416**. Pull slot **6416** can be similar to pull slot **3515** (FIG. 35). In many embodiments, pull slot **6416** can be located between device slot **6411** and one side of alignment base **6414** and can extend to the bottom and/or side of cradle **6410**. In many embodiments, a pull tab, such as pull tab **3555** (FIG. 35) can be inserted through pull slot **6416**, which can allow pull tab **3555** (FIG. 35) to be pulled while overlay applicator **3550** (FIG. 35) is secured at both ends of alignment base **6414**.

(377) Cradle **6420** can include an alignment base **6424**, and/or cradle **6430** can include an alignment base **6434**. Alignment base **6424** and/or alignment base **6434** can be similar or identical to alignment base **6414**. Cradle **6420** can include one or more bottom apertures **6425**, and/or cradle **6430** can include one or more bottom apertures **6435**. Bottom apertures **6425** and/or bottom apertures **6435** can be similar or identical to bottom apertures **6415**. Cradle **6420** can include a pull slot **6426**, and/or cradle **6430** can include a pull slot **6436**. Pull slot **6426** and/or pull slot **6436** can be similar or identical to pull slot **6416**.

(378) Set of cradles **6400** can be used with overlay applicators, such as overlay applicator **3550** (FIG. 35), to apply overlays to various different devices. For example, cradle **6410** can be configured to apply an overlay on the first device (e.g., a Samsung Galaxy S®4), cradle **6420** can be configured to apply an overlay on the second device (e.g., an Apple iPhone® 5), and cradle **6430** can be configured to apply an overlay on the third device (e.g., an Apple iPhone® 4). In other embodiments, set of cradles **6400** can include fewer or additional cradles, and/or can include cradles configured to be used with overlay applicator **3550** (FIG. 35) to apply overlays on additional devices.

(379) Turning ahead in the drawings, FIG. 65 illustrates a perspective view of overlay applicator **3550** being utilized with cradle **6410**, which is holding a device **6550**. As shown in FIG. 65, device **6550** can be inserted in device slot **6411** with the screen of device **6550** facing upwards or away from device slot

6411. Next, pull tab **3555** can be inserted in and/or lowered through pull slot **6416** until device portion **3560** of overlay applicator **3550** is positioned over the screen of device **6550**.

(380) FIG. **66** illustrates a perspective view of overlay applicator **3550** being utilized with cradle **6410**, which is holding a device **6550**. As shown in FIG. **66**, overlay applicator **3550** can be secured to cradle **6410** by engaging alignment mechanism **3557** on alignment tabs **3556** with alignment base **6414**. After overlay applicator **3550** is secured to cradle **6410**, pull tab **3555** can be pulled to remove the adhesive release liner from the bottom of the overlay and expose the adhesive on the bottom of the overlay to the screen of device **6550** (FIG. **65**). As the adhesive release liner is removed, or alternatively, after the adhesive release liner is partially or fully removed, from the overlay, the overlay can be adhered to the screen of device **6550** (FIG. **65**). In some embodiments, the overlay can be secured at the screen of device **6550** (FIG. **65**), such that adhesion can begin to occur upon removal of the adhesive release liner. After the overlay is adhered to the screen of device **6550** (FIG. **65**), device **6550** (FIG. **65**) can be removed from cradle **6410** and protective film **3552** (FIG. **35**) can be peeled off of the overlay.

(381) Turning ahead in the drawings, FIG. **67** illustrates a perspective view of set of cradles **6400**, with cradles **6410**, **6420**, and **6430** in a stacked configuration. FIG. **68** illustrates a side view of set of cradles **6400** in a stacked configuration. In a number of embodiments, each cradle in set of cradles **6400** can be stackable with the other cradles in set of cradles **6400**. In various embodiments, each cradle of set of cradles **6400** can include stacking slots (not shown) at each end on the bottom side of the cradle (e.g., **6410**, **6420**, **6430**), which can engage with an alignment base (e.g., **6414**, **6424**, **6434**) of the next lower cradle in the stacked set of cradles **6400**. For example, as shown in FIGS. **67-68**, alignment base **6414** of cradle **6410** can engage with stacking slots (not shown) on cradle **6420** to secure cradle **6420** above cradle **6410**, and alignment base **6424** of cradle **6420** can engage with stacking slots (not shown) on cradle **6430** to secure cradle **6430** above cradle **6420**, such that cradle **6410**, cradle **6420**, and cradle **6430** are stacked in a coterminous configuration. Stacking each cradle of set of cradles **6400** can advantageously save table space and allow set of cradles to be kept in a stable compact arrangement.

(382) Turning ahead in the drawings, FIG. **69** illustrates a perspective view of a machine **6900**, which can be used with an overlay applicator, such as overlay applicator **3000** (FIG. **30**), to apply an overlay, such as overlay **2930** (FIGS. **29-30**) to the screen of a device. Machine **6900** is merely exemplary and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **6900** can include a clamshell frame **6910** and a cradle **6950**. In a number of embodiments, clamshell frame **6910** can include a support base **6920**, a lid **6930**, and a hinge mechanism **6940**. In some embodiments, cradle **6950** can be removably attached to support base **6920**.

(383) Cradle **6950** can be similar to cradle **3100** (FIG. **31-34**). In some embodiments, cradle **6950** can include a bottom frame **6954**, corner frames **6951**, and/or side frames **6952**, which together can form a device slot **6956**, and which can provide support for the device and/or provide a snug fit for the device to prevent movement of the device when held by cradle **6950**. In many embodiments, cradle **6950** can include an alignment base **6953**, which can engage with alignment mechanism **2915** (FIGS. **29-30**) of overlay applicator **3000** (FIG. **30**). In some embodiments, alignment base **6953** can be one or more protrusions that can fit inside the one or more slots of alignment mechanism **2915** (FIGS. **29-30**). Alignment base **6953** and alignment mechanism **2915** (FIGS. **29-30**) can be configured and positioned such that when alignment mechanism **2915** (FIGS. **29-30**) is engaged with alignment base **6953**, overlay **2930** (FIGS. **29-30**) can be positioned directly above the screen of the device held by cradle **6950**, and aligned such that overlay **2930** (FIGS. **29-30**) can be adhered in an accurate position on the screen of the device when adhesive release liner **2740** (FIGS. **27-30**) is removed, as described below.

(384) In many embodiments, cradle **6950** can include central support **6955**. Central support **6955** can be similar to central support **3150** (FIG. **31**). In many embodiments, central support **6955** can provide support for overlay applicator **3000** (FIG. **30**). In a number of embodiments, central support **6955** can press overlay applicator **3000** (FIG. **30**) against the screen of the device as adhesive release liner **2740** (FIGS. **27-30**) is peeled away from overlay **2930** (FIGS. **29-30**), as described below.

(385) Turning ahead in the drawings, FIG. **70** illustrates a perspective view of clamshell frame **6910**. In several embodiments, support base **6920** can include a cradle support **7021**, which can securely hold cradle **6950** (FIG. **69**). In a number of embodiments, cradle **6950** (FIG. **69**) can be removably inserted in

cradle support **7021**. In other embodiments, cradle **6950** (FIG. **69**) can be fixedly attached to cradle support **7021**. In a number of embodiments, cradle support **7021** can hold various different cradles, such as cradles configured for various different devices.

(386) In various embodiments, hinge mechanism **6940** attach lid **6930** to support base **6920**, and/or can allow lid **6930** rotate with respect to support base **6920** between an open configuration, as shown in FIGS. **70-71** (FIG. **71** is described below), and a closed configuration, as shown in FIG. **72**, described below. In some embodiments, hinge mechanism **6940** can include one or more axles **7041**. In certain embodiments, axles **7041** can be secured in one or more base axle mounts **7042**, and/or can be attached to lid **6930** by one or more lid axle supports **7034**. In a number of embodiments, lid axle supports **7034** can be fixedly attached to axles **7041**. In various embodiments, hinge mechanism **6940** can include one or more springs **7043**, which can be attached to axles **7041** and support base **6920**, and which can bias lid **6930** to rotate away from support base **6920** in an open configuration, as shown in FIGS. **70-71**.

(387) In many embodiments, support base **6920** can include one or more latching slots **7022**, one or more release buttons **7023**, and/or one or more latches (not shown). Lid **6930** can include one or more catches **7032**. In a number of embodiments, when machine **6900** (FIG. **69**) is in the closed configuration, as shown in FIG. **72**, catches **7032** can be inserted inside latching slots **7022** and can be engaged with the latches to secure lid **6930** proximate to support base **6920** in the closed configuration. In various embodiments, release buttons **7023** can be pressed to release catches **7032** from the latches, which can allow lid **6930** to rotate open away from support base **6920**, so as to allow machine **6900** to open to the open configuration, as shown in FIG. **70**. As described above, hinge assembly **6940** can be spring-loaded such that, upon pressing release buttons **7023** when machine **6900** is in a closed configuration, as shown in FIG. **72**, machine **6900** (FIG. **69**) can open to an open configuration, as shown in FIGS. **70-71**. In certain embodiments, support base **6920** can include one or more bumpers **7024**, which can support one or more rear portions **7033** of lid **6930** when machine **6900** (FIG. **69**) is in an open configuration, and can prevent lid **6930** from opening further.

(388) In a number of embodiments, lid **6930** can include one or more pads **7031**. Pads **7031** can be made of foam or an elastomeric material. In a number of embodiments, pads **7031** can press the device down upon overlay applicator **2930** (FIGS. **29-30**) when machine **6900** (FIG. **69**) is in a closed configuration, as shown in FIG. **72**.

(389) Turning ahead in the drawings, FIG. **71** illustrates a perspective view of machine **6900** in an open configuration while holding a device **7100**. In the open configuration, lid **6930** can be rotated about hinge assembly **6940** away from support base **6920**. In many embodiments, cradle **6950** can be inserted and/or removed from clamshell frame **6910** while machine **6900** is in the open configuration. In several embodiments, overlay applicator **3000** (FIG. **30**) can be attached to cradle **6950** while machine **6900** is in the open configuration. Overlay applicator **3000** (FIG. **30**) can be positioned on cradle **7150** such that protective film **2920** (FIGS. **29-30**) is placed against central support **6955**, and adhesive release liner **2740** (FIGS. **27-30**) and pull tab **2750** are above protective film **2920** (FIGS. **29-30**). Pull tab **2750** (FIGS. **27-30**) can be folded back across adhesive release liner **2740** (FIGS. **27-30**), such that alignment tab **2910** (FIGS. **29-30**) is partially or fully uncovered and wiper **2857** (FIGS. **28-30**) is face up. In a number of embodiments, device **7100** can be inserted in device slot **6956** of cradle **6950**. Device **7100** can be inserted with the screen of device **7100** facing downward against overlay applicator **3000** (FIG. **30**).

(390) Turning ahead in the drawings, FIG. **72** illustrates a perspective view of machine **6900** in a closed configuration while holding device **7100**. In a closed configuration, lid **6930** can be rotated about hinge assembly **6940** proximate to support base **6920**. As described above, catches **7032** can engage with the latches in support base **6920** to securely hold machine **6900** in a closed configuration. In many embodiments, pads **7031** (FIG. **70**) can press down upon the back of device **7100** to press the screen of device **7100** against overlay applicator **3000** (FIG. **30**). In many embodiments, machine **6900** can include an end slot **7225** in clamshell frame **6910** and/or cradle **6950** through which pull tab **2750** (FIGS. **27-30**) can extend and be pulled to remove adhesive release liner **2740** (FIGS. **27-30**) from overlay **2930** (FIGS. **29-30**).

(391) Turning ahead in the drawings, FIGS. **73-74** illustrate using machine **6900** to apply overlay **2930** (FIGS. **29-30**) to the screen of device **7100** (FIG. **71**). FIG. **73** illustrates a perspective view of machine

6900 in an open configuration with overlay applicator **3000** placed on cradle **6950**. Overlay applicator **3000** can be positioned such that protective film **2920** (FIGS. 29-30) is placed against central support **6955** (FIG. 69), and adhesive release liner **2740** (FIGS. 27-30) and pull tab **2750** are above protective film **2920** (FIGS. 29-30). Pull tab **2750** can be folded back across adhesive release liner **2740** (FIGS. 27-30), such that alignment tab **2910** is partially or fully uncovered and wiper **2857** is face up. In many embodiments, alignment mechanism **2915** of alignment tab **2910** can be inserted on alignment base **6953** of cradle **6950**. Machine **6900** can be in an open configuration, with lid **6930** opened away from support base **6920** when overlay applicator **3000** is placed on cradle **6950**.

(392) In many embodiments, device **7100** can be placed in device slot **6956** (FIG. 69) of cradle **6950**. In many embodiments, device **7100** can be placed in device slot **6956** (FIG. 69) with the screen of device **7100** facing downwards. In various embodiments, the screen of device **7100** can rest against or be proximate to pull tab **2750** and/or wiper **2857**.

(393) FIG. 74 illustrates a perspective view of machine **6900** in a closed configuration holding overlay applicator **3000** (FIG. 73) and device **7100**, with pull tab **2750** being pulled. In many embodiments, lid **6930** can be lowered until catches **7032** (FIG. 70) engage with the latches in latching slots **7022** (FIG. 70), so as to change machine **6900** to a closed configuration. In many embodiments, lid **6930** can rotate with respect to support base **6920** about hinge mechanism **6940**. In a closed configuration, pads **7031** (FIG. 70) can press downward on the back of device **7100** and hold device **7100** securely within machine **6900**. In many embodiments, central support **6955** (FIG. 69) and pads **7031** (FIG. 70) can press the screen of device **7100** and overlay applicator **3000** (FIG. 73) closely together.

(394) As shown in FIG. 74, pull tab **2750** can be pulled to remove adhesive release liner **2740** (FIGS. 27-30) from the adhesive side of overlay **2930** (FIGS. 29-30). In many embodiments, as pull tab **2750** is pulled, wiper **2857** (FIG. 73) can wipe across the screen of device **7100** to remove any dust from the screen of device **7100**. In a number of embodiments, as pull tab **2750** is pulled and adhesive release liner **2740** (FIGS. 27-30) is removed, central support **6955** (FIG. 69) can be depressed slightly as the fold in adhesive release liner **2740** (FIGS. 27-30) moves from one end to the other end of device **7100**, and can rebound to provide pressure against protective film **2920** (FIGS. 29-30) to press the exposed adhesive of overlay **2930** (FIGS. 29-30) against the screen of device **7100** as it is exposed.

(395) In many embodiments, lid **6930** can next be raised so as to change machine **6900** to an open configuration. In a number of embodiments, lid **6930** can be raised by pushing release buttons **7023**, so as to release catches **7032** (FIG. 70) from the latches in latching slots **7022** (FIG. 70), such that springs **7043** (FIG. 70) cause axles **7041** (FIG. 70) to rotate and open lid **6930**. Lid **6930** can be raised to an open configuration to facilitate removal of device **7100** from cradle **6950**.

(396) In a number of embodiments, device **7100** can be removed, along with overlay **2930** (FIGS. 29-30) and protective film **2920** (FIGS. 29-30), from cradle **6950** of machine **6900**. Protective film **2920** (FIGS. 29-30) can be removed from overlay **2930** (FIGS. 29-30), which is adhered to device **7100**. After protective film **2920** (FIGS. 29-30) has been peeled away from overlay **2930** (FIGS. 29-30), application of overlay **2930** (FIGS. 29-30) to the screen of device **7100** can be complete.

(397) Proceeding to the next drawing, FIG. 75 illustrates a flow chart for an embodiment of a method **7500** of providing a machine. Method **7500** is merely exemplary and is not limited to the embodiments presented herein. Method **7500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **7500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **7500** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **7500** can be combined or skipped. In some embodiments, the machine can be similar or identical to machine **6900** (FIGS. 69-74).

(398) Referring to FIG. 75, method **7500** can include a block **7501** of providing a base. In a number of embodiments, the base can be similar or identical to support base **6920** (FIGS. 69-74). In some embodiments, the base can include a first attachment mechanism. In various embodiments, the first attachment mechanism can be similar or identical to latching slots **7022** (FIG. 70) and/or release buttons **7023** (FIGS. 70, 72).

(399) In many embodiments, method **7500** next can include a block **7502** of providing a first cradle. The

cradle can be similar or identical to cradle **3100** (FIGS. **31-34**) and/or **6950** (FIGS. **69, 71-73**). In several embodiments, the cradle can be configured to hold a first electronic device. The first electronic device can be similar or identical to device **7100** (FIG. **71-72, 74**). In some embodiments, the first cradle can be integral with the base. In other embodiments, the first cradle can be removable from the base. In a number of embodiments, the base can be configured to hold a second cradle different from the first cradle. The second cradle can be similar or identical to cradle **3100** (FIGS. **31-34**) and/or cradle **6950** (FIGS. **69, 71-72**). The second cradle can be configured to hold a second electronic device having one or more different dimensions than the first electronic device.

(400) In various embodiments, method **7500** next can include a block **7503** of providing an alignment base. The alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), and/or alignment base **6953** (FIGS. **69, 73**). In some embodiments, the first cradle can include the alignment base. In a number of embodiments, the base can include the alignment base.

(401) In several embodiments, the alignment base can be configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**). In many embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), and/or alignment mechanism **3557** (FIGS. **35-36**). The overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**). In several embodiments, the alignment base can be configured to align the overlay applicator as the overlay of the overlay applicator is applied to the screen of the first electronic device.

(402) In some embodiments, the first cradle can include one or more frame pieces configured to securely hold the first electronic device in a device slot in a fixed position with respect to the alignment base. The one or more frame pieces can be similar or identical to bottom frame **6954** (FIG. **69**), corner frames **6951** (FIG. **69**), and/or side frames **6952** (FIG. **69**). The device slot can be similar or identical to device slot **6956** (FIG. **69**). In some embodiments, the one or more frame pieces can include four corner frames located at each corner of the first cradle. For example, the four corner frames can be similar or identical to corner frames **6951** (FIG. **69**). In a number of embodiments, the machine can be configured to hold the overlay applicator between the first cradle and the screen of the electronic device when the screen of the first electronic device is facing toward the first cradle, such as shown in FIG. **71**, for example.

(403) In many embodiments, method **7500** next can include a block **7504** of providing a lid. The lid can be similar or identical to lid **6930** (FIGS. **69-74**). In some embodiments, the lid can be hingedly attached to the base. For example, the lid can be hingedly attached to the base at hinge mechanism **6940** (FIGS. **69-72, 74**). In several embodiments, the machine can be configured such that the lid can be rotated with respect to the base between an open configuration, as shown in FIGS. **69-71** and **73**, and a closed configuration, as shown in FIGS. **72** and **74**. In many embodiments, the machine can be configured in the closed configuration to facilitate applying the overlay of the overlay applicator to the screen of the first electronic device.

(404) In many embodiments, the machine can be configured in the open configuration such that the overlay applicator and the first electronic device can be inserted and removed from the machine. In some embodiments, the machine can be configured in the closed configuration to prevent removal of the first electronic device and at least a portion of the overlay applicator from the machine. In various embodiments, the machine can be configured in the closed configuration such that a pull tab of the overlay applicator can be pulled to remove an adhesive release liner of the overlay applicator from the

overlay to expose an adhesive agent of the overlay to the screen of the first electronic device. The pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), pull tab **750** (FIGS. 7, 42, 44-45, 48-49), pull tab **1550** (FIG. 15), pull tab **2750** (FIGS. 27-30) and/or pull tab **6055** (FIG. 60). The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7), adhesive release liner **1540** (FIG. 15), and/or adhesive release liner **2740** (FIGS. 27-30).

(405) In some embodiments, the lid can include one or more pads configured to press the first electronic device toward the overlay applicator when (a) the first electronic device is in first cradle, (b) the overlay applicator is engaged with the alignment base, and (c) the machine is in the closed configuration. In various embodiments, the lid can include a second attachment mechanism configured to removably attach to the first attachment mechanism to hold the lid in the closed configuration. The second attachment mechanism can be similar or identical to catches **7032**.

(406) In various embodiments, the first cradle can include a support piece extending in a first direction. The support piece can be similar or identical to central support **3150** (FIG. 31) and/or central support **6955**. In many embodiments, the support piece can include an elastomeric material. The support piece can be configured to press the adhesive agent of the overlay of the overlay applicator toward the screen of the first electronic device when the screen of the first electronic device is facing toward the support piece and the adhesive release liner of the overlay applicator is removed to expose the adhesive agent of the overlay to the screen of the first electronic device. In a number of embodiments, the support piece can be configured to press a wiper of the pull tab toward the screen of the first electronic device as the wiper moves across the screen of the electronic device in first direction when the pull tab is pulled in the first direction. The wiper can be similar or identical to wiper **157** (FIG. 1), wiper **457** (FIG. 4), wiper **657** (FIG. 6), wiper **757** (FIG. 7), wiper **2857** (FIGS. 28-30), wiper **6200** (FIG. 62), and/or wiper **6300** (FIG. 63).

(407) Proceeding to the next drawing, FIG. 76 illustrates a flow chart for an embodiment of a method **7600** of providing a cradle. Method **7600** is merely exemplary and is not limited to the embodiments presented herein. Method **7600** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **7600** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **7600** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **7600** can be combined or skipped. In some embodiments, the cradle can be similar or identical to cradle **6410** (FIGS. 64-68), cradle **6420** (FIGS. 64, 67-68), and/or cradle **6430** (FIGS. 64, 67-68).

(408) Referring to FIG. 76, method **7600** can include a block **7601** of providing a device slot. In a number of embodiments, the device slot can be similar or identical to device slot **6411** (FIG. 64), device slot **6421** (FIG. 64), and/or device slot **6431** (FIG. 64). In many embodiments, the device slot can be configured to securely hold an electronic device. The electronic device can be similar or identical to device **6550**.

(409) In many embodiments, method **7600** next can include a block **7602** of providing an alignment base. The alignment base can be similar or identical to alignment base **212** (FIG. 2), alignment base **312** (FIG. 3), alignment base **835** (FIGS. 8-9, 13-14), alignment base **1632** (FIGS. 16-19), alignment base **2035** (FIG. 20), alignment base **3112** (FIGS. 31-34), alignment base **3514** (FIGS. 35-36), alignment base **3814** (FIG. 38), alignment base **4734** (FIG. 47), alignment base **6414** (FIG. 64), alignment base **6424** (FIG. 64), alignment base **6434** (FIG. 64), and/or alignment base **6953** (FIGS. 69, 73). In several embodiments, the alignment base can be configured to engage with an alignment mechanism of an overlay applicator. The overlay applicator can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), and/or overlay applicator **6050** (FIG. 60). In many embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. 1), alignment mechanism **415** (FIG. 4), alignment mechanism **615** (FIG. 6), alignment mechanism **715** (FIG. 7), alignment mechanism **1515** (FIG. 15), alignment mechanism **2915** (FIGS. 29-30), and/or alignment mechanism **3557** (FIGS. 35-36).

(410) In a number of embodiments, the overlay applicator can include a first alignment tab and a second

alignment tab. The first alignment tab can include a first portion of the alignment mechanism. The second alignment tab can include the second portion of the alignment mechanism. In a number of embodiments, the alignment base can include a first side configured to engage with the first portion of the alignment mechanism of the overlay applicator and a second side configured to engage with the second portion of the alignment mechanism of the overlay applicator. The first and second sides of the alignment base can be similar or identical to alignment base **3514**.

(411) In many embodiments, method **7600** next can include a block **7603** of providing a first pull slot. The first pull slot can be similar or identical to pull slot **3515** (FIGS. **35-36**), pull slot **6416** (FIGS. **64-65**), pull slot **6426** (FIG. **64**), and/or pull slot **6436** (FIG. **64**). In a number of embodiments, the pull slot can be disposed between the device slot and the second side of the alignment base. In various embodiments, the cradle can be configured, when the electronic device is held within the device slot with a screen of the electronic device facing upwards or away from the device slot and/or the cradle, to hold the overlay applicator over the electronic device such that a pull tab of the overlay applicator can be pulled through the pull slot to expose an overlay of the overlay applicator to the screen of the electronic device. The pull tab can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIGS. **7, 42, 44-45, 48-49**), pull tab **1550** (FIG. **15**), pull tab **2750** (FIGS. **27-30**) and/or pull tab **6055** (FIG. **60**). The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**).

(412) Proceeding to the next drawing, FIG. **77** illustrates a flow chart for an embodiment of a method **7700** of providing a set of cradles. Method **7700** is merely exemplary and is not limited to the embodiments presented herein. Method **7700** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **7700** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **7700** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **7700** can be combined or skipped. In some embodiments, the set of cradles can be similar or identical to set of cradles **6400** (FIGS. **64, 67-68**).

(413) Referring to FIG. **77**, method **7700** can include a block **7701** of providing a first cradle. The first cradle can be similar or identical to cradle **6410** (FIGS. **64-68**), cradle **6420** (FIGS. **64, 67-68**), and/or cradle **6430** (FIGS. **64, 67-68**). In a number of embodiments, the first cradle can include a first device slot having first dimensions. In a number of embodiments, the first device slot can be similar or identical to device slot **6411** (FIG. **64**), device slot **6421** (FIG. **64**), and/or device slot **6431** (FIG. **64**). In many embodiments, the first device slot can be configured to securely hold a first electronic device. The first electronic device can be similar or identical to device **6550**.

(414) In various embodiments, the first cradle can include a first alignment base. The first alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), and/or alignment base **6953** (FIGS. **69, 73**). In several embodiments, the first alignment base can be configured to engage with an alignment mechanism of a first overlay applicator. The first overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**). In many embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), and/or alignment mechanism **3557** (FIGS. **35-36**). In a number of embodiments, the first overlay applicator can include an overlay configured to be applied to a screen of the first electronic device. The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**).

(415) In a number of embodiments, the first alignment base can include a first side and a second side.

The first and second sides of the first alignment base can be similar or identical to alignment base **3514**. The first side of the first alignment base can be configured to engage with a first portion of the alignment mechanism of the first overlay applicator. The second side of the first alignment base can be configured to engage with a second portion of the alignment mechanism of the first overlay applicator. The first and second portions of the alignment mechanism can be similar or identical to alignment tabs **3556** and/or alignment mechanisms **3557**. In several embodiments, the first device slot can be disposed between the first side of the first alignment base and the second side of the first alignment base.

(416) In many embodiments, the first cradle can further include a first pull slot. The first pull slot can be similar or identical to pull slot **3515** (FIGS. **35-36**), pull slot **6416** (FIGS. **64-65**), pull slot **6426** (FIG. **64**), and/or pull slot **6436** (FIG. **64**). In a number of embodiments, the first pull slot can be disposed between the first device slot and the second side of the first alignment base.

(417) In various embodiments, the first cradle can be configured, when the first electronic device is held within the first device slot with the screen of the first electronic device facing upwards or away from the first device slot and/or the first cradle, to hold the first overlay applicator over the first electronic device such that a pull tab of the first overlay applicator can be pulled through the first pull slot to expose the overlay of the first overlay applicator to the screen of the first electronic device. The pull tab of the first overlay applicator can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIGS. **7, 42, 44-45, 48-49**), pull tab **1550** (FIG. **15**), pull tab **2750** (FIGS. **27-30**) and/or pull tab **6055** (FIG. **60**).

(418) In many embodiments, method **7700** next can include a block **7702** of providing a second cradle. The second cradle can be similar or identical to cradle **6410** (FIGS. **64-68**), cradle **6420** (FIGS. **64, 67-68**), and/or cradle **6430** (FIGS. **64, 67-68**). In a number of embodiments, the second cradle can include a second device slot having second dimensions. In many embodiments, the first dimensions of the first device slot of the first cradle can be different from the second dimensions of the second device slot of the second cradle. In a number of embodiments, the second device slot can be similar or identical to device slot **6411** (FIG. **64**), device slot **6421** (FIG. **64**), and/or device slot **6431** (FIG. **64**). In many embodiments, the second device slot can be configured to securely hold a second electronic device. The second electronic device can be similar or identical to device **6550**. In many embodiments, the first cradle and the second cradle can be configured to be stacked in a first coterminous configuration, such as shown in FIGS. **67-68**, for example.

(419) In various embodiments, the second cradle can include a second alignment base. The second alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), and/or alignment base **6953** (FIGS. **69, 73**). In several embodiments, the second alignment base can be configured to engage with an alignment mechanism of a second overlay applicator. The second overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**). In many embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), and/or alignment mechanism **3557** (FIGS. **35-36**). In a number of embodiments, the second overlay applicator can include an overlay configured to be applied to a screen of the second electronic device. The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**).

(420) In a number of embodiments, the second alignment base can include a first side and a second side. The first and second sides of the second alignment base can be similar or identical to alignment base **3514**. The first side of the second alignment base can be configured to engage with a first portion of the alignment mechanism of the second overlay applicator. The second side of the second alignment base can be configured to engage with a second portion of the alignment mechanism of the second overlay

applicator. The first and second portions of the alignment mechanism can be similar or identical to alignment tabs **3556** and/or alignment mechanisms **3557**. In several embodiments, the second device slot can be disposed between the first side of the second alignment base and the second side of the second alignment base.

(421) In many embodiments, the second cradle can further include a second pull slot. The second pull slot can be similar or identical to pull slot **3515** (FIGS. **35-36**), pull slot **6416** (FIGS. **64-65**), pull slot **6426** (FIG. **64**), and/or pull slot **6436** (FIG. **64**). In a number of embodiments, the second pull slot can be disposed between the second device slot and the second side of the second alignment base.

(422) In various embodiments, the second cradle can be configured, when the second electronic device is held within the second device slot with the screen of the second electronic device facing upwards or away from the second device slot and/or the second cradle, to hold the second overlay applicator over the second electronic device such that a pull tab of the second overlay applicator can be pulled through the second pull slot to expose the overlay of the second overlay applicator to the screen of the second electronic device. The pull tab of the second overlay applicator can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIGS. **7, 42, 44-45, 48-49**), pull tab **1550** (FIG. **15**), pull tab **2750** (FIGS. **27-30**) and/or pull tab **6055** (FIG. **60**).

(423) In some embodiments, method **7700** optionally can include a block **7703** of providing a third cradle. The third cradle can be similar or identical to cradle **6410** (FIGS. **64-68**), cradle **6420** (FIGS. **64, 67-68**), and/or cradle **6430** (FIGS. **64, 67-68**). In a number of embodiments, the third cradle can include a third device slot having third dimensions. In many embodiments, the third dimensions of the third device slot of the third cradle can be different from the first dimensions of the first device slot of the first cradle and the second dimensions of the second device slot of the second cradle. In a number of embodiments, the third device slot can be similar or identical to device slot **6411** (FIG. **64**), device slot **6421** (FIG. **64**), and/or device slot **6431** (FIG. **64**). In many embodiments, the third device slot can be configured to securely hold a third electronic device. The third electronic device can be similar or identical to device **6550**. In many embodiments, the third cradle can be configured to be stacked with the first cradle and the second cradle in a second coterminous configuration, such as shown in FIGS. **67-68**, for example.

(424) In various embodiments, the third cradle can include a third alignment base. The third alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), and/or alignment base **6953** (FIGS. **69, 73**). In several embodiments, the third alignment base can be configured to engage with an alignment mechanism of a third overlay applicator. The third overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**). In many embodiments, the alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), and/or alignment mechanism **3557**. In a number of embodiments, the third overlay applicator can include an overlay configured to be applied to a screen of the third electronic device. The overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**).

(425) Turning ahead in the drawings, FIG. **78** illustrates a flow chart for an embodiment of a method **7800** of providing an overlay applicator. Method **7800** is merely exemplary and is not limited to the embodiments presented herein. Method **7800** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **7800** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **7800** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **7800** can be combined or skipped. In some embodiments, the overlay applicator

can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), and/or overlay applicator **6050** (FIG. 60).

(426) Referring to FIG. 78, method **7800** can include a block **7801** of providing an overlay. In many embodiments, the overlay can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15), and/or overlay **2930** (FIGS. 29-30). In a number of embodiments, the overlay can have a top side and a bottom side. The top side of the overlay can be similar or identical to top side **131** (FIG. 1) of overlay **130** (FIG. 1). The bottom side of the overlay can be similar or identical to bottom side **132** (FIG. 1) of overlay **130** (FIG. 1). In various embodiments, the bottom side can include an adhesive agent configured to adhere to a screen of an electronic device.

(427) In some embodiments, method **7800** next can include a block **7802** of providing an adhesive release liner. The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7), adhesive release liner **1540** (FIG. 15), and/or adhesive release liner **2740** (FIGS. 27-30). In a number of embodiments, the adhesive release liner can have a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. In some embodiments, the adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants.

(428) In many embodiments, method **7800** next can include a block **7803** of providing an alignment tab. In some embodiments, the alignment tab can be similar or identical to alignment tab **110** (FIG. 1), alignment tab **410** (FIGS. 4-5), alignment tab **610** (FIG. 6), alignment frame **710** (FIG. 7), and/or alignment flaps **1510** (FIG. 15), alignment tab **2910** (FIGS. 29-30), and/or alignment tab **3556** (FIGS. 35-36). In many embodiments, the alignment tab can include an alignment mechanism. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. 1), alignment mechanism **415** (FIG. 4), alignment mechanism **615** (FIG. 6), alignment mechanism **715** (FIG. 7), alignment mechanism **1515** (FIG. 15), alignment mechanism **2915** (FIGS. 29-30), and/or alignment mechanism **3557** (FIGS. 35-36).

(429) In several embodiments, method **7800** next can include a block **7804** of providing a pull tab. In some embodiments, the pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), pull tab **750** (FIGS. 7, 42, 44-45, 48-49), pull tab **1550** (FIG. 15), pull tab **2750** (FIGS. 27-30) and/or pull tab **6055** (FIG. 60).

(430) In many embodiments, method **7800** next can include a block **7805** of providing a wiper. The wiper can be similar or identical to wiper **157** (FIG. 1), wiper **457** (FIG. 4), wiper **657** (FIG. 6), wiper **757** (FIG. 7), wiper **2857** (FIGS. 28-30), wiper **6200** (FIG. 62), and/or wiper **6300** (FIG. 63). In some embodiments, the wiper can include a surface. The surface can be similar or identical to wiper surface **6220** (FIG. 62) and/or wiper surface **6320** (FIG. 62). In several embodiments, the wiper can include a first slot. The first slot can be similar or identical to slot **6230** (FIG. 62), slot **6330** (FIG. 63), and/or slot **6340** (FIG. 63). In many embodiments, the first slot can extend at least partially through the surface of the wiper. In a number of embodiments, the wiper can include a second slot. The second slot can be similar or identical to slot **6230** (FIG. 62), slot **6330** (FIG. 63), and/or slot **6340** (FIG. 63). In many embodiments, the second slot can extend at least partially through the surface of the wiper. In some embodiments, the wiper can include a support portion disposed between the surface of the wiper and the pull tab. The support portion can be similar or identical to wiper support **6210** (FIGS. 62-63).

(431) In a number of embodiments, method **7800** next can include a block **7806** of attaching the wiper to the pull tab. In several embodiments, the wiper can be attached to the pull tab with an adhesive. In many embodiments, the pull tab, the wiper, and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner and can be pulled to remove the adhesive release liner from the bottom side of the overlay to expose the adhesive agent. In various embodiments, the pull tab, the wiper, and the adhesive release liner can be configured such that, when the pull tab is pulled, the wiper can wipe across and clean the screen of the electronic device.

(432) In some embodiments, method **7800** optionally can include a block **7807** of providing a protective

film. In some embodiments, the protective film can be similar or identical to protective film **120** (FIG. **1**), protective film **420** (FIGS. **4-5**), protective film **620** (FIG. **6**), protective film **720** (FIG. **7**), protective film **1520** (FIG. **15**), protective film **2920** (FIGS. **29-30**), protective film **3552** (FIG. **35**), and/or protective film **6052** (FIG. **60**). In many embodiments, the protective film can be removably attached to the top side of the overlay.

(433) Proceeding to the next drawing, FIG. **79** illustrates a flow chart for an embodiment of a method **7900** of providing a system. Method **7900** is merely exemplary and is not limited to the embodiments presented herein. Method **7900** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **7900** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **7900** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **7900** can be combined or skipped.

(434) Referring to FIG. **79**, method **7900** can include a block **7901** of providing an overlay applicator. In many embodiments, the overlay applicator can be similar or identical to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**). In a number of embodiments, the overlay applicator can include an overlay. In many embodiments, the overlay can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**). In a number of embodiments, the overlay can have a top side and a bottom side. The top side of the overlay can be similar or identical to top side **131** (FIG. **1**) of overlay **130** (FIG. **1**). The bottom side of the overlay can be similar or identical to bottom side **132** (FIG. **1**) of overlay **130** (FIG. **1**). In various embodiments, the bottom side can include an adhesive agent configured to adhere to a screen of an electronic device.

(435) In several embodiments, the overlay applicator can include an adhesive release liner. The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**), adhesive release liner **1540** (FIG. **15**), and/or adhesive release liner **2740** (FIGS. **27-30**). In a number of embodiments, the adhesive release liner can have a top side and a bottom side. The top side of the adhesive release liner can be removably attached to the bottom side of the overlay. In some embodiments, the adhesive release liner can be configured to protect the adhesive agent at the bottom side of the overlay from contaminants.

(436) In some embodiments, the overlay applicator can include a protective film. The protective film can be similar or identical to protective film **120** (FIG. **1**), protective film **420** (FIGS. **4-5**), protective film **620** (FIG. **6**), protective film **720** (FIG. **7**), protective film **1520** (FIG. **15**), protective film **2920** (FIGS. **29-30**), protective film **3552** (FIG. **35**), and/or protective film **6052** (FIG. **60**). In many embodiments, the protective film can be removably attached to the top side of the overlay.

(437) In many embodiments, the overlay applicator can include an alignment tab. In some embodiments, the alignment tab can be similar or identical to alignment tab **110** (FIG. **1**), alignment tab **410** (FIGS. **4-5**), alignment tab **610** (FIG. **6**), alignment frame **710** (FIG. **7**), and/or alignment flaps **1510** (FIG. **15**), alignment tab **2910** (FIGS. **29-30**), and/or alignment tab **3556** (FIGS. **35-36**). In many embodiments, the alignment tab can include an alignment mechanism. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), and/or alignment mechanism **3557** (FIGS. **35-36**). In many embodiments, the alignment tab can include a first alignment portion extending at and/or toward a first end of the overlay applicator; and a second alignment portion extending at and/or toward a second end of the overlay applicator. The first alignment portion and the second alignment portion can include the alignment mechanism.

(438) In some embodiments, the alignment tab can be configured to engage with an alignment base. The alignment base can be similar or identical to alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG.

38), alignment base **4734** (FIG. 47), alignment base **6414** (FIG. 64), alignment base **6424** (FIG. 64), alignment base **6434** (FIG. 64), and/or alignment base **6953** (FIGS. 69, 73). The alignment base can include a first portion and a second portion. The first alignment portion can be configured to engage with the first portion of the alignment base. The second alignment portion can be configured to engage with the second portion of the alignment base. The first and second portions of the alignment mechanism can be similar or identical to alignment mechanisms **3557** and/or alignment mechanisms **6057** (FIG. 60) (439) In various embodiments, the overlay applicator can include a pull tab. In some embodiments, the pull tab can be similar or identical to pull tab **150** (FIG. 1), pull tab **450** (FIGS. 4-5), pull tab **650** (FIG. 6), pull tab **750** (FIGS. 7, 42, 44-45, 48-49), pull tab **1550** (FIG. 15), pull tab **2750** (FIGS. 27-30) and/or pull tab **6055** (FIG. 60).

(440) In many embodiments, method **7900** next can include a block **7902** of providing a sticker assembly. In some embodiments, the sticker assembly can be similar or identical to dust sticker assembly **5500** (FIGS. 55-61). In several embodiments, the sticker assembly can include a sticker. The sticker can be similar or identical to dust removal sticker **5510** (FIGS. 55-61). The sticker can include a top side and a bottom side and an end portion. The end portion of the sticker can be similar or identical to adhesive end region **5922** (FIGS. 59-61). The bottom side can include a second adhesive agent configured to removably adhere to the screen of the electronic device.

(441) In some embodiments, the sticker assembly can include a release liner. The release liner can be similar or identical to release liner **5520** (FIG. 55). In many embodiments, the release liner can be removably attached to the bottom side of the sticker. In some embodiments, the release liner can include a device portion and an end portion. The device portion can be similar or identical to device portion **5521** (FIGS. 55-56). The end portion of the release liner can be similar or identical to **5522** (FIGS. 55-56, 58-59). In several embodiments, the end portion of the release liner can be removably attached to the end portion of the sticker, such as shown in FIGS. 56 and 58-59.

(442) In many embodiments, the sticker assembly can be configured such that, when the device portion of the release liner is removed to expose the second adhesive agent, such as shown in FIG. 56, the second adhesive agent of the bottom side of the sticker can be adhered to the screen of the electronic device, and the end portion of the sticker can be folded back over the top side of the sticker to expose the end portion of the release liner, such as shown in FIG. 58. In a number of embodiments, the pull tab and the adhesive release liner can be configured such that the pull tab can be folded across the bottom side of the adhesive release liner, such as shown in FIGS. 60-61. In some embodiments, the sticker assembly can be configured such that, when the end portion of the sticker is folded back over the top side of the sticker and the end portion of the release liner is removed from the sticker to expose the second adhesive agent, such as shown in FIG. 59, the end portion of the sticker can be adhered to the pull tab while the pull tab is folded across the bottom side of the adhesive release liner, such as shown in FIG. 60-61. In several embodiments, the overlay applicator and sticker assembly can be configured such that, when the end portion of the sticker is adhered to the pull tab, the pull tab can be pulled to remove the sticker from the screen of the electronic device and to remove the adhesive release liner from the bottom side of the overlay to expose the first adhesive agent to the screen of the device. In a number of embodiments, the sticker can be configured to remove dust from the screen of the electronic device when the sticker is removed from the screen of the electronic device.

(443) In certain embodiments, the overlay applicator and the sticker assembly can be configured such that, when the pull tab is pulled to remove the sticker from the screen of the electronic device and to remove the adhesive release liner from the bottom side of the overlay, at least a portion of the sticker is adhered to at least a portion of the adhesive release liner. In many embodiments, the overlay applicator and the sticker assembly can be configured such that, when (a) the first alignment portion is engaged with the first portion of the alignment base, (b) the second alignment portion is engaged with the second portion of the alignment base, and (c) the pull tab is pulled, the pull tab, the sticker, and the adhesive release liner can be pulled through a pull slot. The pull slot can be similar or identical to pull slot **3515** (FIGS. 35-36), pull slot **6416** (FIGS. 64-65), pull slot **6426** (FIG. 64), and/or pull slot **6436** (FIG. 64).

(444) Turning ahead in the drawings, FIG. 80 illustrates a top, front, right side perspective view of an overlay applicator tray **8000**, according to another embodiment. FIG. 81 illustrates a front side elevational view of overlay applicator tray **8000**. FIG. 82 illustrates an enlarged front side elevational

view of a portion of overlay applicator tray **8000**, as identified in FIG. **81**. FIG. **95** illustrates an enlarged front side elevational view of a portion of an overlay applicator **8001** of overlay applicator tray **8000**, as identified in FIG. **82**. Overlay applicator tray **8000** is merely exemplary, and embodiments of the overlay applicator tray are not limited to the embodiments presented herein. The overlay applicator tray can be employed in many different embodiments or examples not specifically depicted or described herein.

(445) In various embodiments, overlay applicator tray **8000** can include overlay applicator **8001**, a cradle **8080**, and/or an alignment piece **8010**. In many embodiments, overlay applicator **8001** can be similar to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**), and various components and/or constructions of overlay applicator **8001** can be substantially identical or similar to various components of overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), and/or overlay applicator **6050** (FIG. **60**).

(446) In a number of embodiments, overlay applicator **8001** can include an overlay **8230** (FIG. **82**). In many embodiments, overlay **8230** (FIG. **82**) can be similar or identical to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), and/or overlay **2930** (FIGS. **29-30**). In a number of embodiments, overlay **8230** (FIG. **82**) can have a top side **9531** (FIG. **95**) and a bottom side **9532** (FIG. **95**). Top side **9531** (FIG. **95**) of overlay **8230** (FIG. **82**) can be similar or identical to top side **131** (FIG. **1**) of overlay **130** (FIG. **1**). Bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) can be similar or identical to bottom side **132** (FIG. **1**) of overlay **130** (FIG. **1**). In various embodiments, bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) can include an adhesive configured to adhere overlay **8230** (FIG. **82**) to a screen of an electronic device.

(447) In several embodiments, overlay applicator **8001** can include an adhesive release liner **8240** (FIG. **82**). Adhesive release liner **8240** (FIG. **82**) can be similar or identical to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**), adhesive release liner **1540** (FIG. **15**), and/or adhesive release liner **2740** (FIGS. **27-30**). In a number of embodiments, adhesive release liner **8240** (FIG. **82**) can have a top side **9541** (FIG. **95**) and a bottom side **9542** (FIG. **95**). Top side **9541** (FIG. **95**) of adhesive release **8240** (FIG. **82**) liner can be removably attached to bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) to cover, and be removed to expose, the adhesive at bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**). In some embodiments, adhesive release liner **8240** (FIG. **82**) can be configured to protect the adhesive agent at or on bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) from contaminants.

(448) In some embodiments, overlay applicator **8001** can include a protective film **8020**. Protective film **8020** can be similar or identical to protective film **120** (FIG. **1**), protective film **420** (FIGS. **4-5**), protective film **620** (FIG. **6**), protective film **720** (FIG. **7**), protective film **1520** (FIG. **15**), protective film **2920** (FIGS. **29-30**), protective film **3552** (FIG. **35**), and/or protective film **6052** (FIG. **60**). In many embodiments, protective film **8020** can have a top side **9521** (FIG. **95**) and a bottom side **9522** (FIG. **95**). In a number of embodiments, protective film **8020** can be removably attached to top side **9531** (FIG. **95**) of overlay **8230** (FIG. **82**). For example, bottom side **9522** (FIG. **95**) of protective film **8020** can be removably attached to top side **9531** (FIG. **95**) of overlay **8230** (FIG. **82**), such as with an adhesive at or on bottom side **9522** (FIG. **95**) of protective film **8020**.

(449) In several embodiments, overlay applicator **8001** can include a first pull tab **8042** and/or a second pull tab **8022**. In a number of embodiments, first pull tab **8042** can be used to remove adhesive release liner **8240** (FIG. **82**) from overlay **8230** (FIG. **82**). In many embodiments, first pull tab **8042** can advantageously help prevent accidental touching of the adhesive at or on bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) when removing adhesive release liner **8240** (FIG. **82**) from overlay **8230** (FIG. **82**). In several embodiments, first pull tab **8042** can be affixed to bottom side **9542** (FIG. **95**) of adhesive release liner **8240** (FIG. **82**), such as shown in FIG. **82**. In other embodiments, first pull tab **8042** can be integral with adhesive release liner **8240** (FIG. **82**). In many embodiments, first pull tab **8042** can be adhered to bottom side **9542** (FIG. **95**) of adhesive release liner **8240** (FIG. **82**) with an adhesive or another suitable fastener. In a number of embodiments, the adhesive adhering first pull tab **8042** to

adhesive release liner **8240** (FIG. **82**) can have a greater adhesive strength than the adhesive at or on bottom side **9532** (FIG. **95**) of overlay **8230** (FIG. **82**) that adheres adhesive release liner **8240** (FIG. **82**) to overlay **8230** (FIG. **82**), such that first pull tab **8042** can be used to pull and remove adhesive release liner **8240** (FIG. **82**) from overlay **8230** (FIG. **82**) without first pull tab **8042** being removed from adhesive release liner **8240** (FIG. **82**).

(450) In a number of embodiments, second pull tab **8022** can be used to remove protective film **8020** from overlay **8230** (FIG. **82**). In many embodiments, second pull tab **8022** can be affixed to top side **9521** (FIG. **95**) of protective film **8020**, such as shown in FIG. **82**. In other embodiments, second pull tab **8022** can be integral with protective film **8020**. In many embodiments, second pull tab **8022** can be adhered to top side **9521** (FIG. **95**) of protective film **8020** with an adhesive or another suitable fastener. In a number of embodiments, the adhesive adhering second pull tab **8022** to protective film **8020** can have a greater adhesive strength than the adhesive at or on bottom side **9522** (FIG. **95**) of protective film **8020** that adheres protective film **8020** to overlay **8230** (FIG. **82**), such that second pull tab **8022** can be used to pull and remove protective film **8020** from overlay **8230** (FIG. **82**) without second pull tab **8022** being removed from protective film **8020**.

(451) In many embodiments, cradle **8080** can be similar to cradle **310** (FIG. **3**), cradle **832** (FIG. **8**), cradle **1620** (FIG. **16**), cradle **2032** (FIG. **20**), cradle **3100** (FIG. **31**), cradle **3520** (FIG. **35**), cradle **3710** (FIGS. **37-38**), cradle **4630** (FIGS. **46-50**), cradle **6410** (FIG. **64**), cradle **6420** (FIG. **64**), cradle **6430** (FIG. **64**), and/or cradle **6950** (FIG. **69**), and various components and/or constructions of cradle **8080** can be substantially identical or similar to various components of cradle **310** (FIG. **3**), cradle **832** (FIG. **8**), cradle **1620** (FIG. **16**), cradle **2032** (FIG. **20**), cradle **3100** (FIG. **31**), cradle **3520** (FIG. **35**), cradle **3710** (FIGS. **37-38**), cradle **4630** (FIGS. **46-50**), cradle **6410** (FIG. **64**), cradle **6420** (FIG. **64**), cradle **6430** (FIG. **64**), and/or cradle **6950** (FIG. **69**).

(452) In several embodiments, cradle **8080** can include a device slot **8090**. Device slot can be similar to slot **311** (FIG. **3**), slot **1621** (FIG. **16**), device slot **3111** (FIG. **31**), slot **3811** (FIG. **38**), slot **4731** (FIG. **47**), device slot **6411** (FIG. **64**), device slot **6421** (FIG. **64**), device slot **6431** (FIG. **64**), and/or device slot **6956** (FIG. **69**). In many embodiments, device slot **8090** can be configured to securely hold an electronic device in device slot **8090**. In many embodiments, the electronic device can be similar or identical to device **220** (FIG. **2**), device **320** (FIG. **3**), device **1650** (FIG. **16**), device **3401** (FIG. **34**), device **3720** (FIG. **37**), device **4800** (FIG. **48**), device **5600** (FIG. **56**), device **6550** (FIG. **65**), device **7100**, and/or electronic device **8350** (shown in FIG. **83** and described below). For example, the electronic device can be a smart phone, a tablet, a smart watch (such as electronic device **8350**, shown in FIG. **83** and described below), or another suitable electronic device. In several embodiments, cradle **8080** can be configured for a specific type of electronic device, such as the 38 mm Apple Watch. The watch band of the Apple Watch can be removed before the Apple Watch is positioned in the device slot **8090**. For example, device slot **8090** can be configured to hold an electronic device having the dimensions of the specific type of electronic device.

(453) In many embodiments, the electronic device can be placed within device slot **8090** with a screen of the electronic device facing upwards or away from device slot **8090**. In other embodiments, the electronic device can be placed within device slot **8090** with the screen of the electronic device facing downwards or towards device slot **8090**. In some embodiments, device slot **8090** can be conformal with the electronic device. In a number of embodiments, device slot **8090** can include one or more side walls, such as side walls **8091**, and/or one or more corner walls, such as corner walls **8092**. In several embodiments, device slot **8090** can include a bottom wall **8093**. In some embodiments, bottom wall **8093** can include a bottom wall recess **8094** to accommodate one or more protrusions on a face of the electronic device.

(454) In a number of embodiments, cradle **8080** can have a thickness greater than a thickness of the electronic device. In some embodiments, cradle **8080** can include a top surface **8081** and one or more side surfaces, such as side surfaces **8082**. In many embodiments, top surface **8081** can at least partially surround device slot **8090**. In some embodiments, cradle **8080** can include one or more openings or affordances, such as opening **8086**, which can accommodate one or more protrusions on one or more sides of the electronic device, such as one or more buttons, crowns, dials, etc., of the electronic device, and/or facilitate removal of the electronic device from device slot **8090**. For example, as shown in FIG. **80**, opening **8086** can extend through one of side walls **8091** of device slot **8090** and/or through one of

side surfaces **8082** of cradle **8080**. In many embodiments, an affordance (not shown) can extend through one or more of side walls **8091** of device slot **8090** without extending through one or more of side surfaces **8082** of cradle **8080**.

(455) In various embodiments, cradle **8080** can include a tab recess **8083**, a tab surface **8084**, and/or an attachment surface **8085**. In several embodiments, attachment surface **8085** can be a surface of cradle **8080** used to attach overlay applicator **8001** to cradle **8080**. In a number of embodiments, tab surface **8084** can be a surface of cradle **8080** upon which first pull tab **8042** and/or second pull tab **8022** can be supported. In several embodiments, tab surface **8084** and/or attachment surface **8085** can be recessed below top surface **8081**, such that overlay applicator **8001** can be disposed in overlay applicator tray **8000** in a position that does not extend above top surface **8081**, which can beneficially protect overlay applicator **8001** from damage. In many embodiments, tab recess **8083** can provide a structural recess that facilitates ease of access to first pull tab **8042** and/or second pull tab **8022**. In several embodiments, tab recess **8083** can allow such ease of access without first pull tab **8042** and/or second pull tab **8022** extending beyond any of side surfaces **8082**, which can advantageously protect first pull tab **8042** and/or second pull tab **8022** from damage.

(456) In many embodiments, alignment piece **8010** can couple cradle **8080** to overlay applicator **8001**. In some embodiments, alignment piece **8010** can include an overlay attachment portion **8011** and a cradle attachment portion **8012**. For example, alignment piece **8010** can include adhesive at cradle attachment portion **8012** to adhere alignment piece **8010** to attachment surface **8085** of cradle **8080**, and alignment piece **8010** also can include an adhesive at overlay attachment portion **8011** to adhere alignment piece **8010** to overlay applicator **8001**, such as at an attachment region **8021** of protective film **8020**. In some embodiments, alignment piece **8010** can be a piece of material separate from the other layers of overlay applicator **8001**, such as shown in FIG. **80** and described above. In other embodiments, alignment piece **8010** can be integral with one or more of the layers of overlay applicator **8001**, such as protective film **8020** extending beyond the dimensions of overlay **8230** (FIG. **82**) to attach to attachment surface **8085** of cradle **8080**, for example. In many embodiments, first pull tab **8042** and second pull tab **8022** can extend beyond the other overlay layers (e.g., protective film **8020**, overlay **8230** (FIG. **82**), adhesive release liner **8240** (FIG. **82**)) in a direction opposite from the direction in which alignment piece **8010** extends. In many embodiments, alignment piece **8010** can couple cradle **8080** to overlay applicator **8001** such that overlay **8230** (FIG. **82**) of overlay applicator **8001** is aligned with the screen of the electronic device when the electronic device is securely held in device slot **8090**. In a number of embodiments, alignment piece **8010** can be made of a flexible material that allows overlay applicator **8001** to be lifted and/or rotated with respect to cradle **8080**.

(457) Turning ahead in the drawings, FIG. **83** illustrates a top view of overlay applicator tray **8000**, with an electronic device **8350** being held in device slot **8090**, and with overlay applicator **8001** resting on or at least over electronic device **8350**. FIG. **84** illustrates a top view of overlay applicator tray **8000**, with electronic device **8350** being held in device slot **8090**, and with overlay applicator **8001** being folded upwards. As shown in FIGS. **83-84**, electronic device **8350** is a 38 mm Apple Watch without a watch band. In other embodiments, the electronic device can be another type of electronic device, and device slot **8090** can be configured to securely hold the electronic device within device slot **8090**.

(458) In many embodiments, overlay applicator tray **8000** can be used to apply overlay **8230** (FIG. **82**) to electronic device **8350**. For example, overlay applicator **8001** can be turned upwards, as shown in FIG. **84**, and electronic device **8350** can be placed into device slot **8090** of cradle **8080** with the screen of electronic device **8350** facing upwards or away from device slot **8090**. In many embodiments, alignment piece **8010** can be flexible to allow overlay applicator **8001** to be lifted upwards, and in some embodiments, to be lifted upwards and folded back over cradle attachment portion **8012**. When overlay applicator **8001** is released or folded back down, overlay applicator **8001** can rest upon electronic device **8350** and tab surface **8084**, as shown in FIG. **83**. In many embodiments, tab surface **8084** and/or attachment surface **8085** can be approximately planar with the screen of electronic device **8350**, such that overlay applicator **8001** is approximately planar when resting upon electronic device **8350** and tab surface **8084**, as shown in FIG. **83**.

(459) In several embodiments, the screen of electronic device **8350** can be cleaned before and/or after being inserted in device slot **8090**. For example, overlay applicator **8001** can be folded back over cradle

attachment portion **8012**, and the screen of electronic device **8350** can be cleaned with a cleaning cloth, such as cleaning cloth **8573** shown in FIG. **85** and described above, and/or cleaned with a dust removal sticker, such as dust removal sticker **8574**, shown in FIG. **85** and described below, which can advantageously remove dirt or other particulates.

(460) After the screen of electronic device **8350** is cleaned, in several embodiments, when overlay applicator **8001** is lifted off the screen of electronic device **8350**, such as shown in FIG. **84**, first pull tab **8042** can be used to remove adhesive release liner **8240** (FIG. **82**) to expose the adhesive on bottom **9532** (FIG. **95**) side of overlay applicator **8230** (FIG. **82**).

(461) Next, in a number of embodiments, overlay applicator **8001** can be returned to rest on the screen of electronic device **8350**, such that the adhesive on bottom side **9532** (FIG. **95**) of overlay applicator **8230** (FIG. **82**) adheres to the screen of electronic device **8350**. In many embodiments, alignment piece **8010** can align overlay applicator **8001** with respect to cradle **8080** such that when overlay applicator **8001** is returned to rest upon the screen of electronic device **8350**, overlay **8230** (FIG. **82**) can be aligned automatically or self-aligned with the screen of electronic device **8350**.

(462) Next, in many embodiments, air bubbles, if any, between overlay applicator **8230** (FIG. **82**) and the screen of electronic device **8350** can be smoothed out, such as by pushing or rubbing a rigid or semi-rigid object along protective film **8020** (FIG. **80**). In several embodiments, protective film **8020** (FIG. **80**) can protect and prevent damage to overlay **8230** (FIG. **82**) from the forceful pushing or rubbing involved with smoothing the bubbles.

(463) Next, in several embodiments, protective film **8020** (FIG. **80**) can be removed, such as by using second pull tab **8022** to remove protective film **8020** (FIG. **80**) from overlay **8230** (FIG. **82**). In many embodiments, alignment piece **8010** can be attached to protective film **8020**, but not to overlay **8230** (FIG. **82**), such that overlay **8230** (FIG. **82**) can be adhered to the screen of electronic device **8350**. Electronic device **8350** can then be removed from device slot **8090** with overlay **8230** (FIG. **82**) applied to the screen of electronic device **8350**.

(464) Turning ahead in the drawings, FIG. **85** illustrates a top view of an overlay applicator tray kit **8500** with an overlay applicator tray book **8560** in an open configuration, according to another embodiment. Overlay applicator tray kit **8500** is merely exemplary, and embodiments of the overlay applicator tray kit are not limited to the embodiments presented herein. The overlay applicator tray kit can be employed in many different embodiments or examples not specifically depicted or described herein.

(465) In various embodiments, overlay applicator tray kit **8500** can include overlay applicator tray book **8560**, a protective cover **8571**, a dust sticker assembly **8572**, and/or a cleaning cloth **8573**. In a number of embodiments, applicator tray book **8560** can include a first cover **8561**, a spine **8562**, and/or a rear cover **8563**, and can be foldable between an open configuration, as shown in FIG. **85**, and a closed configuration, as shown in FIG. **86**, described below. In many embodiments, first cover **8561** can be coupled to an overlay applicator tray, such as overlay applicator tray **8000**. In several embodiments, second cover **8563** can include a flap **8564**, which can be used to store dust sticker assembly **8572** and/or cleaning cloth **8573** within overlay applicator tray book **8560**. In many embodiments, overlay applicator tray **8000** can be used when overlay applicator tray book **8560** is in the open configuration shown in FIG. **85**.

(466) In many embodiments, dust sticker assembly **8572** can be similar to dust sticker assembly **5500** (FIG. **55**). For example, dust sticker assembly **8572** can include a dust removal sticker **8574** and/or a release liner **8575**. In many embodiments, release liner **8575** can be attached to the bottom side of dust removal sticker **8574** and/or can cover the adhesive on the bottom side of dust removal sticker **8574**. In many embodiments, release liner **8575** can be removed from the bottom side of dust removal sticker **8574** to expose the adhesive on the bottom side of dust removal sticker **8574**, and dust removal sticker **8574** can be adhered to, and then removed from, the screen of electronic device **8350** (FIGS. **83-84**) to remove dust and other particulates from the screen of electronic device **8350**.

(467) In several embodiments, cleaning cloth **8573** can be a microfiber cloth or another suitable material that can be used to clean the screen of electronic device **8350** (FIGS. **83-84**) without leaving dust or other particulates on the screen of electronic device **8350** (FIGS. **83-84**).

(468) In several embodiments, protective cover **8571** can be used to cover overlay applicator tray **8000**, such as when overlay applicator tray book is closed, to protect overlay applicator tray **8000** and keep dust

out from overlay applicator tray **8000**.

(469) In many embodiments, overlay applicator tray kit can include the elements to apply an overlay, such as overlay **8230** (FIG. **82**), to the screen of an electronic device, such as electronic device **8350** (FIGS. **83-84**).

(470) Turning ahead in the drawings, FIG. **86** illustrates a top, front view of overlay applicator tray book **8560** in a closed configuration. FIG. **87** illustrates a bottom, front view of a package **8700** used to enclose overlay applicator tray kit **8500** (FIG. **85**), according to another embodiment. In many embodiments, overlay applicator tray kit **8500** (FIG. **85**) can be included in overlay applicator tray book **8560** in the closed configuration shown in FIG. **86** and packaged within package **8700**. In several embodiments, package **8700** can be a package that can keep dust and other particulates out of overlay applicator tray **8000** (FIGS. **80-85**). In a number of embodiments, packages such as package **8700** can be provided to consumers to allow consumers to accurately and easily apply overlays, such as overlay **8230** (FIG. **82**) to the screens of electronic devices, such as electronic device **8350** (FIGS. **83-84**). In many embodiments, instructions for the consumer can be provided in and/or on package **8700**.

(471) Turning ahead in the drawings, FIG. **88** illustrates a top, front, right side perspective view of an overlay applicator tray **8800**, according to another embodiment. FIG. **89** illustrates a front side elevational view of overlay applicator tray **8800**. FIG. **90** illustrates an enlarged front side elevational view of a portion of overlay applicator tray **8800**, as identified in FIG. **89**. Overlay applicator tray **8800** is merely exemplary, and embodiments of the overlay applicator tray are not limited to the embodiments presented herein. The overlay applicator tray can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay applicator tray **8800** can be similar to overlay applicator tray **8000** (FIG. **80**), and various components or constructions of overlay applicator tray **8800** can be substantially identical or similar to various components of overlay applicator tray **8000** (FIG. **80**).

(472) In many embodiments, overlay applicator tray **8800** can include cradle **8080**, alignment piece **8010**, and an overlay applicator **8801**. Overlay applicator **8801** can be similar to overlay applicator **8001** (FIG. **80**), and various components or constructions of overlay applicator **8801** can be substantially identical or similar to various components of overlay applicator **8001** (FIG. **80**). In many embodiments, overlay applicator **8801** can include overlay **8230** and adhesive release liner **8240**, as shown in FIG. **90**, but not include protective film **8020** (FIG. **80**). In several embodiments, overlay attachment portion **8011** of alignment piece **8010** can be adhered to overlay **8230**, as shown in FIG. **90**, instead of protective film **8010** (FIG. **80**). In many embodiments, overlay applicator **8801** can include first pull tab **8042**, but not second pull tab **8022** (FIG. **80**). As described above, first pull tab **8042** can be used to remove adhesive release liner **8240** from overlay **8230**, such that overlay **8230** can be adhered to the screen of an electronic device, such as electronic device **8350** (FIGS. **83-84**), when the electronic device is securely held in device slot **8090**.

(473) Turning ahead in the drawings, FIG. **91** illustrates a top view of an overlay applicator tray **9100** with an overlay applicator **9101** in a lowered position, according to another embodiment. FIG. **92** illustrates a top, right side view of overlay applicator tray **9100** with overlay applicator **9101** in a raised position. FIG. **96** illustrates an enlarged top, right side view of a portion of overlay applicator **9101** of overlay applicator tray **9100**, as identified in FIG. **92**. Overlay applicator tray **9100** is merely exemplary, and embodiments of the overlay applicator tray are not limited to the embodiments presented herein. The overlay applicator tray can be employed in many different embodiments or examples not specifically depicted or described herein. In many embodiments, overlay applicator tray **9100** can be similar to overlay applicator tray **8000** (FIG. **80**), and various components or constructions of overlay applicator tray **9100** can be substantially identical or similar to various components of overlay applicator tray **8000** (FIG. **80**).

(474) In various embodiments, overlay applicator tray **9100** can include overlay applicator **9101**, a cradle **9180**, and/or an alignment piece **9110**. In many embodiments, overlay applicator **9101** can be similar to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), and/or overlay applicator **8001** (FIG. **80**), and various components and/or constructions of overlay applicator **9101** can be substantially

identical or similar to components of overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), overlay applicator **6050** (FIG. 60), and/or overlay applicator **8001** (FIG. 80).

(475) In a number of embodiments, overlay applicator **9101** can include an overlay **9230** (FIG. 92). In many embodiments, overlay **9230** (FIG. 92) can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15), overlay **2930** (FIGS. 29-30), and/or overlay **8230** (FIG. 82). In a number of embodiments, overlay **9230** (FIG. 92) can have a top side **9631** (FIG. 96) and a bottom side **9632** (FIG. 96). Top side **9631** (FIG. 96) of overlay **9230** (FIG. 92) can be similar or identical to top side **131** (FIG. 1) of overlay **130** (FIG. 1). Bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) can be similar or identical to bottom side **132** (FIG. 1) of overlay **130** (FIG. 1). In various embodiments, bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) can include an adhesive configured to adhere overlay **9230** (FIG. 92) to a screen of an electronic device, such as an electronic device held in cradle **9180**.

(476) In several embodiments, overlay applicator **9001** can include an adhesive release liner **9240** (FIG. 92). Adhesive release liner **9240** (FIG. 92) can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7), adhesive release liner **1540** (FIG. 15), adhesive release liner **2740** (FIGS. 27-30), and/or adhesive release liner **8240** (FIG. 82). In a number of embodiments, adhesive release liner **9240** (FIG. 92) can have a top side **9641** (FIG. 96) and a bottom side **9642** (FIG. 96). Top side **9641** (FIG. 96) of adhesive release **9240** (FIG. 92) liner can be removably attached to bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) to expose the adhesive at bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 82). In some embodiments, adhesive release liner **9240** (FIG. 92) can be configured to protect the adhesive agent at or on bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) from contaminants.

(477) In some embodiments, overlay applicator **9001** can include a protective film **9220** (FIG. 92). Protective film **9220** (FIG. 92) can be similar or identical to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), protective film **720** (FIG. 7), protective film **1520** (FIG. 15), protective film **2920** (FIGS. 29-30), protective film **3552** (FIG. 35), protective film **6052** (FIG. 60), and/or protective film **8020** (FIG. 80). In many embodiments, protective film **9220** (FIG. 92) can have a top side **9621** (FIG. 96) and a bottom side **9622** (FIG. 96). In a number of embodiments, protective film **9220** (FIG. 92) can be removably attached to the top side **9631** (FIG. 96) of overlay **9230** (FIG. 92). For example, bottom side **9622** (FIG. 96) of protective film **9220** (FIG. 92) can be removably attached to top side **9631** (FIG. 96) of overlay **9230** (FIG. 92), such as with an adhesive at or on bottom side **9622** (FIG. 96) of protective film **9220** (FIG. 92).

(478) In several embodiments, overlay applicator **9101** can include a first pull tab **9142** and/or a second pull tab **9122**. First pull tab **9142** can be similar or identical to first pull tab **8042** (FIG. 80), and/or second pull tab **9122** can be similar or identical to second pull tab **8022** (FIG. 80). In a number of embodiments, first pull tab **9142** can be used to remove adhesive release liner **9240** (FIG. 92) from overlay **9230** (FIG. 92). In many embodiments, first pull tab **9142** can advantageously help prevent accidental touching of the adhesive at or on bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) when removing adhesive release liner **9240** (FIG. 92) from overlay **9230** (FIG. 92). In several embodiments, first pull tab **9142** can be affixed to bottom side **9642** (FIG. 96) or adhesive release liner **9240** (FIG. 92), such as shown in FIG. 92. In other embodiments, first pull tab **9142** can be integral with adhesive release liner **9240** (FIG. 92). In many embodiments, first pull tab **9142** can be adhered to bottom side **9642** (FIG. 96) of adhesive release liner **9240** (FIG. 92) with an adhesive or another suitable fastener. In a number of embodiments, the adhesive adhering first pull tab **9142** to adhesive release liner **9240** (FIG. 92) can have a greater adhesive strength than the adhesive at or on bottom side **9632** (FIG. 96) of overlay **9230** (FIG. 92) that adheres adhesive release liner **9240** (FIG. 92) to overlay **9230** (FIG. 82), such that first pull tab **9142** can be used to pull and remove adhesive release liner **9240** (FIG. 92) from overlay **9230** (FIG. 92) without first pull tab **9142** being removed from adhesive release liner **9240** (FIG. 92).

(479) In a number of embodiments, second pull tab **9122** can be used to remove protective film **9220** (FIG. 92) from overlay **9230** (FIG. 92). In many embodiments, second pull tab **9122** can be affixed to top side **9621** (FIG. 96) of protective film **9220** (FIG. 92), such as shown in FIG. 92. In other embodiments,

second pull tab **9122** can be integral with protective film **9220** (FIG. 92). In many embodiments, second pull tab **9122** can be adhered to top side **9621** (FIG. 96) of protective film **9220** (FIG. 92) with an adhesive or another suitable fastener. In a number of embodiments, the adhesive adhering second pull tab **9122** to protective film **9220** (FIG. 92) can have a greater adhesive strength than the adhesive at or on bottom side **9622** (FIG. 96) of protective film **9220** (FIG. 92) that adheres protective film **9220** (FIG. 92) to overlay **9230** (FIG. 92), such that second pull tab **9122** can be used to pull and remove protective film **9220** (FIG. 92) from overlay **9230** (FIG. 92) without second pull tab **9122** being removed from protective film **9220** (FIG. 92).

(480) In many embodiments, cradle **9180** can be similar to cradle **310** (FIG. 3), cradle **832** (FIG. 8), cradle **1620** (FIG. 16), cradle **2032** (FIG. 20), cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38), cradle **4630** (FIGS. 46-50), cradle **6410** (FIG. 64), cradle **6420** (FIG. 64), cradle **6430** (FIG. 64), cradle **6950** (FIG. 69), and/or cradle **8080** (FIG. 80), and various components and/or constructions of cradle **9180** can be substantially identical or similar to various components of cradle **310** (FIG. 3), cradle **832** (FIG. 8), cradle **1620** (FIG. 16), cradle **2032** (FIG. 20), cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38), cradle **4630** (FIGS. 46-50), cradle **6410** (FIG. 64), cradle **6420** (FIG. 64), cradle **6430** (FIG. 64), cradle **6950** (FIG. 69), and/or cradle **8080** (FIG. 80).

(481) In several embodiments, cradle **9180** can include a device slot **9190**. Device slot can be similar to slot **311** (FIG. 3), slot **1621** (FIG. 16), device slot **3111** (FIG. 31), slot **3811** (FIG. 38), slot **4731** (FIG. 47), device slot **6411** (FIG. 64), device slot **6421** (FIG. 64), device slot **6431** (FIG. 64), device slot **6956** (FIG. 69), and/or device slot **8090** (FIG. 80). In many embodiments, device slot **9190** can be configured to securely hold an electronic device in device slot **9190**. In many embodiments, the electronic device can be similar or identical to device **220** (FIG. 2), device **320** (FIG. 3), device **1650** (FIG. 16), device **3401** (FIG. 34), device **3720** (FIG. 37), device **4800** (FIG. 48), device **5600** (FIG. 56), device **6550** (FIG. 65), device **7100**, and/or electronic device **8350** (FIG. 83). For example, the electronic device can be a smart phone, a tablet, a smart watch, or another suitable electronic device. In several embodiments, cradle **9180** can be configured for a specific type of electronic device, such as the iPhone 6 Plus or iPhone 6s Plus. For example, device slot **9190** can be configured to hold an electronic device having the dimensions of the specific type of electronic device.

(482) In many embodiments, the electronic device can be placed within device slot **9190** with a screen of the electronic device facing upwards or away from device slot **9190**. In other embodiments, the electronic device can be placed within device slot **9190** with the screen of the electronic device facing downwards or towards device slot **9190**. In some embodiments, device slot **9190** can be conformal with the electronic device. In a number of embodiments, device slot **9190** can include one or more side walls, such as side walls **9191**, and/or one or more corner walls, such as corner walls **9192**. In several embodiments, device slot **9190** can include a bottom wall **9293** (FIG. 92). In some embodiments, bottom wall **9293** can include one or more recesses or apertures, such as apertures **9294** (FIG. 92) to accommodate one or more protrusions on a face of the electronic device, such as a camera, or two facilitate removal of the electronic device from device slot **9190**.

(483) In a number of embodiments, cradle **9180** can have a thickness greater than a thickness of the electronic device. In some embodiments, cradle **9180** can include a top surface **9181** and one or more side surfaces, such as side surfaces **9282** (FIG. 92). In many embodiments, top surface **9180** can at least partially surround device slot **9190**. In some embodiments, cradle **9180** can include one or more openings or affordances, such as affordances **9186**, which can accommodate one or more protrusions on one or more sides of the electronic device, such as one or more buttons, crowns, dials, etc., of the electronic device, and/or facilitate removal of the electronic device from device slot **9190**. For example, as shown in FIG. 91, affordances **9186** can extend outward from device slot **9190** through one or more of side walls **9191** of device slot **9190** without extending through one or more of side surfaces **9282** (FIG. 92) of cradle **9180**. In other embodiments, an opening (not shown) can extend through one of side walls **9191** of device slot **9190** and/or through one of side surfaces **9282** (FIG. 92) of cradle **9180**.

(484) In various embodiments, cradle **9180** can include a tab surface **9184** and/or an attachment surface **9185**. Tab surface **9184** can be similar or identical to tab surface **8084** (FIG. 80), and/or attachment surface **9185** can be similar or identical to attachment surface **8085** (FIG. 80). In several embodiments, attachment surface **9185** can be a surface of cradle **9180** used to attach overlay applicator **9101** to cradle

9180. In a number of embodiments, tab surface **9184** can be a surface of cradle **9180** upon which first pull tab **9142** and/or second pull tab **9122** can be supported. In several embodiments, tab surface **9184** and/or attachment surface **9185** can be recessed below top surface **9181**, such that overlay applicator **9101** can be disposed in overlay applicator tray **9100** in a position that does not extend above top surface **9181**, which can beneficially protect overlay applicator **9101** from damage.

(485) In many embodiments, alignment piece **9110** can couple cradle **9180** to overlay applicator **9101**. Alignment piece **9110** can be similar or identical to alignment piece **8010** (FIG. **80**). In some embodiments, alignment piece **9110** can include an overlay attachment portion **9111** and a cradle attachment portion **9112**. For example, alignment piece **9110** can include adhesive at cradle attachment portion **9112** to adhere alignment piece **9110** to attachment surface **9185** of cradle **9180**, and alignment piece **9110** also can include an adhesive at overlay attachment portion **9111** to adhere alignment piece **9110** to overlay applicator **9101**. In some embodiments, alignment piece **9110** can be a piece of material separate from the other layers of overlay applicator **9101**, such as shown in FIGS. **91-92** and described above. In other embodiments, alignment piece **9110** can be integral with one or more of the layers of overlay applicator **9101**, such as protective film **9220** (FIG. **92**) extending beyond the dimensions of overlay **9230** (FIG. **92**) to attach to attachment surface **9185** of cradle **9180**, for example. In many embodiments, first pull tab **9142** and second pull tab **9122** can extend beyond the other overlay layers (e.g., protective film **922** (FIG. **92**), overlay **9230** (FIG. **92**), adhesive release liner **9240** (FIG. **92**)) in a direction opposite from the direction in which alignment piece **9010** extends. In many embodiments, alignment piece **9110** can couple cradle **9180** to overlay applicator **9101** such that overlay **9230** (FIG. **92**) of overlay applicator **9101** is aligned with the screen of the electronic device when the electronic device is securely held in device slot **9190**. In a number of embodiments, alignment piece **9110** can be made of a flexible material that allows overlay applicator **9101** to be lifted and/or rotated with respect to cradle **9180**.

(486) In the embodiments of the overlay applicator trays (e.g., **8000** (FIG. **80**), **8800** (FIG. **88**), **9100** (FIG. **91**)) described above, the first pull tab (e.g., **8022** (FIG. **80**), **9122** (FIG. **91**)) can be configured to peel the adhesive release liner (e.g., **8240** (FIG. **82**), **9240** (FIG. **92**)) starting at a side of the overlay (e.g., **8230** (FIG. **82**), **9230** (FIG. **92**)) that is opposite from the side to which the alignment piece (e.g., **8010** (FIG. **80**), **9110** (FIG. **91**)) is attached. In other embodiments, the first pull tab can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIGS. **7, 42, 44-45, 48-49**), pull tab **1550** (FIG. **15**), pull tab **2750** (FIGS. **27-30**) and/or pull tab **6055** (FIG. **60**), such that the first pull tab is folded under the adhesive release liner (e.g., **8240** (FIG. **82**), **9240** (FIG. **92**)) proximate to the side at which the alignment piece (e.g., **8010** (FIG. **80**), **9110** (FIG. **91**)) is attached, and pulling the first pull tab results in the adhesive release liner (e.g., **8240** (FIG. **82**), **9240** (FIG. **92**)) being peeled starting at the side to which the alignment piece (e.g., **8010** (FIG. **80**), **9110** (FIG. **91**)) is attached. In some such embodiments, the first pull tab can be integral with the adhesive release liner, and in other such embodiments, the first pull tab can be attached to the adhesive release liner. In some embodiments, the first pull tab can include a wiper, such as wiper **157** (FIG. **1**), wiper **457** (FIG. **4**), wiper **657** (FIG. **6**), wiper **757** (FIG. **7**), wiper **2857** (FIGS. **28-30**), wiper **6200** (FIG. **62**), and/or wiper **6300** (FIG. **63**), which can be pulled across the screen of the electronic device when the first pull tab is pulled to remove the adhesive release liner (e.g., **8240** (FIG. **82**), **9240** (FIG. **92**)) from the overlay (e.g., **8230** (FIG. **82**), **9230** (FIG. **92**)).

(487) In the embodiments of the overlay applicator trays (e.g., **8000** (FIG. **80**), **8800** (FIG. **88**), **9100** (FIG. **91**)) described above, the electronic device is placed in the device slot (e.g., **8090** (FIG. **80, 88**), **9190** (FIG. **91**)) of the cradle (e.g., **8080** (FIG. **80, 88**), **9180** (FIG. **91**)) with the screen of the electronic device facing upwards or away from the device slot (e.g., **8090** (FIG. **80, 88**), **9190** (FIG. **91**)). In other embodiments, the electronic device can be placed in the device slot (e.g., **8090** (FIG. **80, 88**), **9190** (FIG. **91**)), such that the screen of the electronic device is downwards or facing towards the device slot (e.g., **8090** (FIG. **80, 88**), **9190** (FIG. **91**)). For example, the tab surface (e.g., **8084** (FIG. **80**), **9184** (FIG. **91**)) and/or the attachment surface (e.g., **8085** (FIG. **80**), **9185** (FIG. **91**)) can be lower so that the overlay applicator can be attached upside-down to accommodate applying the overlay (e.g., **8230** (FIG. **82**), **9230** (FIG. **92**)) to the screen of the device when the electronic device is facing the opposite direction.

(488) In several embodiments, the alignment piece (e.g., **8010** (FIG. **80**), **9110** (FIG. **91**)) can be a

permanent part of the overlay applicator tray (e.g., **8000** (FIG. 80), **8800** (FIG. 88), **9100** (FIG. 91)) that is integrated during manufacturing. For example, the overlay applicator can be manufacturing with the alignment piece such that the overlay applicator (e.g., **8001** (FIG. 80), **8801** (FIG. 88), **9101** (FIG. 91)) and the cradle (e.g., **8080** (FIG. 80, 88), **9180** (FIG. 91)) are attached and pre-aligned using the alignment piece during the manufacturing process of the overlay applicator tray. When the overlay applicator tray is used by a consumer, the overlay applicator tray can be a single apparatus, due to the attachment and pre-alignment of the alignment piece to the overlay applicator and the cradle, such that the consumer does not need to align the overlay applicator with the cradle using pins, fasteners, adhesive, or any other attachment and/or alignment method. Instead, the consumer need only place the electronic device within the device slot (e.g., **8090** (FIG. 80, 88), **9190** (FIG. 91)) of the cradle (e.g., **8080** (FIG. 80, 88), **9180** (FIG. 91)), and the overlay applicator will be aligned automatically or self-aligned with the electronic device such that the overlay (e.g., **8230** (FIG. 82)) will be aligned with the screen of the electronic device when adhered to the screen of the electronic device.

(489) In a number of embodiments, the overlay applicator trays (e.g., **8000** (FIG. 80), **8800** (FIG. 88), **9100** (FIG. 91)) can be disposable for one-time use. In several embodiments, the disposable nature of the overlay applicator trays can allow the overlay applicator trays to be procured by individual consumers that prefer to apply an overlay (e.g., **8230** (FIG. 82), **9230** (FIG. 92)) to an electronic device (e.g., **8350** (FIG. 83)) by themselves, and not relinquish full control of their electronic device to another, such as a sales associate.

(490) In many embodiments, the cradles (e.g., **8080** (FIG. 80, 88), **9180** (FIG. 91)) can made using vacuum forming with a thermoplastic or other suitable material. In various embodiments, the vacuum formed manufacturing of the cradle can faster and less expensive to manufacture than a cradle formed with injection molding.

(491) Turning ahead in the drawings, FIG. 93 illustrates a flow chart for an embodiment of a method **9300**, according to another embodiment. Method **9300** is merely exemplary and is not limited to the embodiments presented herein. Method **9300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **9300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **9300** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **9300** can be combined or skipped. In many embodiments, method **9300** can be a method of providing an overlay applicator tray. In some embodiments, the overlay applicator tray can be similar or identical to overlay applicator tray **8000** (FIG. 80), overlay applicator tray **8800** (FIG. 88), and/or overlay applicator tray **9100** (FIG. 91).

(492) Referring to FIG. 93, method **9300** can include a block **9301** of providing a cradle. In many embodiments, the cradle can be similar or identical to cradle **310** (FIG. 3), cradle **832** (FIG. 8), cradle **1620** (FIG. 16), cradle **2032** (FIG. 20), cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38), cradle **4630** (FIGS. 46-50), cradle **6410** (FIG. 64), cradle **6420** (FIG. 64), cradle **6430** (FIG. 64), cradle **6950** (FIG. 69), cradle **8080** (FIG. 80), and/or cradle **9180** (FIG. 91). In many embodiments, the cradle can include a device slot. The device slot can be similar or identical to slot **311** (FIG. 3), slot **1621** (FIG. 16), device slot **3111** (FIG. 31), slot **3811** (FIG. 38), slot **4731** (FIG. 47), device slot **6411** (FIG. 64), device slot **6421** (FIG. 64), device slot **6431** (FIG. 64), device slot **6956** (FIG. 69), device slot **8090** (FIG. 80), and/or device slot **9190** (FIG. 91). In many embodiments, the device slot can be configured to securely hold an electronic device in the device slot. The electronic device can be to device **220** (FIG. 2), device **320** (FIG. 3), device **1650** (FIG. 16), device **3401** (FIG. 34), device **3720** (FIG. 37), device **4800** (FIG. 48), device **5600** (FIG. 56), device **6550** (FIG. 65), device **7100**, and/or electronic device **8350** (FIG. 83). In many embodiments, the cradle can be provided by being vacuum formed.

(493) In some embodiments, method **9300** next can include a block **9302** of providing an overlay applicator. The overlay applicator can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), overlay applicator **6050** (FIG. 60), overlay applicator **8001** (FIG. 80), and/or overlay applicator **9101** (FIG. 91).

(494) In many embodiments, block **9302** optionally can include a block **9303** of providing an overlay layer. The overlay layer can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15), overlay **2930** (FIGS. 29-30), overlay **8230** (FIG. 82), and/or overlay **9230** (FIG. 92). In a number of embodiments, the overlay layer can include a first side and a second side. The first side can be similar or identical to top side **9531** (FIG. 95) and/or top side **9631** (FIG. 96). The second side can be similar or identical to bottom side **9532** (FIG. 95) and/or bottom side **9632** (FIG. 96). In several embodiments, the second side is configured to be adhered to a screen of the electronic device.

(495) In several embodiments, block **9302** next can include a block **9304** of providing a release liner. The release liner can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7), adhesive release liner **1540** (FIG. 15), adhesive release liner **2740** (FIGS. 27-30), adhesive release liner **8240** (FIG. 82), and/or adhesive release liner **9240** (FIG. 92). In many embodiments, the release liner can be configured to be removed from the second side of the overlay layer to permit the second side of the overlay layer to be adhered to the screen of the electronic device.

(496) In many embodiments, block **9302** optionally can include a block **9305** of providing a protective layer. The protective layer can be similar or identical to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), protective film **720** (FIG. 7), protective film **1520** (FIG. 15), protective film **2920** (FIGS. 29-30), protective film **3552** (FIG. 35), protective film **6052** (FIG. 60), protective film **8020** (FIG. 80), and/or protective film **9220** (FIG. 92). In several embodiments, a side of the protective layer can be removably attached to the first side of the overlay layer. The side of the protective layer can be similar or identical to second side **9522** (FIG. 95) or second side **9622** (FIG. 96).

(497) In a number of embodiments, method **9300** next can include a block **9306** of providing an alignment piece. The alignment piece can be similar or identical to alignment piece **8010** (FIG. 80) and/or alignment piece **9110** (FIG. 91). In a number of embodiments, the alignment piece can couple the cradle to the overlay applicator such that the overlay layer is aligned with the screen of the electronic device when the electronic device is securely held in the device slot as the overlay applicator is applied to the screen of the electronic device.

(498) Turning ahead in the drawings, FIG. **94** illustrates a flow chart for an embodiment of a method **9400**, according to another embodiment. Method **9400** is merely exemplary and is not limited to the embodiments presented herein. Method **9400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **9400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **9400** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **9400** can be combined or skipped. In many embodiments, method **9400** can be a method of using an overlay applicator tray, such as using an overlay applicator tray to apply an overlay to a screen of an electronic device.

(499) Referring to FIG. **94**, method **9400** can include a block **9401** of inserting an electronic device in a device slot of a cradle of an overlay applicator tray. The overlay applicator tray can be similar or identical to overlay applicator tray **8000** (FIG. 80), overlay applicator tray **8800** (FIG. 88), and/or overlay applicator tray **9100** (FIG. 91). The cradle can be similar or identical to cradle **310** (FIG. 3), cradle **832** (FIG. 8), cradle **1620** (FIG. 16), cradle **2032** (FIG. 20), cradle **3100** (FIG. 31), cradle **3520** (FIG. 35), cradle **3710** (FIGS. 37-38), cradle **4630** (FIGS. 46-50), cradle **6410** (FIG. 64), cradle **6420** (FIG. 64), cradle **6430** (FIG. 64), cradle **6950** (FIG. 69), cradle **8080** (FIG. 80), and/or cradle **9180** (FIG. 91). The device slot can be similar or identical to slot **311** (FIG. 3), slot **1621** (FIG. 16), device slot **3111** (FIG. 31), slot **3811** (FIG. 38), slot **4731** (FIG. 47), device slot **6411** (FIG. 64), device slot **6421** (FIG. 64), device slot **6431** (FIG. 64), device slot **6956** (FIG. 69), device slot **8090** (FIG. 80), and/or device slot **9190** (FIG. 91). The electronic device can be to device **220** (FIG. 2), device **320** (FIG. 3), device **1650** (FIG. 16), device **3401** (FIG. 34), device **3720** (FIG. 37), device **4800** (FIG. 48), device **5600** (FIG. 56), device **6550** (FIG. 65), device **7100**, and/or electronic device **8350** (FIG. 83). In many embodiments, the device slot can be configured to securely hold the electronic device in the device slot when the electronic device is inserted in the device slot.

(500) In some embodiments, method **9400** next can include a block **9402** of removing a release liner from an overlay layer. In many embodiments, the release liner and the overlay layer can be part of an overlay applicator attached to the cradle using an alignment piece. The overlay applicator can be similar or identical to overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), overlay applicator **6050** (FIG. 60), overlay applicator **8001** (FIG. 80), and/or overlay applicator **9101** (FIG. 91). The alignment piece can be similar or identical to alignment piece **8010** (FIG. 80) and/or alignment piece **9110** (FIG. 91).

(501) The release liner can be similar or identical to adhesive release liner **140** (FIG. 1), adhesive release liner **440** (FIGS. 4-5), adhesive release liner **640** (FIG. 6), adhesive release liner **740** (FIG. 7), adhesive release liner **1540** (FIG. 15), adhesive release liner **2740** (FIGS. 27-30), adhesive release liner **8240** (FIG. 82), and/or adhesive release liner **9240** (FIG. 92). The overlay layer can be similar or identical to overlay **130** (FIG. 1), overlay **430** (FIGS. 4-5), overlay **630** (FIG. 6), overlay **730** (FIG. 7), and/or overlay **1530** (FIG. 15), overlay **2930** (FIGS. 29-30), overlay **8230** (FIG. 82), and/or overlay **9230** (FIG. 92). In a number of embodiments, the alignment piece can couple the cradle to the overlay applicator such that the overlay layer is aligned with the screen of the electronic device when the electronic device is securely held in the device slot as the overlay applicator is applied to the screen of the electronic device.

(502) In several embodiments, block **9402** of removing a release liner from an overlay layer can include lifting (or rotating) the overlay applicator to peel back the release liner from the overlay layer, such as by using a first pull tab of the overlay applicator. The first pull tab can be similar or identical to first pull tab **8042** (FIG. 80) and/or **9122** (FIG. 91). In other embodiments, block **9402** of removing the release liner from the overlay layer can include pulling a pull tab of the overlay applicator when the overlay applicator is disposed proximate to the screen of the electronic device. For example, the overlay applicator can be disposed proximate to the screen of the electronic device by resting on or being held against the screen of the electronic device, such as when the electronic device is inserted in the device slot with the screen up, or disposed between the device slot at the screen of the electronic device, such as when the electronic device is inserted in the device slot with the screen down.

(503) In many embodiments, method **9400** next can include a block **9403** of adhering the overlay layer to a screen of the electronic device. In some embodiments, such as when block **9402** of removing the release liner from the overlay applicator includes lifting (or rotating) the overlay applicator to peel back the release liner from the overlay layer, block **9403** of adhering the overlay layer to the screen of the electronic device can include lowering the overlay applicator to the screen of the electronic device to adhere the overlay layer to the screen of the electronic device. In other embodiments, such as when block **9402** of removing the release liner from the overlay applicator involves pulling a pull tab of the overlay applicator when the overlay applicator is disposed proximate to the screen of the electronic device, block **9403** of adhering the overlay layer to the screen of the electronic device can be performed simultaneously when block **9402** of removing the release liner from the overlay applicator.

(504) In several embodiments, method **9400** optionally can include a block **9404** of smoothing out bubbles between the overlay layer and the screen of the electronic device. In many embodiments, a rigid or semi-rigid object can be used to rub the overlay layer or a protective layer on the overlay layer to work out any bubbles between the overlay layer and the screen of the electronic device.

(505) In many embodiments, method **9400** optionally can include a block **9405** of removing a protective layer from the overlay layer. The protective layer can be similar or identical to protective film **120** (FIG. 1), protective film **420** (FIGS. 4-5), protective film **620** (FIG. 6), protective film **720** (FIG. 7), protective film **1520** (FIG. 15), protective film **2920** (FIGS. 29-30), protective film **3552** (FIG. 35), protective film **6052** (FIG. 60), protective film **8020** (FIG. 80), and/or protective film **9220** (FIG. 92). The protective layer can be part of the overlay applicator. In other embodiments, the overlay applicator does not include a protective layer. In some embodiments in which the protective layer is part of the overlay applicator, a second pull tab can be used to peel back the protective layer from the overlay layer. The second pull tab can be similar or identical to second pull tab **8022** (FIG. 80) and/or second pull tab **9122** (FIG. 91).

(506) In a number of embodiments, method **9400** next can include a block **9406** of removing the electronic device from the device slot. In some embodiments, such as when the protective layer has been removed from the overlay layer, the electronic device can be removed from the device slot with the

overlay layer adhered to the screen of the electronic device. In other embodiments, such as when a screen of the electronic device is facing downwards towards the device slot, the removal of the electronic device from the device slot can cause the protective layer to be removed from the overlay layer (thus performing block **9405** of removing the protective layer from the overlay layer), or can cause the electronic device to be removed with the protective layer still attached to the overlay layer, such that block **9404** of smoothing out bubbles between the overlay layer and the screen of the electronic device can be performed after performing block **9406** of removing the electronic device from the device slot.

(507) Turning ahead in the drawings, FIG. **97** illustrates a perspective view of an exemplary overlay **9750** attached to an electronic device **9700**, according to an embodiment. As an example, overlay **9750** can be made of glass, PET, or another suitable material. However, overlay **9750** is merely exemplary, and embodiments of the overlay are not limited to the embodiments presented herein. The overlay can be employed in many different embodiments or examples not specifically depicted or described herein. In several embodiments, overlay **9750** can be similar to overlay **130** (FIG. **1**), overlay **430** (FIGS. **4-5**), overlay **630** (FIG. **6**), overlay **730** (FIG. **7**), and/or overlay **1530** (FIG. **15**), overlay **2930** (FIGS. **29-30**), overlay **8230** (FIG. **82**), and/or overlay **9230** (FIG. **92**). In many embodiments, overlay **9750** can be applied to electronic device **9700** (e.g., to a touchscreen **9701** (FIG. **97**) or electronic device **9700**) using an overlay applicator. For example, the overlay applicator can be similar to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), and/or overlay applicator **9101** (FIG. **91**). In some embodiments, overlay **9750** can be applied to electronic device **9700** using an overlay applicator tray. For example, the overlay applicator tray can be similar to overlay applicator tray **8000** (FIG. **80**) and/or overlay applicator tray **9100** (FIG. **91**).

(508) In many embodiments, electronic device **9700** can be a portable and/or handheld electronic device, such as the Galaxy S6 Edge, Galaxy S7 Edge, and/or Galaxy S8 smartphones developed by Samsung of Seoul, South Korea. In other embodiments, the electronic device can be another suitable portable and/or handheld electronic device. In many embodiments, electronic device **9700** can include a touchscreen **9701** and a non-touchscreen portion **9702**. Touchscreen **9701** can be a capacitive touchscreen or another suitable type of touchscreen. In several embodiments, non-touchscreen portion **9702** can surround touchscreen **9701** on one or more sides, such as on a top end **9705** and a bottom end **9710**, and/or can be beneath touchscreen **9701**, as shown in FIGS. **98-99** and described below. In many embodiments, the non-touchscreen portion **9702** can include buttons, such as button **9711**, speakers, such as speaker **9706**, and/or other elements, such as cameras, light sensors, etc. In many embodiments, overlay **9750** can cover both touchscreen **9701** and all or portions of non-touchscreen portion **9702**, or overlay **9750** can cover only touchscreen **9701** and not cover non-touchscreen portion **9702**.

(509) In a number of embodiments, electronic device **9700** can include curved edges at a right side **9703** and/or left side **9704**. In some embodiments, the curved edges can curve downward from, and/or decline below, the top plane of the face of electronic device **9700** at the sides (e.g., **9703**, **9704**) of electronic device **9700**. In some embodiments, touchscreen **9701** can extend at least partially into the curved edges at right side **9703** and/or left side **9704**. In several embodiments, overlay **9750** can include curves that correspond to the curved edges at right side **9703** and/or left side **9704** of electronic device **9700**, as described below in further detail.

(510) Proceeding to the next drawings, FIG. **98** illustrates a cross-sectional view of electronic device **9700** along cross-section line **98-98** in FIG. **97**, and the bottom edge of touchscreen **9701** and overlay **9750**. FIG. **99** illustrates an enlarged cross-sectional view of a portion of electronic device **9700** along cross-section line **98-98** in FIG. **97**, and a portion of the bottom edge of touchscreen **9701** and overlay **9750**, as identified in FIG. **98**. In many embodiments, touchscreen **9701** can extend over non-touchscreen portion **9702** from right side **9703** to left side **9704** of electronic device **9700**. In some embodiments, as shown in FIG. **99**, touchscreen **9701** can include a flat portion **9905** and one or more curved portions, such as curved portion **9906** at right side **9703**. In a number of embodiments, the curved portions (e.g. **9906**) can curve downward from, and/or decline below, the plane of flat portion **9905** as touchscreen **9701** extends from flat portion **9905** to the side of the device (e.g., right side **9703**).

(511) In many embodiments, as shown in FIG. **98**, overlay **9750** can include a flat overlay portion **9853**

and/or curved overlay portions, such as curved overlay portions **9851** and **9852**, which can correspond to the curved edges at left side **9704** and right side **9703**, respectively, of electronic device **9700**. In many embodiments, curved overlay portions **9851** and **9852** can curve downward from and/or decline below, the plane of flat overlay portion **9853** as overlay **9750** extends towards the sides (e.g., **9703**, **9704**) of electronic device **9700**. In a number of embodiments, overlay **9750** can have an approximately uniform thickness, such that the thickness of overlay **9750** at flat overlay portion **9853** is approximately the same as the thickness of curved overlay portions **9851** and **9852**. In several embodiments, overlay **9750** can have a top side **9981** and a bottom side **9982**.

(512) In a number of embodiments, overlay **9750** can be made of be glass, tempered glass, silica-infused plastic, polyethylene terephthalate (PET), or another suitable material, which can be optically clear and transmit through light from touchscreen **9701**. In some embodiments, overlay **9750** can be rigid or semi-rigid, such that overlay **9750** can maintain the formed planar shape of flat overlay portion **9853** and maintains the formed curved shape of curved overlay portions **9851** and **9852**. In other embodiments, overlay **9750** can be flexible, such that curved overlay portions **9851** and/or **9852** can be curved manually by the user and/or automatically by gravity to form their curved shape, such as when overlay **9750** is adhered to electronic device **9750**.

(513) In many embodiments, overlay **9750** can be attached and/or adhered to electronic device **9700** with one or more layers of adhesive and/or adhesive carrier. For example, such as shown in FIG. **99**, overlay **9750** can be attached and/or adhered to electronic device **9700** using an adhesive component **9970**. In a number of embodiments, adhesive component **9970** can include a top side **9983** and a bottom side **9984**. In several embodiments, adhesive component **9970** can include an adhesive carrier **9972**, a first adhesive layer **9971**, and/or a second adhesive layer **9973**. In many embodiments, adhesive carrier can have a top side **9985** and a bottom side **9986**. In some embodiments, first adhesive layer **9971** can be at top side **9985** of adhesive carrier **9972**, and/or second adhesive layer **9973** can be at bottom side **9986** of adhesive carrier **9972**. FIGS. **98** and **99** do not necessarily show the proportional thicknesses of overlay **9750**, device **9700**, and/or adhesive component **9970**. For example, in some embodiments, adhesive component **9970** can be the thinnest component of overlay **9750**, device **9700**, and adhesive component **9970**. In these embodiments, overlay **9750** can have a thickness of approximately 0.1 mm to approximately 1.0 mm, and adhesive component **9970** can have a thickness of approximately 0.02 mm to approximately 0.3 mm.

(514) In many embodiments, first adhesive layer **9971** can be configured to attach and/or adhere top side **9985** of adhesive carrier **9972** to bottom side **9981** of overlay **9750**. In several embodiments, second adhesive layer **9973** can be configured to attach and/or adhere bottom side **9986** of adhesive carrier **9972** to touchscreen **9701** of electronic device **9700**. In a number of embodiments, adhesive carrier **9972** can be an optically clear carrier layer, and can be a thin sheet of PET (polyethylene terephthalate) or other suitable material. For example, in some embodiments, adhesive carrier **9972** can have a thickness of approximately 0.02 millimeters (mm) to approximately 0.2 mm.

(515) In many embodiments, first adhesive layer **9971** and/or second adhesive layer **9973** can be an optically clear adhesive, an adhesive silicone, or another suitable adhesive. In several embodiments, layers **9971-9973** can provide a single-use adhesive of the overlay. For example, in some embodiments, an adhesive strength of second adhesive layer **9973** can be greater than an adhesive strength of first adhesive layer **9971**, such that once overlay **9750** is applied to electronic device **9700**, layers **9971-9973** can remain on electronic device **9700** if overlay **9750** is removed and/or peeled away from electronic device **9700**. In a number of embodiments, after overlay **9750** is removed from electronic device **9700** and layers **9971-9973** are left on electronic device, layers **9971-9973** can be peeled away from electronic device **9900**. In several embodiments, removing layers **9971-9973** from electronic device **9700** when peeling away overlay **9750** can beneficially allow for a single-use application of overlay **9750** and layers **9971-9973** without permitting reattachment of the same one of overlay **9750** to electronic device **9700**.

(516) In other embodiments, the adhesive strength of first adhesive layer **9971** can be greater than the adhesive strength of second adhesive layer **9973**, such that when overlay **9750** is peeled away from electronic device **9700**, layers **9971-9973** are removed with overlay **9750**, which can allow reattachment of overlay **9750** to electronic device **9700**. In each of the embodiments presented in this paragraph, all of layers **9971-9973** can remain on electronic device **9700** or can be removed from electronic device **9700**.

when removing overlay **9750** from electronic device **9700**, or only portions of one or more of layers **9971-9973** can remain on electronic device **9700** or can be removed from electronic device **9700** when removing overlay **9750** from electronic device. In these embodiments, layers **9971-9973** can be designed to make overlay **9750** and layers **9971-9973** a single-use component.

(517) In several embodiments, overlay **9750** can be provided as part of an overlay applicator, as described above, which can facilitate applying overlay **9750** to electronic device **9700**. For example, in many embodiments, the overlay applicator can include overlay **9750**, layers **9971-9973**, an adhesive release liner, and/or other elements or constructions, such as described above. In several embodiments, the adhesive release liner can be similar to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**), adhesive release liner **1540** (FIG. **15**), adhesive release liner **2740** (FIGS. **27-30**), adhesive release liner **8240** (FIG. **82**), and/or adhesive release liner **9240** (FIG. **92**). In many embodiments, the adhesive release liner can cover the adhesive and protect it from contaminants until it is ready to be exposed and applied to electronic device **9700**. For example, the adhesive release liner can be adhered to second adhesive layer **9973** to cover layers **9971-9973**. For embodiments in which the adhesive strength of second adhesive layer **9973** is stronger than the adhesive strength of first adhesive layer **9971**, the adhesive release liner can be made of a suitable non-stick material, or treated with a suitable non-stick coating, such that the adhesive release liner can be peeled off from second adhesive layer **9973** without removing first adhesive layer **9971** from overlay **9750**. By removing the adhesive release liner and exposing second adhesive layer **9973** in a manner in which layers **9971-9973** remain adhered to overlay **9750**, overlay **9750** can be adhered to electronic device **9700** using layers **9971-9973**, as shown in FIG. **99**.

(518) In many embodiments, overlay **9750** can have dimensions coterminous with touchscreen **9701**. In other embodiments, overlay **9750** can extend beyond one or more of the curved sides (e.g., curved portion **9906**) of touchscreen **9701** to adhere in part to non-touchscreen portion **9702**, as shown in FIG. **99**. In many embodiments, adhesive component **9970** can have dimensions coterminous with overlay **9750**, such that layers adhesive component **9970** attach overlay **9750** to electronic device **9700** both at flat overlay portion **9853** and at curved overlay portions **9851** and **9852**. In a number of embodiments, adhesive carrier **9972** can be flexible to conform to the shape of overlay **9750**, such as at flat overlay portion **9853** and at curved overlay portions **9851** and **9852**. In certain other embodiments, adhesive component **9970** can have dimensions that extend only to the sides of flat overlay portion **9853**, and not extend along the curved overlay portions (e.g., **9851**, **9852**). In each of the embodiments presented in this paragraph, first adhesive layer **9971** and second adhesive layer **9973** can be configured to avoid having any air pockets between overlay **9750** and touchscreen **9701** across all of flat overlay portion **9853** and/or along the curved overlay portions (e.g., **9851**, **9852**). In the “certain other embodiments” presented in this paragraph, one or more air gaps or other material can be located between overlay **9750** and electronic device **9700** at curved overlay portions **9851** and/or **9852**.

(519) In a different embodiment, second adhesive layer **9973** is eliminated such that adhesive carrier **9972** directly contacts electronic device **9700**. In this embodiment, particularly when overlay **9750** is made of glass and touchscreen **9701** also is made of glass, overlay **9750**, first adhesive layer **9971**, and second adhesive layer **9973** can be part of a protective case for electronic device **9700** such that the case keeps adhesive carrier **9972** (which is not adhesive on bottom side **9986** in this embodiment) in physical contact against touchscreen **9701**.

(520) Returning to FIG. **97**, although overlay **9750** is shown in FIG. **97** as not extending onto top end **9705** or bottom end **9710**, various embodiments of the overlay (e.g., **9750**) and/or the adhesive component (e.g., **9970** (FIG. **99**)) can be shaped to cover all or portions of top end **9705** or bottom end **9710**. In some embodiments, the overlay (e.g., **9750**) and/or the adhesive component (e.g., **9970** (FIG. **99**)) can include cut-outs for the buttons, such as button **9711**, speakers, such as speaker **9706**, and/or other elements, such as cameras, light sensors, etc.

(521) Turning ahead in the drawings, FIG. **100** illustrates an enlarged cross-sectional view of an electronic device **10000**, and the bottom edge of a touchscreen **10001** of electronic device **10000**, and an overlay **10050**. The cross-sectional view can be similar to the cross-sectional view in FIG. **99**, and can correspond to a cross-section line similar to cross-section line **98-98** in FIG. **97**, and the enlarged portion of electronic device **10000** can be similar to the enlarged portion of electronic device **9700** identified in

FIG. 98. Overlay **10050** is merely exemplary, and embodiments of the overlay are not limited to the embodiments presented herein. The overlay can be employed in many different embodiments or examples not specifically depicted or described herein. Electronic device **10000** can be similar to electronic device **9700** (FIGS. **97-99**), and touchscreen **10001** can be similar to touchscreen **9701** (FIGS. **97-99**), but touchscreen **10001** of electronic device **10000** can be flat (e.g., similar to flat portion **9905** of touchscreen **9701**) without curved portions (e.g., without curved portions such as curved portions **9906**). (522) In many embodiments, electronic device **10000** can include a non-touchscreen portion **10002**, which can be similar to non-touchscreen portion **9702** (FIGS. **97-99**), but which can surround touchscreen **10001** on four sides. In several embodiments, non-touchscreen portion **10002** of electronic device **10000** can include declining portions, such as a declining portion **10006** at a curved edge at a right side **10003** of electronic device **10000**, at one or more sides of electronic device **10000**. In some embodiments, the declining portions (e.g., **10006**) can curve downward from, and/or decline below, the plane of the face (e.g., the plane of touchscreen **10001**) of electronic device **10000** at the sides (e.g., **10003**) of electronic device **10000**.

(523) Overlay **10050** can be similar to overlay **9750** (FIGS. **97-99**), and elements or constructions of overlay **10050** can be similar or identical to various elements or constructions of overlay **9750** (FIGS. **97-99**). For example, overlay **10050** can include a flat overlay portion **10053** and/or curved overlay portions, such as curved overlay portion **10052**. In many embodiments, the curved overlay portions (e.g., **10052**) can curve downward from and/or decline below, the plane of flat overlay portion **10053** as overlay **10050** extends towards the sides (e.g., **10003**) of electronic device **10000**.

(524) In many embodiments, overlay **10050** can be adhered to electronic device **10000** using an adhesive component **10070**. In some embodiments, adhesive component **10070** can be a single adhesive layer. In other embodiments, adhesive component **10070** can include an adhesive carrier, such as adhesive carrier **9972** (FIG. **97**), with adhesive layers on each side, such as first adhesive layer **9971** (FIG. **97**) and second adhesive layer **9973** (FIG. **97**). In yet other embodiments, the adhesive carrier can be a spacer that spaces overlay **10050** at a predetermined distance away from electronic device **10000**, creating an air gap **10062**. In some embodiments, the spacer of adhesive component **10070** can space overlay **10050** at a distance near but, not in contact with, touchscreen **10001**, which can be a distance of approximately 0.05 mm to approximately 0.5 mm, as examples. In a number of embodiments, the distance can be sufficiently small to transfer a capacitive value to touchscreen **10001** through overlay **10050** and across air gap **10062** when overlay **10050** is touched.

(525) In several embodiments, adhesive component **10070** can be attached to electronic device **10000** on curved portions and/or declining portions (e.g., **10006**) of electronic device **10000**. In many embodiments, adhesive component **10070** can be curved to conform to declining portion **10006** and/or curved overlay portion **10052**, as shown in FIG. **100**. In a number of embodiments, adhesive component **10070** can be attached to electronic device **10000** at non-touchscreen portion **10002**, such as on two or more sides surrounding touchscreen **10001**. In many embodiments, adhesive component **10070** is not attached to touchscreen **10001**. In other embodiments, an adhesive component, such as adhesive component **10070**, can be attached on a curved portion of a touchscreen, such as curved portion **9906** (FIG. **99**) of touchscreen **9701** (FIGS. **97-99**). In many embodiments, adhesive component **10070** can be transparent. For example, the adhesive, adhesive carrier, and/or spacer in the adhesive component (e.g., **10070**) can be optically clear and transmit through the light and/or display from the touchscreen (e.g., **10001**). In other embodiments, adhesive component **10070** can be non-transparent.

(526) In a different embodiment, air gap **10062** can be filled with a non-adhesive material. For example, air gap **10062** can be replaced with a transparent PET layer that is not adhesive. In the same or different embodiment, adhesive component **10070** can be similar or identical to adhesive component **9970** (FIG. **99**), first adhesive layer **9971** (FIG. **99**), and/or second adhesive layer **9973** (FIG. **99**) while still maintaining air gap **10062**.

(527) Proceeding to the next drawing, FIG. **101** illustrates a cross-sectional view of electronic device **9700** along cross-section line **98-98** in FIG. **97**, and a portion of the bottom edge of touchscreen **9701**, as identified in FIG. **98**, and an overlay **10150**. Overlay **10150** is merely exemplary, and embodiments of the overlay are not limited to the embodiments presented herein. The overlay can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay **10150** can be

similar to overlay **9750** (FIGS. **97-99**) and/or overlay **10050** (FIG. **100**), and elements or constructions of overlay **10150** can be similar or identical to various elements or constructions of overlay **9750** (FIGS. **97-99**) and/or overlay **10050** (FIG. **100**). For example, overlay **10150** can include a flat overlay portion **10153** and/or curved overlay portions, such as curved overlay portion **10152**. In many embodiments, the curved overlay portions (e.g., **10152**) can curve downward from and/or decline below, the plane of flat overlay portion **10153** as overlay **10150** extends towards the sides (e.g., **9703**) of electronic device **9700**. (528) In many embodiments, overlay **10150** can be attached to electronic device **9700** using an adhesive component **10170**. Adhesive component **10170** can be similar or identical to adhesive component **9970** (FIG. **99**), first adhesive layer **9971** (FIG. **99**), and/or second adhesive layer **9973** (FIG. **99**). In several embodiments, adhesive component **10170** can be a single layer of adhesive that can attach overlay **10150** to electronic device **9700**, such that overlay **10150** is adhered to electronic device **9700** (i.e., touchscreen **9701** only, or both touchscreen **9701** and one or more other portions (e.g., non-touchscreen portion **9702** (FIGS. **97-99**) of electronic device **9700**)) with a single layer of adhesive without an adhesive carrier, such as adhesive carrier **9972** (FIG. **99**). In many embodiments, adhesive component **10170** on overlay **10150** can be covered by an adhesive release liner, as described above, which can be peeled off to expose adhesive component **10170** and allow overlay **10150** to be attached to electronic device **9700**.

(529) In some embodiments, overlay **10150** the adhesive strength of adhesive component **10170** can be sufficiently strong such that the overlay breaks, fractures, and/or tears when the overlay is removed from electronic device **9750**, although overlay **10150** is devoid of being manufactured to create vulnerabilities, such as vulnerabilities **10483-10489** (FIG. **104**, described below). In other embodiments, overlay **10150** and/or adhesive component **10170** can be removed from electronic device **9750** without damaging overlay **10150**.

(530) Proceeding to the next drawing, FIG. **102** illustrates a cross-sectional view of electronic device **9700** along cross-section line **98-98** in FIG. **97**, and a portion of the bottom edge of touchscreen **9701**, as identified in FIG. **98**, and an overlay **10250**. Overlay **10250** is merely exemplary, and embodiments of the overlay are not limited to the embodiments presented herein. The overlay can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay **10250** can be similar to overlay **9750** (FIGS. **97-99**), overlay **10050** (FIG. **100**), and/or overlay **10150** (FIG. **101**), and elements or constructions of overlay **10250** can be similar or identical to various elements or constructions of overlay **9750** (FIGS. **97-99**), overlay **10050** (FIG. **100**), and/or overlay **10150** (FIG. **101**). In many embodiments, overlay **10250** can be flat across the top of overlay **10250** from side to side, and the bottom of overlay **10250** can include a flat overlay bottom portion **10253** and one or more curved overlay bottom portions, such as curved overlay bottom portion **10252**. As shown in FIG. **102**, a thickness of overlay **10250** can be greater at the sides around curved overlay bottom portion **10252** than in the middle portion of overlay **10250** around flat overlay bottom portion **10253**.

(531) In many embodiments, overlay **10250** can be attached to electronic device **9700** using an adhesive component **10270**. Adhesive component **10270** can be similar or identical to adhesive component **9970** (FIG. **99**), first adhesive layer **351** (FIG. **3**), second adhesive layer **353** (FIG. **3**), and/or adhesive component **10170** (FIG. **101**). In several embodiments, adhesive component **10270** can be a single layer of adhesive that can attach overlay **10250** to electronic device **9700**, such that overlay **10250** is adhered to electronic device **9700** (i.e., touchscreen **9701** only, or both touchscreen **9701** and one or more other portions (e.g., non-touchscreen portion **9702** (FIGS. **97-99**) of electronic device **9700**)) with a single layer of adhesive without an adhesive carrier, such as adhesive carrier **9972** (FIG. **99**). In other embodiments, adhesive component **10270** can optionally include an adhesive carrier, such as adhesive carrier **9972** (FIG. **99**), as well as adhesive layers on each side, such as first adhesive layer **9971** (FIG. **99**) and second adhesive layer **9973** (FIG. **99**). In many embodiments, adhesive component **10270** on overlay **10250** can be covered by an adhesive release liner, as described above, which can be peeled off to expose adhesive component **10270** and allow overlay **10250** to be attached to electronic device **9700**.

(532) Turning ahead in the drawings, FIG. **103** illustrates a perspective view of an adhesive carrier **10372**. Adhesive carrier **10372** is merely exemplary, and embodiments of the adhesive carrier are not limited to the embodiments presented herein. The adhesive carrier can be employed in many different embodiments or examples not specifically depicted or described herein. Adhesive carrier **10372** can be similar to adhesive carrier **9972** (FIG. **99**), and elements or constructions or adhesive carrier **10372** can

be similar or identical to various elements or constructions of adhesive carrier **9972** (FIG. **99**). In many embodiments, adhesive carrier **10372** can be a transparent PET layer or other suitable material. In several embodiments, adhesive carrier **10372** can include one or more perforations, such as perforations **10383-10389**.

(533) In a number of embodiments, the perforations (e.g., **10383-10389**) can include a series of microscopic holes along a line or other path that generally are not visible to the unaided eye. In a number of embodiments, the holes can be sufficiently small to not distort a noticeable amount of the light optically transmitted through adhesive carrier **10372**. For example, the holes can each be less than approximately 0.1 mm in diameter. In some embodiments, for example, the holes can be approximately 0.001 mm to 0.09 mm in diameter. In a number of embodiments, the holes can each extend through the thickness of adhesive carrier **10372**. In other embodiments, the holes can extend partially through the thickness of adhesive carrier **10372**, such as in a top portion and/or a bottom portion of adhesive carrier **10372**, but not extend fully through the thickness of adhesive carrier **10372**.

(534) In many embodiments, adhesive carrier **10372** can be used with adhesive layers on each side, similarly to layers **9971-9973** in FIG. **99**, to attach an overlay (e.g., **9750** (FIGS. **97-99**), **10050** (FIG. **100**), **10150** (FIG. **101**), **10250** (FIG. **102**)) to an electronic device (e.g., **9700** (FIGS. **97-99**), **10000** (FIG. **100**)). The one or more of the perforations (e.g., **10383-10389**) can provide structural vulnerabilities in adhesive carrier **10372**, such that adhesive carrier **10372** can tear at one or more of the perforations (e.g., **10383-10389**) when the overlay is removed from the electronic device. In many embodiments, one or more of the adhesive layers can have a sufficient adhesive strength in certain portions of the adhesive layers such that lifting and/or peeling off the overlay from the electronic device can result in a tear in adhesive carrier **10372** along a perforation (e.g., **10383-10389**). The perforation(s) can assist in making adhesive carrier **10372** a single-use item.

(535) In several embodiments, the perforations (e.g., **10383-10389**) can extend partially or fully across a portion of adhesive carrier **10372**. For example, perforation **10383** can extend fully across adhesive carrier **10372** from one end to the other end. As other examples, perforations **10388** and **10389** can extend fully across adhesive carrier **10372** from one side to the other side. When the overlay is peeled away from the electronic device, adhesive carrier **10372** can tear along the perforations fully across adhesive carrier **10372**. For example, adhesive carrier **10372** includes perforation **10383**, which invisibly divides adhesive carrier **10372** into a first side **10361** and a second side **10362**. In many embodiments, first side **10361** can include a stronger adhesive on the top adhesive layer than on the bottom adhesive layer, and second side **10362** can include a stronger adhesive on the bottom adhesive layer than the top adhesive layer. When the overlay is peeled away from the electronic device, adhesive carrier **10372** can be more strongly adhered to the overlay on first side **10361** and more strongly adhered to the electronic device on second side **10362**, such that peeling across perforation **10383** results in a tear along perforation **10383**.

(536) As further examples, perforations **10384**, **10385**, and **10387** can extend partially across adhesive carrier **10372**. When the overlay is peeled away from the electronic device, adhesive carrier **10372** can start tearing along the partial perforations (e.g., **10384**, **10385**, **10387**) and, in many embodiments, can continue tearing beyond the end of the perforation as the overlay is peeled away from the electronic device.

(537) As yet another example, perforation **10386** can have a non-linear shape, such as a curved shape shown in FIG. **103**, and can extend from a first side to an adjacent side. When the overlay is peeled away from the electronic device, adhesive carrier **10372** can tear along the curved perforation (e.g., **10386**).

(538) In a number of embodiments, each hole in the series of holes can be spaced apart sufficiently close to facilitate tearing adhesive carrier **10372** when the overlay is peeled away from the electronic device. For example, adjacent holes can be spaced approximately 0.005 mm to approximately 0.2 mm apart from each other, depending on the size of the holes and the strength of the adhesive layers.

(539) Turning ahead in the drawings, FIG. **104** illustrates a perspective view of an overlay **10450** and an adhesive component **10470**. Overlay **10450** and adhesive component **10470** are merely exemplary, and embodiments of the overlay and adhesive component are not limited to the embodiments presented herein. The overlay and adhesive component can be employed in many different embodiments or examples not specifically depicted or described herein. Overlay **10450** can be similar to overlay (e.g.,

9750 (FIGS. 97-99), 10050 (FIG. 100), 10150 (FIG. 101), 10250 (FIG. 102)), and elements or constructions of overlay 10450 can be similar or identical to various elements or constructions of overlay (e.g., 9750 (FIGS. 97-99), 10050 (FIG. 100), 10150 (FIG. 101), 10250 (FIG. 102)). Adhesive component 10470 can be similar to adhesive component 9970 (FIG. 99), adhesive component 10170 (FIG. 101), adhesive component 10270 (FIG. 102), and/or adhesive carrier 10372 (FIG. 103), and elements or constructions or adhesive component 10270 can be similar or identical to various elements or constructions of adhesive component 9970 (FIG. 99), adhesive component 10170 (FIG. 101), adhesive component 10270 (FIG. 102), and/or adhesive carrier 10372 (FIG. 103).

(540) In many embodiments, overlay **10450** can include one or more vulnerabilities, such as vulnerabilities **10483-10489**. Vulnerabilities **10483-10489** can be similar or identical to perforations **10383-10389** (FIG. 103). In several embodiments, vulnerabilities **10483-10839** can be configured such that overlay **10450** breaks when peeled away or removed from the electronic device (e.g., **9700** (FIGS. 97-99), **10000** (FIG. 100)). In some overlay embodiments, such as glass overlays, vulnerabilities **10483-10489** can be nicks, perforations, or other vulnerabilities to fracture. In many embodiments, the overlay can be used with a single adhesive layer (e.g., adhesive component **10170** (FIG. 101), adhesive component **10270** (FIG. 102)). In other embodiments, the overlay can be used with an adhesive carrier (e.g., **9972** (FIG. 99), **10372**).

(541) In a number of embodiments, the perforations (e.g., **10383-10389**), nicks, or vulnerabilities in the adhesive carrier (e.g., **10372**) and/or overlay can advantageously allow for single use of the overlay, and destruction of adhesive component e.g., **10470** and/or overlay **10350** upon removal to prevent reattachment of the overlay and adhesive component **10470** to the electronic device. Although adhesive carrier **10372** (FIG. 103), adhesive component **10470**, and overlay **10750** are shown as rounded at the sides, similar to adhesive carrier **9972** (FIG. 99), adhesive component **9970** (FIG. 99), and overlay **9750** (FIGS. 97-99) respectively, various embodiments of adhesive carrier **10372** (FIG. 103), adhesive component **10470**, and overlay **10750** can be flat. For example, adhesive carrier **10372** (FIG. 103), adhesive component **10470**, and overlay **10750** can be flat and can be attached to a flat touchscreen without curved portions, such as touchscreen **10001** (FIG. 100) of electronic device **10000** (FIG. 100).

(542) In several embodiments, the vulnerabilities (e.g., **10483-10489**) can extend partially or fully across a portion of overlay **10450**. For example, when overlay **10450** is peeled away and/or removed from the electronic device, overlay **10450** can tear along the vulnerabilities. For example, overlay **10450** includes vulnerability **10483**, which invisibly divides overlay **10450** into a first side **10461** and a second side **10462**. When overlay **10450** is peeled away from the electronic device, overlay **10450** can break along vulnerability **10483**.

(543) In many embodiments, the overlay (e.g., overlay (e.g., **9750** (FIGS. 97-99), **10050** (FIG. 100), **10150** (FIG. 101), **10250** (FIG. 102), and/or overlay **10450** (FIG. 104)), and/or the adhesive component (e.g., adhesive component **9970** (FIG. 99), adhesive component **10170** (FIG. 101), adhesive component **10270** (FIG. 102), adhesive carrier **10372** (FIG. 103), and/or adhesive component **10470**) can be configured for single-use application of the overlay, such that when the overlay is removed from the electronic device, at least a portion of the adhesive component is detached from at least a portion of the overlay. For example, if overlay **9750** (FIGS. 97-99) is removed from electronic device **9700** (FIGS. 97-99), at least a portion of adhesive component **9970** (FIG. 99) remain adhered to electronic device **9700** (FIGS. 97-99) and become separated from overlay **9750** (FIGS. 97-99), such as when the adhesive strength of second adhesive layer **9973** (FIG. 99) is stronger than the adhesive strength of first adhesive layer **9971** (FIG. 99). As another example, if overlay **10150** (FIG. 101) is removed from electronic device **9700** (FIG. 101), overlay **10150** (FIG. 101) can break, resulting in at least a portion of adhesive component **10170** (FIG. 101) becoming separated from overlay **10150** (FIG. 101). As yet another example, if an overlay (e.g., overlay (e.g., **9750** (FIGS. 97-99), **10050** (FIG. 100), **10150** (FIG. 101), **10250** (FIG. 102), and/or **10450** (FIG. 104)) is used with adhesive carrier **10372** (FIG. 103), adhesive carrier **10372** can tear, such as along one or more of perforations **10383-10389** (FIG. 103), when the overlay is removed from the electronic device, which can result in at least a portion of adhesive carrier **10372** being detached from the overlay. As a further example, if overlay **10450** (FIG. 104) and adhesive component **10470** (FIG. 104) are attached to an electronic device, then removed, overlay **10450** (FIG. 104) can break, such as along one or more of vulnerabilities **10483-10489** (FIG. 104), when overlay

10450 (FIG. 104) is removed from the electronic device, which can result in at least a portion of adhesive component **10470 (FIG. 104)** being detached from overlay **10450 (FIG. 104)**.

(544) In many embodiments, the overlay (e.g., overlay (e.g., **9750 (FIGS. 97-99)**, **10050 (FIG. 100)**, **10150 (FIG. 101)**, **10250 (FIG. 102)**, and/or **10450 (FIG. 104)**), and/or the adhesive component (e.g., adhesive component **9970 (FIG. 99)**, adhesive component **10170 (FIG. 101)**, adhesive component **10270 (FIG. 102)**, adhesive carrier **10372 (FIG. 103)**, and/or adhesive component **10470**) can be configured such that the overlay and/or the adhesive component cannot be re-adhered to the electronic device using the adhesive component after the single-use application of the overlay and after removal of the overlay from the screen of the device. For example, the overlay and/or the adhesive component can be damaged and/or destroyed, such that the overlay and/or the adhesive component cannot be re-adhered in the same way as the initial adhesion of the overlay to the electronic device in the single-use application of the overlay. In several embodiments, the overlay and/or the adhesive component can be configured such that re-adhesion of the overlay to the electronic device using the adhesive component after the single-use application of the overlay and after removal of the overlay from the electronic device can produce a distortion of at least a portion of a display of the screen (e.g., touchscreen **9701 (FIG. 97)**) of the electronic device (e.g., **9700 (FIG. 97)**) that is seen through the overlay and the adhesive component.

(545) Turning ahead in the drawings, FIG. **105** illustrates a flow chart for an embodiment of a method **10500**, according to another embodiment. Method **10500** is merely exemplary and is not limited to the embodiments presented herein. Method **10500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **10500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **10500** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **10500** can be combined or skipped.

(546) Referring to FIG. **105**, method **10500** can include a block **10501** of providing an overlay. The overlay can be similar or identical to overlay **130 (FIG. 1)**, overlay **430 (FIGS. 4-5)**, overlay **630 (FIG. 6)**, overlay **730 (FIG. 7)**, and/or overlay **1530 (FIG. 15)**, overlay **2930 (FIGS. 29-30)**, overlay **8230 (FIG. 82)**, overlay **9230 (FIG. 92)**, overlay **9750 (FIGS. 97-99)**, overlay **10050 (FIG. 100)**, overlay **10150 (FIG. 101)**, overlay **10250 (FIG. 102)**, and/or overlay **10450 (FIG. 104)**. In many embodiments, the overlay can include a top side and a bottom side. The top side can be similar or identical to top side **9981 (FIG. 99)**. The bottom side can be similar or identical to bottom side **9982 (FIG. 99)**.

(547) In a number of embodiments, block **10501** of providing an overlay can include providing the overlay such that the overlay can include one or more curved portions configured to correspond to one or more curved areas of a screen of an electronic device. The curved portions can be similar to curved overlay portions **9851 (FIG. 98)** and/or **9852 (FIGS. 98-99)**.

(548) In some embodiments, method **10500** next can include a block **10502** of providing an adhesive component. In the same or different embodiments, block **10502** can include coupling together the overlay and the adhesive component. The adhesive component can be similar or identical to adhesive component **9970 (FIG. 99)**, adhesive component **10170 (FIG. 101)**, adhesive component **10270 (FIG. 102)**, adhesive carrier **10372 (FIG. 103)**, and/or adhesive component **10470**. In several embodiments, the adhesive component can include a top side and a bottom side. The top side can be similar or identical to top side **9983 (FIG. 99)**. The bottom side can be similar or identical to bottom side **9984 (FIG. 99)**. In many embodiments, the top side of the adhesive component can be adhered to the bottom side of the overlay. In a number of embodiments the adhesive component can be configured to adhere the bottom side of the overlay to a screen of an electronic device in a single-use application of the overlay by adhering the bottom side of the adhesive component to the screen of the electronic device. The electronic device can be similar or identical to electronic device **9700 (FIGS. 97-99)** and/or electronic device **10000 (FIG. 100)**. The screen can be similar or identical to touchscreen **9701 (FIGS. 97-99)** and/or touchscreen **10001 (FIG. 100)**.

(549) In several embodiments, the overlay and the adhesive component can be configured such that, when the overlay is removed from being adhered to the screen of the electronic device after the single-use application of the overlay, at least a portion of the adhesive component can be detached from at least a portion of the overlay.

(550) In various embodiments, the overlay and the adhesive component can be configured such that the overlay cannot be re-adhered to the screen of the electronic device using the adhesive component after the single-use application of the overlay and after removal of the overlay from the screen of the electronic device.

(551) In many embodiments, the overlay and the adhesive component are configured such that re-adhesion of the overlay to the screen of the electronic device using the adhesive component after the single-use application of the overlay and after removal of the overlay from the screen of the electronic device produces a distortion of at least a portion of a display of the screen of the electronic device that is seen through the overlay and the adhesive component.

(552) In several embodiments, the adhesive component can include an adhesive carrier including a top side and a bottom side. The adhesive carrier can be similar or identical to adhesive carrier **9972** (FIG. **99**) and/or adhesive carrier **10372** (FIG. **103**). The top side can be similar or identical to top side **9985** (FIG. **99**). The bottom side can be similar or identical to bottom side **9986** (FIG. **99**). In many embodiments, the adhesive component also can include a first adhesive layer at the top side of the adhesive carrier. The first adhesive layer can be similar or identical to first adhesive layer **9971** (FIG. **99**). In several embodiments, the first adhesive layer can adhere the top side of the adhesive carrier to the bottom side of the overlay. In some embodiments, the adhesive component additionally can include a second adhesive layer at the bottom side of the adhesive carrier. The second adhesive layer can be similar or identical to second adhesive layer **9973** (FIG. **99**). In many embodiments, the second adhesive layer can be configured to adhere the bottom side of the adhesive carrier to the screen of the electronic device in the single-use application of the overlay.

(553) In various embodiments, an adhesive strength of the second adhesive layer is stronger than an adhesive strength of the first adhesive layer. In other embodiments, the adhesive strength of the second adhesive layer can be weaker than or the same as the adhesive strength of the first adhesive layer.

(554) In many embodiments, the adhesive carrier can include one or more perforations. The perforations can be similar or identical to perforations **10383-10389** (FIG. **103**). In several embodiments, the one or more perforations each can include a series of holes extending at least partially through the adhesive carrier. In various embodiments, each hole of the series of holes can have a diameter between approximately 0.001 mm and approximately 0.1 mm.

(555) In several embodiments, the adhesive component can be configured such that the adhesive component includes a single layer of adhesive and is devoid of an adhesive carrier. For example, the adhesive component can be similar or identical to adhesive component **10070** (FIG. **100**), adhesive component **10170** (FIG. **102**), and/or adhesive component **10270** (FIG. **103**). In several embodiments, the overlay can include one or more vulnerabilities to fracture. For example, the vulnerabilities to fracture can be similar or identical to vulnerabilities **10483-10489** (FIG. **104**). In a number of embodiments, the single layer of adhesive can have an adhesive strength such that the overlay fractures at the one or more vulnerabilities to fracture when the overlay is removed from being adhered to the screen of the electronic device after the single-use application of the overlay.

(556) In many embodiments, method **10500** optionally can include a block **10503** of providing an overlay applicator. In the same or different embodiments, block **10503** can include coupling together the overlay applicator and the adhesive component. The overlay applicator can be similar to overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator tray **8000** (FIG. **80**), and/or overlay applicator tray **9100** (FIG. **91**). In many embodiments, the overlay applicator can include the overlay and the adhesive component.

(557) In several embodiments, the overlay applicator can include an adhesive release liner that includes a top side and a bottom side. The adhesive release liner can be similar or identical to adhesive release liner **140** (FIG. **1**), adhesive release liner **440** (FIGS. **4-5**), adhesive release liner **640** (FIG. **6**), adhesive release liner **740** (FIG. **7**), adhesive release liner **1540** (FIG. **15**), adhesive release liner **2740** (FIGS. **27-30**), adhesive release liner **8240** (FIG. **82**), and/or adhesive release liner **9240** (FIG. **92**). In many embodiments, the top side of the adhesive release liner can be removably attached to the bottom side of the overlay using the adhesive component. In several embodiments, the adhesive release liner can be

configured to protect the adhesive component at the bottom side of the overlay from contaminants. (558) In a number of embodiments, the overlay applicator can include an alignment mechanism. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), alignment mechanism **3557** (FIGS. **35-36**), alignment piece **8010** (FIG. **80**), and/or alignment piece **9110** (FIG. **91**). In various embodiments, the alignment mechanism can be configured to align the overlay with the screen of the electronic device as the overlay is adhered to the screen of the electronic device.

(559) In several embodiments, the overlay applicator can include a pull tab. The pull tab can be similar or identical to pull tab **150** (FIG. **1**), pull tab **450** (FIGS. **4-5**), pull tab **650** (FIG. **6**), pull tab **750** (FIGS. **7, 42, 44-45, 48-49**), pull tab **1550** (FIG. **15**), pull tab **2750** (FIGS. **27-30**), pull tab **6055** (FIG. **60**), first pull tab **8042** (FIG. **80**), second pull tab **8022** (FIG. **80**), first pull tab **9142** (FIG. **91**), and/or second pull tab **9122** (FIG. **91**). In a number of embodiments, the pull tab can be configured to facilitate removal of the adhesive release liner from the bottom side of the overlay to expose the adhesive component to the screen of the electronic device.

(560) Turning to the drawings, FIG. **106** illustrates a perspective view of a machine **10600** in a closed configuration, according to an embodiment. FIG. **107** illustrates a perspective view of a machine **10600** in an opened configuration. Machine **10600** is merely exemplary, and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **10600** can include a base **10620**, a lid **10630**, and/or a hinge mechanism **10640**. Machine **10600** can be similar to machine **6900** in FIGS. **69-74**, and various elements of machine **10600** can be similar or identical to various elements of machine **6900** in FIGS. **69-74**. Base **10620** can be similar to support base **6920** in FIGS. **69-74**, and various elements of base **10620** can be similar or identical to various elements of base **6920** in FIGS. **69-74**. Lid **10630** can be similar to lid **6930** in FIGS. **69-74**, and various elements of lid **10630** can be similar or identical to various elements of lid **6930** in FIGS. **69-74**. Hinge **10640** can be similar to hinge **6940** in FIGS. **69-74**, and various elements of hinge **10640** can be similar or identical to various elements of hinge **6940** in FIGS. **69-74**.

(561) In many embodiments, hinge mechanism **10640** can attach lid **10630** to base **10620**, and/or can allow lid **10630** to rotate with respect to base **10620** between a closed configuration, as shown in FIG. **106**, and an opened configuration, as shown in FIG. **107**, and vice versa. In some embodiments, hinge mechanism **10640** can include one or more axles, base axle mounts, lid axle supports, and/or springs (not shown), which can be similar or identical to corresponding elements of hinge **6940** in FIGS. **69-74**. In many embodiments, the one or more springs can bias lid **10630** to rotate away from base **10620** toward an opened configuration, as shown in FIG. **107**. In several embodiments, lid **10630** can include a release button **10633**. Release button **10633** can be similar to release buttons **7023** in FIG. **71**. In several embodiments, when machine **10600** is in the closed configuration, as shown in FIG. **106**, release button **10633** can be depressed to release lid **10630** to rotate open to the opened configuration, as shown in FIG. **107**.

(562) In many embodiments, base **10620** can include an adjustable cradle **10750**, as shown in FIG. **107**. Adjustable cradle **10750** can be similar to cradle **6950** in FIG. **69**, and various elements of adjustable cradle **10750** can be similar or identical to various elements of cradle **6950** in FIG. **69**, but instead of being for a single size of electronic device and/or replaceable with different cradles to hold different device sizes, adjustable cradle **10750** can be configured to hold electronic devices of varying sizes. In many embodiments, adjustable cradle **10750** can be part a permanent part of base **10620**.

(563) Turning ahead in the drawings, FIG. **108** illustrates a perspective view of base **10620** and adjustable cradle **10750**. As shown in FIG. **108**, adjustable cradle **10750** can include a slot **10856**, a left side holder **10851**, a right side holder **10852**, and/or a top holder **10853**. Slot **10856** can be similar to slot **6956** in FIG. **69**. In a number of embodiments, slot **10856** can include a recessed region below an upper surface **10870** of cradle **10750**. In several embodiments, slot **10856** can include a left side wall **10871**, a right side wall **10872**, a top side wall **10873**, a bottom side wall **10874**, and/or a slot base surface **10875**. In many embodiments, adjustable cradle **10750** can hold an electronic device having a size up to the dimensions of slot **10856**. In a number of embodiments, left side holder **10851** and/or right side holder

10852 can be adjustable side-to-side within slot **10856** along an x-direction (as shown in FIGS. **106**, **108**, **109**, **110**, **111**, and **112**) that extends between left side wall **10871** and right side wall **10872** (and vice versa) of slot **10856**. In various embodiments, left side holder **10851** can be configured to hold a left side of the electronic device, and/or right side holder **10852** can be configured to hold a right side of the electronic device. In some embodiments, left side holder **10851** can adjust leftward to a fully opened position in which the rightmost face of left side holder **10851** is parallel with left side wall **10871**, and/or right side holder **10852** can adjust rightward to a fully opened position in which the leftmost face of right side holder **10852** is parallel with right side wall **10872**.

(564) Continuing to the next drawing, FIG. **109** illustrates a perspective view of a portion of adjustable cradle **10750**, showing internal components of a portion of adjustable cradle **10750**. In many embodiments, left side holder **10851** can be attached to, or integrally formed with, a left side plate **10951**, and/or right side holder **10852** can be attached to, and/or integrally formed with, a right side plate **10952**. In a number of embodiments, left side plate **10951** and/or right side plate **10952** can be positioned internally within base **10620**, below upper surface **10870** (FIG. **108**) and/or slot base surface **10875**. In several embodiments, left side plate **10951** and/or right side plate **10952** can slide side to side (e.g., along the x-direction) along one or more guide rails **10955**. In a number of embodiments, left side plate **10951** can include a gear engagement portion **10953**, and/or right side plate **10952** can include a gear engagement portion **10954**.

(565) In several embodiments, gear engagement portion **10953** and/or gear engagement portion **10954** can be configured to engage with a spur gear **10956**. Spur gear **10956** can rotate counterclockwise when left side plate **10951** and left side holder **10851** move leftward and when right side plate **10952** and right side holder **10852** move rightward. Spur gear **10956** can rotate clockwise when left side plate **10951** and left side holder **10851** move rightward and when right side plate **10952** and right side holder **10852** move leftward. Spur gear **10956** can regulate the movement of left side holder **10851** and right side holder **10852** with respect to each other, such that left side holder **10851** and right side holder **10852** can be approximately the same distance from a center of slot **10856** between left side wall **10871** and right side wall **10872**.

(566) In a number of embodiments, spur gear **10956** can be attached to a rotor spring **10957**, which can bias spur gear clockwise, which can bias left side holder **10851** and right side holder **10852** toward each other (e.g., left side holder **10851** rightward and right side holder **10852** leftward), which can advantageously automatically center an electronic device to the center of slot **10856** between left side wall **10871** and right side wall **10872** when the electronic device is placed between left side holder **10851** and right side holder **10852**. In some embodiments, when left side holder **10851** and right side holder **10852** are opened away from each other beyond a predetermined distance, one or more hooks can engage with left side holder **10851** and/or right side holder **10852** to hold left side holder **10851** and right side holder **10852** open and apart from each other in an opened position until a release latch **10958** is activated (e.g., depressed), after which the spring bias provided by rotor spring **10957** can cause left side holder **10851** and right side holder **10852** to close towards each other to a closed position. In some embodiments, release latch **10958** can be positioned such that an electronic device can activate (e.g., depress) it when the electronic device is seated into adjustable cradle **10750**. In other embodiments, the release latch (e.g., **10958**) can be positioned in another suitable position on base **10620**.

(567) Turning ahead in the drawings, FIG. **110** illustrates a perspective view of base **10620**, in which an electronic device **11000** is being inserted into adjustable cradle **10750**. As shown in FIG. **110**, left side holder **10851** and right side holder **10852** can be held open and apart, as described above, which can allow electronic device **11000** to be inserted between left side holder **10851** and right side holder **10852**. In a number of embodiments, top holder **10853** can be adjustable within slot **10856** along a y-direction (as shown in FIGS. **106**, **108**, **109**, **110**, **111**, **112**, and **116**, in which the arrow points “top-ward” and the opposite is “bottomward”) that extends between top side wall **10873** and bottom side wall **10874** (and vice versa) of slot **10856**.

(568) In several embodiments, base **10620** can include an alignment base **11051**, which can include a left alignment pin and/or a right alignment pin. Alignment base **11051** can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9**, **13-14**), alignment base **1632** (FIGS. **16-19**), alignment base

2035 (FIG. 20), alignment base 3112 (FIGS. 31-34), alignment base 3514 (FIGS. 35-36), alignment base 3814 (FIG. 38), alignment base 4734 (FIG. 47), alignment base 6414 (FIG. 64), alignment base 6424 (FIG. 64), alignment base 6434 (FIG. 64), and/or alignment base 6953 (FIGS. 69, 73). In many embodiments, alignment base 11051 can be configured to hold an alignment tab of an overlay applicator, as described below in further detail. In some embodiments, the alignment pins of alignment base 11051 can be different sizes, such that the alignment tab can be inserted on alignment base 11051 with a first side (e.g., an adhesive side configured to adhere to the screen or other surface of electronic device 11000) of the overlay applicator face down, but not with the first side of the overlay applicator face up.

(569) In a number of embodiments, top 11003 of device 11000 can be used to press top holder 10853 top-ward away from bottom side wall 10874. In a number of embodiments, when top holder 10853 is pressed top-ward away from bottom side wall 10874, a portion or all of top holder 10853 can be positioned within a top holder well 11053, which can be a recessed cavity extending top-ward (e.g., away from bottom side wall 10874) beyond top side wall 10873. In a number of embodiments, base 10620 can include one or more guide rails 11055. In some embodiments, top holder 10853 can adjust top-ward to a fully opened position in which the bottom most face of top holder 10853 is parallel with top side wall 10873.

(570) In many embodiments, electronic device 11000 can be manually used to push top holder 10853 top-ward until electronic device 11000 can fit between top holder 10853 and bottom side wall 10874, at which point electronic device 11000 can be lowered to slot base surface 10875. When electronic device 11000 approaches slot base surface 10875, electronic device 11000 can activate (e.g., depress) latch 10958, which can cause left side holder 10851 and right side holder 10852 to move inward toward each other, which can center electronic device 11000 within slot 10856. For example, left side holder 10851 can press rightward on a left side 11001 of electronic device 11000, and right side holder 10852 can press leftward on a right side 11002 of electronic device 11000. Top holder 10853 can push electronic device 11000 bottomward within slot 10856, such that a bottom 11004 of electronic device 11000 abuts bottom side wall 10874. In many embodiments, the electronic device (e.g., 11000) can be inserted such that a side of the electronic device that is used to push top holder 10853 top-ward runs along a width (e.g., a shorter dimension than the length) of electronic device 11000, such as top 11003 shown in FIG. 110. In other embodiments, adjustable cradle 10750 can be configured such that the electronic device can be inserted such that the side of the electronic device that is used to push top holder 10853 top-ward runs along a length of the electronic device, such that slot 10856 is larger in the x-direction than in the y-direction.

(571) Turning ahead to the next drawing, FIG. 111 illustrates a plan view of alignment base 11051, a pin holder plate 11151, top holder 10853, a top holder plate 11153, a spur gear 11157, and/or a rotor spring 11158. In many embodiments, alignment base 11051 can be attached to, or integrally formed with, pin holder side plate 11151. In several embodiments, top holder 10853 can be attached to, or integrally formed with, top holder plate 11153. In a number of embodiments, pin holder plate 11151, top holder plate 11153, spur gear 11157, and/or rotor spring 11158 can be positioned internally within base 10620, below upper surface 10870 (FIG. 108) and/or slot base surface 10875 (FIG. 108). In a number of embodiments, pin holder plate 11151 and/or top holder plate 11153 can be adjustable between top and bottom positions (e.g., along the y-direction) along guide rails 11055 (FIG. 110).

(572) In several embodiments, spur gear 11157 can be a two-step spur gear, with an outer step 11159 and an inner step 11160. In several embodiments, pin holder plate 11151 can include a gear engagement portion 11152, which can engage with inner step 11160 of spur gear 11157, and/or top holder plate 11153 can include a gear engagement portion 11154, which can engage with outer step 11159 of spur gear 11157. In many embodiments, rotor spring 11158 can bias spur gear 11157 to rotate clockwise, which can bias top holder 10853 and/or alignment base 11051 bottomward toward bottom side wall 10874 (FIG. 108). In many embodiments, outer step 11159 of spur gear 11157 can have a radius approximately double a radius of inner step 11160 of spur gear 11157 (e.g., a 2:1 gear ratio), such that when top holder 10853 moves a first distance top-ward or bottomward along the y-direction, alignment base 11051 can move a second distance that is half the first distance top-ward or bottomward, respectively, along the y-direction. In several embodiments, alignment base 11051 can protrude outward (in the z-direction, as shown in FIGS. 106, 110, and 116, in which the arrow points “outward,” and the opposite is “inward”), extending

base **10620** (FIG. **106**) to lid **10630** (FIG. **106**) (and vice versa)) through top holder **10853**, and top holder **10853** can include apertures **11155** and **11156**, which can allow alignment base **11051** to move with respect to top holder **10853** when alignment base **11051** and top holder **10853** move different distances along the y-direction. For example, when top holder **10853** is at a bottommost position (e.g., closest to bottom side wall **10874** (FIG. **108**)), alignment base **11051** can be positioned at a topmost position within apertures **11155** and **11156**, and when top holder **10853** is at a topmost relative position (e.g., furthest away from bottom side wall **10874** (FIG. **108**)), alignment base **11051** can be positioned at a bottommost relative position within apertures **11155** and **11156**.

(573) For clarity, as used herein for FIGS. **106-142**, the z-direction (and the associated terms outward and inward) can refer to an axis running orthogonal to a plane of the adjustable cradle (e.g., **10750**) that is parallel to the screen of the electronic device (e.g., **11000**) when the electronic device is seated in the adjustable cradle. For example, the z-direction can be orthogonal to slot base surface **10875**. The x-direction (and the associated terms left/leftward and right/rightward) and the y-direction (and the associated terms top/top-ward and bottom/bottomward) are in the plane that is orthogonal to the z-direction. The machine (e.g., **10600**) can be rotated about the z-direction and used in any orientation. The x-direction and y-direction are not limited to any specific absolute directions, but rather are used as an indication of directions that are orthogonal to the z-direction and perpendicular to each other. The terms “top” and “bottom” in the y-direction are used merely to designate opposite sides, not absolute top or absolute bottom, and are synonymous with a first side and a second side opposite the first side. Similarly, the terms “right” and “left” in the x-direction are used merely to designate opposite sides, and are synonymous with a third side and a fourth side opposite the third side, with the x-direction being perpendicular to the y-direction in the plane that is orthogonal to the z-direction. As an example, regardless of how the adjustable cradle is oriented in front of a user, top holder **10853** can be designated as being at the “top” of adjustable cradle **10750**, while bottom side wall **10874** is at the “bottom” of adjustable cradle **10750** at an opposite side of adjustable cradle **10750**, thus forming the y-direction between the top and the bottom of adjustable cradle **10750**.

(574) Continuing to the next drawing, FIG. **112** illustrates a plan view of base **10620**, in which electronic device **11000** is seated within adjustable cradle **10750**. As shown in FIG. **112**, when electronic device **11000** is seated within adjustable cradle **10750**, bottom **11004** of electronic device **11000** abuts bottom side wall **10874**, and electronic device **11000** is horizontally centered (along the x-direction) within slot **10856**. In many embodiments, adjustable cradle **10750** can advantageously be configured such that, when electronic device **11000** is seated within adjustable cradle **10750** with bottom **11004** abutting bottom side wall **10874**, a distance **11261** between a center **11262** (e.g., top-to-bottom center along the y-direction) of a first dimension (e.g., the length of electronic device **11000** as shown in FIG. **112**, or alternatively, the width of electronic device **11000**) and a y-position **11263** of alignment base **11051** along the y-direction can be approximately the same for any size of electronic device (e.g., **11000**) that is seated within adjustable cradle **10750**. This approximately constant distance for distance **11261** can be maintained by the 2:1 gear ratio of spur gear **11157** (FIG. **111**). By maintaining this approximately constant distance, design and application of overlay applicators for different sizes of electronic devices (e.g., **11000**) can be facilitated. When the electronic device (e.g., **11000**) is horizontally centered (along with x-direction) within slot **10856**, the electronic device (e.g., **11000**) can beneficially be horizontally aligned (along with x-direction) with alignment base **11051**, which can allow an overlay applicator to be used with the electronic device (e.g., **11000**) to apply an overlay to the screen or other surface of the electronic device (e.g., **11000**).

(575) Turning ahead in the drawings, FIG. **113** illustrates a plan view of a portion of machine **10600** in an opened configuration with electronic device **11000** seated within adjustable cradle **10750**, with a screen or other surface of the electronic device **11000** facing outwards (in a z-direction) and an overlay applicator **11300** attached to alignment base **11051** so as to be positioned over the screen or other surface of electronic device **11000**. FIG. **114** illustrates a plan view of machine **10600** in a closed configuration, after electronic device **11000** and overlay applicator **11300** have been installed inside machine **10600**. FIG. **115** illustrate a cross-sectional elevational view of machine **10600** as lid **10630** is being closed, but ajar, before lid **10630** has been latched into base **10620**. Overlay applicator **11300** can be similar or identical to one or more of the overlay applicators described above, such as overlay applicator **100** (FIG.

1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), overlay applicator **6050** (FIG. 60), overlay applicator **8001** (FIG. 80), and/or overlay applicator **9101** (FIG. 91). In a number of embodiments, overlay applicator **11300** can include an alignment tab **11310**, a protective film **11320**, an overlay (not shown), an adhesive release liner (not shown), a pull tab **11350**, and/or a joining sticker **11380**, which can be similar or identical to corresponding components described above.

(576) As shown in FIGS. **113** and **115**, once electronic device **11000** is seated within adjustable cradle **10750**, overlay applicator **11300** can be installed on alignment base **11051**, such as alignment tab **11310** engaging with alignment base **11051**. Electronic device **11000** can be positioned such that, when overlay applicator **11300** is installed on alignment base **11051**, the overlay of overlay applicator **11300** can be positioned over a screen or other surface of electronic device **11000**. Once electronic device **11000** is seated in adjustable cradle **10750** and overlay applicator **11300** is installed on alignment base **11051**, lid **11330** can be closed. As shown in FIG. **115**, lid **10630** can include one or more catches, such as catch **11532**, which can be inserted inside one or more latching slots **11522** in base **10620** to engage with one or more latches inside the latching slots **11522** to secure lid **10630** in the closed configuration, as shown in FIG. **114**. In many embodiments, when machine **10600** is in the closed configuration, pull tab **11350** can be pulled to remove the adhesive release liner to expose an adhesive on a bottom side of the overlay to the screen or other surface of electronic device **11000**.

(577) Turning ahead in the drawings, FIG. **116** illustrates a cross-sectional elevational view of a portion of machine **10600** in a closed configuration with electronic device **11000** seated within adjustable cradle **10750**. As shown in FIG. **116**, lid **10630** can include an outer frame **11631**, which can provide an outer structural shell, and/or a foam holder **11632**. When lid **10630** is closed, in several embodiments, foam holder **11632** can press inwards (in the z-direction) on overlay applicator **11300** to secure overlay applicator on alignment base **11051** and press overlay applicator **11300** down against the screen or other surface of electronic device **11000**, such that when pull tab **11350** (FIGS. **113-115**) is pulled (e.g., pulled bottomward in the y-direction away from machine **10600**), the overlay can be adhered to the screen or other surface of electronic device **11000**. In many embodiments, foam holder **11632** can press the exposed adhesive on the overlay to the screen or other surface of electronic device **11000**, to apply the overlay to the screen or other surface of electronic device **11000**. In a number of embodiments, foam holder **11632** can be pushed inward with one or more springs **11633**.

(578) In several embodiments, base **10620** can include, in addition to elements described above, a frame **11621**, which can provide an outer structural shell, and/or one or more springs (not shown), which can be configured to bias adjustable cradle **10750** and/or slot base surface **10875** outward (e.g., upward toward lid **10630**) along a z-direction that extends between frame **11621** and outer frame **11631**. In many embodiments, when lid **10630** is closed, foam holder **11632** can press inward along the z-direction, such that adjustable cradle **10750** and/or slot base surface **10875** are adjusted inward (in the z-direction) to allow electronic device **11000** to fit between foam holder **11632** and overlay applicator **11300** at the top, and slot base surface **10875** at the bottom. The springs can beneficially allow adjustable cradle **10750** and/or slot base surface **10875** to adjust along the z-direction for electronic devices (e.g., **11000**) that have different thicknesses, which can advantageously allow machine **10600** to apply overlays to the screen or other surface of electronic devices (e.g., **11000**) having various different thicknesses. In many embodiments, machine **10600** can apply overlays to the screens or other surfaces of electronic devices (e.g., **11000**) having various different dimensions of length (e.g., in the y-direction, or alternatively, in the x-direction), width (in the x-direction, or alternatively, in the y-direction), and/or thickness (in the z-direction), without replacing the cradle that is used in machine **10600**.

(579) Turning ahead in the drawings, FIG. **117** illustrates a plan view of a machine **11700** in an opened configuration, according to another embodiment. FIG. **118** illustrates a perspective view of machine **11700** in an opened configuration. FIG. **119** illustrates a perspective view of a portion of base **11720**. Machine **11700** is merely exemplary, and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **11700** can include a base **11720**, a lid **11730**, and/or a hinge mechanism **11740**. Machine **11700** can be similar to

machine **6900** in FIGS. **69-74** and/or machine **10600** (FIG. **106**), and various elements of machine **11700** can be similar or identical to various elements of machine **6900** in FIGS. **69-74** and/or machine **10600** (FIG. **106**). Base **11720** can be similar to support base **6920** in FIGS. **69-74** and/or base **10620** (FIG. **106**), and various elements of base **11720** can be similar or identical to various elements of base **6920** in FIGS. **69-74** and/or base **10620** (FIG. **106**). Lid **11730** can be similar to lid **6930** in FIGS. **69-74** and/or lid **10630** (FIG. **106**), and various elements of lid **11730** can be similar or identical to various elements of lid **6930** in FIGS. **69-74** and/or lid **10630** (FIG. **106**). Hinge **11740** can be similar to hinge **6940** in FIGS. **69-74** and/or hinge **10640** (FIG. **106**), and various elements of hinge **11740** can be similar or identical to various elements of hinge **6940** in FIGS. **69-74** and/or hinge **10640** (FIG. **106**).

(580) In many embodiments, as shown in FIGS. **117-118**, lid **11730** can include an outer frame **11731**, which can provide an outer structural shell, and/or a foam holder **11732**. Outer frame **11731** can be similar or identical to outer frame **11631** (FIG. **116**), and foam holder **11732** can be similar or identical to foam holder **11632** (FIG. **116**).

(581) In several embodiments, base **11720** can include alignment base **11751**, which can include a left alignment pin and/or a right alignment pin. Alignment base **11751** can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69, 73**), and/or alignment base **11051** (FIG. **110**). In many embodiments, alignment base **11751** can be configured to hold an alignment tab of an overlay applicator. In some embodiments, the alignment pins of alignment base **11751** can be different sizes, such that the alignment tab can be inserted on alignment base **11751** with a first side (e.g., an adhesive side configured to adhere to the screen or other surface of an electronic device) of the overlay applicator face down, but not with the first side of the overlay applicator face up.

(582) In several embodiments, as shown in FIGS. **117-119**, base **11720** can include an adjustable cradle **11750**. Adjustable cradle **11750** can be similar to cradle **6950** in FIG. **69** and/or adjustable cradle **10750** (FIG. **107**), and various elements of adjustable cradle **11750** can be similar or identical to various elements of cradle **6950** in FIG. **69** and/or adjustable cradle **10750** (FIG. **107**). Adjustable cradle **11750** can be configured to hold electronic devices of varying sizes. In many embodiments, instead of being for a single size of electronic device and/or replaceable with different cradles to hold different device sizes, adjustable cradle **11750** can be configured to hold electronic devices of varying sizes. In many embodiments, adjustable cradle **11750** can be part a permanent part of base **11720**.

(583) In several embodiments, adjustable cradle **11750** can include a slot **11756**, a side holder **11752**, and/or a top holder **11753**. Slot **11756** can be similar to slot **6956** in FIG. **69** and/or slot **10856** (FIG. **108**). In a number of embodiments, slot **11756** can include a left side wall **11771**, a right side wall **11772**, a top side wall **11773**, a bottom side wall **11774**, and/or a slot base surface **11775**. In many embodiments, slot **11756** can have dimensions that are larger than an electronic device (e.g., an electronic device **11790**) that can be seated within adjustable cradle **11750**. In a number of embodiments, side holder **11752** can be adjustable within slot **11756** along an x-direction (as shown in FIGS. **117, 118, 119, 120, 122, 123**, and **124**) that extends between left side wall **11771** and right side wall **11772** (and vice versa) of slot **11756**. In various embodiments, left side wall **11771** can be configured to hold a left side of electronic device **11790**, and/or right side holder **11752** can be configured to hold a right side of electronic device **11790**.

(584) In a number of embodiments, top holder **11753** can be adjustable within slot **11756** along a y-direction (as shown in FIGS. **117, 118, 119, 120, 122, 123**, and **124**, in which the arrow points “top-ward” and the opposite is “bottomward”) that extends between the top side wall **11773** and bottom side wall **11774** (and vice versa) of slot **11756**. In several embodiments, top holder **11753** can be configured to hold a top side of electronic device **11790**, and/or bottom side wall **11774** can be configured to hold a bottom side of electronic device **11790**. In a number of embodiments, alignment base **11751** can be similar or identical to alignment base **11051** (FIG. **110**), and in a number of embodiments can include two pins having different sizes, such as shown in FIG. **117**. In many embodiments, the electronic device (e.g., **11790**) can be inserted such that a side of the electronic device that is used to push top holder **11753** top-ward runs along a width (e.g., a shorter dimension than the length) of electronic device **11790**, as shown

in FIG. 117. In many embodiments, adjustable cradle **11750** can be configured such that the electronic device can be inserted such that the side of the electronic device that is used to push top holder **11753** top-ward runs along a length of the electronic device.

(585) In many embodiments, as shown in FIGS. **117-119**, electronic device **11790** can be seated within adjustable cradle **11750** with the screen or other surface of electronic device **11790** facing outwards (in the z-direction, as shown in FIGS. **118**, **119**, and **122**, in which the arrow points “outward,” and the opposite is “inward”), and an overlay applicator **11780** can be attached to alignment base **11751** above (outward of) the electronic device **11790**. Overlay applicator **11780** can be similar or identical to one or more of the overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), and/or overlay applicator **11300** (FIG. **113**). In a number of embodiments, overlay applicator **11780** can include an alignment tab **11781**, a protective film **11782**, an overlay (not shown), an adhesive release liner (not shown), a pull tab **11785**, and/or a joining sticker **11788**, which can be similar or identical to corresponding components described above. In many embodiments, when electronic device **11790** has been seated in adjustable cradle **11750** and overlay applicator **11780** has been installed on alignment base **11751**, lid **11730** of machine **11700** can be closed to a closed configuration of machine **11700** (which can be similar to the closed configuration of machine **10600** shown in FIGS. **106** and **114** and described above), and pull tab **11785** can be pulled to remove the adhesive release liner to expose an adhesive on a bottom side of the overlay to the screen or other surface of electronic device **11790**.

(586) Turning ahead in the drawings, FIG. **120** illustrates a plan view of base **11720**, showing various external and internal components of base **11720**, with side holder **11752** in a partially opened position. FIG. **121** illustrates a plan view of base **11720**, showing various external and internal components of base **11720**, with side holder **11752** in a closed position. In many embodiments, alignment base **11751** can be attached to, or integrally formed with, a pin holder **12051**. In many embodiments, pin holder **12051** can be attached to a pin holder plate **12061**. For example, pin holder **12051** can be attached to pin holder plate **12061** using a linkage bar **12358** (FIG. **123**, described below). In a number of embodiments, pin holder plate **12061** can be positioned internally within base **10620**, below slot base surface **11775** (FIG. **117**). In a number of embodiments, side holder **11752** can be attached to, or integrally formed with, a side holder plate **12052**, which can be positioned below slot base surface **11775** (FIG. **117**). In several embodiments, side holder plate **12052** can slide side-to-side (e.g., along the x-direction) along one or more guide rails **12055**.

(587) In many embodiments, side holder plate **12052** can be connected to a first end of a linkage bar **12058** at a pivot **12056**. A second end of linkage bar **12058** can be connected to base **11720** at a pivot **12057**. In a number of embodiments, linkage bar **12058** can be connected at an approximate midpoint between the first end and the second end of linkage bar **12058** to pin holder plate **12061** at a pivot **12059**. In several embodiments, pin holder plate **12061** can move side-to-side along the x-direction when side holder **11752** moves side-to-side along the x-direction. Due to pivot **12059** being located at a midpoint of linkage **12058**, when side holder **11752** moves a first distance left or right in the x-direction, pin holder plate **12061**, pin holder **12051** and/or alignment base **11751** can move a second distance left or right, respectively, in which the second distance is half of the first distance. For example, as shown in FIG. **121**, when side holder **11752** is adjusted leftward to a closed position, alignment base **11751** can be automatically adjusted leftward half the distance that side holder **11752** moves leftward. By alignment base **11751** adjusting half the distance of side holder **11752**, alignment base **11751** can advantageously be approximately centered between the sides (in the x-direction) of electronic devices (e.g., **11790** (FIG. **117**)) that are seated in adjustable cradle **11750** (FIG. **117**), for different widths (or alternatively, lengths) of electronic devices (e.g., **11790** (FIG. **117**)).

(588) Turning ahead in the drawings, FIG. **122** illustrates a perspective view of a portion of base **11720**, showing various external and internal components of base **11720**, with side holder **11752** in a closed position. In many embodiments, side holder plate **12052** can include an attachment pin **12252**, which can be attached to a first end of a spring **12223**. In a number of embodiments, base **11720** can include a fixed attachment pin **12222**, which can be attached to a second end of spring **12223**. Spring **12223** can be a

retention spring that biases side holder **11752** in the closed position. In some embodiments, attachment pin **12222** can facilitate alignment of side holder plate **12052** when side holder plate **12052** moves in the x-direction.

(589) In several embodiments, top holder **11753** can be attached to, or integrally formed with, a top holder plate **12253**, which can be positioned below slot base surface **11775** (FIG. **117**), and/or which can be configured to slide top-ward and bottomward in the y-direction. In a number of embodiments, top holder plate **12253** can include one or more attachment pins **12254**, which each can be attached to one or more respective first ends of one or more springs **12225**. In several embodiments, base **11720** can include one or more fixed attachment pins **12224**, which each can be attached to one or more respective second ends of springs **12225**. Springs **12225** can be retention springs, which can bias top holder **11753** bottomward toward bottom side wall **11774**. In some embodiments, attachment pins **12224** can facilitate alignment of top holder plate **12253** when top holder plate **12253** moves in the y-direction.

(590) Turning ahead in the drawings, FIG. **123** illustrates a plan view of a portion of base **11720**, showing various external and internal components of base **11720**, with top holder **11753** in a seated position holding electronic device **11790**. FIG. **124** illustrates a plan view of a portion of base **11720**, showing various external and internal components of base **11720**, with top holder **11753** in a closed position. In many embodiments, top holder plate **12253** can be connected to a first end of a linkage bar **12358** at a pivot **12356**. A second end of linkage bar **12358** can be connected to pin holder plate **12061** at a pivot **12357**. In a number of embodiments, linkage bar **12358** can be connected at an approximate midpoint between the first end and the second end of linkage bar **12358** to pin holder **12051** at a pivot **12359**. In several embodiments, pin holder **12051** can move top-ward and bottomward along the y-direction when top holder **11753** moves top-ward and bottomward along the y-direction. Due to pivot **12359** being located at a midpoint of linkage **12358**, when top holder **11753** moves a first distance top-ward or bottomward in the y-direction, pin holder **12051** and/or alignment base **11751** can move a second distance top-ward or bottomward, respectively, in which the second distance is half of the first distance. For example, as shown in FIGS. **123-124**, when top holder **11753** is adjusted from the seated position in FIG. **123** to the closed position in FIG. **124**, alignment base **11751** can be automatically adjusted bottomward half the distance that top holder **11753** moves bottomward. By alignment base **11751** adjusting half the distance of top holder **11753**, alignment base **11751** can advantageously be positioned approximately at a constant distance from the center of the electronic device (e.g., **11790**) seated in adjustable cradle **11750** (FIG. **117**), even when electronic devices with different dimensions are seated in adjustable cradle **11750** (FIG. **117**), for different dimensions (e.g., lengths, or alternatively, widths) of electronic devices (e.g., **11790** (FIG. **117**)).

(591) Turning ahead in the drawings, FIG. **125** illustrates a perspective view of a machine **12500** in a closed configuration with an overlay applicator **12580** installed, according to another embodiment. FIG. **126** illustrates a perspective view of a base **12520** of machine **12500** with overlay applicator **12580** installed and without an electronic device installed. FIG. **127** illustrates a perspective view of base **12520** with overlay applicator **12580** and an electronic device **12700** installed. Machine **12500** is merely exemplary, and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **12500** can include base **12520**, a lid **12530**, and/or a hinge mechanism **12540**. Machine **12500** can be similar to machine **6900** in FIGS. **69-74**, machine **10600** (FIG. **106**), and/or machine **11700** (FIG. **117**), and various elements of machine **12500** can be similar or identical to various elements of machine **6900** in FIGS. **69-74**, machine **10600** (FIG. **106**), and/or machine **11700** (FIG. **117**). Base **12520** can be similar to support base **6920** in FIGS. **69-74**, base **10620** (FIG. **106**), and/or base **11720** (FIG. **117**), and various elements of base **12520** can be similar or identical to various elements of base **6920** in FIGS. **69-74**, base **10620** (FIG. **106**), and/or base **11720** (FIG. **117**). Lid **12530** can be similar to lid **6930** in FIGS. **69-74**, lid **10630** (FIG. **106**), and/or lid **11730** (FIG. **117**), and various elements of lid **12530** can be similar or identical to various elements of lid **6930** in FIGS. **69-74**, lid **10630** (FIG. **106**), and/or lid **11730** (FIG. **117**). Hinge **12540** can be similar to hinge **6940** in FIGS. **69-74**, hinge **10640** (FIG. **106**), and/or hinge **11740** (FIG. **117**), and various elements of hinge **12540** can be similar or identical to various elements of hinge **6940** in FIGS. **69-74**, hinge **10640** (FIG. **106**), and/or hinge **11740** (FIG. **117**).

(592) In several embodiments, machine **12500** can be configured to have an overlay applicator, such as overlay applicator **12580** installed, and/or to have an electronic device, such as electronic device **12700**, installed. Overlay applicator **12580** can be similar or identical to one or more of the overlay applicators described above, such as overlay applicator **100** (FIG. 1), overlay applicator **400** (FIGS. 4-5), overlay applicator **600** (FIG. 6), overlay applicator **700** (FIG. 7), overlay applicator **1500** (FIG. 15), overlay applicator **3000** (FIG. 30), overlay applicator **3550** (FIGS. 35-36), overlay applicator **6050** (FIG. 60), overlay applicator **8001** (FIG. 80), overlay applicator **9101** (FIG. 91), overlay applicator **11300** (FIG. 113), and/or overlay applicator **11780** (FIG. 117). In a number of embodiments, overlay applicator **12580** can include an alignment tab **12681**, a protective film (not shown), an overlay (not shown), an adhesive release liner **12684**, a pull tab **12585**, and/or a joining sticker **12688**, which can be similar or identical to corresponding components described above. In several embodiments, pull tab **12585** can include a wiper **12686**, which can be similar or identical to the wipers described above. In many embodiments, when overlay applicator **12580** has been installed on an alignment base **12651** of base **12520**, and electronic device **12700** has been seated (e.g., with electronic device **12700** facing screen down or other surface down toward overlay applicator **12580**) in an adjustable cradle **12650** of base **12520**, lid **12530** of machine **12500** can be closed to a closed configuration of machine **12500**, such as shown in FIG. 125, and pull tab **12585** can be pulled to remove the adhesive release liner to expose an adhesive on the overlay to the screen or other surface of electronic device **12700**.

(593) In several embodiments, base **12520** can include alignment base **12651**, which can include a left alignment pin and/or a right alignment pin. Alignment base **12651** can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. 2), alignment base **312** (FIG. 3), alignment base **835** (FIGS. 8-9, 13-14), alignment base **1632** (FIGS. 16-19), alignment base **2035** (FIG. 20), alignment base **3112** (FIGS. 31-34), alignment base **3514** (FIGS. 35-36), alignment base **3814** (FIG. 38), alignment base **4734** (FIG. 47), alignment base **6414** (FIG. 64), alignment base **6424** (FIG. 64), alignment base **6434** (FIG. 64), alignment base **6953** (FIGS. 69, 73), alignment base **11051** (FIG. 110), and/or alignment base **11751** (FIG. 117). In many embodiments, alignment base **12651** can be configured to hold an alignment tab of an overlay applicator. In some embodiments, the alignment pins of alignment base **12651** can be different sizes, such that the alignment tab can be inserted on alignment base **12651** with a first side (e.g., an adhesive side configured to adhere to the screen or other surface of an electronic device) of the overlay applicator face down, but not with the first side of the overlay applicator face up.

(594) In several embodiments, base **12520** can include adjustable cradle **12650**. Adjustable cradle **12650** can be similar to cradle **6950** in FIG. 69, adjustable cradle **10750** (FIG. 107), and/or adjustable cradle **11750** (FIG. 117), and various elements of adjustable cradle **12650** can be similar or identical to various elements of cradle **6950** in FIG. 69, adjustable cradle **10750** (FIG. 107), and/or adjustable cradle **11750** (FIG. 117). Adjustable cradle **12650** can be configured to hold electronic devices (e.g., **12700**) of varying sizes. In many embodiments, instead of being for a single size of electronic device and/or replaceable with different cradles to hold different device sizes, adjustable cradle **12650** can be configured to hold electronic devices of varying sizes. In many embodiments, adjustable cradle **12650** can be part a permanent part of base **12520**.

(595) In several embodiments, adjustable cradle **12650** can include a left side holder **12751**, a right side holder **12752**, a left top corner holder **12753**, a right top corner holder **12754**, a bottom side support **12774**, and/or a base support surface **12775**. In many embodiments, alignment tab **12681** of overlay applicator **12580** can engage with alignment base **12651**, which, in some embodiments, can be two pins of different sizes, as shown in FIGS. 126-127. In a number of embodiments, pull tab **12585** can extend through a pull tab slot **12776** located between bottom side support **12674** and base support surface **12775**.

(596) In a number of embodiments, left side holder **12751** and/or right side holder **12752** can be adjustable along an x-direction (as shown in FIGS. 125, 127, 130, and 131) between the left and right sides of base **12520**. In various embodiments, left side holder **12751** can be configured to hold a left side of electronic device **12700**, and/or right side holder **12752** can be configured to hold a right side of electronic device **12700**. In a number of embodiments, left top corner holder **12753** and/or right top corner holder **12754** can be adjustable along a y-direction (as shown in FIGS. 125, 127, 130, and 131, in which the arrow points “top-ward” and the opposite is “bottomward”) that extends between the top and

bottom (and vice versa) of base **12520**. In several embodiments, left top corner holder **12753** and/or right top corner holder **12754** can hold a top left corner and a top right corner, respectively, of electronic device **12700**, and/or bottom side support **12674** can hold a bottom side of electronic device **12700**. In many embodiments, the electronic device (e.g., **12700**) can be inserted such that a side of the electronic device that extends between left top corner holder **12753** and right top corner holder **12754** runs along a width (e.g., a shorter dimension than the length) of electronic device **12700**, as shown in FIG. **127**. In other embodiments, adjustable cradle **12650** can be configured such that the electronic device can be inserted such that the side of the electronic device that extends between left top corner holder **12753** and right top corner holder **12754** runs along a length of the electronic device.

(597) In a number of embodiments, base **12520** can include an opening button **12759**, which can open left side holder **12751**, right side holder **12752**, left top corner holder **12753**, and right top corner holder **12754** to an opened position, as shown in FIG. **128** and described below. In many embodiments, base **12520** can include a release button **12758**, which can release left side holder **12751**, right side holder **12752**, left top corner holder **12753**, and right top corner holder **12754** to a closed (released) position, as shown in FIG. **129** and described below.

(598) Turning ahead in the drawings, FIG. **128** illustrates a plan view of base **12520** with left side holder **12751**, right side holder **12752**, left top corner holder **12753**, and right top corner holder **12754** in an opened position. FIG. **129** illustrates a plan view of base **12520** with left side holder **12751**, right side holder **12752**, left top corner holder **12753**, and right top corner holder **12754** in a closed (released) position. FIG. **130** illustrates a plan view of a portion of base **12520** below base support surface **12775**, as viewed outward (in the z-direction, as shown in FIGS. **125** and **127**, in which the arrow points “outward,” and the opposite is “inward”) from below base support surface **12775** to view an under surface **13085** on the opposite side of base support surface **12775**.

(599) In many embodiments, when opening button **12759** is depressed leftward (as viewed in FIG. **130**), a plate **13058** that is attached to, or integrally formed with, opening button **12759** can move leftward (as viewed in FIG. **130**). In a number of embodiments, plate **13058** can include a protrusion **13062**, which can engage a plate **13063**. Plate **13063** can be pivotably attached to under surface **13085** at a pivot **13064**, and can be pivotably attached to a plate **13065** at a pivot **13066**, such that when protrusion **13062** pushes leftward (as viewed in FIG. **130**), plate **13063** can rotate counterclockwise (as viewed in FIG. **130**), which can push plate **13065** bottomward. In many embodiments, plate **13065** can be pivotably attached to plates **13071** and **13072** at pivots **13067** and **13068**, respectively. In several embodiments, plate **13071** can be pivotably attached to under surface **13085** at a pivot **13075** and can be pivotably attached to a right holder plate **13052** at a pivot **13073**. In various embodiments, plate **13072** can be pivotably attached to under surface **13085** at a pivot **13076** and can be pivotably attached to a left holder plate **13051** at a pivot **13074**. When plate **13065** is pushed bottomward, plate **13071** can be rotated clockwise (as viewed in FIG. **130**), which can push right holder plate **13052** leftward (as viewed in FIG. **130**); and plate **13072** can be rotated counterclockwise (as viewed in FIG. **130**), which can push left holder plate **13051** rightward (as viewed in FIG. **130**). In several embodiments, left holder plate **13051** can be attached, or integrally formed with, left side holder **12751** (FIGS. **128-129**), and/or right holder plate **13052** can be attached, or integrally formed with, right side holder **12752** (FIGS. **128-129**), such that when button **12759** is depressed, left side holder **12751** opens leftward (as viewed in FIGS. **128-129**), and right side holder **12752** opens rightward (as viewed in FIGS. **128-129**) to the opened position shown in FIG. **128**.

(600) In a number of embodiments, plate **13058** can include a catch **13061**, which can engage with a latch **13057** (e.g., a lock pawl), which can be attached to under surface **13085** and spring loaded to rotate clockwise to engage with catch **13061** when opening button **12759** is depressed. In several embodiments, release button **12758** can be depressed to release latch **13057** from catch **13061**, such that plate **13058** can move rightward (as viewed in FIG. **130**), based on a spring bias of plate **13058** to move rightward (as viewed in FIG. **130**). When plate **13058** moves rightward (as viewed in FIG. **130**), plate **13063** can rotate clockwise (as viewed in FIG. **130**), based on a spring bias in pivot **13064**, which can ultimately cause left side holder **12751** and right side holder **12752** to move inward to a closed (released) position, as shown in FIG. **129**.

(601) In many embodiments, when opening button **12759** is depressed leftward (as viewed in FIG. **130**), and plate **13058** moves leftward (as viewed in FIG. **130**), plate **13058** can engage with a protrusion

13060 in plate **13059**. Plate **13059** can be pivotably attached to under surface **13085** at a pivot **13077** (which can be spring biased rightward, as viewed in FIG. **130**), such that when plate **13058** pushes leftward (as viewed in FIG. **130**), plate **13059** can rotate counterclockwise (as viewed in FIG. **130**). In several embodiments, plate **13059** can include a gear engagement region, which can engage with a drive gear **13056** to rotate drive gear **13056** clockwise (as viewed in FIG. **130**). In a number of embodiments, left top corner holder **12753** (FIGS. **128-129**) and/or right top corner holder **12754** (FIGS. **128-129**) can be attached to a top holder plate **13053**, which can include a gear engagement region **13055**, which can engage with drive gear **13056**. When opening button **12759** is depressed and drive gear **13056** rotates clockwise (as viewed in FIG. **130**), top holder plate **13053** can be pushed top-wards along slots **13054**. When opening button **12759** is depressed far enough to latch, left top corner holder **12753** and/or right top corner holder **12754** can be held open in the opened position shown in FIG. **128**. When release button **12758** is depressed to release the latch, the spring bias of pivot **13077** (which can be spring biased rightward, as viewed in FIG. **130**) can cause left top corner holder **12753** and/or right top corner holder **12754** to adjust bottomward to a closed (released) position, as shown in FIG. **129**.

(602) In several embodiments, machine **12500** can be configured such that opening button **12759** can be depressed to open left side holder **12751**, right side holder **12752**, left top corner holder **12753**, and right top corner holder **12754** to an opened position, as shown in FIG. **128**. An electronic device (e.g., **12700** (FIG. **127**)) can be inserted into adjustable cradle **12650**, and release button **12758** can be pressed, which can cause left side holder **12751** and right side holder **12752** to move inward toward electronic device **12700** (FIG. **127**), and can cause left top corner holder **12753**, and right top corner holder **12754** to move bottomward toward electronic device **12700** (FIG. **127**), to seat electronic device **12700** (FIG. **127**) in a horizontally centered position (along with x-direction) and a bottomward position (along the y-direction). This position can allow overlay applicator **12580** to be used to apply the overlay to the screen or other surface of electronic device **12700** (FIG. **127**).

(603) Turning ahead in the drawings, FIG. **131** illustrates a plan view of a portion of base **12520** with an alignment plate **13151** installed. FIG. **132** illustrates a plan view of a portion of base **12520** with alignment plate **13151** removed. In several embodiments, alignment base **12651** can be attached to, or integrally formed with, an alignment base holder **13251**. In several embodiments, alignment base holder **13251** can adjust top-ward and/or bottomward along, within, or about a top-to-bottom slot **13253**. In a number of embodiments, various different alignment plates, such as alignment plate **13151**, can be used for different sizes of electronic devices (e.g., **12700** (FIG. **127**)). Alignment plate **13151** can include holes **13152**, which can be used to define a position for alignment base holder **13251**, where the position can be dependent upon a size of the electronic device (e.g., **12700** (FIG. **127**)) that corresponds with alignment plate **13151**. Other alignment plates (e.g., **13151**) can have holes (e.g., **13152**) in different locations along the y-direction for different devices having different sizes. In many embodiments, alignment plate **13151** can fit within a recess **13252** within base support surface **12775**.

(604) Turning ahead in the drawings, FIG. **133** illustrates a perspective view of a machine **13300** in an opened configuration, according to another embodiment. FIG. **134** illustrates a perspective view of machine **13300** in a closed configuration. Machine **13300** is merely exemplary, and embodiments of the machine are not limited to the embodiments presented herein. The machine can be employed in many different embodiments or examples not specifically depicted or described herein. In various embodiments, machine **13300** can include a base **13320**, a lid **13330**, and/or a hinge mechanism **13340**. Machine **13300** can be similar to machine **6900** in FIGS. **69-74**, machine **10600** (FIG. **106**), and/or machine **11700** (FIG. **117**), and/or machine **12500** (FIG. **125**), and various elements of machine **13300** can be similar or identical to various elements of machine **6900** in FIGS. **69-74**, machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), and/or machine **12500** (FIG. **125**). Base **13320** can be similar to support base **6920** in FIGS. **69-74**, base **10620** (FIG. **106**), **11720** (FIG. **117**), and/or base **12520** (FIG. **125**), and various elements of base **13320** can be similar or identical to various elements of base **6920** in FIGS. **69-74**, base **10620** (FIG. **106**), **11720** (FIG. **117**), and/or base **12520** (FIG. **25**). Lid **13330** can be similar to lid **6930** in FIGS. **69-74**, lid **10630** (FIG. **106**), **11730** (FIG. **117**), and/or lid **12530** (FIG. **125**), and various elements of lid **13330** can be similar or identical to various elements of lid **6930** in FIGS. **69-74**, lid **10630** (FIG. **106**), lid **11730** (FIG. **117**), and/or lid **12530** (FIG. **125**). Hinge **13340** can be similar to hinge **6940** in FIGS. **69-74**, hinge **10640** (FIG. **106**), hinge **11740** (FIG. **117**), and/or hinge **12540** (FIG.

125), and various elements of hinge **13340** can be similar or identical to various elements of hinge **6940** in FIGS. **69-74**, hinge **10640** (FIG. **106**), hinge **11740** (FIG. **117**), and/or hinge **12540** (FIG. **125**). (605) In several embodiments, machine **13300** can be configured to have an overlay applicator, such as overlay applicator (not shown) installed, and/or to have an electronic device (now shown) installed. The overlay applicator can be similar or identical to one or more of the overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator **11300** (FIG. **113**), overlay applicator **11780** (FIG. **117**), and/or overlay applicator **12580** (FIG. **125**). In many embodiments, when the overlay applicator has been installed on an alignment base **13371** of base **13320**, and an electronic device has been seated in an adjustable cradle **13350** of base **13320**, lid **13330** of machine **13300** can be closed to a closed configuration of machine **13300**, such as shown in FIG. **134**, and a pull tab of the overlay applicator can be pulled to remove the adhesive release liner to expose an adhesive on the overlay to the screen or other surface of the electronic device.

(606) In several embodiments, base **13320** can include alignment base **13371**, which can include a left alignment pin and/or a right alignment pin. Alignment base **13371** can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69, 73**), alignment base **11051** (FIG. **110**), alignment base **11751** (FIG. **117**), and/or alignment base **12651** (FIG. **126**). In many embodiments, alignment base **13371** can be configured to hold an alignment tab of an overlay applicator. In some embodiments, the alignment pins of alignment base **13371** can be different sizes, such that the alignment tab can be inserted on alignment base **13371** with a first side (e.g., an adhesive side configured to adhere to the screen or other surface of an electronic device) of the overlay applicator face down, but not with the first side of the overlay applicator face up.

(607) In several embodiments, base **13320** can include adjustable cradle **13350**. Adjustable cradle **13350** can be similar to cradle **6950** in FIG. **69**, adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), and/or adjustable cradle **12650** (FIG. **126**), and various elements of adjustable cradle **13350** can be similar or identical to various elements of cradle **6950** in FIG. **69**, adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), and/or adjustable cradle **12650** (FIG. **126**). Adjustable cradle **13350** can be configured to hold electronic devices (e.g., **12700** (FIG. **127**)) of varying sizes. In many embodiments, instead of being for a single size of electronic device and/or replaceable with different cradles to hold different device sizes, adjustable cradle **13350** can be configured to hold electronic devices of varying sizes. In many embodiments, adjustable cradle **13350** can be part a permanent part of base **13320**.

(608) In several embodiments, adjustable cradle **13350** can include a slot **13356**, a left bottom corner holder **13351**, a right top corner holder **13352**, an adjustment well **13353**, and/or a base support surface **13375**. Slot **13356** can be similar to slot **6956** (FIG. **69**), slot **10856** (FIG. **108**), and/or slot **11756** (FIG. **117**). In many embodiments, slot **13356** can have dimensions that are larger than an electronic device that can be seated within adjustable cradle **13350**. In a number of embodiments, left bottom corner holder **13351** can be fixed in slot **13356**. In many embodiments, right top corner holder **13352** can be adjustable within slot **13356** along an x-direction (as shown in FIGS. **133** and **135**) and/or a y-direction (as shown in FIGS. **133, 135**, and **137**, in which the arrow points “top-ward” and the opposite is “bottomward”). In various embodiments, left bottom corner holder **13351** can be configured to hold a bottom left corner of an electronic device (e.g., a portion of a left side and a bottom side of the electronic device proximate to the bottom left corner), and/or right top corner holder **13352** can be configured to hold a top right corner of the electronic device (e.g., a portion of a right side and a top side of the electronic device proximate to the top right corner). In many embodiments, the electronic device can be inserted such that a top of the electronic device that is used to push right top corner holder **13352** top-ward in the y-direction runs along a width (e.g., a shorter dimension than the length) of the electronic device, such as shown in FIG. **133**. In

other embodiments, adjustable cradle **13350** can be configured such that the electronic device can be inserted such that the top of the electronic device that is used to push right top corner holder **13352** topward in the y-direction runs along a length of the electronic device.

(609) Turning ahead in the drawings, FIG. **135** illustrates a plan view of base **13320** with right top corner holder **13352** in a closed position. FIG. **136** illustrates a plan view of a base **13320** with right top corner holder **13352** in an opened position. In several embodiments, right top corner holder **13352** can be configured to be adjusted in the x-direction and/or y-direction within adjustment well **13353**. In many embodiments, left bottom corner holder **13351** can include a left holder piece **13551** and a bottom holder piece **13554**, and/or right top corner holder **13352** can include a right holder piece **13552** and a top holder piece **13553**. As shown in FIGS. **135** and **136**, right top corner holder **13352** can adjust within well **13353** between the closed position in FIG. **135** and the opened position in FIG. **136**. In several embodiments, right top corner holder **13352** can be spring biased toward left bottom corner holder **13351**. For example, when an electronic device (not shown) is being inserted in adjustable cradle **13350**, a top right corner of the electronic device can push right top corner holder **13352** topward and rightward toward the opened position, as shown in FIG. **136**. The electronic device can be lowered inward (in the z-direction, as shown in FIGS. **133** and **137**, in which the arrow points “outward,” and the opposite is “inward”) toward base support surface **13375** and released, such that right top corner holder **13352** moves leftward and bottomward to push the electronic device toward left bottom corner holder **13351** to be held securely between left bottom corner holder **13351** and right top corner holder **13352**. In some embodiments, right top corner holder **13352** can include alignment base **13371**, such that alignment base **13371** can adjust with right top corner holder **13352**. In other embodiments, alignment base **13371** can adjust half the distance of the adjustment of right top corner holder **13352** in the x-direction and/or y-direction, such as described above in connection with machine **11700** (FIG. **117**).

(610) Turning ahead in the drawings, FIG. **137** illustrates a cross-sectional elevational view of machine **13300** in a closed configuration. FIG. **138** illustrates an enlarged cross-sectional view of a portion of machine **13300**, as identified in FIG. **137**, in the closed configuration. As shown in FIG. **137**, lid **13330** can include an outer frame **13331**, which can provide an outer structural shell, and/or a foam holder **13332**. When lid **13330** is closed, in several embodiments, foam holder **13332** can press inwards (in the z-direction) on an overlay applicator (not shown) to secure overlay applicator on alignment base **13571** and press the overlay applicator down against the screen or other surface of an electronic device (not shown), such that when a pull tab of the overlay applicator is pulled (e.g., pulled bottomward in the y-direction away from machine **13300**), the overlay can be adhered to the screen or other surface of the electronic device. In many embodiments, foam holder **13332** can press the exposed adhesive on the overlay to the screen or other surface of the electronic device, to apply the overlay to the screen or other surface of the electronic device. In a number of embodiments, foam holder **13332** can be pushed inward with one or more springs **13733**. In some embodiments, lid **13330** can include foam holder **13734** in addition to, or in alternative to, foam holder **13332**. For example, foam holder **13734** can be narrower than foam holder **13332**, and can be centered in the x-direction in foam holder **13332**, so as to provide additional pressure to a center (in the x-direction) of the overlay as it is adhered to the electronic device.

(611) In several embodiments, base **10620** can include, in addition to elements described above, a frame **13721**, which can provide an outer structural shell. In a number of embodiments, base **10630** can include a spring **13771**, a spring **13772**, and/or an attachment pin **13752**. In many embodiments, attachment pin **13752** can be attached to right top corner holder **13352** below base support surface **13375**. In several embodiments, one end of spring **13772** can be attached to attachment pin **13752**, and another end of spring **13772** can be attached to another attachment pin (not shown) that is attached to a fixed position on base **13320**, such as attached to frame **13721** or below left bottom corner holder **13351** (FIG. **133**).

Spring **13772** can spring bias right top corner holder **13352** toward the left bottom corner. In several embodiments, spring **13771** can press outward in the z-direction on alignment base **13571**. In some embodiments, base **13320** can include one or more additional springs (not shown), which can be configured to bias adjustable cradle **13350** (FIG. **133**) and/or slot base surface **13375** outward (e.g., toward lid **13330**) along a z-direction. In many embodiments, when lid **13330** is closed, foam holder **13332** can press inward along the z-direction, such that adjustable cradle **13350** and/or slot base surface **13375** are adjusted inward (in the z-direction) to allow the electronic device to fit between foam holder **13332** and

the overlay applicator at the top, and slot base surface **13375** at the bottom, similar as described above in connection with machine **10600** in FIG. **116**. In many embodiments, machine **13300** can apply overlays to the screens or other surfaces of electronic devices having various different dimensions of length (in the y-direction, or alternatively, in the x-direction), width (in the x-direction, or alternatively, in the y-direction), and/or thickness (in the z-direction), without replacing the cradle that is used in machine **13300**.

(612) Proceeding to the next drawing, FIG. **139** illustrates a flow chart for an embodiment of a method **13900** of providing a machine. Method **13900** is merely exemplary and is not limited to the embodiments presented herein. Method **13900** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **13900** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **13900** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **13900** can be combined or skipped. The machine can be similar or identical to machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), machine **12500** (FIG. **125**), and/or machine **13300** (FIG. **133**).

(613) Referring to FIG. **139**, method **13900** can include a block **13910** of providing an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions. The adjustable cradle can be similar or identical to adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), adjustable cradle **12650** (FIG. **126**), and/or adjustable cradle **13350** (FIG. **133**). The electronic devices can be similar or identical to device **220** (FIG. **2**), device **320** (FIG. **3**), device **1650** (FIG. **16**), device **3401** (FIG. **34**), device **3720** (FIG. **37**), device **4800** (FIG. **48**), device **5600** (FIG. **56**), device **6550** (FIG. **65**), device **7100**, electronic device **8350** (FIG. **83**), electronic device **9700** (FIGS. **97-99**), electronic device **10000** (FIG. **100**), electronic device **11000** (FIG. **110**), electronic device **11790** (FIG. **117**), and/or electronic device **12700** (FIG. **127**).

(614) In a number of embodiments, the electronic devices can include a first electronic device and a second electronic device, and/or other electronic devices having different dimensions (sizes). In some embodiments, the adjustable cradle can be configured to hold, individually at different times, the first electronic device and the second electronic device, and/or the other electronic devices. For example, each electronic device can be inserted separately at different times. In several embodiments, the first electronic device of the electronic devices can have a first length and a first width, and the second electronic device of the electronic devices can have a second length different from the first length and a second width different from the first width. In some embodiments, the different dimensions can include the first length, the first width, the second length, and the second width. In various embodiments, the first electronic device can have a first thickness and the second electronic device can have a second thickness different from the first thickness.

(615) In many embodiments, method **13900** next can include a block **13920** of providing an alignment base configured to engage, individually at different times, with alignment mechanisms of overlay applicators. The alignment base can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9, 13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69, 73**), alignment base **11051** (FIG. **110**), alignment base **11751** (FIG. **117**), alignment base **12651** (FIG. **126**), and/or alignment base **13371** (FIG. **133**). The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), alignment mechanism **3557** (FIGS. **35-36**), alignment piece **8010** (FIG. **80**), alignment piece **9110** (FIG. **91**), alignment tab **11310** (FIG. **113**), alignment tab **11781** (FIG. **117**), and/or alignment tab **12681** (FIG. **126**). The overlay applicators can be similar or identical to overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-**

36), overlay applicator **6050** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator **11300** (FIG. **113**), overlay applicator **11780** (FIG. **117**), and/or overlay applicator **12580** (FIG. **125**). In several embodiments, each respective one of the overlay applicators can include a respective overlay configured to be applied to a respective surface of each of the electronic devices. The respective surface can be a screen of the electronic device or another surface of the electronic device, such as a rear surface of the electronic device. In a number of embodiments, the machine can be configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices.

(616) In many embodiments, the machine can be configured in an opened configuration such that (a) either of the first electronic device or the second electronic device and/or (b) a respective one of the overlay applicators can be inserted and removed from the machine. The opened configuration can be similar or identical to the opened configuration shown in FIGS. **107**, **113**, **117**, **118**, and **133**. In some embodiments, the machine can be configured in a closed configuration to prevent removal of (a) the either of the first electronic device or the second electronic device and/or (b) at least a portion of the respective one of the overlay applicators from the machine. The closed configuration can be similar or identical to the closed configuration shown in FIGS. **106**, **114**, **116**, **125**, **133**, and **137**. In a number of embodiments, the machine can be configured in the closed configuration such that a respective pull tab of the respective one of the overlay applicators can be pulled to remove a respective adhesive release liner of the respective one of the overlay applicators from the respective overlay of the respective one of the overlay applicators to expose an adhesive agent of the respective overlay to the respective surface of the either of the first electronic device or the second electronic device.

(617) In a number of embodiments, the adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to center each of the electronic devices held in the adjustable cradle with respect to the alignment base. The second adjustable holder can be similar or identical to left side holder **10851** (FIG. **108**) and/or left side holder **12751** (FIG. **127**). The third adjustable holder can be similar or identical to right side holder **10852** (FIG. **108**) and/or right side holder **12752** (FIG. **127**).

(618) In some embodiments, the adjustable cradle can be configured to hold the second adjustable holder and the third adjustable holder in an opened position until a button is activated by insertion of each of the electronic devices into the adjustable cradle to (a) transition the second adjustable holder and the third adjustable holder from the opened position to a closed position and (b) hold each of the electronic devices within the adjustable cradle. The button can be similar or identical to release latch **10958** (FIG. **109**) and/or release button **12758** (FIG. **127**).

(619) In a number of embodiments, the adjustable cradle can include a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a respective first side of each of the electronic devices upon insertion of each of the electronic devices into the adjustable cradle and/or (b) hold each of the electronic devices against a second side wall of the adjustable cradle opposite the first side wall when each of the electronic devices is held within the adjustable cradle. The first adjustable holder can be similar or identical to top holder **10853** (FIG. **108**), top holder **11753** (FIG. **117**), left top corner holder **12753** (FIG. **127**), and/or right top corner holder **12754** (FIG. **127**). The first side wall can be similar or identical to top side wall **10873** (FIG. **108**) and/or top side wall **11773** (FIG. **117**). In many embodiments, the second side wall can be fixed. The second side wall can be similar or identical to bottom side wall **10874** (FIG. **108**), bottom side wall **11774** (FIG. **117**), bottom side support **12774** (FIG. **127**), left bottom corner holder **13351** (FIG. **133**), and/or bottom holder piece **13554** (FIG. **133**). In some embodiments, the first side of the electronic device can run along a width of the electronic device. In other embodiments, the first side of the electronic device can run along a length of the electronic device. The first direction can be the y-direction.

(620) In several embodiments, the adjustable cradle can be configured to adjust a position in the first direction (e.g., a position in the y-direction) of the alignment base for different first dimensions of the electronic devices with respect to the first adjustable holder such that a distance between the alignment base and a respective center of a respective first dimension of each of the electronic devices is constant between the electronic devices when each of the electronic devices is held within the adjustable cradle. The distance can be similar or identical to distance **11261** (FIG. **112**). In some embodiments, the first

dimension can be the length of the electronic device. In other embodiments, the first dimension can be the width of the electronic device.

(621) In various embodiments, the adjustable cradle can include springs configured to adjust an inward position (e.g., in the z-direction) of the adjustable cradle for different thicknesses of the electronic devices.

(622) In many embodiments, the adjustable cradle can include an adjustable side holder configured to hold each of the electronic devices against a fixed opposing side wall of the adjustable cradle that is opposite the adjustable side holder when each of the electronic devices is held within the adjustable cradle. The adjustable side holder can be similar or identical to side holder **11752** (FIG. **117**). The fixed opposing side wall can be similar or identical to left side wall **11771** (FIG. **117**). In a number of embodiments, the adjustable cradle can be configured to adjust an position (e.g., a position in the x-direction) of the alignment base to be centered between different second dimensions of the electronic devices when the adjustable side holder holds each of the electronic devices in the adjustable cradle. In some embodiments, the second dimension can be the width of the electronic device. In other embodiments, the second dimension can be the length of the electronic device.

(623) In several embodiments, the adjustable cradle can include a second adjustable holder, a third adjustable holder, and a pair of adjustable corner holders. The second adjustable holder can be similar or identical to left side holder **10851** (FIG. **108**) and/or left side holder **12751** (FIG. **127**). The third adjustable holder can be similar or identical to right side holder **10852** (FIG. **108**) and/or right side holder **12752** (FIG. **127**). The adjustable corner holders can be similar or identical to left top corner holder **12753** (FIG. **127**) and/or right top corner holder **12754** (FIG. **127**). In some embodiments, when each of the electronic devices is held within the adjustable cradle, the second adjustable holder and the third adjustable holder are configured to center each of the electronic devices with respect to the alignment base, and/or the pair of adjustable corner holders are configured to hold each of the electronic devices against a second side wall of the adjustable cradle opposite the pair of adjustable corner holders. In many embodiments, the second side wall can be fixed. The second side wall can be similar or identical to bottom side wall **10874** (FIG. **108**), bottom side wall **11774** (FIG. **117**), bottom side support **12774** (FIG. **127**), left bottom corner holder **13351** (FIG. **133**), and/or bottom holder piece **13554** (FIG. **133**).

(624) In some embodiments, the adjustable cradle can include one or more buttons configured to: (a) transition the second adjustable holder, the third adjustable holder, and the pair of adjustable corner holders to an opened position to allow insertion of each of the electronic devices into the adjustable cradle, and/or (b) transition the second adjustable holder, the third adjustable right side holder, and the pair of adjustable corner holders to a closed position to hold each of the electronic devices within the adjustable cradle. The open position can be similar or identical to the opened position shown in FIG. **128**, and the closed position can be similar or identical to the closed position shown in FIG. **129**. The buttons can be similar or identical to release button **12758** (FIG. **127**) and/or opening button **12759** (FIG. **127**).

(625) In several embodiments, the adjustable cradle can include a fixed corner holder at a first corner of the adjustable cradle and an adjustable corner holder at a second corner of the adjustable cradle opposite the first corner. The fixed corner holder can be similar or identical to left bottom corner holder **13351** (FIG. **133**). The adjustable corner can be similar or identical to right top corner holder **13352** (FIG. **133**). In a number of embodiments, the adjustable corner holder can be configured to (a) be pushed diagonally away from the fixed corner holder by a respective first corner of each of the electronic devices upon insertion of each of the electronic devices into the adjustable cradle and (b) hold each of the electronic devices against the fixed corner holder of the adjustable cradle when each of the electronic devices is held within the adjustable cradle.

(626) In a number of embodiments, the walls of the adjustable cradle, such as the second adjustable holder, the third adjustable holder, the adjustable side holder, the first adjustable holder, the adjustable corner holder, and/or other walls of the adjustable cradle, can adjust automatically to fit the size of differently sized electronic device in order to securely hold the electronic devices to apply the overlay to the surface of the electronic device.

(627) In various embodiments, method **13900** additionally and optionally can include a block **13930** of providing a support base including the adjustable cradle and the alignment base. The support base can be similar or identical to base **10620** (FIG. **106**), **11720** (FIG. **117**), base **12520** (FIG. **125**), and/or base

13320 (FIG. **133**). In some embodiments, the alignment base can be adjustable with respect to the support base. In several embodiments, the support base can include a recess configured to hold different alignment plates. In various embodiments, the different alignment plates each can be configured to position the alignment base at a different respective position (e.g., a position along the y-direction) with respect to the support base. The alignment plates can be similar or identical to alignment plate **13151** (FIG. **131**).

(628) In many embodiments, method **13900** further and optionally can include a block **13940** of providing a lid hingedly attached to the support base and configured to rotate with respect to the support base between an opened configuration and a closed configuration. The lid can be similar or identical to lid **10630** (FIG. **106**), lid **11730** (FIG. **117**), lid **12530** (FIG. **125**), and/or lid **13330** (FIG. **133**). In other embodiments, the machine does not include a lid.

(629) Proceeding to the next drawing, FIG. **140** illustrates a flow chart for an embodiment of a method **14000** of providing a machine. Method **14000** is merely exemplary and is not limited to the embodiments presented herein. Method **14000** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **14000** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **14000** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **14000** can be combined or skipped. The machine can be similar or identical to machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), machine **12500** (FIG. **125**), and/or machine **13300** (FIG. **133**).

(630) Referring to FIG. **140**, method **14000** can include a block **14010** of providing an alignment base. The alignment base can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9**, **13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69**, **73**), alignment base **11051** (FIG. **110**), alignment base **11751** (FIG. **117**), alignment base **12651** (FIG. **126**), and/or alignment base **13371** (FIG. **133**). In many embodiments, the alignment base can engage an alignment mechanism of an overlay applicator. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), alignment mechanism **3557** (FIGS. **35-36**), alignment piece **8010** (FIG. **80**), alignment piece **9110** (FIG. **91**), alignment tab **11310** (FIG. **113**), alignment tab **11781** (FIG. **117**), and/or alignment tab **12681** (FIG. **126**). The overlay applicator can be similar or identical to overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator **11300** (FIG. **113**), overlay applicator **11780** (FIG. **117**), and/or overlay applicator **12580** (FIG. **125**).

(631) In many embodiments, method **14000** next can include a block **14020** of providing an adjustable cradle including one or more adjustable side holders configured to center an electronic device held in the adjustable cradle with respect to the alignment base. The adjustable cradle can be similar or identical to adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), adjustable cradle **12650** (FIG. **126**), and/or adjustable cradle **13350** (FIG. **133**). The electronic device can be similar or identical to device **220** (FIG. **2**), device **320** (FIG. **3**), device **1650** (FIG. **16**), device **3401** (FIG. **34**), device **3720** (FIG. **37**), device **4800** (FIG. **48**), device **5600** (FIG. **56**), device **6550** (FIG. **65**), device **7100**, electronic device **8350** (FIG. **83**), electronic device **9700** (FIGS. **97-99**), electronic device **10000** (FIG. **100**), electronic device **11000** (FIG. **110**), electronic device **11790** (FIG. **117**), and/or electronic device **12700** (FIG. **127**). The one or more adjustable side holders can be similar or identical to left side holder **10851** (FIG. **108**), left side holder **12751** (FIG. **127**), right side holder **10852** (FIG. **108**), right side holder **12752** (FIG. **127**), side holder **11752** (FIG. **117**), right top corner holder **13352** (FIG. **133**), and/or right holder

piece **13552** (FIG. **135**).

(632) In several embodiments, the one or more adjustable side holders of the adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to center a position (e.g., position in the x-direction) of the electronic device within the adjustable cradle. The second adjustable holder can be similar or identical to left side holder **10851** (FIG. **108**) and/or left side holder **12751** (FIG. **127**). The third adjustable holder can be similar or identical to right side holder **10852** (FIG. **108**) and/or right side holder **12752** (FIG. **127**). In some embodiments, a position of the alignment base in a direction between the second adjustable holder and the third adjustable holder (e.g., an x-position) is fixed.

(633) In a number of embodiments, the one or more adjustable side holders of the adjustable cradle can include an adjustable side holder configured to hold the electronic device against a fixed opposing side wall of the adjustable cradle that is opposite the adjustable side holder when the electronic device is held within the adjustable cradle. The adjustable side holder can be similar or identical to side holder **11752** (FIG. **117**), right top corner holder **13352** (FIG. **133**), and/or right holder piece **13552** (FIG. **135**). The fixed opposing side wall can be similar or identical to left side wall **11771** (FIG. **117**), left bottom corner holder **13351** (FIG. **133**), and/or left holder piece **13551** (FIG. **135**). In some embodiments, when the adjustable side holder moves a first distance in a direction between the adjustable side holder and the fixed opposing side wall (e.g., in the x-direction), the alignment base moves a second distance in the direction between the adjustable side holder and the fixed opposing side wall (e.g., the x-direction), and the second distance is half of the first distance.

(634) In various embodiments, the adjustable cradle can include a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a first side of the electronic device upon insertion of the electronic device into the adjustable cradle and (b) hold the electronic device against a second side wall of the adjustable cradle opposite the first side wall when the electronic device is held within the adjustable cradle. The first adjustable holder can be similar or identical to top holder **10853** (FIG. **108**), top holder **11753** (FIG. **117**), left top corner holder **12753** (FIG. **127**), right top corner holder **12754** (FIG. **127**), right top corner holder **13352** (FIG. **133**), and/or top holder piece **13553** (FIG. **135**). The first side wall can be similar or identical to top side wall **10873** (FIG. **108**) and/or top side wall **11773** (FIG. **117**). In many embodiments, the second side wall can be fixed. The second side wall can be similar or identical to bottom side wall **10874** (FIG. **108**), bottom side wall **11774** (FIG. **117**), bottom side support **12774** (FIG. **127**), left bottom corner holder **13351** (FIG. **133**), and/or bottom holder piece **13554** (FIG. **135**). In some embodiments, the first side of the electronic device can run along a width of the electronic device. In other embodiments, the first side of the electronic device can run along a length of the electronic device. The first direction can be similar or identical to the y-direction.

(635) In several embodiments, the adjustable cradle can be configured to adjust a position in the first direction (e.g., a position in the y-direction) of the alignment base with respect to the first adjustable holder such that a distance between the alignment base and a center of a first dimension of the electronic device is a fixed predetermined distance when the electronic device is held within the adjustable cradle. The distance can be similar or identical to distance **11261** (FIG. **112**). In some embodiments, the first dimension can be the length of the electronic device. In other embodiments, the first dimension can be the width of the electronic device.

(636) In a number of embodiments, when the first adjustable holder moves a first distance in the first direction, the alignment base can move a second distance in the first direction, such that the second distance is half of the first distance. In some embodiments, the adjustable cradle can include springs configured to adjust an inward position of the adjustable cradle for a thickness of the electronic device.

(637) Proceeding to the next drawing, FIG. **141** illustrates a flow chart for an embodiment of a method **14100** of providing a machine. Method **14100** is merely exemplary and is not limited to the embodiments presented herein. Method **14100** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **14100** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **14100** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the

activities in method **14100** can be combined or skipped. The machine can be similar or identical to machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), machine **12500** (FIG. **125**), and/or machine **13300** (FIG. **133**).

(638) Referring to FIG. **141**, method **14100** can include a block **14110** of providing an alignment base. The alignment base can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9**, **13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69**, **73**), alignment base **11051** (FIG. **110**), alignment base **11751** (FIG. **117**), alignment base **12651** (FIG. **126**), and/or alignment base **13371** (FIG. **133**). In many embodiments, the alignment base can engage an alignment mechanism of an overlay applicator. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), alignment mechanism **3557** (FIGS. **35-36**), alignment piece **8010** (FIG. **80**), alignment piece **9110** (FIG. **91**), alignment tab **11310** (FIG. **113**), alignment tab **11781** (FIG. **117**), and/or alignment tab **12681** (FIG. **126**). The overlay applicator can be similar or identical to overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator **11300** (FIG. **113**), overlay applicator **11780** (FIG. **117**), and/or overlay applicator **12580** (FIG. **125**).

(639) In many embodiments, method **14100** next can include a block **14120** of providing an adjustable cradle including a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a first side of an electronic device upon insertion of the electronic device into the adjustable cradle and (b) hold the electronic device against a second side wall of the adjustable cradle opposite the first side wall when the electronic device is held within the adjustable cradle. The adjustable cradle can be similar or identical to adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), adjustable cradle **12650** (FIG. **126**), and/or adjustable cradle **13350** (FIG. **133**). The electronic device can be similar or identical to device **220** (FIG. **2**), device **320** (FIG. **3**), device **1650** (FIG. **16**), device **3401** (FIG. **34**), device **3720** (FIG. **37**), device **4800** (FIG. **48**), device **5600** (FIG. **56**), device **6550** (FIG. **65**), device **7100**, electronic device **8350** (FIG. **83**), electronic device **9700** (FIGS. **97-99**), electronic device **10000** (FIG. **100**), electronic device **11000** (FIG. **110**), electronic device **11790** (FIG. **117**), and/or electronic device **12700** (FIG. **127**). The first adjustable holder can be similar or identical to top holder **10853** (FIG. **108**), top holder **11753** (FIG. **117**), left top corner holder **12753** (FIG. **127**), right top corner holder **12754** (FIG. **127**), right top corner holder **13352** (FIG. **133**), and/or top holder piece **13553** (FIG. **135**). The first side wall can be similar or identical to top side wall **10873** (FIG. **108**) and/or top side wall **11773** (FIG. **117**). In many embodiments, the second side wall can be fixed. The second side wall can be similar or identical to bottom side wall **10874** (FIG. **108**), bottom side wall **11774** (FIG. **117**), bottom side support **12774** (FIG. **127**), left bottom corner holder **13351** (FIG. **133**), and/or bottom holder piece **13554** (FIG. **135**). In some embodiments, the first side of the electronic device can run along a width of the electronic device. In other embodiments, the first side of the electronic device can run along a length of the electronic device. The first direction can be similar or identical to the y-direction. In some embodiments, the first adjustable holder can include a pair of adjustable corner holders. The pair of adjustable corner holders can be similar or identical to left top corner holder **12753** (FIG. **127**) and/or right top corner holder **12754** (FIG. **127**).

(640) In several embodiments, the adjustable cradle can be configured to adjust a position (e.g., a position in the y-direction) of the alignment base with respect to the first adjustable holder such that a distance between the alignment base and a center of a first dimension of the electronic device is a fixed predetermined distance when the electronic device is held within the adjustable cradle. The distance can be similar or identical to distance **11261** (FIG. **112**). In some embodiments, the first dimension can be the length of the electronic device. In other embodiments, the first dimension can be the width of the

electronic device. In a number of embodiments, when the first adjustable holder moves a first distance in the first direction, the alignment base can move a second distance in the first direction, such that the second distance is half of the first distance.

(641) In a number of embodiments, the adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to center a position of the electronic device in a second direction perpendicular the first direction (e.g., an position in the x-direction) within the adjustable cradle. The second adjustable holder can be similar or identical to left side holder **10851** (FIG. **108**) and/or left side holder **12751** (FIG. **127**). The third adjustable holder can be similar or identical to right side holder **10852** (FIG. **108**) and/or right side holder **12752** (FIG. **127**). In some embodiments, a position of the alignment base in the second direction (e.g., the x-direction) is fixed.

(642) In various embodiments, the adjustable cradle can include an adjustable side holder configured to hold the electronic device against a fixed opposing side wall of the adjustable cradle that is opposite the adjustable side holder when the electronic device is held within the adjustable cradle. The adjustable side holder can be similar or identical to side holder **11752** (FIG. **117**), right top corner holder **13352** (FIG. **133**), and/or right holder piece **13552** (FIG. **135**). The fixed opposing side wall can be similar or identical to left side wall **11771** (FIG. **117**), left bottom corner holder **13351** (FIG. **133**), and/or left holder piece **13551** (FIG. **135**). In some embodiments, when the adjustable side holder moves a first distance in a direction between the adjustable side holder and the fixed opposing side wall (e.g., an x-direction), the alignment base moves a second distance in the direction between the adjustable side holder and the fixed opposing side wall (e.g., the x-direction), and the second distance is half of the first distance.

(643) In some embodiments, the adjustable cradle can include springs configured to adjust an inward position (e.g., in the z-direction) of the adjustable cradle for a thickness of the electronic device.

(644) Proceeding to the next drawing, FIG. **142** illustrates a flow chart for an embodiment of a method **14200** of providing a machine. Method **14200** is merely exemplary and is not limited to the embodiments presented herein. Method **14200** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **14200** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of the method **14200** can be performed in any other suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities in method **14200** can be combined or skipped. The machine can be similar or identical to machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), machine **12500** (FIG. **125**), and/or machine **13300** (FIG. **133**).

(645) Referring to FIG. **142**, method **14200** can include a block **14210** of providing an alignment base. The alignment base can be similar or identical to one or more of the alignment bases described above, such as alignment base **212** (FIG. **2**), alignment base **312** (FIG. **3**), alignment base **835** (FIGS. **8-9**, **13-14**), alignment base **1632** (FIGS. **16-19**), alignment base **2035** (FIG. **20**), alignment base **3112** (FIGS. **31-34**), alignment base **3514** (FIGS. **35-36**), alignment base **3814** (FIG. **38**), alignment base **4734** (FIG. **47**), alignment base **6414** (FIG. **64**), alignment base **6424** (FIG. **64**), alignment base **6434** (FIG. **64**), alignment base **6953** (FIGS. **69**, **73**), alignment base **11051** (FIG. **110**), alignment base **11751** (FIG. **117**), alignment base **12651** (FIG. **126**), and/or alignment base **13371** (FIG. **133**). In many embodiments, the alignment base can engage an alignment mechanism of an overlay applicator. The alignment mechanism can be similar or identical to alignment mechanism **115** (FIG. **1**), alignment mechanism **415** (FIG. **4**), alignment mechanism **615** (FIG. **6**), alignment mechanism **715** (FIG. **7**), alignment mechanism **1515** (FIG. **15**), alignment mechanism **2915** (FIGS. **29-30**), alignment mechanism **3557** (FIGS. **35-36**), alignment piece **8010** (FIG. **80**), alignment piece **9110** (FIG. **91**), alignment tab **11310** (FIG. **113**), alignment tab **11781** (FIG. **117**), and/or alignment tab **12681** (FIG. **126**). The overlay applicator can be similar or identical to overlay applicators described above, such as overlay applicator **100** (FIG. **1**), overlay applicator **400** (FIGS. **4-5**), overlay applicator **600** (FIG. **6**), overlay applicator **700** (FIG. **7**), overlay applicator **1500** (FIG. **15**), overlay applicator **3000** (FIG. **30**), overlay applicator **3550** (FIGS. **35-36**), overlay applicator **6050** (FIG. **60**), overlay applicator **8001** (FIG. **80**), overlay applicator **9101** (FIG. **91**), overlay applicator **11300** (FIG. **113**), overlay applicator **11780** (FIG. **117**), and/or overlay applicator **12580** (FIG. **125**).

(646) In many embodiments, method **14200** next can include a block **14220** of providing an adjustable cradle including springs configured to adjust an inward position (e.g., in the z-direction) of the adjustable cradle for a thickness of an electronic device held in the adjustable cradle. The adjustable cradle can be similar or identical to adjustable cradle **10750** (FIG. **107**), adjustable cradle **11750** (FIG. **117**), adjustable cradle **12650** (FIG. **126**), and/or adjustable cradle **13350** (FIG. **133**). The electronic device can be similar or identical to device **220** (FIG. **2**), device **320** (FIG. **3**), device **1650** (FIG. **16**), device **3401** (FIG. **34**), device **3720** (FIG. **37**), device **4800** (FIG. **48**), device **5600** (FIG. **56**), device **6550** (FIG. **65**), device **7100**, electronic device **8350** (FIG. **83**), electronic device **9700** (FIGS. **97-99**), electronic device **10000** (FIG. **100**), electronic device **11000** (FIG. **110**), electronic device **11790** (FIG. **117**), and/or electronic device **12700** (FIG. **127**). The adjustment of the position of the adjustable cradle in the inward direction (e.g., z-direction) can move the adjustable cradle with respect to a support base or a lid of the machine. (647) In some embodiments, the adjustable cradle can include a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle by a first side of an electronic device upon insertion of the electronic device into the adjustable cradle and (b) hold the electronic device against a second side wall of the adjustable cradle opposite the first side wall when the electronic device is held within the adjustable cradle. The first adjustable holder can be similar or identical to top holder **10853** (FIG. **108**), top holder **11753** (FIG. **117**), left top corner holder **12753** (FIG. **127**), right top corner holder **12754** (FIG. **127**), right top corner holder **13352** (FIG. **133**), and/or top holder piece **13553** (FIG. **135**). The first side wall can be similar or identical to top side wall **10873** (FIG. **108**) and/or top side wall **11773** (FIG. **117**). In many embodiments, the second side wall can be fixed. The second side wall can be similar or identical to bottom side wall **10874** (FIG. **108**), bottom side wall **11774** (FIG. **117**), bottom side support **12774** (FIG. **127**), left bottom corner holder **13351** (FIG. **133**), and/or bottom holder piece **13554** (FIG. **135**). In some embodiments, the first side of the electronic device can run along a width of the electronic device. In other embodiments, the first side of the electronic device can run along a length of the electronic device. The first direction can be similar or identical to the y-direction. In some embodiments, the adjustable holder can include a pair of adjustable corner holders. The pair of adjustable corner holders can be similar or identical to left top corner holder **12753** (FIG. **127**) and/or right top corner holder **12754** (FIG. **127**). In several embodiments, the adjustable cradle can be configured to adjust a position the the first direction (e.g., a position in the y-direction) of the alignment base with respect to the first adjustable holder such that a distance between the alignment base and a center of a first dimension of the electronic device is a fixed predetermined distance when the electronic device is held within the adjustable cradle. The distance can be similar or identical to distance **11261** (FIG. **112**). In some embodiments, the first dimension can be the length of the electronic device. In other embodiments, the first dimension can be the width of the electronic device. In a number of embodiments, when the first adjustable holder moves a first distance in the y-direction, the alignment base can move a second distance in the y-direction, such that the second distance is half of the first distance.

(648) In a number of embodiments, the adjustable cradle can include a second adjustable holder and a third adjustable holder opposite the second adjustable holder. The second adjustable holder and the third adjustable holder can be configured to center a position (e.g., an x-position) of the electronic device within the adjustable cradle. The second adjustable holder can be similar or identical to left side holder **10851** (FIG. **108**) and/or left side holder **12751** (FIG. **127**). The third adjustable holder can be similar or identical to right side holder **10852** (FIG. **108**) and/or right side holder **12752** (FIG. **127**). In some embodiments, a position of the alignment base in a direction between the second adjustable holder and the third adjustable holder (e.g., a position in the x-direction) is fixed.

(649) In various embodiments, the adjustable cradle can include an adjustable side holder configured to hold the electronic device against a fixed opposing side wall of the adjustable cradle that is opposite the adjustable side holder when the electronic device is held within the adjustable cradle. The adjustable side holder can be similar or identical to side holder **11752** (FIG. **117**), right top corner holder **13352** (FIG. **133**), and/or right holder piece **13552** (FIG. **135**). The fixed opposing side wall can be similar or identical to left side wall **11771** (FIG. **117**), left bottom corner holder **13351** (FIG. **133**), and/or left holder piece **13551** (FIG. **135**). In some embodiments, when the adjustable side holder moves a first distance in a direction between the adjustable side holder and the fixed opposing side wall (e.g., the x-direction), the

alignment base moves a second distance in the direction between the adjustable side holder and the fixed opposing side wall, and the second distance is half of the first distance.

(650) In various embodiments, method **14200** additionally and optionally can include a block **14230** of providing a support base including the adjustable cradle and the alignment base. The support base can be similar or identical to base **10620** (FIG. **106**), **11720** (FIG. **117**), base **12520** (FIG. **125**), and/or base **13320** (FIG. **133**). In some embodiments, the alignment base can be adjustable with respect to the support base. In several embodiments, the support base can include a recess configured to hold different alignment plates. In various embodiments, the different alignment plates each can be configured to position the alignment base at a different respective y-position (e.g., position along the y-direction) with respect to the support base. The alignment plates can be similar or identical to alignment plate **13151** (FIG. **131**).

(651) In many embodiments, method **14200** further and optionally can include a block **14240** of providing a lid hingedly attached to the support base and configured to rotate with respect to the support base between an opened configuration and a closed configuration. The lid can be similar or identical to lid **10630** (FIG. **106**), lid **11730** (FIG. **117**), lid **12530** (FIG. **125**), and/or lid **13330** (FIG. **133**). In other embodiments, the machine does not include a lid. In some embodiments, the lid can be configured to push inward (e.g., in the z-direction) on the electronic device to adjust the position (e.g., position in the z-direction) of the adjustable cradle when the lid is rotated to the closed configuration with the electronic device held in the adjustable cradle. The opened configuration can be similar or identical to the opened configuration shown in FIGS. **107**, **113**, **117**, **118**, and **133**. The closed configuration can be similar or identical to the closed configuration shown in FIGS. **106**, **114**, **116**, **125**, **133**, and **137**.

(652) Although the invention has been described with reference to specific embodiments, it will be understood by those skilled in the art that various changes may be made without departing from the spirit or scope of the invention. Accordingly, the disclosure of embodiments of the invention is intended to be illustrative of the scope of the invention and is not intended to be limiting. It is intended that the scope of the invention shall be limited only to the extent required by the appended claims. For example, to one of ordinary skill in the art, it will be readily apparent that various elements of FIGS. **1-142** may be modified, combined, and/or interchanged, and that the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments. As another example, one or more of the procedures, processes, or activities of FIGS. **23-26**, **51-54**, **75-79**, **93-94**, **105**, and/or **139-142** may include different procedures, processes, and/or activities and be performed in many different orders, and/or one or more of the procedures, processes, or activities of FIGS. **23-26**, **51-54**, **75-79**, **93-94**, **105**, and/or **139-142** may include one or more of the procedures, processes, or activities of another different one of FIGS. **23-26**, **51-54**, **75-79**, **93-94**, **105**, and/or **139-142**. As another example, the elements of frame **210** (FIG. **2**), cradle **310** (FIG. **3**), machine **800** (FIGS. **8-14**), machine **1600** (FIGS. **16-19**), and/or machine **2000** (FIGS. **20-22**), cradle **3100** (FIG. **31**), machine **3500** (FIG. **35**), system **3700** (FIG. **37**), machine **3740** (FIG. **37**), machine **4100** (FIG. **41**), machine **4600** (FIG. **46**), cradle **6410** (FIG. **64**), cradle **6420** (FIG. **64**), cradle **6430** (FIG. **64**), machine **6900** (FIG. **69**), cradle **8080** (FIG. **80**), and/or cradle **9180** (FIG. **91**), machine **10600** (FIG. **106**), machine **11700** (FIG. **117**), machine **12500** (FIG. **125**), and/or machine **13300** (FIG. **133**) can be interchanged or otherwise modified.

(653) Replacement of one or more claimed elements constitutes reconstruction and not repair.

Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are expressly stated in such claim.

(654) Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

Claims

1. A machine comprising: an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions; and an alignment base configured to engage, individually at different times, with overlay applicators, each respective one of the overlay applicators comprising a respective overlay configured to be applied to a respective surface of each of the electronic devices, wherein: the machine is configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices; the adjustable cradle comprises a second adjustable holder and a third adjustable holder; the second adjustable holder and the third adjustable holder are on opposite sides of the adjustable cradle; and the second adjustable holder and the third adjustable holder are configured to adjust a respective position of each of the electronic devices held in the adjustable cradle with respect to the alignment base.
2. The machine of claim 1, wherein: the electronic devices comprise a first electronic device and a second electronic device; the adjustable cradle is configured to hold, individually at different times, the first electronic device and the second electronic device; the first electronic device of the electronic devices has a first length and a first width; the second electronic device of the electronic devices has a second length different from the first length and a second width different from the first width; and the different dimensions comprise the first length, the first width, the second length, and the second width.
3. The machine of claim 2, wherein: the machine is configured in an opened configuration such that (a) either of the first electronic device or the second electronic device and (b) a respective one of the overlay applicators can be inserted and removed from the machine; the machine is configured in a closed configuration to prevent removal of (a) the either of the first electronic device or the second electronic device and (b) at least a portion of the respective one of the overlay applicators from the machine; and the machine is configured in the closed configuration such that a respective pull tab of the respective one of the overlay applicators can be pulled to remove a respective adhesive release liner of the respective one of the overlay applicators from the respective overlay of the respective one of the overlay applicators to expose an adhesive agent of the respective overlay to the respective surface of the either of the first electronic device or the second electronic device.
4. The machine of claim 1 further comprising: a support base comprising the adjustable cradle and the alignment base.
5. The machine of claim 4 further comprising: a lid is hingedly attached to the support base and configured to rotate with respect to the support base between an opened configuration and a closed configuration.
6. The machine of claim 1, wherein: the adjustable cradle is configured to hold the second adjustable holder and the third adjustable holder in an opened position until a button is activated by insertion of each of the electronic devices into the adjustable cradle to (a) transition the second adjustable holder and the third adjustable holder from the opened position to a closed position and (b) hold each of the electronic devices within the adjustable cradle.
7. The machine of claim 1, wherein: the adjustable cradle comprises a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle to allow insertion of each of the electronic devices into the adjustable cradle and (b) hold each of the electronic devices against a second side wall of the adjustable cradle opposite the first side wall when each of the electronic devices is held within the adjustable cradle.
8. The machine of claim 7, wherein: the adjustable cradle is configured to adjust a position in the first direction of the alignment base for different first dimensions of the electronic devices with respect to the first adjustable holder such that a distance between the alignment base and a respective center of a respective first dimension of each of the electronic devices is constant between the electronic devices when each of the electronic devices is held within the adjustable cradle.
9. The machine of claim 7, wherein the adjustable cradle comprises one or more buttons configured to: transition the first adjustable holder, the second adjustable holder, the third adjustable holder to a closed position to hold each of the electronic devices within the adjustable cradle.
10. The machine of claim 1, wherein: when each of the electronic devices is held within the adjustable cradle, the second adjustable holder and the third adjustable holder are configured to center each of the electronic devices with respect to the alignment base.

11. A method of providing a machine, the method comprising: providing an adjustable cradle configured to hold, individually at different times, electronic devices having different dimensions; and providing an alignment base configured to engage, individually at different times, with overlay applicators, each respective one of the overlay applicators comprising a respective overlay configured to be applied to a respective surface of each of the electronic devices, wherein: the machine is configured to facilitate applying, individually at different times, the respective overlays to the respective surfaces of the electronic devices; the adjustable cradle comprises a second adjustable holder and a third adjustable holder; the second adjustable holder and the third adjustable holder are on opposite sides of the adjustable cradle; and the second adjustable holder and the third adjustable holder are configured to adjust a respective position of each of the electronic devices held in the adjustable cradle with respect to the alignment base.

12. The method of claim 11, wherein: the electronic devices comprise a first electronic device and a second electronic device; the adjustable cradle is configured to hold, individually at different times, the first electronic device and the second electronic device; the first electronic device of the electronic devices has a first length and a first width; the second electronic device of the electronic devices has a second length different from the first length and a second width different from the first width; and the different dimensions comprise the first length, the first width, the second length, and the second width.

13. The method of claim 12, wherein: the machine is configured in an opened configuration such that (a) either of the first electronic device or the second electronic device and (b) a respective one of the overlay applicators can be inserted and removed from the machine; the machine is configured in a closed configuration to prevent removal of (a) the either of the first electronic device or the second electronic device and (b) at least a portion of the respective one of the overlay applicators from the machine; and the machine is configured in the closed configuration such that a respective pull tab of the respective one of the overlay applicators can be pulled to remove a respective adhesive release liner of the respective one of the overlay applicators from the respective overlay of the respective one of the overlay applicators to expose an adhesive agent of the respective overlay to the respective surface of the either of the first electronic device or the second electronic device.

14. The method of claim 11 further comprising: providing a support base comprising the adjustable cradle and the alignment base.

15. The method of claim 14 further comprising: providing a lid is hingedly attached to the support base and configured to rotate with respect to the support base between an opened configuration and a closed configuration.

16. The method of claim 11, wherein: the adjustable cradle is configured to hold the second adjustable holder and the third adjustable holder in an opened position until a button is activated by insertion of each of the electronic devices into the adjustable cradle to (a) transition the second adjustable holder and the third adjustable holder from the opened position to a closed position and (b) hold each of the electronic devices within the adjustable cradle.

17. The method of claim 11, wherein: the adjustable cradle comprises a first adjustable holder configured to (a) be pushed in a first direction toward a first side wall of the adjustable cradle to allow insertion of each of the electronic devices into the adjustable cradle and (b) hold each of the electronic devices against a second side wall of the adjustable cradle opposite the first side wall when each of the electronic devices is held within the adjustable cradle.

18. The method of claim 17, wherein: the adjustable cradle is configured to adjust a position in the first direction of the alignment base for different first dimensions of the electronic devices with respect to the first adjustable holder such that a distance between the alignment base and a respective center of a respective first dimension of each of the electronic devices is constant between the electronic devices when each of the electronic devices is held within the adjustable cradle.

19. The method of claim 17, wherein the adjustable cradle comprises one or more buttons configured to: transition the first adjustable holder, the second adjustable holder, the third adjustable holder to a closed position to hold each of the electronic devices within the adjustable cradle.

20. The method of claim 11, wherein: when each of the electronic devices is held within the adjustable cradle, the second adjustable holder and the third adjustable holder are configured to center each of the electronic devices with respect to the alignment base.

