

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415354
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Mori; Tatsurou et al.

Liquid ejection head and ejection apparatus

Abstract

A liquid ejection head includes an ejection element substrate, an electrical contact portion, a housing, and an opening/closing member. The ejection element substrate ejects liquid to perform recording. The electrical contact portion is electrically connected to an electrical wiring unit of an ejection apparatus to supply power to the ejection element substrate. The housing includes an opening portion into which the electrical wiring unit is inserted and to be provided with the electrical contact portion inside. The opening/closing member opens and closes the opening portion. In a closed state in which the opening/closing member closes the opening portion, the electrical wiring unit is sandwiched between the opening/closing member and a part of the housing.

Inventors: Mori; Tatsurou (Tokyo, JP), Iwano; Takuya (Tokyo, JP), Tsuji; Tomoki (Kanagawa, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008819097

Assignee: Canon Kabushiki Kaisha (Tokyo, JP)

Appl. No.: 18/513118

Filed: November 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240173975 A1	May. 30, 2024

Foreign Application Priority Data

JP	2022-191507	Nov. 30, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: B41J2/14 (20060101)

U.S. Cl.:

CPC B41J2/14201 (20130101); B41J2002/14491 (20130101)

Field of Classification Search

CPC: B41J (2/14201); B41J (2002/14491)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0001604	12/2019	Takeuchi	N/A	B41J 2/1623

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2014004767	12/2013	JP	N/A

Primary Examiner: Solomon; Lisa

Attorney, Agent or Firm: Canon U.S.A., Inc. IP Division

Background/Summary

BACKGROUND

Field

(1) The present disclosure relates to a liquid ejection head and an ejection apparatus.

Description of the Related Art

(2) Ink jet recording apparatuses include liquid ejection heads that eject liquid to recording media. In particular, the liquid ejection heads used for business purposes, such as business, commercial, and industrial applications, require high durability for long-term use. One factor that reduces durability of a liquid ejection head is, for example, infiltration of liquid into electrical contact portions between an ink jet recording apparatus and the liquid ejection head. The factors causing the infiltration of liquid into the electrical contact portions include, for example, dripping of liquid from liquid connection portions at a time of attaching and detaching the liquid ejection head to and from the recording apparatus or mist generated when liquid such as ink is ejected. In these cases, there is an issue that an electrical circuit may be short-circuited and cause the liquid ejection head to break down.

(3) Japanese Patent Application Laid-Open No. 2014-004767 discusses, as a method for addressing the above-described issue, a liquid ejection head including a cover member for covering electrical contact portions between a recording apparatus and a liquid ejection head. The cover member is also configured to be deformable so as to reduce a gap between the cover member and the electrical contact portions and thus suppresses infiltration of liquid into the electrical contact portions of the liquid ejection head.

(4) The configuration discussed in Japanese Patent Application Laid-Open No. 2014-004767, however, can suppress infiltration of the liquid into the electrical contact portions, but the cover

member cannot be opened and closed. Thus, there is a concern that the electrical contact portion cannot be easily attached and detached in a case where the liquid ejection head is attached to and detached from an ejection apparatus.

SUMMARY

(5) The present disclosure is directed to the provision of a liquid ejection head that can suppress infiltration of liquid into electrical contact portions of the liquid ejection head and can be easily attached to and detached from an ejection apparatus.

(6) According to an aspect of the present disclosure, a liquid ejection head includes an ejection element substrate configured to eject liquid to perform recording, an electrical contact portion configured to be electrically connected to an electrical wiring unit of an ejection apparatus to supply power to the ejection element substrate, a housing configured to include an opening portion into which the electrical wiring unit is inserted and to be provided with the electrical contact portion inside, and an opening/closing member configured to open and close the opening portion, wherein, in a closed state in which the opening/closing member closes the opening portion, the electrical wiring unit is sandwiched between the opening/closing member and a part of the housing.

(7) Further features of the present disclosure will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of an ejection apparatus.

(2) FIG. 2 is a perspective view of a liquid ejection head.

(3) FIG. 3 is a perspective view of the liquid ejection head.

(4) FIG. 4 is an exploded perspective view of the liquid ejection head.

(5) FIG. 5 is a perspective view illustrating an electrical connection configuration of the liquid ejection head.

(6) FIG. 6 is a perspective view of an ejection unit.

(7) FIG. 7 is a perspective view of the ejection unit.

(8) FIG. 8 is an exploded perspective view of the ejection unit.

(9) FIG. 9 is an enlarged view of an electrode portion of the ejection unit.

(10) FIG. 10 is a plan view of the liquid ejection head viewed from a surface of the ejection unit.

(11) FIG. 11 is a cross-sectional view of the liquid ejection head taken along a line A-A.

(12) FIG. 12 is a cross-sectional view of the liquid ejection head taken along a line B-B.

(13) FIG. 13 is a cross-sectional view of the liquid ejection head taken along a line C-C.

(14) FIG. 14 is perspective views illustrating a liquid connection configuration of the liquid ejection head.

(15) FIG. 15 is a cross-sectional view of a liquid connection portion between a liquid supply unit and a liquid supply member.

(16) FIG. 16 is a cross-sectional view of a flow path of the ejection unit.

(17) FIG. 17 is a cross-sectional view of a flow path in a recording element substrate.

(18) FIG. 18 is a perspective view of a cooling unit.

(19) FIG. 19 is an exploded perspective view of the cooling unit.

(20) FIG. 20 is a cross-sectional view of the cooling unit taken along a line D-D.

(21) FIG. 21 is cross-sectional views of electrical contact portions between the ejection apparatus and the liquid ejection head.

(22) FIG. 22 is a perspective view of the liquid ejection head to which electrical wiring units are connected.

(23) FIG. 23 is a perspective view of the liquid ejection head to which the electrical wiring units

are connected.

DESCRIPTION OF THE EMBODIMENTS

(24) Exemplary embodiments of the present disclosure will be described below with reference to the attached drawings. The following exemplary embodiments are not meant to limit the scope of the present disclosure and, not all combinations of features described in the present exemplary embodiment are essential. The same reference numerals are used for the same components.

(25) According to a first exemplary embodiment, a method is described in which liquid is ejected by using a piezoelectric element that generates pressure by applying voltage. The present disclosure can be applied to a liquid ejection head that adopts a thermal method for ejecting liquid using a thermoelectric conversion element and other various liquid ejection methods.

(26) According to the present exemplary embodiment, a liquid ejection head to be used in an ink jet recording apparatus that ejects ink is described. However, liquid to be ejected is not limited to ink. In other words, the present disclosure can be applied to a liquid ejection head that is used in an ejection apparatus. The present disclosure is applied to an ink jet recording apparatus that has a form of circulating liquid, such as ink, between a tank and a liquid ejection head, but other forms can also be used. For example, a form can be used in which two tanks are provided on an upstream side and a downstream side of a liquid ejection head, and ink in a pressure chamber flows from one tank to the other without circulating the ink.

(27) FIG. 1 is a perspective view of a recording apparatus **10** according to the present exemplary embodiment. The recording apparatus **10** according to the present exemplary embodiment is a one-pass type inkjet recording apparatus that records an image or the like by moving a printing medium **20** with respect to a liquid ejection head **100** that is arranged over an entire width of the printing medium **20** to eject liquid. The printing medium **20** is conveyed by a conveyance unit **11** in a direction of an arrow A, and recording is performed thereon by the liquid ejection head **100**. The liquid ejection head **100** of the ink jet recording apparatus according to the present exemplary embodiment is composed of two liquid ejection heads in two rows a and b for each of cyan (liquid ejection heads **100Ca** and **100Cb**), magenta (liquid ejection heads **100Ma** and **100Mb**), yellow (liquid ejection heads **100Ya** and **100Yb**), and black (liquid ejection heads **100Ka** and **100Kb**). Arrangement and the number of the liquid ejection heads **100** are not limited to this.

(28) A configuration of the liquid ejection head **100** according to the present exemplary embodiment will now be described. FIGS. 2 and 3 are perspective views and FIG. 4 is an exploded perspective view of the liquid ejection head **100** according to the present exemplary embodiment. In the liquid ejection head **100** according to the present exemplary embodiment, four recording element substrates **210**, which are ejection element substrates capable of ejecting liquid, are arranged in a staggered pattern on a support member **310**. The number of recording element substrates **210** is not limited to four. The recording element substrate **210** does not have to be arranged in the staggered pattern. Approximately at the center of an upper end of a housing **420** of the liquid ejection head **100**, an ink connection portion **501** and a refrigerant connection portion **611**, which are liquid connection portions, are provided. The ink connection portion **501** and the refrigerant connection portion **611** are respectively connected to an ink supply unit and a refrigerant supply unit on a side of the recording apparatus **10**, so that liquid, such as ink and refrigerant, are supplied into the liquid ejection head **100**. A liquid ejection head exterior unit includes a housing **420** that covers an ejection unit **200** that ejects liquid.

(29) The housing **420** further includes opening/closing members **430** that cover an electrical contact portion **402** electrically connected to an electrical wiring unit **12** (FIG. 21) of the ink jet recording apparatus. According to the present exemplary embodiment, two each of the electrical contact portions **402** and the opening/closing members **430** are provided for one liquid ejection head **100**. However, the present disclosure is not limited to this configuration. In a case where at least two electrical contact portions **402** and two opening/closing members **430** are provided, it is desirable that the at least two opening/closing members **430** face each other so as to sandwich the

liquid connection portion therebetween. Accordingly, in FIG. 21, this arrangement can suppress both the opening/closing members **430** on a left side of a paper surface and the opening/closing members **430** on a right side of the paper surface from being soiled by liquid. The reasons is that, if liquid leaks from the ink connection portion **501** to an area illustrated in the left side of the paper surface, there is a possibility that the liquid will adhere to the opening/closing member **430** on the left side of the paper surface, but the opening/closing member **430** on the right side of the paper surface is on the opposite side, and thus there is a low possibility that the liquid will adhere to the opening/closing member **430** on the right side.

(30) The liquid ejection head **100** includes a support unit **300** that includes the support member **310**, electrical relay boards **400**, and electrical relay board support members **410** that hold the electrical relay boards **400**. In other words, the electrical relay boards **400** are arranged inside the housing **420**. The liquid ejection head **100** further includes a liquid supply unit **500** that supplies liquid to the ejection unit **200** via the support unit **300**, and a cooling unit **600** that cools a drive circuit. The support member **310** is arranged between the ejection unit **200** and the housing **420**. A structure of each part of the liquid ejection head **100** is described in detail below.

(31) FIG. 5 is a perspective view illustrating an electrical connection configuration of the liquid ejection head **100** according to the present exemplary embodiment. The liquid ejection head **100** includes, as the electrical connection configuration, the electrical contact portions **402**, the electrical relay boards **400**, electrical contact portions **401**, and flexible wiring boards **250**. The recording apparatus **10** and the liquid ejection head **100** are electrically connected by connecting the electrical wiring unit **12** (FIG. 21) and the electrical relay boards **400** with the electrical contact portions **402**. The electrical relay boards **400** supply (relay) electricity supplied from the recording apparatus **10** to the flexible wiring boards **250** via the electrical contact portions **401**. The electricity supplied to the flexible wiring boards **250** is supplied to the recording element substrates **210** via an electrode portion **212** (FIG. 9), which will be described below. In this way, an ejection drive signal and power used for ejecting liquid from the liquid ejection head **100** are supplied from the recording apparatus **10** to the liquid ejection head **100**. In other words, the electricity is supplied from the recording apparatus **10** to the ejection unit **200** via the electrical contact portions **402**. Wiring is consolidated by an electric circuit in the electrical relay board **400**, and thus the number of terminals of the electrical contact portion **402** can be reduced compared with the number of terminals of the recording element substrate **210**. Accordingly, the number of electrical contact portions required for attaching and detaching the liquid ejection head **100** to and from the recording apparatus **10** can be reduced. It is desirable that the electrical contact portion **402** is formed at an end of the electrical relay board **400**.

(32) FIGS. 6 and 7 are perspective views and FIG. 8 is an exploded perspective view of the ejection unit **200**. The ejection unit **200** includes the recording element substrate **210** provided with a pressure generation element that generates pressure for ejecting liquid. The ejection unit **200** further includes a recording element substrate flow path member **220** for supplying liquid to the recording element substrate **210**, a flow path member **240**, and a recording element substrate support member **230** joined to an ejection surface side of the recording element substrate **210**. As a pressure generation element, it is desirable to include a piezoelectric element that is driven by application of voltage. A piezoelectric element typically has a longer service life than a thermoelectric conversion element, which is a thermal type pressure generation element, and the number of times of replacing the liquid ejection head **100** tends to be large in a piezoelectric type recording apparatus. Thus, the present disclosure is suitable for the piezoelectric type recording apparatus.

(33) FIG. 9 is an enlarged view of the electrode portion **212** of the ejection unit **200**. As illustrated in FIG. 9, the electrode portions **212** are provided on thin plate portions **261** at both ends of the recording element substrate **210**. A first electrical contact portion **252** of the flexible wiring board **250** is brought into contact with the electrode portion **212**, and thus the recording element substrate

210 is electrically connected and to the flexible wiring board **250**. In order to prevent infiltration of liquid into the first electrical contact portion **252** and to reinforce the thin plate portion **261** of the recording element substrate **210**, the recording element substrate support member **230** is joined to the ejection surface side of the thin plate portion **261**. The flexible wiring board **250** includes a drive circuit board **251** for driving recording elements of the recording element substrate **210**.

(34) FIG. **10** is a plan view of the liquid ejection head **100** viewed from a surface of the ejection unit **200**. FIGS. **11**, **12**, and **13** are cross-sectional views of the liquid ejection head **100** according to the present exemplary embodiment respectively taken along a line A-A, a line B-B, and a line C-C, respectively. The ejection unit **200** is surrounded by a frame body member **320**. The housing **420** is connected above the support member **310**, and the liquid supplied from the housing **420** is supplied to a plurality of liquid paths **242** via a support member path **311**. The housing **420** also includes a sealing member **421** that can seal a gap, between the housing **420** and the support member **310**. With this configuration, it is possible to suppress, for example, liquid from dripping from the ink connection portion **501** and the refrigerant connection portion **611** at a time of attaching and detaching the liquid ejection head **100** to and from the recording apparatus **10**, and infiltration of liquid into the liquid ejection head **100** due to mist at the time of ejecting liquid such as ink. As a material for the sealing member **421**, an elastomer or the like can be suitably used.

(35) A method for forming the sealing member **421** with respect to the housing **420** includes, for example, two-color molding (joining) and bonding methods. In a case where the housing **420** and the sealing member **421** are molded by two-color molding (joining), difficulty of molding the housing **420** increases, but the number of parts and mounting processes for configuring the liquid ejection head **100** can be reduced. In contrast, in a case where the housing **420** and the sealing member **421** are bonded, the number of parts and the mounting processes for configuring the liquid ejection head **100** are increased, but the sealing member **421** can be manufactured more easily compared with the two-color molding method.

(36) FIG. **14** is a perspective view illustrating a liquid connection configuration of the liquid ejection head **100** according to the present exemplary embodiment. The liquid supply unit **500** includes ink connection portions **501** and is connected to a liquid supply system of the recording apparatus **10**. Liquid is thereby supplied from the supply system of the recording apparatus **10** to the liquid ejection head **100**, and liquid not ejected from the liquid ejection head **100** is collected into the supply system of the recording apparatus **10**. In this way, liquid can be circulated between the recording apparatus **10** and the liquid ejection head **100**. It is desirable that the liquid supply unit **500** is provided with a filter (not illustrated) communicating with each opening of the ink connection portion **501** to remove foreign matter from the supplied ink.

(37) FIG. **15** is a cross-sectional view of the liquid connection portion between the liquid supply unit **500** and a liquid supply member **330**. Liquid flowing into the liquid ejection head **100** from the recording apparatus **10** side through the ink connection portion **501** passes through a communication port **502** and the liquid is supplied to the liquid supply member **330**. A space between the liquid supply unit **500** and the liquid supply member **330** is sealed by an elastic member **503**.

(38) The support member **310** and each ejection unit **200** are fluidly connected through a communication port **241** of the flow path member **240**. A liquid flow path **242** is formed in the flow path member **240** and is fluidly connected to the recording element substrate flow path member **220** via a communication port **221**.

(39) FIG. **17** is a cross-sectional view of a flow path in the recording element substrate **210**. The liquid flowing from each communication port **221** passes through a common flow path **222** and is supplied to the recording element substrate **210**. The ejection unit **200** (the recording element substrate **210**) includes a piezoelectric element **262** that is driven by application of voltage, and ejects the liquid from an ejection port **213** using pressure generated by driving the piezoelectric element **262**. In the liquid ejection head **100** according to the present exemplary embodiment,

liquid that is not ejected from the ejection port **213** passes through the common flow path **222** and the communication port **221** and the liquid is collected into the ink jet recording apparatus as described above.

(40) FIGS. **18** and **19** are respectively a perspective view and an exploded perspective view of the cooling unit **600** for cooling the drive circuit board **251**. FIG. **20** is a cross-sectional view of the cooling unit **600** taken along a D-D line. The cooling unit **600** includes the refrigerant connection portion **611** and is connected to a refrigerant supply system of the recording apparatus **10**. The refrigerant is thereby supplied from the refrigerant supply system of the recording apparatus **10** to the cooling unit **600**. The refrigerant having passed through refrigerant paths **631** included in the cooling unit **600** is collected to the refrigerant supply system of the recording apparatus **10**. In this way, the refrigerant can be circulated between the recording apparatus **10** and the cooling unit **600**. The refrigerant flowing from the refrigerant connection portion **611** branches at a refrigerant flow path formed between a first refrigerant supply member **610** and a second refrigerant supply member **620**. The second refrigerant supply member **620** and a first cooling member **630** are fluidly connected via a seal member **670**. The refrigerant branched in the second refrigerant supply member **620** then circulates in the refrigerant flow path formed between the first cooling member **630** and a second cooling member **640**, and flows into the second refrigerant supply member **620** again. The first cooling member **630** is brought into contact with the drive circuit board **251** with a heat conductive member **650** in between, so that heat generated during an operation of the drive circuit board **251** is transferred to the refrigerant inside the first cooling member **630**. An elastic member **660** is provided between two flexible wiring boards **250**, and it is thereby possible to reliably bring the heat conductive member **650** into close contact with the drive circuit board **251**. It is desirable for the first cooling member **630** to select a material with high thermal conductivity, such as aluminum, in order to easily transfer the heat generated by the drive circuit board **251**.

(41) The opening/closing member **430**, which is a characteristic part of the present disclosure, will now be described in detail. FIG. **21** is cross-sectional views of the electrical contact portion between the recording apparatus **10** and the liquid ejection head **100**. FIGS. **22** and **23** are respectively a perspective view and a cross-sectional view of the liquid ejection head to which the electrical wiring units **12** are connected. As described above, the liquid ejection head **100** includes the ink connection portion **501** and the refrigerant connection portion **611** approximately at the center of an upper end of the liquid ejection head **100**. The ink connection portion **501** and the refrigerant connection portion **611** are respectively connected to the liquid supply unit and the refrigerant supply unit on the recording apparatus side, and liquid, such as ink and the refrigerant, are supplied into the liquid ejection head **100**. In the liquid ejection head **100** according to the present exemplary embodiment, two each of the electrical contact portions **402** and the opening/closing members **430** are provided for one liquid ejection head **100** and are arranged to face each other so as to sandwich the liquid connection portion therebetween. A connection direction between the electrical contact portion **402** and the electrical wiring unit **12** is approximately the same direction as connection directions between the ink connection portion **501** and the liquid supply unit and between the refrigerant connection portion **611** and the refrigerant supply unit on the recording apparatus side, and is an approximately vertical direction in using the liquid ejection head **100**. Here, in using the liquid ejection head **100** refers to an arrangement state of the liquid ejection head **100** in a state where the recording apparatus **10** can normally record an image, a character, and the like.

(42) The housing **420** includes the opening/closing member **430** that covers the electrical contact portion **402**. The electrical contact portion **402** is covered by the opening/closing member **430** (is in a closed state), and accordingly, for example, it is possible to suppress liquid from dripping from the liquid connection portion at the time of attaching and detaching the liquid ejection head to and from the recording apparatus and the infiltration of liquid into the electrical contact portion **402** due to mist at the time of ejecting liquid such as ink. In addition, the opening/closing member **430** is

configured to be openable/closable with respect to the electrical contact portion **402**. It is noted that the electrical contact portion **402** being covered by the opening/closing member **430** (being in the closed state) refers to a state in which an edge of an opening (an opening portion) into which the electrical wiring unit **12** is inserted is closed by the opening/closing member **430**.

(43) Specifically, the opening/closing member **430** includes a fixing portion **450** fixed to the housing **420** and an abutting unit **460** that abuts on the electrical wiring unit **12** of the recording apparatus **10**, and has a rotation shaft for rotating using the fixing portion **450** as a starting point. The opening/closing member **430** has the rotation shaft and thus can rotate in a direction of a curved arrow illustrated in FIG. **21**. In a case where the opening/closing members **430** are arranged to face each other to sandwich the liquid connection portion as illustrated in FIG. **21**, the opening/closing members **430** can be opened and closed in opposite directions. With this configuration, the opening/closing member **430** protects the electrical contact portion **402** in using the recording apparatus **10**, and the liquid ejection head **100** can be easily attached to and detached from the recording apparatus **10** at the time of attaching and detaching the liquid ejection head **100**.

(44) The opening/closing member **430** includes a protruding portion **480**, and the housing **420** includes a concave portion **470** with which the protruding portion **480** engages. If the opening/closing member **430** is in a closed state with respect to the electrical contact portion **402**, the protruding portion **480** thereby engages with the concave portion **470**, so that the closed state can be maintained, and the infiltration of liquid into the electrical contact portion **402** can be further suppressed.

(45) In a closed state in which an opening portion **491** is closed, the electrical wiring unit **12** is sandwiched between the opening/closing member **430** and a part of the housing **420**. It is also desirable that the abutting unit **460** is formed with an elastic member **431** that seals around the electrical contact portion **402** in the closed state of the opening/closing member **430**. With this configuration, sealing performance around the electrical contact portion **402** is improved, and the infiltration of liquid into the electrical contact portion **402** can be further suppressed. As a material of the elastic member **431**, elastomer or the like can be suitably used. A method for forming the elastic member **431** with respect to the opening/closing member **430** includes, for example, the two-color molding (joining) and bonding methods. In a case of the two-color molding (joining), difficulty of molding the opening/closing member **430** increases, but the number of parts or the mounting processes for configuring the liquid ejection head **100** can be reduced. In contrast, in a case of bonding, the number of parts and the mounting processes for configuring the liquid ejection head **100** are increased, but the elastic member **431** can be manufactured more easily compared with the two-color molding method.

(46) It is also desirable that the electrical wiring unit **12** that abuts on the abutting unit **460** is a flexible wiring board. In a case where the electrical wiring unit **12** is formed with a flexible member, such as a flexible wiring board, sealing performance between the abutting unit **460** and the electrical wiring unit **12** is improved, and the infiltration of liquid into the electrical contact portion **402** can be further suppressed.

(47) As described above, the liquid ejection head **100** according to the present exemplary embodiment can be easily attached to and detached from the recording apparatus **10** while suppressing infiltration of liquid into the electrical contact portion **402** with the recording apparatus **10**.

(48) To summarize the present disclosure described above, the present disclosure includes the following configurations.

(49) According to the present disclosure, it is possible to provide a liquid ejection head that suppresses infiltration of liquid into an electrical contact portion of the liquid ejection head and can be easily attached to and detached from a recording apparatus, and a recording apparatus having the liquid ejection head.

(50) While the present disclosure has been described with reference to exemplary embodiments, it

is to be understood that the disclosure is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(51) This application claims the benefit of Japanese Patent Application No. 2022-191507, filed Nov. 30, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. A liquid ejection head comprising: an ejection element substrate configured to eject liquid to perform recording; an electrical contact portion configured to be electrically connected to an electrical wiring unit of an ejection apparatus to supply power to the ejection element substrate; a housing configured to include an opening portion into which the electrical wiring unit is inserted and to be provided with the electrical contact portion inside; and an opening/closing member configured to open and close the opening portion, wherein, in a closed state in which the opening/closing member closes the opening portion, the electrical wiring unit is sandwiched between the opening/closing member and a part of the housing.
2. The liquid ejection head according to claim 1, wherein the opening/closing member includes a protruding portion, and wherein the housing includes a concave portion with which the protruding portion engages in the closed state.
3. The liquid ejection head according to claim 1, wherein the opening/closing member includes a fixing portion fixed to the housing and is configured to rotate using the fixing portion as a fulcrum.
4. The liquid ejection head according to claim 1, wherein the opening/closing member includes an elastic portion that abuts on the electrical wiring unit in the closed state.
5. The liquid ejection head according to claim 4, wherein the elastic portion is joined to the opening/closing member.
6. The liquid ejection head according to claim 1, further comprising an ejection unit provided with the ejection element substrate including a pressure generation element configured to generate pressure for ejecting liquid, and a flexible wiring board electrically connected to the ejection element substrate, wherein an electrical relay board electrically connected to the flexible wiring board to relay electricity to the flexible wiring board is arranged inside the housing, and wherein the electrical contact portion is formed at an end of the electrical relay board.
7. The liquid ejection head according to claim 6, wherein the pressure generation element is a piezoelectric element driven by application of voltage.
8. The liquid ejection head according to claim 6, further comprising: a support member configured to support the ejection unit and to be arranged between the ejection unit and the housing; and a sealing member configured to seal a gap between the housing and the support member.
9. The liquid ejection head according to claim 8, wherein the sealing member is bonded to the housing.
10. The liquid ejection head according to claim 8, wherein the sealing member is joined to the housing.
11. The liquid ejection head according to claim 1, wherein the housing includes a liquid connection portion fluidly connected to the ejection apparatus.
12. The liquid ejection head according to claim 11, wherein the liquid ejection head includes at least two electrical contact portions and two opening/closing members, and wherein the at least two opening/closing members face each other so as to sandwich the liquid connection portion.
13. The liquid ejection head according to claim 12, wherein the at least two opening/closing members are configured to be respectively opened and closed in opposite directions.
14. The liquid ejection head according to claim 1, wherein the electrical wiring unit is a flexible wiring board.
15. An ejection apparatus comprising: a liquid ejection head having: an ejection element substrate

configured to eject liquid to perform recording, an electrical contact portion configured to be electrically connected to an electrical wiring unit of the ejection apparatus to supply power to the ejection element substrate, a housing configured to include an opening portion into which the electrical wiring unit is inserted and to be provided with the electrical contact portion inside, and an opening/closing member configured to open and close the opening portion, wherein, in a closed state in which the opening/closing member closes the opening portion, the electrical wiring unit is sandwiched between the opening/closing member and a part of the housing.
