

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415479
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Fang; Yu et al.

System, method, and apparatus for managing vehicle data collection

Abstract

An apparatus for managing vehicle data collection that includes a controller. The controller includes: an automation definition circuit structured to implement an automation user interface, and to interpret an automation request in response to user communications with the automation user interface; an automation management circuit structured to determine an automation description in response to the automation request; and an automation command circuit structured to provide the automation description to a controller of a vehicle. The controller of the vehicle is configured to implement an automated vehicle response, responsive to the automation description.

Inventors: Fang; Yu (Palo Alto, CA), Zhu; Thurston (San Francisco, CA), Dhankhar; Sudhir Ramphal (Dublin, CA)

Applicant: Sonatus, Inc. (Sunnyvale, CA)

Family ID: 1000008819007

Assignee: Sonatus, Inc. (Sunnyvale, CA)

Appl. No.: 18/743953

Filed: June 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240326743 A1	Oct. 03, 2024

Related U.S. Application Data

continuation parent-doc US 17833614 20220606 PENDING child-doc US 18743953
continuation-in-part parent-doc US 17195589 20210308 US 11538287 20221227 child-doc US 17833614
us-provisional-application US 63197021 20210604
us-provisional-application US 63123531 20201210

Publication Classification

Int. Cl.: **G06F15/16** (20060101); **B60R25/24** (20130101); **G06F9/54** (20060101); **H04L29/06** (20060101)

U.S. Cl.:

CPC **B60R25/24** (20130101);

Field of Classification Search

CPC: H04L (41/0893); H04L (2012/40215); H04L (29/12849); H04L (45/72); H04L (67/125); H04W (4/40); G07C (5/008); G07C (5/0808); B60R (25/24); B60R (16/023)

USPC: 701/36

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4396202	12/1982	Kami	280/124.16	B60G 11/58
6292731	12/2000	Kirchhoffer et al.	N/A	N/A
7702739	12/2009	Cheng et al.	N/A	N/A
7904569	12/2010	Gelvin et al.	N/A	N/A
8024486	12/2010	Beers et al.	N/A	N/A
8140358	12/2011	Ling et al.	N/A	N/A
8705527	12/2013	Addepalli et al.	N/A	N/A
8718905	12/2013	Mosher et al.	N/A	N/A
8881038	12/2013	Palmer	N/A	N/A
9299029	12/2015	Kim	N/A	G05B 15/02
9355507	12/2015	Lee et al.	N/A	N/A
9380428	12/2015	Dame et al.	N/A	N/A
9470579	12/2015	Ritter et al.	N/A	N/A
9634892	12/2016	Das	N/A	N/A
9852636	12/2016	Chow et al.	N/A	N/A
9871819	12/2017	Liyanage et al.	N/A	N/A
10181059	12/2018	Brewton et al.	N/A	N/A
10410182	12/2018	Tang et al.	N/A	N/A
10573168	12/2019	Razak et al.	N/A	N/A
10616176	12/2019	Lei et al.	N/A	N/A
10650621	12/2019	King et al.	N/A	N/A
10723229	12/2019	Yao et al.	N/A	N/A
10743159	12/2019	Ameixieira	N/A	N/A
10759424	12/2019	Misu et al.	N/A	N/A
10945199	12/2020	Omiya et al.	N/A	N/A

10951728	12/2020	Lepp	N/A	H04L 67/566
11072356	12/2020	Mong et al.	N/A	N/A
11165651	12/2020	Fang et al.	N/A	N/A
11228496	12/2021	Fang et al.	N/A	N/A
11252039	12/2021	Fang	N/A	H04L 47/20
11287150	12/2021	Guan et al.	N/A	N/A
11312374	12/2021	Zhao	N/A	G06F 17/18
11349717	12/2021	Fang et al.	N/A	N/A
11362899	12/2021	Fang et al.	N/A	N/A
11386229	12/2021	Adams et al.	N/A	N/A
11411823	12/2021	Fang et al.	N/A	N/A
11520677	12/2021	Arazi	N/A	G06F 11/3065
11538287	12/2021	Fang et al.	N/A	N/A
11636719	12/2022	Mattern et al.	N/A	N/A
11721137	12/2022	Fang et al.	N/A	N/A
11736357	12/2022	Fang et al.	N/A	N/A
11750462	12/2022	Fang et al.	N/A	N/A
11772583	12/2022	Fang et al.	N/A	N/A
11778434	12/2022	Kim	701/31.4	H04W 4/90
11805018	12/2022	Fang et al.	N/A	N/A
11824722	12/2022	Fang et al.	N/A	N/A
11929878	12/2023	Fang et al.	N/A	N/A
11943109	12/2023	Fang et al.	N/A	N/A
12003374	12/2023	Fang et al.	N/A	N/A
12034601	12/2023	Fang et al.	N/A	N/A
12046085	12/2023	Fang et al.	N/A	N/A
12046086	12/2023	Fang et al.	N/A	N/A
12047238	12/2023	Fang et al.	N/A	N/A
12073664	12/2023	Fang et al.	N/A	N/A
12073665	12/2023	Fang et al.	N/A	N/A
12094259	12/2023	Fang et al.	N/A	N/A
12095622	12/2023	Fang et al.	N/A	N/A
12103479	12/2023	Fang et al.	N/A	N/A
12118830	12/2023	Fang et al.	N/A	N/A
12119996	12/2023	Fang et al.	N/A	N/A
12142091	12/2023	Fang et al.	N/A	N/A
12159492	12/2023	Fang et al.	N/A	N/A
12166635	12/2023	Fang et al.	N/A	N/A
12177079	12/2023	Fang et al.	N/A	N/A
12177080	12/2023	Fang et al.	N/A	N/A
12177081	12/2023	Fang et al.	N/A	N/A
12199824	12/2024	Fang et al.	N/A	N/A
12211323	12/2024	Fang et al.	N/A	N/A
12211324	12/2024	Fang et al.	N/A	N/A
12230071	12/2024	Fang et al.	N/A	N/A
12244464	12/2024	Fang et al.	N/A	N/A
12261747	12/2024	Fang et al.	N/A	N/A
2001/0033225	12/2000	Razavi	340/988	H04L 67/34

2002/0128751	12/2001	Engstrom et al.	N/A	N/A
2003/0120401	12/2002	Bauer et al.	N/A	N/A
2004/0068350	12/2003	Tomson	N/A	N/A
2004/0093434	12/2003	Hovell et al.	N/A	N/A
2004/0193912	12/2003	Li et al.	N/A	N/A
2004/0267410	12/2003	Duri et al.	N/A	N/A
2005/0075760	12/2004	Moisel et al.	N/A	N/A
2005/0108444	12/2004	Flauaus et al.	N/A	N/A
2005/0182534	12/2004	Legate et al.	N/A	N/A
2005/0187680	12/2004	Kamdar et al.	N/A	N/A
2006/0089938	12/2005	Leonard et al.	N/A	N/A
2006/0155438	12/2005	Tsunoda et al.	N/A	N/A
2007/0088635	12/2006	King	N/A	N/A
2007/0229350	12/2006	Scalisi	342/350	G08B 21/0272
2008/0086241	12/2007	Phillips et al.	N/A	N/A
2008/0094311	12/2007	Garbey et al.	N/A	N/A
2008/0119983	12/2007	Inbarajan et al.	N/A	N/A
2008/0147250	12/2007	Oesterling et al.	N/A	N/A
2008/0195257	12/2007	Rauch	N/A	N/A
2008/0258939	12/2007	Smith et al.	N/A	N/A
2009/0125153	12/2008	Yang et al.	N/A	N/A
2009/0187968	12/2008	Roese et al.	N/A	N/A
2009/0207818	12/2008	Tsai et al.	N/A	N/A
2009/0256690	12/2008	Golenski	N/A	N/A
2010/0169353	12/2009	Soetarman	N/A	N/A
2010/0269155	12/2009	Droms et al.	N/A	N/A
2010/0332584	12/2009	Ramakrishnan et al.	N/A	N/A
2011/0078299	12/2010	Nagapudi et al.	N/A	N/A
2011/0130916	12/2010	Mayer	N/A	N/A
2011/0153149	12/2010	Jeon	701/1	H04L 69/169
2011/0169755	12/2010	Murphy	345/173	G06F 9/451
2011/0196571	12/2010	Foladare et al.	N/A	N/A
2011/0260884	12/2010	Yi et al.	N/A	N/A
2011/0269441	12/2010	Silver	N/A	N/A
2012/0139489	12/2011	Gaul et al.	N/A	N/A
2012/0271849	12/2011	Lesser	707/E17.014	G06F 16/245
2013/0159489	12/2012	Cha	709/223	H04L 61/5038
2013/0204943	12/2012	Ricci	N/A	N/A
2013/0303192	12/2012	Louboutin et al.	N/A	N/A
2013/0311774	12/2012	Larson et al.	N/A	N/A
2014/0032800	12/2013	Peirce et al.	N/A	N/A
2014/0173076	12/2013	Ravindran et al.	N/A	N/A
2014/0215491	12/2013	Addepalli et al.	N/A	N/A
2014/0276090	12/2013	Breed	600/473	A61B 5/1455

2014/0277935	12/2013	Daman et al.	N/A	N/A
2014/0304830	12/2013	Gammon	N/A	N/A
2014/0325602	12/2013	Kwon	726/4	H04L 67/12
2014/0350768	12/2013	Filippov	701/23	H04L 67/12
2014/0359185	12/2013	Sawal et al.	N/A	N/A
2015/0049168	12/2014	Dielacher et al.	N/A	N/A
2015/0051787	12/2014	Doughty et al.	N/A	N/A
2015/0071115	12/2014	Neff et al.	N/A	N/A
2015/0112504	12/2014	Binion et al.	N/A	N/A
2015/0112800	12/2014	Binion et al.	N/A	N/A
2015/0149017	12/2014	Attard et al.	N/A	N/A
2015/0180891	12/2014	Seward et al.	N/A	N/A
2015/0200969	12/2014	Leung et al.	N/A	N/A
2015/0210287	12/2014	Penilla et al.	N/A	N/A
2015/0228130	12/2014	Zinner et al.	N/A	N/A
2015/0244806	12/2014	Renac et al.	N/A	N/A
2015/0276415	12/2014	Shrinath et al.	N/A	N/A
2015/0278371	12/2014	Anand et al.	N/A	N/A
2016/0031441	12/2015	Foley	N/A	N/A
2016/0082903	12/2015	Haggerty et al.	N/A	N/A
2016/0133063	12/2015	Lim et al.	N/A	N/A
2016/0163136	12/2015	Lee et al.	N/A	N/A
2016/0182341	12/2015	Fischer et al.	N/A	N/A
2016/0197776	12/2015	Das	455/419	H04W 8/265
2016/0253849	12/2015	Kwak	N/A	N/A
2016/0255154	12/2015	Kim	726/25	H04L 63/08
2016/0269225	12/2015	Kirchmeier et al.	N/A	N/A
2016/0275158	12/2015	Baset	N/A	G06F 16/248
2016/0294605	12/2015	Searle et al.	N/A	N/A
2016/0328197	12/2015	Bai et al.	N/A	N/A
2017/0054574	12/2016	Wu et al.	N/A	N/A
2017/0060559	12/2016	Ye et al.	N/A	N/A
2017/0126810	12/2016	Kentley et al.	N/A	N/A
2017/0134164	12/2016	Haga et al.	N/A	N/A
2017/0147989	12/2016	Onimaru	N/A	G08G 1/0145
2017/0161973	12/2016	Katta et al.	N/A	N/A
2017/0169634	12/2016	Mattern et al.	N/A	N/A
2017/0210228	12/2016	Katayama et al.	N/A	N/A
2017/0228410	12/2016	Slusar	N/A	N/A
2017/0248965	12/2016	Wellman et al.	N/A	N/A
2017/0251339	12/2016	Addepalli et al.	N/A	N/A
2017/0262277	12/2016	Endo et al.	N/A	N/A
2017/0264634	12/2016	Carter et al.	N/A	N/A
2017/0272442	12/2016	Klimovs et al.	N/A	N/A
2017/0339056	12/2016	Uno	N/A	N/A
2017/0339095	12/2016	Lei	N/A	H04L 67/141
2017/0359128	12/2016	Xi et al.	N/A	N/A

2018/0007161	12/2017	Hwang et al.	N/A	N/A
2018/0017404	12/2017	Mendels et al.	N/A	N/A
2018/0062988	12/2017	Sikaria et al.	N/A	N/A
2018/0072250	12/2017	Kim et al.	N/A	N/A
2018/0076970	12/2017	Han et al.	N/A	N/A
2018/0131524	12/2017	Shin	N/A	H04L 9/14
2018/0189323	12/2017	Wheeler	N/A	N/A
2018/0191636	12/2017	Wang	N/A	H04L 47/762
2018/0205703	12/2017	Grau	N/A	N/A
2018/0229977	12/2017	Hangoebl	N/A	N/A
2018/0232235	12/2017	Gaur et al.	N/A	N/A
2018/0237039	12/2017	Mong et al.	N/A	N/A
2018/0255082	12/2017	Ostergaard	N/A	N/A
2018/0261020	12/2017	Petousis et al.	N/A	N/A
2018/0267530	12/2017	Sugaiwa et al.	N/A	N/A
2018/0270230	12/2017	Schmidt et al.	N/A	N/A
2018/0286152	12/2017	Iwaasa	N/A	N/A
2018/0287815	12/2017	Yamamoto et al.	N/A	N/A
2018/0293809	12/2017	James et al.	N/A	N/A
2018/0329545	12/2017	Li et al.	N/A	N/A
2018/0357561	12/2017	Selvarajan et al.	N/A	N/A
2018/0367525	12/2017	Kassimis et al.	N/A	N/A
2019/0007794	12/2018	Thakur et al.	N/A	N/A
2019/0010881	12/2018	Baria	N/A	F02B 37/24
2019/0020985	12/2018	Dai et al.	N/A	N/A
2019/0028864	12/2018	Liang et al.	N/A	N/A
2019/0068407	12/2018	Haga et al.	N/A	N/A
2019/0079842	12/2018	Chae et al.	N/A	N/A
2019/0095650	12/2018	Midgley	N/A	N/A
2019/0097932	12/2018	Buczek	N/A	B60W 50/023
2019/0098472	12/2018	Yoshihara	N/A	N/A
2019/0108049	12/2018	Singh et al.	N/A	N/A
2019/0123908	12/2018	Morita et al.	N/A	N/A
2019/0124423	12/2018	Stamatakis et al.	N/A	N/A
2019/0129778	12/2018	Olson et al.	N/A	N/A
2019/0141133	12/2018	Rajan et al.	N/A	N/A
2019/0141142	12/2018	Filippou et al.	N/A	N/A
2019/0161104	12/2018	Betis et al.	N/A	N/A
2019/0166054	12/2018	Grant et al.	N/A	N/A
2019/0179304	12/2018	Iagnemma	N/A	N/A
2019/0188651	12/2018	Penilla et al.	N/A	N/A
2019/0207862	12/2018	Kajio et al.	N/A	N/A
2019/0215185	12/2018	Hellenthal	N/A	N/A
2019/0217777	12/2018	John Naum Vangelov et al.	N/A	N/A
2019/0256049	12/2018	Jawany	N/A	B60R 25/01
2019/0258252	12/2018	Muta	N/A	G05D 1/0223

2019/0260800	12/2018	Shalev et al.	N/A	N/A
2019/0268743	12/2018	Cho et al.	N/A	N/A
2019/0287080	12/2018	Penilla et al.	N/A	N/A
2019/0320328	12/2018	Magzimof et al.	N/A	N/A
2019/0334763	12/2018	Cawse	N/A	H04L 43/0817
2019/0349071	12/2018	Saxena	N/A	G08G 5/26
2019/0356574	12/2018	Schoch	N/A	N/A
2019/0379683	12/2018	Overby et al.	N/A	N/A
2019/0394089	12/2018	Barrett	N/A	G06F 8/75
2019/0394305	12/2018	Kim et al.	N/A	N/A
2020/0036717	12/2019	Akella et al.	N/A	N/A
2020/0041997	12/2019	Tuukkanen et al.	N/A	N/A
2020/0053577	12/2019	Sundar	N/A	N/A
2020/0057630	12/2019	Cho et al.	N/A	N/A
2020/0090504	12/2019	Kadar et al.	N/A	N/A
2020/0110401	12/2019	Cella et al.	N/A	N/A
2020/0145252	12/2019	Torisaki et al.	N/A	N/A
2020/0160633	12/2019	Zhang	N/A	B60R 25/102
2020/0164882	12/2019	Beiderbeck et al.	N/A	N/A
2020/0167839	12/2019	Botea	N/A	B62D 15/0285
2020/0186449	12/2019	Tofighbakhsh et al.	N/A	N/A
2020/0186898	12/2019	Fischer et al.	N/A	N/A
2020/0192603	12/2019	Tanriover et al.	N/A	N/A
2020/0208998	12/2019	Xiang et al.	N/A	N/A
2020/0209002	12/2019	Hou	N/A	G06N 20/00
2020/0210336	12/2019	Bräutigam et al.	N/A	N/A
2020/0218531	12/2019	Kushwaha et al.	N/A	N/A
2020/0252339	12/2019	McKeefery et al.	N/A	N/A
2020/0257317	12/2019	Musk et al.	N/A	N/A
2020/0259919	12/2019	Lepp	N/A	H04W 4/44
2020/0264632	12/2019	Sugimoto	N/A	G05D 1/0276
2020/0267080	12/2019	Joshi et al.	N/A	N/A
2020/0274927	12/2019	Richmond et al.	N/A	N/A
2020/0284912	12/2019	Bush et al.	N/A	N/A
2020/0286477	12/2019	Jaygarl et al.	N/A	N/A
2020/0296139	12/2019	Fainberg	N/A	H04L 63/205
2020/0341956	12/2019	Bayer et al.	N/A	N/A
2020/0342691	12/2019	Saers et al.	N/A	N/A
2020/0344090	12/2019	Park	N/A	N/A
2020/0346628	12/2019	Whitfield, Jr.	N/A	B60T 7/22
2020/0361487	12/2019	Sakamoto	N/A	G05B 9/02
2020/0371774	12/2019	Kato	N/A	G06F 8/65
2020/0374221	12/2019	Tandon	N/A	H04L 45/54
2020/0389469	12/2019	Litichever et al.	N/A	N/A

2020/0406910	12/2019	Ruan et al.	N/A	N/A
2020/0409368	12/2019	Caldwell	N/A	G05D 1/0044
2020/0413408	12/2019	Bailey et al.	N/A	N/A
2021/0004486	12/2020	Adams et al.	N/A	N/A
2021/0021497	12/2020	Brinkman et al.	N/A	N/A
2021/0024035	12/2020	Nakashima et al.	N/A	N/A
2021/0026617	12/2020	Maru et al.	N/A	N/A
2021/0070321	12/2020	Serizawa	N/A	G07C 5/0808
2021/0075800	12/2020	Paraskevas	N/A	H04L 63/1441
2021/0092018	12/2020	Fang et al.	N/A	N/A
2021/0092019	12/2020	Fang et al.	N/A	N/A
2021/0116256	12/2020	Konrardy et al.	N/A	N/A
2021/0144068	12/2020	Mo et al.	N/A	N/A
2021/0152639	12/2020	Madden	N/A	N/A
2021/0155267	12/2020	Goto	N/A	B60W 30/165
2021/0155269	12/2020	Oba	N/A	G08G 1/096775
2021/0158688	12/2020	Lau et al.	N/A	N/A
2021/0171042	12/2020	Hayakawa	N/A	G08G 1/167
2021/0173911	12/2020	Ohashi	N/A	G06F 21/32
2021/0192867	12/2020	Fang et al.	N/A	N/A
2021/0197831	12/2020	Choi et al.	N/A	N/A
2021/0209519	12/2020	Baskin	N/A	G06Q 50/40
2021/0232687	12/2020	Sasaki et al.	N/A	N/A
2021/0234760	12/2020	Fang et al.	N/A	N/A
2021/0234761	12/2020	Fang et al.	N/A	N/A
2021/0234762	12/2020	Fang et al.	N/A	N/A
2021/0234763	12/2020	Fang	N/A	H04L 41/28
2021/0234767	12/2020	Ricci et al.	N/A	N/A
2021/0241548	12/2020	Maurer	N/A	N/A
2021/0258189	12/2020	Toyoda	N/A	H04L 12/40202
2021/0264693	12/2020	Rueck et al.	N/A	N/A
2021/0300259	12/2020	Shibata et al.	N/A	N/A
2021/0300393	12/2020	Nielsen et al.	N/A	N/A
2021/0310217	12/2020	Akiyama	N/A	E02F 9/2054
2021/0341935	12/2020	Du	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0383209	12/2020	Brahma et al.	N/A	N/A
2021/0387640	12/2020	Tamori	N/A	G16H 50/30
2021/0407220	12/2020	Fang	N/A	G07C 5/008
2021/0410134	12/2020	Cheraghi	N/A	H04W 72/0453
2022/0046460	12/2021	Samuel et al.	N/A	N/A
2022/0070063	12/2021	Fang et al.	N/A	N/A
2022/0078084	12/2021	Fang et al.	N/A	N/A

2022/0118924	12/2021	Wortberg	N/A	B60R 16/03
2022/0131751	12/2021	Fang et al.	N/A	N/A
2022/0131752	12/2021	Fang et al.	N/A	N/A
2022/0131753	12/2021	Fang et al.	N/A	N/A
2022/0131754	12/2021	Fang	N/A	H04L 41/28
2022/0131755	12/2021	Fang et al.	N/A	N/A
2022/0158974	12/2021	Wang	N/A	H04L 63/104
2022/0173969	12/2021	Fang	N/A	G07C 5/008
2022/0173970	12/2021	Fang et al.	N/A	N/A
2022/0173971	12/2021	Fang et al.	N/A	N/A
2022/0173972	12/2021	Fang et al.	N/A	N/A
2022/0217074	12/2021	Akhavain Mohammadi	N/A	H04L 45/64
2022/0231917	12/2021	Fang et al.	N/A	N/A
2022/0271971	12/2021	Newald et al.	N/A	N/A
2022/0297635	12/2021	Fang et al.	N/A	N/A
2022/0303194	12/2021	Palaos et al.	N/A	N/A
2023/0043675	12/2022	Liu et al.	N/A	N/A
2023/0060890	12/2022	Agahi et al.	N/A	N/A
2023/0109635	12/2022	Palermo et al.	N/A	N/A
2023/0150523	12/2022	Fang et al.	N/A	N/A
2023/0154244	12/2022	Fang et al.	N/A	N/A
2023/0154245	12/2022	Fang et al.	N/A	N/A
2023/0154246	12/2022	Fang et al.	N/A	N/A
2023/0156748	12/2022	Li	370/329	H04W 4/08
2023/0158974	12/2022	Fang et al.	N/A	N/A
2023/0158975	12/2022	Fang et al.	N/A	N/A
2023/0161583	12/2022	Fang et al.	N/A	N/A
2023/0298398	12/2022	Fang et al.	N/A	N/A
2023/0298399	12/2022	Fang et al.	N/A	N/A
2023/0298400	12/2022	Fang et al.	N/A	N/A
2023/0298401	12/2022	Fang et al.	N/A	N/A
2023/0298402	12/2022	Fang et al.	N/A	N/A
2023/0298403	12/2022	Fang et al.	N/A	N/A
2023/0298404	12/2022	Fang et al.	N/A	N/A
2023/0298405	12/2022	Fang et al.	N/A	N/A
2023/0298406	12/2022	Fang et al.	N/A	N/A
2023/0306796	12/2022	Tsuchiya et al.	N/A	N/A
2023/0316817	12/2022	Fang et al.	N/A	N/A
2023/0353446	12/2022	Ichimaru	N/A	H04L 43/08
2023/0360448	12/2022	Fang et al.	N/A	N/A
2023/0396634	12/2022	Fang et al.	N/A	N/A
2024/0022524	12/2023	Bibernell et al.	N/A	N/A
2024/0031439	12/2023	Chevalier et al.	N/A	N/A
2024/0073093	12/2023	Fang	N/A	H04L 43/0876
2024/0098592	12/2023	Janneteau et al.	N/A	N/A
2024/0154867	12/2023	Fang et al.	N/A	N/A
2024/0154868	12/2023	Fang et al.	N/A	N/A

2024/0154869	12/2023	Fang et al.	N/A	N/A
2024/0163172	12/2023	Fang et al.	N/A	N/A
2024/0163173	12/2023	Fang et al.	N/A	N/A
2024/0163174	12/2023	Fang et al.	N/A	N/A
2024/0179063	12/2023	Fang et al.	N/A	N/A
2024/0214271	12/2023	Fang et al.	N/A	N/A
2024/0326742	12/2023	Fang et al.	N/A	N/A
2024/0326744	12/2023	Fang et al.	N/A	N/A
2024/0336224	12/2023	Fang et al.	N/A	N/A
2025/0023786	12/2024	Fang et al.	N/A	N/A
2025/0030599	12/2024	Fang et al.	N/A	N/A
2025/0030600	12/2024	Fang et al.	N/A	N/A
2025/0030601	12/2024	Fang et al.	N/A	N/A
2025/0030602	12/2024	Fang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101379757	12/2008	CN	N/A
103019167	12/2012	CN	N/A
103685000	12/2013	CN	N/A
106961437	12/2016	CN	N/A
107395497	12/2016	CN	N/A
107409079	12/2016	CN	N/A
107819736	12/2017	CN	N/A
107925594	12/2017	CN	N/A
108900400	12/2017	CN	N/A
208401892	12/2018	CN	N/A
111835627	12/2019	CN	N/A
118945009	12/2023	CN	N/A
118945010	12/2023	CN	N/A
102006023137	12/2006	DE	N/A
1571788	12/2004	EP	N/A
1627778	12/2005	EP	N/A
2959654	12/2014	EP	N/A
3572939	12/2018	EP	N/A
2004173179	12/2003	JP	N/A
2004179772	12/2003	JP	N/A
2009194733	12/2008	JP	N/A
2009223460	12/2008	JP	N/A
2010519638	12/2009	JP	N/A
2012101788	12/2011	JP	N/A
2018182430	12/2017	JP	N/A
20010027471	12/2000	KR	N/A
100310412	12/2000	KR	N/A
20060029191	12/2005	KR	N/A
101470206	12/2013	KR	N/A
2001026332	12/2000	WO	N/A
WO-2007050406	12/2006	WO	B60T 7/22
2011055425	12/2010	WO	N/A

2020039295	12/2019	WO	N/A
2020100584	12/2019	WO	N/A
2020150872	12/2019	WO	N/A
2021055952	12/2020	WO	N/A
WO-2021055955	12/2020	WO	G07C 5/008
2021178979	12/2020	WO	N/A
2021178979	12/2020	WO	N/A
2022218554	12/2021	WO	N/A
2022256742	12/2021	WO	N/A
2023059938	12/2022	WO	N/A
2024054664	12/2023	WO	N/A
2024238789	12/2023	WO	N/A
2024243560	12/2023	WO	N/A
2024238789	12/2024	WO	N/A

OTHER PUBLICATIONS

“Automotive testing and Engineering services”, 2022, 20 pages. cited by applicant

202080080424.7, , “Chinese Application No. 202080080424.7, First Office Action and Search Report mailed Oct. 12, 2023”, Sonatus, Inc., 11 pages. cited by applicant

202217011087, , “Indian Application Serial No. 202217011087 First Examination Report, mailed Jan. 12, 2024”, Sonatus, Inc., 6 pages. cited by applicant

202217011256, , “Indian Application Serial No. 202217011256 First Examination Report, mailed Mar. 27, 2024”, Sonatus, Inc., 6 pages. cited by applicant

20864819.6, , “European Application Serial No. 20864819.6, Extended European Search Report mailed Jun. 28, 2023”, Sonatus, Inc., 9 pages. cited by applicant

20865060.6, , “European Application Serial No. 20865060.6, Extended European Search Report mailed Jul. 10, 2023”, Sonatus, Inc., 8 pages. cited by applicant

21764127.3, , “European Application Serial No. 21764127.3, Extended European Search Report mailed Mar. 11, 2024”, Sonatus, Inc., 7 pages. cited by applicant

Chapin, Peter C. et al., “Authorization in Trust Management: Features and Foundations”, Retrieved on Dec. 2, 2020 (Dec. 2, 2020) from <<http://lemuria.cis.vtc.edu/~pchapin/papers/chapin-skalka-wang-ACMCS2008.pdf>> entire document, 48 pages. cited by applicant

Chen, Wai et al., “Ad hoc peer-to-peer network architecture for vehicle safety communications”, IEEE Communications Magazine, vol. 43, No. 4, doi: 10.1109/MCOM.2005.1421912, 2005, pp. 100-107. cited by applicant

Felser, Max et al., “Coexistence Standardization of Operation Technology and Information Technology”, Proceedings of the IEEE, IEEE. New York, US, vol. 107, No. 6., XP011725969, ISSN: 0018-9219, DOI: 10.1109/JPROC.2019.2901314 [retrieved on May 29, 2019] * the whole document *, Jun. 1, 2019, pp. 962-976. cited by applicant

Herber, Christian et al., “Real-time capable CAN to AVB ethernet gateway using frame aggregation and scheduling”, 2015 Design, Automation & Test in Europe Conference & Exhibition (Date), EDAA,, Mar. 9, 2015, pp. 61-66. cited by applicant

Ishak, Mohamad K. et al., “Vehicle Sensors Programming BAsed on Controller Area Network (CAN) Bus Using Canoe”, 2019, 4 pages. cited by applicant

Nguyen-Duy, Jonathan , “Smart Cars: A Peek Into the Future of Converged Networks”, Jan. 9, 2018, 4 pages. cited by applicant

PCT/US2020/051817, , “International Application Serial No. PCT/US2020/051817, International Preliminary Report on Patentability mailed Mar. 31, 2022”, Sonatus, Inc., 22 pages. cited by applicant

PCT/US2020/051817, , “International Application Serial No. PCT/US2020/051817, International

Search Report and Written Opinion mailed Feb. 24, 2021”, Sonatus, Inc., 23 pages. cited by applicant

PCT/US2020/051817, , “International Application Serial No. PCT/US2020/051817, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Dec. 1, 2020”, Sonatus, Inc., 2 pages. cited by applicant

PCT/US2020/051825, , “International Application Serial No. PCT/US2020/051825, International Search Report and Written Opinion mailed Jan. 13, 2021”, Sonatus, Inc., 15 pages. cited by applicant

PCT/US2021/021421, , “International Application Serial No. PCT/US2021/021421, International Preliminary Report on Patentability mailed Sep. 15, 2022”, Sonatus, Inc., 17 pages. cited by applicant

PCT/US2021/021421, , “International Application Serial No. PCT/US2021/021421, International Search Report and Written Opinion mailed Jul. 21, 2021”, Sonatus, Inc., 19 pages. cited by applicant

PCT/US2021/021421, , “International Application Serial No. PCT/US2021/021421, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed May 10, 2021”, Sonatus, Inc., 2 pages. cited by applicant

PCT/US2022/032380, , “International Application Serial No. PCT/US2022/032380, International Preliminary Report on Patentability mailed Nov. 21, 2023”, Sonatus, Inc., 13 pages. cited by applicant

PCT/US2022/032380, , “International Application Serial No. PCT/US2022/032380, International Search Report and Written Opinion mailed Sep. 8, 2022”, Sonatus, Inc., 12 pages. cited by applicant

PCT/US2022/046292, , “International Application Serial No. PCT/US2022/046292, International Preliminary Report on Patentability mailed Apr. 18, 2024”, Sonatus, Inc., 15 pages. cited by applicant

PCT/US2022/046292, , “International Application Serial No. PCT/US2022/046292, International Search Report and Written Opinion mailed Mar. 7, 2023”, Sonatus, Inc., 18 pages. cited by applicant

PCT/US2022/046292, , “International Application Serial No. PCT/US2022/046292, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Jan. 11, 2023”, Sonatus, Inc., 2 pages. cited by applicant

PCT/US2023/032346, , “International Application Serial No. PCT/US2023/032346, International Search Report and Written Opinion mailed Nov. 27, 2023”, Sonatus, Inc., 3 pages. cited by applicant

PCTUS2020051825, , “International Application Serial No. SONA-0007-WO, International Preliminary Report on Patentability mailed Mar. 31, 2022”, Sonatus, Inc., 16 pages. cited by applicant

Wakikawa, Ryuji et al., “Design of Vehicle Network: Mobile Gateway for MANET and NEMO Converged Communication”, Sep. 2, 2005, 2 pages. cited by applicant

Wang, Yujing et al., “Adapting a Container Infrastructure for Autonomous Vehicle Development”, Cornell University Library/ Computer Science/Software Engineering, Nov. 19, 2019, [online] [retrieved on Jun. 22, 2021 (Jun. 22, 2021)] Retrieved from the Internet <URL: <https://arxiv.org/abs/1911.01075>>, entire document,, 6 pages. cited by applicant

“European Application Serial No. 22816990.0, Extended European Search Report mailed Jan. 24, 2025”, Sonatus, Inc., 10 pages. cited by applicant

Jeong, et al., “DNS Name Autoconfiguration for Internet of Things Devices”, Jul. 8, 2019, 14 pages. cited by applicant

Jeong, et al., “DNS Name Autoconfiguration for Internet of Things Devices”, Sonatus, Inc., Jul. 8, 2019, 17 pages. cited by applicant

Lee, et al., “DNSNA: DNS Name Autoconfiguration for Internet of Things Devices”, Department of Computer Science & Engineering, Sungkyunkwan University, Republic of Korea, 7 pages. cited by applicant

“International Application Serial No. PCT/US2023/032346, International Preliminary Report on Patentability mailed Mar. 20, 2025”, Sonatus, Inc., 10 pages. cited by applicant

“International Application Serial No. PCT/US2024/029686, International Search Report and Written Opinion mailed Oct. 17, 2024”, Sonatus, Inc., 19 pages. cited by applicant

“International Application Serial No. PCT/US2024/031110, International Search Report and Written Opinion mailed Oct. 17, 2024”, PCT/US2024/031110, 14 pages. cited by applicant

“International Application Serial No. PCT/US2024/031110, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Aug. 5, 2024”, Sonatus, Inc., 2 pages. cited by applicant

“International Application Serial No. PCT/US2025/010485, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Feb. 20, 2025”, Sonatus, Inc., 3 pages. cited by applicant

Primary Examiner: Algibhah; Hamza N

Attorney, Agent or Firm: GTC Law Group PC & Affiliates

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to, and is a continuation of, U.S. patent application Ser. No. 17/833,614, U.S. Publication No. 2022-0297635, filed 6 Jun. 2022 and entitled “SYSTEM, METHOD, AND APPARATUS FOR MANAGING VEHICLE DATA COLLECTION” (SONA-0012-U01). (2) U.S. patent application Ser. No. 17/833,614 (SONA-0012-U01) claims priority to, and is a continuation-in-part of, U.S. patent application Ser. No. 17/195,589, filed 8 Mar. 2021, now U.S. Pat. No. 11,538,287 issued 27 Dec. 2022 and entitled “SYSTEM, METHOD, AND APPARATUS FOR MANAGING VEHICLE DATA COLLECTION” (SONA-0010-U01). (3) U.S. patent application Ser. No. 17/833,614 (SONA-0012-U01) claims priority to U.S. Provisional Patent Application Ser. No. 63/197,021, filed 4 Jun. 2021, and entitled “SYSTEM, METHOD, AND APPARATUS FOR VEHICLE AUTOMATION MANAGEMENT” (SONA-0011-P01). (4) U.S. patent application Ser. No. 17/195,589 (SONA-0010-U01) claims priority to U.S. Provisional Patent Application Ser. No. 62/986,444, filed Mar. 6, 2020 and entitled “SYSTEM, METHOD AND APPARATUS FOR IMPLEMENTING CONFIGURABLE DATA COLLECTION FOR A VEHICLE” (SONA-0004-P01), U.S. Provisional Patent Application Ser. No. 63/024,383, filed May 13, 2020 and entitled “SYSTEM, METHOD AND APPARATUS FOR IMPLEMENTING CONFIGURABLE DATA COLLECTION FOR A VEHICLE” (SONA-0005-P01), and U.S. Provisional Patent Application Ser. No. 63/123,531, filed Dec. 10, 2020 and entitled “SYSTEM METHOD AND APPARATUS FOR IMPLEMENTING CONFIGURABLE DATA COLLECTION FOR A VEHICLE” (SONA-0009-P01). (5) All of the above patents and patent applications are incorporated herein by reference in their entirety for all purposes.

BACKGROUND

(1) Previously known systems are available for updating vehicle operational capabilities, adjusting the operation of vehicle features, or the like. However, previously known systems suffer from a number of drawbacks. For example, previously known systems require direct vehicle access, or utilize over the air (OTA) software updates to perform these functions. However, previously known systems introduce significant risks, for example requiring a shutdown of the vehicle, updating software or firmware on the vehicle that imposes downtime and a risk that the vehicle will not be

operational (e.g., if the update is interrupted) and/or significant management expense (e.g., keeping multiple versions of software available in case an update is unsuccessful) is imposed on updates or changes. Additionally, functionality for previously known systems is limited, for example features that result in version changes to software may be limited, or require additional verification or certification before they can be implemented. Further, previously known systems require that the entity performing the update or change has full vehicle knowledge (e.g., parameter names, hardware layout of end points, controllers, memory locations, and the like) and authority (e.g., permission to access and adjust software on a controller of the vehicle). Thus, previously known systems introduce significant costs, risks, and have limited functionality.

(2) Vehicle communication networks are utilized to connect sensors, actuators, controllers, user interfaces, rider personal devices, trailers, and communication devices throughout a vehicle. Recent trends have been increasing the burden on these vehicle communication networks, with more devices being connected, more data passing between devices, lower latency requirements to meet vehicle performance, safety, and emissions requirements, and added vehicle features. Additionally, consumers expect increasing connectivity, enhanced and/or customized features for the vehicle, features to reduce driver burden, and other features that increase the burdens on vehicle communication networks. These trends are expected to continue, and to accelerate, for the foreseeable future.

(3) The evolution of vehicle capabilities drives the situation where it is desirable that a greater number of entities have access to vehicle functions (e.g., manufacturers, dealers, service providers, OEMs, bodybuilders, aftermarket feature providers, and/or individual consumers). However, a number of factors drive the situation where providing capability for vehicle function changes is becoming more expensive and higher risk. For example, regulations related to safety and/or emissions, a desire for high vehicle reliability and low failure rates, and increased complexity of the vehicle itself, with multiple networks, configurations, and numerous interacting controllers on the vehicle, all come together to increase the expense, risk, and complexity to implement new functionality on the vehicle. Further, the pace of change for a given vehicle design, including changing network types, sensors, actuators, driveline components, and the like, is increasing, which makes providing capability that reaches a broader audience, and that can reach a greater content cross-section of the vehicle even more complex, expensive, and higher risk. Additionally, a significant amount of data available on the vehicle is sensitive data, whether such data includes personally identifiable information, proprietary information, vehicle control information, or information that could be a security risk (e.g., locations of the vehicle at particular times, etc.). In sum, there is a desire to expand the base of entities that can implement functions on the vehicle and interact with the vehicle from a data or functional standpoint, while the cost and risk to do these things is increasing.

(4) The complexities and other challenges set forth preceding have synergistic effects that cause the complexity of the vehicle data environment to be even greater than the sum of the individual contributions from each challenge.

SUMMARY

(5) An example system includes a vehicle having a network including a plurality of end points; a controller, including: an automation definition circuit structured to interpret an automation description; an automation management circuit structured to provide an automated action plan in response to the automation description; and an automation execution circuit structured to provide an automation command in response to the automated action plan; and wherein an end point of the plurality of end points is responsive to the automation command to implement an automated vehicle response.

(6) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. The automation description includes at least a portion of a policy for the vehicle. The automated action plan includes at least one of: a data

description of data to be collected; an actuator response; or a trigger description. The end point of the plurality of end points includes an actuator of the vehicle. The end point of the plurality of end points includes a sensor of the vehicle. The end point of the plurality of end points includes a second controller. The second controller is configured to provide one of a selected data value or a selected actuator command value in response to the automation command. The second controller is further configured to provide a confirmation value to the controller in response to implementing the automate vehicle response. The system further including a second end point of the plurality of end points, wherein the second end point is responsive to the automation command to implement the automated vehicle response. The end point includes a sensor, and wherein the second end point includes an actuator. The system further including the vehicle having a second network having a second plurality of end points; a second end point of the second plurality of end points, wherein the second end point is responsive to the automation command to implement the automated vehicle response. The end point includes a sensor, and wherein the second end point includes an actuator. The network includes a first network type, wherein the second network includes a second network type, and wherein the first network type is distinct from the second network type. The automated vehicle response includes at least one of: selectively activating an actuator; collection of selected data; moving an actuator to a selected position; delaying the automated vehicle response for a hold period; delaying the automated vehicle response for a detected event, wherein the automated action plan includes an event detection description; or providing a notification associated with any one or more of the foregoing. The automated action plan includes an event detection description, and wherein the automation execution circuit is further structured to detect an event in response to the event detection description, and to implement the automated vehicle response further in response to the detected event. The automation description further includes a vehicle operating condition, and wherein the automation management circuit is further structured to provide the automated action plan in response to the vehicle operating condition. The automation description further includes an external operating condition, and wherein the automation management circuit is further structured to provide the automated action plan in response to the external operating condition. The automation definition circuit is further structured to receive the automation description from an external device.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is schematic diagram of an automated vehicle system according to certain embodiments of the present disclosure.
- (2) FIG. 2 is schematic diagram of an automation command system according to certain embodiments of the present disclosure.
- (3) FIG. 3 is a schematic diagram of an example automated action plan according to certain embodiments of the present disclosure.
- (4) FIG. 4 is a schematic diagram of an example automated vehicle response system according to certain embodiments of the present disclosure.
- (5) FIG. 5 is a schematic diagram of an example automation description according to certain embodiments of the present disclosure.
- (6) FIG. 6 is a schematic diagram of an example controller system according to certain embodiments of the present disclosure.
- (7) FIG. 7 is a schematic diagram of an example automation action description according to certain embodiments of the present disclosure.
- (8) FIG. 8 is a schematic diagram of an example automation trigger description according to certain embodiments of the present disclosure.

- (9) FIG. 9 is a schematic diagram of example automated vehicle responses according to certain embodiments of the present disclosure.
- (10) FIG. 10 is a schematic diagram of example automated vehicle responses according to certain embodiments of the present disclosure.
- (11) FIG. 11 is a schematic diagram of an example controller apparatus according to certain embodiments of the present disclosure.
- (12) FIG. 12 is a schematic diagram of an example task description according to certain embodiments of the present disclosure.
- (13) FIG. 13 is a schematic diagram of task descriptions according to certain embodiments of the present disclosure.
- (14) FIG. 14 is a schematic diagram of an example automation action plan according to certain embodiments of the present disclosure.
- (15) FIG. 15 is a schematic diagram of an example controller configured to provide an automation description according to certain embodiments of the present disclosure.
- (16) FIG. 16 is a schematic diagram of example authorizations according to certain embodiments of the present disclosure.
- (17) FIG. 17 is a schematic diagram of example triggered automated actions according to certain embodiments of the present disclosure.
- (18) FIG. 18 is a schematic diagram of example data storage command(s) according to certain embodiments of the present disclosure.
- (19) FIG. 19 is a schematic diagram of example data storage command(s) according to certain embodiments of the present disclosure.
- (20) FIG. 20 is a schematic diagram of an example controller configured to provide an automation description apparatus according to certain embodiments of the present disclosure.
- (21) FIG. 21 is a schematic diagram of example automation command(s) according to certain embodiments of the present disclosure.
- (22) FIG. 22 is a schematic diagram of an example controller configured to store collected data apparatus according to certain embodiments of the present disclosure.
- (23) FIG. 23 is a schematic diagram of an example automated user interface according to certain embodiments of the present disclosure.
- (24) FIG. 24 is a schematic diagram of an example recipe access interface according to certain embodiments of the present disclosure.
- (25) FIG. 25 is a schematic diagram of an example trigger workflows according to certain embodiments of the present disclosure.
- (26) FIG. 26 is a schematic diagram of an example workflows according to certain embodiments of the present disclosure.
- (27) FIG. 27 is a schematic diagram of an example workflow according to certain embodiments of the present disclosure.
- (28) FIG. 28 is a schematic diagram of an example implementation of an automated vehicle response activity according to certain embodiments of the present disclosure.
- (29) FIG. 29 is a schematic diagram of an example trigger evaluation engine according to certain embodiments of the present disclosure.
- (30) FIG. 30 is a schematic diagram of an example task execution engine according to certain embodiments of the present disclosure.
- (31) FIG. 31 is a schematic diagram of an example automated user interface according to certain embodiments of the present disclosure.
- (32) FIG. 32 is a schematic diagram of an example controller configured to provide automation continuity command(s) according to certain embodiments of the present disclosure.
- (33) FIG. 33 is a schematic diagram of example automation continuity command(s) according to certain embodiments of the present disclosure.

- (34) FIG. **34** is a schematic diagram of an example controller configured to manage a service oriented architecture according to certain embodiments of the present disclosure.
- (35) FIG. **35** is a schematic diagram of an example controller configured to manage a service oriented architecture according to certain embodiments of the present disclosure.
- (36) FIG. **36** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (37) FIG. **37** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (38) FIG. **38** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (39) FIG. **39** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (40) FIG. **40** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (41) FIG. **41** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (42) FIG. **42** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (43) FIG. **43** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (44) FIG. **44** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (45) FIG. **45** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (46) FIG. **46** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (47) FIG. **47** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (48) FIG. **48** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (49) FIG. **49** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (50) FIG. **50** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (51) FIG. **51** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (52) FIG. **52** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (53) FIG. **53** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (54) FIG. **54** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (55) FIG. **55** is a schematic flow diagram according to certain embodiments of the present disclosure.
- (56) FIG. **56** is a schematic diagram of an example automation manager according to certain embodiments of the present disclosure.

DETAILED DESCRIPTION

(57) Without limitation to any other aspect of the present disclosure, aspects of the disclosure herein reduce and/or eliminate any one or more of: a cost per entity added to a vehicle functionality interaction system, a basic learning cost for a new entity to implement an application to implement

new vehicle functionality, an adaptation cost to changing vehicle network configuration(s), a cost incurred to meet the increasing demand to support new vehicle functions, a cost to adapt to a changing regulatory environment, a cost to secure data and/or losses incurred for breaches or unauthorized use, and a cost to modify vehicle functions or features via software development and deployment. Certain embodiments and/or aspects of the disclosure herein may address one or more of the described cost parameters. Certain embodiments and/or aspects of the disclosure herein may increase one or more given cost parameters, but nevertheless be beneficial by decreasing the overall cost function for a target vehicle, vehicle type, entity, industry, etc. Certain embodiments and/or aspects of the disclosure herein may increase one or more given cost parameters, but provide other benefits such as improved functionality and improve time-to-market for a feature. In certain embodiments, improved functionality may be achieved at an increased cost, but at a lower cost than previously known systems configured to achieve a similar improved functionality.

(58) For the purposes of promoting an understanding of the principles of the disclosure, reference will now be made to the embodiments illustrated in the drawings and described in the following written specification. It is understood that no limitation to the scope of the disclosure is thereby intended. It is further understood that the present disclosure includes any alterations and modifications to the illustrated embodiments and includes further applications of the principles disclosed herein as would normally occur to one skilled in the art to which this disclosure pertains.

(59) Without limitation to any aspect of the present disclosure, the present disclosure references numerous operations that may be supported, in whole or part, by procedures, circuits, controllers, assemblies, engines, systems, or other components described in one or more of U.S. patent applications: U.S. Ser. No. 17/027,167, filed 21 Sep. 2020, entitled “SYSTEM, METHOD, AND APPARATUS TO SUPPORT MIXED NETWORK COMMUNICATIONS ON A VEHICLE (SONA-0006-U01), issued on 9 Aug. 2022 as U.S. Pat. No. 11,411,823; U.S. Ser. No. 17/027,187, filed 21 Sep. 2020, entitled “SYSTEM, METHOD, AND APPARATUS TO EXTRA VEHICLE COMMUNICATIONS CONTROL” (SONA-0007-U01), issued on 18 Jan. 2022 as U.S. Pat. No. 11,228,496; and U.S. Ser. No. 17/195,589, filed 8 Mar. 2021, entitled “SYSTEM, METHOD, AND APPARATUS FOR MANAGING VEHICLE DATA COLLECTION” (SONA-0010-U01), issued on 27 Dec. 2022 as U.S. Pat. No. 11,538,287. Each one of the foregoing applications is incorporated herein by reference in the entirety for all purposes. Example supported operations include, without limitation: operations to collect data from, provide data to, and/or provide instructions to end points on a vehicle network, regardless of the network zone, and without the requestor requiring vehicle-specific information about the end point address or network location, data configuration, communication protocol, etc.; implementation of a policy for a vehicle, for example initialization, amendment, replacement, updating, authorization, etc. for the policy; configuration of network communications between zones; configuration of collected or provided data, including for example adjusting data units, data resolution, performing up-sampling and/or down-sampling of data, and/or passing data between end points on distinct network zones; storage of collected data, including short-term, medium-term, and/or long-term storage, storage of rolling buffer data to support trigger evaluations and/or execution of trigger operations, and including treatment of aging data including prioritization, deletion, transmission, summarization, and/or compression of aging data, and including a determination of whether data is aging data; transmission of any data from off-vehicle to any end point of the vehicle, and/or from any end point of the vehicle to an off-vehicle recipient, including operations to manage transmission resources and/or prioritize data for transmission; operations to support a service oriented architecture (SOA), including controlling the publication and visibility of services, controlling the subscription to services for applications, flows, end points, or the like, and operations to support execution of a service including collecting or providing related data, commands, communications, or the like; and/or operations to support providing notifications and/or alerts to users, end points, applications, or the like. Support for any of these features, as well as any other features described throughout the

present disclosure, may include configurations such as: the inclusion, in whole or part, of one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the referenced applications with one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the present disclosure; cooperation between one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the referenced applications with one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the present disclosure; the inclusion, in whole or part, of one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the present disclosure with one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the referenced applications; and/or performing one or more operations, using one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the present disclosure to perform one or more operations described in a procedure and/or performable by one or more circuits, controllers, processors, engines, apparatus, and/or computing devices of the referenced applications.

(60) Embodiments herein reference a recipe, workflow, automation description, automated action plan, automation trigger description, automation trigger plan, rules, task description, task action plan, or the like. Such terminology is utilized for clarity of the description to set forth automated vehicle operations to be performed, where the automated vehicle operations may exist in more than one location for a given embodiment, to illustrate the context of the automated vehicle operations description at various stages and/or locations in the embodiments herein. For example, a requestor of the automated vehicle operations may work with and/or request the automated vehicle operations on an automated user interface, by exercising an API, or the like, where the description of the automated vehicle operations may be simplified (e.g., using industry standard names, descriptive names for parameters, graphical depictions of operations and/or workflows, etc.), vehicle agnostic (e.g., configured without knowledge of the vehicle specific parameter names, end point locations, end point addresses, distribution of parameters on controllers and/or networks of the vehicle, etc.). In another example, a cloud application or circuit and/or a vehicle side application or circuit may adjust the description of the automated vehicle operations, for example converting the description into a data file, as a part of a policy, as a separate policy, or the like, for communication to the vehicle or as an intra-vehicle communication to an implementer of the automated vehicle operations. The example description of the automated vehicle operations utilized by the communicator of the data file, policy, plan, or the like may be distinct from the version of the description submitted by the requestor, for example configured such that the desired operations according to the automated vehicle operations can be identified and performed as desired. In another example, an implementing component, such as a vehicle controller, a circuit on the vehicle, and/or a distributed group of these, may have yet another version of the description, for example allowing the implementing component to provide specific actuator commands that can be utilized by the actuator to perform the desired operations. A recipe, workflow, automation description, automated action plan, automation trigger description, automation trigger plan, rules, task description, task action plan, or the like may be distinct elements for a particular embodiments, and one or more of these may be the same for a particular embodiment, for example depending upon where the automated vehicle operations are requested (e.g., by a cloud-connected device and/or by a direct vehicle-connected device), and/or the implementing circuit(s) for communication of the operations to the vehicle, and/or for implementing the operations on the vehicle (e.g., whether translation from an agnostic description to a vehicle description occurs on the vehicle, in the cloud, in another location such as a tool, and/or a combination of these). In certain embodiments, recipes, workflows, descriptions, plans, rules, or the like may be encrypted, for example during transmission and/or while stored (e.g., preventing access to memory from accessing an unencrypted version). In certain embodiments, the recipes, workflows, descriptions, plans, rules, or the like may be decrypted just before utilization, for example before parsing, processing for conversion to the

next stage (e.g., converting and automation description to an automated action plan), execution (e.g., of a workflow on the vehicle), and/or checks (e.g., authorization, operational capability, etc.). (61) The present disclosure describes systems, method, and apparatuses to perform automated vehicle operations, including, without limitation to any other aspect of the present disclosure, operations to manipulate (e.g., move to a selected position, limit a range of available positions, enable or disable actuation, etc.) any actuator on the vehicle, operations to manipulate (e.g., enable or disable, adjust calibrations or other behaviors of the feature, and/or to create or eliminate features in certain instances) any feature on the vehicle, to have the vehicle perform selected functions, to collect data (e.g., data related to any actuator, sensor, fault condition, vehicle function, application, flow, or the like, and/or to collect data for utilization at a later time, whether on the vehicle or off the vehicle—for example operations to confirm or verify an aspect of the vehicle and/or another aspect of an automated vehicle operation, to support fault detection or state determination for the vehicle and/or for a group of related vehicles, etc.), operations to respond to a vehicle condition (e.g., a fault code, off-nominal operation or data value, an operator complaint or description of vehicle behavior, or the like; where the responsive operations may include responses such as: modifications to vehicle behavior to correct or mitigate the condition, operations to confirm, verify, and/or repeat the vehicle condition or behavior, and/or operations to determine conditions relevant to the vehicle condition or behavior, such as related conditions, triggering conditions, resulting conditions, etc.); operations to modify vehicle behavior (e.g., vehicle operations, data collection, actuator or feature parameters, etc.) based on selected conditions (e.g., selected trigger conditions; and/or operating parameters such as vehicle location, operator characteristics, duty cycle, etc.). In certain embodiments, performance of automated vehicle operations, including the addition of vehicle features, can be performed without modification to base software for the vehicle—for example control software for the vehicle, for example by providing an interface where parameters in a data structure (e.g., a policy, an automation recipe, an automation action description, a task description, or the like) can be implemented to effect the automated vehicle operations without changes to the base software of the vehicle.

(62) An example embodiment allows for the building of a feature for operation on the vehicle, either for a selected time period, to be executed a selected number of times (e.g., a single time, multiple times, periodically, etc.), to be executed until it is later removed (e.g., by the creator of the feature), or the like. A feature includes any selected operation or operational behavior of the vehicle performed or adjusted in response to any selected condition (e.g., vehicle operating condition, operator input, external condition, etc.), and may include a feature that might typically be on the vehicle (e.g., cruise control, windshield wiper delay, automatic seat positioning, etc.) or a feature that is created by a user for any purpose, such as service operations, manufacturer operations, operator convenience, operator preference, or the like.

(63) An example embodiment allows for the modification of a feature on the vehicle, whether the feature is a pre-existing feature, or a feature created by an embodiment of the present disclosure. Modifications to a feature may include any one or more of: adjusting calibrations of the feature (e.g., which may include providing values utilized to override calibrations, with or without adjusting the actual calibrations on the vehicle); changing initiating conditions for a feature; changing enabling conditions for a feature; changing responses of the feature to vehicle operating conditions and/or to external conditions (e.g., time of day, weather, traffic, location, etc.); adjusting a range of the feature (e.g., allowed settings, speed ranges, response times, etc.); applying or adjusting a limit related to the feature, etc.

(64) An example embodiment allows for automation of a number of operations, for example to perform a test on the vehicle without requiring dedicated tools (e.g., a service tool, manufacturing tool, or engineering tool). A test, as utilized herein, should be understood broadly, and may include operations to perform one or more of: observation of vehicle behavior, driver behavior, and/or a feature on the vehicle, which may include observing one or more of these based on specific

conditions; exercising of one or more vehicle actuators, features, flows, applications, or the like; observation of vehicle behavior, driver behavior, and/or a feature on the vehicle, for example in response to the exercised aspects; confirmation of the behavior (e.g., collecting relevant data, repeating as needed based on the confidence level that the observed behavior is due to the exercising, etc.); and reporting (e.g., communicating parameters relevant to the test, including for example result values, confidence values, related data, or the like).

(65) An example embodiment allows for automation of operations to respond to an off-nominal condition, such as an operation to respond to a detected intrusion event (e.g., where it is determined that an improper actor may be attempting to collect data, provide improper data, introduce disruptive information such as through a denial of service attack, and/or modify data improperly such as trying to perform an unauthorized control operation of the vehicle). Example operations to respond to a detected intrusion event include, without limitation, performing operations to reconfigure the network (e.g., listing requestors, addresses, or the like that should be blocked or ignored), reporting data related to the detected intrusion event (e.g., identifiers of an intrusion source; operational parameters related to the intrusion, such as attempt frequency, targets such as data, end points, control parameters, etc.; authorization data utilized during the intrusion event; and/or values utilized by the intrusion, such as communication headers, communication payloads, etc.). In certain embodiments, operations to respond to a detected intrusion event can mitigate the intrusion attempt, prevent the intrusion attempt, be utilized to detect later intrusion attempts on the vehicle or other vehicles, and/or capture data relevant to the intrusion attempt (e.g., to mitigate further damage, to identify a perpetrator, and/or to prove aspects related to the intrusion attempt).

(66) An example embodiment allows for automation of operations to provide additional information to a user, and/or to adjust vehicle operations based on a user preference and/or user characteristic. For example, a vehicle owner that is a parent may set up a feature using embodiments of the present disclosure to provide information about another driver (e.g., their child), for example determining significant operational events such as vehicle speed values, time of day of operation, location of operation, significant acceleration events, or the like. Such information may be utilized to monitor the other driver, and/or to assist the other driver (e.g., contacting the parent when the vehicle is in a location unlikely to be consistent with normal operation, such as stopped for an extended period on a highway). In certain embodiments, automation of operations may additionally or alternatively include adjustment of the vehicle features based on the driver, for example the parent operator may set up various vehicle features (e.g., maximum speed, power rating, light configurations such as daytime headlight usage, etc.) that can assist a child driver in safe operation of the vehicle. In certain embodiments, data may be provided to the parent directly (e.g., acceleration events provided in a reporting message), and/or may be stored for selective access. The examples utilize a parent-child relationship between a primary vehicle operator and a secondary vehicle operator as a non-limiting example, but any other primary/secondary relationship is understood herein, including in a situation such as: a fleet of vehicles, vehicles used for employment, a stolen vehicle (e.g., taking certain operations in response to a vehicle theft, which may include allowing some level of vehicle operation, for example to allow the vehicle to be moved to a safe location), a loaned vehicle, a rental vehicle, etc.

(67) The description herein utilizing off-vehicle, extra-vehicle, and/or cloud-based interactions references any external network communications of the vehicle, including without limitation wireless-based communications (e.g., mobile data, WiFi, and/or Bluetooth) to external devices. Communications to external devices may be to a general network (e.g., over the internet), a WAN, a LAN, a mobile device in proximity to the vehicle, and/or combinations of these. Certain systems and procedures described herein particularly contemplate run-time operations of the vehicle, for example external communications occurring during operating conditions wherein the vehicle is executing a mission (e.g., moving, performing operations while not moving, etc.). The disclosure herein further contemplates communications that may occur during any period, including during

down-time of the vehicle and/or during service events. The disclosure herein further contemplates communications that may occur through wired communication channels, such as when the vehicle network is in communication with a service tool, on-board diagnostics (OBD) instrument, or other physically coupled device.

(68) The description herein references vehicle applications as a non-limiting example and for clarity of the present description. However, embodiments herein are applicable to other applications having similar challenges and/or implementations. Without limitation to any other application, embodiments herein are applicable to any application having multiple end points, including multiple data sources, controllers, sensors, and/or actuators, and which may further include end points present in distinct or distributed network environments, and/or applications having historical or legacy networking or communication systems that may be transitioning (within a given system, as a class of systems, and/or as an industry) to newer and/or more capable networking or communication systems. Example and non-limiting embodiments include one or more of: industrial equipment; robotic systems (including at least mobile robots, autonomous vehicle systems, and/or industrial robots); mobile applications (that may be considered “vehicles”, or not) and/or manufacturing systems. It will be understood that certain features, aspects, and/or benefits of the present disclosure are applicable to any one or more of these applications, not applicable to others of these applications, and the applicability of certain features, aspects, and/or benefits of the present disclosure may vary depending upon the operating conditions, constraints, cost parameters (e.g., operating cost, integration cost, operating cost, data communication and/or storage costs, service costs and/or downtime costs, etc.) of the particular application. Accordingly, wherever the present disclosure references a vehicle, a vehicle system, a mobile application, industrial equipment, robotic system, and/or manufacturing systems, each one of these are also contemplated herein, and may be applicable in certain embodiments, or not applicable in certain other embodiments, as will be understood to one of skill in the art having the benefit of the present disclosure.

(69) A flow, as utilized herein, should be understood broadly. An example flow includes a related group of data (e.g., speed data, temperature data, audio-visual data, navigation data, etc.), a related group of functions (e.g., among vehicle functions, extra-vehicle functions such as service operations and/or data collection, aggregations between related vehicles, and/or combinations of these that are related for a particular system), a related group of devices (e.g., door actuators), and/or a related group of applications. Flows, as used herein, provide an organizing concept that may be utilized to relate certain data, certain end points, certain applications, and/or related functions of the vehicle or apart from the vehicle. In certain embodiments, a controller can utilize a flow to identify a data source, a data destination, permissions available for the flow, priority information related to the flow, or the like, to implement certain data regulating operations here. In certain embodiments, the controller can utilize a flow to identify a data intrusion attempt, for example by determining that a flow is providing unexpected information or operational requests, by determining that information or operational requests are coming from an unexpected location, and/or according to the frequency and/or values of information or operational requests relative to historical parameters, expected parameters, and/or pre-determined limits. In certain embodiments, the utilization of the flow allows the controller to perform separate operations that may involve the same end points to support the desired network management. For example, a vehicle speed management application may have a high priority, and a speedometer end point may be associated with the vehicle speed management application. In the example, if the vehicle speed is being communicated to support the vehicle speed management application, then the controller applies a high priority to the vehicle speed message. However, if the vehicle speed is being communicated to support a trip planning flow (e.g., where a trip planning flow is present and does not have a high priority), the controller may apply a lower priority to the vehicle speed message. In a further example, a failure of a vehicle controller, portion of a network, or other off-nominal condition may

result in the migration of the vehicle speed management application to another controller in the system, whereby the vehicle speed message is being communicated (e.g., where the backup controller is on another network) to support the vehicle speed management application, and the controller may apply a higher priority to the vehicle speed message. The utilization of flows and applications to organize the components of the system allows for the same or similar information to be regulated by the controller in a differential manner to support various functions, allowing for improvements in the performance and security of network regulation operations (e.g., reducing unnecessary cross-network traffic, and providing information only as needed), and supports additional functionality relative to previously known systems, such as redundancy support, distributed control, and granular cross-network messaging.

(70) Embodiments of the present disclosure provide for systems, apparatuses, and methods for operating and/or managing vehicle automation features and/or functions. Embodiments herein allow for the addition, deployment, configuration, and/or updating of vehicle automation features and/or functions without coding (e.g., algorithm development, compiling, and/or updating of computer readable instructions, operating system changes, and/or firmware updates). Embodiments herein allow for the addition, deployment, configuration, and/or updating of vehicle automation features utilizing an index of automation recipes, interactions with an operator, and/or interactions with an application that further interfaces with an operator, owner, service personnel, manufacturer, fleet personnel, and/or OEM. Embodiments herein support management, initiation, and/or updating of flexible triggers for vehicle automation features and/or functions, and/or execution of vehicle automation features and/or functions.

(71) Embodiments of the present disclosure provide for systems, apparatuses, and methods for managing and/or operating vehicle remote control enhancements. Embodiments herein allow for reduced latency and/or no latency vehicle-external network communications, for example utilizing low power persistent vehicle-cloud communications. Embodiments herein allow for extensive control functions for customer support, customer service, business analysis, manufacturer/OEM application differentiation, consumer applications, customized features, and/or aftermarket features. Embodiments herein allow for implementation of remote control enhancements utilizing programmable complex control procedures, with high capability for secure access to vehicle networks, devices, end points, and/or flows, and for access to ancillary aspects to allow for implementation of high capability features (e.g., determining supporting vehicle states, conditions, etc., and/or capabilities to ensure mission functions are not inhibited).

(72) Embodiments of the present disclosure provide for systems, apparatuses, and methods for management and/or operation of shared network storage for a mobile application having a number of data storage devices associated therewith, and/or may further include where the number of data storage devices are distributed across at least two networks and/or across networks of a mixed network for the mobile application. Embodiments include a unified storage shared by multiple applications, flows, processors, circuits, end points, devices, services, and the like. Embodiments herein provide for network file system access to end points, devices, applications, and/or flows on the networks of the mobile application. Embodiments herein provide for an overlaid database service for shared stored data, and/or portions thereof. Embodiments herein provide for selected encryption schemes for shared stored data, including at least encryption of data at rest. Embodiments herein provide for authentication, access control, and auditing of shared network storage operations, including at least scheduled operations according to a policy, permissions of participating devices, etc. Embodiments herein provide for data life cycle management of shared stored data, including at least: implementation of policies; data retention schemes; and/or prioritization between devices, end points, applications, flows, related services, data types, and/or determined operating conditions of the mobile application.

(73) Implementations of the present disclosure are provided as a service oriented architecture (SOA), faster development, code reuse, reduced complexity, and easier deployment. OEMs benefit

from reduced development costs, improved time-to-market, reduced warranty expenses, and recall expenses. Customer benefits include vehicles with more capabilities, feature upgrades after purchase, and less inconveniences due to work associated with warranties and/or recalls. A SOA, as used herein, includes operations for devices, end points, applications, and/or flows to publish (e.g., a service provider) the availability of a service (e.g., data values, actuator operations, and/or functions available), and to subscribe (e.g., a service requestor) or otherwise request an available service. Services may be selectively published (e.g., only to subscribers having sufficient permissions, and/or only by providers having sufficient permissions). Services may have distinct permissions on both the publication and request side, for example with owners, manufacturers, OEMs, body builders, fleet operators, third-party applications, etc. having distinct permissions to publish and/or request services. Service providers and/or requestors may be on-vehicle or off-vehicle.

(74) Examples of the present disclosure provide for the ability to provide frequent feature upgrades, addition or removal of features, and a personalized configuration of features for a mobile application. An example embodiment enables customized vehicle behavior by providing a simple, flexible, automation capability. An example embodiment includes an interface and integration tools allowing developers and users to quickly and easily create custom workflows that manipulate vehicle features based on user input and vehicle state.

(75) Example embodiments allow users to create custom trigger-action rules to automate the vehicle environment, and to allow in-vehicle capabilities that were not previously available. For example, embodiments herein include customer control of cabin temperature, lighting, infotainment, seats, windows, sunroof, cabriolet top, driving mode, and/or adjustment of any other actuator or vehicle interface in response to voice commands, smart phone inputs, buttons in the vehicle, and/or detected vehicle operating conditions or events.

(76) Example operations are described following to illustrate a few operations of a type supportable by embodiments of the present disclosure. The example operations are non-limiting, and an example automation manager is capable to respond to any input capable of being provided as a network communication and/or data parameter stored on a computer readable medium, and to provide any response capable of being commanded to any actuator in the system, including actuators under the control of another controller in the system (e.g., a vehicle display, system speakers, vehicle powertrain, etc.).

(77) An example customized operation includes an operation to set the passenger's seat heating in response to a driver tapping a driver's seat heating switch twice and setting the passenger's seat heating. The example operation returns the driver's seat heating switch to control of the driver's side heating after a brief delay (e.g., a few seconds). The example operation allows the driver to conveniently set the passenger seat heating from the driver's side of the vehicle.

(78) An example customized operation includes an operation to configure a number of vehicle aspects in response to a command, such as "Hey car, start my morning commute." In the example, configured vehicle aspects may include tuning the radio to a selected station and volume, setting a pre-selected navigation destination (e.g., an office), setting the performance mode of the vehicle (e.g., fuel economy mode), setting the driver's seat position (e.g., forward/reverse, height, tilt, lumbar support, etc.), and/or setting HVAC parameters (e.g., selected cabin temperature). In certain embodiments, a customized operation may include further interactions based on ambient or external conditions, such as utilizing a different radio station depending upon the day of the week, adjusting HVAC settings based on ambient temperature, adjusting navigation according to a number of people in the vehicle, and the like.

(79) An example customized operation includes an operation to configure a number of vehicle aspects in response to a system condition, such as an approach of the vehicle to the driver's home at night. In the example, the customized operation implements a workflow that dims the headlights, lowers the radio volume, sends a message to a home automation system to turn on lights and open

the garage door, and retracts the side mirrors as the car pulls into the garage. In certain embodiments, the approach of the vehicle to the driver's home at night may be determined by any operations, such as determining from GPS coordinates, direct interaction with a network of the home automation system, etc.

(80) An example customized operation includes an operation to configure a number of vehicle aspects in response to an input, such as a hard coded button on a vehicle display. An example includes setting an HVAC system of the vehicle to a desired temperature in response to the hard coded button, without having to navigate a climate control system, utilize multiple button presses, and/or turn related knobs where visibility may be lacking (e.g., the vehicle is dark) and/or the driver does not want to utilize attention to find and focus on the related knobs.

(81) An example automation manager (or vehicle automation manager) allows users to create arbitrary trigger-action rules which can be executed on the vehicle, such as by the centralized controller. For instance, the user could create a trigger-action rule that would automatically turn on the high-beam headlights when there is no oncoming traffic while driving at night. An example schematic flow description of the customized operation includes: The user accesses an app on her phone or web browser and uses it to create custom trigger-action rules, or enable predefined ones created by the OEM; The trigger-action rules are sent to the cloud, and the enabled trigger-action rules are consolidated as a “recipe” on the cloud side; The cloud pushes the recipe to the vehicle through a vehicle update controller (VUC—for example embodied on an automation manager **1404**) (e.g., downloading, storing, and installing configuration information related to customized operations); When the trigger evaluation engine receives the latest recipe, it analyzes each workflow in the recipe and executes each workflow in a controlled and isolated manner;

Accounting data (such as the number of times a trigger-action rule has been executed, trigger event detections, trigger event data, and/or events where the action is taken or triggered but suppressed based on operating conditions, etc.) is sent back to the cloud, where it can be further reviewed, e.g., from the phone app and/or other monitoring application. It can be seen that the vehicle automation manager **1404** allows users to enrich their vehicle experience without waiting for a feature request, approval, and update process. The example vehicle automation manager further allows the user to leverage their own creativity and/or the creativity of 3rd party application providers to implement improved vehicle interactions. Additionally, the vehicle brand owner (e.g., manufacturer or OEM) or other supporting or responsible party can implement trigger-action rules to more rapidly and/or more frequently provide updates or features to many users, or even to specific users.

(82) An example Vehicle Automation Manager (VAM) takes recipes from the cloud as inputs and executes the trigger-action rules in the recipes. Each trigger-action rule is composed of triggers, conditions, and actions. The triggers are the inputs to the rule that encompass signals from the CAN bus, time, location, diagnostic states, vehicle status, video/audio, driving log, etc. Conditions take trigger input values and decide if certain conditions are met.

(83) The conditions are described using a custom syntax, in order to express complex logical conditions, such as multi-level AND/OR logic, comparators, and advanced utility functions to calculate sum/mean/stddev etc. If the conditions are met, then the corresponding actions will be executed, and/or requested (but may be blocked due to operating conditions, etc.). The actions could include calling services in the SOA or sending CAN signals to the CAN ECUs.

(84) Referencing FIG. 56, an example apparatus **5600** includes an automation manager **1404** is schematically depicted, and positioned on a centralized controller. In the example of FIG. 56, the automation manager **1404** receives recipes (and/or configuration information describing a customized operation) from the cloud using MQTT/HTTP/WebSocket, etc. The VAM controls the vehicle automation based on the recipes, and includes a lexical engine to parse the recipes, and a rule engine to orchestrate the rule execution by leveraging a trigger evaluation engine and a task execution engine (and/or a trigger execution engine). Operations of the automation manager such as in FIG. 56 may include vehicle automation operations, event trigger operations, remote control

operations, and/or any configurable operations performed in response to an application, feature, trigger, or other automated application created by a manufacturer, OEM, fleet owner, vehicle owner, vehicle operator, and/or a third party.

(85) An example trigger evaluation engine takes trigger data as inputs and evaluates the trigger conditions based on the trigger data values. The trigger data can come from any network, such as a CAN bus, for example using a configurable edge gateway to adjust the routing table to retrieve the signal values dynamically. In addition, the data could also come from any ECU **1406**, such as a Ethernet ECU through a SOA, from other modules on the centralized controller (e.g., Diagnostic Server), or raw sensor data such as video/RADAR/LiDAR streams over Ethernet or other types of network (for example to support an advanced driver assistance system-ADAS **1408**). The centralized controller may further share the data collection performed for customized operations with other aspects of the system, such as data collection operations for other purposes, and/or between multiple customized operations utilizing at least some of the same trigger data parameters, thereby reducing redundant requests for the same data parameters. In certain embodiments, data collection may be a separate operation that may additionally be based on a trigger condition, and/or data collection may be performed as a customized operation.

(86) In the example of FIG. **56**, the trigger manager (e.g., as the automation/remote manager in the example of FIG. **56**) manages triggers from various trigger related clients, such as vehicle automation, remote control, and/or data collection triggered flows. The example in FIG. **56** further includes a data listener that receives data related to the triggers, which may be taken from any location in the vehicle, such as: a CAN bus; Ethernet packets (including EthCC packets having state information such as vehicle location); a diagnostic manager providing DET errors, RDBI data, fault codes, etc.; a system manager (e.g., providing vehicle power state information); a time manager (e.g., providing a current time value); and/or any other information such as from the SOA. The trigger data may also be taken from any location outside of the vehicle, such as a REST API endpoint in the cloud.

(87) In the example of FIG. **56**, the data cache stores the data for condition evaluation, for example including buffered data, intermediate parameters, etc.

(88) In the example of FIG. **56**, the condition evaluation runtime is an engine to evaluate the conditions based on the trigger values in the cache, and to determine whether the trigger condition is met in response to the evaluation. The condition evaluation supports any type of analysis or determination operations, including at least: basic logical operators (e.g., AND, OR, numerical comparisons, etc.); nested logical expressions with appropriate formatting (e.g., $((X > 5 \ \&\& \ Y < 10) \parallel Z \neq 100) \ \&\& \ P < 0.05$); math functions (e.g., arithmetic, exponential, trigonometric, modular, gamma, etc.); and/or complex data transformation functions over a range of data (e.g., median; mean; standard deviation; map; reduce; min/max; bucketing; filtering; integrating; derivating; and/or frequency analysis operations).

(89) In the example of FIG. **56**, the task execution engine performs actions defined in the action catalog (e.g., the actuators to be adjusted according to the customized operation). Example and non-limiting actions include turning on a light, turning on and/or adjusting the HVAC, turning on the ignition, etc. Embodiments of the present disclosure are capable to access any actuator that is reachable through any network, including actuators provided on more than one network (e.g., an Ethernet for one actuator, and a CAN for the other actuator). In certain embodiments, actions include a request for operation of an actuator (e.g., to another controller having direct control of the actuator), actions to request a published service be performed, and/or actions having complex interactions which may further be present on more than one other controller. For example, an action includes adjusting the ambient environment for the current user, which may include interacting with multiple controllers and/or flows, for example to determine a current user identity, her preferences, and adjusting the environment such as seat position, HVAC settings, radio channels, etc. The actions may also include calling a REST API in the cloud, sending a SMS message to a

contact, etc. . . .

(90) In certain embodiments, the automation manager advertises one or more customized operations as a service (e.g., which may be selectable by the requestor of the customized operation, defined in a policy, etc.). In certain embodiments, components, circuits, controllers, and/or engines of the automation manager are shared in whole or part with other managers such as a remote control manager, and/or may be responsive to other managers using an API, library calls, or other interaction interface, for example to determine whether a specified group of data and trigger logic (e.g., passed from the other manager to the automation manager) indicates that a trigger event has occurred (e.g., determined by the condition evaluation runtime), and/or to implement an operation provided by another manager (e.g., passed as an operation request from the other manager to the automation manager) to be implemented (e.g., operated by the task execution engine to move the actuator and/or provide appropriate commands to other controllers).

(91) Implementations of the present disclosure provide for rapid development and deployment of customizable operations, automation implementation without coding and/or compilation requirements, access to customization for customers, 3rd party applications, aftermarket suppliers, etc. Implementations of the present disclosure provide for case of implementation of customizable operations even where data providers and/or actuators are distributed across more than one network type, and do not require that providers for customizable operations have knowledge of the present configuration of on vehicle networks.

(92) Examples of the present disclosure provide for the ability to perform remote control operations for a mobile application. Remote control operations for certain features may be hard-coded in the ECU software—for example simple operations such as start/stop operations of the engine, lock/unlock operations of the doors, open/close operations of the windows and/or sunroof, etc. However, adding or changing functionality after production is complete for such features requires code changes and verification, which may include re-qualification of one or more ECUs, and/or software builds on those ECUs, that participate in remote functions. Embodiments of the present disclosure are capable to configure remote control operations of a mobile application at any point in the life cycle of the vehicle, and further allow for configuration, updating, and fixing of remote operations included at the time of manufacture. Additionally or alternatively, where a more robust remote control implementation is present such as set forth in the present disclosure, features that would previously be hard-coded may be implemented as a dynamic feature as set forth herein.

(93) Example operations are described following to illustrate a few remote control operations of a type supportable by embodiments of the present disclosure. The example operations are non-limiting, and an example remote control manager is capable to respond to any input capable of being provided as a network communication and/or data parameter stored on a computer readable medium, and to provide any response capable of being commanded to any actuator in the system, including actuators under the control of another controller in the system (e.g., a vehicle display, system speakers, vehicle powertrain, etc.).

(94) An example operation includes receiving a customer configuration of a scheduled acclimatization, where remote control operations include activating the HVAC system at a scheduled time (e.g., 7 AM) on selected days (e.g., weekdays), to a selected condition (e.g., a selected temperature, and/or utilization of defrost to ensure the windows are clear). In certain embodiments, the customer may configure the operation using an application (e.g., a 3rd party application), using a cloud or web-based interface, and/or using an application provided by a manufacturer, dealer, etc. In certain embodiments, an operator selects a recipe for a remote control operation (e.g., which may include prompts to set certain parameters, and/or may be only an instruction or approval to turn a feature on or off). In certain embodiments, an operator builds a customized remote control operation, which may, for example, be based upon customized operation features present on the vehicle, available in a recipe, and/or may be built entirely by the user interacting with an interface to allow the entry of operations to be performed, any conditions to be

applied, and settings for any thresholds, etc.

(95) An example operation includes the remote control manager responding to a progressive preconditioning command to heat the cabin of the vehicle in a selected order, such as using the HVAC to get cabin air to a desired temperature, then activating a heated steering wheel and/or heated seat function.

(96) An example operation includes the remote control manager responding to a user setting request, and adjusting the vehicle configuration (e.g., steering column position, ambient light color, interior/dash light brightness, UI/UX style selection, etc.) in response to the user setting request.

(97) An example operation includes a vehicle management setting (e.g., a valet mode, borrowed vehicle mode, configured mode for a child of the parent owner when driving the vehicle, etc.), for example to reduce a vehicle speed limit, a location limit (e.g., a geofence perimeter of 500 m from an activation location, limits with defined areas such as a city limit, and/or outside of defined areas such as a state line, another city limit, a total distance from an activation location, etc.). The applied limits for the vehicle management setting may be an actual applied limit (e.g., a maximum speed, performance value, etc.) or a notification limit (e.g., typically a geographic restriction may be implemented as a notification limit rather than a shutdown limit), where a notification is sent to the owner and/or to a selected device if a limit of the vehicle management setting is exceeded (and/or tested, such as with an actual applied limit).

(98) An example operation includes a security mode, for example requesting data from a camera, microphone, vehicle display, dashboard, etc., in response to a request for the security mode. In certain embodiments, the user can select one or more devices (e.g., specific cameras and/or locations within or relative to the vehicle), and can receive streaming video and/or a snapshot from the selected device(s). In certain embodiments, the security mode allows for a data request from a device communicatively coupled to the vehicle, for example a security camera of a home security system in communication with the vehicle (e.g., see customized operations preceding).

(99) An example operation includes a personalized operation, such as playing “Happy Birthday to You” and/or manipulating cabin lights upon the driver entering the vehicle on her birthday. Additionally or alternatively, a personalized operation can be any type of operation such as: playing a selected song or play list on a given calendar date, day of the week, etc.; reminding an operator of a calendar event (e.g., linking to a calendar function of a smart phone, etc.), an anniversary, etc. upon entry to the vehicle; and/or reminding an operator of a scheduled stop (e.g., picking up groceries upon entering the vehicle to return home from work).

(100) Example and non-limiting remote control operations include performing one or more operations, such as: sending a note to the operator, showing the note on a vehicle display, and/or announcing the note on a speaker; taking a snapshot from one or more cameras and sending it to an operator and/or requestor; allowing a 3.sup.rd party service (e.g., mobile re-fueling, vehicle service, and/or delivery company) to access vehicle location and door status, but only under specified conditions (e.g., selected times of the day, until the completion of an event, and/or in response to a proximity of the 3.sup.rd party service to the vehicle); beginning start-up operations of the vehicle, a controller, the head unit, etc., as an operator approaches; reacting to environmental changes by defrosting the vehicle (e.g., in response to frost build-up, ambient temperature determination, etc.); and/or running a scheduled test for diagnostic purposes (e.g., running an active diagnostic test when the operator is away from the vehicle, reducing impact of the test on the vehicle mission).

(101) Example remote control operations include a prerequisite condition, a task, and/or a status report. The prerequisite condition includes any combination of vehicle status, CAN signals, Ethernet packets, information stored on a computer readable medium (e.g., log information, trip information, and/or other vehicle information stored in a memory location), time and/or date, location, etc. to be utilized as a prerequisite trigger condition for the remote operation, and can further be configured as a complex logical expression and may further be based on a number of conditions. The task includes an action that can be performed utilizing a CAN signal, Ethernet

packet, or other network communication, including at least any action described under customized operation preceding. The status report includes acknowledgement information, confirmation that an operation was performed and/or notification that an operation was not performed, related data, confirming data, utilization data related to the remote control operation, etc. The content of the status report may vary with the recipient and/or requestor of the status report—for example the operator may receive a simple status report confirming the operation, a service personnel may receive a more detailed status report with associated parameters related to the operation, and a manufacturer may receive a detailed status report with personally identifiable information removed (e.g., to compile reliability data, while allowing for storage and aggregation of the data without having to manage personally identifiable information). The presence and/or content of the prerequisite condition, task, and/or status report may be provided and/or updated by user input, policy, and/or configuration information.

(102) An example remote control solution supports the specification of a final vehicle state (to which the vehicle should return) after all the remote control functions are completed (e.g., an operating condition, interior cabin settings, a battery state of charge, etc.). This vehicle state can be different than the vehicle state when the request was received. It is also configurable and programmable, similar to the task.

(103) Again referencing FIG. 56, an example remote control manager is schematically depicted, being a part of a centralized controller in the example, although the remote control manager may be a distinct device, and/or positioned on another device. The interface to the CAN controller may be performed through a configurable edge gateway. In the example, the task execution engine and trigger evaluation engine is depicted as separate and dedicated to the remote control manager, solely for clarity of the present description. The task execution engine and/or trigger evaluation engine may be positioned, in whole or part, with another device or controller such as an automation manager, shared between the remote control manager and the automation manager, and/or each of the remote control manager and automation manager (where present) may have separate trigger evaluation engine(s) and/or task execution engine(s).

(104) A mission, vehicle mission, or other similar terminology as used herein should be understood broadly. A mission, as utilized herein, references any one of: a primary function; an intended function; a critical function; and/or a minimum enabling function (e.g., a function required for operations to be considered normal, and/or acceptable to allow continued operation). A mission, for example of the vehicle, may depend upon the current operating condition of the vehicle and/or an intended use of the vehicle. For example, a vehicle mission may include an ability to provide motive power and/or motive operation, and may further include a performance description such as a minimum available power, torque, and/or vehicle speed (e.g., which may be the same as, or lower than, rated values for these). In another example, a mission may be an ability to provide power and/or functionality of a system of the vehicle—such as a light, communication operations, holding operations, cabin environment operations, or the like. In certain embodiments, some level of operation of the vehicle or component may be available, where the vehicle or component is not mission capable—for example where motive operation is available, but below acceptable performance characteristics for the vehicle. In certain embodiments, a mission related aspect may not affect the performance of the vehicle but nevertheless be mission critical—for example a loss of air bag function, ABS function, or the like may not prevent operation of the mission (e.g., motive operation), but nevertheless be considered mission critical for the vehicle to continue operation in an acceptable manner. It can be seen that the mission of a vehicle, component, control operation, or the like may depend on the context of the vehicle, including design considerations, purpose of the vehicle, policies and/or preferences of an entity related to the vehicle (e.g., a fleet owner, vehicle owner, regulatory authority, etc.), geographic location of the vehicle, and/or terrain position of the vehicle (e.g., current altitude, grade, road type, etc.). A data value or other feature may be a mission critical and/or mission related data value or feature on a first vehicle but not on a

second vehicle, and/or at a first time for a given vehicle but not at a second time for the given vehicle. One of skill in the art, having the benefit of the present disclosure and information ordinarily available for a vehicle and components thereof, can readily determine whether a data value, control operation, component, or other element of the system is mission critical and/or mission related. Certain considerations to determine whether a data value, control operation, component, or other element of the system is mission critical and/or mission related include, without limitation: a rating of the vehicle, an intended use of the vehicle, a quality of service requirement associated with the vehicle, a warranty description of the vehicle or a component thereof, a duty cycle expected for the vehicle, a geographical operating region of the vehicle, a terrain operating region of the vehicle, regulatory requirements associated with the vehicle, and/or policy considerations associated with the vehicle.

(105) The methods and systems described herein may be deployed in part or in whole through a machine having a computer, computing device, processor, circuit, and/or server that executes computer readable instructions, program codes, instructions, and/or includes hardware configured to functionally execute one or more operations of the methods and systems herein. The terms computer, computing device, processor, circuit, and/or server, (“computing device”) as utilized herein, should be understood broadly.

(106) An example computing device includes a computer of any type, capable to access instructions stored in communication thereto such as upon a non-transient computer readable medium, whereupon the computer performs operations of the computing device upon executing the instructions. In certain embodiments, such instructions themselves comprise a computing device. Additionally or alternatively, a computing device may be a separate hardware device, one or more computing resources distributed across hardware devices, and/or may include such aspects as logical circuits, embedded circuits, sensors, actuators, input and/or output devices, network and/or communication resources, memory resources of any type, processing resources of any type, and/or hardware devices configured to be responsive to determined conditions to functionally execute one or more operations of systems and methods herein.

(107) Referencing FIG. 1, an example system **100** to provide, create, deploy, implement, and/or support automated vehicle response activities. An automated vehicle response activity as used herein should be understood broadly, and includes, without limitation to any other aspect of the present disclosure, operations such as: control of any actuator on the vehicle, and/or communicatively coupled to the vehicle; collection of selected data available on the vehicle, including operations to generate and/or communicate data that might otherwise not be available; providing notifications or alerts, for example in response to detected conditions, vehicle data having selected values, ranges, or thresholds, etc.; enabling or commencing monitoring operations, conditional operations, or the like; triggered embodiments of any one or more of the foregoing (e.g., determining whether a trigger is present, and responding to the presence, or lack, of the conditions detected by the trigger); scheduled embodiments of any one or more of the foregoing (e.g., where the scheduling includes commencement timing, implementation timing, data storage timing, delay periods, or the like, and where the scheduling may be applied to trigger evaluation, automated operations, notifications, alerts, data storage, data transmission, related communications, etc.); and/or implementing a workflow of any type (e.g., implementing a single action, a sequence of actions, a branched action sequence, a cyclical action sequence, a repeated action sequence, and/or an operation of a state machine).

(108) The system **100** of FIG. 1, as well as systems, apparatuses, assemblies, controllers, circuits, procedures, and/or other embodiments of the present disclosure allow for implementation of automated vehicle responses with one or more features such as: the ability to provide robust vehicle functionality and complex workflows without changing the base software, firmware, or other aspects of a vehicle controller that may otherwise require additional certification, testing, debugging, or the like; the ability to expand automated vehicle response implementation to a wider

group of people or entities, such as end consumers, vehicle owners, vehicle operators, fleet managers, dealers, service personnel, original equipment manufacturers (OEMs), vehicle assemblers/body builders, aftermarket component providers, or the like; the ability to provide robust vehicle functionality and complex workflows without requiring that the creator have vehicle specific knowledge about available data, sensors, actuators, or the like; the ability to schedule permissions and authorization to ensure that creators do not have access to data or vehicle functions that they should not; the ability to configure data for the specific creator and/or recipient of the data, for example to protect proprietary information (e.g., control algorithms, including algorithmic steps, response times, data resolution, or the like), to protect personally identifiable information (PII), etc., while expanding the available data that can be used by creators (e.g., sensitive data may be available in embodiments of the present disclosure that would not be otherwise, for example by providing the data with reduced resolution, with some dynamic information removed or changed, and/or at a changed sampling rate); and/or the ability to configure actuator or vehicle control access for the specific creator and/or beneficiary of automated vehicle responses (e.g., the vehicle operator) while expanding the available automated vehicle responses that can be used by creators (e.g., by limiting the access to the actuators/controls to specified conditions, set points, requested vs. commanded operations, or the like, according to permissions or authorizations associated with the creator and/or the beneficiary, and/or according to separate rules that protect selected vehicle functions).

(109) The example system **100** includes a vehicle **102** having a number of network zones **106**, **108**, each having a number of end points. For example, network zone **106** in the example of FIG. 1 depicts four end points on the network zone **106**, including one end point represented as a data store, and three end points on the network zone **108**. The example of FIG. 1 includes a controller **104**, depicted schematically as being in communication with each network zone **106**, **108**, and having a separate associated data store. In certain embodiments, the controller **104** may be provided as an end point of a network zone **106**, **108**, and/or the controller **104** may include a converged network device (CND)—for example to regulate and facilitate communications between network zones **106**, **108** of the vehicle, and/or communications with external devices, cloud servers, service tools, manufacturing tools, etc. The example system **100** includes a cloud server **110** having a controller **112** and separate data stores **114**, **116**, and a tool **122** having a controller **124** and data store **126**. The example tool **122** may be any type of tool, including for example a service tool, manufacturing tool, but may include any type of tool such as an engineering tool, aftermarket tool, consumer oriented tool, or the like. The example system **100** depicts an external device **120** connected directly to the vehicle **102** (e.g., a mobile phone or laptop connected directly to the vehicle **102**), for example an operator device, a service device, a fleet management device, or the like. The example system **100** depicts an external device **118** connected to the cloud server **110**, for example using a web portal, a mobile application, proprietary application, or the like. The example components depicted in FIG. 1 are a non-limiting example, and a given system **100** may include or omit any of the components depicted in FIG. 1. In certain embodiments, a component may be a part of the system **100** at a first time (e.g., while external device **120** is communicatively coupled to the vehicle **102**), and not a part of the system **100** at a second time.

(110) The example controllers **104**, **112**, **124** are depicted in an example arrangement. Aspects of the present disclosure, including circuits, controllers, engines, or the like, may be provided in whole or part on depicted controllers **104**, **112**, **124** in any arrangement, distributed across depicted controllers, positioned in other locations (e.g., on a network zone **106**, **108**, including being positioned in whole or part on an end point of a network zone **106**, **108**), and/or positioned in distinct locations depending upon the current operating condition of the system (e.g., a circuit positioned on the cloud server **110** in a first operating condition, and positioned on a service tool **122** in a second operating condition), time of day, calendar date, position of the operator, position of the vehicle **102**, etc. The example data stores depicted in FIG. 1 may be positioned at any place

in the system **100**, and any data store that is at least selectively or intermittently in communication with any controller embodying a portion of the system **100** is contemplated herein as a data store for certain operations herein, including at least storing data, moving stored data, providing data to an operator or other entity associated with the vehicle (e.g., service personnel, fleet management personnel, a manufacturer, owner, dealer, aftermarket provider, etc.).

(111) Referencing FIG. 2, an example apparatus **200** is schematically depicted to provide, without limitation, automation commands **214** where end points of the vehicle **102** are responsive to the automation commands **214** to implement automated vehicle response activities. The example controller **202**, as well as all controllers depicted herein (e.g., reference FIGS. 6, 11, 15, 17, 20, 22, 32, 34, and 35, and the related descriptions), may be positioned, in whole or part, on the vehicle, the cloud server, a tool, and/or an external device, and may be distributed across more than one of these, including distribution within one or more of these (e.g., a controller having a first portion positioned on a first end point of the vehicle, and a second portion positioned on a second end point of the vehicle).

(112) Example controllers herein are depicted having a number of circuits configured to perform operations of the controller. Without limitation to any other aspect of the present disclosure, a circuit includes components configured to perform the operations set forth for the circuit, and may include components such as: an actuator responsive to commands to perform selected operations and/or to provide communications such as an actuator state, fault condition, or the like; a sensor providing one or more information values utilized by the circuit, including direct sensors (e.g., a temperature, speed, voltage, etc.) and/or virtual sensors (e.g., a value determined from a number of other values available on the system); a processor and/or executable instructions stored on a computer readable medium, where a processor is configured to execute the instructions to perform one or more operations of the circuit; and/or a data store configured to store related data, executable instructions, or the like associated with the circuit. In certain embodiments, the components and/or distribution of the circuit are dependent upon the operations performed by the circuit, the operating conditions of the vehicle, and/or the communication connectivity of components (e.g., availability of communications with the cloud server, a tool, and/or an external device). In certain embodiments, a sensor, actuator, supporting controller, data store, or the like may be communicatively coupled to the circuit, for example a circuit that interprets a temperature value may include a data store having a data value stored thereon representing the temperature value, where the operations of the circuit to interpret the temperature value may include reading the data value, and in another example a circuit that interprets a temperature value may include a temperature sensor that provides the temperature value for utilization by the remainder of the circuit. An example circuit may be embodied by any configuration of hardware, executable instructions, sensors, actuators, logic circuits, or the like, that are configured to cooperate to perform the functions of the circuit. In certain embodiments, portions of a circuit may be distributed across more than one controller, with portions on the vehicle and/or off the vehicle, and/or with portions of the circuit distributed across more than one end point of the vehicle. For clarity of the present description, each circuit and/or controller herein is depicted as a single component, but may be distributed and/or positioned in any manner as set forth herein.

(113) The example controller **202** includes an automation definition circuit **204** structured to interpret an automation description **212**. The example automation description **212** includes operations to be performed to implement an automated vehicle response, and may be provided by an external device, tool, cloud server, or the like. The utilization of the automation description **212** allows for the planning of the automated vehicle response to be performed by a user that does not have vehicle specific information (e.g., parameter names, end point locations, network addresses, and/or information about the distribution of control operations and/or end points on the vehicle). In certain embodiments, a user interface allowing for a user to provide the automation description **212** can inherently limit the user to seeing or accessing only information, functions, or the like that are

permitted for that user. In certain embodiments, operations of the controller **202** to determine an automated action plan **222** in response to the automation description **212** include checking whether aspects of the automation description **212** are permitted by the requestor (e.g., the user providing the automation description **212**), in addition to or alternatively to a user interface that limits the user to permitted activity.

(114) The example controller **202** includes an automation management circuit **206** structured to provide an automated action plan **222** in response to the automation description **212**. In certain embodiments, the automated action plan **222** includes vehicle specific information, such as the addresses, owners, network locations, etc. of end points of the vehicle that are responsive to the automation description **212**, for example end points that provide requested data, end points that can perform requested functions, and/or end points that include, or are in command of, selected actuators of the vehicle that are exercised as a part of the automated vehicle response activities. The automated action plan **222** may further include information such as: trigger evaluation information (e.g., information utilized to determine if aspects of the automated vehicle response activity should be initiated, performed, continued, interrupted, etc.), data to be collected, actuator(s) to be manipulated, data values that should be communicated, or the like. In certain embodiments, the automated action plan **222** further includes information such as data processing (e.g., collected data resolution, units, sampling rate, adjustments, summarization, up-sampling, down-sampling, or the like), calibration adjustments to make (e.g., calibrations associated with flows, applications, end points, etc. of the vehicle), data storage to support operations (e.g., including storage of collected data, storage of trigger evaluation data, and/or storage to support automated operations such as a rolling buffer of certain vehicle data which may be stored for a longer term in response to a detected event). The example controller **202** further includes an automation execution circuit **208** that provides automation command(s) **214** in response to the automated action plan **222**, for example to implement the automated action plan **222**, and/or to perform a workflow and/or tasks of a workflow set forth in the automated action plan **222**. One or more end points of the vehicle, regardless of which network zone of the vehicle such end points are located on, are responsive to the automation command(s) **214** to perform selected operations of the automated vehicle response activity.

(115) An example apparatus **200**, the controller **202** includes an automation reporting circuit **210** that provides a confirmation communication **220** to an external device in response to the implementation of the automated vehicle response **402**. An example automation management circuit **206** further stores a policy responsive to the automated action plan **222**, and where the automation execution circuit **208** provides the automation command **214** in response to the policy. An example automation management circuit **206** further adjusts a stored policy responsive to the automated action plan **222**, where the automation execution circuit **208** provides the automation command **214** in response to the adjusted stored policy. An example automation command **214** includes an actuator command and/or a data collection command. An example an automation reporting circuit **210** provides, to the external device, at least portion of data collected in response to the data collection command. Example and non-limiting automation commands **214** include a calibration adjustment for one of a flow, an application, or a service of a vehicle having the controller **202**. An example automation management circuit **206** further structured to determine an authorization of the external device to provide the automation description **212**. Example operations of the controller **202** may be responsive to vehicle operating parameters **218**, for example as set forth in relation to FIG. **8** and the related description.

(116) Referencing FIG. **5**, an example automation description **212** is provided as a portion of a policy **502** for the vehicle, for example a policy defining rules, priority information, hierarchy information, or the like for inter-network communications, intra-network communications, extra-vehicular communications, or the like. In certain embodiments, the policy **502** is utilized by a CND or other network control device to implement permissions, facilitate communications between end

points, or the like to ensure that network utilization data security, data transmission resource utilization, vehicle operational impact, and other aspects of vehicle operations related to the network are performed within designated parameters, and to ensure that end points and/or external devices can access allowed data, flows, end points, applications, and the like without requiring individualized knowledge of communication protocols, network addresses, network location, data units, data resolution, and/or data sampling rates associated with other end points, flows, applications, etc. Example parameters that may be a part of the automation description **212** include parameters such as: vehicle operating conditions **504** (e.g., operating conditions associated with commencing, continuing, or performing operations, including operating conditions to be utilized as trigger evaluation parameters associated with the automated vehicle response activity); external operating conditions **506** (e.g., operating conditions associated with commencing, continuing, or performing operations, including operating conditions to be utilized as trigger evaluation parameters associated with the automated vehicle response activity, where external operating conditions include off-vehicle operating conditions such as weather, traffic, ambient conditions, an indication from the cloud server such as an update indication and/or a recall indication, etc.); data collection parameters **508** (e.g., parameters to be collected as a part of the automated operations, to prepare for automated operations, to verify automated operations, and/or any of these related to trigger evaluation); event detection parameters **510** (e.g., parameters utilized to evaluate, confirm, and/or verify that an event has occurred); actuator control parameters **512** (e.g., parameters associated with actuators that may be utilized in automated operations, such as actuator identifiers, actuator command values, actuator threshold values, etc.); calibration changes **514** (e.g., parameters associated with changes made to calibrations as a part of automated operations, such as identifiers of the associated flow, application, end point, vehicle function, or the like, identifiers of the calibration parameters to be changed, and/or values associated with the calibration changes to be applied, including for example conditions detected to implement, adjust, or revert calibration changes, and/or including storage of previous calibration values, for example to support a system restore or rollback operation); notification parameters **516** (e.g., content and/or location information for notifications, alerts, or the like, such as network addresses, entity names, communication header information, as well as data to be included in the notification or alert); selected recipes, templates, and/or adjustments to these (e.g., identification and/or content of a recipe and/or template utilized for an automated operation, and/or adjustments from a baseline of the recipe and/or template to be utilized for the automation description **212**, and/or selected recipes, templates, and/or adjustments **518**); life cycle values **520** (e.g., data retention for collected data, the relevant time period for the automation description **212** such as “perform a single time”, “perform continuously”, “perform within a selected time window”, etc., and which may include priority values associated with the automation description **212** and/or related data, etc.); operational impact **522** (e.g., to limit utilization of network communication resources, processing resources, data storage resources, or the like, and/or to limit interference or interruption of vehicle functions, applications, or flows—for example limiting the utilization of vehicle controllers that perform critical functions such as motive power operation, an engine controller, transmission controller, etc.); hierarchy values **524** (e.g., utilized to control prioritization, scheduling, and/or implementation of multiple automated operations, multiple blocks of stored data, or the like); and/or priority values **526** (e.g., priority of an event detection, a trigger evaluation, the automated operations associated with the automation description **212**, data collected pursuant to the automated operations, and including interactions or relationships among these—for example a first priority associated with the automation description **212** before a specific event is detected, and a second priority associated with the automation description **212** after the specific event, for example increasing the priority of the automated description **212** for an event such as a determination that an anomalous vehicle condition is present, or decreasing the priority of the automated description **212** for an event such as confirming that a component of the vehicle is operating properly). Limits to utilization, for example from the

operational impact **522**, may include calculated limits (e.g., determining a network communication rate resulting from the automated action plan **222** and/or the vehicle generally, for example from historical utilization information and/or previously estimated utilization information, and which may further include determining utilization impact due to the actual distribution of end points on the vehicle—for example considering CND traffic to support inter-network communications and the like), rules based limits (e.g., limiting an automated action plan **222** to a data storage cap, network utilization cap, etc., which may further be determined according to a priority of the automated action plan **222**, and/or a permissions value associated with the requestor or other entity associated with the automated action plan **222**), and/or flexible limits (e.g., allowing all automated action plans **222** until a utilization limit is reached, and then prioritizing between automated action plans **222** in a selected manner, which may be set by a policy or by any other prioritization scheme set forth herein). In certain embodiments, for example when an automated action plan **222** is not implemented and/or is modified due to a utilization limit, an example controller **202** provides a notification or alert to indicate that an automated action plan **222** has been refused, discontinued, and/or modified. The notification or alert may be communicated to the requestor, an administrator (e.g., of a cloud server **110** or application running on controller **112**), a vehicle manufacturer, or any other entity associated with the system **100**.

(117) Referencing FIG. 3, an example automated action plan **222** includes aspects of the automated description **212** that are configured for the specific vehicle, such as: a data description of data to be collected **302** (e.g., including network addresses, end point identifiers, data processing values, etc.); actuator responses **304** (e.g., including network addresses, end point identifiers, actuator command values, etc.); data transmission operations **306** (e.g., including transmission timing, priority, loss of transmission responses, etc.); data storage operations **308** (e.g., including data storage locations, data storage format, data storage life cycle, etc.); event detection descriptions **310** (e.g., events to be detected relevant to the automated vehicle response activities, for example utilized to initiate actions, to modify actions, to initiate or set timer values, to set state values, or the like); trigger descriptions **312** (e.g., triggers utilized to initiate an action or workflow, to initiate data collection, to initiate a timer or other delay operation, etc.); and/or action sequences or schedules **314** (e.g., providing a description of actions sequenced in a workflow—e.g., reference FIG. 25-27 or 31, and the related descriptions, providing a description of timing to initiate actions and/or delay periods between actions, schedules of actions based on events, triggers, state values, or operating conditions, etc.). In certain embodiments, the automated action plan **222** further includes data descriptions setting forth data processing, units, resolution, sampling rates, and/or other information related to data utilized during automated vehicle response activities, and/or data stored, communicated, or transmitted during automated vehicle response activities.

(118) Referencing FIG. 4, example automated vehicle responses **402**, for example setting forth actions to be performed as an automated vehicle response activity, are schematically depicted. The example automated vehicle responses **402** are not values that will appear, typically, as a data value in a system, but are rather high level descriptions that may be the target of a procedure (e.g., reference FIGS. 36-55 and the related descriptions), that are the intended target activities by a user providing an automation request **1506** and/or an automation description **212**, and/or may be provided as a description related to a template or recipe, for example to be provided on a user interface. Example and non-limiting automated vehicle responses **402** include responses such as: selectively activating an actuator **404** (e.g., commanding the actuator to open or closed, commanding the actuator to a selected position, and/or commanding an outcome for the actuator—for example a set point for a control algorithm that utilizes the actuator); collection of selected data **406** (e.g., data collected relating to an event detection, a trigger evaluation, during operations of the automated commands, confirmation data related to the automated commands, and/or alerts or notifications related to the automated commands); delaying the automated vehicle response for a hold period **408** (e.g., detecting that a trigger evaluation indicates that the automated vehicle

response activity is to be performed, and delaying to perform the activity for a predetermined period, until another condition is detected, and/or according to an operating condition of the vehicle, such as waiting until the vehicle is stopped, moving at a threshold speed, below a set fuel or battery level, in a shutdown condition, etc.); delaying the automated vehicle response for a detected event **410** (e.g., a vehicle accident event, a fault code event, an off-nominal operation event, and/or any other event detection as set forth throughout the present disclosure); moving an actuator to a selected position **412**; and/or providing a notification **414** (e.g., a notification that an automated vehicle response activity has been performed, that a trigger evaluation has been confirmed, that an event has been detected and/or information related to the event detection, that an automated vehicle response activity has not been, or will not be performed, etc.). The automated vehicle responses **402** are a non-limiting example of a few operations that may be performed by an automation command **214**. In certain embodiments, a given automated vehicle response activity may include a number of automated vehicle responses **402**. In certain embodiments, an automated vehicle response **402** may be performed as a task in a workflow, such as set forth in relation to FIGS. 25-27 and 31).

(119) An example system includes the end point responsive to the automation command **214** as a second controller (e.g., where the automation command **214** is a communication to the second controller) separate from the controller **202**. An example system includes the second controller providing a selected data value (e.g., requested data for collection) or a selected actuator command value (e.g., commanding an actuator responsive to the automation command **214**) in response to the automation command **214**. In certain embodiments, the second controller further provides a confirmation value **216** to the controller **202**, for example to confirm that the automation command **214** was received, to confirm that the actuator has been commanded, and/or to confirm that the actuator has responded to the command. In certain embodiments, the second controller provides the confirmation value **216** in response to implementing the automated vehicle response, for example in response to the automation command **214** being provided to the second controller, in response to a detected event, and/or in response to a trigger evaluation determining that the automated vehicle response is active. In certain embodiments, the second controller provides the confirmation value **216** as a task of a workflow performed as a part of the automated vehicle response. An example system includes a second end point, for example, a sensor or an actuator, that is responsive to a command from the second controller. In certain embodiments, an end point responsive to the automation command **214** may be a sensor or an actuator that performs an action in accordance with the automation command **214**. In certain embodiments, more than one end point is involved with various automation commands **214**, where each end point may be on any network zone of the vehicle, including with end points distributed across more than one network zone of the vehicle. In certain embodiments, the controller **202** provides an automation command **214** to each relevant end point, for example passing commands through a CND that configures and communicates the automation commands **214**, confirmation values **216**, and/or any other communications provided between the controller **202** and responsive end points, including providing communications according to the relevant network protocols, messaging paradigm, etc., for each end point and the controller **202**. Network zones in the vehicle may be of distinct types (e.g., ethernet vs. CAN), utilize different communications protocols, or the like. End points of network zones of the vehicles may utilize different network communication rates or schemes, different data types or resolutions (e.g., 2-byte fixed point data versus 4-byte floating point data), or have any other differences that are managed by a CND, edge gateways, and/or a policy engine or policy manager, as set forth herein and in U.S. application Ser. Nos. 17/027,167, 17/027,187, and/or U.S. Ser. No. 17/195,589, which have previously been incorporated herein by reference.

(120) An example automation execution circuit **208** detects an event in response to an event detection description **224** of the automated action plan, and implements the automated vehicle further in response to the detected event. An example automation management circuit **206** provides

the automated action plan **222** in response to an external operating condition of the automation description **212**, and the automation execution circuit **208** receives the external operating condition from an external device (e.g., a device at least intermittently in communication with controller **202** and/or the vehicle, for example a web based service operating on an external device). An example automation definition circuit **204** receives the automation description **212** from an external device, for example by operations such as: receiving the automation description **212** from a cloud server as an automation workflow to be performed on the vehicle; as a policy including the automation description **212**; as a portion of a policy including the automation description **212** (e.g., to be appended to a main policy, and/or to be performed as a second policy where the system implementation allows for multiple policies to be serviced); and/or as a remote command (e.g., provided by a data file having the automation description **212**, and formatted to be recognized and implemented by controller **202**) by any external device such as a service tool, an application on the cloud server in communication with the vehicle, a web portal in communication with the vehicle, and/or a mobile application such as an application on a mobile device of an operator of the vehicle.

(121) Referencing FIG. **6**, an example apparatus **600** depicts a controller **601** including the automation definition circuit **204** that interprets an automation trigger description **602** (e.g., describing criteria to initiate, continue, discontinue, and/or move between tasks or states of a workflow associated with an automated vehicle response activity), and an automation action description **604** (e.g., describing operations performed as a part of a workflow associated with an automated vehicle response activity). The example controller **601** includes the automation management circuit that provides a trigger detection plan **610** and an automated action plan **222** in response to the automation trigger description **602** and the automation action description **604** (e.g., providing vehicle specific parameters to implement the descriptions **602**, **604**, appending within a policy, and/or performing any other operations to implement the automated vehicle response activity as set forth herein). The example controller **601** includes the automation execution circuit **208** that determines a trigger event value **612** (e.g., checking current vehicle conditions or other relevant data to determine whether criteria for a trigger of the trigger detection plan **610** have been met), and provides an automation command **214** in response to the trigger event value **612** (e.g., beginning execution of automation commands **214** after the trigger is confirmed) and the automated action plan **222** (e.g., executing the selected automation operations).

(122) An example automation execution circuit **208** further provides a trigger evaluation command **606** in response to the trigger detection plan **610**, for example allowing for serial trigger conditions (e.g., check for condition A to exist before beginning to check for condition B). End point(s) responsive to the trigger evaluation commands **606** may be distinct from end points performing the automation commands **214**, and further end points supporting each trigger level (e.g., where serial trigger conditions are considered) may be distinct from end points supporting other trigger levels (e.g., the check for condition A versus condition B may use a distinct set of sensors, vehicle data, etc. to determine whether the trigger conditions for each one are met). An example automation execution circuit **208** is responsive to a trigger evaluation value **608** determined from the trigger evaluation commands **606**, for example where the trigger evaluation value **608** includes data from end points utilized to check whether the related trigger condition has been met (e.g., a temperature from a sensor, a position feedback from an actuator, and/or a state parameter from a controller of the vehicle such as “door ajar”), where the automation execution circuit **208** executes the appropriate aspects of the automated action plan **222** and/or trigger detection plan **610** in response to the trigger evaluation data **608**.

(123) Referencing FIG. **7**, an example automation action description **604** includes an automation scheduling value **706** (e.g., times and/or sequencing of tasks of a workflow). Example aspects of the automation action description **604** include one or more of: a data description of data to be collected **702**; an actuator response **704** of actuators to be controlled; an event detection description **708** (e.g., for events to be detected as part of a workflow); an action repeat value **710** (e.g., a

number of times for an action to be repeated, a repeating schedule, a time window during with the repeating behavior is adjusted, etc.); and/or an action interruption description **712** (e.g., describing criteria such as operating conditions, response times, state values, etc., at which an action should be considered to be interrupted; and/or a description of actions that should be performed in the event of an interruption, such as data deletion or management, setting of state values or other stored parameters, and/or a description of whether the action should be resumed and/or related criteria for resumption).

(124) Referencing FIG. **8**, an example automation trigger description **602** includes a trigger scheduling value **810** (e.g., times and/or sequencing of various trigger determinations for a workflow). Example aspects of the automation trigger description **602** include one or more of: an event detection description **802** (e.g., for events relevant to trigger determinations); a trigger description **806** (e.g., criteria to be evaluated to determine the trigger event value **612**); a trigger time description **814** (e.g., relevant time frames for the trigger check, including delay periods relative to other values, such as 10 minutes after vehicle start, and 5 seconds after engine speed exceeds 1000 rpm, and continue for 30 seconds); a filter description for vehicle operating parameter(s) **804** (e.g., allowing for a change in response time and/or real-time accuracy for operating parameters, for example to hide system dynamics from an observer of the related data, or to increase the difficulty of reverse engineering an aspect of the vehicle, while providing sufficient data for the purpose of the trigger and action of the workflow); a map description **808** (e.g., allowing for geographic and/or jurisdictional trigger detection, for example to implement a different set of display units in a different country, to adjust engine performance or emissions for compliance with each country, etc.); an aggregated data description **812** (e.g., allowing trigger determination from a summation, moving average, integration, etc. of various data elements); a statistical analysis description **816** (e.g., allowing trigger determination from anomalous data such as: a temperature value outside a range expected by a temperature model, a data value that is several standard deviations outside of an expected value, and/or a metadata statistic, such as a number of times a value is communicated that exceeds or falls below an expected frequency or distribution of frequencies); and/or a data parsing description **818** for vehicle operating parameters, network messages, and/or controller parameters (e.g., allowing the automation execution circuit **208** to: provide or utilize only data of interest such as data within selected time windows and/or data associated with a detected event or trigger; to adjust reported data according to a selected formatting, message protocols, or the like, and/or providing reporting utilizing the payload (e.g., the data values) with full or partially removed headers (e.g., network addresses, etc., which may depend upon the network type and protocols for the end point providing the data). In certain embodiments, information about the message apart from the payload, such as time stamps, network addresses, etc., may be removed from the data—for example due to permissions values (e.g., a requestor providing an automation request **1506** that is not authorized to see certain aspects of the data), to reduce utilization (e.g., providing only the payload with message headers removed reduces network communications and data storage utilization), and/or to normalize data (e.g., an end point utilizing the wrong system time may have time corrected data, for example to allow for later synchronization of data).

(125) Referencing FIG. **9**, example automated vehicle responses **902** include one or more of: providing an actuator command **904**, providing an actuator activation **906** (e.g., blocking or allowing the use of an actuator, for example enabling or disabling a feature of the vehicle such as a cruise control system, door lock actuator, or steering wheel); and/or an actuator trajectory **908** (e.g., controlling a rate of the actuator response, commanding the actuator through a series of time-position commands; commanding the actuator through a series of time-set point commands; etc.). An automated vehicle response **902**, as utilized herein, includes actions provided by any controller herein that performs operations to: complete an automated vehicle response activity, execute an automated workflow, to perform an automated vehicle response, or any other similar automation

operations described herein.

(126) Referencing FIG. **10**, example automated vehicle responses **902** include one or more of: selectively enabling a vehicle feature **1002** (e.g., turning on or off a vehicle capability); adjusting a calibration of a vehicle feature **1004** (e.g., adjusting a maximum speed, limiting a radio volume to selected values, and/or adjusting any other feature of the vehicle); adjusting a display of the vehicle **1006** (e.g., providing a selected camera to a screen; providing a light or notification to the operator; and/or changing which values are displayed on a screen or dashboard); adjusting an operator control response of the vehicle **1008** (e.g., switching to an economy or performance mode; adjusting a maximum speed or power; and/or adjusting a transmission shifting scheme); adjusting an environmental management system of a vehicle **1010** (e.g., adjusting a temperature, blower level, blower scheme, etc., for example allowing a response according to the operator identity, time of day, weather information, etc.); adjusting a sound system of the vehicle **1012** (e.g., setting volume, station, presets, allowed values, etc.); and/or adjusting a lighting of the vehicle **1014** (e.g., interior lighting, headlight thresholds such as high beam oncoming distance, headlight aim location, and/or headlight light level activation thresholds, which may be configured for the driver, time of day, season, etc.).

(127) An example automation action description **604** includes an action repeat value, and the automation management circuit **206** further provides the automated action plan **222** in response to the action repeat value. For example, an action may be repeated as a part of a workflow (e.g., reference FIGS. **25-27**, and **31**), or a given action may be repeated multiple times (e.g., which may be treated together as a single task in a workflow such as in FIGS. **25-27**, and **31**), depending upon the organization of the automation description **212**, automation trigger description **602**, and/or automation action description **604**, and/or the implementation scheme for a workflow for a particular system.

(128) An example automation description **604** includes an action interruption description, where the automation management circuit **206** further provides the automated action plan **222** in response to the action interruption description. Example and non-limiting action interruption descriptions include one or more of: an action response description for a vehicle off event (e.g., actions to be taken when a vehicle off event is detected, for example in response to an operator requested state, key removal, etc.); an action response description for a vehicle fault event (e.g., actions to be taken when a fault disrupts the action, for example when a commanded actuator indicates a fault has occurred); an action response description for a vehicle operation interruption (e.g., the action requires 10 seconds at 60 mph, and the vehicle has just reduced speed to 55 mph after 6 seconds; in another example a network communication dropout for selected parameters has exceeded a threshold value); and/or a timeout event such as an amount of time for an interruption (e.g., loss of a parameter, loss of a trigger condition, failure to progress to a task stage, etc.) of task progress is deemed to be an interruption of the action. Example interruption descriptions include determinations of whether to pause or cancel operations (e.g., of a related workflow), whether to reinstate trigger conditions before proceeding or restarting, whether to count the action as complete or incomplete, whether and where to provide a notification or alert of the action interruption, and/or treatment of stored data pursuant to the action (e.g., hold the data, delete the data, move the data, etc.).

(129) Referencing FIG. **11**, an example apparatus **1100** includes a controller **1101** having an automation definition circuit structured to interpret a task description **1102** (e.g., for a task provided by a requestor that may not have knowledge of the vehicle, end point configurations, and/or parameter names), an automation management circuit **206** that provides a task action plan **1106** in response to the task description **1102** (e.g., where the task is converted into vehicle specific parameters and configured into a workflow or other organizing scheme for tasks as set forth throughout the present disclosure), and an automation execution circuit **208** that provides task execution command(s) **1104** in response to the task action plan **1106** (e.g., providing network

communications, actuator commands, and/or collecting data pursuant to the task action plan **1106**). An example system **100** includes one or more end points responsive to the task execution command(s) **1104** to implement a task for the vehicle.

(130) Referencing FIG. **12**, an example task description **1102** includes one or more of: a task scheduling value **1206** (e.g., setting time values and/or command sequences associated with the task); a task initiation value **1208** (e.g., setting criteria for the task to begin); actuator response(s) **1204** (e.g., actuator commands to be provided during execution of the task); and/or a data description of data to be collected **1202** (e.g., setting criteria, parameters, etc., for data to be collected pursuant to execution of the task).

(131) Referencing FIG. **13**, example and non-limiting tasks **1302** are provided. In certain embodiments, a task may be any automated vehicle response activity, automated workflow, or automated vehicle response, and/or an operation within any one or more of these. The example tasks **1302** include operations such as: monitoring a vehicle operating condition **1304** (e.g., speed, fuel economy, alarm system, etc.); selectively activating an actuator **1306** (e.g., disabling or enabling any actuator, feature, or other aspect of the vehicle); moving an actuator to a selected position **1308** (e.g., open the trunk; and/or set an actuator rate limit or target, move the actuator through a time-position or time-value trajectory, etc.); transmitting task data (e.g., any data associated with the task, for example data confirming the task, verification data, and/or data collected as an operation of the task) in response to a task execution command (e.g., if the task was attempted) and/or an end point response (e.g., if the task was completed) **1310**; storing task data in response to a task execution command and/or an end point response **1312**; providing a report (e.g., with selected data, formatting, verification data, headers, metadata, etc.) in response to a task execution command and/or an end point response (e.g., providing the report accessible on an automation user interface **1504**) **1314**; and/or providing a notification (e.g., an alert that the task has commenced and/or completed, which may include summary information of the task outcome—e.g., maximum temperature, fault codes, etc.) in response to a task execution command and/or an end point response **1316**. In certain embodiments, example tasks for the vehicle **1302** include collecting selected data for the vehicle **1318**, determining whether an event has occurred **1320**, and/or monitoring an external operating condition **1322**.

(132) Referencing FIG. **14**, an example automated action plan **222** is schematically depicted. The example automated action plan **222** includes one or more actions such as: implementing a conditional operation **1410** (e.g., performing a task based on the completion of another task, the detection of an event, and/or a trigger evaluation); implementing a branched operation **1412** (e.g., performing more than one task based upon a single completion of another task, detected event, and/or trigger evaluation); implementing a state machine operation **1414** (e.g., any state machine based workflow, for example moving between operating modes based upon selected trigger conditions, where each operating mode has a distinct task set from other operating modes); and/or implementing a cyclical operation **1416** (e.g., allowing for looping and/or repeating behavior for one or more tasks). An example automated action plan **222** includes a continuity description **1418**, for example describing interruption parameters (e.g., to determine whether an interruption of a task, workflow, automated vehicle response activity, etc., has occurred) and continuity parameters (e.g., treatment of data, resumption criteria, etc., for the interrupted task, workflow, and/or automated vehicle response activity). In certain embodiments, aspects of the action interruption description **712** are applicable to embodiments of the automated action plan **222**.

(133) Referencing FIG. **15**, an example apparatus **1500** includes a controller **1501** to provide an automation description **212** to a vehicle controller **1510** is schematically depicted. The example controller **1501** includes an automation definition circuit **204** that implements an automation user interface **1504**, and interprets an automation request **1506** in response to user communications with the automation user interface **1504**. The automation user interface **1504** may include any interface, such as an interactive user interface allowing a user to build a task, workflow, or the like, a coding

interface allowing a user to insert a code element into a file that is utilized to generate the automation request **1506**, and/or an API where exercising the API is utilized to submit automation requests **1506** to the controller **1501**. In certain embodiments, a user accesses the automation user interface **1504** using an external device **1508**, for example by accessing a web portal, mobile application, cloud server, and/or by direct vehicle access such as using a tool, laptop, mobile device, or the like (which access may be supported by a cloud server having at least a portion of the controller **1701**, and/or with the controller **1701** positioned on the vehicle).

(134) The example controller **1501** includes an automation management circuit **206** that determines an automation description **212** in response to the automation request **1506**. In certain embodiments, the automation request **1506** and the automation description **212** may be the same, for example where the automation user interface **1504** allows for the user to provide an automation description **212** directly. In certain embodiments, the automation request **1506** and the automation description **212** may be distinct, for example where the automation request **1506** references a recipe by reference (e.g., Recipe **178**, or “Rapid warm-up recipe”), and/or where the automation request **1506** utilizes shorthand parameters (e.g., Task A, rather than the steps executed in Task A) or abbreviations. In certain embodiments, allowing the automation request **1506** and automation description **212** to be distinct allows for a reduction in resource utilization to support embodiments herein, and/or allows for convenient implementation for a user (e.g., allowing the user to simply select recipes or templates, and/or to modify those). In certain embodiments, allowing the automation request **1506** and automation description **212** to be the same provides for a simplified implementation, and/or ease of troubleshooting and/or debugging of the system. The example controller **1501** includes an automation command circuit **1502** that provides the automation description **212** to the vehicle controller **1510**, where the vehicle controller **1510** is configured to implement an automated vehicle response that is responsive to the automation description **212**. In the example of FIG. **15**, the controller **1501** may be positioned, at least in part, on the vehicle (e.g., determining all or a portion of the automation description **212** on a vehicle side controller). The vehicle side portion of the controller **1501**, where present, may be positioned on a same substrate (e.g., board, memory, processor) as vehicle controller **1510**, or on another controller in the vehicle (not shown). In certain embodiments, the controller **1501** is positioned completely apart from the vehicle. In certain embodiments, the controller **1501** is positioned on a cloud server, and/or implemented as a web portal.

(135) An example automation management circuit **206** confirms an authorization **1512** of the user for the automation request **1506**, and determines the automation description **212** in response to the authorization **1512**. For example, where the automation request **1506** includes an aspect such as a parameter value, parameter characteristic (e.g., resolution, sampling rate), operation request (e.g., specific actuators affected), data storage request (e.g., explicit, such as data storage to support data collection operations, or implicit, such as data storage to support event detection, trigger evaluation, data processing operations, or the like to support the task, workflow, etc.), or the like that requires a specific authorization to access, the example automation management circuit **206** compares an authorization **1512** associated with the user (e.g., for the user personally, according to an entity associated with the user, according to an access location of the user, etc.) to the required authorization for the aspect. Depending upon the type of lack of authorization, design selection for the system, and the organization of tasks, workflows, and the like, the automation management circuit **206** may refuse the automation description **212** (e.g., prohibit the automation description **212** from including the automation request **1506**, for example by providing an automation description **212** including only other-authorized-requests, and/or omitting the automation description **212** altogether), and/or provide an adjusted automation description **212** (e.g., removing the aspects that are not authorized, such as parameters, tasks, data storage, etc.). In certain embodiments, where the automation description **212** is adjusted, an example automation management circuit **206** provides an amendment and/or notification communication **1514** to the

automation user interface **1504**, which may be provided to the requesting user (e.g., an amendment to the automation request **1506**, and/or including information about the amendment), and/or to another user (e.g., allowing the other user to monitor access to sensitive parameters, to adjust the authorization of the requesting user, to improve interface elements of the automation user interface **1504**, and/or to assist other users through direct communications and/or training about the automation user interface **1504**). In certain embodiments, where the automation description **212** is refused, an example automation management circuit **206** provides a refusal communication to the automation user interface **1504**, which may be provided to the requesting user (e.g., a rejection of the automation request **1506**, and/or including information about the rejection) and/or to another user. An example automation command circuit **1502** provides the automation description **212** as a policy and/or a policy update. An example automation command circuit **1502** receives a confirmation communication **1516** from the vehicle controller **1510**, where the confirmation communication **1516** confirms one or more aspects, such as: a confirmation the automation description was received; a confirmation the automation description is approved (e.g., based on availability of parameters, actuators, etc. to support the task, and/or authorization of the requesting user and/or of the controller **1501**—such as an identity of an entity associated with the controller **1501**, login information provided by the controller **1501**, encrypted communication operations between the controller **1501** and the vehicle controller **1510**, etc.); a confirmation the vehicle has capability to perform the automation description (e.g., memory storage, transmission capability, network support capability, etc.); a confirmation that one or more tasks have been executed (and/or execution statistics related thereto); and/or a confirmation that data related to one or more tasks is available. In certain embodiments, the automation definition circuit **204** is further structured to provide a confirmation communication, which may be the same as, or based upon, the confirmation communication **1516**, to the automation user interface **1504**. In certain embodiments, the confirmation communication **1516** is provided to the same or a distinct user than a requesting user (e.g., where a first user is responsible to set up the task, and a second user utilizes data from the task).

(136) Referencing FIG. **16**, example authorizations **1512** may relate to one or more of: data to be collected **1602** for the automated vehicle response; data to be provided on a network **1604** of the vehicle for the automated vehicle response (e.g., including an impact to network traffic to support the task, and/or to support inter-network traffic such as by a CND to connect end points on distinct network zones); an actuator to be accessed **1606** for the automated vehicle response; a service to be accessed **1608** for the automated vehicle response; a flow to be accessed **1610** for the automated vehicle response; an application to be accessed **1612** for the automated vehicle response; and/or an operational impact **1614** associated with the automated vehicle response (e.g., fuel economy impact, data storage impact, network utilization impact, etc.). Aspects of the authorization **1512** may be binary (e.g., the user has permission or does not have permission) or graduated (e.g., the user has authorization for a selected amount of memory storage).

(137) Referencing FIG. **17**, an apparatus **1700** includes a controller **1701** for performing triggered automated actions for a vehicle. The example controller **1701** includes an automation definition circuit **204** that interprets an automation trigger description **602** and an automation action description **604**, and an automation management circuit **206** that provides a trigger detection plan **610** and an automated action plan **222** in response to the automation trigger description **602** and the automation action description **604**. The example automation management circuit **206** further provides a data storage command **1704** in response to the trigger detection plan **610** (e.g., providing sufficient storage to perform trigger operations, including trigger evaluation, support for rolling buffers of data, and/or support for data collection operations instructed as part of the trigger detection plan **610**). The example controller **1701** includes a data caching circuit **1702** that confirms available data storage on a data storage device, and/or reserves storage on a data storage device, in response to the data storage command(s) **1704**. In certain embodiments, the availability

of data storage (e.g., whether current available storage, reservable storage, or a combination) may be a part of approval, amendment, or refusal of an automation trigger description, an automation action description, and/or an automation description **212**. In certain embodiments, the availability of data storage may be a part of determining an event detection, such as an interruption of a task, workflow, or automated vehicle response activity (e.g., deciding a task is interrupted when memory storage to complete the task is determined to be unavailable). The example controller **1701** includes an automation execution circuit **208** that determines a trigger event value **1706** (e.g., whether a trigger event has occurred) in response to the trigger detection plan **610**, and stores trigger evaluation data in response to the trigger event value **1706** and the automated action plan **222** (e.g., as data storage commands **1704** storing the trigger evaluation data). The example automation execution circuit **208** further provides an automation command **214** in response to the trigger event value **1706** (e.g., providing the automation command **214** after the trigger event has occurred, which may further include a delay period). An example system includes one or more end points responsive to the automation command(s) **214** to thereby implement an automated vehicle response. An example data caching circuit **1702** reserves and/or confirms data storage on a memory storage associated with at least one vehicle controller, which may be the controller **1701** including the data caching circuit **1702**, or another controller on the vehicle.

(138) Referencing FIG. **18**, example data storage command(s) **1704** provided by the automation manager circuit **206** include one or more of: a data storage schedule **1810** of the trigger evaluation data **1802** (e.g., a data retention time, priority information related to the data or portions thereof, etc.); a data storage trajectory **1808** of the trigger evaluation data **1802** (e.g., storage amount over time); a conditional data storage command **1812** (e.g., data storage based upon detected events, triggers that are met, etc., for example allowing for statistical estimation of a data storage amount to support a number of tasks, workflows, automated vehicle responses, or the like, for example based upon the likelihood of simultaneous trigger events for a number of tasks, workflows, automated vehicle responses, etc.); a priority description **1814** for at least one data element of the trigger evaluation data **1802** (e.g., allowing for a prioritization within the data, differential treatment for aging data, and the like); an aging data description **1816** for at least one data element of the trigger evaluation data **1802** (e.g., residence time, transmission priority, activities to be performed to compress, summarize, aggregate, or otherwise reduce the data, and/or deletion aspects such as notifications, alerts, or residual data to be sent upon the deletion of the data); a confirmation of data storage **1804** (e.g., a confirmation that data storage is reserved, and/or that responsive data is stored); and/or a reservation of data storage **1806** (e.g., an amount of data storage to support the tasks, workflows, automated vehicle responses, or the like). The example of FIG. **19** is similar to the example of FIG. **18**, with commands related to automated collected data **1902** rather than trigger evaluation data **1802**. In certain embodiments, data storage commands **1704** may be present to support both trigger evaluation data **1802** and automated collected data **1902**.

(139) An example data caching circuit **1702** performs memory management operations in response to the aging data description **1816**, such as: performing a scheduled deletion of at least a portion of the trigger evaluation data **1802**; performing a compression operation of at least a portion of the trigger evaluation data **1802**; performing a summarization operation of at least a portion of the trigger evaluation data **1802**; confirming available storage on a shared data storage device; and/or reserving and/or confirming the reservation of data storage on a shared data storage device.

Example embodiments herein utilizing shared storage may include a shared storage controller and/or any aspects thereof, for example as described in U.S. patent application Ser. No. 17/195,589 (SONA-0010-U01), for example at FIG. 16 of the '589 application, and the related descriptions.

(140) Again referencing FIG. **17**, an example automation management circuit **206** provides a data storage command **1704** in response to the automation action description **604**. All preceding operations and aspects set forth in relation to FIG. **17**, which were described in relation to trigger evaluation data **1802**, are also applicable to data collected as a part of the task, workflow, and/or

automated vehicle response, determined from the automation action description **604**. Example operations include confirming and/or reserving data storage, management of aging data, confirmation communications, conditional data storage, and/or any data storage command **1704** examples, including for example those depicted in relation to FIG. **18** or **19**.

(141) Referencing FIG. **20**, an example apparatus **2000** includes a controller **2001** configured to provide an automation description **212** to a vehicle controller **1510**. The example controller includes an automation definition circuit **204** that implements an automation user interface **1504**, and provides at least one automation recipe **2004** to the automation user interface **1504**, and interprets an automation request **1506** in response to user communications with the automation user interface **1504**. In certain embodiments, the automation request **1506** may include one or more selected recipes from the automation recipes **2004**, a modified or adjusted version (e.g., by the user) of one or more selected recipes, and/or may be generated independently of the automation recipes **2004** (e.g., through a task or workflow builder, such as depicted in FIGS. **25-27**, and **31**). An example automation definition circuit **204** selects a group of automation recipes **2004** in response to a user characteristic **2002** of the user, and provides the at least one automation recipe to the automation user interface **1504** in response to the selected group (e.g., provide all of the selected recipes, provide the top 10 selected recipes, etc.). The selection of recipes from the automation recipes **2004** based on the user characteristic **2002** includes selecting recipes for which the user has authorization, and/or selecting recipes that may be of interest to the user (e.g., based on a role of the user, and tags for the recipes, and/or recipes utilized by users having a similar role, and/or based on another aspect of the user such as an entity type—e.g., manufacturer, OEM, dealer, fleet owner, operator, etc.). Example and non-limiting user characteristics **2002** include one or more of: a user role, an entity associated with the user, a user authorization, or a user historical activity with the automation user interface **1504**. In certain embodiments, each of the automation recipes **2004** includes operations for one or more of: an automated operation of the vehicle; a portion of an automated operation of the vehicle (e.g., with portions to be completed by the user); and/or a template for an automated operation of the vehicle (e.g., a recipe built to be a good starting point for a range of potential automated operations). An example automation request **1506** includes at least one parameter description that is an agnostic parameter description, or a parameter description that is not vehicle-specific, for example including parameter naming, units, resolution, sampling rate, etc. that is consistent with an industry standard, a standard for an entity (e.g., a company employing the user), a parameter description for a different vehicle (e.g., a prior year model compared to the target vehicle, a similar vehicle having a different component and/or network configuration from the target vehicle, or another vehicle unrelated to the target vehicle, for example a parameter consistent with a vehicle recently accessed by the user). In certain embodiments, the automation description **212** includes vehicle specific parameters. In certain embodiments, the automation description **212** includes normalized parameters, where vehicle specific parameters are determined on the vehicle controller **1510**, for example by a CND, policy engine, or the like.

(142) Referencing FIG. **21**, a number of aspects of an example automation command **214** are schematically depicted. The example automation commands **214** may each include one or more aspects depicted in FIG. **21**, and an automation command **214** may include other aspects that are not depicted in the example of FIG. **21**. An example automation command **214** includes one or more of: a data collection command **2102** (e.g., data to be collected for trigger evaluation, event detection, and/or as a part of a task, workflow, automated vehicle response, etc.); a data processing command **2104** (e.g., parameter naming; unit selection; resolution such as byte depth, display resolution, or the like; sampling rates including up-sampling and/or down-sampling operations; synchronizing or time spacing processing of sequential data values; a data communication command **2106** (e.g., which elements of data are to be communicated on a network, to which end points, as a multi-cast, etc.); a data transmission command **2108** (e.g., which elements of data are to be transmitted, including potentially related time frames, priority, etc.); an actuator command **2110**;

a calibration adjustment **2112**; and/or a data storage command **2114** (e.g., including data reservation, aging data treatment, storage priority, etc.).

(143) Again referencing FIG. 2, an example automation definition circuit **204** interprets a number of automation requests **1506** and/or automation descriptions **212**, where the automation management circuit **206** provides an automated action plan **222** in response to the automation requests **1506** and/or automation descriptions **212**. In certain embodiments, the automation requests **1506** and/or automation descriptions **212** further include corresponding priority values, and to provide the automated action plan **222** in response to the priority values. In certain embodiments, the automation requests **1506** and/or automation descriptions **212** further include corresponding hierarchy values, and to provide the automated action plan **222** in response to the hierarchy values. A hierarchy value may relate to an ordering of automation descriptions, tasks, workflows, or the like, and/or may relate to an entity associated with the automation descriptions, tasks, workflows, or the like. An entity associated with an automation descriptions, tasks, workflows, or the like may relate to any entity requesting information (e.g., a user, user role, and/or entity role such as of a company for the user), any entity providing information (e.g., a vehicle controller, end point, flow, application, vehicle function, or the like that provides information as a part of the automation description, task, workflow, or the like), and/or any entity significantly affected by the automation description, task, workflow, or the like (e.g., due to related network zone traffic, controller processing operations to support the task, and/or data storage operations to support the task). The utilization of a hierarchy value allows for granular response to different users, entities, roles, and application types on the vehicle (e.g., improving support for a fuel system function of the vehicle versus an entertainment display function of the vehicle). An example automation management circuit **206** determines a dependency value between at least two of the automation descriptions **212** (e.g., based on parameter determination and/or ordering, an indicated dependency in the automation descriptions **212**, and/or based on enforced execution schedules of related functions of the vehicle that provide or respond to data affected by the automation description, task, workflow, or the like). An example automation management circuit **206** determines an operation impact for at least one of the automation descriptions **212**, and provides the automated action plan **222** in response to the operation impact. In certain embodiments, the automation management circuit determines a life cycle value for an automation recipe and/or for an automation description **212**, and stores the automation recipe and/or an automation description **212** in response to the life cycle value. For example, the life cycle value may indicate that the automation description **212** (and/or an automation recipe) should be performed one time, should be performed a selected number of times, should be performed persistently, should be performed over a selected time period (e.g., for the next six months), and/or should be performed while another condition is true or false (e.g., ending the life cycle of the automation description **212** and/or automation recipe, for example when the condition changes). An example automation management circuit **206** deprecates at least one of the automation descriptions **212**, for example by marking a description for removal, by deleting a description, and/or by ceasing operations to support a description (e.g., including stopping trigger evaluation, data storage, data storage reservation, etc.). Example and non-limiting operations to deprecate an automation description **212** and/or an automation recipe include one or more of: updating the automated action plan **222** to remove deprecated automation descriptions; deleting stored data responsive to the deprecated automation descriptions; deleting a stored recipe corresponding to the deprecated automation descriptions; and/or adjusting at least one of a priority value or a hierarchy value corresponding to the deprecated automation descriptions.

(144) Referencing FIG. 22, an example apparatus **2200** includes a controller **2201** configured to store collected data related to a task, workflow, automated vehicle response, or the like. The example controller **2201** includes an automation definition circuit **204** that implements an automation user interface **1504** includes at least one available input parameter (e.g., a data parameter that is available on the vehicle, and/or that can be made available on the vehicle), at least

one available actuation parameter (e.g., an actuator that is available for at least partial manipulation; and/or a feature that is available for at least partial manipulation, such as having available calibration adjustments, and/or feature enable/disable operations), and at least one responsive data selection, such as data available for collection, confirmation data that can be provided, verification data that can be provided, and/or confirmation communications that can be provided. The example controller **2201** includes an automation confirmation circuit **2202** that receives collected data **2208** from the vehicle in response to the automated vehicle response (e.g., the performance of tasks, workflows, automated vehicle response activity, etc.), and to store the collected data **2204** for asynchronous access. In certain embodiments, for example where the automation confirmation circuit **2202** is positioned at least partially on the vehicle, receiving the collected data **2208** from the vehicle includes receiving the collected data **2208** from an end point of the vehicle that may be a separate end point from an end point hosting the portion of the automation confirmation circuit **2202**. The stored collected data **2204** may be stored on the vehicle, on a cloud server, and/or on a shared data store. In certain embodiments, the stored collected data **2204** is made available for a vehicle function, flow, application, or end point to access at a later time. In certain embodiments, the stored collected data **2204** is stored on a cloud server, and accessed by a vehicle function, flow, application, or end point at a later time, where at least a portion of the stored collected data **2204** is brought back to the vehicle at a later time (e.g., when requested). In certain embodiments, the stored collected data **2204** is made available for an external device, for example a cloud server application, fleet manager application, manufacturer application, or the like, for example to allow access to data for a number of vehicles together, for a fleet of vehicles, and/or for a machine learning process that performs an iterative improvement operation for the vehicle using the stored collected data **2204**. In certain embodiments, a portion of the stored collected data **2204** is provided, for example by the automation confirmation circuit **2202**, to the automation user interface **1504** in response to a user request (e.g., a request for the data, and/or a request by an application operated by the user for the data). In certain embodiments, a user receiving and/or requesting the stored collected data **2204** may be a distinct user from the user providing the automation request **1506**. In certain embodiments, a redacted portion of the stored collected data **2204** is provided to a vehicle function, flow, application, or end point, to an application operating on an external device, and/or to the automation user interface **1504**. In certain embodiments, the redacted portion of the data to be supplied, and/or the portion of the data to be supplied otherwise, may be stored on a separate data store (e.g., data store **116** versus data store **114**) from the stored collected data **2204**, which may include separate encryption and credentials. Operations to redact the stored collected data **2204** and/or to utilize segregated storage and/or credentials, allows for a convenient mechanism to limit exposure of users to certain data types (e.g., proprietary data, personally identifiable information, etc.), as well as protect the stored collected data **2204** from a security breach of the requesting user or device for the stored collected data **2204**. In certain embodiments, the automation confirmation circuit **2202** determines the redacted portion of the stored collected data **2204** in response to information such as: a characteristic **2206** of the stored collected data **2204** (e.g., proprietary information in the stored collected data **2204**, personally identifiable information in the stored collected data **2204**, and/or metadata in the stored collected data **2204**). In certain embodiments, a responsive data selection for display and/or selection on the automation user interface **1504** include one or more of: a confirmation value associated with the automated vehicle response, data collected pursuant to the automated vehicle response, and/or a modification value associated with the automated vehicle response.

(145) An example automation definition circuit **204** provides available input parameters in a menu of available input parameters. An example automation definition circuit **204** determines available input parameters in response to a user characteristic **2002**, such as a user role, user authorization, and/or an entity associated with the user. An example automation definition circuit **204** provides

automation recipe(s) to the automated user interface **1504**, and may further determine the automation description **212** in response to selection(s) and/or modification(s) of the automation recipe(s) by the user.

(146) Referencing FIG. **23**, an example automated user interface **1504** is depicted, which may be utilized to help users determine available parameters, to provide parameters to a workflow, to request specific parameter formatting, processing, and the like. The example automated user interface **1504** is depicted to illustrate certain aspects of the present disclosure, but is not limiting to embodiments herein. The example automated user interface **1504** includes an input parameter portion **2302**, allowing the user to confirm or select a parameter name, parameter units, parameter resolution (e.g., byte depth, but may instead be a precision description or the like), and/or a sampling rate for the parameter. In the example of FIG. **23**, optional action buttons are provided to allow the user to convenient set the parameter for data collection, to make the parameter available to a workflow, and/or to confirm or edit the data processing to be applied to the parameter. Some selections may not be available to the user based on permissions, authorizations, user characteristics, or the like—for example certain parameters, resolution values, sampling rate values, or the like. In certain embodiments, unavailable selections may be hidden from the automated user interface **1504**, and/or may be displayed in a distinct manner (e.g., grayed out values that cannot be selected in a menu). The example automated user interface **1504** includes an actuator parameter portion **2304**, including an actuator parameter name, available values, and/or a value type (e.g., Boolean, integer, etc.). The example actuator parameter portion **2304** allows a user to convenient confirm proper parameter notation in a workflow, and to make an actuation parameter available to a workflow. In the example of FIG. **23**, an action button is provided to allow a user to conveniently open a workflow creation window, and/or to review a list of available recipes.

(147) Referencing FIG. **24**, an example recipe access interface, which may be a part of an automated user interface **1504**, is schematically depicted. The example of FIG. **24** depicts which workflow and/or features are related to the recipe (e.g., which workflows use the recipe, and/or which workflows are included in the recipe), where each workflow includes one or more actions to be performed, and/or one or more triggers associated with the workflow.

(148) Referencing FIG. **25**, two example workflows are schematically depicted. A first workflow **2502** includes a single trigger and an action associated with the trigger. The example workflow **2502**, which may be a collection recipe, provides a convenient data collection format based on a trigger of interest. A second workflow **2504** includes a two-task sequence, with a trigger associated with each task, providing a convenient conditional data collection format based on triggers of interest. Referencing FIG. **26**, three example workflows **2602**, **2604**, **2606** are schematically depicted. The example of FIG. **26** illustrates the flexibility of workflow creation of embodiments herein, including allowing for sequenced tasks (workflow **2602**), branched tasks (workflow **2604**), and/or cyclical tasks **2606**. Referencing FIG. **27**, an example workflow is depicted as a state machine, with tasks associated with each state, and with transition conditions provided for transitioning between states. The displays of FIGS. **25-27** may be provided to an automated user interface **1504**, for example to allow a user to visualize, arrange, and edit workflows.

(149) Referencing FIG. **28**, an example system **2800** is schematically depicted to support implementation of automated vehicle response activity, for example including aspects of, and/or embodied in whole or part, by controllers and/or circuits herein that are configured to perform operations associated with the components depicted in the example of FIG. **28**. The example system **2800** includes a recipe manager **2802** configured to create a recipe (e.g., through interaction with a user exercising the automated user interface **1504**, and/or to create an auto-generated recipe to detect certain conditions, data elements, and/or to support data collection for machine learning operations designed to improve vehicle operations, detect fault conditions, or the like). The example system **2800** includes an analytics component including an analytics engine **2814**

configured to determine analytics **2812** such as trends, predict future failures, identify anomalous data (e.g., for a vehicle, a vehicle component, and/or related to an associated group of vehicles such as a model year, specific fleet, vehicles have a related role or duty cycle, etc.), which may be utilized to determine recipes, to suggest recipes (or tasks, workflows, or data collection activities), and/or to assist a user in determining whether a recipe (or task, workflow, or data collection activity) is likely to develop more information about a particular condition, and/or to provide useful information for a specific goal of the user.

(150) The example system **2800** includes a recipe processing engine **2804**, for example processing the recipe as an automation description **212**, and determining a trigger detection plan **610** and an automated action plan **222**. In the example system **2800**, the trigger detection plan **610** is provided to a trigger evaluation engine **2808**, and the automated action plan **222** is provided to a task execution engine **2806**. The example trigger evaluation engine **2808** processes the trigger detection plan **610** to determine when a task is indicated, and the example task execution engine **2806** processes the automated action plan **222** to perform the operations of the task described therein. The example system **2800** includes a data preparation engine **2810** that collects data related to the trigger evaluation and/or task execution, storage and/or caching associated with the data, processing associated with the data, and transmission of the data off-vehicle (e.g., back to the analytics engine **2814** in the example of FIG. **28**).

(151) Referencing FIG. **29**, an example trigger evaluation engine **2900** is schematically depicted. The example trigger evaluation engine **2900** may be utilized in a system **2800**, and/or may be embodied, in whole or part, by one or more circuits or controllers described herein and configured to perform operations of the trigger evaluation engine **2900**. The example trigger evaluation engine **2900** includes a support layer **2902**, which in the example of FIG. **29** manages communications, retrieving external data, configuring messages to a network zone, and the like. the example trigger evaluation engine **2900** includes an analysis layer **2904** configured to parse and/or extract relevant data, for example data utilized to determine whether the trigger condition is TRUE or FALSE. The example analysis layer **2904** is further configured to filter the data, for example utilizing a sampling of data, aspects of the data (e.g., maximum or minimum values, or the like), perform mapping of the data (e.g., comparing the data to relevant criteria and/or task operations for the data), and/or may further be configured to aggregate the data (e.g., summarization, moving averages, bucketed data, state values based on the whole of the data or aggregated subsets of the data, or the like), and/or to perform statistical analysis of the data (e.g., where statistical values are related to trigger thresholds, to determine outlier data, and/or to support heuristic triggers such as heuristics based on certain data effects, dynamics, likelihood that the data is meaningful, etc.). In the example of FIG. **29**, the trigger evaluation engine **2900** provides a trigger event value **1706**, for example providing an indication of whether the trigger condition has been met.

(152) Referencing FIG. **30**, an example task execution engine **3000** is schematically depicted. The example task execution engine **3000** may be utilized in a system **2800**, and/or may be embodied, in whole or part, by one or more circuits or controllers described herein and configured to perform operations of the task execution engine **3000**. The example task execution engine **3000** includes an action selection layer **3002**, for example selecting a task for execution based on trigger conditions, task priority, task hierarchy, or the like. The example task execution engine **3000** includes an action scheduling layer **3004**, for example scheduling the commencement, duration, ordering, and the like for a number of active tasks on the system **2800**. The example task execution engine **3000** includes an action initiation layer **3006**, for example commencing the operation of one or more actions for a task. The example task execution engine **3000** includes a support layer **3008**, controlling data communications, data storage, API interactions, database interactions, and/or service interactions (e.g., publishing and/or subscribing to service(s) related to tasks, for example to provide data utilized by the task, and/or to provide actions that may be available as a service and performed as a part of a task). The example task execution engine **3000** includes an action monitor layer **3010**, for

example determining a task state, task stage, determining confirmation values associated with the task, and/or determining an outcome of the task.

(153) Referencing FIG. 31, an example automated user interface **1504** is schematically depicted, providing an example interface that illustrates aspects of an example recipe and/or recipe creation interface. The example of FIG. 31 includes a recipe name (which may be a name such as “Morning seat adjustment recipe”), and a display area to depict data utilized by the recipe, and/or modifications made to the original data available in the unmodified recipe. The example of FIG. 31 further depicts a number of tasks included in the recipe (e.g., A, B, . . . H in FIG. 31), which in the example of FIG. 31 includes a description of a trigger for the task, actions performed by the task, and/or other tasks called by each given task. In the example of FIG. 31, a graphical depiction of the task relationships is depicted for the convenient reference of the user. In certain embodiments, the automated user interface **1504** is provided for user reference, for example by parsing a code block embodying the recipe, and/or the automated user interface **1504** may be interactive, for example allowing the user to edit the tasks, triggers for the tasks, actions associated with the tasks, and/or relationships between tasks—for example by text edits of the user in data fields, dragging and dropping tasks in the graphical portion, or the like.

(154) Referencing FIG. 32, an example apparatus **3200** includes a controller **3201** configured to provide automation continuity command(s) **3208**, for example to control interruption and/or recovery of tasks, workflows, and/or automated vehicle response activities. The example controller **3201** includes an automation management circuit **206** that provides an automated action plan **222**, an automation execution circuit **208** that provides an automation command **214** in response to the automated action plan **222**, and an automation continuity circuit **3202** that determines whether an automation interruption event **3206** has occurred. The example automation continuity circuit **3202** provides an automation continuity command **214** in response to the automation interruption event **3206**. Referencing FIG. 33, an example and non-limiting automation continuity command(s) **3208** include one or more of: a cancel command **3302** (e.g., the task is canceled, and will not be resumed, and/or will only be resumed based on future determined trigger conditions); a restart command **3304** (e.g., the task is stopped, and will be resumed when operating conditions are consistent with further progression of the task); a stage command **3306** (e.g., the task is stopped, and should be continued at a particular stage, whether in response to a future determined trigger condition and/or when operating conditions are consistent with further progression of the task—for example when relevant data collected in earlier stages of the task are likely to be still applicable to later stages of the task); and/or a continuation command **3308** (e.g., when an interrupted task can be continued, for example when a limiting value such as data storage availability is relieved). Example and non-limiting automation interruption event(s) **3206** include one or more of: determining that a vehicle shutdown event has occurred or is imminent; a determination that a vehicle operating condition precludes the completion of the automated action plan (e.g., data utilized for a later stage trigger or action is presently unavailable); a determination that a vehicle operating condition precludes the continuation of the automated action plan (e.g., data utilized for the present stage trigger or action is presently unavailable, and/or an operating condition is inconsistent with continuing the task); and/or a determination that a vehicle operating condition precludes the execution of at least one aspect of the automated action plan (e.g., a related task is interrupted, where the automated action plan including the currently contemplated task cannot be completed without the completion of the related task). In certain embodiments, the automated action plan **222** is provided as a part of a policy, where the policy includes a continuity description defining criteria to determine whether an interruption has occurred, and/or to adjust a response of the automation continuity circuit **3202** to an interruption of a task. For example, the policy may be utilized by a user to define global or default task interruption responses, responses for selected applications, flows, vehicle functions, end points, or the like.

(155) Referencing FIG. 34, an example apparatus **3400** includes a controller **3402** configured to

manage a service oriented architecture to support tasks, workflows, automated vehicle response activities, and the like. In certain embodiments, the controller **3402** manages a service oriented architecture for utilization by any end point, vehicle function, flow, or the like on the vehicle, and/or for utilization by an external device, for example accessing an automation user interface **1504** and allowing the user to publish services to the vehicle, and/or to subscribe to services available on the vehicle. Without limitation, a service may include a task, workflow, and/or automated vehicle response activity, for example providing a selected actuator response, an automated operation, a data collection operation, or the like.

(156) The example controller **3402** includes a storage manager circuit **3404** that selectively accesses a data store, and that is configured to selectively read data, write data, or edit data on the data store. The example data store may be on-vehicle, off-vehicle, or a combination. The example controller **3402** includes a storage gatekeeper circuit **3406** that interprets a data storage request value **3410** (e.g., from a flow, vehicle function, application, and/or end point), and provides a data storage profile **3418** in response to the data storage request value **3410**. For example, the data storage profile **3418** may indicate a reserved amount of memory, and/or a physical location of the memory (e.g., where a shared memory store is distributed across multiple physical devices). The determination of the data storage profile **3418** may be based upon one or more of a priority associated with a requestor of the data storage request value **310**, a priority of a supported flow, vehicle function, and/or end point by the requestor, and/or according to available storage on the system. The example storage manager circuit **3404** further performs reserving memory on the data store, and/or saving requestor associated data on the data store in response to the data storage profile **3418**.

(157) An example vehicle data storage requestor includes at least one of: an end point on a network zone of a vehicle; a flow associated with a vehicle; an application associated with a vehicle; or a vehicle controller positioned on a vehicle. An example data store includes a shared data store positioned on a controller of a vehicle, for example a single consolidated large memory, and/or a distributed data store that is collectively treated by the storage manager circuit **3404** as the shared data store. An example data store includes a shared data store positioned at least partially off the vehicle, which may be utilized for long-term data storage, low access frequency data storage, and/or to preserve data that would otherwise be lost due to operations related to aging data and/or limited available on-vehicle storage. An example data store is configured as a file system based shared storage, for example where stored data **3408** is stored in files (e.g., delimited files, XML files, and/or files stored in a database configured data file). An example storage gatekeeper circuit **3406** publishes available data storage as a service **3412** on a vehicle.

(158) An example storage gatekeeper circuit **3406** publishes data storage access as a service **3414** on a vehicle, and potentially to an automated user interface **1504**, and interprets the data storage request value **3410** in response to a subscription request **3416** for the data storage access (e.g., where the data storage is provided as a service, where data storage is obtained by appropriately subscribing to the data storage surface).

(159) An example storage gatekeeper circuit **3406** provides the data storage profile **3418** in response to a permissions value associated with the vehicle data storage requestor (e.g., a permissions value associated with a requesting flow, application, vehicle function, and/or end point). An example data storage profile **3418** further includes a parameter such as: a data storage amount; a data storage priority; and/or a data storage retention description. An example data store is configured, at least in part, as an object store. An example data store is configured, at least in part, as a relational database. An example data store is configured, at least in part, as a key-value store.

(160) An example storage gatekeeper circuit **3406** further publishes stored data **3408** on the data store as a service on a vehicle, and/or to an automated user interface **1504**. The example of FIG. **34** allows the storage gatekeeper circuit **3406** to provide data storage as a service, and/or to provide collected data, stored on the data store, as a service. The example storage gatekeeper circuit **3406**

controls access to data storage, and/or to the stored data, utilizing permissions associated with a requestor to regulate the data storage profile **3418**, a data access profile **3420**, and/or regulating approval to published services in response to the permissions. In certain embodiments, a published service may be regulated by allowing or disallowing a subscription to the published service, and/or by allowing or disallowing visibility of the published subscription based on permissions of the requestor or a prospective requestor (e.g., where the request cannot be made by an entity that does not have visibility).

(161) Referencing FIG. **35**, an example apparatus **3500** includes a controller **3502** configured to manage a service oriented architecture to support tasks, workflows, automated vehicle response activities, and the like. The example controller **3502** includes a service manager circuit **3504** that maintains a service registry **3516** including a listing of vehicle associated entities **3522** (e.g., a vehicle function, flow, application, and/or end point, and which may include off-vehicle entities such as a user interacting with an automated user interface **1504**). The example controller **3502** includes a service gatekeeper circuit **3506** that interprets a service request value **3510** from a vehicle service requestor **3520** (and/or certain off-vehicle requestors having sufficient permissions), and provides a service access profile **3518** in response to the service request value **3510**. An example service access profile **3518** includes a permission to access a service, and/or a permission to publish a service, for example utilized by the service manager circuit **3504** to update the service registry **3516** accordingly. The example controller **3502** includes a service execution circuit **3508** that allows a service publication **3514** and/or a service subscription **3512**, for example in response to the service request value **3510** and the service registry **3516**.

(162) An example service description, for example on the service registry **3516**, includes a vehicle function (e.g., an actuator, task, workflow, or the like) controllable by the service. An example service description includes vehicle data values provided by one or more end points on one or more network zones of the vehicle. An example service description includes vehicle data values provided by multiple end points, and distributed across at least two network zones of the vehicle. In certain embodiments, the at least two network zones include distinct network protocols, and/or distinct network types. An example service description includes vehicle data values provided, at least in part, by an off-vehicle end point. An example service description includes a vehicle related function performed, at least in part, by an off-vehicle end point. For example, some of the data may be determined off-vehicle, and/or certain vehicle related operations may be performed off-vehicle, for example longer cycle incremental improvement operations, operations for certain virtual sensors and/or determination of state parameters for the vehicle, and/or determination of parameters that rely, at least in part, on off-vehicle data (e.g., fuel costs, traffic information, weather information, geography-based and/or jurisdiction-based rules, regulations, preferences, or the like).

(163) The descriptions following depict various example procedures for performing operations to create and implement vehicle automated response activities. The example procedures may be performed utilizing any controllers, circuits, components, managers, engines, or the like as set forth throughout the present disclosure. The example procedures are non-limiting examples, and may be utilized in whole or part in certain embodiments. Operations of the example procedures may be omitted, combined in whole or part, and/or re-ordered in whole or part, as will be evident in view of the disclosure herein.

(164) Referencing FIG. **36**, an example procedure **3600** for providing an automation command is schematically depicted. The example procedure **3600** includes an operation **3602** to interpret an automation command, an operation **3604** to provide an automated action plan in response to the automation command, and an operation **3606** to provide an automation command in response to the automated action plan.

(165) Referencing FIG. **37**, an example procedure **3700** for providing an automation command is schematically depicted. The example procedure **3700** includes the operation **3602** and the operation **3604**, and further includes an operation **3702** to determine

whether an event has been detected. In response to operation **3702** indicating YES, the example procedure **3700** includes the operation **3606** to provide the automation command. In response to operation **3702** indicating NO, the example procedure **3700** continues operation **3702** (e.g., monitoring for the detection of the event).

(166) Referencing FIG. **38**, an example procedure **3800** to provide an automation command is schematically depicted. The example procedure **3800** includes an operation **3802** to interpret an automation description and an action description, where the automation description may further include a trigger description. The example procedure **3800** includes an operation **3804** to provide a trigger detection plan and an automation plan in response to the automation description (and/or trigger description) and the action description. The example procedure **3800** includes an operation **3806** to determine a trigger event value, and an operation **3606** to provide an automation command in response to the trigger event value.

(167) Referencing FIG. **39**, an example procedure **3900** to provide an automation command is schematically depicted. The example procedure **3900** includes the operation **3802** and operation **3804**, and further includes an operation **3902** to determine whether a trigger scheduling value is met. In response to operation **3902** indicating YES, the procedure **3900** includes an operation **3904** to provide a trigger evaluation command, operation **3806** to determine a trigger event value, and an operation **3906** to determine whether an automation scheduling value is met (e.g., where a delay period is applied after the trigger event before the automated operations are performed). In response to operation **3906** indicating YES, the procedure **3900** includes an operation **3906** to provide an automation command. In response to operation **3902** indicating NO, the example procedure **3900** continues operation **3902** (e.g., continuing to monitor against the trigger scheduling value). In response to operation **3906** indicating NO, the example procedure **3900** continues operation **3906** (e.g., continuing to monitor against the automation scheduling value).

(168) Referencing FIG. **40**, an example procedure **4000** to provide a task execution command is schematically depicted. The example procedure **4000** includes an operation **4002** to interpret a task description, an operation **4004** to provide a task action plan in response to the task description, and an operation **4006** to provide a task execution command in response to the task action plan.

(169) Referencing FIG. **41**, an example procedure **4100** for providing a task execution command is schematically depicted. The example procedure **4100** includes the operation **4002** and operation **4004**, and further includes operation **4102** to determine whether a task scheduling value and/or a task initiation value is met. In response to operation **4102** indicating YES, the example procedure **4100** includes operation **4006** to provide the task execution command. In response to operation **4102** indicating NO, the example procedure continues operation **4102** (e.g., continuing to monitor against the task scheduling value, and/or whether the task initiation value is met).

(170) Referencing FIG. **42**, an example procedure **4200** to provide an automation command is schematically depicted. The example procedure **4200** includes an operation **4202** to interpret an automation trigger description including a trigger time description, and an automation action description. The example procedure further includes the operation **3804** to provide a trigger detection plan and an automation plan, operation **3806** to determine a trigger event value, and the operation **3606** to provide an automation command.

(171) Referencing FIG. **43**, an example procedure **4300** to provide an automation command is schematically depicted. The example procedure **4300** is similar to procedure **3600**, **3800**, and/or **4200**. The example procedure **4300** further includes operation **4302** to store the automated action plan as a data file (e.g., providing an automated vehicle function that is parsed and/or implemented, without changing base software, firmware, or the like on a vehicle controller).

(172) Referencing FIG. **44**, an example procedure **4400** to provide confirmation of an automated vehicle operation, and/or to provide collected data associated with the automated vehicle operation, is schematically depicted. The example procedure **4400** includes a process to provide an automation command, for example and without limitation procedure **3600**. The example procedure

4400 includes an operation **4402** to store a policy responsive to the automated action plan (e.g., an updated policy, a dedicated policy for the automated action plan, and/or a new policy including the automated action plan as at least a portion thereof). The example procedure **4400** further includes an operation **4404** to provide a confirmation communication in response to implementation of the policy (e.g., confirming that the policy includes the automation plan, that the automation plan can be executed, and/or that the automation plan has been executed). The example procedure **4400** optionally includes an operation **4406** to provide collected data associated with the automation plan.

(173) Referencing FIG. **45**, an example procedure **4500** includes an operation **4502** to implement an automation user interface, an operation **4504** to interpret an automation request (e.g., a code block, data structure block, selected recipe, selected workflow, modified recipe, modified workflow, and/or interactively created automation description), an operation **4506** to determine an automation description **4506** in response to the automation request, and an operation **4508** to provide the automation description to a controller of a vehicle.

(174) Referencing FIG. **46**, an example procedure **4600** to selectively provide an automation description to a vehicle controller and/or to an automation definition circuit is schematically depicted. The example procedure **4600** includes an operation **4602** to determine whether an automation request can be fulfilled (e.g., if the requestor has authorization to implement the automation request, and/or whether the vehicle is capable to implement the automation request—for example due to resource limitations such as processing, network communication, and/or data storage, and/or due to operational limitations such as the unavailability of requested data, features, actuators, etc.). In response to operation **4602** indicating YES, the example procedure **4600** includes an operation **4604** to determine an automation description in response to the automation request, and an operation **4606** to provide the automation description. In response to operation **4602** indicating NO, the example procedure **4600** includes an operation **4608** to determine whether the automation request can be amended (e.g., whether the requestor allows an amendment, whether amended operations are available, such as a subset of operations, closely related or similar operations are available, and/or whether the priority of the automation request allows an amendment to be made). In response to operation **4608** indicating YES, the example procedure **4600** includes an operation **4610** to amend the automation request and determine the automation description in response to the amended automation request. Operation **4610** may optionally include providing a notification related to the amendment, for example to the requestor or to another entity such as a recipient or beneficiary of the automated operations. In response to operation **4608** determining NO, the example procedure **4600** includes an operation **4612** to refuse (or reject) the automation request—for example where no automation description will be provided based on the automation request. The example operation **4612** optionally includes providing a notification related to the refusal, for example to the requestor or to another entity such as a recipient or beneficiary of the automated operation, and/or an administrator of an automated user interface, a vehicle manufacturer, a security person, or the like.

(175) Referencing FIG. **47**, an example procedure **4700** to provide an automation command is schematically depicted. The example procedure **4700** includes an operation **4702** to interpret an automation trigger description and/or an automation action description, an operation **4704** to provide a trigger detection plan and/or an automated action plan in response to the description(s), an operation **4706** to provide a data storage command in response to the plan(s), and operation **4708** to confirm and/or reserve available data storage in response to the data storage command (e.g., to support trigger evaluations, event detections, and/or to support data collection operations of the automated operation described in the automated action plan). The example procedure **4700** further includes an operation **4710** to determine a trigger event value, and an operation **4712** to store trigger evaluation data. The example operation **4712** may optionally include managing aging data of the stored trigger evaluation data. The example procedure **4700** further includes an

operation **4714** to provide an automation command, for example in response to the plan(s). Referencing FIG. **48**, an example procedure **4800** is schematically depicted. In the example of FIG. **48**, the data storage command may additionally or alternatively include data storage sufficient to support data collected as a part of the automated action plan, where the procedure **4800** further includes an operation **4802** to store the automated collected data. The operation **4802** optionally includes managing aging data of the automated collected data.

(176) Referencing FIG. **49**, an example procedure **4900** includes an operation **4502** to implement an automation user interface, an operation **4902** to provide at least one recipe to the automation user interface, and an operation **4504** to interpret an automation request (e.g., as a selected one and/or modified one of the recipe(s) provided to the automation user interface). The example procedure **4900** further includes an operation **4506** to determine an automation description in response to the automation request, and an operation **4508** to provide the automation description to a controller of a vehicle.

(177) Referencing FIG. **50**, an example procedure **5000** includes an operation **5002** to interpret a number of automation descriptions, an operation **5004** to prioritize and/or apply a hierarchy between the number of automation descriptions, and an operation **5006** to determine an automated action plan in response to the prioritized and/or hierarchical automation descriptions.

(178) Referencing FIG. **51**, an example procedure **5100** includes an operation **5102** to deprecate at least one automation description (e.g., automation descriptions that have expired, that have already been completed or performed, that have no relevant scheduled actions or trigger conditions available, that no longer have a sufficient priority to be kept, that have been requested for removal such as by the requestor, and/or that can no longer be performed, for example due to a resource limitation, expiration of an authorization, or the like). The example procedure **5100** includes an operation **5104** to update an automated action plan, and/or a priority or hierarchy of the automated action plan, in response to the operation **5102** to deprecate the automated action plan. The example procedure **5106** further includes an operation **5106** to delete selected data in response to the updates of operation **5104**, for example deleting data that is no longer needed, deleting data due to a reduced priority of the automation description, or the like.

(179) Referencing FIG. **52**, an example procedure **5200** includes an operation **5202** to provide an automated action plan, an operation **5204** to provide automation commands in response to the automated action plan. The example procedure **5200** includes an operation **5206** to determine whether an interruption event of automated operations has occurred. In response to operation **5206** indicating YES, the procedure **5200** includes an operation **5208** to provide an automation continuity command, for example to continue, discontinue, pause, resume, perform data clean-up operations, or the like. In response to operation **5206** determining NO, the example procedure **5200** continues operation **5206** (e.g., continuing to monitor the automated operations for an interruption event).

(180) Referencing FIG. **53**, an example procedure **5300** includes an operation **5302** to interpret a data storage request value, an operation **5304** to provide a data storage profile in response to the data storage request value, and an operation **5306** to reserve memory, confirm memory storage, and/or store data (e.g., trigger evaluation data, automated collected data, and/or other associated data with an automated vehicle response) in response to the data storage profile.

(181) Referencing FIG. **54**, an example procedure **5400** includes operation **5302** and operation **5304**, and further includes an operation **5402** to reserve memory and/or store data in response to the data storage profile. The example procedure **5400** further includes an operation **5404** to publish the stored data as a service, and/or an operation **5406** to publish available data storage as a service.

(182) Referencing FIG. **55**, an example procedure **5500** includes an operation **5502** to maintain a service registry (e.g., listing entities such as end points, controllers, flows, applications, etc., and corresponding service(s) for the listed entities), and an operation **5504** to interpret a service request value from a vehicle service requestor (e.g., a requesting end point, flow, application, controller,

etc.). The example procedure **5500** includes an operation **5506** to provide a service access profile, an operation **5508** to update the service registry in response to the service access profile, and an operation **5510** to selectively allow a service publication (e.g., allow an entity to publish a service) and/or a service subscription (e.g., allow an entity to subscribe to a service) in response to the updated service registry.

(183) An example embodiment includes a cloud-side executed vehicle automation manager, which can be utilized to create, delete, and/or query vehicle automation descriptions, such as a recipe, automation description, workflow, or the like. The example cloud-side executed vehicle automation manager may be embodied in any controllers, circuits, components, managers, engines, or the like as set forth throughout the present disclosure. In certain embodiments, a vehicle automation description may be stored in a data store accessible to a cloud server, and selectively sent to the vehicle for execution. In certain embodiments, a single vehicle automation description may be active on the vehicle at a given time, although embodiments support multiple vehicle automation descriptions at a given time, and/or multiple automated functions contained within a vehicle automation description. In certain embodiments, the cloud-side executed vehicle automation manager is configured to receive reports about the status, execution, and/or results of vehicle automated response activity. An example cloud-side executed vehicle automation manager provides a function, for example implemented on an automation user interface, to allow for querying of deployments of vehicle automation descriptions on vehicles associated with the cloud server, for example including time values (e.g., related to communicating vehicle automation descriptions to vehicles, time of execution, time of removal, etc.), content of the vehicle automation descriptions, and vehicle details to allow for identification of the associated vehicles. In certain embodiments, the cloud-side executed automation manager allows for the determination of vehicle automation description status and/or statistics, such as time frames, execution status, execution results, and the like, as well as identification of off-nominal cases (e.g., where vehicles have refused or not been able to intake and/or execute operations for the vehicle automation description). In certain embodiments, a cloud-side executed automation manager may be implemented on a mini-cloud device, for example a device in direct communication with the vehicle (e.g., a hard connection, such as an ethernet or CAN connection, and/or a wireless connection such as a WiFi connection or a Bluetooth connection), for example to provide cloud level capability when the vehicle is not capable, or it is not desirable, for the vehicle to communicate fully to the cloud. In certain embodiments, an external device embodying the mini-cloud device can selectively couple to the cloud server at a later time, syncing up information from the automation management operations performed with the vehicle.

(184) The example embodiments herein provide for the ability to create, implement, get status information, verify, and/or troubleshoot automated operations for a vehicle, including by users that do not have vehicle specific information such as an understanding of the control algorithms, parameter names, network names and/or locations of end points, sensors, actuators, etc. on the vehicle. Automated operations for the vehicle, in certain embodiments, are organized into one or more workflows, each workflow having one or more tasks, and each task having one or more related actions. In certain embodiments, plans (and/or an automated description, and/or a recipe) as utilized herein include a number of workflows utilized to implement the plan. The nomenclature utilized to organize the automated operations are not limiting, but the example nomenclature is utilized for clarity to illustrate aspects of the present disclosure. An example organization includes the workflow having a schedule and/or associated trigger evaluation utilized to determine when the workflow should be commenced, which may be determined according to any aspects of the description, such as a time based determination, a determination based upon operating conditions (e.g., vehicle operating conditions and/or external operating conditions), a determination based upon a specific request (e.g., by an operator, user of an automated user interface, service personnel, manufacturer, etc.), and/or a determination based upon a detected event. In the example

organization, a number of tasks may be performed by the workflow, where some or all of the tasks may each have a schedule and/or associated trigger evaluation utilized to determine when each task should be commenced. In certain embodiments, multiple tasks may be evaluated against a schedule and/or associated trigger simultaneously (e.g., checking multiple tasks simultaneously to determine whether a given task is ready to commence execution). The example organization includes each task having a number of actions, for example specific operations such as the movement of an actuator, collection and/or interpretation of a data element, providing a communication, or the like. The actions for a task may be scheduled, and may include actions performed in parallel, in serial, with looping or cycling operations, or the like. In certain embodiments, the actions of a given task are performed before another task is commenced, although in certain embodiments more than one task may be executed at the same time.

(185) In a further example, the progression of a workflow at any level (e.g., task level, action level, and/or global workflow level) may be reported as a status value, for example as data collected and/or as trigger evaluation data, allowing for a user to confirm the progression and/or status of the workflow, to perform statistical analysis for the workflow (e.g., for the vehicle, and/or across a group of vehicles), and/or to troubleshoot the workflow, task, or action, for example to see where the workflow, task, or action had a problem, and/or to see what else was happening on the vehicle at the time of the problem and/or before the problem occurred. In certain embodiments, notifications may be provided for detected events, selected status values, and/or error values during the performance of a workflow, task, or action. In certain embodiments, detected events, selected status values, and/or error values may be utilized to trigger additional workflows or tasks, for example to collect relevant data, to determine effects of the problem on the vehicle or for a system including the vehicle, or the like. In certain embodiments, progression data about a workflow and/or task, status data, other operating condition data relevant to the workflow and/or task (e.g., before, during, or after) may be utilized for future development and/or iterative improvement, for example to make the implementation and/or execution of tasks or workflows more efficient, more effective, and/or to reduce undesirable side effects of the task and/or workflow.

(186) As set forth throughout the present disclosure, data observed and/or collected in relation to a task or workflow, for example trigger evaluation data, event detection data, and/or directly utilized data (e.g., data utilized as a parameter for an action) may be data present on the vehicle, data external to the vehicle, and/or data created on the vehicle or externally (e.g., a virtual sensor, determined state value, etc.) to specifically support the task or workflow, and/or to support selected capability for the automation user interface (e.g., to give users a specific type of information for utilization in workflows, recipes, and/or automation descriptions). Additionally or alternatively, any action may be performed on the vehicle or may be performed off the vehicle (e.g., opening a door, interacting with a camera, sending a notification, etc.). Without limitation to any other aspect of the present disclosure, an action may be implemented by an automation command as set forth throughout the present disclosure.

(187) In certain embodiments, the creation of a recipe, workflow, automation description, or the like, as set forth herein, further provides for the creation of constants and/or variables which may be utilized in workflows, tasks, actions, or other automated operations as set forth herein. In certain embodiments, constants and/or variables may be created in a manner similar to the inclusion of input parameters (e.g., reference FIG. 23 and the related description). In certain embodiments, the scope of a constant and/or variable may be selectable, for example making the constant and/or variable available to any workflow, available to any task within a workflow, and/or available to any action within a task. In certain embodiments, a variable may be any value that is capable to hold selectable values, and/or where a task, workflow, and/or action can write values to the variable. In certain embodiments, some tasks, actions, or workflows may have write access to a variable, where other tasks, actions, or workflows may have only read access to a given variable. In certain embodiments, a constant or variable may be determined from, or represent, a value related to the

vehicle or an external data value that is also otherwise available on the vehicle (e.g., for convenience in developing the task, workflow, or action), or may be a value that is not related to a value already available on the vehicle or as an external data value (e.g., parameters that are utilized to implement the task, workflow, or action).

(188) Without limitation to any other aspect of the present disclosure, a workflow, automation description, plan, or the like may be implemented at a file—for example a JSON file setting forth the operations of the workflow, automation description, or plan. In certain embodiments, other types of data structures may be utilized, such as an XML file, a script, or the like. In certain embodiments, the workflow, automation description, and/or plan may be created in a domain specific language, for example a proprietary language utilized to implement automated vehicle operations, for example a language created for convenient reading and understanding by the user, including for users that may not have sophisticated knowledge of programming operations, and/or to create an easily understandable environment for the user to understand the vehicle and/or the automated operations being created and/or implemented. In certain embodiments, the automated user interface may be configured to support graphical creation and/or modification of recipes, descriptions, plans, or the like.

(189) Network and/or communication resources include, without limitation, local area network, wide area network, wireless, internet, or any other known communication resources and protocols. Example and non-limiting hardware and/or computing devices include, without limitation, a general purpose computer, a server, an embedded computer, a mobile device, a virtual machine, and/or an emulated computing device. A computing device may be a distributed resource included as an aspect of several devices, included as an interoperable set of resources to perform described functions of the computing device, such that the distributed resources function together to perform the operations of the computing device. In certain embodiments, each computing device may be on separate hardware, and/or one or more hardware devices may include aspects of more than one computing device, for example as separately executable instructions stored on the device, and/or as logically partitioned aspects of a set of executable instructions, with some aspects comprising a part of one of a first computing device, and some aspects comprising a part of another of the computing devices.

(190) A computing device may be part of a server, client, network infrastructure, mobile computing platform, stationary computing platform, or other computing platform. A processor may be any kind of computational or processing device capable of executing program instructions, codes, binary instructions and the like. The processor may be or include a signal processor, digital processor, embedded processor, microprocessor or any variant such as a co-processor (math co-processor, graphic co-processor, communication co-processor and the like) and the like that may directly or indirectly facilitate execution of program code or program instructions stored thereon. In addition, the processor may enable execution of multiple programs, threads, and codes. The threads may be executed simultaneously to enhance the performance of the processor and to facilitate simultaneous operations of the application. By way of implementation, methods, program codes, program instructions and the like described herein may be implemented in one or more threads. The thread may spawn other threads that may have assigned priorities associated with them; the processor may execute these threads based on priority or any other order based on instructions provided in the program code. The processor may include memory that stores methods, codes, instructions and programs as described herein and elsewhere. The processor may access a storage medium through an interface that may store methods, codes, and instructions as described herein and elsewhere. The storage medium associated with the processor for storing methods, programs, codes, program instructions or other type of instructions capable of being executed by the computing or processing device may include but may not be limited to one or more of a CD-ROM, DVD, memory, hard disk, flash drive, RAM, ROM, cache and the like.

(191) A processor may include one or more cores that may enhance speed and performance of a

multiprocessor. In embodiments, the process may be a dual core processor, quad core processors, other chip-level multiprocessor and the like that combine two or more independent cores (called a die).

(192) The methods and systems described herein may be deployed in part or in whole through a machine that executes computer readable instructions on a server, client, firewall, gateway, hub, router, or other such computer and/or networking hardware. The computer readable instructions may be associated with a server that may include a file server, print server, domain server, internet server, intranet server and other variants such as secondary server, host server, distributed server and the like. The server may include one or more of memories, processors, computer readable transitory and/or non-transitory media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing other servers, clients, machines, and devices through a wired or a wireless medium, and the like. The methods, programs, or codes as described herein and elsewhere may be executed by the server. In addition, other devices required for execution of methods as described in this application may be considered as a part of the infrastructure associated with the server.

(193) The server may provide an interface to other devices including, without limitation, clients, other servers, printers, database servers, print servers, file servers, communication servers, distributed servers, and the like. Additionally, this coupling and/or connection may facilitate remote execution of instructions across the network. The networking of some or all of these devices may facilitate parallel processing of program code, instructions, and/or programs at one or more locations without deviating from the scope of the disclosure. In addition, all the devices attached to the server through an interface may include at least one storage medium capable of storing methods, program code, instructions, and/or programs. A central repository may provide program instructions to be executed on different devices. In this implementation, the remote repository may act as a storage medium for methods, program code, instructions, and/or programs.

(194) The methods, program code, instructions, and/or programs may be associated with a client that may include a file client, print client, domain client, internet client, intranet client and other variants such as secondary client, host client, distributed client and the like. The client may include one or more of memories, processors, computer readable transitory and/or non-transitory media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing other clients, servers, machines, and devices through a wired or a wireless medium, and the like. The methods, program code, instructions, and/or programs as described herein and elsewhere may be executed by the client. In addition, other devices required for execution of methods as described in this application may be considered as a part of the infrastructure associated with the client.

(195) The client may provide an interface to other devices including, without limitation, servers, other clients, printers, database servers, print servers, file servers, communication servers, distributed servers, and the like. Additionally, this coupling and/or connection may facilitate remote execution of methods, program code, instructions, and/or programs across the network. The networking of some or all of these devices may facilitate parallel processing of methods, program code, instructions, and/or programs at one or more locations without deviating from the scope of the disclosure. In addition, all the devices attached to the client through an interface may include at least one storage medium capable of storing methods, program code, instructions, and/or programs. A central repository may provide program instructions to be executed on different devices. In this implementation, the remote repository may act as a storage medium for methods, program code, instructions, and/or programs.

(196) The methods and systems described herein may be deployed in part or in whole through network infrastructures. The network infrastructure may include elements such as computing devices, servers, routers, hubs, firewalls, clients, personal computers, communication devices, routing devices and other active and passive devices, modules, and/or components as known in the

art. The computing and/or non-computing device(s) associated with the network infrastructure may include, apart from other components, a storage medium such as flash memory, buffer, stack, RAM, ROM and the like. The methods, program code, instructions, and/or programs described herein and elsewhere may be executed by one or more of the network infrastructural elements.

(197) The methods, program code, instructions, and/or programs described herein and elsewhere may be implemented on a cellular network having multiple cells. The cellular network may either be frequency division multiple access (FDMA) network or code division multiple access (CDMA) network. The cellular network may include mobile devices, cell sites, base stations, repeaters, antennas, towers, and the like.

(198) The methods, program code, instructions, and/or programs described herein and elsewhere may be implemented on or through mobile devices. The mobile devices may include navigation devices, cell phones, mobile phones, mobile personal digital assistants, laptops, palmtops, netbooks, pagers, electronic books readers, music players and the like. These devices may include, apart from other components, a storage medium such as a flash memory, buffer, RAM, ROM and one or more computing devices. The computing devices associated with mobile devices may be enabled to execute methods, program code, instructions, and/or programs stored thereon. Alternatively, the mobile devices may be configured to execute instructions in collaboration with other devices. The mobile devices may communicate with base stations interfaced with servers and configured to execute methods, program code, instructions, and/or programs. The mobile devices may communicate on a peer to peer network, mesh network, or other communications network. The methods, program code, instructions, and/or programs may be stored on the storage medium associated with the server and executed by a computing device embedded within the server. The base station may include a computing device and a storage medium. The storage device may store methods, program code, instructions, and/or programs executed by the computing devices associated with the base station.

(199) The methods, program code, instructions, and/or programs may be stored and/or accessed on machine readable transitory and/or non-transitory media that may include: computer components, devices, and recording media that retain digital data used for computing for some interval of time; semiconductor storage known as random access memory (RAM); mass storage typically for more permanent storage, such as optical discs, forms of magnetic storage like hard disks, tapes, drums, cards and other types; processor registers, cache memory, volatile memory, non-volatile memory; optical storage such as CD, DVD; removable media such as flash memory (e.g. USB sticks or keys), floppy disks, magnetic tape, paper tape, punch cards, standalone RAM disks, Zip drives, removable mass storage, off-line, and the like; other computer memory such as dynamic memory, static memory, read/write storage, mutable storage, read only, random access, sequential access, location addressable, file addressable, content addressable, network attached storage, storage area network, bar codes, magnetic ink, and the like.

(200) Certain operations described herein include interpreting, receiving, and/or determining one or more values, parameters, inputs, data, or other information (“receiving data”). Operations to receive data include, without limitation: receiving data via a user input; receiving data over a network of any type; reading a data value from a memory location in communication with the receiving device; utilizing a default value as a received data value; estimating, calculating, or deriving a data value based on other information available to the receiving device; and/or updating any of these in response to a later received data value. In certain embodiments, a data value may be received by a first operation, and later updated by a second operation, as part of the receiving a data value. For example, when communications are down, intermittent, or interrupted, a first receiving operation may be performed, and when communications are restored an updated receiving operation may be performed.

(201) Certain logical groupings of operations herein, for example methods or procedures of the current disclosure, are provided to illustrate aspects of the present disclosure. Operations described

herein are schematically described and/or depicted, and operations may be combined, divided, re-ordered, added, or removed in a manner consistent with the disclosure herein. It is understood that the context of an operational description may require an ordering for one or more operations, and/or an order for one or more operations may be explicitly disclosed, but the order of operations should be understood broadly, where any equivalent grouping of operations to provide an equivalent outcome of operations is specifically contemplated herein. For example, if a value is used in one operational step, the determining of the value may be required before that operational step in certain contexts (e.g. where the time delay of data for an operation to achieve a certain effect is important), but may not be required before that operation step in other contexts (e.g. where usage of the value from a previous execution cycle of the operations would be sufficient for those purposes). Accordingly, in certain embodiments an order of operations and grouping of operations as described is explicitly contemplated herein, and in certain embodiments re-ordering, subdivision, and/or different grouping of operations is explicitly contemplated herein.

(202) The methods and systems described herein may transform physical and/or or intangible items from one state to another. The methods and systems described herein may also transform data representing physical and/or intangible items from one state to another.

(203) The methods and/or processes described above, and steps thereof, may be realized in hardware, program code, instructions, and/or programs or any combination of hardware and methods, program code, instructions, and/or programs suitable for a particular application. The hardware may include a dedicated computing device or specific computing device, a particular aspect or component of a specific computing device, and/or an arrangement of hardware components and/or logical circuits to perform one or more of the operations of a method and/or system. The processes may be realized in one or more microprocessors, microcontrollers, embedded microcontrollers, programmable digital signal processors or other programmable device, along with internal and/or external memory. The processes may also, or instead, be embodied in an application specific integrated circuit, a programmable gate array, programmable array logic, or any other device or combination of devices that may be configured to process electronic signals. It will further be appreciated that one or more of the processes may be realized as a computer executable code capable of being executed on a machine readable medium.

(204) The computer executable code may be created using a structured programming language such as C, an object oriented programming language such as C++, or any other high-level or low-level programming language (including assembly languages, hardware description languages, and database programming languages and technologies) that may be stored, compiled or interpreted to run on one of the above devices, as well as heterogeneous combinations of processors, processor architectures, or combinations of different hardware and computer readable instructions, or any other machine capable of executing program instructions.

(205) Thus, in one aspect, each method described above and combinations thereof may be embodied in computer executable code that, when executing on one or more computing devices, performs the steps thereof. In another aspect, the methods may be embodied in systems that perform the steps thereof, and may be distributed across devices in a number of ways, or all of the functionality may be integrated into a dedicated, standalone device or other hardware. In another aspect, the means for performing the steps associated with the processes described above may include any of the hardware and/or computer readable instructions described above. All such permutations and combinations are intended to fall within the scope of the present disclosure.

(206) While the disclosure has been disclosed in connection with certain embodiments shown and described in detail, various modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present disclosure is not to be limited by the foregoing examples, but is to be understood in the broadest sense allowable by law.

Claims

1. An apparatus, comprising: a controller, comprising: an automation definition circuit structured to implement an automation user interface, and to interpret an automation request in response to user communications with the automation user interface; an automation management circuit structured to: determine whether the automation request is authorized based on at least one of vehicle capability or resource availability; in response to determining that the automation request is not authorized, evaluate whether the automation request is eligible for amendment based on one or more amendment criteria; and in response to determining that the automation request is eligible for amendment, amend the automation request and determine an automation description in response to the amended automation request; and an automation command circuit structured to provide the automation description to a controller of a vehicle, wherein the controller of the vehicle is configured to implement an automated vehicle response, responsive to the automation description.
2. The apparatus of claim 1, wherein the automation management circuit is further structured to confirm the authorization in response to at least one of: data to be collected for the automated vehicle response; data to be provided on a network of the vehicle for the automated vehicle response; an actuator to be accessed for the automated vehicle response; a service to be accessed for the automated vehicle response; a flow to be accessed for the automated vehicle response; an application to be accessed for the automated vehicle response; or an operational impact associated with the automated vehicle response.
3. The apparatus of claim 1, wherein the automation management circuit is further structured to determine the automation description as an amended version of the automation request in response to the authorization.
4. The apparatus of claim 3, wherein the automation definition circuit is further structured to provide an amendment communication to the automation user interface in response to the amended version of the automation request.
5. The apparatus of claim 1, wherein the automation management circuit is further structured to refuse the automation request in response to the authorization.
6. The apparatus of claim 5, wherein the automation management circuit is further structured to provide a refusal communication to the automation user interface in response to the refusal of the automation request.
7. The apparatus of claim 1, wherein the automation command circuit is further structured to provide the automation description as one of a policy or a policy update.
8. The apparatus of claim 1, wherein the automation command circuit is further structured to receive a confirmation communication from the controller of the vehicle.
9. The apparatus of claim 1, wherein the automation definition circuit is further structured to provide a confirmation communication to the automation user interface.
10. A method, comprising: implementing an automation user interface; interpreting an automation request in response to user communications with the automation user interface; determining whether the automation request is authorized based on at least one of vehicle capability or resource availability; in response to determining that the automation request is not authorized, evaluating whether the automation request is eligible for amendment based on one or more amendment criteria; and in response to determining that the automation request is eligible for amendment, amending the automation request and determining an automation description in response to the amended automation request; and providing the automation description to a controller of a vehicle, wherein the controller of the vehicle is configured to implement an automated vehicle response, responsive to the automation description.
11. The method of claim 10, wherein confirming the authorization in response to at least one of: data to be collected for the automated vehicle response; data to be provided on a network of the

vehicle for the automated vehicle response; an actuator to be accessed for the automated vehicle response; a service to be accessed for the automated vehicle response; a flow to be accessed for the automated vehicle response; an application to be accessed for the automated vehicle response; or an operational impact associated with the automated vehicle response.

12. The method of claim 10, wherein determining an automation description comprises: determining the automation description as an amended version of the automation request in response to the authorization.

13. The method of claim 12 further comprising: providing an amendment communication to the automation user interface in response to the amended version of the automation request.

14. The method of claim 10, wherein providing the automation description comprises: providing the automation description as one of a policy or a policy update.

15. The method of claim 10 further comprising: receiving a confirmation communication from the controller of the vehicle.

16. The method of claim 10 further comprising: providing a confirmation communication to the automation user interface.

17. A non-transitory computer-readable medium storing instructions that, when loaded into at least one processor, cause the at least one processor to: implement an automation user interface; interpret an automation request in response to user communications with the automation user interface; determine whether the automation request is authorized based on at least one of vehicle capability or resource availability; in response to determining that the automation request is not authorized, evaluate whether the automation request is eligible for amendment based on one or more amendment criteria; and in response to determining that the automation request is eligible for amendment, amend the automation request and determine an automation description in response to the amended automation request; and provide the automation description to a controller of a vehicle, wherein the controller of the vehicle is configured to implement an automated vehicle response, responsive to the automation description.
