

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415716
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Thomas; Aaron et al.

Automated beverage dispenser system and method

Abstract

A beverage production system is provided that includes a turntable assembly comprising a central axis. The turntable assembly further includes an inner turntable and an outer turntable disposed circumferentially about the inner turntable. The beverage production system also includes a cup dispensing station configured to dispense cups onto one of the inner or outer turntables. The beverage production system also includes a beverage dispensing station configured to dispense a beverage into the cups.

Inventors: Thomas; Aaron (Louisville, KY), Szatrowski; Karl Thomas (Louisville, KY), Wyer; Hunter Patrick (Lexington, SC), Dulcie; Zachary Logan (Columbia, SC), Hance, Jr.; James Timothy (Columbia, SC), Phillips; Grant Rorie (Columbia, SC), Brown; Paul Christopher (Elgin, SC), Ahring; Mark William (Columbia, SC), Gilliam; Sarah Kathrine (Charleston, SC)

Applicant: YUM CONNECT, LLC (Louisville, KY)

Family ID: 1000008818992

Assignee: YUM CONNECT, LLC (Louisville, KY)

Appl. No.: 18/306848

Filed: April 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240359964 A1	Oct. 31, 2024

Publication Classification

Int. Cl.: B67D3/00 (20060101)

U.S. Cl.:

CPC **B67D3/0016** (20130101); **B67D3/0003** (20130101); **B67D3/0074** (20130101);
B67D3/0077 (20130101); **B67D3/0083** (20130101); **B67D3/009** (20130101);
B67D3/0096 (20130101); B67D2210/00041 (20130101); B67D2210/00076 (20130101);
B67D2210/00078 (20130101); B67D2210/00144 (20130101)

Field of Classification Search

CPC: B67D (3/009); B67D (3/0083); B67D (2210/00078); B67D (2210/00041)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1442983	12/1922	Smith	N/A	N/A
2497748	12/1949	Von Stoesser	N/A	N/A
2699281	12/1954	Duke	N/A	N/A
2814317	12/1956	Gale	N/A	N/A
2953171	12/1959	Arnett et al.	N/A	N/A
2969632	12/1960	Carew et al.	N/A	N/A
3308602	12/1966	Dubie et al.	N/A	N/A
3364959	12/1967	Herman et al.	N/A	N/A
3367959	12/1967	Fetscher et al.	N/A	N/A
3545173	12/1969	Christine et al.	N/A	N/A
3838805	12/1973	Amberg	N/A	N/A
4098058	12/1977	Carrigan et al.	N/A	N/A
4282698	12/1980	Zimmermann	N/A	N/A
4319441	12/1981	Credle	N/A	N/A
4345412	12/1981	Balzer et al.	N/A	N/A
4590975	12/1985	Credle, Jr.	N/A	N/A
4738290	12/1987	Ciekanski	N/A	N/A
4944337	12/1989	Credle, Jr. et al.	N/A	N/A
4949526	12/1989	Brojna et al.	N/A	N/A
4951719	12/1989	Wiley et al.	N/A	N/A
4961447	12/1989	Credle, Jr. et al.	N/A	N/A
4989753	12/1990	Brojna et al.	N/A	N/A
5000345	12/1990	Brojna et al.	N/A	N/A
5058630	12/1990	Wiley et al.	N/A	N/A
5249410	12/1992	Bakker et al.	N/A	N/A
5350082	12/1993	Kiriakides, Jr. et al.	N/A	N/A
5996316	12/1998	Kirschner	N/A	N/A
6045007	12/1999	Simmons	N/A	N/A
6053359	12/1999	Goulet et al.	N/A	N/A
6102246	12/1999	Goulet et al.	N/A	N/A
6152325	12/1999	Edwards	N/A	N/A
6286720	12/2000	Simmons et al.	N/A	N/A
6345729	12/2001	Santy, Jr.	N/A	N/A

6418701	12/2001	Navarro	N/A	N/A
6442954	12/2001	Shapiro et al.	N/A	N/A
6490845	12/2001	Tyreman	N/A	N/A
6607096	12/2002	Glass et al.	N/A	N/A
6940845	12/2004	Benveniste	N/A	N/A
6983863	12/2005	Santy, Jr.	N/A	N/A
7089718	12/2005	Biba et al.	N/A	N/A
7168593	12/2006	Schroeder et al.	N/A	N/A
7334706	12/2007	Schroeder et al.	N/A	N/A
7373784	12/2007	Haskayne	N/A	N/A
7600360	12/2008	Schroeder et al.	N/A	N/A
7624895	12/2008	Haskayne	N/A	N/A
7669732	12/2009	Njaastad	N/A	N/A
7810676	12/2009	Romanyszyn et al.	N/A	N/A
7813834	12/2009	Sudolcan et al.	N/A	N/A
7997048	12/2010	Bernhard	N/A	N/A
8006464	12/2010	Krulitsch	N/A	N/A
8025184	12/2010	Minard et al.	N/A	N/A
8091737	12/2011	Smeller et al.	N/A	N/A
D657369	12/2011	Hecht et al.	N/A	N/A
D657370	12/2011	Hecht et al.	N/A	N/A
D657371	12/2011	Hecht et al.	N/A	N/A
8225960	12/2011	Njaastad et al.	N/A	N/A
8245488	12/2011	Dunn	N/A	N/A
8448823	12/2012	Engels et al.	N/A	N/A
8490834	12/2012	Edwards et al.	N/A	N/A
8511478	12/2012	Terzini	N/A	N/A
8606396	12/2012	Claesson et al.	N/A	N/A
8607831	12/2012	Doglioni Majer	N/A	N/A
8756950	12/2013	Brunner et al.	N/A	N/A
8807392	12/2013	Smeller et al.	N/A	N/A
9010579	12/2014	Baker et al.	N/A	N/A
9045323	12/2014	Crane et al.	N/A	N/A
9132929	12/2014	Nash	N/A	N/A
9141562	12/2014	Pickett et al.	N/A	N/A
9204734	12/2014	Jablonski et al.	N/A	N/A
9227830	12/2015	Angus et al.	N/A	N/A
9242776	12/2015	Mikula	N/A	N/A
9285149	12/2015	Bamberger et al.	N/A	N/A
9290371	12/2015	Crane et al.	N/A	N/A
9327958	12/2015	Angus et al.	N/A	N/A
9346659	12/2015	Brown	N/A	N/A
9364114	12/2015	Claesson et al.	N/A	N/A
9511988	12/2015	Hernandez et al.	N/A	N/A
9566776	12/2016	Mikula	N/A	N/A
9588608	12/2016	Hecht et al.	N/A	N/A
9622615	12/2016	Hecht et al.	N/A	N/A
9624460	12/2016	Wunder	N/A	N/A
9643828	12/2016	Brown et al.	N/A	N/A
9656226	12/2016	Solera et al.	N/A	N/A

9656849	12/2016	Hawken	N/A	N/A
9675206	12/2016	Minard	N/A	N/A
9878891	12/2017	Balzarín et al.	N/A	N/A
9932216	12/2017	Hernandez et al.	N/A	N/A
9944472	12/2017	Crane et al.	N/A	N/A
9994340	12/2017	Angus et al.	N/A	N/A
10005655	12/2017	Broen et al.	N/A	N/A
10012345	12/2017	Derby et al.	N/A	N/A
10031505	12/2017	Martindale et al.	N/A	N/A
10182587	12/2018	Lundberg et al.	N/A	N/A
10183854	12/2018	Tuyls et al.	N/A	N/A
10239742	12/2018	Dresser et al.	N/A	N/A
10351409	12/2018	Smeller et al.	N/A	N/A
10407292	12/2018	Hecht et al.	N/A	N/A
10442671	12/2018	Hecht et al.	N/A	N/A
10489868	12/2018	Long, II	N/A	N/A
10494246	12/2018	Hecht et al.	N/A	N/A
10507941	12/2018	Seversky et al.	N/A	N/A
10577235	12/2019	Hecht et al.	N/A	N/A
10626003	12/2019	Wyatt et al.	N/A	N/A
10654700	12/2019	Hecht	N/A	N/A
10654703	12/2019	Hecht et al.	N/A	N/A
10676337	12/2019	Hecht	N/A	N/A
10689240	12/2019	Schultz et al.	N/A	N/A
10689241	12/2019	Dresser et al.	N/A	N/A
10752448	12/2019	Yoder et al.	N/A	N/A
10865093	12/2019	Yang	N/A	N/A
10988270	12/2020	Gorbatenko et al.	N/A	N/A
11053109	12/2020	Knight et al.	N/A	N/A
11116352	12/2020	Herbert et al.	N/A	N/A
11208313	12/2020	Conover et al.	N/A	N/A
11208316	12/2020	Dresser et al.	N/A	N/A
11305977	12/2021	O'Nan et al.	N/A	N/A
11311138	12/2021	Huang et al.	N/A	N/A
11338444	12/2021	Ostrow et al.	N/A	N/A
11358742	12/2021	Vari	N/A	N/A
11440785	12/2021	Schultz et al.	N/A	N/A
11472579	12/2021	Cittadino et al.	N/A	N/A
11548667	12/2022	Cittadino et al.	N/A	N/A
11629042	12/2022	Robinson et al.	N/A	N/A
11738987	12/2022	Degnan et al.	N/A	N/A
11794998	12/2022	Sirbu Villa	N/A	N/A
11802038	12/2022	Cole	N/A	N/A
11814278	12/2022	Conover et al.	N/A	N/A
11897748	12/2023	Kleinrichert	N/A	N/A
11897751	12/2023	Robinson et al.	N/A	N/A
2003/0192912	12/2002	Chadwell et al.	N/A	N/A
2004/0168465	12/2003	Renken et al.	N/A	N/A
2008/0164274	12/2007	Stettes	N/A	N/A
2010/0223888	12/2009	Aarts	N/A	N/A

2011/0153066	12/2010	Terzini	N/A	N/A
2011/0260828	12/2010	Zhang et al.	N/A	N/A
2013/0282164	12/2012	Veloo	N/A	N/A
2017/0293983	12/2016	Long	N/A	N/A
2018/0273369	12/2017	Joseph	N/A	N/A
2019/0352161	12/2018	Knight et al.	N/A	N/A
2020/0255278	12/2019	O'nan et al.	N/A	N/A
2020/0270115	12/2019	Schultz et al.	N/A	N/A
2020/0316785	12/2019	Ostrow et al.	N/A	N/A
2020/0317498	12/2019	Dresser et al.	N/A	N/A
2021/0087045	12/2020	Carignan et al.	N/A	N/A
2021/0206617	12/2020	Maharaj et al.	N/A	N/A
2021/0292016	12/2020	Peters et al.	N/A	N/A
2022/0089424	12/2021	Dirik et al.	N/A	N/A
2022/0106181	12/2021	Miller et al.	N/A	N/A
2022/0267135	12/2021	Degnan et al.	N/A	N/A
2022/0274726	12/2021	Vari	N/A	N/A
2022/0289547	12/2021	Richardson	N/A	N/A
2023/0045788	12/2022	Cittadino et al.	N/A	N/A
2023/0096441	12/2022	Wach et al.	N/A	N/A
2023/0141811	12/2022	Dresser	141/174	B67D 1/0892
2023/0348256	12/2022	Degnan et al.	N/A	N/A
2023/0377406	12/2022	Edwards	N/A	N/A
2024/0034609	12/2023	Lange et al.	N/A	N/A
2024/0034611	12/2023	Cavazos et al.	N/A	N/A
2024/0076180	12/2023	Degnan et al.	N/A	N/A
2024/0270427	12/2023	Thomas et al.	N/A	N/A
2024/0359964	12/2023	Thomas et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
115005675	12/2021	CN	N/A
19627360	12/1997	DE	N/A
2546818	12/2017	GB	N/A
S57-066171	12/1981	JP	N/A
2003237721	12/2002	JP	N/A
2004240654	12/2003	JP	N/A
2004272331	12/2003	JP	N/A
2010-163211	12/2009	JP	N/A
2018176294	12/2017	JP	N/A
200285575	12/2001	KR	N/A
2010022336	12/2009	WO	N/A
2014115073	12/2013	WO	N/A
2017134431	12/2016	WO	N/A
2019177476	12/2018	WO	N/A
2019222144	12/2018	WO	N/A
WO-2023/049795	12/2022	WO	N/A
WO-2023/158764	12/2022	WO	N/A

OTHER PUBLICATIONS

Degnan, Nicholas Michael; U.S. Appl. No. 18/507,960, filed Nov. 13, 2023; Title: Automated Beverage Dispensing System and Method; 100 pages. cited by applicant
PCT International Search Report & Written Opinion of the International Searching Authority; PCT/US2023/062412; Nov. 3, 2023; 12 pages. cited by applicant
PCT International Search Report & Written Opinion of the International Searching Authority; PCT/US2023/022550; Jan. 24, 2024; 10 pages. cited by applicant
Office Action dated Jan. 23, 2024; U.S. Appl. No. 18/345,810, filed Jun. 30, 2023; 26 pages. cited by applicant
Degnan, Nicholas Michael; U.S. Appl. No. 18/345,810, filed Jun. 30, 2023; Title: Automated Beverage Dispensing System and Method; 100 pages. cited by applicant
Thomas, Aaron; U.S. Appl. No. 18/167,630, filed Feb. 10, 2023; Title: Automated Beverage Dispenser System and Method; 119 pages. cited by applicant
Miso Robotics; "SIPPY—The World's First POS-Integrated Automatic Beverage Dispenser and Sealer"; Retrieved from: <https://misorobotics.com/sippy/>; Jun. 22, 2021; 5 pages. cited by applicant
Notice of Allowance dated Dec. 14, 2022; U.S. Appl. No. 17/680,120, filed Feb. 24, 2022; 23 pages. cited by applicant
Notice of Allowance dated Apr. 5, 2023; U.S. Appl. No. 17/680,120, filed Feb. 24, 2022; 14 pages. cited by applicant
PCT International Search Report & Written Opinion of the International Searching Authority; PCT/US2022/017768; Jun. 17, 2022; 7 pages. cited by applicant
Cornelius Inc. "ABS 2.0 Illustrated Parts List", Cornelius ABS 2.0 Product Manual, Jul. 24, 2019. cited by applicant
Foreign Action other than Search Report on JP Dtd Jun. 28, 2024. cited by applicant
Foreign Search Report on EP Dtd Jan. 16, 2025. cited by applicant
Japan Office Action (Notice of Reasons for Rejection Dtd Jun. 26, 24) re Japan Appl No. 2023-551197. cited by applicant
Non-Final Office Action on U.S. Appl. No. 18/167,630 Dtd Jun. 10, 2024. cited by applicant
Notice of Allowance on U.S. Appl. No. 18/167,630 Dtd Nov. 12, 2024. cited by applicant
US Notice of Allowance on US Dtd Feb. 21, 2024. cited by applicant

Primary Examiner: Maust; Timothy L

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary**CROSS-REFERENCE TO RELATED APPLICATIONS**

(1) Not applicable.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not applicable.

BACKGROUND

(3) Restaurants and other dining facilities may distribute large numbers of beverages to patrons during periods of operation. As a result, dining facilities may have a beverage fountain or other similar system that may be used by patrons and/or employees to efficiently produce beverages.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a detailed description of various exemplary embodiments, reference will now be made to the accompanying drawings in which:
- (2) FIG. 1 is a perspective view of a beverage production system according to some embodiments;
- (3) FIG. 2 is a perspective view of the beverage handling assembly of the beverage production system of FIG. 1 according to some embodiments;
- (4) FIG. 3 is an exploded view of the turntable assembly of the beverage production system of FIG. 1 according to some embodiments;
- (5) FIG. 4 is an exploded view of a cup dispensing station of the beverage production system of FIG. 1 according to some embodiments;
- (6) FIG. 5 is an exploded view of the dispenser of the cup dispensing station of FIG. 4 according to some embodiments;
- (7) FIG. 6 is an enlarged side view of a ring gear and wedge assembly of the dispenser of FIG. 5 in a first position according to some embodiments;
- (8) FIG. 7 is an enlarged side view of the ring gear and wedge assembly of FIG. 6 in a second position according to some embodiments;
- (9) FIG. 8 is a top view of a wedge assembly that may be used within the cup dispensing station of the beverage production and dispensing system of FIG. 1 according to some embodiments;
- (10) FIGS. 9-11 are perspective views of cup dispensing stations of the beverage production system of FIG. 1 according to some embodiments;
- (11) FIG. 12 is a schematic view of an ice dispensing station of the beverage production system of FIG. 1 according to some embodiments;
- (12) FIG. 13 is a schematic view of a beverage dispensing station of the beverage production system of FIG. 1 according to some embodiments;
- (13) FIGS. 14 and 15 are schematic side views of a lidding station of the beverage production system of FIG. 1 according to some embodiments;
- (14) FIG. 16 is a perspective view of a lidding station of the beverage production and dispensing system of FIG. 1 according to some embodiments;
- (15) FIG. 17 is a top view of a pair of converging rails of a lidding station of the beverage production system of FIG. 1 according to some embodiments;
- (16) FIG. 18 is a perspective view of a lid press of the lidding station of the beverage production system of FIG. 1 according to some embodiments;
- (17) FIG. 19 is a perspective view of a compressive belt for securing lids to cups within a lidding station of the beverage production system of FIG. 1 according to some embodiments;
- (18) FIG. 20 is a perspective view of a roller assembly for securing lids to cups within a lidding station of the beverage production and dispensing system of FIG. 1 according to some embodiments;
- (19) FIG. 21 is a schematic view of a heat seal lidding assembly of the lidding station of the beverage production system of FIG. 1 according to some embodiments;
- (20) FIG. 22 is a side view of a beverage identification assembly of the beverage production system of FIG. 1 according to some embodiments;
- (21) FIG. 23 is a flow diagram of a method for producing a beverage according to some embodiments;
- (22) FIG. 24 is a schematic diagram of a computer system suitable for implementing one or more embodiments disclosed herein;
- (23) FIG. 25 is a perspective view of the beverage production system according to yet another embodiment;

(24) FIG. 26 is a perspective view of a modified turntable assembly of the beverage production system of FIG. 25 according to one embodiment;

(25) FIG. 27 is partial cut-away view of the modified turntable assembly of FIG. 26 shown with a slide assembly according to one embodiment;

(26) FIG. 28 is an enlarged perspective view of the slide assembly illustrated in FIG. 27 according to one embodiment;

(27) FIG. 29 is a side perspective view of the modified turntable assembly and another embodiment of the slide assembly;

(28) FIG. 30A is a perspective view of the upper and lower magnetic assemblies of the slide assembly shown in FIG. 29 according to another embodiment;

(29) FIG. 30B is a perspective view of the upper and lower magnetic assemblies and inner turntable according to another embodiment;

(30) FIG. 30C is a perspective view of the underside of the slide assembly and modified turntable according to another embodiment;

(31) FIG. 31 is a perspective view of the modified turntable assembly positioned in a sink according to another embodiment;

(32) FIG. 32 is a perspective view of the sink and drain according to one embodiment;

(33) FIG. 33 is a perspective view of the modified turntable assembly and positioned in a sink with the cup holders removed according to another embodiment;

(34) FIG. 34 is a perspective view of another embodiment of the sink with the modified turntable assembly removed;

(35) FIG. 35 is a perspective view of the sink and drain according to one embodiment;

(36) FIGS. 36A-E are views of the modified turntable assembly drive system, according to one embodiment;

(37) FIG. 37 is another perspective view of the beverage production system of FIG. 25 illustrating a lidding and printing assembly according to one embodiment;

(38) FIG. 38 is view of the lidding and printing assemblies and lift assembly according to one embodiment;

(39) FIG. 39A is a top view of a portion of the modified turntable assembly and the lift assembly according to one embodiment;

(40) FIG. 39B is a perspective view of a cup receptacle according to one embodiment;

(41) FIG. 40A a perspective view of a portion of the beverage production system of FIG. 25 according to one embodiment;

(42) FIGS. 40B and 40C are perspective views of other portions of the beverage production system of FIG. 25 according to further embodiments;

(43) FIG. 41 is a perspective view of another embodiment of the beverage production system;

(44) FIG. 42 is a perspective view of the conveyor assembly of the beverage production system of FIG. 41 according to some embodiments;

(45) FIG. 43 is a top view of the conveyor assembly of FIG. 42 according to some embodiments;

(46) FIGS. 44-47 are perspective views of the cup receptacles of the conveyor assembly of FIG. 42 according to some embodiments;

(47) FIG. 48 is a perspective view of another embodiment of the beverage production system;

(48) FIG. 49 is a side cross-sectional view of a cup dispensing station of the beverage production system of FIG. 48 according to some embodiments;

(49) FIG. 50 is a perspective view of yet another embodiment of the beverage production system;

(50) FIG. 51 is a perspective view of yet another embodiment of the beverage production system;

(51) FIG. 52 is another perspective view of the beverage production system illustrated in FIG. 51;

(52) FIG. 53 is a perspective view illustrating the turntables of the beverage production system illustrated in FIGS. 51 and 52;

(53) FIG. 54 is a view of an embodiment of the cup holders and the transition assembly of the

beverage production system;

(54) FIG. 55 is another view of the beverage production system and the transition assembly;

(55) FIG. 56 is a rear perspective view of a cup holder according to one embodiment;

(56) FIG. 57 is a bottom perspective view of the cup holder according to one embodiment;

(57) FIG. 58 is a perspective view of a lift mechanism according to one embodiment;

(58) FIG. 59 is a perspective view of a positioning plate according to one embodiment;

(59) FIG. 60 is a perspective view of a lidding and printing system according to one embodiment;

(60) FIG. 61 is another perspective view of the lidding and printing system according to one embodiment;

(61) FIG. 62 is a perspective view of another embodiment of the beverage production system;

(62) FIG. 63 is a perspective view of a wiper according to one embodiment of the present disclosure;

(63) FIG. 64 is a perspective view of another embodiment of the beverage production system;

(64) FIG. 65 is a top view of an ice bin according to one embodiment of the present disclosure;

(65) FIG. 66 is a perspective view of a fill chute and chute cover according to one embodiment of the present disclosure;

(66) FIG. 67 is a perspective view of an embodiment of the beverage production system;

(67) FIG. 68 is a view of an upper interior of the beverage production system according to one embodiment of the present disclosure;

(68) FIG. 69 is a view of the beverage production system illustrating a cup dispenser in an open position according to one embodiment of the present disclosure;

(69) FIG. 70 is a perspective view a lidding and printing assembly according to another embodiment of the present disclosure;

(70) FIG. 71 illustrates the lidding and printing assembly on slide rails according to one embodiment of the present disclosure;

(71) FIG. 72 is another illustration of the lidding and printing assembly on slide rails according to one embodiment of the present disclosure;

(72) FIG. 73 illustrates an upper frame of the beverage production system according to one embodiment of the present disclosure; and

(73) FIG. 74 is illustrates a drive mechanism of the beverage production system according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

(74) The following discussion is directed to various embodiments. However, one of ordinary skill in the art will understand that the examples disclosed herein have broad application, and that the discussion of any embodiment is meant only to be exemplary of that embodiment, and not intended to suggest that the scope of the disclosure, including the claims, is limited to that embodiment.

(75) The drawing figures are not necessarily to scale. Certain features and components herein may be shown exaggerated in scale or in somewhat schematic form and some details of conventional elements may not be shown in interest of clarity and conciseness.

(76) In the following discussion and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus should be interpreted to mean “including, but not limited to” Also, the term “couple” or “couples” is intended to mean either an indirect or direct connection. Thus, if a first device couples to a second device, that connection may be through a direct connection of the two devices, or through an indirect connection that is established via other devices, components, nodes, and connections. In addition, as used herein, the terms “axial” and “axially” generally mean along or parallel to a given axis (e.g., central axis of a body or a port), while the terms “radial” and “radially” generally mean perpendicular to the given axis. For instance, an axial distance refers to a distance measured along or parallel to the axis, and a radial distance means a distance measured perpendicular to the axis.

(77) As previously described, beverages may be produced at a restaurant or dining facility with a

beverage fountain or other similar system. However, many such devices require physical human interaction for many (or all) of the steps of the beverage production process. For instance, when producing beverages at a beverage fountain, a server, customer, etc. may still be required to fetch a cup, align and hold the cup under the nozzle of the selected beverage type, and engage or otherwise interact with the device to cause the desired beverage to be dispensed. Each of these additional, manual interactions may add time and complexity to the beverage production process and may therefore reduce the efficiency of food service operations overall.

(78) Accordingly, embodiments disclosed herein include beverage production systems and related methods that may further enhance the efficiency of the beverage production and distribution process by automating many, most, or substantially all of the steps for producing a beverage. Thus, through use of the embodiments disclosed herein, the number of manual steps that may be necessary for fulfilling beverage orders may be reduced, thereby increasing the efficiency of the beverage production process and improving food service operations overall.

(79) Referring now to FIG. 1, a beverage production system **100** according to some embodiments is shown. As will be described in more detail below, beverage production system **100** may be used to automatically prepare and dispense complete or substantially complete beverages during operations thereby reducing the number of manual actions performed by servers, customers, etc. In general, beverage production system **100** includes an ice chamber **112**, a cabinet **114**, and a beverage handling assembly **120** positioned between the ice chamber **112** and cabinet **114**.

(80) Referring now to FIGS. 1 and 2, beverage handling assembly **120** includes a plurality of stations for performing various stages or steps of the beverage production process. In particular, beverage handling assembly **120** includes a cup dispensing station **130**, an ice dispensing station **180**, a beverage dispensing station **190**, and a lidding station **200**. Beverages may be produced by progressing through the stations **130**, **180**, **190**, **200** with a turntable assembly **122**.

(81) Referring now to FIGS. 2 and 3, turntable assembly **122** includes a central axis **155** and a pair of concentric turntables **124**, **126**. Specifically, turntable assembly **122** includes an inner turntable **124** and an outer turntable **126** disposed circumferentially about the inner turntable **124**. The inner turntable **124** includes and defines a first or inner row **154** of cup receptacles **125**, and the outer turntable **126** includes and defines a second or outer row **156** of cup receptacles **125**. Both the inner row **154** and the outer row **156** extend annularly about a central axis **155**, with the inner row **154** being disposed radially inward of the outer row **156**. In particular, in some embodiments, the first row **154** and the second row **156** extends circumferentially about the central axis **155** such that the cup receptacles **125** of rows **154**, **156** are arranged in concentric circles about axis **155**.

(82) Referring specifically to FIG. 3, the inner turntable **126** and outer turntable **124** are supported by a base plate **149**. More particular, the base plate **149** includes a pair of circumferential rails **148**, **147** that support the turntables **124**, **126**, respectively, via a pair of bearings **144**, **146**, respectively. The bearings **144**, **146** may facilitate rotation of the turntables **124**, **126**, respectively, about central axis **155** relative to base plate **149** during operation. In some embodiments, bearings **144**, **146** may comprise wheels, sliding surfaces, and/or other suitable components or features to facilitate movement (e.g., rotation) of the turntables **124**, **126** relative to base plate **149**. In other embodiments, the inner turntable **126** may be supported by a shaft (not shown) and the outer turntable **124** is supported along an outer diameter of the outer turntable **124** by a support structure (not shown) of the beverage production system **100**.

(83) Inner turntable **124** and outer turntable **126** are received within an outer housing **140** that is in turn mounted on base plate **149** to conceal rails **147**, **148**, and bearings **144**, **146**. A gearbox **142** is mounted to outer housing **140** that includes one or more gears (not shown) that mesh with gear teeth or other suitable structures formed on outer turntable **126**. In other embodiments, either or both the outer turntable **126** and inner turntables **124** may be driven by a rubber wheel (not shown) frictionally engaged on an outside or with other portions of the turntables **124** and/or **126**.

(84) A first driver **141** and a second driver **143** are supported in a housing **145** that is coupled to

base plate **149** on a side that is opposite from the turntables **124**, **126** and outer housing **140**. However, in other embodiments (not shown), the second driver **143** may be mounted on the same side as the as the turntables **124**, **126**. In the present embodiment, an output shaft of the first driver **141** extends through a first aperture **150** in the base plate **149** to couple with the inner turntable **124**, and an output shaft of the second driver **143** extends through a second aperture **152** in base plate **149** to engage with the gears within the gearbox **142**. In some embodiments, the drivers **141**, **143** may comprise electric motors; however, in other embodiments, the drivers **141**, **143** may comprise pneumatic motors, hydraulic motors, etc.

(85) During operations, the drivers **141**, **143** may be energized to rotate the turntables **124**, **126**, respectively, about the central axis **155**. In particular, the first driver **141** may be energized to rotate the inner turntable **124** about axis **155**; and the second driver **143** may be energized to rotate the outer turntable **126** about axis **155** via the gears (not shown) within gearbox **142**. Referring back to FIGS. **1** and **2**, the rotation of turntables **124**, **126** about axis **155** may selectively progress beverages through the stations **130**, **180**, **190**, **200** within beverage handling assembly **120**. Because the turntables **124**, **126** are rotated about axis **155** via separate drivers (e.g., drivers **141**, **143** shown in FIG. **3**), the turntables **124**, **126** may be rotated about axis **155** independently from one another about axis **155** during operations. Without being limited to this or any other theory, independent rotation of turntables **124**, **126** may provide redundancy to beverage production system **100** in case of failure of one or more components thereof. In addition, independent rotation of turntables **124**, **126** may allow beverage production to be subdivided and organized via rows **154**, **156**. For instance, the rows **154**, **156** may be arranged to produce beverages for different sources (e.g., drive through orders vs. dine-in orders), and/or may be used to produce different beverage types (e.g., carbonated vs. non-carbonated, hot vs. cold). Further details of embodiments of the stations **130**, **180**, **190**, **200** are now described below.

(86) Referring now to FIGS. **1** and **4**, in some embodiments cup dispensing station **130** includes a central axis **135**, a dispenser **134**, and a plurality of tubular magazines **132** coupled to and extending axially from dispenser **134** with respect to axis **135**. Each magazine **132** includes a first or upper end **132a** and a second or lower end **132b** opposite upper end **132a**. The lower end **132b** is coupled to a corresponding receptacle **136** in dispenser **134**, and upper end **132a** is axially projected away from dispenser **134**. Each magazine **132** may receive and store a plurality of stacked cups **50**. In some embodiments, cups **50** may be loaded into magazines **132** from upper end **132a**. In some embodiments, magazines **132** may be de-coupled from dispenser **134** to facilitate loading of cups **50** therein. In other embodiments (not shown), the outer configuration of the plurality of tubular magazines **132** may not be round but instead be hexagonal or other shapes and may include an opening on the side of the tubular magazine **132** to receive cups such that the cups may be loaded from the side instead of the top or bottom. In such embodiment, the hexagonal or other shape may retain the cups based on the geometry of the open-faced tubular magazines **132**.

(87) Dispenser **134** is a generally cylindrical member that includes a first or upper side **134a**, a second or lower side **134b** opposite upper side **134a**, and a cylindrical outer surface **134c** extending axially between sides **134a**, **134b**. The receptacles **136** extend axially through dispenser **134** between sides **134a**, **134b** with respect to axis **135**. Magazines **132** are engaged within receptacles **136** on upper side **134a**, such that during operations, cups **50** that are dispensed from magazines **132** move through receptacle **136** and are ejected from lower side **134b**.

(88) Dispenser **134** is positioned within a housing **131**. During operations, dispenser **134** may rotate within housing **131** about axis **135**. A bearing **139** may be inserted within housing **131** to engage with lower side **134b** of dispenser **134** and therefore facilitate the rotation of dispenser **134** about axis **135** during operations. A driver **138** may be coupled to one or more gears **133** positioned within a gearbox **129** of housing **131**. In some embodiments, driver **138** comprises an electric motor; however, in other embodiments, the driver **138** may comprise a pneumatic motor, a hydraulic motor, etc. The one or more gears **133** may be coupled (e.g., meshed) with gear teeth or

other suitable structures on the cylindrical outer surface **134c** of dispenser **134**. A top plate **137** may cover gearbox **129** and driver **138** may be supported on top plate **137**. In other embodiments, the dispenser **134** may be driven by a timing belt pulley (not shown) engaged with a top portion of the dispenser **134**.

(89) Referring still to FIGS. **1** and **4**, during operations, driver **138** may rotate dispenser **134** about axis **135** via the one or more gears **133**. Specifically, driver **138** may rotate dispenser **134** to align selected ones of the magazines **132** and receptacles **136** in dispenser **134** with the rows **154**, **156** of cup receptacles **125** on turntable assembly **122**. In some embodiments, the magazines **132** may hold different sizes and/or types of cups that may be selectively aligned with the rows **154**, **156** to produce the desired beverages during operations.

(90) Referring now to FIG. **5**, in some embodiments dispenser **134** includes an outer housing **163** that defines an internal chamber **167**. A cap **160** may be fitted to the housing **163** to close off the chamber **167** and to conceal the components disposed therein (described in more detail below). The cap **160** may define upper side **134a**, and housing **163** may define lower side **134b** and cylindrical outer surface **134c** of dispenser **134**.

(91) A plurality of ring gears **166** are disposed within chamber **167** and aligned with each of the receptacles **136** along a corresponding axis **165**. A driving gear **168** is engaged (e.g., meshed) with gear teeth or other suitable structures on a radially outer surface of each of the ring gears **166**. Driving gears **168** are coupled to drivers **162** that may be mounted to cap **160**. For instance, driving gears **168** may be engaged with output shafts (not shown) of drivers **162** that extend through suitable apertures (not shown) in cap **160**. During operations, drivers **162** may rotate driving gears **168** to thereby drive rotation of the ring gears **166** about the corresponding axes **165**. Bearings **169** may be installed within chamber **167** to facilitate and support the rotation of ring gears **166** about axes **165**. In some embodiments, drivers **162** comprise electric motors; however, in other embodiments, the drivers **162** may comprise pneumatic motors, hydraulic motors, etc.

(92) Each axis **165** is parallel to and radially offset from central axis **135**. In some embodiments, axes **165** are evenly-circumferentially spaced about axis **135**. In the embodiment of cup dispensing station **130** shown in FIGS. **4** and **5**, there are a total of three magazines **132** and therefore three receptacles **136**. As a result, the axes **165** are circumferentially spaced approximately 120° from one another about axis **135**. In other embodiments, more or fewer than three magazines **132** may be included to accommodate a desired number of cup sizes or types.

(93) A plurality of wedge members **164** are positioned within each ring gear **166**. Referring now to FIGS. **6** and **7**, each wedge member **164** includes a cylindrical body **174** including a central or longitudinal axis **175**. Within each ring gear **166**, the axes **175** of wedge members **164** may be parallel to and radially offset from axis **165**. Body **174** includes a plurality of gear teeth **176** that extend circumferentially about axis **175**. Teeth **176** may engage (e.g., mesh) with corresponding teeth **172** on the radially inner surface **170** of ring gears **166**. Accordingly, the rotation of ring gears **166** about axes **165** results in rotation of wedge members **164** about axes **175** via engagement of teeth **172**, **176**.

(94) A pair of wedges **178**, **179** extend radially outward from body **174**. Wedges **178**, **179** may extend radially outward from radially opposite sides of body **174** with respect to axis **175**. In some embodiments, wedges **178**, **179** may extend circumferentially approximately 180° about body **174**; however, wedges **178**, **179** may extend circumferentially more or less than 180° about body **174** in some embodiments. In addition, the wedges **178**, **179** are axially spaced from one another such that wedge **178** may be positioned axially above wedge **179** along axis **175**. Accordingly, the wedge **178** may be referred to herein as a first or upper wedge **178** and the wedge **179** may be referred to herein as a second or lower wedge **179**.

(95) During operations, the wedge members **164** may rotate about axes **175** so as to engage wedges **178**, **179** with cups **50** extending into receptacles **136** of dispenser **134**. Generally speaking, the upper wedge **178** may engage between axially adjacent cups **50** to dislodge cups **50** from dispenser

134 when desired, and the lower wedges **179** may support the cups **50** within dispenser **134** when a cup **50** is not to be dispensed therefrom. In particular, during operations, each wedge member **164** may be transitioned between a first position shown in FIG. 6, and a second position shown in FIG. 7 in order to selectively dislodge and dispense cups **50** from dispenser **134**. In the first position (FIG. 6), the lower wedge **179** may be circumferentially rotated about axis **175** so as to extend radially inward toward axis **165** and therefore cups **50**. As a result, the lower wedge **179** of each wedge member **164** may engage with the lip **52** of the lowest cup **50** within dispenser **134** to prevent cups **50** from falling through dispenser **134** when wedge assemblies **164** are in the first position (FIG. 6).

(96) When it is desired to dispense a cup **50** from dispenser **134**, the wedge members **164** may be transitioned from the first position (FIG. 6) to the second position (FIG. 7) by rotating bodies **174** about axes **175** to thereby engage upper wedges **178** between the lips **52** of the two lowest cups **50** within dispenser **134**. The upper wedges **178** may comprise axial widths (e.g., with respect to axes **175**) that axially taper when moving circumferentially about body **174** so that as body **174** rotates about axis **175** from the first position (FIG. 6) to the second position (FIG. 7), the lips **52** of the adjacent cups **50** are gradually forced apart along axis **165**, until the contact between the adjacent cups **50** is reduced to a point that the axially lowermost cup **50** may fall through receptacle **136** and into a cup receptacle **125** in one of the rows **154**, **156** on turntable assembly **122** shown in FIGS. 1 and 2. When in the second position (FIG. 7), the un-dispensed cups **50** within dispenser **134** may be supported by the upper wedges **178**.

(97) Once the lowermost cup **50** has been dispensed from dispenser **134**, the wedge assemblies **164** may then be again transitioned from the second position (FIG. 7) back to the first position (FIG. 6) by rotating bodies **174** about axes **175** to thereby re-align the lower wedges **179** within the cups **50**. As the bodies **174** are rotated about axes **175** from the second position (FIG. 7) to the first position (FIG. 6), the cups **50** may fall downward along axis **165** so that the lip **52** of the lowest cup **50** within dispenser **134** engages with the lower wedges **179** as before. Accordingly, once the wedge assemblies **164** return to the first position (FIG. 6) the dispenser **134** is once again ready to dispense another cup **50** in the manner described above. In some embodiments, the wedge assemblies **164** may be transitioned from the first position (FIG. 6) to the second position (FIG. 7) and back to the first position (FIG. 6) via a continuous rotation of the bodies **174** about axes **175** (e.g., a full 360° about axes **175**).

(98) While some particular examples of cup dispensing station **130** have been described above, it should be appreciated that various features of cup dispensing station **130** may be altered, replaced, or removed in various embodiments, and that some embodiments of cup dispensing station **130** may include additional features. For instance, referring to FIG. 8, in some embodiments, dispenser **134** may include one or more reciprocating wedge members **270** within and about the receptacles **136** in lieu of or in addition to the wedge members **164**. Wedge member **270** includes one or more wedges **272** that may slidably engage between axially adjacent cups **50** along lips **52** as wedge **270** is translated radially inward toward axis **165**. The wedges **272** may include ramped or angled surfaces so that as wedge **270** translates radially inward toward axis **165**, adjacent cups **50** are moved axially away from one another along axis **165** so that a lowermost cup **50** may be dislodged to fall through receptacle **136** as generally described above.

(99) Referring now to FIG. 9, in some embodiments, cup dispensing station **130** may include a gripper arm **274** that may grasp cups **50** that extend through the dispenser **134** and pull them downward toward the turntable assembly **122** (note: only a schematic depiction of outer row **156** is provided in FIG. 9 to simplify the drawing).

(100) Referring now to FIG. 10, in some embodiments, magazines **132** may reciprocate linearly along a track **276** or other structure to selectively align magazines **132** with the rows **154**, **156** of turntable assembly **122** (FIG. 2) (note: FIG. 10 again only includes a schematic representation of one of the rows **156** to simplify the drawings). In some of these embodiments, cups **50** may be

dispensed from magazines **132** via any of the methods and systems described herein and/or other known methods and systems. FIG. **10** depicts the gripper arm **274** of FIG. **9** to illustrate some examples.

(101) Referring now to FIG. **11**, in some embodiments, magazines **132** may be fixed and aligned with the rows **154**, **156** of turntable assembly **122** (FIG. **2**). In some of these embodiments, additional magazines **132** may be included so as to allow different cup sizes and types to be dispensed onto each of the rows **154**, **156** (note: FIG. **11** again only includes a schematic representation of one of the rows **156** to simplify the drawings). In some of these embodiments, cups **50** may be dispensed from magazines **132** via any of the methods and systems described herein.

(102) Referring again to FIG. **2**, after a cup **50** is dispensed into the cup receptacles **125** of one or both of the rows **154**, **156** of turntable assembly **122**, the turntables **124**, **126** are rotated about axis **155** to advance the empty cups **50** to the ice dispensing station **180**. Referring now to FIG. **12**, in some embodiments ice dispensing station **180** includes an inlet **182**, a pair of outlets **188**, **189**, and a chute **185** positioned between the inlet **182** and the outlets **188**, **189**. The outlet **188** may be aligned with the inner row **154** of cup receptacles **125** (FIG. **2**), and the outlet **189** may be aligned with the outer row **156** of cup receptacles **125** (FIG. **2**).

(103) Inlet **182** may be coupled to or may comprise part or all of the ice chamber **112** shown in FIG. **1**. An agitator **184** is disposed within inlet **182**. Agitator **184** includes a plurality of paddles **186** that are driven to rotate within inlet **182** by a driver **187**. The engagement between the paddles **186** and ice within the inlet **182** breaks up ice blockages therein and helps to ensure the continued progression of ice through the inlet **182** and into the chute **185**.

(104) A dispensing valve **181** is positioned within chute **185**. Dispensing valve **181** may generally comprise a gate valve that is transitionable between a first or closed position (shown in solid line in FIG. **12**) to block progression of ice through the chute **185** toward outlets **188**, **189** and a second or open position (shown in dotted line in FIG. **12**) to allow ice to progress through chute **185** toward outlets **188**, **189**. In some embodiments, a driver **183** may actuate the dispensing valve **181** between the closed position and the open position by pivoting the valve **181** about a hinge **177**. In some embodiments, dispensing valve **181** may translate into and out of chute **185** in a direction that is generally perpendicular to the flow or movement of ice within chute **185** during operations.

(105) In some embodiments, an outlet selection valve **193** is coupled to the outlets **188**, **189**. The outlet selection valve **193** may comprise a gate **173** that is pivotable about a hinge **191** to selectively block one of the outlets **188**, **189**. In particular, a driver **192** may pivot gate **173** about hinge **191** to a first position (shown in solid line in FIG. **12**) to block the outlet **188** so that ice progressing out of the chute **185** is directed into the outlet **189**. In addition, the driver **192** may pivot gate **173** about hinge **191** to a second position (shown in dotted line in FIG. **12**) to block outlet **189** so that ice progressing out of the chute **185** is directed into the outlet **188**.

(106) Referring briefly now to FIGS. **2** and **12**, the outlets **188**, **189** may be aligned with the rows **154**, **156**. Thus, during operations, when ice is to be dispensed into a cup **50** received within a cup receptacle **125** of one of the rows **154**, **156**, the driver **183** may transition dispensing valve **181** to the open position so that ice may progress through chute **185** under the force of gravity. Depending on whether the cup to receive the ice is positioned in a cup receptacle **125** of the inner row **154** or the outer row **156**, the driver **192** may pivot the gate **173** of outlet selection valve **193** to the first or second position to direct ice out of the desired, corresponding outlet **188**, **189**. During these operations, the driver **187** may rotate paddles **186** of agitator **184** within inlet **182** to ensure the continued progression of ice toward chute **185**.

(107) In some embodiments, outlet selection valve **193** may be replaced with a pair of valve or gate assemblies that are coupled to the outlets **188**, **189**. Accordingly, in these embodiments, ice may be dispensed out of one or both of the outlets **188**, **189** by actuating the gate assemblies (not shown) for the selected outlet(s) **188**, **189** during operations.

(108) The valves (e.g., valves **181**, **193**, etc.) may be actuated to dispense ice out of an outlet **188**, **189** for a specified period of time to prevent overfilling. In some embodiments, suitable sensors or other measurement devices may be included within ice dispensing station **180** to monitor the volume of ice that is dispensed from outlets **188**, **189** to prevent overfilling. In some embodiments, a weight or force sensor may be employed (e.g., within the cup receptacles **125** in FIGS. **1** and **2**) to monitor the combined weight of the cup and dispensed ice to prevent overfilling. In these various embodiments, the amount of ice to be dispensed (and therefore the various parameters for monitoring the amount of dispensed ice) may depend upon the size of cup **50** aligned with the ice dispensing station **180**.

(109) In some embodiments, drivers **187**, **183**, **192** may comprise electric motors. However, drivers **187**, **183**, **192** may comprise any suitable driving device such as, for instance, pneumatic motors, hydraulic motors, etc.

(110) In other embodiments, instead of a pair of outlets **188**, **189**, ice dispensing station **180** may include only one outlet, such as either outlet **188** or **189**, and dispense ice into cups **50** only one of the rows, such as either outer or inner row **154** or **156**. For example, in this embodiment (not shown), outlet **189** may be omitted as would driver **192** and pivot gate **173**. Also in this embodiment, the agitator **184** and paddle **186** may be replaced with an auger or other element in communication with timing circuitry to operate for a specified duration to dispense the appropriate amount of ice into the cups. This embodiment is intended for variations of the beverage dispensing system **100** that provide for beverage fulfillment on only one of the inner row **154** or the outer row **156**, instead of beverage fulfillment on both rows **154** and **156**.

(111) Referring again to FIG. **2**, after ice is dispensed into the cups **50** at the ice dispensing station **180**, the turntables **124**, **126** may rotate about axis **155** to align the cups **50** with the beverage dispensing station **190**. Beverage dispensing station **190** includes a pair of nozzles **194**, **196**—with a first nozzle **194** being aligned with the inner row **154** of cup receptacles **125**, and a second nozzle **196** being aligned with the outer row **156** of cup receptacles **125**. During operations, the nozzles **194**, **196** may dispense a selected beverage into cups **50** disposed in rows **154**, **156**, respectively.

(112) Referring now to FIG. **13**, in some embodiments each of the nozzles **194**, **196** may be coupled to a distribution valve assembly **195**. In turn, the distribution valve assembly **195** may be coupled to a carbonated water source **197**, a non-carbonated water source **198**, and a plurality of flavoring sources **199**. Additional valving, pumps, and other components may be included to facilitate and control the flow of fluid from sources **197**, **198**, **199**; however, these additional components are not shown so as to simplify the drawing. During operations, when a cup (e.g., cup **50** in FIGS. **1** and **2**) is aligned with one of the nozzles **194**, **196**, a selected beverage is dispensed by flowing water from one (or both) of the sources **197**, **198**, and flowing flavoring from one or more of the sources **199** to the distribution valve assembly **195**. Thereafter, the distribution valve assembly **195** may actuate to route the fluids to the selected nozzle **194**, **196**. The fluids may mix within the distribution valve assembly **195**, the nozzle(s) **194**, **196**, and/or therebetween to form the selected beverage. In other embodiments, additional fluid sources may be connected to distribution valve assembly **195** for dispensing beverages that do not require mixing, such as, but not limited to, juice, coffee, and milk.

(113) The distribution valve assembly **195** may include or be coupled to a timer to ensure that the correct amounts of fluids are dispensed from the selected nozzle **194**, **196** while preventing overfilling. In some embodiments, distribution valve assembly **195** may additionally or alternatively monitor a volume of dispensed fluids to and from the nozzles **194**, **196** (e.g., via flow rate sensors, pressure sensors, etc.) to prevent overfilling. In some embodiments, a weight or force sensor may be employed (e.g., within the cup receptacles **125** in FIGS. **1** and **2**) to monitor the combined weight of the cup, ice (if any), and dispensed beverage to prevent overfilling. In these various embodiments, the amount of fluids to be dispensed (and therefore the various parameters for monitoring the amount of dispensed fluids) may depend upon the size of cup **50** aligned with

the beverage dispensing station **190**.

(114) While the embodiment of beverage dispensing station **190** shown in FIG. **13** includes two nozzles **194**, **196**, it should be appreciated that different numbers and arrangements of nozzles may be utilized in other embodiments. For instance, referring again to FIGS. **1** and **2**, in some embodiments, beverage dispensing station **190** may include a plurality of nozzles for dispensing beverages into cups **50** disposed in the inner row **154** and/or a plurality of nozzles for dispensing beverages into cups **50** disposed in the outer row **156**. Without being limited to this or any other theory, the number and arrangement of the nozzles (e.g., nozzles **194**, **196**) of beverage dispensing station **190** may allow specific beverages or groups of beverages to be dispensed from selected nozzles and may increase the number of beverages that may be dispensed into cups **50** over a period of time. In addition, the nozzles of the beverage dispensing station **190** (e.g., nozzles **194**, **196**) may be separately coupled to the sources **197**, **198**, **199** so that beverages may be dispensed simultaneously from the various nozzles during operations. In embodiments where beverages are filled only on one of the inner or outer rows **154**, **156** of cup receptacles, only one of the nozzles **194**, **196** may be present.

(115) Referring again to FIG. **2**, after a beverage is dispensed into the cups **50** via the beverage dispensing station **190**, the turntables **124**, **126** rotate about axis **155** to align the cups **50** with the lidding station **200**. Generally speaking, lidding station **200** may comprise a plurality of tubular magazines **202** that may receive and hold a plurality of lids **60** to be dispensed and deposited on cups **50** during operations.

(116) Reference is now made to FIGS. **14** and **15**, in which an embodiment of lidding station **200** is shown. As shown in FIGS. **14** and **15**, magazine **202** includes a central or longitudinal axis **205**, a first or upper end **202a**, and a second or lower end **202b** opposite upper end **202a**. Lids **60** may be stacked into magazine **202** from the upper end **202a** and may be dispensed from magazine **202** at lower end **202b** via a lid dispensing assembly **210**.

(117) In some embodiments, lid dispensing assembly **210** may comprise a grapple **214** pivotably coupled to magazine **202** via a hinge **212**, proximate lower end **202b**. A driver **226** is coupled to grapple **214** and/or hinge **212** that may selectively rotate grapple **214** about hinge **212** between a first position shown in FIG. **14** and a second position shown in FIG. **15**. In some embodiments, driver **226** may comprise an electric motor; however, in other embodiments, driver **226** may comprise a pneumatic motor, a hydraulic motor, etc.

(118) Grapple **214** includes a first or inner end **214a** proximate hinge **212** and a second or outer end **214b** projecting away from hinge **212**. In addition, grapple **214** includes a first lid grip **216** at (or proximate to) outer end **214b**, and a second lid grip **218** at (or proximate to) inner end **214a**. First lid grip **216** and second lid grip **218** may comprise teeth or other suitable structures that may engage with and hold a lid **60** during dispensing operations. First lid grip **216** may be fixed in position at (or proximate to) outer end **214b** of grapple **214**, while second lid grip **218** may be pivotably coupled to grapple **214** at (or proximate to) inner end **214a** via a hinge **220**. Moreover, second lid grip **218** may be rotationally biased (e.g., via a torsion spring or other suitable device) about hinge **220** so that second lid grip **218** is biased into engagement with a lid **60** that is being held by grapple **214** (FIG. **14**).

(119) Lids **60** may be dispensed from magazine **202** by rotating grapple **214** to the first position of FIG. **14**, to engage with the lowermost lid **60** within magazine **202**. More particularly, in the position of FIG. **14**, the lid **60** is gripped or engaged between the first lid grip **216** and the second lid grip **218**. As previously described, the second lid grip **218** may be biased about hinge **220** to engage with lid **60**. Next, when it is desired to dispense the lid **60** onto the top of a cup (e.g., cup **50** in FIGS. **1** and **2**) that is aligned with the lidding station **200**, driver **226** may rotate grapple **214** about hinge **212** from the first position of FIG. **14** to the second position of FIG. **15**. As grapple **214** rotates about hinge **212** to the second position of FIG. **15**, the second lid grip **218** may engage with a camming surface **224** coupled to (or mounted proximate to) hinge **212**. As a result, the continued

rotation of grapple **214** about hinge **212** toward the second position following engagement of the second lid grip **218** with camming surface **224** may force second lid grip **218** to rotate about hinge **220** and thereby disengage from lid **60** so that lid **60** may fall, under the force of gravity, toward a cup **50** aligned therewith. Afterward, driver **226** may rotate grapple **214** about hinge **212** back toward the first position of FIG. **14** so as to engage with another lid **60**. Because the grapple **214** pivots about hinge **212** between the first position (FIG. **14**) and second position (FIG. **15**) during lid dispensing operations as described above, the lids **60** may be inserted within magazine “upside-down,” so that when they are rotated with grapple **214** to the second position of FIG. **15**, the bottom side of the lid **60** is facing the cup **50** (not shown).

(120) In some embodiments, grapple **214** may be omitted and lids **60** may be dispensed from magazine(s) **202** via other systems and methods. Referring now to FIG. **16**, in some embodiments, magazine **202** may include a slot **230** extending radially through the wall of magazine **202** at a point that is more proximate the lower end **202b** than the upper end **202a**. Lids **60** that are inserted into upper end **202a** of magazine **202** may fall or otherwise progress axially downward through magazine **202** along axis **205** to eventually align with the slot **230**. A ram **232** may be coupled to magazine **202** and aligned with slot **230**. Ram **232** may be selectively translated (e.g., via a suitable driver or actuator) in a radial direction with respect to axis **205**, through the slot **230** during operations. Each time ram **232** translates radially through slot **230**, a lid **60** may be pushed radially out of slot **230** and magazine **202** whereby it may fall downward toward a cup **50** (which may be positioned within a receptacle **125**).

(121) In some embodiments, a lid **60** dispensed from lidding station **200** may be misaligned with the cup **50**. Thus, in some embodiments, the dispensing mechanism of the lidding station **200** (e.g., grapple **214**) may align the lid **60** with the cup **50** (e.g., such that the lid **60** is substantially centered on the top of the cup **50**). In some embodiments, a lidding station **200** may include a separate device or assembly for aligning the lid **60** with the cup **50** following dispensing of the lid **60** (e.g., from magazine **202**). For instance, reference is now made to FIG. **17**, a cup **50** and dispensed lid **60** may be routed (e.g., via turntables **124**, **126**) between a pair of converging rails **234**. The shape and position of the rails **234** may be selected so that as the cup **50** and lid **60** are moved therebetween, the lid **60** may be aligned with the underlying cup **50**.

(122) Once a lid **60** is dispensed onto a cup **50** and aligned therewith, the lid **60** may then be secured or pressed onto the cup **50**. In some embodiments, grapple **214** of FIGS. **14** and **15** may be translated axially (e.g., independently or together with magazine **202**) with respect to axis **205** to press the dispensed lid **60** onto the cup **50**.

(123) In some embodiments, a dispensed lid **60** may be compressed onto the cup **50** via a separate press or other suitable device. For instance, referring now to FIG. **18**, in some embodiments a press **237** may engage with lid **60** after it is loosely fitted (e.g., dropped) onto a cup **50**. Press **237** includes a plunger **236** that is coupled to a linear actuator **238**. Plunger **236** may comprise any suitable shape that may correspond with the shape of the lid (e.g., lid **60** in FIGS. **14** and **15**). Plunger **236** may be selectively extended and retracted along a central axis **235** via linear actuator **238**. In some embodiments, linear actuator **238** may comprise a hydraulic or pneumatic cylinder. In some embodiments linear actuator **238** may comprise an electric linear actuator.

(124) Referring now to FIG. **19**, in some embodiments, a dispensed lid **60** may be compressed onto cup **50** via a belt **240** that is spaced from the rows **154**, **156** (FIG. **2**). In particular, during operations the lid **60** and cup **50** are compressed between the corresponding cup receptacle **125** (not shown in FIG. **19**) of the rows **154**, **156** and the belt **240** to thereby secure lid **60** to the cup **50**.

(125) Referring now to FIG. **20**, in some embodiments, lidding station **200** may comprise a roller assembly **242** to compress and secure dispensed lids **60** onto cups **50**. The roller assembly **242** may comprise a ring **244** and a plurality of rollers **246** rotatably mounted to ring **244**. The rollers **246** may be generally cylindrical in shape and include central axes **245**. The rollers **246** may be mounted to ring **244** such that axes **245** are angled relative to central axis **55** of cup **50**. In some

embodiments, the axes **245** are disposed at an angle θ that is greater than 0° and less than 90° relative to central axis **55**. During operations, a cup **50** and dispensed lid **60** is aligned with the roller assembly **242**, and the roller assembly **242** is lowered into engagement with lid **60** along axis **55** and simultaneously rotated about axis **55** such that rollers **246** compress lid **60** onto cup **50**.

(126) Referring now to FIG. **21**, in some embodiments, lidding station **200** (FIGS. **1** and **2**) may comprise a heat seal lidding assembly **250**. Heat seal lidding assembly **250** includes a heat sealer **256** that may cut and heat seal a lid onto a cup **50** from a continuous belt of lidding material **258** (e.g., a polymer membrane) that is unrolled from a start roller **252** and taken up by a finish roller **254**. In particular, heat sealer **256** may include a heating element (not shown) and may be translated toward cup **50** along an axis **55** to cut out a portion of the lidding material **258** and fuse the lidding material **258** to the rim of cup **50**. In some embodiments, a pair of heat sealers **256** may be included within heat seal lidding assembly **250**, with each heat sealer **256** being aligned with a corresponding one of the rows **154**, **156** of turntable assembly **122**. In some embodiments, each row **154**, **156** may be aligned with a separate, independent heat seal lidding assembly **250**.

(127) In some embodiments, some or all of the lidding process may be carried out manually (e.g., by an employee or customer). For instance, in some embodiments, lids **60** may be retrieved and secured to cups **50** manually. In some embodiments, lidding station **200** may dispense (and possibly align) lids **60** onto cups **50**, but an employee/customer may manually compress the lids **60** onto the cups **50** thereafter. Thus, in some embodiments, some or all of the lidding station **200** may be omitted from beverage handling assembly **120** (FIGS. **1** and **2**).

(128) Referring now to FIGS. **1** and **22**, in some embodiments, beverage production system **100** may include a beverage identification assembly **260** to identify beverages that have advanced through the stations **130**, **180**, **190**, **200** and are ready for retrieval by an employee or customer. In particular, as best shown in FIG. **22**, beverage identification assembly **260** may comprise a plurality of emitters **262** coupled to beverage handling assembly **120** that are configured to emit light **264** onto cups **50** and (if present) lids **60** that may be used to identify a particular beverage or beverage order. In some embodiments, the light **264** may be color-coded so as to identify a particular beverage (or order) with a different color. In some embodiments, the light **264** may form images (e.g., text and/or symbols) on the beverages that may provide sufficient information (e.g., names, order number, table number, vehicle identification). In some embodiments, emitters **262** may comprise light emitting diodes (LEDs) and/or other suitable light emitting devices.

(129) Referring again to FIGS. **1** and **2**, during operations, commands to produce selected beverages may be received by suitable electronics (not shown) of beverage production system **100**. For instance, an employee or customer may select the desired beverage(s) on a user interface **110** which then initiates the beverage production process generally described above. In some embodiments, the user interface **110** may comprise a touch-sensitive electronic display. In some embodiments, the beverage production system **100** may receive commands to produce beverages via other electronic devices that are communicatively coupled to beverage production and dispensing system **100** via a suitable network or connection. For instance in some embodiments, beverage production system **100** may receive commands to produce beverages from a point of sale system of the restaurant or dining facility that may receive orders via customer or employee. In some embodiments, the point-of-sale system may comprise part of a computer system that also includes the beverage production system **100** (e.g., computer system **400** described below).

(130) Once commands to produce beverage(s) are received by beverage production system **100**, turntables **124**, **126** may be rotated about axis **155** to progress the cup receptacles **125** through the stations **130**, **180**, **190**, **200**. Simultaneously, the assemblies and mechanisms within each of the stations **130**, **180**, **190**, **200** may actuate in the manner described above to produce beverages. Specifically, as described above, cup dispensing assembly **130** may dispense cups **50** from magazines **132** into cup receptacles **125** in one or both of the rows **154**, **156**, thereafter the cups **50** are aligned with the ice dispensing station **180** whereby ice is dispensed into the cups **50**. In some

instances, depending on the selected preferences for each requested beverage, ice may not be dispensed into a cup or cups when aligned with the ice dispensing station **180**. Next, the cups **50** and ice (if dispensed) are aligned with the beverage dispensing station **190**, whereby the selected beverage is dispensed into the cups **50** (e.g., via nozzles **194, 196**). Next, depending on the lidding system that is employed, cups **50** may be progressed to the lidding station **200** whereby a lid **60** may be dispensed from magazines **202** and secured onto the cups **50** or a film lid is placed and secured on the cup, such as by heat sealing. Finally, referring briefly to FIGS. **1** and **22** after the cups **50** are progressed past the lidding station **200**, the cups are generally moved to align with the beverage identification assembly **260**, which may then identify the particular, completed beverages via the projected light **264** as generally describe above. As previously described, in some embodiments, some or all of the lidding process may be performed manually, such that lidding station **200** may be simplified or omitted entirely from beverage handling assembly **120**.

(131) Referring now to FIG. **23**, a method **300** of producing beverages with embodiments of the beverage dispensing system **100** according to some embodiments is shown. In some embodiments, one or more elements of method **300** may be carried out by components of the beverage handling assembly **120** as described herein and/or by a computer system (e.g., such as computer system **400** described in more detail below). Thus, in describing the features of method **300**, continuing reference is made to the beverage production system **100** shown in FIG. **1** and the beverage handling assembly **120** depicted in FIG. **2**.

(132) Initially, method **300** includes receiving instructions (or commands) for producing a desired beverage (or beverages) at block **302**. The instructions may be generated or received via interaction of an employee or customer with a user interface device, such as the user interface **110** shown in FIG. **1**. In some embodiments, the instructions may be generated or received by a point-of-sale system utilized by the restaurant or dining facility as described above.

(133) Method **300** also includes selecting a row **154, 156** on the turntable assembly **122** to produce the beverage at block **304**. In particular, in some embodiments, the row selection at block **304** may be determined based on a previously defined rule for producing beverages with the beverage production system **100**. For instance, as noted above, in some embodiments, the source of the beverage order (e.g., drive through, dine-in) may dictate which row **154, 156** is selected at block **304**. In addition, in some embodiments, the type and/or size of the desired beverage may also dictate which row **154, 156** is selected at block **304**.

(134) Method **300** also includes aligning a magazine **132** of the cup dispensing station **130** with the selected row **154, 156**, and dispensing a cup **50** from the magazine **132** at block **306**. As previously described, the magazines **132** may hold different sizes and/or types of cups **50** therein. Thus, during operations, a magazine **132** holding the cup size and type that is desired, based on the instructions received at block **302**, may dictate which magazine **132** is to be utilized to dispense a cup **50** for beverage production operations. In some embodiments, as previously described, the dispenser **134** of cup dispensing station **130** may be rotated (e.g., via driver **138** shown in FIG. **4**) to align the selected magazine **132** with the selected row **154, 156** on turntable assembly **122**.

(135) Method **300** also includes aligning the dispensed cup **50** with an outlet **188, 189** of the ice dispensing station **180** and dispensing ice into the cup **50** from the aligned outlet **188, 189** at block **308**. The outlet **188, 189** utilized for dispensing the ice at block **308** may be dictated by the row **154, 156** selected at block **304**. As described above, in some embodiments, an outlet selection valve **193** (FIG. **12**) may be actuated to direct dispensed ice out of the selected outlet **188, 189**.

(136) Method **300** also includes aligning a nozzle **194, 196** of the beverage dispensing station **190** with the cup **50**, and dispensing the beverage from the aligned nozzle **194, 196** at block **310**. As with the ice dispensing station **180**, the nozzle **194, 196** utilized to dispense the beverage at block **310** may be dictated by the row **154, 156** selection at block **304**. In some embodiments, the nozzle aligned at block **310** may be selected based on the type of beverage being produced based on the instructions received at block **302**.

(137) Method **300** also includes dispensing a lid **60** onto the cup **50** with the lidding station **200** at block **312**. In some embodiments, the lidding station **200** may be actuated to dispense a lid **60** onto the cup **50**, which may then be manually secured by an employee or customer. In some embodiments, the lidding station **200** may be actuated to both dispense the lid **60** and secure the lid **60** to the cup **50**.

(138) In each of the blocks **306**, **308**, **310**, **312** of method **300**, the turntables **124**, **126** of the turntable assembly **122** may be rotated (e.g., via drivers **141**, **143**) to align a cup receptacle **125** (and/or a cup **50** positioned therein) with each of the cup dispensing station **130**, ice dispensing station **180**, beverage dispensing station **190**, and lidding station **200**.

(139) FIG. **24** illustrates a computer system **400** suitable for implementing one or more embodiments disclosed herein. For instance, beverage production system **100** (FIG. **1**) may include or be coupled to computer system **400**. During operations beverage production system **100** may utilize computer system **400** to receive and process beverage orders (or commands associated therewith), and to actuate the various components of beverage handling assembly **120** as described above. In some embodiments, one or more components of computer system **400** may be positioned within the cabinet **114** shown in FIG. **1**. In other embodiments, the beverage production system **100** may include all or some aspects of the computer system **400** which is connected to a point-of-sale or other systems, which also contains all or some aspects of the computer system **400** or combinations thereof. Such configurations allow the selection of beverages to be made at either the beverage dispensing production system **100**, at the point-of-sale system, or both.

(140) The computer system **400** includes a processor **402** (which may be referred to as a central processor unit or CPU) that is in communication with memory devices including secondary storage **404**, read only memory (ROM) **406**, random access memory (RAM) **408**, input/output (I/O) devices **410**, and network connectivity devices **412**. The processor **402** may be implemented as one or more CPU chips.

(141) It is understood that by programming and/or loading executable instructions onto the computer system **400**, at least one of the CPU **402**, the RAM **408**, and the ROM **406** are changed, transforming the computer system **400** in part into a particular machine or apparatus having the novel functionality taught by the present disclosure. It is fundamental to the electrical engineering and software engineering arts that functionality that can be implemented by loading executable software into a computer can be converted to a hardware implementation by well-known design rules. Decisions between implementing a concept in software versus hardware typically hinge on considerations of stability of the design and numbers of units to be produced rather than any issues involved in translating from the software domain to the hardware domain. Generally, a design that is still subject to frequent change may be preferred to be implemented in software, because re-spinning a hardware implementation is more expensive than re-spinning a software design. Generally, a design that is stable that will be produced in large volume may be preferred to be implemented in hardware, for example in an application specific integrated circuit (ASIC), because for large production runs the hardware implementation may be less expensive than the software implementation. Often a design may be developed and tested in a software form and later transformed, by well-known design rules, to an equivalent hardware implementation in an application specific integrated circuit that hardwires the instructions of the software. In the same manner as a machine controlled by a new ASIC is a particular machine or apparatus, likewise a computer that has been programmed and/or loaded with executable instructions may be viewed as a particular machine or apparatus.

(142) Additionally, after the system **400** is turned on or booted, the CPU **402** may execute a computer program or application. For example, the CPU **402** may execute software or firmware stored in the ROM **406** or stored in the RAM **408**. In some cases, on boot and/or when the application is initiated, the CPU **402** may copy the application or portions of the application from the secondary storage **404** to the RAM **408** or to memory space within the CPU **402** itself, and the

CPU **402** may then execute instructions that the application is comprised of. In some cases, the CPU **402** may copy the application or portions of the application from memory accessed via the network connectivity devices **412** or via the I/O devices **410** to the RAM **408** or to memory space within the CPU **402**, and the CPU **402** may then execute instructions that the application is comprised of. During execution, an application may load instructions into the CPU **402**, for example load some of the instructions of the application into a cache of the CPU **402**. In some contexts, an application that is executed may be said to configure the CPU **402** to do something, e.g., to configure the CPU **402** to perform the function or functions promoted by the subject application. When the CPU **402** is configured in this way by the application, the CPU **402** becomes a specific purpose computer or a specific purpose machine.

(143) The secondary storage **404** is typically comprised of one or more disk drives or tape drives and is used for non-volatile storage of data and as an over-flow data storage device if RAM **408** is not large enough to hold all working data. Secondary storage **404** may be used to store programs which are loaded into RAM **408** when such programs are selected for execution. The ROM **406** is used to store instructions and perhaps data which are read during program execution. ROM **406** is a non-volatile memory device which typically has a small memory capacity relative to the larger memory capacity of secondary storage **404**. The RAM **408** is used to store volatile data and perhaps to store instructions. Access to both ROM **406** and RAM **408** is typically faster than to secondary storage **404**. The secondary storage **404**, the RAM **408**, and/or the ROM **406** may be referred to in some contexts as computer readable storage media and/or non-transitory computer readable media.

(144) I/O devices **410** may include printers, video monitors, liquid crystal displays (LCDs), touch screen displays (e.g., user interface **110** shown in FIG. **1**), keyboards, keypads, switches, dials, mice, track balls, voice recognizers, card readers, paper tape readers, or other well-known input and output devices.

(145) The network connectivity devices **412** may take the form of modems, modem banks, Ethernet cards, universal serial bus (USB) interface cards, serial interfaces, token ring cards, fiber distributed data interface (FDDI) cards, wireless local area network (WLAN) cards, radio transceiver cards, and/or other well-known network devices. The network connectivity devices **412** may provide wired communication links and/or wireless communication links (e.g., a first network connectivity device **412** may provide a wired communication link and a second network connectivity device **412** may provide a wireless communication link). Wired communication links may be provided in accordance with Ethernet (IEEE 802.3), Internet protocol (IP), time division multiplex (TDM), data over cable service interface specification (DOCSIS), wavelength division multiplexing (WDM), and/or the like. In an embodiment, the radio transceiver cards may provide wireless communication links using protocols such as code division multiple access (CDMA), global system for mobile communications (GSM), long-term evolution (LTE), WiFi (IEEE 802.11), Bluetooth, Zigbee, narrowband Internet of things (NB IoT), near field communications (NFC), radio frequency identity (RFID). The radio transceiver cards may promote radio communications using 5G, 5G New Radio, or 5G LTE radio communication protocols. These network connectivity devices **412** may enable the processor **402** to communicate with the Internet or one or more intranets. With such a network connection, it is contemplated that the processor **402** might receive information from the network, or might output information to the network in the course of performing the above-described method steps. Such information, which is often represented as a sequence of instructions to be executed using processor **402**, may be received from and outputted to the network, for example, in the form of a computer data signal embodied in a carrier wave. Thus, the present disclosure contemplates receiving instructions, such as customer orders received via online or so called internet applications or otherwise, via network connectivity devices **412**, including orders for beverages, that are then produced automatically by the beverage production system **100** without input from employees or personnel located at or operating the beverage

production system **100**.

(146) Such information, which may include data or instructions to be executed using processor **402** for example, may be received from and outputted to the network, for example, in the form of a computer data baseband signal or signal embodied in a carrier wave. The baseband signal or signal embedded in the carrier wave, or other types of signals currently used or hereafter developed, may be generated according to several methods well-known to one skilled in the art. The baseband signal and/or signal embedded in the carrier wave may be referred to in some contexts as a transitory signal.

(147) The processor **402** executes instructions, codes, computer programs, scripts which it accesses from hard disk, floppy disk, optical disk (these various disk-based systems may all be considered secondary storage **404**), flash drive, ROM **406**, RAM **408**, or the network connectivity devices **412**. While only one processor **402** is shown, multiple processors may be present. Thus, while instructions may be discussed as executed by a processor, the instructions may be executed simultaneously, serially, or otherwise executed by one or multiple processors. Instructions, codes, computer programs, scripts, and/or data that may be accessed from the secondary storage **404**, for example, hard drives, floppy disks, optical disks, and/or other device, the ROM **406**, and/or the RAM **408** may be referred to in some contexts as non-transitory instructions and/or non-transitory information.

(148) In an embodiment, the computer system **400** may comprise two or more computers in communication with each other that collaborate to perform a task. For example, but not by way of limitation, an application may be partitioned in such a way as to permit concurrent and/or parallel processing of the instructions of the application. Alternatively, the data processed by the application may be partitioned in such a way as to permit concurrent and/or parallel processing of different portions of a data set by the two or more computers. In an embodiment, virtualization software may be employed by the computer system **400** to provide the functionality of a number of servers that is not directly bound to the number of computers in the computer system **400**. For example, virtualization software may provide twenty virtual servers on four physical computers. In an embodiment, the functionality disclosed above may be provided by executing the application and/or applications in a cloud computing environment. Cloud computing may comprise providing computing services via a network connection using dynamically scalable computing resources. Cloud computing may be supported, at least in part, by virtualization software. A cloud computing environment may be established by an enterprise and/or may be hired on an as-needed basis from a third-party provider. Some cloud computing environments may comprise cloud computing resources owned and operated by the enterprise as well as cloud computing resources hired and/or leased from a third-party provider.

(149) In an embodiment, some or all of the functionality described herein may be provided as a computer program product. The computer program product may comprise one or more computer readable storage medium having computer usable program code embodied therein to implement the functionality disclosed above. The computer program product may comprise data structures, executable instructions, and other computer usable program code. The computer program product may be embodied in removable computer storage media and/or non-removable computer storage media. The removable computer readable storage medium may comprise, without limitation, a paper tape, a magnetic tape, magnetic disk, an optical disk, a solid-state memory chip, for example analog magnetic tape, compact disk read only memory (CD-ROM) disks, floppy disks, jump drives, digital cards, multimedia cards, and others. The computer program product may be suitable for loading, by the computer system **400**, at least portions of the contents of the computer program product to the secondary storage **404**, to the ROM **406**, to the RAM **408**, and/or to other non-volatile memory and volatile memory of the computer system **400**. The processor **402** may process the executable instructions and/or data structures in part by directly accessing the computer program product, for example by reading from a CD-ROM disk inserted into a disk drive

peripheral of the computer system **400**. Alternatively, the processor **402** may process the executable instructions and/or data structures by remotely accessing the computer program product, for example by downloading the executable instructions and/or data structures from a remote server through the network connectivity devices **412**. The computer program product may comprise instructions that promote the loading and/or copying of data, data structures, files, and/or executable instructions to the secondary storage **404**, to the ROM **406**, to the RAM **408**, and/or to other non-volatile memory and volatile memory of the computer system **400**.

(150) In some contexts, the secondary storage **404**, the ROM **406**, and the RAM **408** may be referred to as a non-transitory computer readable medium or a computer readable storage media. A dynamic RAM embodiment of the RAM **408**, likewise, may be referred to as a non-transitory computer readable medium in that while the dynamic RAM receives electrical power and is operated in accordance with its design, for example during a period of time during which the computer system **400** is turned on and operational, the dynamic RAM stores information that is written to it. Similarly, the processor **402** may comprise an internal RAM, an internal ROM, a cache memory, and/or other internal non-transitory storage blocks, sections, or components that may be referred to in some contexts as non-transitory computer readable media or computer readable storage media.

(151) FIG. **25** illustrates another embodiment of a beverage production system **500**. The beverage production system **500** may be similar to the beverage production system **100** in some respects. For example, the beverage production system **500** may employ the cup dispensing station **130** described above. However, the beverage production system **500** includes some notable differences, such as a lidding and printing assembly **502** for sealing and identifying filled beverages, discussed further below. While it is anticipated that beverages may be dispensed in both rows, in this embodiment, the beverage production system **500** may be configured such that cups, ice, and beverages are dispensed on only one row, such as on either the inner or outer row, but not in both rows of the turntable. This embodiment illustrates beverages fulfillment in cup holders in the outer row.

(152) Referring also to FIG. **26**, the beverage production system **500** may also employ a modified turntable assembly **504** (also shown in cut-away in FIG. **25**). The modified turntable assembly **504** may be similar to the turntable assembly **122** described above in some respects. The modified turntable assembly **504** is configured with an outer turntable **505** having an outer row of cup receptacles **506** and an inner turntable **507** having an inner row of cup receptacles **508**. The inner and outer turntables **505** and **507**, which may be collectively referred to as modified turntable **510**, are configured to rotate independently from one another and may comprise drives, motors, and gearboxes (not shown) that operate similar to those described above with regard to inner turntable **124** and outer turntable **126** described above.

(153) The cup receptacles **506** and **508** are configured to retain cups **50** dispensed from the cup dispensing station **130**. The cup receptacles **506** and **508** may be sized to retain cups **50** of various sizes. The outer row of cup receptacles **506** may include an opening **512** near a bottom outer side **511** of the outer row of cup receptacles **506**. Also, instead of being circular, the outer and inner row of cup receptacles **506** and **508** are U-shaped in this embodiment. As such, the outer and inner turntables **505** and **507** may be rotated so that the U-shaped opening of a particular outer row of cup receptacles **506** may be aligned with the U-shaped opening of a particular inner row of cup receptacles **508**. For example, a cup **520** is shown in FIG. **26** disposed in an outer row cup receptacle **506** that is aligned with an inner row cup receptacle **508**. The cup **520** may be filled with a beverage, via beverage dispensing station **502**, while positioned in the outer row of cup receptacle **508**.

(154) Referring also to FIG. **27** in a partial cut-away view, a slide assembly **530** positioned below the turntable assembly **510** includes an arm **532** that may be actuated to extend through the opening **512** in the outer row of cup receptacles **506** retaining the cup **520** and slide or move cup **520** from a

position in the outer row cup receptacle **506** to the into the aligned inner row cup receptacle **508**. Once cups **520** are filled with beverages, the cups **520** may remain in the outer row of cup receptacles **506** or slide into unoccupied cup receptacles in one of the inner row of cup receptacles **508**. Thus, in this embodiment, the inner row of cup receptacles **508** provides extra space for storing beverages filled on the outer row of cup receptacles **506** until they are retrieved for delivery to or by customers.

(155) FIG. **28** illustrates one embodiment of the slide assembly **530** in more detail. The slide assembly **530** includes the arm **532**, a rail **534**, a motor **536**, and a belt drive **538**. The arm **532** includes a portion **533** shaped to engage a curved side of cup **520**. The arm **532** is slideably mounted to the rail **534** and also connected to the belt drive **538**. The motor **536** is an electric motor, however in other embodiments, the motor **536** may comprise pneumatic motors, hydraulic motors, etc. The motor **536** is coupled to the belt drive **538** and when actuated, drives the belt drive **538** which causes the arm **532** to traverse the rail **534** and move the cup **520** as discussed above. The motor **536** may be coupled to computer and/or other systems that operate in concert to rotate the turntable **510** to bring the opening **512** (also referring to FIGS. **26** and **27**) in one of the outer row of cup receptacles **506** into alignment with the arm **532** for sliding cups, such as cup **520**, from the outer to the inner row of cup receptacles **506**, **508**.

(156) While the modified turntable assembly **504** shown in FIGS. **26** and **27** is illustrated with twelve cup receptacles in the outer row of cup receptacles **506** and seven cup receptacles in the inner row of cup receptacles **508**, the present disclosure contemplates fewer or more cup receptacles and fewer or more rows as may be determined by the overall size of the beverage production system **500**, size of the cups **520**, and other considerations as will suggest themselves to one skilled in the art.

(157) FIG. **29** is another partial cut-away view of the modified turntable assembly **504** illustrating the outer turntable **505** having the outer row of cup receptacles **506**. FIG. **29** illustrates another embodiment of the slide assembly **530** positioned below the modified turntable assembly **504**. As also shown in an exploded perspective view in FIG. **30A**, the slide assembly **530** in this embodiment includes an upper magnetic assembly **560** and a lower magnetic assembly **561**. The upper magnetic assembly **560** includes arm **532** with portion **533** configured to engage the cups **50** to transfer cups **50** from the outer row of cup receptacles **506** to the inner row of cup receptacles **508** via the opening **512** in the outer row of cup receptacles **506** substantially as discussed above. The upper magnetic assembly **560** includes a body **562** that may be a metal, plastic, or polymeric body or covering that houses a magnet located within in a lower plate area **563** of the upper magnetic assembly **560**. The magnet located in the lower plate area **563** may be integrally formed with the lower plate area **563** or may be housed in an opening formed within the lower plate area **563**.

(158) The lower magnetic assembly **561** includes a bracket **564** that is generally L-shaped and includes a flat upper portion **565** that is generally parallel to the lower plate area **563** of the upper magnetic assembly **560**. The upper portion **565** includes a magnet **570** coupled to the upper portion **565**. The bracket **564** also includes a side portion **566** that is generally perpendicular to the upper portion **565**. The bracket **564** includes a lip **567** and a mounting point **568**. The lower magnetic assembly **561** is mounted to the rail **534** of the slide assembly **530** by engagement of the lip **567** with an upper portion of the rail **534** and attached at the mounting point **568** to an arm **569** mounted on a side of the rail **534**. In this manner, as a belt drive **538** of the slide assembly **530** engages the arm **569** and traverses rail **534**, the lower magnetic assembly **561** is carried forward and backward atop the rail **534**. In some embodiments, the lip **567** of the lower magnetic assembly **561** may be mounted to a carriage **572** that is positioned atop the rail **534** and the belt drive **538** engages the carriage **572** and/or arm **569** to promote movement of the lower magnetic assembly **561** along slide assembly **530**. The magnets of the upper and lower magnetic assemblies **560**, **561** may be integrally formed, provided in openings or recesses in respective assemblies, press fitted, glued, mechanically

fastened, or otherwise configured as will be readily apparent to one skilled in the art.

(159) The magnets in the upper and lower magnetic assemblies **560**, **561** may in some embodiment include multiple magnets in each of the upper and lower assemblies **560**, **561**. In embodiments with multiple magnets in each of the upper and lower assemblies **560**, **561**, some of the magnets may be positioned with a different direction of polarity relative to the polarities of the other magnets in each of the upper and lower assemblies **560**, **561** so that the upper magnetic assembly **560** can only be magnetically positioned in one (the correct position, as show for example in FIG. **29**) direction or orientation to prevent the operator from inadvertently placing the upper magnetic assembly **560** facing the wrong direction.

(160) The rail **534** and lower magnetic assembly **561** are position below a sink **600** (discussed below with regard to FIGS. **31-35**, not shown in FIG. **29**). The modified turntable assembly **504** is disposed within the sink **600** so that spillage and waste from beverage preparation spills into the sink for draining and cleaning. The upper magnetic assembly **560** is mounted above the sink **600** just above the lower magnetic assembly **561**. Thus, the sink **600** is positioned in a gap **571** between upper and lower magnetic assemblies **560**, **561**. In this manner, when the rail **534** causes the lower magnetic assembly **561** to traverse the slide assembly **530**, the attraction of the magnet **570** on the upper portion **565** of the lower magnetic assembly **561** to the magnet in the body **562** in the upper magnetic assembly **560** causes the upper magnetic assembly **560** to traverse a course corresponding to the lower magnetic assembly **561** within and along the bottom of the sink **600**.

(161) Since the upper magnetic assembly **560** is disposed in the bottom of the sink **600** where spillage from beverages prepared by the beverage production system **500** may collect, the upper magnetic assembly **560** may require periodic cleaning. As discussed above, the upper magnetic assembly **560** may be fabricated such that the outer surfaces are plastic, polymeric, or otherwise provided with a coating that allows for easy cleaning. In this manner, the upper magnetic assembly **560** may be easily removed for cleaning since there is no mechanical or fixed connection with the slide assembly **530** and the only engagement between the upper and lower magnetic assemblies **560**, **561** is magnetic. Thus, the magnetic coupling of the upper and lower magnetic assemblies **560**, **561** allows for easy, by-hand removal and replacement by a user or operator of the beverage production system **500** without need of tools or disassembly of the slide assembly **530**. Further this configuration prevents spillage from preparation of beverages to contact the lower magnetic assembly **561**, the motor **536**, the belt drive **538**, rail **534**, and so on positioned below or under the sink.

(162) FIG. **30B** is a perspective view of another embodiment illustrating the lower magnetic assembly **561** coupled to the carriage **572** with the remainder of the slide assembly **530** and outer turntable **505** cut-away. FIG. **30C** illustrates a lower or underneath perspective view of the inner and outer turntables **505**, **507** and the slide assembly **530**. In the illustrated embodiments, the upper magnetic assembly **560** is provided with a pusher plate **573** that may be attached to a bottom or lower portion of the body **562** of the upper magnetic assembly **560**. In some embodiments, the pusher plate **573** may not be attached to the bottom of the body **562** but instead merely attached or fitted to the front end **574** of the body **562**. The pusher plate **573** may be configured with a wedge **575** or V-shaped front edge. It will be appreciated that ice dispensed into cups **50** located in the outer turntable **505** may spill and collect in the outer row of cup receptacles **506**, and as cups **50** are moved to the inner row of cup receptacles **508**, ice may be pushed by the cups **50** and consequently also collect in to the inner row of cup receptacles **508**. The ice may further fall and collect in the sink **600** below the inner and outer turntables **505**, **507**. Since the upper magnetic assembly **560** is positioned in the bottom of the sink **600**, the ice may impede the smooth and efficient transition of the upper slide assembly **560** along the bottom of the sink **600** while transferring cups **50** between the outer and inner turntables **505**, **507**. The wedge **575** front edge of the pusher plate **573** acts as a snow plow moving or displacing ice located in the bottom of the sink **600** in the path of the upper magnetic assembly **560** during cup transfer.

(163) FIGS. 30B-C also show another embodiment of the inner turntable 507 with modifications to the inner row of cup receptacles 508. In this embodiment, an opening 576 is provided in a back low portion 577 of each of the inner row of cup receptacles 508. The opening 576 allows for ice that collects or is pushed into the inner row of cup receptacles 508, for example by cups 50, to further be pushed and exit the inner row of cup receptacles 508, via opening 576, and fall into the sink 600 position below the inner turntable 507. This prevents the build-up of ice that might otherwise collect in bottom of the inner row of cup receptacles 508 and impede the transfer of cups 50 into the inner row of cup receptacles 508.

(164) Further in this embodiment, the inner row of cup receptacles 508 includes a ramp 578 along a lower front edge 579 of the inner row of cup receptacles 508. The ramp 578 gradually increases in height or thickness from the lower front edge 579 toward a height of a bottom 585 of the inner row of cup receptacles 508. The ramp 578 allows a bottom edge of the cups 50 to transition more smoothly from the outer to the inner row of cup receptacles 506, 508, instead of striking or catching on a vertical or abrupt edge at the lower front edge 579 of the inner row of cup receptacles 508.

(165) Also shown in FIGS. 30B-C is a notch 587 that forms a rectangular opening along the lower front edge 579 of the inner row of cup receptacles 508. The notch 587 allows the arm 532 of the upper magnetic assembly 560 to extend sufficiently into the inner row of cup receptacles 508 to allow for movement of the cup 50 completely into position in the inner row of cup receptacles 508.

(166) FIG. 31 is a perspective view of the modified turntable assembly 504 disposed in a sink 600 according to another embodiment of the beverage production system 500. In this embodiment, an upper sensor 588 is shown positioned above the inner turntable 507. The upper sensor 588 may be attached to a portion or structure of the beverage production system 500 above the inner turntable 507. The upper sensor 588 is positioned to sense, vertically relative to the surface of the turntable 504, the presence or absence of a cup 50 in the inner row of cup receptacles 508. In this embodiment, only one sensor 588 is provided and positioned to determine whether a cup 50 is located in the inner row cup receptacle 508 at the position where cups 50 are transitioned by the slide assembly 530 from the outer to the inner row of cup receptacles 506, 508. However, it should be appreciated that in other embodiments, one or more additional sensors may be used and positioned to detect the presence of cups 50 in other locations or the presence of cups 50 in all the cup receptacles in the inner turntable 507. Further upper sensor 588 may be movable, such as driven by a motor, to sense cups 50 in other locations, or may include an array of sensors variously directed to sense cups 50 in any combination of cup receptacles in the inner turntable 507.

(167) Similarly, a side sensor 589 is position adjacent the outer turntable 505 and may be attached to the sink 600 or to other structures of the beverage production system 500. The side sensor 589 is positioned to sense, horizontally relative to the surface of the turntable 504, the presence or absence of a cup 50 in the outer row of cup receptacles 506. In this embodiment, only one sensor 589 is provided and positioned to determine whether a cup 50 is located in the outer row cup receptacle 506 at the position where cups 50 are transitioned by the slide assembly 530 from the outer to the inner row of cup receptacles 506, 508. The side sensor 589 may be positioned at a height so as to detect horizontally across and above the outer turntable 505 and a portion of a cup 50 extending above outer turntable 505. It should be appreciated that in other embodiments, one or more additional sensors may be used and positioned to detect the presence of cups in other locations or the presence of cups 50 in all the cup receptacles in the outer turntable 505. Further, lower sensor 589 may be movable, such as driven by a motor, to sense cups 50 in other locations, or may include an array of sensors variously directed to sense cups 50 in any combination of cup receptacles in the outer turntable 505. The sensor 588, 589 may be photoelectric, ultrasonic, passive infrared or other motion sensors, infrared transducers, ultrasonic, cameras, computer visions, combinations thereof, or any known or after developed sensor capable of detecting the presence of one or more cups 50 in the inner and/or outer row of cup receptacles 506, 508.

(168) The following is a brief overview, according to one embodiment, of the operation of a portion of the beverage production system **500**. In one embodiment, the slide assembly **530** is positioned to transition cups **50** from the outer to the inner row of cup receptacles **506**, **508** at a location immediately preceding the location in the outer turntable **505** where cups **50** are dispensed and filled. As cups **50** are dispensed and filled, the fulfilled beverages remain in cup receptacles in the outer turntable **505**. As the outer turntable **505** is rotated, for example in a clock-wise direction, to continue dispensing and filling beverages, the side sensor **589** determines whether a cup **50** is present in the cup receptacle located adjacent the slide assembly **530**. If no cup **50** is detected, the outer turntable **505** may be rotated to continue filling beverages. However, if the side sensor **589** detects a cup **50** in the adjacent cup receptacle in the outer turntable **505**, then the upper sensor **588** detects whether a cup **50** is present in the inner row cup receptacle **508** at the location a cup **50** is transitioned to the inner turntable **507** by the slide assembly **530**. If the upper sensor **588** determines no cup **50** is present in the adjacent inner row cup receptacle **508**, then the slide assembly is actuated and the cup **50** is moved or transitioned from the outer row cup receptacle **506** to the inner row cup receptacle **508**. The outer turntable **505** is then rotated to fill the next beverage in the cup receptacle vacated by the transition. If however the upper sensor **588** detects a cup **50** in the inner row cup receptacle **508** located adjacent the slide assembly **530**, then the inner turntable **507** is rotated, for example in either direction, to determine whether the next inner cup receptacle is occupied. If the next cup receptacle on the inner row is occupied, the inner turntable **507** continues to be rotated until an empty cup receptacle is located or it is determined that all cup receptacles in the inner turntable **507** are occupied. The system may employ logic to periodically rotate or re-check for empty cup receptacles on either or both the outer and inner turntables **505**, **507**.

(169) FIG. **31** illustrates details about the sink **600**. The sink **600** is substantially rectangular in this embodiment but may be oval, round, or otherwise shaped in other embodiments. The sink **600** may be constructed of plastic, polymeric, aluminum, or other materials. In this embodiment, the sink **600** a single, unitary component constructed of substantially polymeric material. Referring also to FIG. **32**, the sink **600** has upper outer edges **601** that extend around the sink **600** from a recessed tub **602**. The upper outer edges **601** are provided to retain and position the sink **600** in a cabinet, frame, or other structure (not shown) of the beverage production system **500**. The recessed tub **602** has a wall **604** that extends from a top surface **606** to a bottom surface **608** of the sink **600** that defines a generally round outer shape of the recessed tub **602**. The sink **600** includes an opening or drain **610** on the bottom surface **608** where spillage and waste from beverages produced by the beverage production system **500** may collect and be removed from the sink **600**. Plumbing (not shown) may be connected the drain **610** to evacuate the spillage and waste.

(170) Referring to FIGS. **31-33**, the sink **600** and recessed tub **602** are resized to receive the modified turntable assembly **504**. In this view, the outer and inner turntables **505** and **507** with outer and inner rows of cup receptacles **506** and **508** are shown positioned in the recessed tub **602** of sink **600**. Notably, cup holders **506a** (discussed in greater detail below) are shown disposed in the outer row of cup receptacles **506** in FIG. **31** and shown removed from the view illustrated in FIG. **33**. In some embodiments, such as illustrated in FIGS. **31-36**, the cup holder **506a** may only be provided in the outer row of cup receptacles **506** and the inner row of cup receptacles **508** may not include the cup holder **506a** but instead the cup holders may be integrally formed as part of the inner turntable **507**.

(171) The recessed tub **602** may include a lip **612** (see FIG. **32**) extending about an upper portion of the recessed tub **602** that is configured to receive an outer edge **614** (see FIG. **31**) of the outer turntable **505**. The wall **604** may include ribs **616** extending from wall **604** or other various configurations to promote engagement with mating portions (not shown) of the outer turntable **505**. Further, a feature **619**, such as a track or channel is formed in the bottom **608** of the sink **600**. The feature **619** is configured to promote guided movement of the upper magnetic assembly **560** along the bottom **608** of the sink **600** as the slide assembly **530** is actuated, as discussed above with

regard to FIGS. 27-30.

(172) The sink **600** may also include a centering post **618** provided in the middle of the recessed tub **602** and extending from the bottom **608** of the sink **600** which is configured to mate with an opening **620** in the center of the inner turntable **507**. In some embodiments, the centering post **618** is provided to orient the inner turntable **507** for rotation about the centering post **618**. In this embodiment, a motor or drive may be positioned elsewhere and engage the inner turntable **507** for rotation of the inner turntable **507**. Referring also to FIG. 34, a side view of the sink **600** is illustrated. In this embodiment, the centering post **618** may be omitted and an opening (not shown) in the bottom **608** of the sink **600** may be provided at the location of the centering post **618**. A motor **630** may drive a shaft **632** that extends through the opening and an engagement end **634** (see also FIG. 35) of the shaft **632** may be configured for attachment to the inner turntable **507** for rotation of the inner turntable **507**. In this embodiment, the inner turntable **507** is formed with a centrally located opening formed to mate with the engagement end **634** of the shaft **632** for rotation. As illustrated in FIG. 34, the sink **600** can be seen as generally sloped from a left side **635** to a right side **636** towards the drain **610** to promote flow of liquid spillage in the recessed tub **602** toward the drain **610** for evacuation.

(173) In the embodiment illustrated in FIG. 35, the sink **600** may also include an inner wall **638** that generally defines an inner concentric ring (relative to an outer concentric ring defined by the wall **604** of the recessed tub **602**) within the recessed tub **602** that is sized and configured to receive the inner turntable **507**. In this embodiment, the inner wall **638** does not form a complete circle and includes an opening **640**. The opening **640** is provided at the location on the modified turntable assembly **504** at which cups **50** are transferred from the outer row of cup receptacles **506** to the inner row of cup receptacles **508** by the slide assembly **530**, as previously discussed, to allow the cups **50** to pass therebetween. The inner wall **638** may provide additional structure to stabilize the inner turntable **507** during rotation and may also act as a barrier to prevent cups **50** not being transitioned between outer and inner turntables **505** and **507** from moving or slipping out of the inner row of cup receptacles **508** during rotation. In this embodiment, the inner wall **638** may prevent liquid spillage from directly reaching the drain **610**. Accordingly, in this embodiment, the inner wall **638** may be provided with a drain access opening **642** along a lower portion of the wall **638** adjacent the bottom **608** portion of the sink **600**. The drain access opening **642** may be located on a side of the wall **638** nearest the drain **610** such that the sloped overall design of the sink **600** bottom **608** discussed above (see FIG. 34) allows spillage to exit the area within the inner wall **638** and flow to the drain **610**.

(174) As can be seen in FIGS. 29-35, each of the individual cup holders **506a**, the outer and inner turntables **505** and **507**, and the upper magnetic assembly **560** of the slide assembly **530** are all readily removeable, separately or together, for ease of cleaning the individual cup holders **506a**, the outer and inner turntables **505** and **507**, and the upper magnetic assembly **560**. Once removed, the sink **600** and recessed tub **602** can be accessed and cleaned, with or without removal of the sink **600**, and any excess fluid from cleaning will slope to the drain **610** and exit the sink **600**. Thus, the inner turntable **507** can be easily removed and replaced back into position in the sink by simply lifting the inner turntable **507** out of resting engagement with the engagement end **634** (see also FIG. 35) of the shaft **632**. Similarly, the outer turntable **505** may be easily removed and replaced into position in the sink **600** without any disassembly or reassembly of drive system or other components.

(175) FIGS. 36A-E, are perspective views illustrating one embodiment of a drive system **700** for driving the outer turntable **505**. FIG. 36A illustrates the outer turntable **505** disposed in the recessed tub **602** of the sink **600**. In this embodiment, the drive system **700** may include two pinch drives **704** and two idlers **706** mounted to the sink **600**. The pinch drives **704** each include an electric motor **702**, but in other embodiments pneumatic or other systems may be employed. The motor **702** drives up-down pinch rollers **708**, **710**. In some embodiments, the electric motor **702** may drive the

rotation of both pinch rollers **708, 710**, while in other embodiments the drive may drive the rotation of only the down pinch roller **710** and the up pinch roller **708** is provided for stability and tensioning or vice-versa. The pinch drive **704** and up-down pinch rollers **708, 710** can be seen in exploded view in FIG. **36E** where an edge portion **712** of the outer turntable **505** is shown positioned between the up-down pinch rollers **708, 710** such that the up-down pinch rollers **708, 710** frictionally engage the upper and lower surfaces of the edge portion **712** of the outer turntable **505**. Thus, as the electric motor **702** drives one or both of the pinch rollers **708, 710**, the frictional engagement of the up-down pinch rollers **708, 710** with the edge portion **712** of the outer turntable **505** promotes rotation of the outer turntable **505** in the desired direction.

(176) Idlers **706** include idle roller **714** and lift bearing **716**. Idle roller **714** is positioned against and engages the outer edge of the outer turntable **505** and is provided to tension and stabilize the outer turntable **505** along a horizontal plane parallel to the upper horizontal surface of the outer turntable **505**. Similarly lift bearing **716** is located under and engages a lower surface of the edge portion **712** of the outer turntable **505** and is provided to tension and stabilize the outer turntable **505** along a vertical plane parallel to the vertical surface of wall **604** of the recessed tub **602**, for example to prevent sagging of the outer turntable **505** near the location of the idler **706**. The up-down pinch rollers **708, 710** and idle roller **714** and lift bearing **716** may be constructed of rubber or other material to promote frictional engagement of the rollers with the outer turntable **505** surfaces.

(177) Although pinch drives **704** and idlers **706** are shown disposed at certain positions about the sink **600** and outer turntable **505**, the pinch drives **704** and idlers **706** may be provided in other arrangements and configurations in other embodiments. Similarly, although two pinch drives **704** and two idlers **706** are shown, it is contemplated that fewer or more may be provided in other embodiments. Also, while two idlers **706** are described, it will be appreciated that the idlers **706** are provided primarily to support the outer turntable **505** and that other support structures or systems may be employed as will readily suggest themselves to one skilled in the art.

(178) Referring to FIG. **37**, a portion of the beverage production system **500** is shown in more detail. A cup **50** is shown disposed in one of the outer row of cup receptacles **506** (shown in partial cut-away) of the modified turntable assembly **504** (also shown in partial cut-away). The lidding and printing assembly **502** and beverage dispensing station **503** are also illustrated.

(179) Referring also to FIG. **38**, the lidding and printing assembly **502** is shown in more detail. The lidding and printing assembly **502** includes sealing film **544**, an in-line printer **540**, and piercer **542**. The sealing film **544** may be provided in a roll (as shown) and positioned on a series of rollers **546**. The sealing film **544** may be fed into one or more motor/rollers **548** such that when the sealing film **544** is drawn by the one or more motor/rollers **548** the roll of sealing film **544** unrolls and extends above the cup **50** into position for sealing as a lid **60**. The in-line printer **540** prints beverage identifying indicia on the upper or top side of the sealing film **544** such that it is visible to the server or customer. The beverage identifying indicia may identify the type and size of the beverage, associated order number, customer name, or other any other useful or identifying information.

(180) The piercer **542** may puncture a hole, score, or make various indentions in the sealing film **544** to promote introduction of, for example but not limited to, a drinking straw through the sealing film **544**. Sealer bulbs **550** are positioned above the sealing film **544** and cup **50** lip or rim. The sealer bulbs **550** may then be electrified to generate heat to heat seal the sealing film **544** about the lip or rim of the cup **50**. The sealing film **544** may then be separated, such as but not limited to, by cutting the sealing film **544** or tearing along perforated or scored sections of the sealing film **544**. The present disclosure also contemplates that the process of printing, piercing, and heat sealing may occur in other orders in other embodiments.

(181) Also shown in FIG. **38** is a lift assembly **580**. The lift assembly **580** operates to lift the cup **50** vertically from a seated position in the outer row of cup receptacles **506** to bring the top lip or rim

of the cup 50 into position below the lidding and printing assembly 502 for lidding the cup 50. Lift assembly 580 includes a linear actuator 582 and cup centering device 584. The cup centering device 584 is coupled to an elbow 586 that extends from the bottom of the linear actuator 582. A belt driven motor (not shown) drives the linear actuator 582 vertically up and down perpendicular to a plane parallel with the surface of the modified turntable assembly 504. The belt driven motor (not shown) may be electric, hydraulic, pneumatic, etc. A plunger and limit switch 583 is configured to determine when the linear actuator 582 has raised the cup 50 vertically sufficient into position for lidding.

(182) Referring also to FIG. 39A, a top down view of a portion of the modified turntable assembly 504 is shown. As can be seen, the cup centering device 584 is positioned in an opening in a bottom 590 of the outer row of cup receptacles 506. In the present embodiment, the cup centering device 584 is cross-shaped and extends through a larger but similarly configured cross-shaped opening 581 in a bottom of the outer row of cup receptacle 506. FIG. 39B further illustrates a perspective view in more detail of one of the outer row cup receptacle 506, which may also be referred to as cup holder 506a. The cup centering device 584 is configured to engage a bottom of the cup 50 and lift the cup 50 vertically out of the outer row of cup receptacles 506 as the linear actuator 582 raises. The cup centering device 584 may be configured to promote engagement of the bottom of the cup 50 so that the cup centering device 584 is generally centered about the bottom of the cup 50 to stabilize the cup 50 during the lifting and lowering process. Although the cup centering device 584 is shown as generally cross-shaped, other shapes and configurations will readily suggest themselves as alternatives for engaging the bottom of the cup 50 for these purposes.

(183) When the lidding and printing process is complete, the linear actuator 582 lowers the cup 50 back into position in the outer row of cup receptacles 506. Before the outer turntable 505 is rotated, the linear actuator 582 may be further lowered such that the cup centering device 584 is positioned below and clear of the bottom of the outer row of cup receptacles 506 so as not to interfere with the rotation of the outer turntable 505.

(184) In other embodiments (not shown), all or portions of the lidding and printing assembly 502 may be positioned above the cup 50 and moved vertically downward toward the cup 50 for lidding the cup 50 while the cup 50 remains stationary in the outer row of cup receptacles 506.

(185) FIG. 40A illustrates another view of a portion of the beverage production system 500. An ice chute 594 is shown connected to a portion of an ice dispenser 596 for dispensing ice into cups 50 positioned in the outer row of the cup receptacles 506. In this embodiment, the ice dispenser 596, as previously discussed with reference to FIG. 12, is configured to provide ice only into cups 50 on the outer row of cup receptacles 506. FIGS. 40B and 40C illustrate yet other portions of the beverage production system 500. As can be seen, the beverage production system 500 includes the cup dispensing station 130, ice dispensing chute 594, beverage dispensing station 503, and printing and lidding assembly 502 positioned in series. Thus, the beverage production system 500 fulfills orders by dispensing cups 50 into the outer row of cup receptacles 506, dispensing ice into the cups 50, filling the cups 50 with the beverage via the beverage dispensing station 503, and lidding and printing the label on the cup 50 via the lidding and printing assembly 502. As discussed above, the process also includes moving, as desired, the filled beverages from the outer row of cup receptacles 506 to the inner row of cup receptacles 508 to enable more beverages to be prepared and stored until retrieved for service.

(186) It will be appreciated that the overall configuration of the beverage production system 500 may have advantages over the beverage production system 100 described further above. For example, fulfilling beverage in only the outer row of cup receptacles 506 may be accomplished with only a single station for each of dispensing cups, ice, beverages, and lidding versus multiple rows which require multiple stations for each process and consequently require extra space, equipment, and complexity.

(187) Referring now to FIG. 41, another embodiment of a beverage production system 800 is

shown. The beverage production system **800** includes support table **810**, as well as several components of the systems described above including a beverage handling assembly **120** positioned on the support table **810**, and an ice chamber **112** and electronics housing **814** disposed under table **810**.

(188) Beverage handling assembly **120** includes a plurality of stations for performing various stages or steps of the beverage production process. In particular, beverage handling assembly **120** includes a cup dispensing station **130**, an ice dispensing station **180**, a beverage dispensing station **190**, and a lidding station **200**. Beverages may be produced by progressing through the stations **130, 180, 190, 200** with a conveyor assembly **822**.

(189) Referring now to FIG. **42**, conveyor assembly **822** includes a central hub **824** and a plurality of cup receptacles **828** movably coupled to hub **824**. In particular, central hub **824** has perimeter or side surface **826** that is obround or stadium shaped. The cup receptacles **828** are moveably coupled to central hub **824** such that during operation cup receptacles **828** may be traversed along the perimeter **826** to progress through the stations **130, 180, 190, 200** of beverage handling assembly **120**.

(190) Referring now to FIG. **43**, in some embodiments, cup receptacles **828** may be coupled to a continuous conveyor **821** that is rotated about a pair of pulleys **823**. The conveyor **821** may comprise a belt or chain that is coupled to the plurality of cup receptacles **828**. In particular, each cup receptacle **828** includes a cup holder **829** that is coupled to the conveyor **821** with a support **827**. Each pulley **823** includes a central axis **825**. During operations, one or both of the pulleys **823** may be actuated (e.g., via an electric, pneumatic, hydraulic motor or other suitable driver) to rotate about the corresponding axes **825** to thereby rotate conveyor **821** generally about central hub **824**. The rotation of conveyor **821** about pulleys **823** also moves the cup receptacles **828** along the perimeter **826** of central hub **824**.

(191) Cup receptacles **828** may include a number of different shapes, designs, and features in various embodiments. For instance, referring now to FIG. **44**, in some embodiments, cup holder **829** may comprise a ring that may tightly engage with a cup **50** so as to prevent (or at least restrict) movement of the cup **50** therein as the cup receptacle **828** is moved along the perimeter **826** of central hub **824** during operations (FIGS. **42** and **43**).

(192) Referring now to FIG. **45**, in some embodiments, cup holders **829** may comprise a cup-shaped member having a sidewall **841** and a bottom **842**. The side wall **841** may loosely contact the cup **50** in some embodiments to allow some movement of cup **50** within the cup holder **829** during operations.

(193) Referring now to FIG. **46**, in some embodiments, cup holders **829** may comprise a plurality of leaf spring elements **844** that are biased into engagement with a cup **50** (FIGS. **42** and **43**) inserted therein. In some embodiments, the leaf spring elements **844** may engage with cup **50** to prevent movement of cup **50** during operations.

(194) Referring now to FIG. **47**, in some embodiments, cup holders **829** may comprise a pair of gripper arms **846** that may actuate to engage with and hold a cup **50** during operations. For instance, in some embodiments, one or both of the gripper arms **846** are pivotably coupled to an elongate member **848** that may telescope into support **827**. A biasing member **849** (e.g., a coiled spring) may be coupled to elongate member **848** to bias elongate member **848** into support **827**. As elongate member **848** moves into support **827** (e.g., via biasing member **849**), the gripper arms **846** may engage with support **827** and rotate toward one another about axes **845**. Thus, during operations, when a cup **50** is inserted within holder **829**, the gripper arms **846** may close on the inserted cup **50** via the spring force provided by biasing member **849**. In addition, in some embodiments, an additional support ring **843** may be included on holder **829**, below gripper arms **846** to provide additional support to cups **50** inserted therein. Without being limited to this or any other theory, the actuation of the gripper arms **846** may allow different sizes (e.g., having different widths) to be securely held within cup holders **829** during operations. In some embodiments,

gripper arms **846** may actuate away from one away from one another against the spring force provide by biasing member **849** to accept a dispensed cup **50** when holder **829** is aligned with the cup dispensing station **130**. The actuation of the gripper arms **846** away from one another may be accomplished via engagement of the gripper arms **846** (or a component coupled thereto) with a camming surface on or adjacent to conveyor assembly **822**.

(195) Referring now to FIGS. **42** and **43**, as will be described in more detail below, during operations, cup receptacles **828** may be moved along perimeter **826** of central hub **824** so as to align the cup receptacles **828** (and particularly cup holders **829**) with the stations **130**, **180**, **190**, **200** to dispense cups **50**, ice, beverages, and lids **60**, respectively, as part of the beverage production process.

(196) Referring to FIG. **41**, the beverage production system **800** may include systems substantially similar in operation and configuration to those previously described above, such as tubular magazines **132**, dispenser **134**, of the cup dispensing station **130**, beverage dispensing nozzle **194**, tubular magazine **202** containing lids **60** of the lidding station **200**.

(197) In addition, beverage production system **800** is provided with a user interface **116**. An employee or customer may select the desired beverage(s) on the user interface **116** which then initiates the beverage production process generally described above. In some embodiments, the beverage production system **800** may receive commands to produce beverages via other electronic devices that are communicatively coupled to beverage production and dispensing system **800** via a suitable network or connection. For instance, in some embodiments, beverage production system **800** may receive commands to produce beverages from a point-of-sale system of the restaurant or dining facility that may receive orders via customer or employee. In some embodiments, the point-of-sale system may comprise part of a computer system that also includes the beverage production system **800** (e.g., computer system **400** described above).

(198) Once commands to produce beverage(s) are received by beverage production system **800**, the cup receptacles **828** may be progressed through the stations **130**, **180**, **190**, **200** via conveyor assembly **822** as previously described. Simultaneously, the assemblies and mechanisms within each of the stations **130**, **180**, **190**, **200** may actuate in the manner described above to produce beverages.

(199) In some embodiments, the beverage production system **800** may include a beverage identification assembly **860** to identify beverages that have advanced through the stations **130**, **180**, **190**, **200** and are ready for retrieval by an employee or customer. In particular, beverage identification assembly **860** may comprise a plurality of lights **862** (e.g., light emitting diodes (LED) and/or other suitable light emitting devices) coupled to beverage handling assembly **120** that are configured to emit a selected color of light that may correspond with a particular beverage (or order). During operations, the cups **50** (including or not including lids **60**) may be aligned with selected ones of the lights **862** via conveyor assembly **822**, and the lights **862** emit a color of light that corresponds with the aligned beverage(s). In some embodiments, the lights **862** may comprise electronic displays (e.g., liquid crystal displays, plasma displays, organic LED (OLED) displays, micro-LED displays) that may display images (e.g., text and/or symbols) to convey sufficient information (e.g., names, order number, table number, vehicle identification) for identifying the beverages.

(200) Referring now to FIG. **48**, another embodiment of a beverage production system **900** is shown. The beverage production system **900** may include a number of features substantially similar in configuration and operation to those previously discussed such as the support table **810**, the beverage handling assembly **120** positioned on the support table **810**, an ice chamber **112** supported above beverage handling assembly **120**, and an electronics housing **814** disposed under table **810**.

(201) Beverage handling assembly **120** includes the plurality of stations for performing various stages or steps of the beverage production process. In particular, beverage handling assembly **120** includes the cup dispensing station **130**, the ice dispensing station **180**, the beverage dispensing station **190**, and the lidding station **200**.

(202) Beverages may be produced by progressing through the stations **130, 180, 190, 200** with a turntable **922**. More specifically, turntable **922** is a cylindrical member that includes a plurality of cup receptacles **925** disposed about a peripheral edge thereof. During operation, a driver (e.g., electric motor, hydraulic motor, magnetic motor, pneumatic motor) may rotate the turntable **922** about a central axis **927** to align the cup receptacles **925** with the stations **130, 180, 190, 200** to dispense cups **50**, ice, beverages, and lids **60**, respectively, as part of the beverage production process.

(203) In this embodiment, referring now to FIGS. **48** and **49**, a plurality of magazines **132** are coupled to and extend from corresponding dispensers **134**.

(204) Magazines **132** may receive a plurality of stacked cups **50** therein. Each dispenser **134** is generally aligned with the cup receptacles **925** so that during operations, cups **50** may be supplied to dispensers **134** from magazines **132**, and then are dispensed from dispensers **134** into aligned cup receptacles **925** on turntable **922**. In some embodiments, magazines **132** may be de-coupled from dispensers **132** to facilitate loading of cups **50** therein.

(205) In some embodiments, each dispenser **134** may be configured to dispense a different size and/or type of cup **50** into cup receptacles **925** during operations. As shown in FIG. **48**, dispensers **134** are arranged such that each dispenser **134** is aligned with a different one of the cup receptacles **925** for a particular rotative position of turntable **922** about axis **927**.

(206) Referring specifically now to FIG. **49**, each dispenser **134** includes a central axis **135**, a first or upper side **134a** and a second or lower side **134b** opposite upper side **134a**. A receptacle **136** extends axially through dispenser **134** between sides **134a, 134b** with respect to axis **135**. The corresponding magazine **132** is engaged within receptacles **136** on upper side **134a** and extends away from upper side **134a** along axis **135**. During operations, cups **50** that are dispensed from magazines **132** move through receptacle **136** and are ejected from lower side **134b**.

(207) Dispenser **134** has an internal chamber **167** that cups **50** may enter and exit through via the receptacle **136**. A ring gear **166** is disposed within chamber **167** and aligned with receptacle **136** along axis **135**. A driving gear **168** is engaged (e.g., meshed) with gear teeth or other suitable structures on a radially outer surface of each of the ring gear **166**. Driving gear **168** is coupled to a driver **162** that may be mounted within internal chamber **167**. During operations, driver **162** may rotate driving gear **168** to thereby drive rotation of the ring gear **166** about axis **135**. In some embodiments, driver **162** comprises an electric motor; however, in other embodiments, the driver **162** may comprise a pneumatic motor, a hydraulic motor, etc. A plurality of wedge members **164** are positioned within ring gear **166**, each wedge member **164** includes a cylindrical body **174** including a central or longitudinal axis. The dispenser **134** otherwise operates substantially similar to that described above with regard to FIGS. **6** and **7**.

(208) Referring now to FIG. **50**, another embodiment of a beverage production system **1000** is shown. Similar to the systems discussed above, the beverage production system **1000** includes support table **810**, a beverage handling assembly **120** positioned on the support table **1110**, an ice chamber **112** supported above the beverage handling assembly **120**, and an electronics housing **814** disposed under table **810**.

(209) Beverage handling assembly **120** includes a plurality of stations for performing various stages or steps of the beverage production process that may be similar in configuration and operation to those previously discussed above, such as the cup dispensing station **130**, the ice dispensing station **180**, the beverage dispensing station **190**, and the lidding station **200**. Beverages may be produced by progressing through the stations **130, 180, 190, 200** with a conveyor assembly **1122**. In some embodiments, conveyor assembly **1122** may be configured and operate similar to conveyor **822** described above with regard to FIGS. **42-47**. Similarly, cup dispensing station **120** and lidding station **200** may operate according to any of the various configuration discussed above.

(210) Beverage production system **1000** may also include beverage identification assembly **1260** may comprise a plurality of emitters **1262** coupled to beverage handling assembly **120** that are

configured to emit light **1264** onto cups **50** and (if present) lids **60** that may be used to identify a particular beverage or beverage order. In some embodiments, the light **1264** may be color-coded so as to identify a particular beverage (or order) with a different color. In some embodiments, the light **1264** may form images (e.g., text and/or symbols) on the beverages that may provide sufficient information (e.g., names, order number, table number, vehicle identification). In some embodiments, emitters **1262** may comprise light emitting diodes (LEDs) and/or other suitable light emitting devices.

(211) FIGS. **51-53** illustrate yet another embodiment of a beverage production system **1300**. The beverage production system **1300** may be similar to the various beverage production systems previously described, such as for example the beverage production system **500**, in some respects. For example, in this embodiment, the modified turntable assembly **504** includes the outer turntable **505** and an inner turntable **507**. However, in this embodiment, the outer turntable **505** does not have the outer row of cup receptacles **506** and instead the outer turntable **505** is a flat rotating surface or dial **1302**. The dial **1302** may be constructed of various materials including plastic or polymeric materials, rubber, stainless steel, or other materials. In some embodiments, the dial **1302** may be constructed of materials that promote frictional engagement of the cup **50** with the dial **1302** to prevent cups from sliding off the dial **1302** while still allowing the cups **50** to be transitioned onto the dial **1302**. The inner turntable **507**, in this embodiment, continues to have the inner row of cup receptacles **508**. In the present embodiment of the beverage production system **1300**, the inner row of cup receptacles **508**, which may also be referred to as cup holders **506a** in this portion of the description, are separate, removable components from the inner turntable **507**, although it is contemplated that these components may be integrally formed in other embodiments. Similar to that described above, the inner and outer turntables **505** and **507** are configured to rotate independently from one another and may comprise drives, motors, and gearboxes (not shown) that operate similar to those described above with regard to inner turntable **124** and outer turntable **126**, and the beverage production system **500** described above.

(212) The beverage production system **1300** employs another embodiment of the cup dispensing station **130**. In this embodiment, the plurality of tubular magazines **132** are fixed above the modified turntable assembly **504** and arranged to dispense cups **50** of various sizes into the inner row of cup receptacles **508**. Cups **50** are dispensed automatically from the tubular magazines **132** in various manners as previously discussed. For example, when a particular size beverage is ordered, the beverage production system **1300** causes the tubular magazine **132** containing the ordered size cup **50** to dispense or drop the cup **50** into the cup receptacle **506** immediately below using techniques described herein.

(213) In this embodiment, beverages are fulfilled in the inner turntable **507** and moved to the outer turntable **505** for retrieval by users. Referring to FIG. **53**, the beverage production system **1300** includes a separating wall **1304** that is rounded and located between the inner and outer turntables **507**, **505**. The separating wall **1304** provides a barrier to assist in the positioning of the cups **50** in the inner row of cup receptacles **508** as the cups **50** are dropped into the inner row of cup receptacles **508** and rotated to the stations for receiving ice and a beverage.

(214) Referring also to FIG. **54**, in some embodiments, a sink **1307**, similar to sink **600** described above, may be employed in the present embodiment and be modified to include the separating wall **1304** as a component of or integral to the sink **1307**. The separating wall **1304** includes a gap **1306** such that the separating wall **1304** does not extend completely around the circumference of the inner turntable **507**. The gap **1306** in the separating wall **1304** is located at a transfer location **1308** where cups **50** are transferred from the inner row cup receptacle **508** to the dial **1302** of the outer turntable **505**. Similar to that described above, cup receptacles **508** may include a receptacle opening **1310** to allow for a transition arm **1312** of a transition assembly (not shown) to slide a cup **50** located in the adjacent cup receptacle **508** onto the outer turntable **505**. The transition assembly may be similar to the slide assembly **530** discussed above and be magnetically driven or may

include other motors or drives to drive the transition arm **1312** to accomplish such movement of the cup **50**, as will be well understood to those skilled in the art. The transition arm **1312** may be similar in function to the arm **532**, discussed above, of the transition assembly **530**. In this embodiment, the transition arm **1312** is a substantially cylindrical shaft but may be otherwise configured in other embodiments.

(215) Referring also to FIG. **55**, the transition arm **1312** is illustrated in an extended position. Also illustrated is a transition platform **1314** located between a cup receptacle bottom **1316** and the dial **1302**. It will be appreciated that a width of the separating wall **1304** may create a spacing differential, in some embodiments, between the cup receptacle bottom **1316** and the dial **1302**. The transition platform **1314** spans the space between the cup receptacle bottom **1316** and the dial **1302** to allow for a smooth and even transition or movement of the cup **50** from the cup receptacle **580** to the dial **1302**. Also, as can be seen in the embodiments illustrated in FIGS. **54** and **55**, the inner turntable **507** includes an upper frame **1318** that is a substantially round plate configured with U-shaped openings **1320** configured to receive the cup holders **506a**. In this embodiment, an upper lip **1322** of the cup holders **506a** extend over the U-shaped openings **1320** and gravitationally rest on the upper frame **1316**.

(216) FIG. **55** illustrates the sink **1307** which is exposed by the removal of the upper frame **1316** and the plurality of cup receptacles **508**. While the upper frame **1318** and cup receptacles **508** are described as separate components, these and other components of the beverage production systems described herein may be integrally formed as one or more unitary components for ease of construction, operation, or based on other considerations.

(217) Also illustrated are drive system components **1324**, which may include motors, rollers, and other components, as previously described or otherwise needed, for rotating the inner and/or outer turntables **507**, **505**.

(218) FIG. **56** illustrates another view of the cup holder **506a**, according to the present embodiment. In this illustration, the upper lip **1322** and cup receptacle opening **1310** can be seen. Also referring to FIG. **57**, a bottom side **1326** of the cup holder **506a** is shown. As will be discussed in more detail below, in the present embodiment, the entire cup holder **506a** may be raised out of the inner turntable **507** as part of the beverage fulfillment process. While in the present embodiment, the cup holder **506a** is raised for the purposes of lidding the cup **50**, in other embodiments, the cup holder **506a** may be raised for dispensing ice and/or adding the beverage to the cup **50** as well. According to this embodiment, the bottom side **1326** of the cup holder **506a** is provided with grooves **1328** for being securely and stably lifted. While the present embodiment illustrates grooves **1328**, other embodiments anticipate various configurations for the bottom side **1326** of the cup receptacle **508** for stably engaging the cup receptacle **508** during vertical movement, as will readily suggest themselves to one skilled in the art.

(219) FIG. **58** illustrates one embodiment of a lift mechanism **1330** configured to vertically lift the cup receptacle **508** during beverage fulfillment. In this embodiment, the lift mechanism **1330** is provided underneath the inner turntable **507** and sink **1307** adjacent the cup receptacle **508** to be raised for lidding and printing. The lift mechanism **1330** includes generally a drive system **1332** and a plurality of lift shafts **1334**. The lift shafts **1334** are attached to the drive system **1332** such that when the drive system **1332** is actuated, the drive system **1332** causes the lift shafts **1334** to raise vertically. While the drive system **1332** may operate in various manners, in this embodiment, the drive system **1332** may include a stepper motor **1336** and lead screw **1338** attached thereto.

(220) Referring also to FIG. **59**, a positioning plate **1340** may be mounted in the sink **1307** adjacent and below the location of the cup receptacle **508** to be lifted. The positioning plate **1340** is provided with plate openings **1342** sized to receive the lift shafts **1334** therethrough. The lift shaft ends **1344** are configured and arranged to engage the grooves **1328** on the bottom side **1326** of the cup holder **506a** when the lift shafts **1334** are actuated by the drive system **1332**. While lift mechanism **1330** is shown having three (3) lift shafts **1334**, other numbers of lift shafts **1334** may be used.

(221) FIGS. **60** and **61** illustrate a view of a lidding and printing system **1350** located above the inner turntable **507** above the cup receptacle **508** to be lifted by the lift mechanism **1330**. In this embodiment, the lift mechanism **1330** lifts the cup holder **506a** for lidding and printing a cup **50** located in the cup receptacle **508**. As discussed above, in other embodiments, other lift mechanisms **1330** may be provided for lifting other cup receptacle **508** at other beverage fulfillment locations. The lidding and printing system **1350** may include aspects of the lidding and printing assembly **502** discussed above for lidding and printing. For example, the lidding and printing system **1350** may include sealing film **544**, an in-line printer **540**, and piercer **542**, as discussed above, as well as other components. In this manner, when the cup receptacle **508** is lifted, a cup **50** located therein is positioned in the opening **1352** of the lidding and printing system **1350** for lidding and printing the cup **50**.

(222) FIG. **62** illustrates locations of the ice dispensing station **180**, the beverage dispensing station **190**, and the lidding and printing system **1350**, according to one embodiment. As can be seen, as the inner turntable **507** rotates clockwise, cups **50** are dispensed into the cup receptacles **508**, a cup **50** is positioned under the ice dispensing station **180** for dispensing ice into the cup **50**, then to the beverage dispensing station **190** for dispensing beverages into the cup **50**, and then to the lidding and printing system **1350** for lidding the cup **50** and providing identifying indicia on the lid.

(223) In this embodiment, the beverage dispensing station **190** includes two (2) nozzles **1353A**, **1353B** for dispensing beverages, although other numbers of nozzles are contemplated. In this embodiment, first nozzle **1353A** may be used to substantially fill the cup **50** with a beverage at a first location **1354**, while second nozzle **1353B** may be used to top-off or complete filling of the beverage at a second location **1356**. It may be useful to provide two beverage fill locations to completely fill the cup **50** with the desired beverage. However, in other embodiments, first and second nozzles **1353A**, **1353B** may be used to dispense different types of beverages, to provide redundancy, or increase the production or number of beverages that may be fulfilled.

(224) Once the beverage fulfillment is completed on the inner turntable **507**, the filled cup **50** may be transitioned to the outer turntable **505** via transitioning arm **132**. The outer turntable **505** may then be indexed or rotated clockwise one or more cup positions to provide space for the next completed beverage. By providing the outer turntable **505** with the dial **1302** instead of separate cup receptacles, this design may provide the benefit of providing additional space for a more completed beverage and also allow easier access to the completed beverages.

(225) Operationally, the beverage production system **1300** may receive input from point-of-sale or other systems, such as the computer system **400** as discussed above. Further, sensors provided at various locations about the beverage production system **1300** may be used to control the advancement of the inner and outer turntables **507**, **505** to ensure, for example, that completed beverages on the dial **1302** are accessible to users and further do not interfere with newly fulfilled beverages transitioning from the inner turntable **507**.

(226) While the beverage production system **1300** has been described as having cup receptacles **508** on only the inner turntable **507** and no cup receptacles on the outer turntable **505**, it is contemplated that the outer turntable **505** might have one or more cup holders **506a** and that the inner turntable **507** might have fewer or no cup receptacles **508** in other embodiments. Further, while beverage production is described in this embodiment as being accomplished on the inner turntable **507**, it is contemplated that beverages might also be fulfilled on the outer turntable **505** instead or in addition. Further, while filled beverages are described as being transitioned from the inner to the outer turntables **507**, **505**, filled beverages might remain in the inner turntable **507** or might be filled on the outer turntable **505** and transitioned to the inner turntable **507**.

(227) FIG. **63** illustrates a wiper **1360** that engages the dial **1302** to remove material **1362** that may collect on an upper surface **1364** of the dial **1302**. It will be appreciated that material, for example, beverage spillage, ice, and moisture may collect on the upper surface **1364** of the dial **1302** during beverage fulfillment. As the cups **50** are transitioned onto the dial **1302** the upper surface **1364** may

become slippery and cups **50** may not remain stable on the dial **1302** and undesirably slide or move on the dial **1302** when the outer turntable **505** is rotated or indexed. The wiper **1360**, in this embodiment, may include a body **1366** with an engaging member **1368** attached to a lower end **1370** of the engaging member **1368**. The engaging member **1368** is positioned adjacent the upper surface **1364** of the dial **1302**. As the dial **1302** rotates, the engaging member **1368** engages and wipes or removes moisture that may collect on the upper surface **1364** of the dial **1302**. In this embodiment, the wiper **1360** is located adjacent a left side **1372** of the beverage production system **1300** and arcs across a width of the dial **1302**. Moisture collected by the engaging member **1368** may be wiped or swept off the dial **1302** for collection into a channel **1374** between the dial **1302** and the separating wall **1304**. The channel **1374** may be formed as part of the sink **1307** or otherwise to provide for waste removal of the materials **1362** to a drain, as discussed above. In some embodiments, multiple wipers **1360** may be used and provided at other locations about the dial **1302** so long as the wipers **1360** do not interfere with the completed beverages rotating on the dial **1302**. For example, during beverage production, it may be convenient to prevent rotation or indexing of filled beverages beyond the left side **1372** of the beverage production system **1300**, since beverages might become unreachable by the users. Accordingly, the wipers **1360** may be preferably located adjacent the dial **1302** at locations that avoid engaging filled beverages. While the wiper **1360** is described as having an arced design, other embodiments are envisioned where the wiper **1360** might be substantially straight, wedge-shaped, or otherwise configured. In other embodiments, the wiper **1360** might be located near the dial **1302** and be periodically actuated, such as via a motor, to wipe across the upper surface **1364** of the dial **1302** and then be stored away from the upper surface **1364** to allow completed beverages on the dial **1302** to pass by without engaging the wiper **1360**. Still other configurations will readily suggest themselves to one skilled in the art.

(228) FIG. **64** illustrates yet another embodiment of the beverage production system **1300**. While the beverage production system **1300** illustrated in FIG. **51** is provided with an ice maker or machine **1390** positioned atop the beverage production system **1300**, in some embodiments, the ice machine may be omitted and the ice may be manually filled. In either case, the embodiment shown in FIG. **64** illustrates an ice bin **1400** which may be automatically or manually filled with ice. The ice bin **1400** sits atop the beverage production system **1300** and may include augers and other systems (not shown) to promote the movement and processing of ice through the beverage production system **1300**, as discussed above. Referring also to FIG. **65**, the ice bin **1400** is shown removed from the beverage production system **1300**. The ice bin **1400** includes a bin tub **1402** for receiving and dispensing ice. The ice bin **1400** may be variously sized to be received in an upper portion **1404** of the beverage production system **1300**. The ice bin **1400**, in this embodiment, includes a fill chute **1406** which extends from a front side **1408** of the ice bin **1400** adjacent the bin tub **1402**. The fill chute **1406** may be sloped from a front **1410** to a back **1412** towards the bin tub **1402** to promote ice placed in the fill chute **1406** to flow into the bin tub **1402**. The fill chute **1406** may be generally rounded along a front side **1414** to conveniently receive ice manually poured into the fill chute **1406**. However, the ice bin **1400** and fill chute **1406** may be otherwise configured in other embodiments. The ice bin **1400** may be constructed of various materials including metallic, such as stainless steel, polymeric materials, thermoform plastic, or the like.

(229) As shown in FIG. **66**, a chute cover **1416** may be pivotally attached to the ice bin **1400** adjacent the fill chute **1406**. In this illustration, the chute cover **1416** is shown in an up or open position **1418** which provides access to load ice into the ice bin **1400** via the fill chute **1406**. FIG. **64** illustrates the chute cover **1416** provided in a down or closed position **1420** which prevents dust or debris from entering the ice bin **1400** and also prevents any hazards from inadvertent contact with moving parts during operation. The chute cover **1416** may be constructed of various materials including metallic, such as stainless steel, or polymeric materials.

(230) Referring to FIG. **67**, a front view of the beverage production system **1300** is provided that

illustrates an embodiment of a cup dispenser **1430**. In this embodiment, the beverage production system **1300** may include a door **1432** mounted on a front **1434** of the beverage production system **1300**. The door **1432** may be provided with door hinges **1436** to enable the door **1432** to open. Referring also to FIG. **68**, the door **1432** is illustrated in an open position which provides access to an upper interior **1438** of the beverage production system **1300** where controls and other systems, which will be discussed below, may be retained. As can be seen, when the door **1432** is opened, both the door **1432** and the cup dispenser **1430** attached thereto pivots or rotates on the door hinges **1436** to expose and allow access to the upper interior **1438** of the beverage production system **1300**.

(231) Referring also to FIG. **69**, the cup dispenser **1430** is shown in an open position while the door **1432** of the beverage production system **1300** is closed. As can be seen, the cup dispenser **1430** is substantially semi-circular and includes an upper and lower support structure **1440**, **1442** and a dispenser cover **1444** extending therebetween. A dispenser back wall **1446** extends from sides **1448a** and **1448b** of the dispenser cover **1444** between the upper and lower structures **1440**, **1442** along a back side **1450** of the cup dispenser **1430**. The dispenser cover **1444** and dispenser back wall **1446** define a cup storage area **1452** therein for retaining cups **50** to be dispensed. As can be seen in FIG. **66**, the upper support structure **1440** may be configured as an arced or curbed member shaped to receive the semi-circular shape of the front side **1414** of the fill chute **1406**. The cup dispenser **1430** may include dispenser hinges **1453** enabling the cup dispenser **1430** to be separately openable for refilling cups **50** while the door **1432** of the beverage production system **1300** remains closed, as shown in FIG. **69**. This configuration allows the cup dispenser **1430** to be opened without opening the door **1432** and allowing moisture or other access to the upper interior **1438** of the beverage production system **1300** when refilling cups **50**. This configuration also allows for refilling the ice via the chute cover **1416** and fill chute **1406** without opening the cup dispenser **1430** or door **1432** which prevents ice from spilling into the cup storage area **1452** or elsewhere. This configuration also allows the cups **50** to be restocked without stopping the beverage production system **1300**, while door **1432** remains closed to protect against hazards in upper area **1438**.

(232) In this embodiment, the dispenser cover **1444** may be clear plastic which allows for visually identifying the number of cups **50** loaded in the cup dispenser **1430** so cups **50** can be reloaded in a timely manner. In some embodiments, the upper support structure **1440** may further cover the cup storage area **1452** to prevent debris or materials from entering and contaminating the cups **50** stored therein. In some embodiments, the upper support structure **1440** may merely provide support or define an upper portion of the dispenser cover **1444**. In that case, the cup dispenser **1430** may merely be opened via the dispenser hinges **1453** to allow for reloading of cups **50** while allowing continued operation of the beverage production system **1300**. Further, the cups **50** stored in cup storage area **1452** may be dispensed using elements of dispenser **134** as described above, for example in FIGS. **5-7**, or by other techniques. In this embodiment, three (3) stacks of cups **50** are illustrated, where each stack includes cups **50** of the same or different size. However, in other embodiments, fewer or more stacks may be provided.

(233) In the embodiment shown in FIG. **69**, the chute cover **1416** may be coupled adjacent the upper support structure **1440** of the cup dispenser **1430**. In this manner, the chute cover **1416** covers the fill chute **1406** when the cup dispenser **1430** is in a closed position. The beverage production system **1300** may further include a safety switch **1454** located adjacent the upper support structure **1440** of the cup dispenser **1430**. The safety switch **1454** is couple to sense both the position of the door **1432** as well as the chute cover **1416**. The safety switch **1454** may be further coupled to communicate with various control systems of the beverage production system **1300**, as discussed above, so as to energize and deenergize all or various components of the beverage production system **1300** upon opening and closing the door **1432** and/or fill chute **1406**. Such operation of the safety switch **1454** may prevents hazards or accidental interference with

various systems within and without the upper interior **1438** while the door **1432** is open and also prevents operations, for example, of augers or other systems associated with dispensing ice when the fill chute **1406** is open. In the present embodiment, the safety switch **1454** is a single switch located and so coupled for such operation, while in other embodiments multiple switches located elsewhere may be provided. In other embodiments, the safety switch **1454** may further be coupled to sense when the cup dispenser **1430** is opened and control operation of the beverage production system **1300** as desired.

(234) As shown in FIG. **68**, when the door **1432** is opened, various components may be accessed in the upper interior **1438** including another embodiment of the lidding and printing assembly **502**. Referring also to FIGS. **70-72**, in this embodiment, the lidding and printing assembly **502** is mounted in the upper interior **1438** of the beverage production system **1300** via slide rails **1460**. Slide rails **1460** may enable the lidding and printing assembly **502** to be extended from a stored or ready position **1462**, as shown in FIG. **70**, to an extended or maintenance position **1464** illustrated in FIG. **71**. The slide rails **1460** may be any type of slide or glide system attachable in the upper interior **1438** and the lidding and printing assembly **502** to enable movement or extension between such positions or locations and may include ball bearings or other types of slide rails or extension designs. The slide rails **1460** allow for ready access to the lidding and printing assembly **502** when pulled out or extended to the maintenance position **1464** for ready access for reloading or changing cup lidding film, such as sealing film **544**, printing ink for the printer, or maintenance or repair and cleaning of components of the lidding and printing assembly **502**. The rail slides **1460** may extend any distance between the ready position **1462** and maintenance position **1464** that is desired to provide sufficient clearance from other components within the upper interior **1438** to allow for ready access by users for these purposes. The slide rails **1460**, the lidding and printing assembly **502**, and door **1432** may further be configured such that when door **1432** is closed, the door **1432** engages or presses the lidding and printing assembly **502** into the proper location, such as the ready position **1462**, or so called “poke-yoke’d” configuration. It will be appreciated that the lidding and printing assembly **502** being correctly positioned ensure a proper alignment to result in obtaining a sound or good film seal on the cup **50**. Other techniques for ensuring proper placement of the lidding and printing assembly **502** may be used, such as locking pin, sensor, and so on to locate or verify that the lidding and printing assembly **502** is in the correct position before operation of the beverage production system **1300** begins.

(235) As discussed above and referring to FIG. **73**, the inner turntable **507** may include the upper frame **1318**, which is a substantially round plate configured with U-shaped openings **1320** to receive the cup holders **506a** (not shown). In one embodiment, the inner upper frame **1318** may include frame coupler **1470** centrally disposed on the lower side **1471** of the upper frame **1318**. The frame coupler **1470** includes a plurality of coupler teeth **1472** disposed thereabout the frame coupler **1470**.

(236) Referring also to FIG. **74**, various drive systems may be provided, as discussed above, to operate systems of the beverage production system **1300** including driving an inner turntable drive mechanism or drive mechanism **1474**. The drive mechanism **1474** includes a drive coupler **1476** centrally disposed on an upper surface **1477** of the drive mechanism **1474**. The drive coupler **1476** includes a plurality of drive teeth **1478** disposed thereabout the drive coupler **1476**. The frame coupler **1470** and coupler teeth **1472** are configured to mate with the drive coupler **1476** and drive teeth **1478**. Thus, as can be seen, when the lower side **1471** of the upper frame **1318** is brought into place adjacent the upper surface **1477** of the drive mechanism **1474**, the frame coupler **1470** engages the drive coupler **1476**. As such that when the drive mechanism **1474** is actuated and rotates, the mating engagement of the drive coupler **1476** with the frame coupler **1470** operates to similarly rotate the upper frame **1318** during operation of the beverage production system **1300**. Since the upper frame **1318** gravitationally rests on the drive mechanism **1474**, the upper frame **1318** may be readily removed by merely lifting the upper frame **1318** from out of placement above

the drive mechanism **1474** for cleaning, and similarly easily replaced to resume operation. This configuration eliminates any complex mechanical attachment and thus simplifies the operation and maintenance of the beverage production system **1300**. Further this configuration provides safety during operation since this design provides enough force to reliably move the cups **50** around in the correct positions, but not enough to create hazards or pinch points if obstructed. In the event of such hazard or pinch point, the configuration allows enough tolerance to lift and slip to prevent any injury or damage.

(237) While the systems described herein including beverage production systems **100**, **500**, **800**, **900**, **1000**, and **1300** and each of their various sub-systems, assemblies, and components have been described separately, the present disclosure contemplates implementations that combine any arrangement of the various systems and sub-systems described above. As just one example of the substitutions and combinations contemplated, the lidding system described with regard to FIG. **37** may be used in lieu of the lidding systems described with regard to FIGS. **15-20**. Further is contemplated that the beverage identification systems, such as those described in FIGS. **41** and **50**, may be employed in any of the other beverage production systems described herein. Similarly, although not all of the described beverage production systems employ the user interface **116** for selection of the desired beverage(s) on the user interface **116** as well as connection via point-of-sale systems, or sinks provided under the conveyors, the present disclosure contemplates such combination with any of the disclosed beverage production systems. As a further example, although only two turntables, outer and inner turntable **505** and **507**, are shown in beverage production system **500**, one or more additional concentric rows of turntables may be added to further the overall number of beverages that may be prepared and stored for retrieval. Also, it is contemplated that the beverage production system **500**, or others, may be used in conjunctions with additional conveyors where beverages are moved from the production conveyor or turntable to conveyors that transport the beverages elsewhere in the establishment to customers or staff for further convenience and efficiency. These are just some of the examples of combinations that are contemplated by the present disclosure. For purposes of brevity, each of the contemplated combinations will not be discussed, but will readily suggest themselves to one skilled in the art. These and other combinations will readily suggest themselves to one skilled in the art in view of the present disclosure. Further, the various components and supporting structures may be constructed of metal or metal alloys, plastic or polymeric materials or any suitable materials.

(238) The embodiments disclosed herein include beverage production systems and related methods that may further enhance the efficiency of the beverage production process by automating many, most, or substantially all of the steps for producing a beverage. Thus, through use of the embodiments disclosed herein, the number of manual steps that may be necessary for producing beverages may be reduced, thereby increasing the efficiency of the beverage production process and improving food service operations overall.

(239) While exemplary embodiments have been shown and described, modifications thereof can be made by one skilled in the art without departing from the scope or teachings herein. The embodiments described herein are exemplary only and are not limiting. Many variations and modifications of the systems, apparatus, and processes described herein are possible and are within the scope of the disclosure. Accordingly, the scope of protection is not limited to the embodiments described herein, but is only limited by the claims that follow, the scope of which shall include all equivalents of the subject matter of the claims. Unless expressly stated otherwise, the steps in a method claim may be performed in any order.

Claims

1. A beverage production system, comprising: a turntable assembly comprising: a central axis; an inner turntable; and an outer turntable disposed circumferentially about the inner turntable; a cup

dispensing station configured to dispense cups onto one of the inner turntable or the outer turntable; a beverage dispensing station configured to dispense a beverage into a cup of the dispensed cups; a cabinet disposed at least partly above the turntable assembly and defining an interior space; a lidding and printing assembly provided in the interior space of the cabinet, the lidding and printing assembly operable to provide a lid on the cup and provide indicia on the lid; and an extension system coupled to the interior space of the cabinet and the lidding and printing assembly, the extension system configured to retain the lidding and printing assembly in a ready position located within the interior space of the cabinet and to extend the lidding and printing assembly to a maintenance position, wherein the lidding and printing assembly is extended from the interior space in the maintenance position relative to the ready position.

2. The beverage production system of claim 1, further comprising: a door attached to the cabinet and partially enclosing the interior space, wherein the door is attached to the cabinet via door hinges such that the door is openable to access the interior space.

3. The beverage production system of claim 2, wherein a cup dispenser of the cup dispensing station is coupled to the door via cup dispenser hinges, wherein the cup dispenser is separately openable from the door.

4. The beverage production system of claim 3, wherein the cup dispenser includes an upper opening to provide access to a cup retaining area within the cup dispenser, and further comprising a removable cup dispenser cover provided over the upper opening of the cup dispenser.

5. The beverage production system of claim 2, further comprising: an ice bin having a bin tub for retaining ice and a fill chute formed along a side of the ice bin, the fill chute including a bottom sloped toward the bin tub; and a chute cover configured to cover the fill chute when the chute cover is in a closed position and further configured to expose the fill chute for receiving ice therein when the chute cover is in an open position.

6. The beverage production system of claim 5, further comprising one or more safety switches coupled to the door and the chute cover and further coupled to a controller to control operation of the beverage production system based on a sensed position of the door and the chute cover.

7. The beverage production system of claim 6, wherein the one or more safety switches is a single switch coupled to the door and the chute cover.

8. The beverage production system of claim 6, wherein a cup dispenser of the cup dispensing station is coupled to the door via cup dispenser hinges, wherein the cup dispenser is separately openable from the door, and wherein the one or more safety switches is further coupled to the cup dispenser to sense a position of the cup dispenser relative to the door.

9. The beverage production system of claim 1, wherein the extension system is further defined as a plurality of extendable rails.

10. The beverage production system of claim 2, further comprising a drive system configured to promote rotation of the inner turntable, wherein the inner turntable includes a frame coupler coupled to the inner turntable, and wherein the drive system includes at least a drive coupler configured to mate with the frame coupler.

11. The beverage production system of claim 10, wherein actuation of the drive system drives the inner turntable via mating engagement of the drive coupler with the frame coupler.

12. The beverage production system of claim 11, wherein at least a portion of the inner turntable that includes the frame coupler gravitationally rests on the drive system via the mating engagement of the drive coupler with the frame coupler.

13. A method of dispensing a beverage, comprising: providing a beverage production system including; a cabinet defining an interior space housing a lidding and printing assembly, the lidding and printing assembly configured for lidding cups and printing on cup lids; and a turntable assembly disposed below the cabinet and comprising: a central axis; an inner turntable; and an outer turntable disposed circumferentially about the inner turntable; dispensing a cup from a cup dispensing station onto one of the inner turntable or the outer turntable; dispensing a beverage from

a beverage dispensing station into the cup; sensing, by one or more switches, an opening of a door of the cabinet; suspending the beverage production system from dispensing cups and beverages in response to sensing the opening of the door; and extending the lidding and printing assembly from a ready position located within the interior space of the cabinet to a maintenance position extended from the interior space relative to the ready position.

14. The method of claim 13, further comprising: retracting the lidding and printing assembly from the maintenance position to the ready position; and sensing, by the one or more switches, a closing of the door of the cabinet; and actuating the beverage production system to resume dispensing cups and beverages in response to sensing the closing of the door.
