

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416285
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kerton; James Matthew

Venturi device with forced induction systems and methods

Abstract

A Venturi device with a primary flow path and a secondary flow path introduced into the primary flow path, wherein a flow of one or more flowable mediums in the primary flow path and the secondary flow path creates a vortex generating a suction at an inlet of the Venturi device. A hydropower system for converting potential energy of a fluid into electrical energy utilize an upper reservoir and a lower reservoir containing the fluid. A system can be used for converting ambient thermal energy into electrical energy. The system can include a fluid loop to circulate a primary flow of a fluid. A forced induction system for a vehicle to induce ambient airflow can be used to generate electrical energy from the ambient airflow. A cooling system can cool a motor of a vehicle with ambient airflow.

Inventors:	Kerton; James Matthew (Duncan, CA)
Applicant:	Zero Nox, Inc. (Porterville, CA)
Family ID:	1000008818954
Assignee:	Zero Nox, Inc. (Porterville, CA)
Appl. No.:	18/719465
Filed (or PCT Filed):	December 14, 2022
PCT No.:	PCT/US2022/081602
PCT Pub. No.:	WO2023/114879
PCT Pub. Date:	June 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250237188 A1	Jul. 24, 2025

Related U.S. Application Data

continuation-in-part parent-doc WO PCT/US2022/050797 20221122 PENDING child-doc US 18719465
continuation-in-part parent-doc WO PCT/US2022/026399 20220426 PENDING child-doc US 18719465
continuation-in-part parent-doc WO PCT/IB2021/000237 20210427 PENDING child-doc US PCT/US2022/050797
us-provisional-application US 63381905 20221101
us-provisional-application US 63381906 20221101
us-provisional-application US 63268053 20220215
us-provisional-application US 63265483 20211215
us-provisional-application US 63265484 20211215
us-provisional-application US 63265486 20211215
us-provisional-application US 63265489 20211215
us-provisional-application US 63265478 20211215
us-provisional-application US 63282556 20211123

Publication Classification

Int. Cl.: F03B13/00 (20060101); F03G6/02 (20060101); F24V99/00 (20180101)

U.S. Cl.:

CPC F03B13/00 (20130101); F03G6/02 (20130101); F24V99/00 (20180501);

Field of Classification Search

CPC: F03B (13/00); F24V (99/00); F03G (6/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1626487	12/1926	Warren	N/A	N/A
2396290	12/1945	Schwarz	N/A	N/A
4372113	12/1982	Ramer	417/169	F03B 1/00
4443707	12/1983	Scieri et al.	N/A	N/A
6267106	12/2000	Feucht	N/A	N/A
6886545	12/2004	Holm	N/A	N/A
7032578	12/2005	Liu et al.	N/A	N/A
8056340	12/2010	Vaught et al.	N/A	N/A
8664781	12/2013	Alvi	N/A	N/A
8807458	12/2013	Al-Ansary	N/A	N/A
9564664	12/2016	Tanigaki et al.	N/A	N/A
9567856	12/2016	Faller	N/A	N/A
9827872	12/2016	Sloan et al.	N/A	N/A
10625868	12/2019	Dasilva et al.	N/A	N/A

2004/0173192	12/2003	Sorter et al.	N/A	N/A
2009/0075160	12/2008	Tezuka et al.	N/A	N/A
2009/0183858	12/2008	Williams et al.	N/A	N/A
2009/0205745	12/2008	Farese et al.	N/A	N/A
2010/0276517	12/2009	Alansary	N/A	N/A
2013/0298532	12/2012	Hamad et al.	N/A	N/A
2013/0333354	12/2012	Hamad	N/A	N/A
2014/0056687	12/2013	Younes et al.	N/A	N/A
2014/0292283	12/2013	Timmons et al.	N/A	N/A
2016/0153404	12/2015	Paolo	N/A	N/A
2016/0319778	12/2015	Shuto et al.	N/A	N/A
2016/0369674	12/2015	Younes et al.	N/A	N/A
2017/0074213	12/2016	Hamad et al.	N/A	N/A
2017/0373511	12/2016	Jo	N/A	N/A
2018/0016017	12/2017	Dasilva et al.	N/A	N/A
2019/0085758	12/2018	Kurtz	N/A	N/A
2019/0097434	12/2018	Kim	N/A	N/A
2019/0120106	12/2018	Hamad	N/A	N/A
2019/0198945	12/2018	Machida et al.	N/A	N/A
2019/0288527	12/2018	Jaensch et al.	N/A	N/A
2020/0171975	12/2019	Ueda et al.	N/A	N/A
2020/0256266	12/2019	Mastbergen et al.	N/A	N/A
2020/0325861	12/2019	Voice et al.	N/A	N/A
2021/0135461	12/2020	Wang et al.	N/A	N/A
2021/0206290	12/2020	Li et al.	N/A	N/A
2022/0126724	12/2021	O'Connor et al.	N/A	N/A
2022/0140620	12/2021	Kang et al.	N/A	N/A
2024/0191650	12/2023	Kerton	N/A	N/A
2024/0350989	12/2023	Kerton	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106532178	12/2016	CN	N/A
114243848	12/2021	CN	N/A
2093475	12/2008	EP	N/A
3093475	12/2015	EP	N/A
3037300	12/2018	EP	N/A
3895933	12/2020	EP	N/A
0552747	12/1942	GB	N/A
2516612	12/2014	GB	N/A
5760097	12/2014	JP	N/A
5841294	12/2015	JP	N/A
6267375	12/2017	JP	N/A
6325516	12/2017	JP	N/A
6763889	12/2019	JP	N/A
2021-522440	12/2020	JP	N/A
7033200	12/2021	JP	N/A
2008/136641	12/2007	WO	N/A
2012/071632	12/2011	WO	N/A
2012/100149	12/2011	WO	N/A

2013/142469	12/2012	WO	N/A
2014/031996	12/2013	WO	N/A
2016/205057	12/2015	WO	N/A
2019/079531	12/2018	WO	N/A
2019/209542	12/2018	WO	N/A
2022/026399	12/2021	WO	N/A
2022/232182	12/2021	WO	N/A
2023/096938	12/2022	WO	N/A
2023/114873	12/2022	WO	N/A
2023/114879	12/2022	WO	N/A
2023/215526	12/2022	WO	N/A

OTHER PUBLICATIONS

European Extended Search Report, re EP Application No. 22796580.3, dated Dec. 19, 2024. cited by applicant

International Preliminary Report on Patentability and Written Opinion, dated Oct. 24, 2023; in International Application No. PCT/US2022/026399, filed Apr. 26, 2022; in 12 pages. cited by applicant

International Search Report and Written Opinion, re PCT Application No. PCT/US2022/081594, mailed Apr. 5, 2023. cited by applicant

International Search Report and Written Opinion, re PCT Application No. PCT/US2022/50797, dated Mar. 28, 2023. cited by applicant

International Search Report and Written Opinion, re PCT Application No. PCT/US2022/81602, dated Apr. 3, 2023. cited by applicant

International Search Report and Written Opinion, re PCT Application No. PCT/US2023/021077, mailed Jul. 31, 2023. cited by applicant

International Search Report/Written Opinion dated Aug. 11, 2022; in International Application No. PCT/US2022/026399, filed Apr. 26, 2022; in 15 pages. cited by applicant

Primary Examiner: Nguyen; Viet P

Attorney, Agent or Firm: Knobbe, Martens Olson & Bear, LLP

Background/Summary

INCORPORATION BY REFERENCE (1) This application claims priority to U.S. Provisional Application No. 63/265,478, filed Dec. 15, 2021, entitled “VENTURI THERMAL ENERGY CONVERSION SYSTEM,” U.S. Provisional Application No. 63/265,483, filed Dec. 15, 2021, entitled “NPR HYDRO TURBINE SYSTEM,” U.S. Provisional Application No. 63/265,489, filed Dec. 15, 2021, entitled “PHASE SHIFTING THERMAL ENERGY CONVERSION SYSTEM,” U.S. Provisional Application No. 63/265,484, filed Dec. 15, 2021, entitled “NPR MOTOR COOLING SYSTEM,” U.S. Provisional Application No. 63/265,486, filed Dec. 15, 2021, entitled “NPR FORCED INDUCTION CHARGING AND HEATING SYSTEM,” U.S. Provisional Application No. 63/268,053, filed Feb. 15, 2022, entitled “STEALTH ORDNANCE THRUSTER,” U.S. Provisional Application No. 63/381,905, filed Nov. 1, 2022, entitled “VENTURI DEVICE WITH FORCED INDUCTION,” U.S. Provisional Application No. 63/381,906, filed Nov. 1, 2022, entitled “VENTURI DEVICE WITH FORCED INDUCTION,” International Patent Application No. PCT/US2022/026399, filed Apr. 26, 2022, entitled “VENTURI DEVICE WITH FORCED INDUCTION,” which claims priority to International Patent Application No. PCT/IB2021/000237,

filed Apr. 27, 2021, entitled “HYBRID HYDRO-AERODYNAMIC FORCED INDUCTION SYSTEM,” and International Patent Application No. PCT/US2022/050797, filed Nov. 22, 2022, entitled “VENTURI DEVICE WITH FORCED INDUCTION SYSTEMS AND METHODS,” which claims priority to U.S. Provisional Application No. 63/282,556, filed Nov. 23, 2021, entitled “PARTICULATE BURNER,” each of which is hereby incorporated by in its entirety herein and made part of this disclosure. Related German Application Nos. DE 102019003025.7, filed Apr. 26, 2019, and DE 102019006055.5, filed Sep. 4, 2019, each of which is hereby incorporated by reference in its entirety herein and made part of this disclosure. Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

FIELD

(1) This disclosure relates to Venturi devices, related devices, and applications thereof.

BACKGROUND

(2) The demand for cleaner energy use and fluid mechanics has increased dramatically over the past century. Accordingly, a way to better use or generate cleaner energy is needed.

SUMMARY

(3) Neither the preceding summary nor the following detailed description purports to limit or define the scope of protection. The scope of protection is defined by the claims.

(4) As the demand for energy increases, the demand to harvest energy from untapped or under-exploited sources has increased as well, especially those sources readily available. Accordingly, various devices and systems are disclosed herein that address one or more of these problems. For example, devices and systems are disclosed herein that incorporate a Venturi device with forced induction to convert potential energy of a fluid into electrical energy.

(5) A hydropower system for converting potential energy of a fluid into electrical energy utilize an upper reservoir containing a fluid and a lower reservoir containing the fluid, where the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity. A fluid loop can circulate a primary flow of the fluid between the upper reservoir and the lower reservoir with a turbine disposed on the fluid loop to be driven by the primary flow from the upper reservoir to the lower reservoir. The turbine can then drive a generator to generate electrical energy. A pump on the fluid loop can pump the primary flow from the lower reservoir to the upper reservoir after the fluid has flows from the top to the bottom reservoir. A first Venturi device downstream of the upper reservoir and upstream of the turbine and second Venturi device Venturi device downstream of the lower reservoir and upstream of the pump can suction in the primary flow of fluid.

(6) A system can be used for converting ambient thermal energy into electrical energy. The system can include a fluid loop to circulate a primary flow of a fluid. The primary flow can drive a turbine disposed on the fluid loop which then drives a generator that generates electrical energy. A first pump on the fluid loop can propel the primary flow through the fluid loop. A cooling coil downstream of the turbine and upstream of the first pump on the fluid loop condenses the primary flow exiting the turbine. A first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop and a second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop can pull the primary flow. A reservoir tank on the fluid looo can contain the fluid flowing through the fluid loop with a first conduit connected to the reservoir tank and the secondary input of the first Venturi device to direct the secondary flow from the primary flow to the secondary input of the first Venturi device. A second pump on the first conduit can drive the secondary flow from the primary flow to the secondary input of the first Venturi device. A heater downstream of the second pump on the first conduit can heat the secondary flow of the first Venturi device such that the secondary flow phase shifts from a liquid state to a gas state.

(7) A Venturi device having an inlet can receive a primary flow of a fluid and an outlet to eject said

flow. A body between the inlet and the outlet can include a converging portion and a diverging portion where a Venturi effect pulls the primary flow in through the inlet and which exits through a reducer. A first nozzle partially in the diverging portion forms a first annular space to create a first low pressure fluid in the first annular space relative to a high-pressure fluid flow of the primary flow flowing through the first nozzle to pull the primary flow through the inlet and into the body. A reduction in the high-pressure fluid flow of the primary flow through the first nozzle causes the first low pressure fluid to partially exit the first annular space for the first low pressure fluid to flow toward the outlet. A second nozzle partially in the reducer forms a second annular space between the second nozzle and the body wall and creates a second low pressure fluid in the second annular space relative to the high-pressure fluid flow of the primary flow flowing through the second nozzle to move the primary flow through the outlet. The reduction in the high-pressure fluid flow of the primary flow through the second nozzle causes the second low pressure fluid to partially exit the second annular space for the second low pressure fluid to flow toward the outlet. The second annular space can be larger than the first annular space. An end of the second nozzle can be spaced axially inward from an end of the reducer such that the end of the reducer partially forms the outlet. A secondary input between the converging portion and the outlet can direct a secondary flow of the fluid into the primary flow to create a vortex that pulls the primary flow through the inlet and into the body.

(8) A forced induction system for a vehicle to induce ambient airflow can be used to generate electrical energy from the ambient airflow. The system can use an intake funnel having an inlet, an outlet, and a body between the inlet and the outlet to direct an ambient airflow. The inlet of the intake funnel has a cross-sectional flow area larger than a cross-section flow area of the outlet of the intake funnel and the body has a shape changing portion that expands or contracts to change a cross-sectional flow area of the body of the intake funnel for the ambient airflow. A Venturi device connected to the intake funnel has an inlet connected to the outlet of the intake funnel to receive a primary flow of ambient air exiting the outlet of the intake funnel. An outlet of the Venturi device can eject the primary flow. A body of the Venturi device between the inlet and outlet of the Venturi device includes a converging portion and a diverging portion which produces a Venturi effect to pull the primary flow through the inlet of the Venturi device. A secondary input between the converging portion and the outlet that can direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device. A turbine can receive the primary flow from the Venturi device. A generator can then be connected to the turbine which then generates electrical energy. A bypass conduit can recirculate the secondary flow from the primary flow flowing through the turbine to the secondary input of the Venturi device. A passenger cabin duct can be connected to the outlet of the turbine to receive the primary flow from the outlet and direct the primary flow toward a passenger cabin of a vehicle. A valve can control the primary flow coming from the turbine. A bypass duct connected to the valve can direct the primary flow outside of the vehicle.

(9) A cooling system can cool a motor of a vehicle with ambient airflow. A Venturi device open to ambient air has an inlet connected to the outlet of the intake funnel to receive a primary flow of ambient air exiting the outlet of the intake funnel. An outlet of the Venturi device can eject the primary flow. A body of the Venturi device between the inlet and outlet of the Venturi device includes a converging portion and a diverging portion which produces a Venturi effect to pull the primary flow through the inlet of the Venturi device. A secondary input between the converging portion and the outlet that can direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device. An air compressor can compress ambient air and direct the compressed air into the secondary input of the Venturi device to provide the secondary flow. A cooling duct can be connected to the outlet of the Venturi device and receive the primary flow ejected from the outlet of the Venturi device. The cooling duct can direct the

primary flow to a motor of a vehicle to cool the motor and utilize fins to direct the primary flow to the warmest parts of the motor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The abovementioned and other features of the embodiments disclosed herein are described below with reference to the drawings of the embodiments. The illustrated embodiments are intended to illustrate, but not to limit, the scope of protection. Various features of the different disclosed embodiments can be combined to form further embodiments, which are part of this disclosure. In the drawings, similar elements may have reference numerals with the same last two digits.
- (2) FIGS. 1A-1C illustrate a section view of an example Venturi device.
- (3) FIG. 2 illustrates a simplified schematic of the Venturi device illustrated in FIG. 1A.
- (4) FIG. 3 illustrates a section view of a configuration of an example Venturi device.
- (5) FIGS. 4A-4D illustrate a section view of a configuration of an example Venturi device.
- (6) FIGS. 5-8 illustrate a hydro-turbine system to convert kinetic energy into electrical energy.
- (7) FIGS. 9-10 illustrate a phase shifting thermal energy conversion system to convert thermal energy into electrical energy.
- (8) FIG. 11 illustrates a forced induction system for a vehicle to induce ambient airflow to generate electrical energy from the ambient airflow.
- (9) FIGS. 12-14 illustrate different configurations of an intake funnel of the forced induction system of FIG. 11.
- (10) FIG. 15 illustrates a configuration of a forced induction system for a vehicle to induce ambient airflow to generate electrical energy from the ambient airflow.
- (11) FIG. 16 illustrates material configurations which can be incorporated in the Venturi device of FIGS. 11-15.
- (12) FIG. 17 illustrates an inlet of non-Euclidean geometry which can be incorporated in the Venturi device of FIGS. 11-16.
- (13) FIG. 18 illustrates a cooling system for cooling a motor of a vehicle with ambient airflow.
- (14) FIG. 19 illustrates a configuration of a cooling system for cooling a motor of a vehicle with ambient airflow.
- (15) FIG. 20 illustrates a configuration of a cooling system for cooling a motor of a vehicle with ambient airflow.
- (16) FIG. 21 illustrates a configuration of a cooling system for cooling a motor of a vehicle with ambient airflow.
- (17) FIGS. 22-24 illustrate different configurations of an intake funnel of the cooling system for cooling a motor of a vehicle with ambient airflow of FIG. 21.

DETAILED DESCRIPTION

- (18) Although certain embodiments and examples are described below, this disclosure extends beyond the specifically disclosed embodiments and/or uses and obvious modifications and equivalents thereof. Thus, it is intended that the scope of this disclosure should not be limited by any particular embodiments described below. Furthermore, this disclosure describes many embodiments in reference to power generation or phase shifting but any embodiment and modifications or equivalents thereof should not be limited to the foregoing.
- (19) According to the 1st Theorem of Thermodynamics, energy can neither be generated nor consumed. It can only be transformed in its form, that is, from one form of energy into another form. For this reason, the total energy in a closed system remains constant.
- (20) There are differences in valence between the forms of energy. Thus, as a possible form of

energy, heat can never flow without action, that is to say, from a body of lesser temperature to a body of higher temperature, although the total amount of energy stored in the bodies in the form of heat may be equal. In the opposite direction, this is quite possible and inevitable, that is, the transition of heat from the warmer to the colder body takes place spontaneously and automatically (2nd Theorem of Thermodynamics). The heat in the warmer body is thus of higher value than the heat in the colder body. This heat can at least be partially converted into mechanical energy in heat engines, in which this automatic flow of heat from the warmer body to the colder body is exploited. The proportion of the mechanical energy which can be obtained can be shown by way of a ratio of the two temperatures according to the formula below.

$$(21) \text{Anteil}_{Mech} = \frac{T_{warm} - T_{cold}}{T_{warm}}$$

(22) This proportion can be referred to as the efficiency of the Carnot process.

(23) As disclosed herein, thermal energy can be converted into mechanical energy by suctioning mechanisms. Described herein are systems and devices for converting low-grade thermal energy (e.g., ambient temperature) into high-quality energy (electricity). For example, Venturi devices are described herein that form one or more flow-induced vortices within a fluid (e.g., air, water, gas, etc.) flowing through the Venturi devices. The one or more vortices can occur at a location within the Venturi device where a secondary fluid flow merges (e.g., mixes, fuses) with a primary fluid flow through the Venturi device. The one or more vortices can form a suction, sucking the primary flow into the Venturi device through an inlet. In some configurations, the suction and the Venturi effect, created by the flow of fluid through the Venturi device, can lower a temperature of the primary flow through at least a portion of the Venturi device, causing thermal energy in an ambient environment outside the Venturi device to be transferred to the primary flow (e.g., charging the primary flow).

(24) Venturi Device with Forced Induction

(25) FIGS. 1A-1C illustrates a section view of an example Venturi device **100**, which can also be referred to as a vortex fusion charger or VFC. The Venturi device **100** can, in some configurations, include a rotationally symmetrical inner periphery, which can include rotational symmetry about the central axis **112**. The Venturi device **100** can be a tubular structure. The inner periphery of the Venturi device **100** can define primary flow path, which can be an inner region, cavity, lumen, etc., that receives a primary flow of a fluid (e.g., water, gas, air, exhaust gases, etc.). In some configurations, the inner periphery of the Venturi device **100** can be a circular shape. In some variations, the inner periphery may be other shapes, such as an oval, polygon, irregular, and/or others. The inner periphery may define a flow path for the primary flow of the fluid in the direction of the arrows in FIGS. 1A-1C. The inner periphery of the Venturi device **100** can define cross-sectional flow areas for the primary flow of fluid, which can be circular. The inner periphery can change such that the cross-sectional flow areas change in size and/or shape along a length of the Venturi device **100**. For example, the inner periphery of the Venturi device **100** can include an inner diameter that assumes different sizes along its length or central axis **112**.

(26) The primary flow of fluid can enter the Venturi device **100** through the inlet **102**. The inlet **102** can be connected to a conduit (e.g., tube) that can circulate the primary flow. In some variants, the inlet **102** can be open to the ambient air. An inner periphery of the inlet **102** can be circular. In some variants, the inner periphery of the inlet **102** can be oval, polygonal, irregular, and/or others. The inlet **102** can, as shown in FIG. 1B, include a velocity stack, trumpet shape, and/or air horn shape. The inlet **102** can include an inner periphery that converges. The inlet **102** can include cross-sectional flow area that converges. The inlet **102** can include an inner periphery that decreases in size in the direction of flow of the primary flow. The inlet **102** can include an inner periphery that continuously decreases in size in the direction of flow of the primary flow. The inlet **102** can include cross-sectional flow areas that decrease in size in the direction of flow of the primary flow. The inlet **102** can include cross-sectional flow areas that continuously decrease in size in the direction of flow of the primary flow. The inlet **102** can include a curved peripheral wall, as shown

in FIG. 1B. The inner periphery of the inlet **102** can converge. The inlet **102** can increase the velocity of the primary flow through the inlet **102**, decreasing a pressure of the primary flow. (27) The primary flow of fluid can exit the Venturi device **100** through the outlet **104**. The outlet **104** can be disposed on an opposing side of the Venturi device **100** as the inlet **102**. The outlet **104** can be connected to a conduit (e.g., tube) that can circulate the primary flow. In some variants, the outlet **104** can be disconnected from another component, as described herein. An inner periphery of the outlet **104** can be circular. In some variants, the inner periphery of the outlet **104** can be oval, polygonal, irregular, and/or others. The inner periphery of the outlet **104** can diverge. A cross-sectional flow area of the outlet **104** can diverge in the direction of flow of the primary flow. The inner periphery of the outlet **104** can increase in size in the direction of flow of the primary flow. The inner periphery of the outlet **104** can continuously increase in size in the direction of flow of the primary flow. The outlet **104** can include cross-sectional flow areas that increase in size in the direction of flow of the primary flow. The outlet **104** can include cross-sectional flow areas that continuously increase in size in the direction of flow of the primary flow. The inner periphery of the outlet **104** can diverge. The outlet **104** can decrease the velocity of the primary flow through the outlet **104**, increasing a pressure of the primary flow.

(28) The Venturi device **100** can include a body (e.g., tubular body) between the inlet **102** and the outlet **104**. The primary flow path can flow through the body between the inlet **102** and the outlet **104**. The body can include a converging portion **106**. The converging portion **106** can increase the velocity of the primary fluid flowing through the converging portion **106**. The converging portion **106** can decrease the pressure of the primary fluid flowing through the converging portion **106**. An inner periphery of the converging portion **106** can be circular. In some variants, the inner periphery of the converging portion **106** can be oval, polygonal, irregular, and/or others. The converging portion **106** can include an inner periphery that converges. The converging portion **106** can include a cross-sectional flow area that converges. The converging portion **106** can include an inner periphery that decreases in size in the direction of flow of the primary flow. The converging portion **106** can include an inner periphery that continuously decreases in size in the direction of flow of the primary flow. The converging portion **106** can include cross-sectional flow areas that decrease in size in the direction of flow of the primary flow. The converging portion **106** can include cross-sectional flow areas that continuously decrease in size in the direction of flow of the primary flow. The converging portion **106** can include a flow area having the shape of a cone. The cross-sectional flow area of the converging portion **106** can decrease at a consistent rate. A temperature of the primary flow flowing through the converging portion **106** can decrease as a result of the increased velocity and decreased pressure.

(29) The body of the Venturi device **100** can include a throat **108**, which can also be referred to as a constriction. The throat **108** can be disposed between the converging portion **106** and a diverging portion **110**. The throat **108** can include an inner periphery that is smaller than that of the converging portion **106** and the diverging portion **110**. For example, the throat **108** can include a diameter that is smaller than a diameter of the converging portion **106** and the diverging portion **110**. The throat **108** can include a cross-sectional flow area that is smaller than that of the converging portion **106** and the diverging portion **110**. In some configurations, the throat **108** can be the junction of the converging portion **106** and the diverging portion **110**. In some configurations, the throat **108** includes a length. In some configurations, the inner periphery of the throat **108** is an inflection point between the converging portion **106** and the diverging portion **110**. In some variants, the converging portion **106** converges to the throat **108** and immediately diverges to the diverging portion **110**.

(30) The body of the Venturi device **100** can include a diverging portion **110**. The diverging portion **110** can be downstream of the inlet **102** and converging portion **106**. The diverging portion **110** can be downstream of the throat **108**. The diverging portion **110** can be disposed between the converging portion **106** and the outlet **104**, second converging portion **114**, and/or secondary input

120. The diverging portion **110** can decrease the velocity of the primary fluid flowing through the diverging portion **110**. The diverging portion **110** can increase the pressure of the primary fluid flowing through the diverging portion **110**. An inner periphery of the diverging portion **110** can be circular. In some variants, the inner periphery of the diverging portion **110** can be oval, polygonal, irregular, and/or others. The diverging portion **110** can include an inner periphery that diverges. The diverging portion **110** can include a cross-sectional flow area that diverges. The diverging portion **110** can include an inner periphery that increases in size in the direction of flow of the primary flow. The diverging portion **110** can include an inner periphery that continuously increases in size in the direction of flow of the primary flow. The diverging portion **110** can include cross-sectional flow areas that increase in size in the direction of flow of the primary flow. The diverging portion **110** can include cross-sectional flow areas that continuously increases in size in the direction of flow of the primary flow. The diverging portion **110** can include a flow area having the shape of a cone. The cross-sectional flow area of the diverging portion **110** can decrease at a consistent rate. The diverging portion **110** can be longer than the converging portion **106**. The size of the cross-sectional flow area of the converging portion **106** can change more rapidly than the size of the cross-sectional flow area of the diverging portion **110** per a unit of length. The angle of the periphery of the converging portion **106** relative to the central axis **112** and/or direction of flow of the primary flow can be larger than the angle of the periphery of the diverging portion **110** relative to the central axis **112** and/or direction of flow of the primary flow.

(31) The flow of the primary flow through the converging portion **106**, throat **108**, and/or diverging portion **110** can produce a Venturi effect, which can create a suction at the inlet **102**. The flow of the primary flow through the converging portion **106** and throat **108** can produce a Venturi effect, which can create a suction at the inlet **102**. The flow of the primary flow through the converging portion **106** can produce a Venturi effect, which can create a suction at the inlet **102**. The increase in the velocity and decrease in pressure of the primary flow through the converging portion **106** and/or throat **108** can decrease a temperature of the primary flow such that thermal energy (e.g., heat) from the ambient environment outside the body of the Venturi device **100** is transferred to the primary flow. In some variants, the body of the Venturi device **100** or at least the converging portion **106** and/or throat **108** can include a conductive material (such as a metal) to facilitate efficient transfer of thermal energy through the body.

(32) The body of the Venturi device **100** can include a second converging portion **114**. The second converging portion **114** can be downstream of the inlet **102**, converging portion **106**, throat **108**, and diverging portion **110**. The second converging portion **114** can be disposed between the diverging portion **110** and the secondary input **120** and the outlet **104**. The second converging portion **114** can increase the velocity of the primary flow flowing through the second converging portion **114**. The second converging portion **114** can decrease the pressure of the primary fluid flowing through the second converging portion **114**. An inner periphery of the second converging portion **114** can be circular. In some variants, the inner periphery of the second converging portion **114** can be oval, polygonal, irregular, and/or others. The second converging portion **114** can include an inner periphery that converges. The second converging portion **114** can include a cross-sectional flow area that converges. The second converging portion **114** can include an inner periphery that decreases in size in the direction of flow of the primary flow. The second converging portion **114** can include an inner periphery that continuously decreases in size in the direction of flow of the primary flow. The second converging portion **114** can include cross-sectional flow areas that decrease in size in the direction of flow of the primary flow. The second converging portion **114** can include cross-sectional flow areas that continuously decreases in size in the direction of flow of the primary flow. The second converging portion **114** can include a flow area having the shape of a cone. The cross-sectional flow area of the second converging portion **114**, converging portion **106**, and/or diverging portion **110** can change at a consistent rate per unit of length. The angle of the periphery of the converging portion **114** relative to the central axis **112** and/or direction of flow of

the primary flow can be larger than the angle of the peripheries of the diverging portion **110**, converging portion **106**, and/or outlet **104** relative to the central axis **112** and/or direction of flow of the primary flow.

(33) A conduit **116**, which can also be referred to as a tube, conduit, chamber, lumen, or the like, can circulate a secondary flow of a fluid (e.g., water, gas, air, exhaust gases, etc.) to the Venturi device **100**. As described herein, the conduit **116** can recirculate a portion of the primary flow as a secondary flow into the primary flow. The conduit **116** can be connected to an annular chamber **118** of the body of the Venturi device **100** to direct the secondary flow to the annular chamber **118**. In some configurations, multiple conduits **116** can be connected to the annular chamber **118** at multiple locations to direct the secondary flow into the annular chamber **118**.

(34) The body of the Venturi device **100** can include an annular chamber **118**. The annular chamber **118** can be ring shaped. In some configurations, the annular chamber **118** can be torus shaped. The annular chamber **118** can encircle the primary flow of fluid. The annular chamber **118** can encircle the central axis **112** of the Venturi device **100**. The annular chamber **118** can circumferentially surround the primary flow of fluid. The secondary flow of fluid can spread throughout the annular chamber **118**. A surface of the annular chamber **118** can include a Coandă surface or profile that can facilitate the secondary flow of fluid spreading throughout the annular chamber **118**. A surface of the annular chamber **118** can be convex to facilitate the secondary flow of fluid spreading throughout the annular chamber **118**. The secondary flow can adhere (e.g., molecular adhesion) to the surface(s) of the annular chamber **118** to spread throughout the annular chamber **118**.

(35) The body of the Venturi device **100** can include a secondary input **120**. The secondary input **120** can be disposed downstream of the inlet **102**, converging portion **106**, throat **108**, diverging portion **110**, and/or second converging portion **114**. The secondary input **120** can be disposed between the converging portion **106**, throat **108**, diverging portion **110**, and/or second converging portion **114** and the outlet **104**. The secondary input **120** can include one or more flow paths from the annular chamber **118** into the primary flow and/or inner region and/or primary flow path of the Venturi device **100** through which the primary flow travels. The secondary input **120** can be an annular passageway, one or more apertures, plurality of apertures, one or more slots, annular gap, and/or ring gap. The secondary input **120** can encircle the primary flow through the body of the Venturi device **100**. The secondary input **120** can circumferentially encircle the primary flow through the body. The secondary input **120** can include one or more openings circumferentially distributed about a flow path of the primary flow. The secondary input **120** can define an annular shaped opening in an inner periphery of the body of the Venturi device **100**. The secondary input **120** can direct the secondary flow into the primary flow at an angle relative to the direction of flow of the primary flow and/or relative to the central axis **112** of the body of the Venturi device **100**. The angle can, in some variants, be ninety degrees. The angle can, in some configurations, be between sixty and one hundred and twenty degrees. The secondary input **120** can direct the secondary flow, at least partially, against the direction of flow of the primary flow. The introduction of the secondary flow by way of the secondary input **120** into the primary flow can create a vortex, swirl(s), one or more vortices, and/or the like in the primary flow. The creation of the vortex can create a suction at the inlet **102** sucking the primary flow into the Venturi device **100** through the inlet **102**. The suction of the primary flow into the Venturi device **100** can cause the velocity to increase and pressure to decrease of the primary flow through the converging portion **106** and throat **108**, which can cause the temperature of the primary flow through the converging portion **106** and/or throat **108** to decrease such that thermal energy (e.g., heat) from the ambient environment outside the body of the Venturi device **100** is transferred to the primary flow through the body, charging the primary flow with the thermal energy. The temperature and pressure of the primary flow downstream of the throat **108** (e.g., in the diverging portion **110**) can increase before exiting through the outlet **104**. An opening of the secondary input **120** into the inner region of the body (e.g., the primary flow path) can be smaller than a cross-sectional flow area of an input from

the conduit **116** into the annular chamber **118**. The secondary input **120** can direct the secondary flow radially inward toward the primary flow of fluid and/or the central axis **112** of the body.

(36) In some configurations, the body can include a check valve. The check valve can facilitate flow of the primary flow from the inlet **102** to the outlet **104** and impede and/or resist the primary flow from flowing out of the body by way of the inlet **102**. In some configurations, the check valve can be a one-way check valve. In some configurations, the check valve can be a valvular conduit. In some configurations, the check valve can be a fixed-geometry passive check valve. In some configurations, the check valve can include a main channel and a series of loops oriented to facilitate flow of the secondary flow towards the Venturi device and resist flow away from the Venturi device. In some configurations, the check valve can be a Tesla valve. In some configurations, the check valve can be disposed in the converging portion **106**. In some configurations, the check valve can be disposed between the converging portion **106** and the diverging portion **110**. In some configurations, the check valve can be disposed in the diverging portion **110**. In some configurations, the check valve can be disposed at the throat **108**. In some configurations, the check valve can be disposed between the diverging portion **110** and the second converging portion **114**. In some configurations, the check valve can be disposed between the second converging portion **114** and the outlet **104**. In some configurations, the check valve can be disposed at the outlet **104**. In some configurations, the check valve can be disposed at the inlet **102**.

(37) As described herein, the Venturi device **100** can include three openings at the locations **116**, **104** and **102**. In some variants, these three openings can be open to the environment. The annular chamber **118** can be connected via the annular gap **120** with the inner region (e.g., primary flow path) of the Venturi device **100**. The inner region of the body can taper at position (E), thus having a smaller inner diameter than at positions (F) and (D). The taper (reduction of the inner diameter) from position (F) to position (E) as well as the extension (enlargement of the inner diameter) from position (E) to position (D) can be continuous, such as conical. When a secondary flow is introduced into the opening **116**, the secondary flow flows into the annular chamber **118** and is distributed radially there in the annular chamber, which can include an entirety of the annular chamber. From the annular chamber **118**, the secondary flow flows via the secondary input **120** into the inner region of the body of the Venturi device **100** and generates there a vortex, which generates a suction effect at the inlet **102**. As a result, the primary flow is sucked in through the inlet **102** and ejected toward the outlet **104**. At position (E) (e.g., throat or constriction **108**), according to the Venturi effect, the flow velocity of the sucked air increases. By combining the effects of the suction and Venturi effect, there can be a reduction in the temperature before the vortex, so that heat from the environment can be absorbed by the primary flow, charging the primary flow with energy from the ambient environment.

(38) In some configurations, a rotationally symmetrical design for the Venturi device **100** may not be used which does not produce a Venturi effect. In some configurations, a body may be used that creates a flow-induced formation of a vortex, with a suction on one side of the vortex and an ejection of a flowable medium surrounding the vortex on the other side of the vortex. The flowable medium sucked in during the sucking process can be cooled. The cooled flowable medium sucked in can absorb heat (e.g., thermal energy) from the environment, for example, and thus the internal energy of the flowable medium increases. The guidance of the free-flowing medium via heat exchangers may be used.

(39) For ease, FIG. 2 illustrates a simplified schematic of the Venturi device **100** of FIGS. 1A-1C. The arrows **116**, **104** and **102** in FIG. 2 correspond to the openings at locations **116**, **104**, and **102** in FIGS. 1A-1C. Stated differently, **102** corresponds with the inlet **102**, **116** corresponds with conduit **116**, and **104** corresponds with outlet **104**.

(40) FIG. 3 illustrates a section view of a configuration of a Venturi device **300**, which can also be referred to as a vortex induction chamber or VIC. The Venturi device **300** can be similar or identical to the Venturi device **100** in some or many respects. With reference to FIG. 3, the Venturi

device **300** can include an inlet **302** configured to receive a primary flow, an outlet **304** configured to eject the primary flow, a converging portion **306**, a throat **308**, a diverging portion **310**, central axis **312**, a second converging portion **314**, a conduit **316**, an annular chamber **318**, and a secondary input **320**. In some configurations, a cross-sectional flow area of the outlet **304** can be smaller than a cross-sectional flow area of the inlet **302**. The secondary input **320** can be an annular passageway, one or more apertures, plurality of apertures, one or more slots, annular gap, and/or ring gap. The secondary input **320** can be disposed between the converging portion **306** and the outlet **304**, said secondary input **320** configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet **302** and into the body **303**.

(41) The Venturi device **300** can include a body **303** having a body wall **305** comprising the converging portion **306** and the diverging portion **310**. The converging portion **306** can be configured to increase a velocity of the primary flow and decrease a pressure of the primary flow, and the diverging portion **310** can be configured to decrease the velocity of the primary flow and increase the pressure of the primary flow. The movement of the primary flow can flow through the converging portion **306** and the diverging portion **310** to produce a Venturi effect, said Venturi effect pulling the primary flow in through the inlet **302**. In some configurations, the converging portion **306** can include a cross-sectional flow area that continuously decreases in size in the direction of flow of the primary flow. Additionally or alternatively, the diverging portion **310** can include a cross-sectional flow area that continuously increases in size in the direction of flow of the primary flow. In some configurations, a length of the diverging portion **310** is greater than a length of the converging portion **306**. In some configurations, a cross-sectional flow area of the converging portion **306** is circular. In some configurations, the converging portion **306** can define a flow area having a conical shape. Additionally or alternatively, a cross-sectional flow area of the diverging portion can be circular. The diverging portion **310** can also define a flow area having a conical shape. In some configurations, a size of a cross-sectional flow area of the converging portion **306** can change less rapidly than a size of a cross-sectional flow area of the diverging portion **310** per a unit of length. Further, a length of the diverging portion **310** can be greater than a length of the converging portion **306**.

(42) The Venturi device **300** can include a throat **308**, which can also be referred to as a constriction. The throat **308** can be disposed between the converging portion **306** and a diverging portion **310**. The throat **308** can include an inner periphery that is smaller than that of the diameter of the converging portion **306** and the diameter of the diverging portion **310**. For example, the throat **308** can include a diameter that is smaller than a diameter of the converging portion **306** and the diverging portion **310**. The throat **308** can include a cross-sectional flow area that is smaller than that of the converging portion **306** and the diverging portion **310**. In some configurations, the throat **308** can be the junction of the converging portion **306** and the diverging portion **310**. In some configurations, the throat **308** includes a length. In some configurations, the inner periphery of the throat **308** is an inflection point between the converging portion **306** and the diverging portion **310**. In some variants, the converging portion **306** converges to the throat **308** and immediately diverges to the diverging portion **310**.

(43) The Venturi device **300** can also include a first nozzle **307** disposed at least partially in the diverging portion **310**. The first nozzle **307** can extend from the body wall **305**, said first nozzle **307** forming a first annular space **309** between the first nozzle **307** and the body wall **305**. In some configurations, the first nozzle **307** can be connected to the body wall **305** between the converging portion **306** and the diverging portion **310**. The first nozzle **307** can be connected to the body wall **305** at the throat **308**.

(44) The first nozzle **307** can be configured to create a first low pressure fluid in the first annular space **309** relative to a high-pressure fluid flow of the primary flow flowing through the first nozzle **307** to pull the primary flow through the inlet **302** and into the body **303**. The reduction in the high-

pressure fluid flow of the primary flow through the first nozzle **307** can cause the first low pressure fluid to at least partially exit the first annular space **309** for the first low pressure fluid to flow toward the outlet **304**.

(45) The first nozzle **307** can provide a high-pressure and low-pressure stage to capture back pressure from engine pulse waves in the exhaust. The captured back pressure can be circled back to the high-pressure primary flow. The high-pressure fluid stream can push the low-pressure back pressure against the boundary layer along the inner side of the body wall **305** to be in the first annular space **309**, said fluid behavior acting as a fluid dynamic check valve. The low-pressure fluid can then be utilized to fill in the primary flow once there is a pulse, and the high-pressure fluid flow is reduced through first nozzle **307**, allowing the low-pressure fluid to exit from the first annular space **309** and fill in the fluid flow when the high-pressure fluid flow is reduced through the first nozzle **307** because of the pulse in primary flow. The first nozzle **307** can provide a higher tuned intake resonance to help amplify an intake charge (e.g., substantially continuous intake sucking/pulling of the primary flow through the inlet **302**. The first nozzle **307** can extend from the body wall **305** toward the central axis **312** of the body **303**.

(46) The first nozzle **307** can be a bell-shaped nozzle **328** configured to be attached to the converging portion **306** and/or diverging portion **310**. The bell-shaped nozzle **328** can be welded to the diverging section **310**. Additionally or alternatively, the bell-shaped nozzle **328** can be welded approximately at the throat **308** along a flared portion **334** of the bell-shaped nozzle **328**. In some configurations, the body **303** or converging portion **306** and the bell-shaped nozzle **328** can comprise one, single, and/or monolithic continuous piece of material. The diverging portion **310** can comprise a separate piece of material that is configured to attach to body **303** or converging portion **306** and the bell-shaped nozzle **328**. The flared portion **334** of the bell-shaped nozzle **328** can include can be configured to contact an interior wall of the converging portion **306**. Further, the bell-shaped nozzle **328** can function as a dynamic check valve by limiting a back pressure to disrupt and/or impede the primary flow through inlet **302**. Additionally or alternatively, an inner diameter of the first nozzle **307** and/or the bell-shaped nozzle **328** can comprise a spoon like profile to assist in the transfer of the fluid from the convergence portion **306**. Further, the spoon like profile of the convergence portion **306** and/or the bell-shaped nozzle **328** can reduce the occurrence of a turbulent flow in the primary fluid.

(47) The Venturi device **300** can include a smallest cross-sectional flow area of the first nozzle **307** can be between ends of the first nozzle **307** such that at least one of the ends of the first nozzle **307** has a larger diameter relative to a diameter at the smallest cross-sectional flow area of the first nozzle **307**. Additionally or alternatively, both of the ends of the first nozzle **307** can have larger diameters relative to the diameter at the smallest cross-sectional flow area of the first nozzle **307**. The Venturi device **300** can further include a smallest cross-sectional flow area of the second nozzle **311** that can be between ends of the second nozzle **311** such that at least one of the ends of the second nozzle **311** has a larger diameter relative to a diameter at the smallest cross-sectional flow area of the second nozzle **311**. Additionally or alternatively, both of the ends of the second nozzle **311** can have larger diameters relative to the diameter at the smallest cross-sectional flow area of the first nozzle **307**. In some configurations, an axial extent of the first nozzle **307** is less than an axial extent of the diverging portion **310**. In some configurations, an axial extent of the second nozzle **311** can be less than an axial extent of the reducer **330**.

(48) Additionally or alternatively, the Venturi device **300** can further include a second nozzle **311** disposed at least partially in the reducer **330**. The second nozzle **311** can be connected to the body wall **305** at a portion of the body wall **305** between the diverging portion **310** and a reducer **330**. The first nozzle **307** can have a cross-sectional flow area that can continually change in size. The second nozzle **311** can extend from the body wall **305** to form a second annular space **313** between the second nozzle **311** and the body wall **305**. For example, the second annular space **313** can be formed between the reducer **330** second nozzle **311**. The second nozzle **311** can be configured to

create a second low pressure fluid in the second annular space **313** relative to the high-pressure fluid flow of the primary flow flowing through the second nozzle to move the primary flow through the outlet **304**. The reduction in the high-pressure fluid flow of the primary flow through the second nozzle **311** can cause the second low pressure fluid to at least partially exit the second annular space **313** for the second low pressure fluid to flow toward the outlet **304**. The second nozzle **311** can function as dynamic check valve to keep fluid flow going through the outlet **304** to, for example, a turbine, in the event of a pulse and temporary reduction in the primary flow through Venturi device **300**. The second nozzle **311** can function as the first nozzle **307**, but push the fluid flow out of the outlet **304**.

(49) The second annular space **313** can be larger than the first annular space **309**. The second annular space **313** can be about two times larger than the first annular space **309**. The second annular space **313** can be about 1.5, 2.5, 3, or more times larger than the first annular space **309**. An end of the second nozzle **311** proximate the outlet **304** relative to the inlet **302** can be spaced axially inward from an end of the reducer **330**, said end of the reducer **330** at least partially forming the outlet **304**. In some configurations, a cross-sectional flow area of the second nozzle **311** can continually change in size. Additionally or alternatively, a cross-sectional flow area at an exit of the first nozzle **307** can be substantially the same as a cross-sectional flow area at an exit of the second nozzle **311**. In some configurations, the converging portion **306** and diverging portion **310** can comprise one single, and/or monolithic continuous piece.

(50) The second nozzle **311** can be a conical nozzle **332** configured to be attached to the body wall **305** and/or the conical interior surface **315**. The conical nozzle **332** can be welded to conical nozzle **332**. In some configurations, the conical interior surface **315** of the Venturi device **300** and the conical nozzle **332** can comprise one, single, and/or monolithic continuous piece of material. Further, the conical nozzle **332** can function as a dynamic check valve by limiting a back pressure to disrupt and/or impede the primary flow through inlet **302**.

(51) As discussed above, the Venturi device **300** can include a reducer **330** connected to the body wall **305** to house the conical nozzle **332** at outlet **304**, said reducer **330** having a volume greater than the volume of sections 2 and 3 by a factor between 1.1 to 5, 1.25 to 4, 1.5 to 3, or 1.75 to 2.5. The reducer **330** can be connected to the body wall **305** at or proximate the conical interior surface **315**. In some configurations, the body wall **305** and the reducer **330** can comprise one, single, and/or monolithic continuous piece of material. The reducer **330** and conical nozzle **332** can function as a fluid dynamic check valve before the flow is transferred to a turbine. The reducer **330** can be configured to be attached to any tubing, pipes, conduits, and the like to transfer the flow as discussed herein. The conical nozzle **332** can remain detached from any tubing, pipes, conduits, and the like to for example allow for low-pressure fluid flow in and out of the second annular space **313** as discussed herein.

(52) The Venturi device can also include a conical interior surface **315** disposed between the diverging portion **310** and the second nozzle **311**. The conical interior surface **315** can be configured to direct the primary flow toward the outlet **304**. The conical interior surface **315** can have a cross-sectional flow area that decreases in size toward the outlet **304**. In some configurations, the secondary input **320** can be configured to direct the secondary flow through the conical interior surface **315**. Additionally or alternatively, the secondary input **320** can direct the secondary flow at a junction or connection between the conical interior surface **315** and the second nozzle **311**. For example, the cross-sectional flow area of the conical interior surface **315** can converge to a size that is smaller than a cross-sectional flow area of the converging portion **306** and a cross-sectional flow area of the diverging portion **310**, the secondary input **320** can direct the secondary flow the smaller cross-section flow area of the conical interior surface.

(53) As can be seen by comparisons to FIGS. 1A-1C and FIG. 3, inlet **302** can include an inner periphery that is longer than the inlet **102** of Venturi device **100**. For example, the inlet **302** can include a longer transition area than the inlet **102** to allow for a smoother transition. For example,

the transition area can be extended by a factor of 5% to 55%, by a factor of 10% to 50%, by a factor of 15% to 45%, or by a factor between 20% to 40%, or by a factor of 25% to 35% than the inlet length of inlet **102**. The inlet **302** can maintain a uniform reduction angle along the convergence portion **306**. In some configurations, the convergence portion **306** can further include a reduction in the convergence angle to a more aggressive angle. The reduction in the convergence angle can occur at the weld point between sections 2 and 3 between the converging portion **306** and the diverging portion **310**. The angle reduction can be between 1% to 25%, between 2.5% to 20%, between 5% to 15%, or 7.5% to 12.5%.

(54) The Venturi device **300** can utilize an annular chamber **318** and secondary input **320** that can be similar and/or identical to that of annular chamber **118** and secondary input **120** of Venturi device **100**. In some configurations, the secondary input **320** can include a Coandă surface. The secondary input **320** can be disposed downstream of the diverging portion **310**. The annular chamber **318** can be configured to receive and direct the secondary flow to the secondary input **320**. In some embodiments, the secondary input **320** can be disposed between the diverging portion **310** and the outlet **304**. The secondary input **320** can be configured to direct the secondary flow of the fluid into the primary flow at an angle relative to a direction of the primary flow. The angle can be between 10 degrees to 170 degrees, between 20 degrees to 160 degrees, between 30 degrees to 150 degrees, between 40 degrees to 140 degrees, between 50 degrees to 130 degrees, or between 60 degrees to 120 degrees. In some configurations, the secondary input **320** can include one or more apertures **322**. In some configurations, the secondary input **320** can include a plurality of apertures **322**. The one or more apertures **322** can direct the secondary flow to the annular chamber **318**. The annular chamber **318** can distribute the secondary flow throughout the annular chamber **318** as discussed herein via, for example, a Coandă surface.

(55) The secondary input **320** can include an annular gap **324** which can be similar or identical to the annular gap **120**. The annular gap **324** can be in fluid communication with the annular chamber **318**. The annular gap **324** can distribute the secondary flow through the annular gap via, for example, a Coandă surface, and direct the secondary flow into the primary flow. The secondary input **320** can also include a ring gap **325**, which can be considered to be annular gap **324**. The secondary input **320** can be configured to encircle the primary flow through the body **303**. In some configurations, the secondary input **320** can be configured to circumferentially encircle the primary flow through the body **303**. The secondary input **320** can also include one or more openings (e.g., one or more gaps **324**) circumferentially distributed about a flow path of the primary flow, said secondary input **320** configured to direct the secondary flow radially inward toward the primary flow. In some configurations, the Venturi device can include a plurality of secondary inputs **320**.

(56) A surface of the annular chamber **318** can include a Coandă surface or profile that can facilitate the secondary flow of fluid spreading throughout the annular chamber **318**. A surface of the annular chamber **318** can be convex to facilitate the secondary flow of fluid spreading throughout the annular chamber **318**. The annular chamber **318** can also be configured to encircle the primary flow through the body **303**. The secondary flow can adhere (e.g., molecular adhesion) to the surface(s) of the annular chamber **318** to spread throughout the annular chamber **318**. When a secondary flow is introduced into the conduit **316**, the secondary flow flows into the annular chamber **318** and is distributed radially there in the annular chamber **318**, which can include an entirety of the annular chamber **318**. Further, the conduit **316** can be configured to distribute the secondary flow throughout the secondary input **320**. In some configurations, the Venturi device **300** can also include an annular passageway **329** fluidically connected to the annular chamber **318**, the annular passageway configured to direct the secondary flow from the annular passageway **329** into the primary flow.

(57) The secondary input **320** can define an annular shaped opening in an inner periphery of the body of the Venturi device **300**. The secondary input **320** can direct the secondary flow into the primary flow at an angle relative to the direction of flow of the primary flow and/or relative to the

central axis **312** of the body of the Venturi device **300**. The Coandă profile of the Venturi device **300** can be extended by a factor of at least 1.5, at least 2, at least 3, at least 4, at least 5, at least 10, or at least 20 than that Venturi device **100**. Additionally or alternatively, the angle of the Coandă profile of the Venturi device **300** can be adjusted by 5 degrees to 85 degrees, by 7.5 degree to 75 degrees, by 10 degrees to 60 degrees, by 12.5 degree to 45 degrees, and by 15 degrees to 30 degrees in comparison to the Venturi device **100**.

(58) The extending and change of angle of the Coandă profile of the Venturi device **300** can allow the secondary flow to have a smoother transition into the primary flow. In some embodiments, the secondary input **320** can direct the secondary flow to eject from the secondary input **320** at angle such that at least a part of the secondary flow is ejected in a direction along the flow of the primary fluid. The secondary input **320** can direct the secondary flow to eject from the secondary input **320** at angle such that at least a part of the secondary flow is ejected from the secondary input **320** toward the outlet **304**. The angle of the Coandă profile can be in line with the flow rather than perpendicular or into the flow for non-compressible fluids. The Coandă profile of the Venturi device **300** can comprise a spoon like profile that can enable molecular adhesion of the high speed, high pressure secondary stream of fluid to the low pressure, high volume primary stream in a hydrodynamic state more efficiently. Additionally or alternatively, the ring gap **320** can be resurfaced with an angle transition between 10 degrees to 80 degrees, between 15 degrees to 75 degrees, between 20 degrees to 65 degrees, between 25 degrees to 65 degrees, between 30 degrees to 60 degrees, between 35 degrees to 55 degrees, or between 40 degrees to 50 degrees to optimize flow rate.

(59) A configuration of another Venturi device **400** is shown schematically in FIGS. **4A-4D**. FIG. **4A** illustrates a sectional view of the Venturi device **400**. The Venturi device **400** can have a similar layout to that of the Venturi devices **100** and **300** with changes noted below. Distinctive positions of the axis are marked by arrows and the letters B, C, D, E and F. As described above, gases can be introduced from the conduit **416** via the annular chamber **418** and the secondary input **420**, which can include a ring gap **430**, into the interior of the Venturi device **400**. In some configurations, the ring gap **430** can be fixed once the chosen fluid is identified. In field adjustment may not be necessary to adjust a ring gap **430**. In some configurations, a tapered machine union can be applied to the ring gap **430** to seal the Venturi device **400**. In the area of D of the charging element (e.g., Venturi device **400**) a vortex may be formed, as described in reference to FIG. **1A**. This vortex creates a vacuum at the inlet **302** (location F). As a result, ambient air can be sucked into the Venturi device **400** via the inlet **402** and the throat **408** (e.g., constriction).

(60) Since this air is compressed on the other side of the vortex (in direction C), the area of the pipe between B and E may be called a compression chamber. In sizing the Venturi device **400**, the volume of the annular chamber **418** can be equal to than circumference times the area of the ring gap **430**. The annular chamber **418** can be configured to receive and direct the secondary flow to the secondary input **420**. In some configurations, the Venturi device **400** can include a single point annular chamber **418** for compressible fluids. In some configurations, the annular chamber **418** can include multiple uniform chambers inputs for non-compressible fluids. In some configurations, the annular chamber **418** can encircle the primary flow in a body **411** of the Venturi device **400**. The annular chamber **418** can include a Coandă surface(s) configured to distribute incoming secondary flow throughout the annular chamber **418** by the secondary fluid flowing along the Coandă surface(s).

(61) The secondary input **420** can be an annular passageway, one or more apertures, plurality of apertures, one or more slots, annular gap, and/or ring gap fluidically connected to the annular chamber **418**. The annular passageway **431** can be configured to direct the secondary flow from the annular passageway **431** into the primary flow. Ambient air and exhaust gases are fused at the position corresponding to B and are pressed into the combustion chamber by passing through the outlet **304** at location C. The diameter of the outlet **404** can be similar and/or equal to the to

distance between the inlet **402** and the throat **408** to produce a ratio for sizing the Venturi device **400**. Also, a cross-sectional flow area of the outlet **304** can be smaller than a cross-sectional flow area of the inlet **402**.

(62) As mentioned above, the body of the Venturi device **400** can also include a throat **408**, which can also be referred to as a constriction. The throat **408** can be disposed between a converging portion **406** and a diverging portion **410**. The cross-sectional flow area of the converging portion **406** can be circular. In some configurations, the converging portion **406** can define a flow area having a conical shape. Further, the cross-sectional flow area of the diverging portion **410** can be circular. In some configurations, the diverging portion **410** can define a flow area having a conical shape. The converging portion **406** can be configured to increase a velocity of the primary flow and decrease a pressure of the primary flow. The diverging portion **410** can be configured to decrease the velocity of the primary flow and increase the pressure of the primary flow. A size of a cross-sectional flow area of the converging portion **406** can change more rapidly than a size of a cross-sectional flow area of the diverging portion **310** per a unit of length.

(63) The Venturi device **400** can include a body wall **405** forming the convergence portion **306** and the diverging portion **410**. An outer shell of the body wall **405** can utilize a fixed reduction angle ratio between 1.25:1 to 5:1, between 1.5:1 to 4:1, between 1.75:1 to 3:1, or 2:1 to 2.5:1. The throat **408** can include a diameter that is smaller than a diameter of the converging portion **406** and a diameter of the diverging portion **410**. The converging portion **406** can include a cross-sectional flow area that continuously decreases in size in the direction of flow of the primary flow. The diverging portion **410** can have a cross-sectional flow area that continuously increases in size in the direction of flow of the primary flow. A length of the diverging portion **410** can be greater than a length of the converging portion **406**. The outer wall of the diverging portion **410** of the Venturi device **400** can be smaller than the outer wall of the converging portion **406**. The outer wall of the diverging portion **410** of the Venturi device **400** can be 1% to 50%, 5% to 45%, 10% to 40%, 15% to 35%, 20% to 30%, or 22.5% to 27.5% smaller than the outer wall of the converging portion **306**. The outer wall of the diverging portion **410** can be attached to the outer layer of the converging portion **406**. The diverging portion **410** entrance can be inset into the body of the Venturi device **400** between inlet **402** and outlet **404** at a similar and/or equal distance as the length of the outlet **404** between locations B and C. Additionally or alternatively, the internal nozzle reduction angle between the throat **408** and the second converging portion **414** can be variable such that the flow rate of the fluid can be increased and create a vacuum at the first fluid dynamic check valve.

(64) A first funnel **407** can be disposed at least partially in the converging portion **406**. The first funnel **407** can be configured to attach to the converging portion **406**. In some configurations, the first funnel **407** can be welded to the converging portion **406**. An end of the first funnel **407** can also be configured to attach to the inlet **402** as well as along the converging portion **406**. In some configuration, a portion of the body wall **405** and the first funnel **407** can comprise a single piece that is attached to sections 3 and 4. The first funnel **407** can form a first annular space **409** between the first funnel **407** and the body wall **405**.

(65) The first funnel **407** can provide a high-pressure and low-pressure stage to capture back pressure from engine pulse waves in the exhaust. The captured back pressure can be circled back to the high-pressure primary flow. The high-pressure fluid stream can push the low-pressure back pressure against the boundary layer along the inner side of the body wall **405** to be in the first annular space **409**, said fluid behavior acting as a fluid dynamic check valve. The low-pressure fluid can then be utilized to fill in the primary flow once there is a pulse, and the high-pressure fluid flow is reduced through first funnel **407**, allowing the low-pressure fluid to exit from the first annular space **409** and fill in the fluid flow when the high-pressure fluid flow is reduced through the first funnel **407** because of the pulse in primary flow. The first funnel **407** can provide a higher tuned intake resonance to help amplify an intake charge (e.g., substantially continuous intake sucking/pulling of the primary flow through the inlet **402**). The first funnel **407** can extend from the

body wall **405** toward the central axis **412** of the body **411**.

(66) In some configurations, the Venturi device **400** can include a pseudosphere-shaped entrance comprising the first funnel **407** which can improve impulse resonance, fluid velocity, and/or the internal geometry by functioning a first fluid dynamic check valve. The first funnel **407** can be configured to create a first low pressure fluid in the first annular space **409** relative to a high-pressure fluid flow of the primary flow flowing through the first funnel **407** to pull the primary flow through the inlet **402** and into the body **411**. In some configurations, the first funnel **407** can be connected to the body wall **405** at the inlet **402**. The reduction in the high-pressure fluid flow of the primary flow through the first funnel **407** can cause the first low pressure fluid to at least partially exit the first annular space **309** for the first low pressure fluid to flow toward the outlet **404**. A cross-sectional flow area of the first funnel **407** can continually decrease in size toward the central axis **412** in the direction of flow of the primary fluid.

(67) A second funnel **413** can be disposed at least partially in the diverging portion **410**. The second funnel **413** can function as an internal extended transition that creates a second low pressure gap. In some configurations, a first portion of the body wall **405a** and an inner wall **417** of FIG. 4D can comprise one, single, and/or monolithic continuous piece of material that is attached to a second portion of body wall **405b**. The second portion of the body wall **405b** can be welded to the first portion of the body wall **405a** and the inner wall **417**. The space between the body wall **405** and the inner wall **417** can create the second funnel **413**. In some configurations, the inner wall **417** and second funnel **413** can comprise a one, single, and/or monolithic continuous piece of material that is configured to be attached to the first portion of the body wall **405a** and the inner wall **417**. The second funnel **413** can extend from the body wall **405** toward the central axis **412** of the body **411**, said second funnel **413** forming a second annular space **415** between the second funnel **413** and the body wall **405**. The second funnel **413** can also act as a dynamic check valve similar to the first funnel **407**.

(68) The first funnel **407** and the second funnel **413** amplify the suction created by the intake charge creating a high-speed jet of fluid as well as recycling any backpressure created by the intake pulse waves from, for example, the combustion process in an internal combustion engine or other pulses in the primary flow. The second funnel **413** can be connected to the body wall **405** at a junction between the converging portion **406** and the diverging portion **410**. The second funnel **413** can be configured to create a second low pressure fluid in the second annular space **415** relative to the high-pressure fluid flow of the primary flow flowing through the second funnel **413** to pull the primary flow through the inlet **402** and into the body **411**. The reduction in the high-pressure fluid flow of the primary flow through the second funnel **413** can cause the second low pressure fluid to at least partially exit the second annular space **415** for the second low pressure fluid to flow toward the outlet **404**. A cross-sectional flow area of the second funnel **413** can continually decreases in size toward the central axis **412** in the direction of flow of the primary fluid. Additionally or alternatively, a cross-sectional flow area at an exit of the first funnel **407** can be substantially the same as a cross-sectional flow area at an exit of the second funnel **413**. The second annular space **415** can act as a second dynamic check valve. The second annular space **415** can be larger than the first annular space **409**. An axial extent of the first funnel **407** can be substantially equal to an axial extent of the converging portion **406** along the central axis **412**. An axial extent of the second funnel **413** is less than an axial extent of the diverging portion **410** along the central axis **412**.

(69) A secondary input **420** can be disposed between the converging portion **406** and the outlet **404**. The secondary input **420** can be disposed downstream of the diverging portion **410**. The secondary input **420** can be configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet **402** and into the body **411**. The secondary input **420** can further include a Coandă surface. In some configurations, the secondary input **420** can be configured to direct the secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow. The angle can be between 10 degrees to 170 degrees,

between 20 degrees to 160 degrees, between 30 degrees to 150 degrees, between 40 degrees to 140 degrees, between 50 degrees to 130 degrees, or between 60 degrees to 120 degrees. In some configurations, the secondary input **420** can include one or more apertures **432**. In some configurations, the secondary input **420** can include a plurality of apertures **432**. The one or more apertures **432** can direct the secondary flow to the annular chamber **418**. The annular chamber **418** can distribute the secondary flow throughout the annular chamber **418** as discussed herein via, for example, a Coandă surface.

(70) The secondary input **420** can include an annular gap **429** which can be similar or identical to the annular gap **120**. The annular gap **429** can be in fluid communication with the annular chamber **418**. The annular gap **429** can distribute the secondary flow through the annular gap via, for example, a Coandă surface, and direct the secondary flow into the primary flow. The secondary input **420** can also include a ring gap **430**, which can be the annular gap **429**. The secondary input **420** can be configured to encircle the primary flow through the body **411**. In some configurations, the secondary input **420** can be configured to circumferentially encircle the primary flow through the body **411**. The secondary input **420** can also include one or more openings (e.g., one or more gaps **429**) circumferentially distributed about a flow path of the primary flow, said secondary input **420** configured to direct the secondary flow radially inward toward the primary flow. In some configurations, the Venturi device **400** can include a plurality of secondary inputs **420**.

(71) A conical interior surface **419** can be disposed downstream of the secondary input **320** relative to the primary flow of the fluid. The conical interior surface **419** can be configured to direct the primary flow toward the outlet **404**. The conical interior surface **419** can also include a cross-sectional flow area that increases in size toward the outlet **404**.

(72) The cross-sectional flow area of the conical interior surface **419** can increase up to the outlet **404**. The conical interior surface **419** can be a first conical interior surface **419** the Venturi device **400** can include a second conical interior surface **421** disposed between the diverging portion **410** and the first conical interior surface **419**. The second conical interior surface **421** can be part of the second converging portion **414**. The second conical interior surface **421** can be configured to direct the primary flow toward the outlet **404**. The second conical interior surface **421** can include a cross-sectional flow area that decreases in size toward the outlet **404**. The secondary input **420** can be configured to direct the secondary flow through the second conical interior surface **421**. The secondary input **420** can be configured to direct the secondary flow between the first conical interior surface **419** and the second conical interior surface **421**.

(73) The cross-sectional flow area of the second conical interior surface **421** can converge to a size that is smaller than a cross-sectional flow area of the converging portion **306** and a cross-sectional flow area of the diverging portion **410**. The first conical interior surface **419** and the second conical interior surface **421** can converge to form a throat **423** having a smallest diameter and smallest cross-sectional flow area relative to the first conical interior surface **419** and second conical interior surface **421**.

(74) Further, the inlet of ambient air (FIG. 4C in FIG. 4A) could be formed like velocity stack allowing smooth and even entry of air at high velocities. Here, also resonance effects can be observed which promote the induction of the generation of the vortex. In addition, the inside wall of the Venturi device **400** can include a radius entry and/or “plenum.” A velocity stack, trumpet, or air horn is a trumpet-shaped design having differing lengths which can be used at the inlet **402**. These designs can allow smooth and even entry of air at high velocities with the flow stream adhering to the walls—known as laminar flow. Additionally or alternatively, modifications can be made to the dynamic tuning range of the intake tract by functioning as a resonating pipe which can adjust the frequency of pressure pulses based on its length within the tract. Modern engines can have tuned intake tract volumes and associated resonance frequencies designed to provide higher than atmospheric intake air pressure while the intake valves are open. These intake tract volumes can increase the density of the trapped air in the combustion chamber providing for higher

compression.

(75) The systems, particulate burner, particulate burner systems, and Venturi devices **300** can be made with varying dimensions. Some non-limiting example dimensions for the particulate burner according to FIG. **4A** are below: Length between (D) and (C)=between 6.00 inches and 7.00 inches Ring gap **120**=between 0.001 inches and 0.003 inches Inner diameter (further referred as “I.D.”) at B=between 1.57 and 1.68 inches Reduction angle between (D) and (B)=between 35° and 55° Reduction angle between (C) and (B)=between 55° and 65° I.D. at (C)=between 1.63 inches and 2.05 inches I.D. at (D)=between 3.25 inches and 4.01 inches Length between (D) and (E)=between 4.50 and 6.00 inches Reduction angle between (D) and (E)=30° and 53° I.D. at (E)=between 1.25 inches and 2.35 inches Reduction angle between (F) and (E)=between 33° and 41° Length between (F) and (E)=between 4.00 inches and 6.00 inches Conduit **316** is steel tubing with I.D. of between 0.75 inches to 1.00 inches Converging portion **406** is modified pressure activated heat riser butterfly valve (F), the inlet **402**, can be made of elastic polymer or programmable metallic polymer to adjust opening in correspondence to incoming intake pressure. Area between (E) and (F) can be made of an elastic polymer or a programmable metallic polymer to adjust the opening according to the input pressure applied (e.g., different dynamic pressure at different driving speeds if the particulate burner should be installed in a vehicle). At the ring gap **430**, a Coandă effect profile of 35° to 80° can be applied. The ring gap **430** can have a 70-degree angle cut into the edge of the ring.

(76) The Venturi device **400** can be constructed out of dissimilar metals. By doing so, the dissimilar metals can create friction at internal points of compression. Further, the dissimilar metals can reduce friction to create higher efficiency boundary layers for fluid acceleration of compressed fluid to the intake charge.

(77) The systems, devices, and components thereof can be made of a variety of materials such metals (such as steel, aluminum, and/or others), metal alloys, polymers (such as plastic), ceramics, shape memory materials, and/or other suitable materials. The systems, devices, and components thereof can be galvanized, painted, zinc coated, powder coated, vinyl coated, plastic dripped, textured, and/or finished with other materials or methods.

(78) Hydro-Turbine System

(79) FIG. **5** illustrates a hydropower system **500** for converting potential energy of a fluid into electrical energy. FIG. **6** illustrates a configuration of a hydropower system **600** for converting potential energy of a fluid into electrical energy. FIG. **7** illustrates a configuration of a hydropower system **700** for converting potential energy of a fluid into electrical energy. FIG. **8** illustrates a configuration of a hydropower system **800** for converting potential energy of a fluid into electrical energy. The systems **500**, **600**, **700**, and **800** can be compatible with hydro and aerodynamic turbine designs with limited or no moving parts as the fluid can be accelerated by the use of Venturi devices along with turbines and/or pumps.

(80) In some embodiments, the systems of FIGS. **5-8** and/or parts can be comprised of 316 stainless steel. The fluid can be passed through a variable size and adjustable Venturi device **510** which can be similar or identical to either the Venturi device **100** described FIG. **1A** and/or the Venturi device **300** described in FIG. **3**. In some embodiments, the fluid is compressed by the Venturi device **510**. The increase in exit velocity and density can be increased by a factor 2, 3, 4, 5, 6, or higher than the original velocity and/or density. The exiting fluid can then be passed into a turbine which generates electricity by spinning the input shaft of a generator and initiating an output of electrical current. In some embodiments, the turbine is an induction turbine.

(81) In FIGS. **5-8**, a fluid loop, conduit, or tunnel **502** can direct or move a primary flow of fluid between an upper reservoir **504** and a lower reservoir **506**. The upper reservoir **504** can be at a higher elevation than the lower reservoir **506**. The fluid from the upper reservoir **504** can flow from the upper reservoir **404** to the lower fluid source **506** via gravity. The fluid loop, conduit, or tunnel **502** can include tubing, conduits, pipes, etc. to circulate the primary flow fluid. The system **500** can

include one or more Venturi devices **510** (e.g., two), one or more pumps **520**, a turbine **522**, a generator **526**, and the like. The one or more Venturi devices **510** (e.g., two), one or more pumps **520**, and/or turbine **522** can be disposed on the fluid loop, conduit, or tunnel **502**. The system **500** can include a fluid loop **502** as illustrated in FIG. 5 such that electricity can be generated via turbine **522** as discussed herein while simultaneously pumping fluid from the lower reservoir **506** to the upper reservoir **504** via pump **520** as discussed herein.

(82) The turbine **522** can be configured to be driven by the primary flow from the upper reservoir **504** to the lower reservoir **506**. The generator **526** can be configured to be driven by the turbine **522** to generate electricity. The pump **520** can be configured to drive the primary flow from the lower reservoir **506** to the upper reservoir **504**. The pump **520** can also include a motor **528** that is configured to be powered by at least one of a generator **526** and/or an external power supply **530**. The pump **520** can drive the primary flow from the lower reservoir **506** to the upper reservoir **504** while turbine **522** is driven by the primary flow from the upper reservoir **504** to the lower reservoir **506** to recirculate the fluid from the lower reservoir **506** to the upper reservoir **504**. The pump **520** drives the primary flow from the lower reservoir **506** to the upper reservoir **504** while flow of the fluid is stopped through the turbine **522**.

(83) In FIG. 5, the first Venturi device **510a** and the turbine **522** can be disposed on a first fluid path **502a** in which the fluid is flowing from the upper reservoir **504** down to the lower reservoir **506**. Flow through a second fluid path **502b** can be stopped or restricted when the fluid is flowing from the upper reservoir **504** down to the lower reservoir **506**. The first Venturi device **510a** can be downstream of the upper reservoir **504** and upstream of the turbine **522** and between the upper reservoir **504** and the turbine **522** on the fluid loop, conduit, or tunnel **502**.

(84) The second Venturi device **510b** and the pump **520** can be disposed on a second fluid path **502b** in which the fluid is transferred from the lower reservoir **506** to the upper reservoir **504**. Flow through the first fluid path **502a** can be stopped or restricted when the fluid is transferred from the lower reservoir **506** to the upper reservoir **504**. The second Venturi device **510b** can be downstream of the lower fluid source **510b** and upstream of the pump **520** and between the lower reservoir **506** and the pump **520** on the fluid loop, conduit, or tunnel **502**.

(85) One or more Venturi devices **510** can be disposed on the second fluid path **502b**. The turbine **522** can be disposed between the first Venturi device **510a** and the lower reservoir **506** on the fluid loop, conduit, or tunnel **502**. The first Venturi device **510a** can be disposed between the upper reservoir **504** and the turbine **522** on the first fluid path **502a** of the fluid loop, conduit, or tunnel **502**. The first Venturi device **510a** can be downstream of the upper reservoir **504** and upstream of the turbine **522**, between the upper reservoir **504** and the turbine **522** on the fluid loop, conduit, or tunnel **502**. The second Venturi device **510b** can be disposed between the pump **520** and the lower reservoir **506** on the second fluid path **502b** of the fluid loop, conduit, or tunnel **502**.

(86) In some embodiments, an other pump **521** can be disposed on the fluid loop, conduit, or tunnel **502**, said other pump **521** can be configured to drive the primary flow from the lower reservoir **506** to the upper reservoir **504**. In some embodiments, a third Venturi device **510c** can be disposed on the fluid loop, conduit, or tunnel **502**. The third Venturi device **510c** can be downstream of the lower reservoir **506** and upstream of the other pump **521** and between the lower reservoir **506** and the other pump **521** on the fluid loop, conduit, or tunnel **502**.

(87) The primary flow can flow start at the upper reservoir **504** and then flow through the first Venturi device **510a** and the turbine **522** on the first fluid path **502a** of the fluid loop, conduit, or tunnel **502** before reaching the lower reservoir **506**. The primary flow can then be recirculated back to the upper reservoir **504** by pumping the fluid through the second Venturi device **510b** and the pump **520**.

(88) System **600** and **700** can be similar or identical to the system **500**. As shown in FIGS. 6 and 7, the pump **420** and the turbine **522** can be disposed on the flow loop **502**. The first Venturi device **510a** can be disposed on a first fluid path **502a** that can be in fluid communication with the upper

reservoir **504** and/or in fluid communication with the fluid loop, conduit, or tunnel **502**. The fluid can flow from the upper reservoir **504**, through the first Venturi device **510a**, through the turbine **522**, and then discharged from the turbine **522** to the lower reservoir **506**. The second Venturi device **510b** can be disposed on a second fluid path **502b** that can be in fluid communication with the lower reservoir **506** and/or in fluid communication with the fluid loop, conduit, or tunnel **502**. The fluid can flow from the lower reservoir **506**, through the second Venturi device **510b**, through the pump **520**, and then discharged from the pump **520** to the upper reservoir **504**.

(89) As shown in FIG. **8**, the system **800**, which can be similar or identical to the system **500**, **600**, **700**, can include the first Venturi device **510a**, second Venturi device **510b**, the pump **520**, and turbine **522** disposed on the fluid loop, conduit, or tunnel **502**. A first fluid path **502a** (also discussed herein as a “first bypass line”) and the second fluid path **502b** (also discussed herein as a “second bypass line”) can perform as a bypass line to direct the fluid around the Venturi devices **510a**, **510b** depending on the direction of the fluid flow.

(90) The first bypass conduit **502a** can be connected to the fluid conduit upstream and downstream of the first Venturi device **510a**. The first bypass conduit **502a** can direct the primary flow around first Venturi device **510a** such that the primary flow does not pass through the first Venturi device **510a** with the primary flow flowing from the lower reservoir **506** to the upper reservoir **504** via the fluid loop **502**. Additionally or alternatively, the second bypass conduit **502b** can connect to the fluid conduit upstream and downstream of the second Venturi device **510b**. The second bypass conduit **502b** can direct the primary flow around second Venturi device **510b** such that the primary flow does not pass through the second Venturi device **510b** with the primary flow flowing from the upper reservoir **504** to the lower reservoir **506** via the fluid loop **502**.

(91) As the fluid flows from the upper reservoir **504** to the lower reservoir **506**, the fluid can pass through the first Venturi device **510a**, through the turbine **522**, and around the second Venturi device **510b** by flowing through the second fluid path **502b**, and then the fluid is discharged into lower reservoir **506**. The fluid can be pumped from the lower reservoir **506** to the upper reservoir **504**, by first passing the fluid through the second Venturi device **510b**, through the pump **520**, through the first fluid path **502a** around the first Venturi device **510a** before being discharged into the upper reservoir **504**. In FIG. **8**, the direction of the flow can determine which fluid path the flow takes. In some configurations, the first and second fluid paths **502a**, **502b** are designed so that the fluid passes through the path in one direction. In some embodiments, the first and second fluid paths **502a**, **502b** can allow the fluid to recirculate back to the inlet of the first and second Venturi devices **510a**, **510b**.

(92) As described herein, and shown in FIGS. **5-8**, a recirculation conduit, a flow line, a bleed line, and/or secondary flow conduit **524** (also mentioned herein as a “fluid conduit”) which can be function as conduit **116** described in reference to FIGS. **1A-1C** and/or the conduit **316** described in reference to FIG. **3**, can route a portion of the primary flow (e.g., secondary flow) from the fluid loop, conduit, or tunnel **502**, such as from the pump **520**, turbine **522**, first fluid path **502a**, or second fluid path **502b**, and back to the first Venturi device **510a** and/or second Venturi device **510b** to create vortices therein, as described above in reference to FIGS. **1A-1C** and/or FIG. **3**, to generate a suction to facilitate the passing of the fluid. The bleed line **524** can assist in creating a smooth transition of energy throughout the system.

(93) The secondary flow of the first Venturi device **510a** flows from the turbine **522** to the secondary input of the first Venturi device **510a**. A first conduit **524a** can be fluidically connected to the turbine **522** and the secondary input of the first Venturi device **510a**, the first conduit **524a** configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device **510a**.

(94) The secondary flow of the second Venturi device **510b** flows from the pump **520** to the secondary input of the second Venturi device **522**. A second conduit **524b** can be fluidically connected to the pump **520** and the secondary input of the second Venturi device **510b**, the second

conduit **524b** configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device **510b**. A third conduit **524c** can be fluidically connected to the fluid loop, conduit, or tunnel **502** between the upper reservoir **504** and the turbine **522**. The third conduit **524c** can be configured to direct the secondary flow of the second Venturi device **510b** from the primary flow from the upper reservoir **504** to the secondary input of the second Venturi device **510b**. The Venturi device **510b** can utilize the third conduit **524c** and the back pressure through the line to provide an energy input for transporting the primary flow from the lower reservoir **506** to the upper reservoir **504**.

(95) A secondary flow of the third Venturi device **510c** can flow from the other pump **521** to a secondary input of the third Venturi device **510c**. A fourth conduit **524d** can be fluidically connected to the other pump **521** and the secondary input of the third Venturi device **510c**. The fourth conduit **524d** can be configured to direct the secondary flow from the primary flow to the secondary input of the third Venturi device **510c**. A fifth conduit **524e** can be fluidically connected to the fluid loop, conduit, or tunnel **502** between the upper reservoir **504** and the turbine **522**. The fifth conduit **524e** can be configured to direct the secondary flow of the third Venturi device **510c** from the primary flow from the upper reservoir **504** to the secondary input of the third Venturi device **510c**. The secondary input of any of the Venturi devices **510** can be adjustable to regulate an input of the secondary flow into the primary flow. A sixth conduit **524f** can be fluidically connected to the turbine **522** and the secondary input of the second Venturi device **510b**. The sixth conduit **524f** can be configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device **510b**. The sixth conduit **524f** can also assist in moving the primary fluid back to the upper reservoir **504** from the lower reservoir **506**. Sixth conduit **524f** can improve the efficiency of the system **500** by eliminating conversion losses from the kinetic energy to electrical energy within the turbine **522**. The secondary input of any of the Venturi devices **510** can be adjustable to regulate an input of the secondary flow into the primary flow.

(96) As shown in FIG. 5, back pressure can be taken from the first fluid path **502a**, such as from a penstock tunnel before the first Venturi device **510a** and be redirected to the second Venturi device **510b** to assist the transfer of water along the second fluid path **502b**. The generator **526** can generate electrical energy from the mechanical energy of the turbine **522** as the primary flow drives the turbine **522**.

(97) Additionally or alternatively, as the load increases on the generator **526** due to the output demand, a bypass line(s) **524** can be pressurized. The bypass line(s) **524** can be connected to an inlet similar and/or identical to the inlet **116** of the Venturi device(s) **100** and/or the conduit **316** of the Venturi device **300**. The pressurized fluid from the bypass line **524** can activate the Venturi device **510** and, in conjunction with the Coandă effect, accelerating and increasing the velocity and/or the density of the flow through the corresponding Venturi devices and fluid loop **502**. As resistance in the turbine increases, the inlet pressure can increase. In some embodiments, the inlet can withstand an inlet pressure up to 350 psi, up to 325 psi, up to 300 psi, up to 275, or up to 250 psi. Additionally or alternatively, heat energy from the turbine can be injected into the system **500** further increasing the pressure at the inlet. By introducing the pressure from the bypass line **524** into the flow loop **502**, a smooth transition of energy can occur that can increase efficiency.

(98) It can be assumed that neither frictional losses, dissipation losses nor the conversion losses between the individual forms of energy occur. In one configuration, as shown in FIG. 5, the primary flow passes through the points (22), (13), (12), (1), (2), (3), (4), (5), (19), (20), (6), (7), (8), (9), (10), (11), (21), (14), (15), (17), (23), (24), (25), (26), (27), (28), (29), (30), (31), (32), (33), and (34) of the fluid loop, conduit, or tunnel **502**, which can be connected by way of tubing, pipes, conduits, and the like, and thus circulates in a circuit (e.g., fluid loop) which links the pump **520**, Venturi device **510** (e.g., first Venturi device **510a**), turbine **522**, and Venturi device **510** (e.g., second Venturi device **510b**). The circulating flow can be referred to as the primary flow. In a configuration, as shown in FIG. 6, the primary flow passes through the points (13), (12), (1), (2),

(3), (4), (5), (19), (20), (6), (7), (8), (9), (10), (11), (16), (14), (15), (17), and (18) of the fluid loop, conduit, or tunnel **502**, which can be connected by way of tubing, pipes, conduits, and the like, and thus circulates in a circuit (e.g., fluid loop) which links the pump **520**, Venturi device **510** (e.g., first Venturi device **510a**), turbine **522**, and Venturi device **510** (e.g., second Venturi device **510b**). In the configuration shown in FIG. 7, the primary flow passes through the points (13), (12), (1), (2), (3), (4), (5), (19), (20), (6), (7), (8), (9), (10), (11), (16), (14), (15), (17), and (18) of the fluid loop, conduit, or tunnel **502**, which can be connected by way of tubing, pipes, conduits, and the like, and thus circulates in a circuit (e.g., fluid loop) which links the pump **520**, Venturi device **510** (e.g., first Venturi device **510a**), turbine **522**, and Venturi device **510** (e.g., second Venturi device **510b**). In the configuration shown in FIG. 8, the primary flow passes through the points (16), (12), (1), (2), (3), (4), (5), (18), (20), (19), (6), (7), (8), (9), (13), (11), (16), (14), (10), (15), and (17), and of the fluid loop, conduit, or tunnel **502**, which can be connected by way of tubing, pipes, conduits, and the like, and thus circulates in a circuit (e.g., fluid loop) which links the pump **520**, Venturi device **510** (e.g., first Venturi device **510a**), turbine **522**, and Venturi device **510** (e.g., second Venturi device **510b**).

(99) The primary flow can cause two effects. First, the turbine **522** can be driven by the primary flow, which drives the generator **526**, which in turn results generates electrical energy in the form of electricity. Second, a secondary flow can be directed via points (14), (15), (18), (32) (where shown) into the Venturi device **510a** and the Venturi device **510b** where it rejoins the primary flow, as detailed herein with reference to the secondary flow being directed into the primary flow. As a result, the vortices described above are formed in the Venturi devices **510**, which generate a suction on the back of the Venturi devices **510** (points (1), (7), and (24)). As described above, in the Venturi device **510**, a vortex is formed which generates a suction on one side (positions (1), (7), and (24)), and an increased pressure on the other side (positions (2), (8), and (25)).

(100) The pressure in position (14), (15), (18), (32), and (34) can continue to increase and is thus also returned to the Venturi devices **510** via the secondary flow. The return of the fluid through the secondary flow can lead to an increase in the vortex in the Venturi devices **510**, which in turn increases the suction effect. It is therefore a self-reinforcing cycle driven by the energy present in the environment. At the same time, the fluid, which can be water, that is circulated through the pump **520**, Venturi device **510a**, turbine **522**, and Venturi device **510b** is energetically charged (increase in internal energy) which can be caused by the increased suction effect. The circulation of the fluid in the closed circuit of the pump **520**, Venturi device **510a**, turbine **522**, and Venturi devices **510b** as well as the secondary air flows can be assisted by the natural back pressure generated by the penstock tunnel. The system **500** can be referred to as a “VIP” (“Vortex Induction Pump”) and/or a “VIC” (“Vortex Induction Chamber”).

(101) The principle of the VIP shown in FIGS. 5-8 is not restricted in the number of Venturi devices **510** used. In principle, the use of one Venturi device **510** is sufficient, but 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100 or more than 100 Venturi devices **510** can be combined in one VIC. One or more Venturi devices **510** can thus be combined in a VIC.

(102) The principle of the VIP shown in FIGS. 5-8 is not limited in the number of pumps used. Characteristic of a pump is the generation of a flow in a free-flowing medium. The principle of the VIP shown in FIGS. 5-8 is not limited in the number of turbines used. Characteristic of a turbine is the withdrawal of internal energy from a free-flowing medium. These turbines can be freely connected to any number of electrical generators.

(103) The flow of fluid (e.g., water) in a VIP can be guided in any way (e.g., in the form of a cascade). However, it is also possible for fluid to be fed into the VIP at one point and out of the VIP at another point and discharged into the environment. In some embodiments, the proportion of the

operating energy required for the operation of the VIP increases in relation to the energy that the flowable medium has when discharging was removed. The number of turbines and generators is also not limited.

(104) In some embodiments, when the systems **500**, **600**, **700**, and **800** are used for hydroelectric storage, the Venturi device **510** can work together with the turbine **522** to help transport water to elevated reservoirs after the water is utilized in electricity generation. The high-pressure bypass line **524** can be split such that pressurized water can be transferred to said elevated reservoirs by using the pressure lost through friction and radiation at the turbine **522**. The systems **500**, **600**, **700**, and **800** can be used for hydroelectric storage when electricity demand on the electricity grid is low, such as at night. Less in demand, cheaper electricity can be used to store fluid in the upper reservoir **504** for electricity generation during the day via the systems **500**, **600**, **700**, and **800** as discussed herein when electricity demand is high.

(105) Phase Shifting Thermal Energy Conversion System

(106) FIG. **9** illustrates a phase shifting system **900** having a phase shifting energy conversion system within a fluid stream in motion. FIG. **10** illustrates a configuration of a phase shifting system **1000** having a phase shifting energy conversion system within a fluid stream in motion. A phase shifting fluid composition used within the systems **900** and **1000** can be designed to maximize boundary layer efficiency, prevent breakdown of fluid through the high heat cyclic operation, to maximize viscosity to reduce potential cavitation, and to store and redirect ionized and thermal energy in the fluid stream to sustain operation past standard physic models of unmodified fluid streams.

(107) The systems **900** and **1000** can use a thermal energy storage using cutting edge physics and thermal, chemical, kinetic reaction. The systems **900** and **1000** can use nanoparticle structures that deploy the graphene and copper particle sizes with unique H₂O, blended glycol formulas to enable high viscosity and low environmental impact. For example, a copper-propylene glycol nanofluid can be as an efficient thermic fluid for application in discharge cycle of thermal energy storage. Nanofluids disclosed herein heat transfer fluids for a wide range of energy management applications. Probe ultrasonication-mediated preparation of copper-propylene glycol nanofluid is accomplished through dispersion of biosurfactant-functionalized copper nanoparticles in propylene glycol. Copper-propylene glycol nanofluids are colloidally stable; retain their thermal conductivity enhancement despite repeated heating-cooling cycles and storage for more than 15 days, for example. These nanofluids exhibit temperature-independent thermal conductivity enhancement, with about ~11% enhancement for 1 vol % nanofluid, attributable to Brownian motion and interfacial layering. The viscosity of nanofluids is lower than that of base fluid (propylene glycol) due to interactions between biosurfactant and propylene glycol. In some examples, 1 vol % copper-propylene glycol nanofluid as coolant can lead to, for example, 13.2% or great improvement in the rate of energy recovery from a constant-temperature hot bath when the heat transfer resistance in the hot fluid side is low. Such nanofluids can be used in energy management in solar thermal systems. In addition, disclosed is a unique reaction with graphene that presents a further efficiency of 20%, for example, with minimal or marginal effect to fluid viscosity by pairing these two particles in a unique sizing on the nano scale. This added storage duration and power density can reduce the size of thermal liquid cooling systems, thermal energy conversion systems, high performance automotive cooling systems, and many other environments with boundary layer fluid interaction. The nanofluid composition can deploy a silicone structure to the phase shifting composition to enable higher rate discharge of the ionization created by the fluid stream in motion to be applied with systems disclosed herein and other applications.

(108) As shown in **9** and **10**, the systems **900** and **1000** can include a fluid loop **602** that circulates the primary flow of fluid. The fluid loop **602** can include tubing, conduits, pipes, etc. to circulate the primary flow fluid. The system **900** can include a fluid reservoir **604**, a condenser such as a cooling coil **606**, a heater **608**, one or more Venturi devices **610** (e.g., two), one or more pumps

620, a turbine **622**, and a generator **626**. In some configurations, the fluid reservoir **604** unit can be the low-pressure point of the system **900**. The fluid reservoir **604** can be the bulk thermal mass interacting with the environment to maintain a baseline thermal energy that is relative and pre-heated through natural convection prior to charging a manifold as discussed herein via for example ambient or solar energy.

(109) The fluid reservoir **604**, the cooling coil **606**, the one or more Venturi devices **610** (e.g., two), the one or more pumps **620**, and/or turbine **622** can be disposed on the fluid loop **602**. A first pump **620a** can be disposed on the fluid loop **602** between an inlet of the reservoir tank **604** and an outlet of the second Venturi device **610b** on the fluid loop **602**. The first pump **620a** can be configured to drive the primary flow of the fluid loop **602**. A first Venturi device **610a** can be disposed on the fluid loop downstream of the first pump **620a** and upstream of the turbine **622** on the fluid loop.

(110) A second Venturi device **610b** can be disposed on the fluid loop **602** downstream of the turbine **622** and upstream of the first pump **620a** on the fluid loop. The reservoir tank **604** can be disposed on the fluid loop **602**, said reservoir tank **604** containing the fluid. The reservoir tank **604** can be downstream of the second Venturi device **610b** and upstream of the first Venturi device **610a**. A second pump **620b** and the heater **608** can be disposed on a secondary fluid path **602a** (also mentioned herein as a “first conduit”) disposed between the fluid reservoir **604** and an inlet of first Venturi device **610a** which can be similar or identical to the inlet **116** of the Venturi device **100** and/or the inlet **316** of the Venturi device **300**.

(111) The first conduit **602a** can be configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device **610a**. The secondary fluid path **602a** can be fluidically connected to the fluid loop **602**. A third pump **620c** can be disposed on a secondary fluid path **602b** (also discussed herein as a “second conduit”) disposed between the upper reservoir **604** and a second Venturi device **610b**. The secondary fluid path **602b** can be fluidically connected to the fluid loop **602**. The secondary flow of the second Venturi **610b** can flow from the fluid reservoir **604** to the secondary input of the second Venturi device **610b** which can be similar and/or identical to the inlet **116** of the Venturi device **100** or conduit **316** of the Venturi device **300**. The third pump **620c** can be configured to drive the secondary flow from the primary flow to the secondary input of the second Venturi device **610b**. The secondary input of the Venturi devices **610** can be adjustable to regulate an input of the secondary flow into the primary flow

(112) As shown in FIG. **10**, the system **1000** can function similarly to system **900** discussed herein without the fluid source **604** and the third pump **620c**. In some embodiments, the fluid source **604** and/or the third pump **620c** can be disconnected from the system **1000** after the primary flow and/or secondary flow reach a determined flow rate.

(113) The first and second pumps **620a**, **620b** can be powered by one or more motors **624** that can be configured to be powered by at least one of the generators **626** and an external power supply. The turbine **622** can be disposed between the first Venturi device **610a** and the condenser **606** on the fluid loop **602**. The fluid reservoir **604** can be disposed between the first Venturi device **610a** and the first pump **620a** on the fluid loop **602**. The cooling coil **606** can be disposed on the fluid loop **602** downstream of the turbine **622** and upstream of the first pump **620a** on the fluid loop **602**. The cooling coil **606** can be configured to condense the primary flow exiting the turbine **622**. The cooling coil **606** can comprise any refrigerant cycle, such as CO₂. In some embodiments, the system **900**, **1000** uses a condenser with or alternatively from the cooling coil **606**.

(114) The primary flow can start at the pump **620b** and then flow through the fluid reservoir **604**, the first Venturi device **610a**, the turbine **622**, the cooling coils **606**, and the second Venturi device **610b** on the fluid loop **602** before reaching the pump **620b** again to recirculate. As described herein, the secondary fluid paths **602a**, **602b**, which can be the same as conduit **116** described in reference to FIGS. **1A-1C** and/or the conduit **316** described in FIG. **3**, can route a portion of the primary flow (e.g., secondary flow) from the fluid loop **602** and back to the first Venturi device **610a** and second Venturi device **610b** to create vortices therein, as described above in reference to

FIGS. 1A-1C and 3, to generate a suction to facilitate the harvesting of thermal energy from the ambient environment outside the first Venturi device **610a** and second Venturi device **610b**. In some configurations, the secondary fluid paths **602a**, **602b** can direct the secondary flow, pulled from the primary flow, from the fluid loop **602** at the one or more pumps **620** to the first Venturi device **610a** and second Venturi device **610b**.

(115) As described herein, the Venturi devices **610** can include a converging portion and a diverging portion, similar to the converging portion **106** and diverging portion **110** of the Venturi device **100** and/or to the converging portion **306** and diverging portion **310** of the Venturi device **300**, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow. A secondary input corresponding to the secondary input **120** of the Venturi device of FIGS. 1A-1C and/or the secondary input **320** of the Venturi device of FIG. 3 can be disposed between the converging portion and the outlet. The secondary input can be configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body. The flowing of the primary flow through the body can decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet.

(116) As described herein, the first Venturi device **610a** can be configured to heat the primary flow passing through the first Venturi device **610a** such that the primary flow phase shifts from the liquid state to the gas state. The phase shifting process can take place at first Venturi **610a** as well as in the secondary flow of the Venturi **610a**. The first Venturi **610a** can heat the fluid by dropping the temperature of the fluid as discussed herein, which cools the Venturi **610a** and then transfers heat from the ambient environment to heat the fluid. The transfer of heat from the ambient environment increases the fluid temperature for the primary flow to phase shift from a liquid state to a gas state in the first Venturi device **610a**.

(117) The heater **608** discussed herein and connected to secondary fluid path **502a** of the first Venturi device **610a** can include one or more solar tubes and/or a heater cartridge configured to heat the fluid flowing through the secondary fluid path **602a**. The one or more solar tubes can be configured to heat the secondary flow of the first Venturi device **610a** via solar radiation. The first conduit **602a** can include a solar tube manifold connected to the one or more solar tubes and transfer heat from the one or more solar tubes to the secondary flow in the first conduit **602a**. In some embodiments, the heater cartridge is powered by a solar panel assembly configured to generate electricity to heat the heater cartridge. The heater cartridge can be powered by an external power source and/or generator **626**. The heater cartridge can be used with or alternatively from the one or more solar tubes. The heater **608** can heat the secondary flow in the secondary fluid path **602a** for the secondary flow to phase shift from a liquid state to a gas before entering the secondary input of the first Venturi device **610a**.

(118) The generator **626** can generate electrical energy from the mechanical energy of the turbine **622** as the primary flow drives the turbine **622**. The turbine **622** can be of a mixed flow style turbine having modified volute casing to manage the density and variable pressure environment and provide a sufficient bypass actuated waste gate system.

(119) It can be assumed that neither frictional losses, dissipation losses nor the conversion losses between the individual forms of energy occur. The primary flow passes through the points (11), (21), (13), (12), (1), (2), (3), (4), (5), (19), (20), (6), (7), (8), (9), (10), (11), (16), (17), (18), (15), (22), (23), (24), (25), (26), and (14) of a fluid loop **602**, which can be connected by way of tubing, pipes, conduits, and the like, and thus circulates in a circuit (e.g., fluid loop) which links the one or

more pumps **620**, the first Venturi device **610a**, turbine **622**, the second Venturi device **610b**, and the generator **626**.

(120) This circulating flow can be referred to as the primary flow. The primary flow can cause two effects. First, the turbine **622** can be driven, which drives the generator **626**, which in turn results in that electrical energy can be taken off in the form of electricity. Second, at points (22) and (16), a secondary flow is directed via points (14) and (15) into the first Venturi device **610a** and second Venturi device **610b** where it rejoins the primary flow, as detailed herein with reference to the secondary flow being directed into the primary flow. As a result, the vortices described above are formed in the Venturi devices **610**, which generate a suction on the back of the Venturi device **610** (points (1) and (7)).

(121) As described above, in the Venturi device **610**, a vortex is formed which generates a suction on one side (positions (1) and (7)), and an increased pressure on the other side (positions (2) and (8)). On the suction side, the intake of the primary flow, in combination with the Venturi effect, causes the primary flow to undergo cooling so that thermal energy is absorbed from the environment in the form of heat. This absorbed energy on the pressure side causes the pressure to continue to increase and thus also be returned to the Venturi device **610** via the secondary air flow. This in turn increases the swirl of the vortex, which in turn increases the suction effect and the associated cooling or the transport of heat into the circulating fluid. It is therefore a self-amplifying loop driven by the heat energy present in the environment.

(122) On the pressure side, this absorbed energy means that the pressure in position (16) and (22) continues to increase and is thus also returned to the Venturi devices **610** via the secondary flow. This in turn leads to an increase in the vortex in the Venturi devices **610**, which in turn increases the suction effect and the associated cooling or transport of heat into the circulating fluid. It is therefore a self-reinforcing cycle driven by the heat energy present in the environment. At the same time, the fluid, which can be the nanofluid, that is circulated through the pump **620**, first Venturi device **610a**, turbine **622**, and second Venturi device **610b** is energetically charged (increase in internal energy). This energy can be converted into electrical energy via the turbine **622** and generator **626** in such a way that energy losses, for example due to friction, can be compensated for by always being able to drive the one or more pumps **620** at full power. The circulation of the fluid in the closed circuit of the one or more pumps **620**, first Venturi device **610a**, turbine **622**, and second Venturi device **610b** as well as the secondary air flows can be maintained. The system **900** can be referred to as a “VIP” (“Vortex Induction Pump”) and/or a “VIC” (“Vortex Induction Chamber”).

(123) As described herein, the characteristics of the system **900** can include: thermal energy (e.g., from the thermal storage unit) is transferred to a flowing fluid medium by means of passing the fluid through the thermal storage unit, internal energy can be withdrawn from the flowing fluid medium (which can be referred to as “discharging the fluid medium”), and part of the energy withdrawn from the flowable medium can compensate for energy losses caused by friction, dissipation (this also can include the effects of electrical resistance in the event that electrical currents flow) and/or conversion losses, the VIP can provide energy such that the cycle of charging and discharging of the flowing flowable medium is maintained (operating energy). the first venturi device, and the turbine are a more efficient pump and boiler system

(124) If the energy produced by the generator **626** has reached a level sufficient to fully drive the motor, the system **900**, **1000** can generate power without an external electrical power source, but instead, the energy of the primary flow can be sufficient to power the system **900** via absorption of thermal energy from the ambient environment. The system **900**, **1000** can be externally powered to, for example, drive the first pump **620a** until the system **900**, **1000** is transferring sufficient thermal energy from the environment for the system **900**, **1000** to operate and generate electricity as discussed herein, including powering the one or more pumps of the system **900**, **1000**.

(125) In some configurations, excess energy from the system **900** can be stored in batteries in the form of electrical energy or fed into an electrical power grid.

(126) The systems **900** and **1000** may also facilitate energy to be taken from an ambient environment at low temperature levels. The Carnot efficiency of a VIP at $T_{\text{warm}}=293\text{ K}$ and $T_{\text{cold}}=283\text{ K}$ (difference=10 K) and an ordinary heat engine at $T_{\text{warm}}=1273\text{ K}$ and $T_{\text{cold}}=1229\text{ K}$ (difference=44 K) according to formula 1 would be the same. With a lower temperature difference, a VIP can thus achieve the same efficiencies, and the demands on the materials can be lower due to the lower temperature.

(127) The principle of the VIP shown in FIG. **9** is not restricted in the number of the Venturi devices **510** used. In principle, the use of one Venturi devices **510** is sufficient, but 2,3,4,5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100 or more than 100 Venturi devices **510** can be combined in one VIP. One or more Venturi devices **510** can thus be combined in a VIP.

(128) The principle of the VIP shown in FIGS. **9-10** is not limited in the number of pumps used. Characteristic of a pump is the generation of a flow in a free-flowing medium. The same applies to the number of engines.

(129) The principle of the VIP shown in FIGS. **9-10** is not limited in the number of turbines used. Characteristic of a turbine is the withdrawal of internal energy from a free-flowing medium. These turbines can be freely connected to any number of electrical generators.

(130) The flow of fluid (e.g., nanofluid) in a VIP can be guided in any way (e.g., in the form of a cascade). However, it is also possible for fluid to be fed into the VIP at one point and out of the VIP at another point and discharged into the closed environment. In this case, the proportion of the operating energy required for the operation of the VIP increases in relation to the energy that the flowable medium has when discharging was removed. The number of turbines and generators is also not limited. As described herein, the discharging of the flowable medium (e.g., nanofluid) in one or more Venturi devices **610** or vortex fusion chargers can be accomplished with and the conversion of this energy into another form of energy, for example electrical energy.

(131) Thermal energy can thus be converted into mechanical energy and ultimately into electrical energy by means of the suction-acting mechanisms in the Venturi device **510**. The advantage of the presented VIP is that low-value thermal energy (ambient temperature) can be converted into higher-value energy (electricity). The VIP accomplish the foregoing based on the suction effect.

(132) The VIP and Venturi device **610** can be used with any flowable media, which can include at least those recited herein.

(133) Forced Induction Charging and Heating

(134) FIG. **11-14** illustrates a forced induction charging system **1100** that can utilize aerodynamic forced induction to capture the incoming fluid flow of a vehicle **1130** in motion to convert wind resistance to electrical energy. Utilizing high resonance and dynamic phenomenon, such as the Coandă effect, the Venturi effect, and pressure differential vortices, the system **1100** can utilize aerodynamic drag with high efficiency to create 1, 2, 3, 4, or more kw per second at freeway speed.

(135) The system **1100** can include an expandable and/or shapeshifting intake funnel, channel, siphon, cowl **1101**, an inlet, entrance, entry **1102** of the intake funnel **1101**, an outlet **1103** of the intake funnel **1101**, and a body, frame, chassis **1104** between the inlet **1102** and outlet **1103** of the intake funnel **1101**. The inlet **1102** of the intake funnel **1101** can have a cross-sectional flow area larger than a cross-sectional flow area of the outlet **1103**. The body **1104** can be made of a shape changing portion **1109** that can expand or contract to change a cross-sectional flow area of the body **1104**. The inlet **1102** can face forward toward the front of the vehicle **1130** to direct the ambient airflow into the inlet **1102** with the moving vehicle in motion in a forward direction. The intake funnel **1101** can direct an ambient airflow caused by the moving vehicle **1130** to travel from the inlet **1102** through the body **1104** and out through the outlet **1103**.

(136) The intake funnel **1101** can be positioned at the front of the vehicle **1130** at the front air dam

assembly to optimize the input of the fluid stream to a high, desired, or predetermined velocity prior to interaction with the Venturi device **1110** and to take advantage of wind shear. The intake funnel **1101** can be positioned towards the bottom and/or the top of the front of the vehicle **1130**. The intake funnel **1101** can be exposed to the ambient air and/or positioned behind a cover such as the grille and/or front air dam of the vehicle **1130**. As the vehicle **1130** travels in a forward direction, an airstream over and/or under the vehicle can be introduced into the intake funnel **1101**. As the vehicle **1130** accelerates, the flow rate of the airstream intake funnel can also accelerate.

(137) As illustrated in FIG. **15**, the system **1100** can also include a fan **1118** that faces the inlet **1102** and direct air into the inlet **1102**. The fan **1118** can also, in some configuration, be connected to a wheel **1119** of the vehicle **1130**. The fan **1118** can be driven by rotation of the wheel **1119**. As the wheel **1119** revolves, the fan can be turned to generate a primary flow.

(138) Additionally or alternatively, the fan **1118** can be connected to a motor **1120** of the vehicle **1130** such that the motor **1120** drives the fan **1118**. A reduction gear drive connected to the motor **1120** can then be connected to the fan **1118**. The system **1100** can then maintain and/or improve the efficiency of the system using the Venturi devices **1110** and primary and secondary flows in conjunction with the motor **1120** to lower the overall energy intake of the system **1100**. By using a fan **1118**, the intake funnel **1101** can face in any direction to entrain air into the system **1100**.

(139) The forced induction system **1100** can also include one or more Venturi devices **1110**, which can be similar or identical to Venturi device **100** shown in FIGS. **1A-1C** and/or Venturi device **400** shown in FIGS. **4A-4D**, connected to the intake funnel **1101**, a turbine **1121** in a volute casing connected to the Venturi devices **1110**, and a generator **1124** driven by the turbine **1121** to generate electricity.

(140) The Venturi device **1110** can be either directly connected to the intake funnel **1101** or by tubing, conduits, pipes, etc. such that the Venturi device **1110** receives a primary flow made up of the ambient air exiting the outlet **1103** of the intake funnel **1101** when can then be ejected by the Venturi device **1110**. As described herein, the Venturi device **1110** can further include a body similar to the body **411** of the Venturi device **400**, a converging portion and a diverging portion similar to the converging portion **406** and the diverging portion **410** of Venturi device **400** such that the movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device. Lastly, the Venturi device **1110** can include a secondary input similar or identical to the secondary input **420** of the Venturi device **400** which can be positioned the converging portion and the outlet to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device.

(141) The turbine **1121** can include an inlet **1122** and an outlet **1123** with the inlet **1122** connected to the outlet of the Venturi device **1110** to receive the primary flow ejected from said outlet. The primary flow can drive the turbine **1121**. To charge a battery **1126**, the system **1100** can maximize dynamic energy translation from potential input by coupling the turbine **1121** and generator **1124** with a drive system **1106** to translate kinetic energy into electricity. The drive system **1106** be a cycloidal (e.g., circular) gear box containing planetary and sun gears acting as a gear reduction drive. A shaft from the turbine **1121** can be connected to the cycloidal gear box with a flange connecting the cycloidal gear box and generator **1124**. The gear box and manage the efficiency of the turbine **1121** and the generator **1124**.

(142) In some configurations, the generator **1124** comprises a matched self-excited induction generator which does not require an input for activation. A self-excited induction generator utilizes some of the power output from a rotor that rotates in a magnetic field within the generator to power field coils. The metallic material (e.g., iron) of the rotor retains a degree of residual magnetism when the generator is shut off. Since the generator is started with no load connected, the residual

magnetism introduces a weak current into the rotor coils, which in turn creates an initial field current and increases the strength of the field. The induced current in the rotor continues in a feedback process until the generator builds up full voltage.

(143) Additionally or alternatively, to charge the battery **1126**, a permanent magnet stator charging system can be used to provide high efficiency charging and a low total footprint. A stator is a stationary component of a rotary system found inside a generator. Energy flows through the stator to and/or from the rotating component causing the stator to generate a magnetic field that drives a rotating armature. The stator converts the rotating magnetic field to electrical current. A permanent magnet stator utilizes an object made from a magnetized material and that creates its own persistent magnetic field.

(144) The Venturi device **1110** and turbine **1121** can be fitted with a bypass conduit, pipe, channel, duct **1115** positioned at the high-pressure point of the turbine **1121** to recirculate the secondary flow and recycle of wasted thermal energy by moving the thermal energy through the bypass conduit **1115** to the low-pressure point of the Venturi device **1110**. The bypass conduit **1115** can be connected to a secondary input **1117** to direct the secondary flow to the Venturi device **1110**. The secondary input **1117** can be adjustable to regulate an input of the secondary flow into the primary flow to control a volume of flow of the secondary flow into the secondary input.

(145) In connecting the Venturi device **1110** and turbine **1121** with the bypass conduit **1115**, the Venturi device **1110** can generate a higher input velocity and mass air density which greatly improves the boundary layer fluid dynamics and fluid potential energy at the turbine **1121** as the fluid passes from the Venturi device **1110** to the turbine **1121**. In some configurations, the input velocity and mass air density can increase by a factor of 2 to 8, by a factor of 3 to 7, or by a factor of 4 to 6.

(146) The system **1100** can also include a first valve **1108**, a second valve **1111**, and/or a third valve **1125** to control the path of the primary flow through the system. The valves **1108**, **1111**, **1125** can be of any type of valve such as a butterfly valve and/or stopcock valve to manage the flow rate of the primary and secondary flows. In some configuration, valves **1108**, **1111**, **1125** can be actuator driven to open and/or close. In some configuration, the valves **1108**, **1111**, **1125** can be actuated by a bimetallic spring that causes said valves **1108**, **1111**, **1125** to open and/or close.

(147) In some configuration, the first valve **1108** can be positioned at the turbine outlet **1123** and be connected to the passenger cabin duct **1105** to control how much of the primary flow is passed through the passenger cabin duct **1105** and into a passenger cabin, compartment **1107**. The valve **1108** can control the temperature of the primary flow (e.g., warm or cold) into the passenger cabin **1107** by opening and closing based on a response provided by a passenger. The valve **1108** can close completely when a response is detected that no flow is to enter the passenger cabin **1107**. The passenger cabin duct **1105** can also be split into two or more conduits that feed into the passenger cabin **1107** in which the valve **1108** or more than one valve **1108** can further balance the flow into either one or more conduits.

(148) In some configuration, the second valve **1111** can be positioned in between the turbine outlet **1123** and the bypass conduit **1115** to control how much of the primary flow is recycled back to the Venturi device **1110** as the secondary flow. Before the bypass conduit **1115** can be utilized, the turbine **1121** should to reach an operating speed between 40,000 rpm to 80,000 rpm, between 45,000 rpm to 75,000 rpm, between 50,000 rpm to 70,000 rpm, or between 55,000 rpm to 65,0000 in order to prevent stalling of the turbine **1121**. Valves **1108**, **1111**, **1125** can remain open during the startup of the turbine **1121** to prevent an accumulation of back pressure on the turbine **1121**. As the turbine **1121** passes through its start up speed and reaches its operational speed, valves **1108**, **1111**, **1125** can be adjusted to regulate the primary flow. Therefore, once the turbine **1121** reaches its operational speed, the primary flow can be adjusted to flow through the bypass conduit **1115** to provide the secondary flow to the Venturi device **1110** by adjusting valve **1111** to the desired flow rate.

(149) Additionally or alternative, valve **1125** can be positioned between the turbine outlet **1123** and a bypass duct, pipe, channel, conduit **1116** that directs the primary flow (e.g., excess primary flow that is not ducted into the passenger cabin **1107** and/or Venturi device **1110**) to the inside and/or the outside of the vehicle **1130** such that the valve **1125** controls the rate at which the primary flow is ducted to the inside and/or the outside of the vehicle **1130**. The bypass duct **1116** can direct the primary flow to an underside of the vehicle **1130** to bypass and/or minimize flow to the passenger cabin **1107** and/or Venturi device **1110**. The bypass duct **1116** can also direct the flow to cool the motor **1120** as described in the Section titled “Motor Cooling System” below. When more flow is needed into the passenger cabin **1107** and/or Venturi device **1110**, the valve **1125** can be adjusted to limit or close off the flow to the bypass duct **1116** such that a greater volume of the primary flow flows into the passenger cabin **1107** and/or Venturi device **1110**.

(150) Valves **1108**, **1111**, **1125** can be controlled simultaneously or independently to ensure that there is a minimal backpressure on the turbine **1121**. Additionally or alternative, the valves **1108**, **1111**, **1125** can be controlled simultaneously or independently to supply an input inlet pressure to the Venturi device **1110** to overcome stalling of the turbine **1121** under heavy load situations, and thus recycling as much dynamic energy as possible back into the system **1100**.

(151) In some configurations, valves **1108**, **1111**, **1125** can be the same valve which operates and be positioned to perform all the functions of valves **1108**, **1111**, **1125**. A common conduit from the turbine outlet **1123** can be directed toward a single valve operating as valves **1108**, **1111**, **1125**, which then adjusts the primary flow into multiple conduits corresponding to the conduits connected to valves **1108**, **1111**, **1125**. The primary flow can then be distributed evenly into the multiple conduits and/or controlled to distribute desired or predetermined volume of flow by the openness and/or closeness of the single valve. The single valve can be the same type or a different type than valves **1108**, **1111**, **1125**.

(152) The use of non-Euclidean geometry for the shaping of the inlet **1102** further improves resonance and flow as the fluid enters the intake funnel **1101**. The inlet **1102** acts as a gateway point into the system for environmental interaction, which can further increase the dynamic output of system **1100**. For example, and as illustrated in FIG. 17, the inlet **1102** of the intake funnel **1101** can be of a non-Euclidean geometry (having a hyperbolic or elliptical shape) such that said inlet **1102** can be a velocity stack, trumpet, or air horn having a trumpet-shaped design with differing lengths with elliptical (boundary line curving towards an opposing boundary line) or hyperbolic lines (boundary line curving away from an opposing boundary line). Using non-Euclidean geometry allows for a smooth and even entry of air at high velocities into the intake funnel **1101** with the flow stream adhering to an inner surface of the intake funnel **1101** as laminar flow. Non-Euclidean geometry can also modify the dynamic tuning range of the intake funnel **1101** by functioning as a resonating pipe which can adjust the frequency of pressure pulses based on the length within the intake funnel **1101**. By having a hyperbolic shape forming inlet **1102**, the intake funnel **1101** can provide an efficient fluid flow to a turbine, such as turbine **1121**. Additionally or alternatively, no intersecting points in the cross sections of the cowl surface wall of the intake cowl **1101** can provide an efficient fluid flow to turbine.

(153) The outlet **1123** of the turbine **1121** can also be connected to a passenger cabin duct **1105** of the vehicle **1130**. The passenger cabin duct **1105** can direct the flow of primary fluid into a passenger cabin **1107** (also referenced herein as “a cabin interior”) of the vehicle **1130**. One or more passengers can then provide inputs into the system **1100** from inside and/or outside the passenger cabin **1107**.

(154) In some configurations, a heat source **1112** (e.g., a glow plug) can be positioned at or near the passenger cabin duct **1105** to minimize conversion losses of the system **1100**. The heat source **1112** can heat the primary flow directed to the passenger cabin **1107**. Residual thermal energy and the exhaust flow from the turbine **1121** can be ducted into the vehicle passenger cabin **1107** to enhance the cabin heating system, offsetting energy consumption of the vehicle heating and blower system.

This will also offset some of the aerodynamic drag losses that may be present the system. In some configurations, the heat source **1112** can be a glow plug. The heat source **1112** can be utilized to increase the cabin heating by using ultra-high efficiency flash heating and the afterglow effect. The flash heating can be in effect for one to twenty seconds, for two to fifteen seconds, for three to ten seconds, or for four to six seconds. The afterglow warming effecting can last for one to twenty minutes, for two to fifteen minutes, for four to twelve minutes, or for five to seven minutes. The flash heating of the heat source **1112** with or without the afterglow warming effect can maintain and/or increase the thermal energy from the flow entering the cabin interior **1107**, reducing the need for other high-energy consumption devices and transferring the saved energy to other systems of the vehicle **1130**.

(155) In some configurations, the heat source **1112** can be a resistance heater the primary flow flowing through the passenger cabin duct **1105**. A resistance heater converts electrical energy into heat supplied to the space by passing an electrical current through a conductive material (e.g., the resistor) and releases heat. The greater the resistance in the resistance heater, the more heat is created. The resistance heater can include one or more resistance wires coiled tightly or laid out in strips. The greater the length of the resistance wire, the more heat the wire will generate. The resistance heater can be sized to adequately warm the primary flow before flowing into the passenger cabin **1107**.

(156) The heat source **1112** can be powered by the generator **1124** once the generator **1124** is charged. The system **1100** can disable a low efficiency stock heating and blower system which can save kilowatts of electricity. The saved electricity can then be directed directly to the drive system **1106** improving the range by at least 30%, by at least 40%, or by at least 50%, even in cold weather environments. The system **1100** can be fitted to electric vehicles to assist in extending the operating range. In some configurations, the heat source **1112** can be powered by the motor **1120** of the vehicle **1130**.

(157) As shown in FIG. **11** and mentioned above, the intake funnel **1101** of the forced induction charging system **1100** can have a shape changing portion **1109** that expands or compresses to change a cross-sectional flow area of the body **1104** to collect the ambient air. The intake funnel **1101** can be constructed from shape memory materials **1113** (e.g., Nitinol or Nafion) and/or a pliable material, flexible material, malleable material **1127** causing the intake funnel **1101** to change shape and/or size of the opening to one or more predetermined shapes.

(158) The shape change portion **1109** can include a pliable material **1127** that can change the cross-sectional flow area of the body **1104** of the intake funnel **1101**. The pliable material can also expand and/or contract based on a force induced on the pliable material by the ambient airflow through the body **1104**. The pliable material **1127** can change their shape based on the temperature of the ambient air flow passing through the body **1104**, pressures of the ambient air flow passing through the body **1104**, rate of flow of the ambient air flow passing through the body **1104**, electrical current applied to the shape changing portion **1109**, and/or heat applied to the shape changing portion **1109**. For example, when the vehicle **1130** is traveling between 70 miles per hour (mph) to 80 mph, a volume of air flowing between 9165 cubic feet per minute (CFM) to 9270 CFM, between 9190 CFM to 9245 CFM, between 9200 CFM to 9230 CFM, or between 9210 CFM to 9220 CFM can cause the pliable material to expand as the ambient air flows through the body **1104**.

(159) In some configurations, the pliable material **1127** can be of a carbon-based polymer which reacts to certain pressures applied to the material and without the use of heat and/or an electrical charge. As discussed above, the pliable material **1127** can be pressure reactive and transform into different shapes when a pressure stimulation is applied. As the pressure along the pliable material **1127** increases as the vehicle **1130** is moving and/or accelerating, the shape changing portion **1109** can expand and/or contract based on the reactive properties of the pliable material **1127**. For example, as the pliable material **1127** experiences increases in stress induced by the pressure, the

pliable material **1127** can expand and/or contract at a faster or slower rate until the pliable material **1127** reaches its final transformed state. The rate of decrease of pressure can cause an opposite effect in the pliable material **1127** until the pliable material reaches the non-stimulated configuration.

(160) In some configurations, the pliable material **1127** can react to an electrical current applied to shape changing portion **1109**. Applying an electrical current can stimulate the pliable material **1127** to expand and/or contract. As the electrical current ran through the pliable material is increased, the pliable material **1127** can expand. As the electrical current is decreased, the pliable material **1127** can return to its resting state.

(161) In some configurations, the pliable material **1127** can react to a change in temperature applied to the shape changing portion **1109**. Applying a temperature change to shape changing portion **1109** can stimulate the pliable material **1127** to expand and/or contract. As the rate of the temperature change is increased, the pliable material **1127** can expand or change shape at a faster rate. As the temperature decreases whether by decreasing the heat stimulus and/or by allowing the ambient air to cool the shape changing portion **1109**, the pliable material **1127** can return to its non-stimulated state. In some configurations, the system **1100** can include a heating element **1114** that applies heat to the shape changing portion **1109**. The heating element **1114** can be disposed along the surface of the shape changing portion **1109** or within a wall of the shape changing portion **1109**. The heating element can be located on an exterior surface of the body **1104**. In some configurations, the heating element **1114** can be an elastic resistance heater wire positioned along the shape changing portion **1109**.

(162) Additionally or alternatively, as the pressure along the pliable material **1127** increases as the vehicle **1130** is moving and/or accelerating, the shape changing portion **1109** can expand in conjunction with an increase in the temperature of the body **1104**, which can be caused by the ambient air flow. In contrast, as the pressure lowers and the temperature lowers, the shape changing portion **1109** can begin to contract to its original shape and/or size. By being susceptible to two inputs, the pliable material **1127** can deform at a faster rate and/or more likely to deform once a stimulant is applied.

(163) In some configurations, the pliable material **1127** can react to an electrical current applied to shape changing portion **1109**. Applying an electrical current can stimulate the pliable material **1127** to expand and/or contract. As the electrical current ran through the pliable material is increased, the pliable material **1127** can expand. As the electrical current is decreased, the pliable material **1127** can return to its resting state.

(164) In some configurations, the pliable material **1127** can be of a piezoelectric material. The piezoelectric material can be cut into sections or applied as one unitary and/or monolithic piece. As a pressure is applied to the piezoelectric material, an electric charge can be generated in response to the mechanical stress generated by the pressure. The electric charge can cause the pliable material **1127** to further expand and/or contract in response to the pressure input. As the pressure is reduced and/or cut-off, the piezoelectric material can stop generating an electrical charge and the pliable material **1127** can reset to the non-stimulated form.

(165) Shape memory materials can memorize one or more shapes in addition to their original shape. Shape memory materials have the advantage of high elastic deformation, low cost, and low density. The shape memory materials, for example, can be heated between 10° C. to 150° C., between 20° C. to 140° C., or between 30° C. to 130° C. to activate the memory learning characteristics once the shape memory materials have been processed and taught the contraction and expansion operations during the training protocol. The shape memory material **1113** can return to its original shape under certain conditions such as under thermal, electrical, or other stimulations. For example, Nitinol exhibited the ability to memorize multiple shapes when under temperature stimulation.

(166) Shape memory materials can include broad glass transition temperatures such as in a range

from 200° C. to 700° C., from 300° C. to 600° C., or from 400° C. to 500° C. for programming the shape memory material with one or more predetermined shapes. One or more shapes can be memorized within the temperature ranges by heating the shape memory materials to temperatures within the broad glass transition temperatures and then quenching the materials. The shape memory material can then recover to its original shape after being heated or cooled to the corresponding temperature. The broad glass transition spectrum can be divided into a series of individual glass switching for each programmed shape. Different shapes can be heated or cooled to programming temperatures. Additionally or alternatively, multiple shapes can be programmed at each temperature range.

(167) In some configurations, the shape memory material **1113** can be a metallic material (e.g., Nickel titanium also known as Nitinol). Metallic materials can be metal alloys have the shape memory effect along with superelasticity. Material such as Nitinol can undergo deformation at one temperature, stay in the deformed shape when the external force is removed, and then recover to its non-stimulated shape. The superelasticity properties allows for the metal material to undergo large deformations and return to its undeformed shape once the stimulant is removed. Nitinol, for example, can deform 10 to 30 times as much as other comparable metals and return to its original shape. The cooling/heating cycle shows thermal hysteresis which depends on the properties of the metallic material.

(168) The shape memory materials **1113** can change their shape based on an increase and/or decrease of temperature of the ambient air flow passing through the body **1104**, an increase and/or decrease of temperature applied to the body **1104**, pressures of the ambient air flow passing through the body **1104**, rate of flow of the ambient air flow passing through the body **1104**, electrical current applied to the shape changing portion **1109**, and/or heat applied to the shape changing portion **1109**.

(169) As mentioned herein, the shape memory material **1113** can react to a change in temperature applied to the shape changing portion **1109**. Applying a temperature change to shape changing portion **1109** can stimulate the shape memory material **1113** to expand and/or contract as mentioned above. The shape memory material **1113** can change be transformed when the temperature of the shape changing portion **1109** reaches a temperature range, in some configurations, of 30° C. to 130° C. For example, a first deformation or predetermined shape can be programmed to occur between 30° C. to 50° C. (e.g., a second cross-sectional flow area larger or greater than a first cross-section flow area when temperature is less than 30° C.); a second more pronounced and/or larger deformation or predetermined shape can occur between 50° C. to 80° C. (e.g., a third cross-sectional flow area larger or greater than a second cross-section flow area), a third more pronounced and/or larger deformation or predetermined shape can occur between 80° C. to 130° C. (e.g., a fourth cross-sectional flow area larger or greater than a third cross-section flow area), and so on until the upper bounds of the temperature deformation range is reached.

(170) Depending on the properties of the shape memory material, the temperature ranges can be shifted up and/or down. As the rate of the temperature change is increased, the shape memory material **1113** can expand or change shape at a faster rate. As the temperature decreases whether by decreasing the heat stimulus and/or by allowing the ambient air to cool the shape changing portion **1109**, the shape memory material **1113** can return to its resting state. In some configurations, the system **1100** can include a heating element **1114** that applies heat to the shape changing portion **1109**. The heating element **1114** can be disposed along the surface of the shape changing portion **1109** or within a wall of the shape changing portion **1109**. The heating element can be located on an exterior surface of the body **1104**. In some configurations, the heating element **1114** can be an elastic resistance heater wire positioned along the shape changing portion **1109**.

(171) Additionally or alternatively, in some configurations, the shape memory material **1113** can react to an electrical current applied to shape changing portion **1109**. Applying an electrical current can stimulate the shape memory material **1113** to expand and/or contract. As the electrical current

ran through the pliable material is increased, the shape memory material **1113** can expand. As the electrical current is decreased, the shape memory material **1113** can return to its resting state.

(172) In some configurations, the materials **1113**, **1127** of the intake funnel **1101** can be fabricated into sections **1140**, such as strips, bars, rods, and like, based on the width and length of the intake funnel **1101** to form the body **1104** of the intake funnel **1101**. The strips **1140** can have a length between 0.5 inches to 36 inches, between 1 inch to 24 inches, between 3 inches and 18 inches, between 5 inches to 11 inches, between 6 inches to 10 inches, or between 7 inches to 9 inches. The strips **1140** can have a width between 0.5 inches to 12 inches, between 1 inch to 6 inches, or between 1.5 inches to 2.5 inches. The sections **1140** can expand and/or contract to change the cross-sectional flow area of the body **1104**. Before forming the body **1104**, the sections **1140** can be processed into the needed shapes and contours. As illustrated in FIG. **16**, after the heat programming, the processed sections **1140** made of materials **1113**, **1127** can be deformed as compared to the original sections. The sections **1140** can then be arranged based on the desired configuration of the intake funnel **1101** with an interlocking seam **1142** connecting the sections **1140** together to form the body **1104**.

(173) In some configurations, the sections **1140** can form a continuous body with an inner surface along the body **1104** in which the ambient air can flow along. The continuous body can have no gaps in between the sections such that the sections can maintain the volume of fluid flowing into the intake funnel **1101**.

(174) In some configurations, the materials **1113**, **1127** can be a unitary and/or monolithic piece that can take the place of the one or more sections **1140**. Rather than be cut into sections **1140**, the materials **1113**, **1127** can be processed into sheets and/or a single piece that is wrapped around the shape changing portion **1109**. An interlocking seam **1142** can then connect the any edges of the monolithic piece and/or sheets to one another. The materials **1113**, **1127** can surround the shape changing portion **1109** such that materials **1113**, **1127** maintain the volume of the primary fluid flowing into the intake funnel **1101**. The materials **1113**, **1127** can be processed to expand and/or change size when a stimulant is applied.

(175) FIGS. **12-14** illustrate different configurations of the longitudinal extent, length, span **1154** of each of the sections **1140** oriented along a central axis **1153**. Each of the different configurations can depend on the type of application and/or the size of the intake funnel **1101**.

(176) In some configurations, as shown in FIG. **12**, a longitudinal extent **1154** of each of the sections **1140** can be oriented along a central axis **1153**. The sections **1140** can then be connected to one another using the interlocking seam **1142** along the longitudinal extent **1154**. The sections **1140** can then create a cylindrical shell with a continuous inner wall to direct the primary flow. The sections **1140** can then expand and/or contract together to change the shape and/or size of the shape shifting portion **1109**. The interlocking seam **1142** can be made by connecting the sections **1140** using welding techniques and/or interlocking fasteners along the longitudinal extents **1154**.

(177) FIG. **13** illustrates a configuration of the intake funnel **1101** in which the longitudinal extent **1154** of each of the strips **1140** can be curved to form a curved strip **1140** which is then oriented perpendicular to a central axis **1153**. One or more curved strips **1140** can be combined from end to end to form a section of a cylindrical shell with the central axis **1153** located at the center. The sections of the cylindrical shell can then be connected to one another using the interlocking seam **1142** to form the body **1104**. As mentioned above, the interlocking seam **1142** can be made using welding techniques and/or interlocking fasteners.

(178) In some configurations, the body **1104** of FIGS. **12** and **13** can then include an elastic polymer **1152** (e.g., polymer and/or rubber sheeting with high elasticity) encasing the shape changing portion **1109** that can also expand and/or contract with the shape changing material **1113**. The elastic polymer **1152** can direct the fluid entering the intake funnel **1101** at the inlet **1102** to the outlet **1103**.

(179) The body **1104** made up of the continuously connected strips **1140** can then be connected to

the Venturi device **1110** such as by welding the body **1104** to the Venturi device **1110**. An expandable ring **1143** or a fixed ring **1155** can be positioned between the outlet **1103** of the intake funnel and the inlet of the Venturi device **1110** to provide supports and/or a connection point. The elastic polymer **1152** can then extend over the body **1104**, the rings **1143**, **1155**, and/or the inlet of the Venturi device **1110** to maintain the primary flow within the system **1100**, in particular for configurations where the strips **1140** are separated to form a skeleton, frame, framework **1151** as discussed herein and do not form a continuous wall structure. The intake funnel **1101** and Venturi device **1110** can thus create a continuous path for the incoming fluid to flow through.

(180) As mentioned above, in some configurations, the strips **1140** illustrated in FIGS. **12** and **13** can be replaced by a unitary and/or a monolithic structure made of materials **1113**, **1127**. The unitary structure can surround the shape changing portion **1109** such that there are no gaps and there is one continuous inner surface.

(181) In some configuration, as shown in FIG. **14**, the sections **1140** of the body **1104** can be spaced apart from one another with gaps or openings in between to form a skeleton or frame **1151**. The skeleton **1151** can provide more flexibility for smaller applications (e.g., electric motorbike) of the intake funnel **1101** as the skeleton **1151** does not use interlocking seams to create the body **1104**. The longitudinal extent **1154** of each of the sections **1140** can be oriented along a central axis **1153**. The body **1104** can then include an elastic polymer **1152** (e.g., polymer and/or rubber sheeting with high elasticity) encasing the shape changing portion **1109** that can also expand and/or contract with the shape changing material **1113**. The elastic polymer **1152** can contain the ambient air flow within the body **1104** of the intake funnel **1101**. An adhesive (e.g., quick drying cement) can be used to attach the elastic polymer **1152** to the strips **1140**. The skeleton **1151** with elastic polymer **1152** can then be clamped to the Venturi device **1110** or to a conduit leading to the Venturi device **1110** to allow for interchangeability of the body **1104** having the skeleton **1151** and elastic polymer **1152**.

(182) As shown in FIG. **16**, the expandable rings **1143** can be of various sizes to correspond to the inlet of the Venturi device **1110**. The rings **1143** can be positioned and connected to either the first end **1104a** and/or the second end **1104b** of the intake funnel **1101** to maintain and/or change the shape and size of the inlet **1102** and/or outlet **1103** of the ends **1104a**, **1104b**. The rings **1143** can also be connected along to the shape changing portion **1109** to assist in changing the cross-sectional flow area that corresponds to the expansion and/or contraction of the shape changing portion **1109**. In some configurations, one of or both of the sections **1140** or rings **1143** can contract and expand to change the shape and size of the intake funnel **1101**.

(183) The rings **1143** can be a solid piece having a thick portion **1144** with a first end **1145** separated from a second end **1146** by a gap. The ring **1143** can then include a thin portion **1147** extending from the first end **1145** that also includes a first end **1148** and a second end **1149**. An opening **1150** can be positioned and recessed at the second end **1146** and extend into the thick portion **1144**. The second end **1149** can then be positioned within the opening **1150** such that the second end **1149** can slide in and out relative to the opening **1150** as the rings **1143** expands or contracts.

(184) In some configurations, the outlet **1103** can include a fixed ring **1155** to maintain a cross-sectional flow area corresponding to a cross-sectional flow area of the inlet **1102** of the Venturi device **1110**. The fixed ring **1155** can be of similar size and/or shape of the expandable rings **1143**. In some configurations, the fixed rings **1155** can also be of a different size and/or shape than the expandable rings **1143**.

(185) Referencing back to FIG. **11**, the system **1100** can also include a first controller **1156**. The first controller **1156** can cause and/or control an electrical current to be applied to the shape changing portion **1109** based on a sensed pressure, temperature, and/or rate of flow of the ambient airflow through the body **1104** of the intake funnel **1101**. Additionally or alternative, the first controller **1156** can cause heat to be applied to the shape changing portion **1109** based on at least

one of pressure, temperature, or rate of flow of the ambient airflow through the body **1104**. The first controller **1156** can be positioned near the system **1100** or inside of the passenger cabin **1107**. The first controller can be powered by the motor **1120** of the vehicle **1130** and/or a battery **1126**.

(186) The system **1100** can also include a second controller **1157** which can direct electrical energy to be generated by the generator **1124** to the battery **1126** of the vehicle **1130** to flow to the battery **1126** based on a charge state of the battery **1126**. The second controller **1157** can monitor the percentage level of the battery **1126** and communicate to the generator **1124** to create electricity. Additionally or alternatively, the second controller **1157** can direct the motor **1120** to transfer power over to the battery **1126**. The second controller **1157** can determine a percentage of range extension accumulated during generation of electrical energy by the generator **1124**. The second controller **1157** can be positioned near the system **1100** or inside of the passenger cabin **1107**. The second controller **1157** be powered by the motor **1120** of the vehicle **1130** and/or a battery **1126**.

(187) In some configurations, the system **1100** can also include a third controller **1158** that can cause the valve **1108** to open and/or close. The third controller **1158** can direct the valve **1108** to alter a flow volume of the primary flow through the bypass duct **1116** based on a desired volume of the secondary flow to the bypass conduit **1115**. The third controller **1158** can change a volume of the primary flow through the bypass duct **1116** based on mitigating backpressure on the turbine outlet **1123**. The third controller **1158** can also mitigate backpressure on the turbine **1121** during startup of the turbine **1121** by detecting a pressure level at the turbine outlet **1123**. The third controller **1158** can be positioned near the system **1100** or inside of the passenger cabin **1107**. The third controller **1158** be powered by the motor **1120** of the vehicle **1130** and/or a battery **1126**.

(188) In some configurations, they system **1100** can further include a fourth controller **1159** that can cause the second valve **1111** to open and/or close. The fourth controller **1159** can direct the second valve **1111** to change a volume of the primary flow through the passenger cabin duct **1105** based on a volume flow setting to the passenger cabin **1107** of the vehicle **1130**. The fourth controller **1159** can monitor the flow rate and/or pressure of the primary flow through the passenger cabin duct **1105**. The fourth controller **1159** can be positioned near the system **1100** or inside of the passenger cabin **1107**. The fourth controller **1159** be powered by the motor **1120** of the vehicle **1130** and/or a battery **1126**.

(189) Any one of the controllers **1156**, **1157**, **1158**, **1159** can be separate from one another and/or function separately from one another. Each of the controllers **1156**, **1157**, **1158**, **1159** can have an independent input that is different from any of the other controllers.

(190) Additionally or alternatively, any one of the controllers **1156**, **1157**, **1158**, **1159** can be the same controller **1161** such that one or more controllers can have one and/or several functions. The controllers **1156**, **1157**, **1158**, **1159** can be one controller **1161** that performs all the functions of each individual controller.

(191) Sensors **1160** can be positioned along the intake funnel **1101**, particularly the inlet **1102** and outlet **1103**, to provide data for at least one of pressure, temperature, and/or rate of flow to any of the controllers **1156**, **1157**, **1158**, **1159**. Additionally or alternative, sensors **1160** can be provide a charge state of the battery **1126** to the second controller **1157** to indicate when electrical energy generated by the generator **1124** should flow to the battery **1126**.

(192) Motor Cooling System

(193) FIG. **18** illustrates a cooling system **1200** for cooling a motor of a vehicle with ambient airflow. The cooling system **1200** can also include one or more Venturi devices **1210**, which can be similar or identical to Venturi device **100** shown in FIGS. **1A-1C** and/or Venturi device **400** shown in FIGS. **4A-4D**. As described herein, the Venturi device **1210** can have an inlet **1202**, similar to the inlet **402** of Venturi device **400**, open to ambient air. The inlet **1202** can receive a primary flow of fluid made up of ambient air passed into the inlet **1202** as a vehicle **1230** is moving in a forward direction. The Venturi device can also include an outlet **1204** which can be similar to the outlet **404** of Venturi device **400** and that ejects the primary flow. The Venturi device **1210** can further include

a body **1211** similar to the body **411** of the Venturi device **400**, a converging portion **1206** and a diverging portion **1212** similar to the converging portion **406** and the diverging portion **410** of Venturi device **400** such that the movement of the primary flow through the converging portion **1206** and the diverging portion **1212** produces a Venturi effect, pulling the primary flow in through the inlet **1202** of the Venturi device **1210**. Lastly, the Venturi device **1210** can include a secondary input **1220** similar or identical to the secondary input **420** of the Venturi device **400** which can be positioned between the converging portion **1206** and the outlet **1204** to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet **1202** of the Venturi device **1210** to pull the primary flow through the inlet **1202** and into the body **1211** of the Venturi device **1210** to increase the primary flow through the outlet **1204** of the Venturi device **1210**.

(194) The cooling system **1200** can further include an air compressor **1214** that can compress ambient air and direct the compressed air into the secondary input **1220** of the Venturi device **1210** to provide the secondary flow. A cooling duct **1216** can be connected to the outlet **1204** receive the primary flow ejected from the outlet **1204**. In some configurations, the cooling duct **1216** can direct the primary flow to a motor **1218** of a vehicle **1230** to cool the motor **1218**. The cooling duct **1216** can include fins, vanes **1222** to direct the primary flow to one or more predetermined portions of the motor **1218** which are the hottest part of the motor **1218** and/or a source of heat. In some configuration, the cooling duct **1216** further includes conduits **1224** to move the primary flow from the outlet **1204** of the Venturi device **1210** toward the one or more predetermined portions of the motor **1218**. The conduits **1224** can also split the primary flow into two or more fluid flows.

(195) The cooling system **1200** can also include a secondary flow duct **1226** connecting the air compressor **1214** and the secondary input **1220** of the Venturi device **1210**. The air compressor **1214** can provide compressed air to the Venturi device **1210** to generate the secondary flow. The secondary flow duct **1226** can be connected to a secondary input **1117** to direct the secondary flow to the Venturi device **1110**. The secondary input **1220** can be adjustable to regulate an input of the secondary flow into the primary flow to control a volume of flow of the secondary flow into the secondary input **1220**.

(196) In some configurations, the air compressor **1214** can be connected to a wheel **1232** of the vehicle such that the air compressor **1214** is driven by the rotation of the wheel **1232**.

(197) In some configurations, the air compressor **1214** can be connected to the motor **1218** of the vehicle. In this configuration, the air compressor **1214** can be driven by operation of the motor **1218**. A drive shaft could be connected between the motor **1218** and the air compressor **1214** which propels the air compressor **1214**. The secondary flow coming from the air compressor **1214** can then be adjusted to provide a sufficient secondary flow into the secondary input

(198) In some configurations, as illustrated in FIG. **19**, a fan **1228** can replace the air compressor **1214** and provide a secondary flow to the Venturi device **1210**. The fan **1228** can direct a flow into the inlet **1202** to provide the primary flow. The inlet **1202** can be positioned in other orientations other than facing in a forward-facing manner. In utilizing the fan **1228**, the inlet **1202** can face in any direction such that the inlet **1202** is not constrained in a forward-facing direction. Thus, the fan **1228** allows the inlet **1202** to be placed in any suitable direction.

(199) In some configurations, the fan **1228** can be connected to the wheel **1232** of the vehicle **1230** such that the fan **1228** is driven by the rotation of the wheel **1232**. As the wheel **1232** revolves, the fan **1228** can be turned to generate a primary flow that is directed towards inlet **1202**.

(200) In some configurations, the fan **1228** can also be connected to a motor **1218** of the vehicle **1130** such that the motor **1218** can provide electricity to power the fan **1228**. A drive shaft (e.g., reduction drive) can be connected between the motor **1218** and the fan **1228**.

(201) As illustrated in FIG. **20**, the Venturi device **1210** and cooling duct **1216** can be fitted with the secondary flow duct **1226** to recirculate the secondary flow from the primary flow passing through the cooling duct **1216**. The secondary flow duct **1226** can be connected to a secondary input **1220** to direct the secondary flow to the Venturi device **1210**. The secondary input **1220** can

be adjustable to regulate an input of the secondary flow into the primary flow to control a volume of flow of the secondary flow into the secondary input.

(202) The system **1200** can also include a first valve **1268**, a second valve **1270**, and/or a third valve **1272** to control the path of the primary flow through the system. The valves **1268**, **1270**, **1272** can be of any type of valve such as a butterfly valve and/or stopcock valve to manage the flow rate of the primary and secondary flows. In some configuration, valves **1268**, **1270**, **1272** can be actuator driven to open and/or close. In some configuration, the valves **1268**, **1270**, **1272** can be actuated by a bimetallic spring that causes said valves **1268**, **1270**, **1272** to open and/or close.

(203) In some configurations, valves **1268**, **1270**, **1272** can be the same valve which operates and be positioned to perform all the functions of valves **1268**, **1270**, **1272**. A common conduit from the Venturi device **1210** can be directed toward a single valve operating as valves **1268**, **1270**, **1272**, which then adjusts the primary flow into multiple conduits corresponding to the conduits connected to valves **1268**, **1270**, **1272**. The primary flow can then be distributed evenly into the multiple conduits and/or controlled by the openness and/or closeness of the single valve. The single valve can be the same type or a different type than valves **1268**, **1270**, **1272**.

(204) In some configuration, the first valve **1268** can be positioned at the Venturi device outlet **1204** and be connected to the cooling duct **1216** to control how much of the primary flow is passed through the cooling duct **1216** and onto the motor **1218**. The valve **1268** can close completely when a response is detected that no flow is needed to cool the motor **1218**. passenger cabin duct **1105** can also be split into two or more conduits that feed into the passenger cabin **1107** in which the valve **1268** or more than one valve **1268** can further balance the flow into either one or more conduits.

(205) In some configuration, the second valve **1270** can be positioned in between the secondary input **1220** and the secondary flow duct **1226** to control how much of the secondary flow is flowed into the Venturi device **1110** as the secondary flow. The secondary valve **1270** can regulate the volume flow into the secondary input **1220**.

(206) Additionally or alternative, valve **1272** can be positioned at the split between conduits **1224** to move the primary flow from the outlet **1204** of the Venturi device **1210** toward the one or more predetermined portions of the motor **1218**.

(207) Valves **1268**, **1270**, **1272** can be controlled simultaneously or independently to ensure that there is a minimal backpressure on the turbine **1121**. Additionally or alternative, the valves **1268**, **1270**, **1272** can be controlled simultaneously or independently to supply an input inlet pressure to the Venturi device **1110** to overcome stalling of the turbine **1121** under heavy load situations, and thus recycling as much dynamic energy as possible back into the system **1100**.

(208) FIGS. **21-24** illustrates a configuration of the cooling system **1200** which can further include an expandable and/or shapeshifting intake funnel, channel, siphon, cowl **1240** that can be similar and/or identical to the intake funnel of FIGS. **11-14**. The intake funnel **1240** can have an inlet, entrance, entry **1242**, an outlet **1244**, a body **1246** between the inlet **1242** and outlet **1244**, a heating element **1248**, shape changing portion **1250**, shape memory materials **1252**, sections **1254**, interlocking seam **1256**, expandable rings **1258**, skeleton, frame, framework **1260**, elastic polymer **1262**, central axis **1264**, and/or longitudinal extent **1266** which can be similar and/or identical to the intake funnel **110**, inlet **1102**, an outlet **1103**, a body **1104**, heating element **1114**, shape changing portion **1109**, shape memory materials **1113**, sections **1140**, interlocking seam **1142**, expandable rings **1143**, skeleton **1151**, elastic polymer **1152**, central axis **1153**, and/or longitudinal extent **1154** in FIGS. **11-14**. The intake funnel **1240** can increase the flow volume that can pass into the system **1200**. Additionally or alternatively, the intake funnel **1240** can expand and/or contract based on similar stimulants at intake funnel **1101** such as temperature, pressure, electrical charge, and the like.

(209) FIGS. **22-24** illustrate different configurations of the longitudinal extent, length, span **1266** of each of the sections **1254** oriented along a central axis **1264**. Each of the different configurations can depend on the type of application and/or the size of the intake funnel **1240**.

(210) In some configurations, as shown in FIG. 22, a longitudinal extent **1266** of each of the sections **1254** can be oriented along a central axis **1264**. The sections **1254** can then be connected to one another using the interlocking seam **1256** along the longitudinal extent **1266**. The sections **1254** can then create a cylindrical shell with a continuous inner wall to direct the primary flow. The sections **1254** can then expand and/or contract together to change the shape and/or size of the shape shifting portion **1250**. The interlocking seam **1256** can be made by connecting the sections **1254** using welding techniques and/or interlocking fasteners along the longitudinal extents **1266**.

(211) FIG. 23 illustrates a configuration of the intake funnel **1240** in which the longitudinal extent **1266** of each of the strips **1254** can be curved to form a curved strip **1254** which is then oriented perpendicular to a central axis **1264**. One or more curved strips **1254** can be combined from end to end to form a section of a cylindrical shell with the central axis **1264** located at the center. The sections of the cylindrical shell can then be connected to one another using the interlocking seam **1256** to form the body **1246**. As mentioned above, the interlocking seam **1142** can be made using welding techniques and/or interlocking fasteners.

(212) In some configurations, the body **1246** of FIGS. 22 and 23 can then include an elastic polymer **1262** (e.g., polymer and/or rubber sheeting with high elasticity) encasing the shape changing portion **1250** that can also expand and/or contract. The elastic polymer **1262** can direct the fluid entering the intake funnel **1240** at the inlet **1242** to the outlet **1244**.

(213) In some configuration, as shown in FIG. 24, the sections **1254** of the body **1246** can be spaced apart from one another with gaps in between to form a skeleton **1260**. The skeleton **1260** can provide more flexibility for smaller applications (e.g., electric motorbike) of the intake funnel **1240** as the skeleton **1260** does not use interlocking seams to create the body **1246**. The longitudinal extent **1266** of each of the sections **1254** can be oriented along a central axis **1264**. The body **1246** can then include an elastic polymer **1262** (e.g., polymer and/or rubber sheeting with high elasticity) encasing the shape changing portion **1250** that can also expand and/or contract. The elastic polymer **1262** can contain the ambient air flow within the body **1246** of the intake funnel **1240**. An adhesive (e.g., quick drying cement) can be used to attach the elastic polymer **1262** to the strips **1254**. The skeleton **1260** with elastic polymer **1262** can then be clamped to the Venturi device **1210** or to a conduit leading to the Venturi device **1210** to allow for interchangeability of the body **1246** having the skeleton **1260** and elastic polymer **1262**.

(214) In some configurations, the ambient air drawn through the Venturi device **1210** can be used to warm up and start the motor **1218**. As the ambient air passes through the Venturi device **1210**, the temperature can be increased from 1° C. to 10° C., from 2° C. to 8° C., from 3° C. to 7° C., or from 4° C. to 6° C. before being passed onto the motor **1218**. Once the motor is on, the ambient air flowing through the system **1200** can be used to cool down the motor **1218** to prevent any overheating.

LIST OF EXAMPLE OF NUMBERED EMBODIMENTS

(215) The following is a list of example numbered embodiments. The features recited in the below list of example embodiments can be combined with additional features disclosed herein. Furthermore, additional inventive combinations of features are disclosed herein, which are not specifically recited in the below list of example embodiments and which do not include the same features as the embodiments listed below. For the sake of brevity, the below list of example embodiments does not identify every inventive aspect of this disclosure. The below list of example embodiments is not intended to identify key features or essential features of any subject matter described herein.

(216) 1. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid loop configured to circulate a primary flow of the fluid between the upper reservoir and the lower reservoir; a

turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow from the upper reservoir to the lower reservoir; a generator configured to be driven by the turbine to generate electrical energy; a pump disposed on the fluid loop, the pump configured to drive the primary flow from the lower reservoir to the upper reservoir; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the upper reservoir and upstream of the turbine, between the upper reservoir and the turbine on the fluid loop; and a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the lower reservoir and upstream of the pump, between the lower reservoir and the pump on the fluid loop, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase through the diverging portion before ejection through the outlet.

(217) 2. The hydropower system of example 1, wherein the secondary flow of the first Venturi flows from the turbine to the secondary input of the first Venturi device.

(218) 3. The hydropower system of example 2, further comprising a first conduit fluidically connected to the turbine and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device.

(219) 4. The hydropower system of any of the preceding examples, wherein the secondary flow of the second Venturi flows from the pump to the secondary input of the second Venturi device.

(220) 5. The hydropower system of example 4, further comprising a second conduit fluidically connected to the pump and the secondary input of the second Venturi device, the second conduit configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device.

(221) 6. The hydropower system of any of the preceding examples, further comprising a third conduit fluidically connected to the fluid loop between the upper reservoir and the turbine, the third conduit configured to direct the secondary flow of the second Venturi device from the primary flow to the secondary input of the second Venturi device.

(222) 7. The hydropower system of any of the preceding examples, further comprising an other pump disposed on the fluid loop, the other pump configured to drive the primary flow from the lower reservoir to the upper reservoir.

(223) 8. The hydropower system of example 7, further comprising a third Venturi device disposed on the fluid loop, the third Venturi device downstream of the lower reservoir and upstream of the other pump, between the lower reservoir and the other pump on the fluid loop.

(224) 9. The hydropower system of example 8, wherein a secondary flow of the third Venturi device flows from the other pump to a secondary input of the third Venturi device.

(225) 10. The hydropower system of example 9, further comprising a fourth conduit fluidically connected to the other pump and the secondary input of the third Venturi device, the fourth conduit configured to direct the secondary flow from the primary flow to the secondary input of the third Venturi device.

(226) 11. The hydropower system of example 9 or 10, further comprising a fifth conduit fluidically connected to the fluid loop between the upper reservoir and the turbine, the fifth conduit configured to direct the secondary flow of the third Venturi device from the primary flow to the secondary input of the third Venturi device.

(227) 12. The hydropower system any of the preceding examples, wherein the pump comprises a

motor that is configured to be powered by at least one of the generator or an external power supply.

(228) 13. The hydropower system of any of the preceding examples, wherein the fluid loop comprises at least one of tubing or piping.

(229) 14. The hydropower system of any of the preceding examples, wherein the secondary input is adjustable to regulate an input of the secondary flow into the primary flow.

(230) 15. The hydropower system of any of the preceding examples, wherein the secondary input is an annular gap.

(231) 16. The hydropower system of any of the preceding examples, wherein the secondary input is a ring gap.

(232) 17. The hydropower system of any of the preceding examples, wherein the secondary input is configured to distribute the secondary flow throughout the secondary input.

(233) 18. The hydropower system of any of the preceding examples, wherein the secondary input comprises a Coanda surface configured to distribute incoming secondary flow throughout the secondary input.

(234) 19. The hydropower system of any of the preceding examples, wherein the secondary input comprises a Coanda surface.

(235) 20. The hydropower system of any of the preceding examples, wherein the secondary input is configured to encircle the primary flow.

(236) 21. The hydropower system of any of the preceding examples, wherein the secondary input is disposed downstream of the diverging portion.

(237) 22. The hydropower system of any of the preceding examples, wherein the secondary input is disposed between the diverging portion and the outlet.

(238) 23. The hydropower system of any of the preceding examples, wherein the secondary input comprises one or more apertures.

(239) 24. The hydropower system of any of the preceding examples, wherein the secondary input comprises a plurality of apertures.

(240) 25. The hydropower system of any of the preceding examples, wherein the secondary input comprises one or more openings circumferentially distributed about a flow path of the primary flow, the secondary input configured to direct the secondary flow radially inward toward the primary flow.

(241) 26. The hydropower system of any of the preceding examples, further comprising a throat disposed between the converging portion and the diverging portion, the throat comprising a diameter that is smaller than a diameter of the converging portion and a diameter of the diverging portion.

(242) 27. The hydropower system of any of the preceding examples, wherein the secondary input comprises an annular chamber configured to receive and direct the secondary flow.

(243) 28. The hydropower system of example 27, wherein the annular chamber is configured to encircle the primary flow through the body.

(244) 29. The hydropower system of any of the preceding examples, wherein the pump drives the primary flow from the from the lower reservoir to the upper reservoir while turbine is driven by the primary flow from the upper reservoir to the lower reservoir to recirculate the fluid from the lower reservoir to the upper reservoir.

(245) 30. The hydropower system of any of examples 1 to 28, wherein the pump drives the primary flow from the from the lower reservoir to the upper reservoir while flow of the fluid is stopped through the turbine.

(246) 31. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid loop configured to circulate a primary flow of the fluid between the upper reservoir and the lower reservoir; a

turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow from the upper reservoir to the lower reservoir; a generator configured to be driven by the turbine to generate electrical energy; a pump disposed on the fluid loop, the pump configured to drive the primary flow from the lower reservoir to the upper reservoir; and a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the upper reservoir and upstream of the turbine, between the upper reservoir and the turbine on the fluid loop, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet.

(247) 32. The hydropower system of example 31, further comprising a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the lower reservoir and upstream of the pump, between the lower reservoir and the pump on the fluid loop.

(248) 33. The hydropower system of example 31 or 32, further comprising any of the features of examples 1-30.

(249) 34. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid loop configured to circulate a primary flow of the fluid between the upper reservoir and the lower reservoir; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow from the upper reservoir to the lower reservoir; a generator configured to be driven by the turbine to generate electrical energy; a pump disposed on the fluid loop, the pump configured to drive the primary flow from the lower reservoir to the upper reservoir; and a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the lower reservoir and upstream of the pump, between the lower reservoir and the pump on the fluid loop, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet.

(250) 35. The hydropower system of example 34, further comprising a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the upper reservoir and upstream of the turbine, between the upper reservoir and the turbine on the fluid loop.

(251) 36. The hydropower system of example 34 or 35, further comprising any of the features of examples 1-30.

(252) 37. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid conduit configured to direct a primary flow of the fluid between the upper reservoir and the lower reservoir;

a turbine and pump assembly disposed on the fluid conduit, the turbine and pump assembly configured to be driven by the primary flow from the upper reservoir to the lower reservoir and configured to drive the primary flow from the lower reservoir to the upper reservoir; a generator configured to be driven by the turbine and pump assembly to generate electrical energy; a first Venturi device disposed on the fluid conduit, the first Venturi device between the upper reservoir and the turbine and pump assembly on the fluid conduit; a second Venturi device disposed on the fluid conduit, the second Venturi device between the lower reservoir and the turbine and pump assembly on the fluid conduit, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet; a first bypass conduit connected to the fluid conduit upstream and downstream of the first Venturi device, the first bypass conduit configured to direct the primary flow around first Venturi device such that the primary flow does not pass through the first Venturi device with the primary flow flowing from the lower reservoir to the upper reservoir via the fluid conduit; and a second bypass conduit connected to the fluid conduit upstream and downstream of the second Venturi device, the second bypass conduit configured to direct the primary flow around second Venturi device such that the primary flow does not pass through the second Venturi device with the primary flow flowing from the upper reservoir to the lower reservoir via the fluid conduit.

(253) 38. The hydropower system of example 37, wherein the secondary flow of the first Venturi device flows from the turbine and pump assembly to the secondary input of the first Venturi device.

(254) 39. The hydropower system of example 38, further comprising a first conduit fluidically connected to the turbine and pump assembly and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device.

(255) 40. The hydropower system of any of example 37 to 39, wherein the secondary flow of the second Venturi device flows from the turbine and pump assembly to the secondary input of the second Venturi device.

(256) 41. The hydropower system of example 40, further comprising a second conduit fluidically connected to the pump and the secondary input of the second Venturi device, the second conduit configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device.

(257) 42. The hydropower system of any of examples 37 to 41, further comprising any of the features of examples 1-30.

(258) 43. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid conduit configured to direct a primary flow of the fluid between the upper reservoir and the lower reservoir; a turbine and pump assembly disposed on the fluid conduit, the turbine and pump assembly configured to be driven by the primary flow from the upper reservoir to the lower reservoir and configured to drive the primary flow from the lower reservoir to the upper reservoir; a generator configured to be driven by the turbine and pump assembly to generate electrical energy; a first Venturi device disposed on the fluid conduit, the first Venturi device between the upper reservoir and the turbine and pump assembly on the fluid conduit, wherein the first Venturi device

comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet; and a first bypass conduit connected to the fluid conduit upstream and downstream of the first Venturi device, the first bypass conduit configured to direct the primary flow around first Venturi device such that the primary flow does not pass through the first Venturi device with the primary flow flowing from the lower reservoir to the upper reservoir via the fluid conduit.

(259) 44. The hydropower system of example 43, further comprising a second Venturi device disposed on the fluid conduit, the second Venturi device between the lower reservoir and the turbine and pump assembly on the fluid conduit.

(260) 45. The hydropower system of example 44, further comprising a second bypass conduit connected to the fluid conduit upstream and downstream of the second Venturi device, the second bypass conduit configured to direct the primary flow around second Venturi device such that the primary flow does not pass through the second Venturi device with the primary flow flowing from the upper reservoir to the lower reservoir via the fluid conduit.

(261) 46. The hydropower system of any of examples 43 to 45, further comprising any of the features of examples 1-30 and 37-41.

(262) 47. A hydropower system for converting potential energy of a fluid into electrical energy, the hydropower system comprising: an upper reservoir containing a fluid; a lower reservoir containing the fluid, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a fluid conduit configured to direct a primary flow of the fluid between the upper reservoir and the lower reservoir; a turbine and pump assembly disposed on the fluid conduit, the turbine and pump assembly configured to be driven by the primary flow from the upper reservoir to the lower reservoir and configured to drive the primary flow from the lower reservoir to the upper reservoir; a generator configured to be driven by the turbine and pump assembly to generate electrical energy; a first Venturi device disposed on the fluid conduit, the first Venturi device between the lower reservoir and the turbine and pump assembly on the fluid conduit, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet; and a first bypass conduit connected to the fluid conduit upstream and downstream of the first Venturi device, the first bypass conduit configured to direct the primary flow around first Venturi device such that the primary flow does not pass through the first Venturi device with the primary flow flowing from the upper reservoir to the lower reservoir via the fluid conduit.

(263) 48. The hydropower system of example 47, further comprising a second Venturi device disposed on the fluid conduit, the second Venturi device between the upper reservoir and the turbine and pump assembly on the fluid conduit.

(264) 49. The hydropower system of example 48, further comprising a second bypass conduit connected to the fluid conduit upstream and downstream of the second Venturi device, the second

bypass conduit configured to direct the primary flow around second Venturi device such that the primary flow does not pass through the second Venturi device with the primary flow flowing from the lower reservoir to the upper reservoir via the fluid conduit.

(265) 50. The hydropower system of any of examples 47 to 49, further comprising any of the features of examples 1-30 and 37-41.

(266) 51. A system for converting potential energy of a fluid into electrical energy, the system comprising: a fluid conduit configured to direct a primary flow of a fluid between an upper reservoir and a lower reservoir, the lower reservoir positioned at a lower elevation relative to the upper reservoir such that the fluid flows from the upper reservoir to the lower reservoir via gravity; a turbine and pump assembly disposed on the fluid conduit, the turbine and pump assembly configured to be driven by the primary flow from the upper reservoir to the lower reservoir and configured to drive the primary flow from the lower reservoir to the upper reservoir; a generator configured to be driven by the turbine and pump assembly to generate electrical energy; a first Venturi device disposed on the fluid conduit, the first Venturi device between the lower reservoir and the turbine and pump assembly on the fluid conduit, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to pull the primary flow through the inlet and into the body causing the pressure of the primary flow to increase before ejection through the outlet; and a first bypass conduit connected to the fluid conduit upstream and downstream of the first Venturi device, the first bypass conduit configured to direct the primary flow around first Venturi device such that the primary flow does not pass through the first Venturi device with the primary flow flowing from the upper reservoir to the lower reservoir via the fluid conduit.

(267) 52. The system of example 51, further comprising the upper reservoir for containing the fluid.

(268) 53. The system of example 52 or 53, further comprising the lower reservoir.

(269) 54. The system of any of examples 51 to 53, further comprising any of the features of examples 1-30 and 37-41.

(270) 55. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow; a generator configured to be driven by the turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a cooling coil disposed on the fluid loop, the cooling coil downstream of the turbine and upstream of the first pump on the fluid loop, the cooling coil configured to condense the primary flow exiting the turbine; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop; a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle

relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a reservoir tank on the fluid loop, the reservoir tank containing the fluid, the reservoir tank downstream of the second Venturi device and upstream of the first Venturi device; a first conduit fluidically connected to the reservoir tank and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

(271) 56. The system of example 55, wherein the first Venturi device is configured to heat the primary flow passing through the first Venturi device such that primary flow at least partially phase shifts from the liquid state to the gas state.

(272) 57. The system of any of example 55 or 56, wherein the heater comprises one or more solar tubes, the one or more solar tubes configured to heat the secondary flow of the first Venturi device via solar radiation.

(273) 58. The system of example 57, wherein the first conduit comprises a solar tube manifold connected to the one or more solar tubes and to transfer heat from the one or more solar tubes to the secondary flow in the first conduit.

(274) 59. The system of any of examples 55 to 58, wherein the heater comprises a heater cartridge on the first conduit, the heater cartridge configured to heat the secondary flow in the first conduit.

(275) 60. The system of example 59, wherein the heater cartridge is powered by a solar panel assembly configured to generate electricity to heat the heater cartridge.

(276) 61. The system of any of examples 55 to 60, wherein the secondary flow of the second Venturi flows from the reservoir to the secondary input of the second Venturi device.

(277) 62. The system of example 61, further comprising a second conduit fluidically connected to the reservoir and the secondary input of the second Venturi device, the second conduit configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device.

(278) 63. The system of example 62, further comprising a third pump disposed on the second conduit, the third pump configured to drive the secondary flow from the primary flow to the secondary input of the second Venturi device.

(279) 64. The system any of examples 55 to 63, wherein the first and second pumps each comprise a motor that is configured to be powered by at least one of the generator or an external power supply.

(280) 65. The system any of examples 55 to 64, wherein the cooling coil is configured to operate using a refrigeration cycle using a refrigerant.

(281) 66. The system of example 65, wherein the refrigerant is CO₂.

(282) 67. The system of any of examples 55 to 66, wherein the fluid loop comprises at least one of tubing or piping.

(283) 68. The system of any of examples 55 to 67, wherein the secondary input is adjustable to regulate an input of the secondary flow into the primary flow.

(284) 69. The system of any of examples 55 to 68, wherein the secondary input is an annular gap.

(285) 70. The system of any of examples 55 to 69, wherein the secondary input is a ring gap.

(286) 71. The system of any of examples 55 to 70, wherein the secondary input is configured to distribute the secondary flow throughout the secondary input.

(287) 72. The system of any of examples 55 to 71, wherein the secondary input comprises a Coanda surface configured to distribute incoming secondary flow throughout the secondary input.

(288) 73. The system of any of examples 55 to 72, wherein the secondary input comprises a Coanda surface.

(289) 74. The system of any of examples 55 to 73, wherein the secondary input is configured to encircle the primary flow.

(290) 75. The system of any of examples 55 to 74, wherein the secondary input is disposed downstream of the diverging portion.

(291) 76. The system of any of examples 55 to 75, wherein the secondary input is disposed between the diverging portion and the outlet.

(292) 77. The system of any of examples 55 to 76, wherein the secondary input comprises one or more apertures.

(293) 78. The system of any of examples 55 to 77, wherein the secondary input comprises a plurality of apertures.

(294) 79. The system of any of examples 55 to 78, wherein the secondary input comprises one or more openings circumferentially distributed about a flow path of the primary flow, the secondary input configured to direct the secondary flow radially inward toward the primary flow.

(295) 80. The system of any of examples 55 to 79, further comprising a throat disposed between the converging portion and the diverging portion, the throat comprising a diameter that is smaller than a diameter of the converging portion and a diameter of the diverging portion.

(296) 81. The system of any of examples 55 to 80, wherein the secondary input comprises an annular chamber configured to receive and direct the secondary flow.

(297) 82. The system of example 81, wherein the annular chamber is configured to encircle the primary flow through the body.

(298) 83. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow; a generator configured to be driven by the turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a condenser disposed on the fluid loop, the condenser downstream of the turbine and upstream of the first pump on the fluid loop, the condenser configured to condense the primary flow exiting the turbine; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop; a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a first conduit fluidically connected to the fluid loop and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the

second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

(299) 84. The system of example 83, further comprising a reservoir tank on the fluid loop, the reservoir tank containing the fluid, the reservoir tank downstream of the second Venturi device and upstream of the first Venturi device.

(300) 85. The system of example 83 or 84, wherein the condenser comprises a cooling coil disposed on the first conduit.

(301) 86. The system of any of examples 83 to 85, further comprising any of the features of examples 55-82.

(302) 87. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow; a generator configured to be driven by the turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a condenser disposed on the fluid loop, the condenser downstream of the turbine and upstream of the first pump on the fluid loop, the condenser configured to condense the primary flow exiting the turbine; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a first conduit fluidically connected to the fluid loop and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

(303) 88. The system of example 87, further comprising a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop.

(304) 89. The system of example 87 or 88, further comprising any of the features of examples 55-82.

(305) 90. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the

diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a reducer connected to the body wall, the reducer connected to the body wall proximate the outlet relative to the inlet; a first nozzle disposed at least partially in the diverging portion, the first nozzle extending from the body wall, the first nozzle forming a first annular space between the first nozzle and the body wall, the first nozzle configured to create a first low pressure fluid in the first annular space relative to a high pressure fluid flow of the primary flow flowing through the first nozzle to pull the primary flow through the inlet and into the body, wherein reduction in the high pressure fluid flow of the primary flow through the first nozzle causes the first low pressure fluid to at least partially exit the first annular space for the first low pressure fluid to flow toward the outlet; a second nozzle disposed at least partially in the reducer, the second nozzle extending from the body wall, the second nozzle forming a second annular space between the second nozzle and the body wall, the second nozzle configured to create a second low pressure fluid in the second annular space relative to the high pressure fluid flow of the primary flow flowing through the second nozzle to move the primary flow through the outlet, wherein reduction in the high pressure fluid flow of the primary flow through the second nozzle causes the second low pressure fluid to at least partially the second annular space for the second low pressure fluid to flow toward the outlet, wherein the second annular space is larger than the first annular space, wherein an end of the second nozzle proximate the outlet relative to the inlet is spaced axially inward from an end of the reducer, the end of the reducer at least partially forming the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.

(306) 91. The Venturi device of example 90, wherein a smallest cross-sectional flow area of the first nozzle is between ends of the first nozzle such that at least one of the ends of the first nozzle has a larger diameter relative to a diameter at the smallest cross-sectional flow area of the first nozzle.

(307) 92. The Venturi device of example 91, wherein both of the ends of the first nozzle have larger diameters relative to the diameter at the smallest cross-sectional flow area of the first nozzle.

(308) 93. The Venturi device of any of examples 91 to 92, wherein a smallest cross-sectional flow area of the second nozzle is between ends of the second nozzle such that at least one of the ends of the second nozzle has a larger diameter relative to a diameter at the smallest cross-sectional flow area of the second nozzle.

(309) 94. The Venturi device of example 93, wherein both of the ends of the second nozzle have larger diameters relative to the diameter at the smallest cross-sectional flow area of the first nozzle.

(310) 95. The Venturi device of any of examples 91 to 94, further comprising a conical interior surface disposed between the diverging portion and the second nozzle, the conical interior surface configured to direct the primary flow toward the outlet, the conical interior surface comprising a cross-sectional flow area that decreases in size toward the outlet.

(311) 96. The Venturi device of example 95, wherein the secondary input is configured to direct the secondary flow through the conical interior surface.

(312) 97. The Venturi device of example 95, wherein the secondary input is configured to direct the secondary flow between the conical interior surface and the second nozzle.

(313) 98. The Venturi device of any of examples 95 to 97, wherein the cross-sectional flow area of the conical interior surface converges to a size that is smaller than a cross-sectional flow area of the converging portion and a cross-sectional flow area of the diverging portion.

(314) 99. The Venturi device of any of examples 91 to 98, wherein an axial extent of the first nozzle is less than an axial extent of the diverging portion.

(315) 100. The Venturi device of any of examples 91 to 99, wherein an axial extent of the second nozzle is less than an axial extent of the reducer.

(316) 101. The Venturi device of any of examples 91 to 100, wherein the first nozzle is connected to the body wall between the converging portion and the diverging portion.

(317) 102. The Venturi device of any of examples 91 to 101, wherein the second nozzle is connected to the body wall at a junction between the diverging portion and the reducer.

(318) 103. The Venturi device of any of examples 91 to 102, wherein the secondary input is configured to direct the secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow.

(319) 104. The Venturi device of example 103, wherein the angle is ninety degrees.

(320) 105. The Venturi device of example 103, wherein the angle is between 60 and 120 degrees.

(321) 106. The Venturi device of any of examples 91 to 105, wherein the secondary input comprises an annular passageway.

(322) 107. The Venturi device of any of examples 91 to 106, wherein the secondary input comprises one or more apertures.

(323) 108. The Venturi device of any of examples 91 to 107, wherein the secondary input comprises a plurality of apertures.

(324) 109. The Venturi device of any of examples 91 to 108, wherein the secondary input comprises an annular gap.

(325) 110. The Venturi device of any of examples 91 to 109, wherein the secondary input comprises a ring gap.

(326) 111. The Venturi device of any of examples 91 to 110, wherein the secondary input is configured to encircle the primary flow through the body.

(327) 112. The Venturi device of any of examples 91 to 111, wherein the secondary input is configured to circumferentially encircle the primary flow through the body.

(328) 113. The Venturi device of any of examples 91 to 112, wherein the secondary input comprises one or more openings circumferentially distributed about a flow path of the primary flow, the secondary input configured to direct the secondary flow radially inward toward the primary flow.

(329) 114. The Venturi device of any of examples 91 to 113, further comprising a throat disposed between the converging portion and the diverging portion, the throat comprising a diameter that is smaller than a diameter of the converging portion and a diameter of the diverging portion.

(330) 115. The Venturi device of any of examples 91 to 114, further comprising an annular chamber configured to receive and direct the secondary flow to the secondary input.

(331) 116. The Venturi device of example 115, wherein the annular chamber is configured to encircle the primary flow in the body.

(332) 117. The Venturi device of example 115 or 116, wherein the annular chamber comprises a Coanda surface configured to distribute incoming secondary flow throughout the annular chamber.

(333) 118. The Venturi device of any of examples 115 to 117, further comprising an annular passageway fluidically connected to the annular chamber, the annular passageway configured to direct the secondary flow from the annular passageway into the primary flow.

(334) 119. The Venturi device of any of examples 91 to 118, wherein the secondary input comprises a Coanda surface.

(335) 120. The Venturi device of any of examples 91 to 119, further comprising a plurality of secondary inputs.

(336) 121. The Venturi device of any of examples 91 to 120, wherein the secondary input is disposed downstream of the diverging portion.

(337) 122. The Venturi device of any of examples 91 to 121, wherein the converging portion comprises a cross-sectional flow area that continuously decreases in size in the direction of flow of the primary flow.

(338) 123. The Venturi device of any of examples 91 to 122, wherein the diverging portion comprises a cross-sectional flow area that continuously increases in size in the direction of flow of the primary flow.

(339) 124. The Venturi device of any of examples 91 to 123, wherein a length of the diverging portion is greater than a length of the converging portion.

- (340) 125. The Venturi device of any of examples 91 to 124, wherein a cross-sectional flow area of the outlet is smaller than a cross-sectional flow area of the inlet.
- (341) 126. The Venturi device of any of examples 91 to 125, wherein the converging portion is configured to increase a velocity of the primary flow and decrease a pressure of the primary flow, and wherein the diverging portion is configured to decrease the velocity of the primary flow and increase the pressure of the primary flow.
- (342) 127. The Venturi device of any of examples 91 to 126, wherein a cross-sectional flow area of the converging portion is circular.
- (343) 128. The Venturi device of any of examples 91 to 127, wherein the converging portion defines a flow area having a conical shape.
- (344) 129. The Venturi device of any of examples 91 to 128, wherein a cross-sectional flow area of the diverging portion is circular.
- (345) 130. The Venturi device of any of examples 91 to 129, wherein the diverging portion defines a flow area having a conical shape.
- (346) 131. The Venturi device of any of examples 91 to 130, wherein a size of a cross-sectional flow area of the converging portion changes less rapidly than a size of a cross-sectional flow area of the diverging portion per a unit of length.
- (347) 132. The Venturi device of any of examples 91 to 131, wherein a length of the diverging portion is greater than a length of the converging portion.
- (348) 133. The Venturi device of any of examples 91 to 132, wherein a cross-sectional flow area of the first nozzle continually changes in size.
- (349) 134. The Venturi device of any of examples 91 to 133, wherein a cross-sectional flow area of the second nozzle continually changes in size.
- (350) 135. The Venturi device of any of examples 91 to 134, wherein a cross-sectional flow area at an exit of the first nozzle is substantially the same as a cross-sectional flow area at an exit of the second nozzle.
- (351) 136. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a reducer connected to the body wall, the reducer connected to the body wall proximate the outlet relative to the inlet; a first nozzle disposed at least partially in the diverging portion, the first nozzle extending from the body wall, the first nozzle forming a first annular space between the first nozzle and the body wall, the first nozzle configured to create a first low pressure fluid in the first annular space relative to a high pressure fluid flow of the primary flow flowing through the first nozzle to pull the primary flow through the inlet and into the body, wherein reduction in the high pressure fluid flow of the primary flow through the first nozzle causes the first low pressure fluid to at least partially exit the first annular space for the first low pressure fluid to flow toward the outlet; a second nozzle disposed at least partially in the reducer, the second nozzle extending from the body wall, the second nozzle forming a second annular space between the second nozzle and the body wall, the second nozzle configured to create a second low pressure fluid in the second annular space relative to the high pressure fluid flow of the primary flow flowing through the second nozzle to move the primary flow through the outlet, wherein reduction in the high pressure fluid flow of the primary flow through the second nozzle causes the second low pressure fluid to at least partially the second annular space for the second low pressure fluid to flow toward the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.
- (352) 137. The Venturi device of example 136, wherein the second annular space is larger than the

first annular space.

(353) 138. The Venturi device of example 136 or 137, wherein an end of the second nozzle proximate the outlet relative to the inlet is spaced axially inward from an end of the reducer, the end of the reducer at least partially forming the outlet.

(354) 139. The Venturi device of any of examples 136 to 138, further comprising any of the features recited in examples 90-135.

(355) 140. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a first nozzle extending from the body wall, the first nozzle forming a first annular space between the first nozzle and the body wall, the first nozzle configured to create a first low pressure fluid in the first annular space relative to a high pressure fluid flow of the primary flow flowing through the first nozzle, wherein reduction in the high pressure fluid flow of the primary flow through the first nozzle causes the first low pressure fluid to at least partially exit the first annular space for the first low pressure fluid to flow toward the outlet; a second nozzle extending from the body wall, the second nozzle forming a second annular space between the second nozzle and the body wall, the second nozzle configured to create a second low pressure fluid in the second annular space relative to the high pressure fluid flow of the primary flow flowing through the second nozzle, wherein reduction in the high pressure fluid flow of the primary flow through the second nozzle causes the second low pressure fluid to at least partially exit the second annular space for the second low pressure fluid to flow toward the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.

(356) 141. The Venturi device of example 140, further comprising a reducer connected to the body wall, the reducer connected to the body wall proximate the outlet relative to the inlet.

(357) 142. The Venturi device of example 141, wherein the second nozzle is disposed at least partially in the reducer.

(358) 143. The Venturi device of any of examples 140 to 142, wherein first nozzle is disposed at least partially in the diverging portion.

(359) 144. The Venturi device of any of examples 140 to 143, further comprising any of the features recited in examples 90-135.

(360) 145. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a nozzle extending from the body wall, the nozzle forming a space between the nozzle and the body wall, the nozzle configured to create a low pressure fluid in the space relative to a high pressure fluid flow of the primary flow flowing through the nozzle, wherein reduction in the high pressure fluid flow of the primary flow through the nozzle causes the low pressure fluid to at least partially exit the annular space for the low pressure fluid to flow toward the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.

(361) 146. The Venturi device of example 145, wherein the nozzle is disposed at least partially in the diverging portion.

(362) 147. The Venturi device of example 145 or 146, further comprising an other nozzle extending from the body wall, the other nozzle forming an other space between the other nozzle and the body

wall, the other nozzle configured to create an other low pressure fluid in the other space relative to the high pressure fluid flow of the primary flow flowing through the other nozzle, wherein reduction in the high pressure fluid flow of the primary flow through the other nozzle causes the other low pressure fluid to at least partially exit the other space for the other low pressure fluid to flow toward the outlet.

(363) 148. The Venturi device of example 147, further comprising a reducer connected to the body wall, the reducer connected to the body wall proximate the outlet relative to the inlet.

(364) 149. The Venturi device of example 148, wherein the other nozzle is disposed at least partially in the reducer.

(365) 150. The Venturi device of any of examples 147 to 149, wherein the other space is annular.

(366) 151. The Venturi device of any of examples 145 to 150, wherein the space is annular.

(367) 152. The Venturi device of any of examples 145 to 151, further comprising any of the features recited in examples 90-135.

(368) 153. A forced induction system for a vehicle to induce ambient airflow to generate electrical energy from the ambient airflow, the system comprising: an intake funnel comprising an inlet, an outlet, and a body disposed between the inlet of the intake funnel and the outlet of the intake funnel, the intake funnel configured to direct an ambient airflow from the inlet of the intake funnel through the body of the intake funnel to the outlet of the intake funnel, the inlet of the intake funnel having a cross-sectional flow area larger than a cross-section flow area of the outlet of the intake funnel, the body of the intake funnel comprising a shape changing portion configured to expand or contract to change a cross-sectional flow area of the body of the intake funnel for the ambient airflow through the body of the intake funnel; a Venturi device in fluid communication with the intake funnel, the Venturi device comprising: an inlet of the Venturi device in fluid communication with the outlet of the intake funnel to receive a primary flow of fluid from the outlet of the intake funnel, the primary flow comprising the ambient airflow exiting the outlet of the intake funnel; an outlet of the Venturi device configured to eject the primary flow; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device; a turbine comprising an inlet of the turbine and an outlet of the turbine, the inlet of the turbine in fluid communication with the outlet of the Venturi device to receive the primary flow ejected from the outlet of the Venturi device, the turbine configured to be driven by the primary flow ejected from the outlet of the Venturi device; a generator configured to be driven by the turbine to generate electrical energy; a bypass conduit in fluid communication with the turbine and the Venturi device, the bypass conduit configured to recirculate the secondary flow from the primary flow flowing through the turbine to the secondary input of the Venturi device; a passenger cabin duct in fluid communication with the outlet of the turbine to receive the primary flow from the outlet of the turbine, the passenger cabin duct configured to direct the primary flow toward a passenger cabin of a vehicle; a valve in fluid communication with the outlet of the turbine to receive the primary flow from the outlet of the turbine; and a bypass duct in fluid communication with the valve, the bypass duct configured to direct the primary flow outside of the vehicle, the valve configured to control flow of the primary flow through the bypass duct.

(369) 154. The system of example 153, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a temperature of the ambient airflow through the body of the intake funnel.

(370) 155. The system of example 153 or 154, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a pressure of the ambient airflow through the body of the intake funnel.

(371) 156. The system of any one of example 153 to 155, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a flow rate of the ambient airflow through the body of the intake funnel.

(372) 157. The system of any one of example 153 to 156, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on electrical current applied to the shape changing portion.

(373) 158. The system of any one of example 153 to 157, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on heat applied to the shape changing portion.

(374) 159. The system of example 158 further comprising a heating element configured to apply heat to the shape changing portion.

(375) 160. The system of example 159, wherein the heating element is disposed on or within a wall of the shape changing portion.

(376) 161. The system of example 159 or 160, wherein the heating element is an elastic resistance heater wire positioned along the shape changing portion.

(377) 162. The system of any one of example 153 to 161, further comprising a first controller, wherein the first controller is configured to at least one of cause electrical current to be applied to the shape changing portion based on at least one of pressure, temperature, or flow rate of the ambient airflow through the body of the intake funnel or cause heat to be applied to the shape changing portion based on at least one of pressure, temperature, or flow rate of the ambient airflow through the body of the intake funnel.

(378) 163. The system of any one of example 153 to 161, wherein the shape changing portion comprises a shape memory material configured to change the cross-sectional flow area of the body of the intake funnel by expanding or contracting to one or more predetermined shapes.

(379) 164. The system of example 163, wherein the shape memory material comprises metallic material.

(380) 165. The system of example 163 or 164, wherein the shape memory material comprises Nafion.

(381) 166. The system of any of examples 163 to 165, wherein the shape memory material comprises Nitinol.

(382) 167. The system of any one of example 153 to 166, wherein shape changing portion comprises a pliable material configured to change the cross-sectional flow area of the body of the intake funnel by expanding or contracting.

(383) 168. The system of example 167, wherein the pliable material is configured to expand or contract based on a force induced on the pliable material by the ambient airflow through the body of the intake funnel.

(384) 169. The system of example 167 or 168, wherein the pliable material comprises piezoelectric material.

(385) 170. The system of any one of example 153 to 169, wherein the shape changing portion comprises strips of material configured to expand or contract to change the cross-sectional flow area of the body of the intake funnel.

(386) 171. The system of example 170, wherein a longitudinal extent of each of the strips of material is oriented along a central axis the intake funnel.

(387) 172. The system of example 170, wherein a longitudinal extent of each of the strips of material is oriented perpendicular to a central axis the intake funnel.

(388) 173. The system of any of example 170 to 172, wherein the strips of material are connected to each other to form a continuous inner surface of the body of the intake funnel along which the

ambient airflow flows.

(389) 174. The system of any of example 170 to 172, wherein the strips of material are spaced apart from each other to form a skeleton or a frame of the body of the intake funnel.

(390) 175. The system of any one of example 153 to 174, wherein the body of the intake funnel comprises an elastic polymer encasing the shape changing portion, the elastic polymer configured to expand or contract with the shape changing portion.

(391) 176. The system of example 175, wherein the elastic polymer is configured to contain the ambient airflow within the body of the intake funnel.

(392) 177. The system of any one of example 153 to 176, wherein the inlet of the intake funnel comprises an expandable ring configured to change in cross-sectional flow area corresponding to expansion or contraction of the shape changing portion, the expandable ring connected to the shape changing portion.

(393) 178. The system of example 177, wherein the expandable ring comprises a thick portion comprising a first end and a second end, the expandable ring comprising a thin portion comprising a first end and a second end, the first end of the thin portion connected to the first end of the thick portion, the thick portion comprising an opening at the second end of the thick portion, the second end of the thin portion positioned within the opening and configured to slide relative to the opening of the thick portion as the expandable ring expands or contracts.

(394) 179. The system of any one of example 153 to 178, wherein the outlet of the intake funnel comprises a fixed ring, the fixed ring configured to maintain a cross-sectional flow area corresponding to a cross-sectional flow area of the inlet of the Venturi device.

(395) 180. The system of any one of example 153 to 179, further comprising a second controller configured to cause electrical energy generated by the generator to flow to a battery of the vehicle based on a charge state of the battery.

(396) 181. The system of example 180, further comprising a switch configured to direct or stop flow of electrical energy generated by the generator to the battery of the vehicle, the second controller configured to cause the switch to direct or to stop electrical energy to the battery based on the charge state of the battery.

(397) 182. The system of example 180 or 181, wherein the second controller is configured to determine a percentage of range extension accumulated during generation of electrical energy by the generator.

(398) 183. The system of any one of example 153 to 182, further comprising a third controller configured to cause the valve to change flow of the primary flow through the bypass duct based on a desired flow of the secondary flow through the bypass conduit.

(399) 184. The system of example 183, wherein the third controller is configured to change flow of the primary flow through the bypass duct based on mitigating backpressure on the outlet of the turbine.

(400) 185. The system of example 184, wherein the third controller is configured to mitigate backpressure on the outlet of the turbine during startup of the turbine.

(401) 186. The system of any one of example 153 to 185, further comprising an other valve in fluid communication with the outlet of the turbine to receive the primary flow from the outlet of the turbine, the other valve configured to control flow of the primary flow through the passenger cabin duct.

(402) 187. The system of example 186, further comprising a fourth controller configured to cause the other valve to change flow of the primary flow through the passenger cabin duct based on a flow setting to the passenger cabin of the vehicle.

(403) 188. The system of any of examples 162, 180 to 185, or 187, wherein any one of the first, second, third, or fourth controllers is separate from any one of the other of the first, second, third, or fourth controllers.

(404) 189. The system of any of examples 162, 180 to 185, or 187, wherein any one of the first,

second, third, or fourth controllers and any one of the other of the first, second, third, or fourth controllers are the same controllers.

(405) 190. The system of any one of example 153 to 189, wherein the bypass duct is configured to direct the primary flow to an underside of the vehicle.

(406) 191. The system of any one of example 153 to 190, further comprising a heater in fluid communication with the passenger cabin duct, the heater configured to heat the primary flow directed to the passenger cabin of the vehicle.

(407) 192. The system of example 191, wherein the heater comprises a glow plug.

(408) 193. The system of example 191, wherein the heater comprises a resistance heater.

(409) 194. The system of any one of example 153 to 193, wherein the secondary input is adjustable to regulate an input of the secondary flow into the primary flow to control a volume of flow of the secondary flow into the secondary input.

(410) 195. The system of any one of example 153 to 194, wherein the inlet of the intake funnel faces toward a front of the vehicle to direct the ambient airflow into the inlet of the intake funnel with the vehicle in motion in a forward direction.

(411) 196. The system of any one of example 153 to 195, further comprising a fan facing the inlet of the intake funnel, the fan configured to direct air into the inlet of the intake funnel.

(412) 197. The system of example 196, wherein the fan is connected to a wheel of the vehicle and configured to be driven by rotation of the wheel of the vehicle.

(413) 198. The system of example 196 or 197, wherein the fan is connected to a motor of the vehicle and configured to be driven by operation of the motor of the vehicle.

(414) 199. A forced induction system to induce ambient airflow to generate electrical energy from the ambient airflow, the system comprising: an intake funnel comprising an inlet, an outlet, and a body disposed between the inlet of the intake funnel and the outlet of the intake funnel, the intake funnel configured to direct an ambient airflow from the inlet of the intake funnel through the body of the intake funnel to the outlet of the intake funnel, the inlet of the intake funnel having a cross-sectional flow area larger than a cross-section flow area of the outlet of the intake funnel, the body of the intake funnel comprising a shape changing portion configured to expand or contract to change a cross-sectional flow area of the body of the intake funnel for the ambient airflow through the body of the intake funnel; a Venturi device in fluid communication with the intake funnel, the Venturi device comprising: an inlet of the Venturi device in fluid communication with the outlet of the intake funnel to receive a primary flow of fluid from the outlet of the intake funnel, the primary flow comprising the ambient airflow exiting the outlet of the intake funnel; an outlet of the Venturi device configured to eject the primary flow; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device; a turbine comprising an inlet of the turbine and an outlet of the turbine, the inlet of the turbine in fluid communication with the outlet of the Venturi device to receive the primary flow ejected from the outlet of the Venturi device, the turbine configured to be driven by the primary flow ejected from the outlet of the Venturi device; a generator configured to be driven by the turbine to generate electrical energy; and a bypass conduit in fluid communication with the turbine and the Venturi device, the bypass conduit configured to recirculate the secondary flow from the primary flow flowing through the turbine to the secondary input of the Venturi device.

(415) 200. The system of example 199, further comprising a passenger cabin duct in fluid

communication with the outlet of the turbine to receive the primary flow from the outlet of the turbine, the passenger cabin duct configured to direct the primary flow toward a passenger cabin of a vehicle.

(416) 201. The system of example 199 or 200, further comprising a valve in fluid communication with the outlet of the turbine to receive the primary flow from the outlet of the turbine and comprising a bypass duct in fluid communication with the valve, the bypass duct configured to direct the primary flow away from the turbine, the valve configured to control flow of the primary flow through the bypass duct.

(417) 202. The system of any of examples 199 to 201, further comprising any of the features recited in examples 153-198.

(418) 203. An induction system for generating electrical energy from fluid flow, the system comprising: an intake funnel comprising an inlet, an outlet, and a body disposed between the inlet of the intake funnel and the outlet of the intake funnel, the intake funnel configured to direct a fluid flow from the inlet of the intake funnel through the body of the intake funnel to the outlet of the intake funnel, the body of the intake funnel comprising a shape changing portion configured to expand or contract to change a cross-sectional flow area of the body of the intake funnel for the fluid flow through the body of the intake funnel; a turbine comprising an inlet of the turbine and an outlet of the turbine, the inlet of the turbine in fluid communication with the outlet of the intake funnel to receive the fluid flow from the outlet of intake funnel, the turbine configured to be driven by the fluid flow exiting from the outlet of the intake funnel; and a generator configured to be driven by the turbine to generate electrical energy.

(419) 204. The system of example 203, further comprising a Venturi device in fluid communication with the intake funnel, the Venturi device comprising: an inlet of the Venturi device in fluid communication with the outlet of the intake funnel to receive a primary flow of fluid from the outlet of the intake funnel, the primary flow comprising the fluid flow exiting the outlet of the intake funnel; an outlet of the Venturi device configured to eject the primary flow to the inlet of the turbine; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device.

(420) 205. The system of example 204, further comprising a bypass conduit in fluid communication with the turbine and the Venturi device, the bypass conduit configured to recirculate the secondary flow from the primary flow flowing through the turbine to the secondary input of the Venturi device.

(421) 206. The system of any of examples 203 to 205, wherein the inlet of the intake funnel is configured to entrain ambient air.

(422) 207. The system of any of examples 203 to 206, wherein the inlet of the intake funnel has a cross-sectional flow area larger than a cross-section flow area of the outlet of the intake funnel.

(423) 208. The system of any of examples 203 to 207, further comprising any of the features recited in examples 153-198.

(424) 209. An intake funnel for inducing fluid flow, the intake funnel comprising: an inlet; an outlet; and a body disposed between the inlet of the intake funnel and the outlet of the intake funnel, the body comprising a shape changing portion configured to expand or contract to change a cross-sectional flow area of the body of the intake funnel for the fluid flow through the body of the intake funnel, wherein the intake funnel is configured to direct a fluid flow from the inlet of the

intake funnel through the body of the intake funnel to the outlet of the intake funnel.

(425) 210. A system comprising the intake funnel of example 209, the system comprising a turbine comprising an inlet of the turbine and an outlet of the turbine, the inlet of the turbine in fluid communication with the outlet of the intake funnel to receive the fluid flow exiting the outlet of the intake funnel, the turbine configured to be driven by the fluid flow exiting the outlet of the intake funnel.

(426) 211. The system of example 210, further comprising a generator configured to be driven by the turbine to generate electrical energy.

(427) 212. The intake funnel of example 209 or the system of example 210 or 211, further comprising any of the features recited in examples 153-198.

(428) 213. A cooling system for cooling a motor of a vehicle with ambient airflow, the system comprising: a Venturi device comprising: an inlet of the Venturi device open to ambient air, the inlet configured to receive a primary flow of fluid, the primary flow comprising ambient air passed into the inlet; an outlet of the Venturi device configured to eject the primary flow; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device; an air compressor configured to compress ambient air and direct the compressed air into the secondary input of the Venturi device to provide the secondary flow; and a cooling duct in fluid communication the outlet of the Venturi device to receive the primary flow ejected from the outlet of the Venturi device, the cooling duct configured to direct the primary flow to a motor of a vehicle to cool the motor, the cooling duct comprising fins configured to direct the primary flow to one or more predetermined portions of the motor.

(429) 214. The system of example 213, wherein the cooling duct comprises conduits configured to move the primary flow from the outlet of the Venturi device toward the one or more predetermined portions of the motor, the conduits configured to split the primary flow into two or more fluid flows.

(430) 215. The system of example 213 or 214, further comprising a secondary flow duct connecting the air compressor and the secondary input of the Venturi device.

(431) 216. The system of any of example 213 to 215, wherein the air compressor is connected to a wheel of the vehicle, the air compressor configured to be driven by rotation of the wheel.

(432) 217. The system of any of example 213 to 216, wherein the air compressor is connected to the motor of the vehicle, the air compressor configured to be driven by operation of the motor.

(433) 218. A cooling system for cooling a motor of a vehicle with ambient airflow, the system comprising: a Venturi device comprising: an inlet of the Venturi device open to ambient air, the inlet configured to receive a primary flow of fluid, the primary flow comprising ambient air passed into the inlet; an outlet of the Venturi device configured to eject the primary flow; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi

device; and a cooling duct in fluid communication the outlet of the Venturi device to receive the primary flow ejected from the outlet of the Venturi device, the cooling duct configured to direct the primary flow to a motor of a vehicle to cool the motor.

(434) 219. The system of example 218, further comprising an air compressor configured to compress ambient air and direct the compressed air into the secondary input of the Venturi device to provide the secondary flow.

(435) 220. The system of example 218 or 219, wherein the cooling duct comprises fins configured to direct the primary flow to one or more predetermined portions of the motor.

(436) 221. The system of any of examples 218 to 220, further comprising any of the features recited in examples 213-217.

(437) 222. A cooling system for cooling with ambient airflow, the system comprising: a Venturi device comprising: an inlet of the Venturi device open to ambient air, the inlet configured to receive a primary flow of fluid, the primary flow comprising ambient air passed into the inlet; an outlet of the Venturi device configured to eject the primary flow, the outlet of the Venturi device configured to direct the primary flow to a component to cool the component; and a body of the Venturi device disposed between the inlet of the Venturi device and the outlet of the Venturi device, the body of the Venturi device comprising: a converging portion and a diverging portion, wherein movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet of the Venturi device; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of fluid into the primary flow to create a vortex for producing a suction at the inlet of the Venturi device to pull the primary flow through the inlet of the Venturi device and into the body of the Venturi device to increase the primary flow through the outlet of the Venturi device.

(438) 223. The system of example 222, further comprising a cooling duct in fluid communication the outlet of the Venturi device to receive the primary flow ejected from the outlet of the Venturi device, the cooling duct configured to direct the primary flow to the component to cool the component.

(439) 224. The system of example 222 or 223, wherein the component comprises a motor of a vehicle.

(440) 225. The system of any of examples 222 to 224, further comprising any of the features recited in examples 213-217.

(441) 226. The system of any of example 213 to 225, further comprising an intake funnel comprising an inlet, an outlet, and a body disposed between the inlet of the intake funnel and the outlet of the intake funnel, the intake funnel configured to direct an ambient airflow from the inlet of the intake funnel through the body of the intake funnel to the outlet of the intake funnel, the inlet of the intake funnel having a cross-sectional flow area larger than a cross-section flow area of the outlet of the intake funnel, the body of the intake funnel comprising a shape changing portion configured to expand or contract to change a cross-sectional flow area of the body of the intake funnel for the ambient airflow through the body of the intake funnel.

(442) 227. The system of example 226, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a temperature of the ambient airflow through the body of the intake funnel.

(443) 228. The system of example 226 or 227, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a pressure of the ambient airflow through the body of the intake funnel.

(444) 229. The system of any one of example 226 to 228, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on a flow rate of the ambient airflow through the body of the intake funnel.

(445) 230. The system of any one of example 226 to 229, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on

electrical current applied to the shape changing portion.

(446) 231. The system of any one of example 226 to 230, wherein the shape changing portion is configured to change the cross-sectional flow area of the body of the intake funnel based on heat applied to the shape changing portion.

(447) 232. The system of example 231 further comprising a heating element configured to apply heat to the shape changing portion.

(448) 233. The system of example 232, wherein the heating element is disposed on or within a wall of the shape changing portion.

(449) 234. The system of example 232 or 233, wherein the heating element is an elastic resistance heater wire positioned along the shape changing portion.

(450) 235. The system of any one of example 226 to 234, wherein the shape changing portion comprises a shape memory material configured to change the cross-sectional flow area of the body of the intake funnel by expanding or contracting to one or more predetermined shapes.

(451) 236. The system of example 235, wherein the shape memory material comprises metallic material.

(452) 237. The system of example 235 or 236, wherein the shape memory material comprises Nafion.

(453) 238. The system of any of examples 235 to 237, wherein the shape memory material comprises Nitinol.

(454) 239. The system of any one of example 226 to 238, wherein shape changing portion comprises a pliable material configured to change the cross-sectional flow area of the body of the intake funnel by expanding or contracting.

(455) 240. The system of example 239, wherein the pliable material is configured to expand or contract based on a force induced on the pliable material by the ambient airflow through the body of the intake funnel.

(456) 241. The system of example 239 or 240, wherein the pliable material comprises piezoelectric material.

(457) 242. The system of any one of example 226 to 241, wherein the shape changing portion comprises strips of material configured to expand or contract to change the cross-sectional flow area of the body of the intake funnel.

(458) 243. The system of example 242, wherein a longitudinal extent of each of the strips of material is oriented along a central axis the intake funnel.

(459) 244. The system of example 242, wherein a longitudinal extent of each of the strips of material is oriented perpendicular to a central axis the intake funnel.

(460) 245. The system of any of example 242 to 244, wherein the strips of material are connected to each other to form a continuous inner surface of the body of the intake funnel along which the ambient airflow flows.

(461) 246. The system of any of example 242 to 244, wherein the strips of material are spaced apart from each other to form a skeleton or a frame of the body of the intake funnel.

(462) 247. The system of any one of example 226 to 246, wherein the body of the intake funnel comprises an elastic polymer encasing the shape changing portion, the elastic polymer configured to expand or contract with the shape changing portion.

(463) 248. The system of example 247, wherein the elastic polymer is configured to contain the ambient airflow within the body of the intake funnel.

(464) 249. The system of any one of example 226 to 248, wherein the inlet of the intake funnel comprises an expandable ring configured to change in cross-sectional flow area corresponding to expansion or contraction of the shape changing portion, the expandable ring connected to the shape changing portion.

(465) 250. The system of example 249, wherein the expandable ring comprises a thick portion comprising a first end and a second end, the expandable ring comprising a thin portion comprising

a first end and a second end, the first end of the thin portion connected to the first end of the thick portion, the thick portion comprising an opening at the second end of the thick portion, the second end of the thin portion positioned within the opening and configured to slide relative to the opening of the thick portion as the expandable ring expands or contracts.

(466) 251. The system of any one of example 226 to 250, wherein the outlet of the intake funnel comprises a fixed ring, the fixed ring configured to maintain a cross-sectional flow area corresponding to a cross-sectional flow area of the inlet of the Venturi device.

(467) 252. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a first funnel disposed at least partially in the converging portion, the first funnel extending from the body wall toward a central axis of the body, the first funnel forming a first annular space between the first funnel and the body wall, the first funnel configured to create a first low pressure fluid in the first annular space relative to a high pressure fluid flow of the primary flow flowing through the first funnel to pull the primary flow through the inlet and into the body, wherein reduction in the high pressure fluid flow of the primary flow through the first funnel causes the first low pressure fluid to at least partially exit the first annular space for the first low pressure fluid to flow toward the outlet; a second funnel disposed at least partially in the diverging portion, the second funnel extending from the body wall toward the central axis of the body, the second funnel forming a second annular space between the second funnel and the body wall, the second funnel configured to create a second low pressure fluid in the second annular space relative to the high pressure fluid flow of the primary flow flowing through the second funnel to pull the primary flow through the inlet and into the body, wherein reduction in the high pressure fluid flow of the primary flow through the second funnel causes the second low pressure fluid to at least partially exit the second annular space for the second low pressure fluid to flow toward the outlet, wherein the second annular space is larger than the first annular space; a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body; and a conical interior surface disposed downstream of the secondary input relative to the primary flow of the fluid, the conical interior surface configured to direct the primary flow toward the outlet, the conical interior surface comprising a cross-sectional flow area that increases in size toward the outlet.

(468) 253. The Venturi device of example 252, wherein the cross-sectional flow area of the conical interior surface increases up to the outlet.

(469) 254. The Venturi device of any of example 252 or 253, wherein the conical interior surface is a first conical interior surface and further comprising a second conical interior surface disposed between the diverging portion and the first conical interior surface, the second conical interior surface configured to direct the primary flow toward the outlet, the second conical interior surface comprising a cross-sectional flow area that decreases in size toward the outlet.

(470) 255. The Venturi device of example 254, wherein the secondary input is configured to direct the secondary flow through the second conical interior surface.

(471) 256. The Venturi device of example 254 or 255, wherein the secondary input is configured to direct the secondary flow between the first conical interior surface and the second conical interior surface.

(472) 257. The Venturi device of any of examples 254 to 256, wherein the cross-sectional flow area of the second conical interior surface converges to a size that is smaller than a cross-sectional flow area of the converging portion and a cross-sectional flow area of the diverging portion.

(473) 258. The Venturi device of any of examples 252 to 257, wherein an axial extent of the first

funnel is substantially equal to an axial extent of the converging portion along the central axis.

(474) 259. The Venturi device of any of examples 252 to 258, wherein an axial extent of the second funnel is less than an axial extent of the diverging portion along the central axis.

(475) 260. The Venturi device of example 259, wherein the axial extent of the second funnel is half the axial extent of the diverging portion along the central axis.

(476) 261. The Venturi device of any of examples 252 to 260, wherein the first funnel is connected to the body wall at the inlet.

(477) 262. The Venturi device of any of examples 252 to 261, wherein the second funnel is connected to the body wall between the converging portion and the diverging portion.

(478) 263. The Venturi device of any of examples 252 to 263, wherein the secondary input is configured to direct the secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow.

(479) 264. The Venturi device of example 263, wherein the angle is ninety degrees.

(480) 265. The Venturi device of example 263, wherein the angle is between 60 and 120 degrees.

(481) 266. The Venturi device of any of examples 252 to 265, wherein the secondary input comprises an annular passageway.

(482) 267. The Venturi device of any of examples 252 to 265, wherein the secondary input comprises one or more apertures.

(483) 268. The Venturi device of any of examples 252 to 265, wherein the secondary input comprises a plurality of apertures.

(484) 269. The Venturi device of any of examples 252 to 268, wherein the secondary input comprises an annular gap.

(485) 270. The Venturi device of any of examples 252 to 269, wherein the secondary input comprises a ring gap.

(486) 271. The Venturi device of any of examples 252 to 270, wherein the secondary input is configured to encircle the primary flow through the body.

(487) 272. The Venturi device of any of examples 252 to 271, wherein the secondary input is configured to circumferentially encircle the primary flow through the body.

(488) 273. The Venturi device of any of examples 252 to 272, wherein the secondary input comprises one or more openings circumferentially distributed about a flow path of the primary flow, the secondary input configured to direct the secondary flow radially inward toward the primary flow.

(489) 274. The Venturi device of any of examples 252 to 273, further comprising a throat disposed between the converging portion and the diverging portion, the throat comprising a diameter that is smaller than a diameter of the converging portion and a diameter of the diverging portion.

(490) 275. The Venturi device of any of examples 252 to 275, further comprising an annular chamber configured to receive and direct the secondary flow to the secondary input.

(491) 276. The Venturi device of example 275, wherein the annular chamber is configured to encircle the primary flow in the body.

(492) 277. The Venturi device of example 275 or 276, wherein the annular chamber comprises a Coanda surface configured to distribute incoming secondary flow throughout the annular chamber.

(493) 278. The Venturi device of any of examples 275 to 277, further comprising an annular passageway fluidically connected to the annular chamber, the annular passageway configured to direct the secondary flow from the annular passageway into the primary flow.

(494) 279. The Venturi device of any of examples 252 to 278, wherein the secondary input comprises a Coanda surface.

(495) 280. The Venturi device of any of examples 252 to 279, further comprising a plurality of secondary inputs.

(496) 281. The Venturi device of any of examples 252 to 280, wherein the secondary input is disposed downstream of the diverging portion.

(497) 282. The Venturi device of any of examples 252 to 281, wherein the converging portion comprises a cross-sectional flow area that continuously decreases in size in the direction of flow of the primary flow.

(498) 283. The Venturi device of any of examples 252 to 282, wherein the diverging portion comprises a cross-sectional flow area that continuously increases in size in the direction of flow of the primary flow.

(499) 284. The Venturi device of any of examples 252 to 283, wherein a length of the diverging portion is greater than a length of the converging portion.

(500) 285. The Venturi device of any of examples 252 to 284, wherein a cross-sectional flow area of the outlet is smaller than a cross-sectional flow area of the inlet.

(501) 286. The Venturi device of any of examples 252 to 285, wherein the converging portion is configured to increase a velocity of the primary flow and decrease a pressure of the primary flow, and wherein the diverging portion is configured to decrease the velocity of the primary flow and increase the pressure of the primary flow.

(502) 287. The Venturi device of any of examples 252 to 286, wherein the cross-sectional flow area of the converging portion is circular.

(503) 288. The Venturi device of any of examples 252 to 287, wherein the converging portion defines a flow area having a conical shape.

(504) 289. The Venturi device of any of examples 252 to 288, wherein the cross-sectional flow area of the diverging portion is circular.

(505) 290. The Venturi device of any of examples 252 to 289, wherein the diverging portion defines a flow area having a conical shape.

(506) 291. The Venturi device of any of examples 252 to 290, wherein a size of a cross-sectional flow area of the converging portion changes more rapidly than a size of a cross-sectional flow area of the diverging portion per a unit of length.

(507) 292. The Venturi device of any of examples 252 to 291, wherein a length of the diverging portion is greater than a length of the converging portion.

(508) 293. The Venturi device of any of examples 252 to 292, wherein a cross-sectional flow area of the first funnel continually decreases in size toward the central axis in the direction of flow of the primary fluid.

(509) 294. The Venturi device of any of examples 252 to 293, wherein a cross-sectional flow area of the second funnel continually decreases in size toward the central axis in the direction of flow of the primary fluid.

(510) 295. The Venturi device of any of examples 252 to 294, wherein a cross-sectional flow area at an exit of the first funnel is substantially the same as a cross-sectional flow area at an exit of the second funnel.

(511) 296. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a first funnel disposed at least partially in the converging portion, the first funnel extending from the body wall toward a central axis of the body, the first funnel forming a first annular space between the first funnel and the body wall, the first funnel configured to create a first low pressure fluid in the first annular space relative to a high pressure fluid flow of the primary flow flowing through the first funnel, wherein reduction in the high pressure fluid flow of the primary flow through the first funnel causes the first low pressure fluid to at least partially exit the first annular space for the first low pressure fluid to flow toward the outlet; a second funnel disposed at least partially in the diverging portion, the second funnel extending from the body wall toward the central axis of the body, the second funnel forming a second annular space between the second funnel and the body

wall, the second funnel configured to create a second low pressure fluid in the second annular space relative to the high pressure fluid flow of the primary flow flowing through the second funnel, wherein reduction in the high pressure fluid flow of the primary flow through the second funnel causes the second low pressure fluid to at least partially exit the second annular space for the second low pressure fluid to flow toward the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.

(512) 297. The Venturi device of example 296, further comprising a conical interior surface disposed downstream of the secondary input relative to the primary flow of the fluid, the conical interior surface configured to direct the primary flow toward the outlet, the conical interior surface comprising a cross-sectional flow area that increases in size toward the outlet.

(513) 298. The Venturi device of example 296 or 297, wherein the second annular space is larger than the first annular space

(514) 299. The Venturi device of any of examples 296 to 298, further comprising any of the features recited in examples 252-295.

(515) 300. A Venturi device, the Venturi device comprising: an inlet configured to receive a primary flow of a fluid; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a body wall comprising a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect, pulling the primary flow in through the inlet; a funnel extending from the body wall toward a central axis of the body, the funnel forming a space between the funnel and the body wall, the funnel configured to create a low pressure fluid in the space relative to a high pressure fluid flow of the primary flow flowing through the funnel, wherein reduction in the high pressure fluid flow of the primary flow through the funnel causes the low pressure fluid to at least partially exit the space for the low pressure fluid to flow toward the outlet; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow to create a vortex, pulling the primary flow through the inlet and into the body.

(516) 301. The Venturi device of example 300, wherein the funnel is disposed at least partially in the converging portion.

(517) 302. The Venturi device of example 300 or 301, further comprising an other funnel extending from the body wall toward the central axis of the body, the other funnel forming an other space between the other funnel and the body wall, the other funnel configured to create an other low pressure fluid in the other space relative to the high pressure fluid flow of the primary flow flowing through the other funnel, wherein reduction in the high pressure fluid flow of the primary flow through the other funnel causes the other low pressure fluid to at least partially exit the other space for the other low pressure fluid to flow toward the outlet.

(518) 303. The Venturi device of example 302, wherein the other funnel is disposed at least partially in the diverging portion.

(519) 304. The Venturi device of example 302 or 303, wherein the other space is annular.

(520) 305. The Venturi device of any of examples 300 to 304, wherein the space is annular.

(521) 306. The Venturi device of any of examples 300 to 305, further comprising any of the features recited in examples 252-295.

(522) 307. The hydropower system of any of examples 1 to 30, further comprising any of the features recited in examples 90-152.

(523) 308. The hydropower system of any of examples 31 to 33, further comprising any of the features recited in examples 90-152.

(524) 309. The hydropower system of any of examples 34 to 36, further comprising any of the features recited in examples 90-152.

(525) 310. The hydropower system of any of examples 37 to 42, further comprising any of the features recited in examples 90-152.

(526) 311. The hydropower system of any of examples 43 to 46, further comprising any of the features recited in examples 90-152.

(527) 312. The hydropower system of any of examples 47 to 50 further comprising any of the features recited in examples 90-152.

(528) 313. The system of any of examples 51 to 54, further comprising any of the features recited in examples 90-152.

(529) 314. The system of any of examples 55 to 82, further comprising any of the features recited in examples 90-152.

(530) 315. The system of any of examples 83 to 86, further comprising any of the features recited in examples 90-152.

(531) 316. The system of any of examples 87 to 89, further comprising any of the features recited in examples 90-152.

(532) 317. The systems of any of examples 55 to 89, wherein the fluid comprises copper-propylene glycol.

(533) 318. The forced induction system of any of examples 153 to 198, further comprising any of the features recited in examples 90-152.

(534) 319. The forced induction system of any of examples 199 to 202, further comprising any of the features recited in examples 90-152.

(535) 320. The induction system of any of examples 203 to 208, further comprising any of the features recited in examples 90-152.

(536) 321. The intake funnel of any of examples 209 to 212, further comprising any of the features recited in examples 90-152.

(537) 322. The cooling systems of any of examples 213 to 251, further comprising any of the features recited in examples 90-152.

(538) 323. The hydropower system of any of examples 1 to 30, further comprising any of the features recited in examples 252-306.

(539) 324. The hydropower system of any of examples 31 to 33, further comprising any of the features recited in examples 252-306.

(540) 325. The hydropower system of any of examples 34 to 36, further comprising any of the features recited in examples 252-306.

(541) 326. The hydropower system of any of examples 37 to 42, further comprising any of the features recited in examples 252-306.

(542) 327. The hydropower system of any of examples 43 to 46, further comprising any of the features recited in examples 252-306.

(543) 328. The hydropower system of any of examples 47 to 50 further comprising any of the features recited in examples 252-306.

(544) 329. The system of any of examples 51 to 54, further comprising any of the features recited in examples 252-306.

(545) 330. The system of any of examples 55 to 82, further comprising any of the features recited in examples 252-306.

(546) 331. The system of any of examples 83 to 86, further comprising any of the features recited in examples 252-306.

(547) 332. The system of any of examples 87 to 89, further comprising any of the features recited in examples 252-306.

(548) 333. The forced induction system of any of examples 153 to 198, further comprising any of the features recited in examples 252-306.

(549) 334. The forced induction system of any of examples 199 to 202, further comprising any of the features recited in examples 252-306.

(550) 335. The induction system of any of examples 203 to 208, further comprising any of the features recited in examples 252-306.

(551) 336. The intake funnel of any of examples 209 to 212, further comprising any of the features recited in examples 252-306.

(552) 337. The cooling systems of any of examples 213 to 251, further comprising any of the features recited in examples 252-306.

(553) Terminology

(554) Moreover, while operations may be depicted in the drawings or described in the specification in a particular order, such operations need not be performed in the particular order shown or in sequential order, and all operations need not be performed, to achieve the desirable results. Other operations that are not depicted or described can be incorporated in the example methods and processes. For example, one or more additional operations can be performed before, after, simultaneously, or between any of the described operations. Further, the operations may be rearranged or reordered in other implementations. Also, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described components and systems can generally be integrated together in a single product or packaged into multiple products. Additionally, other implementations are within the scope of this disclosure.

(555) Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain configurations include or do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more configurations.

(556) Conjunctive language, such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain configurations require the presence of at least one of X, at least one of Y, and at least one of Z.

(557) Some configurations have been described in connection with the accompanying drawings. Components can be added, removed, and/or rearranged. Orientation references such as, for example, “top” and “bottom” are for ease of discussion and may be rearranged such that top features are proximate the bottom and bottom features are proximate the top. Further, the disclosure herein of any particular feature, aspect, method, property, characteristic, quality, attribute, element, or the like in connection with various configurations can be used in all other configurations set forth herein. Additionally, it will be recognized that any methods described herein may be practiced using any device suitable for performing the recited steps.

(558) In summary, various configurations and examples of energy converting devices and methods have been disclosed. Although the systems and methods have been disclosed in the context of those configurations and examples, it will be understood by those skilled in the art that this disclosure extends beyond the specifically disclosed configurations to other alternative configurations and/or other uses of the configurations, as well as to certain modifications and equivalents thereof. This disclosure expressly contemplates that various features and aspects of the disclosed configurations can be combined with, or substituted for, one another. Accordingly, the scope of this disclosure should not be limited by the particular disclosed configurations described above, but should be determined only by a fair reading of the claims that follow.

Claims

1. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the

turbine configured to be driven by the primary flow; a generator configured to be driven by the turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a cooling coil disposed on the fluid loop, the cooling coil downstream of the turbine and upstream of the first pump on the fluid loop, the cooling coil configured to condense the primary flow exiting the turbine; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop; a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a reservoir tank on the fluid loop, the reservoir tank containing the fluid, the reservoir tank downstream of the second Venturi device and upstream of the first Venturi device; a first conduit fluidically connected to the reservoir tank and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

2. The system of claim 1, wherein the first Venturi device is configured to heat the primary flow passing through the first Venturi device such that primary flow at least partially phase shifts from the liquid state to the gas state.
3. The system of claim 1, wherein the heater comprises one or more solar tubes, the one or more solar tubes configured to heat the secondary flow of the first Venturi device via solar radiation.
4. The system of claim 3, wherein the first conduit comprises a solar tube manifold connected to the one or more solar tubes and to transfer heat from the one or more solar tubes to the secondary flow in the first conduit.
5. The system of claim 1, wherein the heater comprises a heater cartridge on the first conduit, the heater cartridge configured to heat the secondary flow in the first conduit.
6. The system of claim 5, wherein the heater cartridge is powered by a solar panel assembly configured to generate electricity to heat the heater cartridge.
7. The system of claim 1, wherein the first and second pumps each comprise a motor that is configured to be powered by at least one of the generator or an external power supply.
8. The system of claim 1, wherein the cooling coil is configured to operate using a refrigeration cycle using a refrigerant.
9. The system of claim 8, wherein the refrigerant is CO₂.
10. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow; a generator configured to be driven by the

turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a condenser disposed on the fluid loop, the condenser downstream of the turbine and upstream of the first pump on the fluid loop, the condenser configured to condense the primary flow exiting the turbine; a first Venturi device disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop; a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop, wherein each of the first and the second Venturi devices comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a first conduit fluidically connected to the fluid loop and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

11. The system of claim 10, further comprising a reservoir tank on the fluid loop, the reservoir tank containing the fluid, the reservoir tank downstream of the second Venturi device and upstream of the first Venturi device.

12. The system of claim 11, wherein the secondary flow of the second Venturi flows from the reservoir to the secondary input of the second Venturi device.

13. The system of claim 12, further comprising a second conduit fluidically connected to the reservoir and the secondary input of the second Venturi device, the second conduit configured to direct the secondary flow from the primary flow to the secondary input of the second Venturi device.

14. The system of claim 13, further comprising a third pump disposed on the second conduit, the third pump configured to drive the secondary flow from the primary flow to the secondary input of the second Venturi device.

15. The system of claim 10, wherein the condenser comprises a cooling coil disposed on the first conduit.

16. The system of claim 10, wherein the secondary input is configured to distribute the secondary flow throughout the secondary input.

17. A system for converting ambient thermal energy into electrical energy, the system comprising: a fluid loop configured to circulate a primary flow of a fluid; a turbine disposed on the fluid loop, the turbine configured to be driven by the primary flow; a generator configured to be driven by the turbine to generate electrical energy; a first pump disposed on the fluid loop, the first pump configured to drive the primary flow through the fluid loop; a condenser disposed on the fluid loop, the condenser downstream of the turbine and upstream of the first pump on the fluid loop, the condenser configured to condense the primary flow exiting the turbine; a first Venturi device

disposed on the fluid loop, the first Venturi device downstream of the first pump and upstream of the turbine on the fluid loop, wherein the first Venturi device comprises: an inlet configured to receive the primary flow; an outlet configured to eject the primary flow; and a body disposed between the inlet and the outlet, the body comprising: a converging portion and a diverging portion, wherein a movement of the primary flow through the converging portion and the diverging portion produces a Venturi effect that decreases a temperature of the primary flow upstream of the diverging portion such that thermal energy from an ambient environment outside the body is transferred to the primary flow; and a secondary input disposed between the converging portion and the outlet, the secondary input configured to direct a secondary flow of the fluid into the primary flow at an angle relative to a direction of flow of the primary flow to create a vortex for producing a suction at the inlet to suck the primary flow through the inlet and into the body to decrease the temperature of the primary flow upstream of the diverging portion such that thermal energy from the ambient environment outside the body is transferred to the primary flow, causing the temperature and the pressure of the primary flow to increase through the diverging portion before ejection through the outlet; a first conduit fluidically connected to the fluid loop and the secondary input of the first Venturi device, the first conduit configured to direct the secondary flow from the primary flow to the secondary input of the first Venturi device; a second pump disposed on the first conduit, the second pump configured to drive the secondary flow from the primary flow to the secondary input of the first Venturi device; and a heater disposed on the first conduit, the heater downstream of the second pump on the first conduit, the heater configured to heat the secondary flow of the first Venturi device such that the secondary flow at least partially phase shifts from a liquid state to a gas state.

18. The system of claim 17, further comprising a second Venturi device disposed on the fluid loop, the second Venturi device downstream of the turbine and upstream of the first pump on the fluid loop.

19. The system of claim 17, wherein the fluid loop comprises at least one of tubing or piping.

20. The system of claim 17, wherein the secondary input is adjustable to regulate an input of the secondary flow into the primary flow.
