

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416513
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Dahl; David et al.

Actuator apparatus with light actuated position sensor and secure position verification

Abstract

An actuator apparatus includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity where the set of rod holes are positioned along a line. The actuator apparatus includes a light assembly positioned to light the cavity. The actuator apparatus includes an actuator block with an opening sized to conform to an outer surface of the actuator rod and a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The actuator apparatus includes a verification module with a light modulator that modulates light of the light assembly to transmit a position signal, and a verification circuit that transmits a verification signal in response to the light sensor receiving the position signal.

Inventors: Dahl; David (Cody, WY), Eichstadt; David E. (Northbrook, IL), DeBlieck; Robert Charles (Algonquin, IL)

Applicant: DTL Linear, LLC. (Cody, WY)

Family ID: 1000008819059

Assignee: DTL Linear, LLC (Cody, WY)

Appl. No.: 18/767594

Filed: July 09, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240361157 A1	Oct. 31, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: G01D5/34 (20060101); F16C41/00 (20060101); G01D5/347 (20060101)

U.S. Cl.:

CPC G01D5/347 (20130101); F16C41/007 (20130101);

Field of Classification Search

CPC: G01D (5/34); G01D (5/347); G01D (5/34715); F16C (41/007)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4894533	12/1989	Abe et al.	N/A	N/A
5065012	12/1990	Moriyama et al.	N/A	N/A
6145213	12/1999	Shimano et al.	N/A	N/A
6603640	12/2002	Prater et al.	N/A	N/A
8376381	12/2012	Shalaby et al.	N/A	N/A
8527101	12/2012	Burris et al.	N/A	N/A
8773237	12/2013	Burris et al.	N/A	N/A
9631712	12/2016	Ikeda	N/A	N/A
9638550	12/2016	Vokinger	N/A	N/A
9869347	12/2017	Fujioka	N/A	N/A
10837532	12/2019	Kwaśniewski	N/A	N/A
12031851	12/2023	Dahl	N/A	F16C 41/007
2002/0070334	12/2001	Hasegawa et al.	N/A	N/A
2002/0088933	12/2001	Yu et al.	N/A	N/A
2004/0256546	12/2003	Hsiao et al.	N/A	N/A
2011/0252598	12/2010	Burris et al.	N/A	N/A
2017/0292543	12/2016	Nikolic	N/A	N/A
2021/0325209	12/2020	Baker	N/A	N/A
2022/0065667	12/2021	Ueno et al.	N/A	N/A
2022/0187104	12/2021	Parpajola	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
208474232	12/2018	CN	N/A
9114056	12/1990	DE	N/A
19619113	12/1995	DE	N/A
2459969	12/2009	EP	N/A
60113110	12/1982	JP	N/A
6173004	12/1983	JP	N/A
9704286	12/1996	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/742,931, Non-Final Office Action received Apr. 16, 2025. cited by applicant

Primary Examiner: Pyo; Kevin K

Attorney, Agent or Firm: Kunzler Bean & Adamson

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This patent application is a continuation of U.S. patent application Ser. No. 18/385,546, filed on Oct. 31, 2023, titled “ACTUATOR APPARATUS WITH LIGHT ACTUATED POSITION SENSOR AND SECURE POSITION VERIFICATION,” which is a continuation-in-part application of and claims priority to U.S. patent application Ser. No. 17/742,931 entitled “ACTUATOR APPARATUS WITH PRECISION BEARINGS AND LIGHT SENSOR” and filed on May 12, 2022 for David Dahl, which are incorporated herein by reference.

FIELD

(1) This invention relates to tracking movement and more particularly relates to an actuator apparatus with a light actuated position sensor and secure position verification.

BACKGROUND

(2) Often robotics, assembly lines, medical procedures, etc. require precise movement. Many approaches have been used for tracking movement for precise placement of various devices and for other purposes. In addition, position verification is crucial in some applications where unwanted movement may be catastrophic.

SUMMARY

(3) An apparatus for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes are positioned along a line. The apparatus includes a light assembly positioned to light the cavity and an actuator block with an opening in the actuator block sized to conform to an outer surface of the actuator rod. The actuator block includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The apparatus includes a verification module with a light modulator configured to modulate light of the light assembly to transmit a position signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal.

(4) A system for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. Each rod hole of the set of rod holes is positioned along a line. The system includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening in the actuator block sized to conform to an outer surface of the actuator rod. The system includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The system includes a verification module. The verification module includes a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold, a light modulator configured to modulate light of the light assembly to transmit a position signal in response to the aligned signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal. The system includes a mover apparatus

configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes.

(5) Another apparatus for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes is positioned along a line. The apparatus includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening in the actuator block sized to conform to an outer surface of the actuator rod. The apparatus includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The apparatus includes a verification module with a light modulator configured to modulate light of the light assembly to transmit a position signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal. The apparatus includes a hole counter module configured to increment or decrement a hole counter in response to the position signal, and a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod. The hole counter module increments the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod. The second direction is opposite the first direction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order that the advantages of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:
- (2) FIG. 1 is (a) an actuator apparatus perspective view, (b) an actuator block end view, (c) an actuator rod side view, and (d) an actuator rod end view illustrating a schematic block diagram of an actuator apparatus with precision bearings and light sensors, according to various embodiments;
- (3) FIG. 2 is a section view further illustrating the schematic block diagram of the actuator apparatus of FIG. 1;
- (4) FIG. 3 is (a) an actuator rod end view, (b) an actuator rod side view, (c) an actuator block section view through light sensors, (d) an actuator block section view through ball bearings and springs, and (e) an actuator block side section view illustrating a schematic block diagram of an actuator apparatus with precision bearings and light sensors in four rows spaced around an actuator rod and opening in an actuator block with offset rod holes, according to various embodiments;
- (5) FIG. 4 is (a) an actuator rod end view, (b) an actuator rod side view, (c) an actuator block section view through light sensors, (d) an actuator block section view through ball bearings and springs, and (e) an actuator block side section view illustrating a schematic block diagram of an actuator apparatus with precision bearings and light sensors in four rows spaced around an actuator rod and opening in an actuator block with offset block holes, according to various embodiments;
- (6) FIG. 5 is (a) an actuator rod end view, and (b) an actuator block section view through light sensors illustrating a schematic block diagram of an actuator apparatus with precision bearings and light sensors in three rows spaced around an actuator rod and opening in an actuator block,

according to various embodiments;

(7) FIG. 6 is a partial section view of a schematic block diagram of an actuator apparatus with replaceable ball bearings, according to various embodiments;

(8) FIG. 7 is a schematic block diagram illustrating an actuator rod connected to a mover apparatus via a slot that allows for discrete movement of the actuator rod with respect to the actuator apparatus, according to various embodiments;

(9) FIG. 8 is a schematic block diagram illustrating an application of an actuator apparatus with a fixed actuator rod and moving actuator block, according to various embodiments;

(10) FIG. 9 is a schematic block diagram illustrating an application of an actuator apparatus with a fixed actuator block and moving actuator rod, according to various embodiments;

(11) FIG. 10A is a schematic block diagram illustrating a ball bearing and spring mechanism, according to various embodiments;

(12) FIG. 10B is a schematic block diagram illustrating a ball bearing and spring mechanism with an alternate to using a ball bearing, according to various embodiments;

(13) FIG. 11 is (a) a side transparent view of an actuator apparatus, (b) is a cross section view of an actuator rod, and (c) a cross section view of an actuator block for a rotary actuator apparatus, according to various embodiments;

(14) FIG. 12 is (a) a side transparent view of an actuator apparatus with a verification module, (b) is a cross section view of an actuator rod, and (c) a cross section view of an actuator block for a rotary actuator apparatus without ball bearings, according to various embodiments;

(15) FIG. 13 is (a) a side transparent view of an actuator apparatus with a verification module, (b) is a cross section view of an actuator rod, and (c) a cross section view of an actuator block for a rotary actuator apparatus with ball bearings, according to various embodiments;

(16) FIG. 14 is a schematic block diagram of an apparatus with a verification module for securely verifying position of a rod hole with respect to a light sensor, according to various embodiments;

(17) FIG. 15 is a schematic block diagram of another apparatus with a verification module for securely verifying position of a rod hole with respect to a light sensor, according to various embodiments;

(18) FIG. 16 is (a) a side transparent view and (b) a top view of an actuator apparatus with a light source in line with a light sensor, according to various embodiments; and

(19) FIG. 17 is a side transparent view an actuator apparatus with a light source offset from a light sensor, according to various embodiments.

DETAILED DESCRIPTION

(20) Reference throughout this specification to “one embodiment,” “an embodiment,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment, but mean “one or more but not all embodiments” unless expressly specified otherwise. The terms “including,” “comprising,” “having,” and variations thereof mean “including but not limited to” unless expressly specified otherwise. An enumerated listing of items does not imply that any or all of the items are mutually exclusive and/or mutually inclusive, unless expressly specified otherwise. The terms “a,” “an,” and “the” also refer to “one or more” unless expressly specified otherwise.

(21) Furthermore, the described features, advantages, and characteristics of the embodiments may be combined in any suitable manner. One skilled in the relevant art will recognize that the embodiments may be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments.

(22) These features and advantages of the embodiments will become more fully apparent from the following description and appended claims, or may be learned by the practice of embodiments as

set forth hereinafter. As will be appreciated by one skilled in the art, aspects of the present invention may be embodied as a system and/or apparatus with controls embodied as a method or computer program product. Accordingly, aspects of controls for the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module,” or “system.” Furthermore, aspects of the controls for the present invention may take the form of a computer program product embodied in one or more computer readable medium(s) having program code embodied thereon.

(23) Many of the functional units for the controls described in this specification have been labeled as modules, in order to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very large scale integrated (“VLSI”) circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as a field programmable gate array (“FPGA”), programmable array logic, programmable logic devices or the like.

(24) Modules may also be implemented in software for execution by various types of processors. An identified module of program code may, for instance, comprise one or more physical or logical blocks of computer instructions which may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together but may comprise disparate instructions stored in different locations which, when joined logically together, comprise the module and achieve the stated purpose for the module. Indeed, a module of program code may be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Where a module or portions of a module are implemented in software, the program code may be stored and/or propagated on in one or more computer readable medium(s).

(25) The computer program product may include a computer readable storage medium (or media) having computer readable program instructions thereon for causing a processor to carry out aspects of the present invention. The computer readable storage medium may be, for example, but is not limited to, an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination of the foregoing. A non-exhaustive list of more specific examples of the computer readable storage medium includes the following: a portable computer diskette, a hard disk, a random access memory (“RAM”), a read-only memory (“ROM”), an erasable programmable read-only memory (“EPROM” or Flash memory), a static random access memory (“SRAM”), a portable compact disc read-only memory (“CD-ROM”), a digital versatile disk (“DVD”), a memory stick, a floppy disk, and any suitable combination of the foregoing. A computer readable storage medium, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire.

(26) As used herein, a list with a conjunction of “and/or” includes any single item in the list or a combination of items in the list. For example, a list of A, B and/or C includes only A, only B, only C, a combination of A and B, a combination of B and C, a combination of A and C or a combination of A, B and C. As used herein, a list using the terminology “one or more of” includes any single item in the list or a combination of items in the list. For example, one or more of A, B and C includes only A, only B, only C, a combination of A and B, a combination of B and C, a combination of A and C or a combination of A, B and C. As used herein, a list using the terminology “one of” includes one and only one of any single item in the list. For example, “one of A, B and C” includes only A, only B or only C and excludes combinations of A, B and C.

(27) An actuator apparatus with precision bearings and light sensor includes an actuator rod with an

interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes is positioned in a straight line. The apparatus includes a light assembly that is positioned to light the cavity. The apparatus includes an actuator block that includes an opening extending through the actuator block sized to conform to an outer surface of the actuator rod and a set of block holes in the opening. Spacing between the block holes matches spacing between the rod holes. The actuator block includes a light sensor positioned in a block hole of the set of block holes to sense light coming through a rod hole aligned with the block hole and a ball bearing for each block hole of the set of block holes without a light sensor and extending partially through the corresponding block hole.

(28) In some embodiments, the set of rod holes is a first set of rod holes, and the set of block holes is a first set of block holes, and the apparatus includes one or more additional sets of rod holes. The first set of rod holes and the one or more additional sets of rod holes are a plurality of sets of rod holes and are spaced equidistant around the actuator rod. In the embodiments, the apparatus includes one or more additional sets of block holes. The first set of block holes and the one or more additional sets of block holes are a plurality of sets of block holes and are spaced equidistant around the opening to align with the sets of rod holes of the plurality of sets of rod holes. In the embodiments, the apparatus includes a light sensor for each of the additional sets of block holes, each positioned in a block hole, and each block hole of the one or more additional sets of block holes without a light sensor includes a ball bearing.

(29) In other embodiments, the rod holes of each of the one or more additional sets of rod holes is offset from the rod holes of the first set of rod holes and from each other in a direction along the first set of rod holes and each block hole of the one or more additional sets of block holes aligns with a block hole of the first set of block holes in a plane running perpendicular to a direction of the first set of block holes such that as the actuator block moves with respect to the actuator rod, rod holes of each of the plurality of sets of rod holes align with block holes at different times. In other embodiments, the block holes of the one or more additional sets of block holes is offset from the block holes of the first set of block holes and from each other in a direction of the first set of block holes and each rod hole of the one or more additional sets of rod holes aligns with a rod hole of the first set of rod holes in a plane running perpendicular to a direction of the first set of rod holes such that as the actuator block moves with respect to the actuator rod, rod holes of each of the plurality of sets of rod holes align with block holes at different times.

(30) In other embodiments, the rod holes of each of the one or more additional sets of rod holes align with each other and the first set of rod holes in a direction of a plane running perpendicular to a direction along the first set of rod holes and the block holes of each of the one or more additional sets of block holes align with each other and block holes of the first set of block holes in a direction of a plane running perpendicular to a direction along the first set of block holes such that the rod holes of the first set of rod holes and the one or more additional sets of rod holes align with block holes of the first set of block holes and each of the one or more additional sets of block holes at a same time.

(31) In some embodiments, the apparatus includes a spring mechanism behind each ball bearing pushing the ball bearing toward the opening where, as the actuator block moves relative to the actuator rod and rod holes align with block holes, each ball bearing extends into a rod hole. In other embodiments, the apparatus includes a hole counter module configured to increment or decrement a hole counter in response to the light sensor sensing light during alignment of a rod hole with a block hole. In further embodiments, the apparatus includes a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod. The hole counter module increments the hole counter in response to the light sensor sensing light and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the light sensor sensing light and the direction detector determining that the actuator block is moving in a

second direction with respect to the actuator rod. The second direction is opposite the first direction.

(32) In some embodiments, the apparatus includes a mover apparatus configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. In other embodiments, the mover apparatus moves the actuator block along the actuator rod or the mover apparatus moves the actuator rod through the actuator block. In other embodiments, where the mover apparatus moves the actuator block along the actuator rod, the actuator rod is in a fixed position. In other embodiments, the mover apparatus includes an internal mover within the actuator block configured to engage the actuator rod, a separate mover component external to the actuator block configured to push and pull the actuator block with respect to the actuator rod, and/or a linear motor configured to move the actuator block with respect to the actuator rod magnetically.

(33) In other embodiments, the mover apparatus is configured to maintain the actuator rod in alignment with the actuator block such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. In other embodiments, the mover apparatus comprises free movement in a direction of movement of the actuator block with respect to the actuator rod. The free movement enables ball bearings positioned in block holes without a sensor to snap forward from one set of rod holes to another set of rod holes as the mover apparatus advances the actuator block with respect to the actuator rod.

(34) In some embodiments, a shape of the actuator rod and a shape of the opening of the actuator block maintain the actuator rod in alignment with the actuator block such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. In other embodiments, the actuator rod is linear and the rod holes run in a direction along a length of the actuator rod and the actuator block moves with respect to the actuator rod in a direction along the length of the actuator rod. In other embodiments, the actuator rod is round and the rod holes run in a direction around a circumference of the actuator rod and the actuator block rotates with respect to the actuator rod in a direction around the circumference of the actuator rod.

(35) In some embodiments, the apparatus includes a bearing track within the actuator block between block holes. The actuator block includes ball bearings within the bearing track in excess of the block holes of the set of block holes. In the embodiments, the apparatus includes a bearing mover configured to move the ball bearings in the bearing track such that, for each block hole in the actuator block, a ball bearing in a block hole is moved out from over the block hole of the block hole and another ball bearing is moved into place over the block hole by action of the bearing mover.

(36) A system with an actuator apparatus with precision bearings and light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes are positioned in a straight line. The system includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening extending through the actuator block sized to conform to an outer surface of the actuator rod, a set of block holes in the opening. Spacing between the block holes matches spacing between the rod holes, a light sensor positioned in a block hole of the set of block holes to sense light coming through a rod hole aligned with the block hole, a ball bearing for each block hole of the set of block holes without a light sensor and extending partially through the corresponding block hole, and a spring mechanism behind each ball bearing pushing the ball bearing toward the opening. As the actuator block moves relative to the actuator rod and rod holes align with block holes, each ball bearing extends into a rod hole.

(37) The system includes a hole counter module configured to increment or decrement a hole counter in response to the light sensor sensing light during alignment of a rod hole with a block hole. The system includes a mover apparatus configured to move the actuator block with respect to

the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. The system includes a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod. The hole counter module increments the hole counter in response to the light sensor sensing light and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the light sensor sensing light and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod, the second direction opposite the first direction.

(38) Another actuator apparatus with precision bearings and light sensor includes an actuator rod with an interior cavity and a plurality of sets of rod holes. Each rod hole extends through the actuator rod to the cavity. Each set of rod holes is positioned in a straight line along a length of the actuator rod. The sets of rod holes are spaced evenly around a circumference of the actuator rod. The apparatus includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening extending through the actuator block sized to conform to an outer surface of the actuator rod, and a plurality of sets of block holes in the opening. Spacing between the block holes matches spacing between the rod holes and each set of block holes aligned with a set of rod holes in a direction along the length of the actuator rod. The actuator block includes a plurality of light sensors with a light sensor for each set of block holes. The light sensor for a set of block holes is positioned in a block hole of the set of block holes to sense light coming through a rod hole aligned with the block hole.

(39) The actuator apparatus includes a ball bearing for each block hole of each of the sets of block holes without a light sensor that extends partially through the corresponding block hole, and a spring mechanism behind each ball bearing pushing the ball bearing toward the opening. As the actuator block moves relative to the actuator rod and rod holes align with block holes, each ball bearing extends into a rod hole. The apparatus includes a hole counter module configured to increment or decrement a hole counter in response to a light sensor of the plurality of light sensors sensing light during alignment of a rod hole with a block hole.

(40) In some embodiments, each set of rod holes of the plurality of sets of rod holes is offset from other sets of rod holes of the plurality of rod holes in a direction along the length of the actuator rod and each set of block holes of the plurality of sets of block holes aligns with other sets of block holes of the plurality of block holes in a direction around a circumference of the actuator rod, or each set of block holes of the plurality of sets of block holes is offset from other sets of block holes of the plurality of block holes in a direction along the length of the actuator rod and each set of rod holes of the plurality of sets of rod holes aligns with other sets of rod holes of the plurality of rod holes in a direction around a circumference of the actuator rod, such that as the actuator block moves with respect to the actuator rod, rod holes of a first set of rod holes of the plurality of rod holes align with corresponding block holes at a different time than rod holes of other sets of rod holes align with corresponding block holes.

(41) An apparatus for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes are positioned along a line. The apparatus includes a light assembly positioned to light the cavity and an actuator block with an opening in the actuator block sized to conform to an outer surface of the actuator rod. The actuator block includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The apparatus includes a verification module with a light modulator configured to modulate light of the light assembly to transmit a position signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal.

(42) In some embodiments, the verification module includes a position module configured to

transmit an aligned signal in response to light at the light sensor reaching an alignment threshold and the light modulator transmits the position signal in response to the aligned signal. In other embodiments, the light assembly includes a fiber optic cable positioned with an end in the cavity and the light sensor comprises a receiver configured to receive light from the fiber optic cable. In other embodiments, the light assembly includes a light emitting diode (“LED”) positioned in the cavity. In other embodiments, the light assembly includes a light source positioned to align with the light sensor through a rod hole of the set of rod holes.

(43) In some embodiments, the cavity includes a surface that reflects light from the light assembly and/or the light assembly includes a light source positioned to illuminate the cavity and light within the cavity reaches the light sensor upon alignment of a rod hole of the set of rod holes with the light sensor. In other embodiments, the position signal is a digital signal. In other embodiments, the position signal includes a code unique to the actuator rod and/or the light assembly. In the embodiments, light sensor receiving the position signal includes receiving the code unique to the actuator rod and the verification signal includes the code unique to the actuator rod. In other embodiments, the verification signal includes an indication of alignment of a rod hole with the light sensor, a location code comprising information indicative of a location of the actuator rod with respect to the actuator block, and/or a unique code transmitted in the position signal.

(44) In some embodiments, the actuator block further includes one or more block holes in the opening of the actuator block. Each of the one or more block holes is positioned to align with each of the set of rod holes as the actuator rod moves with respect to the actuator block. The light sensor is positioned in a block hole of the one or more block holes and is configured to sense light coming through a rod hole aligned with the block hole. In other embodiments, the one or more block holes are a set of block holes and spacing between the block holes matches spacing between the rod holes and the apparatus includes a ball bearing for each block hole of the set of block holes without a light sensor. Each ball bearing extends partially through a block hole corresponding to the ball bearing. In further embodiments, the apparatus includes a spring mechanism behind each ball bearing pushing the ball bearing toward the opening. As the actuator block moves relative to the actuator rod and rod holes align with block holes, each ball bearing extends into a rod hole.

(45) In other embodiments, the set of rod holes is a first set of rod holes, and the set of block holes is a first set of block holes and the apparatus includes one or more additional sets of rod holes. The first set of rod holes and the one or more additional sets of rod holes are a plurality of sets of rod holes and are spaced equidistant around the actuator rod. In the embodiments, the apparatus includes one or more additional sets of block holes where the first set of block holes and the one or more additional sets of block holes are a plurality of sets of block holes and are spaced equidistant around the opening to align with the sets of rod holes of the plurality of sets of rod holes. In the embodiments, the apparatus includes a light sensor for each of the additional sets of block holes. Each light sensor is positioned in a block hole. Each block hole of the one or more additional sets of block holes without a light sensor includes a ball bearing.

(46) In further embodiments, the apparatus includes a bearing track within the actuator block between block holes. The actuator block includes ball bearings within the bearing track in excess of the block holes of the set of block holes, and the apparatus includes a bearing mover configured to move the ball bearings in the bearing track such that, for each block hole in the actuator block, a ball bearing in a block hole is moved out from over the block hole of the block hole and another ball bearing is moved into place over the block hole by action of the bearing mover.

(47) In some embodiments, the verification module includes a hole counter module configured to increment or decrement a hole counter in response to the position signal, and/or a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod. In the embodiments, the hole counter module increments the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter

in response to the position signal and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod. The second direction is opposite the first direction.

(48) In some embodiments, the apparatus includes a mover apparatus configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. In other embodiments, a shape of the actuator rod and a shape of the opening of the actuator block maintain the actuator rod in alignment with the actuator block such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes. In other embodiments, the actuator rod is linear and the rod holes run in a direction along a length of the actuator rod and the actuator block moves with respect to the actuator rod in a direction along the length of the actuator rod. In other embodiments, the actuator rod is round and the rod holes run in a direction around a circumference of the actuator rod and the actuator block rotates with respect to the actuator rod in a direction around the circumference of the actuator rod.

(49) A system for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. Each rod hole of the set of rod holes is positioned along a line. The system includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening in the actuator block sized to conform to an outer surface of the actuator rod. The system includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The system includes a verification module. The verification module includes a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold, a light modulator configured to modulate light of the light assembly to transmit a position signal in response to the aligned signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal. The system includes a mover apparatus configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes.

(50) Another apparatus for securely verifying position of a rod hole with respect to a light sensor includes an actuator rod with an interior cavity and a set of rod holes. Each rod hole of the set of rod holes extends through the actuator rod to the cavity. The set of rod holes is positioned along a line. The apparatus includes a light assembly positioned to light the cavity and an actuator block. The actuator block includes an opening in the actuator block sized to conform to an outer surface of the actuator rod. The apparatus includes a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor. The apparatus includes a verification module with a light modulator configured to modulate light of the light assembly to transmit a position signal, and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal. The apparatus includes a hole counter module configured to increment or decrement a hole counter in response to the position signal, and a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod. The hole counter module increments the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod. The second direction is opposite the first direction.

(51) In some embodiments, the verification module includes a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold

and the light modulator transmits the position signal in response to the aligned signal.

(52) FIG. 1 is (a) an actuator apparatus perspective view, (b) an actuator block end view, (c) an actuator rod side view, and (d) an actuator rod end view illustrating a schematic block diagram of an actuator apparatus **100** with precision bearings and light sensors, according to various embodiments. FIG. 2 is a section view A-A' further illustrating the schematic block diagram of the actuator apparatus **100** of FIG. 1. The actuator apparatus **100** includes an actuator rod **102** with an interior cavity **110** and a set of rod holes **106**. Each rod hole **106** of the set of rod holes **106** extends through the actuator rod **102** to the cavity **110**. The set of rod holes **106** are positioned in a straight line. In some embodiments, the actuator apparatus **100** is an encoder configured to precisely report position of the actuator rod **102** with respect to an actuator block **104**.

(53) The actuator apparatus **100** includes a light assembly **112** positioned to light the cavity **110**. Light from the light assembly **112** shines through the rod holes **106** because the rod holes **106** extend through the actuator rod **102** into the cavity **110**. In some embodiments, the light assembly **112** includes a point source at an end of the actuator rod **102**. In other embodiments, the light assembly **112** is located further inside the cavity **110** of the actuator rod **102**. In other embodiments, the light assembly **112** includes multiple light sources, such as light emitting diodes ("LEDs"). In other embodiments, the multiple light sources are spread out within the actuator rod **102**. In other embodiments, the light assembly **112** is located in the actuator block opposite from a light sensor **120** and the actuator rod **102** includes rod holes **106** on either side that align to allow light from the light assembly **112** in on one side of the actuator block **104** to shine across to the light sensor **120** through two aligned rod holes **106**.

(54) In some embodiments, the light assembly **112** includes point source for light, such as a single LED, that is capable of shining light in multiple directions. In some embodiments, the light assembly **112** produces light within a particular spectrum of light, such as visible light, colored light of a specific wavelength, infrared light, ultraviolet light, and the like. One of skill in the art will recognize other configurations for the light assembly **112** and other locations for part or all of the light assembly **112**.

(55) The actuator block **104** includes an opening **108** that extends through the actuator block **104** and is sized to conform to an outer surface of the actuator rod **102**. The actuator rod **102** in the actuator apparatus **100** of FIG. 1 is round so the opening **108** is also round. In other embodiments, the actuator rod **102** has a different shaped cross section, such as an oval, square, rectangle, etc. and the opening **108** is similarly shaped and is slightly larger than an outer shape of the actuator rod **102** so that the actuator rod **102** is able to pass through the opening **108**. An actuator rod **102** shaped differently than with a round cross section, in some embodiments, provides a mechanism to maintain the actuator rod **102** and actuator block **104** in a same alignment while the actuator rod **102** passes through the actuator block **104**. In some embodiments, the actuator rod **102** and opening **108** in the actuator block **104** include a protrusion and corresponding groove, a key and a corresponding channel, or the like to keep the actuator rod **102** and actuator block **104** in alignment as the actuator rod **102** passes through the actuator block **104**.

(56) The actuator block **104** includes two sets of block holes **114** in the opening **108**. Other embodiments include one set of block holes **114** or more than two sets of block holes **114**, as depicted in FIGS. 3-5. Spacing between the block holes **114** matches spacing between the rod holes **106**. The actuator block **104** includes a light sensor **120** positioned in a block hole **114** of each of the sets of block holes **114** to sense light coming through a rod hole **106** aligned with the block hole **114**. In other embodiments, the actuator block **104** includes sets of block holes **114** without a light sensor **120** which are used to reduce friction, used for alignment, etc. For example, the actuator block **104** may include four sets of block holes **114** and the actuator rod **102** also includes four sets of rod holes **106** aligned with the block holes **114** and only a single set of block holes **114** includes a light sensor **120**. One of skill in the art will recognize other configurations with multiple sets of rod holes **106** and corresponding block holes **114** in an actuator rod **102** where one or more of the

sets of block holes **114** include a light sensor **120**.

(57) In some embodiments, the actuator apparatus **100** includes a hole counter module **122** configured to increment or decrement a hole counter in response to the light sensor **120** sensing light during alignment of a rod hole **106** with a block hole **114**. In some embodiments, the hole counter module **122** includes a zeroing function that resets the hole counter to zero. In some examples, the zeroing function zeros out the hole counter when the actuator rod **102** is in a particular position with respect to the actuator block **104**. In other embodiments, the zeroing function zeros out the hole counter before the actuator rod **102** is inserted into the actuator block **104**. One of skill in the art will recognize other times for the zeroing function to zero out the hole counter.

(58) In some embodiments, the actuator apparatus **100** includes a direction detector **124** configured to determine a direction of movement of the actuator block **104** with respect to the actuator rod **102**. The hole counter module **122** increments the hole counter in response to the light sensor **120** sensing light and the direction detector **124** determining that the actuator block **104** is moving in a first direction with respect to the actuator rod **102** and the hole counter module **122** decrements the hole counter in response to the light sensor **120** sensing light and the direction detector **124** determining that the actuator block **104** is moving in a second direction with respect to the actuator rod **102** where the second direction opposite the first direction.

(59) In some embodiments, the size of the rod holes **106** and block holes relative to spacing between each of the rod holes **106**, spacing between each of the block holes **114**, and/or a size of a gap between the actuator rod **102** and opening **108** are configured so that the one or more light sensors **120** detect light from the light assembly **112** when a rod hole **106** aligns with a block hole **114** and do not detect light from the light assembly **112** with a rod hole **106** not aligned with a block hole **114**. In some embodiments, the light sensor **120** typically begins to sense light just before alignment and/or upon partial alignment of the rod holes **106** and block holes **114** and light intensity reaches a peak upon full alignment. Typically, as a rod hole **106** passes a block hole **114**, light intensity will increase to a peak value and then decrease to zero or at least to a minimum value. In some embodiments, the hole counter module **122** registers alignment of a rod hole **106** with a block hole **114** when light intensity sensed by the light sensors **120** reaches a light threshold.

(60) The actuator block **104** includes a ball bearing **116** for each block hole **114** of the set of block holes without a light sensor **120** that extends partially through the corresponding block hole **114**. The size of the opening **108** in the actuator block **104** relative to the actuator rod **102** along with the size of the block holes **114** and the ball bearings **116** are such that, for each ball bearing **116** of the actuator block **104**, the ball bearing **116** extend partially into a rod hole **106** when the rod hole **106** is aligned with the block hole **114** from which the ball bearing **116** extends.

(61) The actuator block **104** includes a spring mechanism **118** behind each ball bearing **116** pushing the ball bearing **116** toward the opening **108**. As the actuator block **104** moves relative to the actuator rod **102** and rod holes **106** align with block holes **114**, each ball bearing **116** extends into a rod hole **106**. As the actuator block **104** moves further relative to the actuator rod **102**, the ball bearings **116** retract slightly and then extend into a next rod hole **106**. In some embodiments, where the actuator rod **102** extends through the opening **108** past a point where rod holes **106** exist, the ball bearings **116** extend to a point where edges of the corresponding block hole **114** retain the ball bearing **116** from popping out of the block hole **114**. A possible configuration is depicted in FIG. **10A**.

(62) The spring mechanism **118**, in some embodiments, is a linear spring. In other embodiments, the spring mechanism **118** includes a spring in another form, such as an extension spring, a torsion spring, or the like. In some embodiments, the spring mechanism **118** is a coil spring, a flat spring, a leaf spring, a molded spring, a Belleville spring, or the like. In other embodiments, the spring mechanism **118** includes other elements, such as a sleeve, an end cap on the sleeve, or the like to keep the spring aligned with the corresponding block hole **114**, from keeping the spring from

popping out when a ball bearing **116** is not present over the block hole **114**, etc. In other embodiments, the spring mechanism **118** includes another device that provides a spring force that is not a metal, such as a compressible rubber, or the like.

(63) While the ball bearing **116** and spring mechanism **118** are depicted in FIG. 2 as a round ball and a spring behind the round ball, other embodiments include other designs. In some embodiments, the ball bearing **116**/spring mechanism **118** include a sleeve with a cap with a spring in the sleeve where the sleeve extends through a corresponding block hole **114** towards the actuator rod **102**. In some examples, the cap of a sleeve is rounded at least in a direction of movement of the actuator rod **102** to provide smooth movement of the actuator rod **102** without a sleeve and cap from catching in a rod hole **106**, as depicted in FIG. 10B.

(64) The ball bearings **116** extending into rod holes **106** provides a mechanism for the actuator rod **102** to move to a stable location during light sensing when ball bearings **116** are resting in rod holes **106**, and then to move along to next rod holes **106** as the actuator block **104** moves with respect to the actuator rod **102**. The ball bearings **116** provide a mechanism to allow movement of the actuator rod **102** with respect to the actuator block **104** in a precise way while discretely moving from rod hole **106** to rod hole **106**.

(65) The actuator apparatus **100**, in some embodiments, includes a mover apparatus **126** configured to move the actuator block **104** with respect to the actuator rod **102** in a direction such that lines connecting each rod hole **106** of the set of rod holes **106** maintain alignment with lines connecting each block hole **114** of the set of block holes **114**. For the actuator apparatus **100** of FIGS. 1 and 2, the actuator rod **102** moves through the actuator block **104** along a length of the actuator rod **102** as indicated by the arrow **132** in FIG. 2. In some embodiments, the actuator rod **102** is fixed and the mover apparatus **126** moves the actuator block **104**. In other embodiments, the actuator block **104** is fixed and the mover apparatus **126** moves the actuator rod **102**. In other embodiments, the mover apparatus **126** moves both the actuator rod **102** and the actuator block **104**.

(66) The mover apparatus **126**, in some embodiments, is located in the actuator block **104**. In some examples, the mover apparatus **126** includes wheels, gears, a gearbox, etc. to move the actuator block **104** from within the actuator block **104**. In other embodiments, the mover apparatus **126** is external to the actuator block and/or actuator rod **102**. In some examples, the mover apparatus **126** includes a gear drive, a worm drive, a pneumatic drive, a chain drive, a linear motor, or any other powered mechanism to move the actuator rod **102** with respect to the actuator block **104**.

(67) In some embodiments, the direction detector **124** is connected to the mover apparatus **126** and receives or derives a direction of the actuator rod **102** with respect to the actuator block **104** from the mover apparatus **126**. In other embodiments, the direction detector **124** is in the mover apparatus **126**. In other embodiments, the direction detector **124** is a signal from the mover apparatus **126**. One of skill in the art will recognize other implementations of the direction detector **124** and/or other ways for the direction detector **124** to derive a direction signal.

(68) In some embodiments, the mover apparatus **126** is controlled by an actuator controller **128**. The actuator controller **128** is depicted external to the actuator block **104** but may be internal to the actuator block **104**. In some embodiments, the actuator controller **128** includes controls, which may be levers, buttons, keys, a display, or other device for a person to control the actuator apparatus. In other embodiments, the actuator controller **128** is controlled by signals from other controls, such as a robotic controller that controls one or more robotic arms, movers, etc. attached to the actuator block **104** and/or actuator rod **102**. In other embodiments, the actuator apparatus **100** is part of an assembly process or other process and the actuator controller **128** is controlled by or is part of a controller for the process. In some embodiments, the actuator controller **128** is connected to the hole counter module **122**, the direction detector **124**, the mover apparatus **126**, the light assembly **112**, the light sensors **120**, and/or other component, which may be connected via wiring **130** or other conductors, and uses information from the direction detector **124**, hole counter module **122**, and other sources to control the mover apparatus **126**. One of skill in the art will recognize other

implementations of an actuator controller **128**.

(69) In some embodiments, the mover apparatus **126** facilitates manual movement of the actuator block **104** with respect to the actuator rod **102**. In some examples, the mover apparatus **126** includes handles, buttons, grips, etc. to allow a user to move the actuator block **104** with respect to the actuator rod **102**. For example, the actuator apparatus **100** may be used in a medical process and a surgeon manually moves the actuator rod **102** with respect to the actuator block **104** for precise placement of a medical device, for precise movement of a scalpel, scissors, etc. One of skill in the art will recognize other uses for the actuator apparatus **100**.

(70) As used herein, the phrasing of “the actuator rod **102** moving with respect to the actuator block **104**” means the same as the phrasing of “the actuator block **104** moving with respect to the actuator rod **102**” and each phrasing is intended only to convey movement of the actuator rod **102** relative to the actuator block **104** and has no bearing on which of the actuator rod **102** and the actuator block **104** is fixed.

(71) FIG. 3 is (a) an actuator rod **302** end view, (b) an actuator rod **302** side view, (c) an actuator block **304** section view through light sensors **320**, (d) an actuator block **304** section view through ball bearings **316** and springs **318**, and (e) an actuator block **304** side section view illustrating a schematic block diagram of an actuator apparatus **300** with precision ball bearings **316** and light sensors **320** in four rows spaced around an actuator rod **302** and opening **308** in an actuator block **304** with offset rod holes **306**, according to various embodiments. The actuator rod **302**, actuator block **304**, rod holes **306**, opening **308** in the actuator block **304**, cavity **310** in the actuator rod **302**, light assembly **312**, block holes **314**, ball bearings **316**, springs **318**, and light sensors **320** are substantially similar to the actuator rod **102**, actuator block **104**, rod holes **106**, opening **108** in the actuator block **104**, cavity **110** in the actuator rod **102**, light assembly **112**, block holes **114**, ball bearings **116**, spring mechanism **118**, and light sensors **120** of the actuator apparatus **100** of FIGS. 1 and 2.

(72) In the actuator apparatus **300** of FIG. 3, there are four sets of rod holes **306** spaced evenly around the actuator rod **302** and four sets of block holes **314** with a same spacing around the opening **308** of the actuator block **304**. In the embodiment of FIG. 3, each set of rod holes **306** is offset from other rod holes **306**, as depicted in FIG. 3(b), while the sets of block holes **314** and light sensors **320** are aligned, as depicted in FIG. 3(c), so that as the actuator block **304** moves with respect to the actuator rod **302**, a rod hole **306** of a first set of rod holes **306** will pass a light sensor **320** at a different time than a rod hole **306** of a second set of rod holes **306** passes a different light sensor **320**. Note that the cross section in FIG. 3(a) is figurative to show spacing of the rod holes **306** around the actuator rod **102** and are offset as depicted in FIG. 3(b).

(73) In the embodiment of FIG. 3, the sets of rod holes **306** are offset in a pattern. In FIG. 3(b), the rod holes **306** of the actuator rod **302** that are in the center that are solid are on a first side of the actuator rod **302** and the rod holes **306** that are in the center of the actuator rod **302** that are dashed are on a side of the actuator rod **302** opposite the first side. Looking at the cross section of the actuator rod **302** in FIG. 3(a), if a rod hole **306** at the top passes a light sensor **320** at the top of the opening **308** of the actuator block **304** first, a rod hole **306** on the left of the cross section of FIG. 3(a) will pass a light sensor **320** on the left side of the opening **308** of the actuator block **304**, then a rod hole **306** at the bottom of the actuator rod **302** will pass a light sensor **320** at the bottom of the opening **308** of the actuator block **304**, and then a rod hole **306** on the right side will pass a light sensor **320** on the right side of the opening **308** of the actuator block **304**. Spacing between offset rod holes **306** is represented in FIG. 3(b) as “W” and spacing between block holes **314** is then 4 W.

(74) In other embodiments, the rod holes **306** are offset in a different pattern, such as two sets of rod holes **306** opposite each other are aligned while two other sets of rod holes **306** are aligned with each other but offset from the other two sets of aligned rod holes **306**. One of skill in the art will recognize other ways to offset rod holes **306** for various purposes.

(75) An advantage of offset rod holes **306** is increased precision because the rod holes **306** have to

travel a shorter distance before a light sensor **320** detects a next passing of a rod hole **306** than the embodiment of FIGS. **1** and **2**. In the embodiment of FIG. **3**, if a rod hole **306** passes a first light sensor **320**, three other rod holes **306** pass different light sensors **320** before alignment of next rod hole **306** passes the first light sensor **320** again. The more sets of rod holes **306** spaced around the actuator rod **302** the more precision that may be provided for movement of the actuator rod **302** with respect to the actuator block **304**.

(76) In another embodiment, with rod holes **306** offset as depicted in FIG. **3(b)**, direction of movement of the actuator rod **302** may be tracked by tracking a sequence, clockwise or counterclockwise, of when each light sensor **320** detects a rod hole **306**. If the sequence is in a clockwise pattern, the actuator rod **302** is moving in a first direction with respect to the actuator block **304** and if the sequence is counterclockwise, the actuator rod **302** is moving in a second direction with respect to the actuator block **304**. In some embodiments, a direction detector **124** determines direction of the actuator rod **302** with respect to the actuator block **304** using the sequence of when light sensors **320** detect passing of a rod hole **306**.

(77) FIG. **4** is (a) an actuator rod **402** end view, (b) an actuator rod **402** side view, (c) an actuator block **404** section view through light sensors **420**, (d) an actuator block **404** section view through ball bearings **416** and springs **418**, and (e) an actuator block **404** side section view illustrating a schematic block diagram of an actuator apparatus **400** with precision ball bearings **416** and light sensors **420** in four rows spaced around an actuator rod **402** and opening **308** in an actuator block **404** with offset block holes **414**, according to various embodiments. The actuator rod **402**, actuator block **404**, rod holes **406**, opening **408** in the actuator block **404**, cavity **410** in the actuator rod **402**, light assembly **412**, block holes **414**, ball bearings **416**, springs **418**, and light sensors **420** are substantially similar to the actuator rod **102**, actuator block **104**, rod holes **106**, opening **108** in the actuator block **104**, cavity **110** in the actuator rod **102**, light assembly **112**, block holes **114**, ball bearings **116**, spring mechanism **118**, and light sensors **120** of the actuator apparatus **100** of FIGS. **1** and **2**.

(78) In FIG. **4**, the block holes **414** are offset while the rod holes **406** are aligned in a direction of along a length of the actuator rod **402**. In the embodiment of FIG. **4**, the sets of block holes **414** are offset in a pattern. In FIG. **4(e)**, the block holes **414** of the actuator block **404** that are in the center that are solid are on a first side of the opening **408** of the actuator block **404** and the block holes **414** that are in the center of the opening **408** of the actuator block **404** in a same row and that are dashed are on a side of the opening **408** opposite the first side, as depicted in FIGS. **4(c)** and **4(d)**.

(79) As with FIG. **3**, looking at the cross section of the actuator rod **402** in FIG. **4(a)**, if a rod hole **406** at the top passes a light sensor **420** at the top of the opening **408** of the actuator block **404** first, a rod hole **406** on the left of the cross section of FIG. **4(a)** will pass a light sensor **420** on the left side of the opening **408** of the actuator block **404**, then a rod hole **406** at the bottom of the actuator rod **402** will pass a light sensor **420** at the bottom of the opening **408** of the actuator block **404**, and then a rod hole **406** on the right side will pass a light sensor **420** on the right side of the opening **408** of the actuator block **404**. Spacing between offset block holes **414** is represented in FIG. **4(c)** as “W” and spacing between rod holes **406** is then 4 W.

(80) Offset of the block holes **414** as in FIG. **4** has a same ability to increase precision as offsetting the rod hole **306** as in FIG. **3**. Again, direction of the actuator rod **402** can be tracked by tracking a sequence of detection of rod holes **406** by the light sensors **420**. The cross sections of FIGS. **4(c)** and **4(d)** are figurative to show spacing of the light sensors **420**, ball bearings **416**, and spring mechanisms **418** around the opening **408** of the actuator block **404** and are not intended to be accurate cross sections.

(81) FIG. **5** is (a) an actuator rod **502** end view, and (b) an actuator block **504** section view through light sensors **520** illustrating a schematic block diagram of an actuator apparatus **500** with precision bearings and light sensors **520** in three rows spaced around an actuator rod **502** and opening **508** in an actuator block **504**, according to various embodiments. FIG. **5** illustrates three rows of sets of

rod holes **506** instead of four rows, as in FIGS. **3** and **4**. The actuator apparatus **500** of FIG. **5** may have less precision of movement tracking than the actuator apparatuses **300**, **400** of FIGS. **3** and **4**. Having five rows would increase precision of movement tracking.

(82) FIG. **6** is a partial section view of a schematic block diagram of an actuator apparatus **600** with replaceable ball bearings **616**, according to various embodiments. The actuator apparatus **600** includes an actuator rod **602** and an actuator block **604**, which are substantially similar to other actuator rods **102**, **302**, **402**, **502** and actuator blocks **104**, **304**, **404**, **504** described herein. Where each block hole (e.g., **114**, **314**, **414**) has a single ball bearing (e.g., **116**, **316**, **416**), the ball bearings may develop a flat spot or may otherwise wear unevenly. The reciprocating ball bearings **616** offer a solution to prevent flats on the ball surface offer high use of the actuator apparatus **600**. The design of the actuator apparatus **600** of FIG. **6** incorporates a unique spring actuated force against each ball bearing **616** to be positioned into a counter-sunk block hole **614** of the actuator block **604** and rod holes **606** along the actuator rod **602** as the ball bearings **616** move from block hole **614** to block hole **614**.

(83) The actuator apparatus **600** of FIG. **6** includes a bearing track **650** and bearing mover assembly **652** that pushes ball bearings **616** through the bearing track **650** so that a ball bearing **616** over block hole **614** and under a spring mechanism **618** that is moving in and out of rod holes **606** is moved aside and replaced with another ball bearing **616** on a regular basis. In some embodiments, the bearing mover assembly **652** moves ball bearings **616** continuously. In other embodiments, the bearing mover assembly **652** moves ball bearings **616** on a periodic basis. In other embodiments, the bearing mover assembly **652** moves ball bearings **616** while the actuator rod **602** is not moving with respect to the actuator block **604**.

(84) The actuator apparatus **600** of FIG. **6** is one possible design. Other actuator apparatuses include bearing replacement systems that are different. In some examples, bearing tracks and bearing mover assemblies are for fewer block hole locations. In other embodiments, the bearing track **650** includes less ball bearings **616** and the bearing mover assembly **652** includes a mechanism to advance ball bearings **616** other than each ball bearing **616** pushing on another ball bearing **616**. One of skill in the art will recognize other ways to replace ball bearings **616**.

(85) FIG. **7** is a schematic block diagram illustrating an actuator rod **702** connected to a mover apparatus **726** via a slot **750** that allows for discrete movement of the actuator rod **702** with respect to the actuator apparatus (not shown), according to various embodiments. In some embodiments, it is advantageous for the actuator rod **702** to snap forward to a next position of alignment of rod holes **706** and ball bearings (not shown but similar to the ball bearings **116**, **316**, **416**, **616** described herein) so that as the actuator rod **702** moves with respect to the actuator block (not shown but similar to the actuator blocks **104**, **304**, **404**, **504**, **604** described herein) such that alignment between rod holes **706** and ball bearings is maintained before snapping to a next alignment of rod holes **706** and ball bearings.

(86) The actuator apparatus **700** provides a mechanism for snapping between alignment positions by having a slot **750** with a pin **752** free to move back and forth within the slot **750**. Length of the slot is based on spacing between the rod holes **706** such that as the mover apparatus **726** pushes or pulls the actuator rod **702**, an end of the slot **750** contacts the pin **752** and motivates the actuator rod to move and snap to a next alignment position as the pin **752** moves within the slot **750**. The actuator apparatus **700** of FIG. **7** includes one possible implementation that provides a more discrete movement of the actuator rod **702** with respect to an actuator block. One of skill in the art will recognize other designs appropriate for an actuator rod and actuator block configuration.

(87) FIG. **8** is a schematic block diagram illustrating an application of an actuator apparatus **800** with a fixed actuator rod **802** and moving actuator block **804**, according to various embodiments. The actuator apparatus **800** of FIG. **8** is one implementation and one of skill in the art will recognize other applications of the actuator apparatuses **100**, **300**, **400**, **500**, **600**, **700** described herein.

(88) The actuator block **804** is suspended from a track **862** connected to roof trusses **860** where the actuator block **804** moves via a wheel **864**. A load **868** is suspended from the actuator block **804** via a cable and hook assembly **866**. A mover apparatus **826** anchored to a wall **870** moves the actuator block **804** via a mover device **827**, such as a rod from a pneumatic press, a worm gear rotated by a motor, a chain and pulley system, etc. The actuator rod **802** is fixed and includes rod holes **806** spaced with enough precision to accurately move the load **868** to a particular position over a floor **872** before the cable and hook assembly **866** lowers the load **868**.

(89) FIG. **9** is a schematic block diagram illustrating an application of an actuator apparatus **900** with a fixed actuator block **904** and moving actuator rod **902**, according to various embodiments. The actuator rod **902** is connected to a hook **966** connected to a load **968** above a floor **972**. The actuator block **904** is suspended with supports **974** above the floor **972**. The actuator rod **902** includes rod holes **906** spaced sufficiently apart to provide adequate precision for keeping track of height of the load **968** above the floor. In the embodiment, a mover apparatus (e.g., **126**) is internal to the actuator block **904** and moves the actuator rod **902**. In other embodiments, an external mover apparatus is connected to the actuator rod **902**. While the examples of FIGS. **8** and **9** include simple mechanisms for supporting a load, other more complex movers, robotics, etc. may be used in a process where an actuator rod and actuator block are used for precision movement.

(90) FIG. **10A** is a schematic block diagram illustrating a ball bearing and spring mechanism **1000**, according to various embodiments. The ball bearing **116** is in a block hole **114** of an actuator block **104** that is slightly narrower than a diameter of the ball bearing **116** to retain the ball bearing **116** when an actuator rod **102** is not present. The ball bearing **116** is resting in a rod hole **106** of an actuator rod **102**. The spring mechanism **118** presses on the ball bearing **116** and is depicted in a pocket **1002** of the actuator block **104**. In some embodiments, the spring mechanism **118** includes a linear spring. In other embodiments, the spring mechanism **118** includes a spring within a sleeve, a capped sleeve, etc. to prevent the spring mechanism **118** from extending past a particular point, which would be useful for the actuator apparatus **600** of FIG. **6** with a bearing track **650**. The block hole **114** is depicted as sloped on both sides, which would be appropriate for a bearing replacement system where a bearing track **650** includes other ball bearings **116** that push out the current ball bearing **116** while another ball bearing **116** moves over the block hole **114**. The spring mechanism **118** is partially within a compartment **1002** that provides a backstop for the spring mechanism **118**.

(91) FIG. **10B** is a schematic block diagram illustrating a ball bearing and spring mechanism **1001** with an alternate to using a ball bearing, according to various embodiments. The ball bearing and spring mechanism **1001** of FIG. **10B** includes a spring **118** pushing on a cap **1004** shaped with a rounded end **1006** and cylindrical portion **1008** to accommodate an end of the spring **118**. A collar section **1010** flairs out from the cylindrical portion **1008** to keep the cap **1004** retained in the block hole **114**. The cap **1004** is long enough to extend into a rod hole **106**. The rounded end **1006** provides ease in pushing the actuator rod **102** past the cap **1004**. The rounded end **1006**, in some embodiments, is spherical shaped. In other embodiments, the rounded end **1006** is rounded in a direction of movement of the actuator rod **102** with respect to the actuator block **104**, such as a portion of a side of a cylinder. In such embodiments, the block holes **114** may be rectangular. As used herein, use of the term ball bearing (e.g. **116**, **316**, **416**, **616**) refers to a round ball bearing, to a ball bearing and spring mechanism **1001** as depicted in FIG. **10B**, or other similar design with a rounded end that protrudes into an aligned rod hole (e.g. **106**, **306**, **406**, **506**, **606**, **706**, **806**, **906**) and is pushed toward an actuator rod (e.g. **102**, **302**, **402**, **502**, **602**, **702**, **802**, **902**) by a spring force.

(92) FIG. **11** is (a) a side transparent view of a rotary actuator apparatus **1100**, (b) is a cross section view of an actuator rod **1102**, and (c) a cross section view of an actuator block **1104** for a rotary actuator apparatus **1100**, according to various embodiments. An actuator rod **1102** rotates in an opening **1108** of an actuator block **1104** instead of being pushed through the actuator block **1104** as depicted in FIGS. **1-9**. Rod holes **1106** are spaced around a circumference of the actuator rod **1102**

and block holes **1114**, ball bearings **1116** and associated springs **1118** are spaced around a circumference of the opening **1108** of the actuator block **1104**. A light assembly **1112** is positioned the cavity **1110** of the actuator rod **1102** to shine through the rod holes **1106** and a light sensor **1120** is in a block hole **1114**. While the rotary actuator apparatus **1100** of FIG. **11** depicts a single set of rod holes **1106** and block holes **1114**, other embodiments may include additional sets of rod holes **1106** and block holes **1114** spaced above and/or below the rod holes **1106** of FIG. **11(a)**. The various descriptions of actuator apparatuses **100**, **300**, **400**, **500**, **600**, **700**, and spring mechanisms **1000**, **1001** are applicable to the rotary actuator apparatus **1100** of FIG. **11**.

(93) In some embodiments, the opening **1108** of the actuator block **1104** extends all the way through the actuator block **1104** and the actuator rod **1102** extends through the opening **1108**. In other embodiments, opening **1108** only extends partially through the actuator block **1104** and the actuator rod **1102** has an end that extends into the opening **1108**. In some embodiments, the rotary actuator apparatus **1100** of FIG. **11** is used for a robotic arm or other location where rotational movement is controlled. In other embodiments, the rotary actuator apparatus **1100** is used for a gearbox. One of skill in the art will recognize other uses for tracking rotational movement.

(94) FIG. **12** is (a) a side transparent view of a rotary actuator apparatus **1200** with a verification module **1250**, (b) is a cross section view of an actuator rod **1202**, and (c) a cross section view of an actuator block **1204** for a rotary actuator apparatus **1200** without ball bearings, according to various embodiments. As with the rotary actuator apparatus **1100** of FIG. **11**, an actuator rod **1202** rotates in an opening **1208** of an actuator block **1204** instead of being pushed through the actuator block **1204** as depicted in FIGS. **1-9**. However, the actuator apparatuses **100**, **300**, **400**, **500**, **600**, **700** of FIGS. **1-9**, in various embodiments, include a verification module **1250** and operate similar to the actuator apparatus **1200** of FIG. **12**.

(95) Rod holes **1206** are spaced around a circumference of the actuator rod **1202** and a single light sensor **1220** is positioned in a block hole (not shown) in the opening **1208**. A light assembly **1212** is positioned the cavity **1210** of the actuator rod **1202** to shine through the rod holes **1206** and the light sensor **1220** is in the block hole **1214**. While the rotary actuator apparatus **1200** of FIG. **12** depicts a single set of rod holes **1206**, other embodiments may include additional sets of rod holes **1206** and block holes spaced above and/or below the rod holes **1206** of FIG. **12(a)**. The various descriptions of actuator apparatuses **100**, **300**, **400**, **500**, **600**, **700**, **1100** and spring mechanisms **1000**, **1001** are applicable to the rotary actuator apparatus **1200** of FIG. **12**.

(96) The rotary actuator apparatus **1200** includes a verification module **1250** that is configured to modulate light of the light assembly **1212** to transmit a position signal and to transmit a verification signal in response to the light sensor **1220** receiving the position signal. In some embodiments, the verification module **1250** is configured to transmit an aligned signal in response to light at the light sensor **1220** reaching an alignment threshold and the verification module **1250** transmits the position signal in response to the aligned signal. In some embodiments, the position signal is a digital signal generated by switching a light source of the light assembly **1212** on and off at a particular frequency where the light source being off represents a logic 0 and the light source being on represents a logic 1, or vice versa.

(97) In some embodiments, the position signal is coded with a identifier specific to the location of the rotary actuator apparatus **1200**. In other embodiments, the verification module **1250** is configured to cause the light assembly **1212** to transmit constant light until receiving the aligned signal and then to transmit the position signal. In other embodiments, the verification module **1250** is configured to cause the light assembly **1212** to continuously transmit the position signal and the light sensor **1220** is configured to transmit the verification signal once the light sensor **1220** is able to receive the position signal based on signal strength. The verification module **1250** is discussed in more detail below with regard to the apparatuses **1400**, **1500** of FIGS. **14**, and **15**.

(98) In some embodiments, the light assembly **1212** includes fiber optics. In some embodiments, the light assembly **1212** includes one or more strands of fiber optic cable that extend into the cavity

1210 and terminate in a way to shine light from an end of the fiber optic cables into the cavity **1210**. Light from the ends of the one or more fiber optic cables reaches the rod holes **1206** and then to the light sensor **1220** upon alignment of a rod hole **1206** with the light sensor **1220**. In some embodiments, at least one fiber optic cable shines light directly towards the rod holes **1206**, and subsequently to the light sensor **1220**.

(99) In other embodiments, the fiber optic cable is positioned within the cavity **1210** to illuminate the cavity **1210** in such a way that light bounces around in the cavity **1210** and reaches the rod holes **1206** and light sensor **1220** upon alignment. In some embodiments, the fiber optic cable includes a spreader or other device to spread light from a fiber optic cable around within the cavity **1210** or at least in a direction of one or more light sensors **1220** in the actuator block **1204**. In some embodiments, the cavity **1210** is treated to transmit light more efficiently than a non-treated cavity **1210**. In some embodiments, the cavity **1210** is polished to increase light transmission. In other embodiments, the cavity **1210** is coated with paint or other reflective coating to increase light transmission. One of skill in the art will recognize other ways to increase light transmission in the cavity **1210**.

(100) In some embodiments, the light assembly **1212** includes a fiber optic transmitter connected to an end of the one or more fiber optic cables opposite the end(s) in the cavity **1210** shining light into the cavity **1210**. The fiber optic transmitter is configured to generate light and/or light pulses over the fiber optic cable. In some embodiments, the fiber optic transmitter is controlled by the verification module **1250**. In some embodiments, the fiber optic transmitter includes a light emitting diode (“LED”). In other embodiments, the fiber optic transmitter includes a laser diode. One of skill in the art will recognize other details, configurations, etc. for a fiber optic transmitter that may be controlled by the verification module **1250** to transmit light on fiber optic cable.

(101) In some embodiments, the light assembly **1212** includes an LED as a light source where the LED shines light into the cavity **1210**, rod holes **1206** and light sensor **1220**. In some embodiments, the LED is positioned to shine light directly through a rod hole **1206** to the light sensor **1220**. In other embodiments, the LED is positioned in the cavity **1210** to indirectly shine light to reach the rod holes **1206** and light sensor **1220**. In other embodiments, the light assembly **1212** includes another type of light source, including light sources developed after filing of this Application.

(102) In some embodiments, the actuator block **1204** includes multiple block holes with multiple light sensors **1220** (not shown). In the embodiments, the light sensors **1220** may be spread out at different locations around the opening **1208**. In some embodiments, the verification module **1250** causes the light assembly **1212** to transmit light at different colors (e.g., different wavelength ranges) where each color has a different position signal encoded therein. In the embodiments, the different light sensors **1220** include a notch filter that filters out light outside of a particular color so that the light sensor **1220** senses the particular color. Thus, the light assembly **1212** is able to transmit different information to the different light sensors **1220** via transmission of different colors.

(103) In some embodiments, the actuator rod **1202** includes multiple rows of rod holes **1206** adjacent to each other around the circumference of the actuator rod **1202** and the actuator block **1204** includes one or more light sensors **1220** per row. In some embodiments, spacing is adjusted between rod holes **1206** of the different rod holes **1206** of the rows to provide a finer position control than a single row of rod holes **1206**. The different rows of rod holes **1206** is a concept similar to the actuator apparatus **300** of FIG. 3 except that the rod holes **106** are around the circumference of the actuator rod **1202**.

(104) FIG. 13 is (a) a side transparent view of a rotary actuator apparatus **1300** with a verification module **1250**, (b) is a cross section view of an actuator rod **1202**, and (c) a cross section view of an actuator block **1204** for a rotary actuator apparatus **1300** with ball bearings **1316**, according to various embodiments. The rotary actuator apparatus **1300** is substantially similar to the rotary actuator apparatus **1200** of FIG. 12 except with ball bearings **1316** in block holes **1214** positioned

to extend into rod holes **1206** upon alignment of rod holes **1206** with the ball bearings **1316**. The ball bearings **1316** and associated springs **1318** are spaced around a circumference of the opening **1208** of the actuator block **1204** and serve to at least momentarily retain the actuator rod **1202** in place when the ball bearings **1316** snap into a rod hole **1206**, as described above. The ball bearings **1316** and associated spring mechanisms **1318** function similar to the ball bearings **1116** and spring mechanisms **1118** of FIG. **11**.

(105) FIG. **14** is a schematic block diagram of an apparatus **1400** with a verification module **1250** for securely verifying position of a rod hole **1206** with respect to a light sensor **1220**, according to various embodiments. The verification module **1250** includes a light modulator **1402** and a verification circuit **1404**, which are described below. In some embodiments, the verification module **1250** is implemented using various hardware circuits, such as a modulation circuit capable of switching light from the light assembly **1212** on and off, logic circuits configured to cause the modulation circuit to send a digital signal, circuitry configured to receive signals from the light sensor **1220** and to process the signals, and the like. In some embodiments, at least a portion of the verification module **1250** is implemented using an application specific integrated circuit (“ASIC”), a programmable logic array (“PAL”), etc. In some embodiments, at least a portion of the verification module **1250** is implemented using executable code stored on computer readable storage media and executed using a processor. One of skill in the art will recognize various ways to implement the verification module **1250** using hardware circuits, a programmable logic device, and code stored on computer readable storage media.

(106) The apparatus **1400** includes a light modulator **1402** configured to modulate light of the light assembly **1212** to transmit a position signal. In some embodiments, the light modulator **1402** modulates light of the light assembly **1212** by turning light from the light assembly **1212** on and off at a particular frequency and/or using a particular pattern. In some embodiments, the position signal is a digital signal transmitted by switching a light source of the light assembly **1212** on and off to send the position signal. In some embodiments, the position signal includes a location code that is unique to the location of the rotary actuator apparatus **1200**, **1300**. In some embodiments, the location code is followed by another bit pattern indicative of a rod hole **1206** being aligned with the light sensor **1220**. In some embodiments, the bit pattern uses a sequence of one or more bits.

(107) In some examples, the location code includes a number of bits sufficient to distinguish between various location codes of locations within a device using the rotary actuator apparatus **1200**, **1300**. In some embodiments, length of the location code is determined by how many locations are within a device using rotary actuator apparatuses **1200**, **1300**. In some examples, three bits may be used for up to eight locations, 5 bits may be used for up to 32 locations, 8 bits may be used for up to 256 locations, etc. A simple bit pattern following the location code may be one bit where logic 0 is not aligned and logic 1 is aligned. In other embodiments, the bit pattern may be more complex. In some examples, the bit pattern and/or position signal includes information related to position of the actuator rod **1202** with respect to the actuator block **1204**, such as which rod hole **1206** is aligned with the light sensor **1220**. In other embodiments, the position signal includes an initial sequence of bits signaling that signals that the location code and/or bit sequence is to follow. One of skill in the art will recognize other forms of a position signal.

(108) The apparatus **1400** includes a verification circuit **1404** configured to transmit a verification signal in response to the light sensor receiving the position signal. In some embodiments, the verification signal merely indicates alignment of a rod hole **1206** with the light sensor **1220**. In other embodiments, the verification signal includes additional information, such as the location code, position of the actuator rod **1202** with respect to the actuator block **1204**, etc. In some embodiments, the verification circuit **1404** transmits the verification signal to a controller for a device that includes the rotary actuator apparatus **1200**, **1300**. In some examples, the device is a robot that includes one or more rotary actuator apparatuses **1200**, **1300** located at various joints, pivot points, etc. The device may be any device described above with respect to the various

descriptions of the actuator apparatuses **100**, **300**, **400**, **500**, **600**, **700**, **1100** and spring mechanisms **1000**, **1001** described above. In some embodiments, the verification signal is in the form of a digital signal transmitted on a conductor to a controller or other device. In other embodiments, the verification signal is in the form of a message sent to a user. One of skill in the art will recognize other forms of a verification signal.

(109) FIG. **15** is a schematic block diagram of another apparatus **1500** with a verification module **1250** for securely verifying position of a rod hole **1206** with respect to a light sensor **1220**, according to various embodiments. The verification module **1250** includes a light modulator **1402** and a verification circuit **1404**, which are substantially similar to those described above with regard to the apparatus **1400** of FIG. **14**. In various embodiments, the verification module **1250** includes a position module **1502**, a hole counter module **1504**, a direction detector **1506**, and/or an encryption module **1508**, which are described below. In various embodiments, the apparatus **1500** of FIG. **15** is implemented similarly to the apparatus **1400** of FIG. **14**.

(110) In some embodiments, the apparatus **1500** includes a position module **1502** configured to transmit an aligned signal in response to light at the light sensor **1220** reaching an alignment threshold. As the actuator rod **1202** moves with respect to the actuator block **1204**, a rod hole **1206** moves from a misaligned position to an aligned position with respect to the light sensor **1220**. As the rod hole **1206** starts to pass over the light sensor **1220**, light from the light assembly **1212** begins to reach the light sensor **1220** and increases in intensity until the rod hole **1206** is aligned with the light sensor **1220**. In some embodiments, initial intensity of light typically is too low for the light sensor **1220** to detect light and/or for the light sensor to function properly.

(111) At a particular light intensity, the light sensor **1220**, in some embodiments, functions to transmit a signal indicative of light being received at the light sensor **1220**. In some embodiments, the light intensity sufficient for the light sensor **1220** to indicate that light is detected is the alignment threshold. In other embodiments, the position module **1502** senses light intensity received by the light sensor **1220** and the alignment threshold is above an intensity sufficient for the light sensor **1220** to indicate light intensity. Having an alignment threshold above a level of minimum function of the light sensor **1220**, in some cases, is beneficial to help to ensure that a signal from the light sensor **1220** is based on proper functioning of the light sensor **1220**.

(112) The position module **1502** transmits the aligned signal in response to light at the light sensor reaching the alignment threshold. In some embodiments, the position module **1502** transmits the aligned signal by passing through a signal from the light sensor **1220**. The aligned signal, in some embodiments, is a digital signal indicative of the rod hole **1206** being aligned with the light sensor **1220**. In some embodiments, the position module **1502** transmits the aligned signal to the light modulator **1402**, which transmits the position signal in response to receiving the aligned signal. In the embodiments, the aligned signal is indicative of the rod hole **1206** being aligned with the light sensor **1220** and the associated block hole **1214** through which the light sensor **1220** is positioned.

(113) The apparatus **1500**, in some embodiments, includes a hole counter module **1504** configured to increment or decrement a hole counter in response to the position signal. In some embodiments, the hole counter module **1504** increments or decrements the hole counter based on the aligned signal. In other embodiments, the hole counter module **1504** increments or decrements the hole counter based on the position signal.

(114) In some embodiments, the verification module **1250** includes a direction detector **1506** configured to determine a direction of movement of the actuator block with respect to the actuator rod **1202**. In some embodiments, the direction detector **1506** is from a mover apparatus **126**, **726** that moves the actuator rod **1202** with respect to the actuator block **1204**. In some examples, the direction detector **1506** derives a direction of the actuator rod **1202** with respect to the actuator block **1204** from a controller of the mover apparatus **126**, **726**. In other embodiments, the direction detector **1506** includes a sensor that detects movement of the actuator rod **1202** with respect to the actuator block **1204**.

(115) In some embodiments, the hole counter module **1504** increments the hole counter in response to the position signal and the direction detector **1506** determining that the actuator block **1204** is moving in a first direction with respect to the actuator rod **1202** and the hole counter module **1504** decrements the hole counter in response to the position signal and the direction detector **1506** determining that the actuator block **1204** is moving in a second direction with respect to the actuator rod **1202**. The second direction is opposite the first direction. In various embodiments, the hole counter module **1504** and the direction detector **1506** are substantially similar to the hole counter module **122** and direction detector **124** of FIG. 2.

(116) In some embodiments, the verification module **1250** includes an encryption module **1508** configured to encrypt one or more signals from the light sensor **1220** to a controller (not shown) and to encrypt one or more signals from the controller to the light assembly **1212**. Encryption provides an additional way for securely verifying position of a rod hole **1206** with respect to a light sensor **1220**. In some embodiments, the encryption module **1508** is dispersed with portions in the light sensor **1220**, the light assembly **1212**, a controller, etc. to encrypt and then to decrypt the position signal, verification signal, etc. The encryption module **1508**, in various embodiments, includes a public key, a private key, and/or other keys and uses an encryption technique known to those of skill in the art.

(117) Beneficially, the verification module **1250** provides a secure way to verify that a particular actuator rod **1202** has moved to a particular position. Providing feedback along with a digital code identifies the particular actuator apparatus **100, 300, 400, 500, 600, 700, 800, 900, 1100, 1200, 1300** and alignment of an actuator hole (e.g., **1206**) with a light sensor (e.g., **1220**). In sensitive equipment where a malicious party may want to intercept a signal from an actuator apparatus **100, 300, 400, 500, 600, 700, 800, 900, 1100, 1200, 1300** to provide false information to a controller, the verification module **1250** provides additional security.

(118) FIG. **16** is (a) a side transparent view and (b) a top view of an actuator apparatus **1600** with a light source **1602** in line with a light sensor **1220**, according to various embodiments. In the embodiments, the light source **1602** is at the end of a light assembly **1212** and is a point source that is positioned to align with the light sensor **1220**. When a rod hole **1206** aligns with the light sensor **1220**, light **1604** from the light source **1602** shines directly on the light sensor **1220**. In some embodiments, the light source is an LED and the light assembly **1212** includes a structure and electrical components supporting the LED. In other embodiments, the light source is a fiber optic cable located and oriented to shine light **1604** directly onto the light sensor **1220**. While the light source **1602** is depicted in the center of the actuator rod **1202**, in other embodiments, the light source **1602** is located closer to the light sensor **1220**.

(119) FIG. **17** is a side transparent view of an actuator apparatus **1700** with a light source **1702** offset from a light sensor **1220**, according to various embodiments. In the embodiments, the light source **1702** is placed so that light **1704** from the light source **1702** reaches the light sensor **1220** indirectly. As depicted, light **1704** from the light source **1702** bounces in the cavity **1210** before reaching the light sensor **1220**. While some light **1704** may reach the rod hole **1206** directly from the light source **1702**, the light **1704** would then need to reflect off sides of the rod hole **1206** to reach the light sensor **1220**.

(120) While two paths for the light **1704** are depicted, light **1704** from the light source **1702** will bounce around through the cavity **1210** in many directions, angles, etc. and some of the light **1704** will reach the light sensor **1220**. Some light **1704** may be attenuated based on reflectiveness of the surface of the cavity **1210** where more reflective surfaces will propagate more light **1704** down the cavity **1210** to the light sensor **1220** than less reflective surfaces. Again, the light source **1702** may be an LED, an end of a fiber optic cable, or other type of lamp that emits light.

(121) In some embodiments, the light modulator **1402** transmits the position signal synchronously. Where the light modulator **1402** transmits the position signal synchronously, data may be transferred at a higher rate than asynchronous transmission. Synchronous transmission typically

includes data transmission in the form of blocks or frames and transmission is synchronized between the light assembly **1212** and light sensor **1220**. In some embodiments, where the light source **1602** is in line with the light sensor **1220**, synchronous transmission may be more feasible due to the direct nature of transmission of light **1604**.

(122) In other embodiments, the light modulator **1402** transmits the position signal asynchronously. Typically, asynchronous transmission includes data being sent in the form of a byte or bit character and is half-duplex type transmission. In asynchronous transmission, start bits and/or stop bits are included to the data to signal start of data and/or an end of the data. Where the light source **1702** is not in line with the light sensor **1220** and bounces at various angles through the cavity **1210**, portions of the transmitted light **1704** may arrive at different times at the light sensor **1220** due to phase shift caused by different path lengths of the light **1704**. To compensate, the light modulator **1402** may control transmission of the position signal at a lower frequency than for synchronous transmission and may use asynchronous transmission.

(123) In some embodiments, the frequency of transmission of the position signal accounts for phase shift within the cavity **1210**. In some examples, for a transition from logic 0 when light **1704** is off to a logic 1 when light **1704** is on, and a transition from logic 1 to logic 0, the transmission frequency is low enough to account for phase shift of light **1704** bouncing around the cavity **1210**. Thus, the frequency is selected provide enough time between transitions between logic 0 and logic 1 and also transitions between logic 1 to logic 0 to compensate for any phase shift of light **1704** bouncing around and taking different pathways to the light sensor **1220**. In various embodiments, asynchronous or synchronous transmission may be used for direct or indirect lighting in the cavity **1210**, depending on the rate of transmission, expected speed of the actuator rod **1202** with respect to the actuator block **1204**, etc.

(124) The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. An apparatus comprising: an actuator rod comprising an interior cavity and a set of rod holes, each rod hole of the set of rod holes extending through the actuator rod to the cavity, the set of rod holes positioned along a line; a light assembly positioned to light the cavity; an actuator block comprising: an opening in the actuator block sized to conform to an outer surface of the actuator rod; a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor; and a verification module comprising: a light modulator configured to modulate light of the light assembly to transmit a position signal; and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal.
2. The apparatus of claim 1, wherein the verification module further comprises a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold and wherein the light modulator transmits the position signal in response to the aligned signal.
3. The apparatus of claim 1, wherein the light assembly comprises a fiber optic cable positioned with an end in the cavity and wherein the light sensor comprises a receiver configured to receive light from the fiber optic cable.
4. The apparatus of claim 1, wherein the light assembly comprises a light emitting diode (“LED”) positioned in the cavity.
5. The apparatus of claim 1, wherein the light assembly comprises a light source positioned to align

with the light sensor through a rod hole of the set of rod holes.

6. The apparatus of claim 1, wherein the cavity comprises a surface that reflects light from the light assembly and/or the light assembly comprises a light source positioned to illuminate the cavity and light within the cavity reaches the light sensor upon alignment of a rod hole of the set of rod holes with the light sensor.

7. The apparatus of claim 1, wherein the position signal comprises a digital signal.

8. The apparatus of claim 1, wherein: the position signal comprises a code unique to the actuator rod and/or the light assembly; the light sensor receiving the position signal further comprises receiving the code unique to the actuator rod; and the verification signal comprises the code unique to the actuator rod.

9. The apparatus of claim 1, wherein the verification signal comprises: an indication of alignment of a rod hole with the light sensor; a location code comprising information indicative of a location of the actuator rod with respect to the actuator block; and/or a unique code transmitted in the position signal.

10. The apparatus of claim 1, wherein the verification module further comprises: a hole counter module configured to increment or decrement a hole counter in response to the position signal; and/or a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod, wherein the hole counter module increments the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod, the second direction opposite the first direction.

11. The apparatus of claim 1, further comprising a mover apparatus configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes.

12. The apparatus of claim 1, wherein a shape of the actuator rod and a shape of the opening of the actuator block maintain the actuator rod in alignment with the actuator block such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes.

13. The apparatus of claim 1, wherein one of: the actuator rod is linear and the rod holes run in a direction along a length of the actuator rod and the actuator block moves with respect to the actuator rod in a direction along the length of the actuator rod; and the actuator rod is round and the rod holes run in a direction around a circumference of the actuator rod and the actuator block rotates with respect to the actuator rod in a direction around the circumference of the actuator rod.

14. A system comprising: an actuator rod comprising an interior cavity and a set of rod holes, each rod hole of the set of rod holes extending through the actuator rod to the cavity, the set of rod holes positioned along a line; a light assembly positioned to light the cavity; an actuator block comprising: an opening in the actuator block sized to conform to an outer surface of the actuator rod; a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor; a verification module comprising: a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold; a light modulator configured to modulate light of the light assembly to transmit a position signal in response to the aligned signal; and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal; and a mover apparatus configured to move the actuator block with respect to the actuator rod in a direction such that lines connecting each rod hole of the set of rod holes maintain alignment with lines connecting each block hole of the set of block holes.

15. An apparatus comprising: an actuator rod comprising an interior cavity and a set of rod holes,

each rod hole of the set of rod holes extending through the actuator rod to the cavity, the set of rod holes positioned along a line; a light assembly positioned to light the cavity; an actuator block comprising: an opening in the actuator block sized to conform to an outer surface of the actuator rod; and a light sensor positioned in the actuator block to sense light coming through a rod hole aligned with the light sensor; a verification module comprising: a light modulator configured to modulate light of the light assembly to transmit a position signal; and a verification circuit configured to transmit a verification signal in response to the light sensor receiving the position signal; a hole counter module configured to increment or decrement a hole counter in response to the position signal; and a direction detector configured to determine a direction of movement of the actuator block with respect to the actuator rod, wherein the hole counter module increments the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a first direction with respect to the actuator rod and the hole counter module decrements the hole counter in response to the position signal and the direction detector determining that the actuator block is moving in a second direction with respect to the actuator rod, the second direction opposite the first direction.

16. The apparatus of claim 15, wherein the verification module further comprises a position module configured to transmit an aligned signal in response to light at the light sensor reaching an alignment threshold and wherein the light modulator transmits the position signal in response to the aligned signal.
