

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416993
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Choi; Jaeho et al.

Electronic device, and notification and connection method for electronic pen

Abstract

A notification and connection method for an electronic pen is provided. Aspects include receiving a touch input of a first electronic pen to a display, identifying whether the first electronic pen is connected to an electronic device through a communication module in response to receiving the touch input, and identifying whether a second electronic pen is connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device. Aspects also include transmitting a notification signal to the second electronic pen in response to identifying that the second electronic pen connected to the electronic device is present and establishing communication connection with the first electronic pen in response to identifying that the second electronic pen is not connected to the electronic device.

Inventors: Choi; Jaeho (Suwon-si, KR), Kim; Seonghun (Suwon-si, KR), Woo; Kwangtaek (Suwon-si, KR), Lee; Changho (Suwon-si, KR), An; Jinwan (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008819085

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 18/778505

Filed: July 19, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240377904 A1	Nov. 14, 2024

Foreign Application Priority Data

KR	10-2022-0010592	Jan. 25, 2022
KR	10-2022-0040396	Mar. 31, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/021431 20221227 PENDING child-doc US 18778505

Publication Classification

Int. Cl.: G06F3/041 (20060101); G06F3/0354 (20130101)

U.S. Cl.:

CPC G06F3/04162 (20190501); G06F3/03545 (20130101);

Field of Classification Search

CPC: G06F (3/04162); G06F (3/03545); G06F (3/038); G06F (3/0484); G06F (3/0354); G06F (3/0383)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10782799	12/2019	Nicholson et al.	N/A	N/A
10877578	12/2019	Hisano	N/A	G06F 3/0446
11048360	12/2020	Jang	N/A	G06F 3/04162
11132072	12/2020	Jeon et al.	N/A	N/A
11307618	12/2021	Seo et al.	N/A	N/A
11327582	12/2021	Kim et al.	N/A	N/A
11874978	12/2023	Kang et al.	N/A	N/A
12001617	12/2023	Jung	N/A	G06F 3/03545
2003/0229859	12/2002	Shiraishi et al.	N/A	N/A
2020/0019255	12/2019	Gilbert et al.	N/A	N/A
2020/0097118	12/2019	Kang	N/A	H04L 69/08
2020/0103988	12/2019	Jeon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111083943	12/2019	CN	N/A
113760124	12/2020	CN	N/A
H11282614	12/1998	JP	N/A
20030091766	12/2002	KR	N/A
101221895	12/2012	KR	N/A
20180129295	12/2017	KR	N/A
101984591	12/2018	KR	N/A
20200017042	12/2019	KR	N/A
20200036374	12/2019	KR	N/A
20210017099	12/2020	KR	N/A
20210034358	12/2020	KR	N/A
102498813	12/2022	KR	N/A

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/KR2022/021431; International Filing Date Dec. 27, 2022; International Search Report Mail Date Mar. 24, 2023; 3 Pages. cited by applicant

Extended European Search Report Issued In EP Application No. 22924394.4-1218; Mail Date Feb. 26, 2025; 12 Pages. cited by applicant

Primary Examiner: Boyd; Jonathan A

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application, claiming priority under § 365 (c), of International Application No. PCT/KR2022/021431, filed on Dec. 27, 2022, which is based on and claims the benefit of Korean Patent Application No. 10-2022-0040396, filed on Mar. 31, 2022, and Korean Patent Application No. 10-2022-0010592, filed on Jan. 25, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

(1) This disclosure relates to an electronic device, for example, a technology for transmitting a notification to an electronic pen and establishing communication connection with the electronic pen by using an electronic device.

(2) With the development of mobile communication technologies and hardware/software technologies, portable electronic devices (hereinafter, referred to as ‘electronic devices’) have been able to implement a variety of functions beyond traditional calling functions. The electronic device may provide various functions to a user by means of an interaction with an external device. For example, the electronic device may receive a touch input made by a stylus and perform predetermined various functions.

(3) The electronic device may establish communication connection, such as Bluetooth connection, with a stylus and send or receive signals to or from the stylus. In the case that the stylus touches a display of the electronic device, the electronic device may provide functions that are correlated with various inputted frequencies. For example, the electronic device may provide a first function mapped to a first frequency when receiving the first frequency, and the electronic device may provide a second function mapped to a second frequency when receiving the second frequency.

SUMMARY

(4) An electronic pen interacts with an electronic device by using frequencies, and the electronic device may receive a touch input when the same frequencies are used even without using an electronic pen in communication connection with the electronic device. However, there is a problem in that in the case that a user touches the electronic device in the related art with a pen, which is not in communication connection with the electronic device, the electronic device may only receive a touch input but cannot support various operations by using the communication connection. Therefore, even though the user intends to use the electronic pen connected to the electronic device, the user has difficulty in recognizing which electronic pen the electronic device is in communication connection with, in the case that the user owns multiple electronic pens.

(5) In addition, the electronic device in the related art has a problem in that it is inconvenient to use the electronic pen because an electronic pen control menu is created only when the user touches the

display in the case that the user intends to control the electronic pen by using the electronic device.
(6) Various embodiments provide a method of notifying the user of an electronic pen that is in communication connection with the electronic device or establishing communication connection with an electronic pen that currently inputs a touch in the case that the user intends to find the electronic pen that is in communication connection with the electronic device or manipulate the electronic pen.

(7) An electronic device according to various embodiments may include: a display; a communication module; a memory; and a processor operatively connected to the display, the communication module, and the memory, in which the processor is configured to: receive a touch input of a first electronic pen to the display; identify whether the first electronic pen is connected to the electronic device through the communication module in response to receiving the touch input; identify whether there is an electronic pen connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device; transmit a notification signal to a second electronic pen in response to identifying that the second electronic pen connected to the electronic device is present; and establish communication connection with the first electronic pen in response to identifying that there is no electronic pen connected to the electronic device.

(8) An electronic pen according to various embodiments may include: a communication module; a memory; and a processor operatively connected to the communication module and the memory, in which the processor is configured to: transmit a communication signal to the electronic device in response to detecting a resonant frequency; receive a response signal corresponding to the communication signal; and transmit a control signal to the electronic device in response to receiving the response signal.

(9) A notification and connection method for an electronic pen according to various embodiments may include: receiving a touch input of a first electronic pen to a display; identifying whether the first electronic pen is connected to an electronic device through a communication module in response to receiving the touch input; identifying whether there is an electronic pen connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device; transmitting a notification signal to a second electronic pen in response to identifying that the second electronic pen connected to the electronic device is present; and establishing communication connection with the first electronic pen in response to identifying that there is no electronic pen connected to the electronic device.

(10) According to various embodiments, in the case that the electronic pen, which is not in communication connection, touches the display, the electronic device may identify whether there is an electronic pen currently being in communication connection. In the case that there is no electronic pen currently being in communication connection, the electronic device may establish communication connection with the electronic pen that currently touches the display. In the case that there is an electronic pen currently being in communication connection, the electronic device may transmit a notification to the electronic pen that is in communication connection. According to the embodiment, in the case that a motion of the electronic pen that is in communication connection is detected, the electronic device may display a graphic object, which indicates the electronic pen on the display, and notify the user that the electronic pen, which currently touches the display, is in communication connection.

(11) Other effects, which may be obtained or expected by various embodiments of the present electronic device, will be directly or implicitly disclosed in the detailed description on the embodiments of the present electronic device. For example, various effects expected according to various embodiments of the electronic device will be disclosed in the detailed description to be described below.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a block diagram of an electronic device in a network environment according to various embodiments.
- (2) FIG. 2 is a block diagram illustrating an electronic pen according to various embodiments.
- (3) FIG. 3 is a block diagram illustrating the electronic device according to various embodiments of the present disclosure.
- (4) FIG. 4 is a view illustrating a configuration of the electronic device according to various embodiments of the present disclosure and a configuration of an external electronic device.
- (5) FIG. 5 is a view illustrating a configuration in which the electronic device according to various embodiments establishes communication connection with an electronic pen or transmits a notification signal to the electronic pen.
- (6) FIG. 6A is a view illustrating a guide screen that allows the electronic device according to various embodiments to establish the communication connection with the electronic pen.
- (7) FIG. 6B is a view illustrating a configuration in which the electronic pen according to various embodiments provides a notification to a user by using a light-emitting element.
- (8) FIG. 6C is a view illustrating a configuration in which a graphic object is displayed on the electronic device in the case that a motion of the electronic pen that is in communication connection with the electronic device according to various embodiments is detected.
- (9) FIG. 7 is a flowchart illustrating a notification and connection method for the electronic pen and the electronic device according to various embodiments.
- (10) FIG. 8 is a flowchart illustrating operations of the electronic device and the electronic pen according to various embodiments.

DETAILED DESCRIPTION

- (11) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.
- (12) When describing the embodiments, a description of technical contents, which are well known in the technical field to which the present disclosure pertains but are not directly related to the present disclosure, will be omitted. In addition, a detailed description of constituent elements having substantially the same configurations and functions will be omitted.
- (13) For the same reason, some constituent elements in the accompanying drawings are illustrated in an exaggerated or schematic form or are omitted, and the size of each constituent element does not entirely reflect an actual size. Therefore, the present disclosure is not limited to relative sizes or intervals drawn in the accompanying drawings.
- (14) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments.
- (15) Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some

embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(16) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(17) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(18) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(19) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(20) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(21) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker

may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(22) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(23) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(24) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(25) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(26) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(27) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(28) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(29) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(30) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(31) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the

communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(32) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(33) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(34) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(35) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(36) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(37) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(38) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(39) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a

single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(40) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(41) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(42) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(43) FIG. 2 is a block diagram illustrating an electronic pen according to various embodiments.

(44) With reference to FIG. 2, an electronic pen **201** according to an embodiment may include a pen processor **220**, a memory **230**, a resonance circuit **287**, a charging circuit **288**, a battery **289**, a communication circuit **290**, an antenna **297**, a trigger circuit **298**, and/or a sensor circuit **299**. In some embodiments, the pen processor **220**, at least a part of the resonance circuit **287**, and/or at least a part of the communication circuit **290** may be provided on a printed circuit board or configured in the form of a chip. The pen processor **220**, the resonance circuit **287**, and/or the communication circuit **290** may be electrically connected to the memory **230**, the charging circuit **288**, the battery **289**, the antenna **297**, the trigger circuit **298**, and/or the sensor circuit **299**.

(45) The pen processor **220** may include a generic processor configured to execute a customized hardware module or software (e.g., application programs). The pen processor **220** may include software elements (programs) or hardware constituent elements (functions) including at least one of various sensors provided in the electronic pen **201**, a data measurement module, an input/output

interface, a module for managing an environment or a state of the electronic pen **201**, and a communication module. For example, the pen processor **220** may include one of hardware, software, and firmware or a combination of two or more of hardware, software, and firmware.

(46) According to the embodiment, the pen processor **220** may be configured to provide an electronic device **101**, through the communication circuit **290**, with information indicating a pushed state of a button, sensing information acquired by the sensor circuit **299**, and/or information (e.g., information related to a position of the electronic pen **201**) calculated on the basis of the sensing information.

(47) The resonance circuit **287** may include a coil (or inductor) and/or a capacitor. The resonance circuit **287** may resonate on the basis of an electromagnetic field signal generated from the digitizer (e.g., the display module **160** in FIG. **1**) of the electronic device **101** and emit electromagnetic resonance (EMR) input signals (or magnetic fields) by resonance. In the case that the electronic pen **201** transmits signals by the EMR method, the electronic pen **201** may generate a signal including resonant frequencies on the basis of an electromagnetic field generated from an inductive panel of the electronic device **101**. In the case that the electronic pen **201** transmits signals by an active electrostatic (AES) method, the electronic pen **201** may generate a signal by using capacity coupling with the electronic device **101**. In the case that the electronic pen **201** transmits signals by an electrically coupled resonance (ECR) method, the electronic pen **201** may generate a signal including resonant frequencies on the basis of an electric field generated from a capacitive device of the electronic device.

(48) The electronic device **101** may identify a position of the electronic pen **201** on the electronic device **101** by using the electromagnetic resonance input signal. For example, the electronic device **101** may identify a position of the electronic pen **201** on the basis of a magnitude of an induced electromotive force (e.g., output electric current) generated by the electromagnetic resonance input signal in each of a plurality of channels (e.g., a plurality of loop coils) in the digitizer. Meanwhile, the configuration has been described above in which the electronic device **101** and the electronic pen **201** are operated by the EMR method. However, this configuration is provided for illustrative purposes only. The electronic device **101** may generate a signal based on the electric field on the basis of the electrically coupled resonance (ECR) method. The resonance circuit of the electronic pen **201** may be resonated by an electric field. The electronic device **101** may identify an electric potential in the plurality of channels (e.g., electrodes) by the resonance of the electronic pen **201**. The electronic device **101** may identify the position of the electronic pen **201** on the basis of electric potential. The electronic pen **201** may be implemented using the active electrostatic (AES) method. It may be understood by those skilled in the art that the type of implemented electronic pen is not limited.

(49) According to the embodiment, the resonance circuit **287** may be used to change the intensity or frequency of the electromagnetic field in accordance with the user's manipulation state. For example, the resonance circuit **287** may provide various frequencies for recognizing a hovering input, a drawing input, a button input, or an erasing input. For example, the resonance circuit **287** may provide various resonant frequencies in accordance with a connection combination of a plurality of capacitors or provide various resonant frequencies based on a variable inductor and/or a variable capacitor.

(50) The memory **230** may store information related to an operation of the electronic pen **201**. For example, the information may include information for communication with the electronic device **101** and frequency information related to an input operation of the electronic pen **201**. Further, the memory **230** may store a program (or application, algorithm, or processing loop) for calculating information (e.g., coordinate information and/or displacement information) related to the position of the electronic pen **201** from sensing data of the sensor circuit **299**. The memory **230** may store a communication stack of the communication circuit **290**. According to the implementation, the communication circuit **290** and/or the pen processor **220** may include a dedicated memory.

(51) The communication circuit **290** may be configured to perform wireless communication function between the electronic pen **201** and a communication module **190** of the electronic device **101**. According to the embodiment, the communication circuit **290** may provide the electronic device **101** with state information, input information, and/or information related to the position of the electronic pen **201** by using a near field communication method. For example, the communication circuit **290** may provide the electronic device **101** with information (e.g., motion sensor data) on a direction of the electronic pen **201** acquired by the sensor circuit **299**, voice information inputted through a microphone, or information related to a residual capacity of the battery **289**. For example, the communication circuit **290** may provide the electronic device **101** with information related to sensing data acquired from the sensor circuit **299** and/or the position of the electronic pen **201** identified on the basis of the sensing data. For example, the communication circuit **290** may provide the electronic device **101** with information related to a state of a button included in the electronic pen **201** acquired through the trigger circuit **298**. For example, the near field communication method may include at least one of Bluetooth, Bluetooth low energy (BLE) NFC, Wi-Fi direct, ultra wideband (UWB), and wireless LAN. However, the type of field communication method is not limited.

(52) The antenna **297** may be used to transmit or receive signals or power to or from the outside (e.g., the electronic device **101**). According to the embodiment, the electronic pen **201** may include a plurality of antennas **297** and select at least one antenna **297** suitable for the communication method among the plurality of antennas **297**. The communication circuit **290** may exchange signals or power with the external electronic device through at least one selected antenna **297**.

(53) The trigger circuit **298** may include at least one button. According to the embodiment, the trigger circuit **298** may transmit a trigger signal to the electronic device **101** by using an input signal of the button.

(54) According to the embodiment, the pen processor **220** may identify an input method (e.g., touch or push) of the button and the type of button (e.g., EMR button or BLE button) of the electronic pen **201** on the basis of the received trigger signal.

(55) The sensor circuit **299** may generate electrical signals or data values corresponding to an internal operating state or an external environment state of the electronic pen **201**. For example, the sensor circuit **299** may include at least one of a motion sensor, a battery residual capacity detection sensor, a pressure sensor, an optical sensor, a temperature sensor, a geomagnetic sensor, and a biosensor.

(56) The sensor circuit **299** may include an acceleration sensor (accelerometer), a gyro sensor, and/or a geomagnetic sensor. The acceleration sensor may sense information on a linear motion of the electronic pen **201** and/or acceleration of the electronic pen **201** with respect to three axes, six axes, or nine axes. The gyro sensor may sense information related to a rotation of the electronic pen **201**. The geomagnetic sensor may sense information on a state (e.g., posture (orientation)) in which the electronic pen **201** is inclined. The sensor circuit **299** may include not only a sensor for measuring a motion, but also a sensor capable of generating electrical signals or data values corresponding to an internal operating state or an external environment state of the electronic pen **201**. For example, the sensor circuit may include at least one of the battery residual capacity detection sensor, the pressure sensor, the optical sensor, the temperature sensor, and the biosensor. The biosensor may sense the manner in which the electronic pen **201** is being held by a user, i.e., a style of the grip that the user has on the electronic pen **201**. The pen processor **220** may transmit the information, which is acquired from the sensor circuit **299**, to the electronic device **101** through the communication circuit **290**. Alternatively, on the basis of the information acquired from the sensor circuit **299**, the pen processor **220** may transmit information, which is related to the position of the electronic pen **201** (e.g., a coordinate of the electronic pen **201** and/or a displacement of the electronic pen **201**), to the electronic device **101** through the communication circuit **290**.

(57) With reference to FIG. 3, an electronic device **300** according to the embodiment may include a

display **320** (e.g., the display module **160** in FIG. **1**), a communication module **330** (e.g., the communication module **190** in FIG. **1**), a processor **310** (e.g., the processor **120** in FIG. **1**), and/or a memory **340** (e.g., the memory **130** in FIG. **1**).

(58) According to the embodiment, the electronic device **300** may accommodate or attach the electronic pen (e.g., the electronic pen **201** in FIG. **2**) in an internal space or an external space of the electronic device **300**. However, the present disclosure is not limited thereto. According to any embodiment, the electronic pen **201** may be configured as a separate external input device.

(59) The display **320** may include an input/output device configured to perform an input function and a display function. The display **320** may include at least some of the configurations of the display module **160** in FIG. **1** and/or at least some of the functions of the input module **150** in FIG. **1**. The display **320** may refer to a flat display or a flexible display. The display **320** may include at least one display. The display **320** may display a graphic user interface (GUI) element and/or visual information (e.g., text, graphic, image, video, or a combination thereof).

(60) According to the embodiment, the display **320** may be coupled to or disposed adjacent to a touch detection circuit, a pressure sensor capable of measuring intensity (pressure) of a touch, and/or a digitizer circuit configured to detect the electronic pen **201**. The display **320** may be a touch-sensitive display. The touch-sensitive display may detect a touch, a touch gesture, an air gesture, or a hovering (or proximity touch) input made by using a user's finger (or other body parts). The touch-sensitive display may detect a touch, an air command, or a hovering input of the electronic pen **201**.

(61) According to the embodiment, the display **320** may perform a function corresponding to the input signal of the electronic pen **201** and display a user interface (UI) related to the function. For example, the display **320** may provide the user with a pen theme UI related to the electronic pen **201**.

(62) The communication module **330** may perform near field communication connection with the electronic pen **201** (e.g., a stylus pen detached from the electronic device **300** or a stylus pen provided separately from the electronic device **300**). For example, the communication module **330** may perform communication with the electronic pen **201** by using (Bluetooth low energy (BLE)) that is one of various types of near field communication methods. However, the present disclosure is not limited thereto. The communication module **330** may perform communication connection between the communication module **330** and the electronic pen **201** when the electronic pen **201** is positioned within a distance in which the near field communication connection may be performed. The communication module **330** according to various embodiments may include at least some of configurations and/or functions of the communication module **190** in FIG. **1**.

(63) For example, the communication module **330** may receive electronic pen information (or sensor information) from the electronic pen **201**. For example, the electronic pen information may include at least one of coordinate information related to a hovering input, gradient information, and action coordinate information related to an air command.

(64) The processor **310** may be configured to control the constituent elements of the electronic device **101** and/or perform computation or data processing related to communication and include at least some of the configurations and/or functions of the processor **120** in FIG. **1**. The operations of the processor **310**, which will be described below, may be performed by loading instructions stored in the memory **340**.

(65) The memory **340** may be operatively connected to the processor **310** and store data and various instructions capable of being executed by the processor **310**. The above-mentioned instructions may include control instructions such as arithmetic and logical operations, data movements, input/output, and the like that may be recognized by the processor **310**.

(66) The memory **340** may store a program for performing the function corresponding to the control signal in accordance with the input of the electronic pen **201** or store a program (or application) for supporting an electronic pen theme configuration.

(67) According to the embodiment, the processor **310** may execute a pen theme application (hereinafter, referred to as an 'app') and display a user interface, which is provided by the pen theme app, on the display **320**. The pen theme app may be an app capable of changing and/or configuring graphic objects (e.g., an air command UI or an electronic pen pointer object) or a pen sound related to the electronic pen **201** in accordance with user preference.

(68) According to the embodiment, the processor **310** may control the performance of operations or functions related to the pen theme app. The processor **310** may display an electronic pen pointer corresponding to a hovering input of the electronic pen **201**. For example, the processor **310** may display a hovering object (e.g., dot pointer) configured as a default. In the case that the user changes the electronic pen pointer theme by using the pen theme app, the processor **310** may display a modified hovering object (e.g., modified pointer) to which the pen theme is applied.

(69) According to the embodiment, the processor **310** may change the position of the electronic pen pointer by determining, adaptively (or in real time or automatically), the direction and coordinate of the electronic pen pointer displayed on the display **320** in consideration of at least some of visual characteristics of the electronic pen pointer, a situation of the electronic pen **201**, and a situation of the display **320**.

(70) According to various embodiments, the processor **310** may be operatively, functionally, and/or electrically connected to the components of the electronic device **300** (e.g., the display **320**, the communication module **330**, and the memory **340**) and configured to control the components, perform computation related to communication, and/or process data. The processor **310** may include at least some of the configurations and/or functions of the processor **120** in FIG. 1.

(71) According to various embodiments, the processor **310** is not limited to computation and data processing functions that may be implemented in the electronic device **300**. However, hereinafter, various embodiments will be described in which the electronic device **300** is used to establish communication connection with the electronic pen and transmit a notification signal to the electronic pen. The operations of the processor **310**, which will be described below, may be performed by loading the instructions stored in the memory **340**.

(72) According to various embodiments, the processor **310** may receive a touch input of the electronic pen to the display **320**. The display **320** may include a touch panel capable of detecting the touch input of the electronic pen. For example, when the user holds a first electronic pen and touches the display **320** of the electronic device **300**, the processor **310** may use the touch panel and receive the touch input of the first electronic pen to the display **320**. In this case, the touch input, which is received by the processor **310**, may be different from a communication signal (e.g., Bluetooth signal) to be described below. Hereinafter, the electronic pen, which touches the display **320**, will be described as the first electronic pen.

(73) According to various embodiments, in response to receiving the touch input, the processor **310** may identify whether the first electronic pen is in communication connection with the electronic device **300**. According to the embodiment, in the case that the electronic pen, which is in communication connection with the electronic device **300**, touches the display **320**, the processor **310** may receive a communication signal simultaneously with the touch input or in a predetermined time interval. The communication signal may include a serial number or a separate pen ID of the electronic pen. For example, in the case that the first electronic pen is in communication connection with the electronic device **300**, the processor **310** may receive the communication signal within the predetermined time interval or at the same time when the user touches the display **320** with the first electronic pen. According to another embodiment, in the case that the user initially touches the display **320** with the first electronic pen, the processor **310** may acquire the communication signal. Thereafter, the processor **310** may not acquire the communication signal for a predetermined time even though the first electronic pen touches the display **320**. For example, the pen processor of the first electronic pen transmits the communication signal to the electronic device when the first electronic pen initially touches the display **320** of the electronic device. After the initial touch, the

pen processor may transmit the communication signal only when a time interval between the previous touch and the current touch is larger than a predetermined time interval. Therefore, in the case that the processor **310** receives the touch input of the electronic pen that is in communication connection with the electronic device **300**, the processor **310** may also receive the communication signal. The processor **310** may not receive the communication signal in the case that the processor **310** receives the touch input of the electronic pen that is not in communication connection with the electronic device **300**. According to the embodiment, in the case that the processor **310** receives the touch input and the communication signal at the same time or in the predetermined time interval, the processor **310** may determine that the electronic pen, which currently touches the display **320**, is in communication connection with the electronic device **300**. In the case that the processor **310** does not receive the touch input and the communication signal at the same time or in the predetermined time interval, the processor **310** may determine that the electronic pen, which currently touches the display **320**, is not in communication connection with the electronic device **300**.

(74) According to various embodiments, the processor **310** may perform a predetermined operation in response to determining that the first electronic pen is in communication connection with the electronic device **300**. The processor **310** may perform a predetermined operation in accordance with the touch input and/or the hovering gesture of the electronic pen. For example, the processor **310** may perform a writing or erasing operation on the basis of the frequencies of the communication signals received from the electronic pen.

(75) According to various embodiments, the processor **310** may identify whether there is another electronic pen that is in communication connection with the electronic device **300** in response to determining that the first electronic pen is not in communication connection with the electronic device **300**. For example, in the case that the display **320** receives the touch input of the first electronic pen without receiving the communication signal, the processor **310** may use the communication module **330** of the electronic device **300** and identify whether there is an electronic pen that is in communication connection with the electronic device **300**. According to the embodiment, the processor **310** may identify that a second electronic pen that is in communication connection with the electronic device **300** is present. According to another embodiment, the processor **310** may identify that there is no electronic pen that is in communication connection with the electronic device **300**.

(76) According to various embodiments, the processor **310** may transmit a notification signal to the second electronic pen in response to identifying that the second electronic pen in communication connection with the electronic device **300** is detected. The notification signal may trigger one or more of a vibration, a sound, and a light on the second electronic pen. For example, the processor **310** may transmit the notification signal, which triggers vibration of the second electronic pen. The pen processor **310** of the second electronic pen may receive the notification signal and operate a vibration motor. The user may identify that the second electronic pen, which generates vibration, is in communication connection with the electronic device **300**, and the user may touch the display **320** with the corresponding pen.

(77) According to various embodiments, the processor **310** may establish the communication connection with the first electronic pen in response to identifying that there is no other electronic pen that is in communication connection with the electronic device **300**. The processor **310** may establish the communication connection with the first electronic pen by using the communication module **330**. The processor **310** may use the memory **340** and identify whether the first electronic pen has previously established the communication connection with the electronic device **300**. According to the embodiment, in the case that there is a record indicating that the first electronic pen has previously established the communication connection with the electronic device **300**, the processor **310** may immediately establish the communication connection of the first electronic pen with the electronic device **300**. According to another embodiment, in the case that the first

electronic pen has not previously established the communication connection with the electronic device **300**, the processor **310** may output a guide for pairing the first electronic pen and the electronic device **300** to the display **320**. That is, the processor **310** may provide the guide for the connection of the electronic pen when the electronic pen is initially connected to the electronic device **300**.

(78) The processor **310** may display a menu icon capable of controlling the electronic pen on the display **320** on the basis of a motion of the pen that is in communication connection with the electronic device **300**.

(79) According to various embodiments, the processor **310** may acquire information on the motion of the electronic pen from the pen processor **310** of the electronic pen. The pen processor **310** may acquire information on the motion of the electronic pen from the sensor circuit. The pen processor **310** may transfer the acquired motion information to the electronic device **300**. For example, in the case that the user picks up the electronic pen that is in communication connection with the electronic device **300**, the processor **310** may receive information, which indicates that the user has come into contact with the corresponding electronic pen, from the electronic pen.

(80) According to various embodiments, the processor **310** may display a graphic object (e.g., menu icon), which is capable of controlling the electronic pen, on the display **320** in response to acquiring the information on the motion of the electronic pen. For example, the processor **310** may not display the graphic object when the user uses the electronic pen that is not in communication connection with the electronic device **300**, and the processor **310** may display the graphic object when the user uses the electronic pen that is in communication connection with the electronic device.

(81) According to various embodiments, the processor **310** may provide a menu capable of displaying information of the electronic pen and/or controlling the electronic pen on the basis of the user input related to the graphic object. For example, the processor **310** may display the serial number and status of the electronic pen on the basis of the user input related to the graphic object. For example, the processor **310** may provide a menu capable of releasing the communication connection with the electronic pen on the basis of the user input related to the graphic object.

(82) FIG. 4 is a view illustrating configurations of the electronic device **101** and the electronic pen **201** according to various embodiments of the present disclosure.

(83) With reference to FIG. 4, according to the embodiment, the electronic device (e.g., the electronic device **101** in FIG. 1, 3, or 4) may communicate with the electronic pen (e.g., the electronic pen **201** in FIGS. 2 and 4). The electronic device **101** and the electronic pen **201** may communicate with each other through the communication circuit by using at least one of various types of near field communication methods. For example, the near field communication method may be Bluetooth low energy (BLE) communication. However, the present disclosure is not limited thereto.

(84) The electronic device **101** may include a pen controller **410** (e.g., the processor **120** in FIG. 1 or the processor **310** in FIG. 3).

(85) For example, the pen controller **410** may include at least one amplifier (not illustrated) connected to at least one of coils **411** and **412**. The pen controller **410** may include at least one of the coils **411** and **412**, and charging power may be provided to the electronic pen **201** through at least one of the coils **411** and **412**.

(86) According to the embodiment, at least one of the coils **411** and **412** may be disposed at a position physically adjacent to a coil **421** of the electronic pen **201** in the case that the electronic pen **201** is inserted into an internal space of the electronic device **101**. However, the arrangement position is not limited. Meanwhile, the insertion into the internal space is an example. In addition to the internal space, the electronic device **101** may include an area (or space) in which the electronic pen **201** is mounted (or attached). In this case, the electronic pen **201** may be attached to or detached from the corresponding area (or space). At least some of the functions of the pen

controller **410** may be performed by the processor **120**. Alternatively, the pen controller **410** and the processor **120** may be integrated and implemented to at least some of the functions.

(87) For example, the pen controller **410** may include a control circuit (e.g., control circuit independent of the processor **120**), an inverter, and/or an amplifier in addition to at least one of the coils **411** and **412**.

(88) A resonance circuit **420** (e.g., the resonance circuit **287** in FIG. 2) of the electronic pen **201** may include the coil **421**, at least one of capacitors **422** and **423**, and/or a switch **424**. In the case that the switch **424** is turned off, the coil **421** and the capacitor **422** may constitute the resonance circuit. In the case that the switch **424** is turned on, the coil **421** and the capacitors **422** and **423** may constitute the resonance circuit. Therefore, the resonant frequency of the resonance circuit **420** may change depending on the state in which the switch **424** is turned on or off. For example, the electronic device **101** may identify the on/off state of the switch **424** on the basis of the frequency of the signal from the electronic pen **201**. For example, in the case that the button of the electronic pen **201** is pushed/released, the switch **424** may be turned on or off. The electronic device **101** may identify whether the button of the electronic pen **201** is pushed on the basis of the frequency of the received signal identified by the digitizer.

(89) At least one rectifier **431** or **435** may commutate and output a signal VPEN with an alternating current waveform output from the resonance circuit **420**. A charging switch controller (SWchg ctrl) **432** may receive a commutated signal VM output from the rectifier **431**. On the basis of the commutated signal VM, the charging switch controller **432** may identify whether the signal generated from the resonance circuit **420** is a charging signal or a signal for detecting a position. For example, the charging switch controller **432** may identify whether the signal, which is generated from the resonance circuit **420**, is the charging signal or the signal for detecting the position, for example, on the basis of a magnitude of a voltage of the commutated signal VM. Alternatively, the charging switch controller **432** may identify whether a signal having a charging initiation pattern is inputted on the basis of a waveform of the commutated signal VM.

(90) The charging switch controller **432** may turn on or off the charging switch **436**. The charging switch controller **432** may control the charging of a battery **437**.

(91) In the embodiment, the charging switch **436** may transmit charging power, which is received from the rectifier **435**, to the battery **437** under the control of the charging switch controller **432**.

(92) In the case that the charging switch **436** is in an on state, the battery **437** may be charged by using a received commutated signal VIN. An over-voltage protection circuit (OVP) **433** may identify a battery voltage VBAT. When the battery voltage VBAT exceeds an overvoltage critical value, the charging switch **436** may be controlled to be in an off state.

(93) In the embodiment, a load switch controller (SWL ctrl) **434** may measure a voltage value output by the battery **437**.

(94) When the load switch controller (SWL ctrl) **434** identifies that the battery voltage VBAT exceeds an operating voltage critical value, the load switch controller (SWL ctrl) **434** may perform control to make a load switch (SWL) **438** in the on state. When the load switch **438** is in the on state, the power from the battery **437** may be transmitted to a BLE communication circuit and a controller (BLE+controller) **439** (e.g., the communication circuit **290** and the processor **220** in FIG. 2). The load switch controller **434** may include an under-voltage lock-out (UVLO) circuit.

(95) In the embodiment, the load switch **438** may supply power required to operate the BLE communication circuit and the controller **439** under the control of the load switch controller **434**. The load switch **438** may control the connection between the BLE communication circuit, the controller **439**, and the battery **437**.

(96) The BLE communication circuit and the controller **439** may operate by using the received power. A button control circuit **440** may transfer information on the input of the button to the BLE communication circuit and the controller **439** in the case that a distance between the electronic pen **201** and the electronic device **101** is longer than a critical distance. The BLE communication circuit

and the controller **439** may transfer the information on the received button input to the electronic device **101** through an antenna **441** (e.g., the antenna **297** in FIG. 2).

(97) A sensor **450** (e.g., the sensor circuit **299** in FIG. 2) may include a gyro sensor **451** and/or an acceleration sensor **452**. Sensing data acquired by the gyro sensor **451** and/or the acceleration sensor **452** may be transmitted to the BLE communication circuit and the controller **439**.

(98) The BLE communication circuit and the controller **439** may transmit communication signals including the received sensing data to the electronic device **101** through the antenna **441**.

Alternatively, the BLE communication circuit and the controller **439** may identify the information (e.g., the coordinate and/or displacement the electronic pen **201**) related to the position of the electronic pen **201** identified on the basis of the received sensing data. The BLE communication circuit and the controller **439** may transfer the information, which is related to the identified position of the electronic pen **201**, to the electronic device **101** through the antenna **441**.

(99) The BLE communication circuit and the controller **439** may activate the acceleration sensor **452** in the case that the electronic pen **201** is withdrawn or detached from the electronic device **101**. In the case that the button is pushed, the BLE communication circuit and the controller **439** may activate the gyro sensor **451**. Meanwhile, the activation time point is just an example. The activation time point for each sensor is not limited. Further, the sensor **450** may further include a geomagnetic sensor. In the case that only the acceleration sensor **452** is activated, the electronic pen **201** may provide information on an acceleration, which is measured by the acceleration sensor **452**, to the electronic device **101**, and the electronic device **101** may operate on the basis of the information on the position and acceleration of the electronic pen **201** identified on the basis of the signal of the electronic pen.

(100) FIG. 5 is a view illustrating a configuration in which the electronic device **500** according to various embodiments establishes communication connection with the electronic pen or transmits a notification signal to the electronic pen **510**.

(101) With reference to FIG. 5, in the case that the electronic device is not in communication connection with a first electronic pen **510** that touches the display (e.g., the display **320** in FIG. 3), the processor (e.g., the processor **310** in FIG. 3) may establish the communication connection with the first electronic pen **510** or transmit a notification signal to a second electronic pen **520** in communication connection with the electronic device. According to various embodiments, the processor may identify whether the first electronic pen **510** and the electronic device **500** are in communication connection with each other. In the case that the touch input and the communication signal are received simultaneously, the processor may determine that the first electronic pen **510** is in communication connection with the electronic device **500**. Alternatively, in the case that the touch input and the communication signal are received in the predetermined time interval, the processor may determine that the first electronic pen **510** is in communication connection with the electronic device **500**. In the case that the touch input and the communication signal are not received simultaneously nor received in a predetermined time interval, the processor may determine that the first electronic pen **510** is not in communication connection with the electronic device **500**.

(102) According to various embodiments, in the case that it is determined that the first electronic pen **510** is not in communication connection with the electronic device **500**, the processor may identify whether there is an electronic pen currently being in communication connection with the electronic device **500**, i.e., the second electronic pen **520**. According to the embodiment, in the case that no electronic pen is currently in communication connection with the electronic device **500**, the processor may establish the communication connection with the first electronic pen **510**. The processor may use the memory (e.g., the memory **340** in FIG. 3) and identify whether the electronic device has previously established the communication connection with the first electronic pen **510**. In the case that the electronic device has previously established the communication connection with the first electronic pen **510**, the processor may immediately establish the

communication connection with the first electronic pen **510** without displaying a separate guide. According to the embodiment, the processor may display a menu for establishing the communication connection with the first electronic pen **510** on the display. In the case that the electronic device has not previously established the communication connection with the first electronic pen **510**, the processor may output the guide screen for establishing the communication connection with the first electronic pen **510** to the display. The user may establish the communication connection with the first electronic pen **510** by using the guide screen and then use the first electronic pen **510**.

(103) According to another embodiment, in the case that the second electronic pen **520** is currently in communication connection with the electronic device **500**, the processor may transmit the notification signal to the second electronic pen **520**. The notification signal may be a signal that triggers vibration, sound, and/or light in the second electronic pen **520**. For example, in the case that the processor transmits the signal, which triggers light, to the second electronic pen **520**, the second electronic pen **520** may output light by using a light-emitting element in response to receiving the corresponding signal. The user may see the output light and identify that the second electronic pen **520** is in communication connection with the electronic device **500**.

(104) FIG. **6A** is a view illustrating the guide screen that allows the electronic device according to various embodiments to establish the communication connection with the electronic pen.

(105) FIG. **6B** is a view illustrating a configuration in which the electronic pen according to various embodiments provides a notification to the user by using the light-emitting element.

(106) FIG. **6C** is a view illustrating a configuration in which a graphic object is displayed on the electronic device in the case that a motion of the electronic pen being in communication connection with the electronic device according to various embodiments is detected.

(107) With reference to FIG. **6A**, the processor (e.g., the processor **310** in FIG. **3**) may provide a guide for establishing communication connection with a new electronic pen. In the case that a touch input of the electronic pen to the display (e.g., the display **320** in FIG. **3**) is received when there is no electronic pen being in communication connection with an electronic device **600**, the processor may output a guide screen **602**, which is illustrated in FIG. **6A**, to establish the communication connection with the electronic pen that currently touches the display. For example, the guide screen **602** may include an image of the electronic pen that currently touches the display, a text indicating a new electronic pen is detected, and a menu for establishing communication connection with the electronic pen. The processor may establish the communication connection with the detected electronic pen on the basis of the user input to the communication connection menu.

(108) With reference to FIG. **6B**, an electronic pen **610** may include a configuration for providing a notification to the user in response to a notification signal received from the electronic device **600**. For example, the electronic pen **610** may include at least one light-emitting element **612**. The electronic pen **610** may output light by using the light-emitting element **612** in response to receiving the notification signal that triggers a light output from the electronic device **600**. According to another embodiment, the electronic pen **610** may include a vibration motor. The electronic pen **610** may provide a notification to the user by generating vibration in response to receiving the notification signal that triggers vibration from the electronic device **600**. According to another embodiment, the electronic pen **610** may include a speaker. The electronic pen **610** may provide a notification to the user by outputting a sound in response to receiving the notification signal that triggers a sound from the electronic device **600**. The notification, which may be provided to the user by the electronic pen **610**, is not limited to light, vibration, and sound. The electronic pen **610** may provide a notification to the user by using a plurality of notification methods.

(109) With reference to FIG. **6C**, the processor may display a graphic object **604** indicating the electronic pen **610** on the display on the basis of information on the motion of the electronic pen

610 being in communication connection with the electronic device **600**. The processor may receive the motion information from the electronic pen **610** being in communication connection. The motion information may include information on a position, a velocity, and an acceleration of the electronic pen **610** acquired by the sensor circuit of the electronic pen **610**. In the case that the motion of the electronic pen **610** is detected, the processor may output the graphic object **604**, which indicates the electronic pen **610**, on the display. On the basis of the user input to the graphic object **604**, the processor may display information on the electronic pen **610** and provide a menu capable of controlling the electronic pen **610**.

(110) According to the embodiment, the processor may move and/or rotate the graphic object **604** in accordance with the motion and/or rotation of the electronic pen **610**. The processor may acquire information on the position and placement direction of the electronic pen and display the graphic object **604** on the basis of the acquired information. For example, in the case that the first electronic pen is placed in a horizontal direction and the second electronic pen is placed in a vertical direction, the processor may display a first graphic object, which corresponds to the first electronic pen, in the horizontal direction on the display and display a second graphic object, which corresponds to the second electronic pen, in the vertical direction on the display. The processor may perform control so that the graphic object **604** moves in the same way as the electronic pen **610** on the basis of the information received from the electronic pen **610**. For example, as the first electronic pen rotates from the horizontal direction to the vertical direction, the processor may output the first graphic object so that the first graphic object also rotates from the horizontal direction to the vertical direction. For example, as the first electronic pen moves in a right direction, the processor may output the first graphic object so that the first graphic object also moves in the right direction.

(111) The electronic device according to various embodiments may include the display, the communication module, the memory, and the processor operatively connected to the display, the communication module, and the memory, in which the processor may be configured to receive the touch input of the first electronic pen to the display, identify whether the first electronic pen is connected to the electronic device through the communication module in response to receiving the touch input, identify whether there is an electronic pen connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device, transmit the notification signal to the second electronic pen on the basis that a second electronic pen connected to the electronic device is present, and establish the communication connection with the first electronic pen on the basis of identifying that there is no electronic pen connected to the electronic device.

(112) According to various embodiments, the processor may be configured to identify whether there is a communication signal received to the communication module in response to receiving the touch input, and determine that the first electronic pen does not establish the communication connection with the electronic device on the basis that the touch input is received but the communication signal is not received.

(113) According to various embodiments, the processor may be configured to identify whether there is a communication signal received to the communication module in response to receiving the touch input, and determine that the first electronic pen establishes the communication connection with the electronic device and perform the predetermined function on the basis that the touch input and the communication signal are received simultaneously or in a predetermined time interval.

(114) According to various embodiments, the processor may be configured to identify whether there is a record of previous connection of the first electronic pen in the memory, and establish the communication connection with the first electronic pen by using the communication module in response to identifying that there is the record of previous connection of the first electronic pen.

(115) According to various embodiments, the processor may be configured to identify whether there is a record of previous connection of the first electronic pen in the memory, and output a pairing guide to the display in response to identifying that there is no record of connection of the

first electronic pen.

(116) According to various embodiments, the processor may be configured to output the second electronic pen and the graphic object, which indicates the state of the second electronic pen, to the display in response to receiving the motion information from the second electronic pen.

(117) The electronic pen according to various embodiments may include the communication module, the memory, and the processor operatively connected to the communication module and the memory, the processor may be configured to transmit the communication signal to the electronic device in response to detecting the resonant frequency, receive a response signal corresponding to the communication signal, and transmit the control signal to the electronic device in response to receiving the response signal.

(118) According to various embodiments, the electronic pen may further include at least one light-emitting element, and the processor may be configured to output light from the light-emitting element in response to receiving the notification signal from the electronic device.

(119) According to various embodiments, the electronic pen may further include the vibration motor, and the processor may be configured to output the vibration notification by using the vibration motor in response to receiving the notification signal from the electronic device.

(120) According to various embodiments, the electronic pen may further include a sensor module, and the processor may be configured to detect contact with the display of the electronic device by using the sensor module, and transmit the serial number to the electronic device in response to the contact with the electronic device.

(121) FIG. 7 is a flowchart illustrating a notification and connection method for the electronic pen the electronic device according to various embodiments.

(122) The method illustrated in FIG. 7 may be performed by the electronic devices (e.g., the electronic device **101** in FIG. 1) described with reference to FIGS. 1 to 6. Hereinafter, the description of the above-mentioned technical feature will be omitted.

(123) According to various embodiments, at operation **702**, the electronic device may receive the touch input of the first electronic pen. The input, which may be received by the electronic device, may include an input signal, such as a hovering or button input, in addition to a physical touch input. The display (e.g., the display **320** in FIG. 3) may include the touch panel capable of detecting the touch input of the electronic pen. For example, when the user holds the first electronic pen and touches the display of the electronic device, the electronic device may use the touch panel and receive the touch input of the first electronic pen to the display.

(124) According to various embodiments, at operation **710**, the electronic device may identify whether a communication signal is received from an electronic pen. According to the embodiment, in the case that the electronic pen, which is in communication connection with the electronic device, touches the display, the electronic device may receive the communication signal simultaneously with the touch input or in a predetermined time interval. The communication signal may include the serial number of the electronic pen. Therefore, in the case that the electronic device receives the touch input of the electronic pen being in communication connection with the electronic device, the electronic device may also receive the communication signal. The electronic device may not receive the communication signal in the case that the electronic device receives the touch input of the electronic pen that is not in communication connection with the electronic device. According to the embodiment, in the case that the electronic device receives the touch input and the communication signal at the same time or in the predetermined time interval, the electronic device may determine that the electronic pen, which currently touches the display, is in communication connection with the electronic device. In the case that the electronic device does not receive the touch input and the communication signal at the same time or in the predetermined time interval, the electronic device may determine that the electronic pen, which currently touches the display, is not in communication connection with the electronic device.

(125) According to various embodiments, the electronic device may perform a predetermined

operation in response to determining that the first electronic pen is in communication connection with the electronic device. The electronic device may perform a predetermined operation in accordance with the touch input and/or the gesture of the electronic pen. For example, the electronic pen may perform various operations, such as information on pressure of the electronic pen, information on the battery state, or information on an event according to the button input through the display of the electronic device being in communication connection with the electronic pen.

(126) In addition, the electronic pen may provide an air gesture function, and the air gesture function may include a button input (button press) function and a gesture function. In the case that the button input (button press) occurs on the electronic pen, a function mapped with a single input (single press) and/or a double input (double press) may be performed by the electronic device. In the case that the gesture occurs on the electronic pen, a function mapped with a left/right motion, an up/down motion, and/or a rotation may be performed by the electronic device. For example, when a gesture operation, such as a clockwise/counterclockwise gesture, occurs on the electronic pen while the electronic device executes a camera application, the electronic device may perform a zoom-in/out function. Alternatively, when a single input (single press) to the button provided on the electronic pen is detected, the electronic device may perform an image capturing (camera capture) function. When the double input (double press) is detected, the electronic device may perform a function of changing a front/rear camera.

(127) In addition, in the case of the electronic pen, like a pointer displayed by using a general mouse, an air pointer, which moves in accordance with the motion of the electronic pen, may be provided to the electronic device. The air pointer may be differently displayed in accordance with the type of application being executed by the electronic device or the type of object included in the application being executed.

(128) According to various embodiments, at operation **720**, the electronic device may identify whether there is a second electronic pen that is currently in communication connection with the electronic device on the basis that the communication signal is not received. For example, in the case that the display receives the touch input of the first electronic pen without receiving the communication signal, the electronic device may use the communication module of the electronic device and identify whether there is an electronic pen that is in communication connection with the electronic device. According to the embodiment, the electronic device may identify that the second electronic pen that is in communication connection with the electronic device is present. According to another embodiment, the electronic device may identify that there is no electronic pen that is in communication connection with the electronic device.

(129) According to various embodiments, at operation **722**, the electronic device may transmit the notification signal to the second electronic pen on the basis that the second electronic pen is currently in communication connection with the electronic device. The notification signal may trigger at least one of a vibration, a sound, and a light to be emitted or produced by the second electronic pen. For example, the electronic device may transmit the notification signal, which triggers vibration, to the second electronic pen. The pen electronic device of the second electronic pen may receive the notification signal and operate a vibration motor. The user may identify that the electronic pen, which generates vibration, is in communication connection with the electronic device, and the user may touch the display with the corresponding pen.

(130) According to various embodiments, at operation **730**, the electronic device may establish the communication connection with the first electronic pen on the basis that there is no electronic pen currently being in communication connection with the electronic device. The electronic device may establish the communication connection with the first electronic pen by using the communication module. The electronic device may use the memory (e.g., the memory **340** in FIG. 3) and identify whether the first electronic pen has previously established the communication connection with the electronic device. According to the embodiment, in the case that there is a record indicating that the

first electronic pen has previously established the communication connection with the electronic device, the electronic device may immediately establish the communication connection of the first electronic pen with the electronic device without a separate guide. According to another embodiment, in the case that the first electronic pen has not previously established the communication connection with the electronic device, the electronic device may output a guide for pairing the first electronic pen and the electronic device to the display. That is, the electronic device may provide the guide for the connection of the electronic pen when the electronic pen is initially connected to the electronic device.

(131) The electronic device may display a menu icon capable of controlling the electronic pen on the display on the basis of a motion of the pen being in communication connection with the electronic device.

(132) According to various embodiments, the electronic device may acquire information on the motion of the electronic pen from the electronic pen. The electronic pen may acquire information on the motion of the electronic pen from the sensor circuit. The electronic pen may transfer the acquired motion information to the electronic device. For example, in the case that the user picks up the electronic pen being in communication connection with the electronic device, the electronic device may receive information, which indicates that the user has come into contact with the corresponding electronic pen, from the electronic pen. For example, the electronic pen may detect user contact through an embedded touch sensor and transmit information on the user contact to the electronic device being in communication connection.

(133) According to various embodiments, the electronic device may display a graphic object (e.g., menu icon), which is capable of controlling the electronic pen, on the display in response to acquiring the information on the motion of the electronic pen. For example, the electronic device may not display the graphic object when the user uses the electronic pen that is not in communication connection with the electronic device, and the electronic device may display the graphic object when the user may use the electronic pen that is in communication connection with the electronic device.

(134) According to various embodiments, the electronic device may provide a menu capable of displaying information of the electronic pen and/or controlling the electronic pen on the basis of the user input related to the graphic object. For example, the electronic device may display the serial number and status of the electronic pen on the basis of the user input related to the graphic object. For example, the electronic device may provide a menu capable of releasing the communication connection with the electronic pen on the basis of the user input related to the graphic object.

(135) FIG. 8 is a flowchart illustrating operations of the electronic device and the electronic pen according to various embodiments.

(136) According to various embodiments, at operation **810**, when the electronic pen approaches the vicinity of the display of the electronic device, the resonant frequency with the electronic device may be formed. When the resonant frequency in a predetermined range (e.g., 530 kHz to 595 kHz) is formed, the electronic pen may transmit the communication signal to the electronic device, at operation **820**. In the state in which the electronic pen is in communication connection with the electronic device by using wireless communication, the electronic pen may receive a response signal to the transmitted communication signal from the electronic device, at operation **830**. At operation **840**, the electronic pen may transmit various control signals to the electronic device by using wireless communication in response to receiving the response to the communication signal. At operation **850**, the electronic pen may perform the communication connection with the electronic device in the case that the electronic pen is not communication connection with the electronic device by using wireless communication. The electronic pen may transmit various control signals to the electronic device in the state in which the electronic pen is in communication connection with the electronic device. The electronic device may receive the control signal from the electronic pen and perform a predetermined function. For example, the electronic device may

perform various functions such as an air gesture function of providing a function mapped with an up/down gesture, a left/right gesture, and/or a rotation when a gesture occurs on the electronic pen, and a function of an air pointer that moves in accordance with the motion of the pen.

(137) According to various embodiments, the electronic device may establish the communication connection with a plurality of electronic pens. According to the embodiment, the electronic device may receive the touch input of the electronic pen to the display and establish the communication connection with the electronic pen on the basis of the received touch input. For example, the electronic device may receive the first touch input of the first electronic pen to the display and establish the communication connection with the first electronic pen. In the state in which the electronic device establishes the communication connection with the first electronic pen, the electronic device may receive a second touch input of the second electronic pen to the display and establish the communication connection with the second electronic pen. In the state in which the electronic device establishes the communication connection with the first electronic pen and the second electronic pen, the electronic device may receive a third touch input of a third electronic pen to the display and establish the communication connection with the third electronic pen. The method of allowing the electronic device to establish the communication connection with at least one pen is not limited to the above-mentioned embodiments.

(138) According to various embodiments, the electronic device may output an indicator (e.g., guide message) and additionally establish the communication connection with a new electronic pen. For example, the electronic device may output the indicator for the communication connection with the electronic pen to the display in response to receiving the touch input of the electronic pen to the display. The electronic device may establish the communication connection with the electronic pen, which is in contact with the electronic device, on the basis of the user input to the indicator.

(139) According to various embodiments, in the case that the electronic device is in communication connection with the plurality of electronic pens, the electronic device may output the graphic objects of the electronic pens while distinguishing the graphic objects. For example, in the case that the electronic device is in communication connection with the first electronic pen, the second electronic pen, and the third electronic pen, the electronic device may output a first graphic object, which corresponds to the first electronic pen, in a first color, output a second graphic object, which corresponds to the second electronic pen, in a second color, and output a third graphic object, which corresponds to the third electronic pen, in a third color. The features of the electronic device, which may be changed to distinguish the graphic objects corresponding to the plurality of electronic pens, is not limited to colors, but may include various visual and sensory features.

(140) A notification and connection method for the electronic pen according to various embodiments may include receiving the touch input of the first electronic pen to the display, identifying whether the first electronic pen is connected to the electronic device through the communication module in response to receiving the touch input, identifying whether there is an electronic pen connected to the electronic device on the basis that the first electronic pen is not connected to the electronic device, transmitting a notification signal to the second electronic pen in response to identifying that there is a second electronic pen connected to the electronic device, and establishing the communication connection with the first electronic pen in response to identifying that there is no electronic pen connected to the electronic device.

(141) According to various embodiments, the identifying of whether the first electronic pen establishes the communication connection with the electronic device may include identifying whether there is a communication signal received to the communication module in response to receiving the touch input, and determining that the first electronic pen does not establish the communication connection with the electronic device on the basis that the touch input is received, but the communication signal is not received.

(142) According to various embodiments, the identifying of whether the first electronic pen establishes the communication connection with the electronic device may include identifying

whether there is a communication signal received to the communication module in response to receiving the touch input, and determining that the first electronic pen establishes the communication connection with the electronic device and performing a predetermined function on the basis that the touch input and the communication signal are received simultaneously or in a predetermined time interval.

(143) According to various embodiments, the establishing of the communication connection with the first electronic pen may include identifying whether there is a record of previous connection of the first electronic pen in the memory, and establishing the communication connection with the first electronic pen by using the communication module in response to identifying that there is the record of connection of the first electronic pen.

(144) According to various embodiments, the establishing of the communication connection with the first electronic pen may include identifying whether there is a record of previous connection of the first electronic pen in the memory, and outputting a pairing guide to the display in response to identifying that there is no record of connection of the first electronic pen.

(145) According to various embodiments, the notification and connection method may include outputting the second electronic pen and the graphic object, which indicates the state of the second electronic pen, to the display in response to receiving the motion information from the second electronic pen.

Claims

1. An electronic device comprising: a display; communication circuitry; memory; and at least one processor including processing circuitry, memory storing instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: receive a touch input of a first electronic pen to the display; identify whether the first electronic pen is connected to the electronic device through the communication circuitry in response to receiving the touch input; identify whether a second electronic pen is connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device; transmit a notification signal to the second electronic pen in response to identifying that the second electronic pen connected to the electronic device is present; and establish communication connection with the first electronic pen in response to identifying that the second electronic pen is not connected to the electronic device.

2. The electronic device of claim 1, wherein the memory stores instructions cause the electronic device to: identify whether there is a communication signal received to the communication circuitry in response to receiving the touch input; and determine that the first electronic pen does not establish the communication connection with the electronic device on the basis that the touch input is received, but the communication signal is not received.

3. The electronic device of claim 1, wherein the memory stores instructions cause the electronic device to: identify whether there is a communication signal received to the communication circuitry in response to receiving the touch input; and determine that the first electronic pen establishes the communication connection with the electronic device and perform a predetermined function on the basis that the touch input and the communication signal are received simultaneously or in a predetermined time interval.

4. The electronic device of claim 1, wherein the memory stores instructions cause the electronic device to: identify whether there is a record of previous connection of the first electronic pen in the memory; and establish the communication connection with the first electronic pen by using the communication circuitry in response to identifying that there is the record of connection of the first electronic pen.

5. The electronic device of claim 1, wherein memory stores instructions cause the electronic device to: identify whether there is a record of previous connection of the first electronic pen in the

memory; and output a pairing guide to the display in response to identifying that there is no record of connection of the first electronic pen.

6. The electronic device of claim 1, wherein the memory stores instructions cause the electronic device to output the second electronic pen and a graphic object, which indicates a state of the second electronic pen, to the display in response to receiving motion information from the second electronic pen.

7. A notification and connection method for an electronic pen, the notification and connection method comprising: receiving a touch input of a first electronic pen to a display; identifying whether the first electronic pen is connected to an electronic device through communication circuitry in response to receiving the touch input; identifying whether a second electronic pen is connected to the electronic device in response to identifying that the first electronic pen is not connected to the electronic device; transmitting a notification signal to the second electronic pen in response to identifying that the second electronic pen connected to the electronic device is present; and establishing communication connection with the first electronic pen in response to identifying that the second electronic pen is not connected to the electronic device.

8. The notification and connection method of claim 7, wherein the identifying of whether the first electronic pen establishes the communication connection with the electronic device comprises: identifying whether there is a communication signal received to the communication circuitry in response to receiving the touch input; and determining that the first electronic pen does not establish the communication connection with the electronic device on the basis that the touch input is received, but the communication signal is not received.

9. The notification and connection method of claim 7, wherein the identifying of whether the first electronic pen establishes the communication connection with the electronic device comprises: identifying whether there is a communication signal received to the communication circuitry in response to receiving the touch input; and determining that the first electronic pen establishes the communication connection with the electronic device and performing a predetermined function on the basis that the touch input and the communication signal are received simultaneously or in a predetermined time interval.

10. The notification and connection method of claim 7, wherein the establishing of the communication connection with the first electronic pen comprises: identifying whether there is a record of previous connection of the first electronic pen in a memory; and establishing the communication connection with the first electronic pen by using the communication circuitry in response to identifying that there is the record of connection of the first electronic pen.

11. The notification and connection method of claim 7, wherein the establishing of the communication connection with the first electronic pen comprises: identifying whether there is a record of previous connection of the first electronic pen in a memory; and outputting a pairing guide to the display in response to identifying that there is no record of connection of the first electronic pen.
