

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417003
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Xiang; Dalin et al.

Display panel and display apparatus with additional electrode layer for improving mutual capacitance variation

Abstract

The present disclosure provides a display panel and a display apparatus. The display panel includes: a display substrate; a touch electrode layer on a light outgoing side of a display substrate and including at least one first electrode and at least one second electrode, which intersect with each other and are insulated from each other; an additional electrode layer in a layer different from the touch electrode layer and including at least one first additional electrode, wherein an orthographic projection of the at least one first additional electrode on the display substrate at least partially overlaps an orthographic projection of a corresponding first electrode on the display substrate; and an insulating layer between the additional electrode layer and the touch electrode layer; wherein the at least one first additional electrode is connected to the corresponding first electrode through at least one first via in the insulating layer.

Inventors: Xiang; Dalin (Beijing, CN), Li; Yuanyuan (Beijing, CN), Bo; Zewen (Beijing, CN)

Applicant: BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Family ID: 1000008819042

Assignee: BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Appl. No.: 18/761081

Filed: July 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240353965 A1	Oct. 24, 2024

Foreign Application Priority Data

CN	202010720017.X	Jul. 24, 2020
CN	202011042892.3	Sep. 28, 2020

Related U.S. Application Data

continuation parent-doc US 17770029 US 12073049 WO PCT/CN2021/108135 20210723 child-doc US 18761081

Publication Classification

Int. Cl.: G06F3/044 (20060101); G06F3/041 (20060101)

U.S. Cl.:

CPC G06F3/0446 (20190501); G06F3/0412 (20130101); G06F3/0448 (20190501); G06F2203/04111 (20130101); G06F2203/04112 (20130101)

Field of Classification Search

CPC: G06F (3/044-0448); G06F (2203/04107); G06F (2203/04111); G06F (2203/04112)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0181943	12/2012	Bulea	345/174	G06F 3/041
2015/0116252	12/2014	Park	345/173	G06F 3/0445
2017/0010738	12/2016	Kurasawa	N/A	G06F 3/04166
2018/0004326	12/2017	Kim	N/A	N/A
2018/0348902	12/2017	Zhang	N/A	N/A
2020/0210025	12/2019	Kim	N/A	N/A
2021/0066401	12/2020	Won	N/A	G06F 3/0446

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103926728	12/2013	CN	N/A
106201151	12/2015	CN	N/A

OTHER PUBLICATIONS

WIPO, International search report issued Oct. 26, 2021 for application No. PCT/CN2021/108135. cited by applicant
USPTO, First Office Action issued Oct. 26, 2023 for U.S. Appl. No. 17/770,029. cited by applicant
USPTO, Final Office Action issued Feb. 7, 2024 for U.S. Appl. No. 17/770,029. cited by applicant
USPTO, Notice of allowance issued Apr. 24, 2024 for U.S. Appl. No. 17/770,029. cited by applicant

Primary Examiner: Flores; Roberto W
Attorney, Agent or Firm: HOUTTEMAN LAW LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This is a continuation application of U.S. patent application Ser. No. 17/770,029, filed on Apr. 18, 2022, which claims priorities of the Chinese Patent Application No. 202010720017.X filed on Jul. 24, 2020 and the Chinese Patent Application No. 202011042892.3 filed on Sep. 28, 2020, the contents of which are incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates to the field of display technology, in particular to a display panel and a display apparatus.

BACKGROUND

(2) Currently, a touch function is generally required to be integrated in an OLED (Organic Light-Emitting Diode) display technology. Specifically, touch display of the OLED display panel may be implemented by forming touch electrodes on an OLED display substrate.

SUMMARY

(3) In a first aspect of the present disclosure, the present disclosure provides a display panel, including: a display substrate; and a touch electrode layer, which is arranged on a light outgoing side of the display substrate, and includes at least one first electrode and at least one second electrode, which intersect with each other and are insulated from each other; wherein the display panel further includes: an additional electrode layer, which is arranged in a layer different from the touch electrode layer and includes at least one first additional electrode; wherein an orthographic projection of the at least one first additional electrode on the display substrate at least partially overlaps an orthographic projection of the at least one first electrode on the display substrate; and an insulating layer, which is arranged between the additional electrode layer and the touch electrode layer; wherein the at least one first additional electrode is connected to the at least one first electrode through at least one first via in the insulating layer.

(4) In some embodiments of the present disclosure, the additional electrode layer further includes at least one second additional electrode, which is insulated from the at least one first additional electrode; and an orthographic projection of the at least one second additional electrode on the display substrate at least partially overlaps the orthographic projection of the at least one second electrode on the display substrate, and the at least one second additional electrode is connected to the at least one second electrode through at least one second via in the insulating layer.

(5) In some embodiments of the present disclosure, the orthographic projection of the at least one first electrode on the display substrate includes a first edge region, and the orthographic projection of the at least one first additional electrode on the display substrate overlaps the first edge region; and the orthogonal projection of the at least one second electrode on the display substrate includes a second edge region, and the orthogonal projection of the at least one second additional electrode on the display substrate overlaps the second edge region.

(6) In some embodiments of the present disclosure, the additional electrode layer further includes at least one bridge portion; and the at least one bridge portion is connected to the at least one first additional electrode; the at least one first electrode includes two first electrode blocks at both sides of one of the at least one second electrode; the at least one bridge portion electrically connects the two first electrode blocks together through at least two third vias in the insulating layer; or the at least one bridge portion is connected to the at least one second additional electrode; the at least one second electrode includes two second electrode blocks at both sides of one of the at least one first electrode; the at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias in the insulating layer.

(7) In some embodiments of the present disclosure, the at least one first via includes a plurality of

first vias, and orthographic projections of the plurality of first vias on the display substrate are uniformly distributed in an area where the orthographic projection of the at least one first additional electrode on the display substrate overlaps the orthographic projection of the at least one first electrode on the display substrate.

(8) In some embodiments of the present disclosure, the at least one second via includes a plurality of second vias, and orthographic projections of the plurality of second vias on the display substrate are uniformly distributed in an area where the orthographic projection of the at least one second additional electrode on the display substrate overlaps the orthographic projection of the at least one second electrode on the display substrate.

(9) In some embodiments of the present disclosure, the at least one first additional electrode includes a plurality of first additional electrodes, and orthographic projection of the plurality of first additional electrodes on the display substrate are distributed on a part of the first edge region or the whole first edge region of the orthographic projection of the at least one first electrode on the display substrate.

(10) In some embodiments of the present disclosure, the at least one second additional electrode includes a plurality of second additional electrodes, and orthographic projection of the plurality of second additional electrodes on the display substrate are distributed on a part of the second edge region or the whole second edge region of the orthographic projection of the at least one second electrode on the display substrate.

(11) In some embodiments of the present disclosure, the orthographic projection of the at least one first additional electrode on the display substrate fully overlaps the orthographic projection of the at least one first electrode on the display substrate.

(12) In some embodiments of the present disclosure, the orthographic projection of the at least one second additional electrode on the display substrate fully overlaps the orthographic projection of the at least one second electrode on the display substrate.

(13) In some embodiments of the present disclosure, the touch electrode layer includes a plurality of sub-units arranged in an array along a first direction and a second direction; and each of the plurality of sub-units includes at least one first electrode and at least one second electrode, which include a plurality of first inter-digital electrodes and a plurality of second inter-digital electrodes, respectively, extending along the first direction and alternately arranged in the second direction.

(14) In some embodiments of the present disclosure, the additional electrode layer includes bridge portions, and each of the plurality of sub-units corresponds to one of the bridge portions.

(15) In some embodiments of the present disclosure, the at least one first electrode and the at least one second electrode are mesh-shaped; the additional electrode layer is mesh-shaped.

(16) In some embodiments of the present disclosure, each of the at least one first electrode and the at least one second electrode is made of a titanium/aluminum/titanium laminated material.

(17) In some embodiments of the present disclosure, the additional electrode layer is made of a titanium/aluminum/titanium laminated material.

(18) In some embodiments of the present disclosure, the insulating layer is made of a silicon nitride material or silicon oxide material.

(19) In some embodiments of the present disclosure, a mesh located at a boundary between the at least one first electrode and the at least one second electrode includes a plurality of metal wires, any two adjacent of which have a fracture therebetween, such that the at least one first electrode and the at least one second electrode are electrically insulated from each other.

(20) In some embodiments of the present disclosure, the display panel further includes a plurality of first floating electrodes; wherein the plurality of first floating electrodes and the touch electrode layer are in a same layer and spaced apart from each other and insulated from each other; and wherein the plurality of first floating electrodes are floated.

(21) In some embodiments of the present disclosure, the display panel further includes at least one second floating electrode; wherein the at least one second floating electrode and the additional

electrode layer are in a same layer, and insulated from each other; an orthographic projection of the at least one second floating electrode and the additional electrode layer on the display substrate overlaps an orthographic projection of the plurality of first floating electrodes and the touch electrode layer on the display substrate.

(22) In a second aspect of the present disclosure, there is also provided a display apparatus including the display panel according to any one of the embodiments of the first aspect of the present disclosure.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic top view illustrating a structure of an additional electrode layer in a display panel according to an embodiment of the present disclosure;
- (2) FIG. 2 is a schematic top view illustrating a structure of a touch electrode layer in a display panel according to an embodiment of the present disclosure;
- (3) FIG. 3 is a schematic cross-sectional view illustrating a structure of a display panel according to an embodiment of the present disclosure;
- (4) FIG. 4 is a schematic top view illustrating a structure at a position of a bridge portion in a display panel according to an embodiment of the present disclosure;
- (5) FIG. 5 is a schematic top view illustrating a structure of an additional electrode layer in another display panel according to an embodiment of the present disclosure;
- (6) FIG. 6 is a schematic top view illustrating a structure of a touch electrode layer in another display panel according to an embodiment of the present disclosure;
- (7) FIGS. 7a to 7c are schematic diagrams illustrating a process for manufacturing a display panel according to an embodiment of the present disclosure;
- (8) FIG. 8 is a schematic top view illustrating a structure of a touch electrode layer in a display panel according to another embodiment of the present disclosure;
- (9) FIG. 9 is a schematic top view illustrating a structure of an additional electrode layer in a display panel according to another embodiment of the present disclosure;
- (10) FIG. 10 is a schematic cross-sectional view illustrating a structure of a display panel according to another embodiment of the present disclosure; and
- (11) FIG. 11 is a schematic top view of an electrode of an additional electrode layer in a display panel according to another embodiment of the present disclosure.

REFERENCE NUMBERS ARE

- (12) 1. display substrate; 2. touch electrode layer; 21. first electrode; 210. first electrode block; 22. second electrode; 211. edge region; 23. bridge portion; 200. sub-unit; 3. additional electrode layer; 31. first additional electrode; 32. second additional electrode; 4. insulating layer; 41. first via; 42. second via; 43. third via; 5. planarization layer; 6. first transparent adhesive layer; 7. polarizer; 8. second transparent adhesive layer; 9. cover plate; 10. first floating electrode. 22. second electrode; 220. second electrode block; 221. connection electrode; 11. second floating electrode; 300. fracture.

DETAIL DESCRIPTION OF EMBODIMENTS

(13) In order to enable one of ordinary skill in the art to better understand the technical solutions of the present disclosure, a display panel and a display apparatus of the present disclosure are further described in detail below with reference to the accompanying drawings and the detailed description.

(14) A capacitance variation between a driving electrode and a sensing electrode in a mutual capacitance type touch is an important parameter which affects the touch performance. Films on a touch electrode in an OLED display panel become thicker, or a touch electrode has a larger load due to a larger capacitance formed between the touch electrode and a metal film (e.g., a cathode)

located below the touch electrode, so that a mutual capacitance variation of the touch electrode during a mutual capacitance touch is very small. For example, a mutual capacitance variation between an active pen and a touch screen is only several femtoFaradays (fF). These small variations not only affect touch performances such as touch accuracy, linearity, jitter, etc., but also are easily covered by various interferences in an external environment, so that a touch chip (Touch IC) cannot detect whether the touch occurs.

(15) In view of the problem that the film on the touch electrode is thicker or the load of the touch electrode is larger, so that the mutual capacitance variation during the touch is very small and thus, it is difficult to detect whether the touch occurs, the present disclosure provides a display panel and a display apparatus. In the display panel provided by the present disclosure, an additional electrode layer is provided, such that the mutual capacitance variation of the display panel during the touch is increased, and the touch sensitivity and accuracy of the display panel are improved.

(16) FIG. 1 is a schematic top view illustrating a structure of an additional electrode layer in a display panel according to an embodiment of the present disclosure; FIG. 2 is a schematic top view illustrating a structure of a touch electrode layer in a display panel according to an embodiment of the present disclosure; FIG. 3 is a schematic cross-sectional view illustrating a structure of a display panel according to an embodiment of the present disclosure. As shown in FIGS. 1 to 3, a display panel in the embodiment of the present disclosure includes: a display substrate **1** and a touch electrode layer **2** arranged on a light outgoing side of the display substrate **1**, wherein the touch electrode layer **2** includes at least one first electrode **21** and at least one second electrode **22**, which intersect with each other and are insulated from each other. The display panel further includes an additional electrode layer **3**, which is arranged in a layer different from the touch electrode layer **2**, and includes at least one first additional electrode **31**; an orthographic projection of the at least one first additional electrode **31** on the display substrate **1** at least partially overlaps an orthographic projection of the at least one first electrode **21** on the display substrate **1**. An insulating layer **4** is arranged between the additional electrode layer **3** and the touch electrode layer **2**; the at least one first additional electrode **31** is connected to a corresponding first electrode **21** through at least one first via **41** in the insulating layer **4**.

(17) In some embodiments of the present disclosure, the at least one first additional electrode **31** is connected in parallel with the corresponding first electrode **21** through at least one first via **41** in the insulating layer **4**. In some embodiments of the present disclosure, the at least one first via is provided in the insulating layer **4**, and the reference number **41** shown in FIG. 2 only indicates a positional relationship between the first via and the touch electrode layer **2**.

(18) In some embodiments of the present disclosure, the orthographic projection of the at least one first electrode **21** on the display substrate **1** includes a first edge region, and the orthographic projection of the at least one first additional electrode **31** on the display substrate **1** overlaps the first edge region.

(19) Optionally, the additional electrode layer **3** further includes at least one second additional electrode **32**, which is insulated from the at least one first additional electrode **31**. The at least one second additional electrode **32** is connected to a corresponding second electrode **22** through at least one second via **42** in the insulating layer **4**. An orthographic projection of the at least one second additional electrode **32** on the display substrate **1** at least partially overlaps an orthographic projection of the corresponding second electrode **22** on the display substrate **1**. The at least one second additional electrode **32** is connected to the corresponding second electrode **22** through at least one second via **42** in the insulating layer **4**.

(20) In some embodiments of the present disclosure, the orthogonal projection of the at least one second electrode **22** on the display substrate **1** includes a second edge region, and the orthogonal projection of the at least one second additional electrode **32** on the display substrate **1** overlaps the second edge region.

(21) FIG. 2 shows edge regions **211**, each of which includes the first edge region and the second

edge region.

(22) In some embodiments of the present disclosure, each edge region **211** extends along a first direction (Y direction) or a second direction (X direction). For example, the edge region **211** shown in FIG. 2 includes an edge of one first electrode **21** and an edge of one second electrode **22**. FIG. 2 only shows the edge region **211** extending in the Y direction, and an edge region extending in the X direction is not shown. As shown in FIGS. 1 and 2, the first direction Y and the second direction X are perpendicular to each other in a plane where the display panel is located (a plane of the display panel).

(23) In some embodiments of the present disclosure, the at least one first electrode **21** is a driving electrode, and the at least one second electrode **22** is a sensing electrode. Alternatively, the at least one first electrode **21** is a sensing electrode and the at least one second electrode **22** is a driving electrode. The at least one first electrode **21** and the at least one second electrode **22** intersect with each other and are insulated from each other, thereby achieving a mutual capacitance touch. In the edge region **211**, electric wires between the first electrode **21** and the second electrode **22** are relatively dense, so that the capacitance variation between the first electrode **21** and the second electrode **22** is relatively great during the touch. Therefore, the electric wires at the edge region **211** are increased, which may improve the touch sensitivity of the display panel.

(24) The additional electrode layer **3** is disposed in a layer different from the touch electrode layer **2**, and an orthogonal projection of the at least one first additional electrode **31** on the display substrate **1** at least partially overlaps an orthogonal projection of the corresponding first electrode **21** on the display substrate **1**, and the at least one first additional electrode **31** in the additional electrode layer **3** is connected to the corresponding first electrode **21**. In this way, the number of electric wires of the first electrode **21** and the second electrode **22** at the edge region **211** is increased, so that an electric field of the first electrode **21** and the second electrode **22** at the edge region **211** is enhanced, and further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased. Furthermore, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs. On the other hand, the at least one first additional electrode **31** is connected in parallel with the corresponding first electrode **21**, so that the overall resistance of the display panel is reduced, and further, the path resistances of the first electrode **21** and the second electrode **22** are reduced along an extending direction of the first electrode **21**, a difference between a product of a resistance and a capacitance at one end of the first electrode **21** and a product of a resistance and a capacitance at the other end of the first electrode **21** is reduced, the uniformity of electrical signals throughout the first electrode **21** is improved, thereby improving touch performances, such as linearity, accuracy, report rate, floating performance and the like, of the touch electrode.

(25) Optionally, the at least one first via **41** includes a plurality of first vias **41**. Orthographic projections of the plurality of first vias **41** on the display substrate **1** are uniformly distributed in the area where the orthographic projection of the at least one first additional electrode **31** on the display substrate **1** overlaps the orthographic projection of the corresponding first electrode **21** on the display substrate **1**. The plurality of first vias **41** are provided, which ensures the robustness of the electrical connection between the first additional electrode **31** and the corresponding first electrode **21**. In addition, the first additional electrode **31** is connected in parallel with the corresponding first electrode **21**, so that the overall resistance of the display panel is reduced, and the touch performance of the touch electrode is improved. Meanwhile, a larger process margin may be reserved in the process for manufacturing the first vias **41**, the process difficulty is reduced, and the yield is improved.

(26) In the embodiment of the present disclosure, as shown in FIGS. 1 and 2, the first electrodes **21**, the first additional electrodes **31** and the first vias **41** are correspondingly disposed.

(27) The at least one second additional electrode 32 in the additional electrode layer 3 is connected to the corresponding second electrode 22. In this way, the number of electric wires of the first electrode 21 and the second electrode 22 at the edge region 211 is further increased, so that an electric field of the first electrode 21 and the second electrode 22 at the edge region 211 is further enhanced, and further, the mutual capacitance variation between the first electrode 21 and the second electrode 22 during the touch is increased. Furthermore, the touch sensitivity of the display panel is improved, and the problems are further solved or avoided that the films on the touch electrode layer 2 become thicker or the load of the touch electrode layer 2 is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs. On the other hand, the at least one second additional electrode 32 is connected in parallel with the corresponding second electrode 22, so that the overall resistance of the display panel is reduced, and further, the path resistances of the first electrode 21 and the second electrode 22 are reduced along an extending direction of the second electrode 22, a difference between a product of a resistance and a capacitance at one end of the second electrode 22 and a product of a resistance and a capacitance at the other end of the second electrode 22 is reduced, the uniformity of electrical signals throughout the second electrode 22 is improved, thereby improving touch performances, such as linearity, accuracy, report rate, floating performance and the like, of the touch electrode.

(28) In some embodiments of the present disclosure, the display panel includes at least one first additional electrode 31 and at least one second additional electrode 32, and includes at least one first electrode 21 and at least one second electrode 22. However, the present disclosure is not limited thereto. In other embodiments of the present disclosure, the display panel includes a plurality of first additional electrodes 31 and a plurality of second additional electrodes 32, and includes a plurality of first electrodes 21 and a plurality of second electrodes 22, as shown in FIGS. 1 and 2.

(29) In some embodiments of the present disclosure, the at least one second additional electrode 32 is connected in parallel with the corresponding second electrode 22 through the at least one second via 42 in the insulating layer 4. In some embodiments of the present disclosure, the at least one second via 42 is provided in the insulating layer 4, and the reference number 42 shown in FIG. 2 only represents a positional relationship between the second via and the touch electrode layer 2.

(30) Optionally, the at least one second via 42 includes a plurality of second vias 42. Orthographic projections of the plurality of second vias 42 on the display substrate 1 are uniformly distributed in the area where the orthographic projection of the at least one second additional electrode 32 on the display substrate 1 overlaps the orthographic projection of the corresponding second electrode 22 on the display substrate 1. The plurality of second vias 42 are provided, which ensures the robustness of the electrical connection between the second additional electrode 32 and the corresponding second electrode 22. In addition, the second additional electrode 32 is connected in parallel with the corresponding second electrode 22, so that the overall resistance of the display panel is reduced, and the touch performance of the touch electrode is improved. Meanwhile, a larger process margin may be reserved in the process for manufacturing the second vias 42, the process difficulty is reduced, and the yield is improved.

(31) In the embodiment of the present disclosure, as shown in FIGS. 1 and 2, the second electrodes 22, the second additional electrodes 32 and the second vias 42 are correspondingly disposed.

(32) It should be noted that in this embodiment, the additional electrode layer 3 is provided on the display substrate 1. Alternatively, the additional electrode layer 3 may also be disposed on a side of the touch electrode layer 2 away from the display substrate 1.

(33) It should be noted that, the additional electrode layer 3 may be provided with only the at least one first additional electrode 31 or only the at least one second additional electrode 32. Alternatively, the additional electrode layer 3 may also be provided with both the at least one first additional electrode 31 and the at least one second additional electrode 32, as shown in FIG. 1.

(34) Optionally, the display substrate 1 includes a back plate provided with a driving circuit, an

array of sub-pixels disposed on the back plate, and an encapsulation layer for encapsulating the sub-pixels. The display substrate **1** further includes a buffer layer, which is arranged on the encapsulation layer, and the buffer layer is favorable for forming the touch electrode layer **2** thereon. In some embodiments of the present disclosure, the sub-pixels may be OLED light emitting elements, and may alternatively be LED or Micro LED light emitting elements.

(35) Optionally, the display panel further includes a planarization layer **5**, a first transparent adhesive layer **6**, a polarizer **7**, a second transparent adhesive layer **8**, and a cover plate **9**, which are sequentially disposed on a side of the touch electrode layer **2** away from the display substrate **1**. The first transparent adhesive layer **6** is used for adhering the planarization layer **5** and the polarizer **7** together; the second transparent adhesive layer **8** is used for adhering the polarizer **7** and the cover plate **9** together. The polarizer **7** is used for reducing the reflectivity of the display panel for light. The planarization layer **5** has a thickness in a range of 0.1 μm to 20 μm .

(36) Optionally, the at least one first electrode **21** and the at least one second electrode **22** are provided in a same layer. As shown in FIGS. **1** and **4**, the additional electrode layer **3** further includes at least one bridge portion **23**, and an orthogonal projection of the at least one bridge portion **23** on the display substrate **1** is located in an orthogonal projection of a position, where the at least one first electrode **21** and the at least one second electrode **22** intersect with each other, on the display substrate **1**. The at least one bridge portion **23** is connected to the at least one first additional electrode **31**. The at least one first electrode **21** includes two first electrode blocks **210** located at two opposite sides of one of the at least one second electrode **22**. The at least one bridge portion **23** electrically connects the two first electrode blocks **210** together through at least two third vias **43** provided in the insulating layer **4**.

(37) Alternatively, the at least one bridge portion is connected to the at least one second additional electrode. The at least one second electrode includes two second electrode blocks located at two opposite sides of one of the at least one first electrode. The at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias provided in the insulating layer (not shown in the drawings).

(38) Optionally, the at least one first electrode **21** and the at least one second electrode **22** are provided in a same layer. As shown in FIG. **4**, the additional electrode layer **3** further includes at least one bridge portion **23**, and an orthogonal projection of the at least one bridge portion **23** on the display substrate **1** is located in an orthogonal projection of a position, where the at least one first electrode **21** and the at least one second electrode **22** intersect with each other, on the display substrate **1**. The at least one bridge portion **23** is electrically connected to the at least one first additional electrode **31**. The at least one first electrode **21** includes two first electrode blocks **210** extending in the X direction and located on two opposite sides of one of the at least one second electrode **22**. The at least one bridge portion **23** electrically connects the two first electrode blocks **210** together through at least two third vias **43** provided in the insulating layer **4**.

(39) Alternatively, the at least one bridge portion is electrically connected to the at least one second additional electrode. The at least one second electrode includes two second electrode blocks extending in the Y direction and located on two opposite sides of one of the at least one first electrode. The at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias provided in the insulating layer (not shown in the drawings).

(40) Specifically, in the embodiment of the present disclosure, as shown in FIGS. **1** and **2**, the at least one first electrode **21** is disconnected at the middle of each sub-unit **200**, and thus, the at least one first electrode **21** is divided into two portions (i.e., the first electrode blocks **210**), while the at least one second electrode **22** is not disconnected. In other embodiments of the present disclosure, as shown in FIGS. **5** and **6**, the at least one first electrode **21** may be not disconnected at the middle of each sub-unit **200**, while the at least one second electrode **22** is disconnected at the middle of each sub-unit **200**, such that the second electrode **22** includes two portions (i.e., the second electrode blocks **220**). In the embodiment of the present disclosure, the at least one bridge portion

23 is disposed at a position corresponding to a position where the first electrode **21** or the second electrode **22** in the touch electrode layer **2** is disconnected, such that an orthographic projection of the at least one bridge portion **23** on the display substrate **1** is located at the position where the first electrode **21** or the second electrode **22** is disconnected. Further, in a case where the at least one second electrode **22** is disconnected at the middle, the at least one bridge portion **23** is connected to the at least one first additional electrode **31** and electrically connects the two adjacent second electrode blocks **220** together through the third vias **43** in the insulating layer **4**. Alternatively, in the case where the at least one first electrode **21** is disconnected at the middle, the at least one bridge portion **23** is connected to the at least one second additional electrode **32** and electrically connects the two adjacent first electrode blocks together through third vias in the insulating layer.

(41) In some embodiments of the present disclosure, as shown in FIG. **1**, the display panel includes a plurality of first additional electrodes **31** and a plurality of second additional electrodes **32** disposed in the additional electrode layer **3** and arranged in the X direction, wherein each of the first additional electrodes **31** and each of the second additional electrodes **32** extend in the Y direction; the plurality of first additional electrodes **31** are disposed in pairs, and the plurality of second additional electrodes **32** are disposed in pairs; each pair of first additional electrodes **31** is arranged in the X direction; one second additional electrode **32** is provided on each of two opposite sides in each pair of first additional electrodes **31**; wherein each second additional electrode **32** is disconnected at a position corresponding to the bridge portion **23** in a length direction of the second additional electrode **32**. In some embodiments of the present disclosure, as shown in FIG. **1**, the display panel includes seven pairs of first additional electrodes **31** and seven pairs of second additional electrodes **32**.

(42) In some embodiments of the present disclosure, as shown in FIGS. **1** and **2**, the display panel includes a plurality of first electrodes **21** and a plurality of second electrodes **22** disposed in the touch electrode layer **2**, and each first electrode **21** and each second electrode **22** correspond to a pair of first additional electrodes **31** and a pair of second additional electrodes **32**, respectively. Specifically, as shown in FIGS. **1** and **2**, orthographic projections of a pair of first additional electrodes **31** on the display substrate **1** are located on two opposite sides of orthographic projection of two adjacent first electrodes **21** on the display substrate **1** in a width direction (the X direction); orthographic projections of a pair of second additional electrodes **32** on the display substrate **1** are located on two opposite sides of an orthographic projection of one second electrode **22** on the display substrate **1** in a width direction (the X direction). In some embodiments of the present disclosure, the touch electrode layer **2** further includes a plurality of first floating electrodes **10** extending along the Y direction, which are respectively located at the outermost sides of the touch electrode layer **2**.

(43) As shown in FIG. **2**, the display panel includes eight first electrodes **21** extending in the Y direction and seven second electrodes **22** extending in the Y direction, wherein the outermost two first additional electrodes **31** in the additional electrode layer **3** are connected to a side of each of the outermost two first electrodes **21** close to the corresponding second electrode **22**, respectively; there is no first additional electrodes **31** connected to a side of each of the outermost two first electrodes **21** close to the corresponding first floating electrode **10**.

(44) In addition, as shown in FIG. **2**, the touch electrode layer **2** further includes a first electrode **21** extending in the X direction and intersecting with each of the plurality of first electrodes **21** extending in the Y direction, and the first electrode **21** extending in the X direction is disconnected at a position corresponding to a bridge portion **23** and divides each of the plurality of second electrodes **22** extending in the Y direction into two portions (i.e., an upper portion and a lower portion), which correspond to the disconnected second additional electrode **32**, respectively. As shown in FIG. **2**, the first electrode **21** extending in the X direction is disconnected at a position corresponding to the bridge portion **23** (i.e., the first electrode **21** extending in the X direction includes the first electrode blocks **210**), while the second electrode **22** extending in the Y direction

and passing through the position corresponding to the bridge portion **23** is not disconnected. However, the present disclosure is not limited thereto. In other embodiments of the present disclosure, the first electrode **21** extending in the X direction is not disconnected at the position corresponding to the bridge portion **23**, while the second electrode **22** extending in the Y direction and passing through the position corresponding to the bridge portion **23** is disconnected (i.e., the second electrode **22** includes the second electrode blocks **220**). As shown in FIG. **6**, in each of the sub-units **200**, the corresponding first electrode **21** and second electrode **22** are disposed in such a manner.

(45) In some embodiments of the present disclosure, as shown in FIGS. **1** to **4**, the bridge portion **23** has a length direction coinciding with the X direction and a width direction coinciding with the Y direction; the bridge portion **23** is electrically connected to the two adjacent first electrode blocks **210** in the X direction, respectively, through a plurality of third vias **43** in the insulating layer **4** (that is, the bridge portion **23** electrically connects two portions of the first electrode **21** extending in the X direction, which is disconnected at the position corresponding to the bridge portion **23**, together through the plurality of third vias **43** in the insulating layer **4**). However, the present disclosure is not limited thereto. In other embodiments of the present disclosure, the width direction of the bridge portion **23** coincides with the X direction, and the length direction of the bridge portion **23** coincides with the Y direction; the bridge portion **23** is electrically connected to two adjacent second electrode blocks **220** in the Y direction, respectively, through the plurality of third vias **43** in the insulating layer **4** (i.e., the bridge portion **23** electrically connects two portions of the second electrode **22** extending in the Y direction, which is disconnected at the position corresponding to the bridge portion **23**, together through the plurality of third vias **43** in the insulating layer **4**). As shown in FIGS. **5** and **6**, in each of the sub-units **200**, the corresponding bridge portion **23** and the disconnected second electrode **22** are disposed in such a manner.

(46) The first direction Y and the second direction X intersect with each other. The first direction Y and the second direction X may be perpendicular to each other or may not be perpendicular to each other.

(47) It should be noted that compared with the case where the at least one first electrode **21**, the at least one second electrode **22** and the additional electrode layer **3** may be provided in three different layers, respectively, when the at least one first electrode **21** and the at least one second electrode **22** are provided in a same layer, and the bridge portion **23** connecting two portions of the first electrode **21** or the second electrode **22**, and the at least one first additional electrode **31** and the at least one second additional electrode **32** of the additional electrode layer **3** are provided in the other layer, a thickness of the display panel may be reduced, which may improve the touch accuracy and the touch sensitivity of the touch electrode.

(48) Optionally, orthographic projections of the plurality of first additional electrodes **31** on the display substrate **1** are distributed on a part of the first edge region or the whole first edge region of the orthographic projection of the corresponding first electrode **21** on the display substrate **1**. That is, the plurality of first additional electrodes **31** may be distributed locally at the edge of the corresponding first electrode **21**, or may be distributed at the entire edge of the corresponding first electrode **21**. Compared with the case that the plurality of first additional electrodes **31** are distributed locally in the first edge region, the plurality of first additional electrodes **31** are distributed in the entire first edge region, so that the electric field of the first electrode **21** and the second electrode **22** in the edge region **211** may be better enhanced. Further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs, thereby improving the touch quality.

(49) Optionally, orthographic projections of the plurality of second additional electrodes **32** on the

display substrate **1** are distributed on a part of the second edge region or the whole first edge region of the orthographic projection of the corresponding second electrode **22** on the display substrate **1**. That is, the plurality of second additional electrodes **32** may be distributed locally at the edge of the corresponding second electrode **22**, or may be distributed at the entire edge of the corresponding second electrode **22**. Compared with the case that the plurality of second additional electrodes **32** are distributed locally in the second edge region, the plurality of second additional electrodes **32** are distributed in the entire second edge region, so that the electric field of the first electrode **21** and the second electrode **22** in the edge region **211** may be better enhanced. Further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs, thereby improving the touch quality.

(50) Optionally, the first additional electrode **31** may not necessarily be a linear electrode extending only in one direction (e.g., the Y direction in FIG. 2). The first additional electrode **31** may have a same shape as the first electrode **21**, i.e., the orthographic projection of the first additional electrode **31** on the display substrate **1** is rectangular and overlaps the orthographic projection of the corresponding first electrode **21** on the display substrate **1**. With such an arrangement, the electric field of the first electrode **21** and the second electrode **22** in the edge region **211** may be better enhanced. Further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs.

(51) Optionally, the second additional electrode **32** may not necessarily be a linear electrode extending only in one direction (e.g., the Y direction in FIG. 2). The second additional electrode **32** may have a same shape as the second electrode **22**, i.e., the orthographic projection of the second additional electrode **32** on the display substrate **1** is rectangular and overlaps the orthographic projection of the corresponding second electrode **22** on the display substrate **1**. With such an arrangement, the electric field of the first electrode **21** and the second electrode **22** in the edge region **211** may be better enhanced. Further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs.

(52) Optionally, as shown in FIG. 6, the touch electrode layer **2** includes a plurality of sub-units **200** arranged in an array (two rows and three columns shown in FIG. 6); each of the sub-units **200** includes at least one first electrode **21** and at least one second electrode **22**, which include a plurality of first inter-digital electrodes and a plurality of second inter-digital electrodes, respectively, extending along the first direction Y and alternately arranged in the second direction X. The first direction Y is a column direction of the array; the second direction X is a row direction of the array.

(53) In some embodiments of the present disclosure, each sub-unit **200** may include at least one first electrode **21** and at least one second electrode **22**. However, the present disclosure is not limited thereto. In other embodiments of the present disclosure, each of the sub-units **200** may include a plurality of first electrodes **21** and a plurality of second electrodes **22**, as shown in FIG. 6.

(54) As shown in FIG. 5, the additional electrode layer **3** is shown including a plurality of bridge portions **23** and a plurality of first additional electrodes **31** and a plurality of second additional electrodes **32**. Here, each bridge portion **23** and the corresponding first additional electrodes **31** and

second additional electrodes **32** are arranged in one sub-unit **200**.

(55) In the embodiment of the present disclosure, the number of the first additional electrodes **31**, the second additional electrodes **32**, the first electrodes **21**, and the second electrodes **22** is not particularly required. For example, the number of the first additional electrodes **31** and the second additional electrodes **32** shown in FIG. 5 is different from that shown in FIG. 1. The number of the first electrodes **21** and the second electrodes **22** of each of the sub-units **200** shown in FIG. 6 is different from that shown in FIG. 2.

(56) Optionally, as shown in FIG. 6, the first electrodes **21** include a plurality of first electrode blocks **210**, two adjacent first electrode blocks **210** are electrically connected through a connection electrode **221** disposed in a same layer as the first electrode blocks **210**.

(57) It should be noted that the pattern and arrangement of the touch electrode layer **2** are not limited to those shown in FIGS. 2 and 6, and any other patterns and arrangements of the touch electrode layer **2** may be applied to the present embodiment for realizing the mutual capacitance touch.

(58) Optionally, as shown in FIGS. 1 and 5, the at least one bridge portion **23** includes one or more bridge portions **23**, and an orthographic projection of each bridge portion **23** on the display substrate **1** is located at a position where the corresponding first electrode **21** or the second electrode **22** is disconnected; the second direction X is the row direction of the array. The number of the bridge portions **23** is determined according to the pattern and arrangement of the first electrodes **21** or the second electrodes **22**.

(59) Optionally, each first additional electrode **31** has a width in a range of 3 μm to 500 μm along the first direction Y or the second direction X; each second additional electrode **32** has a width in a range of 3 μm to 500 μm along the first direction Y or the second direction X. The first additional electrode **31** and the second additional electrode **32** have the above width, the electric field of the first electrode **21** and the second electrode **22** in the edge region **211** may be better enhanced. Further, the mutual capacitance variation between the first electrode **21** and the second electrode **22** during the touch is increased, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer **2** become thicker or the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs.

(60) Optionally, the at least one first electrode **21** and the at least one second electrode **22** are mesh-shaped. The additional electrode layer **3** is mesh-shaped.

(61) Optionally, as shown in FIG. 6, a mesh located at a boundary between the at least one first electrode **21** and the at least one second electrode **22** includes a plurality of metal wires, any two adjacent of which have a fracture **300** therebetween, such that the at least one first electrode **21** and the at least one second electrode **22** are electrically insulated from each other.

(62) Optionally, the at least one first electrode **21** and the at least one second electrode **22** each is made of a titanium/aluminum/titanium laminated material; the at least one first electrode **21** and the at least one second electrode **22** each has a mesh line width in a range of 3 μm to 20 μm , and a thickness in a range of 0.1 μm to 10 μm .

(63) Optionally, the additional electrode layer **3** is made of a titanium/aluminum/titanium laminated material; the additional electrode layer **3** has a mesh line width in a range of 3 μm to 20 μm , and a thickness in a range of 0.1 μm to 10 μm .

(64) Optionally, the insulating layer **4** is made of a silicon nitride or silicon oxide material, and has a thickness in a range of 0.1 μm to 10 μm .

(65) The layers have the above thickness, so that a thickness of the display panel is reduced and the touch performance of the display panel is improved.

(66) Optionally, as shown in FIG. 6, the display panel further includes the plurality of first floating electrodes **10**; the plurality of first floating electrodes **10** and the touch electrode layer **2** are disposed in a same layer, and are spaced from each other and insulated from each other; the

plurality of first floating electrodes **10** are independently disposed and floated. That is, the plurality of first floating electrodes **10** are not electrically connected to any electrode in the display panel, and no electrical signal is fed into the plurality of first floating electrodes **10**. The plurality of first floating electrodes **10** are mesh-shaped. In some embodiments of the present disclosure, the plurality of first floating electrodes **10** are separate electrodes that are not connected to any metal conductive layer. The capacitance between the touch electrode layer **2** and other conductive layers (such as a cathode) located below the touch electrode layer **2** may be reduced by providing the plurality of first floating electrodes **10**, so that the load of the touch electrode layer **2** is reduced, and the problems are solved or avoided that the load of the touch electrode layer **2** is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs.

(67) Finite element simulations were performed on a display panel in the related art and the display panel in the present embodiment, respectively. The laminated structure of the display panel in the present embodiment is shown in table 1. In the display panel in the related art, the disconnected two portions of the first electrode or the second electrode in the touch electrode layer **2** are connected together only through the bridge portion (i.e., the bridge portion connects two first electrode blocks or two second electrode blocks in the touch electrode layer **2** together), but the display panel in the related art does not include the first additional electrode and the second additional electrode in the embodiment of the present disclosure, and the other layers in the display panel in the related art have a same arrangement as the laminated structure of the display panel in the present embodiment. A simulation result is shown in table 2, from which it may be seen that compared to the display panel in the related art, in the display panel in the present embodiment, the sensing amount of the touch electrode is increased by 40 fF (i.e., by 38.6%), so that the anti-environmental-interference ability becomes stronger, and a resistance of the first electrode **21** is decreased from 27.8Ω to 21Ω, and the load of the first electrode **21** (a capacitance C.sub.S between the touch electrode layer and the additional electrode layer) is increased by only 6.6%, which still meets the requirement on driving parameters of the touch driving.

(68) TABLE-US-00001

TABLE 1	Laminated structure	Layers	Thickness (μm)	Dielectric constant
Cover plate	60	4.63	Transparent	adhesive layer
50	3.5	Polarizer	67	2
Planarization layer	2	3	Touch electrode	0.3
Insulating layer	0.4	3	Additional electrode layer	0.2
Buffer layer	0.3	6	Encapsulation layer	13
Cathode	0.008			

(69) TABLE-US-00002

TABLE 2	Simulation result	Related art	Present embodiment	Cs (pF)
11.82	12.59	Cm (pF)	0.382	0.452
ΔCm (pF)	0.104	0.144	ΔCm/Cm (%)	27.22%
31.8%	Cctx (pF)	0.67	0.780	Cfrx (pF)
0.83	0.83	Rs-Tx (Ω)	27.8	21
Rs-Rx (Ω)	31.5	31.5		

(70) In table 2, C.sub.S is the load (capacitance) between the touch electrode layer and the cathode in the design in the related art; and C.sub.S is the load between the touch electrode layer and the additional electrode layer in the design in the present embodiment. As may be seen from table 2, in the embodiment, the load of the touch electrode layer is increased by a small amount by providing one additional electrode layer. Cm is a basic mutual capacitance value of the touch electrode layer; ΔCm is the mutual capacitance variation; Δ Cm/Cm is a rate of the mutual capacitance variation (i.e., touch sensitivity); Cctx is a capacitance between a finger and the first electrode; Cfrx is a capacitance between the finger and the second electrode; Rs-Tx is the resistance of the first electrode; Rs-Rx is the resistance of the second electrode (in simulation, no additional electrode layer (i.e. parallel metal layer) is provided to be connected to the second electrode, so that the resistance of the second electrode is not changed in the design in the related art and the design in the present embodiment).

(71) Based on the above structure of the display panel, the present embodiment further provides a method for manufacturing a display panel, as shown in FIGS. 7a to 7c, including steps of: Step S01: forming the display substrate **1**, as shown in FIG. 7a; Step S01 includes forming the driving circuit, the array of sub-pixels, the encapsulation layer and the buffer layer on the substrate in

sequence.

(72) In the embodiment of the present disclosure, as shown in FIG. 7a, the display substrate **1** includes the substrate, and the driving circuit, the array of sub-pixels, the encapsulation layer and the buffer layer sequentially formed on the substrate. Step S02: forming the additional electrode layer **3** and the touch electrode layer **2** on a light outgoing side of the display substrate; Step S02 includes sequentially forming the additional electrode layer **3**, the insulating layer **4**, and the touch electrode layer **2** on the buffer layer, as shown in FIG. 7b. Step S03: sequentially forming the planarization layer **5**, the first transparent adhesive layer **6**, the polarizer **7**, the second transparent adhesive layer **8** and the cover plate **9** on the touch electrode layer **2**, as shown in FIG. 7c.

(73) Processes for forming layers in the manufacturing method all are the traditional processes, and are not described again.

(74) The embodiment of the present disclosure also provides a display panel. In the present embodiment, as shown in FIGS. **8** to **10**, the at least one bridge portion **23** is electrically connected to the corresponding first additional electrode **31** and spaced apart from the at least one second additional electrode **32**; and the at least one first electrode **21** and the at least one second electrode **22** are mesh-shaped; the additional electrode layer is mesh-shaped.

(75) In the present embodiment, the first electrode **21** and the second electrode **22** shown in FIG. **8** are the same as the first electrode **21** and the second electrode **22** shown in FIG. **6**.

(76) In the present embodiment, the sub-unit **200** includes a plurality of bridge portions **23** arranged in an array along the first direction Y and the second direction X, and the first additional electrodes **31** and the second additional electrodes **32** are disposed in rows or columns in which the bridge portions **23** are located. Each of the plurality of first additional electrodes **31** extends in the X direction; and each of the plurality of second additional electrodes **32** extends in the Y direction.

(77) In the present embodiment, in one sub-unit **200** of the touch electrode layer, the at least one first additional electrode **31** includes a plurality of first mesh electrodes, each of which has an extending direction parallel to an extending direction of a transverse mesh line in the at least one first electrode **21** (i.e. the second direction X), and the orthographic projection of the at least one first additional electrode **31** on the display substrate **1** falls into the orthographic projection of the corresponding first electrode **21** on the display substrate **1**. The at least one first additional electrode **31** is connected to the corresponding first electrode **21** through the plurality of first vias **41** in the insulating layer **4**. The at least one first additional electrode **31** is connected to the corresponding bridge portion **23**. In this way, the at least one first additional electrode **31** is connected in parallel with the corresponding first electrode **21**, so that the overall resistance of the display panel is reduced, and further, the path resistance of the first electrode **21** is reduced along an extending direction of the first electrode **21**, a difference between a product of a resistance and a capacitance at one end of the first electrode **21** and a product of a resistance and a capacitance at the other end of the first electrode **21** is reduced, the uniformity of electrical signals throughout the first electrode **21** is improved, thereby improving touch performances, such as linearity, accuracy, report rate, floating performance and the like, of the touch electrode.

(78) In the present embodiment, in one sub-unit **200** of the touch electrode layer, the at least one second additional electrode **32** includes a plurality of second mesh electrodes, each of which has an extending direction parallel to an extending direction of a longitudinal mesh line in the at least one second electrode **22** (i.e. the first direction Y), and the orthographic projection of the at least one second additional electrode **32** on the display substrate **1** falls into the orthographic projection of the corresponding second electrode **22** on the display substrate **1**. The at least one second additional electrode **32** is disconnected at a position where the at least one second additional electrode **32** intersects with the corresponding first additional electrode **31**. The at least one second additional electrode **32** is connected to the corresponding second electrode **22** through the plurality of second vias **42** in the insulating layer **4**. In this way, the at least one second additional electrode **32** is connected in parallel with the corresponding second electrode **22**, so that the overall resistance of

the display panel is reduced, and further, the path resistances of the first electrode **21** and the second electrode **22** are reduced along an extending direction of the second electrode **22**, a difference between a product of a resistance and a capacitance at one end of the second electrode **22** and a product of a resistance and a capacitance at the other end of the second electrode **22** is reduced, the uniformity of electrical signals throughout the second electrode **22** is improved, thereby improving touch performances, such as linearity, accuracy, report rate, floating performance and the like, of the touch electrode.

(79) In some embodiments of the present disclosure, the at least one first additional electrode **31** is connected in parallel with the corresponding first electrode **21** through the plurality of first vias **41** in the insulating layer **4**. In some embodiments of the present disclosure, the plurality of first vias **41** are provided in the insulating layer **4**, and the reference number **41** shown in FIG. **9** merely represents a positional relationship between the first via and the additional electrode layer **3**.

(80) In some embodiments of the present disclosure, the at least one second additional electrode **32** is connected in parallel with the corresponding second electrode **22** through the plurality of second vias **42** in the insulating layer **4**. In some embodiments of the present disclosure, the plurality of second vias **42** are provided in the insulating layer **4**, and the reference number **42** shown in FIG. **9** merely represents a positional relationship between the second via and the additional electrode layer **3**.

(81) In the present embodiment, as shown in FIG. **11**, the display panel further includes at least one second floating electrode **11**; the at least one second floating electrode **11** and the additional electrode layer are disposed in a same layer, and are insulated from each other; an orthographic projection of the at least one second floating electrode **11** and the additional electrode layer on the display substrate **1** overlaps an orthographic projection of the plurality of first floating electrodes **10** and the touch electrode layer on the display substrate **1**. The at least one second floating electrode **11** is provided so that a poor visual effect due to the light reflected by the additional electrode layer at sides may be avoided when viewing at a side viewing angle, and further, the problem may be avoided that metal wires of the additional electrode layer are visible when viewing at the side viewing angle.

(82) Other structures of the display panel and manufacturing methods for the display panel in the present embodiment are the same as those in the above embodiment, and are not described herein again.

(83) In the display panel provided in the present embodiment, the additional electrode layer is disposed in a layer different from the touch electrode layer, and the orthographic projection of the at least one first additional electrode on the display substrate at least partially overlaps the orthographic projection of the corresponding first electrode on the display substrate, and the at least one first additional electrode in the additional electrode layer is connected in parallel with the corresponding first electrode, and/or, the at least one second additional electrode in the additional electrode layer is connected in parallel with the corresponding second electrode, so that the number of electric wires of the first electrode and the second electrode at the edge region is increased, so that an electric field of the first electrode and the second electrode at the edge region is enhanced, and further, the mutual capacitance variation between the first electrode and the second electrode during the touch is increased. Furthermore, the touch sensitivity of the display panel is improved, and the problems are solved or avoided that the films on the touch electrode layer become thicker or the load of the touch electrode layer is larger, so that the mutual capacitance variation is very small and thus, it is difficult to detect whether the touch occurs. On the other hand, the at least one first additional electrode is connected in parallel with the corresponding first electrode, and/or, the at least one second additional electrode is connected in parallel with the corresponding second electrode, so that the overall resistance of the display panel is reduced, and further, the path resistances of the first electrode and the second electrode are reduced along an extending direction of the first electrode and/or the second electrode, a difference between a product of a resistance and

a capacitance at one end of the first electrode and/or the second electrode and a product of a resistance and a capacitance at the other end of the first electrode and/or the second electrode is reduced, the uniformity of electrical signals throughout the first electrode and/or the second electrode is improved, thereby improving touch performances, such as linearity, accuracy, report rate, floating performance and the like, of the touch electrode.

(84) The embodiment of the present disclosure further provides a display apparatus, which includes the display panel in the above embodiment.

(85) The display panel in the above embodiment is provided, such that the mutual capacitance variation of touch electrodes of the display apparatus during the touch is increased, the touch sensitivity of the display apparatus is improved, and the problems, that the film on the touch electrode is thicker or the load of the touch electrode is larger and therefore the mutual capacitance variation is very small and it is difficult to detect whether the touch occurs, of the display apparatus are solved or avoided, thereby improving the touch quality of the display apparatus.

(86) The display apparatus provided by the embodiment of the present disclosure may be any product or component with a display function, such as an OLED panel, an OLED television, an LED panel, an LED television, a Micro LED panel, a Micro LED television, a display, a mobile phone, a navigator and the like.

(87) It should be understood that the above embodiments are merely exemplary embodiments adopted to explain the principles of the present disclosure, and the present disclosure is not limited thereto. It will be apparent to one of ordinary skill in the art that various changes and modifications may be made therein without departing from the spirit and scope of the present disclosure, and such changes and modifications also fall within the scope of the present disclosure.

Claims

1. A display panel, comprising: a display substrate; and a touch electrode layer, which is arranged on a light outgoing side of the display substrate, and comprises at least one first electrode and at least one second electrode, which intersect with each other and are insulated from each other; wherein the display panel further comprises: an additional electrode layer, which is arranged in a layer different from the touch electrode layer and comprises at least one first additional electrode; wherein an orthographic projection of the at least one first additional electrode on the display substrate fully overlaps an orthographic projection of the at least one first electrode on the display substrate; and an insulating layer, which is arranged between the additional electrode layer and the touch electrode layer; wherein the at least one first additional electrode is connected to the at least one first electrode through at least one first via in the insulating layer; the additional electrode layer further comprises at least one second additional electrode, which is insulated from the at least one first additional electrode; and an orthographic projection of the at least one second additional electrode on the display substrate at least partially overlaps the orthographic projection of the at least one second electrode on the display substrate, and the at least one second additional electrode is connected to the at least one second electrode through at least one second via in the insulating layer; and the additional electrode layer further comprises at least one bridge portion; and the at least one bridge portion is connected to the at least one first additional electrode; the at least one first electrode comprises two first electrode blocks at both sides of one of the at least one second electrode; the at least one bridge portion electrically connects the two first electrode blocks together through at least two third vias in the insulating layer; or the at least one bridge portion is connected to the at least one second additional electrode; the at least one second electrode comprises two second electrode blocks at both sides of one of the at least one first electrode; the at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias in the insulating layer.

2. The display panel of claim 1, wherein the orthographic projection of an edge of each first

electrode of the at least one first electrode, close to an adjacent second electrode of this first electrode, on the display substrate comprises a first edge region, and the orthographic projection of a first additional electrode of the at least one first additional electrode, corresponding to this first electrode, on the display substrate overlaps the first edge region; and the orthographic projection of an edge of each second electrode of the at least one second electrode, close to an adjacent first electrode of this second electrode, on the display substrate comprises a second edge region, and the orthographic projection of a second additional electrode of the at least one second additional electrode, corresponding to this second electrode, on the display substrate overlaps the second edge region.

3. The display panel of claim 1, wherein the at least one first via comprises a plurality of first vias, and orthographic projections of the plurality of first vias on the display substrate are uniformly distributed in an area where the orthographic projection of the at least one first additional electrode on the display substrate overlaps the orthographic projection of the at least one first electrode on the display substrate.

4. The display panel of claim 3, wherein the at least one second via comprises a plurality of second vias, and orthographic projections of the plurality of second vias on the display substrate are uniformly distributed in an area where the orthographic projection of the at least one second additional electrode on the display substrate overlaps the orthographic projection of the at least one second electrode on the display substrate.

5. The display panel of claim 4, wherein the at least one first additional electrode comprises a plurality of first additional electrodes, and orthographic projection of the plurality of first additional electrodes on the display substrate are distributed in a part or an entirety of the first edge region of the orthographic projection of the at least one first electrode on the display substrate.

6. The display panel of claim 5, wherein the at least one second additional electrode comprises a plurality of second additional electrodes, and orthographic projection of the plurality of second additional electrodes on the display substrate are distributed on a part or an entirety of the second edge region the orthographic projection of the at least one second electrode on the display substrate.

7. The display panel of claim 1, wherein the orthographic projection of the at least one second additional electrode on the display substrate fully overlaps the orthographic projection of the at least one second electrode on the display substrate.

8. A display apparatus, comprising the display panel of claim 1.

9. A display panel, comprising: a display substrate; and a touch electrode layer, which is arranged on a light outgoing side of the display substrate, and comprises at least one first electrode and at least one second electrode, which intersect with each other and are insulated from each other; wherein the display panel further comprises: an additional electrode layer, which is arranged in a layer different from the touch electrode layer and comprises at least one first additional electrode; wherein an orthographic projection of the at least one first additional electrode on the display substrate fully overlaps an orthographic projection of the at least one first electrode on the display substrate; and an insulating layer, which is arranged between the additional electrode layer and the touch electrode layer; wherein the at least one first additional electrode is connected to the at least one first electrode through at least one first via in the insulating layer; the additional electrode layer further comprises at least one second additional electrode, which is insulated from the at least one first additional electrode; and an orthographic projection of the at least one second additional electrode on the display substrate at least partially overlaps the orthographic projection of the at least one second electrode on the display substrate, and the at least one second additional electrode is connected to the at least one second electrode through at least one second via in the insulating layer; and the additional electrode layer further comprises at least one bridge portion; and the at least one bridge portion is connected to the at least one first additional electrode; the at least one first electrode comprises two first electrode blocks at both sides of one of the at least one second

electrode; the at least one bridge portion electrically connects the two first electrode blocks together through at least two third vias in the insulating layer; or the at least one bridge portion is connected to the at least one second additional electrode; the at least one second electrode comprises two second electrode blocks at both sides of one of the at least one first electrode; the at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias in the insulating layer, wherein the touch electrode layer comprises a plurality of sub-units arranged in an array along a first direction and a second direction; and each of the plurality of sub-units comprises at least one first electrode and at least one second electrode, which comprise a plurality of first inter-digital electrodes and a plurality of second inter-digital electrodes, respectively, extending along the first direction and alternately arranged in the second direction.

10. The display panel of claim 9, wherein for each of the plurality of sub-units, the additional electrode layer is provided with a corresponding bridge portion of the at least one bridge portion.

11. The display panel of claim 10, wherein the at least one first electrode and the at least one second electrode are mesh-shaped; the additional electrode layer is mesh-shaped.

12. The display panel of claim 11, wherein each of the at least one first electrode and the at least one second electrode comprises a titanium/aluminum/titanium laminated material.

13. The display panel of claim 12, wherein the additional electrode layer comprises a titanium/aluminum/titanium laminated material.

14. The display panel of claim 13, wherein the insulating layer comprises a silicon nitride material or a silicon oxide material.

15. The display panel of claim 14, wherein a mesh located at a boundary between the at least one first electrode and the at least one second electrode comprises a plurality of metal wires, any two adjacent of which have a fracture therebetween, such that the at least one first electrode and the at least one second electrode are electrically insulated from each other.

16. A display panel, comprising: a display substrate; and a touch electrode layer, which is arranged on a light outgoing side of the display substrate, and comprises at least one first electrode and at least one second electrode, which intersect with each other and are insulated from each other; wherein the display panel further comprises: an additional electrode layer, which is arranged in a layer different from the touch electrode layer and comprises at least one first additional electrode; wherein an orthographic projection of the at least one first additional electrode on the display substrate fully overlaps an orthographic projection of the at least one first electrode on the display substrate; and an insulating layer, which is arranged between the additional electrode layer and the touch electrode layer; wherein the at least one first additional electrode is connected to the at least one first electrode through at least one first via in the insulating layer; the additional electrode layer further comprises at least one second additional electrode, which is insulated from the at least one first additional electrode; and an orthographic projection of the at least one second additional electrode on the display substrate at least partially overlaps the orthographic projection of the at least one second electrode on the display substrate, and the at least one second additional electrode is connected to the at least one second electrode through at least one second via in the insulating layer; and the additional electrode layer further comprises at least one bridge portion; and the at least one bridge portion is connected to the at least one first additional electrode; the at least one first electrode comprises two first electrode blocks at both sides of one of the at least one second electrode; the at least one bridge portion electrically connects the two first electrode blocks together through at least two third vias in the insulating layer; or the at least one bridge portion is connected to the at least one second additional electrode; the at least one second electrode comprises two second electrode blocks at both sides of one of the at least one first electrode; the at least one bridge portion electrically connects the two second electrode blocks together through at least two third vias in the insulating layer, the display panel further comprises at least one first floating electrode; wherein the at least one first floating electrode and the touch electrode layer are in a same layer, and spaced apart from each other and insulated from each other; and wherein the at

least one first floating electrode is floated.

17. The display panel of claim 16, further comprising at least one second floating electrode; wherein the at least one second floating electrode and the additional electrode layer are in a same layer, and insulated from each other; an orthographic projection of the at least one second floating electrode and the additional electrode layer on the display substrate overlaps an orthographic projection of the at least one first floating electrode and the touch electrode layer on the display substrate.

18. The display panel of claim 16, wherein the at least one second via comprises a plurality of second vias, and orthographic projections of the plurality of second vias on the display substrate are uniformly distributed in an area where the orthographic projection of the at least one second additional electrode on the display substrate overlaps the orthographic projection of the at least one second electrode on the display substrate.

19. The display panel of claim 16, wherein the at least one first additional electrode comprises a plurality of first additional electrodes, and orthographic projection of the plurality of first additional electrodes on the display substrate are distributed in a part or an entirety of the first edge region of the orthographic projection of the at least one first electrode on the display substrate; and the at least one second additional electrode comprises a plurality of second additional electrodes, and orthographic projection of the plurality of second additional electrodes on the display substrate are distributed on a part or an entirety of the second edge region the orthographic projection of the at least one second electrode on the display substrate.
