

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417219
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Pat; Ankit

Technologies for filtering and querying Trie data structures for generating real-time bot flow visualizations and analytics

Abstract

A method for filtering a Trie data structure for real-time bot flow visualization according to an embodiment includes receiving data associated with the Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event, receiving a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, performing a search of the Trie data structure to identify events of the Trie data structure to be deleted, deleting the identified events to generate an updated Trie data structure, updating event attributes of remaining events of the updated Trie data structure in response to deleting the identified events, and providing the updated Trie data structure for real-time bot flow visualization.

Inventors:	Pat; Ankit (Menlo Park, CA)
Applicant:	Genesys Cloud Services, Inc. (Menlo Park, CA)
Family ID:	1000008819089
Assignee:	Genesys Cloud Services, Inc. (Menlo Park, CA)
Appl. No.:	18/505900
Filed:	November 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250156389 A1	May. 15, 2025

Publication Classification

Int. Cl.: G06F16/22 (20190101); G06F16/23 (20190101); G06F16/2457 (20190101)

U.S. Cl.:

CPC **G06F16/2246** (20190101); **G06F16/23** (20190101); **G06F16/24573** (20190101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11252113	12/2021	Orkin	N/A	H04L 51/02
12153556	12/2023	Anand	N/A	G06F 16/2462
2014/0032555	12/2013	Kiff	707/737	G05B 19/042
2017/0109426	12/2016	Arora	N/A	G06F 16/24578
2021/0279225	12/2020	Jeon	N/A	G06F 16/2343
2024/0202096	12/2023	Pat	N/A	G06F 11/3438

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113779176	12/2020	CN	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion regarding the co-pending PCT application, having application No. PCT/US2024/055032, mailed on Jan. 27, 2025. cited by applicant

Primary Examiner: Raab; Christopher J

Attorney, Agent or Firm: Taft Stettinius & Hollister LLP

Background/Summary

BACKGROUND

(1) Call centers and other contact centers are used by many organizations to provide technical and other support to their end users. The end user may interact with human and/or virtual agents of the contact center by establishing electronic communications via one or more communication technologies including, for example, telephone, email, web chat, Short Message Service (SMS), dedicated software application(s), and/or other technologies. In particular, the end user may interact with an interactive voice response (IVR) system of the contact center that uses a series of predefined prompts and user responses to determine how to address the user's concerns, for example, by leveraging one or more bot flows defined by a contact center administrator.

SUMMARY

(2) One embodiment is directed to a unique system, components, and methods for filtering Trie data structures for real-time bot flow visualizations. Other embodiments are directed to apparatuses, systems, devices, hardware, methods, and combinations thereof for filtering Trie data structures for real-time bot flow visualizations.

(3) According to an embodiment, method for filtering a Trie data structure for real-time bot flow

visualization may include receiving, by a computing system, data associated with the Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event, receiving, by the computing system, a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, performing, by the computing system, a search of the Trie data structure to identify events of the Trie data structure to be deleted, deleting, by the computing system, the identified events to generate an updated Trie data structure, updating, by the computing system, event attributes of remaining events of the updated Trie data structure in response to deleting the identified events, and providing, by the computing system, the updated Trie data structure for real-time bot flow visualization.

(4) In some embodiments, receiving the user selection associated with filtering the Trie data structure may include receiving a user request to filter the Trie data structure by a selected bot flow.

(5) In some embodiments, performing the search of the Trie data structure to identify events of the Trie data structure to be deleted may include identifying events of the Trie data structure that are not associated with the selected bot flow.

(6) In some embodiments, receiving the user selection associated with filtering the Trie data structure may include receiving a user request to filter the Trie data structure to include only events that include a selected event attribute value.

(7) In some embodiments, performing the search of the Trie data structure to identify events of the Trie data structure to be deleted may include identifying events of the Trie data structure that do not include the selected event attribute value.

(8) In some embodiments, deleting the identified events to generate the updated Trie data structure may include updating parent-child relationships of events impacted by deletion of the identified events.

(9) In some embodiments, the method may further include identifying, by the computing system and subsequent to deleting the identified events, one or more sub-Trie data structures of an intermediate Trie data structure, wherein each sub-Trie data structure of the one or more sub-Trie data structures is a parent event having an updated parent-child relationship.

(10) In some embodiments, the method may further include merging, by the computing system, each of the one or more sub-Tries to generate the updated Trie data structure.

(11) In some embodiments, performing the search of the Trie data structure may include performing a depth first search of the Trie data structure.

(12) According to another embodiment, a system for filtering a Trie data structure for real-time bot flow visualization may include at least one processor and at least one memory comprising a plurality of instructions stored thereon that, in response to execution by the at least one processor, causes the system to receive data associated with the Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event, receive a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, perform a search of the Trie data structure to identify events of the Trie data structure to be deleted, delete the identified events to generate an updated Trie data structure, update event attributes of remaining events of the updated Trie data structure in response to deleting the identified events, and provide the updated Trie data structure for real-time bot flow visualization.

(13) In some embodiments, to receive the user selection associated with filtering the Trie data structure may include to receive a user request to filter the Trie data structure by a selected bot flow.

(14) In some embodiments, to perform the search of the Trie data structure to identify events of the Trie data structure to be deleted may include to identify events of the Trie data structure that are not associated with the selected bot flow.

(15) In some embodiments, to receive the user selection associated with filtering the Trie data

structure may include to receive a user request to filter the Trie data structure to include only events that include a selected event attribute value.

(16) In some embodiments, to perform the search of the Trie data structure to identify events of the Trie data structure to be deleted may include to identify events of the Trie data structure that do not include the selected event attribute value.

(17) In some embodiments, to delete the identified events to generate the updated Trie data structure may include to update parent-child relationships of events impacted by deletion of the identified events.

(18) In some embodiments, the plurality of instructions may further cause the system to identify, subsequent to deletion of the identified events, one or more sub-Trie data structures of an intermediate Trie data structure, wherein each sub-Trie data structure of the one or more sub-Trie data structures is a parent event having an updated parent-child relationship.

(19) In some embodiments, the plurality of instructions may further cause the system to merge each of the one or more sub-Tries to generate the updated Trie data structure.

(20) In some embodiments, to perform the search of the Trie data structure may include to perform a depth first search of the Trie data structure.

(21) According to yet another embodiment, one or more non-transitory machine-readable storage media may include a plurality of instructions stored thereon that, in response to execution by a computing system, causes the computing system to receive data associated with a Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event, receive a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, wherein the user selection requests that the Trie data structure be filtered to include only journeys that have a selected starting event, perform a search of the Trie data structure to identify each occurrence of the selected starting event in the Trie data structure, extract a sub-Trie data structure associated with each identified starting event, merge the extracted sub-Trie data structures to generate an updated Trie data structure, and provide the updated Trie data structure for real-time bot flow visualization.

(22) In some embodiments, to perform the search of the Trie data structure may include to perform a depth first search of the Trie data structure.

(23) This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used as an aid in limiting the scope of the claimed subject matter. Further embodiments, forms, features, and aspects of the present application shall become apparent from the descriptions and figures provided herewith.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The concepts described herein are illustrative by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. Where considered appropriate, references labels have been repeated among the figures to indicate corresponding or analogous elements.

(2) FIG. 1 depicts a simplified block diagram of at least one embodiment of a contact center system;

(3) FIG. 2 is a simplified block diagram of at least one embodiment of a computing device;

(4) FIG. 3 is a simplified flow diagram of at least one embodiment of a method for filtering a Trie data structure by a specific event;

(5) FIG. 4 is a simplified flow diagram of at least one embodiment a method for filtering a Trie data structure by an event attribute;

- (6) FIG. 5 is a simplified flow diagram of at least one embodiment of a method for filtering a Trie data structure by a bot flow;
- (7) FIGS. 6-7 illustrate various states of an example Trie data structure being filtered by a specific event;
- (8) FIGS. 8-10 illustrate various states of an example Trie data structure being filtered by an event attribute; and
- (9) FIGS. 11-12 illustrate various states of an example Trie data structure being filtered by a bot flow.

DETAILED DESCRIPTION

(10) Although the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described herein in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives consistent with the present disclosure and the appended claims.

(11) References in the specification to “one embodiment,” “an embodiment,” “an illustrative embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may or may not necessarily include that particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. It should be further appreciated that although reference to a “preferred” component or feature may indicate the desirability of a particular component or feature with respect to an embodiment, the disclosure is not so limiting with respect to other embodiments, which may omit such a component or feature. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to implement such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. Further, particular features, structures, or characteristics may be combined in any suitable combinations and/or sub-combinations in various embodiments.

(12) Additionally, it should be appreciated that items included in a list in the form of “at least one of A, B, and C” can mean (A); (B); (C); (A and B); (B and C); (A and C); or (A, B, and C). Similarly, items listed in the form of “at least one of A, B, or C” can mean (A); (B); (C); (A and B); (B and C); (A and C); or (A, B, and C). Further, with respect to the claims, the use of words and phrases such as “a,” “an,” “at least one,” and/or “at least one portion” should not be interpreted so as to be limiting to only one such element unless specifically stated to the contrary, and the use of phrases such as “at least a portion” and/or “a portion” should be interpreted as encompassing both embodiments including only a portion of such element and embodiments including the entirety of such element unless specifically stated to the contrary.

(13) The disclosed embodiments may, in some cases, be implemented in hardware, firmware, software, or a combination thereof. The disclosed embodiments may also be implemented as instructions carried by or stored on one or more transitory or non-transitory machine-readable (e.g., computer-readable) storage media, which may be read and executed by one or more processors. A machine-readable storage medium may be embodied as any storage device, mechanism, or other physical structure for storing or transmitting information in a form readable by a machine (e.g., a volatile or non-volatile memory, a media disc, or other media device).

(14) In the drawings, some structural or method features may be shown in specific arrangements and/or orderings. However, it should be appreciated that such specific arrangements and/or orderings may not be required. Rather, in some embodiments, such features may be arranged in a different manner and/or order than shown in the illustrative figures unless indicated to the contrary. Additionally, the inclusion of a structural or method feature in a particular figure is not meant to imply that such feature is required in all embodiments and, in some embodiments, may not be

included or may be combined with other features.

(15) It should be appreciated that the technologies described below provide user-friendly visualizations that help customer-experience managers of contact centers to improve the “big picture” bot experience by visualizing the flow milestones/outcomes in interactions which influence bot containment. More specifically, the illustrative technologies leverage a Trie data structure while allowing for filtering, searching, and/or querying to show events in customers' journeys starting at a particular event, events that include a particular attribute value, and/or events associated with a particular bot flow (e.g., executed by a bot or automated agent of the contact center system). Trie data structure implementations traditionally have drawbacks that limit their capabilities in certain use cases. For example, to enable filtering and querying capabilities based on any event and visualizing paths to/from that event, it is possible to simply create multiple Trie data structures, with one Trie data structure for each event or node within the Trie data structure. However, such an approach is computationally intensive and leads to significant scalability issues. Accordingly, the technologies described herein provide for a scalable solution that permits such types of filtering and querying using Trie data structures (i.e., without building separate Tries for each query event). Further, the technologies described herein allow for an online (e.g., cloud-based) computational approach while maintaining reasonable latency (e.g., latency that satisfies typical service level agreement requirements, such as maximum query responses of one second). Instead of creating a Trie for each filtering criterion, a single “big picture” Trie may be stored for each organization, which includes each of the bot flows and associated event attributes. This approach significantly reduces the processing and read/write operations required, resulting in improved efficiency. The reduced number of files and their corresponding read/write operations also result in lower operational cost. The system can also seamlessly integrate with various bot flows, allowing for diverse and customizable functionalities. It should be appreciated that a “Trie data structure” may be simplified referred to herein as a “Trie” for simplicity and brevity of the description. Further, although the technologies are described herein in reference to “bot flows,” it should be appreciated that similar technologies may be applied to other types of flows or client journeys in other embodiments.

(16) Referring now to FIG. 1, a simplified block diagram of at least one embodiment of a communications infrastructure and/or contact center system, which may be used in conjunction with one or more of the embodiments described herein, is shown. The contact center system **100** may be embodied as any system capable of providing contact center services (e.g., call center services, chat center services, SMS center services, etc.) to an end user and otherwise performing the functions described herein. The illustrative contact center system **100** includes a customer device **102**, a network **104**, a switch/media gateway **106**, a call controller **108**, an interactive media response (IMR) server **110**, a routing server **112**, a storage device **114**, a statistics server **116**, agent devices **118A**, **118B**, **118C**, a media server **120**, a knowledge management server **122**, a knowledge system **124**, chat server **126**, web servers **128**, an interaction (iXn) server **130**, a universal contact server **132**, a reporting server **134**, a media services server **136**, and an analytics module **138**. Although only one customer device **102**, one network **104**, one switch/media gateway **106**, one call controller **108**, one IMR server **110**, one routing server **112**, one storage device **114**, one statistics server **116**, one media server **120**, one knowledge management server **122**, one knowledge system **124**, one chat server **126**, one iXn server **130**, one universal contact server **132**, one reporting server **134**, one media services server **136**, and one analytics module **138** are shown in the illustrative embodiment of FIG. 1, the contact center system **100** may include multiple customer devices **102**, networks **104**, switch/media gateways **106**, call controllers **108**, IMR servers **110**, routing servers **112**, storage devices **114**, statistics servers **116**, media servers **120**, knowledge management servers **122**, knowledge systems **124**, chat servers **126**, iXn servers **130**, universal contact servers **132**, reporting servers **134**, media services servers **136**, and/or analytics modules **138** in other embodiments. Further, in some embodiments, one or more of the components described herein may

be excluded from the system **100**, one or more of the components described as being independent may form a portion of another component, and/or one or more of the component described as forming a portion of another component may be independent.

(17) It should be understood that the term “contact center system” is used herein to refer to the system depicted in FIG. 1 and/or the components thereof, while the term “contact center” is used more generally to refer to contact center systems, customer service providers operating those systems, and/or the organizations or enterprises associated therewith. Thus, unless otherwise specifically limited, the term “contact center” refers generally to a contact center system (such as the contact center system **100**), the associated customer service provider (such as a particular customer service provider/agent providing customer services through the contact center system **100**), as well as the organization or enterprise on behalf of which those customer services are being provided.

(18) By way of background, customer service providers may offer many types of services through contact centers. Such contact centers may be staffed with employees or customer service agents (or simply “agents”), with the agents serving as an interface between a company, enterprise, government agency, or organization (hereinafter referred to interchangeably as an “organization” or “enterprise”) and persons, such as users, individuals, or customers (hereinafter referred to interchangeably as “individuals,” “customers,” or “contact center clients”). For example, the agents at a contact center may assist customers in making purchasing decisions, receiving orders, or solving problems with products or services already received. Within a contact center, such interactions between contact center agents and outside entities or customers may be conducted over a variety of communication channels, such as, for example, via voice (e.g., telephone calls or voice over IP or VOIP calls), video (e.g., video conferencing), text (e.g., emails and text chat), screen sharing, co-browsing, and/or other communication channels.

(19) Operationally, contact centers generally strive to provide quality services to customers while minimizing costs. For example, one way for a contact center to operate is to handle every customer interaction with a live agent. While this approach may score well in terms of the service quality, it likely would also be prohibitively expensive due to the high cost of agent labor. Because of this, most contact centers utilize some level of automated processes in place of live agents, such as, for example, interactive voice response (IVR) systems, interactive media response (IMR) systems, internet robots or “bots”, automated chat modules or “chatbots”, and/or other automated processed. In many cases, this has proven to be a successful strategy, as automated processes can be highly efficient in handling certain types of interactions and effective at decreasing the need for live agents. Such automation allows contact centers to target the use of human agents for the more difficult customer interactions, while the automated processes handle the more repetitive or routine tasks. Further, automated processes can be structured in a way that optimizes efficiency and promotes repeatability. Whereas a human or live agent may forget to ask certain questions or follow-up on particular details, such mistakes are typically avoided through the use of automated processes. While customer service providers are increasingly relying on automated processes to interact with customers, the use of such technologies by customers remains far less developed. Thus, while IVR systems, IMR systems, and/or bots are used to automate portions of the interaction on the contact center-side of an interaction, the actions on the customer-side remain for the customer to perform manually.

(20) It should be appreciated that the contact center system **100** may be used by a customer service provider to provide various types of services to customers. For example, the contact center system **100** may be used to engage and manage interactions in which automated processes (or bots) or human agents communicate with customers. As should be understood, the contact center system **100** may be an in-house facility to a business or enterprise for performing the functions of sales and customer service relative to products and services available through the enterprise. In another embodiment, the contact center system **100** may be operated by a third-party service provider that

contracts to provide services for another organization. Further, the contact center system **100** may be deployed on equipment dedicated to the enterprise or third-party service provider, and/or deployed in a remote computing environment such as, for example, a private or public cloud environment with infrastructure for supporting multiple contact centers for multiple enterprises. The contact center system **100** may include software applications or programs, which may be executed on premises or remotely or some combination thereof. It should further be appreciated that the various components of the contact center system **100** may be distributed across various geographic locations and not necessarily contained in a single location or computing environment.

(21) It should further be understood that, unless otherwise specifically limited, any of the computing elements of the present invention may be implemented in cloud-based or cloud computing environments. As used herein and further described below in reference to the computing device **200**, “cloud computing”—or, simply, the “cloud”—is defined as a model for enabling ubiquitous, convenient, on-demand network access to a shared pool of configurable computing resources (e.g., networks, servers, storage, applications, and services) that can be rapidly provisioned via virtualization and released with minimal management effort or service provider interaction, and then scaled accordingly. Cloud computing can be composed of various characteristics (e.g., on-demand self-service, broad network access, resource pooling, rapid elasticity, measured service, etc.), service models (e.g., Software as a Service (“SaaS”), Platform as a Service (“PaaS”), Infrastructure as a Service (“IaaS”), and deployment models (e.g., private cloud, community cloud, public cloud, hybrid cloud, etc.). Often referred to as a “serverless architecture,” a cloud execution model generally includes a service provider dynamically managing an allocation and provisioning of remote servers for achieving a desired functionality.

(22) It should be understood that any of the computer-implemented components, modules, or servers described in relation to FIG. **1** may be implemented via one or more types of computing devices, such as, for example, the computing device **200** of FIG. **2**. As will be seen, the contact center system **100** generally manages resources (e.g., personnel, computers, telecommunication equipment, etc.) to enable delivery of services via telephone, email, chat, or other communication mechanisms. Such services may vary depending on the type of contact center and, for example, may include customer service, help desk functionality, emergency response, telemarketing, order taking, and/or other characteristics.

(23) Customers desiring to receive services from the contact center system **100** may initiate inbound communications (e.g., telephone calls, emails, chats, etc.) to the contact center system **100** via a customer device **102**. While FIG. **1** shows one such customer device—i.e., customer device **102**—it should be understood that any number of customer devices **102** may be present. The customer devices **102**, for example, may be a communication device, such as a telephone, smart phone, computer, tablet, or laptop. In accordance with functionality described herein, customers may generally use the customer devices **102** to initiate, manage, and conduct communications with the contact center system **100**, such as telephone calls, emails, chats, text messages, web-browsing sessions, and other multi-media transactions.

(24) Inbound and outbound communications from and to the customer devices **102** may traverse the network **104**, with the nature of the network typically depending on the type of customer device being used and the form of communication. As an example, the network **104** may include a communication network of telephone, cellular, and/or data services. The network **104** may be a private or public switched telephone network (PSTN), local area network (LAN), private wide area network (WAN), and/or public WAN such as the Internet. Further, the network **104** may include a wireless carrier network including a code division multiple access (CDMA) network, global system for mobile communications (GSM) network, or any wireless network/technology conventional in the art, including but not limited to 3G, 4G, LTE, 5G, etc.

(25) The switch/media gateway **106** may be coupled to the network **104** for receiving and transmitting telephone calls between customers and the contact center system **100**. The

switch/media gateway **106** may include a telephone or communication switch configured to function as a central switch for agent level routing within the center. The switch may be a hardware switching system or implemented via software. For example, the switch **106** may include an automatic call distributor, a private branch exchange (PBX), an IP-based software switch, and/or any other switch with specialized hardware and software configured to receive Internet-sourced interactions and/or telephone network-sourced interactions from a customer, and route those interactions to, for example, one of the agent devices **118**. Thus, in general, the switch/media gateway **106** establishes a voice connection between the customer and the agent by establishing a connection between the customer device **102** and agent device **118**.

(26) As further shown, the switch/media gateway **106** may be coupled to the call controller **108** which, for example, serves as an adapter or interface between the switch and the other routing, monitoring, and communication-handling components of the contact center system **100**. The call controller **108** may be configured to process PSTN calls, VOIP calls, and/or other types of calls. For example, the call controller **108** may include computer-telephone integration (CTI) software for interfacing with the switch/media gateway and other components. The call controller **108** may include a session initiation protocol (SIP) server for processing SIP calls. The call controller **108** may also extract data about an incoming interaction, such as the customer's telephone number, IP address, or email address, and then communicate these with other contact center components in processing the interaction.

(27) The interactive media response (IMR) server **110** may be configured to enable self-help or virtual assistant functionality. Specifically, the IMR server **110** may be similar to an interactive voice response (IVR) server, except that the IMR server **110** is not restricted to voice and may also cover a variety of media channels. In an example illustrating voice, the IMR server **110** may be configured with an IMR script for querying customers on their needs. For example, a contact center for a bank may instruct customers via the IMR script to “press **1**” if they wish to retrieve their account balance. Through continued interaction with the IMR server **110**, customers may receive service without needing to speak with an agent. The IMR server **110** may also be configured to ascertain why a customer is contacting the contact center so that the communication may be routed to the appropriate resource. The IMR configuration may be performed through the use of a self-service and/or assisted service tool which comprises a web-based tool for developing IVR applications and routing applications running in the contact center environment.

(28) The routing server **112** may function to route incoming interactions. For example, once it is determined that an inbound communication should be handled by a human agent, functionality within the routing server **112** may select the most appropriate agent and route the communication thereto. This agent selection may be based on which available agent is best suited for handling the communication. More specifically, the selection of appropriate agent may be based on a routing strategy or algorithm that is implemented by the routing server **112**. In doing this, the routing server **112** may query data that is relevant to the incoming interaction, for example, data relating to the particular customer, available agents, and the type of interaction, which, as described herein, may be stored in particular databases. Once the agent is selected, the routing server **112** may interact with the call controller **108** to route (i.e., connect) the incoming interaction to the corresponding agent device **118**. As part of this connection, information about the customer may be provided to the selected agent via their agent device **118**. This information is intended to enhance the service the agent is able to provide to the customer.

(29) It should be appreciated that the contact center system **100** may include one or more mass storage devices—represented generally by the storage device **114**—for storing data in one or more databases relevant to the functioning of the contact center. For example, the storage device **114** may store customer data that is maintained in a customer database. Such customer data may include, for example, customer profiles, contact information, service level agreement (SLA), and interaction history (e.g., details of previous interactions with a particular customer, including the nature of

previous interactions, disposition data, wait time, handle time, and actions taken by the contact center to resolve customer issues). As another example, the storage device **114** may store agent data in an agent database. Agent data maintained by the contact center system **100** may include, for example, agent availability and agent profiles, schedules, skills, handle time, and/or other relevant data. As another example, the storage device **114** may store interaction data in an interaction database. Interaction data may include, for example, data relating to numerous past interactions between customers and contact centers. More generally, it should be understood that, unless otherwise specified, the storage device **114** may be configured to include databases and/or store data related to any of the types of information described herein, with those databases and/or data being accessible to the other modules or servers of the contact center system **100** in ways that facilitate the functionality described herein. For example, the servers or modules of the contact center system **100** may query such databases to retrieve data stored therein or transmit data thereto for storage. The storage device **114**, for example, may take the form of any conventional storage medium and may be locally housed or operated from a remote location. As an example, the databases may be Cassandra database, NoSQL database, or a SQL database and managed by a database management system, such as, Oracle, IBM DB2, Microsoft SQL server, or Microsoft Access, PostgreSQL.

(30) The statistics server **116** may be configured to record and aggregate data relating to the performance and operational aspects of the contact center system **100**. Such information may be compiled by the statistics server **116** and made available to other servers and modules, such as the reporting server **134**, which then may use the data to produce reports that are used to manage operational aspects of the contact center and execute automated actions in accordance with functionality described herein. Such data may relate to the state of contact center resources, e.g., average wait time, abandonment rate, agent occupancy, and others as functionality described herein would require.

(31) The agent devices **118** of the contact center system **100** may be communication devices configured to interact with the various components and modules of the contact center system **100** in ways that facilitate functionality described herein. An agent device **118**, for example, may include a telephone adapted for regular telephone calls or VoIP calls. An agent device **118** may further include a computing device configured to communicate with the servers of the contact center system **100**, perform data processing associated with operations, and interface with customers via voice, chat, email, and other multimedia communication mechanisms according to functionality described herein. Although FIG. 1 shows three such agent devices **118**—i.e., agent devices **118A**, **118B** and **118C**—it should be understood that any number of agent devices **118** may be present in a particular embodiment.

(32) The multimedia/social media server **120** may be configured to facilitate media interactions (other than voice) with the customer devices **102** and/or the servers **128**. Such media interactions may be related, for example, to email, voice mail, chat, video, text-messaging, web, social media, co-browsing, etc. The multimedia/social media server **120** may take the form of any IP router conventional in the art with specialized hardware and software for receiving, processing, and forwarding multi-media events and communications.

(33) The knowledge management server **122** may be configured to facilitate interactions between customers and the knowledge system **124**. In general, the knowledge system **124** may be a computer system capable of receiving questions or queries and providing answers in response. The knowledge system **124** may be included as part of the contact center system **100** or operated remotely by a third party. The knowledge system **124** may include an artificially intelligent computer system capable of answering questions posed in natural language by retrieving information from information sources such as encyclopedias, dictionaries, newswire articles, literary works, or other documents submitted to the knowledge system **124** as reference materials. As an example, the knowledge system **124** may be embodied as IBM Watson or a similar system.

(34) The chat server **126**, it may be configured to conduct, orchestrate, and manage electronic chat communications with customers. In general, the chat server **126** is configured to implement and maintain chat conversations and generate chat transcripts. Such chat communications may be conducted by the chat server **126** in such a way that a customer communicates with automated chatbots, human agents, or both. In exemplary embodiments, the chat server **126** may perform as a chat orchestration server that dispatches chat conversations among the chatbots and available human agents. In such cases, the processing logic of the chat server **126** may be rules driven so to leverage an intelligent workload distribution among available chat resources. The chat server **126** further may implement, manage, and facilitate user interfaces (UIs) associated with the chat feature, including those UIs generated at either the customer device **102** or the agent device **118**. The chat server **126** may be configured to transfer chats within a single chat session with a particular customer between automated and human sources such that, for example, a chat session transfers from a chatbot to a human agent or from a human agent to a chatbot. The chat server **126** may also be coupled to the knowledge management server **122** and the knowledge systems **124** for receiving suggestions and answers to queries posed by customers during a chat so that, for example, links to relevant articles can be provided.

(35) The web servers **128** may be included to provide site hosts for a variety of social interaction sites to which customers subscribe, such as Facebook, Twitter, Instagram, etc. Though depicted as part of the contact center system **100**, it should be understood that the web servers **128** may be provided by third parties and/or maintained remotely. The web servers **128** may also provide webpages for the enterprise or organization being supported by the contact center system **100**. For example, customers may browse the webpages and receive information about the products and services of a particular enterprise. Within such enterprise webpages, mechanisms may be provided for initiating an interaction with the contact center system **100**, for example, via web chat, voice, or email. An example of such a mechanism is a widget, which can be deployed on the webpages or websites hosted on the web servers **128**. As used herein, a widget refers to a user interface component that performs a particular function. In some implementations, a widget may include a graphical user interface control that can be overlaid on a webpage displayed to a customer via the Internet. The widget may show information, such as in a window or text box, or include buttons or other controls that allow the customer to access certain functionalities, such as sharing or opening a file or initiating a communication. In some implementations, a widget includes a user interface component having a portable portion of code that can be installed and executed within a separate webpage without compilation. Some widgets can include corresponding or additional user interfaces and be configured to access a variety of local resources (e.g., a calendar or contact information on the customer device) or remote resources via network (e.g., instant messaging, electronic mail, or social networking updates).

(36) The interaction (iXn) server **130** may be configured to manage deferrable activities of the contact center and the routing thereof to human agents for completion. As used herein, deferrable activities may include back-office work that can be performed off-line, e.g., responding to emails, attending training, and other activities that do not entail real-time communication with a customer. As an example, the interaction (iXn) server **130** may be configured to interact with the routing server **112** for selecting an appropriate agent to handle each of the deferrable activities. Once assigned to a particular agent, the deferrable activity is pushed to that agent so that it appears on the agent device **118** of the selected agent. The deferrable activity may appear in a workbin as a task for the selected agent to complete. The functionality of the workbin may be implemented via any conventional data structure, such as, for example, a linked list, array, and/or other suitable data structure. Each of the agent devices **118** may include a workbin. As an example, a workbin may be maintained in the buffer memory of the corresponding agent device **118**.

(37) The universal contact server (UCS) **132** may be configured to retrieve information stored in the customer database and/or transmit information thereto for storage therein. For example, the

UCS **132** may be utilized as part of the chat feature to facilitate maintaining a history on how chats with a particular customer were handled, which then may be used as a reference for how future chats should be handled. More generally, the UCS **132** may be configured to facilitate maintaining a history of customer preferences, such as preferred media channels and best times to contact. To do this, the UCS **132** may be configured to identify data pertinent to the interaction history for each customer such as, for example, data related to comments from agents, customer communication history, and the like. Each of these data types then may be stored in the customer database **222** or on other modules and retrieved as functionality described herein requires.

(38) The reporting server **134** may be configured to generate reports from data compiled and aggregated by the statistics server **116** or other sources. Such reports may include near real-time reports or historical reports and concern the state of contact center resources and performance characteristics, such as, for example, average wait time, abandonment rate, and/or agent occupancy. The reports may be generated automatically or in response to specific requests from a requestor (e.g., agent, administrator, contact center application, etc.). The reports then may be used toward managing the contact center operations in accordance with functionality described herein.

(39) The media services server **136** may be configured to provide audio and/or video services to support contact center features. In accordance with functionality described herein, such features may include prompts for an IVR or IMR system (e.g., playback of audio files), hold music, voicemails/single party recordings, multi-party recordings (e.g., of audio and/or video calls), screen recording, speech recognition, dual tone multi frequency (DTMF) recognition, faxes, audio and video transcoding, secure real-time transport protocol (SRTP), audio conferencing, video conferencing, coaching (e.g., support for a coach to listen in on an interaction between a customer and an agent and for the coach to provide comments to the agent without the customer hearing the comments), call analysis, keyword spotting, and/or other relevant features.

(40) The analytics module **138** may be configured to provide systems and methods for performing analytics on data received from a plurality of different data sources as functionality described herein may require. In accordance with example embodiments, the analytics module **138** also may generate, update, train, and modify predictors or models based on collected data, such as, for example, customer data, agent data, and interaction data. The models may include behavior models of customers or agents. The behavior models may be used to predict behaviors of, for example, customers or agents, in a variety of situations, thereby allowing embodiments of the present invention to tailor interactions based on such predictions or to allocate resources in preparation for predicted characteristics of future interactions, thereby improving overall contact center performance and the customer experience. It will be appreciated that, while the analytics module is described as being part of a contact center, such behavior models also may be implemented on customer systems (or, as also used herein, on the “customer-side” of the interaction) and used for the benefit of customers.

(41) According to exemplary embodiments, the analytics module **138** may have access to the data stored in the storage device **114**, including the customer database and agent database. The analytics module **138** also may have access to the interaction database, which stores data related to interactions and interaction content (e.g., transcripts of the interactions and events detected therein), interaction metadata (e.g., customer identifier, agent identifier, medium of interaction, length of interaction, interaction start and end time, department, tagged categories), and the application setting (e.g., the interaction path through the contact center). Further, the analytic module **138** may be configured to retrieve data stored within the storage device **114** for use in developing and training algorithms and models, for example, by applying machine learning techniques.

(42) One or more of the included models may be configured to predict customer or agent behavior and/or aspects related to contact center operation and performance. Further, one or more of the models may be used in natural language processing and, for example, include intent recognition and the like. The models may be developed based upon known first principle equations describing

a system; data, resulting in an empirical model; or a combination of known first principle equations and data. In developing a model for use with present embodiments, because first principles equations are often not available or easily derived, it may be generally preferred to build an empirical model based upon collected and stored data. To properly capture the relationship between the manipulated/disturbance variables and the controlled variables of complex systems, in some embodiments, it may be preferable that the models are nonlinear. This is because nonlinear models can represent curved rather than straight-line relationships between manipulated/disturbance variables and controlled variables, which are common to complex systems such as those discussed herein. Given the foregoing requirements, a machine learning or neural network-based approach may be a preferred embodiment for implementing the models. Neural networks, for example, may be developed based upon empirical data using advanced regression algorithms.

(43) The analytics module **138** may further include an optimizer. As will be appreciated, an optimizer may be used to minimize a “cost function” subject to a set of constraints, where the cost function is a mathematical representation of desired objectives or system operation. Because the models may be non-linear, the optimizer may be a nonlinear programming optimizer. It is contemplated, however, that the technologies described herein may be implemented by using, individually or in combination, a variety of different types of optimization approaches, including, but not limited to, linear programming, quadratic programming, mixed integer non-linear programming, stochastic programming, global non-linear programming, genetic algorithms, particle/swarm techniques, and the like.

(44) According to some embodiments, the models and the optimizer may together be used within an optimization system. For example, the analytics module **138** may utilize the optimization system as part of an optimization process by which aspects of contact center performance and operation are optimized or, at least, enhanced. This, for example, may include features related to the customer experience, agent experience, interaction routing, natural language processing, intent recognition, or other functionality related to automated processes.

(45) The various components, modules, and/or servers of FIG. **1** (as well as the other figures included herein) may each include one or more processors executing computer program instructions and interacting with other system components for performing the various functionalities described herein. Such computer program instructions may be stored in a memory implemented using a standard memory device, such as, for example, a random-access memory (RAM), or stored in other non-transitory computer readable media such as, for example, a CD-ROM, flash drive, etc. Although the functionality of each of the servers is described as being provided by the particular server, a person of skill in the art should recognize that the functionality of various servers may be combined or integrated into a single server, or the functionality of a particular server may be distributed across one or more other servers without departing from the scope of the present invention. Further, the terms “interaction” and “communication” are used interchangeably, and generally refer to any real-time and non-real-time interaction that uses any communication channel including, without limitation, telephone calls (PSTN or VOIP calls), emails, vmails, video, chat, screen-sharing, text messages, social media messages, WebRTC calls, etc. Access to and control of the components of the contact center system **100** may be affected through user interfaces (UIs) which may be generated on the customer devices **102** and/or the agent devices **118**.

(46) As noted above, in some embodiments, the contact center system **100** may operate as a hybrid system in which some or all components are hosted remotely, such as in a cloud-based or cloud computing environment. It should be appreciated that each of the devices of the contact center system **100** may be embodied as, include, or form a portion of one or more computing devices similar to the computing device **200** described below in reference to FIG. **2**.

(47) Referring now to FIG. **2**, a simplified block diagram of at least one embodiment of a computing device **200** is shown. The illustrative computing device **200** depicts at least one

embodiment of each of the computing devices, systems, servicers, controllers, switches, gateways, engines, modules, and/or computing components described herein (e.g., which collectively may be referred to interchangeably as computing devices, servers, or modules for brevity of the description). For example, the various computing devices may be a process or thread running on one or more processors of one or more computing devices **200**, which may be executing computer program instructions and interacting with other system modules in order to perform the various functionalities described herein. Unless otherwise specifically limited, the functionality described in relation to a plurality of computing devices may be integrated into a single computing device, or the various functionalities described in relation to a single computing device may be distributed across several computing devices. Further, in relation to the computing systems described herein—such as the contact center system **100** of FIG. **1**—the various servers and computer devices thereof may be located on local computing devices **200** (e.g., on-site at the same physical location as the agents of the contact center), remote computing devices **200** (e.g., off-site or in a cloud-based or cloud computing environment, for example, in a remote data center connected via a network), or some combination thereof. In some embodiments, functionality provided by servers located on computing devices off-site may be accessed and provided over a virtual private network (VPN), as if such servers were on-site, or the functionality may be provided using a software as a service (SaaS) accessed over the Internet using various protocols, such as by exchanging data via extensible markup language (XML), JSON, and/or the functionality may be otherwise accessed/leveraged.

(48) In some embodiments, the computing device **200** may be embodied as a server, desktop computer, laptop computer, tablet computer, notebook, netbook, Ultrabook™, cellular phone, mobile computing device, smartphone, wearable computing device, personal digital assistant, Internet of Things (IoT) device, processing system, wireless access point, router, gateway, and/or any other computing, processing, and/or communication device capable of performing the functions described herein.

(49) The computing device **200** includes a processing device **202** that executes algorithms and/or processes data in accordance with operating logic **208**, an input/output device **204** that enables communication between the computing device **200** and one or more external devices **210**, and memory **206** which stores, for example, data received from the external device **210** via the input/output device **204**.

(50) The input/output device **204** allows the computing device **200** to communicate with the external device **210**. For example, the input/output device **204** may include a transceiver, a network adapter, a network card, an interface, one or more communication ports (e.g., a USB port, serial port, parallel port, an analog port, a digital port, VGA, DVI, HDMI, FireWire, CAT 5, or any other type of communication port or interface), and/or other communication circuitry. Communication circuitry of the computing device **200** may be configured to use any one or more communication technologies (e.g., wireless or wired communications) and associated protocols (e.g., Ethernet, Bluetooth®, Wi-Fi®, WiMAX, etc.) to effect such communication depending on the particular computing device **200**. The input/output device **204** may include hardware, software, and/or firmware suitable for performing the techniques described herein.

(51) The external device **210** may be any type of device that allows data to be inputted or outputted from the computing device **200**. For example, in various embodiments, the external device **210** may be embodied as one or more of the devices/systems described herein, and/or a portion thereof. Further, in some embodiments, the external device **210** may be embodied as another computing device, switch, diagnostic tool, controller, printer, display, alarm, peripheral device (e.g., keyboard, mouse, touch screen display, etc.), and/or any other computing, processing, and/or communication device capable of performing the functions described herein. Furthermore, in some embodiments, it should be appreciated that the external device **210** may be integrated into the computing device **200**.

(52) The processing device **202** may be embodied as any type of processor(s) capable of performing the functions described herein. In particular, the processing device **202** may be embodied as one or more single or multi-core processors, microcontrollers, or other processor or processing/controlling circuits. For example, in some embodiments, the processing device **202** may include or be embodied as an arithmetic logic unit (ALU), central processing unit (CPU), digital signal processor (DSP), graphics processing unit (GPU), field-programmable gate array (FPGA), application-specific integrated circuit (ASIC), and/or another suitable processor(s). The processing device **202** may be a programmable type, a dedicated hardwired state machine, or a combination thereof. Processing devices **202** with multiple processing units may utilize distributed, pipelined, and/or parallel processing in various embodiments. Further, the processing device **202** may be dedicated to performance of just the operations described herein, or may be utilized in one or more additional applications. In the illustrative embodiment, the processing device **202** is programmable and executes algorithms and/or processes data in accordance with operating logic **208** as defined by programming instructions (such as software or firmware) stored in memory **206**. Additionally or alternatively, the operating logic **208** for processing device **202** may be at least partially defined by hardwired logic or other hardware. Further, the processing device **202** may include one or more components of any type suitable to process the signals received from input/output device **204** or from other components or devices and to provide desired output signals. Such components may include digital circuitry, analog circuitry, or a combination thereof.

(53) The memory **206** may be of one or more types of non-transitory computer-readable media, such as a solid-state memory, electromagnetic memory, optical memory, or a combination thereof. Furthermore, the memory **206** may be volatile and/or nonvolatile and, in some embodiments, some or all of the memory **206** may be of a portable type, such as a disk, tape, memory stick, cartridge, and/or other suitable portable memory. In operation, the memory **206** may store various data and software used during operation of the computing device **200** such as operating systems, applications, programs, libraries, and drivers. It should be appreciated that the memory **206** may store data that is manipulated by the operating logic **208** of processing device **202**, such as, for example, data representative of signals received from and/or sent to the input/output device **204** in addition to or in lieu of storing programming instructions defining operating logic **208**. As shown in FIG. 2, the memory **206** may be included with the processing device **202** and/or coupled to the processing device **202** depending on the particular embodiment. For example, in some embodiments, the processing device **202**, the memory **206**, and/or other components of the computing device **200** may form a portion of a system-on-a-chip (SoC) and be incorporated on a single integrated circuit chip.

(54) In some embodiments, various components of the computing device **200** (e.g., the processing device **202** and the memory **206**) may be communicatively coupled via an input/output subsystem, which may be embodied as circuitry and/or components to facilitate input/output operations with the processing device **202**, the memory **206**, and other components of the computing device **200**. For example, the input/output subsystem may be embodied as, or otherwise include, memory controller hubs, input/output control hubs, firmware devices, communication links (i.e., point-to-point links, bus links, wires, cables, light guides, printed circuit board traces, etc.) and/or other components and subsystems to facilitate the input/output operations.

(55) The computing device **200** may include other or additional components, such as those commonly found in a typical computing device (e.g., various input/output devices and/or other components), in other embodiments. It should be further appreciated that one or more of the components of the computing device **200** described herein may be distributed across multiple computing devices. In other words, the techniques described herein may be employed by a computing system that includes one or more computing devices. Additionally, although only a single processing device **202**, I/O device **204**, and memory **206** are illustratively shown in FIG. 2, it should be appreciated that a particular computing device **200** may include multiple processing

devices **202**, I/O devices **204**, and/or memories **206** in other embodiments. Further, in some embodiments, more than one external device **210** may be in communication with the computing device **200**.

(56) The computing device **200** may be one of a plurality of devices connected by a network or connected to other systems/resources via a network. The network may be embodied as any one or more types of communication networks that are capable of facilitating communication between the various devices communicatively connected via the network. As such, the network may include one or more networks, routers, switches, access points, hubs, computers, client devices, endpoints, nodes, and/or other intervening network devices. For example, the network may be embodied as or otherwise include one or more cellular networks, telephone networks, local or wide area networks, publicly available global networks (e.g., the Internet), ad hoc networks, short-range communication links, or a combination thereof. In some embodiments, the network may include a circuit-switched voice or data network, a packet-switched voice or data network, and/or any other network able to carry voice and/or data. In particular, in some embodiments, the network may include Internet Protocol (IP)-based and/or asynchronous transfer mode (ATM)-based networks. In some embodiments, the network may handle voice traffic (e.g., via a Voice over IP (VOIP) network), web traffic, and/or other network traffic depending on the particular embodiment and/or devices of the system in communication with one another. In various embodiments, the network may include analog or digital wired and wireless networks (e.g., IEEE 802.11 networks, Public Switched Telephone Network (PSTN), Integrated Services Digital Network (ISDN), and Digital Subscriber Line (xDSL)), Third Generation (3G) mobile telecommunications networks, Fourth Generation (4G) mobile telecommunications networks, Fifth Generation (5G) mobile telecommunications networks, a wired Ethernet network, a private network (e.g., such as an intranet), radio, television, cable, satellite, and/or any other delivery or tunneling mechanism for carrying data, or any appropriate combination of such networks. It should be appreciated that the various devices/systems may communicate with one another via different networks depending on the source and/or destination devices/systems.

(57) It should be appreciated that the computing device **200** may communicate with other computing devices **200** via any type of gateway or tunneling protocol such as secure socket layer or transport layer security. The network interface may include a built-in network adapter, such as a network interface card, suitable for interfacing the computing device to any type of network capable of performing the operations described herein. Further, the network environment may be a virtual network environment where the various network components are virtualized. For example, the various machines may be virtual machines implemented as a software-based computer running on a physical machine. The virtual machines may share the same operating system, or, in other embodiments, different operating system may be run on each virtual machine instance. For example, a “hypervisor” type of virtualizing is used where multiple virtual machines run on the same host physical machine, each acting as if it has its own dedicated box. Other types of virtualization may be employed in other embodiments, such as, for example, the network (e.g., via software defined networking) or functions (e.g., via network functions virtualization).

(58) Accordingly, one or more of the computing devices **200** described herein may be embodied as, or form a portion of, one or more cloud-based systems. In cloud-based embodiments, the cloud-based system may be embodied as a server-ambiguous computing solution, for example, that executes a plurality of instructions on-demand, contains logic to execute instructions only when prompted by a particular activity/trigger, and does not consume computing resources when not in use. That is, system may be embodied as a virtual computing environment residing “on” a computing system (e.g., a distributed network of devices) in which various virtual functions (e.g., Lambda functions, Azure functions, Google cloud functions, and/or other suitable virtual functions) may be executed corresponding with the functions of the system described herein. For example, when an event occurs (e.g., data is transferred to the system for handling), the virtual computing

environment may be communicated with (e.g., via a request to an API of the virtual computing environment), whereby the API may route the request to the correct virtual function (e.g., a particular server-ambiguous computing resource) based on a set of rules. As such, when a request for the transmission of data is made by a user (e.g., via an appropriate user interface to the system), the appropriate virtual function(s) may be executed to perform the actions before eliminating the instance of the virtual function(s).

(59) Referring now to FIG. 3, in use, a computing system (e.g., the contact center system **100**, one or more computing devices **200**, and/or other computing devices described herein) may execute a method **300** for filtering a Trie data structure by a specific event. It should be appreciated that the particular blocks of the method **300** are illustrated by way of example, and such blocks may be combined or divided, added or removed, and/or reordered in whole or in part depending on the particular embodiment, unless stated to the contrary.

(60) The illustrative method **300** begins with block **302** in which the computing system receives a Trie for the entire data set for the organization. For example, as described above, the illustrative technologies may involve the creation of a single “big picture” Trie that includes all of the bot flows (e.g., including relative attributes and/or other metadata) for the organization. For simplicity and brevity of the description, this Trie may be referred to as a “mother Trie” or a “big picture Trie.” This mother Trie is able to be received by or otherwise accessed by the computing system (e.g., for filtering and querying). FIG. 6 illustrates an example Trie in a state **600** in which it has been organized as a “big picture” mother Trie (e.g., the state in which the Trie is stored). In other embodiments, it should be appreciated that the mother Trie may include a plurality of bot flows of the organization, but not necessarily all of the bot flows. For example, a particular organization may have an interest in partitioning its analyses and/or visualizations of bot flows and events.

(61) As described above, FIG. 6 illustrates the initial state **600** of an example “big picture” mother Trie after it has been created. The illustrative Trie is a simple example created for an organization that includes three basic bot flows. For simplicity and clarity of the description, the possible event sequences or “journeys” are described in reference to “words.” A first bot flow includes the journeys BALL (representing a sequence of the events B, A, L, and L), CAR (representing a sequence of the events C, A, and R), and A (representing a sequence including only the event A). A second bot flow includes the journeys BAT (representing a sequence of the events B, A, and T) and CART (representing a sequence of the events C, A, R, and T). A third bot flow includes the journeys CAT (representing a sequence of the events C, A, and T), A (representing a sequence including only the event A), XP (representing a sequence of the events X and P), and BLL (representing a sequence of the events B, L, and L). The same Trie is also illustrated in state **1100** of FIG. 11, which further illustrates the bot flow identifiers of the bot flows associated with each event adjacent the corresponding event.

(62) In block **304**, the computing system receives a selection of a starting event of the Trie by which to filter the Trie. For example, as described above, an administrative user may visualize the Trie in a graphical user interface and provide user input indicating that the user would like to filter the Trie to include only events that include a particular starting event. In the illustrative embodiment of FIGS. 6-7, the user has selected the event “a” to be the starting event. In block **306**, the computing system identifies each occurrence of the selected starting event in the Trie. For example, as depicted in the state **602** of FIG. 6, the computing system has identified each occurrence of the event “a” in the mother Trie, which includes each of the events in the data set as described above. In some embodiments, in block **308**, the computing system may perform a depth first search in order to identify each occurrence of the selected starting event in the Trie. In other embodiments, the computing system may utilize another search algorithm. In some embodiments, it should be appreciated that, in finding each occurrence of a particular starting event (e.g., the event “a” of the state **602** of FIG. 6), the computing system may also identify each sub-Trie that includes the selected event as the starting event (e.g., the three sub-Tries highlighted in the state

602 of FIG. 6).

(63) If the computing system determines, in block **310**, that one or more occurrences of the selected event have been identified in the Trie, the method **300** advances to block **312** in which the computing system extracts the sub-Trie associated with each identified starting event. For example, as depicted in the state **700** of FIG. 7, the computing system has extracted three sub-Tries from the Trie of state **602**, each of which sub-Trie starts with the selected event “a.” In block **314**, the computing system merges the extracted sub-Tries to generate an updated Trie. For example, as depicted in the state **702** of FIG. 7, the computing system has merged the three illustrative sub-Tries of state **700** into a single Trie. It should be appreciated that the resultant updated Trie satisfies the properties of a Trie and, therefore, duplicative journeys are not present, for example. In block **316**, the computing system updates the event attributes of the merged and updated Trie. For example, if an event in the merged Trie was previously present in multiple sub-Tries, the counts of the events from the sub-Tries may be aggregated, and/or the other attributes may be aggregated or otherwise combined.

(64) In block **318**, the computing system provides the updated Trie to the administrative user. For example, in some embodiments, the updated Trie may be returned to the requesting administrative user device for display on a graphical user interface, for visualization by the administrative user.

(65) Although the blocks **302-318** are described in a relatively serial manner, it should be appreciated that various blocks of the method **300** may be performed in parallel in some embodiments.

(66) Referring now to FIG. 4, in use, a computing system (e.g., the contact center system **100**, one or more computing devices **200**, and/or other computing devices described herein) may execute a method **400** for filtering a Trie data structure by an event attribute. It should be appreciated that the particular blocks of the method **400** are illustrated by way of example, and such blocks may be combined or divided, added or removed, and/or reordered in whole or in part depending on the particular embodiment, unless stated to the contrary.

(67) The illustrative method **400** begins with block **402** in which the computing system receives a Trie for the entire data set for the organization. For example, as described above, the illustrative technologies may involve the creation of a single “big picture” Trie that includes all of the bot flows (e.g., including relative attributes and/or other metadata) for the organization (e.g., a “mother Trie”). FIG. 8 illustrates an example Trie in a state **800** in which it has been organized as a “big picture” mother Trie (e.g., the state in which the Trie is stored). The illustrative Trie is a simple example created for an organization that includes the three basic bot flows described above.

However, in the illustrative embodiment, each of the events includes an “animal” attribute, which includes possible values of at least “dog,” “cat”, and/or “hen.” The attribute values associated with each event are illustrated in FIGS. 8-10 adjacent each corresponding event.

(68) In block **404**, the computing system receives a selection of an event attribute of the Trie by which to filter the Trie or, more specifically, an event attribute value of the Trie by which to filter the Trie. For example, as described above, an administrative user may visualize the Trie in a graphical user interface and provide user input indicating that the user would like to filter the Trie to include only events that include a particular selected event attribute value. For example, in the illustrative embodiment of FIGS. 8-10, the user has selected the “animal” attribute and, more specifically, the attribute value of “dog.” In block **406**, the computing system identifies each event that does not include the selected event attribute or, more specifically, the selected event attribute value in the Trie. For example, as depicted in the state **802** of FIG. 8, the computing system has identified each event/node that does not include the attribute value “dog.” That is, one event was identified as including the attribute value “cat,” one event was identified as including the attribute value [“cat”, “hen”], and another event was identified as including the attribute value “hen.” In some embodiments, the computing system may perform a depth first search in order to identify each event in the Trie that does not include the selected event attribute value. In other

embodiments, the computing system may utilize another search algorithm.

(69) If the computing system determines, in block **410**, that one or more event has been identified that does not include the selected event attribute value, the method **400** advances to block **412** in which the computing system deletes the identified events from the Trie. In doing so, in block **414**, the computing system may update the parent-child relationships impacted by the deletion of the identified events. For example, the prior parent event/node of the deleted event may be temporarily connected (e.g., via a pointer) to the prior child events/nodes of the deleted event. As depicted in the state **900** of FIG. **9**, the computing system has deleted each of the identified events and created the temporary connections **902** to update the parent/child relationships impacted by the deletion of the events.

(70) In block **416**, the computing system identifies each of the sub-Tries of the parent events impacted by the deletion of the events. For example, in some embodiments, each prior parent event/node of a deleted event may be identified as the eldest parent node or root node of a sub-Trie. For example, as depicted in the state **904** of FIG. **9**, the computing system has identified the sub-Tries **906** based on the deleted events. In block **418**, the computing system merges the identified sub-Tries (e.g., merges the events within each corresponding sub-Trie) to generate an updated Trie. For example, as depicted in the state **1000** of FIG. **10**, the computing system has merged the two illustrative sub-Tries **906** of FIG. **9** to create a single Trie. As described above, it should be appreciated that the resultant updated Trie satisfies the properties of a Trie and, therefore, duplicative journeys are not present, for example. In block **420**, the computing system updates the event attributes of the merged and updated Trie. For example, if an event in the merged Trie was previously present in multiple sub-Tries, the counts of the events from the sub-Tries may be aggregated, and/or the other attributes may be aggregated or otherwise combined.

(71) In block **422**, the computing system provides the updated Trie to the administrative user. For example, in some embodiments, the updated Trie may be returned to the requesting administrative user device for display on a graphical user interface, for visualization by the administrative user.

(72) Although the blocks **402-422** are described in a relatively serial manner, it should be appreciated that various blocks of the method **400** may be performed in parallel in some embodiments.

(73) Referring now to FIG. **5**, in use, a computing system (e.g., the contact center system **100**, one or more computing devices **200**, and/or other computing devices described herein) may execute a method **500** for filtering a Trie data structure by a bot flow. It should be appreciated that the particular blocks of the method **500** are illustrated by way of example, and such blocks may be combined or divided, added or removed, and/or reordered in whole or in part depending on the particular embodiment, unless stated to the contrary.

(74) The illustrative method **500** begins with block **502** in which the computing system receives a Trie for the entire data set for the organization. For example, as described above, the illustrative technologies may involve the creation of a single “big picture” Trie that includes all of the bot flows (e.g., including relative attributes and/or other metadata) for the organization (e.g., a “mother” Trie). FIG. **11** illustrates an example Trie in a state **1100** in which it has been organized as a “big picture” mother Trie (e.g., the state in which the Trie is stored). As shown in FIG. **11**, the state **1100** also illustrates the bot flow identifiers (of bot flow **1**, bot flow **2**, and bot flow **3**) associated with each event adjacent the corresponding event.

(75) In block **504**, the computing system receives a selection of a bot flow of the Trie by which to filter the Trie. For example, as described above, an administrative user may visualize the Trie in a graphical user interface and provide user input indicating that the user would like to filter the Trie to include only events that are associated with a particular bot flow. In the illustrative embodiment of FIGS. **11-12**, the user has selected to filter the Trie to include only events that are from bot flow **2**. In block **506**, the computing system identifies each event that is not associated with the selected bot flow (e.g., based on associated bot flow identifiers stored as attributes in association with the

events). For example, as depicted in the state **1102** of FIG. **11**, the computing system has identified each event/node that is not associated with bot flow **2**. Those events associated with only bot flow **1** and/or bot flow **3** (and therefore not bot flow **2**) have been highlighted for illustrative purposes. In some embodiments, the computing system may perform a depth first search in order to identify each event in the Trie that is not associated with the selected bot flow. In other embodiments, the computing system may utilize another search algorithm.

(76) If the computing system determines, in block **510**, that one or more events have been identified that are not associated with the selected bot flow, the method **500** advances to block **512** in which the computing system deletes the identified events from the Trie. It should be appreciated that if a particular event/node is not associated with a particular bot flow, then none of its children will be associated with that particular bot flow as a matter of inherency. Accordingly, in some embodiments, during a depth first search, the computing system may identify an event/node that is not associated with the selected flow and delete the entire sub-Trie of that node without further searching of that sub-Trie, which makes the search more efficient. As depicted in the state **1200** of FIG. **12**, the computing system has deleted each of the identified events to generate an updated Trie. In block **514**, the computing system updates the event attributes of the updated Trie. It should be appreciated that the deletion of non-selected bot flows may result in the frequency counts changing for events, and attributes may be updated as well as described above. For example, the event/node attributes of the state **1200** reflect the counts and/or other attributes from before deletion of the identified events, whereas the event/node attributes of the state **1202** reflect the updated counts and/or other attributes after deletion of the identified events. Additionally, it should be appreciated that bot flow **2** is the only bot flow identified as being associated with the remaining events.

(77) In block **516**, the computing system provides the updated Trie to the administrative user. For example, in some embodiments, the updated Trie may be returned to the requesting administrative user device for display on a graphical user interface, for visualization by the administrative user.

(78) Although the blocks **502-516** are described in a relatively serial manner, it should be appreciated that various blocks of the method **500** may be performed in parallel in some embodiments.

Claims

1. A method for filtering a Trie data structure for real-time bot flow visualization, the method comprising: receiving, by a computing system, data associated with the Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event; receiving, by the computing system, a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, wherein receiving the user selection associated with filtering the Trie data structure comprises receiving a user request to filter the Trie data structure to include only events that include a selected event attribute value; performing, by the computing system, a search of the Trie data structure to identify events of the Trie data structure to be deleted, wherein performing the search of the Trie data structure to identify events of the Trie data structure to be deleted comprises identifying events of the Trie data structure that do not include the selected event attribute value; deleting, by the computing system, the identified events to generate an updated Trie data structure, wherein deleting the identified events to generate the updated Trie data structure comprises updating parent-child relationships of events impacted by deletion of the identified events; updating, by the computing system, event attributes of remaining events of the updated Trie data structure in response to deleting the identified events; and providing, by the computing system, the updated Trie data structure for real-time bot flow visualization.

2. The method of claim 1, wherein receiving the user selection associated with filtering the Trie data structure comprises receiving a user request to filter the Trie data structure by a selected bot flow.
3. The method of claim 2, wherein performing the search of the Trie data structure to identify events of the Trie data structure to be deleted comprises identifying events of the Trie data structure that are not associated with the selected bot flow.
4. The method of claim 1, further comprising identifying, by the computing system and subsequent to deleting the identified events, one or more sub-Trie data structures of an intermediate Trie data structure, wherein each sub-Trie data structure of the one or more sub-Trie data structures is a parent event having an updated parent-child relationship.
5. The method of claim 4, further comprising merging, by the computing system, each of the one or more sub-Tries to generate the updated Trie data structure.
6. The method of claim 1, wherein performing the search of the Trie data structure comprises performing a depth first search of the Trie data structure.
7. A system for filtering a Trie data structure for real-time bot flow visualization, the system comprising: at least one processor; and at least one memory comprising a plurality of instructions stored thereon that, in response to execution by the at least one processor, causes the system to: receive data associated with the Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein each bot flow of the plurality of contact center bot flows includes at least one event; receive a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, wherein to receive the user selection associated with filtering the Trie data structure comprises to receive a user request to filter the Trie data structure to include only events that include a selected event attribute value; perform a search of the Trie data structure to identify events of the Trie data structure to be deleted, wherein to perform the search of the Trie data structure to identify events of the Trie data structure to be deleted comprises to identify events of the Trie data structure that do not include the selected event attribute value; delete the identified events to generate an updated Trie data structure, wherein to delete the identified events to generate the updated Trie data structure comprises to update parent-child relationships of events impacted by deletion of the identified events; update event attributes of remaining events of the updated Trie data structure in response to deleting the identified events; and provide the updated Trie data structure for real-time bot flow visualization.
8. The system of claim 7, wherein to receive the user selection associated with filtering the Trie data structure comprises to receive a user request to filter the Trie data structure by a selected bot flow.
9. The system of claim 8, wherein to perform the search of the Trie data structure to identify events of the Trie data structure to be deleted comprises to identify events of the Trie data structure that are not associated with the selected bot flow.
10. The system of claim 7, wherein the plurality of instructions further causes the system to identify, subsequent to deletion of the identified events, one or more sub-Trie data structures of an intermediate Trie data structure, wherein each sub-Trie data structure of the one or more sub-Trie data structures is a parent event having an updated parent-child relationship.
11. The system of claim 10, wherein the plurality of instructions further causes the system to merge each of the one or more sub-Tries to generate the updated Trie data structure.
12. The system of claim 7, wherein to perform the search of the Trie data structure comprises to perform a depth first search of the Trie data structure.
13. One or more non-transitory machine-readable storage media comprising a plurality of instructions stored thereon that, in response to execution by a computing system, causes the computing system to: receive data associated with a Trie data structure, wherein the Trie data structure includes data for a plurality of contact center bot flows of an organization, and wherein

each bot flow of the plurality of contact center bot flows includes at least one event; receive a user selection associated with filtering the Trie data structure for modified visualization of the Trie data structure, wherein the user selection requests that the Trie data structure be filtered to include only journeys that have a selected event attribute value; perform a search of the Trie data structure to identify events of the Trie data structure to be deleted, wherein to perform the search of the Trie data structure to identify events of the Trie data structure to be deleted comprises to identify events of the Trie data structure that do not include the selected event attribute value; delete the identified events to generate an updated Trie data structure, wherein to delete the identified events to generate the updated Trie data structure comprises to update parent-child relationships of events impacted by deletion of the identified events; and provide the updated Trie data structure for real-time bot flow visualization.

14. The one or more non-transitory machine-readable storage media of claim 13, wherein to perform the search of the Trie data structure comprises to perform a depth first search of the Trie data structure.

15. The one or more non-transitory machine-readable storage media of claim 13, wherein the plurality of instructions further causes the computing system to identify, subsequent to deletion of the identified events, one or more sub-Trie data structures of an intermediate Trie data structure, wherein each sub-Trie data structure of the one or more sub-Trie data structures is a parent event having an updated parent-child relationship.

16. The one or more non-transitory machine-readable storage media of claim 15, wherein the plurality of instructions further causes the computing system to merge each of the one or more sub-Tries to generate the updated Trie data structure.
